

Jenkins 빌드 아이템 생성

- Jenkins 에 SSH 인증 등록
 - Jenkins 관리 > Credentials > System 탭의 (Global)
 - Add Credentials
 - Kind
 - SSH Username with private key
 - ID
 - pipeline 에서 활용될 ID
 - Username
 - Host 의 사용자이름
 - Private key
 - Jenkins docker container 내에서
 - `$ cat /var/jenkins_home/.ssh/id_rsa`
 - 내용 복사

The screenshot shows the 'Add Credentials' form in Jenkins. The 'Kind' is set to 'SSH Username with private key'. The 'Scope' is 'Global (Jenkins, nodes, items, all child items, etc)'. The 'ID' is 'docker_ssh'. The 'Description' is empty. The 'Username' is 'kw.idea.14'. The 'Treat username as secret' checkbox is unchecked. The 'Private Key' section has 'Enter directly' selected. The 'Key' field contains a long base64-encoded string. An orange arrow points from the '내용 복사' (Copy content) step in the list to the 'Key' field.

Kind

SSH Username with private key

Scope ?

Global (Jenkins, nodes, items, all child items, etc)

ID ?

docker_ssh

Description ?

Username

kw.idea.14

☐ Treat username as secret ?

Private Key

☒ Enter directly

Key

Enter New Secret Below

```
■HJ / ZPukb3ANb4xrh4Xn j D1 bnbA9Ub fASTwUp/ YkY/ Pf-w / bBcHr3nr bblan0P / XsJ / NVJ Kf-  
Sxj 948CdwsvNYZl KcDyW3t SXucZBWl 07mzD6Da09S23nm09qmS9zLUGT vEckX327FDq5zq  
4XSFaygn2pedZ/ yKHai fgtCU+ofAj XpDwUS+ l cHsGh0mr CMgz/ oadHT cWndd9NHai sBwXET  
pLGj BdHy l 9MAAAAUamYua2l ucDAwMGMyNTJmYj YyZGEBAGMEBQYH
```