

---

# **Sage Reference Manual: Plane curves**

***Release 8.2***

**The Sage Development Team**

**May 07, 2018**



# CONTENTS

<b>1</b>	<b>General curve constructors.</b>	<b>1</b>
<b>2</b>	<b>Affine curves.</b>	<b>5</b>
<b>3</b>	<b>Projective curves.</b>	<b>23</b>
<b>4</b>	<b>Generic curves.</b>	<b>43</b>
<b>5</b>	<b>Curve points</b>	<b>49</b>
<b>6</b>	<b>Plane conic constructor</b>	<b>55</b>
<b>7</b>	<b>Projective plane conics over a field</b>	<b>57</b>
<b>8</b>	<b>Projective plane conics over a number field</b>	<b>71</b>
<b>9</b>	<b>Projective plane conics over <math>\mathbb{Q}</math></b>	<b>75</b>
<b>10</b>	<b>Projective plane conics over finite fields</b>	<b>79</b>
<b>11</b>	<b>Projective plane conics over prime finite fields</b>	<b>81</b>
<b>12</b>	<b>Projective plane conics over a rational function field</b>	<b>83</b>
<b>13</b>	<b>Base class for Jacobians of curves</b>	<b>87</b>
<b>14</b>	<b>Plane quartics</b>	<b>89</b>
14.1	Quartic curve constructor . . . . .	89
14.2	Plane quartic curves over a general ring. These are generic genus 3 curves, . . . . .	89
<b>15</b>	<b>Elliptic curves</b>	<b>91</b>
15.1	Elliptic curve constructor . . . . .	91
15.2	Construct elliptic curves as Jacobians . . . . .	106
15.3	Points on elliptic curves . . . . .	108
15.4	Elliptic curves over a general ring . . . . .	140
15.5	Elliptic curves over a general field . . . . .	164
15.6	Elliptic curves over finite fields . . . . .	177
15.7	Formal groups of elliptic curves . . . . .	195
15.8	Isomorphisms between Weierstrass models of elliptic curves . . . . .	200
15.9	Isogenies . . . . .	202
15.10	Isogenies of small prime degree. . . . .	231
15.11	Elliptic curves over number fields . . . . .	253

15.12 To be sorted . . . . .	582
<b>16 Hyperelliptic curves</b>	<b>595</b>
16.1 Hyperelliptic curve constructor . . . . .	595
16.2 Hyperelliptic curves over a general ring . . . . .	597
16.3 Hyperelliptic curves over a finite field . . . . .	603
16.4 Hyperelliptic curves over a p-adic field. . . . .	617
16.5 Hyperelliptic curves over the rationals . . . . .	633
16.6 Mestre’s algorithm . . . . .	633
16.7 Computation of Frobenius matrix on Monsky-Washnitzer cohomology . . . . .	637
16.8 Frobenius on Monsky-Washnitzer cohomology of a hyperelliptic curve over $\text{GF}(p)$ , . . . . .	663
16.9 Jacobian of a General Hyperelliptic Curve . . . . .	664
16.10 Jacobian of a Hyperelliptic curve of Genus 2 . . . . .	666
16.11 Rational point sets on a Jacobian . . . . .	666
16.12 Jacobian ‘morphism’ as a class in the Picard group . . . . .	667
16.13 Hyperelliptic curves of genus 2 over a general ring . . . . .	672
16.14 Hyperelliptic curves of genus 2 over a finite field . . . . .	674
16.15 Hyperelliptic curves of genus 2 over a p-adic field . . . . .	674
16.16 Hyperelliptic curves of genus 2 over the rationals . . . . .	674
16.17 Compute invariants of quintics and sextics via ‘Ueberschiebung’. . . . .	675
16.18 Kummer surfaces over a general ring . . . . .	679
16.19 Conductor and Reduction Types for Genus 2 Curves . . . . .	679
<b>17 Indices and Tables</b>	<b>685</b>
<b>Bibliography</b>	<b>687</b>
<b>Python Module Index</b>	<b>691</b>
<b>Index</b>	<b>693</b>

## GENERAL CURVE CONSTRUCTORS.

## AUTHORS:

- William Stein (2005-11-13)
- David Kohel (2006-01)
- Grayson Jorgenson (2016-6)

`sage.schemes.curves.constructor.Curve` ( $F, A=None$ )

Return the plane or space curve defined by  $F$ , where  $F$  can be either a multivariate polynomial, a list or tuple of polynomials, or an algebraic scheme.

If no ambient space is passed in for  $A$ , and if  $F$  is not an algebraic scheme, a new ambient space is constructed.

Also not specifying an ambient space will cause the curve to be defined in either affine or projective space based on properties of  $F$ . In particular, if  $F$  contains a nonhomogenous polynomial, the curve is affine, and if  $F$  consists of homogenous polynomials, then the curve is projective.

## INPUT:

- $F$  – a multivariate polynomial, or a list or tuple of polynomials, or an algebraic scheme.
- $A$  – (default: None) an ambient space in which to create the curve.

## EXAMPLES: A projective plane curve

```
sage: x,y,z = QQ['x,y,z'].gens()
sage: C = Curve(x^3 + y^3 + z^3); C
Projective Plane Curve over Rational Field defined by x^3 + y^3 + z^3
sage: C.genus()
1
```

## EXAMPLES: Affine plane curves

```
sage: x,y = GF(7)['x,y'].gens()
sage: C = Curve(y^2 + x^3 + x^10); C
Affine Plane Curve over Finite Field of size 7 defined by x^10 + x^3 + y^2
sage: C.genus()
0
sage: x,y = QQ['x,y'].gens()
sage: Curve(x^3 + y^3 + 1)
Affine Plane Curve over Rational Field defined by x^3 + y^3 + 1
```

## EXAMPLES: A projective space curve

```
sage: x,y,z,w = QQ['x,y,z,w'].gens()
sage: C = Curve([x^3 + y^3 - z^3 - w^3, x^5 - y*z^4]); C
Projective Curve over Rational Field defined by x^3 + y^3 - z^3 - w^3, x^5 - y*z^4
```

```
sage: C.genus()
13
```

EXAMPLES: An affine space curve

```
sage: x,y,z = QQ['x,y,z'].gens()
sage: C = Curve([y^2 + x^3 + x^10 + z^7, x^2 + y^2]); C
Affine Curve over Rational Field defined by x^10 + z^7 + x^3 + y^2, x^2 + y^2
sage: C.genus()
47
```

EXAMPLES: We can also make non-reduced non-irreducible curves.

```
sage: x,y,z = QQ['x,y,z'].gens()
sage: Curve((x-y)*(x+y))
Projective Conic Curve over Rational Field defined by x^2 - y^2
sage: Curve((x-y)^2*(x+y)^2)
Projective Plane Curve over Rational Field defined by x^4 - 2*x^2*y^2 + y^4
```

EXAMPLES: A union of curves is a curve.

```
sage: x,y,z = QQ['x,y,z'].gens()
sage: C = Curve(x^3 + y^3 + z^3)
sage: D = Curve(x^4 + y^4 + z^4)
sage: C.union(D)
Projective Plane Curve over Rational Field defined by
x^7 + x^4*y^3 + x^3*y^4 + y^7 + x^4*z^3 + y^4*z^3 + x^3*z^4 + y^3*z^4 + z^7
```

The intersection is not a curve, though it is a scheme.

```
sage: X = C.intersection(D); X
Closed subscheme of Projective Space of dimension 2 over Rational Field defined
↳by:
x^3 + y^3 + z^3,
x^4 + y^4 + z^4
```

Note that the intersection has dimension 0.

```
sage: X.dimension()
0
sage: I = X.defining_ideal(); I
Ideal (x^3 + y^3 + z^3, x^4 + y^4 + z^4) of Multivariate Polynomial Ring in x, y,
↳z over Rational Field
```

EXAMPLES: In three variables, the defining equation must be homogeneous.

If the parent polynomial ring is in three variables, then the defining ideal must be homogeneous.

```
sage: x,y,z = QQ['x,y,z'].gens()
sage: Curve(x^2+y^2)
Projective Conic Curve over Rational Field defined by x^2 + y^2
sage: Curve(x^2+y^2+z)
Traceback (most recent call last):
...
TypeError: x^2 + y^2 + z is not a homogeneous polynomial
```

The defining polynomial must always be nonzero:

```
sage: P1.<x,y> = ProjectiveSpace(1, GF(5))
sage: Curve(0*x)
Traceback (most recent call last):
...
ValueError: defining polynomial of curve must be nonzero
```

```
sage: A.<x,y,z> = AffineSpace(QQ, 3)
sage: C = Curve([y - x^2, z - x^3], A)
sage: A == C.ambient_space()
True
```





## AFFINE CURVES.

### EXAMPLES:

We can construct curves in either an affine plane:

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y - x^2], A); C
Affine Plane Curve over Rational Field defined by -x^2 + y
```

or in higher dimensional affine space:

```
sage: A.<x,y,z,w> = AffineSpace(QQ, 4)
sage: C = Curve([y - x^2, z - w^3, w - y^4], A); C
Affine Curve over Rational Field defined by -x^2 + y, -w^3 + z, -y^4 + w
```

### AUTHORS:

- William Stein (2005-11-13)
- David Joyner (2005-11-13)
- David Kohel (2006-01)
- Grayson Jorgenson (2016-8)

```
class sage.schemes.curves.affine_curve.AffineCurve(A,X)
  Bases: sage.schemes.curves.curve.Curve_generic, sage.schemes.affine.
          affine_subscheme.AlgebraicScheme_subscheme_affine
```

Initialization function.

### EXAMPLES:

```
sage: R.<v> = QQ[]
sage: K.<u> = NumberField(v^2 + 3)
sage: A.<x,y,z> = AffineSpace(K, 3)
sage: C = Curve([z - u*x^2, y^2], A); C
Affine Curve over Number Field in u with defining polynomial v^2 + 3
defined by (-u)*x^2 + z, y^2
```

```
sage: A.<x,y,z> = AffineSpace(GF(7), 3)
sage: C = Curve([x^2 - z, z - 8*x], A); C
Affine Curve over Finite Field of size 7 defined by x^2 - z, -x + z
```

**blowup** ( $P=None$ )

Return the blow up of this affine curve at the point  $P$ .

The blow up is described by affine charts. This curve must be irreducible.

INPUT:

- $P$  – (default: None) a point on this curve at which to blow up. If None, then  $P$  is taken to be the origin.

OUTPUT:

- a tuple consisting of three elements. The first is a tuple of curves in affine space of the same dimension as the ambient space of this curve, which define the blow up in each affine chart. The second is a tuple of tuples such that the  $j$ th element of the  $i$ th tuple is the transition map from the  $i$ th affine patch to the  $j$ th affine patch. Lastly, the third element is a tuple consisting of the restrictions of the projection map from the blow up back to the original curve, restricted to each affine patch. There the  $i$ th element will be the projection from the  $i$ th affine patch.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y^2 - x^3], A)
sage: C.blowup()
((Affine Plane Curve over Rational Field defined by s1^2 - x,
 Affine Plane Curve over Rational Field defined by y*s0^3 - 1),
 ([Scheme endomorphism of Affine Plane Curve over Rational Field defined by s1^
 ↪ 2 - x
   Defn: Defined on coordinates by sending (x, s1) to
       (x, s1), Scheme morphism:
   From: Affine Plane Curve over Rational Field defined by s1^2 - x
   To:   Affine Plane Curve over Rational Field defined by y*s0^3 - 1
   Defn: Defined on coordinates by sending (x, s1) to
       (x*s1, 1/s1)], [Scheme morphism:
   From: Affine Plane Curve over Rational Field defined by y*s0^3 - 1
   To:   Affine Plane Curve over Rational Field defined by s1^2 - x
   Defn: Defined on coordinates by sending (y, s0) to
       (y*s0, 1/s0),
 Scheme endomorphism of Affine Plane Curve over Rational Field defined by y
 ↪ y*s0^3 - 1
   Defn: Defined on coordinates by sending (y, s0) to
       (y, s0)]),
 (Scheme morphism:
   From: Affine Plane Curve over Rational Field defined by s1^2 - x
   To:   Affine Plane Curve over Rational Field defined by -x^3 + y^2
   Defn: Defined on coordinates by sending (x, s1) to
       (x, x*s1), Scheme morphism:
   From: Affine Plane Curve over Rational Field defined by y*s0^3 - 1
   To:   Affine Plane Curve over Rational Field defined by -x^3 + y^2
   Defn: Defined on coordinates by sending (y, s0) to
       (y*s0, y)))
```

```
sage: K.<a> = QuadraticField(2)
sage: A.<x,y,z> = AffineSpace(K, 3)
sage: C = Curve([y^2 - a*x^5, x - z], A)
sage: B = C.blowup()
sage: B[0]
(Affine Curve over Number Field in a with defining polynomial x^2 - 2 defined
 ↪ by s2 - 1,
 2*x^3 + (-a)*s1^2,
 Affine Curve over Number Field in a with defining polynomial x^2 - 2 defined
 ↪ by s0 - s2,
 2*y^3*s2^5 + (-a),
 Affine Curve over Number Field in a with defining polynomial x^2 - 2 defined
 ↪ by s0 - 1,
```

```

2*z^3 + (-a)*s1^2)
sage: B[1][0][2]
Scheme morphism:
From: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by s2 - 1,
2*x^3 + (-a)*s1^2
To: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by s0 - 1,
2*z^3 + (-a)*s1^2
Defn: Defined on coordinates by sending (x, s1, s2) to
(x*s2, 1/s2, s1/s2)
sage: B[1][2][0]
Scheme morphism:
From: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by s0 - 1,
2*z^3 + (-a)*s1^2
To: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by s2 - 1,
2*x^3 + (-a)*s1^2
Defn: Defined on coordinates by sending (z, s0, s1) to
(z*s0, s1/s0, 1/s0)
sage: B[2]
(Scheme morphism:
From: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by
s2 - 1, 2*x^3 + (-a)*s1^2
To: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by
(-a)*x^5 + y^2, x - z
Defn: Defined on coordinates by sending (x, s1, s2) to
(x, x*s1, x*s2), Scheme morphism:
From: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by
s0 - s2, 2*y^3*s2^5 + (-a)
To: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by
(-a)*x^5 + y^2, x - z
Defn: Defined on coordinates by sending (y, s0, s2) to
(y*s0, y, y*s2), Scheme morphism:
From: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by
s0 - 1, 2*z^3 + (-a)*s1^2
To: Affine Curve over Number Field in a with defining polynomial x^2 - 2
↳ defined by
(-a)*x^5 + y^2, x - z
Defn: Defined on coordinates by sending (z, s0, s1) to
(z*s0, z*s1, z))

```

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve((y - 3/2)^3 - (x + 2)^5 - (x + 2)^6)
sage: Q = A([-2, 3/2])
sage: C.blowup(Q)
((Affine Plane Curve over Rational Field defined by x^3 - s1^3 + 7*x^2 + 16*x
↳ + 12,
Affine Plane Curve over Rational Field defined by 8*y^3*s0^6 - 36*y^2*s0^6
↳ + 8*y^2*s0^5 +
54*y*s0^6 - 24*y*s0^5 - 27*s0^6 + 18*s0^5 - 8),
([Scheme endomorphism of Affine Plane Curve over Rational Field defined by x^
↳ 3 - s1^3 + 7*x^2 +

```

```

16*x + 12
  Defn: Defined on coordinates by sending (x, s1) to
        (x, s1), Scheme morphism:
  From: Affine Plane Curve over Rational Field defined by x^3 - s1^3 + 7*x^
↪2 + 16*x + 12
  To:   Affine Plane Curve over Rational Field defined by 8*y^3*s0^6 -
↪36*y^2*s0^6 + 8*y^2*s0^5 +
        54*y*s0^6 - 24*y*s0^5 - 27*s0^6 + 18*s0^5 - 8
  Defn: Defined on coordinates by sending (x, s1) to
        (x*s1 + 2*s1 + 3/2, 1/s1)], [Scheme morphism:
  From: Affine Plane Curve over Rational Field defined by 8*y^3*s0^6 -
↪36*y^2*s0^6 + 8*y^2*s0^5 +
        54*y*s0^6 - 24*y*s0^5 - 27*s0^6 + 18*s0^5 - 8
  To:   Affine Plane Curve over Rational Field defined by x^3 - s1^3 + 7*x^
↪2 + 16*x + 12
  Defn: Defined on coordinates by sending (y, s0) to
        (y*s0 - 3/2*s0 - 2, 1/s0),
  Scheme endomorphism of Affine Plane Curve over Rational Field defined by
↪8*y^3*s0^6 - 36*y^2*s0^6 +
        8*y^2*s0^5 + 54*y*s0^6 - 24*y*s0^5 - 27*s0^6 + 18*s0^5 - 8
  Defn: Defined on coordinates by sending (y, s0) to
        (y, s0)]),
(Scheme morphism:
  From: Affine Plane Curve over Rational Field defined by x^3 - s1^3 + 7*x^
↪2 + 16*x + 12
  To:   Affine Plane Curve over Rational Field defined by -x^6 - 13*x^5 -
↪70*x^4 - 200*x^3 + y^3 -
        320*x^2 - 9/2*y^2 - 272*x + 27/4*y - 795/8
  Defn: Defined on coordinates by sending (x, s1) to
        (x, x*s1 + 2*s1 + 3/2), Scheme morphism:
  From: Affine Plane Curve over Rational Field defined by 8*y^3*s0^6 - 36*y^
↪2*s0^6 + 8*y^2*s0^5 +
        54*y*s0^6 - 24*y*s0^5 - 27*s0^6 + 18*s0^5 - 8
  To:   Affine Plane Curve over Rational Field defined by -x^6 - 13*x^5 -
↪70*x^4 - 200*x^3 + y^3 -
        320*x^2 - 9/2*y^2 - 272*x + 27/4*y - 795/8
  Defn: Defined on coordinates by sending (y, s0) to
        (y*s0 - 3/2*s0 - 2, y))

```

```

sage: A.<x,y,z,w> = AffineSpace(QQ, 4)
sage: C = A.curve([(x + 1)^2 + y^2]^3 - 4*(x + 1)^2*y^2, y - z, w - 4])
sage: Q = C([-1,0,0,4])
sage: B = C.blowup(Q)
sage: B[0]
(Affine Curve over Rational Field defined by s3, s1 - s2, x^2*s2^6 +
2*x*s2^6 + 3*x^2*s2^4 + s2^6 + 6*x*s2^4 + 3*x^2*s2^2 + 3*s2^4 + 6*x*s2^2
+ x^2 - s2^2 + 2*x + 1,
 Affine Curve over Rational Field defined by s3, s2 - 1, y^2*s0^6 +
3*y^2*s0^4 + 3*y^2*s0^2 + y^2 - 4*s0^2,
 Affine Curve over Rational Field defined by s3, s1 - 1, z^2*s0^6 +
3*z^2*s0^4 + 3*z^2*s0^2 + z^2 - 4*s0^2,
 Closed subscheme of Affine Space of dimension 4 over Rational Field
defined by:
  1)
sage: Q = A([6,2,3,1])
sage: B = C.blowup(Q)
Traceback (most recent call last):
...
```

```
TypeError: (=(6, 2, 3, 1)) must be a point on this curve
```

```
sage: A.<x,y> = AffineSpace(QuadraticField(-1), 2)
sage: C = A.curve([y^2 + x^2])
sage: C.blowup()
Traceback (most recent call last):
...
TypeError: this curve must be irreducible
```

### **plane\_projection** (*AP=None*)

Return a projection of this curve into an affine plane so that the image of the projection is a plane curve.

INPUT:

- *AP* – (default: *None*) the affine plane to project this curve into. This space must be defined over the same base field as this curve, and must have dimension two. This space will be constructed if not specified.

OUTPUT:

- a tuple consisting of two elements: a scheme morphism from this curve into an affine plane, and the plane curve that defines the image of that morphism.

EXAMPLES:

```
sage: A.<x,y,z,w> = AffineSpace(QQ, 4)
sage: C = Curve([x^2 - y*z*w, z^3 - w, w + x*y - 3*z^3], A)
sage: C.plane_projection()
(Scheme morphism:
  From: Affine Curve over Rational Field defined by -y*z*w + x^2, z^3 -
w, -3*z^3 + x*y + w
  To:   Affine Space of dimension 2 over Rational Field
  Defn: Defined on coordinates by sending (x, y, z, w) to
        (x, y), Affine Plane Curve over Rational Field defined by
x0^2*x1^7 - 16*x0^4)
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 + 2)
sage: A.<x,y,z> = AffineSpace(K, 3)
sage: C = A.curve([x - b, y - 2])
sage: B.<a,b> = AffineSpace(K, 2)
sage: proj1 = C.plane_projection(AP=B)
sage: proj1
(Scheme morphism:
  From: Affine Curve over Number Field in b with defining polynomial
a^2 + 2 defined by x + (-b), y - 2
  To:   Affine Space of dimension 2 over Number Field in b with
defining polynomial a^2 + 2
  Defn: Defined on coordinates by sending (x, y, z) to
        (x, z),
  Affine Plane Curve over Number Field in b with defining polynomial a^2
+ 2 defined by a + (-b))
sage: proj1[1].ambient_space() is B
True
sage: proj2 = C.plane_projection()
sage: proj2[1].ambient_space() is B
False
```

**projection** (*indices*, *AS=None*)

Return the projection of this curve onto the coordinates specified by *indices*.

INPUT:

- *indices* – a list or tuple of distinct integers specifying the indices of the coordinates to use in the projection. Can also be a list or tuple consisting of variables of the coordinate ring of the ambient space of this curve. If integers are used to specify the coordinates, 0 denotes the first coordinate. The length of *indices* must be between two and one less than the dimension of the ambient space of this curve, inclusive.
- *AS* – (default: None) the affine space the projected curve will be defined in. This space must be defined over the same base field as this curve, and must have dimension equal to the length of *indices*. This space is constructed if not specified.

OUTPUT:

- a tuple consisting of two elements: a scheme morphism from this curve to affine space of dimension equal to the number of coordinates specified in *indices*, and the affine subscheme that is the image of that morphism. If the image is a curve, the second element of the tuple will be a curve.

EXAMPLES:

```
sage: A.<x,y,z> = AffineSpace(QQ, 3)
sage: C = Curve([y^7 - x^2 + x^3 - 2*z, z^2 - x^7 - y^2], A)
sage: C.projection([0,1])
(Scheme morphism:
  From: Affine Curve over Rational Field defined by y^7 + x^3 - x^2 -
  2*z, -x^7 - y^2 + z^2
  To:   Affine Space of dimension 2 over Rational Field
  Defn: Defined on coordinates by sending (x, y, z) to
        (x, y),
  Affine Plane Curve over Rational Field defined by x1^14 + 2*x0^3*x1^7 -
  2*x0^2*x1^7 - 4*x0^7 + x0^6 - 2*x0^5 + x0^4 - 4*x1^2)
sage: C.projection([0,1,3,4])
Traceback (most recent call last):
...
ValueError: ([0, 1, 3, 4]) must be a list or tuple of length between 2
and (=2), inclusive
```

```
sage: A.<x,y,z,w> = AffineSpace(QQ, 4)
sage: C = Curve([x - 2, y - 3, z - 1], A)
sage: B.<a,b,c> = AffineSpace(QQ, 3)
sage: C.projection([0,1,2], AS=B)
(Scheme morphism:
  From: Affine Curve over Rational Field defined by x - 2, y - 3, z - 1
  To:   Affine Space of dimension 3 over Rational Field
  Defn: Defined on coordinates by sending (x, y, z, w) to
        (x, y, z),
  Closed subscheme of Affine Space of dimension 3 over Rational Field
  defined by:
    c - 1,
    b - 3,
    a - 2)
```

```
sage: A.<x,y,z,w,u> = AffineSpace(GF(11), 5)
sage: C = Curve([x^3 - 5*y*z + u^2, x - y^2 + 3*z^2, w^2 + 2*u^3*y, y - u^2 +
↪ z*x], A)
sage: B.<a,b,c> = AffineSpace(GF(11), 3)
```

```

sage: proj1 = C.projection([1,2,4], AS=B)
sage: proj1
(Scheme morphism:
  From: Affine Curve over Finite Field of size 11 defined by  $x^3 - 5*y*z + u^2, -y^2 + 3*z^2 + x, 2*y*u^3 + w^2, x*z - u^2 + y$ 
  To:   Affine Space of dimension 3 over Finite Field of size 11
  Defn: Defined on coordinates by sending  $(x, y, z, w, u)$  to
         $(y, z, u)$ ,
  Affine Curve over Finite Field of size 11 defined by  $a^2*b - 3*b^3 - c^2 + a, c^6 - 5*a*b^4 + b^3*c^2 - 3*a*c^4 + 3*a^2*c^2 - a^3, a^2*c^4 - 3*b^2*c^4 - 2*a^3*c^2 - 5*a*b^2*c^2 + a^4 - 5*a*b^3 + 2*b^4 + b^2*c^2 - 3*b*c^2 + 3*a*b, a^4*c^2 + 2*b^4*c^2 - a^5 - 2*a*b^4 + 5*b*c^4 + a*b*c^2 - 5*a*b^2 + 4*b^3 + b*c^2 + 5*c^2 - 5*a, a^6 - 5*b^6 - 5*b^3*c^2 + 5*a*b^3 + 2*c^4 - 4*a*c^2 + 2*a^2 - 5*a*b + c^2)$ 
sage: proj1[1].ambient_space() is B
True
sage: proj2 = C.projection([1,2,4])
sage: proj2[1].ambient_space() is B
False
sage: C.projection([1,2,3,5], AS=B)
Traceback (most recent call last):
...
TypeError: (=Affine Space of dimension 3 over Finite Field of size 11)
must have dimension (=4)

```

```

sage: A.<x,y,z,w> = AffineSpace(QQ, 4)
sage: C = A.curve([x*y - z^3, x*z - w^3, w^2 - x^3])
sage: C.projection([y,z])
(Scheme morphism:
  From: Affine Curve over Rational Field defined by  $-z^3 + x*y, -w^3 + x*z, -x^3 + w^2$ 
  To:   Affine Space of dimension 2 over Rational Field
  Defn: Defined on coordinates by sending  $(x, y, z, w)$  to
         $(y, z)$ ,
  Affine Plane Curve over Rational Field defined by  $x_1^2 x_3 - x_0^7 x_1^4$ )
sage: B.<x,y,z> = AffineSpace(QQ, 3)
sage: C.projection([x,y,z], AS=B)
(Scheme morphism:
  From: Affine Curve over Rational Field defined by  $-z^3 + x*y, -w^3 + x*z, -x^3 + w^2$ 
  To:   Affine Space of dimension 3 over Rational Field
  Defn: Defined on coordinates by sending  $(x, y, z, w)$  to
         $(x, y, z)$ ,
  Affine Curve over Rational Field defined by  $z^3 - x*y, x^8 - x*z^2, x^7*z^2 - x*y*z$ )
sage: C.projection([y,z,z])
Traceback (most recent call last):
...
ValueError: ([y, z, z]) must be a list or tuple of distinct indices or
variables

```

### **projective\_closure** (*i=0, PP=None*)

Return the projective closure of this affine curve.

INPUT:

- *i* – (default: 0) the index of the affine coordinate chart of the projective space that the affine ambient space of this curve embeds into.

- `PP` – (default: `None`) ambient projective space to compute the projective closure in. This is constructed if it is not given.

OUTPUT:

- a curve in projective space.

EXAMPLES:

```
sage: A.<x,y,z> = AffineSpace(QQ, 3)
sage: C = Curve([y-x^2,z-x^3], A)
sage: C.projective_closure()
Projective Curve over Rational Field defined by x1^2 - x0*x2,
x1*x2 - x0*x3, x2^2 - x1*x3
```

```
sage: A.<x,y,z> = AffineSpace(QQ, 3)
sage: C = Curve([y - x^2, z - x^3], A)
sage: C.projective_closure()
Projective Curve over Rational Field defined by
x1^2 - x0*x2, x1*x2 - x0*x3, x2^2 - x1*x3
```

```
sage: A.<x,y> = AffineSpace(CC, 2)
sage: C = Curve(y - x^3 + x - 1, A)
sage: C.projective_closure(1)
Projective Plane Curve over Complex Field with 53 bits of precision defined by
x0^3 - x0*x1^2 + x1^3 - x1^2*x2
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: P.<u,v,w> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y - x^2], A)
sage: C.projective_closure(1, P).ambient_space() == P
True
```

**resolution\_of\_singularities** (*extend=False*)

Return a nonsingular model for this affine curve created by blowing up its singular points.

The nonsingular model is given as a collection of affine patches that cover it. If `extend` is `False` and if the base field is a number field, or if the base field is a finite field, the model returned may have singularities with coordinates not contained in the base field. An error is returned if this curve is already nonsingular, or if it has no singular points over its base field. This curve must be irreducible, and must be defined over a number field or finite field.

INPUT:

- `extend` – (default: `False`) specifies whether to extend the base field when necessary to find all singular points when this curve is defined over a number field. If `extend` is `False`, then only singularities with coordinates in the base field of this curve will be resolved. However, setting `extend` to `True` will slow down computations.

OUTPUT:

- a tuple consisting of three elements. The first is a tuple of curves in affine space of the same dimension as the ambient space of this curve, which represent affine patches of the resolution of singularities. The second is a tuple of tuples such that the  $j$ th element of the  $i$ th tuple is the transition map from the  $i$ th patch to the  $j$ th patch. Lastly, the third element is a tuple consisting of birational maps from the patches back to the original curve that were created by composing the projection maps generated from the blow up computations. There the  $i$ th element will be a map from the  $i$ th patch.

EXAMPLES:



```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y^2 - x^3], A)
sage: C.resolution_of_singularities()
((Affine Plane Curve over Rational Field defined by s1^2 - x,
  Affine Plane Curve over Rational Field defined by y*s0^3 - 1),
  ((Scheme endomorphism of Affine Plane Curve over Rational Field defined by
↪s1^2 - x
    Defn: Defined on coordinates by sending (x, s1) to
        (x, s1), Scheme morphism:
    From: Affine Plane Curve over Rational Field defined by s1^2 - x
    To:   Affine Plane Curve over Rational Field defined by y*s0^3 - 1
    Defn: Defined on coordinates by sending (x, s1) to
        (x*s1, 1/s1)), (Scheme morphism:
    From: Affine Plane Curve over Rational Field defined by y*s0^3 - 1
    To:   Affine Plane Curve over Rational Field defined by s1^2 - x
    Defn: Defined on coordinates by sending (y, s0) to
        (y*s0, 1/s0),
  Scheme endomorphism of Affine Plane Curve over Rational Field defined by
↪y*s0^3 - 1
    Defn: Defined on coordinates by sending (y, s0) to
        (y, s0))),
  (Scheme morphism:
    From: Affine Plane Curve over Rational Field defined by s1^2 - x
    To:   Affine Plane Curve over Rational Field defined by -x^3 + y^2
    Defn: Defined on coordinates by sending (x, s1) to
        (x, x*s1), Scheme morphism:
    From: Affine Plane Curve over Rational Field defined by y*s0^3 - 1
    To:   Affine Plane Curve over Rational Field defined by -x^3 + y^2
    Defn: Defined on coordinates by sending (y, s0) to
        (y*s0, y)))

```

```

sage: set_verbose(-1)
sage: K.<a> = QuadraticField(3)
sage: A.<x,y> = AffineSpace(K, 2)
sage: C = A.curve(x^4 + 2*x^2 + a*y^3 + 1)
sage: C.resolution_of_singularities(extend=True)[0] # long time (2 seconds)
(Affine Plane Curve over Number Field in a0 with defining polynomial y^4 -
↪4*y^2 + 16 defined by
24*x^2*ss1^3 + 24*ss1^3 + (a0^3 - 8*a0),
  Affine Plane Curve over Number Field in a0 with defining polynomial y^4 -
↪4*y^2 + 16 defined by
24*s1^2*ss0 + (a0^3 - 8*a0)*ss0^2 + (-6*a0^3)*s1,
  Affine Plane Curve over Number Field in a0 with defining polynomial y^4 -
↪4*y^2 + 16 defined by
8*y^2*s0^4 + (4*a0^3)*y*s0^3 - 32*s0^2 + (a0^3 - 8*a0)*y)

```

```

sage: A.<x,y,z> = AffineSpace(GF(5), 3)
sage: C = Curve([y - x^3, (z - 2)^2 - y^3 - x^3], A)
sage: R = C.resolution_of_singularities()
sage: R[0]
(Affine Curve over Finite Field of size 5 defined by x^2 - s1, s1^4 - x*s2^2,
↪+ s1, x*s1^3 - s2^2 + x,
  Affine Curve over Finite Field of size 5 defined by y*s2^2 - y^2 - 1, s2^4 -
↪s0^3 - y^2 - 2, y*s0^3
  - s2^2 + y, Affine Curve over Finite Field of size 5 defined by s0^3*s1 +
↪z*s1^3 + s1^4 - 2*s1^3 - 1,
  z*s0^3 + z*s1^3 - 2*s0^3 - 2*s1^3 - 1, z^2*s1^3 + z*s1^3 - s1^3 - z + s1 + 2)

```

```

sage: A.<x,y,z,w> = AffineSpace(QQ, 4)
sage: C = A.curve([(x - 2)^2 + y^2)^2 - (x - 2)^2 - y^2 + (x - 2)^3, z - y -
↪7, w - 4])
sage: B = C.resolution_of_singularities()
sage: B[0]
(Affine Curve over Rational Field defined by s3, s1 - s2, x^2*s2^4 -
4*x*s2^4 + 2*x^2*s2^2 + 4*s2^4 - 8*x*s2^2 + x^2 + 7*s2^2 - 3*x + 1,
Affine Curve over Rational Field defined by s3, s2 - 1, y^2*s0^4 +
2*y^2*s0^2 + y*s0^3 + y^2 - s0^2 - 1,
Affine Curve over Rational Field defined by s3, s1 - 1, z^2*s0^4 -
14*z*s0^4 + 2*z^2*s0^2 + z*s0^3 + 49*s0^4 - 28*z*s0^2 - 7*s0^3 + z^2 +
97*s0^2 - 14*z + 48,
Closed subscheme of Affine Space of dimension 4 over Rational Field
defined by:
1)

```

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y - x^2 + 1], A)
sage: C.resolution_of_singularities()
Traceback (most recent call last):
...
TypeError: this curve is already nonsingular

```

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([(x^2 + y^2 - y - 2)*(y - x^2 + 2) + y^3])
sage: C.resolution_of_singularities()
Traceback (most recent call last):
...
TypeError: this curve has no singular points over its base field. If
working over a number field use extend=True

```

**class** sage.schemes.curves.affine\_curve.**AffinePlaneCurve**(A,f)

Bases: *sage.schemes.curves.affine\_curve.AffineCurve*

Initialization function.

EXAMPLES:

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([x^3 - y^2], A); C
Affine Plane Curve over Rational Field defined by x^3 - y^2

```

```

sage: A.<x,y> = AffineSpace(CC, 2)
sage: C = Curve([y^2 + x^2], A); C
Affine Plane Curve over Complex Field with 53 bits of precision defined
by x^2 + y^2

```

**divisor\_of\_function**(r)

Return the divisor of a function on a curve.

INPUT: r is a rational function on X

OUTPUT:

- list - The divisor of r represented as a list of coefficients and points. (TODO: This will change to a more structural output in the future.)

EXAMPLES:

```

sage: F = GF(5)
sage: P2 = AffineSpace(2, F, names = 'xy')
sage: R = P2.coordinate_ring()
sage: x, y = R.gens()
sage: f = y^2 - x^9 - x
sage: C = Curve(f)
sage: K = FractionField(R)
sage: r = 1/x
sage: C.divisor_of_function(r)      # todo: not implemented (broken)
      [[-1, (0, 0, 1)]]
sage: r = 1/x^3
sage: C.divisor_of_function(r)      # todo: not implemented (broken)
      [[-3, (0, 0, 1)]]

```

**fundamental\_group()**

Return a presentation of the fundamental group of the complement of `self`.

---

**Note:** The curve must be defined over the rationals or a number field with an embedding over  $\overline{\mathbb{Q}}$ .

---

**EXAMPLES:**

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve(y^2 - x^3 - x^2)
sage: C.fundamental_group() # optional - sirocco
Finitely presented group < x0 | >

```

In the case of number fields, they need to have an embedding to the algebraic field:

```

sage: a = QQ[x](x^2+5).roots(QQbar)[0][0]
sage: F = NumberField(a.minpoly(), 'a', embedding=a)
sage: F.inject_variables()
Defining a
sage: A.<x,y> = AffineSpace(F, 2)
sage: C = A.curve(y^2 - a*x^3 - x^2)
sage: C.fundamental_group() # optional - sirocco
Finitely presented group < x0 | >

```

**Warning:** This functionality requires the sirocco package to be installed.

**is\_ordinary\_singularity(P)**

Return whether the singular point  $P$  of this affine plane curve is an ordinary singularity.

The point  $P$  is an ordinary singularity of this curve if it is a singular point, and if the tangents of this curve at  $P$  are distinct.

**INPUT:**

- $P$  – a point on this curve.

**OUTPUT:**

- Boolean. True or False depending on whether  $P$  is or is not an ordinary singularity of this curve, respectively. An error is raised if  $P$  is not a singular point of this curve.

**EXAMPLES:**

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y^2 - x^3], A)
sage: Q = A([0,0])
sage: C.is_ordinary_singularity(Q)
False
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 - 3)
sage: A.<x,y> = AffineSpace(K, 2)
sage: C = Curve([(x^2 + y^2 - 2*x)^2 - x^2 - y^2], A)
sage: Q = A([0,0])
sage: C.is_ordinary_singularity(Q)
True
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([x^2*y - y^2*x + y^2 + x^3])
sage: Q = A([-1,-1])
sage: C.is_ordinary_singularity(Q)
Traceback (most recent call last):
...
TypeError: ((-1, -1)) is not a singular point of (=Affine Plane Curve
over Rational Field defined by x^3 + x^2*y - x*y^2 + y^2)
```

**is\_transverse(C, P)**

Return whether the intersection of this curve with the curve C at the point P is transverse.

The intersection at P is transverse if P is a nonsingular point of both curves, and if the tangents of the curves at P are distinct.

INPUT:

- C – a curve in the ambient space of this curve.
- P – a point in the intersection of both curves.

OUTPUT: Boolean.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([x^2 + y^2 - 1], A)
sage: D = Curve([x - 1], A)
sage: Q = A([1,0])
sage: C.is_transverse(D, Q)
False
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^3 + 2)
sage: A.<x,y> = AffineSpace(K, 2)
sage: C = A.curve([x*y])
sage: D = A.curve([y - b*x])
sage: Q = A([0,0])
sage: C.is_transverse(D, Q)
False
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y - x^3], A)
sage: D = Curve([y + x], A)
```

```
sage: Q = A([0,0])
sage: C.is_transverse(D, Q)
True
```

**local\_coordinates** (*pt*, *n*)

Return local coordinates to precision *n* at the given point.

Behaviour is flaky - some choices of *n* are worst than others.

INPUT:

- *pt* - an F-rational point on *X* which is not a point of ramification for the projection  $(x,y) \rightarrow x$ .
- *n* - the number of terms desired

OUTPUT:  $x = x_0 + t$   $y = y_0 +$  power series in *t*

EXAMPLES:

```
sage: F = GF(5)
sage: pt = (2,3)
sage: R = PolynomialRing(F,2, names = ['x','y'])
sage: x,y = R.gens()
sage: f = y^2-x^9-x
sage: C = Curve(f)
sage: C.local_coordinates(pt, 9)
[t + 2, -2*t^12 - 2*t^11 + 2*t^9 + t^8 - 2*t^7 - 2*t^6 - 2*t^4 + t^3 - 2*t^2 -
↪ 2]
```

**multiplicity** (*P*)

Return the multiplicity of this affine plane curve at the point *P*.

In the special case of affine plane curves, the multiplicity of an affine plane curve at the point (0,0) can be computed as the minimum of the degrees of the homogeneous components of its defining polynomial. To compute the multiplicity of a different point, a linear change of coordinates is used.

This curve must be defined over a field. An error is raised if *P* is not a point on this curve.

INPUT:

- *P* – a point in the ambient space of this curve.

OUTPUT:

An integer.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y^2 - x^3], A)
sage: Q1 = A([1,1])
sage: C.multiplicity(Q1)
1
sage: Q2 = A([0,0])
sage: C.multiplicity(Q2)
2

sage: A.<x,y> = AffineSpace(QQbar,2)
sage: C = Curve([-x^7 + (-7)*x^6 + y^6 + (-21)*x^5 + 12*y^5 + (-35)*x^4 +
↪ 60*y^4 + \
(-35)*x^3 + 160*y^3 + (-21)*x^2 + 240*y^2 + (-7)*x + 192*y + 63], A)
sage: Q = A([-1,-2])
```

```
sage: C.multiplicity(Q)
6
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([y^3 - x^3 + x^6])
sage: Q = A([1,1])
sage: C.multiplicity(Q)
Traceback (most recent call last):
...
TypeError: (=(1, 1)) is not a point on (=Affine Plane Curve over
Rational Field defined by x^6 - x^3 + y^3)
```

**plot** (\*args, \*\*kws)

Plot the real points on this affine plane curve.

INPUT:

- self - an affine plane curve
- \*args - optional tuples (variable, minimum, maximum) for plotting dimensions
- \*\*kws - optional keyword arguments passed on to `implicit_plot`

EXAMPLES:

A cuspidal curve:

```
sage: R.<x, y> = QQ[]
sage: C = Curve(x^3 - y^2)
sage: C.plot()
Graphics object consisting of 1 graphics primitive
```

A 5-nodal curve of degree 11. This example also illustrates some of the optional arguments:

```
sage: R.<x, y> = ZZ[]
sage: C = Curve(32*x^2 - 2097152*y^11 + 1441792*y^9 - 360448*y^7 + 39424*y^5 -
↪ 1760*y^3 + 22*y - 1)
sage: C.plot((x, -1, 1), (y, -1, 1), plot_points=400)
Graphics object consisting of 1 graphics primitive
```

A line over **RR**:

```
sage: R.<x, y> = RR[]
sage: C = Curve(R(y - sqrt(2)*x))
sage: C.plot()
Graphics object consisting of 1 graphics primitive
```

**rational\_parameterization()**

Return a rational parameterization of this curve.

This curve must have rational coefficients and be absolutely irreducible (i.e. irreducible over the algebraic closure of the rational field). The curve must also be rational (have geometric genus zero).

The rational parameterization may have coefficients in a quadratic extension of the rational field.

OUTPUT:

- a birational map between  $\mathbb{A}^1$  and this curve, given as a scheme morphism.

EXAMPLES:

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y^2 - x], A)
sage: C.rational_parameterization()
Scheme morphism:
  From: Affine Space of dimension 1 over Rational Field
  To:   Affine Plane Curve over Rational Field defined by y^2 - x
  Defn: Defined on coordinates by sending (t) to
        (t^2, t)

```

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([(x^2 + y^2 - 2*x)^2 - x^2 - y^2], A)
sage: C.rational_parameterization()
Scheme morphism:
  From: Affine Space of dimension 1 over Rational Field
  To:   Affine Plane Curve over Rational Field defined by x^4 +
        2*x^2*y^2 + y^4 - 4*x^3 - 4*x*y^2 + 3*x^2 - y^2
  Defn: Defined on coordinates by sending (t) to
        ((-12*t^4 + 6*t^3 + 4*t^2 - 2*t)/(-25*t^4 + 40*t^3 - 26*t^2 +
        8*t - 1), (-9*t^4 + 12*t^3 - 4*t + 1)/(-25*t^4 + 40*t^3 - 26*t^2 + 8*t - 1))

```

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([x^2 + y^2 + 7], A)
sage: C.rational_parameterization()
Scheme morphism:
  From: Affine Space of dimension 1 over Number Field in a with defining_
  ↪ polynomial a^2 + 7
  To:   Affine Plane Curve over Number Field in a with defining
  polynomial a^2 + 7 defined by x^2 + y^2 + 7
  Defn: Defined on coordinates by sending (t) to
        ((-7*t^2 + 7)/((-a)*t^2 + (-a)), 14*t/((-a)*t^2 + (-a)))

```

### **riemann\_surface** (\*\*kwargs)

Return the complex riemann surface determined by this curve

OUTPUT:

- RiemannSurface object

EXAMPLES:

```

sage: R.<x,y>=QQ[]
sage: C=Curve(x^3+3*y^3+5)
sage: C.riemann_surface()
Riemann surface defined by polynomial f = x^3 + 3*y^3 + 5 = 0, with 53 bits_
  ↪ of precision

```

### **tangents** (P, factor=True)

Return the tangents of this affine plane curve at the point P.

The point P must be a point on this curve.

INPUT:

- P – a point on this curve.
- factor – (default: True) whether to attempt computing the polynomials of the individual tangent lines over the base field of this curve, or to just return the polynomial corresponding to the union of the tangent lines (which requires fewer computations).

OUTPUT:

- a list of polynomials in the coordinate ring of the ambient space of this curve.

EXAMPLES:

```
sage: set_verbose(-1)
sage: A.<x,y> = AffineSpace(QQbar, 2)
sage: C = Curve([x^5*y^3 + 2*x^4*y^4 + x^3*y^5 + 3*x^4*y^3 + 6*x^3*y^4 + 3*x^
↪ 2*y^5\
+ 3*x^3*y^3 + 6*x^2*y^4 + 3*x*y^5 + x^5 + 10*x^4*y + 40*x^3*y^2 + 81*x^2*y^3,
↪ + 82*x*y^4\
+ 33*y^5], A)
sage: Q = A([0,0])
sage: C.tangents(Q)
[x + 3.425299577684700*y, x + (1.949159013086856? + 1.179307909383728?*I)*y,
x + (1.949159013086856? - 1.179307909383728?*I)*y, x + (1.338191198070795? +
↪ 0.2560234251008043?*I)*y,
x + (1.338191198070795? - 0.2560234251008043?*I)*y]
sage: C.tangents(Q, factor=False)
[120*x^5 + 1200*x^4*y + 4800*x^3*y^2 + 9720*x^2*y^3 + 9840*x*y^4 + 3960*y^5]
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 - 3)
sage: A.<x,y> = AffineSpace(K, 2)
sage: C = Curve([(x^2 + y^2 - 2*x)^2 - x^2 - y^2], A)
sage: Q = A([0,0])
sage: C.tangents(Q)
[x + (-1/3*b)*y, x + (1/3*b)*y]
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([y^2 - x^3 - x^2])
sage: Q = A([0,0])
sage: C.tangents(Q)
[x - y, x + y]
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([y*x - x^4 + 2*x^2])
sage: Q = A([1,1])
sage: C.tangents(Q)
Traceback (most recent call last):
...
TypeError: (=(1, 1)) is not a point on (=(Affine Plane Curve over
Rational Field defined by -x^4 + 2*x^2 + x*y)
```

**class** sage.schemes.curves.affine\_curve.**AffinePlaneCurve\_finite\_field**(A,f)

Bases: *sage.schemes.curves.affine\_curve.AffinePlaneCurve*

**rational\_points** (algorithm='enum')

Return sorted list of all rational points on this curve.

Use very naive point enumeration to find all rational points on this curve over a finite field.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(2,GF(9,'a'))
sage: C = Curve(x^2 + y^2 - 1)
sage: C
Affine Plane Curve over Finite Field in a of size 3^2 defined by x^2 + y^2 - 1
sage: C.rational_points()
[(0, 1), (0, 2), (1, 0), (2, 0), (a + 1, a + 1), (a + 1, 2*a + 2), (2*a + 2,
↪ a + 1), (2*a + 2, 2*a + 2)]
```



---

```
class sage.schemes.curves.affine_curve.AffinePlaneCurve_prime_finite_field(A,
                                                                           f)
```

Bases: `sage.schemes.curves.affine_curve.AffinePlaneCurve_finite_field`

**rational\_points** (*algorithm*='enum')

Return sorted list of all rational points on this curve.

INPUT:

- *algorithm* - string:
  - 'enum' - straightforward enumeration
  - 'bn' - via Singular's Brill-Noether package.
  - 'all' - use all implemented algorithms and verify that they give the same answer, then return it

---

**Note:** The Brill-Noether package does not always work. When it fails a `RuntimeError` exception is raised.

---

EXAMPLES:

```
sage: x, y = (GF(5) ['x,y']).gens()
sage: f = y^2 - x^9 - x
sage: C = Curve(f); C
Affine Plane Curve over Finite Field of size 5 defined by -x^9 + y^2 - x
sage: C.rational_points(algorithm='bn')
[(0, 0), (2, 2), (2, 3), (3, 1), (3, 4)]
sage: C = Curve(x - y + 1)
sage: C.rational_points()
[(0, 1), (1, 2), (2, 3), (3, 4), (4, 0)]
```

We compare Brill-Noether and enumeration:

```
sage: x, y = (GF(17) ['x,y']).gens()
sage: C = Curve(x^2 + y^5 + x*y - 19)
sage: v = C.rational_points(algorithm='bn')
sage: w = C.rational_points(algorithm='enum')
sage: len(v)
20
sage: v == w
True
```

**riemann\_roch\_basis** (*D*)

Interfaces with Singular's BrillNoether command.

INPUT:

- *self* - a plane curve defined by a polynomial eqn  $f(x,y) = 0$  over a prime finite field  $F = \text{GF}(p)$  in 2 variables  $x,y$  representing a curve  $X: f(x,y) = 0$  having  $n$   $F$ -rational points (see the Sage function `places_on_curve`)
- *D* - an  $n$ -tuple of integers  $(d_1, \dots, d_n)$  representing the divisor  $\text{Div} = d_1 * P_1 + \dots + d_n * P_n$ , where  $X(F) = \{P_1, \dots, P_n\}$ . The ordering is that dictated by `places_on_curve`.

OUTPUT: basis of  $L(\text{Div})$

EXAMPLES:

```
sage: R = PolynomialRing(GF(5), 2, names = ["x", "y"])
sage: x, y = R.gens()
sage: f = y^2 - x^9 - x
sage: C = Curve(f)
sage: D = [6, 0, 0, 0, 0, 0]
sage: C.riemann_roch_basis(D)
[1, (y^2*z^4 - x*z^5)/x^6, (y^2*z^5 - x*z^6)/x^7, (y^2*z^6 - x*z^7)/x^8]
```

## PROJECTIVE CURVES.

EXAMPLES:

We can construct curves in either a projective plane:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y*z^2 - x^3], P); C
Projective Plane Curve over Rational Field defined by -x^3 + y*z^2
```

or in higher dimensional projective spaces:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([y*w^3 - x^4, z*w^3 - x^4], P); C
Projective Curve over Rational Field defined by -x^4 + y*w^3, -x^4 + z*w^3
```

**AUTHORS:**

- William Stein (2005-11-13)
- David Joyner (2005-11-13)
- David Kohel (2006-01)
- Moritz Minzloff (2010-11)
- Grayson Jorgenson (2016-8)

`sage.schemes.curves.projective_curve.Hasse_bounds(q, genus=1)`  
Return the Hasse-Weil bounds for the cardinality of a nonsingular curve defined over  $\mathbf{F}_q$  of given *genus*.

INPUT:

- `q` (int) – a prime power
- `genus` (int, default 1) – a non-negative integer,

OUTPUT:

(tuple) The Hasse bounds (lb,ub) for the cardinality of a curve of genus `genus` defined over  $\mathbb{F}_q$ .

EXAMPLES:

```
sage: Hasse_bounds(2)
(1, 5)
sage: Hasse_bounds(next_prime(10^30))
(9999999999999980000000000000058, 1000000000000002000000000000058)
```

```
class sage.schemes.curves.projective_curve.ProjectiveCurve(A,X)
    Bases: sage.schemes.curves.curve.Curve\_generic, sage.schemes.projective.projective\_subscheme.AlgebraicScheme\_subscheme\_projective
```

Initialization function.

EXAMPLES:

```
sage: P.<x,y,z,w,u> = ProjectiveSpace(GF(7), 4)
sage: C = Curve([y*u^2 - x^3, z*u^2 - x^3, w*u^2 - x^3, y^3 - x^3], P); C
Projective Curve over Finite Field of size 7 defined by -x^3 + y*u^2,
-x^3 + z*u^2, -x^3 + w*u^2, -x^3 + y^3
```

```
sage: K.<u> = CyclotomicField(11)
sage: P.<x,y,z,w> = ProjectiveSpace(K, 3)
sage: C = Curve([y*w - u*z^2 - x^2, x*w - 3*u^2*z*w], P); C
Projective Curve over Cyclotomic Field of order 11 and degree 10 defined
by -x^2 + (-u)*z^2 + y*w, x*w + (-3*u^2)*z*w
```

**affine\_patch**(*i*, AA=None)

Return the *i*-th affine patch of this projective curve.

INPUT:

- *i* – affine coordinate chart of the projective ambient space of this curve to compute affine patch with respect to.
- AA – (default: None) ambient affine space, this is constructed if it is not given.

OUTPUT:

- a curve in affine space.

EXAMPLES:

```
sage: P.<x,y,z,w> = ProjectiveSpace(CC, 3)
sage: C = Curve([y*z - x^2, w^2 - x*y], P)
sage: C.affine_patch(0)
Affine Curve over Complex Field with 53 bits of precision defined by
x0*x1 - 1.000000000000000, x2^2 - x0
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve(x^3 - x^2*y + y^3 - x^2*z, P)
sage: C.affine_patch(1)
Affine Plane Curve over Rational Field defined by x0^3 - x0^2*x1 - x0^2 + 1
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: P.<u,v,w> = ProjectiveSpace(QQ, 2)
sage: C = Curve([u^2 - v^2], P)
sage: C.affine_patch(1, A).ambient_space() == A
True
```

**arithmetic\_genus**()

Return the arithmetic genus of this projective curve.

This is the arithmetic genus  $g_a(C)$  as defined in [Hartshorne]. If  $P$  is the Hilbert polynomial of the defining ideal of this curve, then the arithmetic genus of this curve is  $1 - P(0)$ . This curve must be irreducible.

OUTPUT: Integer.

EXAMPLES:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = P.curve([w*z - x^2, w^2 + y^2 + z^2])
sage: C.arithmetic_genus()
1
```

```
sage: P.<x,y,z,w,t> = ProjectiveSpace(GF(7), 4)
sage: C = P.curve([t^3 - x*y*w, x^3 + y^3 + z^3, z - w])
sage: C.arithmetic_genus()
10
```

**is\_complete\_intersection()**

Return whether this projective curve is or is not a complete intersection.

OUTPUT: Boolean.

EXAMPLES:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([x*y - z*w, x^2 - y*w, y^2*w - x*z*w], P)
sage: C.is_complete_intersection()
False
```

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([y*w - x^2, z*w^2 - x^3], P)
sage: C.is_complete_intersection()
True
```

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([z^2 - y*w, y*z - x*w, y^2 - x*z], P)
sage: C.is_complete_intersection()
False
```

**plane\_projection (PP=None)**

Return a projection of this curve into a projective plane.

INPUT:

- PP – (default: None) the projective plane the projected curve will be defined in. This space must be defined over the same base field as this curve, and must have dimension two. This space is constructed if not specified.

OUTPUT:

- a tuple consisting of two elements: a scheme morphism from this curve into a projective plane, and the projective curve that is the image of that morphism.

EXAMPLES:

```
sage: P.<x,y,z,w,u,v> = ProjectiveSpace(QQ, 5)
sage: C = P.curve([x*u - z*v, w - y, w*y - x^2, y^3*u^2*z - w^4*w])
sage: L.<a,b,c> = ProjectiveSpace(QQ, 2)
sage: proj1 = C.plane_projection(PP=L)
sage: proj1
(Scheme morphism:
  From: Projective Curve over Rational Field defined by x*u - z*v, -y +
w, -x^2 + y*w, -w^5 + 2*y^3*z*u
  To: Projective Space of dimension 2 over Rational Field
  Defn: Defined on coordinates by sending (x : y : z : w : u : v) to
      (x : -z + u : -z + v),
```

```

Projective Plane Curve over Rational Field defined by  $a^8 + 6a^7b + 4a^5b^3 - 4a^7c - 2a^6bc - 4a^5b^2c + 2a^6c^2$ 
sage: proj1[1].ambient_space() is L
True
sage: proj2 = C.projection()
sage: proj2[1].ambient_space() is L
False

```

```

sage: P.<x,y,z,w,u> = ProjectiveSpace(GF(7), 4)
sage: C = P.curve([x^2 - 6*y^2, w*z*u - y^3 + 4*y^2*z, u^2 - x^2])
sage: C.plane_projection()
(Scheme morphism:
  From: Projective Curve over Finite Field of size 7 defined by  $x^2 + y^2, -y^3 - 3y^2z + zwu, -x^2 + u^2$ 
  To:   Projective Space of dimension 2 over Finite Field of size 7
  Defn: Defined on coordinates by sending  $(x : y : z : w : u)$  to
         $(y : z : -x + w),$ 
  Projective Plane Curve over Finite Field of size 7 defined by  $x_0^{10} - 2x_0^9x_1 + 3x_0^8x_1^2 - 2x_0^7x_1^3 + x_0^6x_1^4 + 2x_0^6x_1^2x_2^2 - 2x_0^5x_1^3x_2^2 - x_0^4x_1^4x_2^2 + x_0^2x_1^4x_2^4$ )

```

```

sage: P.<x,y,z> = ProjectiveSpace(GF(17), 2)
sage: C = P.curve(x^2 - y*z - z^2)
sage: C.plane_projection()
Traceback (most recent call last):
...
TypeError: this curve is already a plane curve

```

### **projection** ( $P=None, PS=None$ )

Return a projection of this curve into projective space of dimension one less than the dimension of the ambient space of this curve.

This curve must not already be a plane curve. Over finite fields, if this curve contains all points in its ambient space, then an error will be returned.

INPUT:

- $P$  – (default: None) a point not on this curve that will be used to define the projection map; this is constructed if not specified.
- $PS$  – (default: None) the projective space the projected curve will be defined in. This space must be defined over the same base ring as this curve, and must have dimension one less than that of the ambient space of this curve. This space will be constructed if not specified.

OUTPUT:

- a tuple consisting of two elements: a scheme morphism from this curve into a projective space of dimension one less than that of the ambient space of this curve, and the projective curve that is the image of that morphism.

EXAMPLES:

```

sage: K.<a> = CyclotomicField(3)
sage: P.<x,y,z,w> = ProjectiveSpace(K, 3)
sage: C = Curve([y*w - x^2, z*w^2 - a*x^3], P)
sage: L.<a,b,c> = ProjectiveSpace(K, 2)
sage: proj1 = C.projection(PS=L)
sage: proj1
(Scheme morphism:

```

```

From: Projective Curve over Cyclotomic Field of order 3 and degree 2
defined by  $-x^2 + yw$ ,  $(-a)x^3 + zw^2$ 
To: Projective Space of dimension 2 over Cyclotomic Field of order
3 and degree 2
Defn: Defined on coordinates by sending  $(x : y : z : w)$  to
       $(x : y : -z + w)$ ,
Projective Plane Curve over Cyclotomic Field of order 3 and degree 2
defined by  $a^6 + (-a)a^3b^3 - a^4b^3c$ 
sage: proj1[1].ambient_space() is L
True
sage: proj2 = C.projection()
sage: proj2[1].ambient_space() is L
False

```

```

sage: P.<x,y,z,w,a,b,c> = ProjectiveSpace(QQ, 6)
sage: C = Curve([y - x, z - a - b, w^2 - c^2, z - x - a, x^2 - w*z], P)
sage: C.projection()
(Scheme morphism:
  From: Projective Curve over Rational Field defined by  $-x + y$ ,  $z - a - b$ ,  $w^2 - c^2$ ,  $-x + z - a$ ,  $x^2 - zw$ 
  To: Projective Space of dimension 5 over Rational Field
  Defn: Defined on coordinates by sending  $(x : y : z : w : a : b : c)$ 
  to
       $(x : y : -z + w : a : b : c)$ ,
  Projective Curve over Rational Field defined by  $x_1 - x_4$ ,  $x_0 - x_4$ ,  $x_2x_3 + x_3^2 + x_2x_4 + 2x_3x_4$ ,  $x_2^2 - x_3^2 - 2x_3x_4 + x_4^2 - x_5^2$ ,  $x_2x_4^2 + x_3x_4^2 + x_4^3 - x_3x_5^2 - x_4x_5^2$ ,  $x_4^4 - x_3^2x_5^2 - 2x_3x_4x_5^2 - x_4^2x_5^2$ )

```

```

sage: P.<x,y,z,w> = ProjectiveSpace(GF(2), 3)
sage: C = P.curve([(x - y)*(x - z)*(x - w)*(y - z)*(y - w),
  ↪x*y*z*w*(x+y+z+w)])
sage: C.projection()
Traceback (most recent call last):
...
NotImplementedError: this curve contains all points of its ambient space

```

```

sage: P.<x,y,z,w,u> = ProjectiveSpace(GF(7), 4)
sage: C = P.curve([x^3 - y*z*u, w^2 - u^2 + 2*x*z, 3*x*w - y^2])
sage: L.<a,b,c,d> = ProjectiveSpace(GF(7), 3)
sage: C.projection(PS=L)
(Scheme morphism:
  From: Projective Curve over Finite Field of size 7 defined by  $x^3 - yz^2u$ ,  $2xz + w^2 - u^2$ ,  $-y^2 + 3xw$ 
  To: Projective Space of dimension 3 over Finite Field of size 7
  Defn: Defined on coordinates by sending  $(x : y : z : w : u)$  to
       $(x : y : z : w)$ ,
  Projective Curve over Finite Field of size 7 defined by  $b^2 - 3a^2d$ ,  $a^5b + a^3b^2c^3d - 3b^2c^2d^3$ ,  $a^6 + a^2c^3d - 3a^2c^2d^3$ )
sage: Q.<a,b,c> = ProjectiveSpace(GF(7), 2)
sage: C.projection(PS=Q)
Traceback (most recent call last):
...
TypeError: (=Projective Space of dimension 2 over Finite Field of size 7) must have dimension (=3)

```

```

sage: PP.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = PP.curve([x^3 - z^2*y, w^2 - z*x])
sage: Q = PP([1,0,1,1])
sage: C.projection(P=Q)
(Scheme morphism:
  From: Projective Curve over Rational Field defined by x^3 - y*z^2,
  -x*z + w^2
  To:   Projective Space of dimension 2 over Rational Field
  Defn: Defined on coordinates by sending (x : y : z : w) to
        (y : -x + z : -x + w),
  Projective Plane Curve over Rational Field defined by x0*x1^5 -
  6*x0*x1^4*x2 + 14*x0*x1^3*x2^2 - 16*x0*x1^2*x2^3 + 9*x0*x1*x2^4 -
  2*x0*x2^5 - x2^6)
sage: LL.<a,b,c> = ProjectiveSpace(QQ, 2)
sage: Q = PP([0,0,0,1])
sage: C.projection(PS=LL, P=Q)
(Scheme morphism:
  From: Projective Curve over Rational Field defined by x^3 - y*z^2,
  -x*z + w^2
  To:   Projective Space of dimension 2 over Rational Field
  Defn: Defined on coordinates by sending (x : y : z : w) to
        (x : y : z),
  Projective Plane Curve over Rational Field defined by a^3 - b*c^2)
sage: Q = PP([0,0,1,0])
sage: C.projection(P=Q)
Traceback (most recent call last):
...
TypeError: (=(0 : 0 : 1 : 0)) must be a point not on this curve

```

```

sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = P.curve(y^2 - x^2 + z^2)
sage: C.projection()
Traceback (most recent call last):
...
TypeError: this curve is already a plane curve

```

**class** sage.schemes.curves.projective\_curve.**ProjectivePlaneCurve**(A,f)

Bases: *sage.schemes.curves.projective\_curve.ProjectiveCurve*

Initialization function.

EXAMPLES:

```

sage: P.<x,y,z> = ProjectiveSpace(QQbar, 2)
sage: C = Curve([y*z - x^2 - QQbar.gen()*z^2], P); C
Projective Plane Curve over Algebraic Field defined by
-x^2 + y*z + (-1)*z^2

```

```

sage: P.<x,y,z> = ProjectiveSpace(GF(5^2, 'v'), 2)
sage: C = Curve([y^2*z - x*z^2 - z^3], P); C
Projective Plane Curve over Finite Field in v of size 5^2 defined by y^2*z - x*z^2
↪ 2 - z^3

```

**arithmetic\_genus**()

Return the arithmetic genus of this projective curve.

This is the arithmetic genus  $g_a(C)$  as defined in [Hartshorne]. For a projective plane curve of degree  $d$ , this is simply  $(d-1)(d-2)/2$ . It need *not* equal the geometric genus (the genus of the normalization of



the curve). This curve must be irreducible.

OUTPUT: Integer.

EXAMPLES:

```
sage: x,y,z = PolynomialRing(GF(5), 3, 'xyz').gens()
sage: C = Curve(y^2*z^7 - x^9 - x*z^8); C
Projective Plane Curve over Finite Field of size 5 defined by -x^9 + y^2*z^7 -
↪ x*z^8
sage: C.arithmetic_genus()
28
sage: C.genus()
4
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y^3*x - x^2*y*z - 7*z^4])
sage: C.arithmetic_genus()
3
```

REFERENCES:

**degree()**

Return the degree of this projective curve.

For a plane curve, this is just the degree of its defining polynomial.

OUTPUT: integer.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = P.curve([y^7 - x^2*z^5 + 7*z^7])
sage: C.degree()
7
```

**divisor\_of\_function(r)**

Return the divisor of a function on a curve.

INPUT: r is a rational function on X

OUTPUT:

- list - The divisor of r represented as a list of coefficients and points. (TODO: This will change to a more structural output in the future.)

EXAMPLES:

```
sage: FF = FiniteField(5)
sage: P2 = ProjectiveSpace(2, FF, names = ['x','y','z'])
sage: R = P2.coordinate_ring()
sage: x, y, z = R.gens()
sage: f = y^2*z^7 - x^9 - x*z^8
sage: C = Curve(f)
sage: K = FractionField(R)
sage: r = 1/x
sage: C.divisor_of_function(r)      # todo: not implemented !!!!
[[-1, (0, 0, 1)]]
sage: r = 1/x^3
sage: C.divisor_of_function(r)      # todo: not implemented !!!!
[[-3, (0, 0, 1)]]
```

**excellent\_position(Q)**

Return a transformation of this curve into one in excellent position with respect to the point  $Q$ .

Here excellent position is defined as in [Fulton89]. A curve  $C$  of degree  $d$  containing the point  $(0 : 0 : 1)$  with multiplicity  $r$  is said to be in excellent position if none of the coordinate lines are tangent to  $C$  at any of the fundamental points  $(1 : 0 : 0)$ ,  $(0 : 1 : 0)$ , and  $(0 : 0 : 1)$ , and if the two coordinate lines containing  $(0 : 0 : 1)$  intersect  $C$  transversally in  $d - r$  distinct non-fundamental points, and if the other coordinate line intersects  $C$  transversally at  $d$  distinct, non-fundamental points.

INPUT:

- $Q$  – a point on this curve.

OUTPUT:

- a scheme morphism from this curve to a curve in excellent position that is a restriction of a change of coordinates map of the projective plane.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([x*y - z^2], P)
sage: Q = P([1,1,1])
sage: C.excellent_position(Q)
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by x*y - z^2
  To:   Projective Plane Curve over Rational Field defined by -x^2 -
3*x*y - 4*y^2 - x*z - 3*y*z
  Defn: Defined on coordinates by sending (x : y : z) to
        (-x + 1/2*y + 1/2*z : -1/2*y + 1/2*z : x + 1/2*y - 1/2*z)
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 - 3)
sage: P.<x,y,z> = ProjectiveSpace(K, 2)
sage: C = P.curve([z^2*y^3*x^4 - y^6*x^3 - 4*z^2*y^4*x^3 - 4*z^4*y^2*x^3 +
↪ 3*y^7*x^2 + 10*z^2*y^5*x^2\
+ 9*z^4*y^3*x^2 + 5*z^6*y*x^2 - 3*y^8*x - 9*z^2*y^6*x - 11*z^4*y^4*x - 7*z^
↪ 6*y^2*x - 2*z^8*x + y^9 +\
2*z^2*y^7 + 3*z^4*y^5 + 4*z^6*y^3 + 2*z^8*y])
sage: Q = P([1,0,0])
sage: C.excellent_position(Q)
Scheme morphism:
  From: Projective Plane Curve over Number Field in b with defining
polynomial a^2 - 3 defined by -x^3*y^6 + 3*x^2*y^7 - 3*x*y^8 + y^9 +
x^4*y^3*z^2 - 4*x^3*y^4*z^2 + 10*x^2*y^5*z^2 - 9*x*y^6*z^2 + 2*y^7*z^2 -
4*x^3*y^2*z^4 + 9*x^2*y^3*z^4 - 11*x*y^4*z^4 + 3*y^5*z^4 + 5*x^2*y*z^6 -
7*x*y^2*z^6 + 4*y^3*z^6 - 2*x*z^8 + 2*y*z^8
  To:   Projective Plane Curve over Number Field in b with defining
polynomial a^2 - 3 defined by 900*x^9 - 7410*x^8*y + 29282*x^7*y^2 -
69710*x^6*y^3 + 110818*x^5*y^4 - 123178*x^4*y^5 + 96550*x^3*y^6 -
52570*x^2*y^7 + 18194*x*y^8 - 3388*y^9 - 1550*x^8*z + 9892*x^7*y*z -
30756*x^6*y^2*z + 58692*x^5*y^3*z - 75600*x^4*y^4*z + 67916*x^3*y^5*z -
42364*x^2*y^6*z + 16844*x*y^7*z - 3586*y^8*z + 786*x^7*z^2 -
3958*x^6*y*z^2 + 9746*x^5*y^2*z^2 - 14694*x^4*y^3*z^2 +
15174*x^3*y^4*z^2 - 10802*x^2*y^5*z^2 + 5014*x*y^6*z^2 - 1266*y^7*z^2 -
144*x^6*z^3 + 512*x^5*y*z^3 - 912*x^4*y^2*z^3 + 1024*x^3*y^3*z^3 -
816*x^2*y^4*z^3 + 512*x*y^5*z^3 - 176*y^6*z^3 + 8*x^5*z^4 - 8*x^4*y*z^4
- 16*x^3*y^2*z^4 + 16*x^2*y^3*z^4 + 8*x*y^4*z^4 - 8*y^5*z^4
  Defn: Defined on coordinates by sending (x : y : z) to
        (1/4*y + 1/2*z : -1/4*y + 1/2*z : x + 1/4*y - 1/2*z)
```

```

sage: set_verbose(-1)
sage: a = QQbar(sqrt(2))
sage: P.<x,y,z> = ProjectiveSpace(QQbar, 2)
sage: C = Curve([(-1/4*a)*x^3 + (-3/4*a)*x^2*y + (-3/4*a)*x*y^2 + (-1/4*a)*y^3 - 2*x*y*z], P)
sage: Q = P([0,0,1])
sage: C.excellent_position(Q)
Scheme morphism:
  From: Projective Plane Curve over Algebraic Field defined by
  (-0.3535533905932738?)*x^3 + (-1.060660171779822?)*x^2*y +
  (-1.060660171779822?)*x*y^2 + (-0.3535533905932738?)*y^3 + (-2)*x*y*z
  To: Projective Plane Curve over Algebraic Field defined by
  (-2.828427124746190?)*x^3 + (-2)*x^2*y + 2*y^3 + (-2)*x^2*z + 2*y^2*z
  Defn: Defined on coordinates by sending (x : y : z) to
        (1/2*x + 1/2*y : (-1/2)*x + 1/2*y : 1/2*x + (-1/2)*y + z)

```

## REFERENCES:

**fundamental\_group()**

Return a presentation of the fundamental group of the complement of self.

---

**Note:** The curve must be defined over the rationals or a number field with an embedding over  $\overline{\mathbb{Q}}$ .

---

## EXAMPLES:

```

sage: P.<x,y,z> = ProjectiveSpace(QQ,2)
sage: C = P.curve(x^2*z-y^3)
sage: C.fundamental_group() # optional - sirocco
Finitely presented group < x0 | x0^3 >

```

In the case of number fields, they need to have an embedding into the algebraic field:

```

sage: a = QQ[x](x^2+5).roots(QQbar)[0][0]
sage: a
-2.236067977499790?*I
sage: F = NumberField(a.minpoly(), 'a', embedding=a)
sage: P.<x,y,z> = ProjectiveSpace(F, 2)
sage: F.inject_variables()
Defining a
sage: C = P.curve(x^2 + a * y^2)
sage: C.fundamental_group() # optional - sirocco
Finitely presented group < x0 | >

```

**Warning:** This functionality requires the sirocco package to be installed.

**is\_ordinary\_singularity(P)**

Return whether the singular point P of this projective plane curve is an ordinary singularity.

The point P is an ordinary singularity of this curve if it is a singular point, and if the tangents of this curve at P are distinct.

INPUT:

- P – a point on this curve.

OUTPUT:

- Boolean. True or False depending on whether  $P$  is or is not an ordinary singularity of this curve, respectively. An error is raised if  $P$  is not a singular point of this curve.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y^2*z^3 - x^5], P)
sage: Q = P([0,0,1])
sage: C.is_ordinary_singularity(Q)
False
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 - 3)
sage: P.<x,y,z> = ProjectiveSpace(K, 2)
sage: C = P.curve([x^2*y^3*z^4 - y^6*z^3 - 4*x^2*y^4*z^3 - 4*x^4*y^2*z^3 +
↪ 3*y^7*z^2 + 10*x^2*y^5*z^2\
+ 9*x^4*y^3*z^2 + 5*x^6*y*z^2 - 3*y^8*z - 9*x^2*y^6*z - 11*x^4*y^4*z - 7*x^
↪ 6*y^2*z - 2*x^8*z + y^9 +\
2*x^2*y^7 + 3*x^4*y^5 + 4*x^6*y^3 + 2*x^8*y])
sage: Q = P([0,1,1])
sage: C.is_ordinary_singularity(Q)
True
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = P.curve([z^5 - y^5 + x^5 + x*y^2*z^2])
sage: Q = P([0,1,1])
sage: C.is_ordinary_singularity(Q)
Traceback (most recent call last):
...
TypeError: (=(0 : 1 : 1)) is not a singular point of (=(Projective Plane
Curve over Rational Field defined by x^5 - y^5 + x*y^2*z^2 + z^5)
```

**is\_singular** ( $P=None$ )

Return whether this curve is singular or not, or if a point  $P$  is provided, whether  $P$  is a singular point of this curve.

INPUT:

- $P$  – (default: None) a point on this curve.

OUTPUT:

- Boolean. If no point  $P$  is provided, returns True or False depending on whether this curve is singular or not. If a point  $P$  is provided, returns True or False depending on whether  $P$  is or is not a singular point of this curve.

EXAMPLES:

Over  $\mathbb{Q}$ :

```
sage: F = QQ
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
sage: C = Curve(X^3-Y^2*Z)
sage: C.is_singular()
True
```

Over a finite field:

```
sage: F = GF(19)
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
```

```

sage: C = Curve(X^3+Y^3+Z^3)
sage: C.is_singular()
False
sage: D = Curve(X^4-X*Z^3)
sage: D.is_singular()
True
sage: E = Curve(X^5+19*Y^5+Z^5)
sage: E.is_singular()
True
sage: E = Curve(X^5+9*Y^5+Z^5)
sage: E.is_singular()
False

```

Over  $C$ :

```

sage: F = CC
sage: P2.<X,Y,Z> = ProjectiveSpace(F, 2)
sage: C = Curve(X)
sage: C.is_singular()
False
sage: D = Curve(Y^2*Z-X^3)
sage: D.is_singular()
True
sage: E = Curve(Y^2*Z-X^3+Z^3)
sage: E.is_singular()
False

```

Showing that [trac ticket #12187](#) is fixed:

```

sage: F.<X,Y,Z> = GF(2)[]
sage: G = Curve(X^2+Y*Z)
sage: G.is_singular()
False

```

```

sage: P.<x,y,z> = ProjectiveSpace(CC, 2)
sage: C = Curve([y^4 - x^3*z], P)
sage: Q = P([0, 0, 1])
sage: C.is_singular()
True

```

### **is\_transverse**( $C, P$ )

Return whether the intersection of this curve with the curve  $C$  at the point  $P$  is transverse.

The intersection at  $P$  is transverse if  $P$  is a nonsingular point of both curves, and if the tangents of the curves at  $P$  are distinct.

INPUT:

- $C$  – a curve in the ambient space of this curve.
- $P$  – a point in the intersection of both curves.

OUTPUT: Boolean.

EXAMPLES:

```

sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([x^2 - y^2], P)
sage: D = Curve([x - y], P)

```

```
sage: Q = P([1,1,0])
sage: C.is_transverse(D, Q)
False
```

```
sage: K = QuadraticField(-1)
sage: P.<x,y,z> = ProjectiveSpace(K, 2)
sage: C = Curve([y^2*z - K.0*x^3], P)
sage: D = Curve([z*x + y^2], P)
sage: Q = P([0,0,1])
sage: C.is_transverse(D, Q)
False
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([x^2 - 2*y^2 - 2*z^2], P)
sage: D = Curve([y - z], P)
sage: Q = P([2,1,1])
sage: C.is_transverse(D, Q)
True
```

**local\_coordinates** (*pt*, *n*)

Return local coordinates to precision *n* at the given point.

Behaviour is flaky - some choices of *n* are worse than others.

INPUT:

- *pt* - an  $F$ -rational point on  $X$  which is not a point of ramification for the projection  $(x,y) \rightarrow x$ .
- *n* - the number of terms desired

OUTPUT:  $x = x_0 + t$   $y = y_0 + \text{power series in } t$

EXAMPLES:

```
sage: FF = FiniteField(5)
sage: P2 = ProjectiveSpace(2, FF, names = ['x','y','z'])
sage: x, y, z = P2.coordinate_ring().gens()
sage: C = Curve(y^2*z^7-x^9-x*z^8)
sage: pt = C([2,3,1])
sage: C.local_coordinates(pt,9)      # todo: not implemented !!!!
[2 + t, 3 + 3*t^2 + t^3 + 3*t^4 + 3*t^6 + 3*t^7 + t^8 + 2*t^9 + 3*t^11,
 ↪ + 3*t^12]
```

**ordinary\_model** ()

Return a birational map from this curve to a plane curve with only ordinary singularities.

Currently only implemented over number fields. If not all of the coordinates of the non-ordinary singularities of this curve are contained in its base field, then the domain and codomain of the map returned will be defined over an extension. This curve must be irreducible.

OUTPUT:

- a scheme morphism from this curve to a curve with only ordinary singularities that defines a birational map between the two curves.

EXAMPLES:

```
sage: set_verbose(-1)
sage: K = QuadraticField(3)
sage: P.<x,y,z> = ProjectiveSpace(K, 2)
```

```

sage: C = Curve([x^5 - K.0*y*z^4], P)
sage: C.ordinary_model()
Scheme morphism:
  From: Projective Plane Curve over Number Field in a with defining
  polynomial x^2 - 3 defined by x^5 + (-a)*y*z^4
  To:   Projective Plane Curve over Number Field in a with defining
  polynomial x^2 - 3 defined by (-a)*x^5*y + (-4*a)*x^4*y^2 +
  (-6*a)*x^3*y^3 + (-4*a)*x^2*y^4 + (-a)*x*y^5 + (-a - 1)*x^5*z + (-4*a +
  5)*x^4*y*z + (-6*a - 10)*x^3*y^2*z + (-4*a + 10)*x^2*y^3*z + (-a -
  5)*x*y^4*z + y^5*z
  Defn: Defined on coordinates by sending (x : y : z) to
        (-1/4*x^2 - 1/2*x*y + 1/2*x*z + 1/2*y*z - 1/4*z^2 : 1/4*x^2 +
        1/2*x*y + 1/2*y*z - 1/4*z^2 : -1/4*x^2 + 1/4*z^2)

```

```

sage: set_verbose(-1)
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y^2*z^2 - x^4 - x^3*z], P)
sage: D = C.ordinary_model(); D # long time (2 seconds)
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by -x^4 -
  x^3*z + y^2*z^2
  To:   Projective Plane Curve over Rational Field defined by 4*x^6*y^3
  - 24*x^5*y^4 + 36*x^4*y^5 + 8*x^6*y^2*z - 40*x^5*y^3*z + 24*x^4*y^4*z +
  72*x^3*y^5*z - 4*x^6*y*z^2 + 8*x^5*y^2*z^2 - 56*x^4*y^3*z^2 +
  104*x^3*y^4*z^2 + 44*x^2*y^5*z^2 + 8*x^6*z^3 - 16*x^5*y*z^3 -
  24*x^4*y^2*z^3 + 40*x^3*y^3*z^3 + 48*x^2*y^4*z^3 + 8*x*y^5*z^3 -
  8*x^5*z^4 + 36*x^4*y*z^4 - 56*x^3*y^2*z^4 + 20*x^2*y^3*z^4 +
  40*x*y^4*z^4 - 16*y^5*z^4
  Defn: Defined on coordinates by sending (x : y : z) to
        (-3/64*x^4 + 9/64*x^2*y^2 - 3/32*x*y^3 - 1/16*x^3*z -
        1/8*x^2*y*z + 1/4*x*y^2*z - 1/16*y^3*z - 1/8*x*y*z^2 + 1/16*y^2*z^2 :
        -1/64*x^4 + 3/64*x^2*y^2 - 1/32*x*y^3 + 1/16*x*y^2*z - 1/16*y^3*z +
        1/16*y^2*z^2 : 3/64*x^4 - 3/32*x^3*y + 3/64*x^2*y^2 + 1/16*x^3*z -
        3/16*x^2*y*z + 1/8*x*y^2*z - 1/8*x*y*z^2 + 1/16*y^2*z^2)
sage: all([D.codomain().is_ordinary_singularity(Q) for Q in D.codomain().
  ↪singular_points()]) # long time
True

```

```

sage: set_verbose(-1)
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([(x^2 + y^2 - y*z - 2*z^2)*(y*z - x^2 + 2*z^2)*z + y^5], P)
sage: C.ordinary_model() # long time (5 seconds)
Scheme morphism:
  From: Projective Plane Curve over Number Field in a with defining
  polynomial y^2 - 2 defined by y^5 - x^4*z - x^2*y^2*z + 2*x^2*y*z^2 +
  y^3*z^2 + 4*x^2*z^3 + y^2*z^3 - 4*y*z^4 - 4*z^5
  To:   Projective Plane Curve over Number Field in a with defining
  polynomial y^2 - 2 defined by (-29*a + 1)*x^8*y^6 + (10*a + 158)*x^7*y^7
  + (-109*a - 31)*x^6*y^8 + (-80*a - 198)*x^8*y^5*z + (531*a +
  272)*x^7*y^6*z + (170*a - 718)*x^6*y^7*z + (19*a - 636)*x^5*y^8*z +
  (-200*a - 628)*x^8*y^4*z^2 + (1557*a - 114)*x^7*y^5*z^2 + (2197*a -
  2449)*x^6*y^6*z^2 + (1223*a - 3800)*x^5*y^7*z^2 + (343*a -
  1329)*x^4*y^8*z^2 + (-323*a - 809)*x^8*y^3*z^3 + (1630*a -
  631)*x^7*y^4*z^3 + (4190*a - 3126)*x^6*y^5*z^3 + (3904*a -
  7110)*x^5*y^6*z^3 + (1789*a - 5161)*x^4*y^7*z^3 + (330*a -
  1083)*x^3*y^8*z^3 + (-259*a - 524)*x^8*y^2*z^4 + (720*a -
  605)*x^7*y^3*z^4 + (3082*a - 2011)*x^6*y^4*z^4 + (4548*a -

```

```

5462)*x^5*y^5*z^4 + (2958*a - 6611)*x^4*y^6*z^4 + (994*a -
2931)*x^3*y^7*z^4 + (117*a - 416)*x^2*y^8*z^4 + (-108*a - 184)*x^8*y*z^5
+ (169*a - 168)*x^7*y^2*z^5 + (831*a - 835)*x^6*y^3*z^5 + (2225*a -
1725)*x^5*y^4*z^5 + (1970*a - 3316)*x^4*y^5*z^5 + (952*a -
2442)*x^3*y^6*z^5 + (217*a - 725)*x^2*y^7*z^5 + (16*a - 77)*x*y^8*z^5 +
(-23*a - 35)*x^8*z^6 + (43*a + 24)*x^7*y*z^6 + (21*a - 198)*x^6*y^2*z^6
+ (377*a - 179)*x^5*y^3*z^6 + (458*a - 537)*x^4*y^4*z^6 + (288*a -
624)*x^3*y^5*z^6 + (100*a - 299)*x^2*y^6*z^6 + (16*a - 67)*x*y^7*z^6 -
5*y^8*z^6
Defn: Defined on coordinates by sending (x : y : z) to
((-5/128*a - 5/128)*x^4 + (-5/32*a + 5/32)*x^3*y + (-1/16*a +
3/32)*x^2*y^2 + (1/16*a - 1/16)*x*y^3 + (1/32*a - 1/32)*y^4 - 1/32*x^3*z
+ (3/16*a - 5/8)*x^2*y*z + (1/8*a - 5/16)*x*y^2*z + (1/8*a +
5/32)*x^2*z^2 + (-3/16*a + 5/16)*x*y*z^2 + (-3/16*a - 1/16)*y^2*z^2 +
1/16*x*z^3 + (1/4*a + 1/4)*y*z^3 + (-3/32*a - 5/32)*z^4 : (-5/128*a -
5/128)*x^4 + (5/32*a)*x^3*y + (3/32*a + 3/32)*x^2*y^2 + (-1/16*a)*x*y^3
+ (-1/32*a - 1/32)*y^4 - 1/32*x^3*z + (-11/32*a)*x^2*y*z + (1/8*a +
5/16)*x*y^2*z + (3/16*a + 1/4)*y^3*z + (1/8*a + 5/32)*x^2*z^2 + (-1/16*a
- 3/8)*x*y*z^2 + (-3/8*a - 9/16)*y^2*z^2 + 1/16*x*z^3 + (5/16*a +
1/2)*y*z^3 + (-3/32*a - 5/32)*z^4 : (1/64*a + 3/128)*x^4 + (-1/32*a -
1/32)*x^3*y + (3/32*a - 9/32)*x^2*y^2 + (1/16*a - 3/16)*x*y^3 - 1/32*y^4
+ (3/32*a + 1/8)*x^2*y*z + (-1/8*a + 1/8)*x*y^2*z + (-1/16*a)*y^3*z +
(-1/16*a - 3/32)*x^2*z^2 + (1/16*a + 1/16)*x*y*z^2 + (3/16*a +
3/16)*y^2*z^2 + (-3/16*a - 1/4)*y*z^3 + (1/16*a + 3/32)*z^4)

```

**plot** (\*args, \*\*kws)

Plot the real points of an affine patch of this projective plane curve.

INPUT:

- self - an affine plane curve
- patch - (optional) the affine patch to be plotted; if not specified, the patch corresponding to the last projective coordinate being nonzero
- \*args - optional tuples (variable, minimum, maximum) for plotting dimensions
- \*\*kws - optional keyword arguments passed on to `implicit_plot`

EXAMPLES:

A cuspidal curve:

```

sage: R.<x, y, z> = QQ[]
sage: C = Curve(x^3 - y^2*z)
sage: C.plot()
Graphics object consisting of 1 graphics primitive

```

The other affine patches of the same curve:

```

sage: C.plot(patch=0)
Graphics object consisting of 1 graphics primitive
sage: C.plot(patch=1)
Graphics object consisting of 1 graphics primitive

```

An elliptic curve:

```

sage: E = EllipticCurve('101a')
sage: C = Curve(E)
sage: C.plot()

```



```
Graphics object consisting of 1 graphics primitive
sage: C.plot(patch=0)
Graphics object consisting of 1 graphics primitive
sage: C.plot(patch=1)
Graphics object consisting of 1 graphics primitive
```

A hyperelliptic curve:

```
sage: P.<x> = QQ[]
sage: f = 4*x^5 - 30*x^3 + 45*x - 22
sage: C = HyperellipticCurve(f)
sage: C.plot()
Graphics object consisting of 1 graphics primitive
sage: C.plot(patch=0)
Graphics object consisting of 1 graphics primitive
sage: C.plot(patch=1)
Graphics object consisting of 1 graphics primitive
```

### **quadratic\_transform()**

Return a birational map from this curve to the proper transform of this curve with respect to the standard Cremona transformation.

The standard Cremona transformation is the birational automorphism of  $\mathbb{P}^2$  defined  $(x : y : z) \mapsto (yz : xz : xy)$ .

OUTPUT:

- a scheme morphism representing the restriction of the standard Cremona transformation from this curve to the proper transform.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve(x^3*y - z^4 - z^2*x^2, P)
sage: C.quadratic_transform()
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by x^3*y -
  x^2*z^2 - z^4
  To: Projective Plane Curve over Rational Field defined by -x^3*y -
  x*y*z^2 + z^4
  Defn: Defined on coordinates by sending (x : y : z) to
        (y*z : x*z : x*y)
```

```
sage: P.<x,y,z> = ProjectiveSpace(GF(17), 2)
sage: C = P.curve([y^7*z^2 - 16*x^9 + x*y*z^7 + 2*z^9])
sage: C.quadratic_transform()
Scheme morphism:
  From: Projective Plane Curve over Finite Field of size 17 defined by
  x^9 + y^7*z^2 + x*y*z^7 + 2*z^9
  To: Projective Plane Curve over Finite Field of size 17 defined by
  2*x^9*y^7 + x^8*y^6*z^2 + x^9*z^7 + y^7*z^9
  Defn: Defined on coordinates by sending (x : y : z) to
        (y*z : x*z : x*y)
```

### **rational\_parameterization()**

Return a rational parameterization of this curve.

This curve must have rational coefficients and be absolutely irreducible (i.e. irreducible over the algebraic closure of the rational field). The curve must also be rational (have geometric genus zero).

The rational parameterization may have coefficients in a quadratic extension of the rational field.

OUTPUT:

- a birational map between  $\mathbb{P}^1$  and this curve, given as a scheme morphism.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y^2*z - x^3], P)
sage: C.rational_parameterization()
Scheme morphism:
  From: Projective Space of dimension 1 over Rational Field
  To:   Projective Plane Curve over Rational Field defined by -x^3 + y^2*z
  Defn: Defined on coordinates by sending (s : t) to
        (s^2*t : s^3 : t^3)
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([x^3 - 4*y*z^2 + x*z^2 - x*y*z], P)
sage: C.rational_parameterization()
Scheme morphism:
  From: Projective Space of dimension 1 over Rational Field
  To:   Projective Plane Curve over Rational Field defined by x^3 - x*y*z +
↪x*z^2 - 4*y*z^2
  Defn: Defined on coordinates by sending (s : t) to
        (4*s^2*t + s*t^2 : s^2*t + t^3 : 4*s^3 + s^2*t)
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([x^2 + y^2 + z^2], P)
sage: C.rational_parameterization()
Scheme morphism:
  From: Projective Space of dimension 1 over Number Field in a with defining
↪polynomial a^2 + 1
  To:   Projective Plane Curve over Number Field in a with defining
        polynomial a^2 + 1 defined by x^2 + y^2 + z^2
  Defn: Defined on coordinates by sending (s : t) to
        ((-a)*s^2 + (-a)*t^2 : s^2 - t^2 : 2*s*t)
```

**riemann\_surface** (\*\*kwargs)

Return the complex riemann surface determined by this curve

OUTPUT:

- RiemannSurface object

EXAMPLES:

```
sage: R.<x,y,z>=QQ[]
sage: C=Curve(x^3+3*y^3+5*z^3)
sage: C.riemann_surface()
Riemann surface defined by polynomial f = x0^3 + 3*x1^3 + 5 = 0, with 53 bits
↪of precision
```

**tangents** (P, factor=True)

Return the tangents of this projective plane curve at the point P.

These are found by homogenizing the tangents of an affine patch of this curve containing P. The point P must be a point on this curve.

INPUT:

- $P$  – a point on this curve.
- `factor` – (default: `True`) whether to attempt computing the polynomials of the individual tangent lines over the base field of this curve, or to just return the polynomial corresponding to the union of the tangent lines (which requires fewer computations).

OUTPUT:

- a list of polynomials in the coordinate ring of the ambient space of this curve.

EXAMPLES:

```
sage: set_verbose(-1)
sage: P.<x,y,z> = ProjectiveSpace(QQbar, 2)
sage: C = Curve([x^3*y + 2*x^2*y^2 + x*y^3 + x^3*z + 7*x^2*y*z + 14*x*y^2*z +
↪ 9*y^3*z], P)
sage: Q = P([0,0,1])
sage: C.tangents(Q)
[x + 4.147899035704788?y, x + (1.426050482147607? + 0.3689894074818041?*I)*y,
x + (1.426050482147607? - 0.3689894074818041?*I)*y]
sage: C.tangents(Q, factor=False)
[6*x^3 + 42*x^2*y + 84*x*y^2 + 54*y^3]
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ,2)
sage: C = P.curve([x^2*y^3*z^4 - y^6*z^3 - 4*x^2*y^4*z^3 - 4*x^4*y^2*z^3 +
↪ 3*y^7*z^2 + \
10*x^2*y^5*z^2 + 9*x^4*y^3*z^2 + 5*x^6*y*z^2 - 3*y^8*z - 9*x^2*y^6*z - 11*x^
↪ 4*y^4*z - \
7*x^6*y^2*z - 2*x^8*z + y^9 + 2*x^2*y^7 + 3*x^4*y^5 + 4*x^6*y^3 + 2*x^8*y])
sage: Q = P([0,1,1])
sage: C.tangents(Q)
[-y + z, 3*x^2 - y^2 + 2*y*z - z^2]
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = P.curve([z^3*x + y^4 - x^2*z^2])
sage: Q = P([1,1,1])
sage: C.tangents(Q)
Traceback (most recent call last):
...
TypeError: (=(1 : 1 : 1)) is not a point on (=Projective Plane Curve
over Rational Field defined by y^4 - x^2*z^2 + x*z^3)
```

**class** `sage.schemes.curves.projective_curve.ProjectivePlaneCurve_finite_field`( $A$ ,  $f$ )

Bases: `sage.schemes.curves.projective_curve.ProjectivePlaneCurve`

**rational\_points** (*algorithm*='enum', *sort*=`True`)

Return the rational points on this curve computed via enumeration.

INPUT:

- *algorithm* (string, default: 'enum') – the algorithm to use. Currently this is ignored.
- *sort* (boolean, default `True`) – whether the output points should be sorted. If `False`, the order of the output is non-deterministic.

OUTPUT:

A list of all the rational points on the curve defined over its base field, possibly sorted.

---

**Note:** This is a slow Python-level implementation.

---

EXAMPLES:

```
sage: F = GF(7)
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
sage: C = Curve(X^3+Y^3-Z^3)
sage: C.rational_points()
[(0 : 1 : 1), (0 : 2 : 1), (0 : 4 : 1), (1 : 0 : 1), (2 : 0 : 1), (3 : 1 : 0),
↪ (4 : 0 : 1), (5 : 1 : 0), (6 : 1 : 0)]
```

```
sage: F = GF(1237)
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
sage: C = Curve(X^7+7*Y^6*Z+Z^4*X^2*Y*89)
sage: len(C.rational_points())
1237
```

```
sage: F = GF(2^6, 'a')
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
sage: C = Curve(X^5+11*X*Y*Z^3 + X^2*Y^3 - 13*Y^2*Z^3)
sage: len(C.rational_points())
104
```

```
sage: R.<x,y,z> = GF(2)[]
sage: f = x^3*y + y^3*z + x*z^3
sage: C = Curve(f); pts = C.rational_points()
sage: pts
[(0 : 0 : 1), (0 : 1 : 0), (1 : 0 : 0)]
```

#### **rational\_points\_iterator()**

Return a generator object for the rational points on this curve.

INPUT:

- self – a projective curve

OUTPUT:

A generator of all the rational points on the curve defined over its base field.

EXAMPLES:

```
sage: F = GF(37)
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
sage: C = Curve(X^7+Y*X*Z^5*55+Y^7*12)
sage: len(list(C.rational_points_iterator()))
37
```

```
sage: F = GF(2)
sage: P2.<X,Y,Z> = ProjectiveSpace(F,2)
sage: C = Curve(X*Y*Z)
sage: a = C.rational_points_iterator()
sage: next(a)
(1 : 0 : 0)
sage: next(a)
(0 : 1 : 0)
sage: next(a)
```

```

(1 : 1 : 0)
sage: next(a)
(0 : 0 : 1)
sage: next(a)
(1 : 0 : 1)
sage: next(a)
(0 : 1 : 1)
sage: next(a)
Traceback (most recent call last):
...
StopIteration

```

```

sage: F = GF(3^2, 'a')
sage: P2.<X,Y,Z> = ProjectiveSpace(F, 2)
sage: C = Curve(X^3+5*Y^2*Z-33*X*Y*X)
sage: b = C.rational_points_iterator()
sage: next(b)
(0 : 1 : 0)
sage: next(b)
(0 : 0 : 1)
sage: next(b)
(2*a + 2 : a : 1)
sage: next(b)
(2 : a + 1 : 1)
sage: next(b)
(a + 1 : 2*a + 1 : 1)
sage: next(b)
(1 : 2 : 1)
sage: next(b)
(2*a + 2 : 2*a : 1)
sage: next(b)
(2 : 2*a + 2 : 1)
sage: next(b)
(a + 1 : a + 2 : 1)
sage: next(b)
(1 : 1 : 1)
sage: next(b)
Traceback (most recent call last):
...
StopIteration

```

**class** sage.schemes.curves.projective\_curve.**ProjectivePlaneCurve\_prime\_finite\_field**( $A$ ,  $f$ )  
 Bases: *sage.schemes.curves.projective\_curve.ProjectivePlaneCurve\_finite\_field*

**rational\_points** (*algorithm*='enum', *sort*=True)

INPUT:

- *algorithm* - string:
- 'enum' - straightforward enumeration
- 'bn' - via Singular's brnoeth package.

EXAMPLES:

```

sage: x, y, z = PolynomialRing(GF(5), 3, 'xyz').gens()
sage: f = y^2*z^7 - x^9 - x*z^8

```

```

sage: C = Curve(f); C
Projective Plane Curve over Finite Field of size 5 defined by
-x^9 + y^2*z^7 - x*z^8
sage: C.rational_points()
[(0 : 0 : 1), (0 : 1 : 0), (2 : 2 : 1), (2 : 3 : 1),
 (3 : 1 : 1), (3 : 4 : 1)]
sage: C = Curve(x - y + z)
sage: C.rational_points()
[(0 : 1 : 1), (1 : 1 : 0), (1 : 2 : 1), (2 : 3 : 1),
 (3 : 4 : 1), (4 : 0 : 1)]
sage: C = Curve(x*z+z^2)
sage: C.rational_points('all')
[(0 : 1 : 0), (1 : 0 : 0), (1 : 1 : 0), (2 : 1 : 0),
 (3 : 1 : 0), (4 : 0 : 1), (4 : 1 : 0), (4 : 1 : 1),
 (4 : 2 : 1), (4 : 3 : 1), (4 : 4 : 1)]

```

---

**Note:** The Brill-Noether package does not always work (i.e., the ‘bn’ algorithm). When it fails a `RuntimeError` exception is raised.

---

### **riemann\_roch\_basis** (*D*)

Return a basis for the Riemann-Roch space corresponding to *D*.

This uses Singular’s Brill-Noether implementation.

INPUT:

- *D* - a divisor

OUTPUT:

A list of function field elements that form a basis of the Riemann-Roch space

EXAMPLES:

```

sage: R.<x,y,z> = GF(2) []
sage: f = x^3*y + y^3*z + x*z^3
sage: C = Curve(f); pts = C.rational_points()
sage: D = C.divisor([ (4, pts[0]), (4, pts[2]) ])
sage: C.riemann_roch_basis(D)
[x/y, 1, z/y, z^2/y^2, z/x, z^2/(x*y)]

```

```

sage: R.<x,y,z> = GF(5) []
sage: f = x^7 + y^7 + z^7
sage: C = Curve(f); pts = C.rational_points()
sage: D = C.divisor([ (3, pts[0]), (-1, pts[1]), (10, pts[5]) ])
sage: C.riemann_roch_basis(D)
[(-x - 2*y)/(-2*x - 2*y), (-x + z)/(x + y)]

```

---

**Note:** Currently this only works over prime field and divisors supported on rational points.

---

## GENERIC CURVES.

```
class sage.schemes.curves.curve.Curve_generic(A, polynomials)
    Bases: sage.schemes.generic.algebraic_scheme.AlgebraicScheme_subscheme
```

Generic curve class.

EXAMPLES:

```
sage: A.<x,y,z> = AffineSpace(QQ, 3)
sage: C = Curve([x-y, z-2])
sage: loads(C.dumps()) == C
True
```

```
change_ring(R)
```

Return a new curve which is this curve coerced to R.

INPUT:

- R – ring or embedding.

OUTPUT:

- a new curve which is this curve coerced to R.

EXAMPLES:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([x^2 - y^2, z*y - 4/5*w^2], P)
sage: C.change_ring(QuadraticField(-1))
Projective Curve over Number Field in a with defining polynomial x^2 + 1
defined by x^2 - y^2, y*z - 4/5*w^2
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^3 + a^2 - 1)
sage: A.<x,y> = AffineSpace(K, 2)
sage: C = Curve([K.0*x^2 - x + y^3 - 11], A)
sage: L = K.embeddings(QQbar)
sage: C.change_ring(L[0])
Affine Plane Curve over Algebraic Field defined by y^3 +
(-0.8774388331233464? - 0.744861766619745?*I)*x^2 - x - 11
```

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = P.curve([y*x - 18*x^2 + 17*z^2])
sage: C.change_ring(GF(17))
Projective Plane Curve over Finite Field of size 17 defined by -x^2 + x*y
```

**defining\_polynomial()**

Return the defining polynomial of the curve.

EXAMPLES:

```
sage: x,y,z = PolynomialRing(QQ, 3, names='x,y,z').gens()
sage: C = Curve(y^2*z - x^3 - 17*x*z^2 + y*z^2)
sage: C.defining_polynomial()
-x^3 + y^2*z - 17*x*z^2 + y*z^2
```

**divisor**(*v*, *base\_ring=None*, *check=True*, *reduce=True*)

Return the divisor specified by *v*.

**Warning:** The coefficients of the divisor must be in the base ring and the terms must be reduced. If you set *check=False* and/or *reduce=False* it is your responsibility to pass a valid object *v*.

**divisor\_group**(*base\_ring=None*)

Return the divisor group of the curve.

INPUT:

- *base\_ring* – the base ring of the divisor group. Usually, this is **Z** (default) or **Q**.

OUTPUT:

The divisor group of the curve.

EXAMPLES:

```
sage: x,y,z = PolynomialRing(QQ, 3, names='x,y,z').gens()
sage: C = Curve(y^2*z - x^3 - 17*x*z^2 + y*z^2)
sage: Cp = Curve(y^2*z - x^3 - 17*x*z^2 + y*z^2)
sage: C.divisor_group() is Cp.divisor_group()
True
```

**genus()**

The geometric genus of the curve.

**geometric\_genus()**

Return the geometric genus of the curve.

This is by definition the genus of the normalization of the projective closure of the curve over the algebraic closure of the base field; the base field must be a prime field.

---

**Note:** This calls Singular's `genus` command.

---

EXAMPLES:

Examples of projective curves.

```
sage: P2 = ProjectiveSpace(2, GF(5), names=['x','y','z'])
sage: x, y, z = P2.coordinate_ring().gens()
sage: C = Curve(y^2*z - x^3 - 17*x*z^2 + y*z^2)
sage: C.geometric_genus()
1
sage: C = Curve(y^2*z - x^3)
sage: C.geometric_genus()
0
```



```
sage: C = Curve(x^10 + y^7*z^3 + z^10)
sage: C.geometric_genus()
3
```

Examples of affine curves.

```
sage: x, y = PolynomialRing(GF(5), 2, 'xy').gens()
sage: C = Curve(y^2 - x^3 - 17*x + y)
sage: C.geometric_genus()
1
sage: C = Curve(y^2 - x^3)
sage: C.geometric_genus()
0
sage: C = Curve(x^10 + y^7 + 1)
sage: C.geometric_genus()
3
```

### **intersection\_points** (*C*, *F=None*)

Return the points in the intersection of this curve and the curve *C*.

If the intersection of these two curves has dimension greater than zero, and if the base ring of this curve is not a finite field, then an error is returned.

INPUT:

- *C* – a curve in the same ambient space as this curve.
- *F* – (default: None). Field over which to compute the intersection points. If not specified, the base ring of this curve is used.

OUTPUT:

- a list of points in the ambient space of this curve.

EXAMPLES:

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 + a + 1)
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([y^2 - w*z, w^3 - y^3], P)
sage: D = Curve([x*y - w*z, z^3 - y^3], P)
sage: C.intersection_points(D, F=K)
[(-b - 1 : -b - 1 : b : 1), (b : b : -b - 1 : 1), (1 : 0 : 0 : 0), (1 : 1 : 1 :
↪: 1)]
```

```
sage: A.<x,y> = AffineSpace(GF(7), 2)
sage: C = Curve([y^3 - x^3], A)
sage: D = Curve([-x*y^3 + y^4 - 2*x^3 + 2*x^2*y], A)
sage: C.intersection_points(D)
[(0, 0), (1, 1), (2, 2), (3, 3), (4, 4), (5, 3), (5, 5), (5, 6), (6, 6)]
```

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y^3 - x^3], A)
sage: D = Curve([-x*y^3 + y^4 - 2*x^3 + 2*x^2*y], A)
sage: C.intersection_points(D)
Traceback (most recent call last):
...
NotImplementedError: the intersection must have dimension zero or
(=Rational Field) must be a finite field
```

**intersects\_at** (*C, P*)

Return whether the point *P* is or is not in the intersection of this curve with the curve *C*.

INPUT:

- *C* – a curve in the same ambient space as this curve.
- *P* – a point in the ambient space of this curve.

OUTPUT:

Boolean.

EXAMPLES:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([x^2 - z^2, y^3 - w*x^2], P)
sage: D = Curve([w^2 - 2*x*y + z^2, y^2 - w^2], P)
sage: Q1 = P([1,1,-1,1])
sage: C.intersects_at(D, Q1)
True
sage: Q2 = P([0,0,1,-1])
sage: C.intersects_at(D, Q2)
False
```

```
sage: A.<x,y> = AffineSpace(GF(13), 2)
sage: C = Curve([y + 12*x^5 + 3*x^3 + 7], A)
sage: D = Curve([y^2 + 7*x^2 + 8], A)
sage: Q1 = A([9,6])
sage: C.intersects_at(D, Q1)
True
sage: Q2 = A([3,7])
sage: C.intersects_at(D, Q2)
False
```

**is\_singular** (*P=None*)

Return whether *P* is a singular point of this curve, or if no point is passed, whether this curve is singular or not.

This just uses the `is_smooth` function for algebraic subschemes.

INPUT:

- *P* – (default: `None`) a point on this curve.

OUTPUT:

- Boolean. If a point *P* is provided, and if *P* lies on this curve, returns `True` if *P* is a singular point of this curve, and `False` otherwise. If no point is provided, returns `True` or `False` depending on whether this curve is or is not singular, respectively.

EXAMPLES:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = P.curve([y^2 - x^2 - z^2, z - w])
sage: C.is_singular()
False
```

```
sage: A.<x,y,z> = AffineSpace(GF(11), 3)
sage: C = A.curve([y^3 - z^5, x^5 - y + 1])
sage: Q = A([7,0,0])
```

```
sage: C.is_singular(Q)
True
```

**singular\_points** (*F=None*)

Return the set of singular points of this curve.

INPUT:

- *F* – (default: None) field over which to find the singular points. If not given, the base ring of this curve is used.

OUTPUT:

- a list of points in the ambient space of this curve.

EXAMPLES:

```
sage: A.<x,y,z> = AffineSpace(QQ, 3)
sage: C = Curve([y^2 - x^5, x - z], A)
sage: C.singular_points()
[(0, 0, 0)]
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^8 - a^4 + 1)
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([359/12*x*y^2*z^2 + 2*y*z^4 + 187/12*y^3*z^2 + x*z^4\
+ 67/3*x^2*y*z^2 + 117/4*y^5 + 9*x^5 + 6*x^3*z^2 + 393/4*x*y^4\
+ 145*x^2*y^3 + 115*x^3*y^2 + 49*x^4*y], P)
sage: C.singular_points(K)
[(b^6 : -b^6 : 1),
 (-b^6 : b^6 : 1),
 (1/2*b^5 + 1/2*b^3 - 1/2*b - 1 : 1 : 0),
 (-1/2*b^5 - 1/2*b^3 + 1/2*b - 1 : 1 : 0),
 (2/3*b^4 - 1/3 : 0 : 1),
 (-2/3*b^4 + 1/3 : 0 : 1)]
```

**singular\_subscheme** ()

Return the subscheme of singular points of this curve.

OUTPUT:

- a subscheme in the ambient space of this curve.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(CC, 2)
sage: C = Curve([y^4 - 2*x^5 - x^2*y], A)
sage: C.singular_subscheme()
Closed subscheme of Affine Space of dimension 2 over Complex Field with
53 bits of precision defined by:
(-2.000000000000000)*x^5 + y^4 - x^2*y,
(-10.000000000000000)*x^4 + (-2.000000000000000)*x*y,
4.000000000000000*y^3 - x^2
```

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([y^8 - x^2*z*w^5, w^2 - 2*y^2 - x*z], P)
sage: C.singular_subscheme()
Closed subscheme of Projective Space of dimension 3 over Rational Field
defined by:
y^8 - x^2*z*w^5,
```

```
-2*y^2 - x*z + w^2,  
-x^3*y*z^4 + 3*x^2*y*z^3*w^2 - 3*x*y*z^2*w^4 + 8*x*y*z*w^5 + y*z*w^6,  
x^2*z*w^5,  
-5*x^2*z^2*w^4 - 4*x*z*w^6,  
x^4*y*z^3 - 3*x^3*y*z^2*w^2 + 3*x^2*y*z*w^4 - 4*x^2*y*w^5 - x*y*w^6,  
-2*x^3*y*z^3*w + 6*x^2*y*z^2*w^3 - 20*x^2*y*z*w^4 - 6*x*y*z*w^5 +  
2*y*w^7,  
-5*x^3*z*w^4 - 2*x^2*w^6
```

**union** (*other*)

Return the union of self and other.

EXAMPLES:

```
sage: x,y,z = PolynomialRing(QQ, 3, names='x,y,z').gens()  
sage: C1 = Curve(z - x)  
sage: C2 = Curve(y - x)  
sage: C1.union(C2).defining_polynomial()  
x^2 - x*y - x*z + y*z
```

## CURVE POINTS

### EXAMPLES:

We can create points on projective curves:

```
sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([x^3 - 2*x*z^2 - y^3, z^3 - w^3 - x*y*z], P)
sage: Q = C([1,1,0,0])
sage: type(Q)
<class 'sage.schemes.curves.point.ProjectiveCurvePoint_field'>
sage: Q.parent()
Set of rational points of Projective Curve over Rational Field defined
by x^3 - y^3 - 2*x*z^2, -x*y*z + z^3 - w^3
```

or on affine curves:

```
sage: A.<x,y> = AffineSpace(GF(23), 2)
sage: C = Curve([y - y^4 + 17*x^2 - 2*x + 22], A)
sage: Q = C([22,21])
sage: type(Q)
<class 'sage.schemes.curves.point.AffinePlaneCurvePoint_finite_field'>
sage: Q.parent()
Set of rational points of Affine Plane Curve over Finite Field of size
23 defined by -y^4 - 6*x^2 - 2*x + y - 1
```

### AUTHORS:

- Grayson Jorgenson (2016-6): initial version

```
class sage.schemes.curves.point.AffineCurvePoint_field(X,v,check=True)
    Bases: sage.schemes.affine.affine_point.SchemeMorphism_point_affine_field

    is_singular()
        Return whether this point is a singular point of the affine curve it is on.

    OUTPUT: Boolean.
```

### EXAMPLES:

```
sage: K = QuadraticField(-1)
sage: A.<x,y,z> = AffineSpace(K, 3)
sage: C = Curve([(x^4 + 2*z + 2)*y, z - y + 1])
sage: Q1 = C([0,0,-1])
sage: Q1.is_singular()
True
sage: Q2 = C([-K.gen(),0,-1])
sage: Q2.is_singular()
False
```

---

```
class sage.schemes.curves.point.AffinePlaneCurvePoint_field(X, v, check=True)
    Bases: sage.schemes.curves.point.AffineCurvePoint_field
```

**is\_ordinary\_singularity()**

Return whether this point is an ordinary singularity of the affine plane curve it is on.

OUTPUT: Boolean.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([x^5 - x^3*y^2 + 5*x^4 - x^3*y - 3*x^2*y^2 + x*y^3 + 10*x^3_
↪ - 3*x^2*y - \
3*x*y^2 + y^3 + 10*x^2 - 3*x*y - y^2 + 5*x - y + 1])
sage: Q = C([-1,0])
sage: Q.is_ordinary_singularity()
True
```

```
sage: A.<x,y> = AffineSpace(GF(7), 2)
sage: C = A.curve([y^2 - x^7 - 6*x^3])
sage: Q = C([0,0])
sage: Q.is_ordinary_singularity()
False
```

**is\_transverse(D)**

Return whether the intersection of the curve D at this point with the curve this point is on is transverse or not.

INPUT:

- D – a curve in the same ambient space as the curve this point is on.

OUTPUT: Boolean.

EXAMPLES:

```
sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = Curve([y - x^2], A)
sage: D = Curve([y], A)
sage: Q = C([0,0])
sage: Q.is_transverse(D)
False
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 - 2)
sage: A.<x,y> = AffineSpace(K, 2)
sage: C = Curve([y^2 + x^2 - 1], A)
sage: D = Curve([y - x], A)
sage: Q = C([-1/2*b, -1/2*b])
sage: Q.is_transverse(D)
True
```

**multiplicity()**

Return the multiplicity of this point with respect to the affine curve it is on.

OUTPUT: Integer.

EXAMPLES:

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([2*x^7 - 3*x^6*y + x^5*y^2 + 31*x^6 - 40*x^5*y + 13*x^4*y^2,
↪ - x^3*y^3\
+ 207*x^5 - 228*x^4*y + 70*x^3*y^2 - 7*x^2*y^3 + 775*x^4 - 713*x^3*y + 193*x^
↪ 2*y^2 - 19*x*y^3\
+ y^4 + 1764*x^3 - 1293*x^2*y + 277*x*y^2 - 22*y^3 + 2451*x^2 - 1297*x*y +
↪ 172*y^2 + 1935*x\
- 570*y + 675])
sage: Q = C([-2,1])
sage: Q.multiplicity()
4

```

**tangents()**

Return the tangents at this point of the affine plane curve this point is on.

OUTPUT:

- a list of polynomials in the coordinate ring of the ambient space of the curve this point is on.

EXAMPLES:

```

sage: A.<x,y> = AffineSpace(QQ, 2)
sage: C = A.curve([x^5 - x^3*y^2 + 5*x^4 - x^3*y - 3*x^2*y^2 + x*y^3 + 10*x^3,
↪ - 3*x^2*y - \
3*x*y^2 + y^3 + 10*x^2 - 3*x*y - y^2 + 5*x - y + 1])
sage: Q = C([-1,0])
sage: Q.tangents()
[y, x + 1, x - y + 1, x + y + 1]

```

```

class sage.schemes.curves.point.AffinePlaneCurvePoint_finite_field(X, v,
                                                                    check=True)
Bases: sage.schemes.curves.point.AffinePlaneCurvePoint_field, sage.schemes.
affine.affine_point.SchemeMorphism_point_affine_finite_field

```

```

class sage.schemes.curves.point.ProjectiveCurvePoint_field(X, v, check=True)
Bases: sage.schemes.projective.projective_point.SchemeMorphism_point_projective_field

```

**is\_singular()**

Return whether this point is a singular point of the projective curve it is on.

OUTPUT: Boolean.

EXAMPLES:

```

sage: P.<x,y,z,w> = ProjectiveSpace(QQ, 3)
sage: C = Curve([x^2 - y^2, z - w], P)
sage: Q1 = C([0,0,1,1])
sage: Q1.is_singular()
True
sage: Q2 = C([1,1,1,1])
sage: Q2.is_singular()
False

```

```

class sage.schemes.curves.point.ProjectivePlaneCurvePoint_field(X, v,
                                                                    check=True)
Bases: sage.schemes.curves.point.ProjectiveCurvePoint_field

```

**is\_ordinary\_singularity()**

Return whether this point is an ordinary singularity of the projective plane curve it is on.

OUTPUT: Boolean.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([z^6 - x^6 - x^3*z^3 - x^3*y^3])
sage: Q = C([0,1,0])
sage: Q.is_ordinary_singularity()
False
```

```
sage: R.<a> = QQ[]
sage: K.<b> = NumberField(a^2 - 3)
sage: P.<x,y,z> = ProjectiveSpace(K, 2)
sage: C = P.curve([x^2*y^3*z^4 - y^6*z^3 - 4*x^2*y^4*z^3 - 4*x^4*y^2*z^3 +
↪ 3*y^7*z^2 + 10*x^2*y^5*z^2\
+ 9*x^4*y^3*z^2 + 5*x^6*y*z^2 - 3*y^8*z - 9*x^2*y^6*z - 11*x^4*y^4*z - 7*x^
↪ 6*y^2*z - 2*x^8*z + y^9\
+ 2*x^2*y^7 + 3*x^4*y^5 + 4*x^6*y^3 + 2*x^8*y])
sage: Q = C([-1/2, 1/2, 1])
sage: Q.is_ordinary_singularity()
True
```

### **is\_transverse(D)**

Return whether the intersection of the curve D at this point with the curve this point is on is transverse or not.

INPUT:

- D – a curve in the same ambient space as the curve this point is on.

OUTPUT: Boolean.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([x^2 - 2*y^2 - 2*z^2], P)
sage: D = Curve([y - z], P)
sage: Q = C([2,1,1])
sage: Q.is_transverse(D)
True
```

```
sage: P.<x,y,z> = ProjectiveSpace(GF(17), 2)
sage: C = Curve([x^4 - 16*y^3*z], P)
sage: D = Curve([y^2 - z*x], P)
sage: Q = C([0,0,1])
sage: Q.is_transverse(D)
False
```

### **multiplicity()**

Return the multiplicity of this point with respect to the projective curve it is on.

OUTPUT: Integer.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(GF(17), 2)
sage: C = Curve([y^3*z - 16*x^4], P)
sage: Q = C([0,0,1])
sage: Q.multiplicity()
3
```



**tangents()**

Return the tangents at this point of the projective plane curve this point is on.

OUTPUT:

- a list of polynomials in the coordinate ring of the ambient space of the curve this point is on.

EXAMPLES:

```
sage: P.<x,y,z> = ProjectiveSpace(QQ, 2)
sage: C = Curve([y^2*z^3 - x^5 + 18*y*x*z^3])
sage: Q = C([0,0,1])
sage: Q.tangents()
[y, 18*x + y]
```

**class** `sage.schemes.curves.point.ProjectivePlaneCurvePoint_finite_field`(*X*, *v*, *check=True*)

Bases: `sage.schemes.curves.point.ProjectivePlaneCurvePoint_field`, `sage.schemes.projective.projective_point.SchemeMorphism_point_projective_finite_field`



## PLANE CONIC CONSTRUCTOR

## AUTHORS:

- Marco Streng (2010-07-20)
- Nick Alexander (2008-01-08)

`sage.schemes.plane_conics.constructor.Conic` (*base\_field*, *F=None*, *names=None*,  
*unique=True*)

Return the plane projective conic curve defined by  $F$  over  $\text{base\_field}$ .

The input form `Conic(F, names=None)` is also accepted, in which case the fraction field of the base ring of  $F$  is used as base field.

## INPUT:

- `base_field` – The base field of the conic.
- `names` – a list, tuple, or comma separated string of three variable names specifying the names of the coordinate functions of the ambient space  $\mathbf{P}^3$ . If not specified or read off from  $F$ , then this defaults to `'x, y, z'`.
- $F$  – a polynomial, list, matrix, ternary quadratic form, or list or tuple of 5 points in the plane.
  - If  $F$  is a polynomial or quadratic form, then the output is the curve in the projective plane defined by  $F = 0$ .
  - If  $F$  is a polynomial, then it must be a polynomial of degree at most 2 in 2 variables, or a homogeneous polynomial in of degree 2 in 3 variables.
  - If  $F$  is a matrix, then the output is the zero locus of  $(x, y, z)F(x, y, z)^t$ .
  - If  $F$  is a list of coefficients, then it has length 3 or 6 and gives the coefficients of the monomials  $x^2, y^2, z^2$  or all 6 monomials  $x^2, xy, xz, y^2, yz, z^2$  in lexicographic order.
  - If  $F$  is a list of 5 points in the plane, then the output is a conic through those points.
- `unique` – Used only if  $F$  is a list of points in the plane. If the conic through the points is not unique, then raise `ValueError` if and only if `unique` is `True`

## OUTPUT:

A plane projective conic curve defined by  $F$  over a field.

## EXAMPLES:

Conic curves given by polynomials

```
sage: X,Y,Z = QQ['X,Y,Z'].gens()
sage: Conic(X^2 - X*Y + Y^2 - Z^2)
Projective Conic Curve over Rational Field defined by X^2 - X*Y + Y^2 - Z^2
```

```

sage: x,y = GF(7)['x,y'].gens()
sage: Conic(x^2 - x + 2*y^2 - 3, 'U,V,W')
Projective Conic Curve over Finite Field of size 7 defined by  $U^2 + 2V^2 - UW - 3W^2$ 

```

### Conic curves given by matrices

```

sage: Conic(matrix(QQ, [[1, 2, 0], [4, 0, 0], [7, 0, 9]]), 'x,y,z')
Projective Conic Curve over Rational Field defined by  $x^2 + 6xy + 7xz + 9z^2$ 

sage: x,y,z = GF(11)['x,y,z'].gens()
sage: C = Conic(x^2+y^2-2*z^2); C
Projective Conic Curve over Finite Field of size 11 defined by  $x^2 + y^2 - 2z^2$ 
sage: Conic(C.symmetric_matrix(), 'x,y,z')
Projective Conic Curve over Finite Field of size 11 defined by  $x^2 + y^2 - 2z^2$ 

```

### Conics given by coefficients

```

sage: Conic(QQ, [1,2,3])
Projective Conic Curve over Rational Field defined by  $x^2 + 2y^2 + 3z^2$ 
sage: Conic(GF(7), [1,2,3,4,5,6], 'X')
Projective Conic Curve over Finite Field of size 7 defined by  $X_0^2 + 2X_0X_1 - 3X_1^2 + 3X_0X_2 - 2X_1X_2 - X_2^2$ 

```

### The conic through a set of points

```

sage: C = Conic(QQ, [[10,2],[3,4],[-7,6],[7,8],[9,10]]); C
Projective Conic Curve over Rational Field defined by  $x^2 + 13/4xy - 17/4y^2 - 35/2xz + 91/4yz - 37/2z^2$ 
sage: C.rational_point()
(10 : 2 : 1)
sage: C.point([3,4])
(3 : 4 : 1)

sage: a=AffineSpace(GF(13),2)
sage: Conic([a([x,x^2]) for x in range(5)])
Projective Conic Curve over Finite Field of size 13 defined by  $x^2 - yz$ 

```

## PROJECTIVE PLANE CONICS OVER A FIELD

AUTHORS:

- Marco Streng (2010-07-20)
- Nick Alexander (2008-01-08)

**class** sage.schemes.plane\_conics.con\_field.**ProjectiveConic\_field**( $A, f$ )  
Bases: [sage.schemes.curves.projective\\_curve.ProjectivePlaneCurve](#)

Create a projective plane conic curve over a field. See `Conic` for full documentation.

EXAMPLES:

```
sage: K = FractionField(PolynomialRing(QQ, 't'))
sage: P.<X, Y, Z> = K[]
sage: Conic(X^2 + Y^2 - Z^2)
Projective Conic Curve over Fraction Field of Univariate Polynomial Ring in t
↪ over Rational Field defined by X^2 + Y^2 - Z^2
```

**base\_extend**( $S$ )

Returns the conic over  $S$  given by the same equation as `self`.

EXAMPLES:

```
sage: c = Conic([1, 1, 1]); c
Projective Conic Curve over Rational Field defined by x^2 + y^2 + z^2
sage: c.has_rational_point()
False
sage: d = c.base_extend(QuadraticField(-1, 'i')); d
Projective Conic Curve over Number Field in i with defining polynomial x^2 +
↪ 1 defined by x^2 + y^2 + z^2
sage: d.rational_point(algorithm = 'rnfisnorm')
(i : 1 : 0)
```

**cache\_point**( $p$ )

Replace the point in the cache of `self` by  $p$  for use by `self.rational_point()` and `self.parametrization()`.

EXAMPLES:

```
sage: c = Conic([1, -1, 1])
sage: c.point([15, 17, 8])
(15/8 : 17/8 : 1)
sage: c.rational_point()
(15/8 : 17/8 : 1)
sage: c.cache_point(c.rational_point(read_cache = False))
```

```
sage: c.rational_point()
(-1 : 1 : 0)
```

**coefficients()**

Gives a the 6 coefficients of the conic `self` in lexicographic order.

EXAMPLES:

```
sage: Conic(QQ, [1, 2, 3, 4, 5, 6]).coefficients()
[1, 2, 3, 4, 5, 6]

sage: P.<x,y,z> = GF(13)[]
sage: a = Conic(x^2+5*x*y+y^2+z^2).coefficients(); a
[1, 5, 0, 1, 0, 1]
sage: Conic(a)
Projective Conic Curve over Finite Field of size 13 defined by x^2 + 5*x*y +
↪y^2 + z^2
```

**derivative\_matrix()**

Gives the derivative of the defining polynomial of the conic `self`, which is a linear map, as a  $3 \times 3$  matrix.

EXAMPLES:

In characteristic different from 2, the derivative matrix is twice the symmetric matrix:

```
sage: c = Conic(QQ, [1, 1, 1, 1, 1, 0])
sage: c.symmetric_matrix()
[ 1 1/2 1/2]
[1/2  1 1/2]
[1/2 1/2  0]
sage: c.derivative_matrix()
[2 1 1]
[1 2 1]
[1 1 0]
```

An example in characteristic 2:

```
sage: P.<t> = GF(2)[]
sage: c = Conic([t, 1, t^2, 1, 1, 0]); c
Projective Conic Curve over Fraction Field of Univariate Polynomial Ring in t
↪over Finite Field of size 2 (using GF2X) defined by t*x^2 + x*y + y^2 + t^
↪2*x*z + y*z
sage: c.is_smooth()
True
sage: c.derivative_matrix()
[ 0  1 t^2]
[ 1  0  1]
[t^2  1  0]
```

**determinant()**

Returns the determinant of the symmetric matrix that defines the conic `self`.

This is defined only if the base field has characteristic different from 2.

EXAMPLES:

```
sage: C = Conic([1, 2, 3, 4, 5, 6])
sage: C.determinant()
41/4
```

```
sage: C.symmetric_matrix().determinant()
41/4
```

Determinants are only defined in characteristic different from 2:

```
sage: C = Conic(GF(2), [1, 1, 1, 1, 1, 0])
sage: C.is_smooth()
True
sage: C.determinant()
Traceback (most recent call last):
...
ValueError: The conic self (= Projective Conic Curve over Finite Field of
↳size 2 defined by x^2 + x*y + y^2 + x*z + y*z) has no symmetric matrix
↳because the base field has characteristic 2
```

### **diagonal\_matrix()**

Returns a diagonal matrix  $D$  and a matrix  $T$  such that  $T^t A T = D$  holds, where  $(x, y, z)A(x, y, z)^t$  is the defining polynomial of the conic self.

EXAMPLES:

```
sage: c = Conic(QQ, [1,2,3,4,5,6])
sage: d, t = c.diagonal_matrix(); d, t
(
[ 1 0 0] [ 1 -1 -7/6]
[ 0 3 0] [ 0 1 -1/3]
[ 0 0 41/12], [ 0 0 1]
)
sage: t.transpose()*c.symmetric_matrix()*t
[ 1 0 0]
[ 0 3 0]
[ 0 0 41/12]
```

Diagonal matrices are only defined in characteristic different from 2:

```
sage: c = Conic(GF(4, 'a'), [0, 1, 1, 1, 1, 1])
sage: c.is_smooth()
True
sage: c.diagonal_matrix()
Traceback (most recent call last):
...
ValueError: The conic self (= Projective Conic Curve over Finite Field in a
↳of size 2^2 defined by x*y + y^2 + x*z + y*z + z^2) has no symmetric matrix
↳because the base field has characteristic 2
```

### **diagonalization (names=None)**

Returns a diagonal conic  $C$ , an isomorphism of schemes  $M : C \rightarrow \text{self}$  and the inverse  $N$  of  $M$ .

EXAMPLES:

```
sage: Conic(GF(5), [1,0,1,1,0,1]).diagonalization()
(Projective Conic Curve over Finite Field of size 5 defined by x^2 + y^2 +
↳2*z^2,
Scheme morphism:
From: Projective Conic Curve over Finite Field of size 5 defined by x^2 + y^
↳2 + 2*z^2
To: Projective Conic Curve over Finite Field of size 5 defined by x^2 + y^
↳2 + x*z + z^2
```

```

Defn: Defined on coordinates by sending (x : y : z) to
      (x + 2*z : y : z),
Scheme morphism:
  From: Projective Conic Curve over Finite Field of size 5 defined by x^2 + y^
↪2 + x*z + z^2
  To:   Projective Conic Curve over Finite Field of size 5 defined by x^2 + y^
↪2 + 2*z^2
Defn: Defined on coordinates by sending (x : y : z) to
      (x - 2*z : y : z))

```

The diagonalization is only defined in characteristic different from 2:

```

sage: Conic(GF(2), [1,1,1,1,1,0]).diagonalization()
Traceback (most recent call last):
...
ValueError: The conic self (= Projective Conic Curve over Finite Field of
↪size 2 defined by x^2 + x*y + y^2 + x*z + y*z) has no symmetric matrix
↪because the base field has characteristic 2

```

An example over a global function field:

```

sage: K = FractionField(PolynomialRing(GF(7), 't'))
sage: (t,) = K.gens()
sage: C = Conic(K, [t/2, 0, 1, 2, 0, 3])
sage: C.diagonalization()
(Projective Conic Curve over Fraction Field of Univariate Polynomial Ring in
↪t over Finite Field of size 7 defined by 4*t*x^2 + 2*y^2 + ((3*t + 3)/t)*z^
↪2,
Scheme morphism:
  From: Projective Conic Curve over Fraction Field of Univariate Polynomial
↪Ring in t over Finite Field of size 7 defined by 4*t*x^2 + 2*y^2 + ((3*t +
↪3)/t)*z^2
  To:   Projective Conic Curve over Fraction Field of Univariate Polynomial
↪Ring in t over Finite Field of size 7 defined by 4*t*x^2 + 2*y^2 + x*z +
↪3*z^2
  Defn: Defined on coordinates by sending (x : y : z) to
        (x + 6/t*z : y : z),
Scheme morphism:
  From: Projective Conic Curve over Fraction Field of Univariate Polynomial
↪Ring in t over Finite Field of size 7 defined by 4*t*x^2 + 2*y^2 + x*z +
↪3*z^2
  To:   Projective Conic Curve over Fraction Field of Univariate Polynomial
↪Ring in t over Finite Field of size 7 defined by 4*t*x^2 + 2*y^2 + ((3*t +
↪3)/t)*z^2
  Defn: Defined on coordinates by sending (x : y : z) to
        (x + 1/t*z : y : z))

```

**gens()**

Returns the generators of the coordinate ring of self.

**EXAMPLES:**

```

sage: P.<x,y,z> = QQ[]
sage: c = Conic(x^2+y^2+z^2)
sage: c.gens()
(xbar, ybar, zbar)
sage: c.defined_polynomial()(c.gens())
0

```



The function `gens()` is required for the following construction:

```
sage: C.<a,b,c> = Conic(GF(3), [1, 1, 1])
sage: C
Projective Conic Curve over Finite Field of size 3 defined by a^2 + b^2 + c^2
```

**has\_rational\_point** (*point=False, algorithm='default', read\_cache=True*)

Returns True if and only if the conic `self` has a point over its base field  $B$ .

If `point` is True, then returns a second output, which is a rational point if one exists.

Points are cached whenever they are found. Cached information is used if and only if `read_cache` is True.

ALGORITHM:

The parameter `algorithm` specifies the algorithm to be used:

- 'default' – If the base field is real or complex, use an elementary native Sage implementation.
- 'magma' (requires Magma to be installed) – delegates the task to the Magma computer algebra system.

EXAMPLES:

```
sage: Conic(RR, [1, 1, 1]).has_rational_point() False
sage: Conic(CC, [1, 1, 1]).has_rational_point() True

sage: Conic(RR, [1, 2, -3]).has_rational_point(point = True) (True, (1.73205080756888 :
0.0000000000000000 : 1.0000000000000000))
```

Conics over polynomial rings can be solved internally:

```
sage: R.<t> = QQ[]
sage: C = Conic([-2, t^2+1, t^2-1])
sage: C.has_rational_point()
True
```

And they can also be solved with Magma:

```
sage: C.has_rational_point(algorithm='magma') # optional - magma
True
sage: C.has_rational_point(algorithm='magma', point=True) # optional - magma
(True, (t : 1 : 1))

sage: D = Conic([t, 1, t^2])
sage: D.has_rational_point(algorithm='magma') # optional - magma
False
```

**has\_singular\_point** (*point=False*)

Return True if and only if the conic `self` has a rational singular point.

If `point` is True, then also return a rational singular point (or None if no such point exists).

EXAMPLES:

```
sage: c = Conic(QQ, [1, 0, 1]); c
Projective Conic Curve over Rational Field defined by x^2 + z^2
sage: c.has_singular_point(point = True)
(True, (0 : 1 : 0))

sage: P.<x,y,z> = GF(7)[]
```

```

sage: e = Conic((x+y+z)*(x-y+2*z)); e
Projective Conic Curve over Finite Field of size 7 defined by  $x^2 - y^2 + 3xz + yz + 2z^2$ 
sage: e.has_singular_point(point = True)
(True, (2 : 4 : 1))

sage: Conic([1, 1, -1]).has_singular_point()
False
sage: Conic([1, 1, -1]).has_singular_point(point = True)
(False, None)

```

`has_singular_point` is not implemented over all fields of characteristic 2. It is implemented over finite fields.

```

sage: F.<a> = FiniteField(8)
sage: Conic([a, a+1, 1]).has_singular_point(point = True)
(True, (a + 1 : 0 : 1))

sage: P.<t> = GF(2)[]
sage: C = Conic(P, [t,t,1]); C
Projective Conic Curve over Fraction Field of Univariate Polynomial Ring in t
over Finite Field of size 2 (using GF2X) defined by  $t^2x^2 + t^2y^2 + z^2$ 
sage: C.has_singular_point(point = False)
Traceback (most recent call last):
...
NotImplementedError: Sorry, find singular point on conics not implemented
over all fields of characteristic 2.

```

**hom**( $x$ ,  $Y=None$ )

Return the scheme morphism from `self` to  $Y$  defined by  $x$ . Here  $x$  can be a matrix or a sequence of polynomials. If  $Y$  is omitted, then a natural image is found if possible.

EXAMPLES:

Here are a few Morphisms given by matrices. In the first example,  $Y$  is omitted, in the second example,  $Y$  is specified.

```

sage: c = Conic([-1, 1, 1])
sage: h = c.hom(Matrix([[1,1,0],[0,1,0],[0,0,1]])); h
Scheme morphism:
  From: Projective Conic Curve over Rational Field defined by  $-x^2 + y^2 + z^2$ 
  To:   Projective Conic Curve over Rational Field defined by  $-x^2 + 2xy + z^2$ 
  Defn: Defined on coordinates by sending (x : y : z) to
        (x + y : y : z)
sage: h([-1, 1, 0])
(0 : 1 : 0)

sage: c = Conic([-1, 1, 1])
sage: d = Conic([4, 1, -1])
sage: c.hom(Matrix([[0, 0, 1/2], [0, 1, 0], [1, 0, 0]]), d)
Scheme morphism:
  From: Projective Conic Curve over Rational Field defined by  $-x^2 + y^2 + z^2$ 
  To:   Projective Conic Curve over Rational Field defined by  $4x^2 + y^2 - z^2$ 
  Defn: Defined on coordinates by sending (x : y : z) to
        (1/2*z : y : x)

```

ValueError is raised if the wrong codomain Y is specified:

```
sage: c = Conic([-1, 1, 1])
sage: c.hom(Matrix([[0, 0, 1/2], [0, 1, 0], [1, 0, 0]]), c)
Traceback (most recent call last):
...
ValueError: The matrix x (= [ 0  0 1/2]
[ 0  1  0]
[ 1  0  0]) does not define a map from self (= Projective Conic Curve over
↪ Rational Field defined by -x^2 + y^2 + z^2) to Y (= Projective Conic Curve
↪ over Rational Field defined by -x^2 + y^2 + z^2)
```

The identity map between two representations of the same conic:

```
sage: C = Conic([1,2,3,4,5,6])
sage: D = Conic([2,4,6,8,10,12])
sage: C.hom(identity_matrix(3), D)
Scheme morphism:
  From: Projective Conic Curve over Rational Field defined by x^2 + 2*x*y +
↪ 4*y^2 + 3*x*z + 5*y*z + 6*z^2
  To:   Projective Conic Curve over Rational Field defined by 2*x^2 + 4*x*y +
↪ 8*y^2 + 6*x*z + 10*y*z + 12*z^2
  Defn: Defined on coordinates by sending (x : y : z) to
        (x : y : z)
```

An example not over the rational numbers:

```
sage: P.<t> = QQ[]
sage: C = Conic([1,0,0,t,0,1/t])
sage: D = Conic([1/t^2, 0, -2/t^2, t, 0, (t + 1)/t^2])
sage: T = Matrix([[t,0,1],[0,1,0],[0,0,1]])
sage: C.hom(T, D)
Scheme morphism:
  From: Projective Conic Curve over Fraction Field of Univariate Polynomial
↪ Ring in t over Rational Field defined by x^2 + t*y^2 + 1/t*z^2
  To:   Projective Conic Curve over Fraction Field of Univariate Polynomial
↪ Ring in t over Rational Field defined by 1/t^2*x^2 + t*y^2 + (-2/t^2)*x*z +
↪ ((t + 1)/t^2)*z^2
  Defn: Defined on coordinates by sending (x : y : z) to
        (t*x + z : y : z)
```

**is\_diagonal()**

Return True if and only if the conic has the form  $a * x^2 + b * y^2 + c * z^2$ .

EXAMPLES:

```
sage: c=Conic([1,1,0,1,0,1]); c
Projective Conic Curve over Rational Field defined by x^2 + x*y + y^2 + z^2
sage: d,t = c.diagonal_matrix()
sage: c.is_diagonal()
False
sage: c.diagonalization()[0].is_diagonal()
True
```

**is\_smooth()**

Returns True if and only if self is smooth.

EXAMPLES:

```

sage: Conic([1,-1,0]).is_smooth()
False
sage: Conic(GF(2), [1,1,1,1,1,0]).is_smooth()
True

```

**matrix()**

Returns a matrix  $M$  such that  $(x, y, z)M(x, y, z)^t$  is the defining equation of `self`.

The matrix  $M$  is upper triangular if the base field has characteristic 2 and symmetric otherwise.

EXAMPLES:

```

sage: R.<x, y, z> = QQ[]
sage: C = Conic(x^2 + x*y + y^2 + z^2)
sage: C.matrix()
[ 1 1/2  0]
[1/2  1  0]
[ 0  0  1]

sage: R.<x, y, z> = GF(2)[]
sage: C = Conic(x^2 + x*y + y^2 + x*z + z^2)
sage: C.matrix()
[1 1 1]
[0 1 0]
[0 0 1]

```

**parametrization** (*point=None, morphism=True*)

Return a parametrization  $f$  of `self` together with the inverse of  $f$ .

If `point` is specified, then that point is used for the parametrization. Otherwise, use `self.rational_point()` to find a point.

If `morphism` is `True`, then  $f$  is returned in the form of a Scheme morphism. Otherwise, it is a tuple of polynomials that gives the parametrization.

EXAMPLES:

An example over a finite field

```

sage: c = Conic(GF(2), [1,1,1,1,1,0])
sage: c.parametrization()
(Scheme morphism:
  From: Projective Space of dimension 1 over Finite Field of size 2
  To:   Projective Conic Curve over Finite Field of size 2 defined by x^2 +
↪x*y
+ y^2 + x*z + y*z
  Defn: Defined on coordinates by sending (x : y) to
        (x*y + y^2 : x^2 + x*y : x^2 + x*y + y^2),
Scheme morphism:
  From: Projective Conic Curve over Finite Field of size 2 defined by x^2 +
↪x*y
+ y^2 + x*z + y*z
  To:   Projective Space of dimension 1 over Finite Field of size 2
  Defn: Defined on coordinates by sending (x : y : z) to
        (y : x))

```

An example with `morphism = False`

```

sage: R.<x,y,z> = QQ[]
sage: C = Curve(7*x^2 + 2*y*z + z^2)

```

```

sage: (p, i) = C.parametrization(morphism = False); (p, i)
([-2*x*y, x^2 + 7*y^2, -2*x^2], [-1/2*x, 1/7*y + 1/14*z])
sage: C.defined_polynomial()(p)
0
sage: i[0](p) / i[1](p)
x/y

```

A `ValueError` is raised if `self` has no rational point

```

sage: C = Conic(x^2 + y^2 + 7*z^2)
sage: C.parametrization()
Traceback (most recent call last):
...
ValueError: Conic Projective Conic Curve over Rational Field defined by x^2 +
↪y^2 + 7*z^2 has no rational points over Rational Field!

```

A `ValueError` is raised if `self` is not smooth

```

sage: C = Conic(x^2 + y^2)
sage: C.parametrization()
Traceback (most recent call last):
...
ValueError: The conic self (=Projective Conic Curve over Rational Field_
↪defined by x^2 + y^2) is not smooth, hence does not have a parametrization.

```

**point** (*v*, *check=True*)

Constructs a point on `self` corresponding to the input `v`.

If `check` is `True`, then checks if `v` defines a valid point on `self`.

If no rational point on `self` is known yet, then also caches the point for use by `self.rational_point()` and `self.parametrization()`.

#### EXAMPLES

```

sage: c = Conic([1, -1, 1])
sage: c.point([15, 17, 8])
(15/8 : 17/8 : 1)
sage: c.rational_point()
(15/8 : 17/8 : 1)
sage: d = Conic([1, -1, 1])
sage: d.rational_point()
(-1 : 1 : 0)

```

**random\_rational\_point** (\*args1, \*\*args2)

Return a random rational point of the conic `self`.

#### ALGORITHM:

1. Compute a parametrization  $f$  of `self` using `self.parametrization()`.
2. Computes a random point  $(x : y)$  on the projective line.
3. Output  $f(x : y)$ .

The coordinates  $x$  and  $y$  are computed using `B.random_element`, where  $B$  is the base field of `self` and additional arguments to `random_rational_point` are passed to `random_element`.

If the base field is a finite field, then the output is uniformly distributed over the points of `self`.

#### EXAMPLES

```

sage: c = Conic(GF(2), [1,1,1,1,1,0])
sage: [c.random_rational_point() for i in range(10)] # output is random
[(1 : 0 : 1), (1 : 0 : 1), (1 : 0 : 1), (0 : 1 : 1), (1 : 0 : 1), (0 : 0 : 1),
↪ (1 : 0 : 1), (1 : 0 : 1), (0 : 0 : 1), (1 : 0 : 1)]

sage: d = Conic(QQ, [1, 1, -1])
sage: d.random_rational_point(den_bound = 1, num_bound = 5) # output is random
(-24/25 : 7/25 : 1)

sage: Conic(QQ, [1, 1, 1]).random_rational_point()
Traceback (most recent call last):
...
ValueError: Conic Projective Conic Curve over Rational Field defined by x^2 +
↪ y^2 + z^2 has no rational points over Rational Field!

```

**rational\_point** (*algorithm='default', read\_cache=True*)

Return a point on self defined over the base field.

Raises ValueError if no rational point exists.

See `self.has_rational_point` for the algorithm used and for the use of the parameters `algorithm` and `read_cache`.

EXAMPLES:

Examples over  $\mathbb{Q}$

```

sage: R.<x,y,z> = QQ[]
sage: C = Conic(7*x^2 + 2*y*z + z^2)
sage: C.rational_point()
(0 : 1 : 0)

sage: C = Conic(x^2 + 2*y^2 + z^2)
sage: C.rational_point()
Traceback (most recent call last):
...
ValueError: Conic Projective Conic Curve over Rational Field defined by x^2 +
↪ 2*y^2 + z^2 has no rational points over Rational Field!

sage: C = Conic(x^2 + y^2 + 7*z^2)
sage: C.rational_point(algorithm = 'rnfisnorm')
Traceback (most recent call last):
...
ValueError: Conic Projective Conic Curve over Rational Field defined by x^2 +
↪ y^2 + 7*z^2 has no rational points over Rational Field!

```

Examples over number fields

```

sage: P.<x> = QQ[]
sage: L.<b> = NumberField(x^3-5)
sage: C = Conic(L, [3, 2, -5])
sage: p = C.rational_point(algorithm = 'rnfisnorm')
sage: p # output is random
(60*b^2 - 196*b + 161 : -120*b^2 - 6*b + 361 : 1)
sage: C.defined_polynomial()(list(p))
0

sage: K.<i> = QuadraticField(-1)
sage: D = Conic(K, [3, 2, 5])

```

```

sage: D.rational_point(algorithm = 'rnfisnorm') # output is random
(-3 : 4*i : 1)

sage: L.<s> = QuadraticField(2)
sage: Conic(QQ, [1, 1, -3]).has_rational_point()
False
sage: E = Conic(L, [1, 1, -3])
sage: E.rational_point() # output is random
(-1 : -s : 1)

```

Currently Magma is better at solving conics over number fields than Sage, so it helps to use the algorithm 'magma' if Magma is installed:

```

sage: q = C.rational_point(algorithm = 'magma', read_cache=False) # optional -
↪ magma
sage: q # output is random, optional - magma
(-1 : -1 : 1)
sage: C.defining_polynomial()(list(p)) # optional - magma
0
sage: len(str(p)) / len(str(q)) > 2 # optional - magma
True

sage: D.rational_point(algorithm = 'magma', read_cache=False) # random, ↪
↪ optional - magma
(1 : 2*i : 1)

sage: E.rational_point(algorithm='magma', read_cache=False) # random, ↪
↪ optional - magma
(-s : 1 : 1)

sage: F = Conic([L.gen(), 30, -20])
sage: q = F.rational_point(algorithm='magma') # optional - magma
sage: q # output is random, optional - magma
(-10/7*s + 40/7 : 5/7*s - 6/7 : 1)
sage: p = F.rational_point(read_cache=False)
sage: p # output is random
(788210*s - 1114700 : -171135*s + 242022 : 1)
sage: len(str(p)) > len(str(q)) # optional - magma
True

sage: Conic([L.gen(), 30, -21]).has_rational_point(algorithm='magma') # ↪
↪ optional - magma
False

```

### Examples over finite fields

```

sage: F.<a> = FiniteField(7^20)
sage: C = Conic([1, a, -5]); C
Projective Conic Curve over Finite Field in a of size 7^20 defined by x^2 + ↪
↪ (a)*y^2 + 2*z^2
sage: C.rational_point() # output is random
(4*a^19 + 5*a^18 + 4*a^17 + a^16 + 6*a^15 + 3*a^13 + 6*a^11 + a^9 + 3*a^8 + ↪
↪ 2*a^7 + 4*a^6 + 3*a^5 + 3*a^4 + a^3 + a + 6 : 5*a^18 + a^17 + a^16 + 6*a^15 ↪
↪ + 4*a^14 + a^13 + 5*a^12 + 5*a^10 + 2*a^9 + 6*a^8 + 6*a^7 + 6*a^6 + 2*a^4 + ↪
↪ 3 : 1)

```

### Examples over $\mathbf{R}$ and $\mathbf{C}$

```

sage: Conic(CC, [1, 2, 3]).rational_point()
(0 : 1.22474487139159*I : 1)

sage: Conic(RR, [1, 1, 1]).rational_point()
Traceback (most recent call last):
...
ValueError: Conic Projective Conic Curve over Real Field with 53 bits of
precision defined by  $x^2 + y^2 + z^2$  has no rational points over Real Field
with 53 bits of precision!

```

**singular\_point()**

Returns a singular rational point of self

EXAMPLES:

```

sage: Conic(GF(2), [1, 1, 1, 1, 1, 1]).singular_point()
(1 : 1 : 1)

```

ValueError is raised if the conic has no rational singular point

```

sage: Conic(QQ, [1, 1, 1, 1, 1, 1]).singular_point()
Traceback (most recent call last):
...
ValueError: The conic self (= Projective Conic Curve over Rational Field
defined by  $x^2 + x*y + y^2 + x*z + y*z + z^2$ ) has no rational singular point

```

**symmetric\_matrix()**

The symmetric matrix  $M$  such that  $(xyz)M(xyz)^t$  is the defining equation of self.

EXAMPLES

```

sage: R.<x, y, z> = QQ[]
sage: C = Conic(x^2 + x*y/2 + y^2 + z^2)
sage: C.symmetric_matrix()
[ 1 1/4  0]
[1/4  1  0]
[ 0  0  1]

sage: C = Conic(x^2 + 2*x*y + y^2 + 3*x*z + z^2)
sage: v = vector([x, y, z])
sage: v * C.symmetric_matrix() * v
x^2 + 2*x*y + y^2 + 3*x*z + z^2

```

**upper\_triangular\_matrix()**

The upper-triangular matrix  $M$  such that  $(xyz)M(xyz)^t$  is the defining equation of self.

EXAMPLES:

```

sage: R.<x, y, z> = QQ[]
sage: C = Conic(x^2 + x*y + y^2 + z^2)
sage: C.upper_triangular_matrix()
[1 1 0]
[0 1 0]
[0 0 1]

sage: C = Conic(x^2 + 2*x*y + y^2 + 3*x*z + z^2)
sage: v = vector([x, y, z])
sage: v * C.upper_triangular_matrix() * v
x^2 + 2*x*y + y^2 + 3*x*z + z^2

```



**variable\_names()**

Returns the variable names of the defining polynomial of `self`.

EXAMPLES:

```
sage: c=Conic([1,1,0,1,0,1], 'x,y,z')
sage: c.variable_names()
('x', 'y', 'z')
sage: c.variable_name()
'x'
```

The function `variable_names()` is required for the following construction:

```
sage: C.<p,q,r> = Conic(QQ, [1, 1, 1])
sage: C
Projective Conic Curve over Rational Field defined by  $p^2 + q^2 + r^2$ 
```



## PROJECTIVE PLANE CONICS OVER A NUMBER FIELD

AUTHORS:

- Marco Streng (2010-07-20)

**class** sage.schemes.plane\_conics.con\_number\_field.**ProjectiveConic\_number\_field**( $A$ ,  $f$ )

Bases: *sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field*

Create a projective plane conic curve over a number field. See *Conic* for full documentation.

EXAMPLES:

```
sage: K.<a> = NumberField(x^3 - 2, 'a')
sage: P.<X, Y, Z> = K[]
sage: Conic(X^2 + Y^2 - a*Z^2)
Projective Conic Curve over Number Field in a with defining polynomial x^3 - 2
↳ defined by X^2 + Y^2 + (-a)*Z^2
```

**has\_rational\_point** (*point=False, obstruction=False, algorithm='default', read\_cache=True*)

Returns True if and only if self has a point defined over its base field  $B$ .

If *point* and *obstruction* are both False (default), then the output is a boolean out saying whether self has a rational point.

If *point* or *obstruction* is True, then the output is a pair (*out*,  $S$ ), where *out* is as above and:

- if *point* is True and self has a rational point, then  $S$  is a rational point,
- if *obstruction* is True, self has no rational point, then  $S$  is a prime or infinite place of  $B$  such that no rational point exists over the completion at  $S$ .

Points and obstructions are cached whenever they are found. Cached information is used for the output if available, but only if *read\_cache* is True.

ALGORITHM:

The parameter *algorithm* specifies the algorithm to be used:

- 'rnfisnorm' – Use PARI's rnfisnorm (cannot be combined with *obstruction = True*)
- 'local' – Check if a local solution exists for all primes and infinite places of  $B$  and apply the Hasse principle. (Cannot be combined with *point = True*.)
- 'default' – Use algorithm 'rnfisnorm' first. Then, if no point exists and obstructions are requested, use algorithm 'local' to find an obstruction.
- 'magma' (requires Magma to be installed) – delegates the task to the Magma computer algebra system.

## EXAMPLES:

An example over  $\mathbb{Q}$ 

```

sage: C = Conic(QQ, [1, 113922743, -310146482690273725409])
sage: C.has_rational_point(point = True)
(True, (-76842858034579/5424 : -5316144401/5424 : 1))
sage: C.has_rational_point(algorithm = 'local', read_cache = False)
True

```

Examples over number fields:

```

sage: K.<i> = QuadraticField(-1)
sage: C = Conic(K, [1, 3, -5])
sage: C.has_rational_point(point = True, obstruction = True)
(False, Fractional ideal (-i - 2))
sage: C.has_rational_point(algorithm = "rnfisnorm")
False
sage: C.has_rational_point(algorithm = "rnfisnorm", obstruction = True, read_
↪cache=False)
Traceback (most recent call last):
...
ValueError: Algorithm rnfisnorm cannot be combined with obstruction = True in_
↪has_rational_point

sage: P.<x> = QQ[]
sage: L.<b> = NumberField(x^3-5)
sage: C = Conic(L, [1, 2, -3])
sage: C.has_rational_point(point = True, algorithm = 'rnfisnorm')
(True, (5/3 : -1/3 : 1))

sage: K.<a> = NumberField(x^4+2)
sage: Conic(QQ, [4,5,6]).has_rational_point()
False
sage: Conic(K, [4,5,6]).has_rational_point()
True
sage: Conic(K, [4,5,6]).has_rational_point(algorithm='magma', read_
↪cache=False) # optional - magma
True

```

**is\_locally\_solvable(p)**

Returns True if and only if `self` has a solution over the completion of the base field  $B$  of `self` at  $p$ . Here  $p$  is a finite prime or infinite place of  $B$ .

## EXAMPLES:

```

sage: P.<x> = QQ[]
sage: K.<a> = NumberField(x^3 + 5)
sage: C = Conic(K, [1, 2, 3 - a])
sage: [p1, p2] = K.places()
sage: C.is_locally_solvable(p1)
False

sage: C.is_locally_solvable(p2)
True

sage: O = K.maximal_order()
sage: f = (2*O).factor()
sage: C.is_locally_solvable(f[0][0])

```

```
True

sage: C.is_locally_solvable(f[1][0])
False
```

**local\_obstructions** (*finite=True, infinite=True, read\_cache=True*)

Returns the sequence of finite primes and/or infinite places such that `self` is locally solvable at those primes and places.

If the base field is  $\mathbb{Q}$ , then the infinite place is denoted  $-1$ .

The parameters `finite` and `infinite` (both `True` by default) are used to specify whether to look at finite and/or infinite places. Note that `finite = True` involves factorization of the determinant of `self`, hence may be slow.

Local obstructions are cached. The parameter `read_cache` specifies whether to look at the cache before computing anything.

#### EXAMPLES

```
sage: K.<i> = QuadraticField(-1)
sage: Conic(K, [1, 2, 3]).local_obstructions()
[]

sage: L.<a> = QuadraticField(5)
sage: Conic(L, [1, 2, 3]).local_obstructions()
[Ring morphism:
  From: Number Field in a with defining polynomial x^2 - 5
  To:   Algebraic Real Field
  Defn: a |--> -2.236067977499790?, Ring morphism:
  From: Number Field in a with defining polynomial x^2 - 5
  To:   Algebraic Real Field
  Defn: a |--> 2.236067977499790?]
```



## PROJECTIVE PLANE CONICS OVER $\mathbb{Q}$

AUTHORS:

- Marco Streng (2010-07-20)
- Nick Alexander (2008-01-08)

**class** sage.schemes.plane\_conics.con\_rational\_field.**ProjectiveConic\_rational\_field**(*A*,  
*f*)

Bases: *sage.schemes.plane\_conics.con\_number\_field.ProjectiveConic\_number\_field*

Create a projective plane conic curve over  $\mathbb{Q}$ . See `Conic` for full documentation.

EXAMPLES:

```
sage: P.<X, Y, Z> = QQ[]
sage: Conic(X^2 + Y^2 - 3*Z^2)
Projective Conic Curve over Rational Field defined by X^2 + Y^2 - 3*Z^2
```

**has\_rational\_point** (*point=False, obstruction=False, algorithm='default', read\_cache=True*)

Returns True if and only if *self* has a point defined over  $\mathbb{Q}$ .

If *point* and *obstruction* are both False (default), then the output is a boolean out saying whether *self* has a rational point.

If *point* or *obstruction* is True, then the output is a pair (*out*, *S*), where *out* is as above and the following holds:

- if *point* is True and *self* has a rational point, then *S* is a rational point,
- if *obstruction* is True and *self* has no rational point, then *S* is a prime such that no rational point exists over the completion at *S* or  $-1$  if no point exists over  $\mathbb{R}$ .

Points and obstructions are cached, whenever they are found. Cached information is used if and only if *read\_cache* is True.

ALGORITHM:

The parameter *algorithm* specifies the algorithm to be used:

- 'qfsolve' – Use PARI/GP function `qfsolve`
- 'rnfisnorm' – Use PARI's function `rnfisnorm` (cannot be combined with *obstruction* = True)
- 'local' – Check if a local solution exists for all primes and infinite places of  $\mathbb{Q}$  and apply the Hasse principle (cannot be combined with *point* = True)
- 'default' – Use 'qfsolve'

- 'magma' (requires Magma to be installed) – delegates the task to the Magma computer algebra system.

EXAMPLES:

```
sage: C = Conic(QQ, [1, 2, -3])
sage: C.has_rational_point(point = True)
(True, (1 : 1 : 1))
sage: D = Conic(QQ, [1, 3, -5])
sage: D.has_rational_point(point = True)
(False, 3)
sage: P.<X,Y,Z> = QQ[]
sage: E = Curve(X^2 + Y^2 + Z^2); E
Projective Conic Curve over Rational Field defined by X^2 + Y^2 + Z^2
sage: E.has_rational_point(obstruction = True)
(False, -1)
```

The following would not terminate quickly with `algorithm = 'rnfnorm'`

```
sage: C = Conic(QQ, [1, 113922743, -310146482690273725409])
sage: C.has_rational_point(point = True)
(True, (-76842858034579/5424 : -5316144401/5424 : 1))
sage: C.has_rational_point(algorithm = 'local', read_cache = False)
True
sage: C.has_rational_point(point=True, algorithm='magma', read_cache=False) #_
↪ optional - magma
(True, (30106379962113/7913 : 12747947692/7913 : 1))
```

**is\_locally\_solvable(*p*)**

Returns True if and only if self has a solution over the  $p$ -adic numbers. Here  $p$  is a prime number or equals  $-1$ , infinity, or  $\mathbf{R}$  to denote the infinite place.

EXAMPLES:

```
sage: C = Conic(QQ, [1,2,3])
sage: C.is_locally_solvable(-1)
False
sage: C.is_locally_solvable(2)
False
sage: C.is_locally_solvable(3)
True
sage: C.is_locally_solvable(QQ.hom(RR))
False
sage: D = Conic(QQ, [1, 2, -3])
sage: D.is_locally_solvable(infinity)
True
sage: D.is_locally_solvable(RR)
True
```

**local\_obstructions(*finite=True, infinite=True, read\_cache=True*)**

Returns the sequence of finite primes and/or infinite places such that self is locally solvable at those primes and places.

The infinite place is denoted  $-1$ .

The parameters `finite` and `infinite` (both True by default) are used to specify whether to look at finite and/or infinite places. Note that `finite = True` involves factorization of the determinant of self, hence may be slow.



Local obstructions are cached. The parameter `read_cache` specifies whether to look at the cache before computing anything.

#### EXAMPLES

```
sage: Conic(QQ, [1, 1, 1]).local_obstructions()
[2, -1]
sage: Conic(QQ, [1, 2, -3]).local_obstructions()
[]
sage: Conic(QQ, [1, 2, 3, 4, 5, 6]).local_obstructions()
[41, -1]
```

#### **parametrization** (*point=None, morphism=True*)

Return a parametrization  $f$  of `self` together with the inverse of  $f$ .

If `point` is specified, then that point is used for the parametrization. Otherwise, use `self.rational_point()` to find a point.

If `morphism` is `True`, then  $f$  is returned in the form of a Scheme morphism. Otherwise, it is a tuple of polynomials that gives the parametrization.

#### ALGORITHM:

Uses the PARI/GP function `qfparam`.

#### EXAMPLES

```
sage: c = Conic([1,1,-1])
sage: c.parametrization()
(Scheme morphism:
  From: Projective Space of dimension 1 over Rational Field
  To:   Projective Conic Curve over Rational Field defined by x^2 + y^2 - z^2
  Defn: Defined on coordinates by sending (x : y) to
        (2*x*y : x^2 - y^2 : x^2 + y^2),
Scheme morphism:
  From: Projective Conic Curve over Rational Field defined by x^2 + y^2 - z^2
  To:   Projective Space of dimension 1 over Rational Field
  Defn: Defined on coordinates by sending (x : y : z) to
        (1/2*x : -1/2*y + 1/2*z))
```

An example with `morphism = False`

```
sage: R.<x,y,z> = QQ[]
sage: C = Curve(7*x^2 + 2*y*z + z^2)
sage: (p, i) = C.parametrization(morphism = False); (p, i)
([-2*x*y, x^2 + 7*y^2, -2*x^2], [-1/2*x, 1/7*y + 1/14*z])
sage: C.defined_polynomial()(p)
0
sage: i[0](p) / i[1](p)
x/y
```

A `ValueError` is raised if `self` has no rational point

```
sage: C = Conic(x^2 + 2*y^2 + z^2)
sage: C.parametrization()
Traceback (most recent call last):
...
ValueError: Conic Projective Conic Curve over Rational Field defined by x^2 +
↪ 2*y^2 + z^2 has no rational points over Rational Field!
```

A `ValueError` is raised if `self` is not smooth

```
sage: C = Conic(x^2 + y^2)
sage: C.parametrization()
Traceback (most recent call last):
...
ValueError: The conic self (=Projective Conic Curve over Rational Field,
↪defined by x^2 + y^2) is not smooth, hence does not have a parametrization.
```

## PROJECTIVE PLANE CONICS OVER FINITE FIELDS

AUTHORS:

- Marco Streng (2010-07-20)

**class** sage.schemes.plane\_conics.con\_finite\_field.**ProjectiveConic\_finite\_field**( $A$ ,  $f$ )

Bases: `sage.schemes.plane_conics.con_field.ProjectiveConic_field`, `sage.schemes.curves.projective_curve.ProjectivePlaneCurve_finite_field`

Create a projective plane conic curve over a finite field. See `Conic` for full documentation.

EXAMPLES:

```
sage: K.<a> = FiniteField(9, 'a')
sage: P.<X, Y, Z> = K[]
sage: Conic(X^2 + Y^2 - a*Z^2)
Projective Conic Curve over Finite Field in a of size 3^2 defined by X^2 + Y^2 +
↪ (-a)*Z^2
```

**count\_points**( $n$ )

If the base field  $B$  of *self* is finite of order  $q$ , then returns the number of points over  $\mathbf{F}_q, \dots, \mathbf{F}_{q^n}$ .

EXAMPLES:

```
sage: P.<x,y,z> = GF(3)[]
sage: c = Curve(x^2+y^2+z^2); c
Projective Conic Curve over Finite Field of size 3 defined by x^2 + y^2 + z^2
sage: c.count_points(4)
[4, 10, 28, 82]
```

**has\_rational\_point**(*point=False*, *read\_cache=True*, *algorithm='default'*)

Always returns `True` because *self* has a point defined over its finite base field  $B$ .

If *point* is `True`, then returns a second output  $S$ , which is a rational point if one exists.

Points are cached. If *read\_cache* is `True`, then cached information is used for the output if available. If no cached point is available or *read\_cache* is `False`, then random  $y$ -coordinates are tried if *self* is smooth and a singular point is returned otherwise.

EXAMPLES:

```
sage: Conic(FiniteField(37), [1, 2, 3, 4, 5, 6]).has_rational_point()
True

sage: C = Conic(FiniteField(2), [1, 1, 1, 1, 1, 0]); C
Projective Conic Curve over Finite Field of size 2 defined by x^2 + x*y + y^2
↪ + x*z + y*z
```



## PROJECTIVE PLANE CONICS OVER PRIME FINITE FIELDS

AUTHORS:

- Marco Streng (2010-07-20)

**class** sage.schemes.plane\_conics.con\_prime\_finite\_field.**ProjectiveConic\_prime\_finite\_field**(*f*)

Bases: *sage.schemes.plane\_conics.con\_finite\_field.ProjectiveConic\_finite\_field*,  
*sage.schemes.curves.projective\_curve.ProjectivePlaneCurve\_prime\_finite\_field*

Create a projective plane conic curve over a prime finite field. See `Conic` for full documentation.

EXAMPLES:

```
sage: P.<X, Y, Z> = FiniteField(5)[]
sage: Conic(X^2 + Y^2 - 2*Z^2)
Projective Conic Curve over Finite Field of size 5 defined by X^2 + Y^2 - 2*Z^2
```



## PROJECTIVE PLANE CONICS OVER A RATIONAL FUNCTION FIELD

The class `ProjectiveConic_rational_function_field` represents a projective plane conic over a rational function field  $F(t)$ , where  $F$  is any field. Instances can be created using `Conic()`.

AUTHORS:

- Lennart Ackermans (2016-02-07): initial version

EXAMPLES:

Create a conic:

```
sage: K = FractionField(PolynomialRing(QQ, 't'))
sage: P.<X, Y, Z> = K[]
sage: Conic(X^2 + Y^2 - Z^2)
Projective Conic Curve over Fraction Field of Univariate
Polynomial Ring in t over Rational Field defined by
X^2 + Y^2 - Z^2
```

Points can be found using `has_rational_point()`:

```
sage: K.<t> = FractionField(QQ['t'])
sage: C = Conic([1,-t,t])
sage: C.has_rational_point(point = True)
(True, (0 : 1 : 1))
```

**class** `sage.schemes.plane_conics.con_rational_function_field.ProjectiveConic_rational_funct`

Bases: `sage.schemes.plane_conics.con_field.ProjectiveConic_field`

Create a projective plane conic curve over a rational function field  $F(t)$ , where  $F$  is any field.

The algorithms used in this class come mostly from [\[HC2006\]](#).

EXAMPLES:

```
sage: K = FractionField(PolynomialRing(QQ, 't'))
sage: P.<X, Y, Z> = K[]
sage: Conic(X^2 + Y^2 - Z^2)
Projective Conic Curve over Fraction Field of Univariate
Polynomial Ring in t over Rational Field defined by
X^2 + Y^2 - Z^2
```

REFERENCES:

**find\_point** (*supports, roots, case, solution=0*)

Given a solubility certificate like in [\[HC2006\]](#), find a point on self. Assumes self is in reduced form (see [\[HC2006\]](#) for a definition).

If you don't have a solubility certificate and just want to find a point, use the function `has_rational_point()` instead.

INPUT:

- `self` – conic in reduced form.
- `supports` – 3-tuple where `supports[i]` is a list of all monic irreducible  $p \in F[t]$  that divide the  $i$ 'th of the 3 coefficients.
- `roots` – 3-tuple containing lists of roots of all elements of `supports[i]`, in the same order.
- `case` – 1 or 0, as in [HC2006].
- `solution` – (default: 0) a solution of (5) in [HC2006], if `case` = 0, 0 otherwise.

OUTPUT:

A point  $(x, y, z) \in F(t)$  of `self`. Output is undefined when the input solubility certificate is incorrect.

ALGORITHM:

The algorithm used is the algorithm FindPoint in [HC2006], with a simplification from [ACKERMANS2016].

EXAMPLES:

```
sage: K.<t> = FractionField(QQ['t'])
sage: C = Conic(K, [t^2-2, 2*t^3, -2*t^3-13*t^2-2*t+18])
sage: C.has_rational_point(point=True) # indirect test
(True, (-3 : (t + 1)/t : 1))
```

Different solubility certificates give different points:

```
sage: K.<t> = PolynomialRing(QQ, 't')
sage: C = Conic(K, [t^2-2, 2*t, -2*t^3-13*t^2-2*t+18])
sage: supp = [[t^2 - 2], [t], [t^3 + 13/2*t^2 + t - 9]]
sage: tbar1 = QQ.extension(supp[0][0], 'tbar').gens()[0]
sage: tbar2 = QQ.extension(supp[1][0], 'tbar').gens()[0]
sage: tbar3 = QQ.extension(supp[2][0], 'tbar').gens()[0]
sage: roots = [[tbar1 + 1], [1/3*tbar2^0], [2/3*tbar3^2 + 11/3*tbar3 - 3]]
sage: C.find_point(supp, roots, 1)
(3 : t + 1 : 1)
sage: roots = [[-tbar1 - 1], [-1/3*tbar2^0], [-2/3*tbar3^2 - 11/3*tbar3 + 3]]
sage: C.find_point(supp, roots, 1)
(3 : -t - 1 : 1)
```

**has\_rational\_point** (*point=False, algorithm='default', read\_cache=True*)

Returns True if and only if the conic `self` has a point over its base field  $F(t)$ , which is a field of rational functions.

If `point` is True, then returns a second output, which is a rational point if one exists.

Points are cached whenever they are found. Cached information is used if and only if `read_cache` is True.

The default algorithm does not (yet) work for all base fields  $F$ . In particular, sage is required to have:

- an algorithm for finding the square root of elements in finite extensions of  $F$ ;
- a factorization and gcd algorithm for  $F[t]$ ;
- an algorithm for solving conics over  $F$ .



## ALGORITHM:

The parameter `algorithm` specifies the algorithm to be used:

- 'default' – use a native Sage implementation, based on the algorithm Conic in [HC2006].
- 'magma' (requires Magma to be installed) – delegates the task to the Magma computer algebra system.

## EXAMPLES:

We can find points for function fields over (extensions of)  $\mathbb{Q}$  and finite fields:

```
sage: K.<t> = FractionField(PolynomialRing(QQ, 't'))
sage: C = Conic(K, [t^2-2, 2*t^3, -2*t^3-13*t^2-2*t+18])
sage: C.has_rational_point(point=True)
(True, (-3 : (t + 1)/t : 1))
sage: R.<t> = FiniteField(23)[]
sage: C = Conic([2, t^2+1, t^2+5])
sage: C.has_rational_point()
True
sage: C.has_rational_point(point=True)
(True, (5*t : 8 : 1))
sage: F.<i> = QuadraticField(-1)
sage: R.<t> = F[]
sage: C = Conic([1, i*t, -t^2+4])
sage: C.has_rational_point(point = True)
(True, (-t - 2*i : -2*i : 1))
```

It works on non-diagonal conics as well:

```
sage: K.<t> = QQ[]
sage: C = Conic([4, -4, 8, 1, -4, t + 4])
sage: C.has_rational_point(point=True)
(True, (1/2 : 1 : 0))
```

If no point exists output still depends on the argument `point`:

```
sage: K.<t> = QQ[]
sage: C = Conic(K, [t^2, (t-1), -2*(t-1)])
sage: C.has_rational_point()
False
sage: C.has_rational_point(point=True)
(False, None)
```

Due to limitations in Sage of algorithms we depend on, it is not yet possible to find points on conics over multivariate function fields (see the requirements above):

```
sage: F.<t1> = FractionField(QQ['t1'])
sage: K.<t2> = FractionField(F['t2'])
sage: a = K(1)
sage: b = 2*t2^2+2*t1*t2-t1^2
sage: c = -3*t2^4-4*t1*t2^3+8*t1^2*t2^2+16*t1^3-t2-48*t1^4
sage: C = Conic([a,b,c])
sage: C.has_rational_point()
...
Traceback (most recent call last):
...
NotImplementedError: is_square() not implemented for elements of
Univariate Quotient Polynomial Ring in tbar over Fraction Field
```

```
of Univariate Polynomial Ring in t1 over Rational Field with
modulus tbar^2 + t1*tbar - 1/2*t1^2
```

In some cases, the algorithm requires us to be able to solve conics over  $F$ . In particular, the following does not work:

```
sage: P.<u> = QQ[]
sage: E = P.fraction_field()
sage: Q.<Y> = E[]
sage: F.<v> = E.extension(Y^2 - u^3 - 1)
sage: R.<t> = F[]
sage: K = R.fraction_field()
sage: C = Conic(K, [u, v, 1])
sage: C.has_rational_point()
...
Traceback (most recent call last):
...
NotImplementedError: has_rational_point not implemented for conics
over base field Univariate Quotient Polynomial Ring in v over
Fraction Field of Univariate Polynomial Ring in u over Rational
Field with modulus v^2 - u^3 - 1
```

`has_rational_point` fails for some conics over function fields over finite fields, due to [trac ticket #20003](#):

```
sage: K.<t> = PolynomialRing(GF(7))
sage: C = Conic([5*t^2+4, t^2+3*t+3, 6*t^2+3*t+2, 5*t^2+5, 4*t+3, 4*t^2+t+5])
sage: C.has_rational_point()
...
Traceback (most recent call last):
...
TypeError: self (=Scheme morphism:
  From: Projective Conic Curve over Fraction Field of Univariate Polynomial
  ↪ Ring in t over Finite Field of size 7 defined by (5*t^2 + 4)*x^2 + ((6*t^3
  ↪ + 3*t^2 + 5*t + 5)/(t + 3))*y^2 + ((6*t^6 + 3*t^5 + t^3 + 6*t^2 + 6*t + 2)/
  ↪ (t^4 + t^3 + 4*t^2 + 3*t + 1))*z^2
  To: Projective Conic Curve over Fraction Field of Univariate Polynomial
  ↪ Ring in t over Finite Field of size 7 defined by (5*t^2 + 4)*x^2 + (t^2 +
  ↪ 3*t + 3)*x*y + (5*t^2 + 5)*y^2 + (6*t^2 + 3*t + 2)*x*z + (4*t + 3)*y*z +
  ↪ (4*t^2 + t + 5)*z^2
  Defn: Defined on coordinates by sending (x : y : z) to
      (x + ((2*t + 5)/(t + 3))*y + ((3*t^4 + 2*t^3 + 5*t^2 + 5*t + 3)/(t^4
  ↪ + t^3 + 4*t^2 + 3*t + 1))*z : y + ((6*t^3 + 6*t^2 + 3*t + 6)/(t^3 + 4*t^2 +
  ↪ 2*t + 2))*z : z)) domain must equal right (=Scheme morphism:
  From: Projective Conic Curve over Fraction Field of Univariate Polynomial
  ↪ Ring in t over Finite Field of size 7 defined by (5*t^3 + 6*t^2 + 3*t +
  ↪ 3)*x^2 + (t + 4)*y^2 + (6*t^7 + 2*t^5 + t^4 + 2*t^3 + 3*t^2 + 6*t + 6)*z^2
  To: Projective Conic Curve over Fraction Field of Univariate Polynomial
  ↪ Ring in t over Finite Field of size 7 defined by (5/(t^3 + 4*t^2 + 2*t +
  ↪ 2))*x^2 + (1/(t^3 + 3*t^2 + 5*t + 1))*y^2 + ((6*t^6 + 3*t^5 + t^3 + 6*t^2 +
  ↪ 6*t + 2)/(t^9 + 5*t^8 + t^7 + 6*t^6 + 3*t^5 + 4*t^3 + t^2 + 5*t + 3))*z^2
  Defn: Defined on coordinates by sending (x : y : z) to
      ((t^3 + 4*t^2 + 2*t + 2)*x : (t^2 + 5)*y : (t^5 + 4*t^4 + t^2 + 3*t +
  ↪ 3)*z)) codomain
```

## BASE CLASS FOR JACOBIANS OF CURVES

`sage.schemes.jacobians.abstract_jacobian.Jacobian(C)`

EXAMPLES:

```
sage: from sage.schemes.jacobians.abstract_jacobian import Jacobian
sage: P2.<x, y, z> = ProjectiveSpace(QQ, 2)
sage: C = Curve(x^3 + y^3 + z^3)
sage: Jacobian(C)
Jacobian of Projective Plane Curve over Rational Field defined by x^3 + y^3 + z^3
```

**class** `sage.schemes.jacobians.abstract_jacobian.Jacobian_generic(C)`

Bases: `sage.schemes.generic.scheme.Scheme`

Base class for Jacobians of projective curves.

The input must be a projective curve over a field.

EXAMPLES:

```
sage: from sage.schemes.jacobians.abstract_jacobian import Jacobian
sage: P2.<x, y, z> = ProjectiveSpace(QQ, 2)
sage: C = Curve(x^3 + y^3 + z^3)
sage: J = Jacobian(C); J
Jacobian of Projective Plane Curve over Rational Field defined by x^3 + y^3 + z^3
```

**base\_extend(R)**

Return the natural extension of self over  $R$

INPUT:

- $R$  – a field. The new base field.

OUTPUT:

The Jacobian over the ring  $R$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: Jac = H.jacobian(); Jac
Jacobian of Hyperelliptic Curve over Rational Field defined by y^2 = x^3 - 10*x + 9
sage: F.<a> = QQ.extension(x^2+1)
sage: Jac.base_extend(F)
Jacobian of Hyperelliptic Curve over Number Field in a with defining
polynomial x^2 + 1 defined by y^2 = x^3 - 10*x + 9
```

**change\_ring(*R*)**

Return the Jacobian over the ring *R*.

INPUT:

- *R* – a field. The new base ring.

OUTPUT:

The Jacobian over the ring *R*.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: Jac = H.jacobian(); Jac
Jacobian of Hyperelliptic Curve over Rational
Field defined by y^2 = x^3 - 10*x + 9
sage: Jac.change_ring(RDF)
Jacobian of Hyperelliptic Curve over Real Double
Field defined by y^2 = x^3 - 10.0*x + 9.0
```

**curve()**

Return the curve of which self is the Jacobian.

EXAMPLES:

```
sage: from sage.schemes.jacobians.abstract_jacobian import Jacobian
sage: P2.<x, y, z> = ProjectiveSpace(QQ, 2)
sage: J = Jacobian(Curve(x^3 + y^3 + z^3))
sage: J.curve()
Projective Plane Curve over Rational Field defined by x^3 + y^3 + z^3
```

`sage.schemes.jacobians.abstract_jacobian.is_Jacobian(J)`

Return True if *J* is of type `Jacobian_generic`.

EXAMPLES:

```
sage: from sage.schemes.jacobians.abstract_jacobian import Jacobian, is_Jacobian
sage: P2.<x, y, z> = ProjectiveSpace(QQ, 2)
sage: C = Curve(x^3 + y^3 + z^3)
sage: J = Jacobian(C)
sage: is_Jacobian(J)
True
```

```
sage: E = EllipticCurve('37a1')
sage: is_Jacobian(E)
False
```

## PLANE QUARTICS

### 14.1 Quartic curve constructor

`sage.schemes.plane_quartics.quartic_constructor.QuarticCurve` ( $F$ ,  $PP=None$ ,  $check=False$ )

Returns the quartic curve defined by the polynomial  $F$ .

INPUT:

- $F$  – a polynomial in three variables, homogeneous of degree 4
- $PP$  – a projective plane (default:None)
- $check$  – whether to check for smoothness or not (default:False)

EXAMPLES:

```
sage: x,y,z=PolynomialRing(QQ,['x','y','z']).gens()
sage: QuarticCurve(x**4+y**4+z**4)
Quartic Curve over Rational Field defined by  $x^4 + y^4 + z^4$ 
```

### 14.2 Plane quartic curves over a general ring. These are generic genus 3 curves,

as distinct from hyperelliptic curves of genus 3.

EXAMPLES:

```
sage: PP.<X,Y,Z> = ProjectiveSpace(2, QQ)
sage: f = X^4 + Y^4 + Z^4 - 3*X*Y*Z*(X+Y+Z)
sage: C = QuarticCurve(f); C
Quartic Curve over Rational Field defined by  $X^4 + Y^4 - 3X^2YZ - 3XY^2Z - 3XYZ^2 + Z^4$ 
```

**class** `sage.schemes.plane_quartics.quartic_generic.QuarticCurve_generic` ( $A$ ,  $f$ )

Bases: `sage.schemes.curves.projective_curve.ProjectivePlaneCurve`

**genus** ()

Returns the genus of self

EXAMPLES:

```
sage: x,y,z=PolynomialRing(QQ,['x','y','z']).gens()
sage: Q = QuarticCurve(x**4+y**4+z**4)
sage: Q.genus()
3
```

`sage.schemes.plane_quartics.quartic_generic.is_QuarticCurve(C)`

Checks whether C is a Quartic Curve

EXAMPLES:

```
sage: from sage.schemes.plane_quartics.quartic_generic import is_QuarticCurve
sage: x,y,z=PolynomialRing(QQ,['x','y','z']).gens()
sage: Q = QuarticCurve(x**4+y**4+z**4)
sage: is_QuarticCurve(Q)
True
```

## ELLIPTIC CURVES

### 15.1 Elliptic curve constructor

AUTHORS:

- William Stein (2005): Initial version
- John Cremona (2008-01): `EllipticCurve(j)` fixed for all cases

**class** `sage.schemes.elliptic_curves.constructor.EllipticCurveFactory`

Bases: `sage.structure.factory.UniqueFactory`

Construct an elliptic curve.

In Sage, an elliptic curve is always specified by (the coefficients of) a long Weierstrass equation

$$y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6.$$

INPUT:

There are several ways to construct an elliptic curve:

- `EllipticCurve([a1, a2, a3, a4, a6])`: Elliptic curve with given  $a$ -invariants. The invariants are coerced into a common parent. If all are integers, they are coerced into the rational numbers.
- `EllipticCurve([a4, a6])`: Same as above, but  $a_1 = a_2 = a_3 = 0$ .
- `EllipticCurve(label)`: Returns the elliptic curve over  $\mathbb{Q}$  from the Cremona database with the given label. The label is a string, such as "11a" or "37b2". The letters in the label *must* be lower case (Cremona's new labeling).
- `EllipticCurve(R, [a1, a2, a3, a4, a6])`: Create the elliptic curve over  $R$  with given  $a$ -invariants. Here  $R$  can be an arbitrary commutative ring, although most functionality is only implemented over fields.
- `EllipticCurve(j=j0)` or `EllipticCurve_from_j(j0)`: Return an elliptic curve with  $j$ -invariant  $j0$ .
- `EllipticCurve(polynomial)`: Read off the  $a$ -invariants from the polynomial coefficients, see `EllipticCurve_from_Weierstrass_polynomial()`.

Instead of giving the coefficients as a *list* of length 2 or 5, one can also give a *tuple*.

EXAMPLES:

We illustrate creating elliptic curves:

```
sage: EllipticCurve([0, 0, 1, -1, 0])
Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field
```

We create a curve from a Cremona label:

```
sage: EllipticCurve('37b2')
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 1873x - 31833$  over Rational Field
sage: EllipticCurve('5077a')
Elliptic Curve defined by  $y^2 + y = x^3 - 7x + 6$  over Rational Field
sage: EllipticCurve('389a')
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 2x$  over Rational Field
```

Old Cremona labels are allowed:

```
sage: EllipticCurve('2400FF')
Elliptic Curve defined by  $y^2 = x^3 + x^2 + 2x + 8$  over Rational Field
```

Unicode labels are allowed:

```
sage: EllipticCurve(u'389a')
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 2x$  over Rational Field
```

We create curves over a finite field as follows:

```
sage: EllipticCurve([GF(5)(0), 0, 1, -1, 0])
Elliptic Curve defined by  $y^2 + y = x^3 + 4x$  over Finite Field of size 5
sage: EllipticCurve(GF(5), [0, 0, 1, -1, 0])
Elliptic Curve defined by  $y^2 + y = x^3 + 4x$  over Finite Field of size 5
```

Elliptic curves over  $\mathbf{Z}/N\mathbf{Z}$  with  $N$  prime are of type “elliptic curve over a finite field”:

```
sage: F = Zmod(101)
sage: EllipticCurve(F, [2, 3])
Elliptic Curve defined by  $y^2 = x^3 + 2x + 3$  over Ring of integers modulo 101
sage: E = EllipticCurve([F(2), F(3)])
sage: type(E)
<class 'sage.schemes.elliptic_curves.ell_finite_field.EllipticCurve_finite_field_
↳with_category'>
sage: E.category()
Category of schemes over Ring of integers modulo 101
```

In contrast, elliptic curves over  $\mathbf{Z}/N\mathbf{Z}$  with  $N$  composite are of type “generic elliptic curve”:

```
sage: F = Zmod(95)
sage: EllipticCurve(F, [2, 3])
Elliptic Curve defined by  $y^2 = x^3 + 2x + 3$  over Ring of integers modulo 95
sage: E = EllipticCurve([F(2), F(3)])
sage: type(E)
<class 'sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic_with_
↳category'>
sage: E.category()
Category of schemes over Ring of integers modulo 95
```

The following is a curve over the complex numbers:

```
sage: E = EllipticCurve(CC, [0, 0, 1, -1, 0])
sage: E
Elliptic Curve defined by  $y^2 + 1.000000000000000*y = x^3 + (-1.000000000000000)*x$ 
↳over Complex Field with 53 bits of precision
sage: E.j_invariant()
2988.97297297297
```



We can also create elliptic curves by giving the Weierstrass equation:

```
sage: x, y = var('x,y')
sage: EllipticCurve(y^2 + y == x^3 + x - 9)
Elliptic Curve defined by y^2 + y = x^3 + x - 9 over Rational Field

sage: R.<x,y> = GF(5)[]
sage: EllipticCurve(x^3 + x^2 + 2 - y^2 - y*x)
Elliptic Curve defined by y^2 + x*y = x^3 + x^2 + 2 over Finite Field of size 5
```

We can explicitly specify the  $j$ -invariant:

```
sage: E = EllipticCurve(j=1728); E; E.j_invariant(); E.label()
Elliptic Curve defined by y^2 = x^3 - x over Rational Field
1728
'32a2'

sage: E = EllipticCurve(j=GF(5)(2)); E; E.j_invariant()
Elliptic Curve defined by y^2 = x^3 + x + 1 over Finite Field of size 5
2
```

See [trac ticket #6657](#)

```
sage: EllipticCurve(GF(144169), j=1728)
Elliptic Curve defined by y^2 = x^3 + x over Finite Field of size 144169
```

Elliptic curves over the same ring with the same Weierstrass coefficients are identical, even when they are constructed in different ways (see [trac ticket #11474](#)):

```
sage: EllipticCurve('11a3') is EllipticCurve(QQ, [0, -1, 1, 0, 0])
True
```

By default, when a rational value of  $j$  is given, the constructed curve is a minimal twist (minimal conductor for curves with that  $j$ -invariant). This can be changed by setting the optional parameter `minimal_twist`, which is `True` by default, to `False`:

```
sage: EllipticCurve(j=100)
Elliptic Curve defined by y^2 = x^3 + x^2 + 3392*x + 307888 over Rational Field
sage: E = EllipticCurve(j=100); E
Elliptic Curve defined by y^2 = x^3 + x^2 + 3392*x + 307888 over Rational Field
sage: E.conductor()
33129800
sage: E.j_invariant()
100
sage: E = EllipticCurve(j=100, minimal_twist=False); E
Elliptic Curve defined by y^2 = x^3 + 488400*x - 530076800 over Rational Field
sage: E.conductor()
298168200
sage: E.j_invariant()
100
```

Without this option, constructing the curve could take a long time since both  $j$  and  $j - 1728$  have to be factored to compute the minimal twist (see [trac ticket #13100](#)):

```
sage: E = EllipticCurve_from_j(2^256+1, minimal_twist=False)
sage: E.j_invariant() == 2^256+1
True
```

**create\_key\_and\_extra\_args** ( $x=None, y=None, j=None, \text{minimal\_twist}=True, **kws$ )

Return a UniqueFactory key and possibly extra parameters.

INPUT:

See the documentation for [EllipticCurveFactory](#).

OUTPUT:

A pair (key, extra\_args):

- key has the form  $(R, (a_1, a_2, a_3, a_4, a_6))$ , representing a ring and the Weierstrass coefficients of an elliptic curve over that ring;
- extra\_args is a dictionary containing additional data to be inserted into the elliptic curve structure.

EXAMPLES:

```
sage: EllipticCurve.create_key_and_extra_args(j=8000)
((Rational Field, (0, -1, 0, -3, -1)), {})
```

When constructing a curve over  $\mathbb{Q}$  from a Cremona or LMFDB label, the invariants from the database are returned as extra\_args:

```
sage: key, data = EllipticCurve.create_key_and_extra_args('389.a1')
sage: key
(Rational Field, (0, 1, 1, -2, 0))
sage: data['conductor']
389
sage: data['cremona_label']
'389a1'
sage: data['lmfdb_label']
'389.a1'
sage: data['rank']
2
sage: data['torsion_order']
1
```

User-specified keywords are also included in extra\_args:

```
sage: key, data = EllipticCurve.create_key_and_extra_args((0, 0, 1, -23737, 960366), rank=4)
sage: data['rank']
4
```

Furthermore, keywords takes precedence over data from the database, which can be used to specify an alternative set of generators for the Mordell-Weil group:

```
sage: key, data = EllipticCurve.create_key_and_extra_args('5077a1', gens=[[1, -1], [-2, 3], [4, -7]])
sage: data['gens']
[[1, -1], [-2, 3], [4, -7]]
sage: E = EllipticCurve.create_object(0, key, **data)
sage: E.gens()
[(-2 : 3 : 1), (1 : -1 : 1), (4 : -7 : 1)]
```

Note that elliptic curves are equal if and only they have the same base ring and Weierstrass equation; the data in extra\_args do not influence comparison of elliptic curves. A consequence of this is that passing keyword arguments only works when constructing an elliptic curve the first time:

```

sage: E = EllipticCurve('433a1', gens=[[-1, 1], [3, 4]])
sage: E.gens()
[(-1 : 1 : 1), (3 : 4 : 1)]
sage: E = EllipticCurve('433a1', gens=[[-1, 0], [0, 1]])
sage: E.gens()
[(-1 : 1 : 1), (3 : 4 : 1)]

```

**Warning:** Manually specifying extra data is almost never necessary and is not guaranteed to have any effect, as the above example shows. Almost no checking is done, so specifying incorrect data may lead to wrong results of computations instead of errors or warnings.

**create\_object** (*version*, *key*, *\*\*kws*)

Create an object from a UniqueFactory key.

EXAMPLES:

```

sage: E = EllipticCurve.create_object(0, (GF(3), (1, 2, 0, 1, 2)))
sage: type(E)
<class 'sage.schemes.elliptic_curves.ell_finite_field.EllipticCurve_finite_
↪field_with_category'>

```

**Note:** Keyword arguments are currently only passed to the constructor for elliptic curves over  $\mathbb{Q}$ ; elliptic curves over other fields do not support them.

`sage.schemes.elliptic_curves.constructor.EllipticCurve_from>Weierstrass_polynomial` (*f*)

Return the elliptic curve defined by a cubic in (long) Weierstrass form.

INPUT:

- *f* – a inhomogeneous cubic polynomial in long Weierstrass form.

OUTPUT:

The elliptic curve defined by it.

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: f = y^2 + 1*x*y + 3*y - (x^3 + 2*x^2 + 4*x + 6)
sage: EllipticCurve(f)
Elliptic Curve defined by y^2 + x*y + 3*y = x^3 + 2*x^2 + 4*x + 6 over Rational_
↪Field
sage: EllipticCurve(f).a_invariants()
(1, 2, 3, 4, 6)

```

The polynomial ring may have extra variables as long as they do not occur in the polynomial itself:

```

sage: R.<x,y,z,w> = QQ[]
sage: EllipticCurve(-y^2 + x^3 + 1)
Elliptic Curve defined by y^2 = x^3 + 1 over Rational Field
sage: EllipticCurve(-x^2 + y^3 + 1)
Elliptic Curve defined by y^2 = x^3 + 1 over Rational Field
sage: EllipticCurve(-w^2 + z^3 + 1)
Elliptic Curve defined by y^2 = x^3 + 1 over Rational Field

```

`sage.schemes.elliptic_curves.constructor.EllipticCurve_from_c4c6(c4, c6)`

Return an elliptic curve with given  $c_4$  and  $c_6$  invariants.

EXAMPLES:

```
sage: E = EllipticCurve_from_c4c6(17, -2005)
sage: E
Elliptic Curve defined by  $y^2 = x^3 - 17/48x + 2005/864$  over Rational Field
sage: E.c_invariants()
(17, -2005)
```

`sage.schemes.elliptic_curves.constructor.EllipticCurve_from_cubic(F, P=None, morphism=True)`

Construct an elliptic curve from a ternary cubic with a rational point.

If you just want the Weierstrass form and are not interested in the morphism then it is easier to use the function `Jacobian()` instead. If there is a rational point on the given cubic, this function will construct the same elliptic curve but you do not have to supply the point  $P$ .

INPUT:

- $F$  – a homogeneous cubic in three variables with rational coefficients, as a polynomial ring element, defining a smooth plane cubic curve  $C$ .
- $P$  – a 3-tuple  $(x, y, z)$  defining a projective point on  $C$ , or `None`. If `None` then a rational flex will be used as a base point if one exists, otherwise an error will be raised.
- `morphism` – boolean (default: `True`). If `True` returns a birational isomorphism from  $C$  to a Weierstrass elliptic curve  $E$ , otherwise just returns  $E$ .

OUTPUT:

Either (when `morphism=False`) an elliptic curve  $E$  in long Weierstrass form isomorphic to the plane cubic curve  $C$  defined by the equation  $F = 0$ .

Or (when `morphism=True`), a birational isomorphism from  $C$  to the elliptic curve  $E$ . If the given point is a flex, this is a linear isomorphism.

---

**Note:** The function `Jacobian()` may be used instead. It constructs the same elliptic curve (which is in all cases the Jacobian of  $(F = 0)$ ) and needs no base point to be provided, but also returns no isomorphism since in general there is none: the plane cubic is only isomorphic to its Jacobian when it has a rational point.

---



---

**Note:** When `morphism=True`, a birational isomorphism between the curve  $F = 0$  and the Weierstrass curve is returned. If the point happens to be a flex, then this is a linear isomorphism. The morphism does not necessarily take the given point  $P$  to the point at infinity on  $E$ , since we always use a rational flex on  $C$  as base-point when one exists.

---

EXAMPLES:

First we find that the Fermat cubic is isomorphic to the curve with Cremona label 27a1:

```
sage: R.<x,y,z> = QQ[]
sage: cubic = x^3+y^3+z^3
sage: P = [1,-1,0]
sage: E = EllipticCurve_from_cubic(cubic, P, morphism=False); E
Elliptic Curve defined by  $y^2 - 9y = x^3 - 27$  over Rational Field
sage: E.cremona_label()
```

```
'27a1'
sage: EllipticCurve_from_cubic(cubic, [0,1,-1], morphism=False).cremona_label()
'27a1'
sage: EllipticCurve_from_cubic(cubic, [1,0,-1], morphism=False).cremona_label()
'27a1'
```

Next we find the minimal model and conductor of the Jacobian of the Selmer curve:

```
sage: R.<a,b,c> = QQ[]
sage: cubic = a^3+b^3+60*c^3
sage: P = [1,-1,0]
sage: E = EllipticCurve_from_cubic(cubic, P, morphism=False); E
Elliptic Curve defined by  $y^2 - 540*y = x^3 - 97200$  over Rational Field
sage: E.minimal_model()
Elliptic Curve defined by  $y^2 = x^3 - 24300$  over Rational Field
sage: E.conductor()
24300
```

We can also get the birational isomorphism to and from the Weierstrass form. We start with an example where  $P$  is a flex and the equivalence is a linear isomorphism:

```
sage: f = EllipticCurve_from_cubic(cubic, P, morphism=True)
sage: f
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by  $a^3 + b^3 + 60*c^3$ 
  To:   Elliptic Curve defined by  $y^2 - 540*y = x^3 - 97200$  over Rational Field
  Defn: Defined on coordinates by sending (a : b : c) to
        (-c : 3*a : 1/180*a + 1/180*b)

sage: finv = f.inverse(); finv
Scheme morphism:
  From: Elliptic Curve defined by  $y^2 - 540*y = x^3 - 97200$  over Rational Field
  To:   Projective Plane Curve over Rational Field defined by  $a^3 + b^3 + 60*c^3$ 
  Defn: Defined on coordinates by sending (x : y : z) to
        (1/3*y : -1/3*y + 180*z : -x)

Scheme morphism:
  From: Elliptic Curve defined by  $y^2 + 2*x*y + 20*y = x^3 - x^2 - 20*x - 400/3$ 
        over Rational Field
  To:   Closed subscheme of Projective Space of dimension 2 over Rational Field,
  ↪ defined by:
         $a^3 + b^3 + 60*c^3$ 
  Defn: Defined on coordinates by sending (x : y : z) to
        (x + y + 20*z : -x - y : -x)
```

We verify that  $f$  maps the chosen point  $P = (1, -1, 0)$  on the cubic to the origin of the elliptic curve:

```
sage: f([1,-1,0])
(0 : 1 : 0)
sage: finv([0,1,0])
(-1 : 1 : 0)
```

To verify the output, we plug in the polynomials to check that this indeed transforms the cubic into Weierstrass form:

```
sage: cubic(finv.defining_polynomials()) * finv.post_rescaling()
-x^3 + y^2*z - 540*y*z^2 + 97200*z^3
```

```
sage: E.defined_polynomial()(f.defined_polynomials()) * f.post_rescaling()
a^3 + b^3 + 60*c^3
```

If the given point is not a flex and the cubic has no rational flexes, then the cubic can not be transformed to a Weierstrass equation by a linear transformation. The general birational transformation is still a birational isomorphism, but is quadratic:

```
sage: R.<x,y,z> = QQ[]
sage: cubic = x^2*y + 4*x*y^2 + x^2*z + 8*x*y*z + 4*y^2*z + 9*x*z^2 + 9*y*z^2
sage: f = EllipticCurve_from_cubic(cubic, [1,-1,1], morphism=True); f
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by x^2*y + 4*x*y^2 + x^
  ↪ 2*z + 8*x*y*z + 4*y^2*z + 9*x*z^2 + 9*y*z^2
  To:   Elliptic Curve defined by y^2 + 7560/19*x*y + 552960000000/2352637*y = x^
  ↪ 3 - 3445200/133*x^2 over Rational Field
  Defn: Defined on coordinates by sending (x : y : z) to
        (2527/17280*x^2 + 133/2160*x*y + 133/108000*y^2 + 133/2880*x*z + 931/
  ↪ 18000*y*z - 3857/48000*z^2 : -6859/288*x^2 + 323/36*x*y + 359/1800*y^2 + 551/
  ↪ 48*x*z + 2813/300*y*z + 24389/800*z^2 : -2352637/995328000000*x^2 - 2352637/
  ↪ 124416000000*x*y - 2352637/622080000000*y^2 + 2352637/82944000000*x*z + 2352637/
  ↪ 207360000000*y*z - 2352637/276480000000*z^2)
```

Note that the morphism returned cannot be evaluated directly at the given point  $P = (1 : -1 : 1)$  since the polynomials defining it all vanish there:

```
sage: f([1,-1,1])
Traceback (most recent call last):
...
ValueError: [0, 0, 0] does not define a valid point since all entries are 0
```

Using the group law on the codomain elliptic curve, which has rank 1 and full 2-torsion, and the inverse morphism, we can find many points on the cubic. First we find the preimages of multiples of the generator:

```
sage: E = f.codomain()
sage: E.label()
'720e2'
sage: E.rank()
1
sage: R = E.gens()[0]; R
(-17280000/2527 : 9331200000/6859 : 1)
sage: finv = f.inverse()
sage: [finv(k*R) for k in range(1,10)]
[(-4 : 1 : 0),
 (-1 : 4 : 1),
 (-20 : -55/76 : 1),
 (319/399 : -11339/7539 : 1),
 (159919/14360 : -4078139/1327840 : 1),
 (-27809119/63578639 : 1856146436/3425378659 : 1),
 (-510646582340/56909753439 : 424000923715/30153806197284 : 1),
 (-56686114363679/4050436059492161 : -2433034816977728281/1072927821085503881 : 1),
 (650589589099815846721/72056273157352822480 : -347376189546061993109881/
 ↪ 194127383495944026752320 : 1)]
```

The elliptic curve also has torsion, which we can map back:

```
sage: E.torsion_points()
[(-144000000/17689 : 3533760000000/2352637 : 1),
 (-92160000/17689 : 2162073600000/2352637 : 1),
```

```
(-5760000/17689 : -124070400000/2352637 : 1),
(0 : 1 : 0)]
sage: [finv(Q) for Q in E.torsion_points() if Q]
[(9 : -9/4 : 1), (-9 : 0 : 1), (0 : 1 : 0)]
```

In this example, the given point  $P$  is not a flex but the cubic does have a rational flex,  $(-4:0:1)$ . We return a linear isomorphism which maps this flex to the point at infinity on the Weierstrass model:

```
sage: R.<a,b,c> = QQ[]
sage: cubic = a^3+7*b^3+64*c^3
sage: P = [2,2,-1]
sage: f = EllipticCurve_from_cubic(cubic, P, morphism=True)
sage: E = f.codomain(); E
Elliptic Curve defined by y^2 - 258048*y = x^3 - 22196256768 over Rational Field
sage: E.minimal_model()
Elliptic Curve defined by y^2 + y = x^3 - 331 over Rational Field

sage: f
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by a^3 + 7*b^3 + 64*c^3
  To:   Elliptic Curve defined by y^2 - 258048*y = x^3 - 22196256768 over
↳Rational Field
  Defn: Defined on coordinates by sending (a : b : c) to
        (b : -48*a : -1/5376*a - 1/1344*c)

sage: finv = f.inverse(); finv
Scheme morphism:
  From: Elliptic Curve defined by y^2 - 258048*y = x^3 - 22196256768 over
↳Rational Field
  To:   Projective Plane Curve over Rational Field defined by a^3 + 7*b^3 + 64*c^3
  Defn: Defined on coordinates by sending (x : y : z) to
        (-1/48*y : x : 1/192*y - 1344*z)

sage: cubic(finv.defined_polynomials()) * finv.post_rescaling()
-x^3 + y^2*z - 258048*y*z^2 + 22196256768*z^3

sage: E.defined_polynomial()(f.defined_polynomials()) * f.post_rescaling()
a^3 + 7*b^3 + 64*c^3

sage: f(P)
(5376 : -258048 : 1)
sage: f([-4,0,1])
(0 : 1 : 0)
```

It is possible to not provide a base point  $P$  provided that the cubic has a rational flex. In this case the flexes will be found and one will be used as a base point:

```
sage: R.<x,y,z> = QQ[]
sage: cubic = x^3+y^3+z^3
sage: f = EllipticCurve_from_cubic(cubic, morphism=True)
sage: f
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by x^3 + y^3 + z^3
  To:   Elliptic Curve defined by y^2 - 9*y = x^3 - 27 over Rational Field
  Defn: Defined on coordinates by sending (x : y : z) to
        (y : -3*x : -1/3*x - 1/3*z)
```

An error will be raised if no point is given and there are no rational flexes:

```

sage: R.<x,y,z> = QQ[]
sage: cubic = 3*x^3+4*y^3+5*z^3
sage: EllipticCurve_from_cubic(cubic)
Traceback (most recent call last):
...
ValueError: A point must be given when the cubic has no rational flexes

```

An example over a finite field, using a flex:

```

sage: K = GF(17)
sage: R.<x,y,z> = K[]
sage: cubic = 2*x^3+3*y^3+4*z^3
sage: EllipticCurve_from_cubic(cubic, [0,3,1])
Scheme morphism:
  From: Projective Plane Curve over Finite Field of size 17 defined by 2*x^3 +
↪ 3*y^3 + 4*z^3
  To:   Elliptic Curve defined by y^2 + 16*y = x^3 + 11 over Finite Field of size
↪ 17
  Defn: Defined on coordinates by sending (x : y : z) to
        (-x : 4*y : 4*y + 5*z)

```

An example in characteristic 3:

```

sage: K = GF(3)
sage: R.<x,y,z> = K[]
sage: cubic = x^3+y^3+z^3+x*y*z
sage: EllipticCurve_from_cubic(cubic, [0,1,-1])
Scheme morphism:
  From: Projective Plane Curve over Finite Field of size 3 defined by x^3 + y^3 +
↪ x*y*z + z^3
  To:   Elliptic Curve defined by y^2 + x*y = x^3 + 1 over Finite Field of size 3
  Defn: Defined on coordinates by sending (x : y : z) to
        (y + z : -y : x)

```

An example over a number field, using a non-flex and where there are no rational flexes:

```

sage: K.<a> = QuadraticField(-3)
sage: R.<x,y,z> = K[]
sage: cubic = 2*x^3+3*y^3+5*z^3
sage: EllipticCurve_from_cubic(cubic, [1,1,-1])
Scheme morphism:
  From: Projective Plane Curve over Number Field in a with defining polynomial x^
↪ 2 + 3 defined by 2*x^3 + 3*y^3 + 5*z^3
  To:   Elliptic Curve defined by y^2 + 1754460/2053*x*y + 5226454388736000/
↪ 8653002877*y = x^3 + (-652253285700/4214809)*x^2 over Number Field in a with
↪ defining polynomial x^2 + 3
  Defn: Defined on coordinates by sending (x : y : z) to
        (-16424/127575*x^2 - 231989/680400*x*y - 14371/64800*y^2 - 26689/
↪ 81648*x*z - 10265/27216*y*z - 2053/163296*z^2 : 24496/315*x^2 + 119243/840*x*y
↪ + 4837/80*y^2 + 67259/504*x*z + 25507/168*y*z + 5135/1008*z^2 : 8653002877/
↪ 2099914709760000*x^2 + 8653002877/699971569920000*x*y + 8653002877/
↪ 933295426560000*y^2 + 8653002877/419982941952000*x*z + 8653002877/
↪ 279988627968000*y*z + 8653002877/335986353561600*z^2)

```

An example over a function field, using a non-flex:

```

sage: K.<t> = FunctionField(QQ)
sage: R.<x,y,z> = K[]

```



```

sage: cubic = x^3+t*y^3+(1+t)*z^3
sage: EllipticCurve_from_cubic(cubic,[1,1,-1], morphism=False)
Elliptic Curve defined by y^2 + ((-236196*t^6-708588*t^5-1180980*t^4-1180980*t^3-
↪ 708588*t^2-236196*t)/(-1458*t^6-17496*t^5+4374*t^4+29160*t^3+4374*t^2-17496*t-
↪ 1458))*x*y + ((-459165024*t^14-5969145312*t^13-34207794288*t^12-113872925952*t^
↪ 11-244304490582*t^10-354331909458*t^9-354331909458*t^8-244304490582*t^7-
↪ 113872925952*t^6-34207794288*t^5-5969145312*t^4-459165024*t^3)/(-1458*t^14-
↪ 58320*t^13-841266*t^12-5137992*t^11-11773350*t^10-7709904*t^9+12627738*t^
↪ 8+25789104*t^7+12627738*t^6-7709904*t^5-11773350*t^4-5137992*t^3-841266*t^2-
↪ 58320*t-1458))*y = x^3 + ((-118098*t^12-708588*t^11+944784*t^10+11219310*t^
↪ 9+27871128*t^8+36374184*t^7+27871128*t^6+11219310*t^5+944784*t^4-708588*t^3-
↪ 118098*t^2)/(-54*t^12-1296*t^11-7452*t^10+6048*t^9+25758*t^8-3888*t^7-38232*t^6-
↪ 3888*t^5+25758*t^4+6048*t^3-7452*t^2-1296*t-54))*x^2 over Rational function_
↪ field in t over Rational Field

```

sage.schemes.elliptic\_curves.constructor.**EllipticCurve\_from\_j**(j, *minimal\_twist=True*)

Return an elliptic curve with given  $j$ -invariant.

INPUT:

- $j$  – an element of some field.
- `minimal_twist` (boolean, default True) – If True and  $j$  is in  $\mathbb{Q}$ , the curve returned is a minimal twist, i.e. has minimal conductor. If  $j$  is not in  $\mathbb{Q}$  this parameter is ignored.

OUTPUT:

An elliptic curve with  $j$ -invariant  $j$ .

EXAMPLES:

```

sage: E = EllipticCurve_from_j(0); E; E.j_invariant(); E.label()
Elliptic Curve defined by y^2 + y = x^3 over Rational Field
0
'27a3'

sage: E = EllipticCurve_from_j(1728); E; E.j_invariant(); E.label()
Elliptic Curve defined by y^2 = x^3 - x over Rational Field
1728
'32a2'

sage: E = EllipticCurve_from_j(1); E; E.j_invariant()
Elliptic Curve defined by y^2 + x*y = x^3 + 36*x + 3455 over Rational Field
1

```

The `minimal_twist` parameter (ignored except over  $\mathbb{Q}$  and True by default) controls whether or not a minimal twist is computed:

```

sage: EllipticCurve_from_j(100)
Elliptic Curve defined by y^2 = x^3 + x^2 + 3392*x + 307888 over Rational Field
sage: _.conductor()
33129800
sage: EllipticCurve_from_j(100, minimal_twist=False)
Elliptic Curve defined by y^2 = x^3 + 488400*x - 530076800 over Rational Field
sage: _.conductor()
298168200

```

Since computing the minimal twist requires factoring both  $j$  and  $j - 1728$  the following example would take a long time without setting `minimal_twist` to False:

```
sage: E = EllipticCurve_from_j(2^256+1,minimal_twist=False)
sage: E.j_invariant() == 2^256+1
True
```

sage.schemes.elliptic\_curves.constructor.**EllipticCurve\_from\_plane\_curve**(C,  
P)

Deprecated way to construct an elliptic curve.

Use `Jacobian()` instead.

EXAMPLES:

```
sage: R.<x,y,z> = QQ[]
sage: C = Curve(x^3+y^3+z^3)
sage: P = C(1,-1,0)
sage: E = EllipticCurve_from_plane_curve(C,P); E # long time (3s on sage.math, ↵
↵2013)
doctest:...: DeprecationWarning: use Jacobian(C) instead
See http://trac.sagemath.org/3416 for details.
Elliptic Curve defined by y^2 = x^3 - 27/4 over Rational Field
```

sage.schemes.elliptic\_curves.constructor.**EllipticCurves\_with\_good\_reduction\_outside\_S**(S=[],  
proof=  
ver=  
bose=

Returns a sorted list of all elliptic curves defined over  $Q$  with good reduction outside the set  $S$  of primes.

INPUT:

- $S$  - list of primes (default: empty list).
- `proof` - True/False (default True): the MW basis for auxiliary curves will be computed with this proof flag.
- `verbose` - True/False (default False): if True, some details of the computation will be output.

**Note:** Proof flag: The algorithm used requires determining all  $S$ -integral points on several auxiliary curves, which in turn requires the computation of their generators. This is not always possible (even in theory) using current knowledge.

The value of this flag is passed to the function which computes generators of various auxiliary elliptic curves, in order to find their  $S$ -integral points. Set to False if the default (True) causes warning messages, but note that you can then not rely on the set of curves returned being complete.

EXAMPLES:

```
sage: EllipticCurves_with_good_reduction_outside_S([])
[]
sage: elist = EllipticCurves_with_good_reduction_outside_S([2])
sage: elist
[Elliptic Curve defined by y^2 = x^3 + 4*x over Rational Field,
Elliptic Curve defined by y^2 = x^3 - x over Rational Field,
...
Elliptic Curve defined by y^2 = x^3 - x^2 - 13*x + 21 over Rational Field]
sage: len(elist)
24
sage: ', '.join([e.label() for e in elist])
'32a1, 32a2, 32a3, 32a4, 64a1, 64a2, 64a3, 64a4, 128a1, 128a2, 128b1, 128b2, ↵
↵128c1, 128c2, 128d1, 128d2, 256a1, 256a2, 256b1, 256b2, 256c1, 256c2, 256d1, ↵
↵256d2'
```

Without `Proof=False`, this example gives two warnings:

```
sage: elist = EllipticCurves_with_good_reduction_outside_S([11],proof=False) #_
↪long time (14s on sage.math, 2011)
sage: len(elist) # long time
12
sage: ', '.join([e.label() for e in elist]) # long time
'11a1, 11a2, 11a3, 121a1, 121a2, 121b1, 121b2, 121c1, 121c2, 121d1, 121d2, 121d3'

sage: elist = EllipticCurves_with_good_reduction_outside_S([2,3]) # long time_
↪(26s on sage.math, 2011)
sage: len(elist) # long time
752
sage: max([e.conductor() for e in elist]) # long time
62208
sage: [N.factor() for N in Set([e.conductor() for e in elist])] # long time
[2^7,
2^8,
2^3 * 3^4,
2^2 * 3^3,
2^8 * 3^4,
2^4 * 3^4,
2^3 * 3,
2^7 * 3,
2^3 * 3^5,
3^3,
2^8 * 3,
2^5 * 3^4,
2^4 * 3,
2 * 3^4,
2^2 * 3^2,
2^6 * 3^4,
2^6,
2^7 * 3^2,
2^4 * 3^5,
2^4 * 3^3,
2 * 3^3,
2^6 * 3^3,
2^6 * 3,
2^5,
2^2 * 3^4,
2^3 * 3^2,
2^5 * 3,
2^7 * 3^4,
2^2 * 3^5,
2^8 * 3^2,
2^5 * 3^2,
2^7 * 3^5,
2^8 * 3^5,
2^3 * 3^3,
2^8 * 3^3,
2^5 * 3^5,
2^4 * 3^2,
2 * 3^5,
2^5 * 3^3,
2^6 * 3^5,
2^7 * 3^3,
```

```
3^5,
2^6 * 3^2]
```

`sage.schemes.elliptic_curves.constructor.are_projectively_equivalent` (*P*, *Q*,  
*base\_ring*)

Test whether *P* and *Q* are projectively equivalent.

INPUT:

- *P*, *Q* – list/tuple of projective coordinates.
- *base\_ring* – the base ring.

OUTPUT:

Boolean.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.constructor import are_projectively_
      ↪equivalent
sage: are_projectively_equivalent([0,1,2,3], [0,1,2,2], base_ring=QQ)
False
sage: are_projectively_equivalent([0,1,2,3], [0,2,4,6], base_ring=QQ)
True
```

`sage.schemes.elliptic_curves.constructor.chord_and_tangent` (*F*, *P*)

Return the third point of intersection of a cubic with the tangent at one point.

INPUT:

- *F* – a homogeneous cubic in three variables with rational coefficients, as a polynomial ring element, defining a smooth plane cubic curve.
- *P* – a 3-tuple  $(x, y, z)$  defining a projective point on the curve  $F = 0$ .

OUTPUT:

A point *Q* such that  $F(Q) = 0$ , namely the third point of intersection of the tangent at *P* with the curve  $F = 0$ , so  $Q = P$  if and only if *P* is a flex.

EXAMPLES:

```
sage: R.<x,y,z> = QQ[]
sage: from sage.schemes.elliptic_curves.constructor import chord_and_tangent
sage: F = x^3+y^3+60*z^3
sage: chord_and_tangent(F, [1,-1,0])
(-1 : 1 : 0)

sage: F = x^3+7*y^3+64*z^3
sage: p0 = [2,2,-1]
sage: p1 = chord_and_tangent(F, p0); p1
(5 : -3 : 1)
sage: p2 = chord_and_tangent(F, p1); p2
(-1265/314 : 183/314 : 1)
```

`sage.schemes.elliptic_curves.constructor.coefficients_from_Weierstrass_polynomial` (*f*)

Return the coefficients  $[a_1, a_2, a_3, a_4, a_6]$  of a cubic in Weierstrass form.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.constructor import coefficients_from_
      ↪ Weierstrass_polynomial
sage: R.<w,z> = QQ[]
sage: coefficients_from_Weierstrass_polynomial(-w^2 + z^3 + 1)
[0, 0, 0, 0, 1]

```

`sage.schemes.elliptic_curves.constructor.coefficients_from_j(j, minimal_twist=True)`  
 Return Weierstrass coefficients  $(a_1, a_2, a_3, a_4, a_6)$  for an elliptic curve with given  $j$ -invariant.

INPUT:

See `EllipticCurve_from_j()`.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.constructor import coefficients_from_j
sage: coefficients_from_j(0)
[0, 0, 1, 0, 0]
sage: coefficients_from_j(1728)
[0, 0, 0, -1, 0]
sage: coefficients_from_j(1)
[1, 0, 0, 36, 3455]

```

The `minimal_twist` parameter (ignored except over  $\mathbb{Q}$  and `True` by default) controls whether or not a minimal twist is computed:

```

sage: coefficients_from_j(100)
[0, 1, 0, 3392, 307888]
sage: coefficients_from_j(100, minimal_twist=False)
[0, 0, 0, 488400, -530076800]

```

`sage.schemes.elliptic_curves.constructor.projective_point(p)`

Return equivalent point with denominators removed

INPUT:

- $P, Q$  – list/tuple of projective coordinates.

OUTPUT:

List of projective coordinates.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.constructor import projective_point
sage: projective_point([4/5, 6/5, 8/5])
[2, 3, 4]
sage: F = GF(11)
sage: projective_point([F(4), F(8), F(2)])
[4, 8, 2]

```

`sage.schemes.elliptic_curves.constructor.tangent_at_smooth_point(C, P)`

Return the tangent at the smooth point  $P$  of projective curve  $C$ .

INPUT:

- $C$  – a projective plane curve.
- $P$  – a 3-tuple  $(x, y, z)$  defining a projective point on  $C$ .

OUTPUT:

The linear form defining the tangent at  $P$  to  $C$ .

EXAMPLES:

```
sage: R.<x,y,z> = QQ[]
sage: from sage.schemes.elliptic_curves.constructor import tangent_at_smooth_point
sage: C = Curve(x^3+y^3+60*z^3)
sage: tangent_at_smooth_point(C, [1,-1,0])
x + y

sage: K.<t> = FunctionField(QQ)
sage: R.<x,y,z> = K[]
sage: C = Curve(x^3+2*y^3+3*z^3)
sage: from sage.schemes.elliptic_curves.constructor import tangent_at_smooth_point
sage: tangent_at_smooth_point(C, [1,1,-1])
3*x + 6*y + 9*z
```

## 15.2 Construct elliptic curves as Jacobians

An elliptic curve is a genus one curve with a designated point. The Jacobian of a genus-one curve can be defined as the set of line bundles on the curve, and is isomorphic to the original genus-one curve. It is also an elliptic curve with the trivial line bundle as designated point. The utility of this construction is that we can construct elliptic curves without having to specify which point we take as the origin.

EXAMPLES:

```
sage: R.<u,v,w> = QQ[]
sage: Jacobian(u^3+v^3+w^3)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field
sage: Jacobian(u^4+v^4+w^2)
Elliptic Curve defined by  $y^2 = x^3 - 4x$  over Rational Field

sage: C = Curve(u^3+v^3+w^3)
sage: Jacobian(C)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field

sage: P2.<u,v,w> = ProjectiveSpace(2, QQ)
sage: C = P2.subscheme(u^3+v^3+w^3)
sage: Jacobian(C)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field
```

One can also define Jacobians of varieties that are not genus-one curves. These are not implemented in this module, but we call the relevant functionality:

```
sage: R.<x> = PolynomialRing(QQ)
sage: f = x**5 + 1184*x**3 + 1846*x**2 + 956*x + 560
sage: C = HyperellipticCurve(f)
sage: Jacobian(C)
Jacobian of Hyperelliptic Curve over Rational Field defined
by  $y^2 = x^5 + 1184x^3 + 1846x^2 + 956x + 560$ 
```

REFERENCES:

```
sage.schemes.elliptic_curves.jacobian.Jacobian(X, **kws)
Return the Jacobian.
```

INPUT:

- $X$  – polynomial, algebraic variety, or anything else that has a Jacobian elliptic curve.
- `kwds` – optional keyword arguments.

The input  $X$  can be one of the following:

- A polynomial, see [Jacobian\\_of\\_equation\(\)](#) for details.
- A curve, see [Jacobian\\_of\\_curve\(\)](#) for details.

EXAMPLES:

```
sage: R.<u,v,w> = QQ[]
sage: Jacobian(u^3+v^3+w^3)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field

sage: C = Curve(u^3+v^3+w^3)
sage: Jacobian(C)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field

sage: P2.<u,v,w> = ProjectiveSpace(2, QQ)
sage: C = P2.subscheme(u^3+v^3+w^3)
sage: Jacobian(C)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field

sage: Jacobian(C, morphism=True)
Scheme morphism:
  From: Closed subscheme of Projective Space of dimension 2 over Rational Field
  → defined by:
       $u^3 + v^3 + w^3$ 
  To: Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field
  Defn: Defined on coordinates by sending  $(u : v : w)$  to
       $(-u^4*v^4*w - u^4*v*w^4 - u*v^4*w^4 :$ 
       $1/2*u^6*v^3 - 1/2*u^3*v^6 - 1/2*u^6*w^3 + 1/2*v^6*w^3 + 1/2*u^3*w^6 - 1/$ 
  →  $2*v^3*w^6 :$ 
       $u^3*v^3*w^3)$ 
```

`sage.schemes.elliptic_curves.jacobian.Jacobian_of_curve` (*curve*, *morphism=False*)

Return the Jacobian of a genus-one curve

INPUT:

- *curve* – a one-dimensional algebraic variety of genus one.

OUTPUT:

Its Jacobian elliptic curve.

EXAMPLES:

```
sage: R.<u,v,w> = QQ[]
sage: C = Curve(u^3+v^3+w^3)
sage: Jacobian(C)
Elliptic Curve defined by  $y^2 = x^3 - 27/4$  over Rational Field
```

`sage.schemes.elliptic_curves.jacobian.Jacobian_of_equation` (*polynomial*, *variables=None*, *curve=None*)

Construct the Jacobian of a genus-one curve given by a polynomial.

INPUT:

- `F` – a polynomial defining a plane curve of genus one. May be homogeneous or inhomogeneous.
- `variables` – list of two or three variables or `None` (default). The inhomogeneous or homogeneous coordinates. By default, all variables in the polynomial are used.
- `curve` – the genus-one curve defined by `polynomial` or `# None` (default). If specified, suitable morphism from the jacobian elliptic curve to the curve is returned.

OUTPUT:

An elliptic curve in short Weierstrass form isomorphic to the curve `polynomial=0`. If the optional argument `curve` is specified, a rational multicover from the Jacobian elliptic curve to the genus-one curve is returned.

EXAMPLES:

```
sage: R.<a,b,c> = QQ[]
sage: f = a^3+b^3+60*c^3
sage: Jacobian(f)
Elliptic Curve defined by y^2 = x^3 - 24300 over Rational Field
sage: Jacobian(f.subs(c=1))
Elliptic Curve defined by y^2 = x^3 - 24300 over Rational Field
```

If we specify the domain curve the birational covering is returned:

```
sage: h = Jacobian(f, curve=Curve(f)); h
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by a^3 + b^3 + 60*c^3
  To:   Elliptic Curve defined by y^2 = x^3 - 24300 over Rational Field
  Defn: Defined on coordinates by sending (a : b : c) to
        (-216000*a^4*b^4*c - 12960000*a^4*b*c^4 - 12960000*a*b^4*c^4 :
         108000*a^6*b^3 - 108000*a^3*b^6 - 6480000*a^6*c^3 + 6480000*b^6*c^3 +
↪ 388800000*a^3*c^6 - 388800000*b^3*c^6 :
         216000*a^3*b^3*c^3)

sage: h([1,-1,0])
(0 : 1 : 0)
```

Plugging in the polynomials defining `h` allows us to verify that it is indeed a rational morphism to the elliptic curve:

```
sage: E = h.codomain()
sage: E.defining_polynomial() (h.defining_polynomials()).factor()
(2519424000000000) * c^3 * b^3 * a^3 * (a^3 + b^3 + 60*c^3) *
(a^9*b^6 + a^6*b^9 - 120*a^9*b^3*c^3 + 900*a^6*b^6*c^3 - 120*a^3*b^9*c^3 +
3600*a^9*c^6 + 54000*a^6*b^3*c^6 + 54000*a^3*b^6*c^6 + 3600*b^9*c^6 +
216000*a^6*c^9 - 432000*a^3*b^3*c^9 + 216000*b^6*c^9)
```

By specifying the variables, we can also construct an elliptic curve over a polynomial ring:

```
sage: R.<u,v,t> = QQ[]
sage: Jacobian(u^3+v^3+t, variables=[u,v])
Elliptic Curve defined by y^2 = x^3 + (-27/4*t^2) over
Multivariate Polynomial Ring in u, v, t over Rational Field
```

## 15.3 Points on elliptic curves

The base class `EllipticCurvePoint_field`, derived from `AdditiveGroupElement`, provides support for points on elliptic curves defined over general fields. The derived classes `EllipticCurvePoint_number_field`



and `EllipticCurvePoint_finite_field` provide further support for point on curves defined over number fields (including the rational field  $\mathbb{Q}$ ) and over finite fields.

The class `EllipticCurvePoint`, which is based on `SchemeMorphism_point_projective_ring`, currently has little extra functionality.

#### EXAMPLES:

An example over  $\mathbb{Q}$ :

```
sage: E = EllipticCurve('389a1')
sage: P = E(-1,1); P
(-1 : 1 : 1)
sage: Q = E(0,-1); Q
(0 : -1 : 1)
sage: P+Q
(4 : 8 : 1)
sage: P-Q
(1 : 0 : 1)
sage: 3*P-5*Q
(328/361 : -2800/6859 : 1)
```

An example over a number field:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [1,0,0,0,-1])
sage: P = E(0,i); P
(0 : i : 1)
sage: P.order()
+Infinity
sage: 101*P-100*P==P
True
```

An example over a finite field:

```
sage: K.<a> = GF(101^3)
sage: E = EllipticCurve(K, [1,0,0,0,-1])
sage: P = E(40*a^2 + 69*a + 84, 58*a^2 + 73*a + 45)
sage: P.order()
1032210
sage: E.cardinality()
1032210
```

Arithmetic with a point over an extension of a finite field:

```
sage: k.<a> = GF(5^2)
sage: E = EllipticCurve(k, [1,0]); E
Elliptic Curve defined by y^2 = x^3 + x over Finite Field in a of size 5^2
sage: P = E([a,2*a+4])
sage: 5*P
(2*a + 3 : 2*a : 1)
sage: P*5
(2*a + 3 : 2*a : 1)
sage: P + P + P + P + P
(2*a + 3 : 2*a : 1)
```

```
sage: F = Zmod(3)
sage: E = EllipticCurve(F, [1,0]);
sage: P = E([2,1])
```

```
sage: import sys
sage: n = sys.maxsize
sage: P*(n+1)-P*n == P
True
```

Arithmetic over  $\mathbb{Z}/N\mathbb{Z}$  with composite  $N$  is supported. When an operation tries to invert a non-invertible element, a `ZeroDivisionError` is raised and a factorization of the modulus appears in the error message:

```
sage: N = 1715761513
sage: E = EllipticCurve(Integers(N), [3, -13])
sage: P = E(2, 1)
sage: LCM([2..60])*P
Traceback (most recent call last):
...
ZeroDivisionError: Inverse of 1520944668 does not exist (characteristic = 1715761513,
↳= 26927*63719)
```

#### AUTHORS:

- William Stein (2005) – Initial version
- Robert Bradshaw et al. ...
- John Cremona (Feb 2008) – Point counting and group structure for non-prime fields, Frobenius endomorphism and order, elliptic logs
- John Cremona (Aug 2008) – Introduced `EllipticCurvePoint_number_field` class
- Tobias Nagel, Michael Mardaus, John Cremona (Dec 2008) –  $p$ -adic elliptic logarithm over  $\mathbb{Q}$
- David Hansen (Jan 2009) – Added `weil_pairing` function to `EllipticCurvePoint_finite_field` class
- Mariah Lenox (March 2011) – Added `tate_pairing` and `ate_pairing` functions to `EllipticCurvePoint_finite_field` class

```
class sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint(X, v,
                                                                check=True)
    Bases: sage.schemes.projective.projective_point.SchemeMorphism_point_projective_ring
    A point on an elliptic curve.
```

```
class sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_field(curve,
                                                                        v,
                                                                        check=True)
    Bases: sage.schemes.projective.projective_point.SchemeMorphism_point_abelian_variety_fie
    A point on an elliptic curve over a field. The point has coordinates in the base field.
```

#### EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E([0, 0])
(0 : 0 : 1)
sage: E(0, 0)                # brackets are optional
(0 : 0 : 1)
sage: E([GF(5)(0), 0])      # entries are coerced
(0 : 0 : 1)

sage: E(0.000, 0)
(0 : 0 : 1)
```

```
sage: E(1,0,0)
Traceback (most recent call last):
...
TypeError: Coordinates [1, 0, 0] do not define a point on
Elliptic Curve defined by  $y^2 + y = x^3 - x$  over Rational Field
```

```
sage: E = EllipticCurve([0,0,1,-1,0])
sage: S = E(QQ); S
Abelian group of points on Elliptic Curve defined by  $y^2 + y = x^3 - x$  over
↪Rational Field

sage: K.<i>=NumberField(x^2+1)
sage: E=EllipticCurve(K,[0,1,0,-160,308])
sage: P=E(26,-120)
sage: Q=E(2+12*i,-36+48*i)
sage: P.order() == Q.order() == 4 # long time (3s)
True
sage: 2*P==2*Q
False
```

```
sage: K.<t>=FractionField(PolynomialRing(QQ,'t'))
sage: E=EllipticCurve([0,0,0,0,t^2])
sage: P=E(0,t)
sage: P,2*P,3*P
((0 : t : 1), (0 : -t : 1), (0 : 1 : 0))
```

**additive\_order()**

Return the order of this point on the elliptic curve.

If the point is zero, returns 1, otherwise raise a `NotImplementedError`.

For curves over number fields and finite fields, see below.

---

**Note:** `additive_order()` is a synonym for `order()`

---

**EXAMPLES:**

```
sage: K.<t>=FractionField(PolynomialRing(QQ,'t'))
sage: E=EllipticCurve([0,0,0,-t^2,0])
sage: P=E(t,0)
sage: P.order()
Traceback (most recent call last):
...
NotImplementedError: Computation of order of a point not implemented over
↪general fields.
sage: E(0).additive_order()
1
sage: E(0).order() == 1
True
```

**ate\_pairing(Q, n, k, t, q=None)**

Return ate pairing of  $n$ -torsion points  $P = self$  and  $Q$ .

Also known as the  $n$ -th modified ate pairing.  $P$  is  $GF(q)$ -rational, and  $Q$  must be an element of  $Ker(\pi - p)$ , where  $\pi$  is the  $q$ -frobenius map (and hence  $Q$  is  $GF(q^k)$ -rational).

INPUT:

- $P = \text{self}$  – a point of order  $n$ , in  $\ker(\pi - 1)$ , where  $\pi$  is the  $q$ -Frobenius map (e.g.,  $P$  is  $q$ -rational).
- $Q$  – a point of order  $n$  in  $\ker(\pi - q)$
- $n$  – the order of  $P$  and  $Q$ .
- $k$  – the embedding degree.
- $t$  – the trace of Frobenius of the curve over  $GF(q)$ .
- $q$  – (default:None) the size of base field (the “big” field is  $GF(q^k)$ ).  $q$  needs to be set only if its value cannot be deduced.

OUTPUT:

FiniteFieldElement in  $GF(q^k)$  – the ate pairing of  $P$  and  $Q$ .

EXAMPLES:

An example with embedding degree 6:

```
sage: p = 7549; A = 0; B = 1; n = 157; k = 6; t = 14
sage: F = GF(p); E = EllipticCurve(F, [A, B])
sage: R.<x> = F[]; K.<a> = GF(p^k, modulus=x^k+2)
sage: EK = E.base_extend(K)
sage: P = EK(3050, 5371); Q = EK(6908*a^4, 3231*a^3)
sage: P.ate_pairing(Q, n, k, t)
6708*a^5 + 4230*a^4 + 4350*a^3 + 2064*a^2 + 4022*a + 6733
sage: s = Integer(randrange(1, n))
sage: (s*P).ate_pairing(Q, n, k, t) == P.ate_pairing(s*Q, n, k, t)
True
sage: P.ate_pairing(s*Q, n, k, t) == P.ate_pairing(Q, n, k, t)^s
True
```

Another example with embedding degree 7 and positive trace:

```
sage: p = 2213; A = 1; B = 49; n = 1093; k = 7; t = 28
sage: F = GF(p); E = EllipticCurve(F, [A, B])
sage: R.<x> = F[]; K.<a> = GF(p^k, modulus=x^k+2)
sage: EK = E.base_extend(K)
sage: P = EK(1583, 1734)
sage: Qx = 1729*a^6+1767*a^5+245*a^4+980*a^3+1592*a^2+1883*a+722
sage: Qy = 1299*a^6+1877*a^5+1030*a^4+1513*a^3+1457*a^2+309*a+1636
sage: Q = EK(Qx, Qy)
sage: P.ate_pairing(Q, n, k, t)
1665*a^6 + 1538*a^5 + 1979*a^4 + 239*a^3 + 2134*a^2 + 2151*a + 654
sage: s = Integer(randrange(1, n))
sage: (s*P).ate_pairing(Q, n, k, t) == P.ate_pairing(s*Q, n, k, t)
True
sage: P.ate_pairing(s*Q, n, k, t) == P.ate_pairing(Q, n, k, t)^s
True
```

Another example with embedding degree 7 and negative trace:

```
sage: p = 2017; A = 1; B = 30; n = 29; k = 7; t = -70
sage: F = GF(p); E = EllipticCurve(F, [A, B])
sage: R.<x> = F[]; K.<a> = GF(p^k, modulus=x^k+2)
sage: EK = E.base_extend(K)
sage: P = EK(369, 716)
sage: Qx = 1226*a^6+1778*a^5+660*a^4+1791*a^3+1750*a^2+867*a+770
sage: Qy = 1764*a^6+198*a^5+1206*a^4+406*a^3+1200*a^2+273*a+1712
sage: Q = EK(Qx, Qy)
```

```

sage: P.ate_pairing(Q, n, k, t)
1794*a^6 + 1161*a^5 + 576*a^4 + 488*a^3 + 1950*a^2 + 1905*a + 1315
sage: s = Integer(randrange(1, n))
sage: (s*P).ate_pairing(Q, n, k, t) == P.ate_pairing(s*Q, n, k, t)
True
sage: P.ate_pairing(s*Q, n, k, t) == P.ate_pairing(Q, n, k, t)^s
True

```

Using the same data, we show that the ate pairing is a power of the Tate pairing (see [\[HSV\]](#) end of section 3.1):

```

sage: c = (k*p^(k-1)).mod(n); T = t - 1
sage: N = gcd(T^k - 1, p^k - 1)
sage: s = Integer(N/n)
sage: L = Integer((T^k - 1)/N)
sage: M = (L*s*c.inverse_mod(n)).mod(n)
sage: P.ate_pairing(Q, n, k, t) == Q.tate_pairing(P, n, k)^M
True

```

An example where we have to pass the base field size (and we again have agreement with the Tate pairing). Note that though  $Px$  is not  $F$ -rational, (it is the homomorphic image of an  $F$ -rational point) it is nonetheless in  $\ker(\pi - 1)$ , and so is a legitimate input:

```

sage: q = 2^5; F.<a>=GF(q)
sage: n = 41; k = 4; t = -8
sage: E=EllipticCurve(F, [0,0,1,1,1])
sage: P = E(a^4 + 1, a^3)
sage: Fx.<b>=GF(q^k)
sage: Ex=EllipticCurve(Fx, [0,0,1,1,1])
sage: phi=Hom(F, Fx) (F.gen().minpoly().roots(Fx)[0][0])
sage: Px=Ex(phi(P.xy()[0]), phi(P.xy()[1]))
sage: Qx = Ex(b^19+b^18+b^16+b^12+b^10+b^9+b^8+b^5+b^3+1, b^18+b^13+b^10+b^
↪ 8+b^5+b^4+b^3+b)
sage: Qx = Ex(Qx[0]^q, Qx[1]^q) - Qx # ensure Qx is in ker(pi - q)
sage: Px.ate_pairing(Qx, n, k, t)
Traceback (most recent call last):
...
ValueError: Unexpected field degree: set keyword argument q equal to the size_
↪ of the base field (big field is GF(q^4)).
sage: Px.ate_pairing(Qx, n, k, t, q)
b^19 + b^18 + b^17 + b^16 + b^15 + b^14 + b^13 + b^12 + b^11 + b^9 + b^8 + b^
↪ 5 + b^4 + b^2 + b + 1
sage: s = Integer(randrange(1, n))
sage: (s*Px).ate_pairing(Qx, n, k, t, q) == Px.ate_pairing(s*Qx, n, k, t, q)
True
sage: Px.ate_pairing(s*Qx, n, k, t, q) == Px.ate_pairing(Qx, n, k, t, q)^s
True
sage: c = (k*q^(k-1)).mod(n); T = t - 1
sage: N = gcd(T^k - 1, q^k - 1)
sage: s = Integer(N/n)
sage: L = Integer((T^k - 1)/N)
sage: M = (L*s*c.inverse_mod(n)).mod(n)
sage: Px.ate_pairing(Qx, n, k, t, q) == Qx.tate_pairing(Px, n, k, q)^M
True

```

It is an error if  $Q$  is not in the kernel of  $\pi - p$ , where  $\pi$  is the Frobenius automorphism:

```

sage: p = 29; A = 1; B = 0; n = 5; k = 2; t = 10
sage: F = GF(p); R.<x> = F[]
sage: E = EllipticCurve(F, [A, B]);
sage: K.<a> = GF(p^k, modulus=x^k+2); EK = E.base_extend(K)
sage: P = EK(13, 8); Q = EK(13, 21)
sage: P.ate_pairing(Q, n, k, t)
Traceback (most recent call last):
...
ValueError: Point (13 : 21 : 1) not in Ker(pi - q)

```

It is also an error if  $P$  is not in the kernel of  $\pi - 1$ :

```

sage: p = 29; A = 1; B = 0; n = 5; k = 2; t = 10
sage: F = GF(p); R.<x> = F[]
sage: E = EllipticCurve(F, [A, B]);
sage: K.<a> = GF(p^k, modulus=x^k+2); EK = E.base_extend(K)
sage: P = EK(14, 10*a); Q = EK(13, 21)
sage: P.ate_pairing(Q, n, k, t)
Traceback (most recent call last):
...
ValueError: This point (14 : 10*a : 1) is not in Ker(pi - 1)

```

#### NOTES:

First defined in the paper of [HSV], the ate pairing can be computationally effective in those cases when the trace of the curve over the base field is significantly smaller than the expected value. This implementation is simply Miller's algorithm followed by a naive exponentiation, and makes no claims towards efficiency.

#### REFERENCES:

#### AUTHORS:

- Mariah Lenox (2011-03-08)

#### **curve()**

Return the curve that this point is on.

#### EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: P = E([-1, 1])
sage: P.curve()
Elliptic Curve defined by y^2 + y = x^3 + x^2 - 2*x over Rational Field

```

#### **division\_points**( $m$ , *poly\_only*=False)

Return a list of all points  $Q$  such that  $mQ = P$  where  $P = \text{self}$ .

Only points on the elliptic curve containing self and defined over the base field are included.

#### INPUT:

- $m$  – a positive integer
- *poly\_only* – bool (default: False); if True return polynomial whose roots give all possible  $x$ -coordinates of  $m$ -th roots of self.

#### OUTPUT:

(list) – a (possibly empty) list of solutions  $Q$  to  $mQ = P$ , where  $P = \text{self}$ .

#### EXAMPLES:

We find the five 5-torsion points on an elliptic curve:

```

sage: E = EllipticCurve('11a'); E
Elliptic Curve defined by  $y^2 + y = x^3 - x^2 - 10x - 20$  over Rational Field
sage: P = E(0); P
(0 : 1 : 0)
sage: P.division_points(5)
[(0 : 1 : 0), (5 : -6 : 1), (5 : 5 : 1), (16 : -61 : 1), (16 : 60 : 1)]

```

Note above that 0 is included since  $[5]*0 = 0$ .

We create a curve of rank 1 with no torsion and do a consistency check:

```

sage: E = EllipticCurve('11a').quadratic_twist(-7)
sage: Q = E([44, -270])
sage: (4*Q).division_points(4)
[(44 : -270 : 1)]

```

We create a curve over a non-prime finite field with group of order 18:

```

sage: k.<a> = GF(25)
sage: E = EllipticCurve(k, [1, 2+a, 3, 4*a, 2])
sage: P = E([3, 3*a+4])
sage: factor(E.order())
2 * 3^2
sage: P.order()
9

```

We find the 1-division points as a consistency check – there is just one, of course:

```

sage: P.division_points(1)
[(3 : 3*a + 4 : 1)]

```

The point  $P$  has order coprime to 2 but divisible by 3, so:

```

sage: P.division_points(2)
[(2*a + 1 : 3*a + 4 : 1), (3*a + 1 : a : 1)]

```

We check that each of the 2-division points works as claimed:

```

sage: [2*Q for Q in P.division_points(2)]
[(3 : 3*a + 4 : 1), (3 : 3*a + 4 : 1)]

```

Some other checks:

```

sage: P.division_points(3)
[]
sage: P.division_points(4)
[(0 : 3*a + 2 : 1), (1 : 0 : 1)]
sage: P.division_points(5)
[(1 : 1 : 1)]

```

An example over a number field (see [trac ticket #3383](#)):

```

sage: E = EllipticCurve('19a1')
sage: K.<t> = NumberField(x^9-3*x^8-4*x^7+16*x^6-3*x^5-21*x^4+5*x^3+7*x^2-
↪ 7*x+1)
sage: EK = E.base_extend(K)
sage: E(0).division_points(3)
[(0 : 1 : 0), (5 : -10 : 1), (5 : 9 : 1)]

```

```

sage: EK(0).division_points(3)
[(0 : 1 : 0), (5 : 9 : 1), (5 : -10 : 1)]
sage: E(0).division_points(9)
[(0 : 1 : 0), (5 : -10 : 1), (5 : 9 : 1)]
sage: EK(0).division_points(9)
[(0 : 1 : 0), (5 : 9 : 1), (5 : -10 : 1), (-150/121*t^8 + 414/121*t^7 + 1481/
↪242*t^6 - 2382/121*t^5 - 103/242*t^4 + 629/22*t^3 - 367/242*t^2 - 1307/
↪121*t + 625/121 : 35/484*t^8 - 133/242*t^7 + 445/242*t^6 - 799/242*t^5 +
↪373/484*t^4 + 113/22*t^3 - 2355/484*t^2 - 753/242*t + 1165/484 : 1), (-150/
↪121*t^8 + 414/121*t^7 + 1481/242*t^6 - 2382/121*t^5 - 103/242*t^4 + 629/
↪22*t^3 - 367/242*t^2 - 1307/121*t + 625/121 : -35/484*t^8 + 133/242*t^7 -
↪445/242*t^6 + 799/242*t^5 - 373/484*t^4 - 113/22*t^3 + 2355/484*t^2 + 753/
↪242*t - 1649/484 : 1), (-1383/484*t^8 + 970/121*t^7 + 3159/242*t^6 - 5211/
↪121*t^5 + 37/484*t^4 + 654/11*t^3 - 909/484*t^2 - 4831/242*t + 6791/484 :
↪927/121*t^8 - 5209/242*t^7 - 8187/242*t^6 + 27975/242*t^5 - 1147/242*t^4 -
↪1729/11*t^3 + 1566/121*t^2 + 12873/242*t - 10871/242 : 1), (-1383/484*t^8 +
↪970/121*t^7 + 3159/242*t^6 - 5211/121*t^5 + 37/484*t^4 + 654/11*t^3 - 909/
↪484*t^2 - 4831/242*t + 6791/484 : -927/121*t^8 + 5209/242*t^7 + 8187/242*t^
↪6 - 27975/242*t^5 + 1147/242*t^4 + 1729/11*t^3 - 1566/121*t^2 - 12873/242*t
↪+ 10629/242 : 1), (-4793/484*t^8 + 6791/242*t^7 + 10727/242*t^6 - 18301/
↪121*t^5 + 2347/484*t^4 + 2293/11*t^3 - 7311/484*t^2 - 17239/242*t + 26767/
↪484 : 30847/484*t^8 - 21789/121*t^7 - 34605/121*t^6 + 117164/121*t^5 -
↪10633/484*t^4 - 29437/22*t^3 + 39725/484*t^2 + 55428/121*t - 176909/484 :
↪1), (-4793/484*t^8 + 6791/242*t^7 + 10727/242*t^6 - 18301/121*t^5 + 2347/
↪484*t^4 + 2293/11*t^3 - 7311/484*t^2 - 17239/242*t + 26767/484 : -30847/
↪484*t^8 + 21789/121*t^7 + 34605/121*t^6 - 117164/121*t^5 + 10633/484*t^4 +
↪29437/22*t^3 - 39725/484*t^2 - 55428/121*t + 176425/484 : 1)]

```

**has\_finite\_order()**

Return True if this point has finite additive order as an element of the group of points on this curve.

For fields other than number fields and finite fields, this is NotImplemented unless self.is\_zero().

EXAMPLES:

```

sage: K.<t>=FractionField(PolynomialRing(QQ, 't'))
sage: E=EllipticCurve([0,0,0,-t^2,0])
sage: P = E(0)
sage: P.has_finite_order()
True
sage: P=E(t,0)
sage: P.has_finite_order()
Traceback (most recent call last):
...
NotImplementedError: Computation of order of a point not implemented over
↪general fields.
sage: (2*P).is_zero()
True

```

**has\_infinite\_order()**

Return True if this point has infinite additive order as an element of the group of points on this curve.

For fields other than number fields and finite fields, this is NotImplemented unless self.is\_zero().

EXAMPLES:

```

sage: K.<t>=FractionField(PolynomialRing(QQ, 't'))
sage: E=EllipticCurve([0,0,0,-t^2,0])
sage: P = E(0)

```



```

sage: P.has_infinite_order()
False
sage: P=E(t,0)
sage: P.has_infinite_order()
Traceback (most recent call last):
...
NotImplementedError: Computation of order of a point not implemented over_
↳ general fields.
sage: (2*P).is_zero()
True

```

**is\_divisible\_by(*m*)**

Return True if there exists a point  $Q$  defined over the same field as self such that  $mQ == \text{self}$ .

INPUT:

- $m$  – a positive integer.

OUTPUT:

(bool) – True if there is a solution, else False.

**Warning:** This function usually triggers the computation of the  $m$ -th division polynomial of the associated elliptic curve, which will be expensive if  $m$  is large, though it will be cached for subsequent calls with the same  $m$ .

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: Q = 5*E(0,0); Q
(-2739/1444 : -77033/54872 : 1)
sage: Q.is_divisible_by(4)
False
sage: Q.is_divisible_by(5)
True

```

A finite field example:

```

sage: E = EllipticCurve(GF(101), [23, 34])
sage: E.cardinality().factor()
2 * 53
sage: Set([T.order() for T in E.points()])
{1, 106, 2, 53}
sage: len([T for T in E.points() if T.is_divisible_by(2)])
53
sage: len([T for T in E.points() if T.is_divisible_by(3)])
106

```

**is\_finite\_order()**

Return True if this point has finite additive order as an element of the group of points on this curve.

For fields other than number fields and finite fields, this is `NotImplemented` unless `self.is_zero()`.

EXAMPLES:

```

sage: K.<t>=FractionField(PolynomialRing(QQ, 't'))
sage: E=EllipticCurve([0,0,0,-t^2,0])
sage: P = E(0)

```

```

sage: P.has_finite_order()
True
sage: P=E(t,0)
sage: P.has_finite_order()
Traceback (most recent call last):
...
NotImplementedError: Computation of order of a point not implemented over_
↳general fields.
sage: (2*P).is_zero()
True

```

**order()**

Return the order of this point on the elliptic curve.

If the point is zero, returns 1, otherwise raise a `NotImplementedError`.

For curves over number fields and finite fields, see below.

---

**Note:** `additive_order()` is a synonym for `order()`

---

**EXAMPLES:**

```

sage: K.<t>=FractionField(PolynomialRing(QQ,'t'))
sage: E=EllipticCurve([0,0,0,-t^2,0])
sage: P=E(t,0)
sage: P.order()
Traceback (most recent call last):
...
NotImplementedError: Computation of order of a point not implemented over_
↳general fields.
sage: E(0).additive_order()
1
sage: E(0).order() == 1
True

```

**plot (\*\*args)**

Plot this point on an elliptic curve.

INPUT:

- `**args` – all arguments get passed directly onto the point plotting function.

**EXAMPLES:**

```

sage: E = EllipticCurve('389a')
sage: P = E([-1,1])
sage: P.plot(pointsize=30, rgbcolor=(1,0,0))
Graphics object consisting of 1 graphics primitive

```

**scheme()**

Return the scheme of this point, i.e., the curve it is on. This is synonymous with `curve()` which is perhaps more intuitive.

**EXAMPLES:**

```

sage: E=EllipticCurve(QQ,[1,1])
sage: P=E(0,1)
sage: P.scheme()

```

```

Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Rational Field
sage: P.scheme() == P.curve()
True
sage: K.<a>=NumberField(x^2-3,'a')
sage: P=E.base_extend(K) (1,a)
sage: P.scheme()
Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Number Field in a with_
↳defining polynomial  $x^2 - 3$ 

```

**set\_order (value)**

Set the value of self.\_order to value.

Use this when you know a priori the order of this point to avoid a potentially expensive order calculation.

INPUT:

- value - positive Integer

OUTPUT:

None

EXAMPLES:

This example illustrates basic usage.

```

sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: G = E(5, 0)
sage: G.set_order(2)
sage: 2*G
(0 : 1 : 0)

```

We now give a more interesting case, the NIST-P521 curve. Its order is too big to calculate with SAGE, and takes a long time using other packages, so it is very useful here.

```

sage: p = 2^521 - 1
sage: prev_proof_state = proof.arithmetic()
sage: proof.arithmetic(False) # turn off primality checking
sage: F = GF(p)
sage: A = p - 3
sage: B =_
↳109384903807373427451111239076680556993620759895168374899458639449595311615073501601370873
sage: q =_
↳686479766013060971498190079908139321726943530014330540939446345918554318339765539424505774
sage: E = EllipticCurve([F(A), F(B)])
sage: G = E.random_point()
sage: G.set_order(q)
sage: G.order() * G # This takes practically no time.
(0 : 1 : 0)
sage: proof.arithmetic(prev_proof_state) # restore state

```

It is an error to pass a *value* equal to 0:

```

sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: G = E.random_point()
sage: G.set_order(0)
Traceback (most recent call last):
...
ValueError: Value 0 illegal for point order
sage: G.set_order(1000)

```

```
Traceback (most recent call last):
...
ValueError: Value 1000 illegal: outside max Hasse bound
```

It is also very likely an error to pass a value which is not the actual order of this point. How unlikely is determined by the factorization of the actual order, and the actual group structure:

```
sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: G = E(5, 0) # G has order 2
sage: G.set_order(11)
Traceback (most recent call last):
...
ValueError: Value 11 illegal: 11 * (5 : 0 : 1) is not the identity
```

However, `set_order` can be fooled, though it's not likely in “real cases of interest”. For instance, the order can be set to a multiple the actual order:

```
sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: G = E(5, 0) # G has order 2
sage: G.set_order(8)
sage: G.order()
8
```

#### NOTES:

The implementation is based of the fact that orders of elliptic curve points are cached in the (pseudo-private) `_order` slot.

#### AUTHORS:

- Mariah Lenox (2011-02-16)

#### **tate\_pairing** ( $Q, n, k, q=None$ )

Return Tate pairing of  $n$ -torsion point  $P = self$  and point  $Q$ .

The value returned is  $f_{n,P}(Q)^e$  where  $f_{n,P}$  is a function with divisor  $n[P] - n[O]$ . This is also known as the “modified Tate pairing”. It is a well-defined bilinear map.

#### INPUT:

- $P=$ `self` – Elliptic curve point having order  $n$
- $Q$  – Elliptic curve point on same curve as  $P$  (can be any order)
- $n$  – positive integer: order of  $P$
- $k$  – positive integer: embedding degree
- $q$  – positive integer: size of base field (the “big” field is  $GF(q^k)$ .  $q$  needs to be set only if its value cannot be deduced.)

#### OUTPUT:

An  $n$ ’th root of unity in the base field `self.curve().base_field()`

#### EXAMPLES:

A simple example, pairing a point with itself, and pairing a point with another rational point:

```
sage: p = 103; A = 1; B = 18; E = EllipticCurve(GF(p), [A, B])
sage: P = E(33, 91); n = P.order(); n
19
sage: k = GF(n)(p).multiplicative_order(); k
```

```

6
sage: P.tate_pairing(P, n, k)
1
sage: Q = E(87, 51)
sage: P.tate_pairing(Q, n, k)
1
sage: set_random_seed(35)
sage: P.tate_pairing(P,n,k)
1

```

We now let  $Q$  be a point on the same curve as above, but defined over the pairing extension field, and we also demonstrate the bilinearity of the pairing:

```

sage: K.<a> = GF(p^k)
sage: EK = E.base_extend(K); P = EK(P)
sage: Qx = 69*a^5 + 96*a^4 + 22*a^3 + 86*a^2 + 6*a + 35
sage: Qy = 34*a^5 + 24*a^4 + 16*a^3 + 41*a^2 + 4*a + 40
sage: Q = EK(Qx, Qy);
sage: # multiply by cofactor so Q has order n:
sage: h = 551269674; Q = h*Q
sage: P = EK(P); P.tate_pairing(Q, n, k)
24*a^5 + 34*a^4 + 3*a^3 + 69*a^2 + 86*a + 45
sage: s = Integer(randrange(1,n))
sage: ans1 = (s*P).tate_pairing(Q, n, k)
sage: ans2 = P.tate_pairing(s*Q, n, k)
sage: ans3 = P.tate_pairing(Q, n, k)^s
sage: ans1 == ans2 == ans3
True
sage: (ans1 != 1) and (ans1^n == 1)
True

```

Here is an example of using the Tate pairing to compute the Weil pairing (using the same data as above):

```

sage: e = Integer((p^k-1)/n); e
62844857712
sage: P.weil_pairing(Q, n)^e
94*a^5 + 99*a^4 + 29*a^3 + 45*a^2 + 57*a + 34
sage: P.tate_pairing(Q, n, k) == P._miller_(Q, n)^e
True
sage: Q.tate_pairing(P, n, k) == Q._miller_(P, n)^e
True
sage: P.tate_pairing(Q, n, k)/Q.tate_pairing(P, n, k)
94*a^5 + 99*a^4 + 29*a^3 + 45*a^2 + 57*a + 34

```

An example where we have to pass the base field size (and we again have agreement with the Weil pairing):

```

sage: F.<a>=GF(2^5)
sage: E=EllipticCurve(F,[0,0,1,1,1])
sage: P = E(a^4 + 1, a^3)
sage: Fx.<b>=GF(2^(4*5))
sage: Ex=EllipticCurve(Fx,[0,0,1,1,1])
sage: phi=Hom(F,Fx)(F.gen().minpoly().roots(Fx)[0][0])
sage: Px=Ex(phi(P.xy()[0]),phi(P.xy()[1]))
sage: Qx = Ex(b^19+b^18+b^16+b^12+b^10+b^9+b^8+b^5+b^3+1, b^18+b^13+b^10+b^8
↪ +b^5+b^4+b^3+b)
sage: Px.tate_pairing(Qx, n=41, k=4)
Traceback (most recent call last):
...

```

```

ValueError: Unexpected field degree: set keyword argument q equal to the size_
↳ of the base field (big field is GF(q^4)).
sage: num = Px.tate_pairing(Qx, n=41, k=4, q=32); num
b^19 + b^14 + b^13 + b^12 + b^6 + b^4 + b^3
sage: den = Px.tate_pairing(Px, n=41, k=4, q=32); den
b^19 + b^17 + b^16 + b^15 + b^14 + b^10 + b^6 + b^2 + 1
sage: e = Integer((32^4-1)/41); e
25575
sage: Px.weil_pairing(Qx, 41)^e == num/den
True

```

## NOTES:

This function uses Miller's algorithm, followed by a naive exponentiation. It does not do anything fancy. In the case that there is an issue with  $Q$  being on one of the lines generated in the  $r * P$  calculation,  $Q$  is offset by a random point  $R$  and  $P.tate\_pairing(Q+R,n,k)/P.tate\_pairing(R,n,k)$  is returned.

## AUTHORS:

- Mariah Lenox (2011-03-07)

**weil\_pairing**( $Q, n$ )

Compute the Weil pairing of self and  $Q$  using Miller's algorithm.

## INPUT:

- $Q$  – a point on `self.curve()`.
- $n$  – an integer  $n$  such that  $nP = nQ = (0 : 1 : 0)$  where  $P = \text{self}$ .

## OUTPUT:

An  $n$ 'th root of unity in the base field `self.curve().base_field()`

## EXAMPLES:

```

sage: F.<a>=GF(2^5)
sage: E=EllipticCurve(F,[0,0,1,1,1])
sage: P = E(a^4 + 1, a^3)
sage: Fx.<b>=GF(2^(4*5))
sage: Ex=EllipticCurve(Fx,[0,0,1,1,1])
sage: phi=Hom(F,Fx)(F.gen().minpoly().roots(Fx)[0][0])
sage: Px=Ex(phi(P.xy()[0]),phi(P.xy()[1]))
sage: O = Ex(0)
sage: Qx = Ex(b^19 + b^18 + b^16 + b^12 + b^10 + b^9 + b^8 + b^5 + b^3 + 1, b^
↳ 18 + b^13 + b^10 + b^8 + b^5 + b^4 + b^3 + b)
sage: Px.weil_pairing(Qx,41) == b^19 + b^15 + b^9 + b^8 + b^6 + b^4 + b^3 + b^
↳ 2 + 1
True
sage: Px.weil_pairing(17*Px,41) == Fx(1)
True
sage: Px.weil_pairing(O,41) == Fx(1)
True

```

An error is raised if either point is not  $n$ -torsion:

```

sage: Px.weil_pairing(O,40)
Traceback (most recent call last):
...
ValueError: points must both be n-torsion

```

A larger example (see [trac ticket #4964](#)):

```
sage: P,Q = EllipticCurve(GF(19^4,'a'),[-1,0]).gens()
sage: P.order(), Q.order()
(360, 360)
sage: z = P.weil_pairing(Q,360)
sage: z.multiplicative_order()
360
```

An example over a number field:

```
sage: P,Q = EllipticCurve('11a1').change_ring(CyclotomicField(5)).torsion_
↪subgroup().gens() # long time (10s)
sage: P,Q = (P.element(), Q.element()) # long time
sage: (P.order(),Q.order()) # long time
(5, 5)
sage: P.weil_pairing(Q,5) # long time
zeta5^2
sage: Q.weil_pairing(P,5) # long time
zeta5^3
```

ALGORITHM:

Implemented using Proposition 8 in [\[Mil04\]](#). The value 1 is returned for linearly dependent input points. This condition is caught via a `DivisionByZeroError`, since the use of a discrete logarithm test for linear dependence, is much too slow for large  $n$ .

REFERENCES:

AUTHOR:

- David Hansen (2009-01-25)

**xy()**

Return the  $x$  and  $y$  coordinates of this point, as a 2-tuple. If this is the point at infinity a `ZeroDivisionError` is raised.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: P = E([-1,1])
sage: P.xy()
(-1, 1)
sage: Q = E(0); Q
(0 : 1 : 0)
sage: Q.xy()
Traceback (most recent call last):
...
ZeroDivisionError: rational division by zero
```

```
class sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field(curve,
                                                                              v,
                                                                              check=True)
```

Bases: `sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_field`

Class for elliptic curve points over finite fields.

**additive\_order()**

Return the order of this point on the elliptic curve.

ALGORITHM:

Use generic functions from `sage.groups.generic`. If the group order is known, use `order_from_multiple()`, otherwise use `order_from_bounds()` with the Hasse bounds for the base field. In the latter case, we might find that we have a generator for the group, in which case it is cached.

We do not cause the group order to be calculated when not known, since this function is used in determining the group order via computation of several random points and their orders. The exceptions to this are (1) when the base field is a prime field and efficient SEA-based methods are available for the cardinality, and (2) when finding the group order is possible quickly, currently only implemented for curves with  $j = 0$  or  $j = 1728$  (see [trac ticket #15567](#)).

---

**Note:** `additive_order()` is a synonym for `order()`

---

AUTHOR:

- John Cremona, 2008-02-10, adapted 2008-04-05 to use generic functions.

EXAMPLES:

```
sage: k.<a> = GF(5^5)
sage: E = EllipticCurve(k, [2,4]); E
Elliptic Curve defined by y^2 = x^3 + 2*x + 4 over Finite Field in a of size
↳5^5
sage: P = E(3*a^4 + 3*a , 2*a + 1 )
sage: P.order()
3227
sage: Q = E(0,2)
sage: Q.order()
7
sage: Q.additive_order()
7
```

In the next example, the cardinality of E will be computed (using SEA) and cached:

```
sage: p=next_prime(2^150)
sage: E=EllipticCurve(GF(p), [1,1])
sage: P=E(831623307675610677632782670796608848711856078,
↳42295786042873366706573292533588638217232964)
sage: P.order()
1427247692705959881058262545272474300628281448
sage: P.order()==E.cardinality()
True
```

In the next example, the cardinality of E will be computed and cached since  $j(E) = 0$ :

```
sage: p = 33554501
sage: F.<u> = GF(p^2)
sage: E = EllipticCurve(F, [0,1])
sage: E.j_invariant()
0
sage: P = E.random_point()
sage: P = E.random_point()
sage: P.order() # random
16777251
sage: E._order # as cached
1125904604468004
```

Similarly when  $j(E) = 1728$ :



```

sage: p = 33554473
sage: F.<u> = GF(p^2)
sage: E = EllipticCurve(F, [1, 0])
sage: E.j_invariant()
1728
sage: P = E.random_point()
sage: P.order() # random
46912611635760
sage: E._order # as cached
1125902679258240

```

**discrete\_log**( $Q$ , *ord=None*)

Returns discrete log of  $Q$  with respect to  $P$  =self.

INPUT:

- $Q$  (point) – another point on the same curve as self.
- *ord* (integer or None (default)) – the order of self.

OUTPUT:

(integer) – The discrete log of  $Q$  with respect to  $P$ , which is an integer  $m$  with  $0 \leq m < o(P)$  such that  $mP = Q$ , if one exists. A `ValueError` is raised if there is no solution.

---

**Note:** The order of self is computed if not supplied.

---

AUTHOR:

- John Cremona. Adapted to use generic functions 2008-04-05.

EXAMPLES:

```

sage: F = GF(3^6, 'a')
sage: a = F.gen()
sage: E = EllipticCurve([0, 1, 1, a, a])
sage: E.cardinality()
762
sage: A = E.abelian_group()
sage: P = A.gen(0).element()
sage: Q = 400*P
sage: P.discrete_log(Q)
400

```

**has\_finite\_order**()

Return True if this point has finite additive order as an element of the group of points on this curve.

Since the base field is finite, the answer will always be `True`.

EXAMPLES:

```

sage: E = EllipticCurve(GF(7), [1, 3])
sage: P = E.points()[3]
sage: P.has_finite_order()
True

```

**order**()

Return the order of this point on the elliptic curve.

ALGORITHM:

Use generic functions from `sage.groups.generic`. If the group order is known, use `order_from_multiple()`, otherwise use `order_from_bounds()` with the Hasse bounds for the base field. In the latter case, we might find that we have a generator for the group, in which case it is cached.

We do not cause the group order to be calculated when not known, since this function is used in determining the group order via computation of several random points and their orders. The exceptions to this are (1) when the base field is a prime field and efficient SEA-based methods are available for the cardinality, and (2) when finding the group order is possible quickly, currently only implemented for curves with  $j = 0$  or  $j = 1728$  (see [trac ticket #15567](#)).

---

**Note:** `additive_order()` is a synonym for `order()`

---

AUTHOR:

- John Cremona, 2008-02-10, adapted 2008-04-05 to use generic functions.

EXAMPLES:

```
sage: k.<a> = GF(5^5)
sage: E = EllipticCurve(k, [2,4]); E
Elliptic Curve defined by y^2 = x^3 + 2*x + 4 over Finite Field in a of size
↳5^5
sage: P = E(3*a^4 + 3*a , 2*a + 1 )
sage: P.order()
3227
sage: Q = E(0,2)
sage: Q.order()
7
sage: Q.additive_order()
7
```

In the next example, the cardinality of E will be computed (using SEA) and cached:

```
sage: p=next_prime(2^150)
sage: E=EllipticCurve(GF(p), [1,1])
sage: P=E(831623307675610677632782670796608848711856078,
↳42295786042873366706573292533588638217232964)
sage: P.order()
1427247692705959881058262545272474300628281448
sage: P.order()==E.cardinality()
True
```

In the next example, the cardinality of E will be computed and cached since  $j(E) = 0$ :

```
sage: p = 33554501
sage: F.<u> = GF(p^2)
sage: E = EllipticCurve(F, [0,1])
sage: E.j_invariant()
0
sage: P = E.random_point()
sage: P = E.random_point()
sage: P.order() # random
16777251
sage: E._order # as cached
1125904604468004
```

Similarly when  $j(E) = 1728$ :

```

sage: p = 33554473
sage: F.<u> = GF(p^2)
sage: E = EllipticCurve(F, [1, 0])
sage: E.j_invariant()
1728
sage: P = E.random_point()
sage: P.order() # random
46912611635760
sage: E._order # as cached
1125902679258240

```

**class** sage.schemes.elliptic\_curves.ell\_point.**EllipticCurvePoint\_number\_field**(*curve*,  
*v*,  
*check=True*

Bases: *sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field*

A point on an elliptic curve over a number field.

Most of the functionality is derived from the parent class `EllipticCurvePoint_field`. In addition we have support for orders, heights, reduction modulo primes, and elliptic logarithms.

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: E([0, 0])
(0 : 0 : 1)
sage: E(0, 0) # brackets are optional
(0 : 0 : 1)
sage: E([GF(5)(0), 0]) # entries are coerced
(0 : 0 : 1)

sage: E(0.000, 0)
(0 : 0 : 1)

sage: E(1, 0, 0)
Traceback (most recent call last):
...
TypeError: Coordinates [1, 0, 0] do not define a point on
Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field

```

```

sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: S = E(QQ); S
Abelian group of points on Elliptic Curve defined by y^2 + y = x^3 - x over
↪Rational Field

```

**additive\_order()**

Return the order of this point on the elliptic curve.

If the point has infinite order, returns `+Infinity`. For curves defined over  $\mathbf{Q}$ , we call PARI; over other number fields we implement the function here.

---

**Note:** *additive\_order()* is a synonym for *order()*

---

EXAMPLES:

```

sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: P = E([0, 0]); P

```

```
(0 : 0 : 1)
sage: P.order()
+Infinity
```

```
sage: E = EllipticCurve([0,1])
sage: P = E([-1,0])
sage: P.order()
2
sage: P.additive_order()
2
```

**archimedean\_local\_height** ( $v=None$ ,  $prec=None$ ,  $weighted=False$ )

Compute the local height of self at the archimedean place  $v$ .

INPUT:

- `self` – a point on an elliptic curve over a number field  $K$ .
- $v$  – a real or complex embedding of  $K$ , or `None` (default). If  $v$  is a real or complex embedding, return the local height of self at  $v$ . If  $v$  is `None`, return the total archimedean contribution to the global height.
- `prec` – integer, or `None` (default). The precision of the computation. If `None`, the precision is deduced from  $v$ .
- `weighted` – boolean. If `False` (default), the height is normalised to be invariant under extension of  $K$ . If `True`, return this normalised height multiplied by the local degree if  $v$  is a single place, or by the degree of  $K$  if  $v$  is `None`.

OUTPUT:

A real number. The normalisation is twice that in Silverman’s paper [Sil1988]. Note that this local height depends on the model of the curve.

ALGORITHM:

See [Sil1988], Section 4.

EXAMPLES:

Examples 1, 2, and 3 from [Sil1988]:

```
sage: K.<a> = QuadraticField(-2)
sage: E = EllipticCurve(K, [0,-1,1,0,0]); E
Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x^2$  over Number Field in  $a$ 
↪with defining polynomial  $x^2 + 2$ 
sage: P = E.lift_x(2+a); P
(a + 2 : 2*a + 1 : 1)
sage: P.archimedean_local_height(K.places(prec=170)[0]) / 2
0.45754773287523276736211210741423654346576029814695

sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve(K, [0,0,4,6*i,0]); E
Elliptic Curve defined by  $y^2 + 4*y = x^3 + 6*i*x$  over Number Field in  $i$  with
↪defining polynomial  $x^2 + 1$ 
sage: P = E((0,0))
sage: P.archimedean_local_height(K.places()[0]) / 2
0.510184995162373

sage: Q = E.lift_x(-9/4); Q
(-9/4 : -27/8*i : 1)
```

```
sage: Q.archimedean_local_height(K.places()[0]) / 2
0.654445619529600
```

An example over the rational numbers:

```
sage: E = EllipticCurve([0, 0, 0, -36, 0])
sage: P = E([-3, 9])
sage: P.archimedean_local_height()
1.98723816350773
```

Local heights of torsion points can be non-zero (unlike the global height):

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0, 0, 0, K(1), 0])
sage: P = E(i, 0)
sage: P.archimedean_local_height()
0.346573590279973
```

**archimedean\_local\_height** (\*args, \*\*kws)

Deprecated: Use `archimedean_local_height()` instead. See [trac ticket #13951](#) for details.

**elliptic\_logarithm** (embedding=None, precision=100, algorithm='pari')

Returns the elliptic logarithm of this elliptic curve point.

An embedding of the base field into  $\mathbf{R}$  or  $\mathbf{C}$  (with arbitrary precision) may be given; otherwise the first real embedding is used (with the specified precision) if any, else the first complex embedding.

INPUT:

- `embedding`: an embedding of the base field into  $\mathbf{R}$  or  $\mathbf{C}$
- `precision`: a positive integer (default 100) setting the number of bits of precision for the computation
- `algorithm`: either 'pari' (default for real embeddings) to use PARI's `ellpointtoz`{}, or 'sage' for a native implementation. Ignored for complex embeddings.

ALGORITHM:

See [Coh1993] for the case of real embeddings, and Cremona, J.E. and Thongjunthug, T. 2010 for the complex case.

AUTHORS:

- Michael Mardaus (2008-07),
- Tobias Nagel (2008-07) – original version from [Coh1993].
- John Cremona (2008-07) – revision following eclib code.
- John Cremona (2010-03) – implementation for complex embeddings.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: E.discriminant() > 0
True
sage: P = E([-1, 1])
sage: P.is_on_identity_component ()
False
sage: P.elliptic_logarithm (precision=96)
0.4793482501902193161295330101 + 0.985868850775824102211203849...*I
```

```

sage: Q=E([3,5])
sage: Q.is_on_identity_component()
True
sage: Q.elliptic_logarithm (precision=96)
1.931128271542559442488585220

```

An example with negative discriminant, and a torsion point:

```

sage: E = EllipticCurve('11a1')
sage: E.discriminant() < 0
True
sage: P = E([16,-61])
sage: P.elliptic_logarithm(precision=70)
0.25384186085591068434
sage: E.period_lattice().real_period(prec=70) / P.elliptic_
↪ logarithm(precision=70)
5.000000000000000000

```

A larger example. The default algorithm uses PARI and makes sure the result has the requested precision:

```

sage: E = EllipticCurve([1, 0, 1, -85357462, 303528987048]) #18074g1
sage: P = E([4458713781401/835903744, -64466909836503771/24167649046528, 1])
sage: P.elliptic_logarithm() # 100 bits
0.27656204014107061464076203097

```

The native algorithm ‘sage’ used to have trouble with precision in this example, but no longer:

```

sage: P.elliptic_logarithm(algorithm='sage') # 100 bits
0.27656204014107061464076203097

```

This shows that the bug reported at [trac ticket #4901](#) has been fixed:

```

sage: E = EllipticCurve("4390c2")
sage: P = E(683762969925/44944, -565388972095220019/9528128)
sage: P.elliptic_logarithm()
0.00025638725886520225353198932529
sage: P.elliptic_logarithm(precision=64)
0.000256387258865202254
sage: P.elliptic_logarithm(precision=65)
0.0002563872588652022535
sage: P.elliptic_logarithm(precision=128)
0.00025638725886520225353198932528666427412
sage: P.elliptic_logarithm(precision=129)
0.00025638725886520225353198932528666427412
sage: P.elliptic_logarithm(precision=256)
0.
↪ 0002563872588652022535319893252866642741168388008346370015005142128009610936373
sage: P.elliptic_logarithm(precision=257)
0.
↪ 00025638725886520225353198932528666427411683880083463700150051421280096109363730

```

Examples over number fields:

```

sage: K.<a> = NumberField(x^3-2)
sage: embs = K.embeddings(CC)
sage: E = EllipticCurve([0,1,0,a,a])
sage: Ls = [E.period_lattice(e) for e in embs]
sage: [L.real_flag for L in Ls]

```

```

[0, 0, -1]
sage: P = E(-1,0) # order 2
sage: [L.elliptic_logarithm(P) for L in Ls]
[-1.73964256006716 - 1.07861534489191*I, -0.363756518406398 - 1.
↪ 50699412135253*I, 1.90726488608927]

sage: E = EllipticCurve([-a^2 - a - 1, a^2 + a])
sage: Ls = [E.period_lattice(e) for e in embs]
sage: pts = [E(2*a^2 - a - 1, -2*a^2 - 2*a + 6), E(-2/3*a^2 - 1/3, -4/3*a -
↪ 2/3), E(5/4*a^2 - 1/2*a, -a^2 - 1/4*a + 9/4), E(2*a^2 + 3*a + 4, -7*a^
↪ 2 - 10*a - 12)]
sage: [[L.elliptic_logarithm(P) for P in pts] for L in Ls]
[[0.250819591818930 - 0.411963479992219*I, -0.290994550611374 - 1.
↪ 37239400324105*I, -0.693473752205595 - 2.45028458830342*I, -0.
↪ 151659609775291 - 1.48985406505459*I], [1.33444787667954 - 1.
↪ 50889756650544*I, 0.792633734249234 - 0.548467043256610*I, 0.
↪ 390154532655013 + 0.529423541805758*I, 0.931968675085317 - 0.
↪ 431006981443071*I], [1.14758249500109 + 0.853389664016075*I, 2.
↪ 59823462472518 + 0.853389664016075*I, 1.75372176444709, 0.303069634723001]]

```

```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,9*i-10,21-i])
sage: emb = K.embeddings(CC)[1]
sage: L = E.period_lattice(emb)
sage: P = E(2-i,4+2*i)
sage: L.elliptic_logarithm(P,prec=100)
0.70448375537782208460499649302 - 0.79246725643650979858266018068*I

```

**has\_finite\_order()**

Return True iff this point has finite order on the elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve([0,0,1,-1,0])
sage: P = E([0,0]); P
(0 : 0 : 1)
sage: P.has_finite_order()
False

```

```

sage: E = EllipticCurve([0,1])
sage: P = E([-1,0])
sage: P.has_finite_order()
True

```

**has\_good\_reduction(*P=None*)**

Returns True iff this point has good reduction modulo a prime.

INPUT:

- *P* – a prime of the base\_field of the point’s curve, or None (default)

OUTPUT:

(bool) If a prime *P* of the base field is specified, returns True iff the point has good reduction at *P*; otherwise, return true if the point has god reduction at all primes in the support of the discriminant of this model.

EXAMPLES:

```

sage: E = EllipticCurve('990e1')
sage: P = E.gen(0); P
(15 : 51 : 1)
sage: [E.has_good_reduction(p) for p in [2,3,5,7]]
[False, False, False, True]
sage: [P.has_good_reduction(p) for p in [2,3,5,7]]
[True, False, True, True]
sage: [E.tamagawa_exponent(p) for p in [2,3,5,7]]
[2, 2, 1, 1]
sage: [(2*P).has_good_reduction(p) for p in [2,3,5,7]]
[True, True, True, True]
sage: P.has_good_reduction()
False
sage: (2*P).has_good_reduction()
True
sage: (3*P).has_good_reduction()
False

```

```

sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve(K, [0,1,0,-160,308])
sage: P = E(26,-120)
sage: E.discriminant().support()
[Fractional ideal (i + 1),
Fractional ideal (-i - 2),
Fractional ideal (2*i + 1),
Fractional ideal (3)]
sage: [E.tamagawa_exponent(p) for p in E.discriminant().support()]
[1, 4, 4, 4]
sage: P.has_good_reduction()
False
sage: (2*P).has_good_reduction()
False
sage: (4*P).has_good_reduction()
True

```

**has\_infinite\_order()**

Return True iff this point has infinite order on the elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve([0,0,1,-1,0])
sage: P = E([0,0]); P
(0 : 0 : 1)
sage: P.has_infinite_order()
True

```

```

sage: E = EllipticCurve([0,1])
sage: P = E([-1,0])
sage: P.has_infinite_order()
False

```

**height** (*precision=None, normalised=True, algorithm='pari'*)

Return the Néron-Tate canonical height of the point.

INPUT:

- `self` – a point on an elliptic curve over a number field  $K$ .



- `precision` – positive integer, or None (default). The precision in bits of the result. If None, the default real precision is used.
- `normalised` – boolean. If True (default), the height is normalised to be invariant under extension of  $K$ . If False, return this normalised height multiplied by the degree of  $K$ .
- `algorithm` – string: either ‘`pari`’ (default) or ‘`sage`’. If ‘`pari`’ and the base field is  $\mathbf{Q}$ , use the PARI library function; otherwise use the Sage implementation.

OUTPUT:

The rational number 0, or a non-negative real number.

There are two normalisations used in the literature, one of which is double the other. We use the larger of the two, which is the one appropriate for the BSD conjecture. This is consistent with [\[Cre\]](#) and double that of [\[SilBook\]](#).

See [Wikipedia article Néron-Tate height](#)

REFERENCES:

EXAMPLES:

```
sage: E = EllipticCurve('11a'); E
Elliptic Curve defined by  $y^2 + y = x^3 - x^2 - 10x - 20$  over Rational Field
sage: P = E([5,5]); P
(5 : 5 : 1)
sage: P.height()
0
sage: Q = 5*P
sage: Q.height()
0
```

```
sage: E = EllipticCurve('37a'); E
Elliptic Curve defined by  $y^2 + y = x^3 - x$  over Rational Field
sage: P = E([0,0])
sage: P.height()
0.0511114082399688
sage: P.order()
+Infinity
sage: E.regulator()
0.0511114082399688...

sage: def naive_height(P):
....:     return log(RR(max(abs(P[0].numerator()), abs(P[0].denominator()))))
sage: for n in [1..10]:
....:     print(naive_height(2^n*P)/4^n)
0.0000000000000000
0.0433216987849966
0.0502949347635656
0.0511006335618645
0.0511007834799612
0.0511013666152466
0.0511034199907743
0.0511106492906471
0.0511114081541082
0.0511114081541180
```

```
sage: E = EllipticCurve('4602a1'); E
Elliptic Curve defined by  $y^2 + x*y = x^3 + x^2 - 37746035x - 89296920339$ 
↪over Rational Field
```

```

sage: x = 77985922458974949246858229195945103471590
sage: y = 19575260230015313702261379022151675961965157108920263594545223
sage: d = 2254020761884782243
sage: E([ x / d^2, y / d^3 ]).height()
86.7406561381275

```

```

sage: E = EllipticCurve([17, -60, -120, 0, 0]); E
Elliptic Curve defined by  $y^2 + 17xy - 120y = x^3 - 60x^2$  over Rational_
↪Field
sage: E([30, -90]).height()
0

sage: E = EllipticCurve('389a1'); E
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 2x$  over Rational Field
sage: [P,Q] = [E(-1,1),E(0,-1)]
sage: P.height(precision=100)
0.68666708330558658572355210295
sage: (3*Q).height(precision=100)/Q.height(precision=100)
9.00000000000000000000000000000000
sage: _.parent()
Real Field with 100 bits of precision

```

Canonical heights over number fields are implemented as well:

```

sage: R.<x> = QQ[]
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([a, 4]); E
Elliptic Curve defined by  $y^2 = x^3 + ax + 4$  over Number Field in a with_
↪defining polynomial  $x^3 - 2$ 
sage: P = E((0,2))
sage: P.height()
0.810463096585925
sage: P.height(precision=100)
0.81046309658592536863991810577
sage: P.height(precision=200)
0.81046309658592536863991810576865158896130286417155832378086
sage: (2*P).height() / P.height()
4.000000000000000
sage: (100*P).height() / P.height()
10000.00000000000

```

Setting `normalised=False` multiplies the height by the degree of  $K$ :

```

sage: E = EllipticCurve('37a')
sage: P = E([0,0])
sage: P.height()
0.0511114082399688
sage: P.height(normalised=False)
0.0511114082399688
sage: K.<z> = CyclotomicField(5)
sage: EK = E.change_ring(K)
sage: PK = EK([0,0])
sage: PK.height()
0.0511114082399688
sage: PK.height(normalised=False)
0.204445632959875

```

Some consistency checks:

```

sage: E = EllipticCurve('5077a1')
sage: P = E([-2, 3, 1])
sage: P.height()
1.36857250535393

sage: EK = E.change_ring(QuadraticField(-3, 'a'))
sage: PK = EK([-2, 3, 1])
sage: PK.height()
1.36857250535393

sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve(K, [0, 0, 4, 6*i, 0])
sage: Q = E.lift_x(-9/4); Q
(-9/4 : -27/8*i : 1)
sage: Q.height()
2.69518560017909
sage: (15*Q).height() / Q.height()
225.000000000000

sage: E = EllipticCurve('37a')
sage: P = E([0, -1])
sage: P.height()
0.0511114082399688
sage: K.<a> = QuadraticField(-7)
sage: ED = E.quadratic_twist(-7)
sage: Q = E.isomorphism_to(ED.change_ring(K))(P); Q
(0 : -7/2*a - 1/2 : 1)
sage: Q.height()
0.0511114082399688
sage: Q.height(precision=100)
0.051111408239968840235886099757

```

An example to show that the bug at [trac ticket #5252](#) is fixed:

```

sage: E = EllipticCurve([1, -1, 1, -2063758701246626370773726978, -
↪ 32838647793306133075103747085833809114881])
sage: P = E([-30987785091199, 258909576181697016447])
sage: P.height()
25.8603170675462
sage: P.height(precision=100)
25.860317067546190743868840741
sage: P.height(precision=250)
25.860317067546190743868840740735110323098872903844416215577171041783572513
sage: P.height(precision=500)
25.
↪ 860317067546190743868840740735110323098872903844416215577171041783572512955113057088981328

sage: P.height(precision=100) == P.non_archimedean_local_height(prec=100)+P.
↪ archimedean_local_height(prec=100)
True

```

An example to show that the bug at [trac ticket #8319](#) is fixed (correct height when the curve is not minimal):

```

sage: E = EllipticCurve([-5580472329446114952805505804593498080000, -
↪ 15733973378536811038297368990353605478770049722330636800000])
sage: xP = -
↪ 204885147732879546487576840131729064308289385547094673627174585676211859152978311600/
↪ 23625501907057948132262217188983681204856907657753178415430361

```

```
sage: P = E.lift_x(xP)
sage: P.height()
157.432598516754
sage: Q = 2*P
sage: Q.height() # long time (4s)
629.730394067016
sage: Q.height()-4*P.height() # long time
0.0000000000000000
```

An example to show that the bug at [trac ticket #12509](#) is fixed (precision issues):

[illegible]

This shows that the bug reported at [trac ticket #13951](#) has been fixed:

```
sage: E = EllipticCurve([0,17])
sage: P1 = E(2,5)
sage: P1.height()
1.06248137652528
sage: F = E.change_ring(QuadraticField(-3,'a'))
sage: P2 = F([2,5])
sage: P2.height()
1.06248137652528
```

```
is_on_identity_component(embedding=None)
```

Returns True iff this point is on the identity component of its curve with respect to a given (real or complex) embedding.

INPUT:

- `self` – a point on a curve over any ordered field (e.g.  $\mathbf{Q}$ )
- `embedding` – an embedding from the `base_field` of the point’s curve into  $\mathbf{R}$  or  $\mathbf{C}$ ; if `None` (the default) it uses the first embedding of the `base_field` into  $\mathbf{R}$  if any, else the first embedding into  $\mathbf{C}$ .

OUTPUT:

(bool) – True iff the point is on the identity component of the curve. (If the point is zero then the result is True.)

EXAMPLES:

For  $K = \mathbf{Q}$  there is no need to specify an embedding:

```
sage: E=EllipticCurve('5077a1')
sage: [E.lift_x(x).is_on_identity_component() for x in xrange(-3,5)]
[False, False, False, False, False, True, True, True]
```

An example over a field with two real embeddings:

```
sage: L.<a> = QuadraticField(2)
sage: E=EllipticCurve(L, [0,1,0,a,a])
sage: P=E(-1,0)
sage: [P.is_on_identity_component(e) for e in L.embeddings(RR)]
[False, True]
```

We can check this as follows:

```
sage: [e(E.discriminant())>0 for e in L.embeddings(RR)]
[True, False]
sage: e = L.embeddings(RR)[0]
sage: E1 = EllipticCurve(RR,[e(ai) for ai in E.ainvs()])
sage: e1,e2,e3 = E1.two_division_polynomial().roots(RR,multiplicities=False)
sage: e1 < e2 < e3 and e(P[0]) < e3
True
```

**non\_archimedean\_local\_height** ( $v=None$ ,  $prec=None$ ,  $weighted=False$ ,  $is_minimal=None$ )

Compute the local height of self at the non-archimedean place  $v$ .

INPUT:

- `self` – a point on an elliptic curve over a number field  $K$ .
- $v$  – a non-archimedean place of  $K$ , or `None` (default). If  $v$  is a non-archimedean place, return the local height of `self` at  $v$ . If  $v$  is `None`, return the total non-archimedean contribution to the global height.
- `prec` – integer, or `None` (default). The precision of the computation. If `None`, the height is returned symbolically.
- `weighted` – boolean. If `False` (default), the height is normalised to be invariant under extension of  $K$ . If `True`, return this normalised height multiplied by the local degree if  $v$  is a single place, or by the degree of  $K$  if  $v$  is `None`.

OUTPUT:

A real number. The normalisation is twice that in Silverman’s paper [Sil1988]. Note that this local height depends on the model of the curve.

ALGORITHM:

See [Sil1988], Section 5.

EXAMPLES:

Examples 2 and 3 from [Sil1988]:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve(K, [0,0,4,6*i,0]); E
Elliptic Curve defined by y^2 + 4*y = x^3 + 6*i*x over Number Field in i with_
↳defining polynomial x^2 + 1
sage: P = E((0,0))
sage: P.non_archimedean_local_height(K.ideal(i+1))
-1/2*log(2)
sage: P.non_archimedean_local_height(K.ideal(3))
0
sage: P.non_archimedean_local_height(K.ideal(1-2*i))
0

sage: Q = E.lift_x(-9/4); Q
(-9/4 : -27/8*i : 1)
```

```

sage: Q.non_archimedean_local_height(K.ideal(1+i))
2*log(2)
sage: Q.non_archimedean_local_height(K.ideal(3))
0
sage: Q.non_archimedean_local_height(K.ideal(1-2*i))
0
sage: Q.non_archimedean_local_height()
2*log(2)

```

An example over the rational numbers:

```

sage: E = EllipticCurve([0, 0, 0, -36, 0])
sage: P = E([-3, 9])
sage: P.non_archimedean_local_height()
-log(3)

```

Local heights of torsion points can be non-zero (unlike the global height):

```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0, 0, 0, K(1), 0])
sage: P = E(i, 0)
sage: P.non_archimedean_local_height()
-1/2*log(2)

```

**nonarchimedean\_local\_height** (\*args, \*\*kws)

Deprecated: Use `non_archimedean_local_height()` instead. See [trac ticket #13951](#) for details.

**order** ()

Return the order of this point on the elliptic curve.

If the point has infinite order, returns +Infinity. For curves defined over  $\mathbb{Q}$ , we call PARI; over other number fields we implement the function here.

---

**Note:** `additive_order()` is a synonym for `order()`

---

EXAMPLES:

```

sage: E = EllipticCurve([0,0,1,-1,0])
sage: P = E([0,0]); P
(0 : 0 : 1)
sage: P.order()
+Infinity

```

```

sage: E = EllipticCurve([0,1])
sage: P = E([-1,0])
sage: P.order()
2
sage: P.additive_order()
2

```

**padic\_elliptic\_logarithm** (p, absprec=20)

Computes the  $p$ -adic elliptic logarithm of this point.

INPUT:

$p$  - integer: a prime  
 absprec - integer (default: 20): the initial  $p$ -adic absolute precision of the computation

OUTPUT:

The  $p$ -adic elliptic logarithm of self, with precision `absprec`.

AUTHORS:

- Tobias Nagel
- Michael Mardaus
- John Cremona

ALGORITHM:

For points in the formal group (i.e. not integral at  $p$ ) we take the `log()` function from the formal groups module and evaluate it at  $-x/y$ . Otherwise we first multiply the point to get into the formal group, and divide the result afterwards.

---

**Todo:** See comments at [trac ticket #4805](#). Currently the absolute precision of the result may be less than the given value of `absprec`, and error-handling is imperfect.

---

EXAMPLES:

```
sage: E = EllipticCurve([0,1,1,-2,0])
sage: E(0).padic_elliptic_logarithm(3)
0
sage: P = E(0,0)
sage: P.padic_elliptic_logarithm(3)
2 + 2*3 + 3^3 + 2*3^7 + 3^8 + 3^9 + 3^11 + 3^15 + 2*3^17 + 3^18 + O(3^19)
sage: P.padic_elliptic_logarithm(3).lift()
660257522
sage: P = E(-11/9,28/27)
sage: [(2*P).padic_elliptic_logarithm(p)/P.padic_elliptic_logarithm(p) for p_
↪in prime_range(20)] # long time (3s)
[2 + O(2^19), 2 + O(3^20), 2 + O(5^19), 2 + O(7^19), 2 + O(11^19), 2 + O(13^
↪19), 2 + O(17^19), 2 + O(19^19)]
sage: [(3*P).padic_elliptic_logarithm(p)/P.padic_elliptic_logarithm(p) for p_
↪in prime_range(12)] # long time (2s)
[1 + 2 + O(2^19), 3 + 3^20 + O(3^21), 3 + O(5^19), 3 + O(7^19), 3 + O(11^19)]
sage: [(5*P).padic_elliptic_logarithm(p)/P.padic_elliptic_logarithm(p) for p_
↪in prime_range(12)] # long time (2s)
[1 + 2^2 + O(2^19), 2 + 3 + O(3^20), 5 + O(5^19), 5 + O(7^19), 5 + O(11^19)]
```

An example which arose during reviewing [trac ticket #4741](#):

```
sage: E = EllipticCurve('794a1')
sage: P = E(-1,2)
sage: P.padic_elliptic_logarithm(2) # default precision=20
2^4 + 2^5 + 2^6 + 2^8 + 2^9 + 2^13 + 2^14 + 2^15 + O(2^16)
sage: P.padic_elliptic_logarithm(2, absprec=30)
2^4 + 2^5 + 2^6 + 2^8 + 2^9 + 2^13 + 2^14 + 2^15 + 2^22 + 2^23 + 2^24 + O(2^
↪26)
sage: P.padic_elliptic_logarithm(2, absprec=40)
2^4 + 2^5 + 2^6 + 2^8 + 2^9 + 2^13 + 2^14 + 2^15 + 2^22 + 2^23 + 2^24 + 2^28_
↪+ 2^29 + 2^31 + 2^34 + O(2^35)
```

**reduction( $p$ )**

This finds the reduction of a point  $P$  on the elliptic curve modulo the prime  $p$ .

INPUT:

- `self` – A point on an elliptic curve.
- `p` – a prime number

OUTPUT:

The point reduced to be a point on the elliptic curve modulo  $p$ .

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 0])
sage: P = E(0, 0)
sage: P.reduction(5)
(0 : 0 : 1)
sage: Q = E(98, 931)
sage: Q.reduction(5)
(3 : 1 : 1)
sage: Q.reduction(5).curve() == E.reduction(5)
True
```

```
sage: F.<a> = NumberField(x^2+5)
sage: E = EllipticCurve(F, [1, 2, 3, 4, 0])
sage: Q = E(98, 931)
sage: Q.reduction(a)
(3 : 1 : 1)
sage: Q.reduction(11)
(10 : 7 : 1)
```

```
sage: F.<a> = NumberField(x^3+x^2+1)
sage: E = EllipticCurve(F, [a, 2])
sage: P = E(a, 1)
sage: P.reduction(F.ideal(5))
(abar : 1 : 1)
sage: P.reduction(F.ideal(a^2-4*a-2))
(abar : 1 : 1)
```

## 15.4 Elliptic curves over a general ring

Sage defines an elliptic curve over a ring  $R$  as a ‘Weierstrass Model’ with five coefficients  $[a_1, a_2, a_3, a_4, a_6]$  in  $R$  given by

$$y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6.$$

Note that the (usual) scheme-theoretic definition of an elliptic curve over  $R$  would require the discriminant to be a unit in  $R$ , Sage only imposes that the discriminant is non-zero. Also, in Magma, ‘Weierstrass Model’ means a model with  $a_1 = a_2 = a_3 = 0$ , which is called ‘Short Weierstrass Model’ in Sage; these do not always exist in characteristics 2 and 3.

EXAMPLES:

We construct an elliptic curve over an elaborate base ring:

```
sage: p = 97; a=1; b=3
sage: R.<u> = GF(p) []
sage: S.<v> = R[]
sage: T = S.fraction_field()
sage: E = EllipticCurve(T, [a, b]); E
Elliptic Curve defined by y^2 = x^3 + x + 3 over Fraction Field of Univariate
Polynomial Ring in v over Univariate Polynomial Ring in u over Finite Field of size
97
```



```
sage: latex(E)
y^2 = x^3 + x + 3
```

**AUTHORS:**

- William Stein (2005): Initial version
- Robert Bradshaw et al. ...
- John Cremona (2008-01): isomorphisms, automorphisms and twists in all characteristics
- Julian Rueth (2014-04-11): improved caching

```
class sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic(K,
                                                                    ainvs)
    Bases: sage.misc.fast_methods.WithEqualityById, sage.schemes.curves.
            projective_curve.ProjectivePlaneCurve
```

Elliptic curve over a generic base ring.

**EXAMPLES:**

```
sage: E = EllipticCurve([1,2,3/4,7,19]); E
Elliptic Curve defined by y^2 + x*y + 3/4*y = x^3 + 2*x^2 + 7*x + 19 over_
↪Rational Field
sage: loads(E.dumps()) == E
True
sage: E = EllipticCurve([1,3])
sage: P = E([-1,1,1])
sage: -5*P
(179051/80089 : -91814227/22665187 : 1)
```

**a1()**

Returns the  $a_1$  invariant of this elliptic curve.

**EXAMPLES:**

```
sage: E = EllipticCurve([1,2,3,4,6])
sage: E.a1()
1
```

**a2()**

Returns the  $a_2$  invariant of this elliptic curve.

**EXAMPLES:**

```
sage: E = EllipticCurve([1,2,3,4,6])
sage: E.a2()
2
```

**a3()**

Returns the  $a_3$  invariant of this elliptic curve.

**EXAMPLES:**

```
sage: E = EllipticCurve([1,2,3,4,6])
sage: E.a3()
3
```

**a4()**

Returns the  $a_4$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 6])
sage: E.a4()
4
```

**a6()**

Returns the  $a_6$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 6])
sage: E.a6()
6
```

**a\_invariants()**

The  $a$ -invariants of this elliptic curve, as a tuple.

OUTPUT:

(tuple) - a 5-tuple of the  $a$ -invariants of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.a_invariants()
(1, 2, 3, 4, 5)
sage: E = EllipticCurve([0, 1])
sage: E
Elliptic Curve defined by  $y^2 = x^3 + 1$  over Rational Field
sage: E.a_invariants()
(0, 0, 0, 0, 1)
sage: E = EllipticCurve([GF(7)(3), 5])
sage: E.a_invariants()
(0, 0, 0, 3, 5)
```

```
sage: E = EllipticCurve([1, 0, 0, 0, 1])
sage: E.a_invariants()[0] = 100000000
Traceback (most recent call last):
...
TypeError: 'tuple' object does not support item assignment
```

**ainvs()**

The  $a$ -invariants of this elliptic curve, as a tuple.

OUTPUT:

(tuple) - a 5-tuple of the  $a$ -invariants of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.a_invariants()
(1, 2, 3, 4, 5)
sage: E = EllipticCurve([0, 1])
sage: E
Elliptic Curve defined by  $y^2 = x^3 + 1$  over Rational Field
sage: E.a_invariants()
(0, 0, 0, 0, 1)
sage: E = EllipticCurve([GF(7)(3), 5])
```

```
sage: E.a_invariants()
(0, 0, 0, 3, 5)
```

```
sage: E = EllipticCurve([1,0,0,0,1])
sage: E.a_invariants()[0] = 100000000
Traceback (most recent call last):
...
TypeError: 'tuple' object does not support item assignment
```

**automorphisms** (*field=None*)

Return the set of isomorphisms from self to itself (as a list).

INPUT:

- *field* (default None) – a field into which the coefficients of the curve may be coerced (by default, uses the base field of the curve).

OUTPUT:

(list) A list of WeierstrassIsomorphism objects consisting of all the isomorphisms from the curve self to itself defined over *field*.

EXAMPLES:

```
sage: E = EllipticCurve_from_j(QQ(0)) # a curve with j=0 over QQ
sage: E.automorphisms();
[Generic endomorphism of Abelian group of points on Elliptic Curve defined by
↪ y^2 + y = x^3 over Rational Field
Via: (u,r,s,t) = (-1, 0, 0, -1), Generic endomorphism of Abelian group of
↪ points on Elliptic Curve defined by y^2 + y = x^3 over Rational Field
Via: (u,r,s,t) = (1, 0, 0, 0)]
```

We can also find automorphisms defined over extension fields:

```
sage: K.<a> = NumberField(x^2+3) # adjoin roots of unity
sage: E.automorphisms(K)
[Generic endomorphism of Abelian group of points on Elliptic Curve defined by
↪ y^2 + y = x^3 over Number Field in a with defining polynomial x^2 + 3
Via: (u,r,s,t) = (-1, 0, 0, -1),
...
Generic endomorphism of Abelian group of points on Elliptic Curve defined by
↪ y^2 + y = x^3 over Number Field in a with defining polynomial x^2 + 3
Via: (u,r,s,t) = (1, 0, 0, 0)]
```

```
sage: [ len(EllipticCurve_from_j(GF(q,'a')(0)).automorphisms()) for q in [2,4,
↪ 3,9,5,25,7,49]]
[2, 24, 2, 12, 2, 6, 6, 6]
```

**b2** ()

Returns the  $b_2$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1,2,3,4,5])
sage: E.b2()
9
```

**b4** ()

Returns the  $b_4$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.b4()
11
```

**b6()**

Returns the  $b_6$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.b6()
29
```

**b8()**

Returns the  $b_8$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.b8()
35
```

**b\_invariants()**

Returns the  $b$ -invariants of this elliptic curve, as a tuple.

OUTPUT:

(tuple) - a 4-tuple of the  $b$ -invariants of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.b_invariants()
(-4, -20, -79, -21)
sage: E = EllipticCurve([-4, 0])
sage: E.b_invariants()
(0, -8, 0, -16)
```

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.b_invariants()
(9, 11, 29, 35)
sage: E.b2()
9
sage: E.b4()
11
sage: E.b6()
29
sage: E.b8()
35
```

ALGORITHM:

These are simple functions of the  $a$ -invariants.

AUTHORS:

- William Stein (2005-04-25)

**base\_extend(*R*)**

Return the base extension of *self* to *R*.

INPUT:

- *R* – either a ring into which the *a*-invariants of *self* may be converted, or a morphism which may be applied to them.

OUTPUT:

An elliptic curve over the new ring whose *a*-invariants are the images of the *a*-invariants of *self*.

EXAMPLES:

```
sage: E=EllipticCurve(GF(5), [1,1]); E
Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Finite Field of size 5
sage: E1=E.base_extend(GF(125, 'a')); E1
Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Finite Field in a of size  $5^3$ 
```

**base\_ring()**

Returns the base ring of the elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve(GF(49, 'a'), [3,5])
sage: E.base_ring()
Finite Field in a of size  $7^2$ 
```

```
sage: E = EllipticCurve([1,1])
sage: E.base_ring()
Rational Field
```

```
sage: E = EllipticCurve(ZZ, [3,5])
sage: E.base_ring()
Integer Ring
```

**c4()**

Returns the  $c_4$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.c4()
496
```

**c6()**

Returns the  $c_6$  invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.c6()
20008
```

**c\_invariants()**

Returns the *c*-invariants of this elliptic curve, as a tuple.

OUTPUT:

(tuple) - a 2-tuple of the *c*-invariants of the elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.c_invariants()
(496, 20008)
sage: E = EllipticCurve([-4, 0])
sage: E.c_invariants()
(192, 0)
```

ALGORITHM:

These are simple functions of the  $a$ -invariants.

AUTHORS:

- William Stein (2005-04-25)

**change\_ring** ( $R$ )

Return the base change of self to  $R$ .

This has the same effect as `self.base_extend(R)`.

EXAMPLES:

```
sage: F2=GF(5^2, 'a'); a=F2.gen()
sage: F4=GF(5^4, 'b'); b=F4.gen()
sage: h=F2.hom([a.charpoly().roots(ring=F4,multiplicities=False)[0]],F4)
sage: E=EllipticCurve(F2,[1,a]); E
Elliptic Curve defined by  $y^2 = x^3 + x + a$  over Finite Field in  $a$  of size  $5^2$ 
sage: E.change_ring(h)
Elliptic Curve defined by  $y^2 = x^3 + x + (4*b^3+4*b^2+4*b+3)$  over Finite_
↪Field in  $b$  of size  $5^4$ 
```

**change\_weierstrass\_model** ( $*ur$ )

Return a new Weierstrass model of self under the standard transformation  $(u, r, s, t)$

$$(x, y) \mapsto (x', y') = (u^2x + r, u^3y + su^2x + t).$$

EXAMPLES:

```
sage: E = EllipticCurve('15a')
sage: F1 = E.change_weierstrass_model([1/2, 0, 0, 0]); F1
Elliptic Curve defined by  $y^2 + 2*x*y + 8*y = x^3 + 4*x^2 - 160*x - 640$  over_
↪Rational Field
sage: F2 = E.change_weierstrass_model([7, 2, 1/3, 5]); F2
Elliptic Curve defined by  $y^2 + 5/21*x*y + 13/343*y = x^3 + 59/441*x^2 - 10/$ 
↪7203*x - 58/117649 over Rational Field
sage: F1.is_isomorphic(F2)
True
```

**discriminant** ()

Returns the discriminant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: E.discriminant()
37
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.discriminant()
-161051
```

```
sage: E = EllipticCurve([GF(7)(2), 1])
sage: E.discriminant()
1
```

**division\_polynomial** ( $m, x=None, two\_torsion\_multiplicity=2$ )

Returns the  $m^{\text{th}}$  division polynomial of this elliptic curve evaluated at  $x$ .

INPUT:

- $m$  - positive integer.
- $x$  - optional ring element to use as the “ $x$ ” variable. If  $x$  is None, then a new polynomial ring will be constructed over the base ring of the elliptic curve, and its generator will be used as  $x$ . Note that  $x$  does not need to be a generator of a polynomial ring; any ring element is ok. This permits fast calculation of the torsion polynomial *evaluated* on any element of a ring.
- $two\_torsion\_multiplicity$  - 0, 1 or 2

If 0: for even  $m$  when  $x$  is None, a univariate polynomial over the base ring of the curve is returned, which omits factors whose roots are the  $x$ -coordinates of the 2-torsion points. Similarly when  $x$  is not none, the evaluation of such a polynomial at  $x$  is returned.

If 2: for even  $m$  when  $x$  is None, a univariate polynomial over the base ring of the curve is returned, which includes a factor of degree 3 whose roots are the  $x$ -coordinates of the 2-torsion points. Similarly when  $x$  is not none, the evaluation of such a polynomial at  $x$  is returned.

If 1: when  $x$  is None, a bivariate polynomial over the base ring of the curve is returned, which includes a factor  $2*y + a1*x + a3$  which has simple zeros at the 2-torsion points. When  $x$  is not none, it should be a tuple of length 2, and the evaluation of such a polynomial at  $x$  is returned.

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: E.division_polynomial(1)
1
sage: E.division_polynomial(2, two_torsion_multiplicity=0)
1
sage: E.division_polynomial(2, two_torsion_multiplicity=1)
2*y + 1
sage: E.division_polynomial(2, two_torsion_multiplicity=2)
4*x^3 - 4*x + 1
sage: E.division_polynomial(2)
4*x^3 - 4*x + 1
sage: [E.division_polynomial(3, two_torsion_multiplicity=i) for i in range(3)]
[3*x^4 - 6*x^2 + 3*x - 1, 3*x^4 - 6*x^2 + 3*x - 1, 3*x^4 - 6*x^2 + 3*x - 1]
sage: [type(E.division_polynomial(3, two_torsion_multiplicity=i)) for i in_
↳ range(3)]
[<... 'sage.rings.polynomial.polynomial_rational_flint.Polynomial_rational_
↳ flint'>,
<... 'sage.rings.polynomial.multi_polynomial_libsingular.MPolynomial_
↳ libsingular'>,
<... 'sage.rings.polynomial.polynomial_rational_flint.Polynomial_rational_
↳ flint'>]
```

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: R.<z>=PolynomialRing(QQ)
sage: E.division_polynomial(4, z, 0)
```

```

2*z^6 - 4*z^5 - 100*z^4 - 790*z^3 - 210*z^2 - 1496*z - 5821
sage: E.division_polynomial(4,z)
8*z^9 - 24*z^8 - 464*z^7 - 2758*z^6 + 6636*z^5 + 34356*z^4 + 53510*z^3 +
↳99714*z^2 + 351024*z + 459859

```

This does not work, since when `two_torsion_multiplicity` is 1, we compute a bivariate polynomial, and must evaluate at a tuple of length 2:

```

sage: E.division_polynomial(4,z,1)
Traceback (most recent call last):
...
ValueError: x should be a tuple of length 2 (or None) when two_torsion_
↳multiplicity is 1
sage: R.<z,w>=PolynomialRing(QQ,2)
sage: E.division_polynomial(4,(z,w),1).factor()
(2*w + 1) * (2*z^6 - 4*z^5 - 100*z^4 - 790*z^3 - 210*z^2 - 1496*z - 5821)

```

We can also evaluate this bivariate polynomial at a point:

```

sage: P = E(5,5)
sage: E.division_polynomial(4,P,two_torsion_multiplicity=1)
-1771561

```

#### `division_polynomial_0` ( $n, x=None$ )

Returns the  $n^{\text{th}}$  torsion (division) polynomial, without the 2-torsion factor if  $n$  is even, as a polynomial in  $x$ .

These are the polynomials  $g_n$  defined in [MazurTate1991], but with the sign flipped for even  $n$ , so that the leading coefficient is always positive.

---

**Note:** This function is intended for internal use; users should use `division_polynomial()`.

---

#### See also:

`multiple_x_numerator()` `multiple_x_denominator()` `division_polynomial()`

#### INPUT:

- $n$  - positive integer, or the special values  $-1$  and  $-2$  which mean  $B_6 = (2y + a_1x + a_3)^2$  and  $B_6^2$  respectively (in the notation of [MazurTate1991]); or a list of integers.
- $x$  - a ring element to use as the “ $x$ ” variable or `None` (default: `None`). If `None`, then a new polynomial ring will be constructed over the base ring of the elliptic curve, and its generator will be used as  $x$ . Note that  $x$  does not need to be a generator of a polynomial ring; any ring element is ok. This permits fast calculation of the torsion polynomial *evaluated* on any element of a ring.

#### ALGORITHM:

Recursion described in [MazurTate1991]. The recursive formulae are evaluated  $O(\log^2 n)$  times.

#### AUTHORS:

- David Harvey (2006-09-24): initial version
- John Cremona (2008-08-26): unified division polynomial code

#### REFERENCES:

#### EXAMPLES:



```

sage: E = EllipticCurve("37a")
sage: E.division_polynomial_0(1)
1
sage: E.division_polynomial_0(2)
1
sage: E.division_polynomial_0(3)
3*x^4 - 6*x^2 + 3*x - 1
sage: E.division_polynomial_0(4)
2*x^6 - 10*x^4 + 10*x^3 - 10*x^2 + 2*x + 1
sage: E.division_polynomial_0(5)
5*x^12 - 62*x^10 + 95*x^9 - 105*x^8 - 60*x^7 + 285*x^6 - 174*x^5 - 5*x^4 -
↪ 5*x^3 + 35*x^2 - 15*x + 2
sage: E.division_polynomial_0(6)
3*x^16 - 72*x^14 + 168*x^13 - 364*x^12 + 1120*x^10 - 1144*x^9 + 300*x^8 -
↪ 540*x^7 + 1120*x^6 - 588*x^5 - 133*x^4 + 252*x^3 - 114*x^2 + 22*x - 1
sage: E.division_polynomial_0(7)
7*x^24 - 308*x^22 + 986*x^21 - 2954*x^20 + 28*x^19 + 17171*x^18 - 23142*x^17 -
↪ 511*x^16 - 5012*x^15 + 43804*x^14 - 7140*x^13 - 96950*x^12 + 111356*x^11 -
↪ 19516*x^10 - 49707*x^9 + 40054*x^8 - 124*x^7 - 18382*x^6 + 13342*x^5 -
↪ 4816*x^4 + 1099*x^3 - 210*x^2 + 35*x - 3
sage: E.division_polynomial_0(8)
4*x^30 - 292*x^28 + 1252*x^27 - 5436*x^26 + 2340*x^25 + 39834*x^24 - 79560*x^
↪ 23 + 51432*x^22 - 142896*x^21 + 451596*x^20 - 212040*x^19 - 1005316*x^18 +
↪ 1726416*x^17 - 671160*x^16 - 954924*x^15 + 1119552*x^14 + 313308*x^13 -
↪ 1502818*x^12 + 1189908*x^11 - 160152*x^10 - 399176*x^9 + 386142*x^8 -
↪ 220128*x^7 + 99558*x^6 - 33528*x^5 + 6042*x^4 + 310*x^3 - 406*x^2 + 78*x - 5

```

```

sage: E.division_polynomial_0(18) % E.division_polynomial_0(6) == 0
True

```

An example to illustrate the relationship with torsion points:

```

sage: F = GF(11)
sage: E = EllipticCurve(F, [0, 2]); E
Elliptic Curve defined by y^2 = x^3 + 2 over Finite Field of size 11
sage: f = E.division_polynomial_0(5); f
5*x^12 + x^9 + 8*x^6 + 4*x^3 + 7
sage: f.factor()
(5) * (x^2 + 5) * (x^2 + 2*x + 5) * (x^2 + 5*x + 7) * (x^2 + 7*x + 7) * (x^2 -
↪ 9*x + 5) * (x^2 + 10*x + 7)

```

This indicates that the  $x$ -coordinates of all the 5-torsion points of  $E$  are in  $\mathbf{F}_{11^2}$ , and therefore the  $y$ -coordinates are in  $\mathbf{F}_{11^4}$ :

```

sage: K = GF(11^4, 'a')
sage: X = E.change_ring(K)
sage: f = X.division_polynomial_0(5)
sage: x_coords = f.roots(multiplicities=False); x_coords
[10*a^3 + 4*a^2 + 5*a + 6,
 9*a^3 + 8*a^2 + 10*a + 8,
 8*a^3 + a^2 + 4*a + 10,
 8*a^3 + a^2 + 4*a + 8,
 8*a^3 + a^2 + 4*a + 4,
 6*a^3 + 9*a^2 + 3*a + 4,
 5*a^3 + 2*a^2 + 8*a + 7,
 3*a^3 + 10*a^2 + 7*a + 8,
 3*a^3 + 10*a^2 + 7*a + 3,

```

```

3*a^3 + 10*a^2 + 7*a + 1,
2*a^3 + 3*a^2 + a + 7,
a^3 + 7*a^2 + 6*a]

```

Now we check that these are exactly the  $x$ -coordinates of the 5-torsion points of  $E$ :

```

sage: for x in x_coords:
....:     assert X.lift_x(x).order() == 5

```

The roots of the polynomial are the  $x$ -coordinates of the points  $P$  such that  $mP = 0$  but  $2P \neq 0$ :

```

sage: E=EllipticCurve('14a1')
sage: T=E.torsion_subgroup()
sage: [n*T.0 for n in range(6)]
[(0 : 1 : 0),
(9 : 23 : 1),
(2 : 2 : 1),
(1 : -1 : 1),
(2 : -5 : 1),
(9 : -33 : 1)]
sage: pol=E.division_polynomial_0(6)
sage: xlist=pol.roots(multiplicities=False); xlist
[9, 2, -1/3, -5]
sage: [E.lift_x(x, all=True) for x in xlist]
[[ (9 : 23 : 1), (9 : -33 : 1)], [(2 : 2 : 1), (2 : -5 : 1)], [], []]

```

**Note:** The point of order 2 and the identity do not appear. The points with  $x = -1/3$  and  $x = -5$  are not rational.

### **formal()**

The formal group associated to this elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve("37a")
sage: E.formal_group()
Formal Group associated to the Elliptic Curve defined by  $y^2 + y = x^3 - x$ 
↪over Rational Field

```

### **formal\_group()**

The formal group associated to this elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve("37a")
sage: E.formal_group()
Formal Group associated to the Elliptic Curve defined by  $y^2 + y = x^3 - x$ 
↪over Rational Field

```

### **gen(i)**

Function returning the  $i$ 'th generator of this elliptic curve.

**Note:** Relies on `gens()` being implemented.

EXAMPLES:

```

sage: R.<a1,a2,a3,a4,a6>=QQ[]
sage: E=EllipticCurve([a1,a2,a3,a4,a6])
sage: E.gen(0)
Traceback (most recent call last):
...
NotImplementedError: not implemented.

```

**gens()**

Placeholder function to return generators of an elliptic curve.

---

**Note:** This functionality is implemented in certain derived classes, such as `EllipticCurve_rational_field`.

---

EXAMPLES:

```

sage: R.<a1,a2,a3,a4,a6>=QQ[]
sage: E=EllipticCurve([a1,a2,a3,a4,a6])
sage: E.gens()
Traceback (most recent call last):
...
NotImplementedError: not implemented.
sage: E=EllipticCurve(QQ,[1,1])
sage: E.gens()
[(0 : 1 : 1)]

```

**hyperelliptic\_polynomials()**

Returns a pair of polynomials  $g(x)$ ,  $h(x)$  such that this elliptic curve can be defined by the standard hyperelliptic equation

$$y^2 + h(x)y = g(x).$$

EXAMPLES:

```

sage: R.<a1,a2,a3,a4,a6>=QQ[]
sage: E=EllipticCurve([a1,a2,a3,a4,a6])
sage: E.hyperelliptic_polynomials()
(x^3 + a2*x^2 + a4*x + a6, a1*x + a3)

```

**is\_isomorphic(other, field=None)**

Returns whether or not self is isomorphic to other.

INPUT:

- `other` – another elliptic curve.
- `field` (default None) – a field into which the coefficients of the curves may be coerced (by default, uses the base field of the curves).

OUTPUT:

(bool) True if there is an isomorphism from curve `self` to curve `other` defined over `field`.

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: F = E.change_weierstrass_model([2,3,4,5]); F
Elliptic Curve defined by y^2 + 4*x*y + 11/8*y = x^3 - 3/2*x^2 - 13/16*x over_
↳ Rational Field
sage: E.is_isomorphic(F)

```

```
True
sage: E.is_isomorphic(F.change_ring(CC))
False
```

**is\_on\_curve**( $x, y$ )

Returns True if  $(x, y)$  is an affine point on this curve.

INPUT:

- $x, y$  - elements of the base ring of the curve.

EXAMPLES:

```
sage: E=EllipticCurve(QQ, [1,1])
sage: E.is_on_curve(0,1)
True
sage: E.is_on_curve(1,1)
False
```

**is\_x\_coord**( $x$ )

Returns True if  $x$  is the  $x$ -coordinate of a point on this curve.

---

**Note:** See also `lift_x()` to find the point(s) with a given  $x$ -coordinate. This function may be useful in cases where testing an element of the base field for being a square is faster than finding its square root.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a'); E
Elliptic Curve defined by  $y^2 + y = x^3 - x$  over Rational Field
sage: E.is_x_coord(1)
True
sage: E.is_x_coord(2)
True
```

There are no rational points with  $x$ -coordinate 3:

```
sage: E.is_x_coord(3)
False
```

However, there are such points in  $E(\mathbf{R})$ :

```
sage: E.change_ring(RR).is_x_coord(3)
True
```

And of course it always works in  $E(\mathbf{C})$ :

```
sage: E.change_ring(RR).is_x_coord(-3)
False
sage: E.change_ring(CC).is_x_coord(-3)
True
```

AUTHORS:

- John Cremona (2008-08-07): adapted from `lift_x()`

```
sage: F=GF(32, 'a')
sage: E=EllipticCurve(F, [1,0,0,0,1])
```

```
sage: set([P[0] for P in E.points() if P!=E(0)]) == set([x for x in F if E.is_
↪x_coord(x)])
True
```

**isomorphism\_to** (*other*)

Given another weierstrass model *other* of self, return an isomorphism from self to *other*.

INPUT:

- *other* – an elliptic curve isomorphic to self.

OUTPUT:

(Weierstrassmorphism) An isomorphism from self to *other*.

---

**Note:** If the curves in question are not isomorphic, a `ValueError` is raised.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: F = E.short_weierstrass_model()
sage: w = E.isomorphism_to(F); w
Generic morphism:
From: Abelian group of points on Elliptic Curve defined by y^2 + y = x^3 - x_
↪over Rational Field
To: Abelian group of points on Elliptic Curve defined by y^2 = x^3 - 16*x_
↪+ 16 over Rational Field
Via: (u,r,s,t) = (1/2, 0, 0, -1/2)
sage: P = E(0,-1,1)
sage: w(P)
(0 : -4 : 1)
sage: w(5*P)
(1 : 1 : 1)
sage: 5*w(P)
(1 : 1 : 1)
sage: 120*w(P) == w(120*P)
True
```

We can also handle injections to different base rings:

```
sage: K.<a> = NumberField(x^3-7)
sage: E.isomorphism_to(E.change_ring(K))
Generic morphism:
From: Abelian group of points on Elliptic Curve defined by y^2 + y = x^3 -_
↪x over Rational Field
To: Abelian group of points on Elliptic Curve defined by y^2 + y = x^3 +_
↪(-1)*x over Number Field in a with defining polynomial x^3 - 7
Via: (u,r,s,t) = (1, 0, 0, 0)
```

**isomorphisms** (*other*, *field=None*)

Return the set of isomorphisms from self to *other* (as a list).

INPUT:

- *other* – another elliptic curve.
- *field* (default `None`) – a field into which the coefficients of the curves may be coerced (by default, uses the base field of the curves).

OUTPUT:

(list) A list of WeierstrassIsomorphism objects consisting of all the isomorphisms from the curve self to the curve other defined over field.

EXAMPLES:

```
sage: E = EllipticCurve_from_j(QQ(0)) # a curve with j=0 over QQ
sage: F = EllipticCurve('27a3') # should be the same one
sage: E.isomorphisms(F);
[Generic endomorphism of Abelian group of points on Elliptic Curve defined by
↪y^2 + y = x^3 over Rational Field
  Via: (u,r,s,t) = (-1, 0, 0, -1),
Generic endomorphism of Abelian group of points on Elliptic Curve defined by
↪y^2 + y = x^3 over Rational Field
  Via: (u,r,s,t) = (1, 0, 0, 0)]
```

We can also find isomorphisms defined over extension fields:

```
sage: E=EllipticCurve(GF(7),[0,0,0,1,1])
sage: F=EllipticCurve(GF(7),[0,0,0,1,-1])
sage: E.isomorphisms(F)
[]
sage: E.isomorphisms(F,GF(49,'a'))
[Generic morphism:
From: Abelian group of points on Elliptic Curve defined by y^2 = x^3 + x + 1
↪over Finite Field in a of size 7^2
To:   Abelian group of points on Elliptic Curve defined by y^2 = x^3 + x + 6
↪over Finite Field in a of size 7^2
Via: (u,r,s,t) = (a + 3, 0, 0, 0), Generic morphism:
From: Abelian group of points on Elliptic Curve defined by y^2 = x^3 + x + 1
↪over Finite Field in a of size 7^2
To:   Abelian group of points on Elliptic Curve defined by y^2 = x^3 + x + 6
↪over Finite Field in a of size 7^2
Via: (u,r,s,t) = (6*a + 4, 0, 0, 0)]
```

**j\_invariant()**

Returns the j-invariant of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0,0,1,-1,0])
sage: E.j_invariant()
110592/37
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.j_invariant()
-122023936/161051
sage: E = EllipticCurve([-4,0])
sage: E.j_invariant()
1728
```

```
sage: E = EllipticCurve([GF(7)(2),1])
sage: E.j_invariant()
1
```

**lift\_x(x, all=False, extend=False)**

Returns one or all points with given x-coordinate.

INPUT:

- $x$  – an element of the base ring of the curve, or of an extension.
- `all` (bool, default False) – if True, return a (possibly empty) list of all points; if False, return just one point, or raise a `ValueError` if there are none.
- `extend` (bool, default False) –
  - if False, extend the base if necessary and possible to include  $x$ , and only return point(s) defined over this ring, or raise an error when there are none with this  $x$ -coordinate;
  - If True, the base ring will be extended if necessary to contain the  $y$ -coordinates of the point(s) with this  $x$ -coordinate, in addition to a possible base change to include  $x$ .

OUTPUT:

A point or list of up to 2 points on this curve, or a base-change of this curve to a larger ring.

---

**Note:** See also `is_x_coord()`.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a'); E
Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field
sage: E.lift_x(1)
(1 : 0 : 1)
sage: E.lift_x(2)
(2 : 2 : 1)
sage: E.lift_x(1/4, all=True)
[(1/4 : -3/8 : 1), (1/4 : -5/8 : 1)]
```

There are no rational points with  $x$ -coordinate 3:

```
sage: E.lift_x(3)
Traceback (most recent call last):
...
ValueError: No point with x-coordinate 3 on Elliptic Curve defined by y^2 + y_
↳ x^3 - x over Rational Field
```

We can use the `extend` parameter to make the necessary quadratic extension. Note that in such cases the returned point is a point on a new curve object, the result of changing the base ring to the parent of  $x$ :

```
sage: P = E.lift_x(3, extend=True); P
(3 : y : 1)
sage: P.curve()
Elliptic Curve defined by y^2 + y = x^3 + (-1)*x over Number Field in y with_
↳ defining polynomial y^2 + y - 24
```

Or we can extend scalars. There are two such points in  $E(\mathbb{R})$ :

```
sage: E.change_ring(RR).lift_x(3, all=True)
[(3.000000000000000 : 4.42442890089805 : 1.000000000000000),
 (3.000000000000000 : -5.42442890089805 : 1.000000000000000)]
```

And of course it always works in  $E(\mathbb{C})$ :

```
sage: E.change_ring(RR).lift_x(.5, all=True)
[]
sage: E.change_ring(CC).lift_x(.5)
(0.500000000000000 : -0.500000000000000 + 0.353553390593274*I : 1.
↳ 0.000000000000000)
```

In this example we start with a curve defined over  $\mathbb{Q}$  which has no rational points with  $x = 0$ , but using `extend = True` we can construct such a point over a quadratic field:

```
sage: E = EllipticCurve([0,0,0,0,2]); E
Elliptic Curve defined by  $y^2 = x^3 + 2$  over Rational Field
sage: P = E.lift_x(0, extend=True); P
(0 : y : 1)
sage: P.curve()
Elliptic Curve defined by  $y^2 = x^3 + 2$  over Number Field in  $y$  with defining_
↪ polynomial  $y^2 - 2$ 
```

We can perform these operations over finite fields too:

```
sage: E = EllipticCurve('37a').change_ring(GF(17)); E
Elliptic Curve defined by  $y^2 + y = x^3 + 16x$  over Finite Field of size 17
sage: E.lift_x(7)
(7 : 11 : 1)
sage: E.lift_x(3)
Traceback (most recent call last):
...
ValueError: No point with x-coordinate 3 on Elliptic Curve defined by  $y^2 + y$ 
↪  $= x^3 + 16x$  over Finite Field of size 17
```

Note that there is only one lift with  $x$ -coordinate 10 in  $E(\mathbb{F}_{17})$ :

```
sage: E.lift_x(10, all=True)
[(10 : 8 : 1)]
```

We can lift over more exotic rings too. If the supplied  $x$  value is in an extension of the base, note that the point returned is on the base-extended curve:

```
sage: E = EllipticCurve('37a')
sage: P = E.lift_x(pAdicField(17, 5)(6)); P
(6 + O(17^5) : 2 + 16*17 + 16*17^2 + 16*17^3 + 16*17^4 + O(17^5) : 1 + O(17^
↪ 5))
sage: P.curve()
Elliptic Curve defined by  $y^2 + (1+O(17^5))*y = x^3 + (16+16*17+16*17^2+16*17^
↪ 3+16*17^4+O(17^5))*x$  over 17-adic Field with capped relative precision 5
sage: K.<t> = PowerSeriesRing(QQ, 't', 5)
sage: P = E.lift_x(1+t); P
(1 + t : 2*t - t^2 + 5*t^3 - 21*t^4 + O(t^5) : 1)
sage: K.<a> = GF(16)
sage: P = E.change_ring(K).lift_x(a^3); P
(a^3 : a^3 + a : 1)
sage: P.curve()
Elliptic Curve defined by  $y^2 + y = x^3 + x$  over Finite Field in  $a$  of size  $2^4$ 
```

We can extend the base field to include the associated  $y$  value(s):

```
sage: E = EllipticCurve([0,0,0,0,2]); E
Elliptic Curve defined by  $y^2 = x^3 + 2$  over Rational Field
sage: x = polygen(QQ)
sage: P = E.lift_x(x, extend=True); P
(x : y : 1)
```

This point is a generic point on  $E$ :



```

sage: P.curve()
Elliptic Curve defined by  $y^2 = x^3 + 2$  over Univariate Quotient Polynomial
↪Ring in  $y$  over Fraction Field of Univariate Polynomial Ring in  $x$  over
↪Rational Field with modulus  $y^2 - x^3 - 2$ 
sage: -P
(x : -y : 1)
sage: 2*P
((1/4*x^4 - 4*x)/(x^3 + 2) : ((-1/8*x^6 - 5*x^3 + 4)/(-x^6 - 4*x^3 - 4))*y :
↪1)

```

AUTHOR:

- Robert Bradshaw (2007-04-24)
- John Cremona (2017-11-10)

**multiplication\_by\_m**( $m$ ,  $x\_only=False$ )

Return the multiplication-by- $m$  map from self to self

The result is a pair of rational functions in two variables  $x, y$  (or a rational function in one variable  $x$  if  $x\_only$  is True).

INPUT:

- $m$  - a nonzero integer
- $x\_only$  - boolean (default: False) if True, return only the  $x$ -coordinate of the map (as a rational function in one variable).

OUTPUT:

- a pair  $(f(x), g(x, y))$ , where  $f$  and  $g$  are rational functions with the degree of  $y$  in  $g(x, y)$  exactly 1,
- or just  $f(x)$  if  $x\_only$  is True

---

**Note:**

- The result is not cached.
  - $m$  is allowed to be negative (but not 0).
- 

EXAMPLES:

```
sage: E = EllipticCurve([-1, 3])
```

We verify that multiplication by 1 is just the identity:

```

sage: E.multiplication_by_m(1)
(x, y)

```

Multiplication by 2 is more complicated:

```

sage: f = E.multiplication_by_m(2)
sage: f
((x^4 + 2*x^2 - 24*x + 1)/(4*x^3 - 4*x + 12), (8*x^6*y - 40*x^4*y + 480*x^3*y
↪ - 40*x^2*y + 96*x*y - 568*y)/(64*x^6 - 128*x^4 + 384*x^3 + 64*x^2 - 384*x +
↪ 576))

```

Grab only the  $x$ -coordinate (less work):

```
sage: mx = E.multiplication_by_m(2, x_only=True); mx
(x^4 + 2*x^2 - 24*x + 1)/(4*x^3 - 4*x + 12)
sage: mx.parent()
Fraction Field of Univariate Polynomial Ring in x over Rational Field
```

We check that it works on a point:

```
sage: P = E([2,3])
sage: eval = lambda f,P: [fi(P[0],P[1]) for fi in f]
sage: assert E(eval(f,P)) == 2*P
```

We do the same but with multiplication by 3:

```
sage: f = E.multiplication_by_m(3)
sage: assert E(eval(f,P)) == 3*P
```

And the same with multiplication by 4:

```
sage: f = E.multiplication_by_m(4)
sage: assert E(eval(f,P)) == 4*P
```

And the same with multiplication by -1,-2,-3,-4:

```
sage: for m in [-1,-2,-3,-4]:
....:     f = E.multiplication_by_m(m)
....:     assert E(eval(f,P)) == m*P
```

#### **`multiplication_by_m_isogeny(m)`**

Return the `EllipticCurveIsogeny` object associated to the multiplication-by- $m$  map on self. The resulting isogeny will have the associated rational maps (i.e. those returned by `self.multiplication_by_m()`) already computed.

NOTE: This function is currently *much* slower than the result of `self.multiplication_by_m()`, because constructing an isogeny precomputes a significant amount of information. See [trac ticket #7368](#) and [trac ticket #8014](#) for the status of improving this situation.

INPUT:

- $m$  - a nonzero integer

OUTPUT:

- An `EllipticCurveIsogeny` object associated to the multiplication-by- $m$  map on self.

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.multiplication_by_m_isogeny(7)
Isogeny of degree 49 from Elliptic Curve defined by y^2 + y = x^3 - x^2 -
↪ 10*x - 20 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 -
↪ x^2 - 10*x - 20 over Rational Field
```

#### **`pari_curve()`**

Return the PARI curve corresponding to this elliptic curve.

The result is cached.

EXAMPLES:

```

sage: E = EllipticCurve([RR(0), RR(0), RR(1), RR(-1), RR(0)])
sage: e = E.pari_curve()
sage: type(e)
<... 'cy pari2.gen.Gen'>
sage: e.type()
't_VEC'
sage: e.disc()
37.00000000000000

```

Over a finite field:

```

sage: EllipticCurve(GF(41), [2, 5]).pari_curve()
[Mod(0, 41), Mod(0, 41), Mod(0, 41), Mod(2, 41), Mod(5, 41), Mod(0, 41), ↵
↵Mod(4, 41), Mod(20, 41), Mod(37, 41), Mod(27, 41), Mod(26, 41), Mod(4, 41), ↵
↵Mod(11, 41), Vecsmall([3]), [41, [9, 31, [6, 0, 0, 0]]], [0, 0, 0, 0]]

```

Over a  $p$ -adic field:

```

sage: Qp = pAdicField(5, prec=3)
sage: E = EllipticCurve(Qp, [3, 4])
sage: E.pari_curve()
[0, 0, 0, 3, 4, 0, 6, 16, -9, -144, -3456, -8640, 1728/5, Vecsmall([2]), [0(5^↵
↵3)], [0, 0]]
sage: E.j_invariant()
3*5^-1 + O(5)

```

PARI no longer requires that the  $j$ -invariant has negative  $p$ -adic valuation:

```

sage: E = EllipticCurve(Qp, [1, 1])
sage: E.j_invariant() # the j-invariant is a p-adic integer
2 + 4*5^2 + O(5^3)
sage: E.pari_curve()
[0, 0, 0, 1, 1, 0, 2, 4, -1, -48, -864, -496, 6912/31, Vecsmall([2]), [0(5^↵
↵3)], [0, 0]]

```

**plot** ( $xmin=None$ ,  $xmax=None$ ,  $components='both'$ ,  $**args$ )

Draw a graph of this elliptic curve.

The plot method is only implemented when there is a natural coercion from the base ring of `self` to `RR`. In this case, `self` is plotted as if it was defined over `RR`.

INPUT:

- `xmin`, `xmax` - (optional) points will be computed at least within this range, but possibly farther.
- `components` - a string, one of the following:
  - `both` – (default), scale so that both bounded and unbounded components appear
  - `bounded` – scale the plot to show the bounded component. Raises an error if there is only one real component.
  - `unbounded` – scale the plot to show the unbounded component, including the two flex points.
- `plot_points` – passed to `sage.plot.generate_plot_points()`
- `adaptive_tolerance` – passed to `sage.plot.generate_plot_points()`
- `adaptive_recursion` – passed to `sage.plot.generate_plot_points()`
- `randomize` – passed to `sage.plot.generate_plot_points()`

- `**args` - all other options are passed to `sage.plot.line.Line`

EXAMPLES:

```
sage: E = EllipticCurve([0,-1])
sage: plot(E, rgbcolor=hue(0.7))
Graphics object consisting of 1 graphics primitive
sage: E = EllipticCurve('37a')
sage: plot(E)
Graphics object consisting of 2 graphics primitives
sage: plot(E, xmin=25,xmax=26)
Graphics object consisting of 2 graphics primitives
```

With [trac ticket #12766](#) we added the `components` keyword:

```
sage: E.real_components()
2
sage: E.plot(components='bounded')
Graphics object consisting of 1 graphics primitive
sage: E.plot(components='unbounded')
Graphics object consisting of 1 graphics primitive
```

If there is only one component then specifying `components='bounded'` raises a `ValueError`:

```
sage: E = EllipticCurve('9990be2')
sage: E.plot(components='bounded')
Traceback (most recent call last):
...
ValueError: no bounded component for this curve
```

An elliptic curve defined over the Complex Field can not be plotted:

```
sage: E = EllipticCurve(CC, [0,0,1,-1,0])
sage: E.plot()
Traceback (most recent call last):
...
NotImplementedError: Plotting of curves over Complex Field with 53 bits of_
↳precision not implemented yet
```

**`rst_transform`**( $r, s, t$ )

Returns the transform of the curve by  $(r, s, t)$  (with  $u = 1$ ).

INPUT:

- $r, s, t$  – three elements of the base ring.

OUTPUT:

The elliptic curve obtained from self by the standard Weierstrass transformation  $(u, r, s, t)$  with  $u = 1$ .

---

**Note:** This is just a special case of `change_weierstrass_model()`, with  $u = 1$ .

---

EXAMPLES:

```
sage: R.<r,s,t>=QQ[]
sage: E=EllipticCurve([1,2,3,4,5])
sage: E.rst_transform(r,s,t)
Elliptic Curve defined by  $y^2 + (2*s+1)*x*y + (r+2*t+3)*y = x^3 + (-s^2+3*r-$ 
↳ $s+2)*x^2 + (3*r^2-r*s-2*s*t+4*r-3*s-t+4)*x + (r^3+2*r^2-r*t-t^2+4*r-3*t+5)$ 
↳over Multivariate Polynomial Ring in  $r, s, t$  over Rational Field
```

**scale\_curve** (*u*)

Returns the transform of the curve by scale factor *u*.

INPUT:

- *u* – an invertible element of the base ring.

OUTPUT:

The elliptic curve obtained from self by the standard Weierstrass transformation  $(u, r, s, t)$  with  $r = s = t = 0$ .

---

**Note:** This is just a special case of `change_weierstrass_model()`, with  $r = s = t = 0$ .

---

EXAMPLES:

```
sage: K=Frac(PolynomialRing(QQ, 'u'))
sage: u=K.gen()
sage: E=EllipticCurve([1,2,3,4,5])
sage: E.scale_curve(u)
Elliptic Curve defined by  $y^2 + u*x*y + 3*u^3*y = x^3 + 2*u^2*x^2 + 4*u^4*x + 5*u^6$  over Fraction Field of Univariate Polynomial Ring in u over Rational Field
```

**short\_weierstrass\_model** (*complete\_cube=True*)

Returns a short Weierstrass model for self.

INPUT:

- *complete\_cube* - bool (default: True); for meaning, see below.

OUTPUT:

An elliptic curve.

If *complete\_cube*=True: Return a model of the form  $y^2 = x^3 + a*x + b$  for this curve. The characteristic must not be 2; in characteristic 3, it is only possible if  $b_2 = 0$ .

If *complete\_cube*=False: Return a model of the form  $y^2 = x^3 + ax^2 + bx + c$  for this curve. The characteristic must not be 2.

EXAMPLES:

```
sage: E = EllipticCurve([1,2,3,4,5])
sage: E
Elliptic Curve defined by  $y^2 + x*y + 3*y = x^3 + 2*x^2 + 4*x + 5$  over Rational Field
sage: F = E.short_weierstrass_model()
sage: F
Elliptic Curve defined by  $y^2 = x^3 + 4941*x + 185166$  over Rational Field
sage: E.is_isomorphic(F)
True
sage: F = E.short_weierstrass_model(complete_cube=False)
sage: F
Elliptic Curve defined by  $y^2 = x^3 + 9*x^2 + 88*x + 464$  over Rational Field
sage: E.is_isomorphic(F)
True
```

```
sage: E = EllipticCurve(GF(3), [1, 2, 3, 4, 5])
sage: E.short_weierstrass_model(complete_cube=False)
Elliptic Curve defined by  $y^2 = x^3 + x + 2$  over Finite Field of size 3
```

This used to be different see [trac ticket #3973](#):

```
sage: E.short_weierstrass_model()
Elliptic Curve defined by  $y^2 = x^3 + x + 2$  over Finite Field of size 3
```

More tests in characteristic 3:

```
sage: E = EllipticCurve(GF(3), [0, 2, 1, 2, 1])
sage: E.short_weierstrass_model()
Traceback (most recent call last):
...
ValueError: short_weierstrass_model(): no short model for Elliptic Curve,
↳ defined by  $y^2 + y = x^3 + 2x^2 + 2x + 1$  over Finite Field of size 3
↳ (characteristic is 3)
sage: E.short_weierstrass_model(complete_cube=False)
Elliptic Curve defined by  $y^2 = x^3 + 2x^2 + 2x + 2$  over Finite Field of
↳ size 3
sage: E.short_weierstrass_model(complete_cube=False).is_isomorphic(E)
True
```

**torsion\_polynomial** (*m*, *x*=None, *two\_torsion\_multiplicity*=2)

Returns the  $m^{\text{th}}$  division polynomial of this elliptic curve evaluated at *x*.

INPUT:

- *m* - positive integer.
- *x* - optional ring element to use as the “*x*” variable. If *x* is None, then a new polynomial ring will be constructed over the base ring of the elliptic curve, and its generator will be used as *x*. Note that *x* does not need to be a generator of a polynomial ring; any ring element is ok. This permits fast calculation of the torsion polynomial *evaluated* on any element of a ring.
- *two\_torsion\_multiplicity* - 0, 1 or 2

If 0: for even *m* when *x* is None, a univariate polynomial over the base ring of the curve is returned, which omits factors whose roots are the *x*-coordinates of the 2-torsion points. Similarly when *x* is not none, the evaluation of such a polynomial at *x* is returned.

If 2: for even *m* when *x* is None, a univariate polynomial over the base ring of the curve is returned, which includes a factor of degree 3 whose roots are the *x*-coordinates of the 2-torsion points. Similarly when *x* is not none, the evaluation of such a polynomial at *x* is returned.

If 1: when *x* is None, a bivariate polynomial over the base ring of the curve is returned, which includes a factor  $2*y + a1*x + a3$  which has simple zeros at the 2-torsion points. When *x* is not none, it should be a tuple of length 2, and the evaluation of such a polynomial at *x* is returned.

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: E.division_polynomial(1)
1
sage: E.division_polynomial(2, two_torsion_multiplicity=0)
1
sage: E.division_polynomial(2, two_torsion_multiplicity=1)
```

```

2*y + 1
sage: E.division_polynomial(2, two_torsion_multiplicity=2)
4*x^3 - 4*x + 1
sage: E.division_polynomial(2)
4*x^3 - 4*x + 1
sage: [E.division_polynomial(3, two_torsion_multiplicity=i) for i in range(3)]
[3*x^4 - 6*x^2 + 3*x - 1, 3*x^4 - 6*x^2 + 3*x - 1, 3*x^4 - 6*x^2 + 3*x - 1]
sage: [type(E.division_polynomial(3, two_torsion_multiplicity=i)) for i in
↪range(3)]
[<... 'sage.rings.polynomial.polynomial_rational_flint.Polynomial_rational_
↪flint'>,
<... 'sage.rings.polynomial.multi_polynomial_libsingular.MPolynomial_
↪libsingular'>,
<... 'sage.rings.polynomial.polynomial_rational_flint.Polynomial_rational_
↪flint'>]

```

```

sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: R.<z>=PolynomialRing(QQ)
sage: E.division_polynomial(4,z,0)
2*z^6 - 4*z^5 - 100*z^4 - 790*z^3 - 210*z^2 - 1496*z - 5821
sage: E.division_polynomial(4,z)
8*z^9 - 24*z^8 - 464*z^7 - 2758*z^6 + 6636*z^5 + 34356*z^4 + 53510*z^3 +
↪99714*z^2 + 351024*z + 459859

```

This does not work, since when `two_torsion_multiplicity` is 1, we compute a bivariate polynomial, and must evaluate at a tuple of length 2:

```

sage: E.division_polynomial(4,z,1)
Traceback (most recent call last):
...
ValueError: x should be a tuple of length 2 (or None) when two_torsion_
↪multiplicity is 1
sage: R.<z,w>=PolynomialRing(QQ,2)
sage: E.division_polynomial(4,(z,w),1).factor()
(2*w + 1) * (2*z^6 - 4*z^5 - 100*z^4 - 790*z^3 - 210*z^2 - 1496*z - 5821)

```

We can also evaluate this bivariate polynomial at a point:

```

sage: P = E(5,5)
sage: E.division_polynomial(4,P,two_torsion_multiplicity=1)
-1771561

```

#### `two_division_polynomial` ( $x=None$ )

Returns the 2-division polynomial of this elliptic curve evaluated at  $x$ .

INPUT:

- $x$  - optional ring element to use as the  $x$  variable. If  $x$  is `None`, then a new polynomial ring will be constructed over the base ring of the elliptic curve, and its generator will be used as  $x$ . Note that  $x$  does not need to be a generator of a polynomial ring; any ring element is ok. This permits fast calculation of the torsion polynomial *evaluated* on any element of a ring.

EXAMPLES:

```

sage: E=EllipticCurve('5077a1')
sage: E.two_division_polynomial()
4*x^3 - 28*x + 25
sage: E=EllipticCurve(GF(3^2,'a'),[1,1,1,1,1])

```

```
sage: E.two_division_polynomial()
x^3 + 2*x^2 + 2
sage: E.two_division_polynomial().roots()
[(2, 1), (2*a, 1), (a + 2, 1)]
```

`sage.schemes.elliptic_curves.ell_generic.is_EllipticCurve(x)`

Utility function to test if `x` is an instance of an Elliptic Curve class.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_generic import is_EllipticCurve
sage: E = EllipticCurve([1,2,3/4,7,19])
sage: is_EllipticCurve(E)
True
sage: is_EllipticCurve(0)
False
```

## 15.5 Elliptic curves over a general field

This module defines the class `EllipticCurve_field`, based on `EllipticCurve_generic`, for elliptic curves over general fields.

**class** `sage.schemes.elliptic_curves.ell_field.EllipticCurve_field(K, ainvs)`  
 Bases: `sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic`

**base\_field()**

Returns the base ring of the elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve(GF(49, 'a'), [3,5])
sage: E.base_ring()
Finite Field in a of size 7^2
```

```
sage: E = EllipticCurve([1,1])
sage: E.base_ring()
Rational Field
```

```
sage: E = EllipticCurve(ZZ, [3,5])
sage: E.base_ring()
Integer Ring
```

**descend\_to(*K*, *f*=None)**

Given an elliptic curve self defined over a field  $L$  and a subfield  $K$  of  $L$ , return all elliptic curves over  $K$  which are isomorphic over  $L$  to self.

INPUT:

- $K$  – a field which embeds into the base field  $L$  of self.
- $f$  (optional) – an embedding of  $K$  into  $L$ . Ignored if  $K$  is  $\mathbb{Q}$ .

OUTPUT:

A list (possibly empty) of elliptic curves defined over  $K$  which are isomorphic to self over  $L$ , up to isomorphism over  $K$ .



**Note:** Currently only implemented over number fields. To extend to other fields of characteristic not 2 or 3, what is needed is a method giving the preimages in  $K^*/(K^*)^m$  of an element of the base field, for  $m = 2, 4, 6$ .

EXAMPLES:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.descend_to(ZZ)
Traceback (most recent call last):
...
TypeError: Input must be a field.
```

```
sage: F.<b> = QuadraticField(23)
sage: G.<a> = F.extension(x^3+5)
sage: E = EllipticCurve(j=1728*b).change_ring(G)
sage: EF = E.descend_to(F); EF
[Elliptic Curve defined by y^2 = x^3 + (27*b-621)*x + (-1296*b+2484) over_
↳Number Field in b with defining polynomial x^2 - 23]
sage: all([Ei.change_ring(G).is_isomorphic(E) for Ei in EF])
True
```

```
sage: L.<a> = NumberField(x^4 - 7)
sage: K.<b> = NumberField(x^2 - 7, embedding=a^2)
sage: E = EllipticCurve([a^6, 0])
sage: EK = E.descend_to(K); EK
[Elliptic Curve defined by y^2 = x^3 + b*x over Number Field in b with_
↳defining polynomial x^2 - 7,
Elliptic Curve defined by y^2 = x^3 + 7*b*x over Number Field in b with_
↳defining polynomial x^2 - 7]
sage: all([Ei.change_ring(L).is_isomorphic(E) for Ei in EK])
True
```

```
sage: K.<a> = QuadraticField(17)
sage: E = EllipticCurve(j = 2*a)
sage: E.descend_to(QQ)
[]
```

**genus ()**

Return 1 for elliptic curves.

EXAMPLES:

```
sage: E = EllipticCurve(GF(3), [0, -1, 0, -346, 2652])
sage: E.genus()
1

sage: R = FractionField(QQ['z'])
sage: E = EllipticCurve(R, [0, -1, 0, -346, 2652])
sage: E.genus()
1
```

**hasse\_invariant ()**

Return the Hasse invariant of this elliptic curve.

OUTPUT:

The Hasse invariant of this elliptic curve, as an element of the base field. This is only defined over fields of positive characteristic, and is an element of the field which is zero if and only if the curve is supersingular. Over a field of characteristic zero, where the Hasse invariant is undefined, a `ValueError` is returned.

EXAMPLES:

```
sage: E = EllipticCurve([Mod(1,2),Mod(1,2),0,0,Mod(1,2)])
sage: E.hasse_invariant()
1
sage: E = EllipticCurve([0,0,Mod(1,3),Mod(1,3),Mod(1,3)])
sage: E.hasse_invariant()
0
sage: E = EllipticCurve([0,0,Mod(1,5),0,Mod(2,5)])
sage: E.hasse_invariant()
0
sage: E = EllipticCurve([0,0,Mod(1,5),Mod(1,5),Mod(2,5)])
sage: E.hasse_invariant()
2
```

Some examples over larger fields:

```
sage: EllipticCurve(GF(101),[0,0,0,0,1]).hasse_invariant()
0
sage: EllipticCurve(GF(101),[0,0,0,1,1]).hasse_invariant()
98
sage: EllipticCurve(GF(103),[0,0,0,0,1]).hasse_invariant()
20
sage: EllipticCurve(GF(103),[0,0,0,1,1]).hasse_invariant()
17
sage: F.<a> = GF(107^2)
sage: EllipticCurve(F,[0,0,0,a,1]).hasse_invariant()
62*a + 75
sage: EllipticCurve(F,[0,0,0,0,a]).hasse_invariant()
0
```

Over fields of characteristic zero, the Hasse invariant is undefined:

```
sage: E = EllipticCurve([0,0,0,0,1])
sage: E.hasse_invariant()
Traceback (most recent call last):
...
ValueError: Hasse invariant only defined in positive characteristic
```

**is\_isogenous** (*other*, *field=None*)

Return whether or not self is isogenous to other.

INPUT:

- *other* – another elliptic curve.
- *field* (default None) – Currently not implemented. A field containing the base fields of the two elliptic curves onto which the two curves may be extended to test if they are isogenous over this field. By default `is_isogenous` will not try to find this field unless one of the curves can be extended into the base field of the other, in which case it will test over the larger base field.

OUTPUT:

(bool) True if there is an isogeny from curve `self` to curve `other` defined over `field`.

METHOD:

Over general fields this is only implemented in trivial cases.

EXAMPLES:

```
sage: E1 = EllipticCurve(CC, [1,18]); E1
Elliptic Curve defined by  $y^2 = x^3 + 1.000000000000000x + 18.00000000000000$ 
↳over Complex Field with 53 bits of precision
sage: E2 = EllipticCurve(CC, [2,7]); E2
Elliptic Curve defined by  $y^2 = x^3 + 2.000000000000000x + 7.00000000000000$ 
↳over Complex Field with 53 bits of precision
sage: E1.is_isogenous(E2)
Traceback (most recent call last):
...
NotImplementedError: Only implemented for isomorphic curves over general
↳fields.

sage: E1 = EllipticCurve(Frac(PolynomialRing(ZZ, 't')), [2,19]); E1
Elliptic Curve defined by  $y^2 = x^3 + 2x + 19$  over Fraction Field of
↳Univariate Polynomial Ring in t over Integer Ring
sage: E2 = EllipticCurve(CC, [23,4]); E2
Elliptic Curve defined by  $y^2 = x^3 + 23.00000000000000x + 4.00000000000000$ 
↳over Complex Field with 53 bits of precision
sage: E1.is_isogenous(E2)
Traceback (most recent call last):
...
NotImplementedError: Only implemented for isomorphic curves over general
↳fields.
```

**is\_quadratic\_twist** (*other*)

Determine whether this curve is a quadratic twist of another.

INPUT:

- *other* – an elliptic curves with the same base field as self.

OUTPUT:

Either 0, if the curves are not quadratic twists, or  $D$  if *other* is *self*.quadratic\_twist( $D$ ) (up to isomorphism). If *self* and *other* are isomorphic, returns 1.

If the curves are defined over  $\mathbb{Q}$ , the output  $D$  is a squarefree integer.

---

**Note:** Not fully implemented in characteristic 2, or in characteristic 3 when both  $j$ -invariants are 0.

---

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: Et = E.quadratic_twist(-24)
sage: E.is_quadratic_twist(Et)
-6

sage: E1=EllipticCurve([0,0,1,0,0])
sage: E1.j_invariant()
0
sage: E2=EllipticCurve([0,0,0,0,2])
sage: E1.is_quadratic_twist(E2)
2
sage: E1.is_quadratic_twist(E1)
1
```

```
sage: type(E1.is_quadratic_twist(E1)) == type(E1.is_quadratic_twist(E2))
↪ #trac 6574
True
```

```
sage: E1=EllipticCurve([0,0,0,1,0])
sage: E1.j_invariant()
1728
sage: E2=EllipticCurve([0,0,0,2,0])
sage: E1.is_quadratic_twist(E2)
0
sage: E2=EllipticCurve([0,0,0,25,0])
sage: E1.is_quadratic_twist(E2)
5
```

```
sage: F = GF(101)
sage: E1 = EllipticCurve(F, [4, 7])
sage: E2 = E1.quadratic_twist()
sage: D = E1.is_quadratic_twist(E2); D!=0
True
sage: F = GF(101)
sage: E1 = EllipticCurve(F, [4, 7])
sage: E2 = E1.quadratic_twist()
sage: D = E1.is_quadratic_twist(E2)
sage: E1.quadratic_twist(D).is_isomorphic(E2)
True
sage: E1.is_isomorphic(E2)
False
sage: F2 = GF(101^2, 'a')
sage: E1.change_ring(F2).is_isomorphic(E2.change_ring(F2))
True
```

A characteristic 3 example:

```
sage: F = GF(3^5, 'a')
sage: E1 = EllipticCurve_from_j(F(1))
sage: E2 = E1.quadratic_twist(-1)
sage: D = E1.is_quadratic_twist(E2); D!=0
True
sage: E1.quadratic_twist(D).is_isomorphic(E2)
True
```

```
sage: E1 = EllipticCurve_from_j(F(0))
sage: E2 = E1.quadratic_twist()
sage: D = E1.is_quadratic_twist(E2); D
1
sage: E1.is_isomorphic(E2)
True
```

### **is\_quartic\_twist** (*other*)

Determine whether this curve is a quartic twist of another.

INPUT:

- *other* – an elliptic curves with the same base field as self.

OUTPUT:

Either 0, if the curves are not quartic twists, or *D* if *other* is `self.quartic_twist(D)` (up to

isomorphism). If `self` and `other` are isomorphic, returns 1.

---

**Note:** Not fully implemented in characteristics 2 or 3.

---

EXAMPLES:

```
sage: E = EllipticCurve_from_j(GF(13)(1728))
sage: E1 = E.quartic_twist(2)
sage: D = E.is_quartic_twist(E1); D!=0
True
sage: E.quartic_twist(D).is_isomorphic(E1)
True
```

```
sage: E = EllipticCurve_from_j(1728)
sage: E1 = E.quartic_twist(12345)
sage: D = E.is_quartic_twist(E1); D
15999120
sage: (D/12345).is_perfect_power(4)
True
```

**is\_sextic\_twist** (*other*)

Determine whether this curve is a sextic twist of another.

INPUT:

- `other` – an elliptic curves with the same base field as `self`.

OUTPUT:

Either 0, if the curves are not sextic twists, or  $D$  if `other` is `self.sextic_twist(D)` (up to isomorphism). If `self` and `other` are isomorphic, returns 1.

---

**Note:** Not fully implemented in characteristics 2 or 3.

---

EXAMPLES:

```
sage: E = EllipticCurve_from_j(GF(13)(0))
sage: E1 = E.sextic_twist(2)
sage: D = E.is_sextic_twist(E1); D!=0
True
sage: E.sextic_twist(D).is_isomorphic(E1)
True
```

```
sage: E = EllipticCurve_from_j(0)
sage: E1 = E.sextic_twist(12345)
sage: D = E.is_sextic_twist(E1); D
575968320
sage: (D/12345).is_perfect_power(6)
True
```

**isogenies\_prime\_degree** ( $l=None$ ,  $max\_l=31$ )

Generic code, valid for all fields, for arbitrary prime  $l$  not equal to the characteristic.

INPUT:

- `l` – either `None`, a prime or a list of primes.

- `max_l` – a bound on the primes to be tested (ignored unless `l` is None).

OUTPUT:

(list) All  $l$ -isogenies for the given  $l$  with domain self.

METHOD:

Calls the generic function `isogenies_prime_degree()`. This requires that certain operations have been implemented over the base field, such as root-finding for univariate polynomials.

EXAMPLES:

```
sage: F = QQbar
sage: E = EllipticCurve(F, [1,18]); E
Elliptic Curve defined by  $y^2 = x^3 + x + 18$  over Algebraic Field
sage: E.isogenies_prime_degree()
Traceback (most recent call last):
...
NotImplementedError: This code could be implemented for QQbar, but has not
↳ been yet.

sage: F = CC
sage: E = EllipticCurve(F, [1,18]); E
Elliptic Curve defined by  $y^2 = x^3 + 1.000000000000000*x + 18.00000000000000$ 
↳ over Complex Field with 53 bits of precision
sage: E.isogenies_prime_degree(11)
Traceback (most recent call last):
...
NotImplementedError: This code could be implemented for general complex
↳ fields, but has not been yet.
```

Examples over finite fields:

```
sage: E = EllipticCurve(GF(next_prime(1000000)), [7,8])
sage: E.isogenies_prime_degree()
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over
↳ Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 +$ 
↳  $970389*x + 794257$  over Finite Field of size 1000003, Isogeny of degree 2
↳ from Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of
↳ size 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 29783*x + 206196$  over
↳ Finite Field of size 1000003, Isogeny of degree 2 from Elliptic Curve
↳ defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of size 1000003 to
↳ Elliptic Curve defined by  $y^2 = x^3 + 999960*x + 78$  over Finite Field of
↳ size 1000003, Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3$ 
↳  $+ 7*x + 8$  over Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 =$ 
↳  $x^3 + 878063*x + 845666$  over Finite Field of size 1000003, Isogeny of
↳ degree 13 from Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over Finite
↳ Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 375648*x +$ 
↳  $342776$  over Finite Field of size 1000003, Isogeny of degree 17 from
↳ Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of size
↳ 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 347438*x + 594729$  over
↳ Finite Field of size 1000003, Isogeny of degree 17 from Elliptic Curve
↳ defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of size 1000003 to
↳ Elliptic Curve defined by  $y^2 = x^3 + 674846*x + 7392$  over Finite Field of
↳ size 1000003, Isogeny of degree 23 from Elliptic Curve defined by  $y^2 = x^3$ 
↳  $+ 7*x + 8$  over Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 =$ 
↳  $x^3 + 390065*x + 605596$  over Finite Field of size 1000003]
sage: E.isogenies_prime_degree(2)
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over
↳ Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 +$ 
↳  $970389*x + 794257$  over Finite Field of size 1000003, Isogeny of degree 2
↳ from Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of
↳ size 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 29783*x + 206196$  over
↳ Finite Field of size 1000003, Isogeny of degree 2 from Elliptic Curve
↳ defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of size 1000003 to
↳ Elliptic Curve defined by  $y^2 = x^3 + 999960*x + 78$  over Finite Field of
↳ size 1000003, Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3$ 
↳  $+ 7*x + 8$  over Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 =$ 
↳  $x^3 + 878063*x + 845666$  over Finite Field of size 1000003, Isogeny of
↳ degree 13 from Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over Finite
↳ Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 375648*x +$ 
↳  $342776$  over Finite Field of size 1000003, Isogeny of degree 17 from
↳ Elliptic Curve defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of size
↳ 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 347438*x + 594729$  over
↳ Finite Field of size 1000003, Isogeny of degree 17 from Elliptic Curve
↳ defined by  $y^2 = x^3 + 7*x + 8$  over Finite Field of size 1000003 to
↳ Elliptic Curve defined by  $y^2 = x^3 + 674846*x + 7392$  over Finite Field of
↳ size 1000003, Isogeny of degree 23 from Elliptic Curve defined by  $y^2 = x^3$ 
↳  $+ 7*x + 8$  over Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 =$ 
↳  $x^3 + 390065*x + 605596$  over Finite Field of size 1000003]
```

```

sage: E.isogenies_prime_degree(3)
[]
sage: E.isogenies_prime_degree(5)
[]
sage: E.isogenies_prime_degree(7)
[]
sage: E.isogenies_prime_degree(13)
[Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3 + 7x + 8$  over
↳ Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 +$ 
↳  $878063x + 845666$  over Finite Field of size 1000003,
Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3 + 7x + 8$  over
↳ Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 +$ 
↳  $375648x + 342776$  over Finite Field of size 1000003]

sage: E.isogenies_prime_degree([2, 3, 5, 7, 13])
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 7x + 8$  over
↳ Finite Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 +$ 
↳  $970389x + 794257$  over Finite Field of size 1000003, Isogeny of degree 2
↳ from Elliptic Curve defined by  $y^2 = x^3 + 7x + 8$  over Finite Field of
↳ size 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 29783x + 206196$  over
↳ Finite Field of size 1000003, Isogeny of degree 2 from Elliptic Curve
↳ defined by  $y^2 = x^3 + 7x + 8$  over Finite Field of size 1000003 to
↳ Elliptic Curve defined by  $y^2 = x^3 + 999960x + 78$  over Finite Field of
↳ size 1000003, Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3$ 
↳  $+ 7x + 8$  over Finite Field of size 1000003 to Elliptic Curve defined by  $y^$ 
↳  $^2 = x^3 + 878063x + 845666$  over Finite Field of size 1000003, Isogeny of
↳ degree 13 from Elliptic Curve defined by  $y^2 = x^3 + 7x + 8$  over Finite
↳ Field of size 1000003 to Elliptic Curve defined by  $y^2 = x^3 + 375648x +$ 
↳  $342776$  over Finite Field of size 1000003]
sage: E.isogenies_prime_degree([2, 4])
Traceback (most recent call last):
...
ValueError: 4 is not prime.
sage: E.isogenies_prime_degree(4)
Traceback (most recent call last):
...
ValueError: 4 is not prime.
sage: E.isogenies_prime_degree(11)
[]
sage: E = EllipticCurve(GF(17), [2, 0])
sage: E.isogenies_prime_degree(3)
[]
sage: E.isogenies_prime_degree(2)
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 2x$  over
↳ Finite Field of size 17 to Elliptic Curve defined by  $y^2 = x^3 + 9x$  over
↳ Finite Field of size 17, Isogeny of degree 2 from Elliptic Curve defined by
↳  $y^2 = x^3 + 2x$  over Finite Field of size 17 to Elliptic Curve defined by  $y^$ 
↳  $^2 = x^3 + 5x + 9$  over Finite Field of size 17, Isogeny of degree 2 from
↳ Elliptic Curve defined by  $y^2 = x^3 + 2x$  over Finite Field of size 17 to
↳ Elliptic Curve defined by  $y^2 = x^3 + 5x + 8$  over Finite Field of size 17]

sage: E = EllipticCurve(GF(13^4, 'a'), [2, 8])
sage: E.isogenies_prime_degree(2)
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 2x + 8$  over
↳ Finite Field in a of size  $13^4$  to Elliptic Curve defined by  $y^2 = x^3 + 7x$ 
↳  $+ 4$  over Finite Field in a of size  $13^4$ , Isogeny of degree 2 from Elliptic
↳ Curve defined by  $y^2 = x^3 + 2x + 8$  over Finite Field in a of size  $13^4$  to
↳ Elliptic Curve defined by  $y^2 = x^3 + (8a^3 + 2a^2 + 7a + 5)x + (12a^3 + 3a^$ 
↳  $^2 + 4a + 4)$  over Finite Field in a of size  $13^4$ , Isogeny of degree 2 from
↳ Elliptic Curve defined by  $y^2 = x^3 + 2x + 8$  over Finite Field in a of
↳ size  $13^4$  to Elliptic Curve defined by  $y^2 = x^3 + (5a^3 + 11a^2 + 6a + 11)x$ 
↳  $+ (a^3 + 10a^2 + 9a)$  over Finite Field in a of size  $13^4$ ]

```

```

sage: E.isogenies_prime_degree(3)
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 = x^3 + 2x + 8$  over
↪ Finite Field in  $a$  of size  $13^4$  to Elliptic Curve defined by  $y^2 = x^3 + 9x$ 
↪ + 11 over Finite Field in  $a$  of size  $13^4$ ]

```

Example to show that separable isogenies of degree equal to the characteristic are now implemented:

```

sage: E.isogenies_prime_degree(13)
[Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3 + 2x + 8$  over
↪ Finite Field in  $a$  of size  $13^4$  to Elliptic Curve defined by  $y^2 = x^3 + 6x$ 
↪ + 5 over Finite Field in  $a$  of size  $13^4$ ]

```

Examples over number fields (other than QQ):

```

sage: QQroot2.<e> = NumberField(x^2-2)
sage: E = EllipticCurve(QQroot2, j=8000)
sage: E.isogenies_prime_degree()
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + (-$ 
↪  $150528000)x + (-629407744000)$  over Number Field in  $e$  with defining
↪ polynomial  $x^2 - 2$  to Elliptic Curve defined by  $y^2 = x^3 + (-36750)x +$ 
↪  $2401000$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$ ,
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + (-150528000)x$ 
↪  $+ (-629407744000)$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$ 
↪ to Elliptic Curve defined by  $y^2 = x^3 + (220500e-257250)x + (54022500e-$ 
↪  $88837000)$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$ ,
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + (-150528000)x$ 
↪  $+ (-629407744000)$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$ 
↪ to Elliptic Curve defined by  $y^2 = x^3 + (-220500e-257250)x + (-$ 
↪  $54022500e-88837000)$  over Number Field in  $e$  with defining polynomial  $x^2 -$ 
↪  $2]$ 

sage: E = EllipticCurve(QQroot2, [1,0,1,4, -6]); E
Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x + (-6)$  over Number Field
↪ in  $e$  with defining polynomial  $x^2 - 2$ 
sage: E.isogenies_prime_degree(2)
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x$ 
↪  $+ (-6)$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$  to Elliptic
↪ Curve defined by  $y^2 + xy + y = x^3 + (-36)x + (-70)$  over Number Field in
↪  $e$  with defining polynomial  $x^2 - 2]$ 
sage: E.isogenies_prime_degree(3)
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x$ 
↪  $+ (-6)$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$  to Elliptic
↪ Curve defined by  $y^2 + xy + y = x^3 + (-1)x$  over Number Field in  $e$  with
↪ defining polynomial  $x^2 - 2$ ,
Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x$ 
↪  $+ (-6)$  over Number Field in  $e$  with defining polynomial  $x^2 - 2$  to Elliptic
↪ Curve defined by  $y^2 + xy + y = x^3 + (-171)x + (-874)$  over Number Field
↪ in  $e$  with defining polynomial  $x^2 - 2]$ 

```

**isogeny** (*kernel*, *codomain=None*, *degree=None*, *model=None*, *check=True*)

Return an elliptic curve isogeny from self.

The isogeny can be determined in two ways, either by a polynomial or a set of torsion points. The methods used are:

- **Velu's Formulas:** Velu's original formulas for computing isogenies. This algorithm is selected by giving as the `kernel` parameter a point or a list of points which generate a finite subgroup.



- **Kohel's Formulas:** Kohel's original formulas for computing isogenies. This algorithm is selected by giving as the `kernel` parameter a polynomial (or a coefficient list (little endian)) which will define the kernel of the isogeny.

INPUT:

- **E** - an elliptic curve, the domain of the isogeny to initialize.
- **kernel** - a kernel, either a point in E, a list of points in E, a univariate kernel polynomial or None. If initiating from a domain/codomain, this must be set to None. Validity of input is *not* fully checked.
- **codomain** - an elliptic curve (default:None). If **kernel** is None, then this must be the codomain of a separable normalized isogeny, furthermore, degree must be the degree of the isogeny from E to codomain. If **kernel** is not None, then this must be isomorphic to the codomain of the normalized separable isogeny defined by **kernel**, in this case, the isogeny is post composed with an isomorphism so that this parameter is the codomain.
- **degree** - an integer (default:None). If **kernel** is None, then this is the degree of the isogeny from E to codomain. If **kernel** is not None, then this is used to determine whether or not to skip a gcd of the kernel polynomial with the two torsion polynomial of E.
- **model** - a string (default:None). Only supported variable is "minimal", in which case if "E" is a curve over the rationals or over a number field, then the codomain is a global minimum model where this exists.
- **check** (default: True) does some partial checks that the input is valid (e.g., that the points defined by the kernel polynomial are torsion); however, invalid input can in some cases still pass, since that the points define a group is not checked.

OUTPUT:

An isogeny between elliptic curves. This is a morphism of curves.

EXAMPLES:

```
sage: F = GF(2^5, 'alpha'); alpha = F.gen()
sage: E = EllipticCurve(F, [1,0,1,1,1])
sage: R.<x> = F[]
sage: phi = E.isogeny(x+1)
sage: phi.rational_maps()
((x^2 + x + 1)/(x + 1), (x^2*y + x)/(x^2 + 1))

sage: E = EllipticCurve('11a1')
sage: P = E.torsion_points()[1]
sage: E.isogeny(P)
Isogeny of degree 5 from Elliptic Curve defined by y^2 + y = x^3 - x^2 - 10*x
↳ - 20 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - x^2 -
↳ 7820*x - 263580 over Rational Field

sage: E = EllipticCurve(GF(19), [1,1])
sage: P = E(15,3); Q = E(2,12);
sage: (P.order(), Q.order())
(7, 3)
sage: phi = E.isogeny([P,Q]); phi
Isogeny of degree 21 from Elliptic Curve defined by y^2 = x^3 + x + 1 over
↳ Finite Field of size 19 to Elliptic Curve defined by y^2 = x^3 + x + 1 over
↳ Finite Field of size 19
sage: phi(E.random_point()) # all points defined over GF(19) are in the kernel
(0 : 1 : 0)
```

Not all polynomials define a finite subgroup ([trac ticket #6384](#)):

```
sage: E = EllipticCurve(GF(31), [1, 0, 0, 1, 2])
sage: phi = E.isogeny([14, 27, 4, 1])
Traceback (most recent call last):
...
ValueError: The polynomial does not define a finite subgroup of the elliptic_
↪curve.
```

An example in which we construct an invalid morphism, which illustrates that the check for correctness of the input is not sufficient. (See [trac ticket #11578](#).):

```
sage: R.<x> = QQ[]
sage: K.<a> = NumberField(x^2-x-1)
sage: E = EllipticCurve(K, [-13392, -1080432])
sage: R.<x> = K[]
sage: phi = E.isogeny((x-564)*(x - 396/5*a + 348/5) )
sage: phi.codomain().conductor().norm().factor()
5^2 * 11^2 * 3271 * 15806939 * 4169267639351
sage: phi.domain().conductor().norm().factor()
11^2
```

**isogeny\_codomain** (*kernel*, *degree=None*)

Return the codomain of the isogeny from self with given kernel.

INPUT:

- **kernel** - Either a list of points in the kernel of the isogeny, or a kernel polynomial (specified as either a univariate polynomial or a coefficient list.)
- **degree** - an integer, (default:None) optionally specified degree of the kernel.

OUTPUT:

An elliptic curve, the codomain of the separable normalized isogeny from this kernel

EXAMPLES:

```
sage: E = EllipticCurve('17a1')
sage: R.<x> = QQ[]
sage: E2 = E.isogeny_codomain(x - 11/4); E2
Elliptic Curve defined by y^2 + x*y + y = x^3 - x^2 - 1461/16*x - 19681/64_
↪over Rational Field
```

**quadratic\_twist** (*D=None*)

Return the quadratic twist of this curve by  $D$ .

INPUT:

- $D$  (default None) the twisting parameter (see below).

In characteristics other than 2,  $D$  must be nonzero, and the twist is isomorphic to self after adjoining  $\sqrt{D}$  to the base.

In characteristic 2,  $D$  is arbitrary, and the twist is isomorphic to self after adjoining a root of  $x^2 + x + D$  to the base.

In characteristic 2 when  $j = 0$ , this is not implemented.

If the base field  $F$  is finite,  $D$  need not be specified, and the curve returned is the unique curve (up to isomorphism) defined over  $F$  isomorphic to the original curve over the quadratic extension of  $F$  but not over  $F$  itself. Over infinite fields, an error is raised if  $D$  is not given.

## EXAMPLES:

```

sage: E = EllipticCurve([GF(1103)(1), 0, 0, 107, 340]); E
Elliptic Curve defined by  $y^2 + x*y = x^3 + 107*x + 340$  over Finite Field of
↳size 1103
sage: F=E.quadratic_twist(-1); F
Elliptic Curve defined by  $y^2 = x^3 + 1102*x^2 + 609*x + 300$  over Finite
↳Field of size 1103
sage: E.is_isomorphic(F)
False
sage: E.is_isomorphic(F, GF(1103^2, 'a'))
True

```

## A characteristic 2 example:

```

sage: E=EllipticCurve(GF(2), [1,0,1,1,1])
sage: E1=E.quadratic_twist(1)
sage: E.is_isomorphic(E1)
False
sage: E.is_isomorphic(E1, GF(4, 'a'))
True

```

Over finite fields, the twisting parameter may be omitted:

```

sage: k.<a> = GF(2^10)
sage: E = EllipticCurve(k, [a^2, a, 1, a+1, 1])
sage: Et = E.quadratic_twist()
sage: Et # random (only determined up to isomorphism)
Elliptic Curve defined by  $y^2 + x*y = x^3 + (a^7+a^4+a^3+a^2+a+1)*x^2 + (a^8+a^6+a^4+1)$  over Finite Field in a of size 2^10
sage: E.is_isomorphic(Et)
False
sage: E.j_invariant()==Et.j_invariant()
True

sage: p=next_prime(10^10)
sage: k = GF(p)
sage: E = EllipticCurve(k, [1,2,3,4,5])
sage: Et = E.quadratic_twist()
sage: Et # random (only determined up to isomorphism)
Elliptic Curve defined by  $y^2 = x^3 + 7860088097*x^2 + 9495240877*x +$ 
↳3048660957 over Finite Field of size 10000000019
sage: E.is_isomorphic(Et)
False
sage: k2 = GF(p^2, 'a')
sage: E.change_ring(k2).is_isomorphic(Et.change_ring(k2))
True

```

**quartic\_twist(*D*)**

Return the quartic twist of this curve by *D*.

## INPUT:

- *D* (must be nonzero) – the twisting parameter..

---

**Note:** The characteristic must not be 2 or 3, and the *j*-invariant must be 1728.

---

## EXAMPLES:

```

sage: E=EllipticCurve_from_j(GF(13)(1728)); E
Elliptic Curve defined by  $y^2 = x^3 + x$  over Finite Field of size 13
sage: E1=E.quartic_twist(2); E1
Elliptic Curve defined by  $y^2 = x^3 + 5x$  over Finite Field of size 13
sage: E.is_isomorphic(E1)
False
sage: E.is_isomorphic(E1,GF(13^2,'a'))
False
sage: E.is_isomorphic(E1,GF(13^4,'a'))
True

```

**sextic\_twist(*D*)**

Return the quartic twist of this curve by  $D$ .

INPUT:

- $D$  (must be nonzero) – the twisting parameter..

---

**Note:** The characteristic must not be 2 or 3, and the  $j$ -invariant must be 0.

---

EXAMPLES:

```

sage: E=EllipticCurve_from_j(GF(13)(0)); E
Elliptic Curve defined by  $y^2 = x^3 + 1$  over Finite Field of size 13
sage: E1=E.sextic_twist(2); E1
Elliptic Curve defined by  $y^2 = x^3 + 11$  over Finite Field of size 13
sage: E.is_isomorphic(E1)
False
sage: E.is_isomorphic(E1,GF(13^2,'a'))
False
sage: E.is_isomorphic(E1,GF(13^4,'a'))
False
sage: E.is_isomorphic(E1,GF(13^6,'a'))
True

```

**two\_torsion\_rank()**

Return the dimension of the 2-torsion subgroup of  $E(K)$ .

This will be 0, 1 or 2.

EXAMPLES:

```

sage: E=EllipticCurve('11a1')
sage: E.two_torsion_rank()
0
sage: K.<alpha>=QQ.extension(E.division_polynomial(2).monic())
sage: E.base_extend(K).two_torsion_rank()
1
sage: E.reduction(53).two_torsion_rank()
2

```

```

sage: E = EllipticCurve('14a1')
sage: E.two_torsion_rank()
1
sage: K.<alpha>=QQ.extension(E.division_polynomial(2).monic().factor()[1][0])
sage: E.base_extend(K).two_torsion_rank()
2

```

```
sage: EllipticCurve('15a1').two_torsion_rank()
2
```

**weierstrass\_p** (*prec=20, algorithm=None*)

Computes the Weierstrass  $\wp$ -function of the elliptic curve.

INPUT:

- **mprec** - precision
- **algorithm** - string (default:None) an algorithm identifier indicating using the pari, fast or quadratic algorithm. If the algorithm is None, then this function determines the best algorithm to use.

OUTPUT:

a Laurent series in one variable  $z$  with coefficients in the base field  $k$  of  $E$ .

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.weierstrass_p(prec=10)
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + 77531/41580*z^8 + O(z^10)
sage: E.weierstrass_p(prec=8)
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + O(z^8)
sage: Esh = E.short_weierstrass_model()
sage: Esh.weierstrass_p(prec=8)
z^-2 + 13392/5*z^2 + 1080432/7*z^4 + 59781888/25*z^6 + O(z^8)
sage: E.weierstrass_p(prec=20, algorithm='fast')
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + 77531/41580*z^8 + 1202285717/
↪ 928746000*z^10 + 2403461/2806650*z^12 + 30211462703/43418875500*z^14 +
↪ 3539374016033/7723451736000*z^16 + 413306031683977/1289540602350000*z^18 +
↪ O(z^20)
sage: E.weierstrass_p(prec=20, algorithm='pari')
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + 77531/41580*z^8 + 1202285717/
↪ 928746000*z^10 + 2403461/2806650*z^12 + 30211462703/43418875500*z^14 +
↪ 3539374016033/7723451736000*z^16 + 413306031683977/1289540602350000*z^18 +
↪ O(z^20)
sage: E.weierstrass_p(prec=20, algorithm='quadratic')
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + 77531/41580*z^8 + 1202285717/
↪ 928746000*z^10 + 2403461/2806650*z^12 + 30211462703/43418875500*z^14 +
↪ 3539374016033/7723451736000*z^16 + 413306031683977/1289540602350000*z^18 +
↪ O(z^20)
```

## 15.6 Elliptic curves over finite fields

AUTHORS:

- William Stein (2005): Initial version
- Robert Bradshaw et al. . . .
- John Cremona (2008-02): Point counting and group structure for non-prime fields, Frobenius endomorphism and order, elliptic logs
- Mariah Lenox (2011-03): Added set\_order method

```
class sage.schemes.elliptic_curves.ell_finite_field.EllipticCurve_finite_field(K,
                                                                           ainv)
    Bases:
        sage.schemes.elliptic_curves.ell_field.EllipticCurve_field,
        sage.schemes.hyperelliptic_curves.hyperelliptic_finite_field.
        HyperellipticCurve_finite_field
```

Elliptic curve over a finite field.

EXAMPLES:

```
sage: EllipticCurve(GF(101), [2, 3])
Elliptic Curve defined by y^2 = x^3 + 2*x + 3 over Finite Field of size 101

sage: F=GF(101^2, 'a')
sage: EllipticCurve([F(2), F(3)])
Elliptic Curve defined by y^2 = x^3 + 2*x + 3 over Finite Field in a of size 101^2
↪2
```

Elliptic curves over  $\mathbf{Z}/N\mathbf{Z}$  with  $N$  prime are of type “elliptic curve over a finite field”:

```
sage: F = Zmod(101)
sage: EllipticCurve(F, [2, 3])
Elliptic Curve defined by y^2 = x^3 + 2*x + 3 over Ring of integers modulo 101
sage: E = EllipticCurve([F(2), F(3)])
sage: type(E)
<class 'sage.schemes.elliptic_curves.ell_finite_field.EllipticCurve_finite_field_
↪with_category'>
sage: E.category()
Category of schemes over Ring of integers modulo 101
```

Elliptic curves over  $\mathbf{Z}/N\mathbf{Z}$  with  $N$  composite are of type “generic elliptic curve”:

```
sage: F = Zmod(95)
sage: EllipticCurve(F, [2, 3])
Elliptic Curve defined by y^2 = x^3 + 2*x + 3 over Ring of integers modulo 95
sage: E = EllipticCurve([F(2), F(3)])
sage: type(E)
<class 'sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic_with_
↪category'>
sage: E.category()
Category of schemes over Ring of integers modulo 95
sage: TestSuite(E).run(skip=["_test_elements"])
```

**abelian\_group** (*debug=False*)

Returns the abelian group structure of the group of points on this elliptic curve.

**Warning:** The algorithm is definitely *not* intended for use with *large* finite fields! The factorization of the orders of elements must be feasible. Also, baby-step-giant-step methods are used which have space and time requirements which are  $O(\sqrt{q})$ .

**See also:**

If you do not need the complete abelian group structure but only generators of the group, use `gens()` which is much faster.

Also, the algorithm uses random points on the curve and hence the generators are likely to differ from one run to another; but the group is cached so the generators will not change in any one run of Sage.

INPUT:

- debug - (default: False): if True, print debugging messages

OUTPUT:

- an abelian group
- tuple of images of each of the generators of the abelian group as points on this curve

AUTHORS:

- John Cremona

EXAMPLES:

```
sage: E=EllipticCurve(GF(11), [2,5])
sage: E.abelian_group()
Additive abelian group isomorphic to Z/10 embedded in Abelian group of points
↪ on Elliptic Curve defined by  $y^2 = x^3 + 2x + 5$  over Finite Field of size
↪ 11
```

```
sage: E=EllipticCurve(GF(41), [2,5])
sage: E.abelian_group()
Additive abelian group isomorphic to  $Z/22 + Z/2 \dots$ 
```

```
sage: F.<a>=GF(3^6, 'a')
sage: E=EllipticCurve([a^4 + a^3 + 2*a^2 + 2*a, 2*a^5 + 2*a^3 + 2*a^2 + 1])
sage: E.abelian_group()
Additive abelian group isomorphic to  $Z/26 + Z/26 \dots$ 
```

```
sage: F.<a>=GF(101^3, 'a')
sage: E=EllipticCurve([2*a^2 + 48*a + 27, 89*a^2 + 76*a + 24])
sage: E.abelian_group()
Additive abelian group isomorphic to  $Z/1031352 \dots$ 
```

The group can be trivial:

```
sage: E=EllipticCurve(GF(2), [0,0,1,1,1])
sage: E.abelian_group()
Trivial group embedded in Abelian group of points on Elliptic Curve defined
↪ by  $y^2 + y = x^3 + x + 1$  over Finite Field of size 2
```

Of course, there are plenty of points if we extend the field:

```
sage: E.cardinality(extension_degree=100)
1267650600228231653296516890625
```

This tests the patch for [trac ticket #3111](#), using 10 primes randomly selected:

```
sage: E = EllipticCurve('389a')
sage: for p in [5927, 2297, 1571, 1709, 3851, 127, 3253, 5783, 3499, 4817]:
....:     G = E.change_ring(GF(p)).abelian_group()
sage: for p in prime_range(10000): # long time (19s on sage.math, 2011)
....:     if p != 389:
....:         G = E.change_ring(GF(p)).abelian_group()
```

This tests that the bug reported in [trac ticket #3926](#) has been fixed:

```

sage: K.<i> = QuadraticField(-1)
sage: OK = K.ring_of_integers()
sage: P=K.factor(10007)[0][0]
sage: OKmodP = OK.residue_field(P)
sage: E = EllipticCurve([0,0,0,i,i+3])
sage: Emod = E.change_ring(OKmodP); Emod
Elliptic Curve defined by y^2 = x^3 + ibar*x + (ibar+3) over Residue field
↪in ibar of Fractional ideal (10007)
sage: Emod.abelian_group() #random generators
(Multiplicative Abelian group isomorphic to C50067594 x C2,
((3152*ibar + 7679 : 7330*ibar + 7913 : 1), (8466*ibar + 1770 : 0 : 1)))

```

**cardinality** (*algorithm*='pari', *extension\_degree*=1)

Return the number of points on this elliptic curve.

INPUT:

- *algorithm* – string (default: 'pari'), used only for point counting over prime fields:
  - 'pari' – use the baby-step giant-step or Schoof-Elkies-Atkin methods as implemented in the PARI C-library function `ellap`
  - 'bsgs' – use the baby-step giant-step method as implemented in Sage, with the Cremona-Sutherland version of Mestre's trick
  - 'all' – compute cardinality with both 'pari' and 'bsgs'; return result if they agree or raise a `RuntimeError` if they do not
- *extension\_degree* – an integer  $d$  (default: 1): if the base field is  $\mathbf{F}_q$ , return the cardinality of `self` over the extension  $\mathbf{F}_{q^d}$  of degree  $d$ .

OUTPUT:

The order of the group of rational points of `self` over its base field, or over an extension field of degree  $d$  as above. The result is cached.

Over prime fields, one of the above algorithms is used. Over non-prime fields, the serious point counting is done on a standard curve with the same  $j$ -invariant over the field  $\mathbf{F}_p(j)$ , then lifted to the base field, and finally account is taken of twists.

For  $j = 0$  and  $j = 1728$  special formulas are used instead.

EXAMPLES:

```

sage: EllipticCurve(GF(4, 'a'), [1,2,3,4,5]).cardinality()
8
sage: k.<a> = GF(3^3)
sage: l = [a^2 + 1, 2*a^2 + 2*a + 1, a^2 + a + 1, 2, 2*a]
sage: EllipticCurve(k,l).cardinality()
29

```

```

sage: l = [1, 1, 0, 2, 0]
sage: EllipticCurve(k, l).cardinality()
38

```

An even bigger extension (which we check against Magma):

```

sage: EllipticCurve(GF(3^100, 'a'), [1,2,3,4,5]).cardinality()
515377520732011331036459693969645888996929981504

```



```
sage: magma.eval("Order(EllipticCurve([GF(3^100)|1,2,3,4,5]))") # optional_
↪- magma
'515377520732011331036459693969645888996929981504'
```

```
sage: EllipticCurve(GF(10007), [1,2,3,4,5]).cardinality()
10076
sage: EllipticCurve(GF(10007), [1,2,3,4,5]).cardinality(algorithm='pari')
10076
sage: EllipticCurve(GF(next_prime(10**20)), [1,2,3,4,5]).cardinality()
100000000011093199520
```

The cardinality is cached:

```
sage: E = EllipticCurve(GF(3^100, 'a'), [1,2,3,4,5])
sage: E.cardinality() is E.cardinality()
True
sage: E = EllipticCurve(GF(11^2, 'a'), [3,3])
sage: E.cardinality()
128
sage: EllipticCurve(GF(11^100, 'a'), [3,3]).cardinality()
13780612339822270184118337172089636776264331200038467184683526694179151034106556517649784650
```

#### **cardinality\_bsgs** (*verbose=False*)

Return the cardinality of self over the base field. Will be called by user function `cardinality` only when necessary, i.e. when the `j_invariant` is not in the prime field.

ALGORITHM: A variant of “Mestre’s trick” extended to all finite fields by Cremona and Sutherland, 2008.

---

#### **Note:**

1. The Mestre-Schoof-Cremona-Sutherland algorithm may fail for a small finite number of curves over  $F_q$  for  $q$  at most 49, so for  $q < 50$  we use an exhaustive count.
  2. Quadratic twists are not implemented in characteristic 2 when  $j = 0 (= 1728)$ ; but this case is treated separately.
- 

#### EXAMPLES:

```
sage: p=next_prime(10^3)
sage: E=EllipticCurve(GF(p), [3,4])
sage: E.cardinality_bsgs()
1020
sage: E=EllipticCurve(GF(3^4, 'a'), [1,1])
sage: E.cardinality_bsgs()
64
sage: F.<a>=GF(101^3, 'a')
sage: E=EllipticCurve([2*a^2 + 48*a + 27, 89*a^2 + 76*a + 24])
sage: E.cardinality_bsgs()
1031352
```

#### **cardinality\_exhaustive** ()

Return the cardinality of self over the base field. Simply adds up the number of points with each x-coordinate: only used for small field sizes!

#### EXAMPLES:

```

sage: p=next_prime(10^3)
sage: E=EllipticCurve(GF(p), [3,4])
sage: E.cardinality_exhaustive()
1020
sage: E=EllipticCurve(GF(3^4, 'a'), [1,1])
sage: E.cardinality_exhaustive()
64

```

**cardinality\_pari()**

Return the cardinality of self over the (prime) base field using PARI.

The result is not cached.

EXAMPLES:

```

sage: p=next_prime(10^3)
sage: E=EllipticCurve(GF(p), [3,4])
sage: E.cardinality_pari()
1020
sage: K=GF(next_prime(10^6))
sage: E=EllipticCurve(K, [1,0,0,1,1])
sage: E.cardinality_pari()
999945

```

**count\_points(n=1)**

Returns the cardinality of this elliptic curve over the base field or extensions.

INPUT:

- $n$  (int) – a positive integer

OUTPUT:

If  $n = 1$ , returns the cardinality of the curve over its base field.

If  $n > 1$ , returns a list  $[c_1, c_2, \dots, c_n]$  where  $c_d$  is the cardinality of the curve over the extension of degree  $d$  of its base field.

EXAMPLES:

```

sage: p = 101
sage: F = GF(p)
sage: E = EllipticCurve(F, [2,3])
sage: E.count_points(1)
96
sage: E.count_points(5)
[96, 10368, 1031904, 104053248, 10509895776]

```

```

sage: F.<a> = GF(p^2)
sage: E = EllipticCurve(F, [a,a])
sage: E.cardinality()
10295
sage: E.count_points()
10295
sage: E.count_points(1)
10295
sage: E.count_points(5)
[10295, 104072155, 1061518108880, 10828567126268595, 110462212555439192375]

```

**frobenius()**

Return the frobenius of self as an element of a quadratic order

---

**Note:** This computes the curve cardinality, which may be time-consuming.

---

Frobenius is only determined up to conjugacy.

EXAMPLES:

```
sage: E=EllipticCurve(GF(11), [3,3])
sage: E.frobenius()
phi
sage: E.frobenius().minpoly()
x^2 - 4*x + 11
```

For some supersingular curves, Frobenius is in Z:

```
sage: E=EllipticCurve(GF(25, 'a'), [0,0,0,0,1])
sage: E.frobenius()
-5
```

**frobenius\_order()**

Return the quadratic order  $\mathbb{Z}[\phi]$  where  $\phi$  is the Frobenius endomorphism of the elliptic curve

---

**Note:** This computes the curve cardinality, which may be time-consuming.

---

EXAMPLES:

```
sage: E=EllipticCurve(GF(11), [3,3])
sage: E.frobenius_order()
Order in Number Field in phi with defining polynomial x^2 - 4*x + 11
```

For some supersingular curves, Frobenius is in  $\mathbb{Z}$  and the Frobenius order is  $\mathbb{Z}$ :

```
sage: E=EllipticCurve(GF(25, 'a'), [0,0,0,0,1])
sage: R=E.frobenius_order()
sage: R
Order in Number Field in phi with defining polynomial x + 5
sage: R.degree()
1
```

**frobenius\_polynomial()**

Return the characteristic polynomial of Frobenius.

The Frobenius endomorphism of the elliptic curve has quadratic characteristic polynomial. In most cases this is irreducible and defines an imaginary quadratic order; for some supersingular curves, Frobenius is an integer  $a$  and the polynomial is  $(x - a)^2$ .

---

**Note:** This computes the curve cardinality, which may be time-consuming.

---

EXAMPLES:

```
sage: E=EllipticCurve(GF(11), [3,3])
sage: E.frobenius_polynomial()
x^2 - 4*x + 11
```

For some supersingular curves, Frobenius is in  $\mathbb{Z}$  and the polynomial is a square:

```
sage: E=EllipticCurve(GF(25,'a'),[0,0,0,0,1])
sage: E.frobenius_polynomial().factor()
(x + 5)^2
```

**gens()**

Return points which generate the abelian group of points on this elliptic curve.

OUTPUT: a tuple of points on the curve.

- if the group is trivial: an empty tuple.
- if the group is cyclic: a tuple with 1 point, a generator.
- if the group is not cyclic: a tuple with 2 points, where the order of the first point equals the exponent of the group.

**Warning:** In the case of 2 generators  $P$  and  $Q$ , it is not guaranteed that the group is the cartesian product of the 2 cyclic groups  $\langle P \rangle$  and  $\langle Q \rangle$ . In other words, the order of  $Q$  isn't as small as possible. If you really need to know the group structure, use `abelian_group()`.

EXAMPLES:

```
sage: E = EllipticCurve(GF(11),[2,5])
sage: P = E.gens()[0]; P # random
(0 : 7 : 1)
sage: E.cardinality(), P.order()
(10, 10)
sage: E = EllipticCurve(GF(41),[2,5])
sage: P, Q = E.gens(); P, Q # random
((30 : 13 : 1), (32 : 23 : 1))
sage: P.order()*Q.order()
484
sage: E.cardinality()
44
```

If the abelian group has been computed, return those generators instead:

```
sage: E.abelian_group()
Additive abelian group isomorphic to Z/22 + Z/2 embedded in Abelian group of
↳ points on Elliptic Curve defined by y^2 = x^3 + 2*x + 5 over Finite Field
↳ of size 41
sage: E.abelian_group().gens()
((30 : 13 : 1), (23 : 0 : 1))
sage: E.gens()
((30 : 13 : 1), (23 : 0 : 1))
sage: E.gens()[0].order()
22
sage: E.gens()[1].order()
2

sage: F.<a> = GF(3^6)
sage: E = EllipticCurve([a,a+1])
sage: pts = E.gens()
sage: len(pts)
```

```

1
sage: pts[0].order() == E.cardinality()
True
sage: E = EllipticCurve(GF(2), [0, 0, 1, 1, 1])
sage: E.gens()
()
```

This works over larger finite fields where :meth:abelian\_group may be too expensive:

```

sage: k.<a> = GF(5^60)
sage: E = EllipticCurve([a, a])
sage: len(E.gens())
2
sage: E.cardinality()          # known bug #16931
867361737988403547205571230383620219837340
sage: E.gens()[0].order()      # known bug #16931
433680868994201773602785615191810109918670
sage: E.gens()[1].order()      # known bug #16931
48186763221577974844753957243534456657630
```

**is\_isogenous** (*other, field=None, proof=True*)

Returns whether or not self is isogenous to other

INPUT:

- *other* – another elliptic curve.
- *field* (default None) – a field containing the base fields of the two elliptic curves into which the two curves may be extended to test if they are isogenous over this field. By default `is_isogenous` will not try to find this field unless one of the curves can be extended into the base field of the other, in which case it will test over the larger base field.
- *proof* (default True) – this parameter is here only to be consistent with versions for other types of elliptic curves.

OUTPUT:

(bool) True if there is an isogeny from curve *self* to curve *other* defined over *field*.

EXAMPLES:

```

sage: E1 = EllipticCurve(GF(11^2, 'a'), [2, 7]); E1
Elliptic Curve defined by y^2 = x^3 + 2*x + 7 over Finite Field in a of size_
↪ 11^2
sage: E1.is_isogenous(5)
Traceback (most recent call last):
...
ValueError: Second argument is not an Elliptic Curve.
sage: E1.is_isogenous(E1)
True

sage: E2 = EllipticCurve(GF(7^3, 'b'), [3, 1]); E2
Elliptic Curve defined by y^2 = x^3 + 3*x + 1 over Finite Field in b of size_
↪ 7^3
sage: E1.is_isogenous(E2)
Traceback (most recent call last):
...
ValueError: The base fields must have the same characteristic.

sage: E3 = EllipticCurve(GF(11^2, 'c'), [4, 3]); E3
```

```

Elliptic Curve defined by  $y^2 = x^3 + 4x + 3$  over Finite Field in c of size  $11^2$ 
↪11^2
sage: E1.is_isogenous(E3)
False

sage: E4 = EllipticCurve(GF(11^6, 'd'), [6, 5]); E4
Elliptic Curve defined by  $y^2 = x^3 + 6x + 5$  over Finite Field in d of size  $11^6$ 
↪11^6
sage: E1.is_isogenous(E4)
True

sage: E5 = EllipticCurve(GF(11^7, 'e'), [4, 2]); E5
Elliptic Curve defined by  $y^2 = x^3 + 4x + 2$  over Finite Field in e of size  $11^7$ 
↪11^7
sage: E1.is_isogenous(E5)
Traceback (most recent call last):
...
ValueError: Curves have different base fields: use the field parameter.

```

When the field is given:

```

sage: E1 = EllipticCurve(GF(13^2, 'a'), [2, 7]); E1 Elliptic Curve defined by  $y^2 = x^3 + 2x + 7$  over Finite Field in a of size  $13^2$ 
sage: E1.is_isogenous(5, GF(13^6, 'f'))
Traceback (most recent call last): ...
ValueError: Second argument is not an Elliptic Curve.
sage: E6 = EllipticCurve(GF(11^3, 'g'), [9, 3]); E6 Elliptic Curve defined by  $y^2 = x^3 + 9x + 3$  over Finite Field in g of size  $11^3$ 
sage: E1.is_isogenous(E6, QQ)
Traceback (most recent call last): ...
ValueError: The base fields must have the same characteristic.
sage: E7 = EllipticCurve(GF(13^5, 'h'), [2, 9]); E7 Elliptic Curve defined by  $y^2 = x^3 + 2x + 9$  over Finite Field in h of size  $13^5$ 
sage: E1.is_isogenous(E7, GF(13^4, 'i'))
Traceback (most recent call last): ...
ValueError: Field must be an extension of the base fields of both curves
sage: E1.is_isogenous(E7, GF(13^10, 'j'))
False
sage: E1.is_isogenous(E7, GF(13^30, 'j'))
False

```

**is\_ordinary** (*proof=True*)

Return True if this elliptic curve is ordinary, else False.

INPUT:

- *proof* (boolean, default True) – If True, returns a proved result. If False, then a return value of True is certain but a return value of False may be based on a probabilistic test. See the documentation of the function `is_j_supersingular()` for more details.

EXAMPLES:

```

sage: F = GF(101)
sage: EllipticCurve(j=F(0)).is_ordinary()
False
sage: EllipticCurve(j=F(1728)).is_ordinary()
True
sage: EllipticCurve(j=F(66)).is_ordinary()
False
sage: EllipticCurve(j=F(99)).is_ordinary()
True

```

**is\_supersingular** (*proof=True*)

Return True if this elliptic curve is supersingular, else False.

INPUT:

- *proof* (boolean, default True) – If True, returns a proved result. If False, then a return value of False

is certain but a return value of True may be based on a probabilistic test. See the documentation of the function `is_j_supersingular()` for more details.

EXAMPLES:

```
sage: F = GF(101)
sage: EllipticCurve(j=F(0)).is_supersingular()
True
sage: EllipticCurve(j=F(1728)).is_supersingular()
False
sage: EllipticCurve(j=F(66)).is_supersingular()
True
sage: EllipticCurve(j=F(99)).is_supersingular()
False
```

**order** (*algorithm*='pari', *extension\_degree*=1)

Return the number of points on this elliptic curve.

INPUT:

- *algorithm* – string (default: 'pari'), used only for point counting over prime fields:
  - 'pari' – use the baby-step giant-step or Schoof-Elkies-Atkin methods as implemented in the PARI C-library function `ellap`
  - 'bsgs' – use the baby-step giant-step method as implemented in Sage, with the Cremona-Sutherland version of Mestre's trick
  - 'all' – compute cardinality with both 'pari' and 'bsgs'; return result if they agree or raise a `RuntimeError` if they do not
- *extension\_degree* – an integer  $d$  (default: 1): if the base field is  $\mathbf{F}_q$ , return the cardinality of `self` over the extension  $\mathbf{F}_{q^d}$  of degree  $d$ .

OUTPUT:

The order of the group of rational points of `self` over its base field, or over an extension field of degree  $d$  as above. The result is cached.

Over prime fields, one of the above algorithms is used. Over non-prime fields, the serious point counting is done on a standard curve with the same  $j$ -invariant over the field  $\mathbf{F}_p(j)$ , then lifted to the base field, and finally account is taken of twists.

For  $j = 0$  and  $j = 1728$  special formulas are used instead.

EXAMPLES:

```
sage: EllipticCurve(GF(4, 'a'), [1, 2, 3, 4, 5]).cardinality()
8
sage: k.<a> = GF(3^3)
sage: l = [a^2 + 1, 2*a^2 + 2*a + 1, a^2 + a + 1, 2, 2*a]
sage: EllipticCurve(k, l).cardinality()
29
```

```
sage: l = [1, 1, 0, 2, 0]
sage: EllipticCurve(k, l).cardinality()
38
```

An even bigger extension (which we check against Magma):

```

sage: EllipticCurve(GF(3^100, 'a'), [1,2,3,4,5]).cardinality()
515377520732011331036459693969645888996929981504
sage: magma.eval("Order(EllipticCurve([GF(3^100)|1,2,3,4,5]))") # optional_
↪- magma
'515377520732011331036459693969645888996929981504'

```

```

sage: EllipticCurve(GF(10007), [1,2,3,4,5]).cardinality()
10076
sage: EllipticCurve(GF(10007), [1,2,3,4,5]).cardinality(algorithm='pari')
10076
sage: EllipticCurve(GF(next_prime(10**20)), [1,2,3,4,5]).cardinality()
100000000011093199520

```

The cardinality is cached:

```

sage: E = EllipticCurve(GF(3^100, 'a'), [1,2,3,4,5])
sage: E.cardinality() is E.cardinality()
True
sage: E = EllipticCurve(GF(11^2, 'a'), [3,3])
sage: E.cardinality()
128
sage: EllipticCurve(GF(11^100, 'a'), [3,3]).cardinality()
13780612339822270184118337172089636776264331200038467184683526694179151034106556517649784650

```

**plot** (\*args, \*\*kws)

Draw a graph of this elliptic curve over a prime finite field.

INPUT:

- \*args, \*\*kws - all other options are passed to the circle graphing primitive.

EXAMPLES:

```

sage: E = EllipticCurve(FiniteField(17), [0,1])
sage: P = plot(E, rgbcolor=(0,0,1))

```

**points** ()

All the points on this elliptic curve. The list of points is cached so subsequent calls are free.

EXAMPLES:

```

sage: p = 5
sage: F = GF(p)
sage: E = EllipticCurve(F, [1, 3])
sage: a_sub_p = E.change_ring(QQ).ap(p); a_sub_p
2

```

```

sage: len(E.points())
4
sage: p + 1 - a_sub_p
4
sage: E.points()
[(0 : 1 : 0), (1 : 0 : 1), (4 : 1 : 1), (4 : 4 : 1)]

```

```

sage: K = GF(p**2, 'a')
sage: E = E.change_ring(K)
sage: len(E.points())
32

```



```

sage: (p + 1)**2 - a_sub_p**2
32
sage: w = E.points(); w
[(0 : 1 : 0), (0 : 2*a + 4 : 1), (0 : 3*a + 1 : 1), (1 : 0 : 1), (2 : 2*a + 4 : 1), (2 : 3*a + 1 : 1), (3 : 2*a + 4 : 1), (3 : 3*a + 1 : 1), (4 : 1 : 1), (4 : 4 : 1), (a : 1 : 1), (a : 4 : 1), (a + 2 : a + 1 : 1), (a + 2 : 4*a + 4 : 1), (a + 3 : a : 1), (a + 3 : 4*a : 1), (a + 4 : 0 : 1), (2*a : 2*a : 1), (2*a : 3*a : 1), (2*a + 4 : a + 1 : 1), (2*a + 4 : 4*a + 4 : 1), (3*a + 1 : a + 3 : 1), (3*a + 1 : 4*a + 2 : 1), (3*a + 2 : 2*a + 3 : 1), (3*a + 2 : 3*a + 2 : 1), (4*a : 0 : 1), (4*a + 1 : 1 : 1), (4*a + 1 : 4 : 1), (4*a + 3 : a + 3 : 1), (4*a + 3 : 4*a + 2 : 1), (4*a + 4 : a + 4 : 1), (4*a + 4 : 4*a + 1 : 1)]

```

Note that the returned list is an immutable sorted Sequence:

```

sage: w[0] = 9
Traceback (most recent call last):
...
ValueError: object is immutable; please change a copy instead.

```

### **random\_element()**

Return a random point on this elliptic curve, uniformly chosen among all rational points.

#### ALGORITHM:

Choose the point at infinity with probability  $1/(2q + 1)$ . Otherwise, take a random element from the field as x-coordinate and compute the possible y-coordinates. Return the  $i$ 'th possible y-coordinate, where  $i$  is randomly chosen to be 0 or 1. If the  $i$ 'th y-coordinate does not exist (either there is no point with the given x-coordinate or we hit a 2-torsion point with  $i == 1$ ), try again.

This gives a uniform distribution because you can imagine  $2q + 1$  buckets, one for the point at infinity and 2 for each element of the field (representing the x-coordinates). This gives a 1-to-1 map of elliptic curve points into buckets. At every iteration, we simply choose a random bucket until we find a bucket containing a point.

#### AUTHOR:

- Jeroen Demeyer (2014-09-09): choose points uniformly random, see [trac ticket #16951](#).

#### EXAMPLES:

```

sage: k = GF(next_prime(7^5))
sage: E = EllipticCurve(k, [2, 4])
sage: P = E.random_element(); P # random
(16740 : 12486 : 1)
sage: type(P)
<class 'sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field'>
sage: P in E
True

```

```

sage: k.<a> = GF(7^5)
sage: E = EllipticCurve(k, [2, 4])
sage: P = E.random_element(); P
(5*a^4 + 3*a^3 + 2*a^2 + a + 4 : 2*a^4 + 3*a^3 + 4*a^2 + a + 5 : 1)
sage: type(P)
<class 'sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field'>
sage: P in E
True

```

```
True
```

```
sage: k.<a> = GF(2^5)
sage: E = EllipticCurve(k, [a^2, a, 1, a+1, 1])
sage: P = E.random_element(); P
(a^4 + a : a^4 + a^3 + a^2 : 1)
sage: type(P)
<class 'sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field'
↪ '>
sage: P in E
True
```

Ensure that the entire point set is reachable:

```
sage: E = EllipticCurve(GF(11), [2, 1])
sage: len(set(E.random_element() for _ in range(100)))
16
sage: E.cardinality()
16
```

### `random_point()`

Return a random point on this elliptic curve, uniformly chosen among all rational points.

#### ALGORITHM:

Choose the point at infinity with probability  $1/(2q + 1)$ . Otherwise, take a random element from the field as x-coordinate and compute the possible y-coordinates. Return the  $i$ 'th possible y-coordinate, where  $i$  is randomly chosen to be 0 or 1. If the  $i$ 'th y-coordinate does not exist (either there is no point with the given x-coordinate or we hit a 2-torsion point with  $i == 1$ ), try again.

This gives a uniform distribution because you can imagine  $2q + 1$  buckets, one for the point at infinity and 2 for each element of the field (representing the x-coordinates). This gives a 1-to-1 map of elliptic curve points into buckets. At every iteration, we simply choose a random bucket until we find a bucket containing a point.

#### AUTHOR:

- Jeroen Demeyer (2014-09-09): choose points uniformly random, see [trac ticket #16951](#).

#### EXAMPLES:

```
sage: k = GF(next_prime(7^5))
sage: E = EllipticCurve(k, [2, 4])
sage: P = E.random_element(); P # random
(16740 : 12486 : 1)
sage: type(P)
<class 'sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field'
↪ '>
sage: P in E
True
```

```
sage: k.<a> = GF(7^5)
sage: E = EllipticCurve(k, [2, 4])
sage: P = E.random_element(); P
(5*a^4 + 3*a^3 + 2*a^2 + a + 4 : 2*a^4 + 3*a^3 + 4*a^2 + a + 5 : 1)
sage: type(P)
<class 'sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field'
↪ '>
```

```
sage: P in E
True
```

```
sage: k.<a> = GF(2^5)
sage: E = EllipticCurve(k, [a^2, a, 1, a+1, 1])
sage: P = E.random_element(); P
(a^4 + a : a^4 + a^3 + a^2 : 1)
sage: type(P)
<class 'sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_finite_field'
↪ '>
sage: P in E
True
```

Ensure that the entire point set is reachable:

```
sage: E = EllipticCurve(GF(11), [2, 1])
sage: len(set(E.random_element() for _ in range(100)))
16
sage: E.cardinality()
16
```

### **rational\_points()**

All the points on this elliptic curve. The list of points is cached so subsequent calls are free.

EXAMPLES:

```
sage: p = 5
sage: F = GF(p)
sage: E = EllipticCurve(F, [1, 3])
sage: a_sub_p = E.change_ring(QQ).ap(p); a_sub_p
2
```

```
sage: len(E.points())
4
sage: p + 1 - a_sub_p
4
sage: E.points()
[(0 : 1 : 0), (1 : 0 : 1), (4 : 1 : 1), (4 : 4 : 1)]
```

```
sage: K = GF(p**2, 'a')
sage: E = E.change_ring(K)
sage: len(E.points())
32
sage: (p + 1)**2 - a_sub_p**2
32
sage: w = E.points(); w
[(0 : 1 : 0), (0 : 2*a + 4 : 1), (0 : 3*a + 1 : 1), (1 : 0 : 1), (2 : 2*a + 4 ↵
↪ : 1), (2 : 3*a + 1 : 1), (3 : 2*a + 4 : 1), (3 : 3*a + 1 : 1), (4 : 1 : 1), ↵
↪ (4 : 4 : 1), (a : 1 : 1), (a : 4 : 1), (a + 2 : a + 1 : 1), (a + 2 : 4*a + ↵
↪ 4 : 1), (a + 3 : a : 1), (a + 3 : 4*a : 1), (a + 4 : 0 : 1), (2*a : 2*a : ↵
↪ 1), (2*a : 3*a : 1), (2*a + 4 : a + 1 : 1), (2*a + 4 : 4*a + 4 : 1), (3*a + ↵
↪ 1 : a + 3 : 1), (3*a + 1 : 4*a + 2 : 1), (3*a + 2 : 2*a + 3 : 1), (3*a + 2 ↵
↪ : 3*a + 2 : 1), (4*a : 0 : 1), (4*a + 1 : 1 : 1), (4*a + 1 : 4 : 1), (4*a + ↵
↪ 3 : a + 3 : 1), (4*a + 3 : 4*a + 2 : 1), (4*a + 4 : a + 4 : 1), (4*a + 4 : ↵
↪ 4*a + 1 : 1)]
```

Note that the returned list is an immutable sorted Sequence:

```
sage: w[0] = 9
Traceback (most recent call last):
...
ValueError: object is immutable; please change a copy instead.
```

**set\_order** (value, num\_checks=8)

Set the value of self.\_order to value.

Use this when you know a priori the order of the curve to avoid a potentially expensive order calculation.

INPUT:

- value - Integer in the Hasse-Weil range for this curve.
- num\_checks - Integer (default: 8) number of times to check whether value\*(a random point on this curve) is equal to the identity.

OUTPUT:

None

EXAMPLES:

This example illustrates basic usage.

```
sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: E.set_order(6)
sage: E.order()
6
sage: E.order() * E.random_point()
(0 : 1 : 0)
```

We now give a more interesting case, the NIST-P521 curve. Its order is too big to calculate with Sage, and takes a long time using other packages, so it is very useful here.

```
sage: p = 2^521 - 1
sage: prev_proof_state = proof.arithmetic()
sage: proof.arithmetic(False) # turn off primality checking
sage: F = GF(p)
sage: A = p - 3
sage: B = _
↪109384903807373427451111239076680556993620759895168374899458639449595311615073501601370873
sage: q = _
↪686479766013060971498190079908139321726943530014330540939446345918554318339765539424505774
sage: E = EllipticCurve([F(A), F(B)])
sage: E.set_order(q)
sage: G = E.random_point()
sage: E.order() * G # This takes practically no time.
(0 : 1 : 0)
sage: proof.arithmetic(prev_proof_state) # restore state
```

It is an error to pass a value which is not an integer in the Hasse-Weil range:

```
sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: E.set_order("hi")
Traceback (most recent call last):
...
ValueError: Value hi illegal (not an integer in the Hasse range)
sage: E.set_order(3.14159)
Traceback (most recent call last):
```

```

...
ValueError: Value 3.141590000000000 illegal (not an integer in the Hasse range)
sage: E.set_order(0)
Traceback (most recent call last):
...
ValueError: Value 0 illegal (not an integer in the Hasse range)
sage: E.set_order(1000)
Traceback (most recent call last):
...
ValueError: Value 1000 illegal (not an integer in the Hasse range)

```

It is also very likely an error to pass a value which is not the actual order of this curve. How unlikely is determined by `num_checks`, the factorization of the actual order, and the actual group structure:

```

sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: E.set_order(11)
Traceback (most recent call last):
...
ValueError: Value 11 illegal (multiple of random point not the identity)

```

However, `set_order` can be fooled, though it's not likely in “real cases of interest”. For instance, the order can be set to a multiple of the actual order:

```

sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: E.set_order(12) # 12 just fits in the Hasse range
sage: E.order()
12

```

Or, the order can be set incorrectly along with `num_checks` set too small:

```

sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: E.set_order(4, num_checks=0)
WARNING: No checking done in set_order
sage: E.order()
4

```

The value of `num_checks` must be an integer. Negative values are interpreted as zero, which means don't do any checking:

```

sage: E = EllipticCurve(GF(7), [0, 1]) # This curve has order 6
sage: E.set_order(4, num_checks=-12)
WARNING: No checking done in set_order
sage: E.order()
4

```

#### NOTES:

The implementation is based on the fact that orders of elliptic curves are cached in the (pseudo-private) `_order` slot.

#### AUTHORS:

- Mariah Lenox (2011-02-16)

#### `trace_of_frobenius()`

Return the trace of Frobenius acting on this elliptic curve.

---

**Note:** This computes the curve cardinality, which may be time-consuming.

---

EXAMPLES:

```
sage: E=EllipticCurve(GF(101), [2, 3])
sage: E.trace_of_frobenius()
6
sage: E=EllipticCurve(GF(11^5, 'a'), [2, 5])
sage: E.trace_of_frobenius()
802
```

The following shows that the issue from [trac ticket #2849](#) is fixed:

```
sage: E=EllipticCurve(GF(3^5, 'a'), [-1, -1])
sage: E.trace_of_frobenius()
-27
```

```
sage.schemes.elliptic_curves.ell_finite_field.is_j_supersingular(j,
                                                                    proof=True)
```

Return True if  $j$  is a supersingular  $j$ -invariant.

INPUT:

- $j$  (finite field element) – an element of a finite field
- `proof` (boolean, default True) – If True, returns a proved result. If False, then a return value of False is certain but a return value of True may be based on a probabilistic test. See the ALGORITHM section below for more details.

OUTPUT:

(boolean) True if  $j$  is supersingular, else False.

ALGORITHM:

For small characteristics  $p$  we check whether the  $j$ -invariant is in a precomputed list of supersingular values. Otherwise we next check the  $j$ -invariant. If  $j = 0$ , the curve is supersingular if and only if  $p = 2$  or  $p \equiv 3 \pmod{4}$ ; if  $j = 1728$ , the curve is supersingular if and only if  $p = 3$  or  $p \equiv 2 \pmod{3}$ . Next, if the base field is the prime field  $\text{GF}(p)$ , we check that  $(p+1)P = 0$  for several random points  $P$ , returning False if any fail: supersingular curves over  $\text{GF}(p)$  have cardinality  $p+1$ . If `Proof` is false we now return True. Otherwise we compute the cardinality and return True if and only if it is divisible by  $p$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_finite_field import is_j_
      ↪ supersingular, supersingular_j_polynomials
sage: [(p, [j for j in GF(p) if is_j_supersingular(j)]) for p in prime_range(30)]
[(2, [0]), (3, [0]), (5, [0]), (7, [6]), (11, [0, 1]), (13, [5]), (17, [0, 8]),
      ↪ (19, [7, 18]), (23, [0, 3, 19]), (29, [0, 2, 25])]

sage: [j for j in GF(109) if is_j_supersingular(j)]
[17, 41, 43]
sage: PolynomialRing(GF(109), 'j')(supersingular_j_polynomials[109]).roots()
[(43, 1), (41, 1), (17, 1)]

sage: [p for p in prime_range(100) if is_j_supersingular(GF(p)(0))]
[2, 3, 5, 11, 17, 23, 29, 41, 47, 53, 59, 71, 83, 89]
sage: [p for p in prime_range(100) if is_j_supersingular(GF(p)(1728))]
[2, 3, 7, 11, 19, 23, 31, 43, 47, 59, 67, 71, 79, 83]
```

```
sage: [p for p in prime_range(100) if is_j_supersingular(GF(p)(123456))]  
[2, 3, 59, 89]
```

`sage.schemes.elliptic_curves.ell_finite_field.supersingular_j_polynomial(p)`  
Return a polynomial whose roots are the supersingular  $j$ -invariants in characteristic  $p$ , other than 0, 1728.

INPUT:

- $p$  (integer) – a prime number.

ALGORITHM:

First compute  $H(X)$  whose roots are the Legendre  $\lambda$ -invariants of supersingular curves (Silverman V.4.1(b)) in characteristic  $p$ . Then, using a resultant computation with the polynomial relating  $\lambda$  and  $j$  (Silverman III.1.7(b)), we recover the polynomial (in variable  $j$ ) whose roots are the  $j$ -invariants. Factors of  $j$  and  $j - 1728$  are removed if present.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_finite_field import supersingular_j_  
      ↪ polynomial  
sage: f = supersingular_j_polynomial(67); f  
j^5 + 53*j^4 + 4*j^3 + 47*j^2 + 36*j + 8  
sage: f.factor()  
(j + 1) * (j^2 + 8*j + 45) * (j^2 + 44*j + 24)
```

```
sage: [supersingular_j_polynomial(p) for p in prime_range(30)]  
[1, 1, 1, 1, 1, j + 8, j + 9, j + 12, j + 4, j^2 + 2*j + 21]
```

## 15.7 Formal groups of elliptic curves

AUTHORS:

- William Stein: original implementations
- David Harvey: improved asymptotics of some methods
- Nick Alexander: separation from `ell_generic.py`, bugfixes and docstrings

**class** `sage.schemes.elliptic_curves.formal_group.EllipticCurveFormalGroup(E)`  
Bases: `sage.structure.sage_object.SageObject`

The formal group associated to an elliptic curve.

**curve**()

Return the elliptic curve this formal group is associated to.

EXAMPLES:

```
sage: E = EllipticCurve("37a")  
sage: F = E.formal_group()  
sage: F.curve()  
Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field
```

**differential**(prec=20)

Return the power series  $f(t) = 1 + \dots$  such that  $f(t)dt$  is the usual invariant differential  $dx/(2y + a_1x + a_3)$ .

INPUT:

- `prec` - nonnegative integer (default 20), answer will be returned  $O(t^{\text{prec}})$

OUTPUT: a power series with given precision

Return the formal series

$$f(t) = 1 + a_1 t + (a_1^2 + a_2) t^2 + \dots$$

to precision  $O(t^{\text{prec}})$  of page 113 of [\[SilBook\]](#).

The result is cached, and a cached version is returned if possible.

**Warning:** The resulting series will have precision `prec`, but its parent `PowerSeriesRing` will have default precision 20 (or whatever the default default is).

EXAMPLES:

```
sage: EllipticCurve([-1, 1/4]).formal_group().differential(15)
1 - 2*t^4 + 3/4*t^6 + 6*t^8 - 5*t^10 - 305/16*t^12 + 105/4*t^14 + O(t^15)
sage: EllipticCurve(Integers(53), [-1, 1/4]).formal_group().differential(15)
1 + 51*t^4 + 14*t^6 + 6*t^8 + 48*t^10 + 24*t^12 + 13*t^14 + O(t^15)
```

AUTHOR:

- David Harvey (2006-09-10): factored out of log

**group\_law** (*prec=10*)

Return the formal group law.

INPUT:

- `prec` - integer (default 10)

OUTPUT: a power series with given precision in  $R[[t_1, t_2]]$ , where the curve is defined over  $R$ .

Return the formal power series

$$F(t_1, t_2) = t_1 + t_2 - a_1 t_1 t_2 - \dots$$

to precision  $O(t_1, t_2)^{\text{prec}}$  of page 115 of [\[SilBook\]](#).

The result is cached, and a cached version is returned if possible.

AUTHORS:

- Nick Alexander: minor fixes, docstring
- Francis Clarke (2012-08): modified to use two-variable power series ring

EXAMPLES:

```
sage: e = EllipticCurve([1, 2])
sage: e.formal_group().group_law(6)
t1 + t2 - 2*t1^4*t2 - 4*t1^3*t2^2 - 4*t1^2*t2^3 - 2*t1*t2^4 + O(t1, t2)^6
sage: e = EllipticCurve('14a1')
sage: ehat = e.formal()
sage: ehat.group_law(3)
t1 + t2 - t1*t2 + O(t1, t2)^3
sage: ehat.group_law(5)
t1 + t2 - t1*t2 - 2*t1^3*t2 - 3*t1^2*t2^2 - 2*t1*t2^3 + O(t1, t2)^5
```



```

sage: e = EllipticCurve(GF(7), [3, 4])
sage: ehat = e.formal()
sage: ehat.group_law(3)
t1 + t2 + O(t1, t2)^3
sage: F = ehat.group_law(7); F
t1 + t2 + t1^4*t2 + 2*t1^3*t2^2 + 2*t1^2*t2^3 + t1*t2^4 + O(t1, t2)^7

```

**inverse** (*prec*=20)

Return the formal group inverse law  $i(t)$ , which satisfies  $F(t, i(t)) = 0$ .

INPUT:

- *prec* - integer (default 20)

OUTPUT: a power series with given precision

Return the formal power series

$$i(t) = -t + a_1 t^2 + \dots$$

to precision  $O(t^{\text{prec}})$  of page 114 of [\[SilBook\]](#).

The result is cached, and a cached version is returned if possible.

**Warning:** The resulting power series will have precision *prec*, but its parent `PowerSeriesRing` will have default precision 20 (or whatever the default default is).

EXAMPLES:

```

sage: P.<a1, a2, a3, a4, a6> = ZZ[]
sage: E = EllipticCurve(list(P.gens()))
sage: i = E.formal_group().inverse(6); i
-t - a1*t^2 - a1^2*t^3 + (-a1^3 - a3)*t^4 + (-a1^4 - 3*a1*a3)*t^5 + O(t^6)
sage: F = E.formal_group().group_law(6)
sage: F(i.parent().gen(), i)
O(t^6)

```

**log** (*prec*=20)

Return the power series  $f(t) = t + \dots$  which is an isomorphism to the additive formal group.

Generally this only makes sense in characteristic zero, although the terms before  $t^p$  may work in characteristic  $p$ .

INPUT:

- *prec* - nonnegative integer (default 20)

OUTPUT: a power series with given precision

EXAMPLES:

```

sage: EllipticCurve([-1, 1/4]).formal_group().log(15)
t - 2/5*t^5 + 3/28*t^7 + 2/3*t^9 - 5/11*t^11 - 305/208*t^13 + O(t^15)

```

AUTHORS:

- David Harvey (2006-09-10): rewrote to use differential

**mult\_by\_n**(*n*, *prec*=10)

Return the formal ‘multiplication by *n*’ endomorphism  $[n]$ .

INPUT:

- *prec* - integer (default 10)

OUTPUT: a power series with given precision

Return the formal power series

$$[n](t) = nt + \cdots$$

to precision  $O(t^{\text{prec}})$  of Proposition 2.3 of [\[SilBook\]](#).

**Warning:** The resulting power series will have precision *prec*, but its parent PowerSeriesRing will have default precision 20 (or whatever the default default is).

AUTHORS:

- Nick Alexander: minor fixes, docstring
- David Harvey (2007-03): faster algorithm for char 0 field case
- Hamish Ivey-Law (2009-06): double-and-add algorithm for non char 0 field case.
- Tom Boothby (2009-06): slight improvement to double-and-add
- Francis Clarke (2012-08): adjustments and simplifications using group\_law code as modified to yield a two-variable power series.

EXAMPLES:

```
sage: e = EllipticCurve([1, 2, 3, 4, 6])
sage: e.formal_group().mult_by_n(0, 5)
O(t^5)
sage: e.formal_group().mult_by_n(1, 5)
t + O(t^5)
```

We verify an identity of low degree:

```
sage: none = e.formal_group().mult_by_n(-1, 5)
sage: two = e.formal_group().mult_by_n(2, 5)
sage: ntwo = e.formal_group().mult_by_n(-2, 5)
sage: ntwo - none(two)
O(t^5)
sage: ntwo - two(none)
O(t^5)
```

It’s quite fast:

```
sage: E = EllipticCurve("37a"); F = E.formal_group()
sage: F.mult_by_n(100, 20)
100*t - 49999950*t^4 + 3999999960*t^5 + 14285614285800*t^7 -
↪ 2999989920000150*t^8 + 13333325333333400*t^9 - 3571378571674999800*t^10 +
↪ 1402585362624965454000*t^11 - 146666057066712847999500*t^12 +
↪ 5336978000014213190385000*t^13 - 519472790950932256570002000*t^14 +
↪ 93851927683683567270392002800*t^15 - 6673787211563812368630730325175*t^16 +
↪ 320129060335050875009191524993000*t^17 -
↪ 45670288869783478472872833214986000*t^18 +
↪ 5302464956134111125466184947310391600*t^19 + O(t^20)
```

**sigma** (*prec*=10)

EXAMPLES:

```
sage: E = EllipticCurve('14a')
sage: F = E.formal_group()
sage: F.sigma(5)
t + 1/2*t^2 + (1/2*c + 1/3)*t^3 + (3/4*c + 3/4)*t^4 + O(t^5)
```

**w** (*prec*=20)

Return the formal group power series  $w$ .

INPUT:

- *prec* - integer (default 20)

OUTPUT: a power series with given precision

Return the formal power series

$$w(t) = t^3 + a_1 t^4 + (a_2 + a_1^2) t^5 + \cdots$$

to precision  $O(t^{\text{prec}})$  of Proposition IV.1.1 of [SilBook]. This is the formal expansion of  $w = -1/y$  about the formal parameter  $t = -x/y$  at  $\infty$ .

The result is cached, and a cached version is returned if possible.

**Warning:** The resulting power series will have precision *prec*, but its parent `PowerSeriesRing` will have default precision 20 (or whatever the default default is).

ALGORITHM: Uses Newton's method to solve the elliptic curve equation at the origin. Complexity is roughly  $O(M(n))$  where  $n$  is the precision and  $M(n)$  is the time required to multiply polynomials of length  $n$  over the coefficient ring of  $E$ .

AUTHOR:

- David Harvey (2006-09-09): modified to use Newton's method instead of a recurrence formula.

EXAMPLES:

```
sage: e = EllipticCurve([0, 0, 1, -1, 0])
sage: e.formal_group().w(10)
t^3 + t^6 - t^7 + 2*t^9 + O(t^10)
```

Check that caching works:

```
sage: e = EllipticCurve([3, 2, -4, -2, 5])
sage: e.formal_group().w(20)
t^3 + 3*t^4 + 11*t^5 + 35*t^6 + 101*t^7 + 237*t^8 + 312*t^9 - 949*t^10 -
↳ 10389*t^11 - 57087*t^12 - 244092*t^13 - 865333*t^14 - 2455206*t^15 -
↳ 4366196*t^16 + 6136610*t^17 + 109938783*t^18 + 688672497*t^19 + O(t^20)
sage: e.formal_group().w(7)
t^3 + 3*t^4 + 11*t^5 + 35*t^6 + O(t^7)
sage: e.formal_group().w(35)
t^3 + 3*t^4 + 11*t^5 + 35*t^6 + 101*t^7 + 237*t^8 + 312*t^9 - 949*t^10 -
↳ 10389*t^11 - 57087*t^12 - 244092*t^13 - 865333*t^14 - 2455206*t^15 -
↳ 4366196*t^16 + 6136610*t^17 + 109938783*t^18 + 688672497*t^19 +
↳ 3219525807*t^20 + 12337076504*t^21 + 38106669615*t^22 + 79452618700*t^23 -
↳ 33430470002*t^24 - 1522228110356*t^25 - 10561222329021*t^26 -
↳ 52449326572178*t^27 - 211701726058446*t^28 - 693522772940043*t^29 -
↳ 1613471639599050*t^30 - 421817906421378*t^31 + 23651687753515182*t^32 +
↳ 181817896929144595*t^33 + 950887648021211163*t^34 + O(t^35)
```

**x** (*prec*=20)

Return the formal series  $x(t) = t/w(t)$  in terms of the local parameter  $t = -x/y$  at infinity.

INPUT:

- *prec* - integer (default 20)

OUTPUT: a Laurent series with given precision

Return the formal series

$$x(t) = t^{-2} - a_1 t^{-1} - a_2 - a_3 t - \dots$$

to precision  $O(t^{\text{prec}})$  of page 113 of [\[SilBook\]](#).

**Warning:** The resulting series will have precision *prec*, but its parent `PowerSeriesRing` will have default precision 20 (or whatever the default default is).

EXAMPLES:

```
sage: EllipticCurve([0, 0, 1, -1, 0]).formal_group().x(10)
t^-2 - t + t^2 - t^4 + 2*t^5 - t^6 - 2*t^7 + 6*t^8 - 6*t^9 + O(t^10)
```

**y** (*prec*=20)

Return the formal series  $y(t) = -1/w(t)$  in terms of the local parameter  $t = -x/y$  at infinity.

INPUT:

- *prec* - integer (default 20)

OUTPUT: a Laurent series with given precision

Return the formal series

$$y(t) = -t^{-3} + a_1 t^{-2} + a_2 t + a_3 + \dots$$

to precision  $O(t^{\text{prec}})$  of page 113 of [\[SilBook\]](#).

The result is cached, and a cached version is returned if possible.

**Warning:** The resulting series will have precision *prec*, but its parent `PowerSeriesRing` will have default precision 20 (or whatever the default default is).

EXAMPLES:

```
sage: EllipticCurve([0, 0, 1, -1, 0]).formal_group().y(10)
-t^-3 + 1 - t + t^3 - 2*t^4 + t^5 + 2*t^6 - 6*t^7 + 6*t^8 + 3*t^9 + O(t^10)
```

Maps between them

## 15.8 Isomorphisms between Weierstrass models of elliptic curves

AUTHORS:

- Robert Bradshaw (2007): initial version
- John Cremona (Jan 2008): isomorphisms, automorphisms and twists in all characteristics

**class** sage.schemes.elliptic\_curves.weierstrass\_morphism.**WeierstrassIsomorphism** (*E=None, urst=None, F=None*)

Bases: `sage.schemes.elliptic_curves.weierstrass_morphism.baseWI`, `sage.categories.morphism.Morphism`

Class representing a Weierstrass isomorphism between two elliptic curves.

**class** sage.schemes.elliptic\_curves.weierstrass\_morphism.**baseWI** (*u=1, r=0, s=0, t=0*)

This class implements the basic arithmetic of isomorphisms between Weierstrass models of elliptic curves.

These are specified by lists of the form  $[u, r, s, t]$  (with  $u \neq 0$ ) which specifies a transformation  $(x, y) \mapsto (x', y')$  where

$$(x, y) = (u^2 x' + r, u^3 y' + su^2 x' + t).$$

INPUT:

- $u, r, s, t$  (default (1,0,0,0)) – standard parameters of an isomorphism between Weierstrass models.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import *
sage: baseWI()
(1, 0, 0, 0)
sage: baseWI(2, 3, 4, 5)
(2, 3, 4, 5)
sage: R.<u,r,s,t> = QQ[]
sage: baseWI(u,r,s,t)
(u, r, s, t)
```

**is\_identity()**

Return True if this is the identity isomorphism.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import *
sage: w = baseWI(); w.is_identity()
True
sage: w = baseWI(2, 3, 4, 5); w.is_identity()
False
```

**tuple()**

Return the parameters  $u, r, s, t$  as a tuple.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import *
sage: w = baseWI(2, 3, 4, 5)
sage: w.tuple()
(2, 3, 4, 5)
```

sage.schemes.elliptic\_curves.weierstrass\_morphism.**isomorphisms** (*E, F, JustOne=False*)

Return one or all isomorphisms between two elliptic curves.

INPUT:

- `E, F (EllipticCurve)` – Two elliptic curves.
- `JustOne (bool)` If `True`, returns one isomorphism, or `None` if the curves are not isomorphic. If `False`, returns a (possibly empty) list of isomorphisms.

OUTPUT:

Either `None`, or a 4-tuple  $(u, r, s, t)$  representing an isomorphism, or a list of these.

---

**Note:** This function is not intended for users, who should use the interface provided by `ell_generic`.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import *
sage: isomorphisms(EllipticCurve_from_j(0), EllipticCurve('27a3'))
[(-1, 0, 0, -1), (1, 0, 0, 0)]
sage: isomorphisms(EllipticCurve_from_j(0), EllipticCurve('27a3'), JustOne=True)
(1, 0, 0, 0)
sage: isomorphisms(EllipticCurve_from_j(0), EllipticCurve('27a1'))
[]
sage: isomorphisms(EllipticCurve_from_j(0), EllipticCurve('27a1'), JustOne=True)
```

## 15.9 Isogenies

An isogeny  $\varphi : E_1 \rightarrow E_2$  between two elliptic curves  $E_1$  and  $E_2$  is a morphism of curves that sends the origin of  $E_1$  to the origin of  $E_2$ . Such a morphism is automatically a morphism of group schemes and the kernel is a finite subgroup scheme of  $E_1$ . Such a subscheme can either be given by a list of generators, which have to be torsion points, or by a polynomial in the coordinate  $x$  of the Weierstrass equation of  $E_1$ .

The usual way to create and work with isogenies is illustrated with the following example:

```
sage: k = GF(11)
sage: E = EllipticCurve(k, [1, 1])
sage: Q = E(6, 5)
sage: phi = E.isogeny(Q)
sage: phi
Isogeny of degree 7 from Elliptic Curve defined by y^2 = x^3 + x + 1 over Finite
↪Field of size 11 to Elliptic Curve defined by y^2 = x^3 + 7*x + 8 over Finite Field
↪of size 11
sage: P = E(4, 5)
sage: phi(P)
(10 : 0 : 1)
sage: phi.codomain()
Elliptic Curve defined by y^2 = x^3 + 7*x + 8 over Finite Field of size 11
sage: phi.rational_maps()
((x^7 + 4*x^6 - 3*x^5 - 2*x^4 - 3*x^3 + 3*x^2 + x - 2)/(x^6 + 4*x^5 - 4*x^4 - 5*x^3 +
↪5*x^2), (x^9*y - 5*x^8*y - x^7*y + x^5*y - x^4*y - 5*x^3*y - 5*x^2*y - 2*x*y - 5*y)/
↪(x^9 - 5*x^8 + 4*x^6 - 3*x^4 + 2*x^3))
```

The functions directly accessible from an elliptic curve  $E$  over a field are `isogeny` and `isogeny_codomain`.

The most useful functions that apply to isogenies are

- `codomain`
- `degree`

- `domain`
- `dual`
- `rational_maps`
- `kernel_polynomial`

**Warning:** Only cyclic, separable isogenies are implemented (except for [2]). Some algorithms may need the isogeny to be normalized.

#### AUTHORS:

- Daniel Shumow <shumow@gmail.com>: 2009-04-19: initial version
- Chris Wuthrich : 7/09: changes: add check of input, not the full list is needed. 10/09: eliminating some bugs.
- John Cremona 2014-08-08: tidying of code and docstrings, systematic use of univariate vs. bivariate polynomials and rational functions.

```
class sage.schemes.elliptic_curves.ell_curve_isogeny.EllipticCurveIsogeny(E,
                                                                    ker-
                                                                    nel,
                                                                    codomain=None,
                                                                    de-
                                                                    gree=None,
                                                                    model=None,
                                                                    check=True)
```

Bases: `sage.categories.morphism.Morphism`

#### Class Implementing Isogenies of Elliptic Curves

This class implements cyclic, separable, normalized isogenies of elliptic curves.

Several different algorithms for computing isogenies are available. These include:

- Velu's Formulas: Velu's original formulas for computing isogenies. This algorithm is selected by giving as the `kernel` parameter a list of points which generate a finite subgroup.
- Kohel's Formulas: Kohel's original formulas for computing isogenies. This algorithm is selected by giving as the `kernel` parameter a monic polynomial (or a coefficient list (little endian)) which will define the kernel of the isogeny.

#### INPUT:

- `E` – an elliptic curve, the domain of the isogeny to initialize.
- `kernel` – a kernel, either a point in `E`, a list of points in `E`, a monic kernel polynomial, or `None`. If initializing from a domain/codomain, this must be set to `None`.
- `codomain` – an elliptic curve (default: `None`). If `kernel` is `None`, then this must be the codomain of a cyclic, separable, normalized isogeny, furthermore, `degree` must be the degree of the isogeny from `E` to `codomain`. If `kernel` is not `None`, then this must be isomorphic to the codomain of the cyclic normalized separable isogeny defined by `kernel`, in this case, the isogeny is post composed with an isomorphism so that this parameter is the codomain.
- `degree` – an integer (default: `None`). If `kernel` is `None`, then this is the degree of the isogeny from `E` to `codomain`. If `kernel` is not `None`, then this is used to determine whether or not to skip a gcd of the kernel polynomial with the two torsion polynomial of `E`.
- `model` – a string (default: `None`). Only supported variable is `minimal`, in which case if `E` is a curve over the rationals or over a number field, then the codomain is a global minimum model where this exists.

- check (default: True) checks if the input is valid to define an isogeny

## EXAMPLES:

A simple example of creating an isogeny of a field of small characteristic:

```
sage: E = EllipticCurve(GF(7), [0,0,0,1,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0))); phi
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + x$  over Finite
↪Field of size 7 to Elliptic Curve defined by  $y^2 = x^3 + 3x$  over Finite Field
↪of size 7
sage: phi.degree() == 2
True
sage: phi.kernel_polynomial()
x
sage: phi.rational_maps()
((x^2 + 1)/x, (x^2*y - y)/x^2)
sage: phi == loads(dumps(phi)) # known bug
True
```

A more complicated example of a characteristic 2 field:

```
sage: E = EllipticCurve(GF(2^4, 'alpha'), [0,0,1,0,1])
sage: P = E((1,1))
sage: phi_v = EllipticCurveIsogeny(E, P); phi_v
Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + y = x^3 + 1$  over Finite
↪Field in alpha of size 2^4 to Elliptic Curve defined by  $y^2 + y = x^3$  over
↪Finite Field in alpha of size 2^4
sage: phi_ker_poly = phi_v.kernel_polynomial()
sage: phi_ker_poly
x + 1
sage: ker_poly_list = phi_ker_poly.list()
sage: phi_k = EllipticCurveIsogeny(E, ker_poly_list)
sage: phi_k == phi_v
True
sage: phi_k.rational_maps()
((x^3 + x + 1)/(x^2 + 1), (x^3*y + x^2*y + x*y + x + y)/(x^3 + x^2 + x + 1))
sage: phi_v.rational_maps()
((x^3 + x + 1)/(x^2 + 1), (x^3*y + x^2*y + x*y + x + y)/(x^3 + x^2 + x + 1))
sage: phi_k.degree() == phi_v.degree() == 3
True
sage: phi_k.is_separable()
True
sage: phi_v(E(0))
(0 : 1 : 0)
sage: alpha = E.base_field().gen()
sage: Q = E((0, alpha*(alpha + 1)))
sage: phi_v(Q)
(1 : alpha^2 + alpha : 1)
sage: phi_v(P) == phi_k(P)
True
sage: phi_k(P) == phi_v.codomain()(0)
True
```

We can create an isogeny that has kernel equal to the full 2 torsion:

```
sage: E = EllipticCurve(GF(3), [0,0,0,1,1])
sage: ker_list = E.division_polynomial(2).list()
sage: phi = EllipticCurveIsogeny(E, ker_list); phi
```



```

Isogeny of degree 4 from Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Finite
↪Field of size 3 to Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Finite
↪Field of size 3
sage: phi(E(0))
(0 : 1 : 0)
sage: phi(E((0,1)))
(1 : 0 : 1)
sage: phi(E((0,2)))
(1 : 0 : 1)
sage: phi(E((1,0)))
(0 : 1 : 0)
sage: phi.degree()
4

```

We can also create trivial isogenies with the trivial kernel:

```

sage: E = EllipticCurve(GF(17), [11, 11, 4, 12, 10])
sage: phi_v = EllipticCurveIsogeny(E, E(0))
sage: phi_v.degree()
1
sage: phi_v.rational_maps()
(x, y)
sage: E == phi_v.codomain()
True
sage: P = E.random_point()
sage: phi_v(P) == P
True

sage: E = EllipticCurve(GF(31), [23, 1, 22, 7, 18])
sage: phi_k = EllipticCurveIsogeny(E, [1]); phi_k
Isogeny of degree 1 from Elliptic Curve defined by  $y^2 + 23xy + 22y = x^3 + x^2 + 7x + 18$  over Finite Field of size 31 to Elliptic Curve defined by  $y^2 + 23xy + 22y = x^3 + x^2 + 7x + 18$  over Finite Field of size 31
sage: phi_k.degree()
1
sage: phi_k.rational_maps()
(x, y)
sage: phi_k.codomain() == E
True
sage: phi_k.kernel_polynomial()
1
sage: P = E.random_point(); P == phi_k(P)
True

```

Velu and Kohel also work in characteristic 0:

```

sage: E = EllipticCurve(QQ, [0, 0, 0, 3, 4])
sage: P_list = E.torsion_points()
sage: phi = EllipticCurveIsogeny(E, P_list); phi
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 3x + 4$  over
↪Rational Field to Elliptic Curve defined by  $y^2 = x^3 - 27x + 46$  over Rational
↪Field
sage: P = E((0,2))
sage: phi(P)
(6 : -10 : 1)
sage: phi_ker_poly = phi.kernel_polynomial()
sage: phi_ker_poly
x + 1

```

```

sage: ker_poly_list = phi_ker_poly.list()
sage: phi_k = EllipticCurveIsogeny(E, ker_poly_list); phi_k
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 3x + 4$  over
↪ Rational Field to Elliptic Curve defined by  $y^2 = x^3 - 27x + 46$  over Rational
↪ Field
sage: phi_k(P) == phi(P)
True
sage: phi_k == phi
True
sage: phi_k.degree()
2
sage: phi_k.is_separable()
True

```

A more complicated example over the rationals (of odd degree):

```

sage: E = EllipticCurve('11a1')
sage: P_list = E.torsion_points()
sage: phi_v = EllipticCurveIsogeny(E, P_list); phi_v
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3 - x^2 - 10x -$ 
↪ 20 over Rational Field to Elliptic Curve defined by  $y^2 + y = x^3 - x^2 -$ 
↪ 7820x - 263580 over Rational Field
sage: P = E((16, -61))
sage: phi_v(P)
(0 : 1 : 0)
sage: ker_poly = phi_v.kernel_polynomial(); ker_poly
x^2 - 21x + 80
sage: ker_poly_list = ker_poly.list()
sage: phi_k = EllipticCurveIsogeny(E, ker_poly_list); phi_k
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3 - x^2 - 10x -$ 
↪ 20 over Rational Field to Elliptic Curve defined by  $y^2 + y = x^3 - x^2 -$ 
↪ 7820x - 263580 over Rational Field
sage: phi_k == phi_v
True
sage: phi_v(P) == phi_k(P)
True
sage: phi_k.is_separable()
True

```

We can also do this same example over the number field defined by the irreducible two torsion polynomial of  $E$ :

```

sage: E = EllipticCurve('11a1')
sage: P_list = E.torsion_points()
sage: K.<alpha> = NumberField(x^3 - 2*x^2 - 40*x - 158)
sage: EK = E.change_ring(K)
sage: P_list = [EK(P) for P in P_list]
sage: phi_v = EllipticCurveIsogeny(EK, P_list); phi_v
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x^2 + (-$ 
↪ 10)x + (-20) over Number Field in alpha with defining polynomial  $x^3 - 2x^2 -$ 
↪ 40x - 158 to Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x^2 + (-7820)x +$ 
↪ (-263580) over Number Field in alpha with defining polynomial  $x^3 - 2x^2 -$ 
↪ 40x - 158
sage: P = EK((alpha/2, -1/2))
sage: phi_v(P)
(122/121*alpha^2 + 1633/242*alpha - 3920/121 : -1/2 : 1)
sage: ker_poly = phi_v.kernel_polynomial()
sage: ker_poly

```

```

x^2 - 21*x + 80
sage: ker_poly_list = ker_poly.list()
sage: phi_k = EllipticCurveIsogeny(EK, ker_poly_list)
sage: phi_k
Isogeny of degree 5 from Elliptic Curve defined by y^2 + y = x^3 + (-1)*x^2 + (-
↳10)*x + (-20) over Number Field in alpha with defining polynomial x^3 - 2*x^2 -
↳40*x - 158 to Elliptic Curve defined by y^2 + y = x^3 + (-1)*x^2 + (-7820)*x +
↳(-263580) over Number Field in alpha with defining polynomial x^3 - 2*x^2 -
↳40*x - 158
sage: phi_v == phi_k
True
sage: phi_k(P) == phi_v(P)
True
sage: phi_k == phi_v
True
sage: phi_k.degree()
5
sage: phi_v.is_separable()
True

```

The following example shows how to specify an isogeny from domain and codomain:

```

sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^2 - 21*x + 80
sage: phi = E.isogeny(f)
sage: E2 = phi.codomain()
sage: phi_s = EllipticCurveIsogeny(E, None, E2, 5)
sage: phi_s
Isogeny of degree 5 from Elliptic Curve defined by y^2 + y = x^3 - x^2 - 10*x -
↳20 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - x^2 -
↳7820*x - 263580 over Rational Field
sage: phi_s == phi
True
sage: phi_s.rational_maps() == phi.rational_maps()
True

```

However only cyclic normalized isogenies can be constructed this way. So it won't find the isogeny [3]:

```

sage: E.isogeny(None, codomain=E, degree=9)
Traceback (most recent call last):
...
ValueError: The two curves are not linked by a cyclic normalized isogeny of
↳degree 9

```

Also the presumed isogeny between the domain and codomain must be normalized:

```

sage: E2.isogeny(None, codomain=E, degree=5)
Traceback (most recent call last):
...
ValueError: The two curves are not linked by a cyclic normalized isogeny of
↳degree 5
sage: phihat = phi.dual(); phihat
Isogeny of degree 5 from Elliptic Curve defined by y^2 + y = x^3 - x^2 - 7820*x -
↳263580 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - x^2 -
↳10*x - 20 over Rational Field
sage: phihat.is_normalized()
False

```

Here an example of a construction of a endomorphisms with cyclic kernel on a CM-curve:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve(K, [1,0])
sage: RK.<X> = K[]
sage: f = X^2 - 2/5*i + 1/5
sage: phi= E.isogeny(f)
sage: isom = phi.codomain().isomorphism_to(E)
sage: phi.set_post_isomorphism(isom)
sage: phi.codomain() == phi.domain()
True
sage: phi.rational_maps()
((4/25*i + 3/25)*x^5 + (4/5*i - 2/5)*x^3 - x)/(x^4 + (-4/5*i + 2/5)*x^2 + (-4/
↪25*i - 3/25)), ((11/125*i + 2/125)*x^6*y + (-23/125*i + 64/125)*x^4*y + (141/
↪125*i + 162/125)*x^2*y + (3/25*i - 4/25)*y)/(x^6 + (-6/5*i + 3/5)*x^4 + (-12/
↪25*i - 9/25)*x^2 + (2/125*i - 11/125)))
```

Domain and codomain tests (see [trac ticket #12880](#)):

```
sage: E = EllipticCurve(QQ, [0,0,0,1,0])
sage: phi = EllipticCurveIsogeny(E, E(0,0))
sage: phi.domain() == E
True
sage: phi.codomain()
Elliptic Curve defined by y^2 = x^3 - 4*x over Rational Field

sage: E = EllipticCurve(GF(31), [1,0,0,1,2])
sage: phi = EllipticCurveIsogeny(E, [17, 1])
sage: phi.domain()
Elliptic Curve defined by y^2 + x*y = x^3 + x + 2 over Finite Field of size 31
sage: phi.codomain()
Elliptic Curve defined by y^2 + x*y = x^3 + 24*x + 6 over Finite Field of size 31
```

Composition tests (see [trac ticket #16245](#)):

```
sage: E = EllipticCurve(j=GF(7)(0))
sage: phi = E.isogeny([E(0), E((0,1)), E((0,-1))]); phi
Isogeny of degree 3 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field of size 7 to Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field of size 7
sage: phi2 = phi * phi; phi2
Composite map:
  From: Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field of size 7
  To:    Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field of size 7
  Defn:  Isogeny of degree 3 from Elliptic Curve defined by y^2 = x^3 + 1 over
↪Finite Field of size 7 to Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field of size 7
  then
    Isogeny of degree 3 from Elliptic Curve defined by y^2 = x^3 + 1 over
↪Finite Field of size 7 to Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field of size 7
```

Examples over relative number fields used not to work (see [trac ticket #16779](#)):

```
sage: pol26 = hilbert_class_polynomial(-4*26)
sage: pol = NumberField(pol26, 'a').optimized_representation()[0].polynomial()
sage: K.<a> = NumberField(pol)
sage: j = pol26.roots(K)[0][0]
sage: E = EllipticCurve(j=j)
```

```

sage: L.<b> = K.extension(x^2+26)
sage: EL = E.change_ring(L)
sage: iso2 = EL.isogenies_prime_degree(2); len(iso2)
1
sage: iso3 = EL.isogenies_prime_degree(3); len(iso3)
2

```

Examples over function fields used not to work (see [trac ticket #11327](#)):

```

sage: F.<t> = FunctionField(QQ)
sage: E = EllipticCurve([0,0,0,-t^2,0])
sage: isogs = E.isogenies_prime_degree(2)
sage: isogs[0]
Isogeny of degree 2 from Elliptic Curve defined by y^2 = x^3 + (-t^2)*x over
↪Rational function field in t over Rational Field to Elliptic Curve defined by y^
↪2 = x^3 + 4*t^2*x over Rational function field in t over Rational Field
sage: isogs[0].rational_maps()
((x^2 - t^2)/x, (x^2*y + t^2*y)/x^2)
sage: duals = [phi.dual() for phi in isogs]
sage: duals[0]
Isogeny of degree 2 from Elliptic Curve defined by y^2 = x^3 + 4*t^2*x over
↪Rational function field in t over Rational Field to Elliptic Curve defined by y^
↪2 = x^3 + (-t^2)*x over Rational function field in t over Rational Field
sage: duals[0].rational_maps()
((1/4*x^2 + t^2)/x, (1/8*x^2*y + (-1/2*t^2)*y)/x^2)
sage: duals[0]
Isogeny of degree 2 from Elliptic Curve defined by y^2 = x^3 + 4*t^2*x over
↪Rational function field in t over Rational Field to Elliptic Curve defined by y^
↪2 = x^3 + (-t^2)*x over Rational function field in t over Rational Field

```

### `degree()`

Returns the degree of this isogeny.

EXAMPLES:

```

sage: E = EllipticCurve(QQ, [0,0,0,1,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0)))
sage: phi.degree()
2
sage: phi = EllipticCurveIsogeny(E, [0,1,0,1])
sage: phi.degree()
4

sage: E = EllipticCurve(GF(31), [1,0,0,1,2])
sage: phi = EllipticCurveIsogeny(E, [17, 1])
sage: phi.degree()
3

```

### `dual()`

Return the isogeny dual to this isogeny.

---

**Note:** If  $\varphi: E \rightarrow E_2$  is the given isogeny and  $n$  is its degree, then the dual is by definition the unique isogeny  $\hat{\varphi}: E_2 \rightarrow E$  such that the compositions  $\hat{\varphi} \circ \varphi$  and  $\varphi \circ \hat{\varphi}$  are the multiplication-by- $n$  maps on  $E$  and  $E_2$ , respectively.

---

EXAMPLES:

```

sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^2 - 21*x + 80
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi_hat = phi.dual()
sage: phi_hat.domain() == phi.codomain()
True
sage: phi_hat.codomain() == phi.domain()
True
sage: (X, Y) = phi.rational_maps()
sage: (Xhat, Yhat) = phi_hat.rational_maps()
sage: Xm = Xhat.subs(x=X, y=Y)
sage: Ym = Yhat.subs(x=X, y=Y)
sage: (Xm, Ym) == E.multiplication_by_m(5)
True

sage: E = EllipticCurve(GF(37), [0,0,0,1,8])
sage: R.<x> = GF(37)[]
sage: f = x^3 + x^2 + 28*x + 33
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi_hat = phi.dual()
sage: phi_hat.codomain() == phi.domain()
True
sage: phi_hat.domain() == phi.codomain()
True
sage: (X, Y) = phi.rational_maps()
sage: (Xhat, Yhat) = phi_hat.rational_maps()
sage: Xm = Xhat.subs(x=X, y=Y)
sage: Ym = Yhat.subs(x=X, y=Y)
sage: (Xm, Ym) == E.multiplication_by_m(7)
True

sage: E = EllipticCurve(GF(31), [0,0,0,1,8])
sage: R.<x> = GF(31)[]
sage: f = x^2 + 17*x + 29
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi_hat = phi.dual()
sage: phi_hat.codomain() == phi.domain()
True
sage: phi_hat.domain() == phi.codomain()
True
sage: (X, Y) = phi.rational_maps()
sage: (Xhat, Yhat) = phi_hat.rational_maps()
sage: Xm = Xhat.subs(x=X, y=Y)
sage: Ym = Yhat.subs(x=X, y=Y)
sage: (Xm, Ym) == E.multiplication_by_m(5)
True

```

Test for [trac ticket #23928](#):

```

sage: E = EllipticCurve(j=GF(431**2)(4))
sage: phi = E.isogeny(E.lift_x(0))
sage: phi.dual()
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + 427x$  over
↳ Finite Field in  $z_2$  of size  $431^2$  to Elliptic Curve defined by  $y^2 = x^3 + x$ 
↳ over Finite Field in  $z_2$  of size  $431^2$ 

```

Test (for [trac ticket #7096](#)):

```

sage: E = EllipticCurve('11a1')
sage: phi = E.isogeny(E(5,5))
sage: phi.dual().dual() == phi
True

sage: k = GF(103)
sage: E = EllipticCurve(k, [11, 11])
sage: phi = E.isogeny(E(4,4))
sage: phi
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + 11x + 11$  over
↪ Finite Field of size 103 to Elliptic Curve defined by  $y^2 = x^3 + 25x + 80$ 
↪ over Finite Field of size 103
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import
↪ WeierstrassIsomorphism
sage: phi.set_post_isomorphism(WeierstrassIsomorphism(phi.codomain(), (5,0,1,
↪ 2)))
sage: phi.dual().dual() == phi
True

sage: E = EllipticCurve(GF(103), [1,0,0,1,-1])
sage: phi = E.isogeny(E(60,85))
sage: phi.dual()
Isogeny of degree 7 from Elliptic Curve defined by  $y^2 + xy = x^3 + 84x +$ 
↪ 34 over Finite Field of size 103 to Elliptic Curve defined by  $y^2 + xy = x^$ 
↪ 3 + x + 102 over Finite Field of size 103

```

Check that [trac ticket #17293](#) is fixed:

```

sage: k.<s> = QuadraticField(2) sage: E = EllipticCurve(k, [-3*s*(4 + 5*s), 2*s*(2 + 14*s +
11*s^2)]) sage: phi = E.isogenies_prime_degree(3)[0] sage: (-phi).dual() == -(phi.dual()) True
sage: phi._EllipticCurveIsogeny__clear_cached_values() # forget the dual sage: (-phi.dual()) ==
(-phi).dual() True

```

**formal** (*prec*=20)

Return the formal isogeny as a power series in the variable  $t = -x/y$  on the domain curve.

INPUT:

- *prec* - (default = 20), the precision with which the computations in the formal group are carried out.

EXAMPLES:

```

sage: E = EllipticCurve(GF(13), [1, 7])
sage: phi = E.isogeny(E(10,4))
sage: phi.formal()
t + 12*t^13 + 2*t^17 + 8*t^19 + 2*t^21 + O(t^23)

sage: E = EllipticCurve([0, 1])
sage: phi = E.isogeny(E(2, 3))
sage: phi.formal(prec=10)
t + 54*t^5 + 255*t^7 + 2430*t^9 + 19278*t^11 + O(t^13)

sage: E = EllipticCurve('11a2')
sage: R.<x> = QQ[]
sage: phi = E.isogeny(x^2 + 101*x + 12751/5)
sage: phi.formal(prec=7)
t - 2724/5*t^5 + 209046/5*t^7 - 4767/5*t^8 + 29200946/5*t^9 + O(t^10)

```

**get\_post\_isomorphism**()

Return the post-isomorphism of this isogeny, or None.

EXAMPLES:

```
sage: E = EllipticCurve(j=GF(31)(0))
sage: R.<x> = GF(31)[]
sage: phi = EllipticCurveIsogeny(E, x+18)
sage: phi.get_post_isomorphism()
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import WeierstrassIsomorphism
sage: isom = WeierstrassIsomorphism(phi.codomain(), (6,8,10,12))
sage: phi.set_post_isomorphism(isom)
sage: isom == phi.get_post_isomorphism()
True

sage: E = EllipticCurve(GF(83), [1,0,1,1,0])
sage: R.<x> = GF(83)[]; f = x+24
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: phi2 = EllipticCurveIsogeny(E, None, E2, 2)
sage: phi2.get_post_isomorphism()
Generic morphism:
From: Abelian group of points on Elliptic Curve defined by  $y^2 = x^3 + 65x + 69$  over Finite Field of size 83
To: Abelian group of points on Elliptic Curve defined by  $y^2 + x*y + y = x^3 + 4*x + 16$  over Finite Field of size 83
Via: (u,r,s,t) = (1, 7, 42, 42)
```

**get\_pre\_isomorphism()**

Return the pre-isomorphism of this isogeny, or None.

EXAMPLES:

```
sage: E = EllipticCurve(GF(31), [1,1,0,1,-1])
sage: R.<x> = GF(31)[]
sage: f = x^3 + 9*x^2 + x + 30
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi.get_post_isomorphism()
sage: Epr = E.short_weierstrass_model()
sage: isom = Epr.isomorphism_to(E)
sage: phi.set_pre_isomorphism(isom)
sage: isom == phi.get_pre_isomorphism()
True

sage: E = EllipticCurve(GF(83), [1,0,1,1,0])
sage: R.<x> = GF(83)[]; f = x+24
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: phi2 = EllipticCurveIsogeny(E, None, E2, 2)
sage: phi2.get_pre_isomorphism()
Generic morphism:
From: Abelian group of points on Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x$  over Finite Field of size 83
To: Abelian group of points on Elliptic Curve defined by  $y^2 = x^3 + 62*x + 74$  over Finite Field of size 83
Via: (u,r,s,t) = (1, 76, 41, 3)
```

**is\_injective()**

Return True if and only if this isogeny has trivial kernel.



EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^2 + x - 29/5
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi.is_injective()
False
sage: phi = EllipticCurveIsogeny(E, R(1))
sage: phi.is_injective()
True

sage: F = GF(7)
sage: E = EllipticCurve(j=F(0))
sage: phi = EllipticCurveIsogeny(E, [E((0,-1)), E((0,1))])
sage: phi.is_injective()
False
sage: phi = EllipticCurveIsogeny(E, E(0))
sage: phi.is_injective()
True
```

**is\_normalized** (*via\_formal=True, check\_by\_pullback=True*)  
Return whether this isogeny is normalized.

---

**Note:** An isogeny  $\varphi: E \rightarrow E_2$  between two given Weierstrass equations is said to be normalized if the constant  $c$  is 1 in  $\varphi^*(\omega_2) = c \cdot \omega$ , where  $\omega$  and  $\omega_2$  are the invariant differentials on  $E$  and  $E_2$  corresponding to the given equation.

---

INPUT:

- *via\_formal* - (default: True) If True it simply checks if the leading term of the formal series is 1. Otherwise it uses a deprecated algorithm involving the second optional argument.
- *check\_by\_pullback* - (default: True) Deprecated.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import_
      WeierstrassIsomorphism
sage: E = EllipticCurve(GF(7), [0,0,0,1,0])
sage: R.<x> = GF(7)[]
sage: phi = EllipticCurveIsogeny(E, x)
sage: phi.is_normalized()
True
sage: isom = WeierstrassIsomorphism(phi.codomain(), (3, 0, 0, 0))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
False
sage: isom = WeierstrassIsomorphism(phi.codomain(), (5, 0, 0, 0))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
True
sage: isom = WeierstrassIsomorphism(phi.codomain(), (1, 1, 1, 1))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
True

sage: F = GF(2^5, 'alpha'); alpha = F.gen()
```

```

sage: E = EllipticCurve(F, [1,0,1,1,1])
sage: R.<x> = F[]
sage: phi = EllipticCurveIsogeny(E, x+1)
sage: isom = WeierstrassIsomorphism(phi.codomain(), (alpha, 0, 0, 0))
sage: phi.is_normalized()
True
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
False
sage: isom = WeierstrassIsomorphism(phi.codomain(), (1/alpha, 0, 0, 0))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
True
sage: isom = WeierstrassIsomorphism(phi.codomain(), (1, 1, 1, 1))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
True

sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^3 - x^2 - 10*x - 79/4
sage: phi = EllipticCurveIsogeny(E, f)
sage: isom = WeierstrassIsomorphism(phi.codomain(), (2, 0, 0, 0))
sage: phi.is_normalized()
True
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
False
sage: isom = WeierstrassIsomorphism(phi.codomain(), (1/2, 0, 0, 0))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
True
sage: isom = WeierstrassIsomorphism(phi.codomain(), (1, 1, 1, 1))
sage: phi.set_post_isomorphism(isom)
sage: phi.is_normalized()
True

```

**is\_separable()**

Return whether or not this isogeny is separable.

---

**Note:** This function always returns True as currently this class only implements separable isogenies.

---

**EXAMPLES:**

```

sage: E = EllipticCurve(GF(17), [0,0,0,3,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0)))
sage: phi.is_separable()
True

sage: E = EllipticCurve('11a1')
sage: phi = EllipticCurveIsogeny(E, E.torsion_points())
sage: phi.is_separable()
True

```

**is\_surjective()**

Return True if and only if this isogeny is surjective.

---

**Note:** This function always returns `True`, as a non-constant map of algebraic curves must be surjective, and this class does not model the constant 0 isogeny.

---

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^2 + x - 29/5
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi.is_surjective()
True

sage: E = EllipticCurve(GF(7), [0,0,0,1,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0)))
sage: phi.is_surjective()
True

sage: F = GF(2^5, 'omega')
sage: E = EllipticCurve(j=F(0))
sage: R.<x> = F[]
sage: phi = EllipticCurveIsogeny(E, x)
sage: phi.is_surjective()
True
```

**is\_zero()**

Return whether this isogeny is zero.

---

**Note:** Currently this class does not allow zero isogenies, so this function will always return `True`.

---

EXAMPLES:

```
sage: E = EllipticCurve(j=GF(7)(0))
sage: phi = EllipticCurveIsogeny(E, [E((0,1)), E((0,-1))])
sage: phi.is_zero()
False
```

**kernel\_polynomial()**

Return the kernel polynomial of this isogeny.

EXAMPLES:

```
sage: E = EllipticCurve(QQ, [0,0,0,2,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0)))
sage: phi.kernel_polynomial()
x

sage: E = EllipticCurve('11a1')
sage: phi = EllipticCurveIsogeny(E, E.torsion_points())
sage: phi.kernel_polynomial()
x^2 - 21*x + 80

sage: E = EllipticCurve(GF(17), [1,-1,1,-1,1])
sage: phi = EllipticCurveIsogeny(E, [1])
sage: phi.kernel_polynomial()
1
```

```

sage: E = EllipticCurve(GF(31), [0,0,0,3,0])
sage: phi = EllipticCurveIsogeny(E, [0,3,0,1])
sage: phi.kernel_polynomial()
x^3 + 3*x

```

**n()**

Numerical Approximation inherited from Map (through morphism), nonsensical for isogenies.

EXAMPLES:

```

sage: E = EllipticCurve(j=GF(7)(0))
sage: phi = EllipticCurveIsogeny(E, [E((0,1)), E((0,-1))])
sage: phi.n()
Traceback (most recent call last):
...
NotImplementedError: Numerical approximations do not make sense for Elliptic_
↪Curve Isogenies

```

**post\_compose(left)**

Return the post-composition of this isogeny with left.

EXAMPLES:

```

sage: E = EllipticCurve(j=GF(7)(0))
sage: phi = EllipticCurveIsogeny(E, [E((0,1)), E((0,-1))])
sage: phi.post_compose(phi)
Traceback (most recent call last):
...
NotImplementedError: post-composition of isogenies not yet implemented

```

**pre\_compose(right)**

Return the pre-composition of this isogeny with right.

EXAMPLES:

```

sage: E = EllipticCurve(j=GF(7)(0))
sage: phi = EllipticCurveIsogeny(E, [E((0,1)), E((0,-1))])
sage: phi.pre_compose(phi)
Traceback (most recent call last):
...
NotImplementedError: pre-composition of isogenies not yet implemented

```

**rational\_maps()**

Return the pair of rational maps defining this isogeny.

---

**Note:** Both components are returned as elements of the function field  $F(x, y)$  in two variables over the base field  $F$ , though the first only involves  $x$ . To obtain the  $x$ -coordinate function as a rational function in  $F(x)$ , use `x_rational_map()`.

---

EXAMPLES:

```

sage: E = EllipticCurve(QQ, [0,2,0,1,-1])
sage: phi = EllipticCurveIsogeny(E, [1])
sage: phi.rational_maps()
(x, y)

```

```

sage: E = EllipticCurve(GF(17), [0,0,0,3,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0)))
sage: phi.rational_maps()
((x^2 + 3)/x, (x^2*y - 3*y)/x^2)

```

**set\_post\_isomorphism** (*postWI*)

Modify this isogeny by postcomposing with a Weierstrass isomorphism.

EXAMPLES:

```

sage: E = EllipticCurve(j=GF(31)(0))
sage: R.<x> = GF(31)[ ]
sage: phi = EllipticCurveIsogeny(E, x+18)
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import
↳ WeierstrassIsomorphism
sage: phi.set_post_isomorphism(WeierstrassIsomorphism(phi.codomain(), (6,8,10,
↳ 12)))
sage: phi
Isogeny of degree 3 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite_
↳ Field of size 31 to Elliptic Curve defined by y^2 + 24*x*y + 7*y = x^3 +
↳ 22*x^2 + 16*x + 20 over Finite Field of size 31

sage: E = EllipticCurve(j=GF(47)(0))
sage: f = E.torsion_polynomial(3)/3
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: post_isom = E2.isomorphism_to(E)
sage: phi.set_post_isomorphism(post_isom)
sage: phi.rational_maps() == E.multiplication_by_m(3)
False
sage: phi.switch_sign()
sage: phi.rational_maps() == E.multiplication_by_m(3)
True

```

Example over a number field:

```

sage: R.<x> = QQ[ ]
sage: K.<a> = NumberField(x^2 + 2)
sage: E = EllipticCurve(j=K(1728))
sage: ker_list = E.torsion_points()
sage: phi = EllipticCurveIsogeny(E, ker_list)
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import
↳ WeierstrassIsomorphism
sage: post_isom = WeierstrassIsomorphism(phi.codomain(), (a,2,3,5))
sage: phi
Isogeny of degree 4 from Elliptic Curve defined by y^2 = x^3 + x over Number_
↳ Field in a with defining polynomial x^2 + 2 to Elliptic Curve defined by y^
↳ 2 = x^3 + (-44)*x + 112 over Number Field in a with defining polynomial x^2_
↳ + 2

```

**set\_pre\_isomorphism** (*preWI*)

Modify this isogeny by precomposing with a Weierstrass isomorphism.

EXAMPLES:

```

sage: E = EllipticCurve(GF(31), [1,1,0,1,-1])
sage: R.<x> = GF(31)[ ]
sage: f = x^3 + 9*x^2 + x + 30

```

```

sage: phi = EllipticCurveIsogeny(E, f)
sage: Epr = E.short_weierstrass_model()
sage: isom = Epr.isomorphism_to(E)
sage: phi.set_pre_isomorphism(isom)
sage: phi.rational_maps()
((-6*x^4 - 3*x^3 + 12*x^2 + 10*x - 1)/(x^3 + x - 12), (3*x^7 + x^6*y - 14*x^6
↪ - 3*x^5 + 5*x^4*y + 7*x^4 + 8*x^3*y - 8*x^3 - 5*x^2*y + 5*x^2 - 14*x*y +
↪ 14*x - 6*y - 6)/(x^6 + 2*x^4 + 7*x^3 + x^2 + 7*x - 11))
sage: phi(Epr((0,22)))
(13 : 21 : 1)
sage: phi(Epr((3,7)))
(14 : 17 : 1)

sage: E = EllipticCurve(GF(29), [0,0,0,1,0])
sage: R.<x> = GF(29)[]
sage: f = x^2 + 5
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi
Isogeny of degree 5 from Elliptic Curve defined by y^2 = x^3 + x over Finite
↪ Field of size 29 to Elliptic Curve defined by y^2 = x^3 + 20*x over Finite
↪ Field of size 29
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import
↪ WeierstrassIsomorphism
sage: inv_isom = WeierstrassIsomorphism(E, (1,-2,5,10))
sage: Epr = inv_isom.codomain().codomain()
sage: isom = Epr.isomorphism_to(E)
sage: phi.set_pre_isomorphism(isom); phi
Isogeny of degree 5 from Elliptic Curve defined by y^2 + 10*x*y + 20*y = x^3
↪ + 27*x^2 + 6 over Finite Field of size 29 to Elliptic Curve defined by y^2
↪ = x^3 + 20*x over Finite Field of size 29
sage: phi(Epr((12,1)))
(26 : 0 : 1)
sage: phi(Epr((2,9)))
(0 : 0 : 1)
sage: phi(Epr((21,12)))
(3 : 0 : 1)
sage: phi.rational_maps()[0]
(x^5 - 10*x^4 - 6*x^3 - 7*x^2 - x + 3)/(x^4 - 8*x^3 + 5*x^2 - 14*x - 6)

sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^2 - 21*x + 80
sage: phi = EllipticCurveIsogeny(E, f); phi
Isogeny of degree 5 from Elliptic Curve defined by y^2 + y = x^3 - x^2 - 10*x
↪ - 20 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - x^2 -
↪ 7820*x - 263580 over Rational Field
sage: from sage.schemes.elliptic_curves.weierstrass_morphism import
↪ WeierstrassIsomorphism
sage: Epr = E.short_weierstrass_model()
sage: isom = Epr.isomorphism_to(E)
sage: phi.set_pre_isomorphism(isom)
sage: phi
Isogeny of degree 5 from Elliptic Curve defined by y^2 = x^3 - 13392*x -
↪ 1080432 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - x^
↪ 2 - 7820*x - 263580 over Rational Field
sage: phi(Epr((168,1188)))
(0 : 1 : 0)

```

**switch\_sign()**

Compose this isogeny with  $[-1]$  (negation).

EXAMPLES:

```
sage: E = EllipticCurve(GF(23), [0,0,0,1,0])
sage: f = E.torsion_polynomial(3)/3
sage: phi = EllipticCurveIsogeny(E, f, E)
sage: phi.rational_maps() == E.multiplication_by_m(3)
False
sage: phi.switch_sign()
sage: phi.rational_maps() == E.multiplication_by_m(3)
True

sage: E = EllipticCurve(GF(17), [-2, 3, -5, 7, -11])
sage: R.<x> = GF(17)[]
sage: f = x+6
sage: phi = EllipticCurveIsogeny(E, f)
sage: phi
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 + 15xy + 12y = x^3 + 3x^2 + 7x + 6$  over Finite Field of size 17 to Elliptic Curve defined by  $y^2 + 15xy + 12y = x^3 + 3x^2 + 4x + 8$  over Finite Field of size 17
sage: phi.rational_maps()
((x^2 + 6*x + 4)/(x + 6), (x^2*y - 5*x*y + 8*x - 2*y)/(x^2 - 5*x + 2))
sage: phi.switch_sign()
sage: phi
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 + 15xy + 12y = x^3 + 3x^2 + 7x + 6$  over Finite Field of size 17 to Elliptic Curve defined by  $y^2 + 15xy + 12y = x^3 + 3x^2 + 4x + 8$  over Finite Field of size 17
sage: phi.rational_maps()
((x^2 + 6*x + 4)/(x + 6),
 (2*x^3 - x^2*y - 5*x^2 + 5*x*y - 4*x + 2*y + 7)/(x^2 - 5*x + 2))

sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]
sage: f = x^2 - 21*x + 80
sage: phi = EllipticCurveIsogeny(E, f)
sage: (xmap1, ymap1) = phi.rational_maps()
sage: phi.switch_sign()
sage: (xmap2, ymap2) = phi.rational_maps()
sage: xmap1 == xmap2
True
sage: ymap1 == -ymap2 - E.a1()*xmap2 - E.a3()
True

sage: K.<a> = NumberField(x^2 + 1)
sage: E = EllipticCurve(K, [0,0,0,1,0])
sage: R.<x> = K[]
sage: phi = EllipticCurveIsogeny(E, x-a)
sage: phi.rational_maps()
((x^2 + (-a)*x - 2)/(x + (-a)), (x^2*y + (-2*a)*x*y + y)/(x^2 + (-2*a)*x - 1))
sage: phi.switch_sign()
sage: phi.rational_maps()
((x^2 + (-a)*x - 2)/(x + (-a)), (-x^2*y + (2*a)*x*y - y)/(x^2 + (-2*a)*x - 1))
```

**x\_rational\_map()**

Return the rational map giving the  $x$ -coordinate of this isogeny.

**Note:** This function returns the  $x$ -coordinate component of the isogeny as a rational function in  $F(x)$ , where  $F$  is the base field. To obtain both coordinate functions as elements of the function field  $F(x, y)$  in two variables, use `rational_maps()`.

EXAMPLES:

```
sage: E = EllipticCurve(QQ, [0,2,0,1,-1])
sage: phi = EllipticCurveIsogeny(E, [1])
sage: phi.x_rational_map()
x

sage: E = EllipticCurve(GF(17), [0,0,0,3,0])
sage: phi = EllipticCurveIsogeny(E, E((0,0)))
sage: phi.x_rational_map()
(x^2 + 3)/x
```

```
sage.schemes.elliptic_curves.ell_curve_isogeny.compute_codomain_formula(E,
                                                                    v,
                                                                    w)
```

Compute the codomain curve given parameters  $v$  and  $w$  (as in Velu / Kohel / etc formulas).

INPUT:

- $E$  – an elliptic curve
- $v, w$  – elements of the base field of  $E$

OUTPUT:

The elliptic curve with invariants  $[a_1, a_2, a_3, a_4 - 5v, a_6 - (a_1^2 + 4a_2)v - 7w]$  where  $E = [a_1, a_2, a_3, a_4, a_6]$ .

EXAMPLES:

This formula is used by every Isogeny instantiation:

```
sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: phi = EllipticCurveIsogeny(E, E((1,2)))
sage: phi.codomain()
Elliptic Curve defined by y^2 + x*y + 3*y = x^3 + 2*x^2 + 9*x + 13 over Finite_
↪Field of size 19
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_codomain_
↪formula
sage: v = phi._EllipticCurveIsogeny__v
sage: w = phi._EllipticCurveIsogeny__w
sage: compute_codomain_formula(E, v, w) == phi.codomain()
True
```

```
sage.schemes.elliptic_curves.ell_curve_isogeny.compute_codomain_kohel(E,
                                                                    ker-
                                                                    nel,
                                                                    de-
                                                                    gree)
```

Compute the codomain from the kernel polynomial using Kohel's formulas.

INPUT:

- $E$  – an elliptic curve
- `kernel` (polynomial or list) – the kernel polynomial, or a list of its coefficients



- degree (int) – degree of the isogeny

OUTPUT:

(elliptic curve) – the codomain elliptic curve  $E/\text{kernel}$

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_codomain_
      ↪ kohel
sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: phi = EllipticCurveIsogeny(E, [9,1])
sage: phi.codomain() == isogeny_codomain_from_kernel(E, [9,1])
True
sage: compute_codomain_kohel(E, [9,1], 2)
Elliptic Curve defined by  $y^2 + x*y + 3*y = x^3 + 2*x^2 + 9*x + 8$  over Finite_
      ↪ Field of size 19
sage: R.<x> = GF(19)[]
sage: E = EllipticCurve(GF(19), [18,17,16,15,14])
sage: phi = EllipticCurveIsogeny(E, x^3 + 14*x^2 + 3*x + 11)
sage: phi.codomain() == isogeny_codomain_from_kernel(E, x^3 + 14*x^2 + 3*x + 11)
True
sage: compute_codomain_kohel(E, x^3 + 14*x^2 + 3*x + 11, 7)
Elliptic Curve defined by  $y^2 + 18*x*y + 16*y = x^3 + 17*x^2 + 18*x + 18$  over_
      ↪ Finite Field of size 19
sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: phi = EllipticCurveIsogeny(E, x^3 + 7*x^2 + 15*x + 12)
sage: isogeny_codomain_from_kernel(E, x^3 + 7*x^2 + 15*x + 12) == phi.codomain()
True
sage: compute_codomain_kohel(E, x^3 + 7*x^2 + 15*x + 12, 4)
Elliptic Curve defined by  $y^2 + x*y + 3*y = x^3 + 2*x^2 + 3*x + 15$  over Finite_
      ↪ Field of size 19
```

**Note:** This function uses the formulas of Section 2.4 of [K96].

REFERENCES:

`sage.schemes.elliptic_curves.ell_curve_isogeny.compute_intermediate_curves` ( $E1$ ,  $E2$ )

Return intermediate curves and isomorphisms.

**Note:** This is used so we can compute  $\wp$  functions from the short Weierstrass model more easily.

**Warning:** The base field must be of characteristic not equal to 2,3.

INPUT:

- $E1$  - an elliptic curve
- $E2$  - an elliptic curve

OUTPUT:

tuple (pre\_isomorphism, post\_isomorphism, intermediate\_domain, intermediate\_codomain):

- intermediate\_domain: a short Weierstrass model isomorphic to  $E1$

- `intermediate_codomain`: a short Weierstrass model isomorphic to  $E_2$
- `pre_isomorphism`: normalized isomorphism from  $E_1$  to `intermediate_domain`
- `post_isomorphism`: normalized isomorphism from `intermediate_codomain` to  $E_2$

## EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_
      ↪ intermediate_curves
sage: E = EllipticCurve(GF(83), [1,0,1,1,0])
sage: R.<x> = GF(83)[]; f = x+24
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: compute_intermediate_curves(E, E2)
(Elliptic Curve defined by  $y^2 = x^3 + 62x + 74$  over Finite Field of size 83,
 Elliptic Curve defined by  $y^2 = x^3 + 65x + 69$  over Finite Field of size 83,
 Generic morphism:
  From: Abelian group of points on Elliptic Curve defined by  $y^2 + x*y + y = x^3$ 
      ↪ + x over Finite Field of size 83
  To:   Abelian group of points on Elliptic Curve defined by  $y^2 = x^3 + 62x +$ 
      ↪ 74 over Finite Field of size 83
  Via:  (u,r,s,t) = (1, 76, 41, 3),
 Generic morphism:
  From: Abelian group of points on Elliptic Curve defined by  $y^2 = x^3 + 65x +$ 
      ↪ 69 over Finite Field of size 83
  To:   Abelian group of points on Elliptic Curve defined by  $y^2 + x*y + y = x^3$ 
      ↪ + 4*x + 16 over Finite Field of size 83
  Via:  (u,r,s,t) = (1, 7, 42, 42))

sage: R.<x> = QQ[]
sage: K.<i> = NumberField(x^2 + 1)
sage: E = EllipticCurve(K, [0,0,0,1,0])
sage: E2 = EllipticCurve(K, [0,0,0,16,0])
sage: compute_intermediate_curves(E, E2)
(Elliptic Curve defined by  $y^2 = x^3 + x$  over Number Field in i with defining
      ↪ polynomial  $x^2 + 1$ ,
 Elliptic Curve defined by  $y^2 = x^3 + 16x$  over Number Field in i with defining
      ↪ polynomial  $x^2 + 1$ ,
 Generic endomorphism of Abelian group of points on Elliptic Curve defined by  $y^2$ 
      ↪ =  $x^3 + x$  over Number Field in i with defining polynomial  $x^2 + 1$ 
  Via:  (u,r,s,t) = (1, 0, 0, 0),
 Generic endomorphism of Abelian group of points on Elliptic Curve defined by  $y^2$ 
      ↪ =  $x^3 + 16x$  over Number Field in i with defining polynomial  $x^2 + 1$ 
  Via:  (u,r,s,t) = (1, 0, 0, 0))

```

`sage.schemes.elliptic_curves.ell_curve_isogeny.compute_isogeny_kernel_polynomial` ( $E_1$ ,  $E_2$ , `ell`, `algorithm`='starks')

Return the kernel polynomial of an isogeny of degree `ell` between  $E_1$  and  $E_2$ .

## INPUT:

- $E_1$  - an elliptic curve in short Weierstrass form.
- $E_2$  - an elliptic curve in short Weierstrass form.
- `ell` - the degree of the isogeny from  $E_1$  to  $E_2$ .

- algorithm - currently only `starks` (default) is implemented.

OUTPUT:

polynomial over the field of definition of  $E_1, E_2$ , that is the kernel polynomial of the isogeny from  $E_1$  to  $E_2$ .

---

**Note:** If there is no degree  $e_{ll}$ , cyclic, separable, normalized isogeny from  $E_1$  to  $E_2$  then an error will be raised.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_isogeny_
      ↪ kernel_polynomial

sage: E = EllipticCurve(GF(37), [0,0,0,1,8])
sage: R.<x> = GF(37)[]
sage: f = (x + 14) * (x + 30)
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: compute_isogeny_kernel_polynomial(E, E2, 5)
x^2 + 7*x + 13
sage: f
x^2 + 7*x + 13

sage: R.<x> = QQ[]
sage: K.<i> = NumberField(x^2 + 1)
sage: E = EllipticCurve(K, [0,0,0,1,0])
sage: E2 = EllipticCurve(K, [0,0,0,16,0])
sage: compute_isogeny_kernel_polynomial(E, E2, 4)
x^3 + x
```

```
sage.schemes.elliptic_curves.ell_curve_isogeny.compute_isogeny_starks(E1,
                                                                    E2,
                                                                    ell)
```

Return the kernel polynomials of an isogeny of degree  $e_{ll}$  between  $E_1$  and  $E_2$ .

INPUT:

- $E_1$  - an elliptic curve in short Weierstrass form.
- $E_2$  - an elliptic curve in short Weierstrass form.
- $e_{ll}$  - the degree of the isogeny from  $E_1$  to  $E_2$ .

OUTPUT:

polynomial over the field of definition of  $E_1, E_2$ , that is the kernel polynomial of the isogeny from  $E_1$  to  $E_2$ .

---

**Note:** There must be a degree  $e_{ll}$ , separable, normalized cyclic isogeny from  $E_1$  to  $E_2$ , or an error will be raised.

---

ALGORITHM:

This function uses Starks Algorithm as presented in section 6.2 of [BMSS].

---

**Note:** As published in [BMSS], the algorithm is incorrect, and a correct version (with slightly different notation) can be found in [M09]. The algorithm originates in [S72].

---

REFERENCES:

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_isogeny_
      ↪starks, compute_sequence_of_maps

sage: E = EllipticCurve(GF(97), [1,0,1,1,0])
sage: R.<x> = GF(97)[]; f = x^5 + 27*x^4 + 61*x^3 + 58*x^2 + 28*x + 21
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: (isom1, isom2, E1pr, E2pr, ker_poly) = compute_sequence_of_maps(E, E2, 11)
sage: compute_isogeny_starks(E1pr, E2pr, 11)
x^10 + 37*x^9 + 53*x^8 + 66*x^7 + 66*x^6 + 17*x^5 + 57*x^4 + 6*x^3 + 89*x^2 +
      ↪53*x + 8

sage: E = EllipticCurve(GF(37), [0,0,0,1,8])
sage: R.<x> = GF(37)[]
sage: f = (x + 14) * (x + 30)
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: compute_isogeny_starks(E, E2, 5)
x^4 + 14*x^3 + x^2 + 34*x + 21
sage: f**2
x^4 + 14*x^3 + x^2 + 34*x + 21

sage: E = EllipticCurve(QQ, [0,0,0,1,0])
sage: R.<x> = QQ[]
sage: f = x
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: compute_isogeny_starks(E, E2, 2)
x

```

`sage.schemes.elliptic_curves.ell_curve_isogeny.compute_sequence_of_maps(E1,  
E2,  
ell)`

Return intermediate curves, isomorphisms and kernel polynomial.

INPUT:

- *E1*, *E2* – elliptic curves.
- *ell* – a prime such that there is a degree *ell* separable normalized isogeny from *E1* to *E2*.

OUTPUT:

(*pre\_isom*, *post\_isom*, *E1pr*, *E2pr*, *ker\_poly*) where:

- *E1pr* is an elliptic curve in short Weierstrass form isomorphic to *E1*;
- *E2pr* is an elliptic curve in short Weierstrass form isomorphic to *E2*;
- *pre\_isom* is a normalised isomorphism from *E1* to *E1pr*;
- *post\_isom* is a normalised isomorphism from *E2pr* to *E2*;
- *ker\_poly* is the kernel polynomial of an *ell*-isogeny from *E1pr* to *E2pr*.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_sequence_
      ↪ of_maps
sage: E = EllipticCurve('11a1')
sage: R.<x> = QQ[]; f = x^2 - 21*x + 80
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: compute_sequence_of_maps(E, E2, 5)
(Generic morphism:
  From: Abelian group of points on Elliptic Curve defined by y^2 + y = x^3 - x^2 -
  ↪ 10*x - 20 over Rational Field
  To:   Abelian group of points on Elliptic Curve defined by y^2 = x^3 - 31/3*x -
  ↪ 2501/108 over Rational Field
  Via:  (u,r,s,t) = (1, 1/3, 0, -1/2),
Generic morphism:
  From: Abelian group of points on Elliptic Curve defined by y^2 = x^3 - 23461/
  ↪ 3*x - 28748141/108 over Rational Field
  To:   Abelian group of points on Elliptic Curve defined by y^2 + y = x^3 - x^2 -
  ↪ 7820*x - 263580 over Rational Field
  Via:  (u,r,s,t) = (1, -1/3, 0, 1/2),
  Elliptic Curve defined by y^2 = x^3 - 31/3*x - 2501/108 over Rational Field,
  Elliptic Curve defined by y^2 = x^3 - 23461/3*x - 28748141/108 over Rational
  ↪ Field,
  ↪ x^2 - 61/3*x + 658/9)

sage: K.<i> = NumberField(x^2 + 1)
sage: E = EllipticCurve(K, [0,0,0,1,0])
sage: E2 = EllipticCurve(K, [0,0,0,16,0])
sage: compute_sequence_of_maps(E, E2, 4)
(Generic endomorphism of Abelian group of points on Elliptic Curve defined by y^2
  ↪ = x^3 + x over Number Field in i with defining polynomial x^2 + 1
  Via:  (u,r,s,t) = (1, 0, 0, 0),
Generic endomorphism of Abelian group of points on Elliptic Curve defined by y^2
  ↪ = x^3 + 16*x over Number Field in i with defining polynomial x^2 + 1
  Via:  (u,r,s,t) = (1, 0, 0, 0),
  Elliptic Curve defined by y^2 = x^3 + x over Number Field in i with defining
  ↪ polynomial x^2 + 1,
  Elliptic Curve defined by y^2 = x^3 + 16*x over Number Field in i with defining
  ↪ polynomial x^2 + 1,
  ↪ x^3 + x)

sage: E = EllipticCurve(GF(97), [1,0,1,1,0])
sage: R.<x> = GF(97)[]; f = x^5 + 27*x^4 + 61*x^3 + 58*x^2 + 28*x + 21
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: compute_sequence_of_maps(E, E2, 11)
(Generic morphism:
  From: Abelian group of points on Elliptic Curve defined by y^2 + x*y + y = x^3
  ↪ + x over Finite Field of size 97
  To:   Abelian group of points on Elliptic Curve defined by y^2 = x^3 + 52*x +
  ↪ 31 over Finite Field of size 97
  Via:  (u,r,s,t) = (1, 8, 48, 44),
Generic morphism:
  From: Abelian group of points on Elliptic Curve defined by y^2 = x^3 + 41*x +
  ↪ 66 over Finite Field of size 97
  To:   Abelian group of points on Elliptic Curve defined by y^2 + x*y + y = x^3
  ↪ + 87*x + 26 over Finite Field of size 97
  Via:  (u,r,s,t) = (1, 89, 49, 49),
  Elliptic Curve defined by y^2 = x^3 + 52*x + 31 over Finite Field of size 97,

```

```
Elliptic Curve defined by  $y^2 = x^3 + 41x + 66$  over Finite Field of size 97,
 $x^5 + 67x^4 + 13x^3 + 35x^2 + 77x + 69$ )
```

```
sage.schemes.elliptic_curves.ell_curve_isogeny.compute_vw_kohel_even_deg1(x0,
                                                                           y0,
                                                                           a1,
                                                                           a2,
                                                                           a4)
```

Compute Velu's  $(v,w)$  using Kohel's formulas for isogenies of degree exactly divisible by 2.

INPUT:

- $x_0, y_0$  – coordinates of a 2-torsion point on an elliptic curve  $E$
- $a_1, a_2, a_4$  – invariants of  $E$

OUTPUT:

(tuple) Velu's isogeny parameters  $(v,w)$ .

EXAMPLES:

This function will be implicitly called by the following example:

```
sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: phi = EllipticCurveIsogeny(E, [9,1]); phi
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 + xy + 3y = x^3 + 2x^2 +$ 
↪  $4x + 5$  over Finite Field of size 19 to Elliptic Curve defined by  $y^2 + xy +$ 
↪  $3y = x^3 + 2x^2 + 9x + 8$  over Finite Field of size 19
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_vw_kohel_
↪ even_deg1
sage: a1,a2,a3,a4,a6 = E.ainvs()
sage: x0 = -9
sage: y0 = -(a1*x0 + a3)/2
sage: compute_vw_kohel_even_deg1(x0, y0, a1, a2, a4)
(18, 9)
```

```
sage.schemes.elliptic_curves.ell_curve_isogeny.compute_vw_kohel_even_deg3(b2,
                                                                           b4,
                                                                           s1,
                                                                           s2,
                                                                           s3)
```

Compute Velu's  $(v,w)$  using Kohel's formulas for isogenies of degree divisible by 4.

INPUT:

- $b_2, b_4$  – invariants of an elliptic curve  $E$
- $s_1, s_2, s_3$  – signed coefficients of the 2-division polynomial of  $E$

OUTPUT:

(tuple) Velu's isogeny parameters  $(v,w)$ .

EXAMPLES:

This function will be implicitly called by the following example:

```
sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: R.<x> = GF(19)[]
sage: phi = EllipticCurveIsogeny(E, x^3 + 7*x^2 + 15*x + 12); phi
Isogeny of degree 4 from Elliptic Curve defined by  $y^2 + xy + 3y = x^3 + 2x^2 +$ 
↪  $4x + 5$  over Finite Field of size 19 to Elliptic Curve defined by  $y^2 + xy +$ 
↪  $3y = x^3 + 2x^2 + 3x + 15$  over Finite Field of size 19
```

```

sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_vw_kohel_
      ↪even_deg3
sage: (b2,b4) = (E.b2(), E.b4())
sage: (s1, s2, s3) = (-7, 15, -12)
sage: compute_vw_kohel_even_deg3(b2, b4, s1, s2, s3)
(4, 7)

```

```

sage.schemes.elliptic_curves.ell_curve_isogeny.compute_vw_kohel_odd(b2, b4,
                                                                    b6, s1,
                                                                    s2, s3,
                                                                    n)

```

Compute Velu's (v,w) using Kohel's formulas for isogenies of odd degree.

INPUT:

- $b_2, b_4, b_6$  – invariants of an elliptic curve  $E$
- $s_1, s_2, s_3$  – signed coefficients of lowest powers of  $x$  in the kernel polynomial.
- $n$  (int) – the degree

OUTPUT:

(tuple) Velu's isogeny parameters (v,w).

EXAMPLES:

This function will be implicitly called by the following example:

```

sage: E = EllipticCurve(GF(19), [18,17,16,15,14])
sage: R.<x> = GF(19)[]
sage: phi = EllipticCurveIsogeny(E, x^3 + 14*x^2 + 3*x + 11); phi
Isogeny of degree 7 from Elliptic Curve defined by y^2 + 18*x*y + 16*y = x^3 +
↪17*x^2 + 15*x + 14 over Finite Field of size 19 to Elliptic Curve defined by y^
↪2 + 18*x*y + 16*y = x^3 + 17*x^2 + 18*x + 18 over Finite Field of size 19
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_vw_kohel_
      ↪odd
sage: (b2,b4,b6) = (E.b2(), E.b4(), E.b6())
sage: (s1,s2,s3) = (-14,3,-11)
sage: compute_vw_kohel_odd(b2,b4,b6,s1,s2,s3,3)
(7, 1)

```

```

sage.schemes.elliptic_curves.ell_curve_isogeny.fill_isogeny_matrix(M)

```

Returns a filled isogeny matrix giving all degrees from one giving only prime degrees.

INPUT:

- $M$  – a square symmetric matrix whose off-diagonal  $i, j$  entry is either a prime  $l$  (if the  $i$ 'th and  $j$ 'th curves have an  $l$ -isogeny between them), otherwise is 0.

OUTPUT:

(matrix) a square matrix with entries 1 on the diagonal, and in general the  $i, j$  entry is  $d > 0$  if  $d$  is the minimal degree of an isogeny from the  $i$ 'th to the  $j$ 'th curve,

EXAMPLES:

```

sage: M = Matrix([[0, 2, 3, 3, 0, 0], [2, 0, 0, 0, 3, 3], [3, 0, 0, 0, 2, 0], [3,
↪0, 0, 0, 0, 2], [0, 3, 2, 0, 0, 0], [0, 3, 0, 2, 0, 0]]); M
[0 2 3 3 0 0]
[2 0 0 0 3 3]
[3 0 0 0 2 0]
[3 0 0 0 2 0]

```

```

[3 0 0 0 0 2]
[0 3 2 0 0 0]
[0 3 0 2 0 0]
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import fill_isogeny_
      ↪matrix
sage: fill_isogeny_matrix(M)
[ 1  2  3  3  6  6]
[ 2  1  6  6  3  3]
[ 3  6  1  9  2 18]
[ 3  6  9  1 18  2]
[ 6  3  2 18  1  9]
[ 6  3 18  2  9  1]

```

`sage.schemes.elliptic_curves.ell_curve_isogeny.isogeny_codomain_from_kernel` (*E*,  
*kernel*,  
*degree=**None*)

Compute the isogeny codomain given a kernel.

INPUT:

- *E* - The domain elliptic curve.
- **kernel** - Either a list of points in the kernel of the isogeny, or a kernel polynomial (specified as a either a univariate polynomial or a coefficient list.)
- **degree** - an integer, (default:*None*) optionally specified degree of the kernel.

OUTPUT:

(elliptic curve) the codomain of the separable normalized isogeny from this kernel

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import isogeny_codomain_
      ↪from_kernel
sage: E = EllipticCurve(GF(7), [1,0,1,0,1])
sage: R.<x> = GF(7)[]
sage: isogeny_codomain_from_kernel(E, [4,1], degree=3)
Elliptic Curve defined by y^2 + x*y + y = x^3 + 4*x + 6 over Finite Field of size_
      ↪7
sage: EllipticCurveIsogeny(E, [4,1]).codomain() == isogeny_codomain_from_kernel(E,
      ↪ [4,1], degree=3)
True
sage: isogeny_codomain_from_kernel(E, x^3 + x^2 + 4*x + 3)
Elliptic Curve defined by y^2 + x*y + y = x^3 + 4*x + 6 over Finite Field of size_
      ↪7
sage: isogeny_codomain_from_kernel(E, x^3 + 2*x^2 + 4*x + 3)
Elliptic Curve defined by y^2 + x*y + y = x^3 + 5*x + 2 over Finite Field of size_
      ↪7

sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: kernel_list = [E((15,10)), E((10,3)), E((6,5))]
sage: isogeny_codomain_from_kernel(E, kernel_list)
Elliptic Curve defined by y^2 + x*y + 3*y = x^3 + 2*x^2 + 3*x + 15 over Finite_
      ↪Field of size 19

```



`sage.schemes.elliptic_curves.ell_curve_isogeny.isogeny_determine_algorithm(E, kernel)`

Helper function that allows the various isogeny functions to infer the algorithm type from the parameters passed in.

INPUT:

- *E* (elliptic curve) – an elliptic curve
- *kernel* – either a list of points on *E*, or a univariate polynomial or list of coefficients of a univariate polynomial.

OUTPUT:

(string) either ‘velu’ or ‘kohel’

If *kernel* is a list of points on the EllipticCurve *E*, then we will try to use Velu’s algorithm.

If *kernel* is a list of coefficients or a univariate polynomial, we will try to use the Kohel’s algorithms.

EXAMPLES:

This helper function will be implicitly called by the following examples:

```
sage: R.<x> = GF(5) []
sage: E = EllipticCurve(GF(5), [0,0,0,1,0])
```

We can construct the same isogeny from a kernel polynomial:

```
sage: phi = EllipticCurveIsogeny(E, x+3)
```

or from a list of coefficients of a kernel polynomial:

```
sage: phi == EllipticCurveIsogeny(E, [3,1])
True
```

or from a rational point which generates the kernel:

```
sage: phi == EllipticCurveIsogeny(E, E((2,0)) )
True
```

In the first two cases, Kohel’s algorithm will be used, while in the third case it is Velu:

```
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import isogeny_
      ↪determine_algorithm
sage: isogeny_determine_algorithm(E, x+3)
'kohel'
sage: isogeny_determine_algorithm(E, [3, 1])
'kohel'
sage: isogeny_determine_algorithm(E, E((2,0)))
'velu'
```

`sage.schemes.elliptic_curves.ell_curve_isogeny.split_kernel_polynomial(poly)`  
Internal helper function for `compute_isogeny_kernel_polynomial`.

INPUT:

- *poly* – a nonzero univariate polynomial.

OUTPUT:

The maximum separable divisor of `poly`. If the input is a full kernel polynomial where the roots which are  $x$ -coordinates of points of order greater than 2 have multiplicity 1, the output will be a polynomial with the same roots, all of multiplicity 1.

EXAMPLES:

The following example implicitly exercises this function:

```
sage: E = EllipticCurve(GF(37), [0,0,0,1,8])
sage: R.<x> = GF(37) []
sage: f = (x + 10) * (x + 12) * (x + 16)
sage: phi = EllipticCurveIsogeny(E, f)
sage: E2 = phi.codomain()
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import compute_isogeny_
      ↪starks
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import split_kernel_
      ↪polynomial
sage: ker_poly = compute_isogeny_starks(E, E2, 7); ker_poly
x^6 + 2*x^5 + 20*x^4 + 11*x^3 + 36*x^2 + 35*x + 16
sage: ker_poly.factor()
(x + 10)^2 * (x + 12)^2 * (x + 16)^2
sage: poly = split_kernel_polynomial(ker_poly); poly
x^3 + x^2 + 28*x + 33
sage: poly.factor()
(x + 10) * (x + 12) * (x + 16)
```

`sage.schemes.elliptic_curves.ell_curve_isogeny.two_torsion_part(E, psi)`  
Returns the greatest common divisor of `psi` and the 2-torsion polynomial of  $E$ .

INPUT:

- $E$  – an elliptic curve
- `psi` – a univariate polynomial over the base field of  $E$

OUTPUT:

(polynomial) the gcd of `psi` and the 2-torsion polynomial of  $E$ .

EXAMPLES:

Every function that computes the kernel polynomial via Kohel's formulas will call this function:

```
sage: E = EllipticCurve(GF(19), [1,2,3,4,5])
sage: R.<x> = GF(19) []
sage: phi = EllipticCurveIsogeny(E, x + 13)
sage: isogeny_codomain_from_kernel(E, x + 13) == phi.codomain()
True
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import two_torsion_part
sage: two_torsion_part(E, x+13)
x + 13
```

`sage.schemes.elliptic_curves.ell_curve_isogeny.unfill_isogeny_matrix(M)`  
Reverses the action of `fill_isogeny_matrix`.

INPUT:

- $M$  – a square symmetric matrix of integers.

OUTPUT:

(matrix) a square symmetric matrix obtained from  $M$  by replacing non-prime entries with 0.

## EXAMPLES:

```

sage: M = Matrix([[0, 2, 3, 3, 0, 0], [2, 0, 0, 0, 3, 3], [3, 0, 0, 0, 2, 0], [3, 0,
↪0, 0, 0, 2], [0, 3, 2, 0, 0, 0], [0, 3, 0, 2, 0, 0]]); M
[0 2 3 3 0 0]
[2 0 0 0 3 3]
[3 0 0 0 2 0]
[3 0 0 0 0 2]
[0 3 2 0 0 0]
[0 3 0 2 0 0]
sage: from sage.schemes.elliptic_curves.ell_curve_isogeny import fill_isogeny_
↪matrix, unfill_isogeny_matrix
sage: M1 = fill_isogeny_matrix(M); M1
[ 1  2  3  3  6  6]
[ 2  1  6  6  3  3]
[ 3  6  1  9  2 18]
[ 3  6  9  1 18  2]
[ 6  3  2 18  1  9]
[ 6  3 18  2  9  1]
sage: unfill_isogeny_matrix(M1)
[0 2 3 3 0 0]
[2 0 0 0 3 3]
[3 0 0 0 2 0]
[3 0 0 0 0 2]
[0 3 2 0 0 0]
[0 3 0 2 0 0]
sage: unfill_isogeny_matrix(M1) == M
True

```

## 15.10 Isogenies of small prime degree.

Functions for the computation of isogenies of small primes degree. First:  $l = 2, 3, 5, 7$ , or  $13$ , where the modular curve  $X_0(l)$  has genus 0. Second:  $l = 11, 17, 19, 23, 29, 31, 41, 47, 59$ , or  $71$ , where  $X_0^+(l)$  has genus 0 and  $X_0(l)$  is elliptic or hyperelliptic. Also:  $l = 11, 17, 19, 37, 43, 67$  or  $163$  over  $\mathbf{Q}$  (the sporadic cases with only finitely many  $j$ -invariants each). All the above only require factorization of a polynomial of degree  $l + 1$ . Finally, a generic function which works for arbitrary odd primes  $l$  (including the characteristic), but requires factorization of the  $l$ -division polynomial, of degree  $(l^2 - 1)/2$ .

## AUTHORS:

- John Cremona and Jenny Cooley: 2009-07..11: the genus 0 cases the sporadic cases over  $\mathbf{Q}$ .
- Kimi Tsukazaki and John Cremona: 2013-07: The 10 (hyper)-elliptic cases and the generic algorithm. See [\[KT2013\]](#).

## REFERENCES:

sage.schemes.elliptic\_curves.isogeny\_small\_degree.**Fricke\_module**( $l$ )  
 Fricke module for  $l = 2, 3, 5, 7, 13$ .

For these primes (and these only) the modular curve  $X_0(l)$  has genus zero, and its field is generated by a single modular function called the Fricke module (or Hauptmodul),  $t$ . There is a classical choice of such a generator  $t$  in each case, and the  $j$ -function is a rational function of  $t$  of degree  $l + 1$  of the form  $P(t)/t$  where  $P$  is a polynomial of degree  $l + 1$ . Up to scaling,  $t$  is determined by the condition that the ramification points above  $j = \infty$  are  $t = 0$  (with ramification degree 1) and  $t = \infty$  (with degree  $l$ ). The ramification above  $j = 0$  and  $j = 1728$  may be seen in the factorizations of  $j(t)$  and  $k(t)$  where  $k = j - 1728$ .

## OUTPUT:

The rational function  $P(t)/t$ .

```
sage.schemes.elliptic_curves.isogeny_small_degree.Fricke_polynomial(l)
Fricke polynomial for  $l=2,3,5,7,13$ .
```

For these primes (and these only) the modular curve  $X_0(l)$  has genus zero, and its field is generated by a single modular function called the Fricke module (or Hauptmodul),  $t$ . There is a classical choice of such a generator  $t$  in each case, and the  $j$ -function is a rational function of  $t$  of degree  $l+1$  of the form  $P(t)/t$  where  $P$  is a polynomial of degree  $l+1$ . Up to scaling,  $t$  is determined by the condition that the ramification points above  $j = \infty$  are  $t = 0$  (with ramification degree 1) and  $t = \infty$  (with degree  $l$ ). The ramification above  $j = 0$  and  $j = 1728$  may be seen in the factorizations of  $j(t)$  and  $k(t)$  where  $k = j - 1728$ .

OUTPUT:

The polynomial  $P(t)$  as an element of  $\mathbf{Z}[t]$ .

```
sage.schemes.elliptic_curves.isogeny_small_degree.Psi(l, use_stored=True)
Generic kernel polynomial for genus zero primes.
```

For each of the primes  $l$  for which  $X_0(l)$  has genus zero (namely  $l = 2, 3, 5, 7, 13$ ), we may define an elliptic curve  $E_t$  over  $\mathbf{Q}(t)$ , with coefficients in  $\mathbf{Z}[t]$ , which has good reduction except at  $t = 0$  and  $t = \infty$  (which lie above  $j = \infty$ ) and at certain other values of  $t$  above  $j = 0$  when  $l = 3$  (one value) or  $l \equiv 1 \pmod{3}$  (two values) and above  $j = 1728$  when  $l = 2$  (one value) or  $l \equiv 1 \pmod{4}$  (two values). (These exceptional values correspond to endomorphisms of  $E_t$  of degree  $l$ .) The  $l$ -division polynomial of  $E_t$  has a unique factor of degree  $(l-1)/2$  (or 1 when  $l = 2$ ), with coefficients in  $\mathbf{Z}[t]$ , which we call the Generic Kernel Polynomial for  $l$ . These are used, by specialising  $t$ , in the function `isogenies_prime_degree_genus_0()`, which also has to take into account the twisting factor between  $E_t$  for a specific value of  $t$  and the short Weierstrass form of an elliptic curve with  $j$ -invariant  $j(t)$ . This enables the computation of the kernel polynomials of isogenies without having to compute and factor division polynomials.

All of this data is quickly computed from the Fricke modules, except that for  $l = 13$  the factorization of the Generic Division Polynomial takes a long time, so the value have been precomputed and cached; by default the cached values are used, but the code here will recompute them when `use_stored` is `False`, as in the doctests.

INPUT:

- $l$  – either 2, 3, 5, 7, or 13.
- `use_stored` (boolean, default `True`) – If `True`, use precomputed values, otherwise compute them on the fly.

---

**Note:** This computation takes a negligible time for  $l = 2, 3, 5, 7$  but more than 100s for  $l = 13$ . The reason for allowing dynamic computation here instead of just using precomputed values is for testing.

---

```
sage.schemes.elliptic_curves.isogeny_small_degree.Psi2(l)
Returns the generic kernel polynomial for hyperelliptic  $l$ -isogenies.
```

INPUT:

- $l$  – either 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71.

OUTPUT:

The generic  $l$ -kernel polynomial.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import Psi2
sage: Psi2(11)
x^5 - 55*x^4*u + 994*x^3*u^2 - 8774*x^2*u^3 + 41453*x*u^4 - 928945/11*u^5 + 33*x^
↪ 4 + 276*x^3*u - 7794*x^2*u^2 + 4452*x*u^3 + 1319331/11*u^4 + 216*x^3*v - 4536*x^
↪ 2*u*v + 31752*x*u^2*v - 842616/11*u^3*v + 162*x^3 + 38718*x^2*u - 610578*x*u^2,
↪ + 33434694/11*u^3 - 4536*x^2*v + 73872*x*u*v - 2745576/11*u^2 - 1660800/11*u
↪ 580068*x*u - 67821354/11*u^2 - 185976*x*v + 14143896/11*u*v + 7533*x - 20437029/
↪ 11*u - 12389112/11*v + 19964151/11
```

```
sage: Psi2(71) # long time (1 second)
-2209380711722505179506258739515288584116147237393815266468076436521/71*u^210 + ..
↪. - 14790739586438315394567393301990769678157425619440464678252277649/71
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_13_0(E)`

Returns list of all 13-isogenies from E when the j-invariant is 0.

OUTPUT:

(list) 13-isogenies with codomain E. In general these are normalised; but if  $-3$  is a square then there are two endomorphisms of degree 13, for which the codomain is the same as the domain.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 13.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(13)`.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_13_0
```

Endomorphisms of degree 13 will exist when  $-3$  is a square:

```
sage: K.<r> = QuadraticField(-3)
sage: E = EllipticCurve(K, [0, r]); E
Elliptic Curve defined by y^2 = x^3 + r over Number Field in r with defining
↪polynomial x^2 + 3
sage: isogenies_13_0(E)
[Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + r over Number
↪Field in r with defining polynomial x^2 + 3 to Elliptic Curve defined by y^2 =
↪x^3 + r over Number Field in r with defining polynomial x^2 + 3,
Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + r over Number
↪Field in r with defining polynomial x^2 + 3 to Elliptic Curve defined by y^2 =
↪x^3 + r over Number Field in r with defining polynomial x^2 + 3]
sage: isogenies_13_0(E)[0].rational_maps()
((7/338*r + 23/338)*x^13 + (-164/13*r - 420/13)*x^10 + (720/13*r + 3168/13)*x^7
↪+ (3840/13*r - 576/13)*x^4 + (4608/13*r + 2304/13)*x)/(x^12 + (4*r + 36)*x^9 +
↪(1080/13*r + 3816/13)*x^6 + (2112/13*r - 5184/13)*x^3 + (-17280/169*r - 1152/
↪169)), ((18/2197*r + 35/2197)*x^18*y + (23142/2197*r + 35478/2197)*x^15*y + (-
↪1127520/2197*r - 1559664/2197)*x^12*y + (-87744/2197*r + 5992704/2197)*x^9*y +
↪(-6625152/2197*r - 9085824/2197)*x^6*y + (-28919808/2197*r - 2239488/2197)*x^
↪3*y + (-1990656/2197*r - 3870720/2197)*y)/(x^18 + (6*r + 54)*x^15 + (3024/13*r
↪+ 11808/13)*x^12 + (31296/13*r + 51840/13)*x^9 + (487296/169*r - 2070144/169)*x^
↪6 + (-940032/169*r + 248832/169)*x^3 + (1990656/2197*r + 3870720/2197)))
```

An example of endomorphisms over a finite field:

```
sage: K = GF(19^2, 'a')
sage: E = EllipticCurve(j=K(0)); E
Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field in a of size 19^2
sage: isogenies_13_0(E)
[Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field in a of size 19^2 to Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field in a of size 19^2,
Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field in a of size 19^2 to Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field in a of size 19^2]
```

```
sage: isogenies_13_0(E)[0].rational_maps()
((6*x^13 - 6*x^10 - 3*x^7 + 6*x^4 + x)/(x^12 - 5*x^9 - 9*x^6 - 7*x^3 + 5), (-8*x^
↪18*y - 9*x^15*y + 9*x^12*y - 5*x^9*y + 5*x^6*y - 7*x^3*y + 7*y)/(x^18 + 2*x^15
↪+ 3*x^12 - x^9 + 8*x^6 - 9*x^3 + 7))
```

A previous implementation did not work in some characteristics:

```
sage: K = GF(29)
sage: E = EllipticCurve(j=K(0))
sage: isogenies_13_0(E)
[Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪Field of size 29 to Elliptic Curve defined by y^2 = x^3 + 26*x + 12 over Finite
↪Field of size 29, Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3
↪+ 1 over Finite Field of size 29 to Elliptic Curve defined by y^2 = x^3 + 16*x
↪+ 28 over Finite Field of size 29]
```

```
sage: K = GF(101)
sage: E = EllipticCurve(j=K(0)); E.ainvs()
(0, 0, 0, 0, 1)
sage: [phi.codomain().ainvs() for phi in isogenies_13_0(E)]
[(0, 0, 0, 64, 36), (0, 0, 0, 42, 66)]
```

```
sage: x = polygen(QQ)
sage: f = x^12 + 78624*x^9 - 130308048*x^6 + 2270840832*x^3 - 54500179968
sage: K.<a> = NumberField(f)
sage: E = EllipticCurve(j=K(0)); E.ainvs()
(0, 0, 0, 0, 1)
sage: [phi.codomain().ainvs() for phi in isogenies_13_0(E)]
[(0,
0,
20360599/165164973653422080*a^11 - 3643073/41291243413355520*a^10 - 101/
↪8789110986240*a^9 + 5557619461/573489491852160*a^8 - 82824971/11947697746920*a^
↪7 - 19487/21127670640*a^6 - 475752603733/29409717530880*a^5 + 87205112531/
↪7352429382720*a^4 + 8349/521670880*a^3 + 5858744881/12764634345*a^2 -
↪1858703809/2836585410*a + 58759402/48906645,
-139861295/2650795873449984*a^11 - 3455957/5664093746688*a^10 - 345310571/
↪50976843720192*a^9 - 500530795/118001953056*a^8 - 12860048113/265504394376*a^7 -
↪25007420461/44250732396*a^6 + 458134176455/1416023436672*a^5 + 16701880631/
↪9077073312*a^4 + 155941666417/9077073312*a^3 + 3499310115/378211388*a^2 -
↪736774863/94552847*a - 21954102381/94552847,
579363345221/13763747804451840*a^11 + 371192377511/860234237778240*a^10 +
↪8855090365657/1146978983704320*a^9 + 5367261541663/1633873196160*a^8 +
↪614883554332193/15930263662560*a^7 + 30485197378483/68078049840*a^6 -
↪131000897588387/2450809794240*a^5 - 203628705777949/306351224280*a^4 -
↪1587619388190379/204234149520*a^3 + 14435069706551/11346341640*a^2 +
↪7537273048614/472764235*a + 89198980034806/472764235),
(0,
0,
20360599/165164973653422080*a^11 - 3643073/41291243413355520*a^10 - 101/
↪8789110986240*a^9 + 5557619461/573489491852160*a^8 - 82824971/11947697746920*a^
↪7 - 19487/21127670640*a^6 - 475752603733/29409717530880*a^5 + 87205112531/
↪7352429382720*a^4 + 8349/521670880*a^3 + 5858744881/12764634345*a^2 -
↪1858703809/2836585410*a + 58759402/48906645,
-6465569317/1325397936724992*a^11 - 112132307/1960647835392*a^10 - 17075412917/
↪25488421860096*a^9 - 207832519229/531008788752*a^8 - 1218275067617/
↪265504394376*a^7 - 9513766502551/177002929584*a^6 + 4297077855437/
↪708011718336*a^5 + 354485975837/4538536656*a^4 + 4199379308059/4538536656*a^3 -
↪30841577919/189105694*a^2 - 181916484042/94552847*a - 2135779171614/94552847,
```

```

-132601797212627/3440936951112960*a^11 - 6212467020502021/13763747804451840*a^
↪10 - 1515926454902497/286744745926080*a^9 - 15154913741799637/4901619588480*a^8
↪- 576888119803859263/15930263662560*a^7 - 86626751639648671/204234149520*a^6 +
↪16436657569218427/306351224280*a^5 + 1540027900265659087/2450809794240*a^4 +
↪375782662805915809/51058537380*a^3 - 14831920924677883/11346341640*a^2 -
↪7237947774817724/472764235*a - 84773764066089509/472764235)]

```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_13_1728(E)`

Returns list of all 13-isogenies from E when the j-invariant is 1728.

OUTPUT:

(list) 13-isogenies with codomain E. In general these are normalised; but if  $-1$  is a square then there are two endomorphisms of degree 13, for which the codomain is the same as the domain; and over  $\mathbb{Q}$  or a number field, the codomain is a global minimal model where possible.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 13.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(13)`.

---

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_13_
↪1728

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,i,0]); E.ainvs()
(0, 0, 0, i, 0)
sage: isogenies_13_1728(E)
[Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + i*x over Number
↪Field in i with defining polynomial x^2 + 1 to Elliptic Curve defined by y^2 =
↪x^3 + i*x over Number Field in i with defining polynomial x^2 + 1,
Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + i*x over Number
↪Field in i with defining polynomial x^2 + 1 to Elliptic Curve defined by y^2 =
↪x^3 + i*x over Number Field in i with defining polynomial x^2 + 1]

```

```

sage: K = GF(83)
sage: E = EllipticCurve(K, [0,0,0,5,0]); E.ainvs()
(0, 0, 0, 5, 0)
sage: isogenies_13_1728(E)
[]
sage: K = GF(89)
sage: E = EllipticCurve(K, [0,0,0,5,0]); E.ainvs()
(0, 0, 0, 5, 0)
sage: isogenies_13_1728(E)
[Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + 5*x over Finite
↪Field of size 89 to Elliptic Curve defined by y^2 = x^3 + 5*x over Finite
↪Field of size 89,
Isogeny of degree 13 from Elliptic Curve defined by y^2 = x^3 + 5*x over Finite
↪Field of size 89 to Elliptic Curve defined by y^2 = x^3 + 5*x over Finite
↪Field of size 89]

```

```

sage: K = GF(23)
sage: E = EllipticCurve(K, [1,0])

```

```
sage: isogenies_13_1728(E)
[Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3 + x$  over Finite
Field of size 23 to Elliptic Curve defined by  $y^2 = x^3 + 16$  over Finite Field
of size 23, Isogeny of degree 13 from Elliptic Curve defined by  $y^2 = x^3 + x$ 
over Finite Field of size 23 to Elliptic Curve defined by  $y^2 = x^3 + 7$  over
Finite Field of size 23]
```

```
sage: x = polygon(QQ)
sage: f = x^12 + 1092*x^10 - 432432*x^8 + 6641024*x^6 - 282896640*x^4 -
149879808*x^2 - 349360128
sage: K.<a> = NumberField(f)
sage: E = EllipticCurve(K, [1,0])
sage: [phi.codomain().ainvs() for phi in isogenies_13_1728(E)]
[(0,
0,
0,
-4225010072113/3063768069807341568*a^10 - 24841071989413/15957125363579904*a^8 +
11179537789374271/21276167151439872*a^6 - 407474562289492049/
47871376090739712*a^4 + 1608052769560747/4522994717568*a^2 + 7786720245212809/
36937790193472,
-363594277511/574456513088876544*a^11 - 7213386922793/2991961005671232*a^9 -
2810970361185589/1329760446964992*a^7 + 281503836888046601/8975883017013696*a^5,
-1287313166530075/848061509544*a^3 + 9768837984886039/6925835661276*a),
(0,
0,
0,
-4225010072113/3063768069807341568*a^10 - 24841071989413/15957125363579904*a^8 +
11179537789374271/21276167151439872*a^6 - 407474562289492049/
47871376090739712*a^4 + 1608052769560747/4522994717568*a^2 + 7786720245212809/
36937790193472,
363594277511/574456513088876544*a^11 + 7213386922793/2991961005671232*a^9 +
2810970361185589/1329760446964992*a^7 - 281503836888046601/8975883017013696*a^5,
+1287313166530075/848061509544*a^3 - 9768837984886039/6925835661276*a)]
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_2(E)`

Returns a list of all 2-isogenies with domain E.

INPUT:

- E – an elliptic curve.

OUTPUT:

(list) 2-isogenies with domain E. In general these are normalised, but over  $\mathbb{Q}$  and other number fields, the codomain is a minimal model where possible.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_2
sage: E = EllipticCurve('14a1'); E
Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x - 6$  over Rational Field
sage: [phi.codomain().ainvs() for phi in isogenies_2(E)]
[(1, 0, 1, -36, -70)]

sage: E = EllipticCurve([1,2,3,4,5]); E
Elliptic Curve defined by  $y^2 + xy + 3y = x^3 + 2x^2 + 4x + 5$  over Rational
Field
sage: [phi.codomain().ainvs() for phi in isogenies_2(E)]
[]
```



```
sage: E = EllipticCurve(QQbar, [9,8]); E
Elliptic Curve defined by  $y^2 = x^3 + 9x + 8$  over Algebraic Field
sage: isogenies_2(E) # not implemented
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_3(E)`

Returns a list of all 3-isogenies with domain E.

INPUT:

- E – an elliptic curve.

OUTPUT:

(list) 3-isogenies with domain E. In general these are normalised, but over  $\mathbb{Q}$  or a number field, the codomain is a global minimal model where possible.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_3
sage: E = EllipticCurve(GF(17), [1,1])
sage: [phi.codomain().ainvs() for phi in isogenies_3(E)]
[(0, 0, 0, 9, 7), (0, 0, 0, 0, 1)]

sage: E = EllipticCurve(GF(17^2, 'a'), [1,1])
sage: [phi.codomain().ainvs() for phi in isogenies_3(E)]
[(0, 0, 0, 9, 7), (0, 0, 0, 0, 1), (0, 0, 0, 5*a + 1, a + 13), (0, 0, 0, 12*a + 6,
↪ 16*a + 14)]

sage: E = EllipticCurve('19a1')
sage: [phi.codomain().ainvs() for phi in isogenies_3(E)]
[(0, 1, 1, 1, 0), (0, 1, 1, -769, -8470)]

sage: E = EllipticCurve([1,1])
sage: [phi.codomain().ainvs() for phi in isogenies_3(E)]
[]
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_5_0(E)`

Returns a list of all the 5-isogenies with domain E when the j-invariant is 0.

OUTPUT:

(list) 5-isogenies with codomain E. In general these are normalised, but over  $\mathbb{Q}$  or a number field, the codomain is a global minimal model where possible.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 5.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(5)`.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_5_0
sage: E = EllipticCurve([0,12])
sage: isogenies_5_0(E)
[]

sage: E = EllipticCurve(GF(13^2, 'a'), [0,-3])
sage: isogenies_5_0(E)
```

```
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + 10$  over Finite
↪Field in a of size  $13^2$  to Elliptic Curve defined by  $y^2 = x^3 + (4*a+6)*x +$ 
↪ $(2*a+10)$  over Finite Field in a of size  $13^2$ , Isogeny of degree 5 from Elliptic
↪Curve defined by  $y^2 = x^3 + 10$  over Finite Field in a of size  $13^2$  to Elliptic
↪Curve defined by  $y^2 = x^3 + (12*a+5)*x + (2*a+10)$  over Finite Field in a of
↪size  $13^2$ , Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + 10$ 
↪over Finite Field in a of size  $13^2$  to Elliptic Curve defined by  $y^2 = x^3 +$ 
↪ $(10*a+2)*x + (2*a+10)$  over Finite Field in a of size  $13^2$ , Isogeny of degree 5
↪from Elliptic Curve defined by  $y^2 = x^3 + 10$  over Finite Field in a of size  $13^2$ 
↪to Elliptic Curve defined by  $y^2 = x^3 + (3*a+12)*x + (11*a+12)$  over Finite
↪Field in a of size  $13^2$ , Isogeny of degree 5 from Elliptic Curve defined by  $y^2$ 
↪ $= x^3 + 10$  over Finite Field in a of size  $13^2$  to Elliptic Curve defined by  $y^2$ 
↪ $= x^3 + (a+4)*x + (11*a+12)$  over Finite Field in a of size  $13^2$ , Isogeny of
↪degree 5 from Elliptic Curve defined by  $y^2 = x^3 + 10$  over Finite Field in a
↪of size  $13^2$  to Elliptic Curve defined by  $y^2 = x^3 + (9*a+10)*x + (11*a+12)$ 
↪over Finite Field in a of size  $13^2$ ]
```

```
sage: K.<a> = NumberField(x**6-320*x**3-320)
```

```
sage: E = EllipticCurve(K, [0,0,1,0,0])
```

```
sage: isogenies_5_0(E)
```

```
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3$  over Number
↪Field in a with defining polynomial  $x^6 - 320*x^3 - 320$  to Elliptic Curve
↪defined by  $y^2 + y = x^3 + (643/8*a^5-15779/48*a^4-32939/24*a^3-71989/2*a^2$ 
↪ $+214321/6*a-112115/3)*x + (2901961/96*a^5+4045805/48*a^4+12594215/18*a^3-$ 
↪ $30029635/6*a^2+15341626/3*a-38944312/9)$  over Number Field in a with defining
↪polynomial  $x^6 - 320*x^3 - 320$ ,
```

```
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3$  over Number
↪Field in a with defining polynomial  $x^6 - 320*x^3 - 320$  to Elliptic Curve
↪defined by  $y^2 + y = x^3 + (-1109/8*a^5-53873/48*a^4-180281/24*a^3-14491/2*a^2$ 
↪ $+35899/6*a-43745/3)*x + (-17790679/96*a^5-60439571/48*a^4-77680504/9*a^3$ 
↪ $+1286245/6*a^2-4961854/3*a-73854632/9)$  over Number Field in a with defining
↪polynomial  $x^6 - 320*x^3 - 320]$ 
```

```
sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_5_1728(E)
```

Returns a list of 5-isogenies with domain E when the j-invariant is 1728.

OUTPUT:

(list) 5-isogenies with codomain E. In general these are normalised; but if  $-1$  is a square then there are two endomorphisms of degree 5, for which the codomain is the same as the domain curve; and over  $\mathbb{Q}$  or a number field, the codomain is a global minimal model where possible.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 5.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(5)`.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_5_
↪1728
sage: E = EllipticCurve([7,0])
sage: isogenies_5_1728(E)
[]

sage: E = EllipticCurve(GF(13), [11,0])
```

```
sage: isogenies_5_1728(E)
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + 11x$  over Finite_
↪Field of size 13 to Elliptic Curve defined by  $y^2 = x^3 + 11x$  over Finite_
↪Field of size 13,
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + 11x$  over Finite_
↪Field of size 13 to Elliptic Curve defined by  $y^2 = x^3 + 11x$  over Finite_
↪Field of size 13]
```

An example of endomorphisms of degree 5:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [0, 0, 0, 1, 0])
sage: isogenies_5_1728(E)
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + x$  over Number_
↪Field in i with defining polynomial  $x^2 + 1$  to Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + x$  over Number Field in i with defining polynomial  $x^2 + 1$ ,
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + x$  over Number_
↪Field in i with defining polynomial  $x^2 + 1$  to Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + x$  over Number Field in i with defining polynomial  $x^2 + 1$ ]
sage: _[0].rational_maps()
(( (4/25*i + 3/25)*x^5 + (4/5*i - 2/5)*x^3 - x)/(x^4 + (-4/5*i + 2/5)*x^2 + (-4/
↪25*i - 3/25)),
( (11/125*i + 2/125)*x^6*y + (-23/125*i + 64/125)*x^4*y + (141/125*i + 162/125)*x^
↪2*y + (3/25*i - 4/25)*y)/(x^6 + (-6/5*i + 3/5)*x^4 + (-12/25*i - 9/25)*x^2 + (2/
↪125*i - 11/125)))
```

An example of 5-isogenies over a number field:

```
sage: K.<a> = NumberField(x**4+20*x**2-80)
sage: K(5).is_square() #necessary but not sufficient!
True
sage: E = EllipticCurve(K, [0, 0, 0, 1, 0])
sage: isogenies_5_1728(E)
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + x$  over Number_
↪Field in a with defining polynomial  $x^4 + 20x^2 - 80$  to Elliptic Curve defined_
↪by  $y^2 = x^3 + (-753/4*a^2-4399)*x + (2779*a^3+65072*a)$  over Number Field in a_
↪with defining polynomial  $x^4 + 20x^2 - 80$ ,
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 = x^3 + x$  over Number_
↪Field in a with defining polynomial  $x^4 + 20x^2 - 80$  to Elliptic Curve defined_
↪by  $y^2 = x^3 + (-753/4*a^2-4399)*x + (-2779*a^3-65072*a)$  over Number Field in a_
↪with defining polynomial  $x^4 + 20x^2 - 80$ ]
```

See [trac ticket #19840](#):

```
sage: K.<a> = NumberField(x^4 - 5*x^2 + 5)
sage: E = EllipticCurve([a^2 + a + 1, a^3 + a^2 + a + 1, a^2 + a, 17*a^3 + 34*a^2_
↪- 16*a - 37, 54*a^3 + 105*a^2 - 66*a - 135])
sage: len(E.isogenies_prime_degree(5))
2
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_5_
↪1728
sage: [phi.codomain().j_invariant() for phi in isogenies_5_1728(E)]
[19691491018752*a^2 - 27212977933632, 19691491018752*a^2 - 27212977933632]
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_7_0(E)`

Returns list of all 7-isogenies from E when the j-invariant is 0.

OUTPUT:

(list) 7-isogenies with codomain  $E$ . In general these are normalised; but if  $-3$  is a square then there are two endomorphisms of degree 7, for which the codomain is the same as the domain; and over  $\mathbf{Q}$  or a number field, the codomain is a global minimal model where possible.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 7.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(7)`.

---

#### EXAMPLES:

First some examples of endomorphisms:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_7_0
sage: K.<r> = QuadraticField(-3)
sage: E = EllipticCurve(K, [0,1])
sage: isogenies_7_0(E)
[Isogeny of degree 7 from Elliptic Curve defined by  $y^2 = x^3 + 1$  over Number
↪Field in r with defining polynomial  $x^2 + 3$  to Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + 1$  over Number Field in r with defining polynomial  $x^2 + 3$ ,
Isogeny of degree 7 from Elliptic Curve defined by  $y^2 = x^3 + 1$  over Number
↪Field in r with defining polynomial  $x^2 + 3$  to Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + 1$  over Number Field in r with defining polynomial  $x^2 + 3$ ]

sage: E = EllipticCurve(GF(13^2, 'a'), [0, -3])
sage: isogenies_7_0(E)
[Isogeny of degree 7 from Elliptic Curve defined by  $y^2 = x^3 + 10$  over Finite
↪Field in a of size  $13^2$  to Elliptic Curve defined by  $y^2 = x^3 + 10$  over Finite
↪Field in a of size  $13^2$ , Isogeny of degree 7 from Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + 10$  over Finite Field in a of size  $13^2$  to Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + 10$  over Finite Field in a of size  $13^2$ ]
```

Now some examples of 7-isogenies which are not endomorphisms:

```
sage: K = GF(101)
sage: E = EllipticCurve(K, [0,1])
sage: isogenies_7_0(E)
[Isogeny of degree 7 from Elliptic Curve defined by  $y^2 = x^3 + 1$  over Finite
↪Field of size 101 to Elliptic Curve defined by  $y^2 = x^3 + 55x + 100$  over
↪Finite Field of size 101, Isogeny of degree 7 from Elliptic Curve defined by  $y^2 =$ 
↪ $x^3 + 1$  over Finite Field of size 101 to Elliptic Curve defined by  $y^2 = x^3 +$ 
↪ $83x + 26$  over Finite Field of size 101]
```

Examples over a number field:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_7_0
sage: E = EllipticCurve('27a1').change_ring(QuadraticField(-3, 'r'))
sage: isogenies_7_0(E)
[Isogeny of degree 7 from Elliptic Curve defined by  $y^2 + y = x^3 + (-7)$  over
↪Number Field in r with defining polynomial  $x^2 + 3$  to Elliptic Curve defined by
↪ $y^2 + y = x^3 + (-7)$  over Number Field in r with defining polynomial  $x^2 + 3$ ,
Isogeny of degree 7 from Elliptic Curve defined by  $y^2 + y = x^3 + (-7)$  over
↪Number Field in r with defining polynomial  $x^2 + 3$  to Elliptic Curve defined by
↪ $y^2 + y = x^3 + (-7)$  over Number Field in r with defining polynomial  $x^2 + 3$ ]

sage: K.<a> = NumberField(x^6 + 1512*x^3 - 21168)
```

```

sage: E = EllipticCurve(K, [0,1])
sage: isogs = isogenies_7_0(E)
sage: [phi.codomain().a_invariants() for phi in isogs]
[(0,
 0,
 0,
 -415/98*a^5 - 675/14*a^4 + 2255/7*a^3 - 74700/7*a^2 - 25110*a - 66420,
 -141163/56*a^5 + 1443453/112*a^4 - 374275/2*a^3 - 3500211/2*a^2 - 17871975/4*a -
 ↪ 7710065),
 (0,
 0,
 0,
 -24485/392*a^5 - 1080/7*a^4 - 2255/7*a^3 - 1340865/14*a^2 - 230040*a - 553500,
 1753037/56*a^5 + 8345733/112*a^4 + 374275/2*a^3 + 95377029/2*a^2 + 458385345/
 ↪ 4*a + 275241835)]
sage: [phi.codomain().j_invariant() for phi in isogs]
[158428486656000/7*a^3 - 313976217600000,
 -158428486656000/7*a^3 - 34534529335296000]

```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_7_1728(E)`  
Returns list of all 7-isogenies from E when the j-invariant is 1728.

OUTPUT:

(list) 7-isogenies with codomain E. In general these are normalised; but over  $\mathbf{Q}$  or a number field, the codomain is a global minimal model where possible.

---

**Note:** This implementation requires that the characteristic is not 2, 3, or 7.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(7)`.

---

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_7_
↪ 1728
sage: E = EllipticCurve(GF(47), [1, 0])
sage: isogenies_7_1728(E)
[Isogeny of degree 7 from Elliptic Curve defined by y^2 = x^3 + x over Finite_
↪ Field of size 47 to Elliptic Curve defined by y^2 = x^3 + 26 over Finite Field_
↪ of size 47,
Isogeny of degree 7 from Elliptic Curve defined by y^2 = x^3 + x over Finite_
↪ Field of size 47 to Elliptic Curve defined by y^2 = x^3 + 21 over Finite Field_
↪ of size 47]

```

An example in characteristic 53 (for which an earlier implementation did not work):

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_7_
↪ 1728
sage: E = EllipticCurve(GF(53), [1, 0])
sage: isogenies_7_1728(E)
[]
sage: E = EllipticCurve(GF(53^2, 'a'), [1, 0])
sage: [iso.codomain().ainvs() for iso in isogenies_7_1728(E)]
[(0, 0, 0, 36, 19*a + 15), (0, 0, 0, 36, 34*a + 38), (0, 0, 0, 33, 39*a + 28), (0,
↪ 0, 0, 33, 14*a + 25), (0, 0, 0, 19, 45*a + 16), (0, 0, 0, 19, 8*a + 37), (0, 0,
↪ 0, 3, 45*a + 16), (0, 0, 0, 3, 8*a + 37)]

```

```

sage: K.<a> = NumberField(x^8 + 84*x^6 - 1890*x^4 + 644*x^2 - 567)
sage: E = EllipticCurve(K, [1, 0])
sage: isogs = isogenies_7_1728(E)
sage: [phi.codomain().j_invariant() for phi in isogs]
[-526110256146528/53*a^6 + 183649373229024*a^4 - 3333881559996576/53*a^2 +
↪ 2910267397643616/53,
-526110256146528/53*a^6 + 183649373229024*a^4 - 3333881559996576/53*a^2 +
↪ 2910267397643616/53]
sage: E1 = isogs[0].codomain()
sage: E2 = isogs[1].codomain()
sage: E1.is_isomorphic(E2)
False
sage: E1.is_quadratic_twist(E2)
-1

```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_prime_degree(E, l)`

Returns a list of  $l$ -isogenies with domain  $E$ .

INPUT:

- $E$  – an elliptic curve.
- $l$  – a prime.

OUTPUT:

(list) a list of all isogenies of degree  $l$ . If the characteristic is  $l$  then only separable isogenies are constructed.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
↪ prime_degree
sage: E = EllipticCurve_from_j(GF(2^6, 'a')(1))
sage: isogenies_prime_degree(E, 7)
[Isogeny of degree 7 from Elliptic Curve defined by y^2 + x*y = x^3 + 1 over
↪ Finite Field in a of size 2^6 to Elliptic Curve defined by y^2 + x*y = x^3 + x
↪ over Finite Field in a of size 2^6]
sage: E = EllipticCurve_from_j(GF(3^12, 'a')(2))
sage: isogenies_prime_degree(E, 17)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 2*x^2 + 2 over
↪ Finite Field in a of size 3^12 to Elliptic Curve defined by y^2 = x^3 + 2*x^2 +
↪ 2*x over Finite Field in a of size 3^12, Isogeny of degree 17 from Elliptic
↪ Curve defined by y^2 = x^3 + 2*x^2 + 2 over Finite Field in a of size 3^12 to
↪ Elliptic Curve defined by y^2 = x^3 + 2*x^2 + x + 2 over Finite Field in a of
↪ size 3^12]
sage: E = EllipticCurve('50a1')
sage: isogenies_prime_degree(E, 3)
[Isogeny of degree 3 from Elliptic Curve defined by y^2 + x*y + y = x^3 - x - 2
↪ over Rational Field to Elliptic Curve defined by y^2 + x*y + y = x^3 - 126*x -
↪ 552 over Rational Field]
sage: isogenies_prime_degree(E, 5)
[Isogeny of degree 5 from Elliptic Curve defined by y^2 + x*y + y = x^3 - x - 2
↪ over Rational Field to Elliptic Curve defined by y^2 + x*y + y = x^3 - 76*x +
↪ 298 over Rational Field]
sage: E = EllipticCurve([0, 0, 1, -1862, -30956])
sage: isogenies_prime_degree(E, 19)
[Isogeny of degree 19 from Elliptic Curve defined by y^2 + y = x^3 - 1862*x -
↪ 30956 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - 672182*x
↪ + 212325489 over Rational Field]

```

```

sage: E = EllipticCurve([0, -1, 0, -6288, 211072])
sage: isogenies_prime_degree(E, 37)
[Isogeny of degree 37 from Elliptic Curve defined by  $y^2 = x^3 - x^2 - 6288x + 211072$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - x^2 - 163137088x - 801950801728$  over Rational Field]

```

Isogenies of degree equal to the characteristic are computed (but only the separable isogeny). In the following example we consider an elliptic curve which is supersingular in characteristic 2 only:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      ↪ prime_degree
sage: ainvs = (0,1,1,-1,-1)
sage: for l in prime_range(50):
.....:     E = EllipticCurve(GF(l),ainvs)
.....:     isogenies_prime_degree(E,l)
[]
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2x + 2$  over Finite Field of size 3 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + x$  over Finite Field of size 3]
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 4x + 4$  over Finite Field of size 5 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 4x + 4$  over Finite Field of size 5]
[Isogeny of degree 7 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 6x + 6$  over Finite Field of size 7 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 4$  over Finite Field of size 7]
[Isogeny of degree 11 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 10x + 10$  over Finite Field of size 11 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + x + 1$  over Finite Field of size 11]
[Isogeny of degree 13 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 12x + 12$  over Finite Field of size 13 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 12x + 12$  over Finite Field of size 13]
[Isogeny of degree 17 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 16x + 16$  over Finite Field of size 17 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 15$  over Finite Field of size 17]
[Isogeny of degree 19 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 18x + 18$  over Finite Field of size 19 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 3x + 12$  over Finite Field of size 19]
[Isogeny of degree 23 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 22x + 22$  over Finite Field of size 23 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 22x + 22$  over Finite Field of size 23]
[Isogeny of degree 29 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 28x + 28$  over Finite Field of size 29 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 7x + 27$  over Finite Field of size 29]
[Isogeny of degree 31 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 30x + 30$  over Finite Field of size 31 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 15x + 16$  over Finite Field of size 31]
[Isogeny of degree 37 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 36x + 36$  over Finite Field of size 37 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 16x + 17$  over Finite Field of size 37]
[Isogeny of degree 41 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 40x + 40$  over Finite Field of size 41 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 33x + 16$  over Finite Field of size 41]
[Isogeny of degree 43 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 42x + 42$  over Finite Field of size 43 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 36$  over Finite Field of size 43]
[Isogeny of degree 47 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 46x + 46$  over Finite Field of size 47 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 42x + 34$  over Finite Field of size 47]

```

Note that the computation is faster for degrees equal to one of the genus 0 primes (2, 3, 5, 7, 13) or one of the hyperelliptic primes (11, 17, 19, 23, 29, 31, 41, 47, 59, 71) than when the generic code must be used:

```
sage: E = EllipticCurve(GF(101), [-3440, 77658])
sage: E.isogenies_prime_degree(71) # fast
[]
sage: E.isogenies_prime_degree(73) # not tested (very long time: 32s)
[]
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_prime_degree_general(E, l)`

Returns a list of  $l$ -isogenies with domain  $E$ .

INPUT:

- $E$  – an elliptic curve.
- $l$  – a prime.

OUTPUT:

(list) a list of all isogenies of degree  $l$ .

ALGORITHM:

This algorithm factors the  $l$ -division polynomial, then combines its factors to obtain kernels. See [KT2013], Chapter 3.

---

**Note:** This function works for any prime  $l$ . Normally one should use the function `isogenies_prime_degree()` which uses special functions for certain small primes.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      ↪ prime_degree_general
sage: E = EllipticCurve_from_j(GF(2^6, 'a')(1))
sage: isogenies_prime_degree_general(E, 7)
[Isogeny of degree 7 from Elliptic Curve defined by y^2 + x*y = x^3 + 1 over
↪ Finite Field in a of size 2^6 to Elliptic Curve defined by y^2 + x*y = x^3 + x
↪ over Finite Field in a of size 2^6]
sage: E = EllipticCurve_from_j(GF(3^12, 'a')(2))
sage: isogenies_prime_degree_general(E, 17)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 2*x^2 + 2 over
↪ Finite Field in a of size 3^12 to Elliptic Curve defined by y^2 = x^3 + 2*x^2 +
↪ 2*x over Finite Field in a of size 3^12, Isogeny of degree 17 from Elliptic
↪ Curve defined by y^2 = x^3 + 2*x^2 + 2 over Finite Field in a of size 3^12 to
↪ Elliptic Curve defined by y^2 = x^3 + 2*x^2 + x + 2 over Finite Field in a of
↪ size 3^12]
sage: E = EllipticCurve('50a1')
sage: isogenies_prime_degree_general(E, 3)
[Isogeny of degree 3 from Elliptic Curve defined by y^2 + x*y + y = x^3 - x - 2
↪ over Rational Field to Elliptic Curve defined by y^2 + x*y + y = x^3 - 126*x -
↪ 552 over Rational Field]
sage: isogenies_prime_degree_general(E, 5)
[Isogeny of degree 5 from Elliptic Curve defined by y^2 + x*y + y = x^3 - x - 2
↪ over Rational Field to Elliptic Curve defined by y^2 + x*y + y = x^3 - 76*x +
↪ 298 over Rational Field]
sage: E = EllipticCurve([0, 0, 1, -1862, -30956])
sage: isogenies_prime_degree_general(E, 19)
[Isogeny of degree 19 from Elliptic Curve defined by y^2 + y = x^3 - 1862*x -
↪ 30956 over Rational Field to Elliptic Curve defined by y^2 + y = x^3 - 672182*x
↪ + 212325489 over Rational Field]
```



```

sage: E = EllipticCurve([0, -1, 0, -6288, 211072])
sage: isogenies_prime_degree_general(E, 37) # long time (10s)
[Isogeny of degree 37 from Elliptic Curve defined by  $y^2 = x^3 - x^2 - 6288x + 211072$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - x^2 - 163137088x - 801950801728$  over Rational Field]

sage: E = EllipticCurve([-3440, 77658])
sage: isogenies_prime_degree_general(E, 43) # long time (16s)
[Isogeny of degree 43 from Elliptic Curve defined by  $y^2 = x^3 - 3440x + 77658$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - 6360560x - 6174354606$  over Rational Field]

```

Isogenies of degree equal to the characteristic are computed (but only the separable isogeny). In the following example we consider an elliptic curve which is supersingular in characteristic 2 only:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      prime_degree_general
sage: ainvs = (0,1,1,-1,-1)
sage: for l in prime_range(50):
....:     E = EllipticCurve(GF(1),ainvs)
....:     isogenies_prime_degree_general(E,l)
[]
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2x + 2$  over Finite Field of size 3 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + x$  over Finite Field of size 3]
[Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 4x + 4$  over Finite Field of size 5 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 4x + 4$  over Finite Field of size 5]
[Isogeny of degree 7 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 6x + 6$  over Finite Field of size 7 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 4$  over Finite Field of size 7]
[Isogeny of degree 11 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 10x + 10$  over Finite Field of size 11 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + x + 1$  over Finite Field of size 11]
[Isogeny of degree 13 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 12x + 12$  over Finite Field of size 13 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 12x + 12$  over Finite Field of size 13]
[Isogeny of degree 17 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 16x + 16$  over Finite Field of size 17 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 15$  over Finite Field of size 17]
[Isogeny of degree 19 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 18x + 18$  over Finite Field of size 19 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 3x + 12$  over Finite Field of size 19]
[Isogeny of degree 23 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 22x + 22$  over Finite Field of size 23 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 22x + 22$  over Finite Field of size 23]
[Isogeny of degree 29 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 28x + 28$  over Finite Field of size 29 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 7x + 27$  over Finite Field of size 29]
[Isogeny of degree 31 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 30x + 30$  over Finite Field of size 31 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 15x + 16$  over Finite Field of size 31]
[Isogeny of degree 37 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 36x + 36$  over Finite Field of size 37 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 16x + 17$  over Finite Field of size 37]
[Isogeny of degree 41 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 40x + 40$  over Finite Field of size 41 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 2 + 33x + 16$  over Finite Field of size 41]

```

```
[Isogeny of degree 43 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 42x + 42$  over Finite Field of size 43 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 36$  over Finite Field of size 43]
[Isogeny of degree 47 from Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 46x + 46$  over Finite Field of size 47 to Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 42x + 34$  over Finite Field of size 47]
```

Note that not all factors of degree  $(l-1)/2$  of the  $l$ -division polynomial are kernel polynomials. In this example, the 13-division polynomial factors as a product of 14 irreducible factors of degree 6 each, but only two those are kernel polynomials:

```
sage: F3 = GF(3)
sage: E = EllipticCurve(F3, [0,0,0,-1,0])
sage: Psi13 = E.division_polynomial(13)
sage: len([f for f,e in Psi13.factor() if f.degree()==6])
14
sage: len(E.isogenies_prime_degree(13))
2
```

Over  $\text{GF}(9)$  the other factors of degree 6 split into pairs of cubics which can be rearranged to give the remaining 12 kernel polynomials:

```
sage: len(E.change_ring(GF(3^2, 'a')).isogenies_prime_degree(13))
14
```

See [trac ticket #18589](#): the following example took 20s before, now only 4s:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [0,0,0,1,0])
sage: [phi.codomain().ainvs() for phi in E.isogenies_prime_degree(37)] # long time
[(0, 0, 0, -840*i + 1081, 0), (0, 0, 0, 840*i + 1081, 0)]
```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_prime_degree_genus_0(E, l=None)`

Returns list of  $l$ -isogenies with domain  $E$ .

INPUT:

- $E$  – an elliptic curve.
- $l$  – either `None` or 2, 3, 5, 7, or 13.

OUTPUT:

(list) When  $l$  is `None` a list of all isogenies of degree 2, 3, 5, 7 and 13, otherwise a list of isogenies of the given degree.

---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(l)`, which automatically calls the appropriate function.

---

ALGORITHM:

Cremona and Watkins [CW2005]. See also [KT2013], Chapter 4.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      ↪ prime_degree_genus_0
sage: E = EllipticCurve([0,12])
```

```

sage: isogenies_prime_degree_genus_0(E, 5)
[]

sage: E = EllipticCurve('1450c1')
sage: isogenies_prime_degree_genus_0(E)
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + x*y = x^3 + x^2 + 300*x - 1000$  over Rational Field to Elliptic Curve defined by  $y^2 + x*y = x^3 + x^2 - 5950*x - 182250$  over Rational Field]

sage: E = EllipticCurve('50a1')
sage: isogenies_prime_degree_genus_0(E)
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + x*y + y = x^3 - x - 2$  over Rational Field to Elliptic Curve defined by  $y^2 + x*y + y = x^3 - 126*x - 552$  over Rational Field,
Isogeny of degree 5 from Elliptic Curve defined by  $y^2 + x*y + y = x^3 - x - 2$  over Rational Field to Elliptic Curve defined by  $y^2 + x*y + y = x^3 - 76*x + 298$  over Rational Field]

```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_prime_degree_genus_plus_0(E, l=None)`

Returns list of  $l$  -isogenies with domain  $E$ .

INPUT:

- $E$  – an elliptic curve.
- $l$  – either None or 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71.

OUTPUT:

(list) When  $l$  is None a list of all isogenies of degree 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71, otherwise a list of isogenies of the given degree.

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(l)`, which automatically calls the appropriate function.

ALGORITHM:

See [KT2013], Chapter 5.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      ↪ prime_degree_genus_plus_0

sage: E = EllipticCurve('121a1')
sage: isogenies_prime_degree_genus_plus_0(E, 11)
[Isogeny of degree 11 from Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 30*x - 76$  over Rational Field to Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 305*x + 7888$  over Rational Field]

sage: E = EllipticCurve([1, 1, 0, -660, -7600])
sage: isogenies_prime_degree_genus_plus_0(E, 17)
[Isogeny of degree 17 from Elliptic Curve defined by  $y^2 + x*y = x^3 + x^2 - 660*x - 7600$  over Rational Field to Elliptic Curve defined by  $y^2 + x*y = x^3 + x^2 - 878710*x + 316677750$  over Rational Field]

sage: E = EllipticCurve([0, 0, 1, -1862, -30956])
sage: isogenies_prime_degree_genus_plus_0(E, 19)

```

```
[Isogeny of degree 19 from Elliptic Curve defined by  $y^2 + y = x^3 - 1862x - 30956$  over Rational Field to Elliptic Curve defined by  $y^2 + y = x^3 - 672182x + 212325489$  over Rational Field]
```

```
sage: K = QuadraticField(-295, 'a')
```

```
sage: a = K.gen()
```

```
sage: E = EllipticCurve_from_j((-484650135/16777216*a + 4549855725/16777216)
```

```
sage: isogenies_prime_degree_genus_plus_0(E, 23)
```

```
[Isogeny of degree 23 from Elliptic Curve defined by  $y^2 = x^3 + (-14460494784192904095/140737488355328*a + 270742665778826768325/140737488355328)*x + (37035998788154488846811217135/590295810358705651712*a - 1447451882571839266752561148725/590295810358705651712)$  over Number Field in a with defining polynomial  $x^2 + 295$  to Elliptic Curve defined by  $y^2 = x^3 + (-5130542435555445498495/140737488355328*a + 173233955029127361005925/140737488355328)*x + (-1104699335561165691575396879260545/590295810358705651712*a + 3169785826904210171629535101419675/590295810358705651712)$  over Number Field in a with defining polynomial  $x^2 + 295]$ 
```

```
sage: K = QuadraticField(-199, 'a')
```

```
sage: a = K.gen()
```

```
sage: E = EllipticCurve_from_j(94743000*a + 269989875)
```

```
sage: isogenies_prime_degree_genus_plus_0(E, 29)
```

```
[Isogeny of degree 29 from Elliptic Curve defined by  $y^2 = x^3 + (-153477413215038000*a + 5140130723072965125)*x + (297036215130547008455526000*a + 2854277047164317800973582250)$  over Number Field in a with defining polynomial  $x^2 + 199$  to Elliptic Curve defined by  $y^2 = x^3 + (251336161378040805000*a - 3071093219933084341875)*x + (-8411064283162168580187643221000*a + 34804337770798389546017184785250)$  over Number Field in a with defining polynomial  $x^2 + 199]$ 
```

```
sage: K = QuadraticField(253, 'a')
```

```
sage: a = K.gen()
```

```
sage: E = EllipticCurve_from_j(208438034112000*a - 3315409892960000)
```

```
sage: isogenies_prime_degree_genus_plus_0(E, 31)
```

```
[Isogeny of degree 31 from Elliptic Curve defined by  $y^2 = x^3 + (4146345122185433034677956608000*a - 65951656549965037259634800640000)*x + (-18329111516954473474583425393698245080252416000*a + 29154236611038392836651036806420414726012928)$  over Number Field in a with defining polynomial  $x^2 - 253$  to Elliptic Curve defined by  $y^2 = x^3 + (200339763852548615776123686912000*a - 3186599019027216904280948275200000)*x + (7443671791411479629112717260182286294850207744000*a - 118398847898864757209685951728838895495168655360000)$  over Number Field in a with defining polynomial  $x^2 - 253]$ 
```

```
sage: E = EllipticCurve_from_j(GF(5)(1))
```

```
sage: isogenies_prime_degree_genus_plus_0(E, 41)
```

```
[Isogeny of degree 41 from Elliptic Curve defined by  $y^2 = x^3 + x + 2$  over Finite Field of size 5 to Elliptic Curve defined by  $y^2 = x^3 + x + 3$  over Finite Field of size 5, Isogeny of degree 41 from Elliptic Curve defined by  $y^2 = x^3 + x + 2$  over Finite Field of size 5 to Elliptic Curve defined by  $y^2 = x^3 + x + 3$  over Finite Field of size 5]
```

```
sage: K = QuadraticField(5, 'a')
```

```
sage: a = K.gen()
```

```
sage: E = EllipticCurve_from_j(184068066743177379840*a - 411588709724712960000)
```

```
sage: isogenies_prime_degree_genus_plus_0(E, 47) # long time (4.3s)
```

```
[Isogeny of degree 47 from Elliptic Curve defined by  $y^2 = x^3 + (454562028554080355857852049849975895490560*a - 1016431595837124114668689286176511361024000)*x + (-249456798429896080881440540950393713303830363999480904280865120*a + 5578023587387104434512733202)$  over Number Field in a with defining polynomial  $x^2 - 5$  to Elliptic Curve defined by  $y^2 = x^3 + (39533118442361013730577638493616965245992960*a - 88398740199669828340617478832005245173760000)*x + (214030321479466610282320528611562368963830105830555363061803253760*a -$ 
```

```

sage: K = QuadraticField(-66827, 'a')
sage: a = K.gen()
sage: E = EllipticCurve_from_j((-98669236224000*a + 4401720074240000)
sage: isogenies_prime_degree_genus_plus_0(E, 59) # long time (25s, 2012)
[Isogeny of degree 59 from Elliptic Curve defined by y^2 = x^3 +
↪ (2605886146782144762297974784000*a+1893681048912773634944634716160000)*x + (-
↪ 116918454256410782232296183198067568744071168000*a+1701204353829466402718588235851401130481287
↪ over Number Field in a with defining polynomial x^2 + 66827 to Elliptic Curve
↪ defined by y^2 = x^3 + (-19387084027159786821400775098368000*a-
↪ 4882059104868154225052787156713472000)*x + (-
↪ 25659862010101415428713331477227179429538847260672000*a-
↪ 2596038148441293485938798119003462972840818381946880000) over Number Field in a
↪ with defining polynomial x^2 + 66827]

sage: E = EllipticCurve_from_j(GF(13)(5))
sage: isogenies_prime_degree_genus_plus_0(E, 71) # long time
[Isogeny of degree 71 from Elliptic Curve defined by y^2 = x^3 + x + 4 over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 = x^3 + 10*x + 7 over
↪ Finite Field of size 13, Isogeny of degree 71 from Elliptic Curve defined by y^
↪ 2 = x^3 + x + 4 over Finite Field of size 13 to Elliptic Curve defined by y^2 =
↪ x^3 + 10*x + 7 over Finite Field of size 13]

sage: E = EllipticCurve(GF(13), [0, 1, 1, 1, 0])
sage: isogenies_prime_degree_genus_plus_0(E)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 + y = x^3 + x^2 + x over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 + y = x^3 + x^2 + 10*x
↪ + 1 over Finite Field of size 13,
Isogeny of degree 17 from Elliptic Curve defined by y^2 + y = x^3 + x^2 + x over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 + y = x^3 + x^2 + 12*x
↪ + 4 over Finite Field of size 13,
Isogeny of degree 29 from Elliptic Curve defined by y^2 + y = x^3 + x^2 + x over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 + y = x^3 + x^2 + 12*x
↪ + 6 over Finite Field of size 13,
Isogeny of degree 29 from Elliptic Curve defined by y^2 + y = x^3 + x^2 + x over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 + y = x^3 + x^2 + 5*x
↪ + 6 over Finite Field of size 13,
Isogeny of degree 41 from Elliptic Curve defined by y^2 + y = x^3 + x^2 + x over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 + y = x^3 + x^2 + 12*x
↪ + 4 over Finite Field of size 13,
Isogeny of degree 41 from Elliptic Curve defined by y^2 + y = x^3 + x^2 + x over
↪ Finite Field of size 13 to Elliptic Curve defined by y^2 + y = x^3 + x^2 + 5*x
↪ + 6 over Finite Field of size 13]

```

sage.schemes.elliptic\_curves.isogeny\_small\_degree.isogenies\_prime\_degree\_genus\_plus\_0\_j0(E, l)

Returns a list of hyperelliptic 1-isogenies with domain  $E$  when  $j(E) = 0$ .

INPUT:

- $E$  – an elliptic curve with  $j$ -invariant 0.
- $l$  – 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71.

OUTPUT:

(list) a list of all isogenies of degree 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 1.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(1)`.

---

**EXAMPLES:**

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      ↪ prime_degree_genus_plus_0_j0

sage: u = polygen(QQ)
sage: K.<a> = NumberField(u^4+228*u^3+486*u^2-540*u+225)
sage: E = EllipticCurve(K, [0, -121/5*a^3-20691/5*a^2-29403/5*a+3267])
sage: isogenies_prime_degree_genus_plus_0_j0(E, 11)
[Isogeny of degree 11 from Elliptic Curve defined by y^2 = x^3 + (-121/5*a^3-
↪ 20691/5*a^2-29403/5*a+3267) over Number Field in a with defining polynomial x^4
↪ + 228*x^3 + 486*x^2 - 540*x + 225 to Elliptic Curve defined by y^2 = x^3 + (-
↪ 44286*a^2+178596*a-32670)*x + (-17863351/5*a^3+125072739/5*a^2-74353653/5*a-
↪ 682803) over Number Field in a with defining polynomial x^4 + 228*x^3 + 486*x^2
↪ - 540*x + 225, Isogeny of degree 11 from Elliptic Curve defined by y^2 = x^3 +
↪ (-121/5*a^3-20691/5*a^2-29403/5*a+3267) over Number Field in a with defining
↪ polynomial x^4 + 228*x^3 + 486*x^2 - 540*x + 225 to Elliptic Curve defined by y^
↪ 2 = x^3 + (-3267*a^3-740157*a^2+600039*a-277695)*x + (-17863351/5*a^3-
↪ 4171554981/5*a^2+3769467867/5*a-272366523) over Number Field in a with defining
↪ polynomial x^4 + 228*x^3 + 486*x^2 - 540*x + 225]

sage: E = EllipticCurve(GF(5^6, 'a'), [0, 1])
sage: isogenies_prime_degree_genus_plus_0_j0(E, 17)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪ Field in a of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2 over Finite
↪ Field in a of size 5^6, Isogeny of degree 17 from Elliptic Curve defined by y^2
↪ = x^3 + 1 over Finite Field in a of size 5^6 to Elliptic Curve defined by y^2 =
↪ x^3 + 2 over Finite Field in a of size 5^6, Isogeny of degree 17 from Elliptic
↪ Curve defined by y^2 = x^3 + 1 over Finite Field in a of size 5^6 to Elliptic
↪ Curve defined by y^2 = x^3 + 2 over Finite Field in a of size 5^6, Isogeny of
↪ degree 17 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field in a
↪ of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2 over Finite Field in a
↪ of size 5^6, Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 1
↪ over Finite Field in a of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2
↪ over Finite Field in a of size 5^6, Isogeny of degree 17 from Elliptic Curve
↪ defined by y^2 = x^3 + 1 over Finite Field in a of size 5^6 to Elliptic Curve
↪ defined by y^2 = x^3 + 2 over Finite Field in a of size 5^6, Isogeny of degree
↪ 17 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field in a of size
↪ 5^6 to Elliptic Curve defined by y^2 = x^3 + 2 over Finite Field in a of size 5^
↪ 6, Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 1 over
↪ Finite Field in a of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2 over
↪ Finite Field in a of size 5^6, Isogeny of degree 17 from Elliptic Curve defined
↪ by y^2 = x^3 + 1 over Finite Field in a of size 5^6 to Elliptic Curve defined
↪ by y^2 = x^3 + 2 over Finite Field in a of size 5^6, Isogeny of degree 17 from
↪ Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field in a of size 5^6 to
↪ Elliptic Curve defined by y^2 = x^3 + 2 over Finite Field in a of size 5^6,
↪ Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite
↪ Field in a of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2 over Finite
↪ Field in a of size 5^6, Isogeny of degree 17 from Elliptic Curve defined by y^2
↪ = x^3 + 1 over Finite Field in a of size 5^6 to Elliptic Curve defined by y^2 =
↪ x^3 + 2 over Finite Field in a of size 5^6, Isogeny of degree 17 from Elliptic
↪ Curve defined by y^2 = x^3 + 1 over Finite Field in a of size 5^6 to Elliptic
↪ Curve defined by y^2 = x^3 + 2 over Finite Field in a of size 5^6, Isogeny of
↪ degree 17 from Elliptic Curve defined by y^2 = x^3 + 1 over Finite Field in a
↪ of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2 over Finite Field in a
↪ of size 5^6, Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + 1
↪ over Finite Field in a of size 5^6 to Elliptic Curve defined by y^2 = x^3 + 2
↪ over Finite Field in a of size 5^6, Isogeny of degree 17 from Elliptic Curve
```

---

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_prime_degree_genus_plus_0_j1728`

Returns a list of 1-isogenies with domain  $E$  when  $j(E) = 1728$ .

INPUT:

- $E$  – an elliptic curve with  $j$ -invariant 1728.
- 1 – 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71.

OUTPUT:

(list) a list of all isogenies of degree 11, 17, 19, 23, 29, 31, 41, 47, 59, or 71.

---

**Note:** This implementation requires that the characteristic is not 2, 3 or 1.

---



---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(1)`.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
      ↪ prime_degree_genus_plus_0_j1728

sage: u = polygen(QQ)
sage: K.<a> = NumberField(u^6 - 522*u^5 - 10017*u^4 + 2484*u^3 - 5265*u^2 +
      ↪ 12150*u - 5103)
sage: E = EllipticCurve(K, [-75295/1335852*a^5+13066735/445284*a^4+44903485/
      ↪ 74214*a^3+17086861/24738*a^2+11373021/16492*a-1246245/2356,0])
sage: isogenies_prime_degree_genus_plus_0_j1728(E,11)
[Isogeny of degree 11 from Elliptic Curve defined by y^2 = x^3 + (-75295/
      ↪ 1335852*a^5+13066735/445284*a^4+44903485/74214*a^3+17086861/24738*a^2+11373021/
      ↪ 16492*a-1246245/2356)*x over Number Field in a with defining polynomial x^6 -
      ↪ 522*x^5 - 10017*x^4 + 2484*x^3 - 5265*x^2 + 12150*x - 5103 to Elliptic Curve
      ↪ defined by y^2 = x^3 + (9110695/1335852*a^5-1581074935/445284*a^4-5433321685/
      ↪ 74214*a^3-3163057249/24738*a^2+1569269691/16492*a+73825125/2356)*x + (-
      ↪ 3540460*a^3+30522492*a^2-7043652*a-5031180) over Number Field in a with
      ↪ defining polynomial x^6 - 522*x^5 - 10017*x^4 + 2484*x^3 - 5265*x^2 + 12150*x -
      ↪ 5103, Isogeny of degree 11 from Elliptic Curve defined by y^2 = x^3 + (-75295/
      ↪ 1335852*a^5+13066735/445284*a^4+44903485/74214*a^3+17086861/24738*a^2+11373021/
      ↪ 16492*a-1246245/2356)*x over Number Field in a with defining polynomial x^6 -
      ↪ 522*x^5 - 10017*x^4 + 2484*x^3 - 5265*x^2 + 12150*x - 5103 to Elliptic Curve
      ↪ defined by y^2 = x^3 + (9110695/1335852*a^5-1581074935/445284*a^4-5433321685/
      ↪ 74214*a^3-3163057249/24738*a^2+1569269691/16492*a+73825125/2356)*x + (3540460*a^
      ↪ 3-30522492*a^2+7043652*a+5031180) over Number Field in a with defining
      ↪ polynomial x^6 - 522*x^5 - 10017*x^4 + 2484*x^3 - 5265*x^2 + 12150*x - 5103]
sage: i = QuadraticField(-1,'i').gen()
sage: E = EllipticCurve([-1-2*i,0])
sage: isogenies_prime_degree_genus_plus_0_j1728(E,17)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + (-2*i-1)*x over
      ↪ Number Field in i with defining polynomial x^2 + 1 to Elliptic Curve defined by
      ↪ y^2 = x^3 + (-82*i-641)*x over Number Field in i with defining polynomial x^2 +
      ↪ 1,
Isogeny of degree 17 from Elliptic Curve defined by y^2 = x^3 + (-2*i-1)*x over
      ↪ Number Field in i with defining polynomial x^2 + 1 to Elliptic Curve defined by
      ↪ y^2 = x^3 + (-562*i+319)*x over Number Field in i with defining polynomial x^2 +
      ↪ 1]
```



```

sage: Emin = E.global_minimal_model()
sage: [(p, len(isogenies_prime_degree_genus_plus_0_j1728(Emin, p))) for p in [17,
↪ 29, 41]]
[(17, 2), (29, 2), (41, 2)]

```

`sage.schemes.elliptic_curves.isogeny_small_degree.isogenies_sporadic_Q(E, l=None)`

Returns list of  $l$ -isogenies with domain  $E$  (defined over  $\mathbb{Q}$ ).

Returns a list of sporadic  $l$ -isogenies from  $E$  ( $l = 11, 17, 19, 37, 43, 67$  or  $163$ ). Only for elliptic curves over  $\mathbb{Q}$ .

INPUT:

- $E$  – an elliptic curve defined over  $\mathbb{Q}$ .
- $l$  – either `None` or a prime number.

OUTPUT:

(list) If  $l$  is `None`, a list of all isogenies with domain  $E$  and of degree 11, 17, 19, 37, 43, 67 or 163; otherwise a list of isogenies of the given degree.

---

**Note:** This function would normally be invoked indirectly via `E.isogenies_prime_degree(l)`, which automatically calls the appropriate function.

---

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.isogeny_small_degree import isogenies_
↪ sporadic_Q
sage: E = EllipticCurve('121a1')
sage: isogenies_sporadic_Q(E, 11)
[Isogeny of degree 11 from Elliptic Curve defined by y^2 + x*y + y = x^3 + x^2 -
↪ 30*x - 76 over Rational Field to Elliptic Curve defined by y^2 + x*y + y = x^3 -
↪ x^2 - 305*x + 7888 over Rational Field]
sage: isogenies_sporadic_Q(E, 13)
[]
sage: isogenies_sporadic_Q(E, 17)
[]
sage: isogenies_sporadic_Q(E)
[Isogeny of degree 11 from Elliptic Curve defined by y^2 + x*y + y = x^3 + x^2 -
↪ 30*x - 76 over Rational Field to Elliptic Curve defined by y^2 + x*y + y = x^3 -
↪ x^2 - 305*x + 7888 over Rational Field]

sage: E = EllipticCurve([1, 1, 0, -660, -7600])
sage: isogenies_sporadic_Q(E, 17)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 + x*y = x^3 + x^2 -
↪ 660*x - 7600 over Rational Field to Elliptic Curve defined by y^2 + x*y = x^3 +
↪ x^2 - 878710*x + 316677750 over Rational Field]
sage: isogenies_sporadic_Q(E)
[Isogeny of degree 17 from Elliptic Curve defined by y^2 + x*y = x^3 + x^2 -
↪ 660*x - 7600 over Rational Field to Elliptic Curve defined by y^2 + x*y = x^3 +
↪ x^2 - 878710*x + 316677750 over Rational Field]
sage: isogenies_sporadic_Q(E, 11)
[]

sage: E = EllipticCurve([0, 0, 1, -1862, -30956])
sage: isogenies_sporadic_Q(E, 11)
[]
sage: isogenies_sporadic_Q(E, 19)

```



```

[Isogeny of degree 19 from Elliptic Curve defined by  $y^2 + y = x^3 - 1862x - 30956$  over Rational Field to Elliptic Curve defined by  $y^2 + y = x^3 - 672182x - 212325489$  over Rational Field]
sage: isogenies_sporadic_Q(E)
[Isogeny of degree 19 from Elliptic Curve defined by  $y^2 + y = x^3 - 1862x - 30956$  over Rational Field to Elliptic Curve defined by  $y^2 + y = x^3 - 672182x - 212325489$  over Rational Field]

sage: E = EllipticCurve([0, -1, 0, -6288, 211072])
sage: E.conductor()
19600
sage: isogenies_sporadic_Q(E, 37)
[Isogeny of degree 37 from Elliptic Curve defined by  $y^2 = x^3 - x^2 - 6288x + 211072$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - x^2 - 163137088x - 801950801728$  over Rational Field]

sage: E = EllipticCurve([1, 1, 0, -25178045, 48616918750])
sage: E.conductor()
148225
sage: isogenies_sporadic_Q(E, 37)
[Isogeny of degree 37 from Elliptic Curve defined by  $y^2 + xy = x^3 + x^2 - 25178045x + 48616918750$  over Rational Field to Elliptic Curve defined by  $y^2 + xy = x^3 + x^2 - 970x - 13075$  over Rational Field]

sage: E = EllipticCurve([-3440, 77658])
sage: E.conductor()
118336
sage: isogenies_sporadic_Q(E, 43)
[Isogeny of degree 43 from Elliptic Curve defined by  $y^2 = x^3 - 3440x + 77658$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - 6360560x - 6174354606$  over Rational Field]

sage: E = EllipticCurve([-29480, -1948226])
sage: E.conductor()
287296
sage: isogenies_sporadic_Q(E, 67)
[Isogeny of degree 67 from Elliptic Curve defined by  $y^2 = x^3 - 29480x - 1948226$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - 132335720x + 585954296438$  over Rational Field]

sage: E = EllipticCurve([-34790720, -78984748304])
sage: E.conductor()
425104
sage: isogenies_sporadic_Q(E, 163)
[Isogeny of degree 163 from Elliptic Curve defined by  $y^2 = x^3 - 34790720x - 78984748304$  over Rational Field to Elliptic Curve defined by  $y^2 = x^3 - 924354639680x + 342062961763303088$  over Rational Field]

```

## 15.11 Elliptic curves over number fields

### 15.11.1 Elliptic curves over the rational numbers

AUTHORS:

- William Stein (2005): first version

- William Stein (2006-02-26): fixed Lseries\_extended which didn't work because of changes elsewhere in Sage.
- David Harvey (2006-09): Added padic\_E2, padic\_sigma, padic\_height, padic\_regulator methods.
- David Harvey (2007-02): reworked padic-height related code
- Christian Wuthrich (2007): added padic sha computation
- David Roe (2007-09): moved sha, l-series and p-adic functionality to separate files.
- John Cremona (2008-01)
- Tobias Nagel and Michael Mardaus (2008-07): added integral\_points
- John Cremona (2008-07): further work on integral\_points
- Christian Wuthrich (2010-01): moved Galois reps and modular parametrization in a separate file
- Simon Spicer (2013-03): Added code for modular degrees and congruence numbers of higher level
- Simon Spicer (2014-08): Added new analytic rank computation functionality

**class** sage.schemes.elliptic\_curves.ell\_rational\_field.**EllipticCurve\_rational\_field**(ainvs, *\*\*kws*)

Bases: *sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field*

Elliptic curve over the Rational Field.

INPUT:

- ainvs – a list or tuple  $[a_1, a_2, a_3, a_4, a_6]$  of Weierstrass coefficients.

---

**Note:** This class should not be called directly; use `sage.constructor.EllipticCurve` to construct elliptic curves.

---

#### EXAMPLES:

Construction from Weierstrass coefficients ( $a$ -invariants), long form:

```
sage: E = EllipticCurve([1, 2, 3, 4, 5]); E
Elliptic Curve defined by  $y^2 + x*y + 3*y = x^3 + 2*x^2 + 4*x + 5$  over Rational_
↪Field
```

Construction from Weierstrass coefficients ( $a$ -invariants), short form (sets  $a_1 = a_2 = a_3 = 0$ ):

```
sage: EllipticCurve([4, 5]).ainvs()
(0, 0, 0, 4, 5)
```

Constructor from a Cremona label:

```
sage: EllipticCurve('389a1')
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 2*x$  over Rational Field
```

Constructor from an LMFDB label:

```
sage: EllipticCurve('462.f3')
Elliptic Curve defined by  $y^2 + x*y = x^3 - 363*x + 1305$  over Rational Field
```

**CPS\_height\_bound()**

Return the Cremona-Prickett-Siksek height bound. This is a floating point number  $B$  such that if  $P$  is a

rational point on the curve, then  $h(P) \leq \hat{h}(P) + B$ , where  $h(P)$  is the naive logarithmic height of  $P$  and  $\hat{h}(P)$  is the canonical height.

**See also:**

`silverman_height_bound()` for a bound that also works for points over number fields.

**EXAMPLES:**

```
sage: E = EllipticCurve("11a")
sage: E.CPS_height_bound()
2.8774743273580445
sage: E = EllipticCurve("5077a")
sage: E.CPS_height_bound()
0.0
sage: E = EllipticCurve([1, 2, 3, 4, 1])
sage: E.CPS_height_bound()
Traceback (most recent call last):
...
RuntimeError: curve must be minimal.
sage: F = E.quadratic_twist(-19)
sage: F
Elliptic Curve defined by y^2 + x*y + y = x^3 - x^2 + 1376*x - 130 over_
↪Rational Field
sage: F.CPS_height_bound()
0.6555158376972852
```

**IMPLEMENTATION:**

Call the corresponding mwrank C++ library function. Note that the formula in the [\[CPS\]](#) paper is given for number fields. It is only the implementation in Sage that restricts to the rational field.

**Lambda** (*s*, *prec*)

Return the value of the Lambda-series of the elliptic curve  $E$  at  $s$ , where  $s$  can be any complex number.

**IMPLEMENTATION:** Fairly *slow* computation using the definitions and implemented in Python.

Uses *prec* terms of the power series.

**EXAMPLES:**

```
sage: E = EllipticCurve('389a')
sage: E.Lambda(1.4+0.5*I, 50)
-0.354172680517... + 0.874518681720...*I
```

**Np** (*p*)

The number of points on  $E$  modulo  $p$ .

**INPUT:**

- $p$  (int) – a prime, not necessarily of good reduction.

**OUTPUT:**

(int) The number of points on the reduction of  $E$  modulo  $p$  (including the singular point when  $p$  is a prime of bad reduction).

**EXAMPLES:**

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.Np(2)
5
sage: E.Np(3)
```

```

5
sage: E.conductor()
11
sage: E.Np(11)
11

```

This even works when the prime is large:

```

sage: E = EllipticCurve('37a')
sage: E.Np(next_prime(10^30))
10000000000000001426441464441649

```

**S\_integral\_points** (*S*, *mw\_base*='auto', *both\_signs*=False, *verbose*=False, *proof*=None)

Compute all S-integral points (up to sign) on this elliptic curve.

INPUT:

- *S* - list of primes
- *mw\_base* - list of EllipticCurvePoint generating the Mordell-Weil group of *E* (default: 'auto' - calls *gens*())
- *both\_signs* - True/False (default False): if True the output contains both *P* and *-P*, otherwise only one of each pair.
- *verbose* - True/False (default False): if True, some details of the computation are output.
- *proof* - True/False (default True): if True ALL S-integral points will be returned. If False, the MW basis will be computed with the *proof*=False flag, and also the time-consuming final call to *S\_integral\_x\_coords\_with\_abs\_bounded\_by*(*abs\_bound*) is omitted. Use this only if the computation takes too long, but be warned that then it cannot be guaranteed that all S-integral points will be found.

OUTPUT:

A sorted list of all the S-integral points on *E* (up to sign unless *both\_signs* is True)

---

**Note:** The complexity increases exponentially in the rank of curve *E* and in the length of *S*. The computation time (but not the output!) depends on the Mordell-Weil basis. If *mw\_base* is given but is not a basis for the Mordell-Weil group (modulo torsion), S-integral points which are not in the subgroup generated by the given points will almost certainly not be listed.

---

EXAMPLES:

A curve of rank 3 with no torsion points:

```

sage: E = EllipticCurve([0,0,1,-7,6])
sage: P1=E.point((2,0)); P2=E.point((-1,3)); P3=E.point((4,6))
sage: a=E.S_integral_points(S=[2,3], mw_base=[P1,P2,P3], verbose=True);a
max_S: 3 len_S: 3 len_tors: 1
lambda 0.485997517468...
k1,k2,k3,k4 7.65200453902598e234 1.31952866480763 3.54035317966420e9 2.
↪42767548272846e17
p= 2 : trying with p_prec = 30
mw_base_p_log_val = [2, 2, 1]
min_psi = 2 + 2^3 + 2^6 + 2^7 + 2^8 + 2^9 + 2^11 + 2^12 + 2^13 + 2^16 + 2^17 ↪
↪+ 2^19 + 2^20 + 2^21 + 2^23 + 2^24 + 2^28 + O(2^30)
p= 3 : trying with p_prec = 30
mw_base_p_log_val = [1, 2, 1]
min_psi = 3 + 3^2 + 2*3^3 + 3^6 + 2*3^7 + 2*3^8 + 3^9 + 2*3^11 + 2*3^12 + ↪
↪2*3^13 + 3^15 + 2*3^16 + 3^18 + 2*3^19 + 2*3^22 + 2*3^23 + 2*3^24 + 2*3^27 ↪
↪+ 3^28 + 3^29 + O(3^30)

```

```

mw_base [(1 : -1 : 1), (2 : 0 : 1), (0 : -3 : 1)]
mw_base_log [0.667789378224099, 0.552642660712417, 0.818477222895703]
mp [5, 7]
mw_base_p_log [[2^2 + 2^3 + 2^6 + 2^7 + 2^8 + 2^9 + 2^14 + 2^15 + 2^18 + 2^19 ↵
↵ + 2^24 + 2^29 + O(2^30), 2^2 + 2^3 + 2^5 + 2^6 + 2^9 + 2^11 + 2^12 + 2^14 + ↵
↵ 2^15 + 2^16 + 2^18 + 2^20 + 2^22 + 2^23 + 2^26 + 2^27 + 2^29 + O(2^30), 2 + ↵
↵ 2^3 + 2^6 + 2^7 + 2^8 + 2^9 + 2^11 + 2^12 + 2^13 + 2^16 + 2^17 + 2^19 + 2^ ↵
↵ 20 + 2^21 + 2^23 + 2^24 + 2^28 + O(2^30)], [2*3^2 + 2*3^5 + 2*3^6 + 2*3^7 + ↵
↵ 3^8 + 3^9 + 2*3^10 + 3^12 + 2*3^14 + 3^15 + 3^17 + 2*3^19 + 2*3^23 + 3^25 + ↵
↵ 3^28 + O(3^30), 2*3 + 2*3^2 + 2*3^3 + 2*3^4 + 2*3^6 + 2*3^7 + 2*3^8 + 3^10 ↵
↵ + 2*3^12 + 3^13 + 2*3^14 + 3^15 + 3^18 + 3^22 + 3^25 + 2*3^26 + 3^27 + 3^28 ↵
↵ + O(3^30), 3 + 3^2 + 2*3^3 + 3^6 + 2*3^7 + 2*3^8 + 3^9 + 2*3^11 + 2*3^12 + ↵
↵ 2*3^13 + 3^15 + 2*3^16 + 3^18 + 2*3^19 + 2*3^22 + 2*3^23 + 2*3^24 + 2*3^27 ↵
↵ + 3^28 + 3^29 + O(3^30)]]
k5,k6,k7 0.321154513240... 1.55246328915... 0.161999172489...
initial bound 2.8057927340...e117
bound_list [58, 58, 58]
bound_list [8, 9, 9]
bound_list [9, 7, 7]
starting search of points using coefficient bound 9
x-coords of S-integral points via linear combination of mw_base and torsion:
[-3, -26/9, -8159/2916, -2759/1024, -151/64, -1343/576, -2, -7/4, -1, -47/256,
↵ 0, 1/4, 4/9, 9/16, 58/81, 7/9, 6169/6561, 1, 17/16, 2, 33/16, 172/81, 9/4, ↵
↵ 25/9, 3, 31/9, 4, 25/4, 1793/256, 8, 625/64, 11, 14, 21, 37, 52, 6142/81, ↵
↵ 93, 4537/36, 342, 406, 816, 207331217/4096]
starting search of extra S-integer points with absolute value bounded by 3.
↵ 89321964979420
x-coords of points with bounded absolute value
[-3, -2, -1, 0, 1, 2]
Total number of S-integral points: 43
[(-3 : 0 : 1), (-26/9 : 28/27 : 1), (-8159/2916 : 233461/157464 : 1), (-2759/ ↵
↵ 1024 : 60819/32768 : 1), (-151/64 : 1333/512 : 1), (-1343/576 : 36575/13824 ↵
↵ : 1), (-2 : 3 : 1), (-7/4 : 25/8 : 1), (-1 : 3 : 1), (-47/256 : 9191/4096 : ↵
↵ 1), (0 : 2 : 1), (1/4 : 13/8 : 1), (4/9 : 35/27 : 1), (9/16 : 69/64 : 1), ↵
↵ (58/81 : 559/729 : 1), (7/9 : 17/27 : 1), (6169/6561 : 109871/531441 : 1), ↵
↵ (1 : 0 : 1), (17/16 : -25/64 : 1), (2 : 0 : 1), (33/16 : 17/64 : 1), (172/ ↵
↵ 81 : 350/729 : 1), (9/4 : 7/8 : 1), (25/9 : 64/27 : 1), (3 : 3 : 1), (31/9 ↵
↵ : 116/27 : 1), (4 : 6 : 1), (25/4 : 111/8 : 1), (1793/256 : 68991/4096 : 1), ↵
↵ (8 : 21 : 1), (625/64 : 14839/512 : 1), (11 : 35 : 1), (14 : 51 : 1), (21 ↵
↵ : 95 : 1), (37 : 224 : 1), (52 : 374 : 1), (6142/81 : 480700/729 : 1), (93 ↵
↵ : 896 : 1), (4537/36 : 305425/216 : 1), (342 : 6324 : 1), (406 : 8180 : 1), ↵
↵ (816 : 23309 : 1), (207331217/4096 : 2985362173625/262144 : 1)]

```

It is not necessary to specify `mw_base`; if it is not provided, then the Mordell-Weil basis must be computed, which may take much longer.

```

sage: a = E.S_integral_points([2,3])
sage: len(a)
43

```

An example with negative discriminant:

```

sage: EllipticCurve('900d1').S_integral_points([17], both_signs=True)
[(-11 : -27 : 1), (-11 : 27 : 1), (-4 : -34 : 1), (-4 : 34 : 1), (4 : -18 : ↵
↵ 1), (4 : 18 : 1), (2636/289 : -98786/4913 : 1), (2636/289 : 98786/4913 : 1), ↵
↵ (16 : -54 : 1), (16 : 54 : 1)]

```

Output checked with Magma (corrected in 3 cases):

```

sage: [len(e.S_integral_points([2], both_signs=False)) for e in cremona_
↪curves([11..100])] # long time (17s on sage.math, 2011)
[2, 0, 2, 3, 3, 1, 3, 1, 3, 5, 3, 5, 4, 1, 1, 2, 2, 2, 3, 1, 2, 1, 0, 1, 3, 3,
↪1, 1, 5, 3, 4, 2, 1, 1, 5, 3, 2, 2, 1, 1, 1, 0, 1, 3, 0, 1, 0, 1, 1, 3, 7,
↪1, 3, 3, 3, 1, 1, 2, 3, 1, 2, 3, 1, 2, 1, 3, 3, 1, 1, 1, 0, 1, 3, 3, 1, 1,
↪7, 1, 0, 1, 1, 0, 1, 2, 0, 3, 1, 2, 1, 3, 1, 2, 2, 4, 5, 3, 2, 1, 1, 6, 1,
↪0, 1, 3, 1, 3, 3, 1, 1, 1, 1, 1, 3, 1, 5, 1, 2, 4, 1, 1, 1, 1, 1, 0, 1, 0,
↪2, 2, 0, 0, 1, 0, 1, 1, 6, 1, 0, 1, 1, 0, 4, 3, 1, 2, 1, 2, 3, 1, 1, 1, 1,
↪8, 3, 1, 2, 1, 2, 0, 8, 2, 0, 6, 2, 3, 1, 1, 1, 3, 1, 3, 2, 1, 3, 1, 2, 1,
↪6, 9, 3, 3, 1, 1, 2, 3, 1, 1, 5, 5, 1, 1, 0, 1, 1, 2, 3, 1, 1, 2, 3, 1, 3,
↪1, 1, 1, 1, 0, 0, 1, 3, 3, 1, 3, 1, 1, 2, 2, 0, 0, 6, 1, 0, 1, 1, 1, 1, 3,
↪1, 2, 6, 3, 1, 2, 2, 1, 1, 1, 1, 7, 5, 4, 3, 3, 1, 1, 1, 1, 1, 1, 8, 5, 1,
↪1, 3, 3, 1, 1, 3, 3, 1, 1, 2, 3, 6, 1, 1, 7, 3, 3, 4, 5, 9, 6, 1, 0, 7, 1,
↪1, 3, 1, 1, 2, 3, 1, 2, 1, 1, 1, 1, 1, 1, 1, 7, 8, 2, 3, 1, 1, 1, 1, 0, 0,
↪0, 1, 1, 1, 1]

```

An example from [PZGH]:

```

sage: E = EllipticCurve([0,0,0,-172,505])
sage: E.rank(), len(E.S_integral_points([3,5,7])) # long time (5s on sage.
↪math, 2011)
(4, 72)

```

This is curve “7690e1” which failed until [trac ticket #4805](#) was fixed:

```

sage: EllipticCurve([1,1,1,-301,-1821]).S_integral_points([13,2])
[(-13 : 16 : 1),
(-9 : 20 : 1),
(-7 : 4 : 1),
(21 : 30 : 1),
(23 : 52 : 1),
(63 : 452 : 1),
(71 : 548 : 1),
(87 : 756 : 1),
(2711 : 139828 : 1),
(7323 : 623052 : 1),
(17687 : 2343476 : 1)]

```

## REFERENCES:

- Some parts of this implementation are partially based on the function `integral_points()`

## AUTHORS:

- Tobias Nagel (2008-12)
- Michael Mardaus (2008-12)
- John Cremona (2008-12)

## `abelian_variety()`

Return self as a modular abelian variety.

## OUTPUT:

- a modular abelian variety

## EXAMPLES:

```

sage: E = EllipticCurve('11a')
sage: E.abelian_variety()

```

```
Abelian variety J0(11) of dimension 1

sage: E = EllipticCurve('33a')
sage: E.abelian_variety()
Abelian subvariety of dimension 1 of J0(33)
```

**an**(*n*)

The *n*-th Fourier coefficient of the modular form corresponding to this elliptic curve, where *n* is a positive integer.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: [E.an(n) for n in range(20) if n>0]
[1, -2, -3, 2, -2, 6, -1, 0, 6, 4, -5, -6, -2, 2, 6, -4, 0, -12, 0]
```

**analytic\_rank**(*algorithm*='pari', *leading\_coefficient*=False)

Return an integer that is *probably* the analytic rank of this elliptic curve.

INPUT:

- *algorithm* – (default: 'pari'), String
  - 'pari' – use the PARI library function.
  - 'sympow' – use Watkins's program sympow
  - 'rubinstein' – use Rubinstein's L-function C++ program lcalc.
  - 'magma' – use MAGMA
  - 'zero\_sum' – Use the rank bounding zero sum method implemented in `self.analytic_rank_upper_bound()`
  - 'all' – compute with PARI, sympow and lcalc, check that the answers agree, and return the common answer.
- *leading\_coefficient* – (default: False) Boolean; if set to True, return a tuple (*rank*, *lead*) where *lead* is the value of the first non-zero derivative of the L-function of the elliptic curve. Only implemented for *algorithm*='pari'.

---

**Note:** If the curve is loaded from the large Cremona database, then the modular degree is taken from the database.

---

Of the first three algorithms above, probably Rubinstein's is the most efficient (in some limited testing done). The zero sum method is often *much* faster, but can return a value which is strictly larger than the analytic rank. For curves with conductor  $\leq 10^9$  using default parameters, testing indicates that for 99.75% of curves the returned rank bound is the true rank.

---

**Note:** If you use `set_verbose(1)`, extra information about the computation will be printed when *algorithm*='zero\_sum'.

---



---

**Note:** It is an open problem to *prove* that *any* particular elliptic curve has analytic rank  $\geq 4$ .

---

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: E.analytic_rank(algorithm='pari')
2
sage: E.analytic_rank(algorithm='rubinstein')
2
sage: E.analytic_rank(algorithm='sympow')
2
sage: E.analytic_rank(algorithm='magma')      # optional - magma
2
sage: E.analytic_rank(algorithm='zero_sum')
2
sage: E.analytic_rank(algorithm='all')
2

```

With the optional parameter `leading_coefficient` set to `True`, a tuple of both the analytic rank and the leading term of the L-series at  $s = 1$  is returned. This only works for `algorithm=='pari'`:

```

sage: EllipticCurve([0,-1,1,-10,-20]).analytic_rank(leading_coefficient=True)
(0, 0.25384186085591068...)
sage: EllipticCurve([0,0,1,-1,0]).analytic_rank(leading_coefficient=True)
(1, 0.30599977383405230...)
sage: EllipticCurve([0,1,1,-2,0]).analytic_rank(leading_coefficient=True)
(2, 1.518633000576853...)
sage: EllipticCurve([0,0,1,-7,6]).analytic_rank(leading_coefficient=True)
(3, 10.39109940071580...)
sage: EllipticCurve([0,0,1,-7,36]).analytic_rank(leading_coefficient=True)
(4, 196.170903794579...)

```

**analytic\_rank\_upper\_bound** (*max\_Delta=None*, *adaptive=True*, *N=None*,  
*root\_number='compute'*, *bad\_primes=None*, *ncpus=None*)

Return an upper bound for the analytic rank of self, conditional on the Generalized Riemann Hypothesis, via computing the zero sum  $\sum_{\gamma} f(\Delta\gamma)$ , where  $\gamma$  ranges over the imaginary parts of the zeros of  $L(E, s)$  along the critical strip,  $f(x) = (\sin(\pi x)/(\pi x))^2$ , and  $\Delta$  is the tightness parameter whose maximum value is specified by `max_Delta`. This computation can be run on curves with very large conductor (so long as the conductor is known or quickly computable) when  $\Delta$  is not too large (see below). Uses Bober's rank bounding method as described in [Bob13].

INPUT:

- `max_Delta` – (default: `None`) If not `None`, a positive real value specifying the maximum Delta value used in the zero sum; larger values of Delta yield better bounds - but runtime is exponential in Delta. If left as `None`, Delta is set to  $\min\{\frac{1}{\pi}(\log(N + 1000)/2 - \log(2\pi) - \eta), 2.5\}$ , where  $N$  is the conductor of the curve attached to self, and  $\eta$  is the Euler-Mascheroni constant = 0.5772...; the crossover point is at conductor around  $8.3 \cdot 10^8$ . For the former value, empirical results show that for about 99.7% of all curves the returned value is the actual analytic rank.
- `adaptive` – (default: `True`) Boolean
  - `True` – the computation is first run with small and then successively larger  $\Delta$  values up to `max_Delta`. If at any point the computed bound is 0 (or 1 when `root_number` is -1 or `True`), the computation halts and that value is returned; otherwise the minimum of the computed bounds is returned.
  - `False` – the computation is run a single time with  $\Delta$  equal to `max_Delta`, and the resulting bound returned.
- `N` – (default: `None`) If not `None`, a positive integer equal to the conductor of self. This is passable so that rank estimation can be done for curves whose (large) conductor has been precomputed.



- `root_number` – (default: “compute”) String or integer
  - “compute” – the root number of self is computed and used to (possibly) lower the analytic rank estimate by 1.
  - “ignore” – the above step is omitted
  - 1 – this value is assumed to be the root number of self. This is passable so that rank estimation can be done for curves whose root number has been precomputed.
  - -1 – this value is assumed to be the root number of self. This is passable so that rank estimation can be done for curves whose root number has been precomputed.
- `bad_primes` – (default: None) If not None, a list of the primes of bad reduction for the curve attached to self. This is passable so that rank estimation can be done for curves of large conductor whose bad primes have been precomputed.
- `ncpus` – (default: None) If not None, a positive integer defining the maximum number of CPUs to be used for the computation. If left as None, the maximum available number of CPUs will be used. Note: Due to parallelization overhead, multiple processors will only be used for Delta values  $\geq 1.75$ .

---

**Note:** Output will be incorrect if the incorrect conductor or root number is specified.

---

**Warning:** Zero sum computation time is exponential in the tightness parameter  $\Delta$ , roughly doubling for every increase of 0.1 thereof. Using  $\Delta = 1$  (and `adaptive=False`) will yield a runtime of a few milliseconds;  $\Delta = 2$  takes a few seconds, and  $\Delta = 3$  may take upwards of an hour. Increase beyond this at your own risk!

OUTPUT:

A non-negative integer greater than or equal to the analytic rank of self.

---

**Note:** If you use `set_verbose(1)`, extra information about the computation will be printed.

---

**See also:**

`LFunctionZeroSum()` `root_number()` `set_verbose()`

EXAMPLES:

For most elliptic curves with small conductor the central zero(s) of  $L_E(s)$  are fairly isolated, so small values of  $\Delta$  will yield tight rank estimates.

```
sage: E = EllipticCurve("11a")
sage: E.rank()
0
sage: E.analytic_rank_upper_bound(max_Delta=1, adaptive=False)
0
sage: E = EllipticCurve([-39, 123])
sage: E.rank()
1
sage: E.analytic_rank_upper_bound(max_Delta=1, adaptive=True)
1
```

This is especially true for elliptic curves with large rank.

```

sage: for r in range(9):
....:     E = elliptic_curves.rank(r)[0]
....:     print((r, E.analytic_rank_upper_bound(max_Delta=1,
....:     adaptive=False, root_number="ignore")))
(0, 0)
(1, 1)
(2, 2)
(3, 3)
(4, 4)
(5, 5)
(6, 6)
(7, 7)
(8, 8)

```

However, some curves have  $L$ -functions with low-lying zeroes, and for these larger values of  $\Delta$  must be used to get tight estimates.

```

sage: E = EllipticCurve("974b1")
sage: r = E.rank(); r
0
sage: E.analytic_rank_upper_bound(max_Delta=1, root_number="ignore")
1
sage: E.analytic_rank_upper_bound(max_Delta=1.3, root_number="ignore")
0

```

Knowing the root number of  $E$  allows us to use smaller Delta values to get tight bounds, thus speeding up runtime considerably.

```

sage: E.analytic_rank_upper_bound(max_Delta=0.6, root_number="compute")
0

```

There are a small number of curves which have pathologically low-lying zeroes. For these curves, this method will produce a bound that is strictly larger than the analytic rank, unless very large values of Delta are used. The following curve ("256944c1" in the Cremona tables) is a rank 0 curve with a zero at 0.0256...; the smallest Delta value for which the zero sum is strictly less than 2 is ~2.815.

```

sage: E = EllipticCurve([0, -1, 0, -7460362000712, -7842981500851012704])
sage: N, r = E.conductor(), E.analytic_rank(); N, r
(256944, 0)
sage: E.analytic_rank_upper_bound(max_Delta=1, adaptive=False)
2
sage: E.analytic_rank_upper_bound(max_Delta=2, adaptive=False)
2

```

This method is can be called on curves with large conductor.

```

sage: E = EllipticCurve([-2934, 19238])
sage: E.analytic_rank_upper_bound()
1

```

And it can bound rank on curves with *very* large conductor, so long as you know beforehand/can easily compute the conductor and primes of bad reduction less than  $e^{2\pi\Delta}$ . The example below is of the rank 28 curve discovered by Elkies that is the elliptic curve of (currently) largest known rank.

```

sage: a4 = -20067762415575526585033208209338542750930230312178956502
sage: a6 = ↵
↵34481611795030556467032985690390720374855944359319180361266008296291939448732243429

```

```

sage: E = EllipticCurve([1,-1,1,a4,a6])
sage: bad_primes = [2,3,5,7,11,13,17,19,48463]
sage: N =
↪345560110835754734153225386490160523119851150579373313890059518947214472478145663538015414
sage: E.analytic_rank_upper_bound(max_Delta=2.37,adaptive=False, # long time
....: N=N,root_number=1,bad_primes=bad_primes,ncpus=2) # long time
32

```

## REFERENCES:

**anlist** (*n*, *python\_ints=False*)

The Fourier coefficients up to and including  $a_n$  of the modular form attached to this elliptic curve. The  $i$ -th element of the return list is  $a[i]$ .

INPUT:

- *n* - integer
- *python\_ints* - bool (default: False); if True return a list of Python ints instead of Sage integers.

OUTPUT: list of integers

EXAMPLES:

```

sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E.anlist(3)
[0, 1, -2, -1]

```

```

sage: E = EllipticCurve([0,1])
sage: E.anlist(20)
[0, 1, 0, 0, 0, 0, 0, -4, 0, 0, 0, 0, 0, 2, 0, 0, 0, 0, 0, 8, 0]

```

**antilogarithm** (*z*, *max\_denominator=None*)

Return the rational point (if any) associated to this complex number; the inverse of the elliptic logarithm function.

INPUT:

- *z* – a complex number representing an element of  $\mathbb{C}/L$  where  $L$  is the period lattice of the elliptic curve
- *max\_denominator* (int or None) – parameter controlling the attempted conversion of real numbers to rationals. If None, `simplest_rational()` will be used; otherwise, `nearby_rational()` will be used with this value of *max\_denominator*.

OUTPUT:

- point on the curve: the rational point which is the image of  $z$  under the Weierstrass parametrization, if it exists and can be determined from  $z$  and the given value of *max\_denominator* (if any); otherwise a `ValueError` exception is raised.

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: P = E(-1,1)
sage: z = P.elliptic_logarithm()
sage: E.antilogarithm(z)
(-1 : 1 : 1)
sage: Q = E(0,-1)
sage: z = Q.elliptic_logarithm()
sage: E.antilogarithm(z)

```

```

Traceback (most recent call last):
...
ValueError: approximated point not on the curve
sage: E.antilogarithm(z, max_denominator=10)
(0 : -1 : 1)

sage: E = EllipticCurve('11a1')
sage: w1,w2 = E.period_lattice().basis()
sage: [E.antilogarithm(a*w1/5,1) for a in range(5)]
[(0 : 1 : 0), (16 : -61 : 1), (5 : -6 : 1), (5 : 5 : 1), (16 : 60 : 1)]

```

**ap(p)**

The  $p$ -th Fourier coefficient of the modular form corresponding to this elliptic curve, where  $p$  is prime.

EXAMPLES:

```

sage: E = EllipticCurve('37a1')
sage: [E.ap(p) for p in prime_range(50)]
[-2, -3, -2, -1, -5, -2, 0, 0, 2, 6, -4, -1, -9, 2, -9]

```

**aplist(n, python\_ints=False)**

The Fourier coefficients  $a_p$  of the modular form attached to this elliptic curve, for all primes  $p \leq n$ .

INPUT:

- $n$  - integer
- `python_ints` - bool (default: False); if True return a list of Python ints instead of Sage integers.

OUTPUT: list of integers

EXAMPLES:

```

sage: e = EllipticCurve('37a')
sage: e.aplist(1)
[]
sage: e.aplist(2)
[-2]
sage: e.aplist(10)
[-2, -3, -2, -1]
sage: v = e.aplist(13); v
[-2, -3, -2, -1, -5, -2]
sage: type(v[0])
<... 'sage.rings.integer.Integer'>
sage: type(e.aplist(13, python_ints=True)[0])
<... 'int'>

```

**cm\_discriminant()**

Return the associated quadratic discriminant if this elliptic curve has Complex Multiplication over the algebraic closure.

A `ValueError` is raised if the curve does not have CM (see the function `has_cm()`).

EXAMPLES:

```

sage: E = EllipticCurve('32a1')
sage: E.cm_discriminant()
-4
sage: E = EllipticCurve('121b1')
sage: E.cm_discriminant()

```

```

-11
sage: E = EllipticCurve('37a1')
sage: E.cm_discriminant()
Traceback (most recent call last):
...
ValueError: Elliptic Curve defined by  $y^2 + y = x^3 - x$  over Rational Field_
↳ does not have CM

```

**conductor** (*algorithm*='pari')

Return the conductor of the elliptic curve.

INPUT:

- *algorithm* - str, (default: "pari")
  - "pari" - use the PARI C-library ellglobalred implementation of Tate's algorithm
  - "mwrnk" - use Cremona's mwrnk implementation of Tate's algorithm; can be faster if the curve has integer coefficients (TODO: limited to small conductor until mwrnk gets integer factorization)
  - "gp" - use the GP interpreter.
  - "generic" - use the general number field implementation
  - "all" - use all four implementations, verify that the results are the same (or raise an error), and output the common value.

EXAMPLES:

```

sage: E = EllipticCurve([1, -1, 1, -29372, -1932937])
sage: E.conductor(algorithm="pari")
3006
sage: E.conductor(algorithm="mwrnk")
3006
sage: E.conductor(algorithm="gp")
3006
sage: E.conductor(algorithm="generic")
3006
sage: E.conductor(algorithm="all")
3006

```

**Note:** The conductor computed using each algorithm is cached separately. Thus calling `E.conductor('pari')`, then `E.conductor('mwrnk')` and getting the same result checks that both systems compute the same answer.

**congruence\_number** ( $M=1$ )

The case  $M == 1$  corresponds to the classical definition of congruence number: Let  $X$  be the subspace of  $S_2(\Gamma_0(N))$  spanned by the newform associated with this elliptic curve, and  $Y$  be orthogonal complement of  $X$  under the Petersson inner product. Let  $S_X$  and  $S_Y$  be the intersections of  $X$  and  $Y$  with  $S_2(\Gamma_0(N), \mathbf{Z})$ . The congruence number is defined to be  $[S_X \oplus S_Y : S_2(\Gamma_0(N), \mathbf{Z})]$ . It measures congruences between  $f$  and elements of  $S_2(\Gamma_0(N), \mathbf{Z})$  orthogonal to  $f$ .

The congruence number for higher levels, when  $M > 1$ , is defined as above, but instead considers  $X$  to be the subspace of  $S_2(\Gamma_0(MN))$  spanned by embeddings into  $S_2(\Gamma_0(MN))$  of the newform associated with this elliptic curve; this subspace has dimension  $\sigma_0(M)$ , i.e. the number of divisors of  $M$ . Let  $Y$  be the orthogonal complement in  $S_2(\Gamma_0(MN))$  of  $X$  under the Petersson inner product, and  $S_X$  and  $S_Y$  the

intersections of  $X$  and  $Y$  with  $S_2(\Gamma_0(MN), \mathbf{Z})$  respectively. Then the congruence number at level  $MN$  is  $[S_X \oplus S_Y : S_2(\Gamma_0(MN), \mathbf{Z})]$ .

INPUT:

- $M$  – Non-negative integer; congruence number is computed at level  $MN$ , where  $N$  is the conductor of `self`.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.congruence_number()
2
sage: E.congruence_number()
2
sage: E = EllipticCurve('54b')
sage: E.congruence_number()
6
sage: E.modular_degree()
2
sage: E = EllipticCurve('242a1')
sage: E.modular_degree()
16
sage: E.congruence_number() # long time (4s on sage.math, 2011)
176
```

Higher level cases:

```
sage: E = EllipticCurve('11a')
sage: for M in range(1,11): print(E.congruence_number(M)) # long time (20s on_
↪ 2009 MBP)
1
1
3
2
7
45
12
4
18
245
```

It is a theorem of Ribet that the congruence number (at level  $N$ ) is equal to the modular degree in the case of square free conductor. It is a conjecture of Agashe, Ribet, and Stein that  $\text{ord}_p(c_f/m_f) \leq \text{ord}_p(N)/2$ .

**cremona\_label** (*space=False*)

Return the Cremona label associated to (the minimal model) of this curve, if it is known. If not, raise a `LookupError` exception.

EXAMPLES:

```
sage: E = EllipticCurve('389a1')
sage: E.cremona_label()
'389a1'
```

The default database only contains conductors up to 10000, so any curve with conductor greater than that will cause an error to be raised. The optional package `database_cremona_ellcurve` contains many more curves.

```

sage: E = EllipticCurve([1, -1, 0, -79, 289])
sage: E.conductor()
234446
sage: E.cremona_label() # optional - database_cremona_ellcurve
'234446a1'
sage: E = EllipticCurve((0, 0, 1, -79, 342))
sage: E.conductor()
19047851
sage: E.cremona_label()
Traceback (most recent call last):
...
LookupError: Cremona database does not contain entry for Elliptic Curve_
↳ defined by  $y^2 + y = x^3 - 79x + 342$  over Rational Field

```

**database\_attributes()**

Return a dictionary containing information about `self` in the elliptic curve database.

If there is no elliptic curve isomorphic to `self` in the database, a `LookupError` is raised.

EXAMPLES:

```

sage: E = EllipticCurve((0, 0, 1, -1, 0))
sage: data = E.database_attributes()
sage: data['conductor']
37
sage: data['cremona_label']
'37a1'
sage: data['rank']
1
sage: data['torsion_order']
1

sage: E = EllipticCurve((8, 13, 21, 34, 55))
sage: E.database_attributes()
Traceback (most recent call last):
...
LookupError: Cremona database does not contain entry for Elliptic Curve_
↳ defined by  $y^2 + 8xy + 21y = x^3 + 13x^2 + 34x + 55$  over Rational Field

```

**database\_curve()**

Return the curve in the elliptic curve database isomorphic to this curve, if possible. Otherwise raise a `LookupError` exception.

Since [trac ticket #11474](#), this returns exactly the same curve as `minimal_model()`; the only difference is the additional work of checking whether the curve is in the database.

EXAMPLES:

```

sage: E = EllipticCurve([0, 1, 2, 3, 4])
sage: E.database_curve()
Elliptic Curve defined by  $y^2 = x^3 + x^2 + 3x + 5$  over Rational Field

```

**Note:** The model of the curve in the database can be different from the Weierstrass model for this curve, e.g., database models are always minimal.

**elliptic\_exponential(z, embedding=None)**

Compute the elliptic exponential of a complex number with respect to the elliptic curve.

- `z (complex)` – a complex number
- `embedding` - ignored (for compatibility with the `period_lattice` function for elliptic curve number field)

The image of  $z$  modulo  $L$  under the Weierstrass parametrization  $\mathbf{C}/L \rightarrow E(\mathbf{C})$ .

**Note:** The precision is that of the input  $z$ , or the default precision of 53 bits if  $z$  is exact.

EXAMPLES:

[illegible][illegible]

Some torsion examples:

```
sage: w1,w2 = E.period_lattice().basis()
sage: E.two_division_polynomial().roots(CC,multiplicities=False)
[-2.0403022002854..., 0.13540924022175..., 0.90489296006371...]
sage: [E.elliptic_exponential((a*w1+b*w2)/2)[0] for a,b in [(0,1),(1,1),(1,
↪0)]]
[-2.0403022002854..., 0.13540924022175..., 0.90489296006371...]

sage: E.division_polynomial(3).roots(CC,multiplicities=False)
[-2.88288879135...,
1.39292799513...,
0.078313731444316... - 0.492840991709...*I,
0.078313731444316... + 0.492840991709...*I]
sage: [E.elliptic_exponential((a*w1+b*w2)/3)[0] for a,b in [(0,1),(1,0),(1,1),
↪(2,1)]]
[-2.8828887913533..., 1.39292799513138,
0.0783137314443... - 0.492840991709...*I,
0.0783137314443... + 0.492840991709...*I]
```



Observe that this is a group homomorphism (modulo rounding error):

```
sage: z = CC.random_element()
sage: 2 * E.elliptic_exponential(z)
(-1.52184235874404 - 0.0581413944316544*I : 0.948655866506124 - 0.
↪0381469928565030*I : 1.000000000000000)
sage: E.elliptic_exponential(2 * z)
(-1.52184235874404 - 0.0581413944316562*I : 0.948655866506128 - 0.
↪0381469928565034*I : 1.000000000000000)
```

#### **eval\_modular\_form**(*points*, *prec*)

Evaluate the modular form of this elliptic curve at points in **C**.

INPUT:

- *points* - a list of points in the half-plane of convergence
- *prec* - precision

OUTPUT: A list of values  $L(E, s)$  for  $s$  in *points*

---

**Note:** Better examples are welcome.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.eval_modular_form([1.5+I, 2.0+I, 2.5+I], 0.000001)
[0, 0, 0]
```

#### **galois\_representation**()

The compatible family of the Galois representation attached to this elliptic curve.

Given an elliptic curve  $E$  over  $\mathbf{Q}$  and a rational prime number  $p$ , the  $p^n$ -torsion  $E[p^n]$  points of  $E$  is a representation of the absolute Galois group of  $\mathbf{Q}$ . As  $n$  varies we obtain the Tate module  $T_p E$  which is a representation of  $G_K$  on a free  $\mathbf{Z}_p$ -module of rank 2. As  $p$  varies the representations are compatible.

EXAMPLES:

```
sage: rho = EllipticCurve('11a1').galois_representation()
sage: rho
Compatible family of Galois representations associated to the Elliptic Curve_
↪defined by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: rho.is_irreducible(7)
True
sage: rho.is_irreducible(5)
False
sage: rho.is_surjective(11)
True
sage: rho.non_surjective()
[5]
sage: rho = EllipticCurve('37a1').galois_representation()
sage: rho.non_surjective()
[]
sage: rho = EllipticCurve('27a1').galois_representation()
sage: rho.is_irreducible(7)
True
sage: rho.non_surjective() # cm-curve
[0]
```

**gens** (*proof=None, \*\*kws*)

Return generators for the Mordell-Weil group  $E(Q)$  modulo torsion.

INPUT:

- **proof** – bool or None (default None), see `proof.elliptic_curve` or `sage.structure.proof.proof`
- **verbose** - (default: None), if specified changes the verbosity of mwrank computations
- **rank1\_search** - (default: 10), if the curve has analytic rank 1, try to find a generator by a direct search up to this logarithmic height. If this fails, the usual mwrank procedure is called.
- **algorithm** – one of the following:
  - 'mwrank\_shell' (default) – call mwrank shell command
  - 'mwrank\_lib' – call mwrank C library
- **only\_use\_mwrank** – bool (default True) if False, first attempts to use more naive, natively implemented methods
- **use\_database** – bool (default True) if True, attempts to find curve and gens in the (optional) database
- **descent\_second\_limit** – (default: 12) used in 2-descent
- **sat\_bound** – (default: 1000) bound on primes used in saturation. If the computed bound on the index of the points found by two-descent in the Mordell-Weil group is greater than this, a warning message will be displayed.

OUTPUT:

- **generators** - list of generators for the Mordell-Weil group modulo torsion

---

**Note:** If you call this with `proof=False`, then you can use the `gens_certain()` method to find out afterwards whether the generators were proved.

---

IMPLEMENTATION: Uses Cremona's mwrank C library.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: E.gens() # random output
[(-1 : 1 : 1), (0 : 0 : 1)]
```

A non-integral example:

```
sage: E = EllipticCurve([-3/8, -2/3])
sage: E.gens() # random (up to sign)
[(10/9 : 29/54 : 1)]
```

A non-minimal example:

```
sage: E = EllipticCurve('389a1')
sage: E1 = E.change_weierstrass_model([1/20, 0, 0, 0]); E1
Elliptic Curve defined by  $y^2 + 8000y = x^3 + 400x^2 - 320000x$  over  $\mathbb{Q}$ 
↪ Rational Field
sage: E1.gens() # random (if database not used)
[(-400 : 8000 : 1), (0 : -8000 : 1)]
```

**gens\_certain()**

Return True if the generators have been proven correct.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.gens()                # random (up to sign)
[(0 : -1 : 1)]
sage: E.gens_certain()
True
```

**global\_integral\_model()**

Return a model of self which is integral at all primes.

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1/216, -7/1296, 1/7776])
sage: F = E.global_integral_model(); F
Elliptic Curve defined by  $y^2 + y = x^3 - 7x + 6$  over Rational Field
sage: F == EllipticCurve('5077a1')
True
```

**has\_cm()**

Return whether or not this curve has a CM  $j$ -invariant.

OUTPUT:

True if the  $j$ -invariant of this curve is the  $j$ -invariant of an imaginary quadratic order, otherwise False.

See also:

`cm_discriminant()` and `has_rational_cm()`

---

**Note:** Even if  $E$  has CM in this sense (that its  $j$ -invariant is a CM  $j$ -invariant), since the associated negative discriminant  $D$  is not a square in  $\mathbf{Q}$ , the extra endomorphisms will not be defined over  $\mathbf{Q}$ . See also the method `has_rational_cm()` which tests whether  $E$  has extra endomorphisms defined over  $\mathbf{Q}$  or a given extension of  $\mathbf{Q}$ .

---

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.has_cm()
False
sage: E = EllipticCurve('32a1')
sage: E.has_cm()
True
sage: E.j_invariant()
1728
```

**has\_good\_reduction\_outside\_S(S=[])**

Test if this elliptic curve has good reduction outside  $S$ .

INPUT:

- $S$  – list of primes (default: empty list).

---

**Note:** Primality of elements of  $S$  is not checked, and the output is undefined if  $S$  is not a list or contains non-primes.

This only tests the given model, so should only be applied to minimal models.

EXAMPLES:

```
sage: EllipticCurve('11a1').has_good_reduction_outside_S([11])
True
sage: EllipticCurve('11a1').has_good_reduction_outside_S([2])
False
sage: EllipticCurve('2310a1').has_good_reduction_outside_S([2,3,5,7])
False
sage: EllipticCurve('2310a1').has_good_reduction_outside_S([2,3,5,7,11])
True
```

**has\_rational\_cm**(*field=None*)

Return whether or not this curve has CM defined over  $\mathbf{Q}$  or the given field.

INPUT:

- *field* – a field, which should be an extension of  $\mathbf{Q}$ . If *field* is *None* (the default), it is taken to be  $\mathbf{Q}$ .

OUTPUT:

True if the ring of endomorphisms of this curve over the given field is larger than  $\mathbf{Z}$ ; otherwise False. If *field* is *None* the output will always be False. See also [cm\\_discriminant\(\)](#) and [has\\_cm\(\)](#).

**Note:** If  $E$  has CM but the discriminant  $D$  is not a square in the given field  $K$ , which will certainly be the case for  $K = \mathbf{Q}$  since  $D < 0$ , then the extra endomorphisms will not be defined over  $K$ , and this function will return False. See also [has\\_cm\(\)](#). To obtain the CM discriminant, use [cm\\_discriminant\(\)](#).

EXAMPLES:

```
sage: E = EllipticCurve(j=0)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: D = E.cm_discriminant(); D
-3
```

If we extend scalars to a field in which the discriminant is a square, the CM becomes rational:

```
sage: E.has_rational_cm(QuadraticField(-3))
True

sage: E = EllipticCurve(j=8000)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: D = E.cm_discriminant(); D
-8
```

Again, we may extend scalars to a field in which the discriminant is a square, where the CM becomes rational:

```
sage: E.has_rational_cm(QuadraticField(-2))
True
```

The field need not be a number field provided that it is an extension of  $\mathbb{Q}$ :

```
sage: E.has_rational_cm(RR)
False
sage: E.has_rational_cm(CC)
True
```

An error is raised if a field is given which is not an extension of  $\mathbb{Q}$ , i.e., not of characteristic 0:

```
sage: E.has_rational_cm(GF(2))
Traceback (most recent call last):
...
ValueError: Error in has_rational_cm: Finite Field of size 2 is not an_
↳extension field of QQ
```

### **heegner\_discriminants** (*bound*)

Return the list of self's Heegner discriminants between -1 and -bound.

INPUT:

- bound (int) - upper bound for -discriminant

OUTPUT: The list of Heegner discriminants between -1 and -bound for the given elliptic curve.

EXAMPLES:

```
sage: E=EllipticCurve('11a')
sage: E.heegner_discriminants(30)                                     # indirect doctest
[-7, -8, -19, -24]
```

### **heegner\_discriminants\_list** (*n*)

Return the list of self's first  $n$  Heegner discriminants smaller than -5.

INPUT:

- n (int) - the number of discriminants to compute

OUTPUT: The list of the first  $n$  Heegner discriminants smaller than -5 for the given elliptic curve.

EXAMPLES:

```
sage: E=EllipticCurve('11a')
sage: E.heegner_discriminants_list(4)                               # indirect doctest
[-7, -8, -19, -24]
```

### **heegner\_index** (*D*, *min\_p*=2, *prec*=5, *descent\_second\_limit*=12, *verbose\_mwrank*=False, *check\_rank*=True)

Return an interval that contains the index of the Heegner point  $y_K$  in the group of  $K$ -rational points modulo torsion on this elliptic curve, computed using the Gross-Zagier formula and/or a point search, or possibly half the index if the rank is greater than one.

If the curve has rank  $> 1$ , then the returned index is infinity.

---

**Note:** If  $\text{min\_p}$  is bigger than 2 then the index can be off by any prime less than  $\text{min\_p}$ . This function returns the index divided by 2 exactly when the rank of  $E(K)$  is greater than 1 and  $E(\mathbb{Q})_{\text{tor}} \oplus E^D(\mathbb{Q})_{\text{tor}}$  has index 2 in  $E(K)_{\text{tor}}$ , where the second factor undergoes a twist.

---

INPUT:

- `D` (int) - Heegner discriminant
- `min_p` (int) - (default: 2) only rule out primes = `min_p` dividing the index.
- `verbose_mwrank` (bool) - (default: False); print lots of mwrank search status information when computing regulator
- `prec` (int) - (default: 5), use `prec*sqrt(N) + 20` terms of L-series in computations, where `N` is the conductor.
- `descent_second_limit` - (default: 12)- used in 2-descent when computing regulator of the twist
- `check_rank` - whether to check if the rank is at least 2 by computing the Mordell-Weil rank directly.

OUTPUT: an interval that contains the index, or half the index

EXAMPLES:

```
sage: E = EllipticCurve('11a')
sage: E.heegner_discriminants(50)
[-7, -8, -19, -24, -35, -39, -40, -43]
sage: E.heegner_index(-7)
1.00000?
```

```
sage: E = EllipticCurve('37b')
sage: E.heegner_discriminants(100)
[-3, -4, -7, -11, -40, -47, -67, -71, -83, -84, -95]
sage: E.heegner_index(-95)          # long time (1 second)
2.00000?
```

This tests doing direct computation of the Mordell-Weil group.

```
sage: EllipticCurve('675b').heegner_index(-11)
3.0000?
```

Currently discriminants -3 and -4 are not supported:

```
sage: E.heegner_index(-3)
Traceback (most recent call last):
...
ArithmeticError: Discriminant (=-3) must not be -3 or -4.
```

The curve 681b returns the true index, which is 3:

```
sage: E = EllipticCurve('681b')
sage: I = E.heegner_index(-8); I
3.0000?
```

In fact, whenever the returned index has a denominator of 2, the true index is got by multiplying the returned index by 2. Unfortunately, this is not an if and only if condition, i.e., sometimes the index must be multiplied by 2 even though the denominator is not 2.

This example demonstrates the `descent_second_limit` option, which can be used to fine tune the 2-descent used to compute the regulator of the twist:

```
sage: E = EllipticCurve([1, -1, 0, -1228, -16267])
sage: E.heegner_index(-8)
Traceback (most recent call last):
```

```
...
RuntimeError: ...
```

However when we search higher, we find the points we need:

```
sage: E.heegner_index(-8, descent_second_limit=16, check_rank=False)
2.00000?
```

Two higher rank examples (of ranks 2 and 3):

```
sage: E = EllipticCurve('389a')
sage: E.heegner_index(-7)
+Infinity
sage: E = EllipticCurve('5077a')
sage: E.heegner_index(-7)
+Infinity
sage: E.heegner_index(-7, check_rank=False)
0.001?
sage: E.heegner_index(-7, check_rank=False).lower() == 0
True
```

**heegner\_index\_bound** ( $D=0$ ,  $prec=5$ ,  $max\_height=None$ )

Assume self has rank 0.

Return a list  $v$  of primes such that if an odd prime  $p$  divides the index of the Heegner point in the group of rational points modulo torsion, then  $p$  is in  $v$ .

If 0 is in the interval of the height of the Heegner point computed to the given  $prec$ , then this function returns  $v = 0$ . This does not mean that the Heegner point is torsion, just that it is very likely torsion.

If we obtain no information from a search up to  $max\_height$ , e.g., if the Siksek et al. bound is bigger than  $max\_height$ , then we return  $v = -1$ .

INPUT:

- $D$  (int) - (default: 0) Heegner discriminant; if 0, use the first discriminant  $-4$  that satisfies the Heegner hypothesis
- $verbose$  (bool) - (default: True)
- $prec$  (int) - (default: 5), use  $prec \cdot \sqrt{(N)} + 20$  terms of  $L$ -series in computations, where  $N$  is the conductor.
- $max\_height$  (float) - should be  $\approx 21$ ; bound on logarithmic naive height used in point searches. Make smaller to make this function faster, at the expense of possibly obtaining a worse answer. A good range is between 13 and 21.

OUTPUT:

- $v$  - list or int (bad primes or 0 or -1)
- $D$  - the discriminant that was used (this is useful if  $D$  was automatically selected).
- $exact$  - either False, or the exact Heegner index (up to factors of 2)

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.heegner_index_bound()
([2], -7, 2)
```

**heegner\_point** ( $D, c=1, f=None, check=True$ )

Returns the Heegner point on this curve associated to the quadratic imaginary field  $K = \mathbf{Q}(\sqrt{D})$ .

If the optional parameter  $c$  is given, returns the higher Heegner point associated to the order of conductor  $c$ .

INPUT:

- $D$  – a Heegner discriminant
- $c$  – (default: 1) conductor, must be coprime to  $DN$
- $f$  – binary quadratic form or 3-tuple  $(A, B, C)$  of coefficients of  $AX^2 + BXY + CY^2$
- $check$  – bool (default: True)

OUTPUT:

The Heegner point  $y_c$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.heegner_discriminants_list(10)
[-7, -11, -40, -47, -67, -71, -83, -84, -95, -104]
sage: P = E.heegner_point(-7); P                                     # indirect doctest
Heegner point of discriminant -7 on elliptic curve of conductor 37
sage: P.point_exact()
(0 : 0 : 1)
sage: P.curve()
Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field
sage: P = E.heegner_point(-40).point_exact(); P
(a : -a + 1 : 1)
sage: P = E.heegner_point(-47).point_exact(); P
(a : a^4 + a - 1 : 1)
sage: P[0].parent()
Number Field in a with defining polynomial x^5 - x^4 + x^3 + x^2 - 2*x + 1
```

Working out the details manually:

```
sage: P = E.heegner_point(-47).numerical_approx(prec=200)
sage: f = algdep(P[0], 5); f
x^5 - x^4 + x^3 + x^2 - 2*x + 1
sage: f.discriminant().factor()
47^2
```

The Heegner hypothesis is checked:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-5, 7);
Traceback (most recent call last):
...
ValueError: N (=389) and D (=-5) must satisfy the Heegner hypothesis
```

We can specify the quadratic form:

```
sage: P = EllipticCurve('389a').heegner_point(-7, 5, (778, 925, 275)); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of_
↪conductor 389
sage: P.quadratic_form()
778*x^2 + 925*x*y + 275*y^2
```



**heegner\_point\_height** ( $D$ ,  $prec=2$ ,  $check\_rank=True$ )

Use the Gross-Zagier formula to compute the Neron-Tate canonical height over  $K$  of the Heegner point corresponding to  $D$ , as an interval (it is computed to some precision using  $L$ -functions).

If the curve has rank at least 2, then the returned height is the exact Sage integer 0.

INPUT:

- $D$  (int) - fundamental discriminant ( $\neq -3, -4$ )
- **prec** (int) - (default: 2), use  $prec \cdot \sqrt{(N)} + 20$  terms of  $L$ -series in computations, where  $N$  is the conductor.
- $check\_rank$  - whether to check if the rank is at least 2 by computing the Mordell-Weil rank directly.

OUTPUT: Interval that contains the height of the Heegner point.

EXAMPLES:

```
sage: E = EllipticCurve('11a')
sage: E.heegner_point_height(-7)
0.22227?
```

Some higher rank examples:

```
sage: E = EllipticCurve('389a')
sage: E.heegner_point_height(-7)
0
sage: E = EllipticCurve('5077a')
sage: E.heegner_point_height(-7)
0
sage: E.heegner_point_height(-7, check_rank=False)
0.0000?
```

**heegner\_sha\_an** ( $D$ ,  $prec=53$ )

Return the conjectural (analytic) order of Sha for  $E$  over the field  $K = \mathbf{Q}(\sqrt{D})$ .

INPUT:

- $D$  - negative integer; the Heegner discriminant
- $prec$  - integer (default: 53); bits of precision to compute analytic order of Sha

OUTPUT:

(floating point number) an approximation to the conjectural order of Sha.

---

**Note:** Often you'll want to do `proof.elliptic_curve(False)` when using this function, since often the twisted elliptic curves that come up have enormous conductor, and Sha is nontrivial, which makes provably finding the Mordell-Weil group using 2-descent difficult.

---

EXAMPLES:

An example where  $E$  has conductor 11:

```
sage: E = EllipticCurve('11a')
sage: E.heegner_sha_an(-7)
1.0000000000000000 # long time
```

The cache works:

```
sage: E.heegner_sha_an(-7) is E.heegner_sha_an(-7)      # long time
True
```

Lower precision:

```
sage: E.heegner_sha_an(-7,10)                          # long time
1.0
```

Checking that the cache works for any precision:

```
sage: E.heegner_sha_an(-7,10) is E.heegner_sha_an(-7,10)  # long time
True
```

Next we consider a rank 1 curve with nontrivial Sha over the quadratic imaginary field  $K$ ; however, there is no Sha for  $E$  over  $\mathbb{Q}$  or for the quadratic twist of  $E$ :

```
sage: E = EllipticCurve('37a')
sage: E.heegner_sha_an(-40)                          # long time
4.0000000000000000
sage: E.quadratic_twist(-40).sha().an()              # long time
1
sage: E.sha().an()                                    # long time
1
```

A rank 2 curve:

```
sage: E = EllipticCurve('389a')                      # long time
sage: E.heegner_sha_an(-7)                          # long time
1.0000000000000000
```

If we remove the hypothesis that  $E(K)$  has rank 1 in Conjecture 2.3 in [Gross-Zagier, 1986, page 311], then that conjecture is false, as the following example shows:

```
sage: E = EllipticCurve('65a')                      # long time
sage: E.heegner_sha_an(-56)                          # long time
1.0000000000000000
sage: E.torsion_order()                              # long time
2
sage: E.tamagawa_product()                          # long time
1
sage: E.quadratic_twist(-56).rank()                  # long time
2
```

**height** (*precision=None*)

Return the real height of this elliptic curve. This is used in `integral_points()`

INPUT:

- `precision` - desired real precision of the result (default real precision if None)

EXAMPLES:

```
sage: E = EllipticCurve('5077a1')
sage: E.height()
17.4513334798896
sage: E.height(100)
17.451333479889612702508579399
sage: E = EllipticCurve([0,0,0,0,1])
```

```
sage: E.height()
1.38629436111989
sage: E = EllipticCurve([0,0,0,1,0])
sage: E.height()
7.45471994936400
```

**integral\_model()**

Return a model of self which is integral at all primes.

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1/216, -7/1296, 1/7776])
sage: F = E.global_integral_model(); F
Elliptic Curve defined by  $y^2 + y = x^3 - 7x + 6$  over Rational Field
sage: F == EllipticCurve('5077a1')
True
```

**integral\_points(mw\_base='auto', both\_signs=False, verbose=False)**

Compute all integral points (up to sign) on this elliptic curve.

INPUT:

- `mw_base` - list of `EllipticCurvePoint` generating the Mordell-Weil group of `E` (default: 'auto' - calls `self.gens()`)
- `both_signs` - True/False (default False): if True the output contains both `P` and `-P`, otherwise only one of each pair.
- `verbose` - True/False (default False): if True, some details of the computation are output

OUTPUT: A sorted list of all the integral points on `E` (up to sign unless `both_signs` is True)

---

**Note:** The complexity increases exponentially in the rank of curve `E`. The computation time (but not the output!) depends on the Mordell-Weil basis. If `mw_base` is given but is not a basis for the Mordell-Weil group (modulo torsion), integral points which are not in the subgroup generated by the given points will almost certainly not be listed.

---

EXAMPLES: A curve of rank 3 with no torsion points

```
sage: E = EllipticCurve([0,0,1,-7,6])
sage: P1=E.point((2,0)); P2=E.point((-1,3)); P3=E.point((4,6))
sage: a=E.integral_points([P1,P2,P3]); a
[(-3 : 0 : 1), (-2 : 3 : 1), (-1 : 3 : 1), (0 : 2 : 1), (1 : 0 : 1), (2 : 0 : 1),
 (3 : 3 : 1), (4 : 6 : 1), (8 : 21 : 1), (11 : 35 : 1), (14 : 51 : 1),
 (21 : 95 : 1), (37 : 224 : 1), (52 : 374 : 1), (93 : 896 : 1), (342 : 6324 : 1),
 (406 : 8180 : 1), (816 : 23309 : 1)]
```

```
sage: a = E.integral_points([P1,P2,P3], verbose=True)
Using mw_basis [(2 : 0 : 1), (3 : -4 : 1), (8 : -22 : 1)]
e1,e2,e3: -3.0124303725933... 1.0658205476962... 1.94660982489710
Minimal and maximal eigenvalues of height pairing matrix: 0.637920814585005,2.
31982967525725
x-coords of points on compact component with -3 <=x<= 1
[-3, -2, -1, 0, 1]
x-coords of points on non-compact component with 2 <=x<= 6
[2, 3, 4]
starting search of remaining points using coefficient bound 5 and |x| bound 1.
53897183921009e25
```

```
x-coords of extra integral points:
[2, 3, 4, 8, 11, 14, 21, 37, 52, 93, 342, 406, 816]
Total number of integral points: 18
```

It is not necessary to specify `mw_base`; if it is not provided, then the Mordell-Weil basis must be computed, which may take much longer.

```
sage: E = EllipticCurve([0,0,1,-7,6])
sage: a=E.integral_points(both_signs=True); a
[(-3 : -1 : 1), (-3 : 0 : 1), (-2 : -4 : 1), (-2 : 3 : 1), (-1 : -4 : 1), (-1 :
↪ 3 : 1), (0 : -3 : 1), (0 : 2 : 1), (1 : -1 : 1), (1 : 0 : 1), (2 : -1 :
↪ 1), (2 : 0 : 1), (3 : -4 : 1), (3 : 3 : 1), (4 : -7 : 1), (4 : 6 : 1), (8 :
↪ -22 : 1), (8 : 21 : 1), (11 : -36 : 1), (11 : 35 : 1), (14 : -52 : 1), (14 :
↪ 51 : 1), (21 : -96 : 1), (21 : 95 : 1), (37 : -225 : 1), (37 : 224 : 1),
↪ (52 : -375 : 1), (52 : 374 : 1), (93 : -897 : 1), (93 : 896 : 1), (342 : -
↪ 6325 : 1), (342 : 6324 : 1), (406 : -8181 : 1), (406 : 8180 : 1), (816 : -
↪ 23310 : 1), (816 : 23309 : 1)]
```

An example with negative discriminant:

```
sage: EllipticCurve('900d1').integral_points()
[(-11 : 27 : 1), (-4 : 34 : 1), (4 : 18 : 1), (16 : 54 : 1)]
```

Another example with rank 5 and no torsion points:

```
sage: E = EllipticCurve([-879984,319138704])
sage: P1=E.point((540,1188)); P2=E.point((576,1836))
sage: P3=E.point((468,3132)); P4=E.point((612,3132))
sage: P5=E.point((432,4428))
sage: a=E.integral_points([P1,P2,P3,P4,P5]); len(a) # long time (18s on sage.
↪ math, 2011)
54
```

```
sage: [len(e.integral_points(both_signs=False)) for e in cremona_curves([11..
↪ 100])] # long time (15s on sage.math, 2011)
[2, 0, 2, 3, 2, 1, 3, 0, 2, 4, 2, 4, 3, 0, 0, 1, 2, 1, 2, 0, 2, 1, 0, 1, 3, 3,
↪ 1, 1, 4, 2, 3, 2, 0, 0, 5, 3, 2, 2, 1, 1, 1, 0, 1, 3, 0, 1, 0, 1, 1, 3, 6,
↪ 1, 2, 2, 2, 0, 0, 2, 3, 1, 2, 2, 1, 1, 0, 3, 2, 1, 0, 1, 0, 1, 3, 3, 1, 1,
↪ 5, 1, 0, 1, 1, 0, 1, 2, 0, 2, 0, 1, 1, 3, 1, 2, 2, 4, 4, 2, 1, 0, 0, 5, 1,
↪ 0, 1, 2, 0, 2, 2, 0, 0, 0, 1, 0, 3, 1, 5, 1, 2, 4, 1, 0, 1, 0, 1, 0, 1, 0,
↪ 2, 2, 0, 0, 1, 0, 1, 1, 4, 1, 0, 1, 1, 0, 4, 2, 0, 1, 1, 2, 3, 1, 1, 1, 1,
↪ 6, 2, 1, 1, 0, 2, 0, 6, 2, 0, 4, 2, 2, 0, 0, 1, 2, 0, 2, 1, 0, 3, 1, 2, 1,
↪ 4, 6, 3, 2, 1, 0, 2, 2, 0, 0, 5, 4, 1, 0, 0, 1, 0, 2, 2, 0, 0, 2, 3, 1, 3,
↪ 1, 1, 0, 1, 0, 0, 1, 2, 2, 0, 2, 0, 0, 1, 2, 0, 0, 4, 1, 0, 1, 1, 0, 1, 2,
↪ 0, 1, 4, 3, 1, 2, 2, 1, 1, 1, 1, 6, 3, 3, 3, 3, 1, 1, 1, 1, 1, 0, 7, 3, 0,
↪ 1, 3, 2, 1, 0, 3, 2, 1, 0, 2, 2, 6, 0, 0, 6, 2, 2, 3, 3, 5, 5, 1, 0, 6, 1,
↪ 0, 3, 1, 1, 2, 3, 1, 2, 1, 1, 0, 1, 0, 1, 0, 5, 5, 2, 2, 0, 0, 1, 0, 0, 0,
↪ 0, 1, 1, 1, 1]
```

The bug reported at [trac ticket #4897](#) is now fixed:

```
sage: [P[0] for P in EllipticCurve([0,0,0,-468,2592]).integral_points()]
[-24, -18, -14, -6, -3, 4, 6, 18, 21, 24, 36, 46, 102, 168, 186, 381, 1476,
↪ 2034, 67246]
```

See [trac ticket #22063](#):

```

sage: for n in [67, 71, 74, 91]:
....:     assert 4*n^6+4*n^2 in [P[0] for P in EllipticCurve([0,0,0,2,n^2]).
↪integral_points()]

```

**Note:** This function uses the algorithm given in [Coh2007I].

AUTHORS:

- Michael Mordaus (2008-07)
- Tobias Nagel (2008-07)
- John Cremona (2008-07)

**integral\_short\_weierstrass\_model()**

Return a model of the form  $y^2 = x^3 + ax + b$  for this curve with  $a, b \in \mathbf{Z}$ .

EXAMPLES:

```

sage: E = EllipticCurve('17a1')
sage: E.integral_short_weierstrass_model()
Elliptic Curve defined by y^2 = x^3 - 11*x - 890 over Rational Field

```

**integral\_weierstrass\_model()**

Return a model of the form  $y^2 = x^3 + ax + b$  for this curve with  $a, b \in \mathbf{Z}$ .

Note that this function is deprecated, and that you should use `integral_short_weierstrass_model` instead as this will be disappearing in the near future.

EXAMPLES:

```

sage: E = EllipticCurve('17a1')
sage: E.integral_weierstrass_model() #random
doctest:...: DeprecationWarning: integral_weierstrass_model is deprecated,
↪use integral_short_weierstrass_model instead!
Elliptic Curve defined by y^2 = x^3 - 11*x - 890 over Rational Field

```

**integral\_x\_coords\_in\_interval(xmin, xmax)**

Return the set of integers  $x$  with  $xmin \leq x \leq xmax$  which are  $x$ -coordinates of rational points on this curve.

INPUT:

- `xmin, xmax` (integers) – two integers.

OUTPUT:

(set) The set of integers  $x$  with  $xmin \leq x \leq xmax$  which are  $x$ -coordinates of rational points on the elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve([0, 0, 1, -7, 6])
sage: xset = E.integral_x_coords_in_interval(-100, 100)
sage: sorted(xset)
[-3, -2, -1, 0, 1, 2, 3, 4, 8, 11, 14, 21, 37, 52, 93]
sage: xset = E.integral_x_coords_in_interval(-100, 0)
sage: sorted(xset)
[-3, -2, -1, 0]

```

**is\_global\_integral\_model()**

Return True iff self is integral at all primes.

EXAMPLES:

```

sage: E = EllipticCurve([1/2, 1/5, 1/5, 1/5, 1/5])
sage: E.is_global_integral_model()
False
sage: Emin=E.global_integral_model()
sage: Emin.is_global_integral_model()
True

```

**is\_good(p, check=True)**Return True if  $p$  is a prime of good reduction for  $E$ .

INPUT:

- $p$  - a prime

OUTPUT: bool

EXAMPLES:

```

sage: e = EllipticCurve('11a')
sage: e.is_good(-8)
Traceback (most recent call last):
...
ValueError: p must be prime
sage: e.is_good(-8, check=False)
True

```

**is\_integral()**Return True if this elliptic curve has integral coefficients (in  $\mathbb{Z}$ ).

EXAMPLES:

```

sage: E = EllipticCurve(QQ, [1, 1]); E
Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Rational Field
sage: E.is_integral()
True
sage: E2=E.change_weierstrass_model(2, 0, 0, 0); E2
Elliptic Curve defined by  $y^2 = x^3 + 1/16x + 1/64$  over Rational Field
sage: E2.is_integral()
False

```

**is\_isogenous(other, proof=True, maxp=200)**

Return whether or not self is isogenous to other.

INPUT:

- other – another elliptic curve.
- proof (default True) – If False, the function will return True whenever the two curves have the same conductor and are isogenous modulo  $p$  for  $p$  up to maxp. If True, this test is followed by a rigorous test (which may be more time-consuming).
- maxp (int, default 200) – The maximum prime  $p$  for which isogeny modulo  $p$  will be checked.

OUTPUT:

(bool) True if there is an isogeny from curve self to curve other.

METHOD:

First the conductors are compared as well as the Traces of Frobenius for good primes up to `maxp`. If any of these tests fail, `False` is returned. If they all pass and `proof` is `False` then `True` is returned, otherwise a complete set of curves isogenous to `self` is computed and `other` is checked for isomorphism with any of these,

EXAMPLES:

```
sage: E1 = EllipticCurve('14a1')
sage: E6 = EllipticCurve('14a6')
sage: E1.is_isogenous(E6)
True
sage: E1.is_isogenous(EllipticCurve('11a1'))
False
```

```
sage: EllipticCurve('37a1').is_isogenous(EllipticCurve('37b1'))
False
```

```
sage: E = EllipticCurve([2, 16])
sage: EE = EllipticCurve([87, 45])
sage: E.is_isogenous(EE)
False
```

**`is_local_integral_model(*p)`**

Tests if `self` is integral at the prime `p`, or at all the primes if `p` is a list or tuple of primes

EXAMPLES:

```
sage: E = EllipticCurve([1/2, 1/5, 1/5, 1/5, 1/5])
sage: [E.is_local_integral_model(p) for p in (2, 3, 5)]
[False, True, False]
sage: E.is_local_integral_model(2, 3, 5)
False
sage: Eint2=E.local_integral_model(2)
sage: Eint2.is_local_integral_model(2)
True
```

**`is_minimal()`**

Return `True` iff this elliptic curve is a reduced minimal model.

The unique minimal Weierstrass equation for this elliptic curve. This is the model with minimal discriminant and  $a_1, a_2, a_3 \in \{0, \pm 1\}$ .

---

**Todo:** This is not very efficient since it just computes the minimal model and compares. A better implementation using the Kraus conditions would be preferable.

---

EXAMPLES:

```
sage: E = EllipticCurve([10, 100, 1000, 10000, 1000000])
sage: E.is_minimal()
False
sage: E = E.minimal_model()
sage: E.is_minimal()
True
```

**`is_ordinary(p, ell=None)`**

Return `True` precisely when the mod-`p` representation attached to this elliptic curve is ordinary at `ell`.

INPUT:

- $p$  - a prime ell - a prime (default:  $p$ )

OUTPUT: bool

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.is_ordinary(37)
True
sage: E = EllipticCurve('32a1')
sage: E.is_ordinary(2)
False
sage: [p for p in prime_range(50) if E.is_ordinary(p)]
[5, 13, 17, 29, 37, 41]
```

**is\_p\_integral( $p$ )**

Return True if this elliptic curve has  $p$ -integral coefficients.

INPUT:

- $p$  – a prime integer

EXAMPLES:

```
sage: E = EllipticCurve(QQ, [1, 1]); E
Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Rational Field
sage: E.is_p_integral(2)
True
sage: E2=E.change_weierstrass_model(2, 0, 0, 0); E2
Elliptic Curve defined by  $y^2 = x^3 + 1/16x + 1/64$  over Rational Field
sage: E2.is_p_integral(2)
False
sage: E2.is_p_integral(3)
True
```

**is\_p\_minimal( $p$ )**

Tests if curve is  $p$ -minimal at a given prime  $p$ .

INPUT:  $p$  - a prime

OUTPUT: True - if curve is  $p$ -minimal

- False - if curve isn't  $p$ -minimal

EXAMPLES:

```
sage: E = EllipticCurve('441a2')
sage: E.is_p_minimal(7)
True
```

```
sage: E = EllipticCurve([0, 0, 0, 0, (2*5*11)**10])
sage: [E.is_p_minimal(p) for p in prime_range(2, 24)]
[False, True, False, True, False, True, True, True, True]
```

**is\_semistable()**

Return True iff this elliptic curve is semi-stable at all primes.

EXAMPLES:



```

sage: E = EllipticCurve('37a1')
sage: E.is_semistable()
True
sage: E = EllipticCurve('90a1')
sage: E.is_semistable()
False

```

**is\_supersingular** (*p, ell=None*)

Return True precisely when *p* is a prime of good reduction and the mod-*p* representation attached to this elliptic curve is supersingular at *ell*.

INPUT:

- *p* - a prime *ell* - a prime (default: *p*)

OUTPUT: bool

EXAMPLES:

```

sage: E = EllipticCurve('37a1')
sage: E.is_supersingular(37)
False
sage: E = EllipticCurve('32a1')
sage: E.is_supersingular(2)
False
sage: E.is_supersingular(7)
True
sage: [p for p in prime_range(50) if E.is_supersingular(p)]
[3, 7, 11, 19, 23, 31, 43, 47]

```

**isogenies\_prime\_degree** (*l=None*)

Return a list of *l*-isogenies from self, where *l* is a prime.

INPUT:

- *l* – either None or a prime or a list of primes.

OUTPUT:

(list) *l*-isogenies for the given *l* or if *l* is None, all *l*-isogenies.

---

**Note:** The codomains of the isogenies returned are standard minimal models. This is because the functions `isogenies_prime_degree_genus_0()` and `isogenies_sporadic_Q()` are implemented that way for curves defined over  $\mathbb{Q}$ .

---

EXAMPLES:

```

sage: E = EllipticCurve([45, 32])
sage: E.isogenies_prime_degree()
[]
sage: E = EllipticCurve(j = -262537412640768000)
sage: E.isogenies_prime_degree()
[Isogeny of degree 163 from Elliptic Curve defined by y^2 + y = x^3 -
↳ 2174420*x + 1234136692 over Rational Field to Elliptic Curve defined by y^2,
↳ + y = x^3 - 57772164980*x - 534473377551611 over Rational Field]
sage: E1 = E.quadratic_twist(6584935282)
sage: E1.isogenies_prime_degree()
[Isogeny of degree 163 from Elliptic Curve defined by y^2 = x^3 -
↳ 94285835957031797981376080*x + 352385311612420041387338054224547830898 over
↳ Rational Field to Elliptic Curve defined by y^2 = x^3 -
↳ 2505080375542377840567181069520*x -
↳ 1526091631109553256978090116318797845018020806 over Rational Field]

```

```

sage: E = EllipticCurve('14a1')
sage: E.isogenies_prime_degree(2)
[Isogeny of degree 2 from Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x^2 - 6$  over Rational Field to Elliptic Curve defined by  $y^2 + xy + y = x^3 - 36x - 70$  over Rational Field]
sage: E.isogenies_prime_degree(3)
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x^2 - 6$  over Rational Field to Elliptic Curve defined by  $y^2 + xy + y = x^3 - x$  over Rational Field, Isogeny of degree 3 from Elliptic Curve defined by  $y^2 + xy + y = x^3 + 4x^2 - 6$  over Rational Field to Elliptic Curve defined by  $y^2 + xy + y = x^3 - 171x - 874$  over Rational Field]
sage: E.isogenies_prime_degree(5)
[]
sage: E.isogenies_prime_degree(11)
[]
sage: E.isogenies_prime_degree(29)
[]
sage: E.isogenies_prime_degree(4)
Traceback (most recent call last):
...
ValueError: 4 is not prime.

```

**isogeny\_class** (*algorithm*='sage', *order*=None)

Return the  $\mathbb{Q}$ -isogeny class of this elliptic curve.

INPUT:

- *algorithm* - string: one of the following:
  - “database” - use the Cremona database (only works if curve is isomorphic to a curve in the database)
  - “sage” (default) - use the native Sage implementation.
- *order* – None, string, or list of curves (default: None): If not None then the curves in the class are reordered after being computed. Note that if the order is None then the resulting order will depend on the algorithm.
  - if *order* is “database” or “sage”, then the reordering is so that the order of curves matches the order produced by that algorithm.
  - if *order* is “lmfdb” then the curves are sorted lexicographically by *a*-invariants, in the LMFDB database.
  - if *order* is a list of curves, then the curves in the class are reordered to be isomorphic with the specified list of curves.

OUTPUT:

An instance of the class `sage.schemes.elliptic_curves.isogeny_class.IsogenyClass_EC_Rational`. This object models a list of minimal models (with containment, index, etc based on isomorphism classes). It also has methods for computing the isogeny matrix and the list of isogenies between curves in this class.

---

**Note:** The curves in the isogeny class will all be standard minimal models.

---

EXAMPLES:

```

sage: isocls = EllipticCurve('37b').isogeny_class(order="lmfdb")
sage: isocls
Elliptic curve isogeny class 37b
sage: isocls.curves
(Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 1873x - 31833$  over Rational
↪Field,
 Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 23x - 50$  over Rational
↪Field,
 Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 3x + 1$  over Rational Field)
sage: isocls.matrix()
[1 3 9]
[3 1 3]
[9 3 1]

```

```

sage: isocls = EllipticCurve('37b').isogeny_class('database', order="lmfdb");
↪isocls.curves
(Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 1873x - 31833$  over Rational
↪Field,
 Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 23x - 50$  over Rational
↪Field,
 Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 3x + 1$  over Rational Field)

```

This is an example of a curve with a 37-isogeny:

```

sage: E = EllipticCurve([1,1,1,-8,6])
sage: isocls = E.isogeny_class(); isocls
Isogeny class of Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 8*x +$ 
↪6 over Rational Field
sage: isocls.matrix()
[ 1 37]
[37  1]
sage: print("\n".join([repr(E) for E in isocls.curves]))
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 8*x + 6$  over Rational
↪Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 208083*x - 36621194$ 
↪over Rational Field

```

This curve had numerous 2-isogenies:

```

sage: e=EllipticCurve([1,0,0,-39,90])
sage: isocls = e.isogeny_class(); isocls.matrix()
[1 2 4 4 8 8]
[2 1 2 2 4 4]
[4 2 1 4 8 8]
[4 2 4 1 2 2]
[8 4 8 2 1 4]
[8 4 8 2 4 1]

```

See <http://math.harvard.edu/~elkies/nature.html> for more interesting examples of isogeny structures.

```

sage: E = EllipticCurve(j = -262537412640768000)
sage: isocls = E.isogeny_class(); isocls.matrix()
[ 1 163]
[163  1]
sage: print("\n".join([repr(C) for C in isocls.curves]))
Elliptic Curve defined by  $y^2 + y = x^3 - 2174420*x + 1234136692$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + y = x^3 - 57772164980*x - 5344733777551611$ 
↪over Rational Field

```

The degrees of isogenies are invariant under twists:

```
sage: E = EllipticCurve(j = -262537412640768000)
sage: E1 = E.quadratic_twist(6584935282)
sage: isocls = E1.isogeny_class(); isocls.matrix()
[ 1 163]
[163  1]
sage: E1.conductor()
18433092966712063653330496
```

```
sage: E = EllipticCurve('14a1')
sage: isocls = E.isogeny_class(); isocls.matrix()
[ 1  2  3  3  6  6]
[ 2  1  6  6  3  3]
[ 3  6  1  9  2 18]
[ 3  6  9  1 18  2]
[ 6  3  2 18  1  9]
[ 6  3 18  2  9  1]
sage: print("\n".join([repr(C) for C in isocls.curves]))
Elliptic Curve defined by y^2 + x*y + y = x^3 + 4*x - 6 over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 36*x - 70 over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - x over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 171*x - 874 over Rational_
↪Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 11*x + 12 over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 2731*x - 55146 over Rational_
↪Field
sage: isocls2 = isocls.reorder('lmfdb'); isocls2.matrix()
[ 1  2  3  9 18  6]
[ 2  1  6 18  9  3]
[ 3  6  1  3  6  2]
[ 9 18  3  1  2  6]
[18  9  6  2  1  3]
[ 6  3  2  6  3  1]
sage: print("\n".join([repr(C) for C in isocls2.curves]))
Elliptic Curve defined by y^2 + x*y + y = x^3 - 2731*x - 55146 over Rational_
↪Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 171*x - 874 over Rational_
↪Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 36*x - 70 over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - 11*x + 12 over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 - x over Rational Field
Elliptic Curve defined by y^2 + x*y + y = x^3 + 4*x - 6 over Rational Field
```

```
sage: E = EllipticCurve('11a1')
sage: isocls = E.isogeny_class(); isocls.matrix()
[ 1  5  5]
[ 5  1 25]
[ 5 25  1]
sage: f = isocls.isogenies()[0][1]; f.kernel_polynomial()
x^2 + x - 29/5
```

### **isogeny\_degree** (*other*)

Return the minimal degree of an isogeny between self and other.

INPUT:

- other – another elliptic curve.

OUTPUT:

(int) The minimal degree of an isogeny from self to other, or 0 if the curves are not isogenous.

EXAMPLES:

```
sage: E = EllipticCurve([-1056, 13552])
sage: E2 = EllipticCurve([-127776, -18037712])
sage: E.isogeny_degree(E2)
11
```

```
sage: E1 = EllipticCurve('14a1')
sage: E2 = EllipticCurve('14a2')
sage: E3 = EllipticCurve('14a3')
sage: E4 = EllipticCurve('14a4')
sage: E5 = EllipticCurve('14a5')
sage: E6 = EllipticCurve('14a6')
sage: E3.isogeny_degree(E1)
3
sage: E3.isogeny_degree(E2)
6
sage: E3.isogeny_degree(E3)
1
sage: E3.isogeny_degree(E4)
9
sage: E3.isogeny_degree(E5)
2
sage: E3.isogeny_degree(E6)
18
```

```
sage: E1 = EllipticCurve('30a1')
sage: E2 = EllipticCurve('30a2')
sage: E3 = EllipticCurve('30a3')
sage: E4 = EllipticCurve('30a4')
sage: E5 = EllipticCurve('30a5')
sage: E6 = EllipticCurve('30a6')
sage: E7 = EllipticCurve('30a7')
sage: E8 = EllipticCurve('30a8')
sage: E1.isogeny_degree(E1)
1
sage: E1.isogeny_degree(E2)
2
sage: E1.isogeny_degree(E3)
3
sage: E1.isogeny_degree(E4)
4
sage: E1.isogeny_degree(E5)
4
sage: E1.isogeny_degree(E6)
6
sage: E1.isogeny_degree(E7)
12
sage: E1.isogeny_degree(E8)
12
```

```
sage: E1 = EllipticCurve('15a1')
sage: E2 = EllipticCurve('15a2')
```

```

sage: E3 = EllipticCurve('15a3')
sage: E4 = EllipticCurve('15a4')
sage: E5 = EllipticCurve('15a5')
sage: E6 = EllipticCurve('15a6')
sage: E7 = EllipticCurve('15a7')
sage: E8 = EllipticCurve('15a8')
sage: E1.isogeny_degree(E1)
1
sage: E7.isogeny_degree(E2)
8
sage: E7.isogeny_degree(E3)
2
sage: E7.isogeny_degree(E4)
8
sage: E7.isogeny_degree(E5)
16
sage: E7.isogeny_degree(E6)
16
sage: E7.isogeny_degree(E8)
4

```

0 is returned when the curves are not isogenous:

```

sage: A = EllipticCurve('37a1')
sage: B = EllipticCurve('37b1')
sage: A.isogeny_degree(B)
0
sage: A.is_isogenous(B)
False

```

### **isogeny\_graph** (*order=None*)

Return a graph representing the isogeny class of this elliptic curve, where the vertices are isogenous curves over  $\mathbb{Q}$  and the edges are prime degree isogenies.

---

**Note:** The vertices are labeled 1 to n rather than 0 to n-1 to correspond to LMFDB and Cremona labels.

---

### EXAMPLES:

```

sage: LL = []
sage: for e in cremona_optimal_curves(range(1, 38)): # long time
....:     G = e.isogeny_graph()
....:     already = False
....:     for H in LL:
....:         if G.is_isomorphic(H):
....:             already = True
....:             break
....:     if not already:
....:         LL.append(G)
sage: graphs_list.show_graphs(LL) # long time

```

```

sage: E = EllipticCurve('195a')
sage: G = E.isogeny_graph()
sage: for v in G: print("{} {}".format(v, G.get_vertex(v)))
....
1 Elliptic Curve defined by y^2 + x*y = x^3 - 110*x + 435 over Rational Field
2 Elliptic Curve defined by y^2 + x*y = x^3 - 115*x + 392 over Rational Field

```

```

3 Elliptic Curve defined by  $y^2 + xy = x^3 + 210x + 2277$  over Rational_
↪Field
4 Elliptic Curve defined by  $y^2 + xy = x^3 - 520x - 4225$  over Rational_
↪Field
5 Elliptic Curve defined by  $y^2 + xy = x^3 + 605x - 19750$  over Rational_
↪Field
6 Elliptic Curve defined by  $y^2 + xy = x^3 - 8125x - 282568$  over Rational_
↪Field
7 Elliptic Curve defined by  $y^2 + xy = x^3 - 7930x - 296725$  over Rational_
↪Field
8 Elliptic Curve defined by  $y^2 + xy = x^3 - 130000x - 18051943$  over_
↪Rational Field
sage: G.plot(edge_labels=True)
Graphics object consisting of 23 graphics primitives

```

**kodaira\_symbol**( $p$ )

Local Kodaira type of the elliptic curve at  $p$ .

INPUT:

- $p$  – an integral prime

OUTPUT:

- the Kodaira type of this elliptic curve at  $p$ , as a KodairaSymbol.

EXAMPLES:

```

sage: E = EllipticCurve('124a')
sage: E.kodaira_type(2)
IV

```

**kodaira\_type**( $p$ )

Local Kodaira type of the elliptic curve at  $p$ .

INPUT:

- $p$  – an integral prime

OUTPUT:

- the Kodaira type of this elliptic curve at  $p$ , as a KodairaSymbol.

EXAMPLES:

```

sage: E = EllipticCurve('124a')
sage: E.kodaira_type(2)
IV

```

**kodaira\_type\_old**( $p$ )

Local Kodaira type of the elliptic curve at  $p$ .

INPUT:

- $p$ , an integral prime

OUTPUT:

- the Kodaira type of this elliptic curve at  $p$ , as a KodairaSymbol.

EXAMPLES:

```
sage: E = EllipticCurve('124a')
sage: E.kodaira_type_old(2)
IV
```

**kolyvagin\_point** ( $D, c=1, check=True$ )

Returns the Kolyvagin point on this curve associated to the quadratic imaginary field  $K = \mathbf{Q}(\sqrt{D})$  and conductor  $c$ .

INPUT:

- $D$  – a Heegner discriminant
- $c$  – (default: 1) conductor, must be coprime to  $DN$
- $check$  – bool (default: True)

OUTPUT:

The Kolyvagin point  $P$  of conductor  $c$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: P = E.kolyvagin_point(-67); P
Kolyvagin point of discriminant -67 on elliptic curve of conductor 37
sage: P.numerical_approx() # abs tol 1e-14
(6.000000000000000 : -15.000000000000000 : 1.000000000000000)
sage: P.index()
6
sage: g = E((0, -1, 1)) # a generator
sage: E.regulator() == E.regulator_of_points([g])
True
sage: 6*g
(6 : -15 : 1)
```

**label** ( $space=False$ )

Return the Cremona label associated to (the minimal model) of this curve, if it is known. If not, raise a `LookupError` exception.

EXAMPLES:

```
sage: E = EllipticCurve('389a1')
sage: E.cremona_label()
'389a1'
```

The default database only contains conductors up to 10000, so any curve with conductor greater than that will cause an error to be raised. The optional package `database_cremona_ellcurve` contains many more curves.

```
sage: E = EllipticCurve([1, -1, 0, -79, 289])
sage: E.conductor()
234446
sage: E.cremona_label() # optional - database_cremona_ellcurve
'234446a1'
sage: E = EllipticCurve((0, 0, 1, -79, 342))
sage: E.conductor()
19047851
sage: E.cremona_label()
Traceback (most recent call last):
```



```
...
LookupError: Cremona database does not contain entry for Elliptic Curve
↳ defined by  $y^2 + y = x^3 - 79x + 342$  over Rational Field
```

**lmfdb\_page()**

Open the LMFDB web page of the elliptic curve in a browser.

See <http://www.lmfdb.org>

EXAMPLES:

```
sage: E = EllipticCurve('5077a1')
sage: E.lmfdb_page() # optional -- webbrowser
```

**local\_integral\_model(p)**

Return a model of self which is integral at the prime  $p$ .

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1/216, -7/1296, 1/7776])
sage: E.local_integral_model(2)
Elliptic Curve defined by  $y^2 + 1/27*y = x^3 - 7/81*x + 2/243$  over Rational
↳ Field
sage: E.local_integral_model(3)
Elliptic Curve defined by  $y^2 + 1/8*y = x^3 - 7/16*x + 3/32$  over Rational
↳ Field
sage: E.local_integral_model(2).local_integral_model(3) == EllipticCurve(
↳ '5077a1')
True
```

**lseries()**

Return the L-series of this elliptic curve.

Further documentation is available for the functions which apply to the L-series.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.lseries()
Complex L-series of the Elliptic Curve defined by  $y^2 + y = x^3 - x$  over
↳ Rational Field
```

**lseries\_gross\_zagier(A)**

Return the Gross-Zagier L-series attached to self and an ideal class  $A$ .

INPUT:

- $A$  – an ideal class in an imaginary quadratic number field  $K$

This L-series  $L(E, A, s)$  is defined as the product of a shifted L-function of the quadratic character associated to  $K$  and the Dirichlet series whose  $n$ -th coefficient is the product of the  $n$ -th factor of the L-series of  $E$  and the number of integral ideal in  $A$  of norm  $n$ . For any character  $\chi$  on the class group of  $K$ , one gets  $L_K(E, \chi, s) = \sum_A \chi(A) L(E, A, s)$  where  $A$  runs through the class group of  $K$ .

For the exact definition see section IV of [GrossZagier].

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: K.<a> = QuadraticField(-40)
sage: A = K.class_group().gen(0); A
```

```

Fractional ideal class (2, 1/2*a)
sage: L = E.lseries_gross_zagier(A) ; L
Gross Zagier L-series attached to Elliptic Curve defined by y^2 + y = x^3 - x
↳over Rational Field with ideal class Fractional ideal class (2, 1/2*a)
sage: L(1)
0.0000000000000000
sage: L.taylor_series(1, 5)
0.0000000000000000 - 5.51899839494458*z + 13.6297841350649*z^2 - 16.
↳2292417817675*z^3 + 7.94788823722712*z^4 + O(z^5)

```

These should be equal:

```

sage: L(2) + E.lseries_gross_zagier(A^2)(2)
0.502803417587467
sage: E.lseries()(2) * E.quadratic_twist(-40).lseries()(2)
0.502803417587467

```

## REFERENCES:

### **manin\_constant()**

Return the Manin constant of this elliptic curve.

If  $\phi : X_0(N) \rightarrow E$  is the modular parametrization of minimal degree, then the Manin constant  $c$  is defined to be the rational number  $c$  such that  $\phi^*(\omega_E) = c \cdot \omega_f$  where  $\omega_E$  is a Néron differential and  $\omega_f = f(q) dq/q$  is the differential on  $X_0(N)$  corresponding to the newform  $f$  attached to the isogeny class of  $E$ .

It is known that the Manin constant is an integer. It is conjectured that in each class there is at least one, more precisely the so-called strong Weil curve or  $X_0(N)$ -optimal curve, that has Manin constant 1.

### OUTPUT:

an integer

This function only works if the curve is in the installed Cremona database. Sage includes by default a small database; for the full database you have to install an optional package.

### EXAMPLES:

```

sage: EllipticCurve('11a1').manin_constant()
1
sage: EllipticCurve('11a2').manin_constant()
1
sage: EllipticCurve('11a3').manin_constant()
5

```

Check that it works even if the curve is non-minimal:

```

sage: EllipticCurve('11a3').change_weierstrass_model([1/35,0,0,0]).manin_
↳constant()
5

```

Rather complicated examples (see [trac ticket #12080](#))

```

sage: [ EllipticCurve('27a%s'%i).manin_constant() for i in [1,2,3,4]]
[1, 1, 3, 3]
sage: [ EllipticCurve('80b%s'%i).manin_constant() for i in [1,2,3,4]]
[1, 2, 1, 2]

```

### **matrix\_of\_frobenius**( $p$ , $prec=20$ , $check=False$ , $check_hypotheses=True$ , $algorithm='auto'$ )

Returns the matrix of Frobenius on the Monsky Washnitzer cohomology of the elliptic curve.

INPUT:

- $p$  - prime ( $\geq 3$ ) for which  $E$  is good and ordinary
- $\text{prec}$  - (relative)  $p$ -adic precision for result (default 20)
- $\text{check}$  - boolean (default: False), whether to perform a consistency check. This will slow down the computation by a constant factor 2. (The consistency check is to verify that its trace is correct to the specified precision. Otherwise, the trace is used to compute one column from the other one (possibly after a change of basis).)
- $\text{check\_hypotheses}$  - boolean, whether to check that this is a curve for which the  $p$ -adic sigma function makes sense
- $\text{algorithm}$  - one of “standard”, “sqrtp”, or “auto”. This selects which version of Kedlaya’s algorithm is used. The “standard” one is the one described in Kedlaya’s paper. The “sqrtp” one has better performance for large  $p$ , but only works when  $p > 6N$  ( $N = \text{prec}$ ). The “auto” option selects “sqrtp” whenever possible.

Note that if the “sqrtp” algorithm is used, a consistency check will automatically be applied, regardless of the setting of the “check” flag.

OUTPUT: a matrix of  $p$ -adic number to precision  $\text{prec}$

See also the documentation of `padic_E2`.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.matrix_of_frobenius(7)
[
      2*7 + 4*7^2 + 5*7^4 + 6*7^5 + 6*7^6 + 7^8 + 4*7^9 + 3*7^10 +
↪ 2*7^11 + 5*7^12 + 4*7^14 + 7^16 + 2*7^17 + 3*7^18 + 4*7^19 + 3*7^20 + O(7^
↪ 21)
↪ 2 + 3*7 + 6*7^2 + 7^3 + 3*7^4 + 5*7^5
↪ + 3*7^7 + 7^8 + 3*7^9 + 6*7^13 + 7^14 + 7^16 + 5*7^17 + 4*7^18 + 7^19 + O(7^
↪ 20) ]
[
      2*7 + 3*7^2 + 7^3 + 3*7^4 + 6*7^5 + 2*7^6 + 3*7^7 + 5*7^8 + 3*7^9 + 2*7^
↪ 11 + 6*7^12 + 5*7^13 + 4*7^16 + 4*7^17 + 6*7^18 + 6*7^19 + 4*7^20 + O(7^21)
↪ 6 + 4*7 + 2*7^2 + 6*7^3 + 7^4 + 6*7^7 + 5*7^8 + 2*7^9 + 3*7^10 + 4*7^11 + 7^
↪ 12 + 6*7^13 + 2*7^14 + 6*7^15 + 5*7^16 + 4*7^17 + 3*7^18 + 2*7^19 + O(7^20) ]
sage: M = E.matrix_of_frobenius(11,prec=3); M
[
      9*11 + 9*11^3 + O(11^4)      10 + 11 + O(11^3) ]
[
      2*11 + 11^2 + O(11^4)  6 + 11 + 10*11^2 + O(11^3) ]
sage: M.det()
11 + O(11^4)
sage: M.trace()
6 + 10*11 + 10*11^2 + O(11^3)
sage: E.ap(11)
-5
sage: E = EllipticCurve('83a1')
sage: E.matrix_of_frobenius(3,6)
[
      2*3 + 3^5 + O(3^6)      2*3 + 2*3^2 + 2*3^3 +
↪ O(3^6) ]
[
      2*3 + 3^2 + 2*3^5 + O(3^6)  2 + 2*3^2 + 2*3^3 + 2*3^4 + 3^5 +
↪ O(3^6) ]
```

**`minimal_model()`**

Return the unique minimal Weierstrass equation for this elliptic curve.

This is the model with minimal discriminant and  $a_1, a_2, a_3 \in \{0, \pm 1\}$ .

EXAMPLES:

```
sage: E = EllipticCurve([10, 100, 1000, 10000, 1000000])
sage: E.minimal_model()
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 + x + 1$  over Rational
↪Field
```

**minimal\_quadratic\_twist()**

Determine a quadratic twist with minimal conductor. Return a global minimal model of the twist and the fundamental discriminant of the quadratic field over which they are isomorphic.

**Note:** If there is more than one curve with minimal conductor, the one returned is the one with smallest label (if in the database), or the one with minimal  $a$ -invariant list (otherwise).

**Note:** For curves with  $j$ -invariant 0 or 1728 the curve returned is the minimal quadratic twist, not necessarily the minimal twist (which would have conductor 27 or 32 respectively).

**EXAMPLES:**

```
sage: E = EllipticCurve('121d1')
sage: E.minimal_quadratic_twist()
(Elliptic Curve defined by  $y^2 + y = x^3 - x^2$  over Rational Field, -11)
sage: Et, D = EllipticCurve('32a1').minimal_quadratic_twist()
sage: D
1

sage: E = EllipticCurve('11a1')
sage: Et, D = E.quadratic_twist(-24).minimal_quadratic_twist()
sage: E == Et
True
sage: D
-24

sage: E = EllipticCurve([0, 0, 0, 0, 1000])
sage: E.minimal_quadratic_twist()
(Elliptic Curve defined by  $y^2 = x^3 + 1$  over Rational Field, 40)
sage: E = EllipticCurve([0, 0, 0, 1600, 0])
sage: E.minimal_quadratic_twist()
(Elliptic Curve defined by  $y^2 = x^3 + 4*x$  over Rational Field, 5)
```

If the curve has square-free conductor then it is already minimal (see [trac ticket #14060](#)):

```
sage: E = next(cremona_optimal_curves([2*3*5*7*11]))
sage: (E, 1) == E.minimal_quadratic_twist()
True
```

An example where the minimal quadratic twist is not the minimal twist (which has conductor 27):

```
sage: E = EllipticCurve([0, 0, 0, 0, 7])
sage: E.j_invariant()
0
sage: E.minimal_quadratic_twist()[0].conductor()
5292
```

**mod5family()**

Return the family of all elliptic curves with the same mod-5 representation as self.

EXAMPLES:

```
sage: E = EllipticCurve('32a1')
sage: E.mod5family()
Elliptic Curve defined by  $y^2 = x^3 + 4x$  over Fraction Field of Univariate
↪Polynomial Ring in t over Rational Field
```

**modular\_degree** (*algorithm*='sympow', *M*=1)

Return the modular degree at level  $MN$  of this elliptic curve. The case  $M == 1$  corresponds to the classical definition of modular degree.

When  $M > 1$ , the function returns the degree of the map from  $X_0(MN) \rightarrow A$ , where  $A$  is the abelian variety generated by embeddings of  $E$  into  $J_0(MN)$ .

The result is cached. Subsequent calls, even with a different algorithm, just returned the cached result. The algorithm argument is ignored when  $M > 1$ .

INPUT:

- *algorithm* - string:
- 'sympow' - (default) use Mark Watkin's (newer) C program sympow
- 'magma' - requires that MAGMA be installed (also implemented by Mark Watkins)
- **M** - Non-negative integer; the modular degree at level  $MN$  is returned (see above)

---

**Note:** On 64-bit computers *ec* does not work, so Sage uses *sympow* even if *ec* is selected on a 64-bit computer.

---

The correctness of this function when called with algorithm “sympow” is subject to the following three hypothesis:

- Manin's conjecture: the Manin constant is 1
- Steven's conjecture: the  $X_1(N)$ -optimal quotient is the curve with minimal Faltings height. (This is proved in most cases.)
- The modular degree fits in a machine double, so it better be less than about 50-some bits. (If you use *sympow* this constraint does not apply.)

Moreover for all algorithms, computing a certain value of an  $L$ -function ‘uses a heuristic method that discerns when the real-number approximation to the modular degree is within epsilon [=0.01 for *algorithm*='sympow'] of the same integer for 3 consecutive trials (which occur maybe every 25000 coefficients or so). Probably it could just round at some point. For rigour, you would need to bound the tail by assuming (essentially) that all the  $a_n$  are as large as possible, but in practice they exhibit significant (square root) cancellation. One difficulty is that it doesn't do the sum in 1-2-3-4 order; it uses 1-2-4-8-3-6-12-24-9-18- (Euler product style) instead, and so you have to guess ahead of time at what point to curtail this expansion.’ (Quote from an email of Mark Watkins.)

---

**Note:** If the curve is loaded from the large Cremona database, then the modular degree is taken from the database.

---

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20])
sage: E
Elliptic Curve defined by  $y^2 + y = x^3 - x^2 - 10x - 20$  over Rational Field
```

```

sage: E.modular_degree()
1
sage: E = EllipticCurve('5077a')
sage: E.modular_degree()
1984
sage: factor(1984)
2^6 * 31

```

```

sage: EllipticCurve([0, 0, 1, -7, 6]).modular_degree()
1984
sage: EllipticCurve([0, 0, 1, -7, 6]).modular_degree(algorithm='sympow')
1984
sage: EllipticCurve([0, 0, 1, -7, 6]).modular_degree(algorithm='magma') #
↳ optional - magma
1984

```

We compute the modular degree of the curve with rank 4 having smallest (known) conductor:

```

sage: E = EllipticCurve([1, -1, 0, -79, 289])
sage: factor(E.conductor()) # conductor is 234446
2 * 117223
sage: factor(E.modular_degree())
2^7 * 2617

```

Higher level cases:

```

sage: E = EllipticCurve('11a')
sage: for M in range(1,11): print(E.modular_degree(M=M)) # long time (20s on
↳ 2009 MBP)
1
1
3
2
7
45
12
16
54
245

```

### `modular_form()`

Return the cuspidal modular form associated to this elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: f = E.modular_form()
sage: f
q - 2*q^2 - 3*q^3 + 2*q^4 - 2*q^5 + O(q^6)

```

If you need to see more terms in the  $q$ -expansion:

```

sage: f.q_expansion(20)
q - 2*q^2 - 3*q^3 + 2*q^4 - 2*q^5 + 6*q^6 - q^7 + 6*q^9 + 4*q^10 - 5*q^11 -
↳ 6*q^12 - 2*q^13 + 2*q^14 + 6*q^15 - 4*q^16 - 12*q^18 + O(q^20)

```

---

**Note:** If you just want the  $q$ -expansion, use `q_expansion()`.

---

### `modular_parametrization()`

Return the modular parametrization of this elliptic curve, which is a map from  $X_0(N)$  to self, where  $N$  is the conductor of self.

EXAMPLES:

```
sage: E = EllipticCurve('15a')
sage: phi = E.modular_parametrization(); phi
Modular parameterization from the upper half plane to Elliptic Curve defined
↳ by  $y^2 + x*y + y = x^3 + x^2 - 10*x - 10$  over Rational Field
sage: z = 0.1 + 0.2j
sage: phi(z)
(8.20822465478531 - 13.1562816054682*I : -8.79855099049364 + 69.
↳ 4006129342200*I : 1.000000000000000)
```

This map is actually a map on  $X_0(N)$ , so equivalent representatives in the upper half plane map to the same point:

```
sage: phi((-7*z-1)/(15*z+2))
(8.20822465478524 - 13.1562816054681*I : -8.79855099049... + 69.4006129342...
↳ *I : 1.000000000000000)
```

We can also get a series expansion of this modular parameterization:

```
sage: E = EllipticCurve('389a1')
sage: X,Y=E.modular_parametrization().power_series()
sage: X
 $q^{-2} + 2*q^{-1} + 4 + 7*q + 13*q^2 + 18*q^3 + 31*q^4 + 49*q^5 + 74*q^6 + 111*q^7$ 
↳  $+ 173*q^8 + 251*q^9 + 379*q^{10} + 560*q^{11} + 824*q^{12} + 1199*q^{13} + 1773*q^{14}$ 
↳  $+ 2548*q^{15} + 3722*q^{16} + 5374*q^{17} + O(q^{18})$ 
sage: Y
 $-q^{-3} - 3*q^{-2} - 8*q^{-1} - 17 - 33*q - 61*q^2 - 110*q^3 - 186*q^4 - 320*q^5 -$ 
↳  $528*q^6 - 861*q^7 - 1383*q^8 - 2218*q^9 - 3472*q^{10} - 5451*q^{11} - 8447*q^{12}$ 
↳  $- 13020*q^{13} - 19923*q^{14} - 30403*q^{15} - 46003*q^{16} + O(q^{17})$ 
```

The following should give 0, but only approximately:

```
sage: q = X.parent().gen()
sage: E.defining_polynomial()(X,Y,1) + O(q^11) == 0
True
```

### `modular_symbol(sign=1, use_eclib=None, normalize=None, implementation='eclib')`

Return the modular symbol associated to this elliptic curve, with given sign.

INPUT:

- `sign` - +1 (default) or -1.
- `use_eclib` - Deprecated. Use the `implementation` parameter instead.
- `normalize` - (default: None); either 'L\_ratio', 'period', or 'none' when `implementation` is 'sage'; ignored if `implementation` is `eclib`. For 'L\_ratio', the modular symbol tries to normalize correctly as explained below by comparing it to `L_ratio` for the curve and some small twists. The normalization 'period' uses the `integral_period_map` for modular symbols which is known to be equal to the desired normalization, up to the sign and a possible power of 2. With normalization 'none', the modular symbol is almost certainly not correctly normalized, i.e. all values

will be a fixed scalar multiple of what they should be. However, the initial computation of the modular symbol is much faster when implementation `sage` is chosen, though evaluation of it after computing it is no faster.

- `implementation` - either 'eclib' (default) or 'sage'. Here 'eclib' uses John Cremona's implementation in the eclib library, while 'sage' uses an implementation in Sage which is often quite a bit slower.

**See also:**

`modular_symbol_numerical()`

**Note:** The value at a rational number  $r$  is proportional to the real or imaginary part of the integral of  $2\pi i f(z)dz$  from  $\infty$  to  $r$ , where  $f$  is the newform attached to  $E$ , suitably normalized so that all values of this map take values in  $\mathbf{Q}$ .

The normalization is such that for sign +1, the value at the cusp  $r$  is equal to the quotient of the real part of  $\int_{\infty}^r 2\pi i f(z)dz$  by the least positive period of  $E$ , where  $f$  is the newform attached to the isogeny class of  $E$ . This is in contrast to the method `L_ratio` of `lseries()`, where the value is also divided by the number of connected components of  $E(\mathbf{R})$ . In particular the modular symbol depends on  $E$  and not only the isogeny class of  $E$ . For negative modular symbols, the value is the quotient of the imaginary part of the above integral by the imaginary part of the smallest positive imaginary period.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: M = E.modular_symbol(); M
Modular symbol with sign 1 over Rational Field attached to Elliptic Curve
↪ defined by y^2 + y = x^3 - x over Rational Field
sage: M(1/2)
0
sage: M(1/5)
1
```

```
sage: E = EllipticCurve('121b1')
sage: M = E.modular_symbol(implementation="sage")
Warning : Could not normalize the modular symbols, maybe all further results
↪ will be multiplied by -1 and a power of 2
sage: M(1/7)
-1/2
```

Different curves in an isogeny class have modular symbols which differ by a nonzero rational factor:

```
sage: E1 = EllipticCurve('11a1')
sage: M1 = E1.modular_symbol()
sage: M1(0)
1/5
sage: E2 = EllipticCurve('11a2')
sage: M2 = E2.modular_symbol()
sage: M2(0)
1
sage: E3 = EllipticCurve('11a3')
sage: M3 = E3.modular_symbol()
sage: M3(0)
1/25
sage: all(5*M1(r)==M2(r)==25*M3(r) for r in QQ.range_by_height(10))
True
```



With the default implementation using `eclib`, the symbols are correctly normalized automatically. With the Sage implementation we can choose to normalize using the L-ratio, unless that is 0 (for curves of positive rank) or using periods. Here is an example where the symbol is already normalized:

```
sage: E = EllipticCurve('11a2')
sage: E.modular_symbol(implementation = 'eclib')(0)
1
sage: E.modular_symbol(implementation = 'sage', normalize='L_ratio')(0)
1
sage: E.modular_symbol(implementation = 'sage', normalize='none')(0)
1
sage: E.modular_symbol(implementation = 'sage', normalize='period')(0)
1
```

Here is an example where both normalization methods work, while the non-normalized symbol is incorrect:

```
sage: E = EllipticCurve('11a3')
sage: E.modular_symbol(implementation = 'eclib')(0)
1/25
sage: E.modular_symbol(implementation = 'sage', normalize='none')(0)
1
sage: E.modular_symbol(implementation = 'sage', normalize='L_ratio')(0)
1/25
sage: E.modular_symbol(implementation = 'sage', normalize='period')(0)
1/25
```

Since [trac ticket #10256](#), the interface for negative modular symbols in `eclib` is available:

```
sage: E = EllipticCurve('11a1')
sage: Mplus = E.modular_symbol(+1); Mplus
Modular symbol with sign 1 over Rational Field attached to Elliptic Curve
↳ defined by  $y^2 + y = x^3 - x^2 - 10x - 20$  over Rational Field
sage: [Mplus(1/i) for i in [1..11]]
[1/5, -4/5, -3/10, 7/10, 6/5, 6/5, 7/10, -3/10, -4/5, 1/5, 0]
sage: Mminus = E.modular_symbol(-1); Mminus
Modular symbol with sign -1 over Rational Field attached to Elliptic Curve
↳ defined by  $y^2 + y = x^3 - x^2 - 10x - 20$  over Rational Field
sage: [Mminus(1/i) for i in [1..11]]
[0, 0, 1/2, 1/2, 0, 0, -1/2, -1/2, 0, 0, 0]
```

**`modular_symbol_numerical`** (*sign=1, prec=53*)

Return the modular symbol as a numerical function.

**Note:** This method does not compute spaces of modular symbols, so it is suitable for curves of larger conductor than can be handled by `modular_symbol()`.

EXAMPLES:

```
sage: E = EllipticCurve('19a1')
sage: f = E.modular_symbol_numerical(1)
sage: g = E.modular_symbol()
sage: f(0), g(0) # abs tol 1e-14
(0.333333333333330, 1/3)
sage: f(oo), g(oo)
(-0.000000000000000, 0)
```

```

sage: E = EllipticCurve('79a1')
sage: f = E.modular_symbol_numerical(-1)
sage: g = E.modular_symbol(-1, implementation="sage")
sage: f(1/3), g(1/3) # abs tol 1e-13
(1.0000000000000001, 1)
sage: f(oo), g(oo)
(0.0000000000000000, 0)

```

**modular\_symbol\_space** (*sign=1, base\_ring=Rational Field, bound=None*)

Return the space of cuspidal modular symbols associated to this elliptic curve, with given sign and base ring.

INPUT:

- sign - 0, -1, or 1
- base\_ring - a ring

EXAMPLES:

```

sage: f = EllipticCurve('37b')
sage: f.modular_symbol_space()
Modular Symbols subspace of dimension 1 of Modular Symbols space of dimension
↪3 for Gamma_0(37) of weight 2 with sign 1 over Rational Field
sage: f.modular_symbol_space(-1)
Modular Symbols subspace of dimension 1 of Modular Symbols space of dimension
↪2 for Gamma_0(37) of weight 2 with sign -1 over Rational Field
sage: f.modular_symbol_space(0, bound=3)
Modular Symbols subspace of dimension 2 of Modular Symbols space of dimension
↪5 for Gamma_0(37) of weight 2 with sign 0 over Rational Field

```

---

**Note:** If you just want the  $q$ -expansion, use `q_expansion()`.

---

**mwrnk** (*options=""*)

Run Cremona's mwrnk program on this elliptic curve and return the result as a string.

INPUT:

- options (string) – run-time options passed when starting mwrnk. The format is as follows (see below for examples of usage):
  - `-v n` (verbosity level) sets verbosity to  $n$  (default=1)
  - `-o` (PARI/GP style output flag) turns ON extra PARI/GP short output (default is OFF)
  - `-p n` (precision) sets precision to  $n$  decimals (default=15)
  - `-b n` (quartic bound) bound on quartic point search (default=10)
  - `-x n` ( $n_{\text{aux}}$ ) number of aux primes used for sieving (default=6)
  - `-l` (generator list flag) turns ON listing of points (default ON unless  $v=0$ )
  - `-s` (selmer\_only flag) if set, computes Selmer rank only (default: not set)
  - `-d` (skip\_2nd\_descent flag) if set, skips the second descent for curves with 2-torsion (default: not set)
  - `-S n` ( $\text{sat\_bd}$ ) upper bound on saturation primes (default=100, -1 for automatic)

OUTPUT:

- string - output of mwrank on this curve

**Note:** The output is a raw string and completely illegible using automatic display, so it is recommended to use print for legible output.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.mwrank() #random
...
sage: print(E.mwrank())
Curve [0,0,1,-1,0] :      Basic pair: I=48, J=-432
disc=255744
...
Generator 1 is [0:-1:1]; height 0.05111...
Regulator = 0.05111...

The rank and full Mordell-Weil basis have been determined unconditionally.
...
```

Options to mwrank can be passed:

```
sage: E = EllipticCurve([0,0,0,877,0])
```

Run mwrank with 'verbose' flag set to 0 but list generators if found

```
sage: print(E.mwrank('-v0 -l'))
Curve [0,0,0,877,0] :    0 <= rank <= 1
Regulator = 1
```

Run mwrank again, this time with a higher bound for point searching on homogeneous spaces:

```
sage: print(E.mwrank('-v0 -l -b11'))
Curve [0,0,0,877,0] :    Rank = 1
Generator 1 is
↪ [29604565304828237474403861024284371796799791624792913256602210:-
↪ 256256267988926809388776834045513089648669153204356603464786949:49007802321978758895980293
↪ height 95.980371987964
Regulator = 95.980371987964
```

**mwrank\_curve** (*verbose=False*)

Construct an mwrank\_EllipticCurve from this elliptic curve

The resulting mwrank\_EllipticCurve has available methods from John Cremona's eclib library.

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: EE = E.mwrank_curve()
sage: EE
y^2+ y = x^3 - x^2 - 10*x - 20
sage: type(EE)
<class 'sage.libs.eclib.interface.mwrank_EllipticCurve'>
sage: EE.isogeny_class()
([[0, -1, 1, -10, -20], [0, -1, 1, -7820, -263580], [0, -1, 1, 0, 0]],
 [[0, 5, 5], [5, 0, 0], [5, 0, 0]])
```

**newform()**Same as `self.modular_form()`.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.newform()
q - 2*q^2 - 3*q^3 + 2*q^4 - 2*q^5 + O(q^6)
sage: E.newform() == E.modular_form()
True
```

**ngens** (*proof=None*)

Return the number of generators of this elliptic curve.

---

**Note:** See `gens()` for further documentation. The function `ngens()` calls `gens()` if not already done, but only with default parameters. Better results may be obtained by calling `mwrnk()` with carefully chosen parameters.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.ngens()
1

sage: E = EllipticCurve([0,0,0,877,0])
sage: E.ngens()
1

sage: print(E.mwrnk('-v0 -b12 -1'))
Curve [0,0,0,877,0] : Rank = 1
Generator 1 is
↳ [29604565304828237474403861024284371796799791624792913256602210:-
↳ 256256267988926809388776834045513089648669153204356603464786949:49007802321978758895980293
↳ height 95.980371987964
Regulator = 95.980...
```

**optimal\_curve()**

Given an elliptic curve that is in the installed Cremona database, return the optimal curve isogenous to it.

EXAMPLES:

The following curve is not optimal:

```
sage: E = EllipticCurve('11a2'); E
Elliptic Curve defined by y^2 + y = x^3 - x^2 - 7820*x - 263580 over Rational
↳Field
sage: E.optimal_curve()
Elliptic Curve defined by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: E.optimal_curve().cremona_label()
'11a1'
```

Note that 990h is the special case where the optimal curve isn't the first in the Cremona labeling:

```
sage: E = EllipticCurve('990h4'); E
Elliptic Curve defined by y^2 + x*y + y = x^3 - x^2 + 6112*x - 41533 over
↳Rational Field
sage: F = E.optimal_curve(); F
Elliptic Curve defined by y^2 + x*y + y = x^3 - x^2 - 1568*x - 4669 over
↳Rational Field
```

```
sage: F.cremona_label()
'990h3'
sage: EllipticCurve('990a1').optimal_curve().cremona_label()    # a isn't h.
'990a1'
```

If the input curve is optimal, this function returns that curve (not just a copy of it or a curve isomorphic to it!):

```
sage: E = EllipticCurve('37a1')
sage: E.optimal_curve() is E
True
```

Also, if this curve is optimal but not given by a minimal model, this curve will still be returned, so this function need not return a minimal model in general.

```
sage: F = E.short_weierstrass_model(); F
Elliptic Curve defined by y^2 = x^3 - 16*x + 16 over Rational Field
sage: F.optimal_curve()
Elliptic Curve defined by y^2 = x^3 - 16*x + 16 over Rational Field
```

### **ordinary\_primes(B)**

Return a list of all ordinary primes for this elliptic curve up to and possibly including B.

EXAMPLES:

```
sage: e = EllipticCurve('11a')
sage: e.aplist(20)
[-2, -1, 1, -2, 1, 4, -2, 0]
sage: e.ordinary_primes(97)
[3, 5, 7, 11, 13, 17, 23, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97]
sage: e = EllipticCurve('49a')
sage: e.aplist(20)
[1, 0, 0, 0, 4, 0, 0, 0]
sage: e.supersingular_primes(97)
[3, 5, 13, 17, 19, 31, 41, 47, 59, 61, 73, 83, 89, 97]
sage: e.ordinary_primes(97)
[2, 11, 23, 29, 37, 43, 53, 67, 71, 79]
sage: e.ordinary_primes(3)
[2]
sage: e.ordinary_primes(2)
[2]
sage: e.ordinary_primes(1)
[]
```

### **padic\_E2(p, prec=20, check=False, check\_hypotheses=True, algorithm='auto')**

Returns the value of the  $p$ -adic modular form  $E2$  for  $(E, \omega)$  where  $\omega$  is the usual invariant differential  $dx/(2y + a_1x + a_3)$ .

INPUT:

- $p$  - prime (= 5) for which  $E$  is good and ordinary
- $prec$  - (relative)  $p$ -adic precision (= 1) for result
- $check$  - boolean, whether to perform a consistency check. This will slow down the computation by a constant factor 2. (The consistency check is to compute the whole matrix of frobenius on Monsky-Washnitzer cohomology, and verify that its trace is correct to the specified precision. Otherwise, the trace is used to compute one column from the other one (possibly after a change of basis).)

- `check_hypotheses` - boolean, whether to check that this is a curve for which the p-adic sigma function makes sense
- `algorithm` - one of “standard”, “sqrtp”, or “auto”. This selects which version of Kedlaya’s algorithm is used. The “standard” one is the one described in Kedlaya’s paper. The “sqrtp” one has better performance for large  $p$ , but only works when  $p > 6N$  ( $N = \text{prec}$ ). The “auto” option selects “sqrtp” whenever possible.

Note that if the “sqrtp” algorithm is used, a consistency check will automatically be applied, regardless of the setting of the “check” flag.

OUTPUT: p-adic number to precision `prec`

---

**Note:** If the discriminant of the curve has nonzero valuation at  $p$ , then the result will not be returned mod  $p^{\text{prec}}$ , but it still *will* have `prec digits` of precision.

---



---

**Todo:** Once we have a better implementation of the “standard” algorithm, the algorithm selection strategy for “auto” needs to be revisited.

---

AUTHORS:

- David Harvey (2006-09-01): partly based on code written by Robert Bradshaw at the MSRI 2006 modular forms workshop

ACKNOWLEDGMENT: - discussion with Eyal Goren that led to the trace trick.

EXAMPLES: Here is the example discussed in the paper “Computation of p-adic Heights and Log Convergence” (Mazur, Stein, Tate):

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^
↪12 + 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + O(5^20)
```

Let’s try to higher precision (this is the same answer the MAGMA implementation gives):

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 100)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^
↪12 + 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + 4*5^20 + 5^21 + ↪
↪4*5^22 + 2*5^23 + 3*5^24 + 3*5^26 + 2*5^27 + 3*5^28 + 2*5^30 + 5^31 + 4*5^
↪33 + 3*5^34 + 4*5^35 + 5^36 + 4*5^37 + 4*5^38 + 3*5^39 + 4*5^41 + 2*5^42 + ↪
↪3*5^43 + 2*5^44 + 2*5^48 + 3*5^49 + 4*5^50 + 2*5^51 + 5^52 + 4*5^53 + 4*5^
↪54 + 3*5^55 + 2*5^56 + 3*5^57 + 4*5^58 + 4*5^59 + 5^60 + 3*5^61 + 5^62 + ↪
↪4*5^63 + 5^65 + 3*5^66 + 2*5^67 + 5^69 + 2*5^70 + 3*5^71 + 3*5^72 + 5^74 + ↪
↪5^75 + 5^76 + 3*5^77 + 4*5^78 + 4*5^79 + 2*5^80 + 3*5^81 + 5^82 + 5^83 + ↪
↪4*5^84 + 3*5^85 + 2*5^86 + 3*5^87 + 5^88 + 2*5^89 + 4*5^90 + 4*5^92 + 3*5^
↪93 + 4*5^94 + 3*5^95 + 2*5^96 + 4*5^97 + 4*5^98 + 2*5^99 + O(5^100)
```

Check it works at low precision too:

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 1)
2 + O(5)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 2)
2 + 4*5 + O(5^2)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 3)
2 + 4*5 + O(5^3)
```

TODO: With the old(-er), i.e., = sage-2.4 p-adics we got  $5 + O(5^2)$  as output, i.e., relative precision 1, but with the newer p-adics we get relative precision 0 and absolute precision 1.

```
sage: EllipticCurve([1, 1, 1, 1, 1]).padic_E2(5, 1)
O(5)
```

Check it works for different models of the same curve (37a), even when the discriminant changes by a power of p (note that E2 depends on the differential too, which is why it gets scaled in some of the examples below):

```
sage: X1 = EllipticCurve([-1, 1/4])
sage: X1.j_invariant(), X1.discriminant()
(110592/37, 37)
sage: X1.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X2 = EllipticCurve([0, 0, 1, -1, 0])
sage: X2.j_invariant(), X2.discriminant()
(110592/37, 37)
sage: X2.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X3 = EllipticCurve([-1*(2**4), 1/4*(2**6)])
sage: X3.j_invariant(), X3.discriminant() / 2**12
(110592/37, 37)
sage: 2**(-2) * X3.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X4 = EllipticCurve([-1*(7**4), 1/4*(7**6)])
sage: X4.j_invariant(), X4.discriminant() / 7**12
(110592/37, 37)
sage: 7**(-2) * X4.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X5 = EllipticCurve([-1*(5**4), 1/4*(5**6)])
sage: X5.j_invariant(), X5.discriminant() / 5**12
(110592/37, 37)
sage: 5**(-2) * X5.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X6 = EllipticCurve([-1/(5**4), 1/4/(5**6)])
sage: X6.j_invariant(), X6.discriminant() * 5**12
(110592/37, 37)
sage: 5**2 * X6.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

Test check=True vs check=False:

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 1, check=False)
2 + O(5)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 1, check=True)
2 + O(5)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 30, check=False)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^
↪ 12 + 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + 4*5^20 + 5^21 +
↪ 4*5^22 + 2*5^23 + 3*5^24 + 3*5^26 + 2*5^27 + 3*5^28 + O(5^30)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 30, check=True)
```

```

2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^
↪12 + 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + 4*5^20 + 5^21 +
↪4*5^22 + 2*5^23 + 3*5^24 + 3*5^26 + 2*5^27 + 3*5^28 + O(5^30)

```

Here's one using the  $p^{1/2}$  algorithm:

```

sage: EllipticCurve([-1, 1/4]).padic_E2(3001, 3, algorithm="sqrtp")
1907 + 2819*3001 + 1124*3001^2 + O(3001^3)

```

**padic\_height** (*p*, *prec*=20, *sigma*=None, *check\_hypotheses*=True)

Compute the cyclotomic  $p$ -adic height.

The equation of the curve must be minimal at  $p$ .

INPUT:

- *p* - prime = 5 for which the curve has semi-stable reduction
- *prec* - integer = 1, desired precision of result
- *sigma* - precomputed value of sigma. If not supplied, this function will call `padic_sigma` to compute it.
- *check\_hypotheses* - boolean, whether to check that this is a curve for which the  $p$ -adic height makes sense

OUTPUT: A function that accepts two parameters:

- a  $\mathbb{Q}$ -rational point on the curve whose height should be computed
- optional boolean flag 'check': if False, it skips some input checking, and returns the  $p$ -adic height of that point to the desired precision.
- The normalization (sign and a factor 1/2 with respect to some other normalizations that appear in the literature) is chosen in such a way as to make the  $p$ -adic Birch Swinnerton-Dyer conjecture hold as stated in [Mazur-Tate-Teitelbaum].

AUTHORS:

- Jennifer Balakrishnan: original code developed at the 2006 MSRI graduate workshop on modular forms
- David Harvey (2006-09-13): integrated into Sage, optimised to speed up repeated evaluations of the returned height function, addressed some thorny precision questions
- David Harvey (2006-09-30): rewrote to use division polynomials for computing denominator of  $nP$ .
- David Harvey (2007-02): cleaned up according to algorithms in "Efficient Computation of  $p$ -adic Heights"
- Chris Wuthrich (2007-05): added supersingular and multiplicative heights

EXAMPLES:

```

sage: E = EllipticCurve("37a")
sage: P = E.gens()[0]
sage: h = E.padic_height(5, 10)
sage: h(P)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)

```

An anomalous case:



```
sage: h = E.padic_height(53, 10)
sage: h(P)
26*53^-1 + 30 + 20*53 + 47*53^2 + 10*53^3 + 32*53^4 + 9*53^5 + 22*53^6 +
↪ 35*53^7 + 30*53^8 + 17*53^9 + O(53^10)
```

Boundary case:

```
sage: E.padic_height(5, 3)(P)
5 + 5^2 + O(5^3)
```

A case that works the division polynomial code a little harder:

```
sage: E.padic_height(5, 10)(5*P)
5^3 + 5^4 + 5^5 + 3*5^8 + 4*5^9 + O(5^10)
```

Check that answers agree over a range of precisions:

```
sage: max_prec = 30      # make sure we get past p^2      # long time
sage: full = E.padic_height(5, max_prec)(P)                # long time
sage: for prec in range(1, max_prec):                      # long time
....:     assert E.padic_height(5, prec)(P) == full        # long time
```

A supersingular prime for a curve:

```
sage: E = EllipticCurve('37a')
sage: E.is_supersingular(3)
True
sage: h = E.padic_height(3, 5)
sage: h(E.gens()[0])
(3 + 3^3 + O(3^6), 2*3^2 + 3^3 + 3^4 + 3^5 + 2*3^6 + O(3^7))
sage: E.padic_regulator(5)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + 5^10 + 3*5^11 + 3*5^12 + 5^13 + 4*5^14
↪ + 5^15 + 2*5^16 + 5^17 + 2*5^18 + 4*5^19 + O(5^20)
sage: E.padic_regulator(3, 5)
(3 + 2*3^2 + 3^3 + O(3^4), 3^2 + 2*3^3 + 3^4 + O(3^5))
```

A torsion point in both the good and supersingular cases:

```
sage: E = EllipticCurve('11a')
sage: P = E.torsion_subgroup().gen(0).element(); P
(5 : 5 : 1)
sage: h = E.padic_height(19, 5)
sage: h(P)
0
sage: h = E.padic_height(5, 5)
sage: h(P)
0
```

The result is not dependent on the model for the curve:

```
sage: E = EllipticCurve([0,0,0,0,2^12*17])
sage: Em = E.minimal_model()
sage: P = E.gens()[0]
sage: Pm = Em.gens()[0]
sage: h = E.padic_height(7)
sage: hm = Em.padic_height(7)
sage: h(P) == hm(Pm)
True
```

**padic\_height\_pairing\_matrix** (*p*, *prec*=20, *height*=None, *check\_hypotheses*=True)

Computes the cyclotomic  $p$ -adic height pairing matrix of this curve with respect to the basis `self.gens()` for the Mordell-Weil group for a given odd prime  $p$  of good ordinary reduction.

INPUT:

- *p* - prime = 5
- *prec* - answer will be returned modulo  $p^{\text{prec}}$
- *height* - precomputed height function. If not supplied, this function will call `padic_height` to compute it.
- *check\_hypotheses* - boolean, whether to check that this is a curve for which the  $p$ -adic height makes sense

OUTPUT: The  $p$ -adic cyclotomic height pairing matrix of this curve to the given precision.

---

**Todo:** remove restriction that curve must be in minimal Weierstrass form. This is currently required for `E.gens()`.

---

AUTHORS:

- David Harvey, Liang Xiao, Robert Bradshaw, Jennifer Balakrishnan: original implementation at the 2006 MSRI graduate workshop on modular forms
- David Harvey (2006-09-13): cleaned up and integrated into Sage, removed some redundant height computations

EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: E.padic_height_pairing_matrix(5, 10)
[5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)]
```

A rank two example:

```
sage: e = EllipticCurve('389a')
sage: e._set_gens([e(-1, 1), e(1, 0)]) # avoid platform dependent gens
sage: e.padic_height_pairing_matrix(5, 10)
[      3*5 + 2*5^2 + 5^4 + 5^5 + 5^7 + 4*5^9 + O(5^10)  5 +
↪ 4*5^2 + 5^3 + 2*5^4 + 3*5^5 + 4*5^6 + 5^7 + 5^8 + 2*5^9 + O(5^10)]
[5 + 4*5^2 + 5^3 + 2*5^4 + 3*5^5 + 4*5^6 + 5^7 + 5^8 + 2*5^9 + O(5^10)
↪      4*5 + 2*5^4 + 3*5^6 + 4*5^7 + 4*5^8 + O(5^10)]
```

An anomalous rank 3 example:

```
sage: e = EllipticCurve("5077a")
sage: e._set_gens([e(-1, 3), e(2, 0), e(4, 6)])
sage: e.padic_height_pairing_matrix(5, 4)
[4 + 3*5 + 4*5^2 + 4*5^3 + O(5^4)      4 + 4*5^2 + 2*5^3 + O(5^4)      3*5
↪ 4*5^2 + 5^3 + O(5^4)]
[      4 + 4*5^2 + 2*5^3 + O(5^4)      3 + 4*5 + 3*5^2 + 5^3 + O(5^4)
↪      2 + 4*5 + O(5^4)]
[      3*5 + 4*5^2 + 5^3 + O(5^4)      2 + 4*5 + O(5^4)      1
↪ 3*5 + 5^2 + 5^3 + O(5^4)]
```

**padic\_height\_via\_multiply** (*p*, *prec*=20, *E2*=None, *check\_hypotheses*=True)

Computes the cyclotomic  $p$ -adic height.

The equation of the curve must be minimal at  $p$ .

INPUT:

- $p$  - prime = 5 for which the curve has good ordinary reduction
- $prec$  - integer = 2, desired precision of result
- $E2$  - precomputed value of  $E2$ . If not supplied, this function will call `padic_E2` to compute it. The value supplied must be correct mod  $p^{(prec-2)}$  (or slightly higher in the anomalous case; see the code for details).
- `check_hypotheses` - boolean, whether to check that this is a curve for which the  $p$ -adic height makes sense

OUTPUT: A function that accepts two parameters:

- a  $\mathbb{Q}$ -rational point on the curve whose height should be computed
- optional boolean flag 'check': if False, it skips some input checking, and returns the  $p$ -adic height of that point to the desired precision.
- The normalization (sign and a factor 1/2 with respect to some other normalizations that appear in the literature) is chosen in such a way as to make the  $p$ -adic Birch Swinnerton-Dyer conjecture hold as stated in [Mazur-Tate-Teitelbaum].

AUTHORS:

- David Harvey (2008-01): based on the `padic_height()` function, using the algorithm of "Computing  $p$ -adic heights via point multiplication"

EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: P = E.gens()[0]
sage: h = E.padic_height_via_multiply(5, 10)
sage: h(P)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

An anomalous case:

```
sage: h = E.padic_height_via_multiply(53, 10)
sage: h(P)
26*53^-1 + 30 + 20*53 + 47*53^2 + 10*53^3 + 32*53^4 + 9*53^5 + 22*53^6 +
↪ 35*53^7 + 30*53^8 + 17*53^9 + O(53^10)
```

Supply the value of  $E2$  manually:

```
sage: E2 = E.padic_E2(5, 8)
sage: E2
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + O(5^8)
sage: h = E.padic_height_via_multiply(5, 10, E2=E2)
sage: h(P)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

Boundary case:

```
sage: E.padic_height_via_multiply(5, 3)(P)
5 + 5^2 + O(5^3)
```

Check that answers agree over a range of precisions:

```

sage: max_prec = 30      # make sure we get past p^2      # long time
sage: full = E.padic_height(5, max_prec)(P)              # long time
sage: for prec in range(2, max_prec):                    # long time
.....:     assert E.padic_height_via_multiply(5, prec)(P) == full # long time

```

**padic\_lseries** (*p*, *normalize=None*, *use\_eclib=None*, *implementation='eclib'*, *precision=None*)

Return the  $p$ -adic  $L$ -series of self at  $p$ , which is an object whose `approx` method computes approximation to the true  $p$ -adic  $L$ -series to any desired precision.

INPUT:

- *p* - prime
- *normalize* - 'L\_ratio' (default), 'period' or 'none'; this describes the way the modular symbols are normalized. See `modular_symbol` for more details.
- *use\_eclib* - deprecated, use *implementation* instead
- *implementation* - 'eclib' (default), 'sage', 'pollackstevens'; Whether to use John Cremona's `eclib`, the Sage implementation, or Pollack-Stevens' implementation of overconvergent modular symbols.

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: L = E.padic_lseries(5); L
5-adic L-series of Elliptic Curve defined by y^2 + y = x^3 - x over Rational_
↪Field
sage: type(L)
<class 'sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesOrdinary'>

```

We compute the 3-adic  $L$ -series of two curves of rank 0 and in each case verify the interpolation property for their leading coefficient (i.e., value at 0):

```

sage: e = EllipticCurve('11a')
sage: ms = e.modular_symbol()
sage: [ms(1/11), ms(1/3), ms(0), ms(oo)]
[0, -3/10, 1/5, 0]
sage: ms(0)
1/5
sage: L = e.padic_lseries(3)
sage: P = L.series(5)
sage: P(0)
2 + 3 + 3^2 + 2*3^3 + 2*3^5 + 3^6 + O(3^7)
sage: alpha = L.alpha(9); alpha
2 + 3^2 + 2*3^3 + 2*3^4 + 2*3^6 + 3^8 + O(3^9)
sage: R.<x> = QQ[]
sage: f = x^2 - e.ap(3)*x + 3
sage: f(alpha)
O(3^9)
sage: r = e.lseries().L_ratio(); r
1/5
sage: (1 - alpha^(-1))^2 * r
2 + 3 + 3^2 + 2*3^3 + 2*3^5 + 3^6 + 3^7 + O(3^9)
sage: P(0)
2 + 3 + 3^2 + 2*3^3 + 2*3^5 + 3^6 + O(3^7)

```

Next consider the curve 37b:

```

sage: e = EllipticCurve('37b')
sage: L = e.padic_lseries(3)
sage: P = L.series(5)
sage: alpha = L.alpha(9); alpha
1 + 2*3 + 3^2 + 2*3^5 + 2*3^7 + 3^8 + O(3^9)
sage: r = e.lseries().L_ratio(); r
1/3
sage: (1 - alpha^(-1))^2 * r
3 + 3^2 + 2*3^4 + 2*3^5 + 2*3^6 + 3^7 + O(3^9)
sage: P(0)
3 + 3^2 + 2*3^4 + 2*3^5 + O(3^6)

```

We can use Sage modular symbols instead to compute the  $L$ -series:

```

sage: e = EllipticCurve('11a')
sage: L = e.padic_lseries(3, implementation = 'sage')
sage: L.series(5, prec=10)
2 + 3 + 3^2 + 2*3^3 + 2*3^5 + 3^6 + O(3^7) + (1 + 3 + 2*3^2 + 3^3 + O(3^4))*T
↪ + (1 + 2*3 + O(3^4))*T^2 + (3 + 2*3^2 + O(3^3))*T^3 + (2*3 + 3^2 + O(3^
↪ 3))*T^4 + (2 + 2*3 + 2*3^2 + O(3^3))*T^5 + (1 + 3^2 + O(3^3))*T^6 + (2 + 3^
↪ 2 + O(3^3))*T^7 + (2 + 2*3 + 2*3^2 + O(3^3))*T^8 + (2 + O(3^2))*T^9 + O(T^
↪ 10)

```

Finally, we can use the overconvergent method of Pollack-Stevens.:

```

sage: e = EllipticCurve('11a')
sage: L = e.padic_lseries(3, implementation = 'pollackstevens', precision = 6)
sage: L.series(5)
2 + 3 + 3^2 + 2*3^3 + 2*3^5 + O(3^6) + (1 + 3 + 2*3^2 + 3^3 + O(3^4))*T + (1
↪ + 2*3 + O(3^2))*T^2 + (3 + O(3^2))*T^3 + O(3^0)*T^4 + O(T^5)
sage: L[3]
3 + O(3^2)

```

Another example with a semistable prime.:

```

sage: E = EllipticCurve("11a1")
sage: L = E.padic_lseries(11, implementation = 'pollackstevens', precision=3)
sage: L[1]
10 + 3*11 + O(11^2)
sage: L[3]
O(11^0)

```

**padic\_regulator** ( $p$ ,  $prec=20$ ,  $height=None$ ,  $check_hypotheses=True$ )

Computes the cyclotomic  $p$ -adic regulator of this curve.

INPUT:

- $p$  - prime = 5
- $prec$  - answer will be returned modulo  $p^{prec}$
- $height$  - precomputed height function. If not supplied, this function will call `padic_height` to compute it.
- $check_hypotheses$  - boolean, whether to check that this is a curve for which the  $p$ -adic height makes sense

OUTPUT: The  $p$ -adic cyclotomic regulator of this curve, to the requested precision.

If the rank is 0, we output 1.

---

**Todo:** Remove restriction that curve must be in minimal Weierstrass form. This is currently required for `E.gens()`.

---

#### AUTHORS:

- Liang Xiao: original implementation at the 2006 MSRI graduate workshop on modular forms
- David Harvey (2006-09-13): cleaned up and integrated into Sage, removed some redundant height computations
- Chris Wuthrich (2007-05-22): added multiplicative and supersingular cases
- David Harvey (2007-09-20): fixed some precision loss that was occurring

#### EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: E.padic_regulator(5, 10)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

#### An anomalous case:

```
sage: E.padic_regulator(53, 10)
26*53^-1 + 30 + 20*53 + 47*53^2 + 10*53^3 + 32*53^4 + 9*53^5 + 22*53^6 +
↪ 35*53^7 + 30*53^8 + O(53^9)
```

#### An anomalous case where the precision drops some:

```
sage: E = EllipticCurve("5077a")
sage: E.padic_regulator(5, 10)
5 + 5^2 + 4*5^3 + 2*5^4 + 2*5^5 + 2*5^6 + 4*5^7 + 2*5^8 + 5^9 + O(5^10)
```

#### Check that answers agree over a range of precisions:

```
sage: max_prec = 30      # make sure we get past p^2      # long time
sage: full = E.padic_regulator(5, max_prec)                # long time
sage: for prec in range(1, max_prec):                      # long time
....:     assert E.padic_regulator(5, prec) == full      # long time
```

#### A case where the generator belongs to the formal group already (trac ticket #3632):

```
sage: E = EllipticCurve([37,0])
sage: E.padic_regulator(5,10)
2*5^2 + 2*5^3 + 5^4 + 5^5 + 4*5^6 + 3*5^8 + 4*5^9 + O(5^10)
```

#### The result is not dependent on the model for the curve:

```
sage: E = EllipticCurve([0,0,0,0,2^12*17])
sage: Em = E.minimal_model()
sage: E.padic_regulator(7) == Em.padic_regulator(7)
True
```

#### Allow a Python int as input:

```
sage: E = EllipticCurve('37a')
sage: E.padic_regulator(int(5))
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + 5^10 + 3*5^11 + 3*5^12 + 5^13 + 4*5^14
↪ + 5^15 + 2*5^16 + 5^17 + 2*5^18 + 4*5^19 + O(5^20)
```

**padic\_sigma** (*p*, *N*=20, *E2*=None, *check*=False, *check\_hypotheses*=True)

Computes the  $p$ -adic sigma function with respect to the standard invariant differential  $dx/(2y + a_1x + a_3)$ , as defined by Mazur and Tate, as a power series in the usual uniformiser  $t$  at the origin.

The equation of the curve must be minimal at  $p$ .

INPUT:

- *p* - prime = 5 for which the curve has good ordinary reduction
- *N* - integer = 1, indicates precision of result; see OUTPUT section for description
- *E2* - precomputed value of  $E_2$ . If not supplied, this function will call `padic_E2` to compute it. The value supplied must be correct mod  $p^{N-2}$ .
- *check* - boolean, whether to perform a consistency check (i.e. verify that the computed sigma satisfies the defining
- *differential equation* - note that this does NOT guarantee correctness of all the returned digits, but it comes pretty close :-))
- *check\_hypotheses* - boolean, whether to check that this is a curve for which the  $p$ -adic sigma function makes sense

OUTPUT: A power series  $t + \dots$  with coefficients in  $\mathbb{Z}_p$ .

The output series will be truncated at  $O(t^{N+1})$ , and the coefficient of  $t^n$  for  $n \geq 1$  will be correct to precision  $O(p^{N-n+1})$ .

In practice this means the following. If  $t_0 = p^k u$ , where  $u$  is a  $p$ -adic unit with at least  $N$  digits of precision, and  $k \geq 1$ , then the returned series may be used to compute  $\sigma(t_0)$  correctly modulo  $p^{N+k}$  (i.e. with  $N$  correct  $p$ -adic digits).

ALGORITHM: Described in “Efficient Computation of  $p$ -adic Heights” (David Harvey), which is basically an optimised version of the algorithm from “ $p$ -adic Heights and Log Convergence” (Mazur, Stein, Tate).

Running time is  $\text{soft-}O(N^2 \log p)$ , plus whatever time is necessary to compute  $E_2$ .

AUTHORS:

- David Harvey (2006-09-12)
- David Harvey (2007-02): rewrote

EXAMPLES:

```
sage: EllipticCurve([-1, 1/4]).padic_sigma(5, 10)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 +
↪ O(5^8))*t^3 + O(5^7)*t^4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 5^5 + O(5^6))*t^5 +
↪ O(5^5)*t^6 + (2 + 2*5 + 5^2 + 4*5^3 + O(5^4))*t^7 + O(5^3)*t^8 + (1 + 2*5 +
↪ O(5^2))*t^9 + O(5)*t^10 + O(t^11)
```

Run it with a consistency check:

```
sage: EllipticCurve("37a").padic_sigma(5, 10, check=True)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 +
↪ O(5^8))*t^3 + (3 + 2*5 + 2*5^2 + 2*5^3 + 2*5^4 + 2*5^5 + 2*5^6 + O(5^7))*t^4
↪ 4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 5^5 + O(5^6))*t^5 + (2 + 3*5 + 5^4 + O(5^
↪ 5))*t^6 + (4 + 3*5 + 2*5^2 + O(5^4))*t^7 + (2 + 3*5 + 2*5^2 + O(5^3))*t^8 +
↪ (4*5 + O(5^2))*t^9 + (1 + O(5))*t^10 + O(t^11)
```

Boundary cases:

```
sage: EllipticCurve([1, 1, 1, 1, 1]).padic_sigma(5, 1)
(1 + O(5))*t + O(t^2)
sage: EllipticCurve([1, 1, 1, 1, 1]).padic_sigma(5, 2)
(1 + O(5^2))*t + (3 + O(5))*t^2 + O(t^3)
```

Supply your very own value of E2:

```
sage: X = EllipticCurve("37a")
sage: my_E2 = X.padic_E2(5, 8)
sage: my_E2 = my_E2 + 5**5      # oops!!!
sage: X.padic_sigma(5, 10, E2=my_E2)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 4*5^5 + 2*5^6 +
↪ 3*5^7 + O(5^8))*t^3 + (3 + 2*5 + 2*5^2 + 2*5^3 + 2*5^4 + 2*5^5 + 2*5^6 +
↪ O(5^7))*t^4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 3*5^5 + O(5^6))*t^5 + (2 + 3*5 + 5^
↪ 4 + O(5^5))*t^6 + (4 + 3*5 + 2*5^2 + O(5^4))*t^7 + (2 + 3*5 + 2*5^2 + O(5^
↪ 3))*t^8 + (4*5 + O(5^2))*t^9 + (1 + O(5))*t^10 + O(t^11)
```

Check that sigma is “weight 1”.

```
sage: f = EllipticCurve([-1, 3]).padic_sigma(5, 10)
sage: g = EllipticCurve([-1*(2**4), 3*(2**6)]).padic_sigma(5, 10)
sage: t = f.parent().gen()
sage: f(2*t)/2
(1 + O(5^10))*t + (4 + 3*5 + 3*5^2 + 3*5^3 + 4*5^4 + 4*5^5 + 3*5^6 + 5^7 +
↪ O(5^8))*t^3 + (3 + 3*5^2 + 5^4 + 2*5^5 + O(5^6))*t^5 + (4 + 5 + 3*5^3 + O(5^
↪ 4))*t^7 + (4 + 2*5 + O(5^2))*t^9 + O(5)*t^10 + O(t^11)
sage: g
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (4 + 3*5 + 3*5^2 + 3*5^3 + 4*5^4 +
↪ 4*5^5 + 3*5^6 + 5^7 + O(5^8))*t^3 + O(5^7)*t^4 + (3 + 3*5^2 + 5^4 + 2*5^5 +
↪ O(5^6))*t^5 + O(5^5)*t^6 + (4 + 5 + 3*5^3 + O(5^4))*t^7 + O(5^3)*t^8 + (4 +
↪ 2*5 + O(5^2))*t^9 + O(5)*t^10 + O(t^11)
sage: f(2*t)/2 - g
O(t^11)
```

Test that it returns consistent results over a range of precision:

```
sage: max_N = 30      # get up to at least p^2          # long time
sage: E = EllipticCurve([1, 1, 1, 1, 1])                # long time
sage: p = 5                                                # long time
sage: E2 = E.padic_E2(5, max_N)                          # long time
sage: max_sigma = E.padic_sigma(p, max_N, E2=E2)         # long time
sage: for N in range(3, max_N):                          # long time
....:     sigma = E.padic_sigma(p, N, E2=E2)             # long time
....:     assert sigma == max_sigma
```

**padic\_sigma\_truncated** ( $p, N=20, \text{lambd}=0, E2=None, \text{check\_hypotheses}=True$ )

Computes the  $p$ -adic sigma function with respect to the standard invariant differential  $dx/(2y + a_1x + a_3)$ , as defined by Mazur and Tate, as a power series in the usual uniformiser  $t$  at the origin.

The equation of the curve must be minimal at  $p$ .

This function differs from `padic_sigma()` in the precision profile of the returned power series; see OUTPUT below.

INPUT:

- $p$  - prime = 5 for which the curve has good ordinary reduction
- $N$  - integer = 2, indicates precision of result; see OUTPUT section for description



- `lamb` - integer = 0, see OUTPUT section for description
- `E2` - precomputed value of  $E_2$ . If not supplied, this function will call `padic_E2` to compute it. The value supplied must be correct mod  $p^{N-2}$ .
- `check_hypotheses` - boolean, whether to check that this is a curve for which the p-adic sigma function makes sense

OUTPUT: A power series  $t + \dots$  with coefficients in  $\mathbb{Z}_p$ .

The coefficient of  $t^j$  for  $j \geq 1$  will be correct to precision  $O(p^{N-2+(3-j)(lamb+1)})$ .

ALGORITHM: Described in “Efficient Computation of p-adic Heights” (David Harvey, to appear in LMS JCM), which is basically an optimised version of the algorithm from “p-adic Heights and Log Convergence” (Mazur, Stein, Tate), and “Computing p-adic heights via point multiplication” (David Harvey, still draft form).

Running time is soft- $O(N^2 \lambda^{-1} \log p)$ , plus whatever time is necessary to compute  $E_2$ .

AUTHOR:

- David Harvey (2008-01): wrote based on previous `padic_sigma` function

EXAMPLES:

```
sage: E = EllipticCurve([-1, 1/4])
sage: E.padic_sigma_truncated(5, 10)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 +
↪ O(5^8))*t^3 + O(5^7)*t^4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 5^5 + O(5^6))*t^5 +
↪ O(5^5)*t^6 + (2 + 2*5 + 5^2 + 4*5^3 + O(5^4))*t^7 + O(5^3)*t^8 + (1 + 2*5 +
↪ O(5^2))*t^9 + O(5)*t^10 + O(t^11)
```

Note the precision of the  $t^3$  coefficient depends only on  $N$ , not on `lamb`:

```
sage: E.padic_sigma_truncated(5, 10, lamb=2)
O(5^17) + (1 + O(5^14))*t + O(5^11)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7
↪ + O(5^8))*t^3 + O(5^5)*t^4 + (2 + O(5^2))*t^5 + O(t^6)
```

Compare against plain `padic_sigma()` function over a dense range of  $N$  and `lamb`

```
sage: E = EllipticCurve([1, 2, 3, 4, 7]) # long
↪time
sage: E2 = E.padic_E2(5, 50) # long
↪time
sage: for N in range(2, 10): # long
↪time
....:     for lamb in range(10): # long
↪time
....:         correct = E.padic_sigma(5, N + 3*lamb, E2=E2) # long
↪time
....:         compare = E.padic_sigma_truncated(5, N=N, lamb=lamb, E2=E2) #
↪long time
....:         assert compare == correct # long
↪time
```

**pari\_curve()**

Return the PARI curve corresponding to this elliptic curve.

INPUT:

- `prec` – Deprecated

- `factor` – Deprecated

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: e = E.pari_curve()
sage: type(e)
<... 'cy pari2.gen.Gen'>
sage: e.type()
't_VEC'
sage: e.ellan(10)
[1, -2, -3, 2, -2, 6, -1, 0, 6, 4]
```

```
sage: E = EllipticCurve(RationalField(), ['1/3', '2/3'])
sage: e = E.pari_curve()
sage: e[:5]
[0, 0, 0, 1/3, 2/3]
```

When doing certain computations, PARI caches the results:

```
sage: E = EllipticCurve('37a1')
sage: _ = E.__dict__.pop('_pari_curve', None) # clear cached data
sage: Epari = E.pari_curve()
sage: Epari
[0, 0, 1, -1, 0, 0, -2, 1, -1, 48, -216, 37, 110592/37, Vecsmall([1]),
↪ [Vecsmall([64, 1])], [0, 0, 0, 0, 0, 0, 0, 0]]
sage: Epari.omega()
[2.99345864623196, -2.45138938198679*I]
sage: Epari
[0, 0, 1, -1, 0, 0, -2, 1, -1, 48, -216, 37, 110592/37, Vecsmall([1]),
↪ [Vecsmall([64, 1])], [[2.99345864623196, -2.45138938198679*I], 0, [0.
↪ 837565435283323, 0.269594436405445, -1.10715987168877, 1.37675430809421, 1.
↪ 94472530697209, 0.567970998877878]~, 0, 0, 0, 0, 0]]
```

This shows that the bug uncovered by [trac ticket #4715](#) is fixed:

```
sage: Ep = EllipticCurve('903b3').pari_curve()
```

This still works, even when the curve coefficients are large (see [trac ticket #13163](#)):

```
sage: E = EllipticCurve([4382696457564794691603442338788106497, 28, 3992,
↪ 16777216, 298])
sage: E.pari_curve()
[4382696457564794691603442338788106497, 28, 3992, 16777216, 298, ...]
sage: E.minimal_model()
Elliptic Curve defined by y^2 + x*y + y = x^3 + x^2 -
↪ 768642393408379739067598116922917190767418358832618451139114672714367242316709148439249798
↪ +
↪ 820228044355376148377310864873427185121598850482021478489975266210045966301170999244686097
↪ over Rational Field
```

**`pari_mincurve()`**

Return the PARI curve corresponding to a minimal model for this elliptic curve.

INPUT:

- `prec` – Deprecated
- `factor` – Deprecated

EXAMPLES:

```
sage: E = EllipticCurve(RationalField(), ['1/3', '2/3'])
sage: e = E.pari_mincurve()
sage: e[:5]
[0, 0, 0, 27, 486]
sage: E.conductor()
47232
sage: e.ellglobalred()
[47232, [1, 0, 0, 0], 2, [2, 7; 3, 2; 41, 1], [[7, 2, 0, 1], [2, -3, 0, 2],
↪ [1, 5, 0, 1]]]
```

**period\_lattice** (*embedding=None*)

Return the period lattice of the elliptic curve with respect to the differential  $dx/(2y + a_1x + a_3)$ .

INPUT:

- *embedding* - ignored (for compatibility with the `period_lattice` function for elliptic\_curve\_number\_field)

OUTPUT:

(period lattice) The `PeriodLattice_ell` object associated to this elliptic curve (with respect to the natural embedding of  $\mathbf{Q}$  into  $\mathbf{R}$ ).

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice()
Period lattice associated to Elliptic Curve defined by  $y^2 + y = x^3 - x$  over
↪ Rational Field
```

**point\_search** (*height\_limit*, *verbose=False*, *rank\_bound=None*)

Search for points on a curve up to an input bound on the naive logarithmic height.

INPUT:

- *height\_limit* (float) - bound on naive height
- *verbose* (bool) - (default: False)  
If True, report on the saturation process.  
If False, just return the result.
- *rank\_bound* (bool) - (default: None)  
If provided, stop saturating once we find this many independent nontorsion points.

OUTPUT: points (list) - list of independent points which generate the subgroup of the Mordell-Weil group generated by the points found and then saturated.

**Warning:** *height\_limit* is logarithmic, so increasing by 1 will cause the running time to increase by a factor of approximately 4.5 ( $=\exp(1.5)$ ).

IMPLEMENTATION: Uses Michael Stoll's `ratpoints` module in PARI/GP.

EXAMPLES:

```
sage: E = EllipticCurve('389a1')
sage: E.point_search(5, verbose=False)
[(-1 : 1 : 1), (0 : 0 : 1)]
```

Increasing the height\_limit takes longer, but finds no more points:

```
sage: E.point_search(10, verbose=False)
[(-1 : 1 : 1), (0 : 0 : 1)]
```

In fact this curve has rank 2 so no more than 2 points will ever be output, but we are not using this fact.

```
sage: E.saturation(_)
[(-1 : 1 : 1), (0 : 0 : 1)], 1, 0.152460177943144)
```

What this shows is that if the rank is 2 then the points listed do generate the Mordell-Weil group (mod torsion). Finally,

```
sage: E.rank()
2
```

If we only need one independent generator:

```
sage: E.point_search(5, verbose=False, rank_bound=1)
[(-2 : 0 : 1)]
```

**pollack\_stevens\_modular\_symbol** (*sign=0, implementation='eclib'*)

Create the modular symbol attached to the elliptic curve, suitable for overconvergent calculations.

INPUT:

- *sign* – +1 or -1 or 0 (default), in which case this is the sum of the two
- *implementation* – either 'eclib' (default) or 'sage'. This determines classical modular symbols which implementation of the underlying classical modular symbols is used

EXAMPLES:

```
sage: E = EllipticCurve('113a1')
sage: symb = E.pollack_stevens_modular_symbol()
sage: symb
Modular symbol of level 113 with values in Sym^0 Q^2
sage: symb.values()
[-1/2, 1, -1, 0, 0, 1, 1, -1, 0, -1, 0, 0, 0, 1, -1, 0, 0, 0, 1, 0, 0]

sage: E = EllipticCurve([0,1])
sage: symb = E.pollack_stevens_modular_symbol(+1)
sage: symb.values()
[-1/6, 1/12, 0, 1/6, 1/12, 1/3, -1/12, 0, -1/6, -1/12, -1/4, -1/6, 1/12]
```

**prove\_BSD** (*E, verbosity=0, two\_desc='mwrnk', proof=None, secs\_hi=5, return\_BSD=False*)

Attempts to prove the Birch and Swinnerton-Dyer conjectural formula for  $E$ , returning a list of primes  $p$  for which this function fails to prove BSD( $E, p$ ). Here, BSD( $E, p$ ) is the statement: “the Birch and Swinnerton-Dyer formula holds up to a rational number coprime to  $p$ .”

INPUT:

- $E$  – an elliptic curve
- *verbosity* – int, how much information about the proof to print.

- 0 - print nothing
- 1 - print sketch of proof
- 2 - print information about remaining primes
- `two_desc` - string (default 'mwrnk'), what to use for the two-descent. Options are 'mwrnk', 'simon', 'sage'
- `proof` - bool or None (default: None, see `proof.elliptic_curve` or `sage.structure.proof`). If False, this function just immediately returns the empty list.
- `secs_hi` - maximum number of seconds to try to compute the Heegner index before switching over to trying to compute the Heegner index bound. (Rank 0 only!)
- `return_BSD` - bool (default: False) whether to return an object which contains information to re-construct a proof

NOTE:

When printing verbose output, phrases such as “by Mazur” are referring to the following list of papers:

REFERENCES:

EXAMPLES:

```
sage: EllipticCurve('11a').prove_BSD(verbosity=2)
p = 2: True by 2-descent
True for p not in {2, 5} by Kolyvagin.
Kolyvagin's bound for p = 5 applies by Lawson-Wuthrich
True for p = 5 by Kolyvagin bound
[]

sage: EllipticCurve('14a').prove_BSD(verbosity=2)
p = 2: True by 2-descent
True for p not in {2, 3} by Kolyvagin.
Kolyvagin's bound for p = 3 applies by Lawson-Wuthrich
True for p = 3 by Kolyvagin bound
[]

sage: E = EllipticCurve("20a1")
sage: E.prove_BSD(verbosity=2)
p = 2: True by 2-descent
True for p not in {2, 3} by Kolyvagin.
Kato further implies that #Sha[3] is trivial.
[]

sage: E = EllipticCurve("50b1")
sage: E.prove_BSD(verbosity=2)
p = 2: True by 2-descent
True for p not in {2, 3, 5} by Kolyvagin.
Kolyvagin's bound for p = 3 applies by Lawson-Wuthrich
True for p = 3 by Kolyvagin bound
Remaining primes:
p = 5: reducible, not surjective, additive, divides a Tamagawa number
      (no bounds found)
      ord_p(#Sha_an) = 0
[5]
sage: E.prove_BSD(two_desc='simon')
[5]
```

A rank two curve:

```
sage: E = EllipticCurve('389a')
```

We know nothing with `proof=True`:

```
sage: E.prove_BSD()
Set of all prime numbers: 2, 3, 5, 7, ...
```

We (think we) know everything with `proof=False`:

```
sage: E.prove_BSD(proof=False)
[]
```

A curve of rank 0 and prime conductor:

```
sage: E = EllipticCurve('19a')
sage: E.prove_BSD(verbosity=2)
p = 2: True by 2-descent
True for p not in {2, 3} by Kolyvagin.
Kolyvagin's bound for p = 3 applies by Lawson-Wuthrich
True for p = 3 by Kolyvagin bound
[]

sage: E = EllipticCurve('37a')
sage: E.rank()
1
sage: E._EllipticCurve_rational_field__rank
(1, True)
sage: E.analytic_rank = lambda : 0
sage: E.prove_BSD()
Traceback (most recent call last):
...
RuntimeError: It seems that the rank conjecture does not hold for this curve_
↳(Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field)! This may_
↳be a counterexample to BSD, but is more likely a bug.
```

We test the consistency check for the 2-part of Sha:

```
sage: E = EllipticCurve('37a')
sage: S = E.sha(); S
Tate-Shafarevich group for the Elliptic Curve defined by y^2 + y = x^3 - x_
↳over Rational Field
sage: def foo(use_database):
....:     return 4
sage: S.an = foo
sage: E.prove_BSD()
Traceback (most recent call last):
...
RuntimeError: Apparent contradiction: 0 <= rank sha[2] <= 0, but ord_2 sha_
↳an) = 2
```

An example with a Tamagawa number at 5:

```
sage: E = EllipticCurve('123a1')
sage: E.prove_BSD(verbosity=2)
p = 2: True by 2-descent
True for p not in {2, 5} by Kolyvagin.
Remaining primes:
p = 5: reducible, not surjective, good ordinary, divides a Tamagawa number
```

```
(no bounds found)
ord_p(#Sha_an) = 0
[5]
```

A curve for which 3 divides the order of the Tate-Shafarevich group:

```
sage: E = EllipticCurve('681b')
sage: E.prove_BSD(verbosity=2)           # long time
p = 2: True by 2-descent...
True for p not in {2, 3} by Kolyvagin....
Remaining primes:
p = 3: irreducible, surjective, non-split multiplicative
      (0 <= ord_p <= 2)
      ord_p(#Sha_an) = 2
[3]
```

A curve for which we need to use heegner\_index\_bound:

```
sage: E = EllipticCurve('198b')
sage: E.prove_BSD(verbosity=1, secs_hi=1)
p = 2: True by 2-descent
True for p not in {2, 3} by Kolyvagin.
[3]
```

The return\_BSD option gives an object with detailed information about the proof:

```
sage: E = EllipticCurve('26b')
sage: B = E.prove_BSD(return_BSD=True)
sage: B.two_tor_rk
0
sage: B.N
26
sage: B.gens
[]
sage: B.primes
[]
sage: B.heegner_indexes
{-23: 2}
```

```
sage: E = EllipticCurve('960d1')
sage: E.prove_BSD(verbosity=1) # long time (4s on sage.math, 2011)
p = 2: True by 2-descent
True for p not in {2} by Kolyvagin.
[]
```

**q\_eigenform**(prec)

Synonym for `self.q_expansion(prec)`.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.q_eigenform(10)
q - 2*q^2 - 3*q^3 + 2*q^4 - 2*q^5 + 6*q^6 - q^7 + 6*q^9 + O(q^10)
sage: E.q_eigenform(10) == E.q_expansion(10)
True
```

**q\_expansion**(prec)

Return the  $q$ -expansion to precision `prec` of the newform attached to this elliptic curve.

INPUT:

- `prec` - an integer

OUTPUT:

a power series (in the variable 'q')

---

**Note:** If you want the output to be a modular form and not just a  $q$ -expansion, use `modular_form()`.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.q_expansion(20)
q - 2*q^2 - 3*q^3 + 2*q^4 - 2*q^5 + 6*q^6 - q^7 + 6*q^9 + 4*q^10 - 5*q^11 -
↳ 6*q^12 - 2*q^13 + 2*q^14 + 6*q^15 - 4*q^16 - 12*q^18 + O(q^20)
```

**quadratic\_twist(D)**

Return the global minimal model of the quadratic twist of this curve by D.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E7=E.quadratic_twist(7); E7
Elliptic Curve defined by y^2 = x^3 - 784*x + 5488 over Rational Field
sage: E7.conductor()
29008
sage: E7.quadratic_twist(7) == E
True
```

**rank**(`use_database=True`, `verbose=False`, `only_use_mwrank=True`, `algorithm='mwrank_lib'`, `proof=None`)

Return the rank of this elliptic curve, assuming no conjectures.

If we fail to provably compute the rank, raises a `RuntimeError` exception.

INPUT:

- `use_database` (bool) – (default: `True`), if `True`, try to look up the rank in the Cremona database.
- `verbose` - (default: `False`), if specified changes the verbosity of mwrank computations.
- `algorithm` - (default: `'mwrank_lib'`), one of:
  - `'mwrank_shell'` - call mwrank shell command
  - `'mwrank_lib'` - call mwrank c library
- `only_use_mwrank` - (default: `True`) if `False` try using analytic rank methods first.
- `proof` - bool or `None` (default: `None`, see `proof.elliptic_curve` or `sage.structure.proof`). Note that results obtained from databases are considered `proof = True`

OUTPUT: the rank of the elliptic curve as `Integer`

IMPLEMENTATION: Uses L-functions, mwrank, and databases.

EXAMPLES:

```
sage: EllipticCurve('11a').rank()
0
sage: EllipticCurve('37a').rank()
```



```

1
sage: EllipticCurve('389a').rank()
2
sage: EllipticCurve('5077a').rank()
3
sage: EllipticCurve([1, -1, 0, -79, 289]).rank()    # This will use the
↪ default proof behavior of True
4
sage: EllipticCurve([0, 0, 1, -79, 342]).rank(proof=False)
5
sage: EllipticCurve([0, 0, 1, -79, 342]).simon_two_descent()[0]    # long time
↪ (7s on sage.math, 2012)
5

```

Examples with denominators in defining equations:

```

sage: E = EllipticCurve([0, 0, 0, 0, -675/4])
sage: E.rank()
0
sage: E = EllipticCurve([0, 0, 1/2, 0, -1/5])
sage: E.rank()
1
sage: E.minimal_model().rank()
1

```

A large example where mwrank doesn't determine the result with certainty:

```

sage: EllipticCurve([1, 0, 0, 0, 37455]).rank(proof=False)
0
sage: EllipticCurve([1, 0, 0, 0, 37455]).rank(proof=True)
Traceback (most recent call last):
...
RuntimeError: rank not provably correct (lower bound: 0)

```

#### **rank\_bound()**

Upper bound on the rank of the curve, computed using 2-descent. In many cases, this is the actual rank of the curve. If the curve has no 2-torsion it is the same as the 2-selmer rank.

EXAMPLES: The following is the curve 960D1, which has rank 0, but Sha of order 4.

```

sage: E = EllipticCurve([0, -1, 0, -900, -10098])
sage: E.rank_bound()
0

```

It gives 0 instead of 2, because it knows Sha is nontrivial. In contrast, for the curve 571A, also with rank 0 and Sha of order 4, we get a worse bound:

```

sage: E = EllipticCurve([0, -1, 1, -929, -10595])
sage: E.rank_bound()
2
sage: E.rank(only_use_mwrank=False)    # uses L-function
0

```

#### **real\_components()**

Return 1 if there is 1 real component and 2 if there are 2.

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: E.real_components ()
2
sage: E = EllipticCurve('37b')
sage: E.real_components ()
2
sage: E = EllipticCurve('11a')
sage: E.real_components ()
1

```

**reduction** (*p*)

Return the reduction of the elliptic curve at a prime of good reduction.

---

**Note:** The actual reduction is done in `self.change_ring(GF(p))`; the reduction is performed after changing to a model which is minimal at *p*.

---

INPUT:

- *p* - a (positive) prime number

OUTPUT: an elliptic curve over the finite field  $\text{GF}(p)$

EXAMPLES:

```

sage: E = EllipticCurve('389a1')
sage: E.reduction(2)
Elliptic Curve defined by  $y^2 + y = x^3 + x^2$  over Finite Field of size 2
sage: E.reduction(3)
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + x$  over Finite Field of size 3
sage: E.reduction(5)
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 + 3x$  over Finite Field of size 5
↪5
sage: E.reduction(38)
Traceback (most recent call last):
...
AttributeError: p must be prime.
sage: E.reduction(389)
Traceback (most recent call last):
...
AttributeError: The curve must have good reduction at p.
sage: E = EllipticCurve([5^4, 5^6])
sage: E.reduction(5)
Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over Finite Field of size 5

```

**regulator** (*proof=None, precision=53, \*\*kws*)

Return the regulator of this curve, which must be defined over  $\mathbb{Q}$ .

INPUT:

- *proof* – bool or None (default: None, see `proof.[tab]` or `sage.structure.proof`). Note that results from databases are considered `proof = True`
- *precision* – (int, default 53): the precision in bits of the result
- *\*\*kws* – passed to `gens()` method

EXAMPLES:

```

sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: E.regulator()
0.0511114082399688
sage: EllipticCurve('11a').regulator()
1.000000000000000
sage: EllipticCurve('37a').regulator()
0.0511114082399688
sage: EllipticCurve('389a').regulator()
0.152460177943144
sage: EllipticCurve('5077a').regulator()
0.41714355875838...
sage: EllipticCurve([1, -1, 0, -79, 289]).regulator()
1.50434488827528
sage: EllipticCurve([0, 0, 1, -79, 342]).regulator(proof=False) # long time_
↪ (6s on sage.math, 2011)
14.790527570131...

```

**root\_number** ( $p=None$ )

Return the root number of this elliptic curve.

This is 1 if the order of vanishing of the L-function  $L(E,s)$  at 1 is even, and -1 if it is odd.

INPUT:

- $p$  – optional, default (None); if given, return the local root number at  $p$

EXAMPLES:

```

sage: EllipticCurve('11a1').root_number()
1
sage: EllipticCurve('37a1').root_number()
-1
sage: EllipticCurve('389a1').root_number()
1
sage: type(EllipticCurve('389a1').root_number())
<... 'sage.rings.integer.Integer'>

sage: E = EllipticCurve('100a1')
sage: E.root_number(2)
-1
sage: E.root_number(5)
1
sage: E.root_number(7)
1

```

The root number is cached:

```

sage: E.root_number(2) is E.root_number(2)
True
sage: E.root_number()
1

```

**satisfies\_heegner\_hypothesis** ( $D$ )

Returns True precisely when  $D$  is a fundamental discriminant that satisfies the Heegner hypothesis for this elliptic curve.

EXAMPLES:

```

sage: E = EllipticCurve('11a1')
sage: E.satisfies_heegner_hypothesis(-7)
True
sage: E.satisfies_heegner_hypothesis(-11)
False

```

**saturation** (*points*, *verbose=False*, *max\_prime=0*, *odd\_primes\_only=False*)

Given a list of rational points on  $E$ , compute the saturation in  $E(\mathbb{Q})$  of the subgroup they generate.

INPUT:

- *points* (list) - list of points on  $E$
- *verbose* (bool) - (default: False), if True, give verbose output
- *max\_prime* (int) - (default: 0), saturation is performed for all primes up to *max\_prime*. If *max\_prime*==0, perform saturation at *all* primes, i.e., compute the true saturation.
- *odd\_primes\_only* (bool) - only do saturation at odd primes

OUTPUT:

- *saturation* (list) - points that form a basis for the saturation
- *index* (int) - the index of the group generated by points in their saturation
- *regulator* (real with default precision) - regulator of saturated points.

ALGORITHM: Uses Cremona's `mwrnk` package. With *max\_prime*=0, we call `mwrnk` with successively larger prime bounds until the full saturation is provably found. The results of saturation at the previous primes is stored in each case, so this should be reasonably fast.

EXAMPLES:

```

sage: E = EllipticCurve('37a1')
sage: P=E(0,0)
sage: Q=5*P; Q
(1/4 : -5/8 : 1)
sage: E.saturation([Q])
[(0 : 0 : 1)], 5, 0.0511114082399688)

```

**selmer\_rank** ()

The rank of the 2-Selmer group of the curve.

EXAMPLES: The following is the curve 960D1, which has rank 0, but Sha of order 4.

```

sage: E = EllipticCurve([0, -1, 0, -900, -10098])
sage: E.selmer_rank()
3

```

Here the Selmer rank is equal to the 2-torsion rank (=1) plus the 2-rank of Sha (=2), and the rank itself is zero:

```

sage: E.rank()
0

```

In contrast, for the curve 571A, also with rank 0 and Sha of order 4, we get a worse bound:

```

sage: E = EllipticCurve([0, -1, 1, -929, -10595])
sage: E.selmer_rank()
2

```

```
sage: E.rank_bound()
2
```

To establish that the rank is in fact 0 in this case, we would need to carry out a higher descent:

```
sage: E.three_selmer_rank() # optional: magma
0
```

Or use the L-function to compute the analytic rank:

```
sage: E.rank(only_use_mwrank=False)
0
```

**sha()**

Return an object of class ‘sage.schemes.elliptic\_curves.sha\_tate.Sha’ attached to this elliptic curve.

This can be used in functions related to bounding the order of Sha (The Tate-Shafarevich group of the curve).

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: S=E.sha()
sage: S
Tate-Shafarevich group for the Elliptic Curve defined by  $y^2 + y = x^3 - x$ 
↪over Rational Field
sage: S.bound_kolyvagin()
([2], 1)
```

**silverman\_height\_bound**(algorithm='default')

Return the Silverman height bound. This is a positive real (floating point) number  $B$  such that for all points  $P$  on the curve over any number field,  $|h(P) - \hat{h}(P)| \leq B$ , where  $h(P)$  is the naive logarithmic height of  $P$  and  $\hat{h}(P)$  is the canonical height.

INPUT:

- algorithm –
  - ‘default’ (default) – compute using a Python implementation in Sage
  - ‘mwrank’ – use a C++ implementation in the mwrank library

NOTES:

- The CPS\_height\_bound is often better (i.e. smaller) than the Silverman bound, but it only applies for points over the base field, whereas the Silverman bound works over all number fields.
- The Silverman bound is also fairly straightforward to compute over number fields, but isn’t implemented here.
- Silverman’s paper is ‘The Difference Between the Weil Height and the Canonical Height on Elliptic Curves’, Math. Comp., Volume 55, Number 192, pages 723-743. We use a correction by Bremner with 0.973 replaced by 0.961, as explained in the source code to mwrank (htconst.cc).

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.silverman_height_bound()
4.825400758180918
sage: E.silverman_height_bound(algorithm='mwrank')
4.825400758180918
```

```
sage: E.CPS_height_bound()
0.16397076103046915
```

**simon\_two\_descent** (*verbose=0, lim1=5, lim3=50, limtriv=3, maxprob=20, limbigprime=30, known\_points=None*)

Return lower and upper bounds on the rank of the Mordell-Weil group  $E(\mathbf{Q})$  and a list of points of infinite order.

INPUT:

- `self` – an elliptic curve  $E$  over  $\mathbf{Q}$
- `verbose` – 0, 1, 2, or 3 (default: 0), the verbosity level
- `lim1` – (default: 5) limit on trivial points on quartics
- `lim3` – (default: 50) limit on points on ELS quartics
- `limtriv` – (default: 3) limit on trivial points on  $E$
- `maxprob` – (default: 20)
- **limbigprime** – (default: 30) to distinguish between small and large prime numbers. Use probabilistic tests for large primes. If 0, don't any probabilistic tests.
- `known_points` – (default: None) list of known points on the curve

OUTPUT: a triple (`lower`, `upper`, `list`) consisting of

- `lower` (integer) – lower bound on the rank
- `upper` (integer) – upper bound on the rank
- `list` – list of points of infinite order in  $E(\mathbf{Q})$

The integer `upper` is in fact an upper bound on the dimension of the 2-Selmer group, hence on the dimension of  $E(\mathbf{Q})/2E(\mathbf{Q})$ . It is equal to the dimension of the 2-Selmer group except possibly if  $E(\mathbf{Q})[2]$  has dimension 1. In that case, `upper` may exceed the dimension of the 2-Selmer group by an even number, due to the fact that the algorithm does not perform a second descent.

To obtain a list of generators, use `E.gens()`.

IMPLEMENTATION: Uses Denis Simon's PARI/GP scripts from <http://www.math.unicaen.fr/~simon/>

EXAMPLES:

We compute the ranks of the curves of lowest known conductor up to rank 8. Amazingly, each of these computations finishes almost instantly!

```
sage: E = EllipticCurve('11a1')
sage: E.simon_two_descent()
(0, 0, [])
sage: E = EllipticCurve('37a1')
sage: E.simon_two_descent()
(1, 1, [(0 : 0 : 1)])
sage: E = EllipticCurve('389a1')
sage: E._known_points = [] # clear cached points
sage: E.simon_two_descent()
(2, 2, [(1 : 0 : 1), (-11/9 : 28/27 : 1)])
sage: E = EllipticCurve('5077a1')
sage: E.simon_two_descent()
(3, 3, [(1 : 0 : 1), (2 : 0 : 1), (0 : 2 : 1)])
```

In this example Simon's program does not find any points, though it does correctly compute the rank of the 2-Selmer group.

```
sage: E = EllipticCurve([1, -1, 0, -751055859, -7922219731979])
sage: E.simon_two_descent()
(1, 1, [])
```

The rest of these entries were taken from Tom Womack's page <http://tom.womack.net/maths/conductors.htm>

```
sage: E = EllipticCurve([1, -1, 0, -79, 289])
sage: E.simon_two_descent()
(4, 4, [(6 : -1 : 1), (4 : 3 : 1), (5 : -2 : 1), (8 : 7 : 1)])
sage: E = EllipticCurve([0, 0, 1, -79, 342])
sage: E.simon_two_descent() # long time (9s on sage.math, 2011)
(5, 5, [(5 : 8 : 1), (10 : 23 : 1), (3 : 11 : 1), (-3 : 23 : 1), (0 : 18 : 1)])
sage: E = EllipticCurve([1, 1, 0, -2582, 48720])
sage: r, s, G = E.simon_two_descent(); r,s
(6, 6)
sage: E = EllipticCurve([0, 0, 0, -10012, 346900])
sage: r, s, G = E.simon_two_descent(); r,s
(7, 7)
sage: E = EllipticCurve([0, 0, 1, -23737, 960366])
sage: r, s, G = E.simon_two_descent(); r,s
(8, 8)
```

Example from [trac ticket #10832](#):

```
sage: E = EllipticCurve([1, 0, 0, -6664, 86543])
sage: E.simon_two_descent()
(2, 3, [(-1/4 : 2377/8 : 1), (323/4 : 1891/8 : 1)])
sage: E.rank()
2
sage: E.gens()
[(-1/4 : 2377/8 : 1), (323/4 : 1891/8 : 1)]
```

Example where the lower bound is known to be 1 despite that the algorithm has not found any points of infinite order

```
sage: E = EllipticCurve([1, 1, 0, -23611790086, 1396491910863060])
sage: E.simon_two_descent()
(1, 2, [])
sage: E.rank()
1
sage: E.gens() # uses mwrank
[(4311692542083/48594841 : -13035144436525227/338754636611 : 1)]
```

Example for [trac ticket #5153](#):

```
sage: E = EllipticCurve([3, 0])
sage: E.simon_two_descent()
(1, 2, [(1 : 2 : 1)])
```

The upper bound on the 2-Selmer rank returned by this method need not be sharp. In following example, the upper bound equals the actual 2-Selmer rank plus 2 (see [trac ticket #10735](#)):

```

sage: E = EllipticCurve('438e1')
sage: E.simon_two_descent()
(0, 3, [])
sage: E.selmer_rank() # uses mwrank
1

```

**supersingular\_primes(*B*)**

Return a list of all supersingular primes for this elliptic curve up to and possibly including *B*.

EXAMPLES:

```

sage: e = EllipticCurve('11a')
sage: e.aplist(20)
[-2, -1, 1, -2, 1, 4, -2, 0]
sage: e.supersingular_primes(1000)
[2, 19, 29, 199, 569, 809]

```

```

sage: e = EllipticCurve('27a')
sage: e.aplist(20)
[0, 0, 0, -1, 0, 5, 0, -7]
sage: e.supersingular_primes(97)
[2, 5, 11, 17, 23, 29, 41, 47, 53, 59, 71, 83, 89]
sage: e.ordinary_primes(97)
[7, 13, 19, 31, 37, 43, 61, 67, 73, 79, 97]
sage: e.supersingular_primes(3)
[2]
sage: e.supersingular_primes(2)
[2]
sage: e.supersingular_primes(1)
[]

```

**tamagawa\_exponent(*p*)**

The Tamagawa index of the elliptic curve at *p*.

This is the index of the component group  $E(\mathbb{Q}_p)/E^0(\mathbb{Q}_p)$ . It equals the Tamagawa number (as the component group is cyclic) except for types  $I_m^*$  (*m* even) when the group can be  $C_2 \text{ times } C_2$ .

EXAMPLES:

```

sage: E = EllipticCurve('816a1')
sage: E.tamagawa_number(2)
4
sage: E.tamagawa_exponent(2)
2
sage: E.kodaira_symbol(2)
I2*

```

```

sage: E = EllipticCurve('200c4')
sage: E.kodaira_symbol(5)
I4*
sage: E.tamagawa_number(5)
4
sage: E.tamagawa_exponent(5)
2

```

See [trac ticket #4715](#):



```
sage: E = EllipticCurve('117a3')
sage: E.tamagawa_exponent(13)
4
```

**tamagawa\_number**( $p$ )

The Tamagawa number of the elliptic curve at  $p$ .

This is the order of the component group  $E(\mathbb{Q}_p)/E^0(\mathbb{Q}_p)$ .

EXAMPLES:

```
sage: E = EllipticCurve('11a')
sage: E.tamagawa_number(11)
5
sage: E = EllipticCurve('37b')
sage: E.tamagawa_number(37)
3
```

**tamagawa\_number\_old**( $p$ )

The Tamagawa number of the elliptic curve at  $p$ .

This is the order of the component group  $E(\mathbb{Q}_p)/E^0(\mathbb{Q}_p)$ .

EXAMPLES:

```
sage: E = EllipticCurve('11a')
sage: E.tamagawa_number_old(11)
5
sage: E = EllipticCurve('37b')
sage: E.tamagawa_number_old(37)
3
```

**tamagawa\_product**()

Return the product of the Tamagawa numbers.

EXAMPLES:

```
sage: E = EllipticCurve('54a')
sage: E.tamagawa_product()
3
```

**tate\_curve**( $p$ )

Create the Tate curve over the  $p$ -adics associated to this elliptic curve.

This Tate curve is a  $p$ -adic curve with split multiplicative reduction of the form  $y^2 + xy = x^3 + s_4x + s_6$  which is isomorphic to the given curve over the algebraic closure of  $\mathbb{Q}_p$ . Its points over  $\mathbb{Q}_p$  are isomorphic to  $\mathbb{Q}_p^\times/q^{\mathbb{Z}}$  for a certain parameter  $q \in \mathbb{Z}_p$ .

INPUT:

- $p$  – a prime where the curve has split multiplicative reduction

EXAMPLES:

```
sage: e = EllipticCurve('130a1')
sage: e.tate_curve(2)
2-adic Tate curve associated to the Elliptic Curve defined by y^2 + x*y + y =
x^3 - 33*x + 68 over Rational Field
```

The input curve must have multiplicative reduction at the prime.

```
sage: e.tate_curve(3)
Traceback (most recent call last):
...
ValueError: The elliptic curve must have multiplicative reduction at 3
```

We compute with  $p = 5$ :

```
sage: T = e.tate_curve(5); T
5-adic Tate curve associated to the Elliptic Curve defined by  $y^2 + x*y + y = x^3 - 33*x + 68$  over Rational Field
```

We find the Tate parameter  $q$ :

```
sage: T.parameter(prec=5)
3*5^3 + 3*5^4 + 2*5^5 + 2*5^6 + 3*5^7 + O(5^8)
```

We compute the  $\mathcal{L}$ -invariant of the curve:

```
sage: T.L_invariant(prec=10)
5^3 + 4*5^4 + 2*5^5 + 2*5^6 + 2*5^7 + 3*5^8 + 5^9 + O(5^10)
```

**three\_selmer\_rank** (*algorithm*='UseSUnits')

Return the 3-selmer rank of this elliptic curve, computed using Magma.

INPUT:

- *algorithm* - 'Heuristic' (which is usually much faster in large examples), 'FindCubeRoots', or 'UseSUnits' (default)

OUTPUT: nonnegative integer

EXAMPLES: A rank 0 curve:

```
sage: EllipticCurve('11a').three_selmer_rank() # optional - magma
0
```

A rank 0 curve with rational 3-isogeny but no 3-torsion

```
sage: EllipticCurve('14a3').three_selmer_rank() # optional - magma
0
```

A rank 0 curve with rational 3-torsion:

```
sage: EllipticCurve('14a1').three_selmer_rank() # optional - magma
1
```

A rank 1 curve with rational 3-isogeny:

```
sage: EllipticCurve('91b').three_selmer_rank() # optional - magma
2
```

A rank 0 curve with nontrivial 3-Sha. The Heuristic option makes this about twice as fast as without it.

```
sage: EllipticCurve('681b').three_selmer_rank(algorithm='Heuristic') # long_
↳ time (10 seconds); optional - magma
2
```

**torsion\_order** ()

Return the order of the torsion subgroup.

EXAMPLES:

```
sage: e = EllipticCurve('11a')
sage: e.torsion_order()
5
sage: type(e.torsion_order())
<... 'sage.rings.integer.Integer'>
sage: e = EllipticCurve([1,2,3,4,5])
sage: e.torsion_order()
1
sage: type(e.torsion_order())
<... 'sage.rings.integer.Integer'>
```

**torsion\_points** (*algorithm=None*)

Return the torsion points of this elliptic curve as a sorted list.

OUTPUT: A list of all the torsion points on this elliptic curve.

EXAMPLES:

```
sage: EllipticCurve('11a').torsion_points()
[(0 : 1 : 0), (5 : -6 : 1), (5 : 5 : 1), (16 : -61 : 1), (16 : 60 : 1)]
sage: EllipticCurve('37b').torsion_points()
[(0 : 1 : 0), (8 : -19 : 1), (8 : 18 : 1)]
```

Some curves with large torsion groups:

```
sage: E = EllipticCurve([-1386747, 368636886])
sage: T = E.torsion_subgroup(); T
Torsion Subgroup isomorphic to Z/8 + Z/2 associated to the
Elliptic Curve defined by y^2 = x^3 - 1386747*x + 368636886 over
Rational Field
sage: T == E.torsion_subgroup(algorithm="doud")
True
sage: T == E.torsion_subgroup(algorithm="lutz_nagell")
True
sage: E.torsion_points()
[(-1293 : 0 : 1),
 (-933 : -29160 : 1),
 (-933 : 29160 : 1),
 (-285 : -27216 : 1),
 (-285 : 27216 : 1),
 (0 : 1 : 0),
 (147 : -12960 : 1),
 (147 : 12960 : 1),
 (282 : 0 : 1),
 (1011 : 0 : 1),
 (1227 : -22680 : 1),
 (1227 : 22680 : 1),
 (2307 : -97200 : 1),
 (2307 : 97200 : 1),
 (8787 : -816480 : 1),
 (8787 : 816480 : 1)]
sage: EllipticCurve('210b5').torsion_points()
[(-41/4 : 37/8 : 1),
 (-5 : -103 : 1),
 (-5 : 107 : 1),
 (0 : 1 : 0),
 (10 : -208 : 1),
```

```

(10 : 197 : 1),
(37 : -397 : 1),
(37 : 359 : 1),
(100 : -1153 : 1),
(100 : 1052 : 1),
(415 : -8713 : 1),
(415 : 8297 : 1)]
sage: EllipticCurve('210e2').torsion_points()
[(-36 : 18 : 1),
 (-26 : -122 : 1),
 (-26 : 148 : 1),
 (-8 : -122 : 1),
 (-8 : 130 : 1),
 (0 : 1 : 0),
 (4 : -62 : 1),
 (4 : 58 : 1),
 (31/4 : -31/8 : 1),
 (28 : -14 : 1),
 (34 : -122 : 1),
 (34 : 88 : 1),
 (64 : -482 : 1),
 (64 : 418 : 1),
 (244 : -3902 : 1),
 (244 : 3658 : 1)]

```

**torsion\_subgroup** (*algorithm=None*)

Return the torsion subgroup of this elliptic curve.

OUTPUT: The EllipticCurveTorsionSubgroup instance associated to this elliptic curve.

---

**Note:** To see the torsion points as a list, use `torsion_points()`.

---

EXAMPLES:

```

sage: EllipticCurve('11a').torsion_subgroup()
Torsion Subgroup isomorphic to Z/5 associated to the Elliptic Curve defined
↳by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: EllipticCurve('37b').torsion_subgroup()
Torsion Subgroup isomorphic to Z/3 associated to the Elliptic Curve defined
↳by y^2 + y = x^3 + x^2 - 23*x - 50 over Rational Field

```

```

sage: e = EllipticCurve([-1386747, 368636886]); e
Elliptic Curve defined by y^2 = x^3 - 1386747*x + 368636886 over Rational
↳Field
sage: G = e.torsion_subgroup(); G
Torsion Subgroup isomorphic to Z/8 + Z/2 associated to the
Elliptic Curve defined by y^2 = x^3 - 1386747*x + 368636886 over
Rational Field
sage: G.0*3 + G.1
(1227 : 22680 : 1)
sage: G.1
(282 : 0 : 1)
sage: list(G)
[(0 : 1 : 0), (147 : 12960 : 1), (2307 : 97200 : 1), (-933 : 29160 : 1),
↳(1011 : 0 : 1), (-933 : -29160 : 1), (2307 : -97200 : 1), (147 : -12960 :
↳1), (282 : 0 : 1), (8787 : 816480 : 1), (-285 : 27216 : 1), (1227 : 22680 :
↳1), (-1293 : 0 : 1), (1227 : -22680 : 1), (-285 : -27216 : 1), (8787 : -
↳816480 : 1)]

```

---

**two\_descent** (*verbose=True, selmer\_only=False, first\_limit=20, second\_limit=8, n\_aux=-1, second\_descent=1*)

Compute 2-descent data for this curve.

INPUT:

- `verbose` - (default: `True`) print what mwrank is doing. If `False`, **no output** is printed.
- `selmer_only` - (default: `False`) `selmer_only` switch
- `first_limit` - (default: 20) `firstlim` is bound on  $x+z$  `second_limit` - (default: 8) `secondlim` is bound on  $\log \max x, z$ , i.e. logarithmic
- `n_aux` - (default: -1) `n_aux` only relevant for general 2-descent when 2-torsion trivial; `n_aux=-1` causes default to be used (depends on method)
- `second_descent` - (default: `True`) `second_descent` only relevant for descent via 2-isogeny

OUTPUT:

Return `True` if the descent succeeded, i.e. if the lower bound and the upper bound for the rank are the same. In this case, generators and the rank are cached. A return value of `False` indicates that either rational points were not found, or that `Sha[2]` is nontrivial and mwrank was unable to determine this for sure.

EXAMPLES:

```
sage: E = EllipticCurve('37a1')
sage: E.two_descent(verbose=False)
True
```

**two\_descent\_simon** (*verbose=0, lim1=5, lim3=50, limtriv=3, maxprob=20, limbigprime=30, known\_points=None*)

Return lower and upper bounds on the rank of the Mordell-Weil group  $E(\mathbb{Q})$  and a list of points of infinite order.

INPUT:

- `self` - an elliptic curve  $E$  over  $\mathbb{Q}$
- `verbose` - 0, 1, 2, or 3 (default: 0), the verbosity level
- `lim1` - (default: 5) limit on trivial points on quartics
- `lim3` - (default: 50) limit on points on ELS quartics
- `limtriv` - (default: 3) limit on trivial points on  $E$
- `maxprob` - (default: 20)
- **limbigprime** - (default: 30) to distinguish between small and large prime numbers. Use probabilistic tests for large primes. If 0, don't any probabilistic tests.
- `known_points` - (default: `None`) list of known points on the curve

OUTPUT: a triple (`lower`, `upper`, `list`) consisting of

- `lower` (integer) - lower bound on the rank
- `upper` (integer) - upper bound on the rank
- `list` - list of points of infinite order in  $E(\mathbb{Q})$

The integer `upper` is in fact an upper bound on the dimension of the 2-Selmer group, hence on the dimension of  $E(\mathbf{Q})/2E(\mathbf{Q})$ . It is equal to the dimension of the 2-Selmer group except possibly if  $E(\mathbf{Q})[2]$  has dimension 1. In that case, `upper` may exceed the dimension of the 2-Selmer group by an even number, due to the fact that the algorithm does not perform a second descent.

To obtain a list of generators, use `E.gens()`.

IMPLEMENTATION: Uses Denis Simon's PARI/GP scripts from <http://www.math.unicaen.fr/~simon/>

EXAMPLES:

We compute the ranks of the curves of lowest known conductor up to rank 8. Amazingly, each of these computations finishes almost instantly!

```
sage: E = EllipticCurve('11a1')
sage: E.simon_two_descent()
(0, 0, [])
sage: E = EllipticCurve('37a1')
sage: E.simon_two_descent()
(1, 1, [(0 : 0 : 1)])
sage: E = EllipticCurve('389a1')
sage: E._known_points = [] # clear cached points
sage: E.simon_two_descent()
(2, 2, [(1 : 0 : 1), (-11/9 : 28/27 : 1)])
sage: E = EllipticCurve('5077a1')
sage: E.simon_two_descent()
(3, 3, [(1 : 0 : 1), (2 : 0 : 1), (0 : 2 : 1)])
```

In this example Simon's program does not find any points, though it does correctly compute the rank of the 2-Selmer group.

```
sage: E = EllipticCurve([1, -1, 0, -751055859, -7922219731979])
sage: E.simon_two_descent()
(1, 1, [])
```

The rest of these entries were taken from Tom Womack's page <http://tom.womack.net/maths/conductors.htm>

```
sage: E = EllipticCurve([1, -1, 0, -79, 289])
sage: E.simon_two_descent()
(4, 4, [(6 : -1 : 1), (4 : 3 : 1), (5 : -2 : 1), (8 : 7 : 1)])
sage: E = EllipticCurve([0, 0, 1, -79, 342])
sage: E.simon_two_descent() # long time (9s on sage.math, 2011)
(5, 5, [(5 : 8 : 1), (10 : 23 : 1), (3 : 11 : 1), (-3 : 23 : 1), (0 : 18 : 1)])
sage: E = EllipticCurve([1, 1, 0, -2582, 48720])
sage: r, s, G = E.simon_two_descent(); r, s
(6, 6)
sage: E = EllipticCurve([0, 0, 0, -10012, 346900])
sage: r, s, G = E.simon_two_descent(); r, s
(7, 7)
sage: E = EllipticCurve([0, 0, 1, -23737, 960366])
sage: r, s, G = E.simon_two_descent(); r, s
(8, 8)
```

Example from [trac ticket #10832](#):

```
sage: E = EllipticCurve([1, 0, 0, -6664, 86543])
sage: E.simon_two_descent()
```

```
(2, 3, [(-1/4 : 2377/8 : 1), (323/4 : 1891/8 : 1)])
sage: E.rank()
2
sage: E.gens()
[(-1/4 : 2377/8 : 1), (323/4 : 1891/8 : 1)]
```

Example where the lower bound is known to be 1 despite that the algorithm has not found any points of infinite order

```
sage: E = EllipticCurve([1, 1, 0, -23611790086, 1396491910863060])
sage: E.simon_two_descent()
(1, 2, [])
sage: E.rank()
1
sage: E.gens() # uses mwrank
[(4311692542083/48594841 : -13035144436525227/338754636611 : 1)]
```

Example for [trac ticket #5153](#):

```
sage: E = EllipticCurve([3,0])
sage: E.simon_two_descent()
(1, 2, [(1 : 2 : 1)])
```

The upper bound on the 2-Selmer rank returned by this method need not be sharp. In following example, the upper bound equals the actual 2-Selmer rank plus 2 (see [trac ticket #10735](#)):

```
sage: E = EllipticCurve('438e1')
sage: E.simon_two_descent()
(0, 3, [])
sage: E.selmer_rank() # uses mwrank
1
```

`sage.schemes.elliptic_curves.ell_rational_field.cremona_curves(conductors)`

Return iterator over all known curves (in database) with conductor in the list of conductors.

EXAMPLES:

```
sage: [(E.label(), E.rank()) for E in cremona_curves(srange(35,40))]
[('35a1', 0),
 ('35a2', 0),
 ('35a3', 0),
 ('36a1', 0),
 ('36a2', 0),
 ('36a3', 0),
 ('36a4', 0),
 ('37a1', 1),
 ('37b1', 0),
 ('37b2', 0),
 ('37b3', 0),
 ('38a1', 0),
 ('38a2', 0),
 ('38a3', 0),
 ('38b1', 0),
 ('38b2', 0),
 ('39a1', 0),
 ('39a2', 0),
 ('39a3', 0),
 ('39a4', 0)]
```

`sage.schemes.elliptic_curves.ell_rational_field.cremona_optimal_curves(conductors)`  
 Return iterator over all known optimal curves (in database) with conductor in the list of conductors.

EXAMPLES:

```
sage: [(E.label(), E.rank()) for E in cremona_optimal_curves(srange(35,40))]
[('35a1', 0),
 ('36a1', 0),
 ('37a1', 1),
 ('37b1', 0),
 ('38a1', 0),
 ('38b1', 0),
 ('39a1', 0)]
```

There is one case – 990h3 – when the optimal curve isn’t labeled with a 1:

```
sage: [e.cremona_label() for e in cremona_optimal_curves([990])]
['990a1', '990b1', '990c1', '990d1', '990e1', '990f1', '990g1', '990h3', '990i1',
↪ '990j1', '990k1', '990l1']
```

`sage.schemes.elliptic_curves.ell_rational_field.elliptic_curve_congruence_graph(curves)`  
 Return the congruence graph for this set of elliptic curves.

INPUT:

- *curves* – a list of elliptic curves

OUTPUT:

The graph with each curve as a vertex (labelled by its Cremona label) and an edge from  $E$  to  $F$  labelled  $p$  if and only if  $E$  is congruent to  $F \bmod p$

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_rational_field import elliptic_curve_
↪ congruence_graph
sage: curves = list(cremona_optimal_curves([11..30]))
sage: G = elliptic_curve_congruence_graph(curves)
sage: G
Graph on 12 vertices
```

`sage.schemes.elliptic_curves.ell_rational_field.integral_points_with_bounded_mw_coeffs(E, mw_base, N, x_bound)`

Return the set of integers  $x$  which are  $x$ -coordinates of points on the curve  $E$  which are linear combinations of the generators (basis and torsion points) with coefficients bounded by  $N$ .

INPUT:

- $E$  - an elliptic curve
- *mw\_base* - a list of points on  $E$  (generators)
- $N$  - a positive integer (bound on coefficients)
- *x\_bound* - a positive real number (upper bound on size of  $x$ -coordinates)

OUTPUT:

(list) list of integral points on  $E$  which are linear combinations of the given points with coefficients bounded by  $N$  in absolute value.



### 15.11.2 Tables of elliptic curves of given rank

The default database of curves contains the following data:

Rank	Number of curves	Maximal conductor
0	30427	9999
1	31871	9999
2	2388	9999
3	836	119888
4	10	1175648
5	5	37396136
6	5	6663562874
7	5	896913586322
8	6	457532830151317
9	7	~9.612839e+21
10	6	~1.971057e+21
11	6	~1.803406e+24
12	1	~2.696017e+29
14	1	~3.627533e+37
15	1	~1.640078e+56
17	1	~2.750021e+56
19	1	~1.373776e+65
20	1	~7.381324e+73
21	1	~2.611208e+85
22	1	~2.272064e+79
23	1	~1.139647e+89
24	1	~3.257638e+95
28	1	~3.455601e+141

Note that lists for  $r \geq 4$  are not exhaustive; there may well be curves of the given rank with conductor less than the listed maximal conductor, which are not included in the tables.

AUTHORS: - William Stein (2007-10-07): initial version - Simon Spicer (2014-10-24): Added examples of more high-rank curves

See also the functions `cremona_curves()` and `cremona_optimal_curves()` which enable easy looping through the Cremona elliptic curve database.

**class** `sage.schemes.elliptic_curves.ec_database.EllipticCurves`

**rank** (*rank*, *tors*=0, *n*=10, *labels*=False)

Return a list of at most  $n$  non-isogenous curves with given rank and torsion order.

INPUT:

- `rank` (int) – the desired rank
- `tors` (int, default 0) – the desired torsion order (ignored if 0)
- `n` (int, default 10) – the maximum number of curves returned.
- `labels` (bool, default False) – if True, return Cremona labels instead of curves.

OUTPUT:

(list) A list at most  $n$  of elliptic curves of required rank.

EXAMPLES:

```
sage: elliptic_curves.rank(n=5, rank=3, tors=2, labels=True)
['59450i1', '59450i2', '61376c1', '61376c2', '65481c1']
```

```
sage: elliptic_curves.rank(n=5, rank=0, tors=5, labels=True)
['11a1', '11a3', '38b1', '50b1', '50b2']
```

```
sage: elliptic_curves.rank(n=5, rank=1, tors=7, labels=True)
['574i1', '4730k1', '6378c1']
```

```
sage: e = elliptic_curves.rank(6)[0]; e.ainvs(), e.conductor()
((1, 1, 0, -2582, 48720), 5187563742)
sage: e = elliptic_curves.rank(7)[0]; e.ainvs(), e.conductor()
((0, 0, 0, -10012, 346900), 382623908456)
sage: e = elliptic_curves.rank(8)[0]; e.ainvs(), e.conductor()
((1, -1, 0, -106384, 13075804), 249649566346838)
```

For large conductors, the labels are not known:

```
sage: L = elliptic_curves.rank(6, n=3); L
[Elliptic Curve defined by y^2 + x*y = x^3 + x^2 - 2582*x + 48720 over_
↪Rational Field,
Elliptic Curve defined by y^2 + y = x^3 - 7077*x + 235516 over Rational_
↪Field,
Elliptic Curve defined by y^2 + x*y = x^3 - x^2 - 2326*x + 43456 over_
↪Rational Field]
sage: L[0].cremona_label()
Traceback (most recent call last):
...
LookupError: Cremona database does not contain entry for Elliptic Curve_
↪defined by y^2 + x*y = x^3 + x^2 - 2582*x + 48720 over Rational Field
sage: elliptic_curves.rank(6, n=3, labels=True)
[]
```

### 15.11.3 Elliptic curves over number fields

An elliptic curve  $E$  over a number field  $K$  can be given by a Weierstrass equation whose coefficients lie in  $K$  or by using `base_extend` on an elliptic curve defined over a subfield.

One major difference to elliptic curves over  $\mathbb{Q}$  is that there might not exist a global minimal equation over  $K$ , when  $K$  does not have class number one. Another difference is the lack of understanding of modularity for general elliptic curves over general number fields.

Currently Sage can obtain local information about  $E/K_v$  for finite places  $v$ , it has an interface to Denis Simon's script for 2-descent, it can compute the torsion subgroup of the Mordell-Weil group  $E(K)$ , and it can work with isogenies defined over  $K$ .

EXAMPLES:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([0,4+i])
sage: E.discriminant()
-3456*i - 6480
sage: P= E([i,2])
sage: P+P
(-2*i + 9/16 : -9/4*i - 101/64 : 1)
```

```

sage: E.has_good_reduction(2+i)
True
sage: E.local_data(4+i)
Local data at Fractional ideal (i + 4):
Reduction type: bad additive
Local minimal model: Elliptic Curve defined by  $y^2 = x^3 + (i+4)$  over Number Field in  $\sqrt{-1}$ 
↪ i with defining polynomial  $x^2 + 1$ 
Minimal discriminant valuation: 2
Conductor exponent: 2
Kodaira Symbol: II
Tamagawa Number: 1
sage: E.tamagawa_product_bsd()
1

```

```

sage: E.simon_two_descent()
(1, 1, [(i : 2 : 1)])

```

```

sage: E.torsion_order()
1

```

```

sage: E.isogenies_prime_degree(3)
[Isogeny of degree 3 from Elliptic Curve defined by  $y^2 = x^3 + (i+4)$  over Number Field in  $\sqrt{-1}$ 
↪ i with defining polynomial  $x^2 + 1$  to Elliptic Curve defined by  $y^2 = x^3 + (14*i+35)$ 
↪ over Number Field in  $\sqrt{-1}$  with defining polynomial  $x^2 + 1$ ]

```

#### AUTHORS:

- Robert Bradshaw 2007
- John Cremona
- Chris Wuthrich

#### REFERENCE:

- [Sil] Silverman, Joseph H. The arithmetic of elliptic curves. Second edition. Graduate Texts in Mathematics, 106. Springer, 2009.
- [Sil2] Silverman, Joseph H. Advanced topics in the arithmetic of elliptic curves. Graduate Texts in Mathematics, 151. Springer, 1994.

**class** sage.schemes.elliptic\_curves.ell\_number\_field.**EllipticCurve\_number\_field**(*K*, *ainvs*)

Bases: *sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field*

Elliptic curve over a number field.

#### EXAMPLES:

```

sage: K.<i>=NumberField(x^2+1)
sage: EllipticCurve([i, i - 1, i + 1, 24*i + 15, 14*i + 35])
Elliptic Curve defined by  $y^2 + i*x*y + (i+1)*y = x^3 + (i-1)*x^2 + (24*i+15)*x + (14*i+35)$ 
↪ over Number Field in  $\sqrt{-1}$  with defining polynomial  $x^2 + 1$ 

```

#### **base\_extend**(*R*)

Return the base extension of self to *R*.

#### EXAMPLES:

```

sage: E = EllipticCurve('11a3')
sage: K = QuadraticField(-5, 'a')
sage: E.base_extend(K)
Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x^2$  over Number Field in  $a$ 
↪with defining polynomial  $x^2 + 5$ 

```

Check that non-torsion points are remembered when extending the base field (see [trac ticket #16034](#)):

```

sage: E = EllipticCurve([1, 0, 1, -1751, -31352])
sage: K.<d> = QuadraticField(5)
sage: E.gens()
[(52 : 111 : 1)]
sage: EK = E.base_extend(K)
sage: EK.gens()
[(52 : 111 : 1)]

```

### **cm\_discriminant()**

Returns the CM discriminant of the  $j$ -invariant of this curve, or 0.

OUTPUT:

An integer  $D$  which is either 0 if this curve  $E$  does not have Complex Multiplication (CM), or an imaginary quadratic discriminant if  $j(E)$  is the  $j$ -invariant of the order with discriminant  $D$ .

---

**Note:** If  $E$  has CM but the discriminant  $D$  is not a square in the base field  $K$  then the extra endomorphisms will not be defined over  $K$ . See also [has\\_rational\\_cm\(\)](#).

---

EXAMPLES:

```

sage: EllipticCurve(j=0).cm_discriminant()
-3
sage: EllipticCurve(j=1).cm_discriminant()
Traceback (most recent call last):
...
ValueError: Elliptic Curve defined by  $y^2 + x*y = x^3 + 36*x + 3455$  over
↪Rational Field does not have CM
sage: EllipticCurve(j=1728).cm_discriminant()
-4
sage: EllipticCurve(j=8000).cm_discriminant()
-8
sage: K.<a> = QuadraticField(5)
sage: EllipticCurve(j=282880*a + 632000).cm_discriminant()
-20
sage: K.<a> = NumberField(x^3 - 2)
sage: EllipticCurve(j=31710790944000*a^2 + 39953093016000*a + 50337742902000).
↪cm_discriminant()
-108

```

### **conductor()**

Returns the conductor of this elliptic curve as a fractional ideal of the base field.

OUTPUT:

(fractional ideal) The conductor of the curve.

EXAMPLES:

```

sage: K.<i>=NumberField(x^2+1)
sage: EllipticCurve([i, i - 1, i + 1, 24*i + 15, 14*i + 35]).conductor()
Fractional ideal (21*i - 3)
sage: K.<a>=NumberField(x^2-x+3)
sage: EllipticCurve([1 + a, -1 + a, 1 + a, -11 + a, 5 - 9*a]).conductor()
Fractional ideal (-6*a)

```

A not so well known curve with everywhere good reduction:

```

sage: K.<a>=NumberField(x^2-38)
sage: E=EllipticCurve([0,0,0, 21796814856932765568243810*a -
↳134364590724198567128296995, 121774567239345229314269094644186997594*a -
↳750668847495706904791115375024037711300])
sage: E.conductor()
Fractional ideal (1)

```

An example which used to fail (see [trac ticket #5307](#)):

```

sage: K.<w>=NumberField(x^2+x+6)
sage: E=EllipticCurve([w,-1,0,-w-6,0])
sage: E.conductor()
Fractional ideal (86304, w + 5898)

```

An example raised in [trac ticket #11346](#):

```

sage: K.<g> = NumberField(x^2 - x - 1)
sage: E1 = EllipticCurve(K, [0,0,0,-1/48,-161/864])
sage: [(p.smallest_integer(),e) for p,e in E1.conductor().factor()]
[(2, 4), (3, 1), (5, 1)]

```

**division\_field**(*p*, *names*, *map=False*, *\*\*kws*)

Given an elliptic curve over a number field  $F$  and a prime number  $p$ , construct the field  $F(E[p])$ .

INPUT:

- $p$  – a prime number (an element of  $\mathbb{Z}$ )
- *names* – a variable name for the number field
- *map* – (default: `False`) also return an embedding of the `base_field()` into the resulting field.
- *kws* – additional keywords passed to `sage.rings.number_field.splitting_field.splitting_field()`.

OUTPUT:

If *map* is `False`, the division field as an absolute number field. If *map* is `True`, a tuple  $(K, \phi)$  where  $\phi$  is an embedding of the base field in the division field  $K$ .

**Warning:** This takes a very long time when the degree of the division field is large (e.g. when  $p$  is large or when the Galois representation is surjective). The `simplify` flag also has a big influence on the running time: sometimes `simplify=False` is faster, sometimes `simplify=True` (the default) is faster.

EXAMPLES:

The 2-division field is the same as the splitting field of the 2-division polynomial (therefore, it has degree 1, 2, 3 or 6):

```

sage: E = EllipticCurve('15a1')
sage: K.<b> = E.division_field(2); K
Number Field in b with defining polynomial x
sage: E = EllipticCurve('14a1')
sage: K.<b> = E.division_field(2); K
Number Field in b with defining polynomial x^2 + 5*x + 92
sage: E = EllipticCurve('196b1')
sage: K.<b> = E.division_field(2); K
Number Field in b with defining polynomial x^3 + x^2 - 114*x - 127
sage: E = EllipticCurve('19a1')
sage: K.<b> = E.division_field(2); K
Number Field in b with defining polynomial x^6 + 10*x^5 + 24*x^4 - 212*x^3 +
↪ 1364*x^2 + 24072*x + 104292

```

For odd primes  $p$ , the division field is either the splitting field of the  $p$ -division polynomial, or a quadratic extension of it.

```

sage: E = EllipticCurve('50a1')
sage: F.<a> = E.division_polynomial(3).splitting_field(simplify_all=True); F
Number Field in a with defining polynomial x^6 - 3*x^5 + 4*x^4 - 3*x^3 - 2*x^
↪ 2 + 3*x + 3
sage: K.<b> = E.division_field(3, simplify_all=True); K
Number Field in b with defining polynomial x^6 - 3*x^5 + 4*x^4 - 3*x^3 - 2*x^
↪ 2 + 3*x + 3

```

If we take any quadratic twist, the splitting field of the 3-division polynomial remains the same, but the 3-division field becomes a quadratic extension:

```

sage: E = E.quadratic_twist(5) # 50b3
sage: F.<a> = E.division_polynomial(3).splitting_field(simplify_all=True); F
Number Field in a with defining polynomial x^6 - 3*x^5 + 4*x^4 - 3*x^3 - 2*x^
↪ 2 + 3*x + 3
sage: K.<b> = E.division_field(3, simplify_all=True); K
Number Field in b with defining polynomial x^12 - 3*x^11 + 8*x^10 - 15*x^9 +
↪ 30*x^8 - 63*x^7 + 109*x^6 - 144*x^5 + 150*x^4 - 120*x^3 + 68*x^2 - 24*x + 4

```

Try another quadratic twist, this time over a subfield of  $F$ :

```

sage: G.<c>,_,_ = F.subfields(3)[0]
sage: E = E.base_extend(G).quadratic_twist(c); E
Elliptic Curve defined by y^2 = x^3 + 5*a0*x^2 + (-200*a0^2)*x + (-42000*a0^
↪ 2+42000*a0+126000) over Number Field in a0 with defining polynomial x^3 -
↪ 3*x^2 + 3*x + 9
sage: K.<b> = E.division_field(3, simplify_all=True); K
Number Field in b with defining polynomial x^12 - 10*x^10 + 55*x^8 - 60*x^6 +
↪ 75*x^4 + 1350*x^2 + 2025

```

Some higher-degree examples:

```

sage: E = EllipticCurve('11a1')
sage: K.<b> = E.division_field(2); K
Number Field in b with defining polynomial x^6 + 2*x^5 - 48*x^4 - 436*x^3 +
↪ 1668*x^2 + 28792*x + 73844
sage: K.<b> = E.division_field(3); K # long time (3s on sage.math, 2014)
Number Field in b with defining polynomial x^48 ...
sage: K.<b> = E.division_field(5); K
Number Field in b with defining polynomial x^4 - x^3 + x^2 - x + 1
sage: E.division_field(5, 'b', simplify=False)

```

```

Number Field in b with defining polynomial x^4 + x^3 + 11*x^2 + 41*x + 101
sage: E.base_extend(K).torsion_subgroup() # long time (2s on sage.math, 2014)
Torsion Subgroup isomorphic to Z/5 + Z/5 associated to the Elliptic Curve
↳ defined by y^2 + y = x^3 + (-1)*x^2 + (-10)*x + (-20) over Number Field in
↳ b with defining polynomial x^4 - x^3 + x^2 - x + 1

sage: E = EllipticCurve('27a1')
sage: K.<b> = E.division_field(3); K
Number Field in b with defining polynomial x^2 + 3*x + 9
sage: K.<b> = E.division_field(2); K
Number Field in b with defining polynomial x^6 + 6*x^5 + 24*x^4 - 52*x^3 -
↳ 228*x^2 + 744*x + 3844
sage: K.<b> = E.division_field(2, simplify_all=True); K
Number Field in b with defining polynomial x^6 - 3*x^5 + 5*x^3 - 3*x + 1
sage: K.<b> = E.division_field(5); K # long time (4s on sage.math, 2014)
Number Field in b with defining polynomial x^48 ...
sage: K.<b> = E.division_field(7); K # long time (8s on sage.math, 2014)
Number Field in b with defining polynomial x^72 ...

```

Over a number field:

```

sage: R.<x> = PolynomialRing(QQ)
sage: K.<i> = NumberField(x^2 + 1)
sage: E = EllipticCurve([0,0,0,0,i])
sage: L.<b> = E.division_field(2); L
Number Field in b with defining polynomial x^4 - x^2 + 1
sage: L.<b>, phi = E.division_field(2, map=True); phi
Ring morphism:
  From: Number Field in i with defining polynomial x^2 + 1
  To:   Number Field in b with defining polynomial x^4 - x^2 + 1
  Defn: i |--> -b^3
sage: L.<b>, phi = E.division_field(3, map=True)
sage: L
Number Field in b with defining polynomial x^24 - 6*x^22 - 12*x^21 - 21*x^20
↳ + 216*x^19 + 48*x^18 + 804*x^17 + 1194*x^16 - 13488*x^15 + 21222*x^14 +
↳ 44196*x^13 - 47977*x^12 - 102888*x^11 + 173424*x^10 - 172308*x^9 + 302046*x^
↳ 8 + 252864*x^7 - 931182*x^6 + 180300*x^5 + 879567*x^4 - 415896*x^3 +
↳ 1941012*x^2 + 650220*x + 443089
sage: phi
Ring morphism:
  From: Number Field in i with defining polynomial x^2 + 1
  To:   Number Field in b with defining polynomial x^24 ...
  Defn: i |--> -215621657062634529/183360797284413355040732*b^23 ...

```

AUTHORS:

- Jeroen Demeyer (2014-01-06): [trac ticket #11905](#), use `splitting_field` method, moved from `gal_reps.py`, make it work over number fields.

### `galois_representation()`

The compatible family of the Galois representation attached to this elliptic curve.

Given an elliptic curve  $E$  over a number field  $K$  and a rational prime number  $p$ , the  $p^n$ -torsion  $E[p^n]$  points of  $E$  is a representation of the absolute Galois group of  $K$ . As  $n$  varies we obtain the Tate module  $T_p E$  which is a representation of  $G_K$  on a free  $\mathbb{Z}_p$ -module of rank 2. As  $p$  varies the representations are compatible.

EXAMPLES:

```

sage: K = NumberField(x**2 + 1, 'a')
sage: E = EllipticCurve('11a1').change_ring(K)
sage: rho = E.galois_representation()
sage: rho
Compatible family of Galois representations associated to the Elliptic Curve
↳ defined by  $y^2 + y = x^3 + (-1)x^2 + (-10)x + (-20)$  over Number Field in
↳  $a$  with defining polynomial  $x^2 + 1$ 
sage: rho.is_surjective(3)
True
sage: rho.is_surjective(5) # long time (4s on sage.math, 2014)
False
sage: rho.non_surjective()
[5]

```

**gens** (*\*\*kws*)

Return some points of infinite order on this elliptic curve.

Contrary to what the name of this method suggests, the points it returns do not always generate a subgroup of full rank in the Mordell-Weil group, nor are they necessarily linearly independent. Moreover, the number of points can be smaller or larger than what one could expect after calling [rank\(\)](#) or [rank\\_bounds\(\)](#).

---

**Note:** The optional parameters control the Simon two descent algorithm; see the documentation of [simon\\_two\\_descent\(\)](#) for more details.

---

INPUT:

- `verbose` – 0, 1, 2, or 3 (default: 0), the verbosity level
- `lim1` – (default: 2) limit on trivial points on quartics
- `lim3` – (default: 4) limit on points on ELS quartics
- `limtriv` – (default: 2) limit on trivial points on elliptic curve
- `maxprob` – (default: 20)
- `limbigprime` – (default: 30) to distinguish between small and large prime numbers. Use probabilistic tests for large primes. If 0, don't use probabilistic tests.
- `known_points` – (default: None) list of known points on the curve

OUTPUT:

A set of points of infinite order given by the Simon two-descent.

---

**Note:** For non-quadratic number fields, this code does return, but it takes a long time.

---

EXAMPLES:

```

sage: K.<a> = NumberField(x^2 + 23, 'a')
sage: E = EllipticCurve(K, [0, 0, 0, 101, 0])
sage: E.gens()
[(23831509/8669448*a - 2867471/8669448 : 76507317707/18049790736*a -
↳ 424166479633/18049790736 : 1),
 (-2031032029/969232392*a + 58813561/969232392 : -15575984630401/
↳ 21336681877488*a + 451041199309/21336681877488 : 1),
 (-186948623/4656964 : 549438861195/10049728312*a : 1)]

```



It can happen that no points are found if the height bounds used in the search are too small (see [trac ticket #10745](#)):

```
sage: K.<y> = NumberField(x^4 + x^2 - 7)
sage: E = EllipticCurve(K, [1, 0, 5*y^2 + 16, 0, 0])
sage: E.gens(lim1=1, lim3=1)
[]
sage: E.rank(), E.gens(lim3=12) # long time (about 4s)
(1,
 [(369/25*y^3 + 539/25*y^2 + 1178/25*y + 1718/25 : -29038/125*y^3 - 43003/
 ↪ 125*y^2 - 92706/125*y - 137286/125 : 1)])
```

Here is a curve of rank 2:

```
sage: K.<t> = NumberField(x^2-17)
sage: E = EllipticCurve(K, [-4,0])
sage: E.gens()
[(-1/2*t + 1/2 : -1/2*t + 1/2 : 1), (-t + 3 : -2*t + 10 : 1)]
sage: E.rank()
2
```

Test that points of finite order are not included (see [trac ticket #13593](#)):

```
sage: E = EllipticCurve("17a3")
sage: K.<t> = NumberField(x^2+3)
sage: EK = E.base_extend(K)
sage: EK.rank()
0
sage: EK.gens()
[]
```

#### IMPLEMENTATION:

For curves over quadratic fields which are base-changes from  $\mathbb{Q}$ , we delegate the work to `gens_quadratic()` where methods over  $\mathbb{Q}$  suffice. Otherwise, we use Denis Simon's PARI/GP scripts from <http://www.math.unicaen.fr/~simon/>.

#### `gens_quadratic(**kws)`

Return generators for the Mordell-Weil group modulo torsion, for a curve which is a base change from  $\mathbb{Q}$  to a quadratic field.

#### EXAMPLES:

```
sage: E = EllipticCurve([1,2,3,40,50])
sage: E.conductor()
2123582
sage: E.gens()
[(5 : 17 : 1)]
sage: K.<i> = QuadraticField(-1)
sage: EK = E.change_ring(K)
sage: EK.gens_quadratic()
[(5 : 17 : 1), (-13 : 48*i + 5 : 1)]

sage: E.change_ring(QuadraticField(3, 'a')).gens_quadratic()
[(5 : 17 : 1), (-1 : 2*a - 1 : 1), (11/4 : 33/4*a - 23/8 : 1)]

sage: K.<a> = QuadraticField(-7)
sage: E = EllipticCurve([0,0,0,197,0])
sage: E.conductor()
```

```

2483776
sage: E.gens()
[(47995604297578081/7389879786648100 : -25038161802544048018837479/
↪ 635266655830129794121000 : 1)]
sage: K.<a> = QuadraticField(7)
sage: E.change_ring(K).gens_quadratic()
[(-1209642055/59583566*a + 1639995844/29791783 : -377240626321899/
↪ 1720892553212*a + 138577803462855/245841793316 : 1),
(1/28 : 393/392*a : 1),
(-61*a + 162 : 1098*a - 2916 : 1)]

sage: E = EllipticCurve([1, a])
sage: E.gens_quadratic()
Traceback (most recent call last):
...
ValueError: gens_quadratic() requires the elliptic curve to be a base change
↪ from Q

```

**global\_integral\_model()**

Return a model of self which is integral at all primes.

**EXAMPLES:**

```

sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([i/5,i/5,i/5,i/5])
sage: P1,P2 = K.primes_above(5)
sage: E.global_integral_model()
Elliptic Curve defined by y^2 + (-i)*x*y + (-25*i)*y = x^3 + 5*i*x^2 +
↪ 125*i*x + 3125*i over Number Field in i with defining polynomial x^2 + 1

```

trac ticket #7935:

```

sage: K.<a> = NumberField(x^2-38)
sage: E = EllipticCurve([a,1/2])
sage: E.global_integral_model()
Elliptic Curve defined by y^2 = x^3 + 1444*a*x + 27436 over Number Field in a
↪ with defining polynomial x^2 - 38

```

trac ticket #9266:

```

sage: K.<s> = NumberField(x^2-5)
sage: w = (1+s)/2
sage: E = EllipticCurve(K,[2,w])
sage: E.global_integral_model()
Elliptic Curve defined by y^2 = x^3 + 2*x + (1/2*s+1/2) over Number Field in
↪ s with defining polynomial x^2 - 5

```

trac ticket #12151:

```

sage: K.<v> = NumberField(x^2 + 161*x - 150)
sage: E = EllipticCurve([25105/216*v - 3839/36, 634768555/7776*v - 98002625/
↪ 1296, 634768555/7776*v - 98002625/1296, 0, 0])
sage: E.global_integral_model()
Elliptic Curve defined by y^2 + (2094779518028859*v-1940492905300351)*x*y +
↪ (477997268472544193101178234454165304071127500*v-
↪ 442791377441346852919930773849502871958097500)*y = x^3 +
↪ (26519784690047674853185542622500*v-24566525306469707225840460652500)*x^2
↪ over Number Field in v with defining polynomial x^2 + 161*x - 150

```

trac ticket #14476:

```
sage: R.<t> = QQ[]
sage: K.<g> = NumberField(t^4 - t^3 - 3*t^2 - t + 1)
sage: E = EllipticCurve([-43/625*g^3 + 14/625*g^2 - 4/625*g + 706/625, -4862/
↪78125*g^3 - 4074/78125*g^2 - 711/78125*g + 10304/78125, -4862/78125*g^3 -
↪4074/78125*g^2 - 711/78125*g + 10304/78125, 0,0])
sage: E.global_integral_model()
Elliptic Curve defined by y^2 + (15*g^3-48*g-42)*x*y + (-111510*g^3-162162*g^
↪2-44145*g+37638)*y = x^3 + (-954*g^3-1134*g^2+81*g+576)*x^2 over Number
↪Field in g with defining polynomial t^4 - t^3 - 3*t^2 - t + 1
```

**global\_minimal\_model** (*proof=None, semi\_global=False*)

Returns a model of self that is integral, and minimal.

---

**Note:** Over fields of class number greater than 1, a global minimal model may not exist. If it does not, set the parameter `semi_global` to `True` to obtain a model minimal at all but one prime.

---

INPUT:

- `proof` – whether to only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the flag are in number fields.
- `semi_global` (boolean, default `False`) – if there is no global minimal model, return a semi-global minimal model (minimal at all but one prime) instead, if `True`; raise an error if `False`. No effect if a global minimal model exists.

OUTPUT:

A global integral and minimal model, or an integral model minimal at all but one prime if there is no global minimal model and the flag `semi_global` is `True`.

EXAMPLES:

```
sage: K.<a> = NumberField(x^2-38)
sage: E = EllipticCurve([0,0,0, 21796814856932765568243810*a -
↪134364590724198567128296995, 121774567239345229314269094644186997594*a -
↪750668847495706904791115375024037711300])
sage: E2 = E.global_minimal_model()
sage: E2
Elliptic Curve defined by y^2 + a*x*y + (a+1)*y = x^3 + (a+1)*x^2 +
↪(4*a+15)*x + (4*a+21) over Number Field in a with defining polynomial x^2 -
↪38
sage: E2.local_data()
[]
```

See trac ticket #11347:

```
sage: K.<g> = NumberField(x^2 - x - 1)
sage: E = EllipticCurve(K, [0,0,0,-1/48,161/864]).integral_model().global_
↪minimal_model(); E
Elliptic Curve defined by y^2 + x*y + y = x^3 + x^2 over Number Field in g
↪with defining polynomial x^2 - x - 1
sage: [(p.norm(), e) for p, e in E.conductor().factor()]
[(9, 1), (5, 1)]
sage: [(p.norm(), e) for p, e in E.discriminant().factor()]
[(-5, 2), (9, 1)]
```

See [trac ticket #14472](#), this used not to work over a relative extension:

```
sage: K1.<w> = NumberField(x^2+x+1)
sage: m = polygen(K1)
sage: K2.<v> = K1.extension(m^2-w+1)
sage: E = EllipticCurve([0*v,-432])
sage: E.global_minimal_model()
Elliptic Curve defined by  $y^2 + y = x^3$  over Number Field in  $v$  with defining
↪ polynomial  $x^2 - w + 1$  over its base field
```

See [trac ticket #18662](#): for fields of class number greater than 1, even when global minimal models did exist, their computation was not implemented. Now it is:

```
sage: K.<a> = NumberField(x^2-10)
sage: K.class_number()
2
sage: E = EllipticCurve([0,0,0,-186408*a - 589491, 78055704*a + 246833838])
sage: E.discriminant().norm()
16375845905239507992576
sage: E.discriminant().norm().factor()
2^31 * 3^27
sage: E.has_global_minimal_model()
True
sage: Emin = E.global_minimal_model(); Emin
Elliptic Curve defined by  $y^2 + (a+1)*x*y + (a+1)*y = x^3 + (-a)*x^2 + (a-12)*x + (-2*a+2)$  over Number Field in  $a$  with defining polynomial  $x^2 - 10$ 
sage: Emin.discriminant().norm()
3456
sage: Emin.discriminant().norm().factor()
2^7 * 3^3
```

If there is no global minimal model, this method will raise an error unless you set the parameter `semi_global` to `True`:

```
sage: K.<a> = NumberField(x^2-10)
sage: K.class_number()
2
sage: E = EllipticCurve([a,a,0,3*a+8,4*a+3])
sage: E.has_global_minimal_model()
False
sage: E.global_minimal_model()
Traceback (most recent call last):
...
ValueError: Elliptic Curve defined by  $y^2 + a*x*y = x^3 + a*x^2 + (3*a+8)*x + (4*a+3)$  over Number Field in  $a$  with defining polynomial  $x^2 - 10$  has no
↪ global minimal model! For a semi-global minimal model use semi_global=True
sage: E.global_minimal_model(semi_global=True)
Elliptic Curve defined by  $y^2 + a*x*y = x^3 + a*x^2 + (3*a+8)*x + (4*a+3)$ 
↪ over Number Field in  $a$  with defining polynomial  $x^2 - 10$ 
```

An example of a curve with everywhere good reduction but which has no model with unit discriminant:

```
sage: K.<a> = NumberField(x^2-x-16)
sage: K.class_number()
2
sage: E = EllipticCurve([0,0,0,-15221331*a - 53748576, -79617688290*a -
↪ 281140318368])
sage: Emin = E.global_minimal_model(semi_global=True)
```

```

sage: Emin.ainvs()
(a, a - 1, a, 605*a - 2728, 15887*a - 71972)
sage: Emin.discriminant()
-17*a - 16
sage: Emin.discriminant().norm()
-4096
sage: Emin.minimal_discriminant_ideal()
Fractional ideal (1)
sage: E.conductor()
Fractional ideal (1)

```

**global\_minimality\_class()**

Returns the obstruction to this curve having a global minimal model.

**OUTPUT:**

An ideal class of the base number field, which is trivial if and only if the elliptic curve has a global minimal model, and which can be used to find global and semi-global minimal models.

**EXAMPLES:**

A curve defined over a field of class number 2 with no global minimal model was a nontrivial minimality class:

```

sage: K.<a> = NumberField(x^2-10)
sage: K.class_number()
2
sage: E = EllipticCurve([0, 0, 0, -22500, 750000*a])
sage: E.global_minimality_class()
Fractional ideal class (10, 5*a)
sage: E.global_minimality_class().order()
2

```

Over the same field, a curve defined by a non-minimal model has trivial class, showing that a global minimal model does exist:

```

sage: K.<a> = NumberField(x^2-10)
sage: E = EllipticCurve([0, 0, 0, 4536*a+14148, -163728*a- 474336])
sage: E.is_global_minimal_model()
False
sage: E.global_minimality_class()
Trivial principal fractional ideal class

```

Over a field of class number 1 the result is always the trivial class:

```

sage: K.<a> = NumberField(x^2-5)
sage: E = EllipticCurve([0, 0, 0, K(16), K(64)])
sage: E.global_minimality_class()
Trivial principal fractional ideal class

sage: E = EllipticCurve([0, 0, 0, 16, 64])
sage: E.base_field()
Rational Field
sage: E.global_minimality_class()
1

```

**has\_additive\_reduction(*P*)**

Return True if this elliptic curve has (bad) additive reduction at the prime *P*.

INPUT:

- $P$  – a prime ideal of the base field of self, or a field element generating such an ideal.

OUTPUT:

(bool) True if the curve has additive reduction at  $P$ , else False.

EXAMPLES:

```
sage: E=EllipticCurve('27a1')
sage: [(p,E.has_additive_reduction(p)) for p in prime_range(15)]
[(2, False), (3, True), (5, False), (7, False), (11, False), (13, False)]

sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.has_additive_reduction(p)) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False),
 (Fractional ideal (2*a + 1), True)]
```

**has\_bad\_reduction( $P$ )**

Return True if this elliptic curve has bad reduction at the prime  $P$ .

INPUT:

- $P$  – a prime ideal of the base field of self, or a field element generating such an ideal.

OUTPUT:

(bool) True if the curve has bad reduction at  $P$ , else False.

---

**Note:** This requires determining a local integral minimal model; we do not just check that the discriminant of the current model has valuation zero.

---

EXAMPLES:

```
sage: E=EllipticCurve('14a1')
sage: [(p,E.has_bad_reduction(p)) for p in prime_range(15)]
[(2, True), (3, False), (5, False), (7, True), (11, False), (13, False)]

sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.has_bad_reduction(p)) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False),
 (Fractional ideal (2*a + 1), True)]
```

**has\_cm()**

Returns whether or not this curve has a CM  $j$ -invariant.

OUTPUT:

True if this curve has CM over the algebraic closure of the base field, otherwise False. See also `cm_discriminant()` and `has_rational_cm()`.

---

**Note:** Even if  $E$  has CM in this sense (that its  $j$ -invariant is a CM  $j$ -invariant), if the associated negative discriminant  $D$  is not a square in the base field  $K$ , the extra endomorphisms will not be defined over  $K$ .

---

See also the method `has_rational_cm()` which tests whether  $E$  has extra endomorphisms defined over  $K$  or a given extension of  $K$ .

EXAMPLES:

```
sage: EllipticCurve(j=0).has_cm()
True
sage: EllipticCurve(j=1).has_cm()
False
sage: EllipticCurve(j=1728).has_cm()
True
sage: EllipticCurve(j=8000).has_cm()
True
sage: K.<a> = QuadraticField(5)
sage: EllipticCurve(j=282880*a + 632000).has_cm()
True
sage: K.<a> = NumberField(x^3 - 2)
sage: EllipticCurve(j=31710790944000*a^2 + 39953093016000*a + 50337742902000).
↪has_cm()
True
```

**has\_global\_minimal\_model()**

Returns whether this elliptic curve has a global minimal model.

OUTPUT:

Boolean, True iff a global minimal model exists, i.e. an integral model which is minimal at every prime.

EXAMPLES:

```
sage: K.<a> = NumberField(x^2-10)
sage: E = EllipticCurve([0,0,0,4536*a+14148,-163728*a-474336])
sage: E.is_global_minimal_model()
False
sage: E.has_global_minimal_model()
True
```

**has\_good\_reduction( $P$ )**

Return True if this elliptic curve has good reduction at the prime  $P$ .

INPUT:

- $P$  – a prime ideal of the base field of self, or a field element generating such an ideal.

OUTPUT:

(bool) – True if the curve has good reduction at  $P$ , else False.

**Note:** This requires determining a local integral minimal model; we do not just check that the discriminant of the current model has valuation zero.

EXAMPLES:

```
sage: E=EllipticCurve('14a1')
sage: [(p,E.has_good_reduction(p)) for p in prime_range(15)]
[(2, False), (3, True), (5, True), (7, False), (11, True), (13, True)]
sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
```

```

sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.has_good_reduction(p)) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), True),
 (Fractional ideal (2*a + 1), False)]

```

**has\_multiplicative\_reduction(*P*)**

Return True if this elliptic curve has (bad) multiplicative reduction at the prime *P*.

---

**Note:** See also `has_split_multiplicative_reduction()` and `has_nonsplit_multiplicative_reduction()`.

---

INPUT:

- *P* – a prime ideal of the base field of self, or a field element generating such an ideal.

OUTPUT:

(bool) True if the curve has multiplicative reduction at *P*, else False.

EXAMPLES:

```

sage: E=EllipticCurve('14a1')
sage: [(p,E.has_multiplicative_reduction(p)) for p in prime_range(15)]
[(2, True), (3, False), (5, False), (7, True), (11, False), (13, False)]

sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.has_multiplicative_reduction(p)) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False), (Fractional ideal (2*a + 1),
↪False)]

```

**has\_nonsplit\_multiplicative\_reduction(*P*)**

Return True if this elliptic curve has (bad) non-split multiplicative reduction at the prime *P*.

INPUT:

- *P* – a prime ideal of the base field of self, or a field element generating such an ideal.

OUTPUT:

(bool) True if the curve has non-split multiplicative reduction at *P*, else False.

EXAMPLES:

```

sage: E=EllipticCurve('14a1')
sage: [(p,E.has_nonsplit_multiplicative_reduction(p)) for p in prime_
↪range(15)]
[(2, True), (3, False), (5, False), (7, False), (11, False), (13, False)]

sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.has_nonsplit_multiplicative_reduction(p)) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False), (Fractional ideal (2*a + 1),
↪False)]

```

**has\_rational\_cm(*field=None*)**

Returns whether or not this curve has CM defined over its base field or a given extension.



INPUT:

- `field` – a field, which should be an extension of the base field of the curve. If `field` is `None` (the default), it is taken to be the base field of the curve.

OUTPUT:

True if the ring of endomorphisms of this curve over the given field is larger than  $\mathbf{Z}$ ; otherwise `False`. See also `cm_discriminant()` and `has_cm()`.

---

**Note:** If  $E$  has CM but the discriminant  $D$  is not a square in the given field  $K$  then the extra endomorphisms will not be defined over  $K$ , and this function will return `False`. See also `has_cm()`. To obtain the CM discriminant, use `cm_discriminant()`.

---

EXAMPLES:

```
sage: E = EllipticCurve(j=0)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: D = E.cm_discriminant(); D
-3
sage: E.has_rational_cm(QuadraticField(D))
True

sage: E = EllipticCurve(j=1728)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: D = E.cm_discriminant(); D
-4
sage: E.has_rational_cm(QuadraticField(D))
True
```

Higher degree examples:

```
sage: K.<a> = QuadraticField(5)
sage: E = EllipticCurve(j=282880*a + 632000)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: E.cm_discriminant()
-20
sage: E.has_rational_cm(K.extension(x^2+5, 'b'))
True
```

An error is raised if a field is given which is not an extension of the base field:

```
sage: E.has_rational_cm(QuadraticField(-20))
Traceback (most recent call last):
...
ValueError: Error in has_rational_cm: Number Field in a with defining_
↳ polynomial x^2 + 20 is not an extension field of Number Field in a with_
↳ defining polynomial x^2 - 5
```

```

sage: K.<a> = NumberField(x^3 - 2)
sage: E = EllipticCurve(j=31710790944000*a^2 + 39953093016000*a +
↪50337742902000)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: D = E.cm_discriminant(); D
-108
sage: E.has_rational_cm(K.extension(x^2+108, 'b'))
True

```

**has\_split\_multiplicative\_reduction(*P*)**

Return True if this elliptic curve has (bad) split multiplicative reduction at the prime *P*.

INPUT:

- *P* – a prime ideal of the base field of self, or a field element generating such an ideal.

OUTPUT:

(bool) True if the curve has split multiplicative reduction at *P*, else False.

EXAMPLES:

```

sage: E=EllipticCurve('14a1')
sage: [(p,E.has_split_multiplicative_reduction(p)) for p in prime_range(15)]
[(2, False), (3, False), (5, False), (7, True), (11, False), (13, False)]

sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.has_split_multiplicative_reduction(p)) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False), (Fractional ideal (2*a + 1),
↪False)]

```

**height\_function()**

Return the canonical height function attached to self.

EXAMPLES:

```

sage: K.<a> = NumberField(x^2 - 5)
sage: E = EllipticCurve(K, '11a3')
sage: E.height_function()
EllipticCurveCanonicalHeight object associated to Elliptic Curve defined by y^
↪2 + y = x^3 + (-1)*x^2 over Number Field in a with defining polynomial x^2 -
↪ 5

```

**height\_pairing\_matrix(*points=None, precision=None*)**

Returns the height pairing matrix of the given points.

INPUT:

- *points* – either a list of points, which must be on this curve, or (default) None, in which case self.gens() will be used.
- *precision* – number of bits of precision of result (default: None, for default RealField precision)

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1, -1, 0])
sage: E.height_pairing_matrix()
[0.05111114082399688]
```

For rank 0 curves, the result is a valid 0x0 matrix:

```
sage: EllipticCurve('11a').height_pairing_matrix()
[]
sage: E=EllipticCurve('5077a1')
sage: E.height_pairing_matrix([E.lift_x(x) for x in [-2,-7/4,1]],
↳precision=100)
[ 1.3685725053539301120518194471 -1.3095767070865761992624519454 -0.
↳63486715783715592064475542573]
[ -1.3095767070865761992624519454 2.7173593928122930896610589220 1.
↳0998184305667292139777571432]
[-0.63486715783715592064475542573 1.0998184305667292139777571432 0.
↳66820516565192793503314205089]

sage: E = EllipticCurve('389a1')
sage: E = EllipticCurve('389a1')
sage: P,Q = E.point([-1,1,1]),E.point([0,-1,1])
sage: E.height_pairing_matrix([P,Q])
[0.686667083305587 0.268478098806726]
[0.268478098806726 0.327000773651605]
```

Over a number field:

```
sage: x = polygen(QQ)
sage: K.<t> = NumberField(x^2+47)
sage: EK = E.base_extend(K)
sage: EK.height_pairing_matrix([EK(P),EK(Q)])
[0.686667083305587 0.268478098806726]
[0.268478098806726 0.327000773651605]
```

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,i,i])
sage: P = E(-9+4*i,-18-25*i)
sage: Q = E(i,-i)
sage: E.height_pairing_matrix([P,Q])
[ 2.16941934493768 -0.870059380421505]
[-0.870059380421505 0.424585837470709]
sage: E.regulator_of_points([P,Q])
0.164101403936070
```

### `integral_model()`

Return a model of self which is integral at all primes.

EXAMPLES:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([i/5,i/5,i/5,i/5,i/5])
sage: P1,P2 = K.primes_above(5)
sage: E.global_integral_model()
Elliptic Curve defined by y^2 + (-i)*x*y + (-25*i)*y = x^3 + 5*i*x^2 +
↳125*i*x + 3125*i over Number Field in i with defining polynomial x^2 + 1
```

trac ticket #7935:

```

sage: K.<a> = NumberField(x^2-38)
sage: E = EllipticCurve([a,1/2])
sage: E.global_integral_model()
Elliptic Curve defined by  $y^2 = x^3 + 1444ax + 27436$  over Number Field in  $a$ 
↳ with defining polynomial  $x^2 - 38$ 

```

trac ticket #9266:

```

sage: K.<s> = NumberField(x^2-5)
sage: w = (1+s)/2
sage: E = EllipticCurve(K,[2,w])
sage: E.global_integral_model()
Elliptic Curve defined by  $y^2 = x^3 + 2x + (1/2s+1/2)$  over Number Field in  $s$ 
↳  $s$  with defining polynomial  $x^2 - 5$ 

```

trac ticket #12151:

```

sage: K.<v> = NumberField(x^2 + 161*x - 150)
sage: E = EllipticCurve([25105/216*v - 3839/36, 634768555/7776*v - 98002625/
↳ 1296, 634768555/7776*v - 98002625/1296, 0, 0])
sage: E.global_integral_model()
Elliptic Curve defined by  $y^2 + (2094779518028859v-1940492905300351)xy +$ 
↳  $(477997268472544193101178234454165304071127500v-$ 
↳  $442791377441346852919930773849502871958097500)y = x^3 +$ 
↳  $(26519784690047674853185542622500v-24566525306469707225840460652500)x^2$ 
↳ over Number Field in  $v$  with defining polynomial  $x^2 + 161x - 150$ 

```

trac ticket #14476:

```

sage: R.<t> = QQ[]
sage: K.<g> = NumberField(t^4 - t^3 - 3*t^2 - t + 1)
sage: E = EllipticCurve([-43/625*g^3 + 14/625*g^2 - 4/625*g + 706/625, -4862/
↳ 78125*g^3 - 4074/78125*g^2 - 711/78125*g + 10304/78125, -4862/78125*g^3 -
↳ 4074/78125*g^2 - 711/78125*g + 10304/78125, 0, 0])
sage: E.global_integral_model()
Elliptic Curve defined by  $y^2 + (15g^3-48g-42)xy + (-111510g^3-162162g^$ 
↳  $2-44145g+37638)y = x^3 + (-954g^3-1134g^2+81g+576)x^2$  over Number
↳ Field in  $g$  with defining polynomial  $t^4 - t^3 - 3t^2 - t + 1$ 

```

**is\_global\_integral\_model()**

Return whether self is integral at all primes.

EXAMPLES:

```

sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([i/5,i/5,i/5,i/5,i/5])
sage: P1,P2 = K.primes_above(5)
sage: Emin = E.global_integral_model()
sage: Emin.is_global_integral_model()
True

```

**is\_global\_minimal\_model()**

Returns whether this elliptic curve is a global minimal model.

OUTPUT:

Boolean, False if E is not integral, or if E is non-minimal at some prime, else True.

EXAMPLES:

```

sage: K.<a> = NumberField(x^2-10)
sage: E = EllipticCurve([0, 0, 0, -22500, 750000*a])
sage: E.is_global_minimal_model()
False
sage: E.non_minimal_primes()
[Fractional ideal (2, a), Fractional ideal (5, a)]

sage: E = EllipticCurve([0, 0, 0, -3024, 46224])
sage: E.is_global_minimal_model()
False
sage: E.non_minimal_primes()
[2, 3]
sage: Emin = E.global_minimal_model()
sage: Emin.is_global_minimal_model()
True

```

A necessary condition to be a global minimal model is that the model must be globally integral:

```

sage: E = EllipticCurve([0, 0, 0, 1/2, 1/3])
sage: E.is_global_minimal_model()
False
sage: Emin.is_global_minimal_model()
True
sage: Emin.ainvs()
(0, 1, 1, -2, 0)

```

**is\_isogenous** (*other*, *proof*=True, *maxnorm*=100)

Returns whether or not self is isogenous to other.

INPUT:

- *other* – another elliptic curve.
- *proof* (default True) – If False, the function will return True whenever the two curves have the same conductor and are isogenous modulo  $p$  for all primes  $p$  of norm up to *maxnorm*. If True, the function returns False when the previous condition does not hold, and if it does hold we compute the complete isogeny class to see if the curves are indeed isogenous.
- *maxnorm* (integer, default 100) – The maximum norm of primes  $p$  for which isogeny modulo  $p$  will be checked.

OUTPUT:

(bool) True if there is an isogeny from curve *self* to curve *other*.

EXAMPLES:

```

sage: x = polygen(QQ, 'x')
sage: F = NumberField(x^2 - 2, 's'); F
Number Field in s with defining polynomial x^2 - 2
sage: E1 = EllipticCurve(F, [7, 8])
sage: E2 = EllipticCurve(F, [0, 5, 0, 1, 0])
sage: E3 = EllipticCurve(F, [0, -10, 0, 21, 0])
sage: E1.is_isogenous(E2)
False
sage: E1.is_isogenous(E1)
True
sage: E2.is_isogenous(E2)
True
sage: E2.is_isogenous(E1)
False

```

```
False
sage: E2.is_isogenous(E3)
True
```

```
sage: x = polygen(QQ, 'x')
sage: F = NumberField(x^2 - 2, 's'); F
Number Field in s with defining polynomial x^2 - 2
sage: E = EllipticCurve('14a1')
sage: EE = EllipticCurve('14a2')
sage: E1 = E.change_ring(F)
sage: E2 = EE.change_ring(F)
sage: E1.is_isogenous(E2)
True
```

```
sage: x = polygen(QQ, 'x')
sage: F = NumberField(x^2 - 2, 's'); F
Number Field in s with defining polynomial x^2 - 2
sage: k.<a> = NumberField(x^3+7)
sage: E = EllipticCurve(F, [7,8])
sage: EE = EllipticCurve(k, [2, 2])
sage: E.is_isogenous(EE)
Traceback (most recent call last):
...
ValueError: Second argument must be defined over the same number field.
```

Some examples from Cremona's 1981 tables:

```
sage: K.<i> = QuadraticField(-1)
sage: E1 = EllipticCurve([i + 1, 0, 1, -240*i - 400, -2869*i - 2627])
sage: E1.conductor()
Fractional ideal (-4*i - 7)
sage: E2 = EllipticCurve([1+i,0,1,0,0])
sage: E2.conductor()
Fractional ideal (-4*i - 7)
sage: E1.is_isogenous(E2) # slower (~500ms)
True
sage: E1.is_isogenous(E2, proof=False) # faster (~170ms)
True
```

In this case  $E1$  and  $E2$  are in fact 9-isogenous, as may be deduced from the following:

```
sage: E3 = EllipticCurve([i + 1, 0, 1, -5*i - 5, -2*i - 5])
sage: E3.is_isogenous(E1)
True
sage: E3.is_isogenous(E2)
True
sage: E1.isogeny_degree(E2)
9
```

### **is\_local\_integral\_model** (\*P)

Tests if self is integral at the prime ideal  $P$ , or at all the primes if  $P$  is a list or tuple.

INPUT:

- \*P – a prime ideal, or a list or tuple of primes.

EXAMPLES:

```

sage: K.<i> = NumberField(x^2+1)
sage: P1,P2 = K.primes_above(5)
sage: E = EllipticCurve([i/5,i/5,i/5,i/5,i/5])
sage: E.is_local_integral_model(P1,P2)
False
sage: Emin = E.local_integral_model(P1,P2)
sage: Emin.is_local_integral_model(P1,P2)
True

```

**isogenies\_prime\_degree** (*l=None*)

Returns a list of  $\ell$ -isogenies from self, where  $\ell$  is a prime.

INPUT:

- $\ell$  – either None or a prime or a list of primes.

OUTPUT:

(list)  $\ell$ -isogenies for the given  $\ell$  or if  $\ell$  is None, all isogenies of prime degree (see below for the CM case).

---

**Note:** Over  $\mathbf{Q}$ , the codomains of the isogenies returned are standard minimal models. Over other number fields they are global minimal models if these exist, otherwise models which are minimal at all but one prime.

---



---

**Note:** For curves with rational CM, isogenies of primes degree exist for infinitely many primes  $\ell$ , though there are only finitely many isogenous curves up to isomorphism. The list returned only includes one isogeny of prime degree for each codomain.

---

EXAMPLES:

```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [0,0,0,0,1])
sage: isogs = E.isogenies_prime_degree()
sage: [phi.degree() for phi in isogs]
[2, 3]

sage: pol = PolynomialRing(QQ, 'x')([1,-3,5,-5,5,-3,1])
sage: L.<a> = NumberField(pol)
sage: js = hilbert_class_polynomial(-23).roots(L,multiplicities=False);
↪ len(js)
3
sage: E = EllipticCurve(j=js[0])
sage: len(E.isogenies_prime_degree())
3

```

**isogeny\_class** ()

Returns the isogeny class of this elliptic curve.

OUTPUT:

An instance of the class `sage.schemes.elliptic_curves.isogeny_class.IsogenyClass_EC_NumberField`. From this object may be obtained a list of curves in the class, a matrix of the degrees of the isogenies between them, and the isogenies themselves.

---

**Note:** The curves in the isogeny class will all be minimal models if these exist (for example, when the

class number is 1); otherwise they will be minimal at all but one prime.

EXAMPLES:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [0,0,0,0,1])
sage: C = E.isogeny_class(); C
Isogeny class of Elliptic Curve defined by  $y^2 = x^3 + 1$  over Number Field in  $\sqrt{-1}$ 
with defining polynomial  $x^2 + 1$ 
```

The curves in the class (sorted):

```
sage: [E1.ainvs() for E1 in C]
[(0, 0, 0, 0, -27),
 (0, 0, 0, 0, 1),
 (i + 1, i, i + 1, -i + 3, 4*i),
 (i + 1, i, i + 1, -i + 33, -58*i)]
```

The matrix of degrees of cyclic isogenies between curves:

```
sage: C.matrix()
[1 3 6 2]
[3 1 2 6]
[6 2 1 3]
[2 6 3 1]
```

The array of isogenies themselves is not filled out but only contains those used to construct the class, the other entries containing the integer 0. This will be changed when the class *EllipticCurveIsogeny* allowed composition. In this case we used 2-isogenies to go from 0 to 2 and from 1 to 3, and 3-isogenies to go from 0 to 1 and from 2 to 3:

```
sage: isogs = C.isogenies()
sage: [(i,j),isogs[i][j].degree()] for i in range(4) for j in range(4) if
↳ isogs[i][j]!=0
[(0, 1), 3],
(0, 3), 2],
(1, 0), 3],
(1, 2), 2],
(2, 1), 2],
(2, 3), 3],
(3, 0), 2],
(3, 2), 3)]
sage: [(i,j),isogs[i][j].x_rational_map()] for i in range(4) for j in
↳ range(4) if isogs[i][j]!=0
[(0, 1), (1/9*x^3 - 12)/x^2),
 (0, 3), (-1/2*i*x^2 + i*x - 12*i)/(x - 3)),
 (1, 0), (x^3 + 4)/x^2),
 (1, 2), (-1/2*i*x^2 - i*x - 2*i)/(x + 1)),
 (2, 1), (1/2*i*x^2 - x)/(x + 3/2*i)),
 (2, 3), (x^3 + 4*i*x^2 - 10*x - 10*i)/(x^2 + 4*i*x - 4)),
 (3, 0), (1/2*i*x^2 + x + 4*i)/(x - 5/2*i)),
 (3, 2), (1/9*x^3 - 4/3*i*x^2 - 34/3*x + 226/9*i)/(x^2 - 8*i*x - 16))]
```

The isogeny class may be visualized by obtaining its graph and plotting it:

```
sage: G = C.graph()
sage: G.show(edge_labels=True) # long time
```



```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([1+i, -i, i, 1, 0])
sage: C = E.isogeny_class(); C
Isogeny class of Elliptic Curve defined by  $y^2 + (i+1)xy + iy = x^3 + (-i)x^2 + x$  over Number Field in  $i$  with defining polynomial  $x^2 + 1$ 
sage: len(C)
6
sage: C.matrix()
[ 1  3  9 18  6  2]
[ 3  1  3  6  2  6]
[ 9  3  1  2  6 18]
[18  6  2  1  3  9]
[ 6  2  6  3  1  3]
[ 2  6 18  9  3  1]
sage: [E1.ainvs() for E1 in C]
[(i + 1, i - 1, i, -i - 1, -i + 1),
 (i + 1, i - 1, i, 14*i + 4, 7*i + 14),
 (i + 1, i - 1, i, 59*i + 99, 372*i - 410),
 (i + 1, -i, i, -240*i - 399, 2869*i + 2627),
 (i + 1, -i, i, -5*i - 4, 2*i + 5),
 (i + 1, -i, i, 1, 0)]

```

An example with CM by  $\sqrt{-5}$ :

```

sage: pol = PolynomialRing(QQ, 'x')([1, 0, 3, 0, 1])
sage: K.<c> = NumberField(pol)
sage: j = 1480640+565760*c^2
sage: E = EllipticCurve(j=j)
sage: E.has_cm()
True
sage: E.has_rational_cm()
True
sage: E.cm_discriminant()
-20
sage: C = E.isogeny_class()
sage: len(C)
2
sage: C.matrix()
[1 2]
[2 1]
sage: [E.ainvs() for E in C]
[(0, 0, 0, 83490*c^2 - 147015, -64739840*c^2 - 84465260),
 (0, 0, 0, -161535*c^2 + 70785, -62264180*c^3 + 6229080*c)]
sage: C.isogenies()[0][1]
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 = x^3 + (83490x^2 - 147015)x + (-64739840x^2 - 84465260)$  over Number Field in  $c$  with defining polynomial  $x^4 + 3x^2 + 1$  to Elliptic Curve defined by  $y^2 = x^3 + (-161535x^2 + 70785)x + (-62264180x^3 + 6229080x)$  over Number Field in  $c$  with defining polynomial  $x^4 + 3x^2 + 1$ 

```

An example with CM by  $\sqrt{-23}$  (class number 3):

```

sage: pol = PolynomialRing(QQ, 'x')([1, -3, 5, -5, 5, -3, 1])
sage: L.<a> = NumberField(pol)
sage: js = hilbert_class_polynomial(-23).roots(L, multiplicities=False);
len(js)
3
sage: E = EllipticCurve(j=js[0])

```

```

sage: E.has_rational_cm()
True
sage: len(E.isogenies_prime_degree())
3
sage: C = E.isogeny_class(); len(C)
6

```

The reason for the isogeny class having size six while the class number is only 3 is that the class also contains three curves with CM by the order of discriminant  $-92 = 4 \cdot (-23)$ , which also has class number 3. The curves in the class are sorted first by CM discriminant (then lexicographically using  $a$ -invariants):

```

sage: [F.cm_discriminant() for F in C]
[-23, -23, -23, -92, -92, -92]

```

2 splits in the order with discriminant  $-23$ , into two primes of order 3 in the class group, each of which induces a 2-isogeny to a curve with the same endomorphism ring; the third 2-isogeny is to a curve with the smaller endomorphism ring:

```

sage: [phi.codomain().cm_discriminant() for phi in E.isogenies_prime_degree()]
[-92, -23, -23]

sage: C.matrix()
[1 2 2 4 2 4]
[2 1 2 2 4 4]
[2 2 1 4 4 2]
[4 2 4 1 3 3]
[2 4 4 3 1 3]
[4 4 2 3 3 1]

```

The graph of this isogeny class has a shape which does not occur over  $\mathbf{Q}$ : a triangular prism. Note that for curves without CM, the graph has an edge between two curves if and only if they are connected by an isogeny of prime degree, and this degree is uniquely determined by the two curves, but in the CM case this property does not hold, since for pairs of curves in the class with the same endomorphism ring  $O$ , the set of degrees of isogenies between them is the set of integers represented by a primitive integral binary quadratic form of discriminant  $\text{disc}(O)$ , and this form represents infinitely many primes. In the matrix we give a small prime represented by the appropriate form. In this example, the matrix is formed by four  $3 \times 3$  blocks. The isogenies of degree 2 indicated by the upper left  $3 \times 3$  block of the matrix could be replaced by isogenies of any degree represented by the quadratic form  $2x^2 + xy + 3y^2$  of discriminant  $-23$ . Similarly in the lower right block, the entries of 3 could be represented by any integers represented by the quadratic form  $3x^2 + 2xy + 8y^2$  of discriminant  $-92$ . In the top right block and lower left blocks, by contrast, the prime entries 2 are unique determined:

```

sage: G = C.graph()
sage: G.adjacency_matrix()
[0 1 1 0 1 0]
[1 0 1 1 0 0]
[1 1 0 0 0 1]
[0 1 0 0 1 1]
[1 0 0 1 0 1]
[0 0 1 1 1 0]

```

To display the graph without any edge labels:

```
G.show() # long time
```

To display the graph with edge labels: by default, for curves with rational CM, the labels are the coefficients of the associated quadratic forms:

```
G.show(edge_labels=True) # long time
```

For an alternative view, first relabel the edges using only 2 labels to distinguish between isogenies between curves with the same endomorphism ring and isogenies between curves with different endomorphism rings, then use a 3-dimensional plot which can be rotated:

```
sage: for i, j, l in G.edge_iterator(): G.set_edge_label(i, j, l.count(','))
sage: G.show3d(color_by_label=True)
```

A class number 6 example. First we set up the fields: `pol` defines the same field as `pol26` but is simpler:

```
sage: pol26 = hilbert_class_polynomial(-4*26)
sage: pol = x^6-x^5+2*x^4+x^3-2*x^2-x-1
sage: K.<a> = NumberField(pol)
sage: L.<b> = K.extension(x^2+26)
```

Only 2 of the  $j$ -invariants with discriminant -104 are in  $K$ , though all are in  $L$ :

```
sage: len(pol26.roots(K))
2
sage: len(pol26.roots(L))
6
```

We create an elliptic curve defined over  $K$  with one of the  $j$ -invariants in  $K$ :

```
sage: j1 = pol26.roots(K)[0][0]
sage: E = EllipticCurve(j=j1)
sage: E.has_cm()
True
sage: E.has_rational_cm()
False
sage: E.has_rational_cm(L)
True
```

Over  $K$  the isogeny class has size 4, with 2 curves for each of the 2  $K$ -rational  $j$ -invariants:

```
sage: C = E.isogeny_class(); len(C) # long time (~11s)
4
sage: C.matrix() # long time
[ 1 13  2 26]
[13  1 26  2]
[ 2 26  1 13]
[26  2 13  1]
sage: len(Set([EE.j_invariant() for EE in C.curves])) # long time
2
```

Over  $L$ , the isogeny class grows to size 6 (the class number):

```
sage: EL = E.change_ring(L)
sage: CL = EL.isogeny_class(); len(CL) # long time (~80s)
6
sage: Set([EE.j_invariant() for EE in CL.curves]) == Set(pol26.roots(L,
↪multiplicities=False)) # long time
True
```

In each position in the matrix of degrees, we see primes (or 1). In fact the set of degrees of cyclic isogenies from curve  $i$  to curve  $j$  is infinite, and is the set of all integers represented by one of the primitive binary quadratic forms of discriminant  $-104$ , from which we have selected a small prime:

```
sage: CL.matrix() # long time # random (see :trac:`19229`)
[1 2 3 3 5 5]
[2 1 5 5 3 3]
[3 5 1 3 2 5]
[3 5 3 1 5 2]
[5 3 2 5 1 3]
[5 3 5 2 3 1]
```

To see the array of binary quadratic forms:

```
sage: CL.qf_matrix() # long time # random (see :trac:`19229`)
[[[1], [2, 0, 13], [3, -2, 9], [3, -2, 9], [5, -4, 6], [5, -4, 6]],
 [[2, 0, 13], [1], [5, -4, 6], [5, -4, 6], [3, -2, 9], [3, -2, 9]],
 [[3, -2, 9], [5, -4, 6], [1], [3, -2, 9], [2, 0, 13], [5, -4, 6]],
 [[3, -2, 9], [5, -4, 6], [3, -2, 9], [1], [5, -4, 6], [2, 0, 13]],
 [[5, -4, 6], [3, -2, 9], [2, 0, 13], [5, -4, 6], [1], [3, -2, 9]],
 [[5, -4, 6], [3, -2, 9], [5, -4, 6], [2, 0, 13], [3, -2, 9], [1]]]
```

As in the non-CM case, the isogeny class may be visualized by obtaining its graph and plotting it. Since there are more edges than in the non-CM case, it may be preferable to omit the `edge_labels`:

```
sage: G = C.graph()
sage: G.show(edge_labels=False) # long time
```

It is possible to display a 3-dimensional plot, with colours to represent the different edge labels, in a form which can be rotated!:

```
sage: G.show3d(color_by_label=True) # long time
```

### **isogeny\_degree** (*other*)

Returns the minimal degree of an isogeny between self and other, or 0 if no isogeny exists.

INPUT:

- `other` – another elliptic curve.

OUTPUT:

(int) The degree of an isogeny from self to other, or 0.

EXAMPLES:

```
sage: x = QQ['x'].0
sage: F = NumberField(x^2 - 2, 's'); F
Number Field in s with defining polynomial x^2 - 2
sage: E = EllipticCurve('14a1')
sage: EE = EllipticCurve('14a2')
sage: E1 = E.change_ring(F)
sage: E2 = EE.change_ring(F)
sage: E1.isogeny_degree(E2)
2
sage: E2.isogeny_degree(E2)
1
sage: E5 = EllipticCurve('14a5').change_ring(F)
sage: E1.isogeny_degree(E5)
6

sage: E = EllipticCurve('11a1')
sage: [E2.label() for E2 in cremona_curves([11..20]) if E.isogeny_degree(E2)]
```

```
['11a1', '11a2', '11a3']

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([1+i, -i, i, 1, 0])
sage: C = E.isogeny_class()
sage: [E.isogeny_degree(F) for F in C]
[2, 6, 18, 9, 3, 1]
```

**kodaira\_symbol** (*P*, *proof*=None)

Returns the Kodaira Symbol of this elliptic curve at the prime *P*.

INPUT:

- *P* – either None or a prime ideal of the base field of self.
- *proof* – whether to only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the flag are in number fields.

OUTPUT:

The Kodaira Symbol of the curve at *P*, represented as a string.

EXAMPLES:

```
sage: K.<a>=NumberField(x^2-5)
sage: E=EllipticCurve([20, 225, 750, 625*a + 6875, 31250*a + 46875])
sage: bad_primes = E.discriminant().support(); bad_primes
[Fractional ideal (-a), Fractional ideal (7/2*a - 81/2), Fractional ideal (-a_
↪ - 52), Fractional ideal (2)]
sage: [E.kodaira_symbol(P) for P in bad_primes]
[I0, I1, I1, II]
sage: K.<a> = QuadraticField(-11)
sage: E = EllipticCurve('11a1').change_ring(K)
sage: [E.kodaira_symbol(P) for P in K(11).support()]
[I10]
```

**l1l\_reduce** (*points*, *height\_matrix*=None, *precision*=None)

Returns an LLL-reduced basis from a given basis, with transform matrix.

INPUT:

- *points* - a list of points on this elliptic curve, which should be independent.
- *height\_matrix* - the height-pairing matrix of the points, or None. If None, it will be computed.
- *precision* - number of bits of precision of intermediate computations (default: None, for default RealField precision; ignored if *height\_matrix* is supplied)

OUTPUT: A tuple (*newpoints*, *U*) where *U* is a unimodular integer matrix, *new\_points* is the transform of points by *U*, such that *new\_points* has LLL-reduced height pairing matrix

---

**Note:** If the input points are not independent, the output depends on the undocumented behaviour of PARI's `qflllgram()` function when applied to a gram matrix which is not positive definite.

---

EXAMPLES:

Some examples over  $\mathbb{Q}$ :

```

sage: E = EllipticCurve([0, 1, 1, -2, 42])
sage: Pi = E.gens(); Pi
[(-4 : 1 : 1), (-3 : 5 : 1), (-11/4 : 43/8 : 1), (-2 : 6 : 1)]
sage: Qi, U = E.lll_reduce(Pi)
sage: all(sum(U[i,j]*Pi[i] for i in range(4)) == Qi[j] for j in range(4))
True
sage: sorted(Qi)
[(-4 : 1 : 1), (-3 : 5 : 1), (-2 : 6 : 1), (0 : 6 : 1)]
sage: U.det()
1
sage: E.regulator_of_points(Pi)
4.59088036960573
sage: E.regulator_of_points(Qi)
4.59088036960574

```

```

sage: E = EllipticCurve([1, 0, 1, -120039822036992245303534619191166796374,
↪ 504224992484910670010801799168082726759443756222911415116])
sage: xi = [2005024558054813068, -4690836759490453344, ↪
↪ 4700156326649806635, 6785546256295273860, ↪
↪ 6823803569166584943, 7788809602110240789, ↪
↪ 27385442304350994620556, 54284682060285253719/4, -
↪ 94200235260395075139/25, -3463661055331841724647/576, ↪
↪ -6684065934033506970637/676, -956077386192640344198/2209, ↪
↪ -27067471797013364392578/2809, -25538866857137199063309/3721, ↪
↪ -1026325011760259051894331/108241, ↪
↪ 9351361230729481250627334/1366561, 10100878635879432897339615/
↪ 1423249, 11499655868211022625340735/17522596, ↪
↪ 110352253665081002517811734/21353641, ↪
↪ 414280096426033094143668538257/285204544, ↪
↪ 36101712290699828042930087436/4098432361, ↪
↪ 45442463408503524215460183165/5424617104, ↪
↪ 983886013344700707678587482584/141566320009, ↪
↪ 1124614335716851053281176544216033/152487126016]
sage: points = [E.lift_x(x) for x in xi]
sage: newpoints, U = E.lll_reduce(points) # long time (35s on sage.math, ↪
↪ 2011)
sage: [P[0] for P in newpoints] # long time
[6823803569166584943, 5949539878899294213, 2005024558054813068, ↪
↪ 5864879778877955778, 23955263915878682727/4, 5922188321411938518, ↪
↪ 5286988283823825378, 175620639884534615751/25, -11451575907286171572, ↪
↪ 3502708072571012181, 1500143935183238709184/225, 27180522378120223419/4, -
↪ 5811874164190604461581/625, 26807786527159569093, 7404442636649562303, ↪
↪ 475656155255883588, 265757454726766017891/49, 7272142121019825303, ↪
↪ 50628679173833693415/4, 6951643522366348968, 68425151518070703, ↪
↪ 111593750389650846885/16, 2607467890531740394315/9, -1829928525835506297]

```

An example to show the explicit use of the height pairing matrix:

```

sage: E = EllipticCurve([0, 1, 1, -2, 42])
sage: Pi = E.gens()
sage: H = E.height_pairing_matrix(Pi, 3)
sage: E.lll_reduce(Pi, height_matrix=H)
(
[(-4 : 1 : 1), (-3 : 5 : 1), (-2 : 6 : 1), (1 : -7 : 1)], [0 0 1 1]
)

```

Some examples over number fields (see [trac ticket #9411](#)):

```
sage: K.<a> = QuadraticField(-23, 'a')
sage: E = EllipticCurve(K, [0,0,1,-1,0])
sage: P = E(-2, -(a+1)/2)
sage: Q = E(0,-1)
sage: E.lll_reduce([P,Q])
(
                                     [0 1]
[(0 : -1 : 1), (-2 : -1/2*a - 1/2 : 1)], [1 0]
)
```

```
sage: K.<a> = QuadraticField(-5)
sage: E = EllipticCurve(K, [0,a])
sage: points = [E.point([-211/841*a - 6044/841, -209584/24389*a + 53634/
↪24389]), E.point([-17/18*a - 1/9, -109/108*a - 277/108]) ]
sage: E.lll_reduce(points)
(
[(-a + 4 : -3*a + 7 : 1), (-17/18*a - 1/9 : 109/108*a + 277/108 : 1)],
[ 1  0]
[ 1 -1]
)
```

**local\_data** (*P=None, proof=None, algorithm='pari', globally=False*)

Local data for this elliptic curve at the prime *P*.

INPUT:

- *P* – either None, a prime ideal of the base field of self, or an element of the base field that generates a prime ideal.
- *proof* – whether to only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the flag are in number fields.
- *algorithm* (string, default: “pari”) – Ignored unless the base field is  $\mathbf{Q}$ . If “pari”, use the PARI C-library `ellglobalred` implementation of Tate’s algorithm over  $\mathbf{Q}$ . If “generic”, use the general number field implementation.
- *globally* – whether the local algorithm uses global generators for the prime ideals. Default is False, which won’t require any information about the class group. If True, a generator for *P* will be used if *P* is principal. Otherwise, or if *globally* is False, the minimal model returned will preserve integrality at other primes, but not minimality.

OUTPUT:

If *P* is specified, returns the `EllipticCurveLocalData` object associated to the prime *P* for this curve. Otherwise, returns a list of such objects, one for each prime *P* in the support of the discriminant of this model.

---

**Note:** The model is not required to be integral on input.

---

EXAMPLES:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([1 + i, 0, 1, 0, 0])
sage: E.local_data()
```

```

[Local data at Fractional ideal (2*i + 1):
Reduction type: bad non-split multiplicative
Local minimal model: Elliptic Curve defined by  $y^2 + (i+1)xy + y = x^3$  over  $\mathbb{Q}[i]$ 
↪Number Field in  $i$  with defining polynomial  $x^2 + 1$ 
Minimal discriminant valuation: 1
Conductor exponent: 1
Kodaira Symbol: I1
Tamagawa Number: 1,
Local data at Fractional ideal (-3*i - 2):
Reduction type: bad split multiplicative
Local minimal model: Elliptic Curve defined by  $y^2 + (i+1)xy + y = x^3$  over  $\mathbb{Q}[i]$ 
↪Number Field in  $i$  with defining polynomial  $x^2 + 1$ 
Minimal discriminant valuation: 2
Conductor exponent: 1
Kodaira Symbol: I2
Tamagawa Number: 2]
sage: E.local_data(K.ideal(3))
Local data at Fractional ideal (3):
Reduction type: good
Local minimal model: Elliptic Curve defined by  $y^2 + (i+1)xy + y = x^3$  over  $\mathbb{Q}[i]$ 
↪Number Field in  $i$  with defining polynomial  $x^2 + 1$ 
Minimal discriminant valuation: 0
Conductor exponent: 0
Kodaira Symbol: I0
Tamagawa Number: 1
sage: E.local_data(2*i + 1)
Local data at Fractional ideal (2*i + 1):
Reduction type: bad non-split multiplicative
Local minimal model: Elliptic Curve defined by  $y^2 + (i+1)xy + y = x^3$  over  $\mathbb{Q}[i]$ 
↪Number Field in  $i$  with defining polynomial  $x^2 + 1$ 
Minimal discriminant valuation: 1
Conductor exponent: 1
Kodaira Symbol: I1
Tamagawa Number: 1

```

An example raised in [trac ticket #3897](#):

```

sage: E = EllipticCurve([1,1])
sage: E.local_data(3)
Local data at Principal ideal (3) of Integer Ring:
Reduction type: good
Local minimal model: Elliptic Curve defined by  $y^2 = x^3 + x + 1$  over  $\mathbb{Q}$ 
↪Rational Field
Minimal discriminant valuation: 0
Conductor exponent: 0
Kodaira Symbol: I0
Tamagawa Number: 1

```

### `local_integral_model(*P)`

Return a model of self which is integral at the prime ideal  $P$ .

---

**Note:** The integrality at other primes is not affected, even if  $P$  is non-principal.

---

INPUT:

- $*P$  – a prime ideal, or a list or tuple of primes.



EXAMPLES:

```
sage: K.<i> = NumberField(x^2+1)
sage: P1,P2 = K.primes_above(5)
sage: E = EllipticCurve([i/5,i/5,i/5,i/5,i/5])
sage: E.local_integral_model((P1,P2))
Elliptic Curve defined by  $y^2 + (-i)*x*y + (-25*i)*y = x^3 + 5*i*x^2 +$ 
 $\hookrightarrow 125*i*x + 3125*i$  over Number Field in  $i$  with defining polynomial  $x^2 + 1$ 
```

**local\_minimal\_model** ( $P$ , *proof*=None, *algorithm*='pari')

Returns a model which is integral at all primes and minimal at  $P$ .

INPUT:

- $P$  – either None or a prime ideal of the base field of self.
- *proof* – whether to only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the flag are in number fields.
- *algorithm* (string, default: “pari”) – Ignored unless the base field is  $\mathbf{Q}$ . If “pari”, use the PARI C-library `ellglobalred` implementation of Tate’s algorithm over  $\mathbf{Q}$ . If “generic”, use the general number field implementation.

OUTPUT:

A model of the curve which is minimal (and integral) at  $P$ .

---

**Note:** The model is not required to be integral on input.

For principal  $P$ , a generator is used as a uniformizer, and integrality or minimality at other primes is not affected. For non-principal  $P$ , the minimal model returned will preserve integrality at other primes, but not minimality.

---

EXAMPLES:

```
sage: K.<a>=NumberField(x^2-5)
sage: E=EllipticCurve([20, 225, 750, 1250*a + 6250, 62500*a + 15625])
sage: P=K.ideal(a)
sage: E.local_minimal_model(P).ainvs()
(0, 1, 0, 2*a - 34, -4*a + 66)
```

**minimal\_discriminant\_ideal** ()

Return the minimal discriminant ideal of this elliptic curve.

OUTPUT:

The integral ideal  $D$  whose valuation at every prime  $P$  is that of the local minimal model for  $E$  at  $P$ . If  $E$  has a global minimal model, this will be the principal ideal generated by the discriminant of any such model, but otherwise it can be a proper divisor of the discriminant of any model.

EXAMPLES:

```
sage: K.<a> = NumberField(x^2-x-57)
sage: K.class_number()
3
sage: E = EllipticCurve([a,-a,a,-5692-820*a,-259213-36720*a])
sage: K.ideal(E.discriminant())
Fractional ideal (90118662980*a + 636812084644)
```

```
sage: K.ideal(E.discriminant()).factor()
(Fractional ideal (2))^2 * (Fractional ideal (3, a + 2))^12
```

Here the minimal discriminant ideal is principal but there is no global minimal model since the quotient is the 12th power of a non-principal ideal:

```
sage: E.minimal_discriminant_ideal()
Fractional ideal (4)
sage: E.minimal_discriminant_ideal().factor()
(Fractional ideal (2))^2
```

If (and only if) the curve has everywhere good reduction the result is the unit ideal:

```
sage: K.<a> = NumberField(x^2-26)
sage: E = EllipticCurve([a, a-1, a+1, 4*a+10, 2*a+6])
sage: E.conductor()
Fractional ideal (1)
sage: E.discriminant()
-104030*a - 530451
sage: E.minimal_discriminant_ideal()
Fractional ideal (1)
```

Over  $\mathbb{Q}$ , the result returned is an ideal of  $\mathbb{Z}$  rather than a fractional ideal of  $\mathbb{Q}$ :

```
sage: E = EllipticCurve([1, 2, 3, 4, 5])
sage: E.minimal_discriminant_ideal()
Principal ideal (10351) of Integer Ring
```

### `non_minimal_primes()`

Returns a list of primes at which this elliptic curve is not minimal.

OUTPUT:

A list of prime ideals (or prime numbers when the base field is  $\mathbb{Q}$ , empty if this is a global minimal model.

EXAMPLES:

```
sage: K.<a> = NumberField(x^2-10)
sage: E = EllipticCurve([0, 0, 0, -22500, 750000*a])
sage: E.non_minimal_primes()
[Fractional ideal (2, a), Fractional ideal (5, a)]
sage: K.ideal(E.discriminant()).factor()
(Fractional ideal (2, a))^24 * (Fractional ideal (3, a + 1))^5 * (Fractional_
↪ ideal (3, a + 2))^5 * (Fractional ideal (5, a))^24 * (Fractional ideal (7))
sage: E.minimal_discriminant_ideal().factor()
(Fractional ideal (2, a))^12 * (Fractional ideal (3, a + 1))^5 * (Fractional_
↪ ideal (3, a + 2))^5 * (Fractional ideal (7))
```

Over  $\mathbb{Q}$ , the primes returned are integers, not ideals:

```
sage: E = EllipticCurve([0, 0, 0, -3024, 46224])
sage: E.non_minimal_primes()
[2, 3]
sage: Emin = E.global_minimal_model()
sage: Emin.non_minimal_primes()
[]
```

If the model is not globally integral, a `ValueError` is raised:

```

sage: E = EllipticCurve([0,0,0,1/2,1/3])
sage: E.non_minimal_primes()
Traceback (most recent call last):
...
ValueError: non_minimal_primes only defined for integral models

```

**period\_lattice** (*embedding*)

Returns the period lattice of the elliptic curve for the given embedding of its base field with respect to the differential  $dx/(2y + a_1x + a_3)$ .

INPUT:

- *embedding* - an embedding of the base number field into  $\mathbf{R}$  or  $\mathbf{C}$ .

**Note:** The precision of the embedding is ignored: we only use the given embedding to determine which embedding into  $\overline{\mathbb{Q}\mathbb{Q}}$  to use. Once the lattice has been initialized, periods can be computed to arbitrary precision.

**EXAMPLES:**

First define a field with two real embeddings:

```

sage: K.<a> = NumberField(x^3-2)
sage: E=EllipticCurve([0,0,0,a,2])
sage: embs=K.embeddings(CC); len(embs)
3

```

For each embedding we have a different period lattice:

```

sage: E.period_lattice(embs[0])
Period lattice associated to Elliptic Curve defined by  $y^2 = x^3 + ax + 2$ 
↳ over Number Field in  $a$  with defining polynomial  $x^3 - 2$  with respect to the
↳ embedding Ring morphism:
From: Number Field in  $a$  with defining polynomial  $x^3 - 2$ 
To: Algebraic Field
Defn:  $a \mapsto -0.6299605249474365? - 1.091123635971722?i$ 

sage: E.period_lattice(embs[1])
Period lattice associated to Elliptic Curve defined by  $y^2 = x^3 + ax + 2$ 
↳ over Number Field in  $a$  with defining polynomial  $x^3 - 2$  with respect to the
↳ embedding Ring morphism:
From: Number Field in  $a$  with defining polynomial  $x^3 - 2$ 
To: Algebraic Field
Defn:  $a \mapsto -0.6299605249474365? + 1.091123635971722?i$ 

sage: E.period_lattice(embs[2])
Period lattice associated to Elliptic Curve defined by  $y^2 = x^3 + ax + 2$ 
↳ over Number Field in  $a$  with defining polynomial  $x^3 - 2$  with respect to the
↳ embedding Ring morphism:
From: Number Field in  $a$  with defining polynomial  $x^3 - 2$ 
To: Algebraic Field
Defn:  $a \mapsto 1.259921049894873?$ 

```

Although the original embeddings have only the default precision, we can obtain the basis with higher precision later:

```

sage: L=E.period_lattice(embs[0])
sage: L.basis()
(1.86405007647981 - 0.903761485143226*I, -0.149344633143919 - 2.
↪06619546272945*I)

sage: L.basis(prec=100)
(1.8640500764798108425920506200 - 0.90376148514322594749786960975*I, -0.
↪14934463314391922099120107422 - 2.0661954627294548995621225062*I)

```

**rank** (*\*\*kws*)

Return the rank of this elliptic curve, if it can be determined.

---

**Note:** The optional parameters control the Simon two descent algorithm; see the documentation of [`simon\_two\_descent\(\)`](#) for more details.

---

INPUT:

- `verbose` – 0, 1, 2, or 3 (default: 0), the verbosity level
- `lim1` – (default: 2) limit on trivial points on quartics
- `lim3` – (default: 4) limit on points on ELS quartics
- `limtriv` – (default: 2) limit on trivial points on elliptic curve
- `maxprob` – (default: 20)
- `limbigprime` – (default: 30) to distinguish between small and large prime numbers. Use probabilistic tests for large primes. If 0, don't use probabilistic tests.
- `known_points` – (default: None) list of known points on the curve

OUTPUT:

If the upper and lower bounds given by Simon two-descent are the same, then the rank has been uniquely identified and we return this. Otherwise, we raise a `ValueError` with an error message specifying the upper and lower bounds.

---

**Note:** For non-quadratic number fields, this code does return, but it takes a long time.

---

EXAMPLES:

```

sage: K.<a> = NumberField(x^2 + 23, 'a')
sage: E = EllipticCurve(K, '37')
sage: E == loads(dumps(E))
True
sage: E.rank()
2

```

Here is a curve with two-torsion in the Tate-Shafarevich group, so here the bounds given by the algorithm do not uniquely determine the rank:

```

sage: E = EllipticCurve("15a5")
sage: K.<t> = NumberField(x^2-6)
sage: EK = E.base_extend(K)
sage: EK.rank(lim1=1, lim3=1, limtriv=1)
Traceback (most recent call last):
...

```

```
ValueError: There is insufficient data to determine the rank -
2-descent gave lower bound 0 and upper bound 2
```

**IMPLEMENTATION:**

Uses Denis Simon's PARI/GP scripts from <http://www.math.unicaen.fr/~simon/>.

**rank\_bounds** (*\*\*kws*)

Returns the lower and upper bounds using `simon_two_descent()`. The results of `simon_two_descent()` are cached.

---

**Note:** The optional parameters control the Simon two descent algorithm; see the documentation of `simon_two_descent()` for more details.

---

**INPUT:**

- `verbose` – 0, 1, 2, or 3 (default: 0), the verbosity level
- `lim1` – (default: 2) limit on trivial points on quartics
- `lim3` – (default: 4) limit on points on ELS quartics
- `limtriv` – (default: 2) limit on trivial points on elliptic curve
- `maxprob` – (default: 20)
- `limbigprime` – (default: 30) to distinguish between small and large prime numbers. Use probabilistic tests for large primes. If 0, don't use probabilistic tests.
- `known_points` – (default: None) list of known points on the curve

**OUTPUT:**

lower and upper bounds for the rank of the Mordell-Weil group

---

**Note:** For non-quadratic number fields, this code does return, but it takes a long time.

---

**EXAMPLES:**

```
sage: K.<a> = NumberField(x^2 + 23, 'a')
sage: E = EllipticCurve(K, '37')
sage: E == loads(dumps(E))
True
sage: E.rank_bounds()
(2, 2)
```

Here is a curve with two-torsion, again the bounds coincide:

```
sage: Qrt5.<rt5>=NumberField(x^2-5)
sage: E=EllipticCurve([0,5-rt5,0,rt5,0])
sage: E.rank_bounds()
(1, 1)
```

Finally an example with non-trivial 2-torsion in Sha. So the 2-descent will not be able to determine the rank, but can only give bounds:

```
sage: E = EllipticCurve("15a5")
sage: K.<t> = NumberField(x^2-6)
```

```

sage: EK = E.base_extend(K)
sage: EK.rank_bounds(lim1=1, lim3=1, limtriv=1)
(0, 2)

```

**IMPLEMENTATION:**

Uses Denis Simon's PARI/GP scripts from <http://www.math.unicaen.fr/~simon/>.

**reduction** (*place*)

Return the reduction of the elliptic curve at a place of good reduction.

**INPUT:**

- *place* – a prime ideal in the base field of the curve

**OUTPUT:**

An elliptic curve over a finite field, the residue field of the place.

**EXAMPLES:**

```

sage: K.<i> = QuadraticField(-1)
sage: EK = EllipticCurve([0,0,0,i,i+3])
sage: v = K.fractional_ideal(2*i+3)
sage: EK.reduction(v)
Elliptic Curve defined by y^2 = x^3 + 5*x + 8 over Residue field of
↪ Fractional ideal (2*i + 3)
sage: EK.reduction(K.ideal(1+i))
Traceback (most recent call last):
...
ValueError: The curve must have good reduction at the place.
sage: EK.reduction(K.ideal(2))
Traceback (most recent call last):
...
ValueError: The ideal must be prime.
sage: K=QQ.extension(x^2+x+1,"a")
sage: E=EllipticCurve([1024*K.0,1024*K.0])
sage: E.reduction(2*K)
Elliptic Curve defined by y^2 + (abar+1)*y = x^3 over Residue field in abar
↪ of Fractional ideal (2)

```

**regulator\_of\_points** (*points=[]*, *precision=None*)

Returns the regulator of the given points on this curve.

**INPUT:**

- *points* -(default: empty list) a list of points on this curve
- *precision* - int or None (default: None): the precision in bits of the result (default real precision if None)

**EXAMPLES:**

```

sage: E = EllipticCurve('37a1')
sage: P = E(0,0)
sage: Q = E(1,0)
sage: E.regulator_of_points([P,Q])
0.000000000000000000
sage: 2*P == Q
True

```

```

sage: E = EllipticCurve('5077a1')
sage: points = [E.lift_x(x) for x in [-2, -7/4, 1]]
sage: E.regulator_of_points(points)
0.417143558758384
sage: E.regulator_of_points(points, precision=100)
0.41714355875838396981711954462

```

```

sage: E = EllipticCurve('389a')
sage: E.regulator_of_points()
1.000000000000000
sage: points = [P, Q] = [E(-1, 1), E(0, -1)]
sage: E.regulator_of_points(points)
0.152460177943144
sage: E.regulator_of_points(points, precision=100)
0.15246017794314375162432475705
sage: E.regulator_of_points(points, precision=200)
0.15246017794314375162432475704945582324372707748663081784028
sage: E.regulator_of_points(points, precision=300)
0.
↪ 152460177943143751624324757049455823243727077486630817840280980046053225683562463604114816

```

Examples over number fields:

```

sage: K.<a> = QuadraticField(97)
sage: E = EllipticCurve(K, [1, 1])
sage: P = E(0, 1)
sage: P.height()
0.476223106404866
sage: E.regulator_of_points([P])
0.476223106404866

```

```

sage: E = EllipticCurve('11a1')
sage: x = polygen(QQ)
sage: K.<t> = NumberField(x^2+47)
sage: EK = E.base_extend(K)
sage: T = EK(5, 5)
sage: T.order()
5
sage: P = EK(-2, -1/2*t - 1/2)
sage: P.order()
+Infinity
sage: EK.regulator_of_points([P, T]) # random very small output
-1.23259516440783e-32
sage: EK.regulator_of_points([P, T]).abs() < 1e-30
True

```

```

sage: E = EllipticCurve('389a1')
sage: P, Q = E.gens()
sage: E.regulator_of_points([P, Q])
0.152460177943144
sage: K.<t> = NumberField(x^2+47)
sage: EK = E.base_extend(K)
sage: EK.regulator_of_points([EK(P), EK(Q)])
0.152460177943144

```

```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,i,i])
sage: P = E(-9+4*i,-18-25*i)
sage: Q = E(i,-i)
sage: E.height_pairing_matrix([P,Q])
[ 2.16941934493768 -0.870059380421505]
[-0.870059380421505  0.424585837470709]
sage: E.regulator_of_points([P,Q])
0.164101403936070

```

**saturation** (*points*, *verbose=False*, *max\_prime=0*, *one\_prime=0*, *odd\_primes\_only=False*, *lower\_ht\_bound=None*, *reg=None*, *debug=False*)

Given a list of rational points on  $E$  over  $K$ , compute the saturation in  $E(K)$  of the subgroup they generate.

INPUT:

- *points* (list) - list of points on  $E$ . Points of finite order are ignored; the remaining points should be independent, or an error is raised.
- *verbose* (bool) - (default: `False`), if `True`, give verbose output.
- *max\_prime* (int, default 0), saturation is performed for all primes up to *max\_prime*. If *max\_prime* is 0, perform saturation at *all* primes, i.e., compute the true saturation.
- *odd\_primes\_only* (bool, default `False`) – only do saturation at odd primes.
- *one\_prime* (int, default 0) – if nonzero, only do saturation at this prime.

The following two inputs are optional, and may be provided to speed up the computation.

- *lower\_ht\_bound* (real, default `None`) – lower bound of the regulator  $E(K)$ , if known.
- *reg* (real, default `None`), regulator of the span of points, if known.
- *debug* (int, default 0) – , used for debugging and testing.

OUTPUT:

- *saturation* (list) - points that form a basis for the saturation.
- *index* (int) - the index of the group generated by the input points in their saturation.
- *regulator* (real with default precision, or `None`) - regulator of saturated points.

EXAMPLES:

```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve('389a1')
sage: EK = E.change_ring(K)
sage: P = EK(-1,1); Q = EK(0,-1)

sage: EK.saturation([2*P], max_prime=2)
[(-1 : 1 : 1)], 2, 0.686667083305587)
sage: EK.saturation([12*P], max_prime=2)
[(26/361 : -5720/6859 : 1)], 4, 6.18000374975028)
sage: EK.saturation([12*P], lower_ht_bound=0.1)
[(-1 : 1 : 1)], 12, 0.686667083305587)
sage: EK.saturation([2*P, Q], max_prime=2)
[(-1 : 1 : 1), (0 : -1 : 1)], 2, 0.152460177943144)
sage: EK.saturation([P+Q, P-Q], lower_ht_bound=.1, debug=2)
[(-1 : 1 : 1), (1 : 0 : 1)], 2, 0.152460177943144)
sage: EK.saturation([P+Q, 17*Q], lower_ht_bound=0.1)
[(4 : 8 : 1), (0 : -1 : 1)], 17, 0.152460177943143)

```



```

sage: R = EK(i-2,-i-3)
sage: EK.saturation([P+R, P+Q, Q+R], lower_ht_bound=0.1)
([ (841/1369*i - 171/1369 : 41334/50653*i - 74525/50653 : 1),
  (4 : 8 : 1),
  (-1/25*i + 18/25 : -69/125*i - 58/125 : 1)],
 2,
 0.103174443217351)
sage: EK.saturation([26*Q], lower_ht_bound=0.1)
([ (0 : -1 : 1)], 26, 0.327000773651605)

```

Another number field:

```

sage: E = EllipticCurve('389a1')
sage: K.<a> = NumberField(x^3-x+1)
sage: EK = E.change_ring(K)
sage: P = EK(-1,1); Q = EK(0,-1)
sage: EK.saturation([P+Q, P-Q], lower_ht_bound=0.1)
([ (-1 : 1 : 1), (1 : 0 : 1)], 2, 0.152460177943144)
sage: EK.saturation([3*P, P+5*Q], lower_ht_bound=0.1)
([ (-185/2209 : -119510/103823 : 1), (80041/34225 : -26714961/6331625 : 1)],
 15,
 0.152460177943144)

```

A different curve:

```

sage: K.<a> = QuadraticField(3)
sage: E = EllipticCurve('37a1')
sage: EK = E.change_ring(K)
sage: P = EK(0,0); Q = EK(2-a,2*a-4)
sage: EK.saturation([3*P-Q, 3*P+Q], lower_ht_bound=.01)
([ (0 : 0 : 1), (1/2*a : -1/4*a - 1/4 : 1)], 6, 0.0317814530725985)

```

The points must be linearly independent:

```

sage: EK.saturation([2*P, 3*Q, P-Q])
Traceback (most recent call last):
...
ValueError: points not linearly independent in saturation()

```

Degenerate case:

```

sage: EK.saturation([])
([], 1, 1.000000000000000)

```

#### ALGORITHM:

For rank 1 subgroups, simply do trial division up to the maximal prime divisor. For higher rank subgroups, perform trial division on all linear combinations for small primes, and look for projections  $E(K) \rightarrow \bigoplus E(k) \otimes \mathbf{F}_p$  which are either full rank or provide  $p$ -divisible linear combinations, where the  $k$  here are residue fields of  $K$ .

**simon\_two\_descent** (*verbose=0, lim1=2, lim3=4, limtriv=2, maxprob=20, limbigprime=30, known\_points=None*)

Return lower and upper bounds on the rank of the Mordell-Weil group  $E(K)$  and a list of points.

This method is used internally by the `rank()`, `rank_bounds()` and `gens()` methods.

INPUT:

- `self` – an elliptic curve  $E$  over a number field  $K$
- `verbose` – 0, 1, 2, or 3 (default: 0), the verbosity level
- `lim1` – (default: 2) limit on trivial points on quartics
- `lim3` – (default: 4) limit on points on ELS quartics
- `limtriv` – (default: 2) limit on trivial points on  $E$
- `maxprob` – (default: 20)
- `limbigprime` – (default: 30) to distinguish between small and large prime numbers. Use probabilistic tests for large primes. If 0, don't use probabilistic tests.
- `known_points` – (default: None) list of known points on the curve

OUTPUT: a triple `(lower, upper, list)` consisting of

- `lower` (integer) – lower bound on the rank
- `upper` (integer) – upper bound on the rank
- `list` – list of points in  $E(K)$

The integer `upper` is in fact an upper bound on the dimension of the 2-Selmer group, hence on the dimension of  $E(K)/2E(K)$ . It is equal to the dimension of the 2-Selmer group except possibly if  $E(K)[2]$  has dimension 1. In that case, `upper` may exceed the dimension of the 2-Selmer group by an even number, due to the fact that the algorithm does not perform a second descent.

---

**Note:** For non-quadratic number fields, this code does return, but it takes a long time.

---

#### ALGORITHM:

Uses Denis Simon's PARI/GP scripts from <http://www.math.unicaen.fr/~simon/>.

#### EXAMPLES:

```
sage: K.<a> = NumberField(x^2 + 23, 'a')
sage: E = EllipticCurve(K, '37')
sage: E == loads(dumps(E))
True
sage: E.simon_two_descent()
(2, 2, [(0 : 0 : 1), (1/8*a + 5/8 : -3/16*a - 7/16 : 1)])
sage: E.simon_two_descent(lim1=3, lim3=20, limtriv=5, maxprob=7,
↪limbigprime=10)
(2, 2, [(-1 : 0 : 1), (-1/8*a + 5/8 : -3/16*a - 9/16 : 1)])
```

```
sage: K.<a> = NumberField(x^2 + 7, 'a')
sage: E = EllipticCurve(K, [0,0,0,1,a]); E
Elliptic Curve defined by y^2 = x^3 + x + a over Number Field in a with
↪defining polynomial x^2 + 7

sage: v = E.simon_two_descent(verbose=1); v
elliptic curve: Y^2 = x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7)
Trivial points on the curve = [[1, 1, 0], [Mod(1/2*y + 3/2, y^2 + 7), Mod(-y
↪- 2, y^2 + 7), 1]]
#S(E/K)[2] = 2
#E(K)/2E(K) = 2
#III(E/K)[2] = 1
rank(E/K) = 1
```

```

listpoints = [[Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 + 7), 1]]
(1, 1, [(1/2*a + 3/2 : -a - 2 : 1)])

sage: v = E.simon_two_descent(verbose=2)
K = bnfinit(y^2 + 7);
a = Mod(y, K.pol);
bnfellrank(K, [0, 0, 0, 1, a], [[Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 +
↪ 7)]]);
elliptic curve: Y^2 = x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7)
A = Mod(0, y^2 + 7)
B = Mod(1, y^2 + 7)
C = Mod(y, y^2 + 7)

Computing L(S, 2)
L(S, 2) = [Mod(Mod(-1/2*y + 1/2, y^2 + 7)*x^2 + Mod(-1/2*y - 1/2, y^2 + 7)*x
↪ + Mod(-y - 1, y^2 + 7), x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7)),
↪ Mod(Mod(-1, y^2 + 7)*x^2 + Mod(-1/2*y - 1/2, y^2 + 7)*x + Mod(1, y^2 + 7),
↪ x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7)), Mod(-1, x^3 + Mod(1, y^2 + 7)*x
↪ + Mod(y, y^2 + 7)), Mod(x^2 + 2, x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7)),
↪ Mod(Mod(1, y^2 + 7)*x + Mod(1/2*y + 3/2, y^2 + 7), x^3 + Mod(1, y^2 + 7)*x
↪ + Mod(y, y^2 + 7)), Mod(Mod(1, y^2 + 7)*x + Mod(1/2*y - 3/2, y^2 + 7), x^3
↪ + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7))]

Computing the Selmer group
#LS2gen = 2
LS2gen = [Mod(Mod(-1/2*y + 1/2, y^2 + 7)*x^2 + Mod(-1/2*y - 1/2, y^2 +
↪ 7)*x + Mod(-y - 1, y^2 + 7), x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7)),
↪ Mod(Mod(1, y^2 + 7)*x^2 + Mod(1/2*y + 1/2, y^2 + 7)*x + Mod(-1, y^2 + 7), x^
↪ 3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7))]
Search for trivial points on the curve
Trivial points on the curve = [[Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 +
↪ 7)], [1, 1, 0], [Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 + 7), 1]]
zc = Mod(Mod(-1/2*y + 1/2, y^2 + 7)*x^2 + Mod(-1/2*y - 1/2, y^2 + 7)*x +
↪ Mod(-y - 1, y^2 + 7), x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7))
Hilbert symbol (Mod(1, y^2 + 7), Mod(-2*y + 2, y^2 + 7)) =
sol of quadratic equation = [1, 1, 0]~
zc*z1^2 = Mod(Mod(4, y^2 + 7)*x + Mod(-2*y + 6, y^2 + 7), x^3 + Mod(1, y^2
↪ + 7)*x + Mod(y, y^2 + 7))
quartic: (-1)*Y^2 = x^4 + (3*y - 9)*x^2 + (-8*y + 16)*x + (9/2*y - 11/2)
reduced: Y^2 = -x^4 + (-3*y + 9)*x^2 + (-8*y + 16)*x + (-9/2*y + 11/2)
not ELS at [2, [0, 1]~, 1, 1, [1, -2; 1, 0]]
zc = Mod(Mod(1, y^2 + 7)*x^2 + Mod(1/2*y + 1/2, y^2 + 7)*x + Mod(-1, y^2 +
↪ 7), x^3 + Mod(1, y^2 + 7)*x + Mod(y, y^2 + 7))
comes from the trivial point [Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 +
↪ 7)]
m1 = 1
m2 = 1
#S(E/K)[2] = 2
#E(K)/2E(K) = 2
#III(E/K)[2] = 1
rank(E/K) = 1
listpoints = [[Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 + 7)]]
v = [1, 1, [[Mod(1/2*y + 3/2, y^2 + 7), Mod(-y - 2, y^2 + 7)]]]
sage: v
(1, 1, [(1/2*a + 3/2 : -a - 2 : 1)])

```

A curve with 2-torsion:

```

sage: K.<a> = NumberField(x^2 + 7)
sage: E = EllipticCurve(K, '15a')
sage: E.simon_two_descent() # long time (3s on sage.math, 2013), points can_
↪ vary
(1, 3, [...])

```

Check that the bug reported in [trac ticket #15483](#) is fixed:

```

sage: K.<s> = QuadraticField(229)
sage: c4 = 2173 - 235*(1 - s)/2
sage: c6 = -124369 + 15988*(1 - s)/2
sage: E = EllipticCurve([-c4/48, -c6/864])
sage: E.simon_two_descent()
(0, 0, [])

sage: R.<t> = QQ[]
sage: L.<g> = NumberField(t^3 - 9*t^2 + 13*t - 4)
sage: E1 = EllipticCurve(L, [1-g*(g-1), -g^2*(g-1), -g^2*(g-1), 0, 0])
sage: E1.rank() # long time (about 5 s)
0

sage: K = CyclotomicField(43).subfields(3)[0][0]
sage: E = EllipticCurve(K, '37')
sage: E.simon_two_descent() # long time (4s on sage.math, 2013)
(3,
 3,
 [(0 : 0 : 1),
  (-1/2*zeta43_0^2 - 1/2*zeta43_0 + 7 : -3/2*zeta43_0^2 - 5/2*zeta43_0 + 18 :_
↪ 1)])

```

**tamagawa\_exponent** ( $P$ ,  $proof=None$ )

Returns the Tamagawa index of this elliptic curve at the prime  $P$ .

INPUT:

- $P$  – either None or a prime ideal of the base field of self.
- $proof$  – whether to only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the flag are in number fields.

OUTPUT:

(positive integer) The Tamagawa index of the curve at  $P$ .

EXAMPLES:

```

sage: K.<a>=NumberField(x^2-5)
sage: E=EllipticCurve([20, 225, 750, 625*a + 6875, 31250*a + 46875])
sage: [E.tamagawa_exponent(P) for P in E.discriminant().support()]
[1, 1, 1, 1]
sage: K.<a> = QuadraticField(-11)
sage: E = EllipticCurve('11a1').change_ring(K)
sage: [E.tamagawa_exponent(P) for P in K(11).support()]
[10]

```

**tamagawa\_number** ( $P$ ,  $proof=None$ )

Returns the Tamagawa number of this elliptic curve at the prime  $P$ .

INPUT:

- $P$  – either None or a prime ideal of the base field of self.
- `proof` – whether to only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the flag are in number fields.

OUTPUT:

(positive integer) The Tamagawa number of the curve at  $P$ .

EXAMPLES:

```
sage: K.<a>=NumberField(x^2-5)
sage: E=EllipticCurve([20, 225, 750, 625*a + 6875, 31250*a + 46875])
sage: [E.tamagawa_number(P) for P in E.discriminant().support()]
[1, 1, 1, 1]
sage: K.<a> = QuadraticField(-11)
sage: E = EllipticCurve('11a1').change_ring(K)
sage: [E.tamagawa_number(P) for P in K(11).support()]
[10]
```

**tamagawa\_numbers()**

Return a list of all Tamagawa numbers for all prime divisors of the conductor (in order).

EXAMPLES:

```
sage: e = EllipticCurve('30a1')
sage: e.tamagawa_numbers()
[2, 3, 1]
sage: vector(e.tamagawa_numbers())
(2, 3, 1)
sage: K.<a>=NumberField(x^2+3)
sage: eK = e.base_extend(K)
sage: eK.tamagawa_numbers()
[4, 6, 1]
```

**tamagawa\_product\_bsd()**

Given an elliptic curve  $E$  over a number field  $K$ , this function returns the integer  $C(E/K)$  that appears in the Birch and Swinnerton-Dyer conjecture accounting for the local information at finite places. If the model is a global minimal model then  $C(E/K)$  is simply the product of the Tamagawa numbers  $c_v$  where  $v$  runs over all prime ideals of  $K$ . Otherwise, if the model has to be changed at a place  $v$  a correction factor appears. The definition is such that  $C(E/K)$  times the periods at the infinite places is invariant under change of the Weierstrass model. See [Tate1966] and [DD2010] for details.

---

**Note:** This definition is slightly different from the definition of `tamagawa_product` for curves defined over  $\mathbb{Q}$ . Over the rational number it is always defined to be the product of the Tamagawa numbers, so the two definitions only agree when the model is global minimal.

---

OUTPUT:

A rational number

EXAMPLES:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([0, 2+i])
sage: E.tamagawa_product_bsd()
1
```

```
sage: E = EllipticCurve([(2*i+1)^2, i*(2*i+1)^7])
sage: E.tamagawa_product_bsd()
4
```

An example where the Neron model changes over  $K$ :

```
sage: K.<t> = NumberField(x^5-10*x^3+5*x^2+10*x+1)
sage: E = EllipticCurve(K, '75a1')
sage: E.tamagawa_product_bsd()
5
sage: da = E.local_data()
sage: [dav.tamagawa_number() for dav in da]
[1, 1]
```

An example over  $\mathbb{Q}$  ([trac ticket #9413](#)):

```
sage: E = EllipticCurve('30a')
sage: E.tamagawa_product_bsd()
6
```

### **torsion\_order()**

Returns the order of the torsion subgroup of this elliptic curve.

OUTPUT:

(integer) the order of the torsion subgroup of this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: K.<t> = NumberField(x^4 + x^3 + 11*x^2 + 41*x + 101)
sage: EK = E.base_extend(K)
sage: EK.torsion_order() # long time (2s on sage.math, 2014)
25
```

```
sage: E = EllipticCurve('15a1')
sage: K.<t> = NumberField(x^2 + 2*x + 10)
sage: EK = E.base_extend(K)
sage: EK.torsion_order()
16
```

```
sage: E = EllipticCurve('19a1')
sage: K.<t> = NumberField(x^9-3*x^8-4*x^7+16*x^6-3*x^5-21*x^4+5*x^3+7*x^2-
↪ 7*x+1)
sage: EK = E.base_extend(K)
sage: EK.torsion_order()
9
```

```
sage: K.<i> = QuadraticField(-1)
sage: EK = EllipticCurve([0,0,0,i,i+3])
sage: EK.torsion_order()
1
```

### **torsion\_points()**

Returns a list of the torsion points of this elliptic curve.

OUTPUT:

(list) A sorted list of the torsion points.

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.torsion_points()
[(0 : 1 : 0), (5 : -6 : 1), (5 : 5 : 1), (16 : -61 : 1), (16 : 60 : 1)]
sage: K.<t> = NumberField(x^4 + x^3 + 11*x^2 + 41*x + 101)
sage: EK = E.base_extend(K)
sage: EK.torsion_points() # long time (1s on sage.math, 2014)
[(0 : 1 : 0),
 (16 : 60 : 1),
 (5 : 5 : 1),
 (5 : -6 : 1),
 (16 : -61 : 1),
 (t : 1/11*t^3 + 6/11*t^2 + 19/11*t + 48/11 : 1),
 (-3/55*t^3 - 7/55*t^2 - 2/55*t - 133/55 : 6/55*t^3 + 3/55*t^2 + 25/11*t +
 ↪ 156/55 : 1),
 (-9/121*t^3 - 21/121*t^2 - 127/121*t - 377/121 : -7/121*t^3 + 24/121*t^2 +
 ↪ 197/121*t + 16/121 : 1),
 (5/121*t^3 - 14/121*t^2 - 158/121*t - 453/121 : -49/121*t^3 - 129/121*t^2 -
 ↪ 315/121*t - 207/121 : 1),
 (10/121*t^3 + 49/121*t^2 + 168/121*t + 73/121 : 32/121*t^3 + 60/121*t^2 -
 ↪ 261/121*t - 807/121 : 1),
 (1/11*t^3 - 5/11*t^2 + 19/11*t - 40/11 : -6/11*t^3 - 3/11*t^2 - 26/11*t -
 ↪ 321/11 : 1),
 (14/121*t^3 - 15/121*t^2 + 90/121*t + 232/121 : 16/121*t^3 - 69/121*t^2 +
 ↪ 293/121*t - 46/121 : 1),
 (3/55*t^3 + 7/55*t^2 + 2/55*t + 78/55 : 7/55*t^3 - 24/55*t^2 + 9/11*t + 17/
 ↪ 55 : 1),
 (-5/121*t^3 + 36/121*t^2 - 84/121*t + 24/121 : 34/121*t^3 - 27/121*t^2 + 305/
 ↪ 121*t + 708/121 : 1),
 (-26/121*t^3 + 20/121*t^2 - 219/121*t - 995/121 : 15/121*t^3 + 156/121*t^2 -
 ↪ 232/121*t + 2766/121 : 1),
 (1/11*t^3 - 5/11*t^2 + 19/11*t - 40/11 : 6/11*t^3 + 3/11*t^2 + 26/11*t + 310/
 ↪ 11 : 1),
 (-26/121*t^3 + 20/121*t^2 - 219/121*t - 995/121 : -15/121*t^3 - 156/121*t^2 -
 ↪ + 232/121*t - 2887/121 : 1),
 (-5/121*t^3 + 36/121*t^2 - 84/121*t + 24/121 : -34/121*t^3 + 27/121*t^2 -
 ↪ 305/121*t - 829/121 : 1),
 (3/55*t^3 + 7/55*t^2 + 2/55*t + 78/55 : -7/55*t^3 + 24/55*t^2 - 9/11*t - 72/
 ↪ 55 : 1),
 (14/121*t^3 - 15/121*t^2 + 90/121*t + 232/121 : -16/121*t^3 + 69/121*t^2 -
 ↪ 293/121*t - 75/121 : 1),
 (t : -1/11*t^3 - 6/11*t^2 - 19/11*t - 59/11 : 1),
 (10/121*t^3 + 49/121*t^2 + 168/121*t + 73/121 : -32/121*t^3 - 60/121*t^2 +
 ↪ 261/121*t + 686/121 : 1),
 (5/121*t^3 - 14/121*t^2 - 158/121*t - 453/121 : 49/121*t^3 + 129/121*t^2 +
 ↪ 315/121*t + 86/121 : 1),
 (-9/121*t^3 - 21/121*t^2 - 127/121*t - 377/121 : 7/121*t^3 - 24/121*t^2 -
 ↪ 197/121*t - 137/121 : 1),
 (-3/55*t^3 - 7/55*t^2 - 2/55*t - 133/55 : -6/55*t^3 - 3/55*t^2 - 25/11*t -
 ↪ 211/55 : 1)]
```

```
sage: E = EllipticCurve('15a1')
sage: K.<t> = NumberField(x^2 + 2*x + 10)
sage: EK = E.base_extend(K)
sage: EK.torsion_points()
[(-7 : -5*t - 2 : 1),
```

```
(-7 : 5*t + 8 : 1),
(-13/4 : 9/8 : 1),
(-2 : -2 : 1),
(-2 : 3 : 1),
(-t - 2 : -t - 7 : 1),
(-t - 2 : 2*t + 8 : 1),
(-1 : 0 : 1),
(t : t - 5 : 1),
(t : -2*t + 4 : 1),
(0 : 1 : 0),
(1/2 : -5/4*t - 2 : 1),
(1/2 : 5/4*t + 1/2 : 1),
(3 : -2 : 1),
(8 : -27 : 1),
(8 : 18 : 1)]
```

```
sage: K.<i> = QuadraticField(-1)
sage: EK = EllipticCurve(K, [0,0,0,0,-1])
sage: EK.torsion_points ()
[(-2 : -3*i : 1), (-2 : 3*i : 1), (0 : -i : 1), (0 : i : 1), (0 : 1 : 0), (1,
↪ : 0 : 1)]
```

**torsion\_subgroup()**

Returns the torsion subgroup of this elliptic curve.

OUTPUT:

(EllipticCurveTorsionSubgroup) The EllipticCurveTorsionSubgroup associated to this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: K.<t>=NumberField(x^4 + x^3 + 11*x^2 + 41*x + 101)
sage: EK = E.base_extend(K)
sage: tor = EK.torsion_subgroup() # long time (2s on sage.math, 2014)
sage: tor # long time
Torsion Subgroup isomorphic to Z/5 + Z/5 associated to the Elliptic Curve
↪ defined by y^2 + y = x^3 + (-1)*x^2 + (-10)*x + (-20) over Number Field in
↪ t with defining polynomial x^4 + x^3 + 11*x^2 + 41*x + 101
sage: tor.gens() # long time
((16 : 60 : 1), (t : 1/11*t^3 + 6/11*t^2 + 19/11*t + 48/11 : 1))
```

```
sage: E = EllipticCurve('15a1')
sage: K.<t>=NumberField(x^2 + 2*x + 10)
sage: EK=E.base_extend(K)
sage: EK.torsion_subgroup()
Torsion Subgroup isomorphic to Z/4 + Z/4 associated to the Elliptic Curve
↪ defined by y^2 + x*y + y = x^3 + x^2 + (-10)*x + (-10) over Number Field in
↪ t with defining polynomial x^2 + 2*x + 10
```

```
sage: E = EllipticCurve('19a1')
sage: K.<t>=NumberField(x^9-3*x^8-4*x^7+16*x^6-3*x^5-21*x^4+5*x^3+7*x^2-7*x+1)
sage: EK=E.base_extend(K)
sage: EK.torsion_subgroup()
Torsion Subgroup isomorphic to Z/9 associated to the Elliptic Curve defined
↪ by y^2 + y = x^3 + x^2 + (-9)*x + (-15) over Number Field in t with
↪ defining polynomial x^9 - 3*x^8 - 4*x^7 + 16*x^6 - 3*x^5 - 21*x^4 + 5*x^3 +
↪ 7*x^2 - 7*x + 1
```



```

sage: K.<i> = QuadraticField(-1)
sage: EK = EllipticCurve([0,0,0,i,i+3])
sage: EK.torsion_subgroup ()
Torsion Subgroup isomorphic to Trivial group associated to the Elliptic Curve
↪ defined by  $y^2 = x^3 + ix + (i+3)$  over Number Field in  $i$  with defining
↪ polynomial  $x^2 + 1$ 

```

### 15.11.4 Canonical heights for elliptic curves over number fields

Also, rigorous lower bounds for the canonical height of non-torsion points, implementing the algorithms in [\[CS\]](#) (over  $\mathbb{Q}$ ) and [\[TT\]](#), which also refer to [\[CPS\]](#).

AUTHORS:

- Robert Bradshaw (2010): initial version
- John Cremona (2014): added many docstrings and doctests

REFERENCES:

**class** sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight ( $E$ )  
 Class for computing canonical heights of points on elliptic curves defined over number fields, including rigorous lower bounds for the canonical height of non-torsion points.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.height import EllipticCurveCanonicalHeight
sage: E = EllipticCurve([0,0,0,0,1])
sage: EllipticCurveCanonicalHeight(E)
EllipticCurveCanonicalHeight object associated to Elliptic Curve defined by  $y^2 =$ 
↪  $x^3 + 1$  over Rational Field

```

Normally this object would be created like this:

```

sage: E.height_function()
EllipticCurveCanonicalHeight object associated to Elliptic Curve defined by  $y^2 =$ 
↪  $x^3 + 1$  over Rational Field

```

**B** ( $n, \mu$ )

Return the value  $B_n(\mu)$ .

INPUT:

- $n$  (int) - a positive integer
- $\mu$  (real) - a positive real number

OUTPUT:

The real value  $B_n(\mu)$  as defined in [\[TT\]](#), section 5.

EXAMPLES:

Example 10.2 from [\[TT\]](#):

```

sage: K.<i>=QuadraticField(-1)
sage: E = EllipticCurve([0,1-i,i,-i,0])
sage: H = E.height_function()

```

In [\[TT\]](#) the value is given as 0.772:

```
sage: RealField(12)( H.B(5, 0.01) )
0.777
```

**DE**( $n$ )

Return the value  $D_E(n)$ .

INPUT:

- $n$  (int) - a positive integer

OUTPUT:

The value  $D_E(n)$  as defined in [\[TT\]](#), section 4.

EXAMPLES:

```
sage: K.<i>=QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,1+5*i,3+i])
sage: H = E.height_function()
sage: [H.DE(n) for n in xrange(1,6)]
[0, 2*log(5) + 2*log(2), 0, 2*log(13) + 2*log(5) + 4*log(2), 0]
```

**ME**()

Return the norm of the ideal  $M_E$ .

OUTPUT:

The norm of the ideal  $M_E$  as defined in [\[TT\]](#), section 3.1. This is 1 if  $E$  is a global minimal model, and in general measures the non-minimality of  $E$ .

EXAMPLES:

```
sage: K.<i>=QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,1+5*i,3+i])
sage: H = E.height_function()
sage: H.ME()
1
sage: E = EllipticCurve([0,0,0,0,1])
sage: E.height_function().ME()
1
sage: E = EllipticCurve([0,0,0,0,64])
sage: E.height_function().ME()
4096
sage: E.discriminant()/E.minimal_model().discriminant()
4096
```

**S**( $xi1, xi2, v$ )

Return the union of intervals  $S^{(v)}(\xi_1, \xi_2)$ .

INPUT:

- $xi1, xi2$  (real) - real numbers with  $\xi_1 \leq \xi_2$ .
- $v$  (embedding) - a real embedding of the field.

OUTPUT:

The union of intervals  $S^{(v)}(\xi_1, \xi_2)$  defined in [\[TT\]](#) section 6.1.

EXAMPLES:

An example over  $\mathbb{Q}$ :

```

sage: E = EllipticCurve('389a')
sage: v = QQ.places()[0]
sage: H = E.height_function()
sage: H.S(2,3,v)
([0.224512677391895, 0.274544821597130] U [0.725455178402870, 0.
↪ 775487322608105])

```

An example over a number field:

```

sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,0,a])
sage: v = K.real_places()[0]
sage: H = E.height_function()
sage: H.S(9,10,v)
([0.0781194447253472, 0.0823423732016403] U [0.917657626798360, 0.
↪ 921880555274653])

```

**Sn** (*xi1*, *xi2*, *n*, *v*)

Return the union of intervals  $S_n^{(v)}(\xi_1, \xi_2)$ .

INPUT:

- *xi1*, *xi2* (real) - real numbers with  $\xi_1 \leq \xi_2$ .
- *n* (integer) - a positive integer.
- *v* (embedding) - a real embedding of the field.

OUTPUT:

The union of intervals  $S_n^{(v)}(\xi_1, \xi_2)$  defined in [TT] (Lemma 6.1).

EXAMPLES:

An example over  $\mathbb{Q}$ :

```

sage: E = EllipticCurve('389a')
sage: v = QQ.places()[0]
sage: H = E.height_function()
sage: H.S(2,3,v) , H.Sn(2,3,1,v)
([0.224512677391895, 0.274544821597130] U [0.725455178402870, 0.
↪ 775487322608105]),
([0.224512677391895, 0.274544821597130] U [0.725455178402870, 0.
↪ 775487322608105]))
sage: H.Sn(2,3,6,v)
([0.0374187795653158, 0.0457574702661884] U [0.120909196400478, 0.
↪ 129247887101351] U [0.204085446231982, 0.212424136932855] U [0.
↪ 287575863067145, 0.295914553768017] U [0.370752112898649, 0.
↪ 379090803599522] U [0.454242529733812, 0.462581220434684] U [0.
↪ 537418779565316, 0.545757470266188] U [0.620909196400478, 0.
↪ 629247887101351] U [0.704085446231982, 0.712424136932855] U [0.
↪ 787575863067145, 0.795914553768017] U [0.870752112898649, 0.
↪ 879090803599522] U [0.954242529733812, 0.962581220434684])

```

An example over a number field:

```

sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,0,a])
sage: v = K.real_places()[0]
sage: H = E.height_function()
sage: H.S(2,3,v) , H.Sn(2,3,1,v)

```

```

([0.142172065860075, 0.172845716928584] U [0.827154283071416, 0.
↪857827934139925]),
([0.142172065860075, 0.172845716928584] U [0.827154283071416, 0.
↪857827934139925]))
sage: H.Sn(2,3,6,v)
([0.0236953443100124, 0.0288076194880974] U [0.137859047178569, 0.
↪142971322356654] U [0.190362010976679, 0.195474286154764] U [0.
↪304525713845236, 0.309637989023321] U [0.357028677643346, 0.
↪362140952821431] U [0.471192380511903, 0.476304655689988] U [0.
↪523695344310012, 0.528807619488097] U [0.637859047178569, 0.
↪642971322356654] U [0.690362010976679, 0.695474286154764] U [0.
↪804525713845236, 0.809637989023321] U [0.857028677643346, 0.
↪862140952821431] U [0.971192380511903, 0.976304655689988])

```

**alpha** (*v*, *tol*=0.01)

Return the constant  $\alpha_v$  associated to the embedding *v*.

INPUT:

- *v* – an embedding of the base field into  $\mathbf{R}$  or  $\mathbf{C}$

OUTPUT:

The constant  $\alpha_v$ . In the notation of [CPS] (2006) and [TT] (section 3.2),  $\alpha_v^3 = \epsilon_v$ . The result is cached since it only depends on the curve.

EXAMPLES:

Example 1 from [CPS] (2006):

```

sage: K.<i>=QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,1+5*i,3+i])
sage: H = E.height_function()
sage: alpha = H.alpha(K.places()[0])
sage: alpha
1.12272013439355

```

Compare with  $\log(\epsilon_v) = 0.344562\dots$  in [CPS]:

```

sage: 3*alpha.log()
0.347263296676126

```

**base\_field** ()

Return the base field.

EXAMPLES:

```

sage: E = EllipticCurve([0,0,0,0,1])
sage: H = E.height_function()
sage: H.base_field()
Rational Field

```

**complex\_intersection\_is\_empty** (*Bk*, *v*, *verbose*=False, *use\_half*=True)

Returns True iff an intersection of  $T_n^{(v)}$  sets is empty.

INPUT:

- *Bk* (list) - a list of reals.
- *v* (embedding) - a complex embedding of the number field.

- `verbose` (boolean, default False) - verbosity flag.
- `use_half` (boolean, default False) - if True, use only half the fundamental region.

OUTPUT:

True or False, according as the intersection of the unions of intervals  $T_n^{(v)}(-b, b)$  for  $b$  in the list  $B_k$  (see [TT], section 7) is empty or not. When  $B_k$  is the list of  $b = \sqrt{B_n(\mu)}$  for  $n = 1, 2, 3, \dots$  for some  $\mu > 0$  this means that all non-torsion points on  $E$  with everywhere good reduction have canonical height strictly greater than  $\mu$ , by [TT], Proposition 7.8.

EXAMPLES:

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,0,a])
sage: v = K.complex_embeddings()[0]
sage: H = E.height_function()
```

The following two lines prove that the heights of non-torsion points on  $E$  with everywhere good reduction have canonical height strictly greater than 0.02, but fail to prove the same for 0.03. For the first proof, using only  $n = 1, 2, 3$  is not sufficient:

```
sage: H.complex_intersection_is_empty([H.B(n,0.02) for n in [1,2,3]],v) #_
↳long time (~6s)
False
sage: H.complex_intersection_is_empty([H.B(n,0.02) for n in [1,2,3,4]],v)
True
sage: H.complex_intersection_is_empty([H.B(n,0.03) for n in [1,2,3,4]],v) #_
↳long time (4s)
False
```

Using  $n \leq 6$  enables us to prove the lower bound 0.03. Note that it takes longer when the result is False than when it is True:

```
sage: H.complex_intersection_is_empty([H.B(n,0.03) for n in [1..6]],v)
True
```

**curve()**

Return the elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve([0,0,0,0,1])
sage: H = E.height_function()
sage: H.curve()
Elliptic Curve defined by y^2 = x^3 + 1 over Rational Field
```

**e\_p(p)**

Return the exponent of the group over the residue field at  $p$ .

INPUT:

- $p$  - a prime ideal of  $K$  (or a prime number if  $K = \mathbb{Q}$ ).

OUTPUT:

A positive integer  $e_p$ , the exponent of the group of nonsingular points on the reduction of the elliptic curve modulo  $p$ . The result is cached.

EXAMPLES:

```

sage: K.<i>=QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,1+5*i,3+i])
sage: H = E.height_function()
sage: H.e_p(K.prime_above(2))
2
sage: H.e_p(K.prime_above(3))
10
sage: H.e_p(K.prime_above(5))
9
sage: E.conductor().norm().factor()
2^10 * 20921
sage: p1, p2 = K.primes_above(20921)
sage: E.local_data(p1)
Local data at Fractional ideal (-40*i + 139):
Reduction type: bad split multiplicative
...
sage: H.e_p(p1)
20920
sage: E.local_data(p2)
Local data at Fractional ideal (40*i + 139):
Reduction type: good
...
sage: H.e_p(p2)
20815

```

**fk\_intervals** ( $v=None$ ,  $N=20$ ,  $domain=Complex\ Interval\ Field\ with\ 53\ bits\ of\ precision$ )

Return a function approximating the Weierstrass function, with error.

INPUT:

- $v$  (embedding) - an embedding of the number field. If  $None$  (default) use the real embedding if the field is  $\mathbb{Q}$  and raise an error for other fields.
- $N$  (int) - The number of terms to use in the  $q$ -expansion of  $\wp$ .
- $domain$  (complex field) - the model of  $\mathbb{C}$  to use, for example CDF or CIF (default).

OUTPUT:

A pair of functions  $fk$ ,  $err$  which can be evaluated at complex numbers  $z$  (in the correct domain) to give an approximation to  $\wp(z)$  and an upper bound on the error, respectively. The Weierstrass function returned is with respect to the normalised lattice  $[1, \tau]$  associated to the given embedding.

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: L = E.period_lattice()
sage: w1, w2 = L.normalised_basis()
sage: z = CDF(0.3, 0.4)

```

Compare the value give by the standard elliptic exponential (scaled since  $fk$  is with respect to the normalised lattice):

```

sage: L.elliptic_exponential(z*w2, to_curve=False)[0] * w2 ** 2
-1.82543539306049 - 2.49336319992847*I

```

to the value given by this function, and see the error:

```

sage: fk, err = E.height_function().fk_intervals(N=10)
sage: fk(CIF(z))

```

```
-1.82543539306049? - 2.49336319992847?*I
sage: err(CIF(z))
2.71750621458744e-31
```

The same, but in the domain CDF instad of CIF:

```
sage: fk, err = E.height_function().fk_intervals(N=10, domain=CDF)
sage: fk(z)
-1.8254353930604... - 2.493363199928...*I
```

**min** (*tol*, *n\_max*, *verbose=False*)

Returns a lower bound for all points of infinite order.

INPUT:

- *tol* - tolerance in output (see below).
- *n\_max* - how many multiples to use in iteration.
- *verbose* (boolean, default False) - verbosity flag.

OUTPUT:

A positive real  $\mu$  for which it has been established rigorously that every point of infinite order on the elliptic curve (defined over its ground field) has canonical height greater than  $\mu$ , and such that it is not possible (at least without increasing *n\_max*) to prove the same for  $\mu \cdot \text{tol}$ .

EXAMPLES:

Example 1 from [CS] (where the same lower bound of 0.1126 was given):

```
sage: E = EllipticCurve([1, 0, 1, 421152067, 105484554028056]) # 60490d1
sage: E.height_function().min(.0001, 5)
0.0011263287309893311
```

Example 10.1 from [TT] (where a lower bound of 0.18 was given):

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,91-26*i,-144-323*i])
sage: H = E.height_function()
sage: H.min(0.1,4) # long time (8.1s)
0.1621049443313762
```

Example 10.2 from [TT]:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,1-i,i,-i,0])
sage: H = E.height_function()
sage: H.min(0.01,5) # long time (4s)
0.020153685521979152
```

In this example the point  $P = (0,0)$  has height 0.023 so our lower bound is quite good:

```
sage: P = E((0,0))
sage: P.height()
0.0230242154471211
```

Example 10.3 from [TT] (where the same bound of 0.0625 is given):

```

sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,-3*a-a^2,a^2])
sage: H = E.height_function()
sage: H.min(0.1,5) # long time (7s)
0.0625

```

More examples over  $\mathbb{Q}$ :

```

sage: E = EllipticCurve('37a')
sage: h = E.height_function()
sage: h.min(.01, 5)
0.03987318057488725
sage: E.gen(0).height()
0.0511114082399688

```

After base change the lower bound can decrease:

```

sage: K.<a> = QuadraticField(-5)
sage: E.change_ring(K).height_function().min(0.5, 10) # long time (8s)
0.04419417382415922

sage: E = EllipticCurve('389a')
sage: h = E.height_function()
sage: h.min(0.1, 5)
0.05731275270029196
sage: [P.height() for P in E.gens()]
[0.686667083305587, 0.327000773651605]

```

**min\_gr** (*tol*, *n\_max*, *verbose=False*)

Returns a lower bound for points of infinite order with good reduction.

INPUT:

- *tol* - tolerance in output (see below).
- *n\_max* - how many multiples to use in iteration.
- *verbose* (boolean, default False) - verbosity flag.

OUTPUT:

A positive real  $\mu$  for which it has been established rigorously that every point of infinite order on the elliptic curve (defined over its ground field), which has good reduction at all primes, has canonical height greater than  $\mu$ , and such that it is not possible (at least without increasing *n\_max*) to prove the same for  $\mu \cdot \text{tol}$ .

EXAMPLES:

Example 1 from [CS] (where a lower bound of 1.9865 was given):

```

sage: E = EllipticCurve([1, 0, 1, 421152067, 105484554028056]) # 60490d1
sage: E.height_function().min_gr(.0001, 5)
1.98684388146518

```

Example 10.1 from [TT] (where a lower bound of 0.18 was given):

```

sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,91-26*i,-144-323*i])
sage: H = E.height_function()
sage: H.min_gr(0.1,4) # long time (8.1s)
0.1621049443313762

```



Example 10.2 from [TT]:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0,1-i,i,-i,0])
sage: H = E.height_function()
sage: H.min_gr(0.01,5)
0.020153685521979152
```

In this example the point  $P = (0, 0)$  has height 0.023 so our lower bound is quite good:

```
sage: P = E((0,0))
sage: P.has_good_reduction()
True
sage: P.height()
0.0230242154471211
```

Example 10.3 from [TT] (where the same bound of 0.25 is given):

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,-3*a-a^2,a^2])
sage: H = E.height_function()
sage: H.min_gr(0.1,5) # long time (7.2s)
0.25
```

**psi** ( $x_i, v$ )

Return the normalised elliptic log of a point with this x-coordinate.

INPUT:

- $x_i$  (real) - the real x-coordinate of a point on the curve in the connected component with respect to a real embedding.
- $v$  (embedding) - a real embedding of the number field.

OUTPUT:

A real number in the interval  $[0.5, 1]$  giving the elliptic logarithm of a point on  $E$  with  $x$ -coordinate  $x_i$ , on the connected component with respect to the embedding  $v$ , scaled by the real period.

EXAMPLES:

An example over  $\mathbb{Q}$ :

```
sage: E = EllipticCurve('389a')
sage: v = QQ.places()[0]
sage: L = E.period_lattice(v)
sage: P = E.lift_x(10/9)
sage: L(P)
1.53151606047462
sage: L(P) / L.real_period()
0.615014189772115
sage: H = E.height_function()
sage: H.psi(10/9, v)
0.615014189772115
```

An example over a number field:

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,0,a])
sage: P = E.lift_x(1/3*a^2 + a + 5/3)
sage: v = K.real_places()[0]
```

```

sage: L = E.period_lattice(v)
sage: L(P)
3.51086196882538
sage: L(P) / L.real_period()
0.867385122699931
sage: xP = v(P.xy()[0])
sage: H = E.height_function()
sage: H.psi(xP, v)
0.867385122699931
sage: H.psi(1.23, v)
0.785854718241495

```

**real\_intersection\_is\_empty**( $Bk, v$ )

Returns True iff an intersection of  $S_n^{(v)}$  sets is empty.

INPUT:

- $Bk$  (list) - a list of reals.
- $v$  (embedding) - a real embedding of the number field.

OUTPUT:

True or False, according as the intersection of the unions of intervals  $S_n^{(v)}(-b, b)$  for  $b$  in the list  $Bk$  is empty or not. When  $Bk$  is the list of  $b = B_n(\mu)$  for  $n = 1, 2, 3, \dots$  for some  $\mu > 0$  this means that all non-torsion points on  $E$  with everywhere good reduction have canonical height strictly greater than  $\mu$ , by [TT], Proposition 6.2.

EXAMPLES:

An example over  $\mathbb{Q}$ :

```

sage: E = EllipticCurve('389a')
sage: v = QQ.places()[0]
sage: H = E.height_function()

```

The following two lines prove that the heights of non-torsion points on  $E$  with everywhere good reduction have canonical height strictly greater than 0.2, but fail to prove the same for 0.3:

```

sage: H.real_intersection_is_empty([H.B(n,0.2) for n in range(1,10)],v)
True
sage: H.real_intersection_is_empty([H.B(n,0.3) for n in range(1,10)],v)
False

```

An example over a number field:

```

sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,0,a])
sage: v = K.real_places()[0]
sage: H = E.height_function()

```

The following two lines prove that the heights of non-torsion points on  $E$  with everywhere good reduction have canonical height strictly greater than 0.07, but fail to prove the same for 0.08:

```

sage: H.real_intersection_is_empty([H.B(n,0.07) for n in range(1,5)],v) #_
↪long time (3.3s)
True
sage: H.real_intersection_is_empty([H.B(n,0.08) for n in range(1,5)],v)
False

```

**tau**( $v$ )Return the normalised upper half-plane parameter  $\tau$  for the period lattice with respect to the embedding  $v$ .

INPUT:

- $v$  (embedding) - a real or complex embedding of the number field.

OUTPUT:

(Complex)  $\tau = \omega_1/\omega_2$  in the fundamental region of the upper half-plane.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: H = E.height_function()
sage: H.tau(QQ.places()[0])
1.22112736076463*I
```

**test\_mu**( $\mu$ ,  $N$ ,  $\text{verbose}=\text{True}$ )Return True if we can prove that  $\mu$  is a lower bound.

INPUT:

- $\mu$  (real) - a positive real number
- $N$  (integer) - upper bound on the multiples to be used.
- $\text{verbose}$  (boolean, default True) - verbosity flag.

OUTPUT:

True or False, according to whether we succeed in proving that  $\mu$  is a lower bound for the canonical heights of points of infinite order with everywhere good reduction.

---

**Note:** A True result is rigorous; False only means that the attempt failed: trying again with larger  $N$  may yield True.

---

EXAMPLES:

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,0,0,0,a])
sage: H = E.height_function()
```

This curve does have a point of good reduction whose canonical point is approximately 1.68:

```
sage: P = E.gens(lim3=5)[0]; P
(1/3*a^2 + a + 5/3 : -2*a^2 - 4/3*a - 5/3 : 1)
sage: P.height()
1.68038085233673
sage: P.has_good_reduction()
True
```

Using  $N = 5$  we can prove that 0.1 is a lower bound (in fact we only need  $N = 2$ ), but not that 0.2 is:

```
sage: H.test_mu(0.1, 5)
B_1(0.100000000000000) = 1.51580969677387
B_2(0.100000000000000) = 0.932072561526720
True
sage: H.test_mu(0.2, 5)
B_1(0.200000000000000) = 2.04612906979932
B_2(0.200000000000000) = 3.09458988474327
```

```

B_3(0.2000000000000000) = 27.6251108409484
B_4(0.2000000000000000) = 1036.24722370223
B_5(0.2000000000000000) = 3.67090854562318e6
False

```

Since 0.1 is a lower bound we can deduce that the point  $P$  is either primitive or divisible by either 2 or 3. In fact it is primitive:

```

sage: (P.height()/0.1).sqrt()
4.09924487233530
sage: P.division_points(2)
[]
sage: P.division_points(3)
[]

```

**wp\_c**( $v$ )

Return a bound for the Weierstrass  $\wp$ -function.

INPUT:

- $v$  (embedding) - a real or complex embedding of the number field.

OUTPUT:

(Real)  $c > 0$  such that

$$|\wp(z) - z^{-2}| \leq \frac{c^2 |z|^2}{1 - c|z|^2}$$

whenever  $c|z|^2 < 1$ . Given the recurrence relations for the Laurent series expansion of  $\wp$ , it is easy to see that there is such a constant  $c$ . [Reference?]

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: H = E.height_function()
sage: H.wp_c(QQ.places()[0])
2.68744508779950

sage: K.<i>=QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,1+5*i,3+i])
sage: H = E.height_function()
sage: H.wp_c(K.places()[0])
2.66213425640096

```

**wp\_intervals**( $v=None, N=20, abs\_only=False$ )

Return a function approximating the Weierstrass function.

INPUT:

- $v$  (embedding) - an embedding of the number field. If None (default) use the real embedding if the field is  $\mathbb{Q}$  and raise an error for other fields.
- $N$  (int, default 20) - The number of terms to use in the  $q$ -expansion of  $\wp$ .
- $abs\_only$  (boolean, default False) - flag to determine whether (if True) the error adjustment should use the absolute value or (if False) the real and imaginary parts.

OUTPUT:

A function `wp` which can be evaluated at complex numbers  $z$  to give an approximation to  $\wp(z)$ . The Weierstrass function returned is with respect to the normalised lattice  $[1, \tau]$  associated to the given embedding. For  $z$  which are not near a lattice point the function `fk` is used, otherwise a better approximation is used.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: wp = E.height_function().wp_intervals()
sage: z = CDF(0.3, 0.4)
sage: wp(CIF(z))
-1.82543539306049? - 2.4933631999285?*I

sage: L = E.period_lattice()
sage: w1, w2 = L.normalised_basis()
sage: L.elliptic_exponential(z*w2, to_curve=False)[0] * w2^2
-1.82543539306049 - 2.49336319992847*I

sage: z = CDF(0.3, 0.1)
sage: wp(CIF(z))
8.5918243572165? - 5.4751982004351?*I
sage: L.elliptic_exponential(z*w2, to_curve=False)[0] * w2^2
8.59182435721650 - 5.47519820043503*I
```

**`wp_on_grid`**( $v, N, \text{half}=\text{False}$ )

Return an array of the values of  $\wp$  on an  $N \times N$  grid.

INPUT:

- $v$  (embedding) - an embedding of the number field.
- $N$  (int) - The number of terms to use in the  $q$ -expansion of  $\wp$ .
- `half` (boolean, default `False`) - if `True`, use an array of size  $N \times N/2$  instead of  $N \times N$ .

OUTPUT:

An array of size either  $N \times N/2$  or  $N \times N$  whose  $(i, j)$  entry is the value of the Weierstrass  $\wp$ -function at  $(i + .5)/N + (j + .5) * \tau/N$ , a grid of points in the fundamental region for the lattice  $[1, \tau]$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: H = E.height_function()
sage: v = QQ.places()[0]
```

The array of values on the grid shows symmetry, since  $\wp$  is even:

```
sage: H.wp_on_grid(v, 4)
array([[ 25.43920182,   5.28760943,   5.28760943,   25.43920182],
 [  6.05099485,   1.83757786,   1.83757786,   6.05099485],
 [  6.05099485,   1.83757786,   1.83757786,   6.05099485],
 [ 25.43920182,   5.28760943,   5.28760943,   25.43920182]])
```

The array of values on the half-grid:

```
sage: H.wp_on_grid(v, 4, True)
array([[ 25.43920182,   5.28760943],
 [  6.05099485,   1.83757786],
 [  6.05099485,   1.83757786],
 [ 25.43920182,   5.28760943]])
```

**class** `sage.schemes.elliptic_curves.height.UnionOfIntervals` (*endpoints*)

A class representing a finite union of closed intervals in  $\mathbb{R}$  which can be scaled, shifted, intersected, etc.

The intervals are represented as an ordered list of their endpoints, which may include  $-\infty$  and  $+\infty$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: R = UnionOfIntervals([1,2,3,infinity]); R
([1, 2] U [3, +Infinity])
sage: R + 5
([6, 7] U [8, +Infinity])
sage: ~R
([-Infinity, 1] U [2, 3])
sage: ~R | (10*R + 100)
([-Infinity, 1] U [2, 3] U [110, 120] U [130, +Infinity])
```

---

**Todo:** Unify `UnionOfIntervals` with the class `RealSet` introduced by [trac ticket #13125](#); see [trac ticket #16063](#).

---

**finite\_endpoints** ()

Returns the finite endpoints of this union of intervals.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: UnionOfIntervals([0,1]).finite_endpoints()
[0, 1]
sage: UnionOfIntervals([-infinity, 0, 1, infinity]).finite_endpoints()
[0, 1]
```

**classmethod** `intersection` (*L*)

Return the intersection of a list of `UnionOfIntervals`.

INPUT:

- *L* (list) – a list of `UnionOfIntervals` instances

OUTPUT:

A new `UnionOfIntervals` instance representing the intersection of the `UnionOfIntervals` in the list.

---

**Note:** This is a class method.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: A = UnionOfIntervals([1,3,5,7]); A
([1, 3] U [5, 7])
sage: B = A+1; B
([2, 4] U [6, 8])
sage: A.intersection([A,B])
([2, 3] U [6, 7])
```

**intervals** ()

Returns the intervals in self, as a list of 2-tuples.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: UnionOfIntervals(list(range(10))).intervals()
[(0, 1), (2, 3), (4, 5), (6, 7), (8, 9)]
sage: UnionOfIntervals([-infinity, pi, 17, infinity]).intervals()
[(-Infinity, pi), (17, +Infinity)]
```

**is\_empty()**

Returns whether self is empty.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: UnionOfIntervals([3,4]).is_empty()
False
sage: all = UnionOfIntervals([-infinity, infinity])
sage: all.is_empty()
False
sage: (~all).is_empty()
True
sage: A = UnionOfIntervals([0,1]) & UnionOfIntervals([2,3])
sage: A.is_empty()
True
```

**static join(*L*, *condition*)**

Utility function to form the union or intersection of a list of UnionOfIntervals.

INPUT:

- *L* (list) – a list of UnionOfIntervals instances
- *condition* (function) – either any or all, or some other boolean function of a list of boolean values.

OUTPUT:

A new UnionOfIntervals instance representing the subset of ‘RR’ equal to those reals in any/all/condition of the UnionOfIntervals in the list.

---

**Note:** This is a static method for the class.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: A = UnionOfIntervals([1,3,5,7]); A
([1, 3] U [5, 7])
sage: B = A+1; B
([2, 4] U [6, 8])
sage: A.join([A,B],any) # union
([1, 4] U [5, 8])
sage: A.join([A,B],all) # intersection
([2, 3] U [6, 7])
sage: A.join([A,B],sum) # symmetric difference
([1, 2] U [3, 4] U [5, 6] U [7, 8])
```

**classmethod union(*L*)**

Return the union of a list of UnionOfIntervals.

INPUT:

- `L` (list) – a list of `UnionOfIntervals` instances

OUTPUT:

A new `UnionOfIntervals` instance representing the union of the `UnionOfIntervals` in the list.

---

**Note:** This is a class method.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import UnionOfIntervals
sage: A = UnionOfIntervals([1, 3, 5, 7]); A
([1, 3] U [5, 7])
sage: B = A+1; B
([2, 4] U [6, 8])
sage: A.union([A, B])
([1, 4] U [5, 8])
```

`sage.schemes.elliptic_curves.height.eps` (*err*, *is\_real*)

Return a Real or Complex interval centered on 0 with radius *err*.

INPUT:

- *err* (real) – a positive real number, the radius of the interval
- *is\_real* (boolean) – if True, returns a real interval in RIF, else a complex interval in CIF

OUTPUT:

An element of RIF or CIF (as specified), centered on 0, with given radius.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import eps
sage: eps(0.01, True)
0.0?
sage: eps(0.01, False)
0.0? + 0.0?*I
```

`sage.schemes.elliptic_curves.height.inf_max_abs` (*f*, *g*, *D*)

Returns  $\inf_D(\max(|f|, |g|))$ .

INPUT:

- *f*, *g* (polynomials) – real univariate polynomials
- *D* (`UnionOfIntervals`) – a subset of  $\mathbf{R}$

OUTPUT:

A real number approximating the value of  $\inf_D(\max(|f|, |g|))$ .

ALGORITHM:

The extreme values must occur at an endpoint of a subinterval of *D* or at a point where one of *f*, *f'*, *g*, *g'*, *f* ± *g* is zero.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.height import inf_max_abs,
↪UnionOfIntervals
sage: x = polygen(RR)
sage: f = (x-10)^4+1
```



```

sage: g = 2*x^3+100
sage: inf_max_abs(f,g,UnionOfIntervals([1,2,3,4,5,6]))
425.638201706391
sage: r0 = (f-g).roots()[0][0]
sage: r0
5.46053402234697
sage: max(abs(f(r0)), abs(g(r0)))
425.638201706391

```

`sage.schemes.elliptic_curves.height.min_on_disk(f, tol, max_iter=10000)`

Returns the minimum of a real-valued complex function on a square.

INPUT:

- `f` – a function from CIF to RIF
- `tol` (real) – a positive real number
- `max_iter` (integer, default 10000) – a positive integer bounding the number of iterations to be used

OUTPUT:

A 2-tuple  $(s, t)$ , where  $t = f(s)$  and  $s$  is a CIF element contained in the disk  $|z| \leq 1$ , at which  $f$  takes its minimum value.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.height import min_on_disk
sage: f = lambda x: (x^2+100).abs()
sage: s, t = min_on_disk(f, 0.0001)
sage: s, f(s), t
(0.01? + 1.00?*I, 99.01?, 99.00000000000000)

```

`sage.schemes.elliptic_curves.height.nonneg_region(f)`

Returns the UnionOfIntervals representing the region where `f` is non-negative.

INPUT:

- `f` (polynomial) – a univariate polynomial over  $\mathbb{R}$ .

OUTPUT:

A UnionOfIntervals representing the set  $\{x \in \mathbb{R} \mid f(x) \geq 0\}$ .

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.height import nonneg_region
sage: x = polygen(RR)
sage: nonneg_region(x^2-1)
([-Infinity, -1.000000000000000] U [1.000000000000000, +Infinity])
sage: nonneg_region(1-x^2)
([-1.000000000000000, 1.000000000000000])
sage: nonneg_region(1-x^3)
([-Infinity, 1.000000000000000])
sage: nonneg_region(x^3-1)
([1.000000000000000, +Infinity])
sage: nonneg_region((x-1)*(x-2))
([-Infinity, 1.000000000000000] U [2.000000000000000, +Infinity])
sage: nonneg_region(-(x-1)*(x-2))
([1.000000000000000, 2.000000000000000])
sage: nonneg_region((x-1)*(x-2)*(x-3))
([1.000000000000000, 2.000000000000000] U [3.000000000000000, +Infinity])

```

```

sage: nonneg_region(-(x-1)*(x-2)*(x-3))
([-Infinity, 1.000000000000000] U [2.000000000000000, 3.000000000000000])
sage: nonneg_region(x^4+1)
([-Infinity, +Infinity])
sage: nonneg_region(-x^4-1)
()

```

`sage.schemes.elliptic_curves.height.rat_term_CIF(z, try_strict=True)`

Compute the value of  $u/(1-u)^2$  in CIF, where  $u = \exp(2\pi iz)$ .

INPUT:

- `z` (complex) – a CIF element
- `try_strict` (bool) – flag

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.height import rat_term_CIF
sage: z = CIF(0.5, 0.2)
sage: rat_term_CIF(z)
-0.172467461182437? + 0.?e-16*I
sage: rat_term_CIF(z, False)
-0.172467461182437? + 0.?e-16*I

```

### 15.11.5 Saturation of Mordell-Weil groups of elliptic curves over number fields

Points  $P_1, \dots, P_r$  in  $E(K)$ , where  $E$  is an elliptic curve over a number field  $K$ , are said to be  $p$ -saturated if no linear combination  $\sum n_i P_i$  is divisible by  $p$  in  $E(K)$  except trivially when all  $n_i$  are multiples of  $p$ . The points are said to be saturated if they are  $p$ -saturated at all primes; this is always true for all but finitely many primes since  $E(K)$  is a finitely-generated Abelian group.

The process of  $p$ -saturating a given set of points is implemented here. The naive algorithm simply checks all  $(p^r - 1)/(p - 1)$  projective combinations of the points, testing each to see if it can be divided by  $p$ . If this occurs then we replace one of the points and continue. The function `p_saturation()` does one step of this, while `full_p_saturation()` repeats until the points are  $p$ -saturated. A more sophisticated algorithm for  $p$ -saturation is implemented which is much more efficient for large  $p$  and  $r$ , and involves computing the reduction of the points modulo auxiliary primes to obtain linear conditions modulo  $p$  which must be satisfied by the coefficients  $a_i$  of any nontrivial relation. When the points are already  $p$ -saturated this sieving technique can prove their saturation quickly.

The method `saturation()` of the class `EllipticCurve_number_field` applies full  $p$ -saturation at any given set of primes, or can compute a bound on the primes  $p$  at which the given points may not be  $p$ -saturated. This involves computing a lower bound for the canonical height of points of infinite order, together with estimates from the geometry of numbers.

AUTHORS:

- Robert Bradshaw
- John Cremona

`sage.schemes.elliptic_curves.saturation.full_p_saturation(Plist, p, lin_combs={}, verbose=False)`

Full  $p$ -saturation of `Plist`.

INPUT:

- `Plist` (list) – a list of independent points on one elliptic curve.
- `p` (integer) – a prime number.

- `lin_combs` (dict, default null) - a dict, possibly empty, with keys coefficient tuples and values the corresponding linear combinations of the points in `Plist`.

OUTPUT:

(`newPlist`, `exponent`) where `newPlist` has the same length as `Plist` and spans the  $p$ -saturation of the span of `Plist`, which contains that span with index  $p \cdot \text{exponent}$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.saturation import full_p_saturation
sage: E = EllipticCurve('389a')
sage: K.<i> = QuadraticField(-1)
sage: EK = E.change_ring(K)
sage: P = EK(1+i, -1-2*i)
sage: full_p_saturation([8*P], 2, verbose=True)
--starting full 2-saturation
Points were not 2-saturated, exponent was 3
([(i + 1 : -2*i - 1 : 1)], 3)

sage: Q = EK(0, 0)
sage: R = EK(-1, 1)
sage: full_p_saturation([P, Q, R], 3)
([(i + 1 : -2*i - 1 : 1), (0 : 0 : 1), (-1 : 1 : 1)], 0)
```

An example where the points are not 7-saturated and we gain index exponent 1. Running this example with `verbose=True` shows that it uses the code for when the reduction has  $p$ -rank 2 (which occurs for the reduction modulo  $(16 - 5i)$ ), which uses the Weil pairing:

```
sage: full_p_saturation([P, Q+3*R, Q-4*R], 7)
([(i + 1 : -2*i - 1 : 1),
(2869/676 : 154413/17576 : 1),
(-7095/502681 : -366258864/356400829 : 1)],
1)
```

`sage.schemes.elliptic_curves.saturation.p_saturation(Plist, p, sieve=True, lin_combs={}, verbose=False)`

Checks whether the list of points is  $p$ -saturated.

INPUT:

- `Plist` (list) - a list of independent points on one elliptic curve.
- `p` (integer) - a prime number.
- `sieve` (boolean) - if `True`, use a sieve (when there are at least 2 points); otherwise test all combinations.
- `lin_combs` (dict) - a dict, possibly empty, with keys coefficient tuples and values the corresponding linear combinations of the points in `Plist`.

**Note:** The sieve is much more efficient when the points are saturated and the number of points or the prime are large.

OUTPUT:

Either (`True`, `lin_combs`) if the points are  $p$ -saturated, or (`False`, `i`, `newP`) if they are not  $p$ -saturated, in which case after replacing the  $i$ 'th point with `newP`, the subgroup generated contains that generated by `Plist` with index  $p$ . Note that while proving the points  $p$ -saturated, the `lin_combs` dict may have been enlarged, so is returned.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.saturation import p_saturation
sage: E = EllipticCurve('389a')
sage: K.<i> = QuadraticField(-1)
sage: EK = E.change_ring(K)
sage: P = EK(1+i, -1-2*i)
sage: p_saturation([P], 2)
(True, {})
sage: p_saturation([2*P], 2)
(False, 0, (i + 1 : -2*i - 1 : 1))

sage: Q = EK(0, 0)
sage: R = EK(-1, 1)
sage: p_saturation([P, Q, R], 3)
(True, {})
```

Here we see an example where 19-saturation is proved, with the verbose flag set to True so that we can see what is going on:

```
sage: p_saturation([P, Q, R], 19, verbose=True)
Using sieve method to saturate...
There is 19-torsion modulo Fractional ideal (i + 14), projecting points
--> [(184 : 27 : 1), (0 : 0 : 1), (196 : 1 : 1)]
--rank is now 1
There is 19-torsion modulo Fractional ideal (i - 14), projecting points
--> [(15 : 168 : 1), (0 : 0 : 1), (196 : 1 : 1)]
--rank is now 2
There is 19-torsion modulo Fractional ideal (-2*i + 17), projecting points
--> [(156 : 275 : 1), (0 : 0 : 1), (292 : 1 : 1)]
--rank is now 3
Reached full rank: points were 19-saturated
(True, {})
```

An example where the points are not 11-saturated:

```
sage: res = p_saturation([P+5*Q, P-6*Q, R], 11); res
(False,
0,
(-5783311/14600041*i + 1396143/14600041 : 37679338314/55786756661*i + 3813624227/
↪55786756661 : 1))
```

That means that the 0'th point may be replaced by the displayed point to achieve an index gain of 11:

```
sage: p_saturation([res[2], P-6*Q, R], 11)
(True, {})
```

### 15.11.6 Torsion subgroups of elliptic curves over number fields (including $\mathbb{Q}$ )

AUTHORS:

- Nick Alexander: original implementation over  $\mathbb{Q}$
- Chris Wuthrich: original implementation over number fields
- **John Cremona**: rewrote p-primary part to use division polynomials, added some features, unified Number Field and  $\mathbb{Q}$  code.

**class** sage.schemes.elliptic\_curves.ell\_torsion.**EllipticCurveTorsionSubgroup**(*E*, *algorithm=None*)

Bases: sage.groups.additive\_abelian.additive\_abelian\_wrapper.  
AdditiveAbelianGroupWrapper

The torsion subgroup of an elliptic curve over a number field.

EXAMPLES:

Examples over  $\mathbb{Q}$ :

```
sage: E = EllipticCurve([-4, 0]); E
Elliptic Curve defined by  $y^2 = x^3 - 4x$  over Rational Field
sage: G = E.torsion_subgroup(); G
Torsion Subgroup isomorphic to  $\mathbb{Z}/2 + \mathbb{Z}/2$  associated to the Elliptic Curve
defined by  $y^2 = x^3 - 4x$  over Rational Field
sage: G.order()
4
sage: G.gen(0)
(-2 : 0 : 1)
sage: G.gen(1)
(0 : 0 : 1)
sage: G.ngens()
2
```

```
sage: E = EllipticCurve([17, -120, -60, 0, 0]); E
Elliptic Curve defined by  $y^2 + 17xy - 60y = x^3 - 120x^2$  over Rational Field
sage: G = E.torsion_subgroup(); G
Torsion Subgroup isomorphic to Trivial group associated to the Elliptic Curve
defined by  $y^2 + 17xy - 60y = x^3 - 120x^2$  over Rational Field
sage: G.ngens()
()
sage: e = EllipticCurve([0, 33076156654533652066609946884, 0, \
347897536144342179642120321790729023127716119338758604800, \
1141128154369274295519023032806804247788154621049857648870032370285851781352816640000])
sage: e.torsion_order()
16
```

Constructing points from the torsion subgroup:

```
sage: E = EllipticCurve('14a1')
sage: T = E.torsion_subgroup()
sage: [E(t) for t in T]
[(0 : 1 : 0),
(9 : 23 : 1),
(2 : 2 : 1),
(1 : -1 : 1),
(2 : -5 : 1),
(9 : -33 : 1)]
```

An example where the torsion subgroup is not cyclic:

```
sage: E = EllipticCurve([0, 0, 0, -49, 0])
sage: T = E.torsion_subgroup()
sage: [E(t) for t in T]
[(0 : 1 : 0), (-7 : 0 : 1), (0 : 0 : 1), (7 : 0 : 1)]
```

An example where the torsion subgroup is trivial:

```
sage: E = EllipticCurve('37a1')
sage: T = E.torsion_subgroup()
sage: T
Torsion Subgroup isomorphic to Trivial group associated to the Elliptic Curve
↳ defined by  $y^2 + y = x^3 - x$  over Rational Field
sage: [E(t) for t in T]
[(0 : 1 : 0)]
```

Examples over other Number Fields:

```
sage: E=EllipticCurve('11a1')
sage: K.<i>=NumberField(x^2+1)
sage: EK=E.change_ring(K)
sage: from sage.schemes.elliptic_curves.ell_torsion import EllipticCurveTorsionSubgroup
sage: T=EllipticCurveTorsionSubgroup(EK)
Torsion Subgroup isomorphic to Z/5 associated to the Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x^2 + (-10)x + (-20)$  over Number Field in i with defining polynomial  $x^2 + 1$ 

sage: E=EllipticCurve('11a1')
sage: K.<i>=NumberField(x^2+1)
sage: EK=E.change_ring(K)
sage: T = EK.torsion_subgroup()
sage: T.ngens()
1
sage: T.gen(0)
(5 : -6 : 1)
```

Note: this class is normally constructed indirectly as follows:

```
sage: T = EK.torsion_subgroup(); T
Torsion Subgroup isomorphic to Z/5 associated to the Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x^2 + (-10)x + (-20)$  over Number Field in i with defining polynomial  $x^2 + 1$ 
sage: type(T)
<class 'sage.schemes.elliptic_curves.ell_torsion.EllipticCurveTorsionSubgroup_
↳ with_category'>
```

AUTHORS:

- Nick Alexander - initial implementation over  $\mathbb{Q}$ .
- Chris Wuthrich - initial implementation over number fields.
- John Cremona - additional features and unification.

**curve()**

Return the curve of this torsion subgroup.

EXAMPLES:

```
sage: E=EllipticCurve('11a1')
sage: K.<i>=NumberField(x^2+1)
sage: EK=E.change_ring(K)
sage: T = EK.torsion_subgroup()
sage: T.curve() is EK
True
```

**points()**

Return a list of all the points in this torsion subgroup. The list is cached.

EXAMPLES:

```
sage: K.<i>=NumberField(x^2 + 1)
sage: E = EllipticCurve(K, [0,0,0,1,0])
sage: tor = E.torsion_subgroup()
sage: tor.points()
[(0 : 1 : 0), (-i : 0 : 1), (0 : 0 : 1), (i : 0 : 1)]
```

### 15.11.7 Galois representations attached to elliptic curves

Given an elliptic curve  $E$  over  $\mathbf{Q}$  and a rational prime number  $p$ , the  $p^n$ -torsion  $E[p^n]$  points of  $E$  is a representation of the absolute Galois group  $G_{\mathbf{Q}}$  of  $\mathbf{Q}$ . As  $n$  varies we obtain the Tate module  $T_p E$  which is a representation of  $G_{\mathbf{Q}}$  on a free  $\mathbf{Z}_p$ -module of rank 2. As  $p$  varies the representations are compatible.

Currently sage can decide whether the Galois module  $E[p]$  is reducible, i.e., if  $E$  admits an isogeny of degree  $p$ , and whether the image of the representation on  $E[p]$  is surjective onto  $\text{Aut}(E[p]) = GL_2(\mathbb{F}_p)$ .

The following are the most useful functions for the class `GaloisRepresentation`.

For the reducibility:

- `is_reducible(p)`
- `is_irreducible(p)`
- `reducible_primes()`

For the image:

- `is_surjective(p)`
- `non_surjective()`
- `image_type(p)`

For the classification of the representation

- `is_semistable(p)`
- `is_unramified(p, ell)`
- `is_crystalline(p)`

EXAMPLES:

```
sage: E = EllipticCurve('196a1')
sage: rho = E.galois_representation()
sage: rho.is_irreducible(7)
True
sage: rho.is_reducible(3)
True
sage: rho.is_irreducible(2)
True
sage: rho.is_surjective(2)
False
sage: rho.is_surjective(3)
False
sage: rho.is_surjective(5)
True
```

```

sage: rho.reducible_primes()
[3]
sage: rho.non_surjective()
[2, 3]
sage: rho.image_type(2)
'The image is cyclic of order 3.'
sage: rho.image_type(3)
'The image is contained in a Borel subgroup as there is a 3-isogeny.'
sage: rho.image_type(5)
'The image is all of GL_2(F_5).'
```

For semi-stable curve it is known that the representation is surjective if and only if it is irreducible:

```

sage: E = EllipticCurve('11a1')
sage: rho = E.galois_representation()
sage: rho.non_surjective()
[5]
sage: rho.reducible_primes()
[5]
```

For cm curves it is not true that there are only finitely many primes for which the Galois representation mod  $p$  is surjective onto  $GL_2(\mathbb{F}_p)$ :

```

sage: E = EllipticCurve('27a1')
sage: rho = E.galois_representation()
sage: rho.non_surjective()
[0]
sage: rho.reducible_primes()
[3]
sage: E.has_cm()
True
sage: rho.image_type(11)
'The image is contained in the normalizer of a non-split Cartan group. (cm)'
```

#### REFERENCES:

#### AUTHORS:

- chris wuthrich (02/10) - moved from ell\_rational\_field.py.

**class** sage.schemes.elliptic\_curves.gal\_reps.**GaloisRepresentation**( $E$ )

Bases: sage.structure.sage\_object.SageObject

The compatible family of Galois representation attached to an elliptic curve over the rational numbers.

Given an elliptic curve  $E$  over  $\mathbb{Q}$  and a rational prime number  $p$ , the  $p^n$ -torsion  $E[p^n]$  points of  $E$  is a representation of the absolute Galois group. As  $n$  varies we obtain the Tate module  $T_p E$  which is a representation of the absolute Galois group on a free  $\mathbb{Z}_p$ -module of rank 2. As  $p$  varies the representations are compatible.

#### EXAMPLES:

```

sage: rho = EllipticCurve('11a1').galois_representation()
sage: rho
Compatible family of Galois representations associated to the Elliptic Curve_
↪ defined by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
```

**elliptic\_curve**()

The elliptic curve associated to this representation.

#### EXAMPLES:



```

sage: E = EllipticCurve('11a1')
sage: rho = E.galois_representation()
sage: rho.elliptic_curve() == E
True

```

**image\_classes** ( $p$ ,  $bound=10000$ )

This function returns, given the representation  $\rho$  a list of  $p$  values that add up to 1, representing the frequency of the conjugacy classes of the projective image of  $\rho$  in  $PGL_2(\mathbb{F}_p)$ .

Let  $M$  be a matrix in  $GL_2(\mathbb{F}_p)$ , then define  $u(M) = \text{tr}(M)^2 / \det(M)$ , which only depends on the conjugacy class of  $M$  in  $PGL_2(\mathbb{F}_p)$ . Hence this defines a map  $u : PGL_2(\mathbb{F}_p) \rightarrow \mathbb{F}_p$ , which is almost a bijection between conjugacy classes of the source and  $\mathbb{F}_p$  (the elements of order  $p$  and the identity map to 4 and both classes of elements of order 2 map to 0).

This function returns the frequency with which the values of  $u$  appeared among the images of the Frobenius elements  $a_\ell$  at  $\ell$  for good primes  $\ell \neq p$  below a given bound.

INPUT:

- a prime  $p$
- a natural number bound (optional, default=10000)

OUTPUT:

- a list of  $p$  real numbers in the interval  $[0, 1]$  adding up to 1

EXAMPLES:

```

sage: E = EllipticCurve('14a1')
sage: rho = E.galois_representation()
sage: rho.image_classes(5)
[0.2095, 0.1516, 0.2445, 0.1728, 0.2217]

```

```

sage: E = EllipticCurve('11a1')
sage: rho = E.galois_representation()
sage: rho.image_classes(5)
[0.2467, 0.0000, 0.5049, 0.0000, 0.2484]

```

```

sage: EllipticCurve('27a1').galois_representation().image_classes(5)
[0.5839, 0.1645, 0.0000, 0.1702, 0.08143]
sage: EllipticCurve('30a1').galois_representation().image_classes(5)
[0.1956, 0.1801, 0.2543, 0.1728, 0.1972]
sage: EllipticCurve('32a1').galois_representation().image_classes(5)
[0.6319, 0.0000, 0.2492, 0.0000, 0.1189]
sage: EllipticCurve('900a1').galois_representation().image_classes(5)
[0.5852, 0.1679, 0.0000, 0.1687, 0.07824]
sage: EllipticCurve('441a1').galois_representation().image_classes(5)
[0.5860, 0.1646, 0.0000, 0.1679, 0.08150]
sage: EllipticCurve('648a1').galois_representation().image_classes(5)
[0.3945, 0.3293, 0.2388, 0.0000, 0.03749]

```

```

sage: EllipticCurve('784h1').galois_representation().image_classes(7)
[0.5049, 0.0000, 0.0000, 0.0000, 0.4951, 0.0000, 0.0000]
sage: EllipticCurve('49a1').galois_representation().image_classes(7)
[0.5045, 0.0000, 0.0000, 0.0000, 0.4955, 0.0000, 0.0000]

sage: EllipticCurve('121c1').galois_representation().image_classes(11)
[0.1001, 0.0000, 0.0000, 0.0000, 0.1017, 0.1953, 0.1993, 0.0000, 0.0000, 0.
↪ 2010, 0.2026]

```

```

sage: EllipticCurve('121d1').galois_representation().image_classes(11)
[0.08869, 0.07974, 0.08706, 0.08137, 0.1001, 0.09439, 0.09764, 0.08218, 0.
↪08625, 0.1017, 0.1009]

sage: EllipticCurve('441f1').galois_representation().image_classes(13)
[0.08232, 0.1663, 0.1663, 0.1663, 0.08232, 0.0000, 0.1549, 0.0000, 0.0000, 0.
↪0000, 0.0000, 0.1817, 0.0000]

```

**REMARKS:**

Conjugacy classes of subgroups of  $PGL_2(\mathbb{F}_5)$

For the case  $p = 5$ , the order of an element determines almost the value of  $u$ :

$u$	0	1	2	3	4
orders	2	3	4	6	1 or 5

Here we give here the full table of all conjugacy classes of subgroups with the values that `image_classes` should give (as bound tends to  $\infty$ ). Comparing with the output of the above examples, it is now easy to guess what the image is.

subgroup	order	frequencies of values of $u$
trivial	1	[0.0000, 0.0000, 0.0000, 0.0000, 1.000]
cyclic	2	[0.5000, 0.0000, 0.0000, 0.0000, 0.5000]
cyclic	2	[0.5000, 0.0000, 0.0000, 0.0000, 0.5000]
cyclic	3	[0.0000, 0.6667, 0.0000, 0.0000, 0.3333]
Klein	4	[0.7500, 0.0000, 0.0000, 0.0000, 0.2500]
cyclic	4	[0.2500, 0.0000, 0.5000, 0.0000, 0.2500]
Klein	4	[0.7500, 0.0000, 0.0000, 0.0000, 0.2500]
cyclic	5	[0.0000, 0.0000, 0.0000, 0.0000, 1.000]
cyclic	6	[0.1667, 0.3333, 0.0000, 0.3333, 0.1667]
$S_3$	6	[0.5000, 0.3333, 0.0000, 0.0000, 0.1667]
$S_3$	6	[0.5000, 0.3333, 0.0000, 0.0000, 0.1667]
$D_4$	8	[0.6250, 0.0000, 0.2500, 0.0000, 0.1250]
$D_5$	10	[0.5000, 0.0000, 0.0000, 0.0000, 0.5000]
$A_4$	12	[0.2500, 0.6667, 0.0000, 0.0000, 0.08333]
$D_6$	12	[0.5833, 0.1667, 0.0000, 0.1667, 0.08333]
Borel	20	[0.2500, 0.0000, 0.5000, 0.0000, 0.2500]
$S_4$	24	[0.3750, 0.3333, 0.2500, 0.0000, 0.04167]
$PSL_2$	60	[0.2500, 0.3333, 0.0000, 0.0000, 0.4167]
$PGL_2$	120	[0.2083, 0.1667, 0.2500, 0.1667, 0.2083]

**image\_type( $p$ )**

Returns a string describing the image of the mod- $p$  representation. The result is provably correct, but only indicates what sort of an image we have. If one wishes to determine the exact group one needs to work a bit harder. The probabilistic method of `image_classes` or Sutherland's `galrep` package can give a very good guess what the image should be.

INPUT:

- $p$  a prime number

OUTPUT:

- a string.

## EXAMPLES

```

sage: E = EllipticCurve('14a1')
sage: rho = E.galois_representation()
sage: rho.image_type(5)
'The image is all of GL_2(F_5).'
```

```

sage: E = EllipticCurve('11a1')
sage: rho = E.galois_representation()
sage: rho.image_type(5)
'The image is meta-cyclic inside a Borel subgroup as there is a 5-torsion_
↪point on the curve.'
```

```

sage: EllipticCurve('27a1').galois_representation().image_type(5)
'The image is contained in the normalizer of a non-split Cartan group. (cm) '
sage: EllipticCurve('30a1').galois_representation().image_type(5)
'The image is all of GL_2(F_5).'
```

```

sage: EllipticCurve("324b1").galois_representation().image_type(5)
'The image in PGL_2(F_5) is the exceptional group S_4.'
```

```

sage: E = EllipticCurve([0,0,0,-56,4848])
sage: rho = E.galois_representation()

sage: rho.image_type(5)
'The image is contained in the normalizer of a split Cartan group.'
```

```

sage: EllipticCurve('49a1').galois_representation().image_type(7)
'The image is contained in a Borel subgroup as there is a 7-isogeny.'
```

```

sage: EllipticCurve('121c1').galois_representation().image_type(11)
'The image is contained in a Borel subgroup as there is a 11-isogeny.'
```

```

sage: EllipticCurve('121d1').galois_representation().image_type(11)
'The image is all of GL_2(F_11).'
```

```

sage: EllipticCurve('441f1').galois_representation().image_type(13)
'The image is contained in a Borel subgroup as there is a 13-isogeny.'
```

```

sage: EllipticCurve([1,-1,1,-5,2]).galois_representation().image_type(5)
'The image is contained in the normalizer of a non-split Cartan group.'
```

```

sage: EllipticCurve([0,0,1,-25650,1570826]).galois_representation().image_
↪type(5)
'The image is contained in the normalizer of a split Cartan group.'
```

```

sage: EllipticCurve([1,-1,1,-2680,-50053]).galois_representation().image_
↪type(7)      # the dots (...) in the output fix #11937 (installed 'Kash' may_
↪give additional output); long time (2s on sage.math, 2014)
'The image is a... group of order 18.'
```

```

sage: EllipticCurve([1,-1,0,-107,-379]).galois_representation().image_type(7)_
↪      # the dots (...) in the output fix #11937 (installed 'Kash' may give_
↪additional output); long time (1s on sage.math, 2014)
'The image is a... group of order 36.'
```

```

sage: EllipticCurve([0,0,1,2580,549326]).galois_representation().image_type(7)
'The image is contained in the normalizer of a split Cartan group.'
```

Test trac ticket #14577:

```

sage: EllipticCurve([0, 1, 0, -4788, 109188]).galois_representation().image_
↪type(13)
'The image in PGL_2(F_13) is the exceptional group S_4.'
```

Test trac ticket #14752:

```
sage: EllipticCurve([0, 0, 0, -1129345880, -86028258620304]).galois_
↪representation().image_type(11)
'The image is contained in the normalizer of a non-split Cartan group.'
```

For  $p = 2$ :

```
sage: E = EllipticCurve('11a1')
sage: rho = E.galois_representation()
sage: rho.image_type(2)
'The image is all of GL_2(F_2), i.e. a symmetric group of order 6.'

sage: rho = EllipticCurve('14a1').galois_representation()
sage: rho.image_type(2)
'The image is cyclic of order 2 as there is exactly one rational 2-torsion_
↪point.'

sage: rho = EllipticCurve('15a1').galois_representation()
sage: rho.image_type(2)
'The image is trivial as all 2-torsion points are rational.'

sage: rho = EllipticCurve('196a1').galois_representation()
sage: rho.image_type(2)
'The image is cyclic of order 3.'
```

$p = 3$ :

```
sage: rho = EllipticCurve('33a1').galois_representation()
sage: rho.image_type(3)
'The image is all of GL_2(F_3).'
```

```
sage: rho = EllipticCurve('30a1').galois_representation()
sage: rho.image_type(3)
'The image is meta-cyclic inside a Borel subgroup as there is a 3-torsion_
↪point on the curve.'
```

```
sage: rho = EllipticCurve('50b1').galois_representation()
sage: rho.image_type(3)
'The image is contained in a Borel subgroup as there is a 3-isogeny.'
```

```
sage: rho = EllipticCurve('3840h1').galois_representation()
sage: rho.image_type(3)
'The image is contained in a dihedral group of order 8.'
```

```
sage: rho = EllipticCurve('32a1').galois_representation()
sage: rho.image_type(3)
'The image is a semi-dihedral group of order 16, gap.SmallGroup([16,8]).'
```

ALGORITHM: Mainly based on Serre's paper.

**is\_crystalline**( $p$ )

Returns true if the  $p$ -adic Galois representation to  $GL_2(\mathbb{Z}_p)$  is crystalline.

For an elliptic curve  $E$ , this is to ask whether  $E$  has good reduction at  $p$ .

INPUT:

- $p$  a prime

OUTPUT:

- a Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('64a1').galois_representation()
sage: rho.is_crystalline(5)
True
sage: rho.is_crystalline(2)
False
```

**is\_irreducible**( $p$ )

Return True if the mod  $p$  representation is irreducible.

INPUT:

- $p$  - a prime number

OUTPUT:

- a boolean

EXAMPLES:

```
sage: rho = EllipticCurve('37b').galois_representation()
sage: rho.is_irreducible(2)
True
sage: rho.is_irreducible(3)
False
sage: rho.is_reducible(2)
False
sage: rho.is_reducible(3)
True
```

**is\_ordinary**( $p$ )

Returns true if the  $p$ -adic Galois representation to  $GL_2(\mathbf{Z}_p)$  is ordinary, i.e. if the image of the decomposition group in  $\text{Gal}(\mathbf{Q}/\mathbf{Q})$  above the prime  $p$  maps into a Borel subgroup.

For an elliptic curve  $E$ , this is to ask whether  $E$  is ordinary at  $p$ , i.e. good ordinary or multiplicative.

INPUT:

- $p$  a prime

OUTPUT:

- a Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('11a3').galois_representation()
sage: rho.is_ordinary(11)
True
sage: rho.is_ordinary(5)
True
sage: rho.is_ordinary(19)
False
```

**is\_potentially\_crystalline**( $p$ )

Returns true if the  $p$ -adic Galois representation to  $GL_2(\mathbf{Z}_p)$  is potentially crystalline, i.e. if there is a finite extension  $K/\mathbf{Q}_p$  such that the  $p$ -adic representation becomes crystalline.

For an elliptic curve  $E$ , this is to ask whether  $E$  has potentially good reduction at  $p$ .

INPUT:

- $p$  a prime

OUTPUT:

- a Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('37b1').galois_representation()
sage: rho.is_potentially_crystalline(37)
False
sage: rho.is_potentially_crystalline(7)
True
```

**is\_potentially\_semistable** ( $p$ )

Returns true if the  $p$ -adic Galois representation to  $GL_2(\mathbf{Z}_p)$  is potentially semistable.

For an elliptic curve  $E$ , this returns True always

INPUT:

- $p$  a prime

OUTPUT:

- a Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('27a2').galois_representation()
sage: rho.is_potentially_semistable(3)
True
```

**is\_quasi\_unipotent** ( $p, \ell$ )

Returns true if the Galois representation to  $GL_2(\mathbf{Z}_p)$  is quasi-unipotent at  $\ell \neq p$ , i.e. if there is a finite extension  $K/\mathbf{Q}$  such that the inertia group at a place above  $\ell$  in  $\text{Gal}(\overline{\mathbf{Q}}/K)$  maps into a Borel subgroup.

For a Galois representation attached to an elliptic curve  $E$ , this returns always True.

INPUT:

- $p$  a prime
- $\ell$  a different prime

OUTPUT:

- Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('11a3').galois_representation()
sage: rho.is_quasi_unipotent(11,13)
True
```

**is\_reducible** ( $p$ )

Return True if the mod- $p$  representation is reducible. This is equivalent to the existence of an isogeny defined over  $\mathbf{Q}$  of degree  $p$  from the elliptic curve.

INPUT:

- $p$  - a prime number

OUTPUT:

- a boolean

The answer is cached.

EXAMPLES:

```
sage: rho = EllipticCurve('121a').galois_representation()
sage: rho.is_reducible(7)
False
sage: rho.is_reducible(11)
True
sage: EllipticCurve('11a').galois_representation().is_reducible(5)
True
sage: rho = EllipticCurve('11a2').galois_representation()
sage: rho.is_reducible(5)
True
sage: EllipticCurve('11a2').torsion_order()
1
```

**is\_semistable**( $p$ )

Returns true if the  $p$ -adic Galois representation to  $GL_2(\mathbb{Z}_p)$  is semistable.

For an elliptic curve  $E$ , this is to ask whether  $E$  has semistable reduction at  $p$ .

INPUT:

- $p$  a prime

OUTPUT:

- a Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('20a3').galois_representation()
sage: rho.is_semistable(2)
False
sage: rho.is_semistable(3)
True
sage: rho.is_semistable(5)
True
```

**is\_surjective**( $p, A=1000$ )

Return True if the mod- $p$  representation is surjective onto  $\text{Aut}(E[p]) = GL_2(\mathbb{F}_p)$ .

False if it is not, or None if we were unable to determine whether it is or not.

INPUT:

- $p$  - int (a prime number)
- $A$  - int (a bound on the number of  $a_p$  to use)

OUTPUT:

- boolean. True if the mod- $p$  representation is surjective and False if not.

The answer is cached.

EXAMPLES:

```

sage: rho = EllipticCurve('37b').galois_representation()
sage: rho.is_surjective(2)
True
sage: rho.is_surjective(3)
False

```

```

sage: rho = EllipticCurve('121a1').galois_representation()
sage: rho.non_surjective()
[11]
sage: rho.is_surjective(5)
True
sage: rho.is_surjective(11)
False

sage: rho = EllipticCurve('121d1').galois_representation()
sage: rho.is_surjective(5)
False
sage: rho.is_surjective(11)
True

```

Here is a case, in which the algorithm does not return an answer:

```

sage: rho = EllipticCurve([0, 0, 1, 2580, 549326]).galois_representation()
sage: rho.is_surjective(7)

```

In these cases, one can use `image_type` to get more information about the image:

```

sage: rho.image_type(7)
'The image is contained in the normalizer of a split Cartan group.'

```

#### REMARKS:

1. If  $p \geq 5$  then the mod- $p$  representation is surjective if and only if the  $p$ -adic representation is surjective. When  $p = 2, 3$  there are counterexamples. See papers of Dokchitsers and Elkies for more details.
2. For the primes  $p = 2$  and  $3$ , this will always answer either True or False. For larger primes it might give None.

#### **is\_unipotent** ( $p, \ell$ )

Returns true if the Galois representation to  $GL_2(\mathbb{Z}_p)$  is unipotent at  $\ell \neq p$ , i.e. if the inertia group at a place above  $\ell$  in  $\text{Gal}(\bar{\mathbb{Q}}/\mathbb{Q})$  maps into a Borel subgroup.

For a Galois representation attached to an elliptic curve  $E$ , this returns True if  $E$  has semi-stable reduction at  $\ell$ .

INPUT:

- $p$  a prime
- $\ell$  a different prime

OUTPUT:

- Boolean

EXAMPLES:

```

sage: rho = EllipticCurve('120a1').galois_representation()
sage: rho.is_unipotent(2, 5)
True
sage: rho.is_unipotent(5, 2)

```



```
False
sage: rho.is_unipotent(5,7)
True
sage: rho.is_unipotent(5,3)
True
sage: rho.is_unipotent(5,5)
Traceback (most recent call last):
...
ValueError: unipotent is not defined for l = p, use semistable instead.
```

**is\_unramified**( $p, \ell$ )

Returns true if the Galois representation to  $GL_2(\mathbf{Z}_p)$  is unramified at  $\ell$ , i.e. if the inertia group at a place above  $\ell$  in  $\text{Gal}(\bar{\mathbf{Q}}/\mathbf{Q})$  has trivial image in  $GL_2(\mathbf{Z}_p)$ .

For a Galois representation attached to an elliptic curve  $E$ , this returns True if  $\ell \neq p$  and  $E$  has good reduction at  $\ell$ .

INPUT:

- $p$  a prime
- $\ell$  another prime

OUTPUT:

- Boolean

EXAMPLES:

```
sage: rho = EllipticCurve('20a3').galois_representation()
sage: rho.is_unramified(5,7)
True
sage: rho.is_unramified(5,5)
False
sage: rho.is_unramified(7,5)
False
```

This says that the 5-adic representation is unramified at 7, but the 7-adic representation is ramified at 5.

**non\_surjective**( $A=1000$ )

Returns a list of primes  $p$  such that the mod- $p$  representation *might* not be surjective. If  $p$  is not in the returned list, then the mod- $p$  representation is provably surjective.

By a theorem of Serre, there are only finitely many primes in this list, except when the curve has complex multiplication.

If the curve has CM, we simply return the sequence [0] and do no further computation.

INPUT:

- $A$  - an integer (default 1000). By increasing this parameter the resulting set might get smaller.

OUTPUT:

- list - if the curve has CM, returns [0]. Otherwise, returns a list of primes where mod- $p$  representation is very likely not surjective. At any prime not in this list, the representation is definitely surjective.

EXAMPLES:

```
sage: E = EllipticCurve([0, 0, 1, -38, 90]) # 361A
sage: E.galois_representation().non_surjective() # CM curve
[0]
```

```

sage: E = EllipticCurve([0, -1, 1, 0, 0]) # X_1(11)
sage: E.galois_representation().non_surjective()
[5]

sage: E = EllipticCurve([0, 0, 1, -1, 0]) # 37A
sage: E.galois_representation().non_surjective()
[]

sage: E = EllipticCurve([0, -1, 1, -2, -1]) # 141C
sage: E.galois_representation().non_surjective()
[13]

```

```

sage: E = EllipticCurve([1, -1, 1, -9965, 385220]) # 9999a1
sage: rho = E.galois_representation()
sage: rho.non_surjective()
[2]

sage: E = EllipticCurve('324b1')
sage: rho = E.galois_representation()
sage: rho.non_surjective()
[3, 5]

```

ALGORITHM: We first find an upper bound  $B$  on the possible primes. If  $E$  is semi-stable, we can take  $B = 11$  by a result of Mazur. There is a bound by Serre in the case that the  $j$ -invariant is not integral in terms of the smallest prime of good reduction. Finally there is an unconditional bound by Cojocaru, but which depends on the conductor of  $E$ . For the prime below that bound we call `is_surjective`.

#### **`reducible_primes()`**

Returns a list of the primes  $p$  such that the mod- $p$  representation is reducible. For all other primes the representation is irreducible.

EXAMPLES:

```

sage: rho = EllipticCurve('225a').galois_representation()
sage: rho.reducible_primes()
[3]

```

## 15.11.8 Galois representations for elliptic curves over number fields.

This file contains the code to compute for which primes the Galois representation attached to an elliptic curve (over an arbitrary number field) is surjective. The functions in this file are called by the `is_surjective` and `non_surjective` methods of an elliptic curve over a number field.

EXAMPLES:

```

sage: K = NumberField(x**2 - 29, 'a'); a = K.gen()
sage: E = EllipticCurve([1, 0, ((5 + a)/2)**2, 0, 0])
sage: rho = E.galois_representation()
sage: rho.is_surjective(29) # Cyclotomic character not surjective.
False
sage: rho.is_surjective(31) # See Section 5.10 of [Serre72].
True
sage: rho.non_surjective() # long time (4s on sage.math, 2014)
[3, 5, 29]

```

```
sage: E = EllipticCurve_from_j(1728).change_ring(K) # CM
sage: E.galois_representation().non_surjective() # long time (2s on sage.math, 2014)
[0]
```

## AUTHORS:

- Eric Larson (2012-05-28): initial version.
- Eric Larson (2014-08-13): added isogeny\_bound function.
- John Cremona (2016, 2017): various efficiency improvements to \_semistable\_reducible\_primes

## REFERENCES:

**class** sage.schemes.elliptic\_curves.gal\_reps\_number\_field.**GaloisRepresentation**(*E*)  
 Bases: sage.structure.sage\_object.SageObject

The compatible family of Galois representation attached to an elliptic curve over a number field.

Given an elliptic curve  $E$  over a number field  $K$  and a rational prime number  $p$ , the  $p^n$ -torsion  $E[p^n]$  points of  $E$  is a representation of the absolute Galois group  $G_K$  of  $K$ . As  $n$  varies we obtain the Tate module  $T_p E$  which is a representation of  $G_K$  on a free  $\mathbf{Z}_p$ -module of rank 2. As  $p$  varies the representations are compatible.

## EXAMPLES:

```
sage: K = NumberField(x**2 + 1, 'a')
sage: E = EllipticCurve('11a1').change_ring(K)
sage: rho = E.galois_representation()
sage: rho
Compatible family of Galois representations associated to the Elliptic Curve
↳ defined by  $y^2 + y = x^3 + (-1)x^2 + (-10)x + (-20)$  over Number Field in  $a$ 
↳ with defining polynomial  $x^2 + 1$ 
```

**elliptic\_curve()**

Return the elliptic curve associated to this representation.

## EXAMPLES:

```
sage: K = NumberField(x**2 + 1, 'a'); a = K.gen()
sage: E = EllipticCurve_from_j(a)
sage: rho = E.galois_representation()
sage: rho.elliptic_curve() == E
True
```

**is\_surjective**(*p*, *A=100*)

Return True if the mod- $p$  representation is (provably) surjective onto  $\text{Aut}(E[p]) = GL_2(\mathbb{F}_p)$ . Return False if it is (probably) not.

## INPUT:

- *p* - int - a prime number.
- **A** - int - a bound on the number of traces of Frobenius to use while trying to prove surjectivity.

## EXAMPLES:

```
sage: K = NumberField(x**2 - 29, 'a'); a = K.gen()
sage: E = EllipticCurve([1, 0, ((5 + a)/2)**2, 0, 0])
sage: rho = E.galois_representation()
sage: rho.is_surjective(29) # Cyclotomic character not surjective.
False
```

```
sage: rho.is_surjective(7) # See Section 5.10 of [Serre72].
True
```

If  $E$  is defined over  $\mathbf{Q}$ , then the exceptional primes for  $E/K$  are the same as the exceptional primes for  $E$ , except for those primes that are ramified in  $K/\mathbf{Q}$  or are less than  $[K : \mathbf{Q}]$ :

```
sage: K = NumberField(x**2 + 11, 'a')
sage: E = EllipticCurve([2, 14])
sage: rhoQQ = E.galois_representation()
sage: rhoK = E.change_ring(K).galois_representation()
sage: rhoQQ.is_surjective(2) == rhoK.is_surjective(2)
False
sage: rhoQQ.is_surjective(3) == rhoK.is_surjective(3)
True
sage: rhoQQ.is_surjective(5) == rhoK.is_surjective(5)
True
```

For CM curves, the mod- $p$  representation is never surjective:

```
sage: K.<a> = NumberField(x^2-x+1)
sage: E = EllipticCurve([0,0,0,0,a])
sage: E.has_cm()
True
sage: rho = E.galois_representation()
sage: any(rho.is_surjective(p) for p in [2,3,5,7])
False
```

### **isogeny\_bound** ( $A=100$ )

Return a list of primes  $p$  including all primes for which the image of the mod- $p$  representation is contained in a Borel.

---

**Note:** For the actual list of primes  $p$  at which the representation is reducible see [`reducible\_primes\(\)`](#).

---

INPUT:

- $A$  – int (a bound on the number of traces of Frobenius to use while trying to prove the mod- $p$  representation is not contained in a Borel).

OUTPUT:

- list – A list of primes which contains (but may not be equal to) all  $p$  for which the image of the mod- $p$  representation is contained in a Borel subgroup. At any prime not in this list, the image is definitely not contained in a Borel. If  $E$  has CM defined over  $K$ , the list  $[0]$  is returned.

EXAMPLES:

```
sage: K = NumberField(x**2 - 29, 'a'); a = K.gen()
sage: E = EllipticCurve([1, 0, ((5 + a)/2)**2, 0, 0])
sage: rho = E.galois_representation()
sage: rho.isogeny_bound() # See Section 5.10 of [Serre72].
[3, 5]
sage: K = NumberField(x**2 + 1, 'a')
sage: EllipticCurve_from_j(K(1728)).galois_representation().isogeny_bound() # CM over K
[0]
sage: EllipticCurve_from_j(K(0)).galois_representation().isogeny_bound() # CM NOT over K
[0]
```

```
[2, 3]
sage: E = EllipticCurve_from_j(K(2268945/128)) # c.f. [Sutherland12]
sage: E.galois_representation().isogeny_bound() # No 7-isogeny, but...
[7]
```

For curves with rational CM, there are infinitely many primes  $p$  for which the mod- $p$  representation is reducible, and [0] is returned:

```
sage: K.<a> = NumberField(x^2-x+1)
sage: E = EllipticCurve([0,0,0,0,a])
sage: E.has_rational_cm()
True
sage: rho = E.galois_representation()
sage: rho.isogeny_bound()
[0]
```

An example (an elliptic curve with everywhere good reduction over an imaginary quadratic field with quite large discriminant), which failed until fixed at [trac ticket #21776](#):

```
sage: K.<a> = NumberField(x^2 - x + 112941801)
sage: E = EllipticCurve([a+1,a-1,a,-23163076*a + 266044005933275,
↪57560769602038*a - 836483958630700313803])
sage: E.conductor().norm()
1
sage: GR = E.galois_representation()
sage: GR.isogeny_bound()
[]
```

#### **non\_surjective** ( $A=100$ )

Return a list of primes  $p$  including all primes for which the mod- $p$  representation might not be surjective.

INPUT:

- $A$  – int (a bound on the number of traces of Frobenius to use while trying to prove surjectivity).

OUTPUT:

- `list` – A list of primes where mod- $p$  representation is very likely not surjective. At any prime not in this list, the representation is definitely surjective. If  $E$  has CM, the list [0] is returned.

EXAMPLES:

```
sage: K = NumberField(x**2 - 29, 'a'); a = K.gen()
sage: E = EllipticCurve([1, 0, ((5 + a)/2)**2, 0, 0])
sage: rho = E.galois_representation()
sage: rho.non_surjective() # See Section 5.10 of [Serre72].
[3, 5, 29]
sage: K = NumberField(x**2 + 3, 'a'); a = K.gen()
sage: E = EllipticCurve([0, -1, 1, -10, -20]).change_ring(K) # X_0(11)
sage: rho = E.galois_representation()
sage: rho.non_surjective() # long time (4s on sage.math, 2014)
[3, 5]
sage: K = NumberField(x**2 + 1, 'a'); a = K.gen()
sage: E = EllipticCurve_from_j(1728).change_ring(K) # CM
sage: rho = E.galois_representation()
sage: rho.non_surjective()
[0]
sage: K = NumberField(x**2 - 5, 'a'); a = K.gen()
sage: E = EllipticCurve_from_j(146329141248*a - 327201914880) # CM
```

```
sage: rho = E.galois_representation()
sage: rho.non_surjective() # long time (3s on sage.math, 2014)
[0]
```

**reducible\_primes()**

Return a list of primes  $p$  for which the mod- $p$  representation is reducible, or [0] for CM curves.

OUTPUT:

- list - A list of those primes  $p$  for which the mod- $p$  representation is contained in a Borel subgroup, i.e. is reducible. If  $E$  has CM *defined over*  $K$ , the list [0] is returned (in this case the representation is reducible for infinitely many primes).

EXAMPLES:

```
sage: K = NumberField(x**2 - 29, 'a'); a = K.gen()
sage: E = EllipticCurve([1, 0, ((5 + a)/2)**2, 0, 0])
sage: rho = E.galois_representation()
sage: rho.isogeny_bound() # See Section 5.10 of [Serre72].
[3, 5]
sage: rho.reducible_primes()
[3, 5]

sage: K = NumberField(x**2 + 1, 'a')
sage: EllipticCurve_from_j(K(1728)).galois_representation().isogeny_bound() #
↪ CM over K
[0]
sage: EllipticCurve_from_j(K(0)).galois_representation().reducible_primes() #
↪ CM but NOT over K
[2, 3]
sage: E = EllipticCurve_from_j(K(2268945/128)) # c.f. [Sutherland12]
sage: rho = E.galois_representation()
sage: rho.isogeny_bound() # ... but there is no 7-isogeny ...
[7]
sage: rho.reducible_primes()
[]
```

For curves with rational CM, there are infinitely many primes  $p$  for which the mod- $p$  representation is reducible, and [0] is returned:

```
sage: K.<a> = NumberField(x^2-x+1)
sage: E = EllipticCurve([0,0,0,0,a])
sage: E.has_rational_cm()
True
sage: rho = E.galois_representation()
sage: rho.reducible_primes()
[0]
```

```
sage.schemes.elliptic_curves.gal_reps_number_field.deg_one_primes_iter(K,
                                                                    prin-
                                                                    ci-
                                                                    pal_only=False)
```

Return an iterator over degree 1 primes of  $K$ .

INPUT:

- $K$  – a number field
- `principal_only` – bool; if True, only yield principal primes

OUTPUT:

An iterator over degree 1 primes of  $K$  up to the given norm, optionally yielding only principal primes.

EXAMPLES:

```
sage: K.<a> = QuadraticField(-5)
sage: from sage.schemes.elliptic_curves.gal_reps_number_field import deg_one_
      ↪primes_iter
sage: it = deg_one_primes_iter(K)
sage: [next(it) for _ in range(6)]
[Fractional ideal (2, a + 1),
 Fractional ideal (3, a + 1),
 Fractional ideal (3, a + 2),
 Fractional ideal (-a),
 Fractional ideal (7, a + 3),
 Fractional ideal (7, a + 4)]
sage: it = deg_one_primes_iter(K, True)
sage: [next(it) for _ in range(6)]
[Fractional ideal (-a),
 Fractional ideal (-2*a + 3),
 Fractional ideal (2*a + 3),
 Fractional ideal (a + 6),
 Fractional ideal (a - 6),
 Fractional ideal (-3*a + 4)]
```

### 15.11.9 Isogeny class of elliptic curves over number fields

AUTHORS:

- David Roe (2012-03-29) – initial version.
- John Cremona (2014-08) – extend to number fields.

```
class sage.schemes.elliptic_curves.isogeny_class.IsogenyClass_EC(E, label=None,
                                                                empty=False)
```

Bases: `sage.structure.sage_object.SageObject`

Isogeny class of an elliptic curve.

---

**Note:** The current implementation chooses a curve from each isomorphism class in the isogeny class. Over  $\mathbf{Q}$  this is a unique reduced minimal model in each isomorphism class. Over number fields the model chosen may change in future.

---

**graph()**

Returns a graph whose vertices correspond to curves in this class, and whose edges correspond to prime degree isogenies.

---

**Note:** There are only finitely many possible isogeny graphs for curves over  $\mathbf{Q}$  [M78]. This function tries to lay out the graph nicely by special casing each isogeny graph. This could also be done over other number fields, such as quadratic fields.

---



---

**Note:** The vertices are labeled 1 to  $n$  rather than 0 to  $n-1$  to match LMFDB and Cremona labels for curves

---

over  $\mathbb{Q}$ .

EXAMPLES:

```
sage: isocls = EllipticCurve('15a3').isogeny_class()
sage: G = isocls.graph()
sage: sorted(G._pos.items())
[(1, [-0.8660254, 0.5]), (2, [-0.8660254, 1.5]), (3, [-1.7320508, 0]), (4, [0,
↪ 0]), (5, [0, -1]), (6, [0.8660254, 0.5]), (7, [0.8660254, 1.5]), (8, [1.
↪ 7320508, 0])]
```

REFERENCES:

**index**( $C$ )

Returns the index of a curve in this class.

INPUT:

- $C$  – an elliptic curve in this isogeny class.

OUTPUT:

- $i$  – an integer so that the  $i$  th curve in the class is isomorphic to  $C$

EXAMPLES:

```
sage: E = EllipticCurve('990j1')
sage: iso = E.isogeny_class(order="lmfdb") # orders lexicographically on a-
↪ invariants
sage: iso.index(E.short_weierstrass_model())
2
```

**isogenies**( $fill=False$ )

Returns a list of lists of isogenies and 0s, corresponding to the entries of `matrix()`

INPUT:

- `fill` – boolean (default `False`). Whether to only return prime degree isogenies. Currently only implemented for `fill=False`.

OUTPUT:

- a list of lists, where the  $j$  th entry of the  $i$  th list is either zero or a prime degree isogeny from the  $i$  th curve in this class to the  $j$  th curve.

**Warning:** The domains and codomains of the isogenies will have the same Weierstrass equation as the curves in this class, but they may not be identical python objects in the current implementation.

EXAMPLES:

```
sage: isocls = EllipticCurve('15a3').isogeny_class()
sage: f = isocls.isogenies()[0][1]; f
Isogeny of degree 2 from Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 5*x + 2$  over Rational Field to Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 80*x + 242$  over Rational Field
sage: f.domain() == isocls.curves[0] and f.codomain() == isocls.curves[1]
True
```



**matrix** (*fill=True*)

Returns the matrix whose entries give the minimal degrees of isogenies between curves in this class.

INPUT:

- *fill* – boolean (default True). If False then the matrix will contain only zeros and prime entries; if True it will fill in the other degrees.

EXAMPLES:

```
sage: isocls = EllipticCurve('15a3').isogeny_class()
sage: isocls.matrix()
[ 1  2  2  2  4  4  8  8]
[ 2  1  4  4  8  8 16 16]
[ 2  4  1  4  8  8 16 16]
[ 2  4  4  1  2  2  4  4]
[ 4  8  8  2  1  4  8  8]
[ 4  8  8  2  4  1  2  2]
[ 8 16 16  4  8  2  1  4]
[ 8 16 16  4  8  2  4  1]
sage: isocls.matrix(fill=False)
[0 2 2 2 0 0 0 0]
[2 0 0 0 0 0 0 0]
[2 0 0 0 0 0 0 0]
[2 0 0 0 2 2 0 0]
[0 0 0 2 0 0 0 0]
[0 0 0 2 0 0 2 2]
[0 0 0 0 0 2 0 0]
[0 0 0 0 0 2 0 0]
```

**qf\_matrix** ()

Returns the array whose entries are quadratic forms representing the degrees of isogenies between curves in this class (CM case only).

OUTPUT:

a 2x2 array (list of lists) of list, each of the form [2] or [2,1,3] representing the coefficients of an integral quadratic form in 1 or 2 variables whose values are the possible isogeny degrees between the *i*'th and *j*'th curve in the class.

EXAMPLES:

```
sage: pol = PolynomialRing(QQ, 'x') ([1, 0, 3, 0, 1])
sage: K.<c> = NumberField(pol)
sage: j = 1480640+565760*c^2
sage: E = EllipticCurve(j=j)
sage: C = E.isogeny_class()
sage: C.qf_matrix()
[[[1], [2, 2, 3]], [[2, 2, 3], [1]]]
```

**reorder** (*order*)

Return a new isogeny class with the curves reordered.

INPUT:

- *order* – None, a string or an iterable over all curves in this class. See `sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field.isogeny_class()` for more details.

OUTPUT:

- Another *IsogenyClass\_EC* with the curves reordered (and matrices and maps changed as appropriate)

EXAMPLES:

```
sage: isocls = EllipticCurve('15a1').isogeny_class()
sage: print("\n".join([repr(C) for C in isocls.curves]))
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 10*x - 10$  over Rational
↪Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 5*x + 2$  over Rational
↪Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 + 35*x - 28$  over Rational
↪Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 135*x - 660$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 80*x + 242$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2$  over Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 110*x - 880$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 2160*x - 39540$  over
↪Rational Field
sage: isocls2 = isocls.reorder('lmfdb')
sage: print("\n".join([repr(C) for C in isocls2.curves]))
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 2160*x - 39540$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 135*x - 660$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 110*x - 880$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 80*x + 242$  over
↪Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 10*x - 10$  over Rational
↪Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 - 5*x + 2$  over Rational
↪Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2$  over Rational Field
Elliptic Curve defined by  $y^2 + x*y + y = x^3 + x^2 + 35*x - 28$  over Rational
↪Field
```

**class** sage.schemes.elliptic\_curves.isogeny\_class.**IsogenyClass\_EC\_NumberField**(*E*)  
 Bases: *sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC*

Isogeny classes for elliptic curves over number fields.

**copy**()

Returns a copy (mostly used in reordering).

EXAMPLES:

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [0,0,0,0,1])
sage: C = E.isogeny_class()
sage: C2 = C.copy()
sage: C is C2
False
sage: C == C2
True
```

```

class sage.schemes.elliptic_curves.isogeny_class.IsogenyClass_EC_Rational(E,
                                                                    al-
                                                                    go-
                                                                    rithm='sage',
                                                                    la-
                                                                    bel=None,
                                                                    empty=False)

```

Bases: `sage.schemes.elliptic_curves.isogeny_class.IsogenyClass_EC_NumberField`

Isogeny classes for elliptic curves over  $\mathbb{Q}$ .

**copy()**

Returns a copy (mostly used in reordering).

EXAMPLES:

```

sage: E = EllipticCurve('11a1')
sage: C = E.isogeny_class()
sage: C2 = C.copy()
sage: C is C2
False
sage: C == C2
True

```

```

sage.schemes.elliptic_curves.isogeny_class.possible_isogeny_degrees(E, ver-
                                                                    bose=False)

```

Return a list of primes  $\ell$  sufficient to generate the isogeny class of  $E$ .

INPUT:

- $E$  – An elliptic curve defined over a number field.

OUTPUT:

A finite list of primes  $\ell$  such that every curve isogenous to this curve can be obtained by a finite sequence of isogenies of degree one of the primes in the list.

ALGORITHM:

For curves without CM, the set may be taken to be the finite set of primes at which the Galois representation is not surjective, since the existence of an  $\ell$ -isogeny is equivalent to the image of the mod- $\ell$  Galois representation being contained in a Borel subgroup.

For curves with CM by the order  $O$  of discriminant  $d$ , the Galois representation is always non-surjective and the curve will admit  $\ell$ -isogenies for infinitely many primes  $\ell$ , but there are (of course) only finitely many codomains  $E'$ . The primes can be divided according to the discriminant  $d'$  of the CM order  $O'$  associated to  $E$ : either  $O = O'$ , or one contains the other with index  $\ell$ , since  $\ell O \subset O'$  and vice versa.

Case (1):  $O = O'$ . The degrees of all isogenies between  $E$  and  $E'$  are precisely the integers represented by one of the classes of binary quadratic forms  $Q$  of discriminant  $d$ . Hence to obtain all possible isomorphism classes of codomain  $E'$ , we need only use one prime  $\ell$  represented by each such class  $Q$ . It would in fact suffice to use primes represented by forms which generate the class group. Here we simply omit the principal class and one from each pair of inverse classes, and include a prime represented by each of the remaining forms.

Case (2):  $[O' : O] = \ell$ : so  $d = \ell^2 d'$ . We include all prime divisors of  $d$ .

Case (3):  $[O : O'] = \ell$ : we may assume that  $\ell$  does not divide  $d$  as we have already included these, so  $\ell$  either splits or is inert in  $O$ ; the class numbers satisfy  $h(O') = (\ell \pm 1)h(O)$  accordingly. We include all primes  $\ell$  such that  $\ell \pm 1$  divides the degree  $[K : \mathbb{Q}]$ .

For curves with only potential CM we proceed as in the CM case, using  $2[K : \mathbb{Q}]$  instead of  $[K : \mathbb{Q}]$ .

EXAMPLES:

For curves without CM we determine the primes at which the mod  $p$  Galois representation is reducible, i.e. contained in a Borel subgroup:

```
sage: from sage.schemes.elliptic_curves.isogeny_class import possible_isogeny_
      ↪degrees
sage: E = EllipticCurve('11a1')
sage: possible_isogeny_degrees(E)
[5]
```

We check that in this case  $E$  really does have rational 5-isogenies:

```
sage: [phi.degree() for phi in E.isogenies_prime_degree()]
[5, 5]
```

Over an extension field:

```
sage: E3 = E.change_ring(CyclotomicField(3))
sage: possible_isogeny_degrees(E3)
[5]
sage: [phi.degree() for phi in E3.isogenies_prime_degree()]
[5, 5]
```

For curves with CM by a quadratic order of class number greater than 1, we use the structure of the class group to only give one prime in each ideal class:

```
sage: pol = PolynomialRing(QQ, 'x')([1, -3, 5, -5, 5, -3, 1])
sage: L.<a> = NumberField(pol)
sage: j = hilbert_class_polynomial(-23).roots(L, multiplicities=False)[0]
sage: E = EllipticCurve(j=j)
sage: from sage.schemes.elliptic_curves.isogeny_class import possible_isogeny_
      ↪degrees
sage: possible_isogeny_degrees(E, verbose=True)
CM case, discriminant = -23
initial primes: {2}
upward primes: {}
downward ramified primes: {}
downward split primes: {2, 3}
downward inert primes: {5}
primes generating the class group: [2]
Complete set of primes: {2, 3, 5}
[2, 3, 5]
```

### 15.11.10 Tate-Shafarevich group

If  $E$  is an elliptic curve over a global field  $K$ , the Tate-Shafarevich group is the subgroup of elements in  $H^1(K, E)$  which map to zero under every global-to-local restriction map  $H^1(K, E) \rightarrow H^1(K_v, E)$ , one for each place  $v$  of  $K$ .

The group is usually denoted by the Russian letter Sha (cyrillic Sha), in this document it will be denoted by  $Sha$ .

$Sha$  is known to be an abelian torsion group. It is conjectured that the Tate-Shafarevich group is finite for any elliptic curve over a global field. But it is not known in general.

A theorem of Kolyvagin and Gross-Zagier using Heegner points shows that if the L-series of an elliptic curve  $E/\mathbb{Q}$  does not vanish at 1 or has a simple zero there, then  $Sha$  is finite.

A theorem of Kato, together with theorems from Iwasawa theory, allows for certain primes  $p$  to show that the  $p$ -primary part of  $Sha$  is finite and gives an effective upper bound for it.

The ( $p$ -adic) conjecture of Birch and Swinnerton-Dyer predicts the order of  $Sha$  from the leading term of the ( $p$ -adic) L-series of the elliptic curve.

Sage can compute a few things about  $Sha$ . The commands `an`, `an_numerical` and `an_padic` compute the conjectural order of  $Sha$  as a real or  $p$ -adic number. With `p_primary_bound` one can find an upper bound of the size of the  $p$ -primary part of  $Sha$ . Finally, if the analytic rank is at most 1, then `bound_kato` and `bound_kolyvagin` find all primes for which the theorems of Kato and Kolyvagin respectively do not prove the triviality the  $p$ -primary part of  $Sha$ .

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: S = E.sha()
sage: S.bound_kato()
[2]
sage: S.bound_kolyvagin()
([2, 5], 1)
sage: S.an_padic(7,3)
1 + O(7^5)
sage: S.an()
1
sage: S.an_numerical()
1.0000000000000000

sage: E = EllipticCurve('389a')
sage: S = E.sha(); S
Tate-Shafarevich group for the Elliptic Curve defined by y^2 + y = x^3 + x^2 - 2*x_
↪over Rational Field
sage: S.an_numerical()
1.0000000000000000
sage: S.p_primary_bound(5)
0
sage: S.an_padic(5)
1 + O(5)
sage: S.an_padic(5,prec=4) # long time (2s on sage.math, 2011)
1 + O(5^3)
```

AUTHORS:

- William Stein (2007) – initial version
- Chris Wuthrich (April 2009) – reformat docstrings
- Aly Deines, Chris Wuthrich, Jeaninne Van Order (2016-03): Added functionality that tests the Skinner-Urban condition.

**class** `sage.schemes.elliptic_curves.sha_tate.Sha` ( $E$ )

Bases: `sage.structure.sage_object.SageObject`

The Tate-Shafarevich group associated to an elliptic curve.

If  $E$  is an elliptic curve over a global field  $K$ , the Tate-Shafarevich group is the subgroup of elements in  $H^1(K, E)$  which map to zero under every global-to-local restriction map  $H^1(K, E) \rightarrow H^1(K_v, E)$ , one for each place  $v$  of  $K$ .

EXAMPLES:

```
sage: E = EllipticCurve('571a1')
sage: E._set_gens([]) # curve has rank 0, but non-trivial Sha[2]
sage: S = E.sha()
sage: S.bound_kato()
```

```
[2]
sage: S.bound_kolyvagin()
([2], 1)
sage: S.an_padic(7,3)
4 + O(7^5)
sage: S.an()
4
sage: S.an_numerical()
4.000000000000000

sage: E = EllipticCurve('389a')
sage: S = E.sha(); S
Tate-Shafarevich group for the Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 2x$  over Rational Field
↪2*x over Rational Field
sage: S.an_numerical()
1.000000000000000
sage: S.p_primary_bound(5) # long time
0
sage: S.an_padic(5) # long time
1 + O(5)
sage: S.an_padic(5,prec=4) # very long time
1 + O(5^3)
```

**an** (*use\_database=False, descent\_second\_limit=12*)

Returns the Birch and Swinnerton-Dyer conjectural order of *Sha* as a provably correct integer, unless the analytic rank is  $> 1$ , in which case this function returns a numerical value.

INPUT:

- *use\_database* – bool (default: False); if True, try to use any databases installed to lookup the analytic order of *Sha*, if possible. The order of *Sha* is computed if it cannot be looked up.
- *descent\_second\_limit* – int (default: 12); limit to use on point searching for the quartic twist in the hard case

This result is proved correct if the order of vanishing is 0 and the Manin constant is  $\leq 2$ .

If the optional parameter *use\_database* is True (default: False), this function returns the analytic order of *Sha* as listed in Cremona's tables, if this curve appears in Cremona's tables.

NOTE:

If you come across the following error:

```
sage: E = EllipticCurve([0, 0, 1, -34874, -2506691])
sage: E.sha().an()
Traceback (most recent call last):
...
RuntimeError: Unable to compute the rank, hence generators, with certainty
↪(lower bound=0, generators found=[]). This could be because Sha(E/Q)[2] is
↪nontrivial.
Try increasing descent_second_limit then trying this command again.
```

You can increase the *descent\_second\_limit* (in the above example, set to the default, 12) option to try again:

```
sage: E.sha().an(descent_second_limit=16) # long time (2s on sage.math, 2011)
1
```

EXAMPLES:

```

sage: E = EllipticCurve([0, -1, 1, -10, -20])    # 11A = X_0(11)
sage: E.sha().an()
1
sage: E = EllipticCurve([0, -1, 1, 0, 0])        # X_1(11)
sage: E.sha().an()
1
sage: EllipticCurve('14a4').sha().an()
1
sage: EllipticCurve('14a4').sha().an(use_database=True)    # will be faster if_
↪you have large Cremona database installed
1

```

The smallest conductor curve with nontrivial *Sha*:

```

sage: E = EllipticCurve([1, 1, 1, -352, -2689])    # 66b3
sage: E.sha().an()
4

```

The four optimal quotients with nontrivial *Sha* and conductor  $\leq 1000$ :

```

sage: E = EllipticCurve([0, -1, 1, -929, -10595])    # 571A
sage: E.sha().an()
4
sage: E = EllipticCurve([1, 1, 0, -1154, -15345])    # 681B
sage: E.sha().an()
9
sage: E = EllipticCurve([0, -1, 0, -900, -10098])    # 960D
sage: E.sha().an()
4
sage: E = EllipticCurve([0, 1, 0, -20, -42])        # 960N
sage: E.sha().an()
4

```

The smallest conductor curve of rank  $> 1$ :

```

sage: E = EllipticCurve([0, 1, 1, -2, 0])          # 389A (rank 2)
sage: E.sha().an()
1.000000000000000

```

The following are examples that require computation of the Mordell-Weil group and regulator:

```

sage: E = EllipticCurve([0, 0, 1, -1, 0])          # 37A (rank 1)
sage: E.sha().an()
1
sage: E = EllipticCurve("1610f3")
sage: E.sha().an()
4

```

In this case the input curve is not minimal, and if this function did not transform it to be minimal, it would give nonsense:

```

sage: E = EllipticCurve([0, -432*6^2])
sage: E.sha().an()
1

```

See [trac ticket #10096](#): this used to give the wrong result 6.0000 before since the minimal model was not used:

```
sage: E = EllipticCurve([1215*1216,0]) # non-minimal model
sage: E.sha().an() # long time (2s on sage.math, 2011)
1.000000000000000
sage: E.minimal_model().sha().an() # long time (1s on sage.math, 2011)
1.000000000000000
```

**an\_numerical** (*prec=None, use\_database=True, proof=None*)

Return the numerical analytic order of  $Sha$ , which is a floating point number in all cases.

INPUT:

- *prec* - integer (default: 53) bits precision – used for the L-series computation, period, regulator, etc.
- *use\_database* - whether the rank and generators should be looked up in the database if possible. Default is True
- *proof* - bool or None (default: None, see `proof.[tab]` or `sage.structure.proof`) proof option passed onto regulator and rank computation.

---

**Note:** See also the `an()` command, which will return a provably correct integer when the rank is 0 or 1.

---

**Warning:** If the curve's generators are not known, computing them may be very time-consuming. Also, computation of the L-series derivative will be time-consuming for large rank and large conductor, and the computation time for this may increase substantially at greater precision. However, use of very low precision less than about 10 can cause the underlying PARI library functions to fail.

EXAMPLES:

```
sage: EllipticCurve('11a').sha().an_numerical()
1.000000000000000
sage: EllipticCurve('37a').sha().an_numerical()
1.000000000000000
sage: EllipticCurve('389a').sha().an_numerical()
1.000000000000000
sage: EllipticCurve('66b3').sha().an_numerical()
4.000000000000000
sage: EllipticCurve('5077a').sha().an_numerical()
1.000000000000000
```

A rank 4 curve:

```
sage: EllipticCurve([1, -1, 0, -79, 289]).sha().an_numerical() # long time
↳ (3s on sage.math, 2011)
1.000000000000000
```

A rank 5 curve:

```
sage: EllipticCurve([0, 0, 1, -79, 342]).sha().an_numerical(prec=10,
↳ proof=False) # long time (22s on sage.math, 2011)
1.0
```

See [trac ticket #1115](#):



```

sage: sha = EllipticCurve('37a1').sha()
sage: [sha.an_numerical(prec) for prec in range(40,100,10)] # long time (3s_
↪on sage.math, 2013)
[1.000000000000,
1.000000000000000,
1.0000000000000000,
1.000000000000000000,
1.00000000000000000000,
1.0000000000000000000000,
1.000000000000000000000000]

```

**an\_padic** ( $p$ ,  $prec=0$ ,  $use\_twists=True$ )

Returns the conjectural order of  $\text{Sha}(E/\mathbf{Q})$ , according to the  $p$ -adic analogue of the Birch and Swinnerton-Dyer conjecture as formulated in [MTT] and [BP].

REFERENCES:

INPUT:

- $p$  - a prime  $> 3$
- $prec$  (optional) - the precision used in the computation of the  $p$ -adic L-Series
- $use\_twists$  (default = True) - If True the algorithm may change to a quadratic twist with minimal conductor to do the modular symbol computations rather than using the modular symbols of the curve itself. If False it forces the computation using the modular symbols of the curve itself.

OUTPUT:  $p$ -adic number - that conjecturally equals  $\#\text{Sha}(E/\mathbf{Q})$ .

If  $prec$  is set to zero (default) then the precision is set so that at least the first  $p$ -adic digit of conjectural  $\#\text{Sha}(E/\mathbf{Q})$  is determined.

EXAMPLES:

Good ordinary examples:

```

sage: EllipticCurve('11a1').sha().an_padic(5) # rank 0
1 + O(5^22)
sage: EllipticCurve('43a1').sha().an_padic(5) # rank 1
1 + O(5)
sage: EllipticCurve('389a1').sha().an_padic(5,4) # rank 2, long time (2s on_
↪sage.math, 2011)
1 + O(5^3)
sage: EllipticCurve('858k2').sha().an_padic(7) # rank 0, non trivial sha,
↪long time (10s on sage.math, 2011)
7^2 + O(7^24)
sage: EllipticCurve('300b2').sha().an_padic(3) # 9 elements in sha, long_
↪time (2s on sage.math, 2011)
3^2 + O(3^24)
sage: EllipticCurve('300b2').sha().an_padic(7, prec=6) # long time
2 + 7 + O(7^8)

```

Exceptional cases:

```

sage: EllipticCurve('11a1').sha().an_padic(11) # rank 0
1 + O(11^22)
sage: EllipticCurve('130a1').sha().an_padic(5) # rank 1
1 + O(5)

```

Non-split, but rank 0 case (trac ticket #7331):

```
sage: EllipticCurve('270b1').sha().an_padic(5) # rank 0, long time (2s on
↪sage.math, 2011)
1 + O(5^22)
```

The output has the correct sign:

```
sage: EllipticCurve('123a1').sha().an_padic(41) # rank 1, long time (3s on
↪sage.math, 2011)
1 + O(41)
```

Supersingular cases:

```
sage: EllipticCurve('34a1').sha().an_padic(5) # rank 0
1 + O(5^22)
sage: EllipticCurve('53a1').sha().an_padic(5) # rank 1, long time (11s on
↪sage.math, 2011)
1 + O(5)
```

Cases that use a twist to a lower conductor:

```
sage: EllipticCurve('99a1').sha().an_padic(5)
1 + O(5)
sage: EllipticCurve('240d3').sha().an_padic(5) # sha has 4 elements here
4 + O(5)
sage: EllipticCurve('448c5').sha().an_padic(7,prec=4, use_twists=False) #
↪long time (2s on sage.math, 2011)
2 + 7 + O(7^6)
sage: EllipticCurve([-19,34]).sha().an_padic(5) # see trac #6455, long time
↪(4s on sage.math, 2011)
1 + O(5)
```

Test for trac ticket #15737:

```
sage: E = EllipticCurve([-100,0])
sage: s = E.sha()
sage: s.an_padic(13)
1 + O(13^20)
```

**bound()**

Compute a provably correct bound on the order of the Tate-Shafarevich group of this curve. The bound is either False (no bound) or a list B of primes such that any prime divisor of the order of  $Sha$  is in this list.

EXAMPLES:

```
sage: EllipticCurve('37a').sha().bound()
([2], 1)
```

**bound\_kato()**

Returns a list of primes  $p$  such that the theorems of Kato's [Ka] and others (e.g., as explained in a thesis of Grigor Grigorov [Gri]) imply that if  $p$  divides the order of  $Sha(E/\mathbb{Q})$  then  $p$  is in the list.

If  $L(E, 1) = 0$ , then this function gives no information, so it returns False.

THEOREM: Suppose  $L(E, 1) \neq 0$  and  $p \neq 2$  is a prime such that

- $E$  does not have additive reduction at  $p$ ,
- either the  $p$ -adic representation is surjective or has its image contained in a Borel subgroup.

Then  $\text{ord}_p(\#Sha(E))$  is bounded from above by the  $p$ -adic valuation of  $L(E, 1) \cdot \#E(\mathbf{Q})_{\text{tor}}^2 / (\Omega_E \cdot \prod c_v)$ .

If the L-series vanishes, the method `p_primary_bound` can be used instead.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20]) # 11A = X_0(11)
sage: E.sha().bound_kato()
[2]
sage: E = EllipticCurve([0, -1, 1, 0, 0]) # X_1(11)
sage: E.sha().bound_kato()
[2]
sage: E = EllipticCurve([1, 1, 1, -352, -2689]) # 66B3
sage: E.sha().bound_kato()
[2]
```

For the following curve one really has that 25 divides the order of *Sha* (by [GJPST]):

```
sage: E = EllipticCurve([1, -1, 0, -332311, -73733731]) # 1058D1
sage: E.sha().bound_kato() # long time (about 1 second)
[2, 5, 23]
sage: E.galois_representation().non_surjective() # long time
↪ (about 1 second)
[]
```

For this one, *Sha* is divisible by 7:

```
sage: E = EllipticCurve([0, 0, 0, -4062871, -3152083138]) # 3364C1
sage: E.sha().bound_kato() # long time (< 10 seconds)
[2, 7, 29]
```

No information about curves of rank > 0:

```
sage: E = EllipticCurve([0, 0, 1, -1, 0]) # 37A (rank 1)
sage: E.sha().bound_kato()
False
```

REFERENCES:

**bound\_kolyvagin** ( $D=0$ , *regulator=None*, *ignore\_nonsurj\_hypothesis=False*)

Given a fundamental discriminant  $D \neq -3, -4$  that satisfies the Heegner hypothesis for  $E$ , return a list of primes so that Kolyvagin's theorem (as in Gross's paper) implies that any prime divisor of *Sha* is in this list.

INPUT:

- `D` - (optional) a fundamental discriminant  $< -4$  that satisfies the Heegner hypothesis for  $E$ ; if not given, use the first such  $D$
- `regulator` - (optional) regulator of  $E(K)$ ; if not given, will be computed (which could take a long time)
- `ignore_nonsurj_hypothesis` (optional: default `False`) - If `True`, then gives the bound coming from Heegner point index, but without any hypothesis on surjectivity of the mod- $p$  representation.

OUTPUT:

- `list` - a list of primes such that if  $p$  divides  $Sha(E/K)$ , then  $p$  is in this list, unless  $E/K$  has complex multiplication or analytic rank greater than 2 (in which case we return 0).

- index – the odd part of the index of the Heegner point in the full group of  $K$ -rational points on  $E$ . (If  $E$  has CM, returns 0.)

## REMARKS:

1. We do not have to assume that the Manin constant is 1 (or a power of 2). If the Manin constant were divisible by a prime, that prime would get included in the list of bad primes.
2. We assume the Gross-Zagier theorem is true under the hypothesis that  $\gcd(N, D) = 1$ , instead of the stronger hypothesis  $\gcd(2 \cdot N, D) = 1$  that is in the original Gross-Zagier paper. That Gross-Zagier is true when  $\gcd(N, D) = 1$  is “well-known” to the experts, but does not seem to be written up well in the literature.
3. Correctness of the computation is guaranteed using interval arithmetic, under the assumption that the regulator, square root, and period lattice are computed to precision at least  $10^{-10}$ , i.e., they are correct up to addition or a real number with absolute value less than  $10^{-10}$ .

## EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.sha().bound_kolyvagin()
([2], 1)
sage: E = EllipticCurve('141a')
sage: E.sha().an()
1
sage: E.sha().bound_kolyvagin()
([2, 7], 49)
```

We get no information when the curve has rank 2.:

```
sage: E = EllipticCurve('389a')
sage: E.sha().bound_kolyvagin()
(0, 0)
sage: E = EllipticCurve('681b')
sage: E.sha().an()
9
sage: E.sha().bound_kolyvagin()
([2, 3], 9)
```

**p\_primary\_bound( $p$ )**

Return a provable upper bound for the order of the  $p$ -primary part  $Sha(E)(p)$  of the Tate-Shafarevich group.

## INPUT:

- $p$  – a prime  $> 2$

## OUTPUT:

- $e$  – a non-negative integer such that  $p^e$  is an upper bound for the order of  $Sha(E)(p)$

In particular, if this algorithm does not fail, then it proves that the  $p$ -primary part of  $Sha$  is finite. This works also for curves of rank  $> 1$ .

Note also that this bound is sharp if one assumes the main conjecture of Iwasawa theory of elliptic curves. One may use the method `p_primary_order` for checking if the extra conditions hold under which the main conjecture is known by the work of Skinner and Urban. This then returns the provable  $p$ -primary part of the Tate-Shafarevich group,

Currently the algorithm is only implemented when the following conditions are verified:

- The  $p$ -adic Galois representation must be surjective or must have its image contained in a Borel subgroup.
- The reduction at  $p$  is not allowed to be additive.
- If the reduction at  $p$  is non-split multiplicative, then the rank must be 0.
- If  $p = 3$ , then the reduction at 3 must be good ordinary or split multiplicative, and the rank must be 0.

**ALGORITHM:**

The algorithm is described in [SW]. The results for the reducible case can be found in [Wu]. The main ingredient is Kato's result on the main conjecture in Iwasawa theory.

**EXAMPLES:**

```
sage: e = EllipticCurve('11a3')
sage: e.sha().p_primary_bound(3)
0
sage: e.sha().p_primary_bound(5)
0
sage: e.sha().p_primary_bound(7)
0
sage: e.sha().p_primary_bound(11)
0
sage: e.sha().p_primary_bound(13)
0

sage: e = EllipticCurve('389a1')
sage: e.sha().p_primary_bound(5)
0
sage: e.sha().p_primary_bound(7)
0
sage: e.sha().p_primary_bound(11)
0
sage: e.sha().p_primary_bound(13)
0

sage: e = EllipticCurve('858k2')
sage: e.sha().p_primary_bound(3) # long time (10s on sage.math, 2011)
0
```

Some checks for [trac ticket #6406](#) and [trac ticket #16959](#):

```
sage: e.sha().p_primary_bound(7) # long time
2

sage: E = EllipticCurve('608b1')
sage: E.sha().p_primary_bound(5)
Traceback (most recent call last):
...
ValueError: The p-adic Galois representation is not surjective or reducible.
↳ Current knowledge about Euler systems does not provide an upper bound in
↳ this case. Try an_padic for a conjectural bound.

sage: E.sha().an_padic(5) # long time
1 + O(5^22)

sage: E = EllipticCurve("5040b11")
sage: E.sha().p_primary_bound(5) # long time
0
```

## REFERENCES:

**p\_primary\_order**( $p$ )

Return the order of the  $p$ -primary part of the Tate-Shafarevich group.

This uses the result of Skinner and Urban [SU] on the main conjecture in Iwasawa theory. In particular the elliptic curve must have good ordinary reduction at  $p$ , the residual Galois representation must be surjective. Furthermore there must be an auxiliary prime  $\ell$  dividing the conductor of the curve exactly once such that the residual representation is ramified at  $p$ .

## INPUT:

- $p$  – an odd prime

## OUTPUT:

- $e$  – a non-negative integer such that  $p^e$  is the order of the  $p$ -primary order if the conditions are satisfied and raises a `ValueError` otherwise.

## EXAMPLES:

```
sage: E = EllipticCurve("389a1") # rank 2
sage: E.sha().p_primary_order(5)
0
sage: E = EllipticCurve("11a1")
sage: E.sha().p_primary_order(7)
0
sage: E.sha().p_primary_order(5)
Traceback (most recent call last):
...
ValueError: The order is not provably known using Skinner-Urban.
Try running p_primary_bound to get a bound.
```

## REFERENCES:

**two\_selmer\_bound**()

This returns the 2-rank, i.e. the  $\mathbf{F}_2$ -dimension of the 2-torsion part of  $Sha$ , provided we can determine the rank of  $E$ .

## EXAMPLES:

```
sage: sh = EllipticCurve('571a1').sha()
sage: sh.two_selmer_bound()
2
sage: sh.an()
4

sage: sh = EllipticCurve('66a1').sha()
sage: sh.two_selmer_bound()
0
sage: sh.an()
1

sage: sh = EllipticCurve('960d1').sha()
sage: sh.two_selmer_bound()
2
sage: sh.an()
4
```

### 15.11.11 Complex multiplication for elliptic curves

This module implements the functions

- `hilbert_class_polynomial`
- `cm_j_invariants`
- `cm_orders`
- `discriminants_with_bounded_class_number`
- `cm_j_invariants_and_orders`
- `largest_fundamental_disc_with_class_number`

AUTHORS:

- Robert Bradshaw
- John Cremona
- William Stein

`sage.schemes.elliptic_curves.cm.cm_j_invariants(K, proof=None)`

Return a list of all CM  $j$ -invariants in the field  $K$ .

INPUT:

- $K$  – a number field
- `proof` – (default: `proof.number_field()`)

OUTPUT:

(list) – A list of CM  $j$ -invariants in the field  $K$ .

EXAMPLES:

```
sage: cm_j_invariants(QQ)
[-262537412640768000, -147197952000, -884736000, -12288000, -884736, -32768, -
↪ 3375, 0, 1728, 8000, 54000, 287496, 16581375]
```

Over imaginary quadratic fields there are no more than over  $QQ$ :

```
sage: cm_j_invariants(QuadraticField(-1, 'i'))
[-262537412640768000, -147197952000, -884736000, -12288000, -884736, -32768, -
↪ 3375, 0, 1728, 8000, 54000, 287496, 16581375]
```

Over real quadratic fields there may be more, for example:

```
sage: len(cm_j_invariants(QuadraticField(5, 'a')))
31
```

Over number fields  $K$  of many higher degrees this also works:

```
sage: K.<a> = NumberField(x^3 - 2)
sage: cm_j_invariants(K)
[-12288000, 54000, 0, 287496, 1728, 16581375, -3375, 8000, -32768, -884736, -
↪ 884736000, -147197952000, -262537412640768000, 31710790944000*a^2 +
↪ 39953093016000*a + 50337742902000]
sage: K.<a> = NumberField(x^4 - 2)
sage: len(cm_j_invariants(K))
23
```

`sage.schemes.elliptic_curves.cm.cm_j_invariants_and_orders(K, proof=None)`

Return a list of all CM  $j$ -invariants in the field  $K$ , together with the associated orders.

INPUT:

- $K$  – a number field
- `proof` – (default: `proof.number_field()`)

OUTPUT:

(list) A list of 3-tuples  $(D, f, j)$  where  $j$  is a CM  $j$ -invariant in  $K$  with quadratic fundamental discriminant  $D$  and conductor  $f$ .

EXAMPLES:

```
sage: cm_j_invariants_and_orders(QQ)
[(-3, 3, -12288000), (-3, 2, 54000), (-3, 1, 0), (-4, 2, 287496), (-4, 1, 1728),
↪ (-7, 2, 16581375), (-7, 1, -3375), (-8, 1, 8000), (-11, 1, -32768), (-19, 1, -
↪ 884736), (-43, 1, -884736000), (-67, 1, -147197952000), (-163, 1, -
↪ 262537412640768000)]
```

Over an imaginary quadratic field there are no more than over  $QQ$ :

```
sage: cm_j_invariants_and_orders(QuadraticField(-1, 'i'))
[(-3, 3, -12288000), (-3, 2, 54000), (-3, 1, 0), (-4, 2, 287496), (-4, 1, 1728),
↪ (-7, 2, 16581375), (-7, 1, -3375), (-8, 1, 8000), (-11, 1, -32768), (-19, 1, -
↪ 884736), (-43, 1, -884736000), (-67, 1, -147197952000), (-163, 1, -
↪ 262537412640768000)]
```

Over real quadratic fields there may be more:

```
sage: v = cm_j_invariants_and_orders(QuadraticField(5, 'a')); len(v)
31
sage: [(D,f) for D,f,j in v if j not in QQ]
[(-3, 5), (-3, 5), (-4, 5), (-4, 5), (-15, 2), (-15, 2), (-15, 1), (-15, 1), (-20,
↪ 1), (-20, 1), (-35, 1), (-35, 1), (-40, 1), (-40, 1), (-115, 1), (-115, 1), (-
↪ 235, 1), (-235, 1)]
```

Over number fields  $K$  of many higher degrees this also works:

```
sage: K.<a> = NumberField(x^3 - 2)
sage: cm_j_invariants_and_orders(K)
[(-3, 3, -12288000), (-3, 2, 54000), (-3, 1, 0), (-4, 2, 287496), (-4, 1, 1728),
↪ (-7, 2, 16581375), (-7, 1, -3375), (-8, 1, 8000), (-11, 1, -32768), (-19, 1, -
↪ 884736), (-43, 1, -884736000), (-67, 1, -147197952000), (-163, 1, -
↪ 262537412640768000), (-3, 6, 31710790944000*a^2 + 39953093016000*a +
↪ 50337742902000)]
```

`sage.schemes.elliptic_curves.cm.cm_orders(h, proof=None)`

Return a list of all pairs  $(D, f)$  where there is a CM order of discriminant  $Df^2$  with class number  $h$ , with  $D$  a fundamental discriminant.

INPUT:

- $h$  – positive integer
- `proof` – (default: `proof.number_field()`)

OUTPUT:

- list of 2-tuples  $(D, f)$



## EXAMPLES:

```

sage: cm_orders(0)
[]
sage: v = cm_orders(1); v
[(-3, 3), (-3, 2), (-3, 1), (-4, 2), (-4, 1), (-7, 2), (-7, 1), (-8, 1), (-11, 1),
↪ (-19, 1), (-43, 1), (-67, 1), (-163, 1)]
sage: type(v[0][0]), type(v[0][1])
(<... 'sage.rings.integer.Integer'>, <... 'sage.rings.integer.Integer'>)
sage: v = cm_orders(2); v
[(-3, 7), (-3, 5), (-3, 4), (-4, 5), (-4, 4), (-4, 3), (-7, 4), (-8, 3), (-8, 2),
↪ (-11, 3), (-15, 2), (-15, 1), (-20, 1), (-24, 1), (-35, 1), (-40, 1), (-51, 1),
↪ (-52, 1), (-88, 1), (-91, 1), (-115, 1), (-123, 1), (-148, 1), (-187, 1), (-
↪ 232, 1), (-235, 1), (-267, 1), (-403, 1), (-427, 1)]
sage: len(v)
29
sage: set([hilbert_class_polynomial(D*f^2).degree() for D,f in v])
{2}

```

Any degree up to 100 is implemented, but may be prohibitively slow:

```

sage: cm_orders(3)
[(-3, 9), (-3, 6), (-11, 2), (-19, 2), (-23, 2), (-23, 1), (-31, 2), (-31, 1), (-
↪ 43, 2), (-59, 1), (-67, 2), (-83, 1), (-107, 1), (-139, 1), (-163, 2), (-211,
↪ 1), (-283, 1), (-307, 1), (-331, 1), (-379, 1), (-499, 1), (-547, 1), (-643, 1),
↪ (-883, 1), (-907, 1)]
sage: len(cm_orders(4))
84

```

`sage.schemes.elliptic_curves.cm.discriminants_with_bounded_class_number(hmax, B=None, proof=None)`

Return dictionary with keys class numbers  $h \leq hmax$  and values the list of all pairs  $(D, f)$ , with  $D < 0$  a fundamental discriminant such that  $Df^2$  has class number  $h$ . If the optional bound  $B$  is given, return only those pairs with fundamental  $|D| \leq B$ , though  $f$  can still be arbitrarily large.

INPUT:

- $hmax$  – integer
- $B$  – integer or None; if None returns all pairs
- `proof` – this code calls the PARI function `qfbclassno`, so it could give wrong answers when `proof`==`False`. The default is whatever `proof.number_field()` is. If `proof==False` and  $B$  is None, at least the number of discriminants is correct, since it is double checked with Watkins’s table.

OUTPUT:

- dictionary

In case  $B$  is not given, we use Mark Watkins’s: “Class numbers of imaginary quadratic fields” to compute a  $B$  that captures all  $h$  up to  $hmax$  (only available for  $hmax \leq 100$ ).

## EXAMPLES:

```

sage: v = sage.schemes.elliptic_curves.cm.discriminants_with_bounded_class_
↪ number(3)
sage: list(v)
[1, 2, 3]
sage: v[1]

```

```

[(-3, 3), (-3, 2), (-3, 1), (-4, 2), (-4, 1), (-7, 2), (-7, 1), (-8, 1), (-11, 1),
↪ (-19, 1), (-43, 1), (-67, 1), (-163, 1)]
sage: v[2]
[(-3, 7), (-3, 5), (-3, 4), (-4, 5), (-4, 4), (-4, 3), (-7, 4), (-8, 3), (-8, 2),
↪ (-11, 3), (-15, 2), (-15, 1), (-20, 1), (-24, 1), (-35, 1), (-40, 1), (-51, 1),
↪ (-52, 1), (-88, 1), (-91, 1), (-115, 1), (-123, 1), (-148, 1), (-187, 1), (-232,
↪ 1), (-235, 1), (-267, 1), (-403, 1), (-427, 1)]
sage: v[3]
[(-3, 9), (-3, 6), (-11, 2), (-19, 2), (-23, 2), (-23, 1), (-31, 2), (-31, 1), (-
↪ 43, 2), (-59, 1), (-67, 2), (-83, 1), (-107, 1), (-139, 1), (-163, 2), (-211,
↪ 1), (-283, 1), (-307, 1), (-331, 1), (-379, 1), (-499, 1), (-547, 1), (-643, 1),
↪ (-883, 1), (-907, 1)]
sage: v = sage.schemes.elliptic_curves.cm.discriminants_with_bounded_class_
↪ number(8, proof=False)
sage: [len(v[h]) for h in v]
[13, 29, 25, 84, 29, 101, 38, 208]

```

Find all class numbers for discriminant up to 50:

```

sage: sage.schemes.elliptic_curves.cm.discriminants_with_bounded_class_
↪ number(hmax=5, B=50)
{1: [(-3, 3), (-3, 2), (-3, 1), (-4, 2), (-4, 1), (-7, 2), (-7, 1), (-8, 1), (-11,
↪ 1), (-19, 1), (-43, 1)], 2: [(-3, 7), (-3, 5), (-3, 4), (-4, 5), (-4, 4), (-4,
↪ 3), (-7, 4), (-8, 3), (-8, 2), (-11, 3), (-15, 2), (-15, 1), (-20, 1), (-24, 1),
↪ (-35, 1), (-40, 1)], 3: [(-3, 9), (-3, 6), (-11, 2), (-19, 2), (-23, 2), (-23,
↪ 1), (-31, 2), (-31, 1), (-43, 2)], 4: [(-3, 13), (-3, 11), (-3, 8), (-4, 10), (-
↪ 4, 8), (-4, 7), (-4, 6), (-7, 8), (-7, 6), (-7, 3), (-8, 6), (-8, 4), (-11, 5),
↪ (-15, 4), (-19, 5), (-19, 3), (-20, 3), (-20, 2), (-24, 2), (-35, 3), (-39, 2),
↪ (-39, 1), (-40, 2), (-43, 3)], 5: [(-47, 2), (-47, 1)]}

```

`sage.schemes.elliptic_curves.cm.hilbert_class_polynomial(D, algorithm=None)`

Returns the Hilbert class polynomial for discriminant *D*.

INPUT:

- *D* (int) – a negative integer congruent to 0 or 1 modulo 4.
- *algorithm* (string, default None).

OUTPUT:

(integer polynomial) The Hilbert class polynomial for the discriminant *D*.

ALGORITHM:

- If *algorithm* = “arb” (default): Use Arb’s implementation which uses complex interval arithmetic.
- If *algorithm* = “sage”: Use complex approximations to the roots.
- If *algorithm* = “magma”: Call the appropriate Magma function (if available).

AUTHORS:

- Sage implementation originally by Eduardo Ocampo Alvarez and Andrey Timofeev
- Sage implementation corrected by John Cremona (using corrected precision bounds from Andreas Enge)
- Magma implementation by David Kohel

EXAMPLES:

```

sage: hilbert_class_polynomial(-4)
x - 1728
sage: hilbert_class_polynomial(-7)
x + 3375
sage: hilbert_class_polynomial(-23)
x^3 + 3491750*x^2 - 5151296875*x + 12771880859375
sage: hilbert_class_polynomial(-37*4)
x^2 - 39660183801072000*x - 7898242515936467904000000
sage: hilbert_class_polynomial(-37*4, algorithm="magma") # optional - magma
x^2 - 39660183801072000*x - 7898242515936467904000000
sage: hilbert_class_polynomial(-163)
x + 262537412640768000
sage: hilbert_class_polynomial(-163, algorithm="sage")
x + 262537412640768000
sage: hilbert_class_polynomial(-163, algorithm="magma") # optional - magma
x + 262537412640768000

```

`sage.schemes.elliptic_curves.cm.is_cm_j_invariant(j, method='new')`

Return whether or not this is a CM  $j$ -invariant.

INPUT:

- $j$  – an element of a number field  $K$

OUTPUT:

A pair (bool, (d,f)) which is either (False, None) if  $j$  is not a CM  $j$ -invariant or (True, (d,f)) if  $j$  is the  $j$ -invariant of the imaginary quadratic order of discriminant  $D = df^2$  where  $d$  is the associated fundamental discriminant and  $f$  the index.

---

**Note:** The current implementation makes use of the classification of all orders of class number up to 100, and hence will raise an error if  $j$  is an algebraic integer of degree greater than this. It would be possible to implement a more general version, using the fact that  $d$  must be supported on the primes dividing the discriminant of the minimal polynomial of  $j$ .

---

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.cm import is_cm_j_invariant
sage: is_cm_j_invariant(0)
(True, (-3, 1))
sage: is_cm_j_invariant(8000)
(True, (-8, 1))

sage: K.<a> = QuadraticField(5)
sage: is_cm_j_invariant(282880*a + 632000)
(True, (-20, 1))
sage: K.<a> = NumberField(x^3 - 2)
sage: is_cm_j_invariant(31710790944000*a^2 + 39953093016000*a + 50337742902000)
(True, (-3, 6))

```

`sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_number(h)`

Return largest absolute value of any fundamental discriminant with class number  $h$ , and the number of fundamental discriminants with that class number. This is known for  $h$  up to 100, by work of Mark Watkins.

INPUT:

- $h$  – integer

EXAMPLES:

```
sage: sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_
↪number(0)
(0, 0)
sage: sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_
↪number(1)
(163, 9)
sage: sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_
↪number(2)
(427, 18)
sage: sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_
↪number(10)
(13843, 87)
sage: sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_
↪number(100)
(1856563, 1736)
sage: sage.schemes.elliptic_curves.cm.largest_fundamental_disc_with_class_
↪number(101)
Traceback (most recent call last):
...
NotImplementedError: largest discriminant not known for class number 101
```

The following relate to elliptic curves over local nonarchimedean fields.

### 15.11.12 Local data for elliptic curves over number fields

Let  $E$  be an elliptic curve over a number field  $K$  (including  $\mathbb{Q}$ ). There are several local invariants at a finite place  $v$  that can be computed via Tate's algorithm (see [Sil1994] IV.9.4 or [Tate1975]).

These include the type of reduction (good, additive, multiplicative), a minimal equation of  $E$  over  $K_v$ , the Tamagawa number  $c_v$ , defined to be the index  $[E(K_v) : E^0(K_v)]$  of the points with good reduction among the local points, and the exponent of the conductor  $f_v$ .

The functions in this file will typically be called by using `local_data`.

EXAMPLES:

```
sage: K.<i> = NumberField(x^2+1)
sage: E = EllipticCurve([(2+i)^2, (2+i)^7])
sage: pp = K.fractional_ideal(2+i)
sage: da = E.local_data(pp)
sage: da.has_bad_reduction()
True
sage: da.has_multiplicative_reduction()
False
sage: da.kodaira_symbol()
I0*
sage: da.tamagawa_number()
4
sage: da.minimal_model()
Elliptic Curve defined by y^2 = x^3 + (4*i+3)*x + (-29*i-278) over Number Field in i_
↪with defining polynomial x^2 + 1
```

An example to show how the Neron model can change as one extends the field:

```
sage: E = EllipticCurve([0,-1])
sage: E.local_data(2)
```

```

Local data at Principal ideal (2) of Integer Ring:
Reduction type: bad additive
Local minimal model: Elliptic Curve defined by  $y^2 = x^3 - 1$  over Rational Field
Minimal discriminant valuation: 4
Conductor exponent: 4
Kodaira Symbol: II
Tamagawa Number: 1

sage: EK = E.base_extend(K)
sage: EK.local_data(1+i)
Local data at Fractional ideal (i + 1):
Reduction type: bad additive
Local minimal model: Elliptic Curve defined by  $y^2 = x^3 + (-1)$  over Number Field in  $\sqrt{-1}$ 
↪i with defining polynomial  $x^2 + 1$ 
Minimal discriminant valuation: 8
Conductor exponent: 2
Kodaira Symbol: IV*
Tamagawa Number: 3

```

Or how the minimal equation changes:

```

sage: E = EllipticCurve([0,8])
sage: E.is_minimal()
True
sage: EK = E.base_extend(K)
sage: da = EK.local_data(1+i)
sage: da.minimal_model()
Elliptic Curve defined by  $y^2 = x^3 + (-i)$  over Number Field in  $i$  with defining
↪polynomial  $x^2 + 1$ 

```

#### AUTHORS:

- John Cremona: First version 2008-09-21 (refactoring code from `ell_number_field.py` and `ell_rational_field.py`)
- Chris Wuthrich: more documentation 2010-01

```

class sage.schemes.elliptic_curves.ell_local_data.EllipticCurveLocalData(E,
                                                                           P,
                                                                           proof=None,
                                                                           al-
                                                                           go-
                                                                           rithm='pari',
                                                                           glob-
                                                                           ally=False)

```

Bases: `sage.structure.sage_object.SageObject`

The class for the local reduction data of an elliptic curve.

Currently supported are elliptic curves defined over  $\mathbf{Q}$ , and elliptic curves defined over a number field, at an arbitrary prime or prime ideal.

#### INPUT:

- $E$  – an elliptic curve defined over a number field, or  $\mathbf{Q}$ .
- $P$  – a prime ideal of the field, or a prime integer if the field is  $\mathbf{Q}$ .
- `proof` (bool)– if True, only use provably correct methods (default controlled by global proof module). Note that the proof module is `number_field`, not `elliptic_curves`, since the functions that actually need the

flag are in number fields.

- `algorithm`(string, default: “pari”) – Ignored unless the base field is  $\mathbb{Q}$ . If “pari”, use the PARI C-library `ellglobalred` implementation of Tate’s algorithm over  $\mathbb{Q}$ . If “generic”, use the general number field implementation.

**Note:** This function is not normally called directly by users, who may access the data via methods of the `EllipticCurve` classes.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import _
      ↪ EllipticCurveLocalData
sage: E = EllipticCurve('14a1')
sage: EllipticCurveLocalData(E, 2)
Local data at Principal ideal (2) of Integer Ring:
Reduction type: bad non-split multiplicative
Local minimal model: Elliptic Curve defined by  $y^2 + x*y + y = x^3 + 4*x - 6$  over
      ↪ Rational Field
Minimal discriminant valuation: 6
Conductor exponent: 1
Kodaira Symbol: I6
Tamagawa Number: 2
```

**bad\_reduction\_type()**

Return the type of bad reduction of this reduction data.

OUTPUT:

(int or None):

- +1 for split multiplicative reduction
- -1 for non-split multiplicative reduction
- 0 for additive reduction
- None for good reduction

EXAMPLES:

```
sage: E=EllipticCurve('14a1')
sage: [(p,E.local_data(p).bad_reduction_type()) for p in prime_range(15)]
[(2, -1), (3, None), (5, None), (7, 1), (11, None), (13, None)]

sage: K.<a>=NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.local_data(p).bad_reduction_type()) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), None), (Fractional ideal (2*a + 1), 0)]
```

**conductor\_valuation()**

Return the valuation of the conductor from this local reduction data.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import _
      ↪ EllipticCurveLocalData
sage: E = EllipticCurve([0,0,0,0,64]); E
Elliptic Curve defined by  $y^2 = x^3 + 64$  over Rational Field
```

```
sage: data = EllipticCurveLocalData(E, 2)
sage: data.conductor_valuation()
2
```

**discriminant\_valuation()**

Return the valuation of the minimal discriminant from this local reduction data.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import EllipticCurveLocalData
sage: E = EllipticCurve([0, 0, 0, 0, 64]); E
Elliptic Curve defined by  $y^2 = x^3 + 64$  over Rational Field
sage: data = EllipticCurveLocalData(E, 2)
sage: data.discriminant_valuation()
4
```

**has\_additive\_reduction()**

Return True if there is additive reduction.

EXAMPLES:

```
sage: E = EllipticCurve('27a1')
sage: [(p, E.local_data(p).has_additive_reduction()) for p in prime_range(15)]
[(2, False), (3, True), (5, False), (7, False), (11, False), (13, False)]
```

```
sage: K.<a> = NumberField(x^3-2)
sage: P17a, P17b = [P for P, e in K.factor(17)]
sage: E = EllipticCurve([0, 0, 0, 0, 2*a+1])
sage: [(p, E.local_data(p).has_additive_reduction()) for p in [P17a, P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False),
 (Fractional ideal (2*a + 1), True)]
```

**has\_bad\_reduction()**

Return True if there is bad reduction.

EXAMPLES:

```
sage: E = EllipticCurve('14a1')
sage: [(p, E.local_data(p).has_bad_reduction()) for p in prime_range(15)]
[(2, True), (3, False), (5, False), (7, True), (11, False), (13, False)]
```

```
sage: K.<a> = NumberField(x^3-2)
sage: P17a, P17b = [P for P, e in K.factor(17)]
sage: E = EllipticCurve([0, 0, 0, 0, 2*a+1])
sage: [(p, E.local_data(p).has_bad_reduction()) for p in [P17a, P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False),
 (Fractional ideal (2*a + 1), True)]
```

**has\_good\_reduction()**

Return True if there is good reduction.

EXAMPLES:

```
sage: E = EllipticCurve('14a1')
sage: [(p, E.local_data(p).has_good_reduction()) for p in prime_range(15)]
[(2, False), (3, True), (5, True), (7, False), (11, True), (13, True)]
```

```

sage: K.<a> = NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.local_data(p).has_good_reduction()) for p in [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), True),
 (Fractional ideal (2*a + 1), False)]

```

**has\_multiplicative\_reduction()**

Return True if there is multiplicative reduction.

---

**Note:** See also `has_split_multiplicative_reduction()` and `has_nonsplit_multiplicative_reduction()`.

---

**EXAMPLES:**

```

sage: E = EllipticCurve('14a1')
sage: [(p,E.local_data(p).has_multiplicative_reduction()) for p in prime_
↪range(15)]
[(2, True), (3, False), (5, False), (7, True), (11, False), (13, False)]

```

```

sage: K.<a> = NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.local_data(p).has_multiplicative_reduction()) for p in [P17a,
↪P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False), (Fractional ideal (2*a + 1),
↪False)]

```

**has\_nonsplit\_multiplicative\_reduction()**

Return True if there is non-split multiplicative reduction.

**EXAMPLES:**

```

sage: E = EllipticCurve('14a1')
sage: [(p,E.local_data(p).has_nonsplit_multiplicative_reduction()) for p in
↪prime_range(15)]
[(2, True), (3, False), (5, False), (7, False), (11, False), (13, False)]

```

```

sage: K.<a> = NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.local_data(p).has_nonsplit_multiplicative_reduction()) for p in
↪[P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False), (Fractional ideal (2*a + 1),
↪False)]

```

**has\_split\_multiplicative\_reduction()**

Return True if there is split multiplicative reduction.

**EXAMPLES:**

```

sage: E = EllipticCurve('14a1')
sage: [(p,E.local_data(p).has_split_multiplicative_reduction()) for p in
↪prime_range(15)]
[(2, False), (3, False), (5, False), (7, True), (11, False), (13, False)]

```



```

sage: K.<a> = NumberField(x^3-2)
sage: P17a, P17b = [P for P,e in K.factor(17)]
sage: E = EllipticCurve([0,0,0,0,2*a+1])
sage: [(p,E.local_data(p).has_split_multiplicative_reduction()) for p in
↪ [P17a,P17b]]
[(Fractional ideal (4*a^2 - 2*a + 1), False),
(Fractional ideal (2*a + 1), False)]

```

**kodaira\_symbol()**

Return the Kodaira symbol from this local reduction data.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_local_data import
↪ EllipticCurveLocalData
sage: E = EllipticCurve([0,0,0,0,64]); E
Elliptic Curve defined by y^2 = x^3 + 64 over Rational Field
sage: data = EllipticCurveLocalData(E,2)
sage: data.kodaira_symbol()
IV

```

**minimal\_model(reduce=True)**

Return the (local) minimal model from this local reduction data.

INPUT:

- `reduce` – (default: `True`) if set to `True` and if the initial elliptic curve had globally integral coefficients, then the elliptic curve returned by Tate’s algorithm will be “reduced” as specified in `_reduce_model()` for curves over number fields.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_local_data import
↪ EllipticCurveLocalData
sage: E = EllipticCurve([0,0,0,0,64]); E
Elliptic Curve defined by y^2 = x^3 + 64 over Rational Field
sage: data = EllipticCurveLocalData(E,2)
sage: data.minimal_model()
Elliptic Curve defined by y^2 = x^3 + 1 over Rational Field
sage: data.minimal_model() == E.local_minimal_model(2)
True

```

To demonstrate the behaviour of the parameter `reduce`:

```

sage: K.<a> = NumberField(x^3+x+1)
sage: E = EllipticCurve(K, [0, 0, a, 0, 1])
sage: E.local_data(K.ideal(a-1)).minimal_model()
Elliptic Curve defined by y^2 + a*y = x^3 + 1 over Number Field in a with
↪ defining polynomial x^3 + x + 1
sage: E.local_data(K.ideal(a-1)).minimal_model(reduce=False)
Elliptic Curve defined by y^2 + (a+2)*y = x^3 + 3*x^2 + 3*x + (-a+1) over
↪ Number Field in a with defining polynomial x^3 + x + 1

sage: E = EllipticCurve([2, 1, 0, -2, -1])
sage: E.local_data(ZZ.ideal(2), algorithm="generic").minimal_
↪ model(reduce=False)
Elliptic Curve defined by y^2 + 2*x*y + 2*y = x^3 + x^2 - 4*x - 2 over
↪ Rational Field
sage: E.local_data(ZZ.ideal(2), algorithm="pari").minimal_model(reduce=False)

```

```
Traceback (most recent call last):
...
ValueError: the argument reduce must not be False if algorithm=pari is used
sage: E.local_data(ZZ.ideal(2), algorithm="generic").minimal_model()
Elliptic Curve defined by  $y^2 = x^3 - x^2 - 3x + 2$  over Rational Field
sage: E.local_data(ZZ.ideal(2), algorithm="pari").minimal_model()
Elliptic Curve defined by  $y^2 = x^3 - x^2 - 3x + 2$  over Rational Field
```

trac ticket #14476:

```
sage: t = QQ['t'].0
sage: K.<g> = NumberField(t^4 - t^3 - 3*t^2 - t + 1)
sage: E = EllipticCurve([-2*g^3 + 10/3*g^2 + 3*g - 2/3, -11/9*g^3 + 34/9*g^2 -
↪ 7/3*g + 4/9, -11/9*g^3 + 34/9*g^2 - 7/3*g + 4/9, 0, 0])
sage: vv = K.fractional_ideal(g^2 - g - 2)
sage: E.local_data(vv).minimal_model()
Elliptic Curve defined by  $y^2 + (-2g^3 + 10/3g^2 + 3g - 2/3)xy + (-11/9g^3 + 34/9g^2 - 7/3g + 4/9)y = x^3 + (-11/9g^3 + 34/9g^2 - 7/3g + 4/9)x^2$  over Number_
↪Field in g with defining polynomial  $t^4 - t^3 - 3t^2 - t + 1$ 
```

### prime()

Return the prime ideal associated with this local reduction data.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import_
↪ EllipticCurveLocalData
sage: E = EllipticCurve([0,0,0,0,64]); E
Elliptic Curve defined by  $y^2 = x^3 + 64$  over Rational Field
sage: data = EllipticCurveLocalData(E, 2)
sage: data.prime()
Principal ideal (2) of Integer Ring
```

### tamagawa\_exponent()

Return the Tamagawa index from this local reduction data.

This is the exponent of  $E(K_v)/E^0(K_v)$ ; in most cases it is the same as the Tamagawa index.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import_
↪ EllipticCurveLocalData
sage: E = EllipticCurve('816a1')
sage: data = EllipticCurveLocalData(E, 2)
sage: data.kodaira_symbol()
I2*
sage: data.tamagawa_number()
4
sage: data.tamagawa_exponent()
2

sage: E = EllipticCurve('200c4')
sage: data = EllipticCurveLocalData(E, 5)
sage: data.kodaira_symbol()
I4*
sage: data.tamagawa_number()
4
sage: data.tamagawa_exponent()
2
```

**tamagawa\_number()**

Return the Tamagawa number from this local reduction data.

This is the index  $[E(K_v) : E^0(K_v)]$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import EllipticCurveLocalData
sage: E = EllipticCurve([0,0,0,0,64]); E
Elliptic Curve defined by y^2 = x^3 + 64 over Rational Field
sage: data = EllipticCurveLocalData(E,2)
sage: data.tamagawa_number()
3
```

`sage.schemes.elliptic_curves.ell_local_data.check_prime(K, P)`

Function to check that  $P$  determines a prime of  $K$ , and return that ideal.

INPUT:

- $K$  – a number field (including  $\mathbb{Q}$ ).
- $P$  – an element of  $K$  or a (fractional) ideal of  $K$ .

OUTPUT:

- If  $K$  is  $\mathbb{Q}$ : the prime integer equal to or which generates  $P$ .
- If  $K$  is not  $\mathbb{Q}$ : the prime ideal equal to or generated by  $P$ .

---

**Note:** If  $P$  is not a prime and does not generate a prime, a `TypeError` is raised.

---

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_local_data import check_prime
sage: check_prime(QQ,3)
3
sage: check_prime(QQ,QQ(3))
3
sage: check_prime(QQ,ZZ.ideal(31))
31
sage: K.<a>=NumberField(x^2-5)
sage: check_prime(K,a)
Fractional ideal (a)
sage: check_prime(K,a+1)
Fractional ideal (a + 1)
sage: [check_prime(K,P) for P in K.primes_above(31)]
[Fractional ideal (5/2*a + 1/2), Fractional ideal (5/2*a - 1/2)]
sage: L.<b>=NumberField(x^2+3)
sage: check_prime(K, L.ideal(5))
Traceback (most recent call last):
..
TypeError: The ideal Fractional ideal (5) is not a prime ideal of Number Field in
  a with defining polynomial x^2 - 5
sage: check_prime(K, L.ideal(b))
Traceback (most recent call last):
TypeError: No compatible natural embeddings found for Number Field in a with
  defining polynomial x^2 - 5 and Number Field in b with defining polynomial x^2
  + 3
```

### 15.11.13 Kodaira symbols

Kodaira symbols encode the type of reduction of an elliptic curve at a (finite) place.

The standard notation for Kodaira Symbols is as a string which is one of  $I_m$ ,  $II$ ,  $III$ ,  $IV$ ,  $I_m^*$ ,  $II^*$ ,  $III^*$ ,  $IV^*$ , where  $m$  denotes a non-negative integer. These have been encoded by single integers by different people. For convenience we give here the conversion table between strings, the eclib coding and the PARI encoding.

Kodaira Symbol	Eclib coding	PARI Coding
$I_0$	0	1
$I_0^*$	1	-1
$I_m (m > 0)$	$10m$	$m + 4$
$I_m^* (m > 0)$	$10m + 1$	$-(m + 4)$
$II$	2	2
$III$	3	3
$IV$	4	4
$II^*$	7	-2
$III^*$	6	-3
$IV^*$	5	-4

AUTHORS:

- David Roe <roed@math.harvard.edu>
- John Cremona

`sage.schemes.elliptic_curves.kodaira_symbol.KodairaSymbol` (*symbol*)

Returns the specified Kodaira symbol.

INPUT:

- *symbol* (string or integer) – Either a string of the form “ $I_0$ ”, “ $I_1$ ”, ..., “ $I_n$ ”, “ $II$ ”, “ $III$ ”, “ $IV$ ”, “ $I_0^*$ ”, “ $I_1^*$ ”, ..., “ $I_n^*$ ”, “ $II^*$ ”, “ $III^*$ ”, or “ $IV^*$ ”, or an integer encoding a Kodaira symbol using PARI’s conventions.

OUTPUT:

(KodairaSymbol) The corresponding Kodaira symbol.

EXAMPLES:

```
sage: KS = KodairaSymbol
sage: [KS(n) for n in range(1,10)]
[I0, II, III, IV, I1, I2, I3, I4, I5]
sage: [KS(-n) for n in range(1,10)]
[I0*, II*, III*, IV*, I1*, I2*, I3*, I4*, I5*]
sage: all([KS(str(KS(n))) == KS(n) for n in range(-10,10) if n != 0])
True
```

**class** `sage.schemes.elliptic_curves.kodaira_symbol.KodairaSymbol_class` (*symbol*)

Bases: `sage.structure.sage_object.SageObject`

Class to hold a Kodaira symbol of an elliptic curve over a  $p$ -adic local field.

Users should use the `KodairaSymbol()` function to construct Kodaira Symbols rather than use the class constructor directly.

### 15.11.14 Tate's parametrisation of $p$ -adic curves with multiplicative reduction

Let  $E$  be an elliptic curve defined over the  $p$ -adic numbers  $\mathbb{Q}_p$ . Suppose that  $E$  has multiplicative reduction, i.e. that the  $j$ -invariant of  $E$  has negative valuation, say  $n$ . Then there exists a parameter  $q$  in  $\mathbb{Z}_p$  of valuation  $n$  such that the points of  $E$  defined over the algebraic closure  $\bar{\mathbb{Q}}_p$  are in bijection with  $\bar{\mathbb{Q}}_p^\times / q^{\mathbb{Z}}$ . More precisely there exists the series  $s_4(q)$  and  $s_6(q)$  such that the  $y^2 + xy = x^3 + s_4(q)x + s_6(q)$  curve is isomorphic to  $E$  over  $\bar{\mathbb{Q}}_p$  (or over  $\mathbb{Q}_p$  if the reduction is *split* multiplicative). There is  $p$ -adic analytic map from  $\bar{\mathbb{Q}}_p^\times$  to this curve with kernel  $q^{\mathbb{Z}}$ . Points of good reduction correspond to points of valuation 0 in  $\bar{\mathbb{Q}}_p^\times$ .

See chapter V of [Sil1994] for more details.

AUTHORS:

- Chris Wuthrich (23/05/2007): first version
- William Stein (2007-05-29): added some examples; editing.
- Chris Wuthrich (04/09): reformatted docstrings.

**class** sage.schemes.elliptic\_curves.ell\_tate\_curve.**TateCurve** ( $E, p$ )

Bases: sage.structure.sage\_object.SageObject

Tate's  $p$ -adic uniformisation of an elliptic curve with multiplicative reduction.

---

**Note:** Some of the methods of this Tate curve only work when the reduction is split multiplicative over  $\mathbb{Q}_p$ .

---

EXAMPLES:

```
sage: e = EllipticCurve('130a1')
sage: eq = e.tate_curve(5); eq
5-adic Tate curve associated to the Elliptic Curve defined by y^2 + x*y + y = x^3_
↪ - 33*x + 68 over Rational Field
sage: eq == loads(dumps(eq))
True
```

REFERENCES: [Sil1994]

**E2** ( $prec=20$ )

Return the value of the  $p$ -adic Eisenstein series of weight 2 evaluated on the elliptic curve having split multiplicative reduction.

INPUT:

- $prec$  - the  $p$ -adic precision, default is 20.

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.E2(prec=10)
4 + 2*5^2 + 2*5^3 + 5^4 + 2*5^5 + 5^7 + 5^8 + 2*5^9 + O(5^10)

sage: T = EllipticCurve('14').tate_curve(7)
sage: T.E2(30)
2 + 4*7 + 7^2 + 3*7^3 + 6*7^4 + 5*7^5 + 2*7^6 + 7^7 + 5*7^8 + 6*7^9 + 5*7^10_
↪ + 2*7^11 + 6*7^12 + 4*7^13 + 3*7^15 + 5*7^16 + 4*7^17 + 4*7^18 + 2*7^20 + 7^
↪ 21 + 5*7^22 + 4*7^23 + 4*7^24 + 3*7^25 + 6*7^26 + 3*7^27 + 6*7^28 + O(7^30)
```

**L\_invariant** ( $prec=20$ )

Returns the *mysterious*  $\mathcal{L}$ -invariant associated to an elliptic curve with split multiplicative reduction.

One instance where this constant appears is in the exceptional case of the  $p$ -adic Birch and Swinnerton-Dyer conjecture as formulated in [MTT]. See [Col] for a detailed discussion.

INPUT:

- `prec` - the  $p$ -adic precision, default is 20.

REFERENCES:

[MTT]

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.L_invariant(prec=10)
5^3 + 4*5^4 + 2*5^5 + 2*5^6 + 2*5^7 + 3*5^8 + 5^9 + O(5^10)
```

**curve** (*prec*=20)

Return the  $p$ -adic elliptic curve of the form  $y^2 + xy = x^3 + s_4x + s_6$ .

This curve with split multiplicative reduction is isomorphic to the given curve over the algebraic closure of  $\mathbb{Q}_p$ .

INPUT:

- `prec` - the  $p$ -adic precision, default is 20.

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.curve(prec=5)
Elliptic Curve defined by y^2 + (1+O(5^5))*x*y = x^3 +
(2*5^4+5^5+2*5^6+5^7+3*5^8+O(5^9))*x +
(2*5^3+5^4+2*5^5+5^7+O(5^8)) over 5-adic
Field with capped relative precision 5
```

**is\_split** ()

Returns True if the given elliptic curve has split multiplicative reduction.

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.is_split()
True

sage: eq = EllipticCurve('37a1').tate_curve(37)
sage: eq.is_split()
False
```

**lift** (*P*, *prec*=20)

Given a point  $P$  in the formal group of the elliptic curve  $E$  with split multiplicative reduction, this produces an element  $u$  in  $\mathbb{Q}_p^\times$  mapped to the point  $P$  by the Tate parametrisation. The algorithm return the unique such element in  $1 + p\mathbb{Z}_p$ .

INPUT:

- $P$  - a point on the elliptic curve.
- `prec` - the  $p$ -adic precision, default is 20.

EXAMPLES:

```

sage: e = EllipticCurve('130a1')
sage: eq = e.tate_curve(5)
sage: P = e([-6,10])
sage: l = eq.lift(12*P, prec=10); l
1 + 4*5 + 5^3 + 5^4 + 4*5^5 + 5^6 + 5^7 + 4*5^8 + 5^9 + O(5^10)

```

Now we map the lift  $l$  back and check that it is indeed right.:

```

sage: eq.parametrisation_onto_original_curve(l)
(4*5^-2 + 2*5^-1 + 4*5 + 3*5^3 + 5^4 + 2*5^5 + 4*5^6 + O(5^7) : 2*5^-3 + 5^-1_
↪ + 4 + 4*5 + 5^2 + 3*5^3 + 4*5^4 + O(5^6) : 1 + O(5^20))
sage: e5 = e.change_ring(Qp(5,9))
sage: e5(12*P)
(4*5^-2 + 2*5^-1 + 4*5 + 3*5^3 + 5^4 + 2*5^5 + 4*5^6 + O(5^7) : 2*5^-3 + 5^-1_
↪ + 4 + 4*5 + 5^2 + 3*5^3 + 4*5^4 + O(5^6) : 1 + O(5^9))

```

### **original\_curve()**

Return the elliptic curve the Tate curve was constructed from.

EXAMPLES:

```

sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.original_curve()
Elliptic Curve defined by  $y^2 + x*y + y = x^3 - 33*x + 68$ 
over Rational Field

```

### **padic\_height(prec=20)**

Return the canonical  $p$ -adic height function on the original curve.

INPUT:

- $prec$  - the  $p$ -adic precision, default is 20.

OUTPUT:

- A function that can be evaluated on rational points of  $E$ .

EXAMPLES:

```

sage: e = EllipticCurve('130a1')
sage: eq = e.tate_curve(5)
sage: h = eq.padic_height(prec=10)
sage: P=e.gens()[0]
sage: h(P)
2*5^-1 + 1 + 2*5 + 2*5^2 + 3*5^3 + 3*5^6 + 5^7 + O(5^8)

```

Check that it is a quadratic function:

```

sage: h(3*P)-3^2*h(P)
O(5^8)

```

### **padic\_regulator(prec=20)**

Compute the canonical  $p$ -adic regulator on the extended Mordell-Weil group as in [MTT] (with the correction of [Wer] and sign convention in [SW].)

The  $p$ -adic Birch and Swinnerton-Dyer conjecture predicts that this value appears in the formula for the leading term of the  $p$ -adic L-function.

INPUT:

- $prec$  - the  $p$ -adic precision, default is 20.

REFERENCES:

[\[MTT\]](#)

[\[SW\]](#)

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.padic_regulator()
2*5^-1 + 1 + 2*5 + 2*5^2 + 3*5^3 + 3*5^6 + 5^7 + 3*5^9 + 3*5^10 + 3*5^12 +
↪ 4*5^13 + 3*5^15 + 2*5^16 + 3*5^18 + 4*5^19 + O(5^20)
```

**parameter** (*prec=20*)

Return the Tate parameter  $q$  such that the curve is isomorphic over the algebraic closure of  $\mathbb{Q}_p$  to the curve  $\mathbb{Q}_p^\times/q^{\mathbb{Z}}$ .

INPUT:

- *prec* - the  $p$ -adic precision, default is 20.

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.parameter(prec=5)
3*5^3 + 3*5^4 + 2*5^5 + 2*5^6 + 3*5^7 + O(5^8)
```

**parametrisation\_onto\_original\_curve** (*u, prec=20*)

Given an element  $u$  in  $\mathbb{Q}_p^\times$ , this computes its image on the original curve under the  $p$ -adic uniformisation of  $E$ .

INPUT:

- $u$  - a non-zero  $p$ -adic number.
- *prec* - the  $p$ -adic precision, default is 20.

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.parametrisation_onto_original_curve(1+5+5^2+O(5^10))
(4*5^-2 + 4*5^-1 + 4 + 2*5^3 + 3*5^4 + 2*5^6 + O(5^7)) :
3*5^-3 + 5^-2 + 4*5^-1 + 1 + 4*5 + 5^2 + 3*5^5 + O(5^6) :
1 + O(5^20))
```

Here is how one gets a 4-torsion point on  $E$  over  $\mathbb{Q}_5$ :

```
sage: R = Qp(5, 10)
sage: i = R(-1).sqrt()
sage: T = eq.parametrisation_onto_original_curve(i); T
(2 + 3*5 + 4*5^2 + 2*5^3 + 5^4 + 4*5^5 + 2*5^7 + 5^8 + 5^9 + O(5^10)) :
3*5 + 5^2 + 5^4 + 3*5^5 + 3*5^7 + 2*5^8 + 4*5^9 + O(5^10) : 1 + O(5^20))
sage: 4*T
(0 : 1 + O(5^20) : 0)
```

**parametrisation\_onto\_tate\_curve** (*u, prec=20*)

Given an element  $u$  in  $\mathbb{Q}_p^\times$ , this computes its image on the Tate curve under the  $p$ -adic uniformisation of  $E$ .

INPUT:

- $u$  - a non-zero  $p$ -adic number.



- `prec` - the  $p$ -adic precision, default is 20.

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.parametrisation_onto_tate_curve(1+5+5^2+O(5^10))
(5^-2 + 4*5^-1 + 1 + 2*5 + 3*5^2 + 2*5^5 + 3*5^6 + O(5^7)) :
4*5^-3 + 2*5^-1 + 4 + 2*5 + 3*5^4 + 2*5^5 + O(5^6) : 1 + O(5^20))
```

**prime()**

Return the residual characteristic  $p$ .

EXAMPLES:

```
sage: eq = EllipticCurve('130a1').tate_curve(5)
sage: eq.original_curve()
Elliptic Curve defined by y^2 + x*y + y = x^3 - 33*x + 68
over Rational Field
sage: eq.prime()
5
```

### 15.11.15 Miscellaneous $p$ -adic functions

$p$ -adic functions from `ell_rational_field.py`, moved here to reduce crowding in that file.

```
sage.schemes.elliptic_curves.padic.matrix_of_frobenius(self, p, prec=20,
                                                         check=False,
                                                         check_hypotheses=True,
                                                         algorithm='auto')
```

Returns the matrix of Frobenius on the Monsky Washnitzer cohomology of the elliptic curve.

INPUT:

- $p$  - prime ( $\geq 3$ ) for which  $E$  is good and ordinary
- `prec` - (relative)  $p$ -adic precision for result (default 20)
- `check` - boolean (default: `False`), whether to perform a consistency check. This will slow down the computation by a constant factor 2. (The consistency check is to verify that its trace is correct to the specified precision. Otherwise, the trace is used to compute one column from the other one (possibly after a change of basis).)
- `check_hypotheses` - boolean, whether to check that this is a curve for which the  $p$ -adic sigma function makes sense
- `algorithm` - one of “standard”, “sqrtp”, or “auto”. This selects which version of Kedlaya’s algorithm is used. The “standard” one is the one described in Kedlaya’s paper. The “sqrtp” one has better performance for large  $p$ , but only works when  $p > 6N$  ( $N = \text{prec}$ ). The “auto” option selects “sqrtp” whenever possible.

Note that if the “sqrtp” algorithm is used, a consistency check will automatically be applied, regardless of the setting of the “check” flag.

OUTPUT: a matrix of  $p$ -adic number to precision `prec`

See also the documentation of `padic_E2`.

EXAMPLES:

```

sage: E = EllipticCurve('37a1')
sage: E.matrix_of_frobenius(7)
[
      2*7 + 4*7^2 + 5*7^4 + 6*7^5 + 6*7^6 + 7^8 + 4*7^9 + 3*7^10 + 2*7^11
↪ + 5*7^12 + 4*7^14 + 7^16 + 2*7^17 + 3*7^18 + 4*7^19 + 3*7^20 + O(7^21)
↪
      2 + 3*7 + 6*7^2 + 7^3 + 3*7^4 + 5*7^5 + 3*7^7 + 7^8 +
↪ 3*7^9 + 6*7^13 + 7^14 + 7^16 + 5*7^17 + 4*7^18 + 7^19 + O(7^20)]
[
      2*7 + 3*7^2 + 7^3 + 3*7^4 + 6*7^5 + 2*7^6 + 3*7^7 + 5*7^8 + 3*7^9 + 2*7^11
↪ 6*7^12 + 5*7^13 + 4*7^16 + 4*7^17 + 6*7^18 + 6*7^19 + 4*7^20 + O(7^21) 6 + 4*7
↪ + 2*7^2 + 6*7^3 + 7^4 + 6*7^7 + 5*7^8 + 2*7^9 + 3*7^10 + 4*7^11 + 7^12 + 6*7^13
↪ + 2*7^14 + 6*7^15 + 5*7^16 + 4*7^17 + 3*7^18 + 2*7^19 + O(7^20)]
sage: M = E.matrix_of_frobenius(11,prec=3); M
[
      9*11 + 9*11^3 + O(11^4)          10 + 11 + O(11^3)]
[
      2*11 + 11^2 + O(11^4) 6 + 11 + 10*11^2 + O(11^3)]
sage: M.det()
11 + O(11^4)
sage: M.trace()
6 + 10*11 + 10*11^2 + O(11^3)
sage: E.ap(11)
-5
sage: E = EllipticCurve('83a1')
sage: E.matrix_of_frobenius(3,6)
[
      2*3 + 3^5 + O(3^6)          2*3 + 2*3^2 + 2*3^3 + O(3^
↪ 6)]
[
      2*3 + 3^2 + 2*3^5 + O(3^6) 2 + 2*3^2 + 2*3^3 + 2*3^4 + 3^5 + O(3^
↪ 6)]

```

`sage.schemes.elliptic_curves.padics.padic_E2`(*self*, *p*, *prec*=20, *check*=False, *check\_hypotheses*=True, *algorithm*='auto')

Returns the value of the  $p$ -adic modular form  $E2$  for  $(E, \omega)$  where  $\omega$  is the usual invariant differential  $dx/(2y + a_1x + a_3)$ .

INPUT:

- *p* - prime (= 5) for which  $E$  is good and ordinary
- *prec* - (relative)  $p$ -adic precision (= 1) for result
- *check* - boolean, whether to perform a consistency check. This will slow down the computation by a constant factor 2. (The consistency check is to compute the whole matrix of frobenius on Monsky-Washnitzer cohomology, and verify that its trace is correct to the specified precision. Otherwise, the trace is used to compute one column from the other one (possibly after a change of basis).)
- *check\_hypotheses* - boolean, whether to check that this is a curve for which the  $p$ -adic sigma function makes sense
- *algorithm* - one of “standard”, “sqrtp”, or “auto”. This selects which version of Kedlaya’s algorithm is used. The “standard” one is the one described in Kedlaya’s paper. The “sqrtp” one has better performance for large  $p$ , but only works when  $p > 6N$  ( $N = \text{prec}$ ). The “auto” option selects “sqrtp” whenever possible.

Note that if the “sqrtp” algorithm is used, a consistency check will automatically be applied, regardless of the setting of the “check” flag.

OUTPUT:  $p$ -adic number to precision *prec*

---

**Note:** If the discriminant of the curve has nonzero valuation at  $p$ , then the result will not be returned mod  $p^{\text{prec}}$ , but it still *will* have *prec* digits of precision.

---

**Todo:** Once we have a better implementation of the “standard” algorithm, the algorithm selection strategy for “auto” needs to be revisited.

**AUTHORS:**

- David Harvey (2006-09-01): partly based on code written by Robert Bradshaw at the MSRI 2006 modular forms workshop

**ACKNOWLEDGMENT:** - discussion with Eyal Goren that led to the trace trick.

**EXAMPLES:** Here is the example discussed in the paper “Computation of p-adic Heights and Log Convergence” (Mazur, Stein, Tate):

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^12 +
↳ 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + O(5^20)
```

Let’s try to higher precision (this is the same answer the MAGMA implementation gives):

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 100)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^12 +
↳ 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + 4*5^20 + 5^21 + 4*5^22 +
↳ 2*5^23 + 3*5^24 + 3*5^26 + 2*5^27 + 3*5^28 + 2*5^30 + 5^31 + 4*5^33 + 3*5^34 +
↳ 4*5^35 + 5^36 + 4*5^37 + 4*5^38 + 3*5^39 + 4*5^41 + 2*5^42 + 3*5^43 + 2*5^44 +
↳ 2*5^48 + 3*5^49 + 4*5^50 + 2*5^51 + 5^52 + 4*5^53 + 4*5^54 + 3*5^55 + 2*5^56 +
↳ 3*5^57 + 4*5^58 + 4*5^59 + 5^60 + 3*5^61 + 5^62 + 4*5^63 + 5^65 + 3*5^66 + 2*5^
↳ 67 + 5^69 + 2*5^70 + 3*5^71 + 3*5^72 + 5^74 + 5^75 + 5^76 + 3*5^77 + 4*5^78 +
↳ 4*5^79 + 2*5^80 + 3*5^81 + 5^82 + 5^83 + 4*5^84 + 3*5^85 + 2*5^86 + 3*5^87 + 5^
↳ 88 + 2*5^89 + 4*5^90 + 4*5^92 + 3*5^93 + 4*5^94 + 3*5^95 + 2*5^96 + 4*5^97 +
↳ 4*5^98 + 2*5^99 + O(5^100)
```

Check it works at low precision too:

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 1)
2 + O(5)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 2)
2 + 4*5 + O(5^2)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 3)
2 + 4*5 + O(5^3)
```

**TODO:** With the old(-er), i.e., = sage-2.4 p-adics we got  $5 + O(5^2)$  as output, i.e., relative precision 1, but with the newer p-adics we get relative precision 0 and absolute precision 1.

```
sage: EllipticCurve([1, 1, 1, 1, 1]).padic_E2(5, 1)
O(5)
```

Check it works for different models of the same curve (37a), even when the discriminant changes by a power of p (note that E2 depends on the differential too, which is why it gets scaled in some of the examples below):

```
sage: X1 = EllipticCurve([-1, 1/4])
sage: X1.j_invariant(), X1.discriminant()
(110592/37, 37)
sage: X1.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X2 = EllipticCurve([0, 0, 1, -1, 0])
sage: X2.j_invariant(), X2.discriminant()
```

```
(110592/37, 37)
sage: X2.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X3 = EllipticCurve([-1*(2**4), 1/4*(2**6)])
sage: X3.j_invariant(), X3.discriminant() / 2**12
(110592/37, 37)
sage: 2**(-2) * X3.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X4 = EllipticCurve([-1*(7**4), 1/4*(7**6)])
sage: X4.j_invariant(), X4.discriminant() / 7**12
(110592/37, 37)
sage: 7**(-2) * X4.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X5 = EllipticCurve([-1*(5**4), 1/4*(5**6)])
sage: X5.j_invariant(), X5.discriminant() / 5**12
(110592/37, 37)
sage: 5**(-2) * X5.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

```
sage: X6 = EllipticCurve([-1/(5**4), 1/4/(5**6)])
sage: X6.j_invariant(), X6.discriminant() * 5**12
(110592/37, 37)
sage: 5**2 * X6.padic_E2(5, 10)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + O(5^10)
```

Test check=True vs check=False:

```
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 1, check=False)
2 + O(5)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 1, check=True)
2 + O(5)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 30, check=False)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^12 +
↪ 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + 4*5^20 + 5^21 + 4*5^22 +
↪ 2*5^23 + 3*5^24 + 3*5^26 + 2*5^27 + 3*5^28 + O(5^30)
sage: EllipticCurve([-1, 1/4]).padic_E2(5, 30, check=True)
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + 5^8 + 3*5^9 + 4*5^10 + 2*5^11 + 2*5^12 +
↪ 2*5^14 + 3*5^15 + 3*5^16 + 3*5^17 + 4*5^18 + 2*5^19 + 4*5^20 + 5^21 + 4*5^22 +
↪ 2*5^23 + 3*5^24 + 3*5^26 + 2*5^27 + 3*5^28 + O(5^30)
```

Here's one using the  $p^{1/2}$  algorithm:

```
sage: EllipticCurve([-1, 1/4]).padic_E2(3001, 3, algorithm="sqrtp")
1907 + 2819*3001 + 1124*3001^2 + O(3001^3)
```

sage.schemes.elliptic\_curves.padics.**padic\_height**(self, p, prec=20, sigma=None, check\_hypotheses=True)

Compute the cyclotomic p-adic height.

The equation of the curve must be minimal at  $p$ .

INPUT:

- $p$  - prime = 5 for which the curve has semi-stable reduction

- `prec` - integer = 1, desired precision of result
- `sigma` - precomputed value of sigma. If not supplied, this function will call `padic_sigma` to compute it.
- `check_hypotheses` - boolean, whether to check that this is a curve for which the p-adic height makes sense

OUTPUT: A function that accepts two parameters:

- a Q-rational point on the curve whose height should be computed
- optional boolean flag 'check': if False, it skips some input checking, and returns the p-adic height of that point to the desired precision.
- The normalization (sign and a factor 1/2 with respect to some other normalizations that appear in the literature) is chosen in such a way as to make the p-adic Birch Swinnerton-Dyer conjecture hold as stated in [Mazur-Tate-Teitelbaum].

AUTHORS:

- Jennifer Balakrishnan: original code developed at the 2006 MSRI graduate workshop on modular forms
- David Harvey (2006-09-13): integrated into Sage, optimised to speed up repeated evaluations of the returned height function, addressed some thorny precision questions
- David Harvey (2006-09-30): rewrote to use division polynomials for computing denominator of  $nP$ .
- David Harvey (2007-02): cleaned up according to algorithms in "Efficient Computation of p-adic Heights"
- Chris Wuthrich (2007-05): added supersingular and multiplicative heights

EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: P = E.gens()[0]
sage: h = E.padic_height(5, 10)
sage: h(P)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

An anomalous case:

```
sage: h = E.padic_height(53, 10)
sage: h(P)
26*53^-1 + 30 + 20*53 + 47*53^2 + 10*53^3 + 32*53^4 + 9*53^5 + 22*53^6 + 35*53^7
↪ + 30*53^8 + 17*53^9 + O(53^10)
```

Boundary case:

```
sage: E.padic_height(5, 3)(P)
5 + 5^2 + O(5^3)
```

A case that works the division polynomial code a little harder:

```
sage: E.padic_height(5, 10)(5*P)
5^3 + 5^4 + 5^5 + 3*5^8 + 4*5^9 + O(5^10)
```

Check that answers agree over a range of precisions:

```
sage: max_prec = 30      # make sure we get past p^2      # long time
sage: full = E.padic_height(5, max_prec)(P)                # long time
sage: for prec in range(1, max_prec):                       # long time
....:     assert E.padic_height(5, prec)(P) == full        # long time
```

A supersingular prime for a curve:

```
sage: E = EllipticCurve('37a')
sage: E.is_supersingular(3)
True
sage: h = E.padic_height(3, 5)
sage: h(E.gens()[0])
(3 + 3^3 + O(3^6), 2*3^2 + 3^3 + 3^4 + 3^5 + 2*3^6 + O(3^7))
sage: E.padic_regulator(5)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + 5^10 + 3*5^11 + 3*5^12 + 5^13 + 4*5^14 + 5^
↪ 15 + 2*5^16 + 5^17 + 2*5^18 + 4*5^19 + O(5^20)
sage: E.padic_regulator(3, 5)
(3 + 2*3^2 + 3^3 + O(3^4), 3^2 + 2*3^3 + 3^4 + O(3^5))
```

A torsion point in both the good and supersingular cases:

```
sage: E = EllipticCurve('11a')
sage: P = E.torsion_subgroup().gen(0).element(); P
(5 : 5 : 1)
sage: h = E.padic_height(19, 5)
sage: h(P)
0
sage: h = E.padic_height(5, 5)
sage: h(P)
0
```

The result is not dependent on the model for the curve:

```
sage: E = EllipticCurve([0,0,0,0,2^12*17])
sage: Em = E.minimal_model()
sage: P = E.gens()[0]
sage: Pm = Em.gens()[0]
sage: h = E.padic_height(7)
sage: hm = Em.padic_height(7)
sage: h(P) == hm(Pm)
True
```

```
sage.schemes.elliptic_curves.padics.padic_height_pairing_matrix(self, p,
                                                                    prec=20,
                                                                    height=None,
                                                                    check_hypotheses=True)
```

Computes the cyclotomic  $p$ -adic height pairing matrix of this curve with respect to the basis `self.gens()` for the Mordell-Weil group for a given odd prime  $p$  of good ordinary reduction.

INPUT:

- $p$  - prime = 5
- $prec$  - answer will be returned modulo  $p^{prec}$
- $height$  - precomputed height function. If not supplied, this function will call `padic_height` to compute it.
- $check\_hypotheses$  - boolean, whether to check that this is a curve for which the  $p$ -adic height makes sense

OUTPUT: The  $p$ -adic cyclotomic height pairing matrix of this curve to the given precision.

---

**Todo:** remove restriction that curve must be in minimal Weierstrass form. This is currently required for `E.gens()`.

---

## AUTHORS:

- David Harvey, Liang Xiao, Robert Bradshaw, Jennifer Balakrishnan: original implementation at the 2006 MSRI graduate workshop on modular forms
- David Harvey (2006-09-13): cleaned up and integrated into Sage, removed some redundant height computations

## EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: E.padic_height_pairing_matrix(5, 10)
[5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)]
```

## A rank two example:

```
sage: e = EllipticCurve('389a')
sage: e._set_gens([e(-1, 1), e(1, 0)]) # avoid platform dependent gens
sage: e.padic_height_pairing_matrix(5, 10)
[
    3*5 + 2*5^2 + 5^4 + 5^5 + 5^7 + 4*5^9 + O(5^10)  5 + 4*5^2 +
    ↪ 5^3 + 2*5^4 + 3*5^5 + 4*5^6 + 5^7 + 5^8 + 2*5^9 + O(5^10) ]
[5 + 4*5^2 + 5^3 + 2*5^4 + 3*5^5 + 4*5^6 + 5^7 + 5^8 + 2*5^9 + O(5^10)
    ↪ 4*5 + 2*5^4 + 3*5^6 + 4*5^7 + 4*5^8 + O(5^10)]
```

## An anomalous rank 3 example:

```
sage: e = EllipticCurve("5077a")
sage: e._set_gens([e(-1, 3), e(2, 0), e(4, 6)])
sage: e.padic_height_pairing_matrix(5, 4)
[4 + 3*5 + 4*5^2 + 4*5^3 + O(5^4)      4 + 4*5^2 + 2*5^3 + O(5^4)      3*5 +
    ↪ 4*5^2 + 5^3 + O(5^4)]
[      4 + 4*5^2 + 2*5^3 + O(5^4)      3 + 4*5 + 3*5^2 + 5^3 + O(5^4)
    ↪ 2 + 4*5 + O(5^4)]
[      3*5 + 4*5^2 + 5^3 + O(5^4)      2 + 4*5 + O(5^4)      1 + 3*5 +
    ↪ 5^2 + 5^3 + O(5^4)]
```

```
sage.schemes.elliptic_curves.padics.padic_height_via_multiply(self, p, prec=20,
                                                                E2=None,
                                                                check_hypotheses=True)
```

Computes the cyclotomic p-adic height.

The equation of the curve must be minimal at  $p$ .

## INPUT:

- $p$  - prime = 5 for which the curve has good ordinary reduction
- $prec$  - integer = 2, desired precision of result
- $E2$  - precomputed value of  $E2$ . If not supplied, this function will call `padic_E2` to compute it. The value supplied must be correct mod  $p^{(prec-2)}$  (or slightly higher in the anomalous case; see the code for details).
- `check_hypotheses` - boolean, whether to check that this is a curve for which the p-adic height makes sense

OUTPUT: A function that accepts two parameters:

- a  $\mathbb{Q}$ -rational point on the curve whose height should be computed
- optional boolean flag 'check': if False, it skips some input checking, and returns the p-adic height of that point to the desired precision.

- The normalization (sign and a factor 1/2 with respect to some other normalizations that appear in the literature) is chosen in such a way as to make the p-adic Birch Swinnerton-Dyer conjecture hold as stated in [Mazur-Tate-Teitelbaum].

AUTHORS:

- David Harvey (2008-01): based on the `padic_height()` function, using the algorithm of "Computing p-adic heights via point multiplication"

EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: P = E.gens()[0]
sage: h = E.padic_height_via_multiply(5, 10)
sage: h(P)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

An anomalous case:

```
sage: h = E.padic_height_via_multiply(53, 10)
sage: h(P)
26*53^-1 + 30 + 20*53 + 47*53^2 + 10*53^3 + 32*53^4 + 9*53^5 + 22*53^6 + 35*53^7 +
↪+ 30*53^8 + 17*53^9 + O(53^10)
```

Supply the value of E2 manually:

```
sage: E2 = E.padic_E2(5, 8)
sage: E2
2 + 4*5 + 2*5^3 + 5^4 + 3*5^5 + 2*5^6 + O(5^8)
sage: h = E.padic_height_via_multiply(5, 10, E2=E2)
sage: h(P)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

Boundary case:

```
sage: E.padic_height_via_multiply(5, 3)(P)
5 + 5^2 + O(5^3)
```

Check that answers agree over a range of precisions:

```
sage: max_prec = 30      # make sure we get past p^2      # long time
sage: full = E.padic_height(5, max_prec)(P)                # long time
sage: for prec in range(2, max_prec):                      # long time
....:     assert E.padic_height_via_multiply(5, prec)(P) == full # long time
```

`sage.schemes.elliptic_curves.padics.padic_lseries`

A decorator that creates a cached version of an instance method of a class.

**Note:** For proper behavior, the method must be a pure function (no side effects). Arguments to the method must be hashable or transformed into something hashable using `key` or they must define `sage.structure.sage_object.SageObject._cache_key()`.

EXAMPLES:

```
sage: class Foo(object):
....:     @cached_method
....:     def f(self, t, x=2):
```



```

.....:         print('computing')
.....:         return t**x
sage: a = Foo()

```

The example shows that the actual computation takes place only once, and that the result is identical for equivalent input:

```

sage: res = a.f(3, 2); res
computing
9
sage: a.f(t = 3, x = 2) is res
True
sage: a.f(3) is res
True

```

Note, however, that the `CachedMethod` is replaced by a `CachedMethodCaller` or `CachedMethodCallerNoArgs` as soon as it is bound to an instance or class:

```

sage: P.<a,b,c,d> = QQ[]
sage: I = P*[a,b]
sage: type(I.__class__.gens)
<type 'sage.misc.cachefunc.CachedMethodCallerNoArgs'>

```

So, you would hardly ever see an instance of this class alive.

The parameter `key` can be used to pass a function which creates a custom cache key for inputs. In the following example, this parameter is used to ignore the `algorithm` keyword for caching:

```

sage: class A(object):
.....:     def _f_normalize(self, x, algorithm): return x
.....:     @cached_method(key=_f_normalize)
.....:     def f(self, x, algorithm='default'): return x
sage: a = A()
sage: a.f(1, algorithm="default") is a.f(1) is a.f(1, algorithm="algorithm")
True

```

The parameter `do_pickle` can be used to enable pickling of the cache. Usually the cache is not stored when pickling:

```

sage: class A(object):
.....:     @cached_method
.....:     def f(self, x): return None
sage: import __main__
sage: __main__.A = A
sage: a = A()
sage: a.f(1)
sage: len(a.f.cache)
1
sage: b = loads(dumps(a))
sage: len(b.f.cache)
0

```

When `do_pickle` is set, the pickle contains the contents of the cache:

```

sage: class A(object):
.....:     @cached_method(do_pickle=True)
.....:     def f(self, x): return None
sage: __main__.A = A

```

```
sage: a = A()
sage: a.f(1)
sage: len(a.f.cache)
1
sage: b = loads(dumps(a))
sage: len(b.f.cache)
1
```

Cached methods can not be copied like usual methods, see [trac ticket #12603](#). Copying them can lead to very surprising results:

```
sage: class A:
....:     @cached_method
....:     def f(self):
....:         return 1
sage: class B:
....:     g=A.f
....:     def f(self):
....:         return 2

sage: b=B()
sage: b.f()
2
sage: b.g()
1
sage: b.f()
1
```

`sage.schemes.elliptic_curves.padics.padic_regulator`(*self*, *p*, *prec*=20, *height*=None, *check\_hypotheses*=True)

Computes the cyclotomic  $p$ -adic regulator of this curve.

INPUT:

- *p* - prime = 5
- *prec* - answer will be returned modulo  $p^{\text{prec}}$
- *height* - precomputed height function. If not supplied, this function will call `padic_height` to compute it.
- *check\_hypotheses* - boolean, whether to check that this is a curve for which the  $p$ -adic height makes sense

OUTPUT: The  $p$ -adic cyclotomic regulator of this curve, to the requested precision.

If the rank is 0, we output 1.

---

**Todo:** Remove restriction that curve must be in minimal Weierstrass form. This is currently required for `E.gens()`.

---

AUTHORS:

- Liang Xiao: original implementation at the 2006 MSRI graduate workshop on modular forms
- David Harvey (2006-09-13): cleaned up and integrated into Sage, removed some redundant height computations
- Chris Wuthrich (2007-05-22): added multiplicative and supersingular cases
- David Harvey (2007-09-20): fixed some precision loss that was occurring

## EXAMPLES:

```
sage: E = EllipticCurve("37a")
sage: E.padic_regulator(5, 10)
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + O(5^10)
```

An anomalous case:

```
sage: E.padic_regulator(53, 10)
26*53^-1 + 30 + 20*53 + 47*53^2 + 10*53^3 + 32*53^4 + 9*53^5 + 22*53^6 + 35*53^7_
↪ + 30*53^8 + O(53^9)
```

An anomalous case where the precision drops some:

```
sage: E = EllipticCurve("5077a")
sage: E.padic_regulator(5, 10)
5 + 5^2 + 4*5^3 + 2*5^4 + 2*5^5 + 2*5^6 + 4*5^7 + 2*5^8 + 5^9 + O(5^10)
```

Check that answers agree over a range of precisions:

```
sage: max_prec = 30      # make sure we get past p^2      # long time
sage: full = E.padic_regulator(5, max_prec)                # long time
sage: for prec in range(1, max_prec):                      # long time
....:     assert E.padic_regulator(5, prec) == full        # long time
```

A case where the generator belongs to the formal group already ([trac ticket #3632](#)):

```
sage: E = EllipticCurve([37,0])
sage: E.padic_regulator(5,10)
2*5^2 + 2*5^3 + 5^4 + 5^5 + 4*5^6 + 3*5^8 + 4*5^9 + O(5^10)
```

The result is not dependent on the model for the curve:

```
sage: E = EllipticCurve([0,0,0,0,2^12*17])
sage: Em = E.minimal_model()
sage: E.padic_regulator(7) == Em.padic_regulator(7)
True
```

Allow a Python int as input:

```
sage: E = EllipticCurve('37a')
sage: E.padic_regulator(int(5))
5 + 5^2 + 5^3 + 3*5^6 + 4*5^7 + 5^9 + 5^10 + 3*5^11 + 3*5^12 + 5^13 + 4*5^14 + 5^
↪ 15 + 2*5^16 + 5^17 + 2*5^18 + 4*5^19 + O(5^20)
```

`sage.schemes.elliptic_curves.padics.padic_sigma` (*self*, *p*, *N*=20, *E2*=None, *check*=False, *check\_hypotheses*=True)

Computes the  $p$ -adic sigma function with respect to the standard invariant differential  $dx/(2y + a_1x + a_3)$ , as defined by Mazur and Tate, as a power series in the usual uniformiser  $t$  at the origin.

The equation of the curve must be minimal at  $p$ .

INPUT:

- $p$  - prime = 5 for which the curve has good ordinary reduction
- $N$  - integer = 1, indicates precision of result; see OUTPUT section for description
- $E2$  - precomputed value of  $E2$ . If not supplied, this function will call `padic_E2` to compute it. The value supplied must be correct mod  $p^{N-2}$ .

- `check` - boolean, whether to perform a consistency check (i.e. verify that the computed sigma satisfies the defining
- `differential equation` - note that this does NOT guarantee correctness of all the returned digits, but it comes pretty close :-))
- `check_hypotheses` - boolean, whether to check that this is a curve for which the p-adic sigma function makes sense

OUTPUT: A power series  $t + \dots$  with coefficients in  $\mathbf{Z}_p$ .

The output series will be truncated at  $O(t^{N+1})$ , and the coefficient of  $t^n$  for  $n \geq 1$  will be correct to precision  $O(p^{N-n+1})$ .

In practice this means the following. If  $t_0 = p^k u$ , where  $u$  is a  $p$ -adic unit with at least  $N$  digits of precision, and  $k \geq 1$ , then the returned series may be used to compute  $\sigma(t_0)$  correctly modulo  $p^{N+k}$  (i.e. with  $N$  correct  $p$ -adic digits).

ALGORITHM: Described in “Efficient Computation of p-adic Heights” (David Harvey), which is basically an optimised version of the algorithm from “p-adic Heights and Log Convergence” (Mazur, Stein, Tate).

Running time is soft- $O(N^2 \log p)$ , plus whatever time is necessary to compute  $E_2$ .

AUTHORS:

- David Harvey (2006-09-12)
- David Harvey (2007-02): rewrote

EXAMPLES:

```
sage: EllipticCurve([-1, 1/4]).padic_sigma(5, 10)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 + O(5^
↪8))*t^3 + O(5^7)*t^4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 5^5 + O(5^6))*t^5 + O(5^5)*t^
↪6 + (2 + 2*5 + 5^2 + 4*5^3 + O(5^4))*t^7 + O(5^3)*t^8 + (1 + 2*5 + O(5^2))*t^9
↪+ O(5)*t^10 + O(t^11)
```

Run it with a consistency check:

```
sage: EllipticCurve("37a").padic_sigma(5, 10, check=True)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 + O(5^
↪8))*t^3 + (3 + 2*5 + 2*5^2 + 2*5^3 + 2*5^4 + 2*5^5 + 2*5^6 + O(5^7))*t^4 + (2 +
↪4*5^2 + 4*5^3 + 5^4 + 5^5 + O(5^6))*t^5 + (2 + 3*5 + 5^4 + O(5^5))*t^6 + (4 +
↪3*5 + 2*5^2 + O(5^4))*t^7 + (2 + 3*5 + 2*5^2 + O(5^3))*t^8 + (4*5 + O(5^2))*t^9
↪+ (1 + O(5))*t^10 + O(t^11)
```

Boundary cases:

```
sage: EllipticCurve([1, 1, 1, 1, 1]).padic_sigma(5, 1)
(1 + O(5))*t + O(t^2)
sage: EllipticCurve([1, 1, 1, 1, 1]).padic_sigma(5, 2)
(1 + O(5^2))*t + (3 + O(5))*t^2 + O(t^3)
```

Supply your very own value of  $E_2$ :

```
sage: X = EllipticCurve("37a")
sage: my_E2 = X.padic_E2(5, 8)
sage: my_E2 = my_E2 + 5**5 # oops!!!
sage: X.padic_sigma(5, 10, E2=my_E2)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 4*5^5 + 2*5^6 + 3*5^
↪7 + O(5^8))*t^3 + (3 + 2*5 + 2*5^2 + 2*5^3 + 2*5^4 + 2*5^5 + 2*5^6 + O(5^7))*t^
↪4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 3*5^5 + O(5^6))*t^5 + (2 + 3*5 + 5^4 + O(5^5))*t^
↪6 + (4 + 3*5 + 2*5^2 + O(5^4))*t^7 + (2 + 3*5 + 2*5^2 + O(5^3))*t^8 + (4*5 +
↪O(5^2))*t^9 + (1 + O(5))*t^10 + O(t^11)
```

Check that sigma is “weight 1”.

```
sage: f = EllipticCurve([-1, 3]).padic_sigma(5, 10)
sage: g = EllipticCurve([-1*(2**4), 3*(2**6)]).padic_sigma(5, 10)
sage: t = f.parent().gen()
sage: f(2*t)/2
(1 + O(5^10))*t + (4 + 3*5 + 3*5^2 + 3*5^3 + 4*5^4 + 4*5^5 + 3*5^6 + 5^7 + O(5^
↪8))*t^3 + (3 + 3*5^2 + 5^4 + 2*5^5 + O(5^6))*t^5 + (4 + 5 + 3*5^3 + O(5^4))*t^7_
↪+ (4 + 2*5 + O(5^2))*t^9 + O(5)*t^10 + O(t^11)
sage: g
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (4 + 3*5 + 3*5^2 + 3*5^3 + 4*5^4 + 4*5^5_
↪+ 3*5^6 + 5^7 + O(5^8))*t^3 + O(5^7)*t^4 + (3 + 3*5^2 + 5^4 + 2*5^5 + O(5^6))*t^
↪5 + O(5^5)*t^6 + (4 + 5 + 3*5^3 + O(5^4))*t^7 + O(5^3)*t^8 + (4 + 2*5 + O(5^
↪2))*t^9 + O(5)*t^10 + O(t^11)
sage: f(2*t)/2 -g
O(t^11)
```

Test that it returns consistent results over a range of precision:

```
sage: max_N = 30 # get up to at least p^2 # long time
sage: E = EllipticCurve([1, 1, 1, 1, 1]) # long time
sage: p = 5 # long time
sage: E2 = E.padic_E2(5, max_N) # long time
sage: max_sigma = E.padic_sigma(p, max_N, E2=E2) # long time
sage: for N in range(3, max_N): # long time
....:     sigma = E.padic_sigma(p, N, E2=E2) # long time
....:     assert sigma == max_sigma
```

`sage.schemes.elliptic_curves.padics.padic_sigma_truncated(self, p, N=20, lamb=0, E2=None, check_hypotheses=True)`

Computes the p-adic sigma function with respect to the standard invariant differential  $dx/(2y + a_1x + a_3)$ , as defined by Mazur and Tate, as a power series in the usual uniformiser  $t$  at the origin.

The equation of the curve must be minimal at  $p$ .

This function differs from `padic_sigma()` in the precision profile of the returned power series; see OUTPUT below.

INPUT:

- $p$  - prime = 5 for which the curve has good ordinary reduction
- $N$  - integer = 2, indicates precision of result; see OUTPUT section for description
- $\text{lamb}$  - integer = 0, see OUTPUT section for description
- $E2$  - precomputed value of  $E2$ . If not supplied, this function will call `padic_E2` to compute it. The value supplied must be correct mod  $p^{N-2}$ .
- `check_hypotheses` - boolean, whether to check that this is a curve for which the p-adic sigma function makes sense

OUTPUT: A power series  $t + \dots$  with coefficients in  $\mathbb{Z}_p$ .

The coefficient of  $t^j$  for  $j \geq 1$  will be correct to precision  $O(p^{N-2+(3-j)(\text{lamb}+1)})$ .

ALGORITHM: Described in “Efficient Computation of p-adic Heights” (David Harvey, to appear in LMS JCM), which is basically an optimised version of the algorithm from “p-adic Heights and Log Convergence” (Mazur, Stein, Tate), and “Computing p-adic heights via point multiplication” (David Harvey, still draft form).

Running time is soft- $O(N^2\lambda^{-1}\log p)$ , plus whatever time is necessary to compute  $E_2$ .

AUTHOR:

- David Harvey (2008-01): wrote based on previous `padic_sigma` function

EXAMPLES:

```
sage: E = EllipticCurve([-1, 1/4])
sage: E.padic_sigma_truncated(5, 10)
O(5^11) + (1 + O(5^10))*t + O(5^9)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 + O(5^
↪8))*t^3 + O(5^7)*t^4 + (2 + 4*5^2 + 4*5^3 + 5^4 + 5^5 + O(5^6))*t^5 + O(5^5)*t^
↪6 + (2 + 2*5 + 5^2 + 4*5^3 + O(5^4))*t^7 + O(5^3)*t^8 + (1 + 2*5 + O(5^2))*t^9
↪+ O(5)*t^10 + O(t^11)
```

Note the precision of the  $t^3$  coefficient depends only on  $N$ , not on  $\lambda$ :

```
sage: E.padic_sigma_truncated(5, 10, lamb=2)
O(5^17) + (1 + O(5^14))*t + O(5^11)*t^2 + (3 + 2*5^2 + 3*5^3 + 3*5^6 + 4*5^7 +
↪O(5^8))*t^3 + O(5^5)*t^4 + (2 + O(5^2))*t^5 + O(t^6)
```

Compare against plain `padic_sigma()` function over a dense range of  $N$  and  $\lambda$

```
sage: E = EllipticCurve([1, 2, 3, 4, 7]) # long time
sage: E2 = E.padic_E2(5, 50) # long time
sage: for N in range(2, 10): # long time
.....:     for lamb in range(10): # long time
.....:         correct = E.padic_sigma(5, N + 3*lamb, E2=E2) # long time
.....:         compare = E.padic_sigma_truncated(5, N=N, lamb=lamb, E2=E2) # long
↪time
.....:         assert compare == correct # long time
```

Analytic properties over  $\mathbb{C}$ .

### 15.11.16 Weierstrass $\wp$ -function for elliptic curves

The Weierstrass  $\wp$  function associated to an elliptic curve over a field  $k$  is a Laurent series of the form

$$\wp(z) = \frac{1}{z^2} + c_2 \cdot z^2 + c_4 \cdot z^4 + \cdots$$

If the field is contained in  $\mathbb{C}$ , then this is the series expansion of the map from  $\mathbb{C}$  to  $E(\mathbb{C})$  whose kernel is the period lattice of  $E$ .

Over other fields, like finite fields, this still makes sense as a formal power series with coefficients in  $k$  - at least its first  $p - 2$  coefficients where  $p$  is the characteristic of  $k$ . It can be defined via the formal group as  $x + c$  in the variable  $z = \log_E(t)$  for a constant  $c$  such that the constant term  $c_0$  in  $\wp(z)$  is zero.

EXAMPLES:

```
sage: E = EllipticCurve([0, 1])
sage: E.weierstrass_p()
z^-2 - 1/7*z^4 + 1/637*z^10 - 1/84721*z^16 + O(z^20)
```

REFERENCES:

- [BMSS] Boston, Morain, Salvy, Schost, “Fast Algorithms for Isogenies.”

AUTHORS:

- Dan Shumov 04/09: original implementation

- Chris Wuthrich 11/09: major restructuring
- Jeroen Demeyer (2014-03-06): code clean up, fix characteristic bound for quadratic algorithm (see [trac ticket #15855](#))

`sage.schemes.elliptic_curves.ell_wp.compute_wp_fast(k, A, B, m)`

Computes the Weierstrass function of an elliptic curve defined by short Weierstrass model:  $y^2 = x^3 + Ax + B$ . It does this with as fast as polynomial of degree  $m$  can be multiplied together in the base ring, i.e.  $O(M(n))$  in the notation of [BMSS].

Let  $p$  be the characteristic of the underlying field: Then we must have either  $p = 0$ , or  $p > m + 3$ .

INPUT:

- $k$  - the base field of the curve
- $A$  - and
- $B$  - as the coefficients of the short Weierstrass model  $y^2 = x^3 + Ax + B$ , and
- $m$  - the precision to which the function is computed to.

OUTPUT:

the Weierstrass  $\wp$  function as a Laurent series to precision  $m$ .

ALGORITHM:

This function uses the algorithm described in section 3.3 of [BMSS].

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_wp import compute_wp_fast
sage: compute_wp_fast(QQ, 1, 8, 7)
z^-2 - 1/5*z^2 - 8/7*z^4 + 1/75*z^6 + O(z^7)

sage: k = GF(37)
sage: compute_wp_fast(k, k(1), k(8), 5)
z^-2 + 22*z^2 + 20*z^4 + O(z^5)
```

`sage.schemes.elliptic_curves.ell_wp.compute_wp_pari(E, prec)`

Computes the Weierstrass  $\wp$ -function with the `ellwp` function from PARI.

EXAMPLES:

```
sage: E = EllipticCurve([0,1])
sage: from sage.schemes.elliptic_curves.ell_wp import compute_wp_pari
sage: compute_wp_pari(E, prec=20)
z^-2 - 1/7*z^4 + 1/637*z^10 - 1/84721*z^16 + O(z^20)
sage: compute_wp_pari(E, prec=30)
z^-2 - 1/7*z^4 + 1/637*z^10 - 1/84721*z^16 + 3/38548055*z^22 - 4/8364927935*z^28
↪+ O(z^30)
```

`sage.schemes.elliptic_curves.ell_wp.compute_wp_quadratic(k, A, B, prec)`

Computes the truncated Weierstrass function of an elliptic curve defined by short Weierstrass model:  $y^2 = x^3 + Ax + B$ . Uses an algorithm that is of complexity  $O(prec^2)$ .

Let  $p$  be the characteristic of the underlying field. Then we must have either  $p = 0$ , or  $p > prec + 2$ .

INPUT:

- $k$  - the field of definition of the curve
- $A$  - and

- B - the coefficients of the elliptic curve
- prec - the precision to which we compute the series.

OUTPUT: A Laurent series approximating the Weierstrass  $\wp$ -function to precision prec.

ALGORITHM: This function uses the algorithm described in section 3.2 of [BMSS].

REFERENCES: [BMSS] Boston, Morain, Salvy, Schost, “Fast Algorithms for Isogenies.”

EXAMPLES:

```
sage: E = EllipticCurve([7,0])
sage: E.weierstrass_p(prec=10, algorithm='quadratic')
z^-2 - 7/5*z^2 + 49/75*z^6 + O(z^10)

sage: E = EllipticCurve(GF(103),[1,2])
sage: E.weierstrass_p(algorithm='quadratic')
z^-2 + 41*z^2 + 88*z^4 + 11*z^6 + 57*z^8 + 55*z^10 + 73*z^12 + 11*z^14 + 17*z^16
↪ + 50*z^18 + O(z^20)

sage: from sage.schemes.elliptic_curves.ell_wp import compute_wp_quadratic
sage: compute_wp_quadratic(E.base_ring(), E.a4(), E.a6(), prec=10)
z^-2 + 41*z^2 + 88*z^4 + 11*z^6 + 57*z^8 + O(z^10)
```

sage.schemes.elliptic\_curves.ell\_wp.**solve\_linear\_differential\_system**(a, b, c,  
alpha)

Solves a system of linear differential equations:  $af' + bf = c$  and  $f'(0) = \alpha$  where  $a$ ,  $b$ , and  $c$  are power series in one variable and  $\alpha$  is a constant in the coefficient ring.

ALGORITHM:

due to Brent and Kung '78.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_wp import solve_linear_differential_
↪ system
sage: k = GF(17)
sage: R.<x> = PowerSeriesRing(k)
sage: a = 1+x+O(x^7); b = x+O(x^7); c = 1+x^3+O(x^7); alpha = k(3)
sage: f = solve_linear_differential_system(a,b,c,alpha)
sage: f
3 + x + 15*x^2 + x^3 + 10*x^5 + 3*x^6 + 13*x^7 + O(x^8)
sage: a*f.derivative()+b*f - c
O(x^7)
sage: f(0) == alpha
True
```

sage.schemes.elliptic\_curves.ell\_wp.**weierstrass\_p**(E, prec=20, algorithm=None)

Computes the Weierstrass  $\wp$ -function on an elliptic curve.

INPUT:

- E – an elliptic curve
- prec – precision
- algorithm – string (default:None) an algorithm identifier indicating the pari, fast or quadratic algorithm. If the algorithm is None, then this function determines the best algorithm to use.

OUTPUT:



a Laurent series in one variable  $z$  with coefficients in the base field  $k$  of  $E$ .

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.weierstrass_p(prec=10)
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + 77531/41580*z^8 + O(z^10)
sage: E.weierstrass_p(prec=8)
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + O(z^8)
sage: Esh = E.short_weierstrass_model()
sage: Esh.weierstrass_p(prec=8)
z^-2 + 13392/5*z^2 + 1080432/7*z^4 + 59781888/25*z^6 + O(z^8)

sage: E.weierstrass_p(prec=8, algorithm='pari')
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + O(z^8)
sage: E.weierstrass_p(prec=8, algorithm='quadratic')
z^-2 + 31/15*z^2 + 2501/756*z^4 + 961/675*z^6 + O(z^8)

sage: k = GF(11)
sage: E = EllipticCurve(k, [1,1])
sage: E.weierstrass_p(prec=6, algorithm='fast')
z^-2 + 2*z^2 + 3*z^4 + O(z^6)
sage: E.weierstrass_p(prec=7, algorithm='fast')
Traceback (most recent call last):
...
ValueError: for computing the Weierstrass p-function via the fast algorithm, the
↳characteristic (11) of the underlying field must be greater than prec + 4 = 11
sage: E.weierstrass_p(prec=8)
z^-2 + 2*z^2 + 3*z^4 + 5*z^6 + O(z^8)
sage: E.weierstrass_p(prec=8, algorithm='quadratic')
z^-2 + 2*z^2 + 3*z^4 + 5*z^6 + O(z^8)
sage: E.weierstrass_p(prec=8, algorithm='pari')
z^-2 + 2*z^2 + 3*z^4 + 5*z^6 + O(z^8)
sage: E.weierstrass_p(prec=9)
Traceback (most recent call last):
...
NotImplementedError: currently no algorithms for computing the Weierstrass p-
↳function for that characteristic / precision pair is implemented. Lower the
↳precision below char(k) - 2
sage: E.weierstrass_p(prec=9, algorithm="quadratic")
Traceback (most recent call last):
...
ValueError: for computing the Weierstrass p-function via the quadratic algorithm,
↳the characteristic (11) of the underlying field must be greater than prec + 2 =
↳11
sage: E.weierstrass_p(prec=9, algorithm='pari')
Traceback (most recent call last):
...
ValueError: for computing the Weierstrass p-function via pari, the characteristic
↳(11) of the underlying field must be greater than prec + 2 = 11
```

### 15.11.17 Period lattices of elliptic curves and related functions

Let  $E$  be an elliptic curve defined over a number field  $K$  (including  $\mathbb{Q}$ ). We attach a period lattice (a discrete rank 2 subgroup of  $\mathbb{C}$ ) to each embedding of  $K$  into  $\mathbb{C}$ .

In the case of real embeddings, the lattice is stable under complex conjugation and is called a real lattice. These have two types: rectangular, (the real curve has two connected components and positive discriminant) or non-rectangular

(one connected component, negative discriminant).

The periods are computed to arbitrary precision using the AGM (Gauss's Arithmetic-Geometric Mean).

EXAMPLES:

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,1,0,a,a])
```

First we try a real embedding:

```
sage: emb = K.embeddings(RealField())[0]
sage: L = E.period_lattice(emb); L
Period lattice associated to Elliptic Curve defined by y^2 = x^3 + x^2 + a*x + a over
↳Number Field in a with defining polynomial x^3 - 2 with respect to the embedding
↳Ring morphism:
From: Number Field in a with defining polynomial x^3 - 2
To:   Algebraic Real Field
Defn: a |--> 1.259921049894873?
```

The first basis period is real:

```
sage: L.basis()
(3.81452977217855, 1.90726488608927 + 1.34047785962440*I)
sage: L.is_real()
True
```

For a basis  $\omega_1, \omega_2$  normalised so that  $\omega_1/\omega_2$  is in the fundamental region of the upper half-plane, use the function `normalised_basis()` instead:

```
sage: L.normalised_basis()
(1.90726488608927 - 1.34047785962440*I, -1.90726488608927 - 1.34047785962440*I)
```

Next a complex embedding:

```
sage: emb = K.embeddings(ComplexField())[0]
sage: L = E.period_lattice(emb); L
Period lattice associated to Elliptic Curve defined by y^2 = x^3 + x^2 + a*x + a over
↳Number Field in a with defining polynomial x^3 - 2 with respect to the embedding
↳Ring morphism:
From: Number Field in a with defining polynomial x^3 - 2
To:   Algebraic Field
Defn: a |--> -0.6299605249474365? - 1.091123635971722?*I
```

In this case, the basis  $\omega_1, \omega_2$  is always normalised so that  $\tau = \omega_1/\omega_2$  is in the fundamental region in the upper half plane:

```
sage: w1,w2 = L.basis(); w1,w2
(-1.37588604166076 - 2.58560946624443*I, -2.10339907847356 + 0.428378776460622*I)
sage: L.is_real()
False
sage: tau = w1/w2; tau
0.387694505032876 + 1.30821088214407*I
sage: L.normalised_basis()
(-1.37588604166076 - 2.58560946624443*I, -2.10339907847356 + 0.428378776460622*I)
```

We test that bug [trac ticket #8415](#) (caused by a PARI bug fixed in v2.3.5) is OK:

```

sage: E = EllipticCurve('37a')
sage: K.<a> = QuadraticField(-7)
sage: EK = E.change_ring(K)
sage: EK.period_lattice(K.complex_embeddings()[0])
Period lattice associated to Elliptic Curve defined by  $y^2 + y = x^3 + (-1)x$  over
↪Number Field in a with defining polynomial  $x^2 + 7$  with respect to the embedding
↪Ring morphism:
  From: Number Field in a with defining polynomial  $x^2 + 7$ 
  To:   Algebraic Field
  Defn: a |--> -2.645751311064591?+I

```

## REFERENCES:

## AUTHORS:

- ? : initial version.
- John Cremona:
  - Adapted to handle real embeddings of number fields, September 2008.
  - Added `basis_matrix` function, November 2008
  - Added support for complex embeddings, May 2009.
  - Added complex elliptic logs, March 2010; enhanced, October 2010.

```

class sage.schemes.elliptic_curves.period_lattice.PeriodLattice (base_ring,
                                                                    rank, degree,
                                                                    sparse=False,
                                                                    coordi-
                                                                    nate_ring=None)

```

Bases: `sage.modules.free_module.FreeModule_generic_pid`

The class for the period lattice of an algebraic variety.

```

class sage.schemes.elliptic_curves.period_lattice.PeriodLattice_ell (E,
                                                                    embed-
                                                                    ding=None)

```

Bases: `sage.schemes.elliptic_curves.period_lattice.PeriodLattice`

The class for the period lattice of an elliptic curve.

Currently supported are elliptic curves defined over  $\mathbf{Q}$ , and elliptic curves defined over a number field with a real or complex embedding, where the lattice constructed depends on that embedding.

**basis** (*prec=None, algorithm='sage'*)

Return a basis for this period lattice as a 2-tuple.

INPUT:

- `prec` (default: None) – precision in bits (default precision if None).
- `algorithm` (string, default 'sage') – choice of implementation (for real embeddings only) between 'sage' (native Sage implementation) or 'pari' (use the PARI library: only available for real embeddings).

OUTPUT:

(tuple of Complex)  $(\omega_1, \omega_2)$  where the lattice is  $\mathbf{Z}\omega_1 + \mathbf{Z}\omega_2$ . If the lattice is real then  $\omega_1$  is real and positive,  $\Im(\omega_2) > 0$  and  $\Re(\omega_1/\omega_2)$  is either 0 (for rectangular lattices) or  $\frac{1}{2}$  (for non-rectangular lattices). Otherwise,  $\omega_1/\omega_2$  is in the fundamental region of the upper half-plane. If the latter normalisation is required for real lattices, use the function `normalised_basis()` instead.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice().basis()
(2.99345864623196, 2.45138938198679*I)
```

This shows that the issue reported at [trac ticket #3954](#) is fixed:

```
sage: E = EllipticCurve('37a')
sage: b1 = E.period_lattice().basis(prec=30)
sage: b2 = E.period_lattice().basis(prec=30)
sage: b1 == b2
True
```

This shows that the issue reported at [trac ticket #4064](#) is fixed:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice().basis(prec=30)[0].parent()
Real Field with 30 bits of precision
sage: E.period_lattice().basis(prec=100)[0].parent()
Real Field with 100 bits of precision
```

```
sage: K.<a> = NumberField(x^3-2)
sage: emb = K.embeddings(RealField())[0]
sage: E = EllipticCurve([0,1,0,a,a])
sage: L = E.period_lattice(emb)
sage: L.basis(64)
(3.81452977217854509, 1.90726488608927255 + 1.34047785962440202*I)

sage: emb = K.embeddings(ComplexField())[0]
sage: L = E.period_lattice(emb)
sage: w1,w2 = L.basis(); w1,w2
(-1.37588604166076 - 2.58560946624443*I, -2.10339907847356 + 0.
↪ 428378776460622*I)
sage: L.is_real()
False
sage: tau = w1/w2; tau
0.387694505032876 + 1.30821088214407*I
```

**basis\_matrix** (*prec=None, normalised=False*)

Return the basis matrix of this period lattice.

INPUT:

- *prec* (int or None) (default) -- real precision in bits (default real precision if None).
- *normalised* (bool, default None) – if True and the embedding is real, use the normalised basis (see `normalised_basis()`) instead of the default.

OUTPUT:

A 2x2 real matrix whose rows are the lattice basis vectors, after identifying  $\mathbf{C}$  with  $\mathbf{R}^2$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice().basis_matrix()
[ 2.99345864623196 0.000000000000000]
[0.000000000000000 2.45138938198679]
```

```

sage: K.<a> = NumberField(x^3-2)
sage: emb = K.embeddings(RealField())[0]
sage: E = EllipticCurve([0,1,0,a,a])
sage: L = E.period_lattice(emb)
sage: L.basis_matrix(64)
[ 3.81452977217854509 0.000000000000000000]
[ 1.90726488608927255 1.34047785962440202]

```

See [trac ticket #4388](#):

```

sage: L = EllipticCurve('11a1').period_lattice()
sage: L.basis_matrix()
[ 1.26920930427955 0.000000000000000000]
[ 0.634604652139777 1.45881661693850]
sage: L.basis_matrix(normalised=True)
[ 0.634604652139777 -1.45881661693850]
[ -1.26920930427955 0.000000000000000000]

```

```

sage: L = EllipticCurve('389a1').period_lattice()
sage: L.basis_matrix()
[ 2.49021256085505 0.000000000000000000]
[ 0.0000000000000000 1.97173770155165]
sage: L.basis_matrix(normalised=True)
[ 2.49021256085505 0.000000000000000000]
[ 0.0000000000000000 -1.97173770155165]

```

**complex\_area** (*prec=None*)

Return the area of a fundamental domain for the period lattice of the elliptic curve.

INPUT:

- *prec* (int or None) (default) -- real precision in bits (default real precision if None).

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: E.period_lattice().complex_area()
7.33813274078958

```

```

sage: K.<a> = NumberField(x^3-2)
sage: embs = K.embeddings(ComplexField())
sage: E = EllipticCurve([0,1,0,a,a])
sage: [E.period_lattice(emb).is_real() for emb in K.embeddings(CC)]
[False, False, True]
sage: [E.period_lattice(emb).complex_area() for emb in embs]
[6.02796894766694, 6.02796894766694, 5.11329270448345]

```

**coordinates** (*z, rounding=None*)

Returns the coordinates of a complex number w.r.t. the lattice basis

INPUT:

- *z* (complex) – A complex number.
- **rounding** (default None) – whether and how to round the output (see below).

OUTPUT:

When rounding is None (the default), returns a tuple of reals  $x, y$  such that  $z = xw_1 + yw_2$  where  $w_1, w_2$  are a basis for the lattice (normalised in the case of complex embeddings).

When rounding is 'round', returns a tuple of integers  $n_1, n_2$  which are the closest integers to the  $x, y$  defined above. If  $z$  is in the lattice these are the coordinates of  $z$  with respect to the lattice basis.

When rounding is 'floor', returns a tuple of integers  $n_1, n_2$  which are the integer parts to the  $x, y$  defined above. These are used in `reduce()`

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: L = E.period_lattice()
sage: w1, w2 = L.basis(prec=100)
sage: P = E([-1, 1])
sage: zP = P.elliptic_logarithm(precision=100); zP
0.47934825019021931612953301006 + 0.98586885077582410221120384908*I
sage: L.coordinates(zP)
(0.19249290511394227352563996419, 0.50000000000000000000000000000000)
sage: sum([x*w for x,w in zip(L.coordinates(zP), L.basis(prec=100))])
0.47934825019021931612953301006 + 0.98586885077582410221120384908*I

sage: L.coordinates(12*w1+23*w2)
(12.000000000000000000000000000000, 23.000000000000000000000000000000)
sage: L.coordinates(12*w1+23*w2, rounding='floor')
(11, 22)
sage: L.coordinates(12*w1+23*w2, rounding='round')
(12, 23)
```

**curve()**

Return the elliptic curve associated with this period lattice.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: L = E.period_lattice()
sage: L.curve() is E
True
```

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0, 1, 0, a, a])
sage: L = E.period_lattice(K.embeddings(RealField())[0])
sage: L.curve() is E
True

sage: L = E.period_lattice(K.embeddings(ComplexField())[0])
sage: L.curve() is E
True
```

**e\_log\_RC(xP, yP, prec=None, reduce=True)**

Return the elliptic logarithm of a real or complex point.

- $xP, yP$  (real or complex) – Coordinates of a point on the embedded elliptic curve associated with this period lattice.
- `prec` (default: None) – real precision in bits (default real precision if None).
- `reduce` (default: True) – if True, the result is reduced with respect to the period lattice basis.

OUTPUT:

(complex number) The elliptic logarithm of the point  $(xP, yP)$  with respect to this period lattice. If  $E$  is the elliptic curve and  $\sigma : K \rightarrow \mathbb{C}$  the embedding, the returned value  $z$  is such that  $z \pmod{L}$  maps to  $(xP, yP) = \sigma(P)$  under the standard Weierstrass isomorphism from  $\mathbb{C}/L$  to  $\sigma(E)$ . If `reduce` is `True`, the output is reduced so that it is in the fundamental period parallelogram with respect to the normalised lattice basis.

ALGORITHM:

Uses the complex AGM. See [CT] for details.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: L = E.period_lattice()
sage: P = E([-1, 1])
sage: xP, yP = [RR(c) for c in P.xy()]
```

The elliptic log from the real coordinates:

```
sage: L.e_log_RC(xP, yP)
0.479348250190219 + 0.985868850775824*I
```

The same elliptic log from the algebraic point:

```
sage: L(P)
0.479348250190219 + 0.985868850775824*I
```

A number field example:

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0, 0, 0, 0, a])
sage: v = K.real_places()[0]
sage: L = E.period_lattice(v)
sage: P = E.lift_x(1/3*a^2 + a + 5/3)
sage: L(P)
3.51086196882538
sage: xP, yP = [v(c) for c in P.xy()]
sage: L.e_log_RC(xP, yP)
3.51086196882538
```

Elliptic logs of real points which do not come from algebraic points:

```
sage: ER = EllipticCurve([v(ai) for ai in E.a_invariants()])
sage: P = ER.lift_x(12.34)
sage: xP, yP = P.xy()
sage: xP, yP
(12.3400000000000, 43.3628968710567)
sage: L.e_log_RC(xP, yP)
3.76298229503967
sage: xP, yP = ER.lift_x(0).xy()
sage: L.e_log_RC(xP, yP)
2.69842609082114
```

Elliptic logs of complex points:

```
sage: v = K.complex_embeddings()[0]
sage: L = E.period_lattice(v)
sage: P = E.lift_x(1/3*a^2 + a + 5/3)
sage: L(P)
```

```

1.68207104397706 - 1.87873661686704*I
sage: xP, yP = [v(c) for c in P.xy()]
sage: L.e_log_RC(xP, yP)
1.68207104397706 - 1.87873661686704*I
sage: EC = EllipticCurve([v(ai) for ai in E.a_invariants()])
sage: xP, yP = EC.lift_x(0).xy()
sage: L.e_log_RC(xP, yP)
1.03355715602040 - 0.867257428417356*I

```

**ei()**

Return the x-coordinates of the 2-division points of the elliptic curve associated with this period lattice, as elements of  $\overline{\mathbb{Q}}^{\text{bar}}$ .

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: L = E.period_lattice()
sage: L.ei()
[-1.107159871688768?, 0.2695944364054446?, 0.8375654352833230?]

```

In the following example, we should have one purely real 2-division point coordinate, and two conjugate purely imaginary coordinates.

```

sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,1,0,a,a])
sage: L = E.period_lattice(K.embeddings(RealField())[0])
sage: x1,x2,x3 = L.ei()
sage: abs(x1.real()) + abs(x2.real()) < 1e-14
True
sage: x1.imag(), x2.imag(), x3
(-1.122462048309373?, 1.122462048309373?, -1.000000000000000?)

```

```

sage: L = E.period_lattice(K.embeddings(ComplexField())[0])
sage: L.ei()
[-1.000000000000000? + 0.?e-1...*I,
-0.9720806486198328? - 0.561231024154687?*I,
0.9720806486198328? + 0.561231024154687?*I]

```

**elliptic\_exponential** ( $z$ ,  $to\_curve=True$ )

Return the elliptic exponential of a complex number.

INPUT:

- $z$  (complex) – A complex number (viewed modulo this period lattice).
- $to\_curve$  (bool, default True): see below.

OUTPUT:

- If  $to\_curve$  is False, a 2-tuple of real or complex numbers representing the point  $(x, y) = (\wp(z), \wp'(z))$  where  $\wp$  denotes the Weierstrass  $\wp$ -function with respect to this lattice.
- If  $to\_curve$  is True, the point  $(X, Y) = (x - b_2/12, y - (a_1(x - b_2/12) - a_3)/2)$  as a point in  $E(\mathbb{R})$  or  $E(\mathbb{C})$ , with  $(x, y) = (\wp(z), \wp'(z))$  as above, where  $E$  is the elliptic curve over  $\mathbb{R}$  or  $\mathbb{C}$  whose period lattice this is.
- If the lattice is real and  $z$  is also real then the output is a pair of real numbers if  $to\_curve$  is True, or a point in  $E(\mathbb{R})$  if  $to\_curve$  is False.



**Note:** The precision is taken from that of the input  $z$ .

EXAMPLES:

[illegible]

Examples over number fields:

```
sage: x = polygen(QQ)
sage: K.<a> = NumberField(x^3-2)
sage: embs = K.embeddings(CC)
sage: E = EllipticCurve('37a')
sage: EK = E.change_ring(K)
sage: Li = [EK.period_lattice(e) for e in embs]
sage: P = EK(-1,-1)
sage: Q = EK(a-1,1-a^2)
sage: zi = [L.elliptic_logarithm(P) for L in Li]
sage: [c.real() for c in Li[0].elliptic_exponential(zi[0])]
[-1.000000000000000, -1.000000000000000, 1.000000000000000]
sage: [c.real() for c in Li[0].elliptic_exponential(zi[1])]
[-1.000000000000000, -1.000000000000000, 1.000000000000000]
sage: [c.real() for c in Li[0].elliptic_exponential(zi[2])]
[-1.000000000000000, -1.000000000000000, 1.000000000000000]

sage: zi = [L.elliptic_logarithm(Q) for L in Li]
sage: Li[0].elliptic_exponential(zi[0])
(-1.62996052494744 - 1.09112363597172*I : 1.79370052598410 - 1.
↳37472963699860*I : 1.000000000000000)
sage: [embs[0](c) for c in Q]
[-1.62996052494744 - 1.09112363597172*I, 1.79370052598410 - 1.
↳37472963699860*I, 1.000000000000000]
sage: Li[1].elliptic_exponential(zi[1])
(-1.62996052494744 + 1.09112363597172*I : 1.79370052598410 + 1.
↳37472963699860*I : 1.000000000000000)
sage: [embs[1](c) for c in Q]
[-1.62996052494744 + 1.09112363597172*I, 1.79370052598410 + 1.
↳37472963699860*I, 1.000000000000000]
sage: [c.real() for c in Li[2].elliptic_exponential(zi[2])]
[0.259921049894873, -0.587401051968199, 1.000000000000000]
```

```
sage: [embs[2](c) for c in Q]
[0.259921049894873, -0.587401051968200, 1.000000000000000]
```

Test to show that [trac ticket #8820](#) is fixed:

```
sage: E = EllipticCurve('37a')
sage: K.<a> = QuadraticField(-5)
sage: L = E.change_ring(K).period_lattice(K.places()[0])
sage: L.elliptic_exponential(CDF(.1,.1))
(0.0000142854026029... - 49.9960001066650*I : 249.520141250950 + 250.
↪ 019855549131*I : 1.000000000000000)
sage: L.elliptic_exponential(CDF(.1,.1), to_curve=False)
(0.0000142854026029447 - 49.9960001066650*I, 500.040282501900 + 500.
↪ 039711098263*I)
```

$z = 0$  is treated as a special case:

```
sage: E = EllipticCurve([1,1,1,-8,6])
sage: L = E.period_lattice()
sage: L.elliptic_exponential(0)
(0.000000000000000 : 1.000000000000000 : 0.000000000000000)
sage: L.elliptic_exponential(0, to_curve=False)
(+infinity, +infinity)
```

```
sage: E = EllipticCurve('37a')
sage: K.<a> = QuadraticField(-5)
sage: L = E.change_ring(K).period_lattice(K.places()[0])
sage: P = L.elliptic_exponential(0); P
(0.000000000000000 : 1.000000000000000 : 0.000000000000000)
sage: P.parent()
Abelian group of points on Elliptic Curve defined by y^2 + 1.000000000000000*y_
↪ = x^3 + (-1.000000000000000)*x over Complex Field with 53 bits of precision
```

Very small  $z$  are handled properly (see [trac ticket #8820](#)):

```
sage: K.<a> = QuadraticField(-1)
sage: E = EllipticCurve([0,0,0,a,0])
sage: L = E.period_lattice(K.complex_embeddings()[0])
sage: L.elliptic_exponential(1e-100)
(0.000000000000000 : 1.000000000000000 : 0.000000000000000)
```

The elliptic exponential of  $z$  is returned as  $(0 : 1 : 0)$  if the coordinates of  $z$  with respect to the period lattice are approximately integral:

```
sage: (100/log(2.0,10))/0.8
415.241011860920
sage: L.elliptic_exponential((RealField(415)(1e-100))).is_zero()
True
sage: L.elliptic_exponential((RealField(420)(1e-100))).is_zero()
False
```

**elliptic\_logarithm**( $P$ ,  $prec=None$ ,  $reduce=True$ )

Return the elliptic logarithm of a point.

INPUT:

- $P$  (point) – A point on the elliptic curve associated with this period lattice.
- $prec$  (default: None) – real precision in bits (default real precision if None).

- OUTPUT:

ALGORITHM:

EXAMPLES:

Note that this is actually the inverse of the Weierstrass isomorphism:

An example with negative discriminant, and a torsion point:

An example where precision is problematic:

487

```
sage: L.elliptic_logarithm(P,prec=100)
0.27656204014107061464076203097
```

Some complex examples, taken from the paper by Cremona and Thongjunthug:

```
sage: K.<i> = QuadraticField(-1)
sage: a4 = 9*i-10
sage: a6 = 21-i
sage: E = EllipticCurve([0,0,0,a4,a6])
sage: e1 = 3-2*i; e2 = 1+i; e3 = -4+i
sage: emb = K.embeddings(CC)[1]
sage: L = E.period_lattice(emb)
sage: P = E(2-i, 4+2*i)
```

By default, the output is reduced with respect to the normalised lattice basis, so that its coordinates with respect to that basis lie in the interval  $[0,1)$ :

```
sage: z = L.elliptic_logarithm(P,prec=100); z
0.70448375537782208460499649302 - 0.79246725643650979858266018068*I
sage: L.coordinates(z)
(0.46247636364807931766105406092, 0.79497588726808704200760395829)
```

Using `reduce=False` this step can be omitted. In this case the coordinates are usually in the interval  $[-0.5,0.5)$ , but this is not guaranteed. This option is mainly for testing purposes:

```
sage: z = L.elliptic_logarithm(P,prec=100, reduce=False); z
0.57002153834710752778063503023 + 0.46476340520469798857457031393*I
sage: L.coordinates(z)
(0.46247636364807931766105406092, -0.20502411273191295799239604171)
```

The elliptic logs of the 2-torsion points are half-periods:

```
sage: L.elliptic_logarithm(E(e1,0),prec=100)
0.64607575874356525952487867052 + 0.22379609053909448304176885364*I
sage: L.elliptic_logarithm(E(e2,0),prec=100)
0.71330686725892253793705940192 - 0.40481924028150941053684639367*I
sage: L.elliptic_logarithm(E(e3,0),prec=100)
0.067231108515357278412180731396 - 0.62861533082060389357861524731*I
```

We check this by doubling and seeing that the resulting coordinates are integers:

```
sage: L.coordinates(2*L.elliptic_logarithm(E(e1,0),prec=100))
(1.00000000000000000000000000000000, 0.00000000000000000000000000000000)
sage: L.coordinates(2*L.elliptic_logarithm(E(e2,0),prec=100))
(1.00000000000000000000000000000000, 1.00000000000000000000000000000000)
sage: L.coordinates(2*L.elliptic_logarithm(E(e3,0),prec=100))
(0.00000000000000000000000000000000, 1.00000000000000000000000000000000)
```

```
sage: a4 = -78*i + 104
sage: a6 = -216*i - 312
sage: E = EllipticCurve([0,0,0,a4,a6])
sage: emb = K.embeddings(CC)[1]
sage: L = E.period_lattice(emb)
sage: P = E(3+2*i, 14-7*i)
sage: L.elliptic_logarithm(P)
0.297147783912228 - 0.546125549639461*I
sage: L.coordinates(L.elliptic_logarithm(P))
```

```
(0.628653378040238, 0.371417754610223)
sage: e1 = 1+3*i; e2 = -4-12*i; e3=-e1-e2
sage: L.coordinates(L.elliptic_logarithm(E(e1,0)))
(0.5000000000000000, 0.5000000000000000)
sage: L.coordinates(L.elliptic_logarithm(E(e2,0)))
(1.0000000000000000, 0.5000000000000000)
sage: L.coordinates(L.elliptic_logarithm(E(e3,0)))
(0.5000000000000000, 0.0000000000000000)
```

**is\_real()**

Return True if this period lattice is real.

EXAMPLES:

```
sage: f = EllipticCurve('11a')
sage: f.period_lattice().is_real()
True
```

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve(K, [0,0,0,i,2*i])
sage: emb = K.embeddings(ComplexField()) [0]
sage: L = E.period_lattice(emb)
sage: L.is_real()
False
```

```
sage: K.<a> = NumberField(x^3-2)
sage: E = EllipticCurve([0,1,0,a,a])
sage: [E.period_lattice(emb).is_real() for emb in K.embeddings(CC)]
[False, False, True]
```

ALGORITHM:

The lattice is real if it is associated to a real embedding; such lattices are stable under conjugation.

**is\_rectangular()**

Return True if this period lattice is rectangular.

---

**Note:** Only defined for real lattices; a `RuntimeError` is raised for non-real lattices.

---

EXAMPLES:

```
sage: f = EllipticCurve('11a')
sage: f.period_lattice().basis()
(1.26920930427955, 0.634604652139777 + 1.45881661693850*I)
sage: f.period_lattice().is_rectangular()
False
```

```
sage: f = EllipticCurve('37b')
sage: f.period_lattice().basis()
(1.08852159290423, 1.76761067023379*I)
sage: f.period_lattice().is_rectangular()
True
```

ALGORITHM:

The period lattice is rectangular precisely if the discriminant of the Weierstrass equation is positive, or equivalently if the number of real components is 2.

**normalised\_basis** (*prec=None, algorithm='sage'*)

Return a normalised basis for this period lattice as a 2-tuple.

INPUT:

- *prec* (default: None) – precision in bits (default precision if None).
- *algorithm* (string, default 'sage') – choice of implementation (for real embeddings only) between 'sage' (native Sage implementation) or 'pari' (use the PARI library: only available for real embeddings).

OUTPUT:

(tuple of Complex)  $(\omega_1, \omega_2)$  where the lattice has the form  $\mathbb{Z}\omega_1 + \mathbb{Z}\omega_2$ . The basis is normalised so that  $\omega_1/\omega_2$  is in the fundamental region of the upper half-plane. For an alternative normalisation for real lattices (with the first period real), use the function `basis()` instead.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice().normalised_basis()
(2.99345864623196, -2.45138938198679*I)
```

```
sage: K.<a> = NumberField(x^3-2)
sage: emb = K.embeddings(RealField())[0]
sage: E = EllipticCurve([0,1,0,a,a])
sage: L = E.period_lattice(emb)
sage: L.normalised_basis(64)
(1.90726488608927255 - 1.34047785962440202*I, -1.90726488608927255 - 1.
↪ 34047785962440202*I)

sage: emb = K.embeddings(ComplexField())[0]
sage: L = E.period_lattice(emb)
sage: w1,w2 = L.normalised_basis(); w1,w2
(-1.37588604166076 - 2.58560946624443*I, -2.10339907847356 + 0.
↪ 428378776460622*I)
sage: L.is_real()
False
sage: tau = w1/w2; tau
0.387694505032876 + 1.30821088214407*I
```

**omega** (*prec=None*)

Returns the real or complex volume of this period lattice.

INPUT:

- *prec* (int or None (default)) -- real precision in bits (default real precision if None)

OUTPUT:

(real) For real lattices, this is the real period times the number of connected components. For non-real lattices it is the complex area.

---

**Note:** If the curve is defined over  $\mathbb{Q}$  and is given by a *minimal* Weierstrass equation, then this is the correct period in the BSD conjecture, i.e., it is the least real period \* 2 when the period lattice is rectangular. More generally the product of this quantity over all embeddings appears in the generalised BSD formula.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice().omega()
5.98691729246392
```

This is not a minimal model:

```
sage: E = EllipticCurve([0, -432*6^2])
sage: E.period_lattice().omega()
0.486109385710056
```

If you were to plug the above omega into the BSD conjecture, you would get nonsense. The following works though:

```
sage: F = E.minimal_model()
sage: F.period_lattice().omega()
0.972218771420113
```

```
sage: K.<a> = NumberField(x^3-2)
sage: emb = K.embeddings(RealField())[0]
sage: E = EllipticCurve([0, 1, 0, a, a])
sage: L = E.period_lattice(emb)
sage: L.omega(64)
3.81452977217854509
```

A complex example (taken from J.E.Cremona and E.Whitley, *Periods of cusp forms and elliptic curves over imaginary quadratic fields*, Mathematics of Computation 62 No. 205 (1994), 407-429):

```
sage: K.<i> = QuadraticField(-1)
sage: E = EllipticCurve([0, 1-i, i, -i, 0])
sage: L = E.period_lattice(K.embeddings(CC)[0])
sage: L.omega()
8.80694160502647
```

**real\_period** (*prec=None, algorithm='sage'*)

Returns the real period of this period lattice.

INPUT:

- *prec* (int or None (default)) – real precision in bits (default real precision if None)
- *algorithm* (string, default 'sage') – choice of implementation (for real embeddings only) between 'sage' (native Sage implementation) or 'pari' (use the PARI library: only available for real embeddings).

---

**Note:** Only defined for real lattices; a RuntimeError is raised for non-real lattices.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.period_lattice().real_period()
2.99345864623196
```

```
sage: K.<a> = NumberField(x^3-2)
sage: emb = K.embeddings(RealField())[0]
sage: E = EllipticCurve([0, 1, 0, a, a])
sage: L = E.period_lattice(emb)
```

```
sage: L.real_period(64)
3.81452977217854509
```

**reduce** (*z*)

Reduce a complex number modulo the lattice

INPUT:

- *z* (complex) – A complex number.

OUTPUT:

(complex) the reduction of *z* modulo the lattice, lying in the fundamental period parallelogram with respect to the lattice basis. For curves defined over the reals (i.e. real embeddings) the output will be real when possible.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: L = E.period_lattice()
sage: w1, w2 = L.basis(prec=100)
sage: P = E([-1, 1])
sage: zP = P.elliptic_logarithm(precision=100); zP
0.47934825019021931612953301006 + 0.98586885077582410221120384908*I
sage: z = zP+10*w1-20*w2; z
25.381473858740770069343110929 - 38.448885180257139986236950114*I
sage: L.reduce(z)
0.47934825019021931612953301006 + 0.98586885077582410221120384908*I
sage: L.elliptic_logarithm(2*P)
0.958696500380439
sage: L.reduce(L.elliptic_logarithm(2*P))
0.958696500380439
sage: L.reduce(L.elliptic_logarithm(2*P)+10*w1-20*w2)
0.958696500380444
```

**sigma** (*z*, *prec=None*, *flag=0*)

Returns the value of the Weierstrass sigma function for this elliptic curve period lattice.

INPUT:

- *z* – a complex number
- **prec** (default: **None**) – **real precision in bits** (default real precision if **None**).
- *flag* –
  - 0: (default) ???;
  - 1: computes an arbitrary determination of  $\log(\text{sigma}(z))$
  - 2, 3: same using the product expansion instead of theta series. ???

---

**Note:** The reason for the ???'s above, is that the PARI documentation for `ellsigma` is very vague. Also this is only implemented for curves defined over  $\mathbf{Q}$ .

---



---

**Todo:** This function does not use any of the `PeriodLattice` functions and so should be moved to `ell_rational_field`.

---

EXAMPLES:



```
sage: EllipticCurve('389a1').period_lattice().sigma(CC(2,1))
2.60912163570108 - 0.200865080824587*I
```

**tau** (*prec=None, algorithm='sage'*)

Return the upper half-plane parameter in the fundamental region.

INPUT:

- *prec* (default: None) – precision in bits (default precision if None).
- *algorithm* (string, default 'sage') – choice of implementation (for real embeddings only) between 'sage' (native Sage implementation) or 'pari' (use the PARI library: only available for real embeddings).

OUTPUT:

(Complex)  $\tau = \omega_1/\omega_2$  where the lattice has the form  $\mathbf{Z}\omega_1 + \mathbf{Z}\omega_2$ , normalised so that  $\tau = \omega_1/\omega_2$  is in the fundamental region of the upper half-plane.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: L = E.period_lattice()
sage: L.tau()
1.22112736076463*I
```

```
sage: K.<a> = NumberField(x^3-2)
sage: emb = K.embeddings(RealField())[0]
sage: E = EllipticCurve([0,1,0,a,a])
sage: L = E.period_lattice(emb)
sage: tau = L.tau(); tau
-0.338718341018919 + 0.940887817679340*I
sage: tau.abs()
1.000000000000000
sage: -0.5 <= tau.real() <= 0.5
True
```

```
sage: emb = K.embeddings(ComplexField())[0]
sage: L = E.period_lattice(emb)
sage: tau = L.tau(); tau
0.387694505032876 + 1.30821088214407*I
sage: tau.abs()
1.36444961115933
sage: -0.5 <= tau.real() <= 0.5
True
```

`sage.schemes.elliptic_curves.period_lattice.extended_agm_iteration(a, b, c)`

Internal function for the extended AGM used in elliptic logarithm computation. INPUT:

- *a, b, c* (real or complex) – three real or complex numbers.

OUTPUT:

(3-tuple)  $(a_0, b_0, c_0)$ , the limit of the iteration  $(a, b, c) \mapsto ((a+b)/2, \sqrt{ab}, (c + \sqrt{(c^2 + b^2 - a^2)})/2)$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.period_lattice import extended_agm_
      ↪ iteration
sage: extended_agm_iteration(RR(1), RR(2), RR(3))
(1.45679103104691, 1.45679103104691, 3.21245294970054)
```

```
sage: extended_agm_iteration(CC(1,2),CC(2,3),CC(3,4))
(1.46242448156430 + 2.47791311676267*I,
1.46242448156430 + 2.47791311676267*I,
3.22202144343535 + 4.28383734262540*I)
```

`sage.schemes.elliptic_curves.period_lattice.normalise_periods(w1, w2)`

Normalise the period basis  $(w_1, w_2)$  so that  $w_1/w_2$  is in the fundamental region.

INPUT:

- $w_1, w_2$  (complex) – two complex numbers with non-real ratio

OUTPUT:

(tuple)  $((\omega'_1, \omega'_2), [a, b, c, d])$  where  $a, b, c, d$  are integers such that

- $ad - bc = \pm 1$ ;
- $(\omega'_1, \omega'_2) = (a\omega_1 + b\omega_2, c\omega_1 + d\omega_2)$ ;
- $\tau = \omega'_1/\omega'_2$  is in the upper half plane;
- $|\tau| \geq 1$  and  $|\Re(\tau)| \leq \frac{1}{2}$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.period_lattice import reduce_tau, _
      ↪ normalise_periods
sage: w1 = CC(1.234, 3.456)
sage: w2 = CC(1.234, 3.456000001)
sage: w1/w2      # in lower half plane!
0.999999999743367 - 9.16334785827644e-11*I
sage: w1w2, abcd = normalise_periods(w1, w2)
sage: a, b, c, d = abcd
sage: w1w2 == (a*w1+b*w2, c*w1+d*w2)
True
sage: w1w2[0]/w1w2[1]
1.23400010389203e9*I
sage: a*d-b*c # note change of orientation
-1
```

`sage.schemes.elliptic_curves.period_lattice.reduce_tau(tau)`

Transform a point in the upper half plane to the fundamental region.

INPUT:

- $\tau$  (complex) – a complex number with positive imaginary part

OUTPUT:

(tuple)  $(\tau', [a, b, c, d])$  where  $a, b, c, d$  are integers such that

- $ad - bc = 1$ ;
- $\tau' = (a\tau + b)/(c\tau + d)$ ;
- $|\tau'| \geq 1$ ;
- $|\Re(\tau')| \leq \frac{1}{2}$ .

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.period_lattice import reduce_tau
sage: reduce_tau(CC(1.23, 3.45))
(0.2300000000000000 + 3.450000000000000*I, [1, -1, 0, 1])
sage: reduce_tau(CC(1.23, 0.0345))
(-0.463960069171512 + 1.35591888067914*I, [-5, 6, 4, -5])
sage: reduce_tau(CC(1.23, 0.0000345))
(0.1300000000001761 + 2.89855072463768*I, [13, -16, 100, -123])

```

### 15.11.18 Regions in fundamental domains of period lattices

This module is used to represent sub-regions of a fundamental parallelogram of the period lattice of an elliptic curve, used in computing minimum height bounds.

In particular, these are the approximating sets  $S^{\{v\}}$  in section 3.2 of Thotsaphon Thongjunthug's Ph.D. Thesis and paper [TT].

AUTHORS:

- Robert Bradshaw (2010): initial version
- John Cremona (2014): added some docstrings and doctests

REFERENCES:

**class** sage.schemes.elliptic\_curves.period\_lattice\_region.**PeriodicRegion**

Bases: object

EXAMPLES:

```

sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
↪PeriodicRegion
sage: S = PeriodicRegion(CDF(2), CDF(2*I), np.zeros((4, 4)))
sage: S.plot()
Graphics object consisting of 1 graphics primitive
sage: data = np.zeros((4, 4))
sage: data[1,1] = True
sage: S = PeriodicRegion(CDF(2), CDF(2*I+1), data)
sage: S.plot()
Graphics object consisting of 5 graphics primitives

```

**border** (*raw=True*)

Returns the boundary of this region as set of tile boundaries.

If *raw* is true, returns a list with respect to the internal bitmap, otherwise returns complex intervals covering the border.

EXAMPLES:

```

sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
↪PeriodicRegion
sage: data = np.zeros((4, 4))
sage: data[1, 1] = True
sage: PeriodicRegion(CDF(1), CDF(I), data).border()
[(1, 1, 0), (2, 1, 0), (1, 1, 1), (1, 2, 1)]
sage: PeriodicRegion(CDF(2), CDF(I-1/2), data).border()
[(1, 1, 0), (2, 1, 0), (1, 1, 1), (1, 2, 1)]

```

```

sage: PeriodicRegion(CDF(1), CDF(I), data).border(raw=False)
[0.25000000000000000? + 1.?*I,
 0.50000000000000000? + 1.?*I,
 1.? + 0.25000000000000000?*I,
 1.? + 0.50000000000000000?*I]
sage: PeriodicRegion(CDF(2), CDF(I-1/2), data).border(raw=False)
[0.3? + 1.?*I,
 0.8? + 1.?*I,
 1.? + 0.25000000000000000?*I,
 1.? + 0.50000000000000000?*I]

sage: data[1:3, 2] = True
sage: PeriodicRegion(CDF(1), CDF(I), data).border()
[(1, 1, 0), (2, 1, 0), (1, 1, 1), (1, 2, 0), (1, 3, 1), (3, 2, 0), (2, 2, 1), ↵
↵(2, 3, 1)]

```

**contract** (*corners=True*)

Opposite (but not inverse) of expand; removes neighbors of complement.

EXAMPLES:

```

sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import ↵
↵PeriodicRegion
sage: data = np.zeros((10, 10))
sage: data[1:4, 1:4] = True
sage: S = PeriodicRegion(CDF(1), CDF(I + 1/2), data)
sage: S.plot()
Graphics object consisting of 13 graphics primitives
sage: S.contract().plot()
Graphics object consisting of 5 graphics primitives
sage: S.contract().data.sum()
1
sage: S.contract().contract().is_empty()
True

```

**data**

**ds()**

Returns the sides of each parallelogram tile.

EXAMPLES:

```

sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import ↵
↵PeriodicRegion
sage: data = np.zeros((4, 4))
sage: S = PeriodicRegion(CDF(2), CDF(2*I), data, full=False)
sage: S.ds()
(0.5, 0.25*I)
sage: _ = S._ensure_full()
sage: S.ds()
(0.5, 0.25*I)

sage: data = np.zeros((8, 8))
sage: S = PeriodicRegion(CDF(1), CDF(I + 1/2), data)
sage: S.ds()
(0.125, 0.0625 + 0.125*I)

```

**expand**(*corners=True*)

Returns a region containing this region by adding all neighbors of internal tiles.

EXAMPLES:

```
sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
      ↪ PeriodicRegion
sage: data = np.zeros((4, 4))
sage: data[1,1] = True
sage: S = PeriodicRegion(CDF(1), CDF(I + 1/2), data)
sage: S.plot()
Graphics object consisting of 5 graphics primitives
sage: S.expand().plot()
Graphics object consisting of 13 graphics primitives
sage: S.expand().data
array([[1, 1, 1, 0],
       [1, 1, 1, 0],
       [1, 1, 1, 0],
       [0, 0, 0, 0]], dtype=int8)
sage: S.expand(corners=False).plot()
Graphics object consisting of 13 graphics primitives
sage: S.expand(corners=False).data
array([[0, 1, 0, 0],
       [1, 1, 1, 0],
       [0, 1, 0, 0],
       [0, 0, 0, 0]], dtype=int8)
```

**full**

**innermost\_point**()

Returns a point well inside the region, specifically the center of (one of) the last tile(s) to be removed on contraction.

EXAMPLES:

```
sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
      ↪ PeriodicRegion
sage: data = np.zeros((10, 10))
sage: data[1:4, 1:4] = True
sage: data[1, 0:8] = True
sage: S = PeriodicRegion(CDF(1), CDF(I+1/2), data)
sage: S.innermost_point()
0.375 + 0.25*I
sage: S.plot() + point(S.innermost_point())
Graphics object consisting of 24 graphics primitives
```

**is\_empty**()

Returns whether this region is empty.

EXAMPLES:

```
sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
      ↪ PeriodicRegion
sage: data = np.zeros((4, 4))
sage: PeriodicRegion(CDF(2), CDF(2*I), data).is_empty()
True
sage: data[1,1] = True
```

```
sage: PeriodicRegion(CDF(2), CDF(2*I), data).is_empty()
False
```

**plot** (*\*\*kws*)

Plots this region in the fundamental lattice. If full is False plots only the lower half. Note that the true nature of this region is periodic.

EXAMPLES:

```
sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
↪PeriodicRegion
sage: data = np.zeros((10, 10))
sage: data[2, 2:8] = True
sage: data[2:5, 2] = True
sage: data[3, 3] = True
sage: S = PeriodicRegion(CDF(1), CDF(I + 1/2), data)
sage: plot(S) + plot(S.expand(), rgbcolor=(1, 0, 1), thickness=2)
Graphics object consisting of 46 graphics primitives
```

**refine** (*condition=None, times=1*)

Recursive function to refine the current tiling.

INPUT:

- *condition* (function, default None) - if not None, only keep tiles in the refinement which satisfy the condition.
- *times* (int, default 1) - the number of times to refine; each refinement step halves the mesh size.

OUTPUT:

The refined PeriodicRegion.

EXAMPLES:

```
sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
↪PeriodicRegion
sage: data = np.zeros((4, 4))
sage: S = PeriodicRegion(CDF(2), CDF(2*I), data, full=False)
sage: S.ds()
(0.5, 0.25*I)
sage: S = S.refine()
sage: S.ds()
(0.25, 0.125*I)
sage: S = S.refine(2)
sage: S.ds()
(0.125, 0.0625*I)
```

**verify** (*condition*)

Given a condition that should hold for every line segment on the boundary, verify that it actually does so.

INPUT:

- *condition* (function) - a boolean-valued function on  $C$ .

OUTPUT:

True or False according to whether the condition holds for all lines on the boundary.

EXAMPLES:

```

sage: import numpy as np
sage: from sage.schemes.elliptic_curves.period_lattice_region import _
↪PeriodicRegion
sage: data = np.zeros((4, 4))
sage: data[1, 1] = True
sage: S = PeriodicRegion(CDF(1), CDF(I), data)
sage: S.border()
[(1, 1, 0), (2, 1, 0), (1, 1, 1), (1, 2, 1)]
sage: condition = lambda z: z.real().abs() < 0.5
sage: S.verify(condition)
False
sage: condition = lambda z: z.real().abs() < 1
sage: S.verify(condition)
True

```

w1

w2

Modularity and  $L$ -series over  $\mathbb{Q}$ .

### 15.11.19 Modular parametrization of elliptic curves over $\mathbb{Q}$

By the work of Taylor–Wiles et al. it is known that there is a surjective morphism

$$\phi_E : X_0(N) \rightarrow E.$$

from the modular curve  $X_0(N)$ , where  $N$  is the conductor of  $E$ . The map sends the cusp  $\infty$  to the origin of  $E$ .

EXAMPLES:

```

sage: phi = EllipticCurve('11a1').modular_parametrization()
sage: phi
Modular parameterization from the upper half plane to Elliptic Curve defined by y^2 +
↪y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: phi(0.5+CDF(I))
(285684.320516... + 7.0...e-11*I : 1.526964169...e8 + 5.6...e-8*I : 1.000000000000000)
sage: phi.power_series(prec = 7)
(q^-2 + 2*q^-1 + 4 + 5*q + 8*q^2 + q^3 + 7*q^4 + O(q^5), -q^-3 - 3*q^-2 - 7*q^-1 - 13
↪- 17*q - 26*q^2 - 19*q^3 + O(q^4))

```

AUTHORS:

- Chris Wuthrich (02/10) - moved from `ell_rational_field.py`.

**class** `sage.schemes.elliptic_curves.modular_parametrization.ModularParameterization` ( $E$ )  
 This class represents the modular parametrization of an elliptic curve

$$\phi_E : X_0(N) \rightarrow E.$$

Evaluation is done by passing through the lattice representation of  $E$ .

EXAMPLES:

```

sage: phi = EllipticCurve('11a1').modular_parametrization()
sage: phi
Modular parameterization from the upper half plane to Elliptic Curve defined by y^
↪2 + y = x^3 - x^2 - 10*x - 20 over Rational Field

```

**curve()**

Return the curve associated to this modular parametrization.

EXAMPLES:

```
sage: E = EllipticCurve('15a')
sage: phi = E.modular_parametrization()
sage: phi.curve() is E
True
```

**map\_to\_complex\_numbers** ( $z$ ,  $prec=None$ )Evaluate `self` at a point  $z \in X_0(N)$  where  $z$  is given by a representative in the upper half plane, returning a point in the complex numbers.All computations are done with `prec` bits of precision. If `prec` is not given, use the precision of  $z$ . Use `self(z)` to compute the image of  $z$  on the Weierstrass equation of the curve.

EXAMPLES:

```
sage: E = EllipticCurve('37a'); phi = E.modular_parametrization()
sage: tau = (sqrt(7)*I - 17)/74
sage: z = phi.map_to_complex_numbers(tau); z
0.929592715285395 - 1.22569469099340*I
sage: E.elliptic_exponential(z)
(...e-16 - ...e-16*I : ...e-16 + ...e-16*I : 1.000000000000000)
sage: phi(tau)
(...e-16 - ...e-16*I : ...e-16 + ...e-16*I : 1.000000000000000)
```

**power\_series** ( $prec=20$ )

Return the power series of this modular parametrization.

The curve must be a minimal model. The `prec` parameter determines the number of significant terms. This means that  $X$  will be given up to  $O(q^{(prec-2)})$  and  $Y$  will be given up to  $O(q^{(prec-3)})$ .OUTPUT: A list of two Laurent series  $[X(x), Y(x)]$  of degrees -2, -3 respectively, which satisfy the equation of the elliptic curve. There are modular functions on  $\Gamma_0(N)$  where  $N$  is the conductor.

The series should satisfy the differential equation

$$\frac{dX}{2Y + a_1X + a_3} = \frac{f(q) dq}{q}$$

where  $f$  is `self.curve().q_expansion()`.

EXAMPLES:

```
sage: E = EllipticCurve('389a1')
sage: phi = E.modular_parametrization()
sage: X, Y = phi.power_series(prec=10)
sage: X
q^-2 + 2*q^-1 + 4 + 7*q + 13*q^2 + 18*q^3 + 31*q^4 + 49*q^5 + 74*q^6 + 111*q^7
↪ 7 + O(q^8)
sage: Y
-q^-3 - 3*q^-2 - 8*q^-1 - 17 - 33*q - 61*q^2 - 110*q^3 - 186*q^4 - 320*q^5 -
↪ 528*q^6 + O(q^7)
sage: X, Y = phi.power_series()
sage: X
q^-2 + 2*q^-1 + 4 + 7*q + 13*q^2 + 18*q^3 + 31*q^4 + 49*q^5 + 74*q^6 + 111*q^7
↪ 173*q^8 + 251*q^9 + 379*q^10 + 560*q^11 + 824*q^12 + 1199*q^13 + 1773*q^14
↪ 2548*q^15 + 3722*q^16 + 5374*q^17 + O(q^18)
sage: Y
```



```
-q^-3 - 3*q^-2 - 8*q^-1 - 17 - 33*q - 61*q^2 - 110*q^3 - 186*q^4 - 320*q^5 -
↪ 528*q^6 - 861*q^7 - 1383*q^8 - 2218*q^9 - 3472*q^10 - 5451*q^11 - 8447*q^12 ↪
↪ - 13020*q^13 - 19923*q^14 - 30403*q^15 - 46003*q^16 + O(q^17)
```

The following should give 0, but only approximately:

```
sage: q = X.parent().gen()
sage: E.defining_polynomial()(X,Y,1) + O(q^11) == 0
True
```

Note that below we have to change variable from  $x$  to  $q$ :

```
sage: a1,_,a3,_,_ = E.a_invariants()
sage: f = E.q_expansion(17)
sage: q = f.parent().gen()
sage: f/q == (X.derivative()/(2*Y+a1*X+a3))
True
```

### 15.11.20 Modular symbols attached to elliptic curves over $\mathbb{Q}$

To an elliptic curve  $E$  over the rational numbers with conductor  $N$ , one can associate a space of modular symbols of level  $N$ , because  $E$  is known to be modular. The space is two-dimensional and contains a subspace on which complex conjugation acts as multiplication by  $+1$  and one on which it acts by  $-1$ .

There are two implementations of modular symbols, one within Sage and the other in Cremona's `eclib` library. One can choose here which one is used.

Associated to  $E$  there is a canonical generator in each space. They are maps  $[.]^+$  and  $[.]^-$ , both  $\mathbb{Q} \rightarrow \mathbb{Q}$ . They are normalized such that

$$[r]^+ \Omega^+ + [r]^- \Omega^- = \int_{\infty}^r 2\pi i f(z) dz$$

where  $f$  is the newform associated to the isogeny class of  $E$  and  $\Omega^+$  is the smallest positive period of the Néron differential of  $E$  and  $\Omega^-$  is the smallest positive purely imaginary period. Note that it depends on  $E$  rather than on its isogeny class.

From `eclib` version v20161230, both plus and minus symbols are available and are correctly normalized. In the Sage implementation, the computation of the space provides initial generators which are not necessarily correctly normalized; here we implement two methods that try to find the correct scaling factor.

Modular symbols are used to compute  $p$ -adic  $L$ -functions.

EXAMPLES:

```
sage: E = EllipticCurve("19a1")
sage: m = E.modular_symbol()
sage: m(0)
1/3
sage: m(1/17)
-2/3
sage: m2 = E.modular_symbol(-1, implementation="sage")
sage: m2(0)
0
sage: m2(1/5)
1/2
sage: V = E.modular_symbol_space()
```

```

sage: V
Modular Symbols subspace of dimension 1 of Modular Symbols space of dimension 2 for
↳Gamma_0(19) of weight 2 with sign 1 over Rational Field
sage: V.q_eigenform(30)
q - 2*q^3 - 2*q^4 + 3*q^5 - q^7 + q^9 + 3*q^11 + 4*q^12 - 4*q^13 - 6*q^15 + 4*q^16 -
↳3*q^17 + q^19 - 6*q^20 + 2*q^21 + 4*q^25 + 4*q^27 + 2*q^28 + 6*q^29 + O(q^30)

```

For more details on modular symbols consult the following

REFERENCES:

AUTHORS:

- William Stein (2007): first version
- Chris Wuthrich (2008): add scaling and reference to eclib
- John Cremona (2016): reworked eclib interface

**class** sage.schemes.elliptic\_curves.ell\_modular\_symbols.**ModularSymbol**

Bases: sage.structure.sage\_object.SageObject

A modular symbol attached to an elliptic curve, which is the map  $\mathbb{Q} \rightarrow \mathbb{Q}$  obtained by sending  $r$  to the normalized symmetrized (or anti-symmetrized) integral  $\infty$  to  $r$ .

This is as defined in [MaTaTe], but normalized to depend on the curve and not only its isogeny class as in [StWu].

See the documentation of `E.modular_symbol()` in elliptic curves over the rational numbers for help.

**base\_ring()**

Return the base ring for this modular symbol.

EXAMPLES:

```

sage: m = EllipticCurve('11a1').modular_symbol()
sage: m.base_ring()
Rational Field

```

**elliptic\_curve()**

Return the elliptic curve of this modular symbol.

EXAMPLES:

```

sage: m = EllipticCurve('11a1').modular_symbol()
sage: m.elliptic_curve()
Elliptic Curve defined by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field

```

**sign()**

Return the sign of this elliptic curve modular symbol.

EXAMPLES:

```

sage: m = EllipticCurve('11a1').modular_symbol()
sage: m.sign()
1
sage: m = EllipticCurve('11a1').modular_symbol(sign=-1, implementation="sage")
sage: m.sign()
-1

```

**class** `sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolECLIB` (*E*, *sign*)  
 Bases: `sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbol`

Modular symbols attached to *E* using `eclib`.

Note that the normalization used within `eclib` differs from the normalization chosen here by a factor of 2 in the case of elliptic curves with negative discriminant (with one real component) since the convention there is to write the above integral as  $[r]^+x + [r]^-yi$ , where the lattice is  $\langle 2x, x + yi \rangle$ , so that  $\Omega^+ = 2x$  and  $\Omega^- = 2yi$ . We allow for this below.

INPUT:

- *E* - an elliptic curve
- *sign* - an integer, -1 or 1

EXAMPLES:

```
sage: import sage.schemes.elliptic_curves.ell_modular_symbols
sage: E=EllipticCurve('11a1')
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolECLIB(E,+1)
sage: M
Modular symbol with sign 1 over Rational Field attached to Elliptic Curve defined_
↳by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: M(0)
1/5
sage: E=EllipticCurve('11a2')
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolECLIB(E,+1)
sage: M(0)
1
```

This is a rank 1 case with vanishing positive twists:

```
sage: E=EllipticCurve('121b1')
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolECLIB(E,+1)
sage: M(0)
0
sage: M(1/7)
1/2

sage: M = EllipticCurve('121d1').modular_symbol(implementation="eclib")
sage: M(0)
2

sage: E = EllipticCurve('15a1')
sage: [C.modular_symbol(implementation="eclib")(0) for C in E.isogeny_class()]
[1/4, 1/8, 1/4, 1/2, 1/8, 1/16, 1/2, 1]
```

Since [trac ticket #10256](#), the interface for negative modular symbols in `eclib` is available:

```
sage: E = EllipticCurve('11a1')
sage: Mplus = E.modular_symbol(+1); Mplus
Modular symbol with sign 1 over Rational Field attached to Elliptic Curve defined_
↳by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: [Mplus(1/i) for i in [1..11]]
[1/5, -4/5, -3/10, 7/10, 6/5, 6/5, 7/10, -3/10, -4/5, 1/5, 0]
sage: Mminus = E.modular_symbol(-1); Mminus
Modular symbol with sign -1 over Rational Field attached to Elliptic Curve_
↳defined by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
```

```
sage: [Mminus(1/i) for i in [1..11]]
[0, 0, 1/2, 1/2, 0, 0, -1/2, -1/2, 0, 0, 0]
```

The scaling factor relative to eclib's normalization is 1/2 for curves of negative discriminant:

```
sage: [E.discriminant() for E in cremona_curves([14])]
[-21952, 941192, -1835008, -28, 25088, 98]
sage: [E.modular_symbol()._scaling for E in cremona_curves([14])]
[1/2, 1, 1/2, 1/2, 1, 1]
```

TESTS (for trac ticket #10236):

```
sage: E = EllipticCurve('11a1')
sage: m = E.modular_symbol(implementation="eclib")
sage: m(1/7)
7/10
sage: m(0)
1/5
```

```
class sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolSage(E,
                                                                    sign,
                                                                    nor-
                                                                    mal-
                                                                    ize='L_ratio')
```

Bases: `sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbol`

Modular symbols attached to  $E$  using sage.

INPUT:

- $E$  – an elliptic curve
- $sign$  – an integer, -1 or 1
- $normalize$  – either 'L\_ratio' (default), 'period', or 'none'; For 'L\_ratio', the modular symbol is correctly normalized by comparing it to the quotient of  $L(E, 1)$  by the least positive period for the curve and some small twists. The normalization 'period' uses the `integral_period_map` for modular symbols and is known to be equal to the above normalization up to the sign and a possible power of 2. For 'none', the modular symbol is almost certainly not correctly normalized, i.e. all values will be a fixed scalar multiple of what they should be. But the initial computation of the modular symbol is much faster, though evaluation of it after computing it won't be any faster.

EXAMPLES:

```
sage: E=EllipticCurve('11a1')
sage: import sage.schemes.elliptic_curves.ell_modular_symbols
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolSage(E,+1)
sage: M
Modular symbol with sign 1 over Rational Field attached to Elliptic Curve defined_
↪by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
sage: M(0)
1/5
sage: E=EllipticCurve('11a2')
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolSage(E,+1)
sage: M(0)
1
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolSage(E,-1)
sage: M(1/3)
1/2
```

This is a rank 1 case with vanishing positive twists. The modular symbol is adjusted by -2:

```
sage: E=EllipticCurve('121b1')
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.ModularSymbolSage(E,-1,
↪normalize='L_ratio')
sage: M(1/3)
1
sage: M._scaling
-1

sage: M = EllipticCurve('121d1').modular_symbol(implementation="sage")
sage: M(0)
2
sage: M = EllipticCurve('121d1').modular_symbol(implementation="sage", normalize=
↪'none')
sage: M(0)
1

sage: E = EllipticCurve('15a1')
sage: [C.modular_symbol(implementation="sage", normalize='L_ratio')(0) for C in E.
↪isogeny_class()]
[1/4, 1/8, 1/4, 1/2, 1/8, 1/16, 1/2, 1]
sage: [C.modular_symbol(implementation="sage", normalize='period')(0) for C in E.
↪isogeny_class()]
[1/8, 1/16, 1/8, 1/4, 1/16, 1/32, 1/4, 1/2]
sage: [C.modular_symbol(implementation="sage", normalize='none')(0) for C in E.
↪isogeny_class()]
[1, 1, 1, 1, 1, 1, 1, 1]
```

`sage.schemes.elliptic_curves.ell_modular_symbols.modular_symbol_space(E,`

*sign,*  
*base\_ring,*  
*bound=None)*

Creates the space of modular symbols of a given sign over a give base\_ring, attached to the isogeny class of the elliptic curve E.

INPUT:

- E - an elliptic curve over  $\mathbb{Q}$
- sign - integer, -1, 0, or 1
- base\_ring - ring
- bound - (default: None) maximum number of Hecke operators to use to cut out modular symbols factor. If None, use enough to provably get the correct answer.

OUTPUT: a space of modular symbols

EXAMPLES:

```
sage: import sage.schemes.elliptic_curves.ell_modular_symbols
sage: E=EllipticCurve('11a1')
sage: M=sage.schemes.elliptic_curves.ell_modular_symbols.modular_symbol_space(E,-
↪1,GF(37))
sage: M
Modular Symbols space of dimension 1 for Gamma_0(11) of weight 2 with sign -1_
↪over Finite Field of size 37
```

### 15.11.21 L-series for elliptic curves

AUTHORS:

- Simon Spicer (2014-08-15) - Added LFunctionZeroSum class interface method
- Jeroen Demeyer (2013-10-17) - Compute L series with arbitrary precision instead of floats.
- William Stein et al. (2005 and later)

**class** sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell(*E*)

Bases: sage.structure.sage\_object.SageObject

An elliptic curve  $L$ -series.

**L1\_vanishes**()

Returns whether or not  $L(E, 1) = 0$ . The result is provably correct if the Manin constant of the associated optimal quotient is  $\leq 2$ . This hypothesis on the Manin constant is true for all curves of conductor  $\leq 40000$  (by Cremona) and all semistable curves (i.e., squarefree conductor).

ALGORITHM: see `L_ratio()`.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20]) # 11A = X_0(11)
sage: E.lseries().L1_vanishes()
False
sage: E = EllipticCurve([0, -1, 1, 0, 0]) # X_1(11)
sage: E.lseries().L1_vanishes()
False
sage: E = EllipticCurve([0, 0, 1, -1, 0]) # 37A (rank 1)
sage: E.lseries().L1_vanishes()
True
sage: E = EllipticCurve([0, 1, 1, -2, 0]) # 389A (rank 2)
sage: E.lseries().L1_vanishes()
True
sage: E = EllipticCurve([0, 0, 1, -38, 90]) # 361A (CM curve)
sage: E.lseries().L1_vanishes()
True
sage: E = EllipticCurve([0, -1, 1, -2, -1]) # 141C (13-isogeny)
sage: E.lseries().L1_vanishes()
False
```

AUTHOR: William Stein, 2005-04-20.

**L\_ratio**()

Returns the ratio  $L(E, 1)/\Omega$  as an exact rational number. The result is *provably* correct if the Manin constant of the associated optimal quotient is  $\leq 2$ . This hypothesis on the Manin constant is true for all semistable curves (i.e., squarefree conductor), by a theorem of Mazur from his *Rational Isogenies of Prime Degree* paper.

EXAMPLES:

```
sage: E = EllipticCurve([0, -1, 1, -10, -20]) # 11A = X_0(11)
sage: E.lseries().L_ratio()
1/5
sage: E = EllipticCurve([0, -1, 1, 0, 0]) # X_1(11)
sage: E.lseries().L_ratio()
1/25
sage: E = EllipticCurve([0, 0, 1, -1, 0]) # 37A (rank 1)
sage: E.lseries().L_ratio()
```

```

0
sage: E = EllipticCurve([0, 1, 1, -2, 0])      # 389A (rank 2)
sage: E.lseries().L_ratio()
0
sage: E = EllipticCurve([0, 0, 1, -38, 90])    # 361A (CM curve)
sage: E.lseries().L_ratio()
0
sage: E = EllipticCurve([0, -1, 1, -2, -1])    # 141C (13-isogeny)
sage: E.lseries().L_ratio()
1
sage: E = EllipticCurve(RationalField(), [1, 0, 0, 1/24624, 1/886464])
sage: E.lseries().L_ratio()
2

```

See [trac ticket #3651](#) and [trac ticket #15299](#):

```

sage: EllipticCurve([0,0,0,-193^2,0]).sha().an()
4
sage: EllipticCurve([1, 0, 1, -131, 558]).sha().an() # long time
1.000000000000000

```

ALGORITHM: Compute the root number. If it is -1 then  $L(E, s)$  vanishes to odd order at 1, hence vanishes. If it is +1, use a result about modular symbols and Mazur's *Rational Isogenies* paper to determine a provably correct bound (assuming Manin constant is  $\leq 2$ ) so that we can determine whether  $L(E, 1) = 0$ .

AUTHOR: William Stein, 2005-04-20.

**at1** ( $k=None$ ,  $prec=None$ )

Compute  $L(E, 1)$  using  $k$  terms of the series for  $L(E, 1)$  as explained in Section 7.5.3 of Henri Cohen's book *A Course in Computational Algebraic Number Theory*. If the argument  $k$  is not specified, then it defaults to  $\sqrt{N}$ , where  $N$  is the conductor.

INPUT:

- $k$  – number of terms of the series. If zero or `None`, use  $k = \sqrt{N}$ , where  $N$  is the conductor.
- $prec$  – numerical precision in bits. If zero or `None`, use a reasonable automatic default.

OUTPUT:

A tuple of real numbers ( $L$ ,  $err$ ) where  $L$  is an approximation for  $L(E, 1)$  and  $err$  is a bound on the error in the approximation.

This function is disjoint from the PARI `elllseries` command, which is for a similar purpose. To use that command (via the PARI C library), simply type `E.pari_mincurve().elllseries(1)`.

ALGORITHM:

- Compute the root number  $\epsilon$ . If it is -1, return 0.
- Compute the Fourier coefficients  $a_n$ , for  $n$  up to and including  $k$ .
- Compute the sum

$$2 \cdot \sum_{n=1}^k \frac{a_n}{n} \cdot \exp(-2 \cdot \pi i \cdot n / \sqrt{N}),$$

where  $N$  is the conductor of  $E$ .

- Compute a bound on the tail end of the series, which is

$$2e^{-2\pi(k+1)/\sqrt{N}}/(1 - e^{-2\pi/\sqrt{N}}).$$

For a proof see [Grigov-Jorza-Patrascu-Patrikis-Stein].

EXAMPLES:

```
sage: L, err = EllipticCurve('11a1').lseries().at1()
sage: L, err
(0.253804, 0.000181444)
sage: parent(L)
Real Field with 24 bits of precision
sage: E = EllipticCurve('37b')
sage: E.lseries().at1()
(0.7257177, 0.000800697)
sage: E.lseries().at1(100)
(0.7256810619361527823362055410263965487367603361763, 1.52469e-45)
sage: L, err = E.lseries().at1(100, prec=128)
sage: L
0.72568106193615278233620554102639654873
sage: parent(L)
Real Field with 128 bits of precision
sage: err
1.70693e-37
sage: parent(err)
Real Field with 24 bits of precision and rounding RNDU
```

Rank 1 through 3 elliptic curves:

```
sage: E = EllipticCurve('37a1')
sage: E.lseries().at1()
(0.0000000, 0.000000)
sage: E = EllipticCurve('389a1')
sage: E.lseries().at1()
(-0.001769566, 0.00911776)
sage: E = EllipticCurve('5077a1')
sage: E.lseries().at1()
(0.0000000, 0.000000)
```

**deriv\_at1** ( $k=None$ ,  $prec=None$ )

Compute  $L'(E, 1)$  using  $k$  terms of the series for  $L'(E, 1)$ , under the assumption that  $L(E, 1) = 0$ .

The algorithm used is from Section 7.5.3 of Henri Cohen's book *A Course in Computational Algebraic Number Theory*.

INPUT:

- $k$  – number of terms of the series. If zero or `None`, use  $k = \sqrt{N}$ , where  $N$  is the conductor.
- $prec$  – numerical precision in bits. If zero or `None`, use a reasonable automatic default.

OUTPUT:

A tuple of real numbers ( $L1$ ,  $err$ ) where  $L1$  is an approximation for  $L'(E, 1)$  and  $err$  is a bound on the error in the approximation.

**Warning:** This function only makes sense if  $L(E)$  has positive order of vanishing at 1, or equivalently if  $L(E, 1) = 0$ .



ALGORITHM:

- Compute the root number  $\epsilon$ . If it is 1, return 0.
- Compute the Fourier coefficients  $a_n$ , for  $n$  up to and including  $k$ .
- Compute the sum

$$2 \cdot \sum_{n=1}^k (a_n/n) \cdot E_1(2\pi n/\sqrt{N}),$$

where  $N$  is the conductor of  $E$ , and  $E_1$  is the exponential integral function.

- Compute a bound on the tail end of the series, which is

$$2e^{-2\pi(k+1)/\sqrt{N}}/(1 - e^{-2\pi/\sqrt{N}}).$$

For a proof see [Grigorov-Jorza-Patrascu-Patrikis-Stein]. This is exactly the same as the bound for the approximation to  $L(E, 1)$  produced by `at1()`.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.lseries().deriv_at1()
(0.3059866, 0.000801045)
sage: E.lseries().deriv_at1(100)
(0.3059997738340523018204836833216764744526377745903, 1.52493e-45)
sage: E.lseries().deriv_at1(1000)
(0.305999773834052301820483683321676474452637774590771998..., 2.75031e-449)
```

With less numerical precision, the error is bounded by numerical accuracy:

```
sage: L, err = E.lseries().deriv_at1(100, prec=64)
sage: L, err
(0.305999773834052302, 5.55318e-18)
sage: parent(L)
Real Field with 64 bits of precision
sage: parent(err)
Real Field with 24 bits of precision and rounding RNDU
```

Rank 2 and rank 3 elliptic curves:

```
sage: E = EllipticCurve('389a1')
sage: E.lseries().deriv_at1()
(0.0000000, 0.000000)
sage: E = EllipticCurve((1, 0, 1, -131, 558)) # curve 59450i1
sage: E.lseries().deriv_at1()
(-0.00010911444, 0.142428)
sage: E.lseries().deriv_at1(4000)
(6.990...e-50, 1.31318e-43)
```

**dokchitser** (*prec=53, max\_imaginary\_part=0, max\_asymp\_coeffs=40, algorithm='gp'*)

Return interface to Tim Dokchitser's program for computing with the  $L$ -series of this elliptic curve; this provides a way to compute Taylor expansions and higher derivatives of  $L$ -series.

INPUT:

- `prec` – integer (bits precision)
- `max_imaginary_part` – real number

- `max_asymp_coeffs` – integer
- `algorithm` – string: ‘gp’ or ‘magma’

---

**Note:** If `algorithm=‘magma’`, then the precision is in digits rather than bits and the object returned is a Magma L-series, which has different functionality from the Sage L-series.

---

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: L = E.lseries().dokchitser()
sage: L(2)
0.381575408260711
sage: L = E.lseries().dokchitser(algorithm='magma')           # optional - magma
sage: L.Evaluate(2)                                           # optional - magma
0.38157540826071121129371040958008663667709753398892116
```

If the curve has too large a conductor, it isn’t possible to compute with the  $L$ -series using this command. Instead a `RuntimeError` is raised:

```
sage: e = EllipticCurve([1, 1, 0, -63900, -1964465932632])
sage: L = e.lseries().dokchitser(15)
Traceback (most recent call last):
...
RuntimeError: Unable to create L-series, due to precision or other limits in_
↳PARI.
```

**elliptic\_curve()**

Return the elliptic curve that this  $L$ -series is attached to.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: L = E.lseries()
sage: L.elliptic_curve()
Elliptic Curve defined by  $y^2 + y = x^3 + x^2 - 2x$  over Rational Field
```

**sympow**( $n$ ,  $prec$ )

Return  $L(\text{Sym}^{(n)}(E, \text{edge}))$  to  $prec$  digits of precision.

INPUT:

- $n$  – integer
- $prec$  – integer

OUTPUT:

- string – real number to  $prec$  digits of precision as a string.

---

**Note:** Before using this function for the first time for a given  $n$ , you may have to type `sympow('new_data <n>')`, where `<n>` is replaced by your value of  $n$ . This command takes a long time to run.

---

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: a = E.lseries().sympow(2,16)      # not tested - requires precomputing
↪ "sympow('-new_data 2') "
sage: a                                  # not tested
'2.492262044273650E+00'
sage: RR(a)                              # not tested
2.49226204427365

```

**sympow\_derivs** (*n*, *prec*, *d*)

Return 0-th to *d*-th derivatives of  $L(\text{Sym}^{(n)}(E, \text{edge}))$  to *prec* digits of precision.

INPUT:

- *n* – integer
- *prec* – integer
- *d* – integer

OUTPUT:

- a string, exactly as output by sympow

---

**Note:** To use this function you may have to run a few commands like `sympow('-new_data 1d2')`, each which takes a few minutes. If this function fails it will indicate what commands have to be run.

---

EXAMPLES:

```

sage: E = EllipticCurve('37a')
sage: print(E.lseries().sympow_derivs(1,16,2))      # not tested -- requires_
↪ precomputing "sympow('-new_data 2') "
sympow 1.018 RELEASE (c) Mark Watkins --- see README and COPYING for details
Minimal model of curve is [0,0,1,-1,0]
At 37: Inertia Group is C1 MULTIPLICATIVE REDUCTION
Conductor is 37
sp 1: Conductor at 37 is 1+0, root number is 1
sp 1: Euler factor at 37 is 1+1*x
1st sym power conductor is 37, global root number is -1
NT 1d0: 35
NT 1d1: 32
NT 1d2: 28
Maximal number of terms is 35
Done with small primes 1049
Computed: 1d0 1d1 1d2
Checked out: 1d1
  1n0: 3.837774351482055E-01
  1w0: 3.777214305638848E-01
  1n1: 3.059997738340522E-01
  1w1: 3.059997738340524E-01
  1n2: 1.519054910249753E-01
  1w2: 1.545605024269432E-01

```

**taylor\_series** (*a*=1, *prec*=53, *series\_prec*=6, *var*='z')

Return the Taylor series of this *L*-series about *a* to the given precision (in bits) and the number of terms.

The output is a series in *var*, where you should view *var* as equal to  $s - a$ . Thus this function returns the formal power series whose coefficients are  $L^{(n)}(a)/n!$ .

INPUT:

- $a$  – complex number
- $\text{prec}$  – integer, precision in bits (default 53)
- $\text{series\_prec}$  – integer (default 6)
- $\text{var}$  – variable (default 'z')

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: L = E.lseries()
sage: L.taylor_series(series_prec=3)
-1.27685190980159e-23 + (7.23588070754027e-24)*z + 0.759316500288427*z^2 +
↪O(z^3) # 32-bit
-2.72911738151096e-23 + (1.54658247036311e-23)*z + 0.759316500288427*z^2 +
↪O(z^3) # 64-bit
```

**twist\_values** ( $s, d_{\min}, d_{\max}$ )

Return values of  $L(E, s, \chi_d)$  for each quadratic character  $\chi_d$  for  $d_{\min} \leq d \leq d_{\max}$ .

---

**Note:** The L-series is normalized so that the center of the critical strip is 1.

---

INPUT:

- $s$  – complex numbers
- $d_{\min}$  – integer
- $d_{\max}$  – integer

OUTPUT:

- list of pairs  $(d, L(E, s, \chi_d))$

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: vals = E.lseries().twist_values(1, -12, -4)
sage: vals # abs tol 1e-15
[(-11, 1.47824342), (-8, 8.9590946e-18), (-7, 1.85307619), (-4, 2.45138938)]
sage: F = E.quadratic_twist(-8)
sage: F.rank()
1
sage: F = E.quadratic_twist(-7)
sage: F.rank()
0
```

**twist\_zeros** ( $n, d_{\min}, d_{\max}$ )

Return first  $n$  real parts of nontrivial zeros of  $L(E, s, \chi_d)$  for each quadratic character  $\chi_d$  with  $d_{\min} \leq d \leq d_{\max}$ .

---

**Note:** The L-series is normalized so that the center of the critical strip is 1.

---

INPUT:

- $n$  – integer
- $d_{\min}$  – integer

- `dmax` – integer

OUTPUT:

- **dict** – keys are the discriminants  $d$ , and values are list of corresponding zeros.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.lseries().twist_zeros(3, -4, -3)           # long time
{-4: [1.60813783, 2.96144840, 3.89751747], -3: [2.06170900, 3.48216881, 4.
↪45853219]}
```

**values\_along\_line** ( $s_0, s_1, \text{number\_samples}$ )

Return values of  $L(E, s)$  at `number_samples` equally-spaced sample points along the line from  $s_0$  to  $s_1$  in the complex plane.

---

**Note:** The  $L$ -series is normalized so that the center of the critical strip is 1.

---

INPUT:

- $s_0, s_1$  – complex numbers
- `number_samples` – integer

OUTPUT:

**list** – list of pairs  $(s, L(E, s))$ , where the  $s$  are equally spaced sampled points on the line from  $s_0$  to  $s_1$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.lseries().values_along_line(1, 0.5 + 20*I, 5)
[(0.500000000, ...),
 (0.400000000 + 4.00000000*I, 3.31920245 - 2.60028054*I),
 (0.300000000 + 8.00000000*I, -0.886341185 - 0.422640337*I),
 (0.200000000 + 12.00000000*I, -3.50558936 - 0.108531690*I),
 (0.100000000 + 16.00000000*I, -3.87043288 - 1.88049411*I)]
```

**zero\_sums** ( $N=None$ )

Return an `LFunctionZeroSum` class object for efficient computation of sums over the zeros of self. This can be used to bound analytic rank from above without having to compute with the  $L$ -series directly.

INPUT:

- $N$  – (default: `None`) If not `None`, the conductor of the elliptic curve attached to self. This is passable so that zero sum computations can be done on curves for which the conductor has been precomputed.

OUTPUT:

A `LFunctionZeroSum_EllipticCurve` instance.

EXAMPLES:

```
sage: E = EllipticCurve("5077a")
sage: E.lseries().zero_sums()
Zero sum estimator for L-function attached to Elliptic Curve defined by y^2 +
↪y = x^3 - 7*x + 6 over Rational Field
```

**zeros** (*n*)

Return the imaginary parts of the first  $n$  nontrivial zeros on the critical line of the  $L$ -function in the upper half plane, as 32-bit reals.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.lseries().zeros(2)
[0.000000000, 5.00317001]

sage: a = E.lseries().zeros(20)           # long time
sage: point([(1,x) for x in a])           # graph (long time)
Graphics object consisting of 1 graphics primitive
```

**AUTHOR:** – Uses Rubinstein’s  $L$ -functions calculator.

**zeros\_in\_interval** (*x*, *y*, *stepsize*)

Return the imaginary parts of (most of) the nontrivial zeros on the critical line  $\Re(s) = 1$  with positive imaginary part between  $x$  and  $y$ , along with a technical quantity for each.

INPUT:

- $x$ – positive floating point number
- $y$ – positive floating point number
- $stepsize$  – positive floating point number

OUTPUT:

- list of pairs  $(zero, S(T))$ .

Rubinstein writes: The first column outputs the imaginary part of the zero, the second column a quantity related to  $S(T)$  (it increases roughly by 2 whenever a sign change, i.e. pair of zeros, is missed). Higher up the critical strip you should use a smaller stepsize so as not to miss zeros.

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.lseries().zeros_in_interval(6, 10, 0.1) # long time
[(6.87039122, 0.248922780), (8.01433081, -0.140168533), (9.93309835, -0.
↪129943029)]
```

### 15.11.22 Heegner points on elliptic curves over the rational numbers

AUTHORS:

- William Stein (August 2009)– most of the initial version
- Robert Bradshaw (July 2009) – an early version of some specific code

EXAMPLES:

```
sage: E = EllipticCurve('433a')
sage: P = E.heegner_point(-8, 3)
sage: z = P.point_exact(201); z
(-4/3 : 1/27*a - 4/27 : 1)
sage: parent(z)
Abelian group of points on Elliptic Curve defined by y^2 + x*y = x^3 + 1 over Number_
↪Field in a with defining polynomial x^2 - 44*x + 1159
```

```

sage: parent(z[0]).discriminant()
-3
sage: E.quadratic_twist(-3).rank()
1
sage: K.<a> = QuadraticField(-8)
sage: K.factor(3)
(Fractional ideal (1/2*a + 1)) * (Fractional ideal (-1/2*a + 1))

```

Next try an inert prime:

```

sage: K.factor(5)
Fractional ideal (5)
sage: P = E.heegner_point(-8,5)
sage: z = P.point_exact(300)
sage: z[0].charpoly().factor()
(x^6 + x^5 - 1/4*x^4 + 19/10*x^3 + 31/20*x^2 - 7/10*x + 49/100)^2
sage: z[1].charpoly().factor()
x^12 - x^11 + 6/5*x^10 - 33/40*x^9 - 89/320*x^8 + 3287/800*x^7 - 5273/1600*x^6 + 993/
↪ 4000*x^5 + 823/320*x^4 - 2424/625*x^3 + 12059/12500*x^2 + 3329/25000*x + 123251/
↪ 250000
sage: f = P.x_poly_exact(300); f
x^6 + x^5 - 1/4*x^4 + 19/10*x^3 + 31/20*x^2 - 7/10*x + 49/100
sage: f.discriminant().factor()
-1 * 2^-9 * 5^-9 * 7^2 * 281^2 * 1021^2

```

We find some Mordell-Weil generators in the rank 1 case using Heegner points:

```

sage: E = EllipticCurve('43a'); P = E.heegner_point(-7)
sage: P.x_poly_exact()
x
sage: P.point_exact()
(0 : 0 : 1)

sage: E = EllipticCurve('997a')
sage: E.rank()
1
sage: E.heegner_discriminants_list(10)
[-19, -23, -31, -35, -39, -40, -52, -55, -56, -59]
sage: P = E.heegner_point(-19)
sage: P.x_poly_exact()
x - 141/49
sage: P.point_exact()
(141/49 : -162/343 : 1)

```

Here we find that the Heegner point generates a subgroup of index 3:

```

sage: E = EllipticCurve('92b1')
sage: E.heegner_discriminants_list(1)
[-7]
sage: P = E.heegner_point(-7); z = P.point_exact(); z
(0 : 1 : 1)
sage: E.regulator()
0.0498083972980648
sage: z.height()
0.448275575682583
sage: P = E(1,1); P # a generator
(1 : 1 : 1)
sage: -3*P

```

```
(0 : 1 : 1)
sage: E.tamagawa_product()
3
```

The above is consistent with the following analytic computation:

```
sage: E.heegner_index(-7)
3.0000?
```

**class** sage.schemes.elliptic\_curves.heegner.**GaloisAutomorphism**(parent)

Bases: sage.structure.sage\_object.SageObject

An abstract automorphism of a ring class field.

---

**Todo:** make *GaloisAutomorphism* derive from GroupElement, so that one gets powers for free, etc.

---

**domain()**

Return the domain of this automorphism.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: s = E.heegner_point(-7,5).ring_class_field().galois_group().complex_
↪conjugation()
sage: s.domain()
Ring class field extension of QQ[sqrt(-7)] of conductor 5
```

**parent()**

Return the parent of this automorphism, which is a Galois group of a ring class field.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: s = E.heegner_point(-7,5).ring_class_field().galois_group().complex_
↪conjugation()
sage: s.parent()
Galois group of Ring class field extension of QQ[sqrt(-7)] of conductor 5
```

**class** sage.schemes.elliptic\_curves.heegner.**GaloisAutomorphismComplexConjugation**(parent)

Bases: *sage.schemes.elliptic\_curves.heegner.GaloisAutomorphism*

The complex conjugation automorphism of a ring class field.

EXAMPLES:

```
sage: conj = heegner_point(37,-7,5).ring_class_field().galois_group().complex_
↪conjugation()
sage: conj
Complex conjugation automorphism of Ring class field extension of QQ[sqrt(-7)] of
↪conductor 5
sage: conj.domain()
Ring class field extension of QQ[sqrt(-7)] of conductor 5
```

**order()**

EXAMPLES:



```

sage: conj = heegner_point(37,-7,5).ring_class_field().galois_group().complex_
↪conjugation()
sage: conj.order()
2

```

**class** sage.schemes.elliptic\_curves.heegner.**GaloisAutomorphismQuadraticForm**(parent, quadratic\_form, alpha=None)

Bases: *sage.schemes.elliptic\_curves.heegner.GaloisAutomorphism*

An automorphism of a ring class field defined by a quadratic form.

EXAMPLES:

```

sage: H = heegner_points(389,-20,3)
sage: sigma = H.ring_class_field().galois_group(H.quadratic_field())[0]; sigma
Class field automorphism defined by x^2 + 45*y^2
sage: type(sigma)
<class 'sage.schemes.elliptic_curves.heegner.GaloisAutomorphismQuadraticForm'>
sage: loads(dumps(sigma)) == sigma
True

```

**alpha()**

Optional data that specified element corresponding element of  $(\mathcal{O}_K/c\mathcal{O}_K)^*/(\mathbb{Z}/c\mathbb{Z})^*$ , via class field theory.

This is a generator of the ideal corresponding to this automorphism.

EXAMPLES:

```

sage: K3 = heegner_points(389,-52,3).ring_class_field()
sage: K1 = heegner_points(389,-52,1).ring_class_field()
sage: G = K3.galois_group(K1)
sage: orb = sorted([g.alpha() for g in G]); orb # random (the sign depends on,
↪the database being installed or not)
[1, 1/2*sqrt_minus_52 + 1, -1/2*sqrt_minus_52, 1/2*sqrt_minus_52 - 1]
sage: sorted([x^2 for x in orb]) # this is just for testing
[-13, -sqrt_minus_52 - 12, sqrt_minus_52 - 12, 1]

sage: K5 = heegner_points(389,-52,5).ring_class_field()
sage: K1 = heegner_points(389,-52,1).ring_class_field()
sage: G = K5.galois_group(K1)
sage: orb = sorted([g.alpha() for g in G]); orb # random (the sign depends on,
↪the database being installed or not)
[1, -1/2*sqrt_minus_52, 1/2*sqrt_minus_52 + 1, 1/2*sqrt_minus_52 - 1, 1/
↪2*sqrt_minus_52 - 2, -1/2*sqrt_minus_52 - 2]
sage: sorted([x^2 for x in orb]) # just for testing
[-13, -sqrt_minus_52 - 12, sqrt_minus_52 - 12, -2*sqrt_minus_52 - 9, 2*sqrt_
↪minus_52 - 9, 1]

```

**ideal()**

Return ideal of ring of integers of quadratic imaginary field corresponding to this quadratic form. This is the ideal

$$I = \left( A, \frac{-B+c\sqrt{D}}{2} \right) \mathcal{O}_K.$$

EXAMPLES:

```

sage: E = EllipticCurve('389a'); F = E.heegner_point(-20, 3).ring_class_field()
sage: G = F.galois_group(F.quadratic_field())
sage: G[1].ideal()
Fractional ideal (2, 1/2*sqrt_minus_20 + 1)
sage: [s.ideal().gens() for s in G]
[(1, 3/2*sqrt_minus_20), (2, 3/2*sqrt_minus_20 - 1), (5, 3/2*sqrt_minus_20),
↪ (7, 3/2*sqrt_minus_20 - 2)]

```

**order()**

Return the multiplicative order of this Galois group automorphism.

EXAMPLES:

```

sage: K3 = heegner_points(389, -52, 3).ring_class_field()
sage: K1 = heegner_points(389, -52, 1).ring_class_field()
sage: G = K3.galois_group(K1)
sage: sorted([g.order() for g in G])
[1, 2, 4, 4]
sage: K5 = heegner_points(389, -52, 5).ring_class_field()
sage: K1 = heegner_points(389, -52, 1).ring_class_field()
sage: G = K5.galois_group(K1)
sage: sorted([g.order() for g in G])
[1, 2, 3, 3, 6, 6]

```

**p1\_element()**

Return element of the projective line corresponding to this automorphism.

This only makes sense if this automorphism is in the Galois group  $\text{Gal}(K_c/K_1)$ .

EXAMPLES:

```

sage: K3 = heegner_points(389, -52, 3).ring_class_field()
sage: K1 = heegner_points(389, -52, 1).ring_class_field()
sage: G = K3.galois_group(K1)
sage: sorted([g.p1_element() for g in G])
[(0, 1), (1, 0), (1, 1), (1, 2)]

sage: K5 = heegner_points(389, -52, 5).ring_class_field()
sage: K1 = heegner_points(389, -52, 1).ring_class_field()
sage: G = K5.galois_group(K1)
sage: sorted([g.p1_element() for g in G])
[(0, 1), (1, 0), (1, 1), (1, 2), (1, 3), (1, 4)]

```

**quadratic\_form()**

Return reduced quadratic form corresponding to this Galois automorphism.

EXAMPLES:

```

sage: H = heegner_points(389, -20, 3); s = H.ring_class_field().galois_group(H.
↪quadratic_field())[0]
sage: s.quadratic_form()
x^2 + 45*y^2

```

**class** sage.schemes.elliptic\_curves.heegner.**GaloisGroup**(field, base=Rational Field)

Bases: sage.structure.sage\_object.SageObject

A Galois group of a ring class field.

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: G = E.heegner_point(-7,5).ring_class_field().galois_group(); G
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
sage: G.field()
Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
sage: G.cardinality()
12
sage: G.complex_conjugation()
Complex conjugation automorphism of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of
↳conductor 5

```

**base\_field()**

Return the base field, which the field fixed by all the automorphisms in this Galois group.

**EXAMPLES:**

```

sage: x = heegner_point(37,-7,5)
sage: Kc = x.ring_class_field(); Kc
Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
sage: K = x.quadratic_field()
sage: G = Kc.galois_group(); G
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
sage: G.base_field()
Rational Field
sage: G.cardinality()
12
sage: Kc.absolute_degree()
12
sage: G = Kc.galois_group(K); G
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
↳over Number Field in sqrt_minus_7 with defining polynomial  $x^2 + 7$ 
sage: G.cardinality()
6
sage: G.base_field()
Number Field in sqrt_minus_7 with defining polynomial  $x^2 + 7$ 
sage: G = Kc.galois_group(Kc); G
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
↳over Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
sage: G.cardinality()
1
sage: G.base_field()
Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5

```

**cardinality()**

Return the cardinality of this Galois group.

**EXAMPLES:**

```

sage: E = EllipticCurve('389a')
sage: G = E.heegner_point(-7,5).ring_class_field().galois_group(); G
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 5
sage: G.cardinality()
12
sage: G = E.heegner_point(-7).ring_class_field().galois_group()
sage: G.cardinality()
2
sage: G = E.heegner_point(-7,55).ring_class_field().galois_group()
sage: G.cardinality()

```

120

**complex\_conjugation()**

Return the automorphism of `self` determined by complex conjugation. The base field must be the rational numbers.

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: G = E.heegner_point(-7,5).ring_class_field().galois_group()
sage: G.complex_conjugation()
Complex conjugation automorphism of Ring class field extension of QQ[sqrt(-
↪7)] of conductor 5
```

**field()**

Return the ring class field that this Galois group acts on.

EXAMPLES:

```
sage: G = heegner_point(389,-7,5).ring_class_field().galois_group()
sage: G.field()
Ring class field extension of QQ[sqrt(-7)] of conductor 5
```

**is\_kolyvagin()**

Return True if conductor  $c$  is prime to the discriminant of the quadratic field,  $c$  is squarefree and each prime dividing  $c$  is inert.

EXAMPLES:

```
sage: K5 = heegner_points(389,-52,5).ring_class_field()
sage: K1 = heegner_points(389,-52,1).ring_class_field()
sage: K5.galois_group(K1).is_kolyvagin()
True
sage: K7 = heegner_points(389,-52,7).ring_class_field()
sage: K7.galois_group(K1).is_kolyvagin()
False
sage: K25 = heegner_points(389,-52,25).ring_class_field()
sage: K25.galois_group(K1).is_kolyvagin()
False
```

**kolyvagin\_generators()**

Assuming this Galois group  $G$  is of the form  $G = \text{Gal}(K_c/K_1)$ , with  $c = p_1 \dots p_n$  satisfying the Kolyvagin hypothesis, this function returns noncanonical choices of lifts of generators for each of the cyclic factors of  $G$  corresponding to the primes dividing  $c$ . Thus the  $i$ -th returned value is an element of  $G$  that maps to the identity element of  $\text{Gal}(K_p/K_1)$  for all  $p \neq p_i$  and to a choice of generator of  $\text{Gal}(K_{p_i}/K_1)$ .

OUTPUT:

- list of elements of `self`

EXAMPLES:

```
sage: K3 = heegner_points(389,-52,3).ring_class_field()
sage: K1 = heegner_points(389,-52,1).ring_class_field()
sage: G = K3.galois_group(K1)
sage: G.kolyvagin_generators()
(Class field automorphism defined by 9*x^2 - 6*x*y + 14*y^2,)
sage: K5 = heegner_points(389,-52,5).ring_class_field()
```

```
sage: K1 = heegner_points(389, -52, 1).ring_class_field()
sage: G = K5.galois_group(K1)
sage: G.kolyvagin_generators()
(Class field automorphism defined by 17*x^2 - 14*x*y + 22*y^2,)
```

**lift\_of\_hilbert\_class\_field\_galois\_group()**

Assuming this Galois group  $G$  is of the form  $G = \text{Gal}(K_c/K)$ , this function returns noncanonical choices of lifts of the elements of the quotient group  $\text{Gal}(K_1/K)$ .

OUTPUT:

- tuple of elements of self

EXAMPLES:

```
sage: K5 = heegner_points(389, -52, 5).ring_class_field()
sage: G = K5.galois_group(K5.quadratic_field())
sage: G.lift_of_hilbert_class_field_galois_group()
(Class field automorphism defined by x^2 + 325*y^2, Class field automorphism_
↪defined by 2*x^2 + 2*x*y + 163*y^2)
sage: G.cardinality()
12
sage: K5.quadratic_field().class_number()
2
```

**class** sage.schemes.elliptic\_curves.heegner.**HeegnerPoint** ( $N, D, c$ )

Bases: sage.structure.sage\_object.SageObject

A Heegner point of level  $N$ , discriminant  $D$  and conductor  $c$  is any point on a modular curve or elliptic curve that is concocted in some way from a quadratic imaginary  $\tau$  in the upper half plane with  $\Delta(\tau) = Dc = \Delta(N\tau)$ .

EXAMPLES:

```
sage: x = sage.schemes.elliptic_curves.heegner.HeegnerPoint(389, -7, 13); x
Heegner point of level 389, discriminant -7, and conductor 13
sage: type(x)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPoint'>
sage: loads(dumps(x)) == x
True
```

**conductor()**

Return the conductor of this Heegner point.

EXAMPLES:

```
sage: heegner_point(389, -7, 5).conductor()
5
sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67, 7); P
Kolyvagin point of discriminant -67 and conductor 7 on elliptic curve of_
↪conductor 37
sage: P.conductor()
7
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5); P.conductor()
5
```

**discriminant()**

Return the discriminant of the quadratic imaginary field associated to this Heegner point.

EXAMPLES:

```

sage: heegner_point(389, -7, 5).discriminant()
-7
sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67, 7); P
Kolyvagin point of discriminant -67 and conductor 7 on elliptic curve of_
↳conductor 37
sage: P.discriminant()
-67
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5); P.discriminant()
-7

```

**level()**

Return the level of this Heegner point, which is the level of the modular curve  $X_0(N)$  on which this is a Heegner point.

EXAMPLES:

```

sage: heegner_point(389, -7, 5).level()
389

```

**quadratic\_field()**

Return the quadratic number field of discriminant  $D$ .

EXAMPLES:

```

sage: x = heegner_point(37, -7, 5)
sage: x.quadratic_field()
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7

sage: E = EllipticCurve('37a'); P = E.heegner_point(-40)
sage: P.quadratic_field()
Number Field in sqrt_minus_40 with defining polynomial x^2 + 40
sage: P.quadratic_field() is P.quadratic_field()
True
sage: type(P.quadratic_field())
<class 'sage.rings.number_field.number_field.NumberField_quadratic_with_
↳category'>

```

**quadratic\_order()**

Return the order in the quadratic imaginary field of conductor  $c$ , where  $c$  is the conductor of this Heegner point.

EXAMPLES:

```

sage: heegner_point(389, -7, 5).quadratic_order()
Order in Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
sage: heegner_point(389, -7, 5).quadratic_order().basis()
[1, 5*sqrt_minus_7]

sage: E = EllipticCurve('37a'); P = E.heegner_point(-40, 11)
sage: P.quadratic_order()
Order in Number Field in sqrt_minus_40 with defining polynomial x^2 + 40
sage: P.quadratic_order().basis()
[1, 11*sqrt_minus_40]

```

**ring\_class\_field()**

Return the ring class field associated to this Heegner point. This is an extension  $K_c$  over  $K$ , where  $K$  is the quadratic imaginary field and  $c$  is the conductor associated to this Heegner point. This Heegner point

is defined over  $K_c$  and the Galois group  $Gal(K_c/K)$  acts transitively on the Galois conjugates of this Heegner point.

EXAMPLES:

```
sage: E = EllipticCurve('389a'); K.<a> = QuadraticField(-5)
sage: len(K.factor(5))
1
sage: len(K.factor(23))
2
sage: E.heegner_point(-7, 5).ring_class_field().degree_over_K()
6
sage: E.heegner_point(-7, 23).ring_class_field().degree_over_K()
22
sage: E.heegner_point(-7, 5*23).ring_class_field().degree_over_K()
132
sage: E.heegner_point(-7, 5^2).ring_class_field().degree_over_K()
30
sage: E.heegner_point(-7, 7).ring_class_field().degree_over_K()
7
```

**class** sage.schemes.elliptic\_curves.heegner.**HeegnerPointOnEllipticCurve**(*E*, *x*, *check=True*)

Bases: *sage.schemes.elliptic\_curves.heegner.HeegnerPoint*

A Heegner point on a curve associated to an order in a quadratic imaginary field.

EXAMPLES:

```
sage: E = EllipticCurve('37a'); P = E.heegner_point(-7,5); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of conductor 37
sage: type(P)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPointOnEllipticCurve'>
```

**conjugates\_over\_K()**

Return the  $Gal(K_c/K)$  conjugates of this Heegner point.

EXAMPLES:

```
sage: E = EllipticCurve('77a')
sage: y = E.heegner_point(-52,5); y
Heegner point of discriminant -52 and conductor 5 on elliptic curve of_
↳conductor 77
sage: print([z.quadratic_form() for z in y.conjugates_over_K()])
[77*x^2 + 52*x*y + 13*y^2, 154*x^2 + 206*x*y + 71*y^2, 539*x^2 + 822*x*y +_
↳314*y^2, 847*x^2 + 1284*x*y + 487*y^2, 1001*x^2 + 52*x*y + y^2, 1078*x^2 +_
↳822*x*y + 157*y^2, 1309*x^2 + 360*x*y + 25*y^2, 1309*x^2 + 2054*x*y + 806*y^_
↳2, 1463*x^2 + 976*x*y + 163*y^2, 2233*x^2 + 2824*x*y + 893*y^2, 2387*x^2 +_
↳2054*x*y + 442*y^2, 3619*x^2 + 3286*x*y + 746*y^2]
sage: y.quadratic_form()
77*x^2 + 52*x*y + 13*y^2
```

**curve()**

Return the elliptic curve on which this is a Heegner point.

EXAMPLES:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5)
sage: P.curve()
Elliptic Curve defined by y^2 + y = x^3 + x^2 - 2*x over Rational Field
```

```
sage: P.curve() is E
True
```

**heegner\_point\_on\_X0N()**

Return Heegner point on  $X_0(N)$  that maps to this Heegner point on  $E$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a'); P = E.heegner_point(-7,5); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of_
↪conductor 37
sage: P.heegner_point_on_X0N()
Heegner point 5/74*sqrt(-7) - 11/74 of discriminant -7 and conductor 5 on X_
↪0(37)
```

**kolyvagin\_cohomology\_class** ( $n=None$ )

Return the Kolyvagin class associated to this Heegner point.

INPUT:

- $n$  – positive integer that divides the gcd of  $a_p$  and  $p+1$  for all  $p$  dividing the conductor. If  $n$  is None, choose the largest valid  $n$ .

EXAMPLES:

```
sage: y = EllipticCurve('389a').heegner_point(-7,5)
sage: y.kolyvagin_cohomology_class(3)
Kolyvagin cohomology class c(5) in H^1(K,E[3])
```

**kolyvagin\_point()**

Return the Kolyvagin point corresponding to this Heegner point.

This is the point obtained by applying the Kolyvagin operator  $J_c I_c$  in the group ring of the Galois group to this Heegner point. It is a point that defines an element of  $H^1(K, E[n])$ , under certain hypotheses on  $n$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a1'); y = E.heegner_point(-7); y
Heegner point of discriminant -7 on elliptic curve of conductor 37
sage: P = y.kolyvagin_point(); P
Kolyvagin point of discriminant -7 on elliptic curve of conductor 37
sage: P.numerical_approx() # abs tol 1e-15
(-3.36910401903861e-16 - 2.22076195576076e-16*I : 3.33066907387547e-16 + 2.
↪22076195576075e-16*I : 1.000000000000000)
```

**map\_to\_complex\_numbers** ( $prec=53$ )

Return the point in the subfield  $M$  of the complex numbers (well defined only modulo the period lattice) corresponding to this Heegner point.

EXAMPLES:

We compute a nonzero Heegner point over a ring class field on a curve of rank 2:

```
sage: E = EllipticCurve('389a'); y = E.heegner_point(-7,5)
sage: y.map_to_complex_numbers()
1.49979679635196 + 0.369156204821526*I
sage: y.map_to_complex_numbers(100)
1.4997967963519640592142411892 + 0.36915620482152626830089145962*I
sage: y.map_to_complex_numbers(10)
1.5 + 0.37*I
```



Here we see that the Heegner point is 0 since it lies in the lattice:

```
sage: E = EllipticCurve('389a'); y = E.heegner_point(-7)
sage: y.map_to_complex_numbers(10)
0.0034 - 3.9*I
sage: y.map_to_complex_numbers()
4.71844785465692e-15 - 3.94347540310330*I
sage: E.period_lattice().basis()
(2.49021256085505, 1.97173770155165*I)
sage: 2*E.period_lattice().basis()[1]
3.94347540310330*I
```

You can also directly coerce to the complex field:

```
sage: E = EllipticCurve('389a'); y = E.heegner_point(-7)
sage: z = ComplexField(100)(y); z # real part approx. 0
-... - 3.9434754031032964088448153963*I
sage: E.period_lattice().elliptic_exponential(z)
(0.00000000000000000000000000000000 : 1.000000000000000000000000 : 0.
↪ 000000000000000000000000)
```

```
numerical_approx (prec=53, algorithm=None)
```

Return a numerical approximation to this Heegner point computed using a working precision of `prec` bits.

**Warning:** The answer is *not* provably correct to prec bits! A priori, due to rounding and other errors, it is possible that not a single digit is correct.

INPUT:

- `prec` – (default: `None`) the working precision

EXAMPLES:

```
sage: E = EllipticCurve('37a'); P = E.heegner_point(-7); P
Heegner point of discriminant -7 on elliptic curve of conductor 37
sage: P.numerical_approx() # abs tol 1e-15
(-3.36910401903861e-16 - 2.22076195576076e-16*I : 3.33066907387547e-16 + 2.
↪22076195576075e-16*I : 1.000000000000000)
sage: P.numerical_approx(10) # expect random digits
(0.0030 - 0.0028*I : -0.0030 + 0.0028*I : 1.0)
sage: P.numerical_approx(100)[0] # expect random digits
8.4...e-31 + 6.0...e-31*I
sage: E = EllipticCurve('37a'); P = E.heegner_point(-40); P
Heegner point of discriminant -40 on elliptic curve of conductor 37
sage: P.numerical_approx() # abs tol 1e-14
(-3.15940603400359e-16 + 1.41421356237309*I : 1.000000000000000 - 1.
↪41421356237309*I : 1.000000000000000)
```

A rank 2 curve, where all Heegner points of conductor 1 are 0:

```
sage: E = EllipticCurve('389a'); E.rank()
2
sage: P = E.heegner_point(-7); P
Heegner point of discriminant -7 on elliptic curve of conductor 389
sage: P.numerical_approx()
(0.0000000000000000 : 1.0000000000000000 : 0.0000000000000000)
```

However, Heegner points of bigger conductor are often nonzero:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of
↳conductor 389
sage: numerical_approx(P)
(0.675507556926806 + 0.344749649302635*I : -0.377142931401887 + 0.
↳843366227137146*I : 1.000000000000000)
sage: P.numerical_approx()
(0.6755075569268... + 0.3447496493026...*I : -0.3771429314018... + 0.
↳8433662271371...*I : 1.000000000000000)
sage: E.heegner_point(-7, 11).numerical_approx()
(0.1795583794118... + 0.02035501750912...*I : -0.5573941377055... + 0.
↳2738940831635...*I : 1.000000000000000)
sage: E.heegner_point(-7, 13).numerical_approx()
(1.034302915374... - 3.302744319777...*I : 1.323937875767... + 6.908264226850.
↳...*I : 1.000000000000000)
```

We find (probably) the defining polynomial of the  $x$ -coordinate of  $P$ , which defines a class field. The shape of the discriminant below is strong confirmation – but not proof – that this polynomial is correct:

```
sage: f = P.numerical_approx(70)[0].algdep(6); f
1225*x^6 + 1750*x^5 - 21675*x^4 - 380*x^3 + 110180*x^2 - 129720*x + 48771
sage: f.discriminant().factor()
2^6 * 3^2 * 5^11 * 7^4 * 13^2 * 19^6 * 199^2 * 719^2 * 26161^2
```

**point\_exact** (*prec=53, algorithm='lll', var='a', optimize=False*)

Return exact point on the elliptic curve over a number field defined by computing this Heegner point to the given number of bits of precision. A `ValueError` is raised if the precision is clearly insignificant to define a point on the curve.

**Warning:** It is in theory possible for this function to not raise a `ValueError`, find a point on the curve, but via some very unlikely coincidence that point is not actually this Heegner point.

**Warning:** Currently we make an arbitrary choice of  $y$ -coordinate for the lift of the  $x$ -coordinate.

INPUT:

- `prec` – integer (default: 53)
- `algorithm` – see the description of the `algorithm` parameter for the `x_poly_exact` method.
- `var` – string (default: 'a')
- `optimize` – bool (default: False) if `True`, try to optimize defining polynomial for the number field that the point is defined over. Off by default, since this can be very expensive.

EXAMPLES:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of
↳conductor 389
sage: z = P.point_exact(100, optimize=True)
sage: z[1].charpoly()
x^12 + 6*x^11 + 90089/1715*x^10 + 71224/343*x^9 + 52563964/588245*x^8 -
↳483814934/588245*x^7 - 156744579/16807*x^6 - 2041518032/84035*x^5 +
↳1259355443184/14706125*x^4 + 3094420220918/14706125*x^3 + 123060442043827/
↳367653125*x^2 + 82963044474852/367653125*x + 211679465261391/1838265625
```

```

sage: f = P.numerical_approx(500)[1].algdep(12); f / f.leading_coefficient()
x^12 + 6*x^11 + 90089/1715*x^10 + 71224/343*x^9 + 52563964/588245*x^8 -
↪ 483814934/588245*x^7 - 156744579/16807*x^6 - 2041518032/84035*x^5 +
↪ 1259355443184/14706125*x^4 + 3094420220918/14706125*x^3 + 123060442043827/
↪ 367653125*x^2 + 82963044474852/367653125*x + 211679465261391/1838265625

sage: E = EllipticCurve('5077a')
sage: P = E.heegner_point(-7)
sage: P.point_exact(prec=100)
(0 : 1 : 0)

```

**quadratic\_form()**

Return the integral primitive positive definite binary quadratic form associated to this Heegner point.

EXAMPLES:

```

sage: EllipticCurve('389a').heegner_point(-7, 5).quadratic_form()
389*x^2 + 147*x*y + 14*y^2

sage: P = EllipticCurve('389a').heegner_point(-7, 5, (778, 925, 275)); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of
↪ conductor 389
sage: P.quadratic_form()
778*x^2 + 925*x*y + 275*y^2

```

**satisfies\_kolyvagin\_hypothesis** ( $n=None$ )

Return True if this Heegner point and  $n$  satisfy the Kolyvagin hypothesis, i.e., that each prime dividing the conductor  $c$  of `self` is inert in  $K$  and coprime to  $ND$ . Moreover, if  $n$  is not None, also check that for each prime  $p$  dividing  $c$  we have that  $n \mid \gcd(a_p(E), p+1)$ .

INPUT:

$n$  – positive integer

EXAMPLES:

```

sage: EllipticCurve('389a').heegner_point(-7).satisfies_kolyvagin_hypothesis()
True
sage: EllipticCurve('389a').heegner_point(-7, 5).satisfies_kolyvagin_
↪ hypothesis()
True
sage: EllipticCurve('389a').heegner_point(-7, 11).satisfies_kolyvagin_
↪ hypothesis()
False

```

**tau()**

Return  $\tau$  in the upper half plane that maps via the modular parametrization to this Heegner point.

EXAMPLES:

```

sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5)
sage: P.tau()
5/778*sqrt_minus_7 - 147/778

```

**x\_poly\_exact** ( $prec=53, algorithm='lll'$ )

Return irreducible polynomial over the rational numbers satisfied by the  $x$  coordinate of this Heegner point. A `ValueError` is raised if the precision is clearly insignificant to define a point on the curve.

**Warning:** It is in theory possible for this function to not raise a `ValueError`, find a polynomial, but via some very unlikely coincidence that point is not actually this Heegner point.

INPUT:

- `prec` – integer (default: 53)
- **algorithm** – ‘conjugates’ or ‘lll’ (default); if ‘conjugates’, compute numerically all the conjugates  $y[i]$  of the Heegner point and construct the characteristic polynomial as the product  $f(X) = (X - y[i])$ . If ‘lll’, compute only one of the conjugates  $y[0]$ , then uses the LLL algorithm to guess  $f(X)$ .

EXAMPLES:

We compute some  $x$ -coordinate polynomials of some conductor 1 Heegner points:

```
sage: E = EllipticCurve('37a')
sage: v = E.heegner_discriminants_list(10)
sage: [E.heegner_point(D).x_poly_exact() for D in v]
[x, x, x^2 + 2, x^5 - x^4 + x^3 + x^2 - 2*x + 1, x - 6, x^7 - 2*x^6 + 9*x^5 -
↪ 10*x^4 - x^3 + 8*x^2 - 5*x + 1, x^3 + 5*x^2 + 10*x + 4, x^4 - 10*x^3 + 10*x^
↪ 2 + 12*x - 12, x^8 - 5*x^7 + 7*x^6 + 13*x^5 - 10*x^4 - 4*x^3 + x^2 - 5*x +
↪ 7, x^6 - 2*x^5 + 11*x^4 - 24*x^3 + 30*x^2 - 16*x + 4]
```

We compute  $x$ -coordinate polynomials for some Heegner points of conductor bigger than 1 on a rank 2 curve:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7, 5); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of
↪ conductor 389
sage: P.x_poly_exact()
Traceback (most recent call last):
...
ValueError: insufficient precision to determine Heegner point (fails
↪ discriminant test)
sage: P.x_poly_exact(75)
x^6 + 10/7*x^5 - 867/49*x^4 - 76/245*x^3 + 3148/35*x^2 - 25944/245*x + 48771/
↪ 1225
sage: E.heegner_point(-7, 11).x_poly_exact(300)
x^10 + 282527/52441*x^9 + 27049007420/2750058481*x^8 - 22058564794/
↪ 2750058481*x^7 - 140054237301/2750058481*x^6 + 696429998952/30250643291*x^5
↪ + 2791387923058/30250643291*x^4 - 3148473886134/30250643291*x^3 +
↪ 1359454055022/30250643291*x^2 - 250620385365/30250643291*x + 181599685425/
↪ 332757076201
```

Here we compute a Heegner point of conductor 5 on a rank 3 curve:

```
sage: E = EllipticCurve('5077a'); P = E.heegner_point(-7, 5); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of
↪ conductor 5077
sage: P.x_poly_exact(300)
x^6 + 1108754853727159228/72351048803252547*x^5 + 88875505551184048168/
↪ 1953478317687818769*x^4 - 2216200271166098662132/3255797196146364615*x^3 +
↪ 14941627504168839449851/9767391588439093845*x^2 - 3456417460183342963918/
↪ 3255797196146364615*x + 1306572835857500500459/5426328660243941025
```

```
class sage.schemes.elliptic_curves.heegner.HeegnerPointOnX0N(N, D, c=1, f=None,
check=True)
```

Bases: `sage.schemes.elliptic_curves.heegner.HeegnerPoint`

A Heegner point as a point on the modular curve  $X_0(N)$ , which we view as the upper half plane modulo the action of  $\Gamma_0(N)$ .

EXAMPLES:

```
sage: x = heegner_point(37,-7,5); x
Heegner point 5/74*sqrt(-7) - 11/74 of discriminant -7 and conductor 5 on X_0(37)
sage: type(x)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPointOnX0N'>
sage: x.level()
37
sage: x.conductor()
5
sage: x.discriminant()
-7
sage: x.quadratic_field()
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
sage: x.quadratic_form()
37*x^2 + 11*x*y + 2*y^2
sage: x.quadratic_order()
Order in Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
sage: x.tau()
5/74*sqrt_minus_7 - 11/74
sage: loads(dumps(x)) == x
True
```

**atkin\_lehner\_act** ( $Q=None$ )

Given an integer  $Q$  dividing the level  $N$  such that  $\gcd(Q, N/Q) = 1$ , returns the image of this Heegner point under the Atkin-Lehner operator  $W_Q$ .

INPUT:

- $Q$  – positive divisor of  $N$ ; if not given, default to  $N$

EXAMPLES:

```
sage: x = heegner_point(389,-7,5)
sage: x.atkin_lehner_act()
Heegner point 5/199168*sqrt(-7) - 631/199168 of discriminant -7 and conductor_
↪5 on X_0(389)

sage: x = heegner_point(45,D=-11,c=1); x
Heegner point 1/90*sqrt(-11) - 13/90 of discriminant -11 on X_0(45)
sage: x.atkin_lehner_act(5)
Heegner point 1/90*sqrt(-11) + 23/90 of discriminant -11 on X_0(45)
sage: y = x.atkin_lehner_act(9); y
Heegner point 1/90*sqrt(-11) - 23/90 of discriminant -11 on X_0(45)
sage: z = y.atkin_lehner_act(9); z
Heegner point 1/90*sqrt(-11) - 13/90 of discriminant -11 on X_0(45)
sage: z == x
True
```

**galois\_orbit\_over\_K**()

Return the  $\text{Gal}(K_c/K)$ -orbit of this Heegner point.

EXAMPLES:

```

sage: x = heegner_point(389,-7,3); x
Heegner point 3/778*sqrt(-7) - 223/778 of discriminant -7 and conductor 3 on
↪X_0(389)
sage: x.galois_orbit_over_K()
[Heegner point 3/778*sqrt(-7) - 223/778 of discriminant -7 and conductor 3 on
↪X_0(389), Heegner point 3/1556*sqrt(-7) - 223/1556 of discriminant -7 and
↪conductor 3 on X_0(389), Heegner point 3/1556*sqrt(-7) - 1001/1556 of
↪discriminant -7 and conductor 3 on X_0(389), Heegner point 3/3112*sqrt(-7) -
↪223/3112 of discriminant -7 and conductor 3 on X_0(389)]

```

**map\_to\_curve(*E*)**

Return the image of this Heegner point on the elliptic curve  $E$ , which must also have conductor  $N$ , where  $N$  is the level of `self`.

EXAMPLES:

```

sage: x = heegner_point(389,-7,5); x
Heegner point 5/778*sqrt(-7) - 147/778 of discriminant -7 and conductor 5 on
↪X_0(389)
sage: y = x.map_to_curve(EllipticCurve('389a')); y
Heegner point of discriminant -7 and conductor 5 on elliptic curve of
↪conductor 389
sage: y.curve().cremona_label()
'389a1'
sage: y.heegner_point_on_X0N()
Heegner point 5/778*sqrt(-7) - 147/778 of discriminant -7 and conductor 5 on
↪X_0(389)

```

You can also directly apply the modular parametrization of the elliptic curve:

```

sage: x = heegner_point(37,-7); x
Heegner point 1/74*sqrt(-7) - 17/74 of discriminant -7 on X_0(37)
sage: E = EllipticCurve('37a'); phi = E.modular_parametrization()
sage: phi(x)
Heegner point of discriminant -7 on elliptic curve of conductor 37

```

**plot(\*\**kws*)**

Draw a point at  $(x, y)$  where this Heegner point is represented by the point  $\tau = x + iy$  in the upper half plane.

The `kws` get passed onto the point plotting command.

EXAMPLES:

```

sage: heegner_point(389,-7,1).plot(pointsize=50)
Graphics object consisting of 1 graphics primitive

```

**quadratic\_form()**

Return the integral primitive positive-definite binary quadratic form associated to this Heegner point.

EXAMPLES:

```

sage: heegner_point(389,-7,5).quadratic_form()
389*x^2 + 147*x*y + 14*y^2

```

**reduced\_quadratic\_form()**

Return reduced binary quadratic corresponding to this Heegner point.

EXAMPLES:

```
sage: x = heegner_point(389,-7,5)
sage: x.quadratic_form()
389*x^2 + 147*x*y + 14*y^2
sage: x.reduced_quadratic_form()
4*x^2 - x*y + 11*y^2
```

**tau()**

Return an element  $\tau$  in the upper half plane that corresponds to this particular Heegner point.

Actually,  $\tau$  is in the quadratic imaginary field  $K$  associated to this Heegner point.

EXAMPLES:

```
sage: x = heegner_point(37,-7,5); tau = x.tau(); tau
5/74*sqrt_minus_7 - 11/74
sage: 37 * tau.minpoly()
37*x^2 + 11*x + 2
sage: x.quadratic_form()
37*x^2 + 11*x*y + 2*y^2
```

**class** sage.schemes.elliptic\_curves.heegner.**HeegnerPoints**( $N$ )

Bases: sage.structure.sage\_object.SageObject

The set of Heegner points with given parameters.

EXAMPLES:

```
sage: H = heegner_points(389); H
Set of all Heegner points on X_0(389)
sage: type(H)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPoints_level'>
sage: isinstance(H, sage.schemes.elliptic_curves.heegner.HeegnerPoints)
True
```

**level()**

Return the level  $N$  of the modular curve  $X_0(N)$ .

EXAMPLES:

```
sage: heegner_points(389).level()
389
```

**class** sage.schemes.elliptic\_curves.heegner.**HeegnerPoints\_level**( $N$ )

Bases: *sage.schemes.elliptic\_curves.heegner.HeegnerPoints*

Return the infinite set of all Heegner points on  $X_0(N)$  for all quadratic imaginary fields.

EXAMPLES:

```
sage: H = heegner_points(11); H
Set of all Heegner points on X_0(11)
sage: type(H)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPoints_level'>
sage: loads(dumps(H)) == H
True
```

**discriminants** ( $n=10$ ,  $weak=False$ )

Return the first  $n$  quadratic imaginary discriminants that satisfy the Heegner hypothesis for  $N$ .

INPUT:

- $n$  – nonnegative integer
- `weak` – bool (default: `False`); if `True` only require weak Heegner hypothesis, which is the same as usual but without the condition that  $\gcd(D, N) = 1$ .

EXAMPLES:

```
sage: X = heegner_points(37)
sage: X.discriminants(5)
[-7, -11, -40, -47, -67]
```

The default is 10:

```
sage: X.discriminants()
[-7, -11, -40, -47, -67, -71, -83, -84, -95, -104]
sage: X.discriminants(15)
[-7, -11, -40, -47, -67, -71, -83, -84, -95, -104, -107, -115, -120, -123, -
↪127]
```

The discriminant -111 satisfies only the weak Heegner hypothesis, since it is divisible by 37:

```
sage: X.discriminants(15, weak=True)
[-7, -11, -40, -47, -67, -71, -83, -84, -95, -104, -107, -111, -115, -120, -
↪123]
```

**reduce\_mod( $\ell$ )**

Return object that allows for computation with Heegner points of level  $N$  modulo the prime  $\ell$ , represented using quaternion algebras.

INPUT:

- $\ell$  – prime

EXAMPLES:

```
sage: heegner_points(389).reduce_mod(7).quaternion_algebra()
Quaternion Algebra (-1, -7) with base ring Rational Field
```

**class** `sage.schemes.elliptic_curves.heegner.HeegnerPoints_level_disc( $N, D$ )`

Bases: `sage.schemes.elliptic_curves.heegner.HeegnerPoints`

Set of Heegner points of given level and all conductors associated to a quadratic imaginary field.

EXAMPLES:

```
sage: H = heegner_points(389, -7); H
Set of all Heegner points on X_0(389) associated to QQ[sqrt(-7)]
sage: type(H)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPoints_level_disc'>
sage: H._repr_()
'Set of all Heegner points on X_0(389) associated to QQ[sqrt(-7)]'
sage: H.discriminant()
-7
sage: H.quadratic_field()
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
sage: H.kolyvagin_conductors()
[1, 3, 5, 13, 15, 17, 19, 31, 39, 41]

sage: loads(dumps(H)) == H
True
```



**discriminant()**

Return the discriminant of the quadratic imaginary extension  $K$ .

EXAMPLES:

```
sage: heegner_points(389,-7).discriminant()
-7
```

**kolyvagin\_conductors** ( $r=None, n=10, E=None, m=None$ )

Return the first  $n$  conductors that are squarefree products of distinct primes inert in the quadratic imaginary field  $K = \mathbf{Q}(\sqrt{D})$ . If  $r$  is specified, return only conductors that are a product of  $r$  distinct primes all inert in  $K$ . If  $r = 0$ , always return the list `[1]`, no matter what.

If the optional elliptic curve  $E$  and integer  $m$  are given, then only include conductors  $c$  such that for each prime divisor  $p$  of  $c$  we have  $m \mid \gcd(a_p(E), p+1)$ .

INPUT:

- $r$  – (default: `None`) nonnegative integer or `None`
- $n$  – positive integer
- $E$  – an elliptic curve
- $m$  – a positive integer

EXAMPLES:

```
sage: H = heegner_points(389,-7)
sage: H.kolyvagin_conductors(0)
[1]
sage: H.kolyvagin_conductors(1)
[3, 5, 13, 17, 19, 31, 41, 47, 59, 61]
sage: H.kolyvagin_conductors(1,15)
[3, 5, 13, 17, 19, 31, 41, 47, 59, 61, 73, 83, 89, 97, 101]
sage: H.kolyvagin_conductors(1,5)
[3, 5, 13, 17, 19]
sage: H.kolyvagin_conductors(1,5,EllipticCurve('389a'),3)
[5, 17, 41, 59, 83]
sage: H.kolyvagin_conductors(2,5,EllipticCurve('389a'),3)
[85, 205, 295, 415, 697]
```

**quadratic\_field()**

Return the quadratic imaginary field  $K = \mathbf{Q}(\sqrt{D})$ .

EXAMPLES:

```
sage: E = EllipticCurve('389a'); K = E.heegner_point(-7,5).ring_class_field()
sage: K.quadratic_field()
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
```

```
class sage.schemes.elliptic_curves.heegner.HeegnerPoints_level_disc_cond(N,
                                                                           D,
                                                                           c=1)
    Bases: sage.schemes.elliptic_curves.heegner.HeegnerPoints_level,
            sage.schemes.elliptic_curves.heegner.HeegnerPoints_level_disc
```

The set of Heegner points of given level, discriminant, and conductor.

EXAMPLES:

```

sage: H = heegner_points(389,-7,5); H
All Heegner points of conductor 5 on X_0(389) associated to QQ[sqrt(-7)]
sage: type(H)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerPoints_level_disc_cond'>
sage: H.discriminant()
-7
sage: H.level()
389

sage: len(H.points())
12
sage: H.points()[0]
Heegner point 5/778*sqrt(-7) - 147/778 of discriminant -7 and conductor 5 on X_
↪ 0(389)
sage: H.betas()
(147, 631)

sage: H.quadratic_field()
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
sage: H.ring_class_field()
Ring class field extension of QQ[sqrt(-7)] of conductor 5

sage: H.kolyvagin_conductors()
[1, 3, 5, 13, 15, 17, 19, 31, 39, 41]
sage: H.satisfies_kolyvagin_hypothesis()
True

sage: H = heegner_points(389,-7,5)
sage: loads(dumps(H)) == H
True

```

**betas()**

Return the square roots of  $Dc^2$  modulo  $4N$  all reduced mod  $2N$ , without multiplicity.

**EXAMPLES:**

```

sage: X = heegner_points(45,-11,1); X
All Heegner points of conductor 1 on X_0(45) associated to QQ[sqrt(-11)]
sage: [x.quadratic_form() for x in X]
[45*x^2 + 13*x*y + y^2,
 45*x^2 + 23*x*y + 3*y^2,
 45*x^2 + 67*x*y + 25*y^2,
 45*x^2 + 77*x*y + 33*y^2]
sage: X.betas()
(13, 23, 67, 77)
sage: X.points(13)
(Heegner point 1/90*sqrt(-11) - 13/90 of discriminant -11 on X_0(45),)
sage: [x.quadratic_form() for x in X.points(13)]
[45*x^2 + 13*x*y + y^2]

```

**conductor()**

Return the level of the conductor.

**EXAMPLES:**

```

sage: heegner_points(389,-7,5).conductor()
5

```

**plot(\*args, \*\*kws)**

Returns plot of all the representatives in the upper half plane of the Heegner points in this set of Heegner points.

The inputs to this function get passed onto the point command.

EXAMPLES:

```
sage: heegner_points(389,-7,5).plot(pointsize=50, rgbcolor='red')
Graphics object consisting of 12 graphics primitives
sage: heegner_points(53,-7,15).plot(pointsize=50, rgbcolor='purple')
Graphics object consisting of 48 graphics primitives
```

**points** (*beta=None*)

Return the Heegner points in *self*. If  $\beta$  is given, return only those Heegner points with given  $\beta$ , i.e., whose quadratic form has  $B$  congruent to  $\beta$  modulo  $2N$ .

Use *self*.*beta*() to get a list of *betas*.

EXAMPLES:

```
sage: H = heegner_points(389,-7,5); H
All Heegner points of conductor 5 on X_0(389) associated to QQ[sqrt(-7)]
sage: H.points()
(Heegner point 5/778*sqrt(-7) - 147/778 of discriminant -7 and conductor 5 on
↳X_0(389), ..., Heegner point 5/5446*sqrt(-7) - 757/778 of discriminant -7
↳and conductor 5 on X_0(389))
sage: H.betas()
(147, 631)
sage: [x.tau() for x in H.points(147)]
[5/778*sqrt_minus_7 - 147/778, 5/1556*sqrt_minus_7 - 147/1556, 5/1556*sqrt_
↳minus_7 - 925/1556, 5/3112*sqrt_minus_7 - 1703/3112, 5/3112*sqrt_minus_7 -
↳2481/3112, 5/5446*sqrt_minus_7 - 21/778]

sage: [x.tau() for x in H.points(631)]
[5/778*sqrt_minus_7 - 631/778, 5/1556*sqrt_minus_7 - 631/1556, 5/1556*sqrt_
↳minus_7 - 1409/1556, 5/3112*sqrt_minus_7 - 631/3112, 5/3112*sqrt_minus_7 -
↳1409/3112, 5/5446*sqrt_minus_7 - 757/778]
```

The result is cached and is a tuple (since it is immutable):

```
sage: H.points() is H.points()
True
sage: type(H.points())
<... 'tuple'>
```

**ring\_class\_field()**

Return the ring class field associated to this set of Heegner points. This is an extension  $K_c$  over  $K$ , where  $K$  is the quadratic imaginary field and  $c$  the conductor associated to this Heegner point. This Heegner point is defined over  $K_c$  and the Galois group  $Gal(K_c/K)$  acts transitively on the Galois conjugates of this Heegner point.

EXAMPLES:

```
sage: heegner_points(389,-7,5).ring_class_field()
Ring class field extension of QQ[sqrt(-7)] of conductor 5
```

**satisfies\_kolyvagin\_hypothesis()**

Return True if *self* satisfies the Kolyvagin hypothesis, i.e., that each prime dividing the conductor  $c$  of *self* is inert in  $K$  and coprime to  $ND$ .

EXAMPLES:

The prime 5 is inert, but the prime 11 is not:

```
sage: heegner_points(389,-7,5).satisfies_kolyvagin_hypothesis()
True
sage: heegner_points(389,-7,11).satisfies_kolyvagin_hypothesis()
False
```

**class** sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg(*level, ell*)

Bases: sage.structure.sage\_object.SageObject

Heegner points viewed as supersingular points on the modular curve  $X_0(N)/\mathbf{F}_\ell$ .

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(13); H
Heegner points on X_0(11) over F_13
sage: type(H)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerQuatAlg'>
sage: loads(dumps(H)) == H
True
```

**brandt\_module()**

Return the Brandt module of right ideal classes that we used to represent the set of supersingular points on the modular curve.

EXAMPLES:

```
sage: heegner_points(11).reduce_mod(3).brandt_module()
Brandt module of dimension 2 of level 3*11 of weight 2 over Rational Field
```

**cyclic\_subideal\_p1**(*I, c*)

Compute dictionary mapping 2-tuples that defined normalized elements of  $P^1(\mathbf{Z}/c\mathbf{Z})$

INPUT:

- *I* – right ideal of Eichler order or in quaternion algebra
- *c* – **square free integer (currently must be odd prime** and coprime to level, discriminant, characteristic, etc.

OUTPUT:

- dictionary mapping 2-tuples (u,v) to ideals

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(7)
sage: I = H.brandt_module().right_ideals()[0]
sage: sorted(H.cyclic_subideal_p1(I,3).items())
[( (0, 1),
  Fractional ideal (2 + 2*j + 32*k, 2*i + 8*j + 82*k, 12*j + 60*k, 132*k)),
  ( (1, 0),
  Fractional ideal (2 + 10*j + 28*k, 2*i + 4*j + 62*k, 12*j + 60*k, 132*k)),
  ( (1, 1),
  Fractional ideal (2 + 2*j + 76*k, 2*i + 4*j + 106*k, 12*j + 60*k, 132*k)),
  ( (1, 2),
  Fractional ideal (2 + 10*j + 116*k, 2*i + 8*j + 38*k, 12*j + 60*k, 132*k))]
sage: len(H.cyclic_subideal_p1(I,17))
18
```

**ell()**

Return the prime  $\ell$  modulo which we are working.

EXAMPLES:

```
sage: heegner_points(11).reduce_mod(3).ell()
3
```

**galois\_group\_over\_hilbert\_class\_field( $D, c$ )**

Return the Galois group of the extension of ring class fields  $K_c$  over the Hilbert class field  $K_1$  of the quadratic imaginary field of discriminant  $D$ .

INPUT:

- $D$  – fundamental discriminant
- $c$  – conductor (square-free integer)

EXAMPLES:

```
sage: N = 37; D = -7; ell = 17; c = 41; p = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: H.galois_group_over_hilbert_class_field(D, c)
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 41
↳ over Hilbert class field of  $\mathbb{Q}[\sqrt{-7}]$ 
```

**galois\_group\_over\_quadratic\_field( $D, c$ )**

Return the Galois group of the extension of ring class fields  $K_c$  over the quadratic imaginary field  $K$  of discriminant  $D$ .

INPUT:

- $D$  – fundamental discriminant
- $c$  – conductor (square-free integer)

EXAMPLES:

```
sage: N = 37; D = -7; ell = 17; c = 41; p = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: H.galois_group_over_quadratic_field(D, c)
Galois group of Ring class field extension of  $\mathbb{Q}[\sqrt{-7}]$  of conductor 41
↳ over Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
```

**heegner\_conductors( $D, n=5$ )**

Return the first  $n$  negative fundamental discriminants coprime to  $N\ell$  such that  $\ell$  is inert in the corresponding quadratic imaginary field and that field satisfies the Heegner hypothesis.

INPUT:

- $D$  – negative integer; a fundamental Heegner discriminant
- $n$  – positive integer (default: 5)

OUTPUT:

- list

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3)
sage: H.heegner_conductors(-7)
[1, 2, 4, 5, 8]
```

```
sage: H.heegner_conductors(-7, 10)
[1, 2, 4, 5, 8, 10, 13, 16, 17, 19]
```

**heegner\_discriminants** ( $n=5$ )

Return the first  $n$  negative fundamental discriminants coprime to  $N\ell$  such that  $\ell$  is inert in the corresponding quadratic imaginary field and that field satisfies the Heegner hypothesis, and  $N$  is the level.

INPUT:

- $n$  – positive integer (default: 5)

OUTPUT:

- list

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3)
sage: H.heegner_discriminants()
[-7, -19, -40, -43, -52]
sage: H.heegner_discriminants(10)
[-7, -19, -40, -43, -52, -79, -127, -139, -151, -184]
```

**heegner\_divisor** ( $D, c=1$ )

Return Heegner divisor as an element of the Brandt module corresponding to the discriminant  $D$  and conductor  $c$ , which both must be coprime to  $N\ell$ .

More precisely, we compute the sum of the reductions of the  $\text{Gal}(K_1/K)$ -conjugates of each choice of  $y_1$ , where the choice comes from choosing the ideal  $\mathcal{N}$ . Then we apply the Hecke operator  $T_c$  to this sum.

INPUT:

- $D$  – discriminant (negative integer)
- $c$  – conductor (positive integer)

OUTPUT:

- Brandt module element

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(7)
sage: H.heegner_discriminants()
[-8, -39, -43, -51, -79]
sage: H.heegner_divisor(-8)
(1, 0, 0, 1, 0, 0)
sage: H.heegner_divisor(-39)
(1, 2, 2, 1, 2, 0)
sage: H.heegner_divisor(-43)
(1, 0, 0, 1, 0, 0)
sage: H.heegner_divisor(-51)
(1, 0, 0, 1, 0, 2)
sage: H.heegner_divisor(-79)
(3, 2, 2, 3, 0, 0)

sage: sum(H.heegner_divisor(-39).element())
8
sage: QuadraticField(-39, 'a').class_number()
4
```

**kolyvagin\_cyclic\_subideals** ( $I, p, \text{alpha\_quaternion}$ )

Return list of pairs  $(J, n)$  where  $J$  runs through the cyclic subideals of  $I$  of index  $(\mathbf{Z}/p\mathbf{Z})^2$ , and  $J \sim \alpha^n(J_0)$  for some fixed choice of cyclic subideal  $J_0$ .

INPUT:

- $I$  – right ideal of the quaternion algebra
- $p$  – prime number
- **alpha\_quaternion** – image in the quaternion algebra of generator  $\alpha$  for  $(\mathcal{O}_K/c\mathcal{O}_K)^*/(\mathbf{Z}/c\mathbf{Z})^*$ .

OUTPUT:

- list of 2-tuples

EXAMPLES:

```
sage: N = 37; D = -7; ell = 17; c=5
sage: H = heegner_points(N).reduce_mod(ell)
sage: B = H.brandt_module(); I = B.right_ideals()[32]
sage: f = H.optimal_embeddings(D, 1, I.left_order())[1]
sage: g = H.kolyvagin_generators(f.domain().number_field(), c)
sage: alpha_quaternion = f(g[0]); alpha_quaternion
1 - 5/128*i - 77/192*j + 137/384*k
sage: H.kolyvagin_cyclic_subideals(I, 5, alpha_quaternion)
[(Fractional ideal (2 + 874/3*j + 128356/3*k, 2*i + 932/3*j + 198806/3*k,
↪ 2560/3*j + 33280/3*k, 94720*k), 0), (Fractional ideal (2 + 462*j + 82892*k,
↪ 2*i + 932/3*j + 141974/3*k, 2560/3*j + 33280/3*k, 94720*k), 1), (Fractional
↪ ideal (2 + 2410/3*j + 261988/3*k, 2*i + 652*j + 89650*k, 2560/3*j + 33280/
↪ 3*k, 94720*k), 2), (Fractional ideal (2 + 2410/3*j + 91492/3*k, 2*i + 1444/
↪ 3*j + 148630/3*k, 2560/3*j + 33280/3*k, 94720*k), 3), (Fractional ideal (2
↪ + 874/3*j + 71524/3*k, 2*i + 2468/3*j + 275606/3*k, 2560/3*j + 33280/3*k,
↪ 94720*k), 4), (Fractional ideal (2 + 462*j + 63948*k, 2*i + 2468/3*j +
↪ 218774/3*k, 2560/3*j + 33280/3*k, 94720*k), 5)]
```

**kolyvagin\_generator** ( $K, p$ )

Return element in  $K$  that maps to the multiplicative generator for the quotient group

$$(\mathcal{O}_K/p\mathcal{O}_K)^*/(\mathbf{Z}/p\mathbf{Z})^*$$

of the form  $\sqrt{D} + n$  with  $n \geq 1$  minimal.

INPUT:

- $K$  – quadratic imaginary field
- $p$  – inert prime

EXAMPLES:

```
sage: N = 37; D = -7; ell = 17; p=5
sage: H = heegner_points(N).reduce_mod(ell)
sage: B = H.brandt_module(); I = B.right_ideals()[32]
sage: f = H.optimal_embeddings(D, 1, I.left_order())[0]
sage: H.kolyvagin_generator(f.domain().number_field(), 5)
a + 1
```

This function requires that  $p$  be prime, but `kolyvagin_generators` works in general:

```
sage: H.kolyvagin_generator(f.domain().number_field(), 5*17)
Traceback (most recent call last):
```

```

...
NotImplementedError: p must be prime
sage: H.kolyvagin_generators(f.domain().number_field(), 5*17)
[-34*a + 1, 35*a + 106]

```

**kolyvagin\_generators** ( $K, c$ )

Return elements in  $\mathcal{O}_K$  that map to multiplicative generators for the factors of the quotient group

$$(\mathcal{O}_K/c\mathcal{O}_K)^*/(\mathbb{Z}/c\mathbb{Z})^*$$

corresponding to the prime divisors of  $c$ . Each generator is of the form  $\sqrt{D} + n$  with  $n \geq 1$  minimal.

INPUT:

- $K$  – quadratic imaginary field
- $c$  – square free product of inert prime

EXAMPLES:

```

sage: N = 37; D = -7; ell = 17; p=5
sage: H = heegner_points(N).reduce_mod(ell)
sage: B = H.brandt_module(); I = B.right_ideals()[32]
sage: f = H.optimal_embeddings(D, 1, I.left_order())[0]
sage: H.kolyvagin_generators(f.domain().number_field(), 5*17)
[-34*a + 1, 35*a + 106]

```

**kolyvagin\_point\_on\_curve** ( $D, c, E, p, \text{bound}=10$ )

Compute image of the Kolyvagin divisor  $P_c$  in  $E(\mathbb{F}_{\ell^2})/pE(\mathbb{F}_{\ell^2})$ .

Note that this image is by definition only well defined up to scalars. However, doing multiple computations will always yield the same result, and working modulo different  $\ell$  is compatible (since we always choose the same generator for  $\text{Gal}(K_c/K_1)$ ).

INPUT:

- $D$  – fundamental negative discriminant
- $c$  – conductor
- $E$  – elliptic curve of conductor the level of self
- $p$  – odd prime number such that we consider image in  $E(\mathbb{F}_{\ell^2})/pE(\mathbb{F}_{\ell^2})$
- bound – integer (default: 10)

EXAMPLES:

```

sage: N = 37; D = -7; ell = 17; c = 41; p = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: H.kolyvagin_point_on_curve(D, c, EllipticCurve('37a'), p)
[2, 2]

```

**kolyvagin\_sigma\_operator** ( $D, c, r, \text{bound}=\text{None}$ )

Return the action of the Kolyvagin sigma operator on the  $r$ -th basis vector.

INPUT:

- $D$  – fundamental discriminant
- $c$  – conductor (square-free integer, need not be prime)
- $r$  – nonnegative integer



- `bound` – (default: `None`), if given, controls precision of computation of theta series, which could impact performance, but does not impact correctness

## EXAMPLES:

We first try to verify Kolyvagin’s conjecture for a rank 2 curve by working modulo 5, but we are unlucky with  $c = 17$ :

```
sage: N = 389; D = -7; ell = 5; c = 17; q = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: E = EllipticCurve('389a')
sage: V = H.modp_dual_elliptic_curve_factor(E, q, 5) # long time (4s on sage.
↳math, 2012)
sage: k118 = H.kolyvagin_sigma_operator(D, c, 118)
sage: k104 = H.kolyvagin_sigma_operator(D, c, 104)
sage: [b.dot_product(k104.element().change_ring(GF(3))) for b in V.basis()]
↳# long time
[0, 0]
sage: [b.dot_product(k118.element().change_ring(GF(3))) for b in V.basis()]
↳# long time
[0, 0]
```

Next we try again with  $c = 41$  and this does work, in that we get something nonzero, when dotting with  $V$ :

```
sage: c = 41
sage: k118 = H.kolyvagin_sigma_operator(D, c, 118)
sage: k104 = H.kolyvagin_sigma_operator(D, c, 104)
sage: [b.dot_product(k118.element().change_ring(GF(3))) for b in V.basis()]
↳# long time
[2, 0]
sage: [b.dot_product(k104.element().change_ring(GF(3))) for b in V.basis()]
↳# long time
[1, 0]
```

By the way, the above is the first ever provable verification of Kolyvagin’s conjecture for any curve of rank at least 2.

Another example, but where the curve has rank 1:

```
sage: N = 37; D = -7; ell = 17; c = 41; q = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: H.heegner_divisor(D, 1).element().nonzero_positions()
[32, 51]
sage: k32 = H.kolyvagin_sigma_operator(D, c, 32); k32
(17, 12, 33, 33, 49, 108, 3, 0, 0, 33, 37, 49, 33, 33, 59, 54, 21, 30, 0, 0,
↳29, 12, 41, 38, 33, 15, 0, 0, 4, 0, 7, 0, 0, 0, 0, 34, 26, 18, 0, 0, 0, 0,
↳0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
sage: k51 = H.kolyvagin_sigma_operator(D, c, 51); k51
(5, 13, 0, 0, 14, 0, 21, 0, 0, 0, 29, 0, 0, 45, 0, 6, 0, 40, 0, 61, 0, 0, 40,
↳32, 0, 9, 0, 0, 0, 0, 17, 0, 0, 0, 77, 40, 2, 10, 18, 0, 0, 61, 19, 45, 26,
↳80, 61, 35, 35, 19, 1, 0)
sage: V = H.modp_dual_elliptic_curve_factor(EllipticCurve('37a'), q, 5); V
Vector space of degree 52 and dimension 2 over Ring of integers modulo 3
Basis matrix:
2 x 52 dense matrix over Ring of integers modulo 3
sage: [b.dot_product(k32.element().change_ring(GF(q))) for b in V.basis()]
[2, 2]
sage: [b.dot_product(k51.element().change_ring(GF(q))) for b in V.basis()]
```

```
[1, 1]
```

An example with  $c$  a product of two primes:

```
sage: N = 389; D = -7; ell = 5; q = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: V = H.modp_dual_elliptic_curve_factor(EllipticCurve('389a'), q, 5)
sage: k = H.kolyvagin_sigma_operator(D, 17*41, 104)      # long time
sage: k                                                  # long time
(990, 656, 219, ..., 246, 534, 1254)
sage: [b.dot_product(k.element().change_ring(GF(3))) for b in V.basis()] #
↳ long time (but only because depends on something slow)
[0, 0]
```

### `left_orders()`

Return the left orders associated to the representative right ideals in the Brandt module.

EXAMPLES:

```
sage: heegner_points(11).reduce_mod(3).left_orders()
[Order of Quaternion Algebra (-1, -3) with base ring Rational Field with
↳ basis (1/2 + 1/2*j + 7*k, 1/2*i + 13/2*k, j + 3*k, 11*k),
Order of Quaternion Algebra (-1, -3) with base ring Rational Field with
↳ basis (1/2 + 1/2*j + 7*k, 1/4*i + 1/2*j + 63/4*k, j + 14*k, 22*k)]
```

### `level()`

Return the level.

EXAMPLES:

```
sage: heegner_points(11).reduce_mod(3).level()
11
```

### `modp_dual_elliptic_curve_factor(E, p, bound=10)`

Return the factor of the Brandt module space modulo  $p$  corresponding to the elliptic curve  $E$ , cut out using Hecke operators up to bound.

INPUT:

- $E$  – elliptic curve of conductor equal to the level of self
- $p$  – prime number
- $bound$  – positive integer (default: 10)

EXAMPLES:

```
sage: N = 37; D = -7; ell = 17; c = 41; q = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: V = H.modp_dual_elliptic_curve_factor(EllipticCurve('37a'), q, 5); V
Vector space of degree 52 and dimension 2 over Ring of integers modulo 3
Basis matrix:
2 x 52 dense matrix over Ring of integers modulo 3
```

### `modp_splitting_data(p)`

Return mod  $p$  splitting data for the quaternion algebra at the unramified prime  $p$ . This is a pair of  $2 \times 2$  matrices  $A, B$  over the finite field  $\mathbf{F}_p$  such that if the quaternion algebra has generators  $i, j, k$ , then the homomorphism sending  $i$  to  $A$  and  $j$  to  $B$  maps any maximal order homomorphically onto the ring of  $2 \times 2$  matrices.

Because of how the homomorphism is defined, we must assume that the prime  $p$  is odd.

INPUT:

- $p$  – unramified odd prime

OUTPUT:

- 2-tuple of matrices over finite field

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(7)
sage: H.quaternion_algebra()
Quaternion Algebra (-1, -7) with base ring Rational Field
sage: I, J = H.modp_splitting_data(13)
sage: I
[ 0 12]
[ 1  0]
sage: J
[7 3]
[3 6]
sage: I^2
[12  0]
[ 0 12]
sage: J^2
[6 0]
[0 6]
sage: I*J == -J*I
True
```

The following is a good test because of the asserts in the code:

```
sage: v = [H.modp_splitting_data(p) for p in primes(13,200)]
```

Some edge cases:

```
sage: H.modp_splitting_data(11)
(
[ 0 10]  [6 1]
[ 1  0], [1 5]
)
```

Proper error handling:

```
sage: H.modp_splitting_data(7)
Traceback (most recent call last):
...
ValueError: p (=7) must be an unramified prime

sage: H.modp_splitting_data(2)
Traceback (most recent call last):
...
ValueError: p must be odd
```

**modp\_splitting\_map** ( $p$ )

Return (algebra) map from the ( $p$ -integral) quaternion algebra to the set of  $2 \times 2$  matrices over  $\mathbf{F}_p$ .

INPUT:

- $p$  – prime number

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(7)
sage: f = H.modp_splitting_map(13)
sage: B = H.quaternion_algebra(); B
Quaternion Algebra (-1, -7) with base ring Rational Field
sage: i, j, k = H.quaternion_algebra().gens()
sage: a = 2+i-j+3*k; b = 7+2*i-4*j+k
sage: f(a*b)
[12  3]
[10  5]
sage: f(a)*f(b)
[12  3]
[10  5]
```

**optimal\_embeddings**( $D, c, R$ )

INPUT:

- $D$  – negative fundamental discriminant
- $c$  – integer coprime
- $R$  – Eichler order

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3)
sage: R = H.left_orders()[0]
sage: H.optimal_embeddings(-7, 1, R)
[Embedding sending sqrt(-7) to i - j - k,
 Embedding sending sqrt(-7) to -i + j + k]
sage: H.optimal_embeddings(-7, 2, R)
[Embedding sending 2*sqrt(-7) to 5*i - k,
 Embedding sending 2*sqrt(-7) to -5*i + k,
 Embedding sending 2*sqrt(-7) to 2*i - 2*j - 2*k,
 Embedding sending 2*sqrt(-7) to -2*i + 2*j + 2*k]
```

**quadratic\_field**( $D$ )

Return our fixed choice of quadratic imaginary field of discriminant  $D$ .

INPUT:

- $D$  – fundamental discriminant

OUTPUT:

- a quadratic number field

EXAMPLES:

```
sage: H = heegner_points(389).reduce_mod(5)
sage: H.quadratic_field(-7)
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7
```

**quaternion\_algebra**()

Return the rational quaternion algebra used to implement self.

EXAMPLES:

```
sage: heegner_points(389).reduce_mod(7).quaternion_algebra()
Quaternion Algebra (-1, -7) with base ring Rational Field
```

**rational\_kolyvagin\_divisor**( $D, c$ )

Return the Kolyvagin divisor as an element of the Brandt module corresponding to the discriminant  $D$  and conductor  $c$ , which both must be coprime to  $N\ell$ .

INPUT:

- $D$  – discriminant (negative integer)
- $c$  – conductor (positive integer)

OUTPUT:

- Brandt module element (or tuple of them)

EXAMPLES:

```
sage: N = 389; D = -7; ell = 5; c = 17; q = 3
sage: H = heegner_points(N).reduce_mod(ell)
sage: k = H.rational_kolyvagin_divisor(D, c); k # long time (5s on sage.math,
↪ 2013)
(2, 0, 0, 0, 0, 0, 0, 16, 0, 0, 0, 0, 4, 0, 0, 9, 11, 0, 6, 0, 0, 7, 0, 0, 0, 0,
↪ 14, 12, 13, 15, 17, 0, 0, 0, 0, 8, 0, 0, 0, 0, 10, 0, 0, 0, 0, 0, 0, 0, 0,
↪ 0, 5, 0, 0, 0, 0, 3, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
↪ 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
↪ 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
↪ 0, 0, 0, 0, 0, 0, 0)
sage: V = H.modp_dual_elliptic_curve_factor(EllipticCurve('389a'), q, 2)
sage: [b.dot_product(k.element().change_ring(GF(q))) for b in V.basis()] #
↪ long time
[0, 0]
sage: k = H.rational_kolyvagin_divisor(D, 59)
sage: [b.dot_product(k.element().change_ring(GF(q))) for b in V.basis()]
[2, 0]
```

**right\_ideals**()

Return representative right ideals in the Brandt module.

EXAMPLES:

```
sage: heegner_points(11).reduce_mod(3).right_ideals()
(Fractional ideal (2 + 2*j + 28*k, 2*i + 26*k, 4*j + 12*k, 44*k),
 Fractional ideal (2 + 2*j + 28*k, 2*i + 4*j + 38*k, 8*j + 24*k, 88*k))
```

**satisfies\_heegner\_hypothesis**( $D, c=1$ )

The fundamental discriminant  $D$  must be coprime to  $N\ell$ , and must define a quadratic imaginary field  $K$  in which  $\ell$  is inert. Also, all primes dividing  $N$  must split in  $K$ , and  $c$  must be squarefree and coprime to  $ND\ell$ .

INPUT:

- $D$  – negative integer
- $c$  – positive integer (default: 1)

OUTPUT:

- bool

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(7)
sage: H.satisfies_heegner_hypothesis(-5)
False
```

```

sage: H.satisfies_heegner_hypothesis(-7)
False
sage: H.satisfies_heegner_hypothesis(-8)
True
sage: [D for D in [-1, -2, ..., -100] if H.satisfies_heegner_hypothesis(D)]
[-8, -39, -43, -51, -79, -95]

```

**class** sage.schemes.elliptic\_curves.heegner.**HeegnerQuatAlgEmbedding**(*D*, *c*, *R*, *beta*)

Bases: sage.structure.sage\_object.SageObject

The homomorphism  $\mathcal{O} \rightarrow R$ , where  $\mathcal{O}$  is the order of conductor  $c$  in the quadratic field of discriminant  $D$ , and  $R$  is an Eichler order in a quaternion algebra.

EXAMPLES:

```

sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: f = H.optimal_embeddings(-7, 2, R)[1]; f
Embedding sending 2*sqrt(-7) to -5*i + k
sage: type(f)
<class 'sage.schemes.elliptic_curves.heegner.HeegnerQuatAlgEmbedding'>
sage: loads(dumps(f)) == f
True

```

**beta**()

Return the element  $\beta$  in the quaternion algebra order that  $c\sqrt{D}$  maps to.

EXAMPLES:

```

sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: H.optimal_embeddings(-7, 2, R)[1].beta()
-5*i + k

```

**codomain**()

Return the codomain of this embedding.

EXAMPLES:

```

sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: H.optimal_embeddings(-7, 2, R)[0].codomain()
Order of Quaternion Algebra (-1, -3) with base ring Rational Field with basis_
↪ (1/2 + 1/2*j + 7*k, 1/2*i + 13/2*k, j + 3*k, 11*k)

```

**conjugate**()

Return the conjugate of this embedding, which is also an embedding.

EXAMPLES:

```

sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: f = H.optimal_embeddings(-7, 2, R)[1]
sage: f.conjugate()
Embedding sending 2*sqrt(-7) to 5*i - k
sage: f
Embedding sending 2*sqrt(-7) to -5*i + k

```

**domain**()

Return the domain of this embedding.

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: H.optimal_embeddings(-7, 2, R)[0].domain()
Order in Number Field in a with defining polynomial x^2 + 7
```

**domain\_conductor()**

Return the conductor of the domain.

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: H.optimal_embeddings(-7, 2, R)[0].domain_conductor()
2
```

**domain\_gen()**

Return the specific generator  $c\sqrt{D}$  for the domain order.

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: f = H.optimal_embeddings(-7, 2, R)[0]
sage: f.domain_gen()
2*a
sage: f.domain_gen()^2
-28
```

**matrix()**

Return matrix over  $\mathbf{Q}$  of this morphism, with respect to the basis  $1, c\sqrt{D}$  of the domain and the basis  $1, i, j, k$  of the ambient rational quaternion algebra (which contains the domain).

EXAMPLES:

```
sage: H = heegner_points(11).reduce_mod(3); R = H.left_orders()[0]
sage: f = H.optimal_embeddings(-7, 1, R)[1]; f
Embedding sending sqrt(-7) to -i + j + k
sage: f.matrix()
[ 1  0  0  0]
[ 0 -1  1  1]
sage: f.conjugate().matrix()
[ 1  0  0  0]
[ 0  1 -1 -1]
```

**class** sage.schemes.elliptic\_curves.heegner.KolyvaginCohomologyClass(*kolyvagin\_point*, *n*)

Bases: sage.structure.sage\_object.SageObject

A Kolyvagin cohomology class in  $H^1(K, E[n])$  or  $H^1(K, E)[n]$  attached to a Heegner point.

EXAMPLES:

```
sage: y = EllipticCurve('37a').heegner_point(-7)
sage: c = y.kolyvagin_cohomology_class(3); c
Kolyvagin cohomology class c(1) in H^1(K, E[3])
sage: type(c)
<class 'sage.schemes.elliptic_curves.heegner.KolyvaginCohomologyClassEn'>
sage: loads(dumps(c)) == c
True
sage: y.kolyvagin_cohomology_class(5)
Kolyvagin cohomology class c(1) in H^1(K, E[5])
```

**conductor()**

Return the integer  $c$  such that this cohomology class is associated to the Heegner point  $y_c$ .

EXAMPLES:

```
sage: y = EllipticCurve('37a').heegner_point(-7, 5)
sage: t = y.kolyvagin_cohomology_class()
sage: t.conductor()
5
```

**heegner\_point()**

Return the Heegner point  $y_c$  to which this cohomology class is associated.

EXAMPLES:

```
sage: y = EllipticCurve('37a').heegner_point(-7, 5)
sage: t = y.kolyvagin_cohomology_class()
sage: t.heegner_point()
Heegner point of discriminant -7 and conductor 5 on elliptic curve of conductor 37
```

**kolyvagin\_point()**

Return the Kolyvagin point  $P_c$  to which this cohomology class is associated.

EXAMPLES:

```
sage: y = EllipticCurve('37a').heegner_point(-7, 5)
sage: t = y.kolyvagin_cohomology_class()
sage: t.kolyvagin_point()
Kolyvagin point of discriminant -7 and conductor 5 on elliptic curve of conductor 37
```

**n()**

Return the integer  $n$  so that this is a cohomology class in  $H^1(K, E[n])$  or  $H^1(K, E)[n]$ .

EXAMPLES:

```
sage: y = EllipticCurve('37a').heegner_point(-7)
sage: t = y.kolyvagin_cohomology_class(3); t
Kolyvagin cohomology class c(1) in H^1(K, E[3])
sage: t.n()
3
```

**class** sage.schemes.elliptic\_curves.heegner.**KolyvaginCohomologyClassEn**(*kolyvagin\_point*, *n*)  
 Bases: *sage.schemes.elliptic\_curves.heegner.KolyvaginCohomologyClass*

EXAMPLES:

**class** sage.schemes.elliptic\_curves.heegner.**KolyvaginPoint**(*heegner\_point*)  
 Bases: *sage.schemes.elliptic\_curves.heegner.HeegnerPoint*

A Kolyvagin point.

EXAMPLES:

We create a few Kolyvagin points:

```
sage: EllipticCurve('11a1').kolyvagin_point(-7)
Kolyvagin point of discriminant -7 on elliptic curve of conductor 11
sage: EllipticCurve('37a1').kolyvagin_point(-7)
```



```

Kolyvagin point of discriminant -7 on elliptic curve of conductor 37
sage: EllipticCurve('37a1').kolyvagin_point(-67)
Kolyvagin point of discriminant -67 on elliptic curve of conductor 37
sage: EllipticCurve('389a1').kolyvagin_point(-7, 5)
Kolyvagin point of discriminant -7 and conductor 5 on elliptic curve of conductor_
↪ 389

```

One can also associated a Kolyvagin point to a Heegner point:

```

sage: y = EllipticCurve('37a1').heegner_point(-7); y
Heegner point of discriminant -7 on elliptic curve of conductor 37
sage: y.kolyvagin_point()
Kolyvagin point of discriminant -7 on elliptic curve of conductor 37

```

**curve()**

Return the elliptic curve over  $\mathbb{Q}$  on which this Kolyvagin point sits.

EXAMPLES:

```

sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67, 3)
sage: P.curve()
Elliptic Curve defined by  $y^2 + y = x^3 - x$  over Rational Field

```

**heegner\_point()**

This Kolyvagin point  $P_c$  is associated to some Heegner point  $y_c$  via Kolyvagin's construction. This function returns that point  $y_c$ .

EXAMPLES:

```

sage: E = EllipticCurve('37a1')
sage: P = E.kolyvagin_point(-67); P
Kolyvagin point of discriminant -67 on elliptic curve of conductor 37
sage: y = P.heegner_point(); y
Heegner point of discriminant -67 on elliptic curve of conductor 37
sage: y.kolyvagin_point() is P
True

```

**index(\*args, \*\*kws)**

Return index of this Kolyvagin point in the full group of  $K_c$  rational points on  $E$ .

When the conductor is 1, this is computed numerically using the Gross-Zagier formula and explicit point search, and it may be off by 2. See the documentation for `E.heegner_index`, where  $E$  is the curve attached to `self`.

EXAMPLES:

```

sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67); P.index()
6

```

**kolyvagin\_cohomology\_class(n=None)**

INPUT:

- $n$  – positive integer that divides the gcd of  $a_p$  and  $p + 1$  for all  $p$  dividing the conductor. If  $n$  is None, choose the largest valid  $n$ .

EXAMPLES:

```

sage: y = EllipticCurve('389a').heegner_point(-7, 5)
sage: P = y.kolyvagin_point()

```

```

sage: P.kolyvagin_cohomology_class(3)
Kolyvagin cohomology class c(5) in H^1(K,E[3])

sage: y = EllipticCurve('37a').heegner_point(-7,5).kolyvagin_point()
sage: y.kolyvagin_cohomology_class()
Kolyvagin cohomology class c(5) in H^1(K,E[2])

```

**mod** ( $p$ ,  $prec=53$ )

Return the trace of the reduction  $Q$  modulo a prime over  $p$  of this Kolyvagin point as an element of  $E(\mathbf{F}_p)$ , where  $p$  is any prime that is inert in  $K$  that is coprime to  $NDc$ .

The point  $Q$  is only well defined up to an element of  $(p+1)E(\mathbf{F}_p)$ , i.e., it gives a well defined element of the abelian group  $E(\mathbf{F}_p)/(p+1)E(\mathbf{F}_p)$ .

See [SteinToward], Proposition 5.4 for a proof of the above well-definedness assertion.

EXAMPLES:

A Kolyvagin point on a rank 1 curve:

```

sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67)
sage: P.mod(2)
(1 : 1 : 1)
sage: P.mod(3)
(1 : 0 : 1)
sage: P.mod(5)
(2 : 2 : 1)
sage: P.mod(7)
(6 : 0 : 1)
sage: P.trace_to_real_numerical()
(1.61355529131986 : -2.18446840788880 : 1.000000000000000)
sage: P._trace_exact_conductor_1() # the actual point we're reducing
(1357/841 : -53277/24389 : 1)
sage: (P._trace_exact_conductor_1().height() / E.regulator()).sqrt()
12.000000000000000

```

Here the Kolyvagin point is a torsion point (since  $E$  has rank 1), and we reduce it modulo several primes.:

```

sage: E = EllipticCurve('11a1'); P = E.kolyvagin_point(-7)
sage: P.mod(3,70) # long time (4s on sage.math, 2013)
(1 : 2 : 1)
sage: P.mod(5,70)
(1 : 4 : 1)
sage: P.mod(7,70)
Traceback (most recent call last):
...
ValueError: p must be coprime to conductors and discriminant
sage: P.mod(11,70)
Traceback (most recent call last):
...
ValueError: p must be coprime to conductors and discriminant
sage: P.mod(13,70)
(3 : 4 : 1)

```

REFERENCES:

**numerical\_approx** ( $prec=53$ )

Return a numerical approximation to this Kolyvagin point using  $prec$  bits of working precision.

INPUT:

- `prec` – precision in bits (default: 53)

EXAMPLES:

```
sage: P = EllipticCurve('37a1').kolyvagin_point(-7); P
Kolyvagin point of discriminant -7 on elliptic curve of conductor 37
sage: P.numerical_approx() # approx. (0 : 0 : 1)
(...e-16 - ...e-16*I : ...e-16 + ...e-16*I : 1.000000000000000)
sage: P.numerical_approx(100)[0].abs() < 2.0^-99
True

sage: P = EllipticCurve('389a1').kolyvagin_point(-7, 5); P
Kolyvagin point of discriminant -7 and conductor 5 on elliptic curve of_
↳conductor 389
```

Numerical approximation is only implemented for points of conductor 1:

```
sage: P.numerical_approx()
Traceback (most recent call last):
...
NotImplementedError
```

**plot** (*prec=53, \*args, \*\*kws*)

Plot a Kolyvagin point  $P_1$  if it is defined over the rational numbers.

EXAMPLES:

```
sage: E = EllipticCurve('37a'); P = E.heegner_point(-11).kolyvagin_point()
sage: P.plot(prec=30, pointsize=50, rgbcolor='red') + E.plot()
Graphics object consisting of 3 graphics primitives
```

**point\_exact** (*prec=53*)

INPUT:

- `prec` – precision in bits (default: 53)

EXAMPLES:

A rank 1 curve:

```
sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67)
sage: P.point_exact()
(6 : -15 : 1)
sage: P.point_exact(40)
(6 : -15 : 1)
sage: P.point_exact(20)
Traceback (most recent call last):
...
RuntimeError: insufficient precision to find exact point
```

A rank 0 curve:

```
sage: E = EllipticCurve('11a1'); P = E.kolyvagin_point(-7)
sage: P.point_exact()
(-1/2*sqrt_minus_7 + 1/2 : -2*sqrt_minus_7 - 2 : 1)
```

A rank 2 curve:

```
sage: E = EllipticCurve('389a1'); P = E.kolyvagin_point(-7)
sage: P.point_exact()
(0 : 1 : 0)
```

**satisfies\_kolyvagin\_hypothesis** ( $n=None$ )

Return `True` if this Kolyagin point satisfies the Heegner hypothesis for  $n$ , so that it defines a Galois equivariant element of  $E(K_c)/nE(K_c)$ .

EXAMPLES:

```
sage: y = EllipticCurve('389a').heegner_point(-7,5); P = y.kolyvagin_point()
sage: P.kolyvagin_cohomology_class(3)
Kolyvagin cohomology class c(5) in H^1(K,E[3])
sage: P.satisfies_kolyvagin_hypothesis(3)
True
sage: P.satisfies_kolyvagin_hypothesis(5)
False
sage: P.satisfies_kolyvagin_hypothesis(7)
False
sage: P.satisfies_kolyvagin_hypothesis(11)
False
```

```
trace to real numerical (prec=53)
```

Return the trace of this Kolyvagin point down to the real numbers, computed numerically using `prec` bits of working precision.

EXAMPLES:

```
sage: E = EllipticCurve('37a1'); P = E.kolyvagin_point(-67)
sage: PP = P.numerical_approx()
sage: [c.real() for c in PP]
[6.000000000000000, -15.000000000000000, 1.000000000000000]
sage: all([c.imag().abs() < 1e-14 for c in PP])
True
sage: P.trace_to_real_numerical()
(1.61355529131986 : -2.18446840788880 : 1.000000000000000)
sage: P.trace_to_real_numerical(prec=80) # abs tol 1e-21
(1.6135552913198573127230 : -2.1844684078888023289187 : 1.
↪ 000000000000000000000000)
```

```
class sage.schemes.elliptic_curves.heegner.RingClassField(D, c, check=True)
```

Bases: sage.structure.sage\_object.SageObject

A Ring class field of a quadratic imaginary field of given conductor.

**Note:** This is a *ring* class field, not a ray class field. In general, the ring class field of given conductor is a subfield of the ray class field of the same conductor.

EXAMPLES:

```
sage: heegner_point(37,-7).ring_class_field()
Hilbert class field of QQ[sqrt(-7)]
sage: heegner_point(37,-7,5).ring_class_field()
Ring class field extension of QQ[sqrt(-7)] of conductor 5
sage: heegner_point(37,-7,55).ring_class_field()
Ring class field extension of QQ[sqrt(-7)] of conductor 55
```

**absolute\_degree()**

Return the absolute degree of this field over  $\mathbb{Q}$ .

EXAMPLES:

```
sage: E = EllipticCurve('389a'); K = E.heegner_point(-7,5).ring_class_field()
sage: K.absolute_degree()
12
sage: K.degree_over_K()
6
```

**conductor()**

Return the conductor of this ring class field.

EXAMPLES:

```
sage: E = EllipticCurve('389a'); K5 = E.heegner_point(-7,5).ring_class_field()
sage: K5.conductor()
5
```

**degree\_over\_H()**

Return the degree of this field over the Hilbert class field  $H$  of  $K$ .

EXAMPLES:

```
sage: E = EllipticCurve('389a')
sage: E.heegner_point(-59).ring_class_field().degree_over_H()
1
sage: E.heegner_point(-59).ring_class_field().degree_over_K()
3
sage: QuadraticField(-59, 'a').class_number()
3
```

Some examples in which prime dividing  $c$  is inert:

```
sage: heegner_point(37, -7, 3).ring_class_field().degree_over_H()
4
sage: heegner_point(37, -7, 3^2).ring_class_field().degree_over_H()
12
sage: heegner_point(37, -7, 3^3).ring_class_field().degree_over_H()
36
```

The prime dividing  $c$  is split. For example, in the first case  $O_K/cO_K$  is isomorphic to a direct sum of two copies of  $\mathbb{GF}(2)$ , so the units are trivial:

```
sage: heegner_point(37, -7, 2).ring_class_field().degree_over_H()
1
sage: heegner_point(37, -7, 4).ring_class_field().degree_over_H()
2
sage: heegner_point(37, -7, 8).ring_class_field().degree_over_H()
4
```

Now  $c$  is ramified:

```
sage: heegner_point(37, -7, 7).ring_class_field().degree_over_H()
7
sage: heegner_point(37, -7, 7^2).ring_class_field().degree_over_H()
49
```

Check that [trac ticket #15218](#) is solved:

```
sage: E = EllipticCurve("19a");
sage: s = E.heegner_point(-3,2).ring_class_field().galois_group().complex_
↪conjugation()
sage: H = s.domain(); H.absolute_degree()
2
```

### **degree\_over\_K()**

Return the relative degree of this ring class field over the quadratic imaginary field  $K$ .

EXAMPLES:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-7,5)
sage: K5 = P.ring_class_field(); K5
Ring class field extension of QQ[sqrt(-7)] of conductor 5
sage: K5.degree_over_K()
6
sage: type(K5.degree_over_K())
<... 'sage.rings.integer.Integer'>

sage: E = EllipticCurve('389a'); E.heegner_point(-20).ring_class_field().
↪degree_over_K()
2
sage: E.heegner_point(-20,3).ring_class_field().degree_over_K()
4
sage: kronecker(-20,11)
-1
sage: E.heegner_point(-20,11).ring_class_field().degree_over_K()
24
```

### **degree\_over\_Q()**

Return the absolute degree of this field over  $\mathbb{Q}$ .

EXAMPLES:

```
sage: E = EllipticCurve('389a'); K = E.heegner_point(-7,5).ring_class_field()
sage: K.absolute_degree()
12
sage: K.degree_over_K()
6
```

### **discriminant\_of\_K()**

Return the discriminant of the quadratic imaginary field  $K$  contained in *self*.

EXAMPLES:

```
sage: E = EllipticCurve('389a'); K5 = E.heegner_point(-7,5).ring_class_field()
sage: K5.discriminant_of_K()
-7
```

### **galois\_group (base=Rational Field)**

Return the Galois group of *self* over *base*.

INPUT:

- *base* – (default:  $\mathbb{Q}$ ) a subfield of *self* or  $\mathbb{Q}$

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: A = E.heegner_point(-7,5).ring_class_field()
sage: A.galois_group()
Galois group of Ring class field extension of  $\mathbb{Q}(\sqrt{-7})$  of conductor 5
sage: B = E.heegner_point(-7).ring_class_field()
sage: C = E.heegner_point(-7,15).ring_class_field()
sage: A.galois_group()
Galois group of Ring class field extension of  $\mathbb{Q}(\sqrt{-7})$  of conductor 5
sage: A.galois_group(B)
Galois group of Ring class field extension of  $\mathbb{Q}(\sqrt{-7})$  of conductor 5
↳ over Hilbert class field of  $\mathbb{Q}(\sqrt{-7})$ 
sage: A.galois_group().cardinality()
12
sage: A.galois_group(B).cardinality()
6
sage: C.galois_group(A)
Galois group of Ring class field extension of  $\mathbb{Q}(\sqrt{-7})$  of conductor 15
↳ over Ring class field extension of  $\mathbb{Q}(\sqrt{-7})$  of conductor 5
sage: C.galois_group(A).cardinality()
4

```

**is\_subfield(*M*)**

Return True if this ring class field is a subfield of the ring class field *M*. If *M* is not a ring class field, then a `TypeError` is raised.

EXAMPLES:

```

sage: E = EllipticCurve('389a')
sage: A = E.heegner_point(-7,5).ring_class_field()
sage: B = E.heegner_point(-7).ring_class_field()
sage: C = E.heegner_point(-20).ring_class_field()
sage: D = E.heegner_point(-7,15).ring_class_field()
sage: B.is_subfield(A)
True
sage: B.is_subfield(B)
True
sage: B.is_subfield(D)
True
sage: B.is_subfield(C)
False
sage: A.is_subfield(B)
False
sage: A.is_subfield(D)
True

```

**quadratic\_field()**

Return the quadratic imaginary field  $K = \mathbb{Q}(\sqrt{D})$ .

EXAMPLES:

```

sage: E = EllipticCurve('389a'); K = E.heegner_point(-7,5).ring_class_field()
sage: K.quadratic_field()
Number Field in sqrt_minus_7 with defining polynomial x^2 + 7

```

**ramified\_primes()**

Return the primes of  $\mathbb{Z}$  that ramify in this ring class field.

EXAMPLES:

```

sage: E = EllipticCurve('389a'); K55 = E.heegner_point(-7,55).ring_class_
↪field()
sage: K55.ramified_primes()
[5, 7, 11]
sage: E.heegner_point(-7).ring_class_field().ramified_primes()
[7]

```

`sage.schemes.elliptic_curves.heegner.class_number(D)`

Return the class number of the quadratic field with fundamental discriminant *D*.

INPUT:

- *D* – integer

EXAMPLES:

```

sage: sage.schemes.elliptic_curves.heegner.class_number(-20)
2
sage: sage.schemes.elliptic_curves.heegner.class_number(-23)
3
sage: sage.schemes.elliptic_curves.heegner.class_number(-163)
1

```

A `ValueError` is raised when *D* is not a fundamental discriminant:

```

sage: sage.schemes.elliptic_curves.heegner.class_number(-5)
Traceback (most recent call last):
...
ValueError: D (=-5) must be a fundamental discriminant

```

`sage.schemes.elliptic_curves.heegner.ell_heegner_discriminants(self, bound)`

Return the list of *self*'s Heegner discriminants between -1 and -bound.

INPUT:

- *bound* (int) - upper bound for -discriminant

OUTPUT: The list of Heegner discriminants between -1 and -bound for the given elliptic curve.

EXAMPLES:

```

sage: E=EllipticCurve('11a')
sage: E.heegner_discriminants(30)                                     # indirect doctest
[-7, -8, -19, -24]

```

`sage.schemes.elliptic_curves.heegner.ell_heegner_discriminants_list(self, n)`

Return the list of *self*'s first *n* Heegner discriminants smaller than -5.

INPUT:

- *n* (int) - the number of discriminants to compute

OUTPUT: The list of the first *n* Heegner discriminants smaller than -5 for the given elliptic curve.

EXAMPLES:

```

sage: E=EllipticCurve('11a')
sage: E.heegner_discriminants_list(4)                               # indirect doctest
[-7, -8, -19, -24]

```



```
sage.schemes.elliptic_curves.heegner.ell_heegner_point(self, D, c=1, f=None,
                                                    check=True)
```

Returns the Heegner point on this curve associated to the quadratic imaginary field  $K = \mathbb{Q}(\sqrt{D})$ .

If the optional parameter  $c$  is given, returns the higher Heegner point associated to the order of conductor  $c$ .

INPUT:

- $D$  – a Heegner discriminant
- $c$  – (default: 1) conductor, must be coprime to  $DN$
- $f$  – binary quadratic form or 3-tuple  $(A, B, C)$  of coefficients of  $AX^2 + BXY + CY^2$
- `check` – bool (default: True)

OUTPUT:

The Heegner point  $y_c$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: E.heegner_discriminants_list(10)
[-7, -11, -40, -47, -67, -71, -83, -84, -95, -104]
sage: P = E.heegner_point(-7); P                                     # indirect doctest
Heegner point of discriminant -7 on elliptic curve of conductor 37
sage: P.point_exact()
(0 : 0 : 1)
sage: P.curve()
Elliptic Curve defined by y^2 + y = x^3 - x over Rational Field
sage: P = E.heegner_point(-40).point_exact(); P
(a : -a + 1 : 1)
sage: P = E.heegner_point(-47).point_exact(); P
(a : a^4 + a - 1 : 1)
sage: P[0].parent()
Number Field in a with defining polynomial x^5 - x^4 + x^3 + x^2 - 2*x + 1
```

Working out the details manually:

```
sage: P = E.heegner_point(-47).numerical_approx(prec=200)
sage: f = algdep(P[0], 5); f
x^5 - x^4 + x^3 + x^2 - 2*x + 1
sage: f.discriminant().factor()
47^2
```

The Heegner hypothesis is checked:

```
sage: E = EllipticCurve('389a'); P = E.heegner_point(-5, 7);
Traceback (most recent call last):
...
ValueError: N (=389) and D (=-5) must satisfy the Heegner hypothesis
```

We can specify the quadratic form:

```
sage: P = EllipticCurve('389a').heegner_point(-7, 5, (778, 925, 275)); P
Heegner point of discriminant -7 and conductor 5 on elliptic curve of conductor_
↪ 389
sage: P.quadratic_form()
778*x^2 + 925*x*y + 275*y^2
```

```
sage.schemes.elliptic_curves.heegner.heegner_index(self, D, min_p=2, prec=5,
                                                    descent_second_limit=12,
                                                    verbose_mwrank=False,
                                                    check_rank=True)
```

Return an interval that contains the index of the Heegner point  $y_K$  in the group of  $K$ -rational points modulo torsion on this elliptic curve, computed using the Gross-Zagier formula and/or a point search, or possibly half the index if the rank is greater than one.

If the curve has rank  $> 1$ , then the returned index is infinity.

---

**Note:** If  $\text{min\_p}$  is bigger than 2 then the index can be off by any prime less than  $\text{min\_p}$ . This function returns the index divided by 2 exactly when the rank of  $E(K)$  is greater than 1 and  $E(\mathbf{Q})_{/tor} \oplus E^D(\mathbf{Q})_{/tor}$  has index 2 in  $E(K)_{/tor}$ , where the second factor undergoes a twist.

---

INPUT:

- `D` (int) - Heegner discriminant
- `min_p` (int) - (default: 2) only rule out primes = `min_p` dividing the index.
- `verbose_mwrank` (bool) - (default: False); print lots of mwrank search status information when computing regulator
- `prec` (int) - (default: 5), use  $\text{prec} \cdot \sqrt{N} + 20$  terms of L-series in computations, where  $N$  is the conductor.
- `descent_second_limit` - (default: 12)- used in 2-descent when computing regulator of the twist
- `check_rank` - whether to check if the rank is at least 2 by computing the Mordell-Weil rank directly.

OUTPUT: an interval that contains the index, or half the index

EXAMPLES:

```
sage: E = EllipticCurve('11a')
sage: E.heegner_discriminants(50)
[-7, -8, -19, -24, -35, -39, -40, -43]
sage: E.heegner_index(-7)
1.00000?
```

```
sage: E = EllipticCurve('37b')
sage: E.heegner_discriminants(100)
[-3, -4, -7, -11, -40, -47, -67, -71, -83, -84, -95]
sage: E.heegner_index(-95)          # long time (1 second)
2.00000?
```

This tests doing direct computation of the Mordell-Weil group.

```
sage: EllipticCurve('675b').heegner_index(-11)
3.0000?
```

Currently discriminants -3 and -4 are not supported:

```
sage: E.heegner_index(-3)
Traceback (most recent call last):
...
ArithmeticError: Discriminant (=-3) must not be -3 or -4.
```

The curve 681b returns the true index, which is 3:

```
sage: E = EllipticCurve('681b')
sage: I = E.heegner_index(-8); I
3.0000?
```

In fact, whenever the returned index has a denominator of 2, the true index is got by multiplying the returned index by 2. Unfortunately, this is not an if and only if condition, i.e., sometimes the index must be multiplied by 2 even though the denominator is not 2.

This example demonstrates the `descent_second_limit` option, which can be used to fine tune the 2-descent used to compute the regulator of the twist:

```
sage: E = EllipticCurve([1,-1,0,-1228,-16267])
sage: E.heegner_index(-8)
Traceback (most recent call last):
...
RuntimeError: ...
```

However when we search higher, we find the points we need:

```
sage: E.heegner_index(-8, descent_second_limit=16, check_rank=False)
2.00000?
```

Two higher rank examples (of ranks 2 and 3):

```
sage: E = EllipticCurve('389a')
sage: E.heegner_index(-7)
+Infinity
sage: E = EllipticCurve('5077a')
sage: E.heegner_index(-7)
+Infinity
sage: E.heegner_index(-7, check_rank=False)
0.001?
sage: E.heegner_index(-7, check_rank=False).lower() == 0
True
```

```
sage.schemes.elliptic_curves.heegner.heegner_index_bound(self, D=0, prec=5,
max_height=None)
```

Assume `self` has rank 0.

Return a list  $v$  of primes such that if an odd prime  $p$  divides the index of the Heegner point in the group of rational points modulo torsion, then  $p$  is in  $v$ .

If 0 is in the interval of the height of the Heegner point computed to the given `prec`, then this function returns  $v = 0$ . This does not mean that the Heegner point is torsion, just that it is very likely torsion.

If we obtain no information from a search up to `max_height`, e.g., if the Siksek et al. bound is bigger than `max_height`, then we return  $v = -1$ .

INPUT:

- `D` (int) - (default: 0) Heegner discriminant; if 0, use the first discriminant -4 that satisfies the Heegner hypothesis
- `verbose` (bool) - (default: True)
- `prec` (int) - (default: 5), use  $prec \cdot \sqrt{(N)} + 20$  terms of  $L$ -series in computations, where  $N$  is the conductor.
- `max_height` (float) - should be  $\geq 21$ ; bound on logarithmic naive height used in point searches. Make smaller to make this function faster, at the expense of possibly obtaining a worse answer. A good

range is between 13 and 21.

OUTPUT:

- $v$  - list or int (bad primes or 0 or -1)
- $D$  - the discriminant that was used (this is useful if  $D$  was automatically selected).
- `exact` - either False, or the exact Heegner index (up to factors of 2)

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.heegner_index_bound()
([2], -7, 2)
```

`sage.schemes.elliptic_curves.heegner.heegner_point` ( $N, D=None, c=1$ )

Return a specific Heegner point of level  $N$  with given discriminant and conductor. If  $D$  is not specified, then the first valid Heegner discriminant is used. If  $c$  is not given, then  $c = 1$  is used.

INPUT:

- $N$  – level (positive integer)
- $D$  – discriminant (optional: default first valid  $D$ )
- $c$  – conductor (positive integer, optional, default: 1)

EXAMPLES:

```
sage: heegner_point(389)
Heegner point 1/778*sqrt(-7) - 185/778 of discriminant -7 on X_0(389)
sage: heegner_point(389,-7)
Heegner point 1/778*sqrt(-7) - 185/778 of discriminant -7 on X_0(389)
sage: heegner_point(389,-7,5)
Heegner point 5/778*sqrt(-7) - 147/778 of discriminant -7 and conductor 5 on X_
↪0(389)
sage: heegner_point(389,-20)
Heegner point 1/778*sqrt(-20) - 165/389 of discriminant -20 on X_0(389)
```

`sage.schemes.elliptic_curves.heegner.heegner_point_height` (*self*,  $D$ ,  $prec=2$ , *check\_rank=True*)

Use the Gross-Zagier formula to compute the Neron-Tate canonical height over  $K$  of the Heegner point corresponding to  $D$ , as an interval (it is computed to some precision using  $L$ -functions).

If the curve has rank at least 2, then the returned height is the exact Sage integer 0.

INPUT:

- $D$  (int) - fundamental discriminant ( $\neq -3, -4$ )
- **`prec` (int) - (default: 2), use  $prec \cdot \sqrt{(N)} + 20$  terms of  $L$ -series in computations, where  $N$  is the conductor.**
- `check_rank` - whether to check if the rank is at least 2 by computing the Mordell-Weil rank directly.

OUTPUT: Interval that contains the height of the Heegner point.

EXAMPLES:

```
sage: E = EllipticCurve('11a')
sage: E.heegner_point_height(-7)
0.22227?
```

Some higher rank examples:

```
sage: E = EllipticCurve('389a')
sage: E.heegner_point_height(-7)
0
sage: E = EllipticCurve('5077a')
sage: E.heegner_point_height(-7)
0
sage: E.heegner_point_height(-7, check_rank=False)
0.0000?
```

`sage.schemes.elliptic_curves.heegner.heegner_points(N, D=None, c=None)`

Return all Heegner points of given level  $N$ . Can also restrict to Heegner points with specified discriminant  $D$  and optionally conductor  $c$ .

INPUT:

- $N$  – level (positive integer)
- $D$  – discriminant (negative integer)
- $c$  – conductor (positive integer)

EXAMPLES:

```
sage: heegner_points(389, -7)
Set of all Heegner points on X_0(389) associated to QQ[sqrt(-7)]
sage: heegner_points(389, -7, 1)
All Heegner points of conductor 1 on X_0(389) associated to QQ[sqrt(-7)]
sage: heegner_points(389, -7, 5)
All Heegner points of conductor 5 on X_0(389) associated to QQ[sqrt(-7)]
```

`sage.schemes.elliptic_curves.heegner.heegner_sha_an(self, D, prec=53)`

Return the conjectural (analytic) order of Sha for  $E$  over the field  $K = \mathbf{Q}(\sqrt{D})$ .

INPUT:

- $D$  – negative integer; the Heegner discriminant
- $prec$  – integer (default: 53); bits of precision to compute analytic order of Sha

OUTPUT:

(floating point number) an approximation to the conjectural order of Sha.

---

**Note:** Often you'll want to do `proof.elliptic_curve(False)` when using this function, since often the twisted elliptic curves that come up have enormous conductor, and Sha is nontrivial, which makes provably finding the Mordell-Weil group using 2-descent difficult.

---

EXAMPLES:

An example where  $E$  has conductor 11:

```
sage: E = EllipticCurve('11a')
sage: E.heegner_sha_an(-7)                                     # long time
1.0000000000000000
```

The cache works:

```
sage: E.heegner_sha_an(-7) is E.heegner_sha_an(-7)           # long time
True
```

Lower precision:

```
sage: E.heegner_sha_an(-7,10) # long time
1.0
```

Checking that the cache works for any precision:

```
sage: E.heegner_sha_an(-7,10) is E.heegner_sha_an(-7,10) # long time
True
```

Next we consider a rank 1 curve with nontrivial Sha over the quadratic imaginary field  $K$ ; however, there is no Sha for  $E$  over  $\mathbf{Q}$  or for the quadratic twist of  $E$ :

```
sage: E = EllipticCurve('37a')
sage: E.heegner_sha_an(-40) # long time
4.000000000000000
sage: E.quadratic_twist(-40).sha().an() # long time
1
sage: E.sha().an() # long time
1
```

A rank 2 curve:

```
sage: E = EllipticCurve('389a') # long time
sage: E.heegner_sha_an(-7) # long time
1.000000000000000
```

If we remove the hypothesis that  $E(K)$  has rank 1 in Conjecture 2.3 in [Gross-Zagier, 1986, page 311], then that conjecture is false, as the following example shows:

```
sage: E = EllipticCurve('65a') # long time
sage: E.heegner_sha_an(-56) # long time
1.000000000000000
sage: E.torsion_order() # long time
2
sage: E.tamagawa_product() # long time
1
sage: E.quadratic_twist(-56).rank() # long time
2
```

`sage.schemes.elliptic_curves.heegner.is_inert( $D, p$ )`

Return True if  $p$  is an inert prime in the field  $\mathbf{Q}(\sqrt{D})$ .

INPUT:

- $D$  – fundamental discriminant
- $p$  – prime integer

EXAMPLES:

```
sage: sage.schemes.elliptic_curves.heegner.is_inert(-7,3)
True
sage: sage.schemes.elliptic_curves.heegner.is_inert(-7,7)
False
sage: sage.schemes.elliptic_curves.heegner.is_inert(-7,11)
False
```

`sage.schemes.elliptic_curves.heegner.is_kolyvagin_conductor(N, E, D, r, n, c)`

Return True if  $c$  is a Kolyvagin conductor for level  $N$ , discriminant  $D$ , mod  $n$ , etc., i.e.,  $c$  is divisible by exactly  $r$  prime factors, is coprime to  $ND$ , each prime dividing  $c$  is inert, and if  $E$  is not None then  $n \mid \gcd(p+1, a_p(E))$  for each prime  $p$  dividing  $c$ .

INPUT:

- $N$  – level (positive integer)
- $E$  – elliptic curve or None
- $D$  – negative fundamental discriminant
- $r$  – number of prime factors (nonnegative integer) or None
- $n$  – torsion order (i.e., do we get class in  $(E(K_c)/nE(K_c))^{Gal(K_c/K)}$ ?)
- $c$  – conductor (positive integer)

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.heegner import is_kolyvagin_conductor
sage: is_kolyvagin_conductor(389, None, -7, 1, None, 5)
True
sage: is_kolyvagin_conductor(389, None, -7, 1, None, 7)
False
sage: is_kolyvagin_conductor(389, None, -7, 1, None, 11)
False
sage: is_kolyvagin_conductor(389, EllipticCurve('389a'), -7, 1, 3, 5)
True
sage: is_kolyvagin_conductor(389, EllipticCurve('389a'), -7, 1, 11, 5)
False
```

`sage.schemes.elliptic_curves.heegner.is_ramified(D, p)`

Return True if  $p$  is a ramified prime in the field  $\mathbf{Q}(\sqrt{D})$ .

INPUT:

- $D$  – fundamental discriminant
- $p$  – prime integer

EXAMPLES:

```
sage: sage.schemes.elliptic_curves.heegner.is_ramified(-7, 2)
False
sage: sage.schemes.elliptic_curves.heegner.is_ramified(-7, 7)
True
sage: sage.schemes.elliptic_curves.heegner.is_ramified(-1, 2)
True
```

`sage.schemes.elliptic_curves.heegner.is_split(D, p)`

Return True if  $p$  is a split prime in the field  $\mathbf{Q}(\sqrt{D})$ .

INPUT:

- $D$  – fundamental discriminant
- $p$  – prime integer

EXAMPLES:

```

sage: sage.schemes.elliptic_curves.heegner.is_split(-7,3)
False
sage: sage.schemes.elliptic_curves.heegner.is_split(-7,7)
False
sage: sage.schemes.elliptic_curves.heegner.is_split(-7,11)
True

```

`sage.schemes.elliptic_curves.heegner.kolyvagin_point` (*self*,  $D$ ,  $c=1$ , *check=True*)  
 Returns the Kolyvagin point on this curve associated to the quadratic imaginary field  $K = \mathbf{Q}(\sqrt{D})$  and conductor  $c$ .

INPUT:

- $D$  – a Heegner discriminant
- $c$  – (default: 1) conductor, must be coprime to  $DN$
- *check* – bool (default: True)

OUTPUT:

The Kolyvagin point  $P$  of conductor  $c$ .

EXAMPLES:

```

sage: E = EllipticCurve('37a1')
sage: P = E.kolyvagin_point(-67); P
Kolyvagin point of discriminant -67 on elliptic curve of conductor 37
sage: P.numerical_approx() # abs tol 1e-14
(6.000000000000000 : -15.000000000000000 : 1.000000000000000)
sage: P.index()
6
sage: g = E((0,-1,1)) # a generator
sage: E.regulator() == E.regulator_of_points([g])
True
sage: 6*g
(6 : -15 : 1)

```

`sage.schemes.elliptic_curves.heegner.kolyvagin_reduction_data` ( $E$ ,  $q$ ,  
*first\_only=True*)

Given an elliptic curve of positive rank and a prime  $q$ , this function returns data about how to use Kolyvagin's  $q$ -torsion Heegner point Euler system to do computations with this curve. See the precise description of the output below.

INPUT:

- $E$  – elliptic curve over  $\mathbf{Q}$  of rank 1 or 2
- $q$  – an odd prime that does not divide the order of the rational torsion subgroup of  $E$
- **first\_only** – bool (default: True) whether to only return the first prime that one can work modulo to get data about the Euler system

OUTPUT in the rank 1 case or when the default flag `first_only=True`:

- $\ell$  – first good odd prime satisfying the Kolyvagin condition that  $q$  divides  $\gcd(a_{\ell}, \ell+1)$  and the reduction map is surjective to  $E(\mathbf{F}_{\ell})/qE(\mathbf{F}_{\ell})$
- $D$  – discriminant of the first quadratic imaginary field  $K$  that satisfies the Heegner hypothesis for  $E$  such that both  $\ell$  is inert in  $K$ , and the twist  $E^D$  has analytic rank  $\leq 1$
- $h_D$  – the class number of  $K$



- the dimension of the Brandt module  $B(\ell, N)$ , where  $N$  is the conductor of  $E$

OUTPUT in the rank 2 case:

- $\ell_1$  – first prime (as above in the rank 1 case) where reduction map is surjective
- $\ell_2$  – second prime (as above) where reduction map is surjective
- $D$  – **discriminant of the first quadratic imaginary field**  $K$  that satisfies the Heegner hypothesis for  $E$  such that both  $\ell_1$  and  $\ell_2$  are simultaneously inert in  $K$ , and the twist  $E^D$  has analytic rank  $\leq 1$
- $h_D$  – the class number of  $K$
- the dimension of the Brandt module  $B(\ell_1, N)$ , where  $N$  is the conductor of  $E$
- the dimension of the Brandt module  $B(\ell_2, N)$

EXAMPLES:

Import this function:

```
sage: from sage.schemes.elliptic_curves.heegner import kolyvagin_reduction_data
```

A rank 1 example:

```
sage: kolyvagin_reduction_data(EllipticCurve('37a1'), 3)
(17, -7, 1, 52)
```

A rank 3 example:

```
sage: kolyvagin_reduction_data(EllipticCurve('5077a1'), 3)
(11, -47, 5, 4234)
sage: H = heegner_points(5077, -47)
sage: [c for c in H.kolyvagin_conductors(2, 10, EllipticCurve('5077a1'), 3) if c%11]
[667, 943, 1189, 2461]
sage: factor(667)
23 * 29
```

A rank 4 example (the first Kolyvagin class that we could try to compute would be  $P_{23 \cdot 29 \cdot 41}$ , and would require working in a space of dimension 293060 (so prohibitive at present):

```
sage: E = elliptic_curves.rank(4)[0]
sage: kolyvagin_reduction_data(E, 3) # long time
(11, -71, 7, 293060)
sage: H = heegner_points(293060, -71)
sage: H.kolyvagin_conductors(1, 4, E, 3)
[11, 17, 23, 41]
```

The first rank 2 example:

```
sage: kolyvagin_reduction_data(EllipticCurve('389a'), 3)
(5, -7, 1, 130)
sage: kolyvagin_reduction_data(EllipticCurve('389a'), 3, first_only=False)
(5, 17, -7, 1, 130, 520)
```

A large  $q = 7$ :

```
sage: kolyvagin_reduction_data(EllipticCurve('1143c1'), 7, first_only=False)
(13, 83, -59, 3, 1536, 10496)
```

Additive reduction:

```
sage: kolyvagin_reduction_data(EllipticCurve('2350g1'), 5, first_only=False)
(19, 239, -311, 19, 6480, 85680)
```

`sage.schemes.elliptic_curves.heegner.make_monik(f)`  
`make_monik` returns a monic integral polynomial  $g$  and an integer  $d$  such that if  $\alpha$  is a root of  $g$  then a root of  $f$  is  $\alpha/d$ .

INPUT:

- $f$  – polynomial over the rational numbers

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: sage.schemes.elliptic_curves.heegner.make_monik(3*x^3 + 14*x^2 - 7*x + 5)
(x^3 + 14*x^2 - 21*x + 45, 3)
```

In this example we verify that `make_monik` does what we claim it does:

```
sage: K.<a> = NumberField(x^3 + 17*x - 3)
sage: f = (a/7+2/3).minpoly(); f
x^3 - 2*x^2 + 247/147*x - 4967/9261
sage: g, d = sage.schemes.elliptic_curves.heegner.make_monik(f)
sage: g
x^3 - 18522*x^2 + 144110421*x - 426000323007
sage: d
9261
sage: K.<b> = NumberField(g)
sage: (b/d).minpoly()
x^3 - 2*x^2 + 247/147*x - 4967/9261
```

`sage.schemes.elliptic_curves.heegner.nearby_rational_poly(f, **kws)`  
Return a polynomial whose coefficients are rational numbers close to the coefficients of  $f$ .

INPUT:

- $f$  – polynomial with real floating point entries
- `**kws` – passed on to `nearby_rational` method

EXAMPLES:

```
sage: R.<x> = RR[]
sage: sage.schemes.elliptic_curves.heegner.nearby_rational_poly(2.1*x^2 + 3.5*x - 1.2, max_error=10e-16)
21/10*X^2 + 7/2*X - 6/5
sage: sage.schemes.elliptic_curves.heegner.nearby_rational_poly(2.1*x^2 + 3.5*x - 1.2, max_error=10e-17)
4728779608739021/2251799813685248*X^2 + 7/2*X - 5404319552844595/4503599627370496
sage: RR(4728779608739021/2251799813685248 - 21/10)
8.88178419700125e-17
```

`sage.schemes.elliptic_curves.heegner.quadratic_order(D, c, names='a')`  
Return order of conductor  $c$  in quadratic field with fundamental discriminant  $D$ .

INPUT:

- $D$  – fundamental discriminant
- $c$  – conductor
- `names` – string (default: 'a')

OUTPUT:

- order  $R$  of conductor  $c$  in an imaginary quadratic field
- the element  $c\sqrt{D}$  as an element of  $R$

The generator for the field is named 'a' by default.

EXAMPLES:

```
sage: sage.schemes.elliptic_curves.heegner.quadratic_order(-7,3)
(Order in Number Field in a with defining polynomial x^2 + 7, 3*a)
sage: sage.schemes.elliptic_curves.heegner.quadratic_order(-7,3,'alpha')
(Order in Number Field in alpha with defining polynomial x^2 + 7, 3*alpha)
```

`sage.schemes.elliptic_curves.heegner.satisfies_heegner_hypothesis` (*self*,  $D$ )

Returns True precisely when  $D$  is a fundamental discriminant that satisfies the Heegner hypothesis for this elliptic curve.

EXAMPLES:

```
sage: E = EllipticCurve('11a1')
sage: E.satisfies_heegner_hypothesis(-7)
True
sage: E.satisfies_heegner_hypothesis(-11)
False
```

`sage.schemes.elliptic_curves.heegner.satisfies_weak_heegner_hypothesis` ( $N$ ,  $D$ )

Check that  $D$  satisfies the weak Heegner hypothesis relative to  $N$ . This is all that is needed to define Heegner points.

The condition is that  $D < 0$  is a fundamental discriminant and that each unramified prime dividing  $N$  splits in  $K = \mathbb{Q}(\sqrt{D})$  and each ramified prime exactly divides  $N$ . We also do not require that  $D < -4$ .

INPUT:

- $N$  – positive integer
- $D$  – negative integer

EXAMPLES:

```
sage: s = sage.schemes.elliptic_curves.heegner.satisfies_weak_heegner_hypothesis
sage: s(37,-7)
True
sage: s(37,-37)
False
sage: s(37,-37*4)
True
sage: s(100,-4)
False
sage: [D for D in [-1,-2,...,-40] if s(37,D)]
[-3, -4, -7, -11, -40]
sage: [D for D in [-1,-2,...,-100] if s(37,D)]
[-3, -4, -7, -11, -40, -47, -67, -71, -83, -84, -95]
sage: EllipticCurve('37a').heegner_discriminants_list(10)
[-7, -11, -40, -47, -67, -71, -83, -84, -95, -104]
```

`sage.schemes.elliptic_curves.heegner.simplest_rational_poly` ( $f$ ,  $prec$ )

Return a polynomial whose coefficients are as simple as possible rationals that are also close to the coefficients of  $f$ .

INPUT:

- $f$  – polynomial with real floating point entries
- $\text{prec}$  – positive integer

EXAMPLES:

```
sage: R.<x> = RR[]
sage: sage.schemes.elliptic_curves.heegner.simplest_rational_poly(2.1*x^2 + 3.5*x,
↪ 1.2, 53)
21/10*x^2 + 7/2*x - 6/5
```

### 15.11.23 $p$ -adic L-functions of elliptic curves

To an elliptic curve  $E$  over the rational numbers and a prime  $p$ , one can associate a  $p$ -adic L-function; at least if  $E$  does not have additive reduction at  $p$ . This function is defined by interpolation of L-values of  $E$  at twists. Through the main conjecture of Iwasawa theory it should also be equal to a characteristic series of a certain Selmer group.

If  $E$  is ordinary, then it is an element of the Iwasawa algebra  $\Lambda(\mathbf{Z}_p^\times) = \mathbf{Z}_p[\Delta][[T]]$ , where  $\Delta$  is the group of  $(p-1)$ -st roots of unity in  $\mathbf{Z}_p^\times$ , and  $T = [\gamma] - 1$  where  $\gamma = 1 + p$  is a generator of  $1 + p\mathbf{Z}_p$ . (There is a slightly different description for  $p = 2$ .)

One can decompose this algebra as the direct product of the subalgebras corresponding to the characters of  $\Delta$ , which are simply the powers  $\tau^\eta$  ( $0 \leq \eta \leq p-2$ ) of the Teichmueller character  $\tau : \Delta \rightarrow \mathbf{Z}_p^\times$ . Projecting the L-function into these components gives  $p-1$  power series in  $T$ , each with coefficients in  $\mathbf{Z}_p$ .

If  $E$  is supersingular, the series will have coefficients in a quadratic extension of  $\mathbf{Q}_p$ , and the coefficients will be unbounded. In this case we have only implemented the series for  $\eta = 0$ . We have also implemented the  $p$ -adic L-series as formulated by Perrin-Riou [BP], which has coefficients in the Dieudonné module  $D_p E = H_{dR}^1(E/\mathbf{Q}_p)$  of  $E$ . There is a different description by Pollack [Po] which is not available here.

According to the  $p$ -adic version of the Birch and Swinnerton-Dyer conjecture [MTT], the order of vanishing of the L-function at the trivial character (i.e. of the series for  $\eta = 0$  at  $T = 0$ ) is just the rank of  $E(\mathbf{Q})$ , or this rank plus one if the reduction at  $p$  is split multiplicative.

See [SW] for more details.

REFERENCES:

- [MTT] B. Mazur, J. Tate, and J. Teitelbaum, On  $p$ -adic analogues of the conjectures of Birch and Swinnerton-Dyer, *Inventiones mathematicae* 84, (1986), 1-48.
- [BP] Dominique Bernardi and Bernadette Perrin-Riou, Variante  $p$ -adique de la conjecture de Birch et Swinnerton-Dyer (le cas supersingulier), *C. R. Acad. Sci. Paris, Sér I. Math.*, 317 (1993), no. 3, 227-232.
- [Po] Robert Pollack, On the  $p$ -adic L-function of a modular form at a supersingular prime, *Duke Math. J.* 118 (2003), no. 3, 523-558.
- [SW] William Stein and Christian Wuthrich, Algorithms for the Arithmetic of Elliptic Curves using Iwasawa Theory, *Mathematics of Computation* 82 (2013), 1757-1792.

AUTHORS:

- William Stein (2007-01-01): first version
- Chris Wuthrich (22/05/2007): changed minor issues and added supersingular things
- Chris Wuthrich (11/2008): added quadratic\_twists
- David Loeffler (01/2011): added nontrivial Teichmueller components

```
class sage.schemes.elliptic_curves.padic_lseries.pAdicLseries(E, p, implementation='eclib',
normal-ize='L_ratio')
```

Bases: `sage.structure.sage_object.SageObject`

The  $p$ -adic L-series of an elliptic curve.

EXAMPLES:

An ordinary example:

```
sage: e = EllipticCurve('389a')
sage: L = e.padic_lseries(5)
sage: L.series(0)
Traceback (most recent call last):
...
ValueError: n (=0) must be a positive integer
sage: L.series(1)
O(T^1)
sage: L.series(2)
O(5^4) + O(5)*T + (4 + O(5))*T^2 + (2 + O(5))*T^3 + (3 + O(5))*T^4 + O(T^5)
sage: L.series(3, prec=10)
O(5^5) + O(5^2)*T + (4 + 4*5 + O(5^2))*T^2 + (2 + 4*5 + O(5^2))*T^3 + (3 + O(5^
↪2))*T^4 + (1 + O(5))*T^5 + O(5)*T^6 + (4 + O(5))*T^7 + (2 + O(5))*T^8 + O(5)*T^
↪9 + O(T^10)
sage: L.series(2,quadratic_twist=-3)
2 + 4*5 + 4*5^2 + O(5^4) + O(5)*T + (1 + O(5))*T^2 + (4 + O(5))*T^3 + O(5)*T^4 +
↪O(T^5)
```

A prime  $p$  such that  $E[p]$  is reducible:

```
sage: L = EllipticCurve('11a').padic_lseries(5)
sage: L.series(1)
5 + O(5^2) + O(T)
sage: L.series(2)
5 + 4*5^2 + O(5^3) + O(5^0)*T + O(5^0)*T^2 + O(5^0)*T^3 + O(5^0)*T^4 + O(T^5)
sage: L.series(3)
5 + 4*5^2 + 4*5^3 + O(5^4) + O(5)*T + O(5)*T^2 + O(5)*T^3 + O(5)*T^4 + O(T^5)
```

An example showing the calculation of nontrivial Teichmueller twists:

```
sage: E=EllipticCurve('11a1')
sage: lp=E.padic_lseries(7)
sage: lp.series(4,eta=1)
3 + 7^3 + 6*7^4 + 3*7^5 + O(7^6) + (2*7 + 7^2 + O(7^3))*T + (1 + 5*7^2 + O(7^
↪3))*T^2 + (4 + 4*7 + 4*7^2 + O(7^3))*T^3 + (4 + 3*7 + 7^2 + O(7^3))*T^4 + O(T^5)
sage: lp.series(4,eta=2)
5 + 6*7 + 4*7^2 + 2*7^3 + 3*7^4 + 2*7^5 + O(7^6) + (6 + 4*7 + 7^2 + O(7^3))*T +
↪(3 + 2*7^2 + O(7^3))*T^2 + (1 + 4*7 + 7^2 + O(7^3))*T^3 + (6 + 6*7 + 6*7^2 +
↪O(7^3))*T^4 + O(T^5)
sage: lp.series(4,eta=3)
O(7^6) + (5 + 4*7 + 2*7^2 + O(7^3))*T + (6 + 5*7 + 2*7^2 + O(7^3))*T^2 + (5*7 +
↪O(7^3))*T^3 + (7 + 4*7^2 + O(7^3))*T^4 + O(T^5)
```

(Note that the last series vanishes at  $T = 0$ , which is consistent with

```
sage: E.quadratic_twist(-7).rank()
1
```

This proves that  $E$  has rank 1 over  $\mathbf{Q}(\zeta_7)$ .)

the load-dumps test:

```
sage: lp = EllipticCurve('11a').padic_lseries(5)
sage: lp == loads(dumps(lp))
True
```

**alpha** (*prec=20*)

Return a  $p$ -adic root  $\alpha$  of the polynomial  $x^2 - a_p x + p$  with  $\text{ord}_p(\alpha) < 1$ . In the ordinary case this is just the unit root.

INPUT:

- *prec* - positive integer, the  $p$ -adic precision of the root.

EXAMPLES:

Consider the elliptic curve 37a:

```
sage: E = EllipticCurve('37a')
```

An ordinary prime:

```
sage: L = E.padicalseries(5)
sage: alpha = L.alpha(10); alpha
3 + 2*5 + 4*5^2 + 2*5^3 + 5^4 + 4*5^5 + 2*5^7 + 5^8 + 5^9 + O(5^10)
sage: alpha^2 - E.ap(5)*alpha + 5
O(5^10)
```

A supersingular prime:

```
sage: L = E.padicalseries(3)
sage: alpha = L.alpha(10); alpha
alpha + O(alpha^21)
sage: alpha^2 - E.ap(3)*alpha + 3
O(alpha^22)
```

A reducible prime:

```
sage: L = EllipticCurve('11a').padicalseries(5)
sage: L.alpha(5)
1 + 4*5 + 3*5^2 + 2*5^3 + 4*5^4 + O(5^5)
```

**elliptic\_curve** ()

Return the elliptic curve to which this  $p$ -adic L-series is associated.

EXAMPLES:

```
sage: L = EllipticCurve('11a').padicalseries(5)
sage: L.elliptic_curve()
Elliptic Curve defined by y^2 + y = x^3 - x^2 - 10*x - 20 over Rational Field
```

**measure** ( $a, n, \text{prec}, \text{quadratic\_twist}=1, \text{sign}=1$ )

Return the measure on  $\mathbf{Z}_p^\times$  defined by

$$\mu_{E,\alpha}^+(a + p^n \mathbf{Z}_p) = \frac{1}{\alpha^n} \left[ \frac{a}{p^n} \right]^+ - \frac{1}{\alpha^{n+1}} \left[ \frac{a}{p^{n+1}} \right]^+$$

where  $[\cdot]^+$  is the modular symbol. This is used to define this  $p$ -adic L-function (at least when the reduction is good).

The optional argument `sign` allows the minus symbol  $[-]$  to be substituted for the plus symbol.

The optional argument `quadratic_twist` replaces  $E$  by the twist in the above formula, but the twisted modular symbol is computed using a sum over modular symbols of  $E$  rather than finding the modular symbols for the twist. Quadratic twists are only implemented if the sign is  $+1$ .

Note that the normalization is not correct at this stage: use `_quotient_of_periods` and `_quotient_of_periods_to_twist` to correct.

Note also that this function does not check if the condition on the `quadratic_twist=D` is satisfied. So the result will only be correct if for each prime  $\ell$  dividing  $D$ , we have  $\text{ord}_\ell(N) \leq \text{ord}_\ell(D)$ , where  $N$  is the conductor of the curve.

INPUT:

- `a` - an integer
- `n` - a non-negative integer
- `prec` - an integer
- `quadratic_twist` (default = 1) - a fundamental discriminant of a quadratic field, should be co-prime to the conductor of  $E$
- `sign` (default = 1) - an integer, which should be  $\pm 1$ .

EXAMPLES:

```
sage: E = EllipticCurve('37a')
sage: L = E.padic_lseries(5)
sage: L.measure(1,2, prec=9)
2 + 3*5 + 4*5^3 + 2*5^4 + 3*5^5 + 3*5^6 + 4*5^7 + 4*5^8 + O(5^9)
sage: L.measure(1,2, quadratic_twist=8,prec=15)
O(5^15)
sage: L.measure(1,2, quadratic_twist=-4,prec=15)
4 + 4*5 + 4*5^2 + 3*5^3 + 2*5^4 + 5^5 + 3*5^6 + 5^8 + 2*5^9 + 3*5^12 + 2*5^13 +
↪ 4*5^14 + O(5^15)

sage: E = EllipticCurve('11a1')
sage: a = E.quadratic_twist(-3).padic_lseries(5).measure(1,2,prec=15)
sage: b = E.padic_lseries(5).measure(1,2, quadratic_twist=-3,prec=15)
sage: a == b * E.padic_lseries(5)._quotient_of_periods_to_twist(-3)
True
```

**modular\_symbol** ( $r$ ,  $sign=1$ ,  $quadratic\_twist=1$ )

Return the modular symbol evaluated at  $r$ . This is used to compute this  $p$ -adic L-series.

Note that the normalization is not correct at this stage: use `_quotient_of_periods_to_twist` to correct.

Note also that this function does not check if the condition on the `quadratic_twist=D` is satisfied. So the result will only be correct if for each prime  $\ell$  dividing  $D$ , we have  $\text{ord}_\ell(N) \leq \text{ord}_\ell(D)$ , where  $N$  is the conductor of the curve.

INPUT:

- `r` - a cusp given as either a rational number or `oo`
- `sign` -  $+1$  (default) or  $-1$  (only implemented without twists)
- `quadratic_twist` - a fundamental discriminant of a quadratic field or  $+1$  (default)

EXAMPLES:

```

sage: E = EllipticCurve('11a1')
sage: lp = E.padic_lseries(5)
sage: [lp.modular_symbol(r) for r in [0, 1/5, oo, 1/11]]
[1/5, 6/5, 0, 0]
sage: [lp.modular_symbol(r, sign=-1) for r in [0, 1/3, oo, 1/7]]
[0, 1/2, 0, -1/2]
sage: [lp.modular_symbol(r, quadratic_twist=-20) for r in [0, 1/5, oo, 1/11]]
[1, 1, 0, 1/2]

sage: E = EllipticCurve('20a1')
sage: Et = E.quadratic_twist(-4)
sage: lpt = Et.padic_lseries(5)
sage: eta = lpt._quotient_of_periods_to_twist(-4)
sage: lpt.modular_symbol(0) == lp.modular_symbol(0, quadratic_twist=-4) / eta
True

```

**order\_of\_vanishing()**

Return the order of vanishing of this  $p$ -adic L-series.

The output of this function is provably correct, due to a theorem of Kato [Ka].

NOTE: currently  $p$  must be a prime of good ordinary reduction.

REFERENCES:

- [MTT] B. Mazur, J. Tate, and J. Teitelbaum, On  $p$ -adic analogues of the conjectures of Birch and Swinnerton-Dyer, *Inventiones mathematicae* 84, (1986), 1-48.
- [Ka] Kayuza Kato,  $p$ -adic Hodge theory and values of zeta functions of modular forms, *Cohomologies  $p$ -adiques et applications arithmétiques III*, Astérisque vol 295, SMF, Paris, 2004.

EXAMPLES:

```

sage: L = EllipticCurve('11a').padic_lseries(3)
sage: L.order_of_vanishing()
0
sage: L = EllipticCurve('11a').padic_lseries(5)
sage: L.order_of_vanishing()
0
sage: L = EllipticCurve('37a').padic_lseries(5)
sage: L.order_of_vanishing()
1
sage: L = EllipticCurve('43a').padic_lseries(3)
sage: L.order_of_vanishing()
1
sage: L = EllipticCurve('37b').padic_lseries(3)
sage: L.order_of_vanishing()
0
sage: L = EllipticCurve('389a').padic_lseries(3)
sage: L.order_of_vanishing()
2
sage: L = EllipticCurve('389a').padic_lseries(5)
sage: L.order_of_vanishing()
2
sage: L = EllipticCurve('5077a').padic_lseries(5, implementation = 'eclib')
sage: L.order_of_vanishing()
3

```

**prime()**

Return the prime  $p$  as in ‘ $p$ -adic L-function’.



EXAMPLES:

```
sage: L = EllipticCurve('11a').padic_lseries(5)
sage: L.prime()
5
```

**teichmuller**(*prec*)

Return Teichmuller lifts to the given precision.

INPUT:

- *prec* - a positive integer.

OUTPUT:

- a list of  $p$ -adic numbers, the cached Teichmuller lifts

EXAMPLES:

```
sage: L = EllipticCurve('11a').padic_lseries(7)
sage: L.teichmuller(1)
[0, 1, 2, 3, 4, 5, 6]
sage: L.teichmuller(2)
[0, 1, 30, 31, 18, 19, 48]
```

```
class sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesOrdinary(E, p,
                                                                    im-
                                                                    ple-
                                                                    men-
                                                                    ta-
                                                                    tion='eclib',
                                                                    nor-
                                                                    mal-
                                                                    ize='L_ratio')
```

Bases: `sage.schemes.elliptic_curves.padic_lseries.pAdicLseries`

**is\_ordinary**()

Return True if the elliptic curve that this L-function is attached to is ordinary.

EXAMPLES:

```
sage: L = EllipticCurve('11a').padic_lseries(5)
sage: L.is_ordinary()
True
```

**is\_supersingular**()

Return True if the elliptic curve that this L function is attached to is supersingular.

EXAMPLES:

```
sage: L = EllipticCurve('11a').padic_lseries(5)
sage: L.is_supersingular()
False
```

**power\_series**(*n=2, quadratic\_twist=1, prec=5, eta=0*)

Return the  $n$ -th approximation to the  $p$ -adic L-series, in the component corresponding to the  $\eta$ -th power of the Teichmueller character, as a power series in  $T$  (corresponding to  $\gamma - 1$  with  $\gamma = 1 + p$  as a generator of  $1 + p\mathbb{Z}_p$ ). Each coefficient is a  $p$ -adic number whose precision is provably correct.

Here the normalization of the  $p$ -adic L-series is chosen such that  $L_p(E, 1) = (1 - 1/\alpha)^2 L(E, 1)/\Omega_E$  where  $\alpha$  is the unit root of the characteristic polynomial of Frobenius on  $T_p E$  and  $\Omega_E$  is the Néron period of  $E$ .

INPUT:

- `n` - (default: 2) a positive integer
- `quadratic_twist` - (default: +1) a fundamental discriminant of a quadratic field, coprime to the conductor of the curve
- `prec` - (default: 5) maximal number of terms of the series to compute; to compute as many as possible just give a very large number for `prec`; the result will still be correct.
- `eta` (default: 0) an integer (specifying the power of the Teichmueller character on the group of roots of unity in  $\mathbf{Z}_p^\times$ )

`power_series()` is identical to `series`.

EXAMPLES:

We compute some  $p$ -adic L-functions associated to the elliptic curve 11a:

```
sage: E = EllipticCurve('11a')
sage: p = 3
sage: E.is_ordinary(p)
True
sage: L = E.padic_lseries(p)
sage: L.series(3)
2 + 3 + 3^2 + 2*3^3 + O(3^5) + (1 + 3 + O(3^2))*T + (1 + 2*3 + O(3^2))*T^2 +
↪ O(3)*T^3 + O(3)*T^4 + O(T^5)
```

Another example at a prime of bad reduction, where the  $p$ -adic L-function has an extra 0 (compared to the non  $p$ -adic L-function):

```
sage: E = EllipticCurve('11a')
sage: p = 11
sage: E.is_ordinary(p)
True
sage: L = E.padic_lseries(p)
sage: L.series(2)
O(11^4) + (10 + O(11))*T + (6 + O(11))*T^2 + (2 + O(11))*T^3 + (5 + O(11))*T^4
↪ 4 + O(T^5)
```

We compute a  $p$ -adic L-function that vanishes to order 2:

```
sage: E = EllipticCurve('389a')
sage: p = 3
sage: E.is_ordinary(p)
True
sage: L = E.padic_lseries(p)
sage: L.series(1)
O(T^1)
sage: L.series(2)
O(3^4) + O(3)*T + (2 + O(3))*T^2 + O(T^3)
sage: L.series(3)
O(3^5) + O(3^2)*T + (2 + 2*3 + O(3^2))*T^2 + (2 + O(3))*T^3 + (1 + O(3))*T^4
↪ + O(T^5)
```

Checks if the precision can be changed ([trac ticket #5846](#)):

```

sage: L.series(3,prec=4)
O(3^5) + O(3^2)*T + (2 + 2*3 + O(3^2))*T^2 + (2 + O(3))*T^3 + O(T^4)
sage: L.series(3,prec=6)
O(3^5) + O(3^2)*T + (2 + 2*3 + O(3^2))*T^2 + (2 + O(3))*T^3 + (1 + O(3))*T^4
↪ + (1 + O(3))*T^5 + O(T^6)

```

Rather than computing the  $p$ -adic L-function for the curve ‘15523a1’, one can compute it as a `quadratic_twist`:

```

sage: E = EllipticCurve('43a1')
sage: lp = E.padic_lseries(3)
sage: lp.series(2,quadratic_twist=-19)
2 + 2*3 + 2*3^2 + O(3^4) + (1 + O(3))*T + (1 + O(3))*T^2 + O(T^3)
sage: E.quadratic_twist(-19).label()      # optional -- database_cremona_
↪ ellcurve
'15523a1'

```

This proves that the rank of ‘15523a1’ is zero, even if `mwrnk` can not determine this.

We calculate the  $L$ -series in the nontrivial Teichmueller components:

```

sage: L = EllipticCurve('110a1').padic_lseries(5)
sage: for j in [0..3]: print(L.series(4, eta=j))
O(5^6) + (2 + 2*5 + 2*5^2 + O(5^3))*T + (5 + 5^2 + O(5^3))*T^2 + (4 + 4*5 +
↪ 2*5^2 + O(5^3))*T^3 + (1 + 5 + 3*5^2 + O(5^3))*T^4 + O(T^5)
4 + 3*5 + 2*5^2 + 3*5^3 + 5^4 + O(5^6) + (1 + 3*5 + 4*5^2 + O(5^3))*T + (3 +
↪ 4*5 + 3*5^2 + O(5^3))*T^2 + (3 + 3*5^2 + O(5^3))*T^3 + (1 + 2*5 + 2*5^2 +
↪ O(5^3))*T^4 + O(T^5)
2 + O(5^6) + (1 + 5 + O(5^3))*T + (2 + 4*5 + 3*5^2 + O(5^3))*T^2 + (4 + 5 +
↪ 2*5^2 + O(5^3))*T^3 + (4 + O(5^3))*T^4 + O(T^5)
3 + 5 + 2*5^2 + 5^3 + 3*5^4 + 4*5^5 + O(5^6) + (1 + 2*5 + 4*5^2 + O(5^3))*T +
↪ (1 + 4*5 + O(5^3))*T^2 + (3 + 2*5 + 2*5^2 + O(5^3))*T^3 + (5 + 5^2 + O(5^
↪ 3))*T^4 + O(T^5)

```

It should now also work with  $p = 2$  (trac ticket #20798):

```

sage: E = EllipticCurve("53a1")
sage: lp = E.padic_lseries(2)
sage: lp.series(7)
O(2^8) + (1 + 2^2 + 2^3 + O(2^5))*T + (1 + 2^3 + O(2^4))*T^2 + (2^2 + 2^3 +
↪ O(2^4))*T^3 + (2 + 2^2 + O(2^3))*T^4 + O(T^5)

sage: E = EllipticCurve("109a1")
sage: lp = E.padic_lseries(2)
sage: lp.series(6)
2^2 + 2^6 + O(2^7) + (2 + O(2^4))*T + O(2^3)*T^2 + (2^2 + O(2^3))*T^3 + (2 +
↪ O(2^2))*T^4 + O(T^5)

```

**series** ( $n=2$ ,  $quadratic\_twist=1$ ,  $prec=5$ ,  $eta=0$ )

Return the  $n$ -th approximation to the  $p$ -adic L-series, in the component corresponding to the  $\eta$ -th power of the Teichmueller character, as a power series in  $T$  (corresponding to  $\gamma - 1$  with  $\gamma = 1 + p$  as a generator of  $1 + p\mathbb{Z}_p$ ). Each coefficient is a  $p$ -adic number whose precision is provably correct.

Here the normalization of the  $p$ -adic L-series is chosen such that  $L_p(E, 1) = (1 - 1/\alpha)^2 L(E, 1)/\Omega_E$  where  $\alpha$  is the unit root of the characteristic polynomial of Frobenius on  $T_p E$  and  $\Omega_E$  is the Néron period of  $E$ .

INPUT:

- `n` - (default: 2) a positive integer
- `quadratic_twist` - (default: +1) a fundamental discriminant of a quadratic field, coprime to the conductor of the curve
- `prec` - (default: 5) maximal number of terms of the series to compute; to compute as many as possible just give a very large number for `prec`; the result will still be correct.
- `eta` (default: 0) an integer (specifying the power of the Teichmueller character on the group of roots of unity in  $\mathbf{Z}_p^\times$ )

`power_series()` is identical to `series`.

#### EXAMPLES:

We compute some  $p$ -adic L-functions associated to the elliptic curve 11a:

```
sage: E = EllipticCurve('11a')
sage: p = 3
sage: E.is_ordinary(p)
True
sage: L = E.padic_lseries(p)
sage: L.series(3)
2 + 3 + 3^2 + 2*3^3 + O(3^5) + (1 + 3 + O(3^2))*T + (1 + 2*3 + O(3^2))*T^2 +
↪ O(3)*T^3 + O(3)*T^4 + O(T^5)
```

Another example at a prime of bad reduction, where the  $p$ -adic L-function has an extra 0 (compared to the non  $p$ -adic L-function):

```
sage: E = EllipticCurve('11a')
sage: p = 11
sage: E.is_ordinary(p)
True
sage: L = E.padic_lseries(p)
sage: L.series(2)
O(11^4) + (10 + O(11))*T + (6 + O(11))*T^2 + (2 + O(11))*T^3 + (5 + O(11))*T^4
↪ 4 + O(T^5)
```

We compute a  $p$ -adic L-function that vanishes to order 2:

```
sage: E = EllipticCurve('389a')
sage: p = 3
sage: E.is_ordinary(p)
True
sage: L = E.padic_lseries(p)
sage: L.series(1)
O(T^1)
sage: L.series(2)
O(3^4) + O(3)*T + (2 + O(3))*T^2 + O(T^3)
sage: L.series(3)
O(3^5) + O(3^2)*T + (2 + 2*3 + O(3^2))*T^2 + (2 + O(3))*T^3 + (1 + O(3))*T^4
↪ + O(T^5)
```

Checks if the precision can be changed ([trac ticket #5846](#)):

```
sage: L.series(3, prec=4)
O(3^5) + O(3^2)*T + (2 + 2*3 + O(3^2))*T^2 + (2 + O(3))*T^3 + O(T^4)
sage: L.series(3, prec=6)
O(3^5) + O(3^2)*T + (2 + 2*3 + O(3^2))*T^2 + (2 + O(3))*T^3 + (1 + O(3))*T^4
↪ + (1 + O(3))*T^5 + O(T^6)
```

Rather than computing the  $p$ -adic L-function for the curve '15523a1', one can compute it as a quadratic\_twist:

```
sage: E = EllipticCurve('43a1')
sage: lp = E.padic_lseries(3)
sage: lp.series(2, quadratic_twist=-19)
2 + 2*3 + 2*3^2 + O(3^4) + (1 + O(3))*T + (1 + O(3))*T^2 + O(T^3)
sage: E.quadratic_twist(-19).label()      # optional -- database_cremona_
↪ellcurve
'15523a1'
```

This proves that the rank of '15523a1' is zero, even if mwrank can not determine this.

We calculate the  $L$ -series in the nontrivial Teichmueller components:

```
sage: L = EllipticCurve('110a1').padic_lseries(5)
sage: for j in [0..3]: print(L.series(4, eta=j))
O(5^6) + (2 + 2*5 + 2*5^2 + O(5^3))*T + (5 + 5^2 + O(5^3))*T^2 + (4 + 4*5 +
↪2*5^2 + O(5^3))*T^3 + (1 + 5 + 3*5^2 + O(5^3))*T^4 + O(T^5)
4 + 3*5 + 2*5^2 + 3*5^3 + 5^4 + O(5^6) + (1 + 3*5 + 4*5^2 + O(5^3))*T + (3 +
↪4*5 + 3*5^2 + O(5^3))*T^2 + (3 + 3*5^2 + O(5^3))*T^3 + (1 + 2*5 + 2*5^2 +
↪O(5^3))*T^4 + O(T^5)
2 + O(5^6) + (1 + 5 + O(5^3))*T + (2 + 4*5 + 3*5^2 + O(5^3))*T^2 + (4 + 5 +
↪2*5^2 + O(5^3))*T^3 + (4 + O(5^3))*T^4 + O(T^5)
3 + 5 + 2*5^2 + 5^3 + 3*5^4 + 4*5^5 + O(5^6) + (1 + 2*5 + 4*5^2 + O(5^3))*T +
↪(1 + 4*5 + O(5^3))*T^2 + (3 + 2*5 + 2*5^2 + O(5^3))*T^3 + (5 + 5^2 + O(5^
↪3))*T^4 + O(T^5)
```

It should now also work with  $p = 2$  (trac ticket #20798):

```
sage: E = EllipticCurve("53a1")
sage: lp = E.padic_lseries(2)
sage: lp.series(7)
O(2^8) + (1 + 2^2 + 2^3 + O(2^5))*T + (1 + 2^3 + O(2^4))*T^2 + (2^2 + 2^3 +
↪O(2^4))*T^3 + (2 + 2^2 + O(2^3))*T^4 + O(T^5)

sage: E = EllipticCurve("109a1")
sage: lp = E.padic_lseries(2)
sage: lp.series(6)
2^2 + 2^6 + O(2^7) + (2 + O(2^4))*T + O(2^3)*T^2 + (2^2 + O(2^3))*T^3 + (2 +
↪O(2^2))*T^4 + O(T^5)
```

```
class sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesSupersingular(E,
                                                                           p,
                                                                           im-
                                                                           ple-
                                                                           men-
                                                                           ta-
                                                                           tion='eclib',
                                                                           nor-
                                                                           mal-
                                                                           ize='L_ratio')
```

Bases: `sage.schemes.elliptic_curves.padic_lseries.pAdicLseries`

**Dp\_valued\_height** (*prec*=20)

Return the canonical  $p$ -adic height with values in the Dieudonné module  $D_p(E)$ . It is defined to be

$$h_\eta \cdot \omega - h_\omega \cdot \eta$$

where  $h_\eta$  is made out of the sigma function of Bernardi and  $h_\omega$  is  $\log_E^2$ . The answer  $v$  is given as  $v[1]*\omega + v[2]*\eta$ . The coordinates of  $v$  are dependent of the Weierstrass equation.

EXAMPLES:

```
sage: E = EllipticCurve('53a')
sage: L = E.padic_lseries(5)
sage: h = L.Dp_valued_height(7)
sage: h(E.gens()[0])
(3*5 + 5^2 + 2*5^3 + 3*5^4 + 4*5^5 + 5^6 + 5^7 + O(5^8), 5^2 + 4*5^4 + 2*5^7 +
+ 3*5^8 + O(5^9))
```

**Dp\_valued\_regulator** (*prec=20, v1=0, v2=0*)

Return the canonical  $p$ -adic regulator with values in the Dieudonné module  $D_p(E)$  as defined by Perrin-Riou using the  $p$ -adic height with values in  $D_p(E)$ . The result is written in the basis  $\omega, \varphi(\omega)$ , and hence the coordinates of the result are independent of the chosen Weierstrass equation.

NOTE: The definition here is corrected with respect to Perrin-Riou's article [PR]. See [SW].

REFERENCES:

- [PR] Perrin Riou, Arithmétique des courbes elliptiques à réduction supersingulière en  $p$ , Experiment. Math. 12 (2003), no. 2, 155-186.
- [SW] William Stein and Christian Wuthrich, Computations About Tate-Shafarevich Groups using Iwasawa theory, preprint 2009.

EXAMPLES:

```
sage: E = EllipticCurve('43a')
sage: L = E.padic_lseries(7)
sage: L.Dp_valued_regulator(7)
(5*7 + 6*7^2 + 4*7^3 + 4*7^4 + 7^5 + 4*7^7 + O(7^8), 4*7^2 + 2*7^3 + 3*7^4 +
+ 7^5 + 6*7^6 + 4*7^7 + O(7^8))
```

**Dp\_valued\_series** (*n=3, quadratic\_twist=1, prec=5*)

Return a vector of two components which are  $p$ -adic power series. The answer  $v$  is such that

$$(1 - \varphi)^{-2} \cdot L_p(E, T) = v[1] \cdot \omega + v[2] \cdot \varphi(\omega)$$

as an element of the Dieudonné module  $D_p(E) = H_{dR}^1(E/\mathbf{Q}_p)$  where  $\omega$  is the invariant differential and  $\varphi$  is the Frobenius on  $D_p(E)$ . According to the  $p$ -adic Birch and Swinnerton-Dyer conjecture [BP] this function has a zero of order rank of  $E(\mathbf{Q})$  and it's leading term is contains the order of the Tate-Shafarevich group, the Tamagawa numbers, the order of the torsion subgroup and the  $D_p$ -valued  $p$ -adic regulator.

INPUT:

- $n$  - (default: 3) a positive integer
- $prec$  - (default: 5) a positive integer

REFERENCE:

- [BP] Dominique Bernardi and Bernadette Perrin-Riou, Variante  $p$ -adique de la conjecture de Birch et Swinnerton-Dyer (le cas supersingulier), C. R. Acad. Sci. Paris, Ser I. Math, 317 (1993), no 3, 227-232.

EXAMPLES:

```
sage: E = EllipticCurve('14a')
sage: L = E.padic_lseries(5)
sage: L.Dp_valued_series(4) # long time (9s on sage.math, 2011)
(1 + 4*5 + O(5^2) + (4 + O(5))*T + (1 + O(5))*T^2 + (4 + O(5))*T^3 + (2 +
+ O(5))*T^4 + O(T^5), 5^2 + O(5^3) + O(5^2)*T + (4*5 + O(5^2))*T^2 + (2*5 +
+ O(5^2))*T^3 + (2 + 2*5 + O(5^2))*T^4 + O(T^5))
```

**bernardi\_sigma\_function** (*prec=20*)

Return the  $p$ -adic sigma function of Bernardi in terms of  $z = \log(t)$ . This is the same as `padic_sigma` with  $E2 = 0$ .

EXAMPLES:

```
sage: E = EllipticCurve('14a')
sage: L = E.padic_lseries(5)
sage: L.bernardi_sigma_function(prec=5) # Todo: some sort of consistency
↪check!?
z + 1/24*z^3 + 29/384*z^5 - 8399/322560*z^7 - 291743/92897280*z^9 + O(z^10)
```

**frobenius** (*prec=20, algorithm='mw'*)

Return a geometric Frobenius  $\varphi$  on the Dieudonné module  $D_p(E)$  with respect to the basis  $\omega$ , the invariant differential, and  $\eta = x\omega$ .

It satisfies  $\varphi^2 - a_p/p \varphi + 1/p = 0$ .

INPUT:

- `prec` - (default: 20) a positive integer
- `algorithm` - either 'mw' (default) for Monsky-Washnitzer or 'approx' for the algorithm described by Bernardi and Perrin-Riou (much slower and not fully tested)

EXAMPLES:

```
sage: E = EllipticCurve('14a')
sage: L = E.padic_lseries(5)
sage: phi = L.frobenius(5)
sage: phi
[
      2 + 5^2 + 5^4 + O(5^5)      3*5^-1 + 3 + 5 + 4*5^2 + 5^3 +
↪O(5^4) ]
[
      3 + 3*5^2 + 4*5^3 + 3*5^4 + O(5^5)  3 + 4*5 + 3*5^2 + 4*5^3 + 3*5^4 +
↪O(5^5) ]
sage: -phi^2
[5^-1 + O(5^4)      O(5^4) ]
[
      O(5^5)  5^-1 + O(5^4) ]
```

**is\_ordinary** ()

Return True if the elliptic curve that this L-function is attached to is ordinary.

EXAMPLES:

```
sage: L = EllipticCurve('11a').padic_lseries(19)
sage: L.is_ordinary()
False
```

**is\_supersingular** ()

Return True if the elliptic curve that this L function is attached to is supersingular.

EXAMPLES:

```
sage: L = EllipticCurve('11a').padic_lseries(19)
sage: L.is_supersingular()
True
```

**power\_series** (*n=3, quadratic\_twist=1, prec=5, eta=0*)

Return the  $n$ -th approximation to the  $p$ -adic L-series as a power series in  $T$  (corresponding to  $\gamma - 1$  with

$\gamma = 1 + p$  as a generator of  $1 + p\mathbb{Z}_p$ ). Each coefficient is an element of a quadratic extension of the  $p$ -adic number whose precision is probably correct.

Here the normalization of the  $p$ -adic L-series is chosen such that  $L_p(E, 1) = (1 - 1/\alpha)^2 L(E, 1)/\Omega_E$  where  $\alpha$  is a root of the characteristic polynomial of Frobenius on  $T_p E$  and  $\Omega_E$  is the Néron period of  $E$ .

INPUT:

- `n` - (default: 2) a positive integer
- `quadratic_twist` - (default: +1) a fundamental discriminant of a quadratic field, coprime to the conductor of the curve
- `prec` - (default: 5) maximal number of terms of the series to compute; to compute as many as possible just give a very large number for `prec`; the result will still be correct.
- `eta` (default: 0) an integer (specifying the power of the Teichmueller character on the group of roots of unity in  $\mathbb{Z}_p^\times$ )

OUTPUT:

a power series with coefficients in a quadratic ramified extension of the  $p$ -adic numbers generated by a root  $\alpha$  of the characteristic polynomial of Frobenius on  $T_p E$ .

ALIAS: `power_series` is identical to `series`.

EXAMPLES:

A supersingular example, where we must compute to higher precision to see anything:

```
sage: e = EllipticCurve('37a')
sage: L = e.padic_lseries(3); L
3-adic L-series of Elliptic Curve defined by y^2 + y = x^3 - x over Rational_
↪Field
sage: L.series(2)
O(T^3)
sage: L.series(4)           # takes a long time (several seconds)
O(alpha) + (alpha^-2 + O(alpha^0))*T + (alpha^-2 + O(alpha^0))*T^2 + O(T^5)
sage: L.alpha(2).parent()
Eisenstein Extension in alpha defined by x^2 + 3*x + 3 with capped relative_
↪precision 4 over 3-adic Field
```

An example where we only compute the leading term ([trac ticket #15737](#)):

```
sage: E = EllipticCurve("17a1")
sage: L = E.padic_lseries(3)
sage: L.series(4, prec=1)
alpha^-2 + alpha^-1 + 2 + 2*alpha + ... + O(alpha^38) + O(T)
```

It works also for  $p = 2$ :

```
sage: E = EllipticCurve("11a1")
sage: lp = E.padic_lseries(2)
sage: lp.series(10)
O(alpha^-3) + (alpha^-4 + O(alpha^-3))*T + (alpha^-4 + O(alpha^-3))*T^2 +
↪(alpha^-5 + alpha^-4 + O(alpha^-3))*T^3 + (alpha^-4 + O(alpha^-3))*T^4 +
↪O(T^5)
```

**series** ( $n=3$ ,  $quadratic\_twist=1$ ,  $prec=5$ ,  $eta=0$ )

Return the  $n$ -th approximation to the  $p$ -adic L-series as a power series in  $T$  (corresponding to  $\gamma - 1$  with  $\gamma = 1 + p$  as a generator of  $1 + p\mathbb{Z}_p$ ). Each coefficient is an element of a quadratic extension of the  $p$ -adic number whose precision is probably correct.



Here the normalization of the  $p$ -adic L-series is chosen such that  $L_p(E, 1) = (1 - 1/\alpha)^2 L(E, 1)/\Omega_E$  where  $\alpha$  is a root of the characteristic polynomial of Frobenius on  $T_p E$  and  $\Omega_E$  is the Néron period of  $E$ .

INPUT:

- `n` - (default: 2) a positive integer
- `quadratic_twist` - (default: +1) a fundamental discriminant of a quadratic field, coprime to the conductor of the curve
- `prec` - (default: 5) maximal number of terms of the series to compute; to compute as many as possible just give a very large number for `prec`; the result will still be correct.
- `eta` (default: 0) an integer (specifying the power of the Teichmueller character on the group of roots of unity in  $\mathbf{Z}_p^\times$ )

OUTPUT:

a power series with coefficients in a quadratic ramified extension of the  $p$ -adic numbers generated by a root  $\alpha$  of the characteristic polynomial of Frobenius on  $T_p E$ .

ALIAS: `power_series` is identical to `series`.

EXAMPLES:

A supersingular example, where we must compute to higher precision to see anything:

```
sage: e = EllipticCurve('37a')
sage: L = e.padic_lseries(3); L
3-adic L-series of Elliptic Curve defined by y^2 + y = x^3 - x over Rational_
↪Field
sage: L.series(2)
O(T^3)
sage: L.series(4)           # takes a long time (several seconds)
O(alpha) + (alpha^-2 + O(alpha^0))*T + (alpha^-2 + O(alpha^0))*T^2 + O(T^5)
sage: L.alpha(2).parent()
Eisenstein Extension in alpha defined by x^2 + 3*x + 3 with capped relative_
↪precision 4 over 3-adic Field
```

An example where we only compute the leading term ([trac ticket #15737](#)):

```
sage: E = EllipticCurve("17a1")
sage: L = E.padic_lseries(3)
sage: L.series(4, prec=1)
alpha^-2 + alpha^-1 + 2 + 2*alpha + ... + O(alpha^38) + O(T)
```

It works also for  $p = 2$ :

```
sage: E = EllipticCurve("11a1")
sage: lp = E.padic_lseries(2)
sage: lp.series(10)
O(alpha^-3) + (alpha^-4 + O(alpha^-3))*T + (alpha^-4 + O(alpha^-3))*T^2 +
↪(alpha^-5 + alpha^-4 + O(alpha^-3))*T^3 + (alpha^-4 + O(alpha^-3))*T^4 +
↪O(T^5)
```

## 15.12 To be sorted

### 15.12.1 Descent on elliptic curves over $\mathbb{Q}$ with a 2-isogeny.

`sage.schemes.elliptic_curves.descent_two_isogeny.test_els(a, b, c, d, e)`  
 Doctest function for cdef int everywhere\_locally\_soluble(mpz\_t, mpz\_t, mpz\_t, mpz\_t, mpz\_t).

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.descent_two_isogeny import test_els
sage: for _ in range(1000):
....:     a,b,c,d,e = randint(1,1000), randint(1,1000), randint(1,1000),
↳randint(1,1000), randint(1,1000)
....:     if pari.Pol([a,b,c,d,e]).hyperellratpoints(1000, 1):
....:         try:
....:             if not test_els(a,b,c,d,e):
....:                 print("This never happened", a, b, c, d, e)
....:         except ValueError:
....:             continue
```

`sage.schemes.elliptic_curves.descent_two_isogeny.test_padic_square(a, p)`  
 Doctest function for cdef int padic\_square(mpz\_t, unsigned long).

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.descent_two_isogeny import test_padic_
↳square as ps
sage: for i in [1..300]:
....:     for p in prime_range(100):
....:         if not Qp(p)(i).is_square()==bool(ps(i,p)):
....:             print(i, p)
```

`sage.schemes.elliptic_curves.descent_two_isogeny.test_qpls(a, b, c, d, e, p)`  
 Testing function for  $\mathbb{Q}_p$ -soluble.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.descent_two_isogeny import test_qpls as tq
sage: tq(1,2,3,4,5,7)
1
```

`sage.schemes.elliptic_curves.descent_two_isogeny.test_valuation(a, p)`  
 Doctest function for cdef long valuation(mpz\_t, mpz\_t).

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.descent_two_isogeny import test_valuation_
↳as tv
sage: for i in [1..20]:
....:     print('{:>10} {} {} {}'.format(factor(i), tv(i,2), tv(i,3), tv(i,5)))
      1 0 0 0
      2 1 0 0
      3 0 1 0
     2^2 2 0 0
      5 0 0 1
    2 * 3 1 1 0
      7 0 0 0
     2^3 3 0 0
```

```

      3^2 0 2 0
    2 * 5 1 0 1
      11 0 0 0
    2^2 * 3 2 1 0
      13 0 0 0
    2 * 7 1 0 0
    3 * 5 0 1 1
      2^4 4 0 0
      17 0 0 0
    2 * 3^2 1 2 0
      19 0 0 0
    2^2 * 5 2 0 1

```

```

sage.schemes.elliptic_curves.descent_two_isogeny.two_descent_by_two_isogeny(E,
                                                                              global_limit_small=1,
                                                                              global_limit_large=1,
                                                                              verbosity=0,
                                                                              selmer_only=0,
                                                                              proof=1)

```

Given an elliptic curve  $E$  with a two-isogeny  $\phi : E \rightarrow E'$  and dual isogeny  $\phi'$ , runs a two-isogeny descent on  $E$ , returning  $n1$ ,  $n2$ ,  $n1'$  and  $n2'$ . Here  $n1$  is the number of quartic covers found with a rational point, and  $n2$  is the number which are ELS.

EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.descent_two_isogeny import two_descent_by_
      ↪two_isogeny
sage: E = EllipticCurve('14a')
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny(E)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
0
sage: E = EllipticCurve('65a')
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny(E)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
1
sage: x,y = var('x,y')
sage: E = EllipticCurve(y^2 == x^3 + x^2 - 25*x + 39)
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny(E)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
2
sage: E = EllipticCurve(y^2 + x*y + y == x^3 - 131*x + 558)
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny(E)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
3

```

Using the verbosity option:

```

sage: E = EllipticCurve('14a')
sage: two_descent_by_two_isogeny(E, verbosity=1)
2-isogeny
Results:
2 <= #E(Q)/phi'(E'(Q)) <= 2
2 <= #E'(Q)/phi(E(Q)) <= 2
#Sel^(phi')(E'/Q) = 2
#Sel^(phi)(E/Q) = 2
1 <= #Sha(E'/Q)[phi'] <= 1
1 <= #Sha(E/Q)[phi] <= 1

```

```

1 <= #Sha(E/Q)[2], #Sha(E'/Q)[2] <= 1
0 <= rank of E(Q) = rank of E'(Q) <= 0
(2, 2, 2, 2)

```

Handling curves whose discriminants involve larger than wordsize primes:

[illegible]

```
sage.schemes.elliptic_curves.descent_two_isogeny.two_descent_by_two_isogeny_work(c,
d,
global_limit_1,
global_limit_2,
ver-
bosity=0,
selmer_only=
proof=1)
```

Do all the work in doing a two-isogeny descent.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.descent_two_isogeny import two_descent_by_
↳two_isogeny_work
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny_work(13,128)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
0
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny_work(1,-16)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
1
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny_work(10,8)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
2
sage: n1, n2, n1_prime, n2_prime = two_descent_by_two_isogeny_work(85,320)
sage: log(n1,2) + log(n1_prime,2) - 2 # the rank
3
```

### 15.12.2 Elliptic curves with prescribed good reduction.

# Construction of elliptic curves with good reduction outside a finite set of primes

A theorem of Shafarevich states that, over a number field  $K$ , given any finite set  $S$  of primes of  $K$ , there are (up to isomorphism) only a finite set of elliptic curves defined over  $K$  with good reduction at all primes outside  $S$ . An explicit form of the theorem with an algorithm for finding this finite set was given in “Finding all elliptic curves with good reduction outside a given set of primes” by John Cremona and Mark Lingham, *Experimental Mathematics* 16

No.3 (2007), 303-312. The method requires computation of the class and unit groups of  $K$  as well as all the  $S$ -integral points on a collection of auxiliary elliptic curves defined over  $K$ .

This implementation (April 2009) is only for the case  $K = \mathbb{Q}$ , where in many cases the determination of the necessary sets of  $S$ -integral points is possible. The main user-level function is `EllipticCurves_with_good_reduction_outside_S()`, defined in `constructor.py`. Users should note carefully the following points:

- (1) the number of auxiliary curves to be considered is exponential in the size of  $S$  (specifically,  $2.6^s$  where  $s = |S|$ ).
- (2) For some of the auxiliary curves it is impossible at present to provably find all the  $S$ -integral points using the current algorithms, which rely on first finding a basis for their Mordell-Weil groups using 2-descent. A warning is output in cases where the set of points (and hence the final output) is not guaranteed to be complete. Using the `proof=False` flag suppresses these warnings.

EXAMPLES: We find all elliptic curves with good reduction outside 2, listing the label of each:

```
sage: [e.label() for e in EllipticCurves_with_good_reduction_outside_S([2])] # long_
↳time (5s on sage.math, 2013)
['32a1',
'32a2',
'32a3',
'32a4',
'64a1',
'64a2',
'64a3',
'64a4',
'128a1',
'128a2',
'128b1',
'128b2',
'128c1',
'128c2',
'128d1',
'128d2',
'256a1',
'256a2',
'256b1',
'256b2',
'256c1',
'256c2',
'256d1',
'256d2']
```

Secondly we try the same with  $S = 11$ ; note that warning messages are printed without `proof=False` (unless the optional database is installed: two of the auxiliary curves whose Mordell-Weil bases are required have conductors 13068 and 52272 so are in the database):

```
sage: [e.label() for e in EllipticCurves_with_good_reduction_outside_S([11],
↳proof=False)] # long time (13s on sage.math, 2011)
['11a1', '11a2', '11a3', '121a1', '121a2', '121b1', '121b2', '121c1', '121c2', '121d1',
↳', '121d2', '121d3']
```

AUTHORS:

- John Cremona (6 April 2009): initial version (over  $\mathbb{Q}$  only).

`sage.schemes.elliptic_curves.ell_egros.curve_key(EI)`  
Comparison key for elliptic curves over  $\mathbb{Q}$ .

The key is a tuple:

- if the curve is in the database: (conductor, 0, label, number)
- otherwise: (conductor, 1, a\_invariants)

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_egros import curve_key
sage: E = EllipticCurve_from_j(1728)
sage: curve_key(E)
(32, 0, 0, 2)
sage: E = EllipticCurve_from_j(1729)
sage: curve_key(E)
(2989441, 1, (1, 0, 0, -36, -1))
```

`sage.schemes.elliptic_curves.ell_egros.egros_from_j(j, S=[])`

Given a rational  $j$  and a list of primes  $S$ , returns a list of elliptic curves over  $\mathbf{Q}$  with  $j$ -invariant  $j$  and good reduction outside  $S$ , by checking all relevant quadratic twists.

INPUT:

- $j$  – a rational number.
- $S$  – list of primes (default: empty list).

---

**Note:** Primality of elements of  $S$  is not checked, and the output is undefined if  $S$  is not a list or contains non-primes.

---

OUTPUT:

A sorted list of all elliptic curves defined over  $\mathbf{Q}$  with  $j$ -invariant equal to  $j$  and with good reduction at all primes outside the list  $S$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_egros import egros_from_j
sage: [e.label() for e in egros_from_j(0, [3])]
['27a1', '27a3', '243a1', '243a2', '243b1', '243b2']
sage: [e.label() for e in egros_from_j(1728, [2])]
['32a1', '32a2', '64a1', '64a4', '256b1', '256b2', '256c1', '256c2']
sage: elist=egros_from_j(-4096/11, [11])
sage: [e.label() for e in elist]
['11a3', '121d1']
```

`sage.schemes.elliptic_curves.ell_egros.egros_from_j_0(S=[])`

Given a list of primes  $S$ , returns a list of elliptic curves over  $\mathbf{Q}$  with  $j$ -invariant 0 and good reduction outside  $S$ , by checking all relevant sextic twists.

INPUT:

- $S$  – list of primes (default: empty list).

---

**Note:** Primality of elements of  $S$  is not checked, and the output is undefined if  $S$  is not a list or contains non-primes.

---

OUTPUT:

A sorted list of all elliptic curves defined over  $\mathbb{Q}$  with  $j$ -invariant equal to 0 and with good reduction at all primes outside the list  $S$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_egros import egros_from_j_0
sage: egros_from_j_0([])
[]
sage: egros_from_j_0([2])
[]
sage: [e.label() for e in egros_from_j_0([3])]
['27a1', '27a3', '243a1', '243a2', '243b1', '243b2']
sage: len(egros_from_j_0([2,3,5])) # long time (8s on sage.math, 2013)
432
```

`sage.schemes.elliptic_curves.ell_egros.egros_from_j_1728( $S=[]$ )`

Given a list of primes  $S$ , returns a list of elliptic curves over  $\mathbb{Q}$  with  $j$ -invariant 1728 and good reduction outside  $S$ , by checking all relevant quartic twists.

INPUT:

- $S$  – list of primes (default: empty list).

---

**Note:** Primality of elements of  $S$  is not checked, and the output is undefined if  $S$  is not a list or contains non-primes.

---

OUTPUT:

A sorted list of all elliptic curves defined over  $\mathbb{Q}$  with  $j$ -invariant equal to 1728 and with good reduction at all primes outside the list  $S$ .

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_egros import egros_from_j_1728
sage: egros_from_j_1728([])
[]
sage: egros_from_j_1728([3])
[]
sage: [e.cremona_label() for e in egros_from_j_1728([2])]
['32a1', '32a2', '64a1', '64a4', '256b1', '256b2', '256c1', '256c2']
```

`sage.schemes.elliptic_curves.ell_egros.egros_from_jlist( $jlist, S=[]$ )`

Given a list of rational  $j$  and a list of primes  $S$ , returns a list of elliptic curves over  $\mathbb{Q}$  with  $j$ -invariant in the list and good reduction outside  $S$ .

INPUT:

- $j$  – list of rational numbers.
- $S$  – list of primes (default: empty list).

---

**Note:** Primality of elements of  $S$  is not checked, and the output is undefined if  $S$  is not a list or contains non-primes.

---

OUTPUT:

A sorted list of all elliptic curves defined over  $\mathbb{Q}$  with  $j$ -invariant in the list `jlist` and with good reduction at all primes outside the list  $S$ .

## EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_egros import egros_get_j, egros_from_
      ↪ jlist
sage: jlist=egros_get_j([3])
sage: elist=egros_from_jlist(jlist,[3])
sage: [e.label() for e in elist]
['27a1', '27a2', '27a3', '27a4', '243a1', '243a2', '243b1', '243b2']
sage: [e.ainvs() for e in elist]
[(0, 0, 1, 0, -7),
 (0, 0, 1, -270, -1708),
 (0, 0, 1, 0, 0),
 (0, 0, 1, -30, 63),
 (0, 0, 1, 0, -1),
 (0, 0, 1, 0, 20),
 (0, 0, 1, 0, 2),
 (0, 0, 1, 0, -61)]

```

`sage.schemes.elliptic_curves.ell_egros.egros_get_j` ( $S=[]$ ,  $proof=None$ ,  $verbose=False$ )

Returns a list of rational  $j$  such that all elliptic curves defined over  $\mathbb{Q}$  with good reduction outside  $S$  have  $j$ -invariant in the list, sorted by height.

## INPUT:

- $S$  – list of primes (default: empty list).
- $proof$  – True/False (default True): the MW basis for auxiliary curves will be computed with this proof flag.
- $verbose$  – True/False (default False): if True, some details of the computation will be output.

**Note:** Proof flag: The algorithm used requires determining all  $S$ -integral points on several auxiliary curves, which in turn requires the computation of their generators. This is not always possible (even in theory) using current knowledge.

The value of this flag is passed to the function which computes generators of various auxiliary elliptic curves, in order to find their  $S$ -integral points. Set to False if the default (True) causes warning messages, but note that you can then not rely on the set of invariants returned being complete.

## EXAMPLES:

```

sage: from sage.schemes.elliptic_curves.ell_egros import egros_get_j
sage: egros_get_j([])
[1728]
sage: egros_get_j([2]) # long time (3s on sage.math, 2013)
[128, 432, -864, 1728, 3375/2, -3456, 6912, 8000, 10976, -35937/4, 287496, -
↪ 7844446336, -189613868625/128]
sage: egros_get_j([3]) # long time (3s on sage.math, 2013)
[0, -576, 1536, 1728, -5184, -13824, 21952/9, -41472, 140608/3, -12288000]
sage: jlist=egros_get_j([2,3]); len(jlist) # long time (30s)
83

```

`sage.schemes.elliptic_curves.ell_egros.is_possible_j` ( $j, S=[]$ )

Tests if the rational  $j$  is a possible  $j$ -invariant of an elliptic curve with good reduction outside  $S$ .

**Note:** The condition used is necessary but not sufficient unless  $S$  contains both 2 and 3.



EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.ell_egros import is_possible_j
sage: is_possible_j(0, [])
False
sage: is_possible_j(1728, [])
True
sage: is_possible_j(-4096/11, [11])
True
```

### 15.12.3 Elliptic curves over padic fields

**class** sage.schemes.elliptic\_curves.ell\_padic\_field.**EllipticCurve\_padic\_field**(*K*, *ainvs*)  
 Bases: *sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field*,  
*sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field*

Elliptic curve over a padic field.

EXAMPLES:

```
sage: Qp=pAdicField(17)
sage: E=EllipticCurve(Qp, [2,3]); E
Elliptic Curve defined by  $y^2 = x^3 + (2+O(17^{20}))x + (3+O(17^{20}))$  over 17-adic_
↪Field with capped relative precision 20
sage: E == loads(dumps(E))
True
```

**frobenius** (*P=None*)

Returns the Frobenius as a function on the group of points of this elliptic curve.

EXAMPLES:

```
sage: Qp=pAdicField(13)
sage: E=EllipticCurve(Qp, [1,1])
sage: type(E.frobenius())
<... 'function'>
sage: point=E(0,1)
sage: E.frobenius(point)
(0 : 1 + O(13^{20}) : 1 + O(13^{20}))
```

### 15.12.4 Denis Simon's PARI scripts

sage.schemes.elliptic\_curves.gp\_simon.**init**()

Function to initialize the gp process

sage.schemes.elliptic\_curves.gp\_simon.**simon\_two\_descent** (*E*, *verbose=0*,  
*lim1=None*, *lim3=None*,  
*limtriv=None*, *max-*  
*prob=20*, *limbigprime=30*,  
*known\_points=[]*)

Interface to Simon's gp script for two-descent.

---

**Note:** Users should instead run `E.simon_two_descent()`

---

EXAMPLES:

```
sage: import sage.schemes.elliptic_curves.gp_simon
sage: E=EllipticCurve('389a1')
sage: sage.schemes.elliptic_curves.gp_simon.simon_two_descent(E)
(2, 2, [(1 : 0 : 1), (-11/9 : 28/27 : 1)])
```

### 15.12.5 Elliptic curves with congruent mod-5 representation.

AUTHORS:

- Alice Silverberg and Karl Rubin (original PARI/GP version)
- William Stein – Sage version.

`sage.schemes.elliptic_curves.mod5family.mod5family(a, b)`

Formulas for computing the family of elliptic curves with congruent mod-5 representation.

EXAMPLES:

```
sage: from sage.schemes.elliptic_curves.mod5family import mod5family
sage: mod5family(0,1)
Elliptic Curve defined by  $y^2 = x^3 + (t^{30} + 30t^{29} + 435t^{28} + 4060t^{27} + 27405t^{26} + 142506t^{25} + 593775t^{24} + 2035800t^{23} + 5852925t^{22} + 14307150t^{21} + 30045015t^{20} + 2054627300t^{19} + 86493225t^{18} + 119759850t^{17} + 145422675t^{16} + 155117520t^{15} + 154422675t^{14} + 119759850t^{13} + 86493225t^{12} + 54627300t^{11} + 30045015t^{10} + 14307150t^9 + 5852925t^8 + 2035800t^7 + 593775t^6 + 142506t^5 + 27405t^4 + 4060t^3 + 435t^2 + 30t + 1)$  over Fraction Field of Univariate Polynomial Ring in t over  $\mathbb{Q}$ 
↪ Rational Field
```

### 15.12.6 Morphism to bring a genus-one curve into Weierstrass form

You should use `EllipticCurve_from_cubic()` or `EllipticCurve_from_curve()` to construct the transformation starting with a cubic or with a genus one curve.

EXAMPLES:

```
sage: R.<u,v,w> = QQ[]
sage: f = EllipticCurve_from_cubic(u^3 + v^3 + w^3, [1,-1,0], morphism=True); f
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by  $u^3 + v^3 + w^3$ 
  To: Elliptic Curve defined by  $y^2 - 9y = x^3 - 27$  over Rational Field
  Defn: Defined on coordinates by sending (u : v : w) to
        (-w : 3*u : 1/3*u + 1/3*v)

sage: finv = f.inverse(); finv
Scheme morphism:
  From: Elliptic Curve defined by  $y^2 - 9y = x^3 - 27$  over Rational Field
  To: Projective Plane Curve over Rational Field defined by  $u^3 + v^3 + w^3$ 
  Defn: Defined on coordinates by sending (x : y : z) to
        (1/3*y : -1/3*y + 3*z : -x)

sage: (u^3 + v^3 + w^3)(f.inverse().defining_polynomials()) * f.inverse().post_
↪ rescaling()
-x^3 + y^2*z - 9*y*z^2 + 27*z^3

sage: E = finv.domain()
```

```
sage: E.defined_polynomial()(f.defined_polynomials()) * f.post_rescaling()
u^3 + v^3 + w^3
```

```
sage: f([1,-1,0])
(0 : 1 : 0)
sage: f([1,0,-1])
(3 : 9 : 1)
sage: f([0,1,-1])
(3 : 0 : 1)
```

**class** sage.schemes.elliptic\_curves.weierstrass\_transform.**WeierstrassTransformation** (*domain*, *codomain*, *defining\_polynomials*, *post\_multiplication*)

Bases: sage.schemes.generic.morphism.SchemeMorphism\_polynomial

A morphism of a a genus-one curve to/from the Weierstrass form.

INPUT:

- *domain*, *codomain* – two schemes, one of which is an elliptic curve.
- *defining\_polynomials* – triplet of polynomials that define the transformation.
- *post\_multiplication* – a polynomial to homogeneously rescale after substituting the defining polynomials.

EXAMPLES:

```
sage: P2.<u,v,w> = ProjectiveSpace(2,QQ)
sage: C = P2.subscheme(u^3 + v^3 + w^3)
sage: E = EllipticCurve([2, -1, -1/3, 1/3, -1/27])
sage: from sage.schemes.elliptic_curves.weierstrass_transform import
↳ WeierstrassTransformation
sage: f = WeierstrassTransformation(C, E, [w, -v-w, -3*u-3*v], 1); f
Scheme morphism:
  From: Closed subscheme of Projective Space of dimension 2 over Rational Field
↳ defined by:
  u^3 + v^3 + w^3
  To: Elliptic Curve defined by y^2 + 2*x*y - 1/3*y = x^3 - x^2 + 1/3*x - 1/27
  over Rational Field
  Defn: Defined on coordinates by sending (u : v : w) to
      (w : -v - w : -3*u - 3*v)

sage: f([-1, 1, 0])
(0 : 1 : 0)
sage: f([-1, 0, 1])
(1/3 : -1/3 : 1)
sage: f([ 0,-1, 1])
(1/3 : 0 : 1)

sage: A2.<a,b> = AffineSpace(2,QQ)
sage: C = A2.subscheme(a^3 + b^3 + 1)
sage: f = WeierstrassTransformation(C, E, [1, -b-1, -3*a-3*b], 1); f
Scheme morphism:
  From: Closed subscheme of Affine Space of dimension 2 over Rational Field
↳ defined by:
  a^3 + b^3 + 1
  To: Elliptic Curve defined by y^2 + 2*x*y - 1/3*y
```

```

      = x^3 - x^2 + 1/3*x - 1/27 over Rational Field
Defn: Defined on coordinates by sending (a, b) to
      (1 : -b - 1 : -3*a - 3*b)
sage: f([-1,0])
(1/3 : -1/3 : 1)
sage: f([0,-1])
(1/3 : 0 : 1)

```

**post\_rescaling()**

Return the homogeneous rescaling to apply after the coordinate substitution.

OUTPUT:

A polynomial. See the example below.

EXAMPLES:

```

sage: R.<a,b,c> = QQ[]
sage: cubic = a^3+7*b^3+64*c^3
sage: P = [2,2,-1]
sage: f = EllipticCurve_from_cubic(cubic, P, morphism=True).inverse()
sage: f.post_rescaling()
-1/7

```

So here is what it does. If we just plug in the coordinate transformation, we get the defining polynomial up to scale. This method returns the overall rescaling of the equation to bring the result into the standard form:

```

sage: cubic(f.defining_polynomials())
7*x^3 - 7*y^2*z + 1806336*y*z^2 - 155373797376*z^3
sage: cubic(f.defining_polynomials()) * f.post_rescaling()
-x^3 + y^2*z - 258048*y*z^2 + 22196256768*z^3

```

sage.schemes.elliptic\_curves.weierstrass\_transform.**WeierstrassTransformationWithInverse** (domain, codomain, defining equation, post\_rescaling, inverse)

Construct morphism of a genus-one curve to/from the Weierstrass form with its inverse.

EXAMPLES:

```

sage: R.<u,v,w> = QQ[]
sage: f = EllipticCurve_from_cubic(u^3 + v^3 + w^3, [1,-1,0], morphism=True); f
Scheme morphism:
  From: Projective Plane Curve over Rational Field defined by u^3 + v^3 + w^3
  To:   Elliptic Curve defined by y^2 - 9*y = x^3 - 27 over Rational Field
  Defn: Defined on coordinates by sending (u : v : w) to
        (-w : 3*u : 1/3*u + 1/3*v)

Scheme morphism:
  From: Closed subscheme of Projective Space of dimension 2 over Rational Field
  defined by:
  u^3 + v^3 + w^3
  To:   Elliptic Curve defined by y^2 + 2*x*y + 1/3*y
        = x^3 - x^2 - 1/3*x - 1/27 over Rational Field

```

Defn: Defined on coordinates by sending  $(u : v : w)$  to  
 $(-w : -v + w : 3*u + 3*v)$

**class** sage.schemes.elliptic\_curves.weierstrass\_transform.WeierstrassTransformationWithInverse

Bases: `sage.schemes.elliptic_curves.weierstrass_transform.WeierstrassTransformation`

**inverse()**

Return the inverse.

OUTPUT:

A morphism in the opposite direction. This may be a rational inverse or an analytic inverse.

EXAMPLES:

```
sage: R.<u,v,w> = QQ[]
sage: f = EllipticCurve_from_cubic(u^3 + v^3 + w^3, [1,-1,0], morphism=True)
sage: f.inverse()
Scheme morphism:
  From: Elliptic Curve defined by  $y^2 - 9*y = x^3 - 27$  over Rational Field
  To:   Projective Plane Curve over Rational Field defined by  $u^3 + v^3 + w^3$ 
  Defn: Defined on coordinates by sending  $(x : y : z)$  to
         $(1/3*y : -1/3*y + 3*z : -x)$ 
```



## HYPERELLIPTIC CURVES

### 16.1 Hyperelliptic curve constructor

`sage.schemes.hyperelliptic_curves.constructor.HyperellipticCurve` (*f*, *h*=0,  
*names*=None,  
*PP*=None,  
*check\_squarefree*=True)

Returns the hyperelliptic curve  $y^2 + hy = f$ , for univariate polynomials  $h$  and  $f$ . If  $h$  is not given, then it defaults to 0.

INPUT:

- $f$  - univariate polynomial
- $h$  - optional univariate polynomial
- *names* (default: ["x", "y"]) - names for the coordinate functions
- *check\_squarefree* (default: True) - test if the input defines a hyperelliptic curve when  $f$  is homogenized to degree  $2g + 2$  and  $h$  to degree  $g + 1$  for some  $g$ .

**Warning:** When setting *check\_squarefree*=False or using a base ring that is not a field, the output curves are not to be trusted. For example, the output of *is\_singular* is always False, without this being properly tested in that case.

---

**Note:** The words “hyperelliptic curve” are normally only used for curves of genus at least two, but this class allows more general smooth double covers of the projective line (conics and elliptic curves), even though the class is not meant for those and some outputs may be incorrect.

---

EXAMPLES:

Basic examples:

```
sage: R.<x> = QQ[]
sage: HyperellipticCurve(x^5 + x + 1)
Hyperelliptic Curve over Rational Field defined by y^2 = x^5 + x + 1
sage: HyperellipticCurve(x^19 + x + 1, x-2)
Hyperelliptic Curve over Rational Field defined by y^2 + (x - 2)*y = x^19 + x + 1

sage: k.<a> = GF(9); R.<x> = k[]
sage: HyperellipticCurve(x^3 + x - 1, x+a)
Hyperelliptic Curve over Finite Field in a of size 3^2 defined by y^2 + (x + a)*y
= x^3 + x + 2
```

Characteristic two:

```
sage: P.<x> = GF(8,'a')[]
sage: HyperellipticCurve(x^7+1, x)
Hyperelliptic Curve over Finite Field in a of size 2^3 defined by y^2 + x*y = x^7
↪ + 1
sage: HyperellipticCurve(x^8+x^7+1, x^4+1)
Hyperelliptic Curve over Finite Field in a of size 2^3 defined by y^2 + (x^4 +
↪ 1)*y = x^8 + x^7 + 1

sage: HyperellipticCurve(x^8+1, x)
Traceback (most recent call last):
...
ValueError: Not a hyperelliptic curve: highly singular at infinity.

sage: HyperellipticCurve(x^8+x^7+1, x^4)
Traceback (most recent call last):
...
ValueError: Not a hyperelliptic curve: singularity in the provided affine patch.

sage: F.<t> = PowerSeriesRing(FiniteField(2))
sage: P.<x> = PolynomialRing(FractionField(F))
sage: HyperellipticCurve(x^5+t, x)
Hyperelliptic Curve over Laurent Series Ring in t over Finite Field of size 2
↪ defined by y^2 + x*y = x^5 + t
```

We can change the names of the variables in the output:

```
sage: k.<a> = GF(9); R.<x> = k[]
sage: HyperellipticCurve(x^3 + x - 1, x+a, names=['X','Y'])
Hyperelliptic Curve over Finite Field in a of size 3^2 defined by Y^2 + (X + a)*Y
↪ = X^3 + X + 2
```

This class also allows curves of genus zero or one, which are strictly speaking not hyperelliptic:

```
sage: P.<x> = QQ[]
sage: HyperellipticCurve(x^2+1)
Hyperelliptic Curve over Rational Field defined by y^2 = x^2 + 1
sage: HyperellipticCurve(x^4-1)
Hyperelliptic Curve over Rational Field defined by y^2 = x^4 - 1
sage: HyperellipticCurve(x^3+2*x+2)
Hyperelliptic Curve over Rational Field defined by y^2 = x^3 + 2*x + 2
```

Double roots:

```
sage: P.<x> = GF(7)[]
sage: HyperellipticCurve((x^3-x+2)^2*(x^6-1))
Traceback (most recent call last):
...
ValueError: Not a hyperelliptic curve: singularity in the provided affine patch.

sage: HyperellipticCurve((x^3-x+2)^2*(x^6-1), check_squarefree=False)
Hyperelliptic Curve over Finite Field of size 7 defined by y^2 = x^12 + 5*x^10 +
↪ 4*x^9 + x^8 + 3*x^7 + 3*x^6 + 2*x^4 + 3*x^3 + 6*x^2 + 4*x + 3
```

The input for a (smooth) hyperelliptic curve of genus  $g$  should not contain polynomials of degree greater than  $2g + 2$ . In the following example, the hyperelliptic curve has genus 2 and there exists a model  $y^2 = F$  of degree



6, so the model  $y^2 + yh = f$  of degree 200 is not allowed.:

```
sage: P.<x> = QQ[]
sage: h = x^100
sage: F = x^6+1
sage: f = F-h^2/4
sage: HyperellipticCurve(f, h)
Traceback (most recent call last):
...
ValueError: Not a hyperelliptic curve: highly singular at infinity.

sage: HyperellipticCurve(F)
Hyperelliptic Curve over Rational Field defined by y^2 = x^6 + 1
```

An example with a singularity over an inseparable extension of the base field:

```
sage: F.<t> = GF(5)[t]
sage: P.<x> = F[]
sage: HyperellipticCurve(x^5+t)
Traceback (most recent call last):
...
ValueError: Not a hyperelliptic curve: singularity in the provided affine patch.
```

Input with integer coefficients creates objects with the integers as base ring, but only checks smoothness over  $\mathbb{Q}$ , not over  $\text{Spec}(\mathbb{Z})$ . In other words, it is checked that the discriminant is non-zero, but it is not checked whether the discriminant is a unit in  $\mathbb{Z}^*$ .

```
sage: P.<x> = ZZ[]
sage: HyperellipticCurve(3*x^7+6*x+6)
Hyperelliptic Curve over Integer Ring defined by y^2 = 3*x^7 + 6*x + 6
```

## 16.2 Hyperelliptic curves over a general ring

EXAMPLES:

```
sage: P.<x> = GF(5)[t]
sage: f = x^5 - 3*x^4 - 2*x^3 + 6*x^2 + 3*x - 1
sage: C = HyperellipticCurve(f); C
Hyperelliptic Curve over Finite Field of size 5 defined by y^2 = x^5 + 2*x^4 + 3*x^3 +
↪+ x^2 + 3*x + 4
```

EXAMPLES:

```
sage: P.<x> = QQ[]
sage: f = 4*x^5 - 30*x^3 + 45*x - 22
sage: C = HyperellipticCurve(f); C
Hyperelliptic Curve over Rational Field defined by y^2 = 4*x^5 - 30*x^3 + 45*x - 22
sage: C.genus()
2

sage: D = C.affine_patch(0)
sage: D.defining_polynomials()[0].parent()
Multivariate Polynomial Ring in x0, x1 over Rational Field
```

**class** sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.**HyperellipticCurve\_generic** (*P*

Bases: *sage.schemes.curves.projective\_curve.ProjectivePlaneCurve*

**base\_extend** (*R*)

Returns this HyperellipticCurve over a new base ring *R*.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: H = HyperellipticCurve(x^5 - 10*x + 9)
sage: K = Qp(3,5)
sage: L.<a> = K.extension(x^30-3)
sage: HK = H.change_ring(K)
sage: HL = HK.change_ring(L); HL
Hyperelliptic Curve over Eisenstein Extension in a defined by x^30 - 3 with
↳ capped relative precision 150 over 3-adic Field defined by (1 + O(a^150))*y^
↳ 2 = (1 + O(a^150))*x^5 + (2 + 2*a^30 + a^60 + 2*a^90 + 2*a^120 + O(a^
↳ 150))*x + a^60 + O(a^210)

sage: R.<x> = FiniteField(7)[]
sage: H = HyperellipticCurve(x^8 + x + 5)
sage: H.base_extend(FiniteField(7^2, 'a'))
Hyperelliptic Curve over Finite Field in a of size 7^2 defined by y^2 = x^8 +
↳ x + 5
```

**change\_ring** (*R*)

Returns this HyperellipticCurve over a new base ring *R*.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: H = HyperellipticCurve(x^5 - 10*x + 9)
sage: K = Qp(3,5)
sage: L.<a> = K.extension(x^30-3)
sage: HK = H.change_ring(K)
sage: HL = HK.change_ring(L); HL
Hyperelliptic Curve over Eisenstein Extension in a defined by x^30 - 3 with
↳ capped relative precision 150 over 3-adic Field defined by (1 + O(a^150))*y^
↳ 2 = (1 + O(a^150))*x^5 + (2 + 2*a^30 + a^60 + 2*a^90 + 2*a^120 + O(a^
↳ 150))*x + a^60 + O(a^210)

sage: R.<x> = FiniteField(7)[]
sage: H = HyperellipticCurve(x^8 + x + 5)
sage: H.base_extend(FiniteField(7^2, 'a'))
Hyperelliptic Curve over Finite Field in a of size 7^2 defined by y^2 = x^8 +
↳ x + 5
```

**genus** ()

**has\_odd\_degree\_model** ()

Return True if an odd degree model of self exists over the field of definition; False otherwise.

Use `odd_degree_model` to calculate an odd degree model.

EXAMPLES:

```

sage: x = QQ['x'].0
sage: HyperellipticCurve(x^5 + x).has_odd_degree_model()
True
sage: HyperellipticCurve(x^6 + x).has_odd_degree_model()
True
sage: HyperellipticCurve(x^6 + x + 1).has_odd_degree_model()
False

```

**hyperelliptic\_polynomials** ( $K=None$ ,  $var='x'$ )

EXAMPLES:

```

sage: R.<x> = QQ[]; C = HyperellipticCurve(x^3 + x - 1, x^3/5); C
Hyperelliptic Curve over Rational Field defined by y^2 + 1/5*x^3*y = x^3 + x -
↪ 1
sage: C.hyperelliptic_polynomials()
(x^3 + x - 1, 1/5*x^3)

```

**invariant\_differential** ()

Returns  $dx/2y$ , as an element of the Monsky-Washnitzer cohomology of self

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5 - 4*x + 4)
sage: C.invariant_differential()
1 dx/2y

```

**is\_singular** ()

Returns False, because hyperelliptic curves are smooth projective curves, as checked on construction.

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: H = HyperellipticCurve(x^5+1)
sage: H.is_singular()
False

```

A hyperelliptic curve with genus at least 2 always has a singularity at infinity when viewed as a *plane* projective curve. This can be seen in the following example.:

```

sage: R.<x> = QQ[]
sage: H = HyperellipticCurve(x^5+2)
sage: set_verbose(None)
sage: H.is_singular()
False
sage: from sage.schemes.curves.projective_curve import ProjectivePlaneCurve
sage: ProjectivePlaneCurve.is_singular(H)
True

```

**is\_smooth** ()

Returns True, because hyperelliptic curves are smooth projective curves, as checked on construction.

EXAMPLES:

```

sage: R.<x> = GF(13)[]
sage: H = HyperellipticCurve(x^8+1)
sage: H.is_smooth()
True

```

A hyperelliptic curve with genus at least 2 always has a singularity at infinity when viewed as a *plane* projective curve. This can be seen in the following example.:

```
sage: R.<x> = GF(27, 'a') []
sage: H = HyperellipticCurve(x^10+2)
sage: set_verbose(None)
sage: H.is_smooth()
True
sage: from sage.schemes.curves.projective_curve import ProjectivePlaneCurve
sage: ProjectivePlaneCurve.is_smooth(H)
False
```

**jacobian()**

**lift\_x**(*x*, *all*=False)

**local\_coord**(*P*, *prec*=20, *name*='t')

Calls the appropriate local\_coordinates function

INPUT:

- *P* – a point on self
- *prec* – desired precision of the local coordinates
- *name* – generator of the power series ring (default: *t*)

OUTPUT:

$(x(t), y(t))$  such that  $y(t)^2 = f(x(t))$ , where  $t$  is the local parameter at  $P$

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^5-23*x^3+18*x^2+40*x)
sage: H.local_coord(H(1, 6), prec=5)
(1 + t + O(t^5), 6 + t - 7/2*t^2 - 1/2*t^3 - 25/48*t^4 + O(t^5))
sage: H.local_coord(H(4, 0), prec=7)
(4 + 1/360*t^2 - 191/23328000*t^4 + 7579/188956800000*t^6 + O(t^7), t + O(t^7))
sage: H.local_coord(H(0, 1, 0), prec=5)
(t^-2 + 23*t^2 - 18*t^4 - 569*t^6 + O(t^7), t^-5 + 46*t^-1 - 36*t - 609*t^3 +
↳ 1656*t^5 + O(t^6))
```

**AUTHOR:**

- Jennifer Balakrishnan (2007-12)

**local\_coordinates\_at\_infinity**(*prec*=20, *name*='t')

For the genus  $g$  hyperelliptic curve  $y^2 = f(x)$ , return  $(x(t), y(t))$  such that  $(y(t))^2 = f(x(t))$ , where  $t = x^g/y$  is the local parameter at infinity

INPUT:

- *prec* – desired precision of the local coordinates
- *name* – generator of the power series ring (default: *t*)

OUTPUT:

$(x(t), y(t))$  such that  $y(t)^2 = f(x(t))$  and  $t = x^g/y$  is the local parameter at infinity

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^5-5*x^2+1)
sage: x,y = H.local_coordinates_at_infinity(10)
sage: x
t^-2 + 5*t^4 - t^8 - 50*t^10 + O(t^12)
sage: y
t^-5 + 10*t - 2*t^5 - 75*t^7 + 50*t^11 + O(t^12)

```

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-x+1)
sage: x,y = H.local_coordinates_at_infinity(10)
sage: x
t^-2 + t^2 - t^4 - t^6 + 3*t^8 + O(t^12)
sage: y
t^-3 + t - t^3 - t^5 + 3*t^7 - 10*t^11 + O(t^12)

```

AUTHOR:

- Jennifer Balakrishnan (2007-12)

**local\_coordinates\_at\_nonweierstrass**( $P$ ,  $prec=20$ ,  $name='t'$ )

For a non-Weierstrass point  $P = (a, b)$  on the hyperelliptic curve  $y^2 = f(x)$ , return  $(x(t), y(t))$  such that  $(y(t))^2 = f(x(t))$ , where  $t = x - a$  is the local parameter.

INPUT:

- $P = (a, b)$  – a non-Weierstrass point on self
- $prec$  – desired precision of the local coordinates
- $name$  – gen of the power series ring (default:  $t$ )

OUTPUT:

$(x(t), y(t))$  such that  $y(t)^2 = f(x(t))$  and  $t = x - a$  is the local parameter at  $P$

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^5-23*x^3+18*x^2+40*x)
sage: P = H(1,6)
sage: x,y = H.local_coordinates_at_nonweierstrass(P,prec=5)
sage: x
1 + t + O(t^5)
sage: y
6 + t - 7/2*t^2 - 1/2*t^3 - 25/48*t^4 + O(t^5)
sage: Q = H(-2,12)
sage: x,y = H.local_coordinates_at_nonweierstrass(Q,prec=5)
sage: x
-2 + t + O(t^5)
sage: y
12 - 19/2*t - 19/32*t^2 + 61/256*t^3 - 5965/24576*t^4 + O(t^5)

```

AUTHOR:

- Jennifer Balakrishnan (2007-12)

**local\_coordinates\_at\_weierstrass**( $P$ ,  $prec=20$ ,  $name='t'$ )

For a finite Weierstrass point on the hyperelliptic curve  $y^2 = f(x)$ , returns  $(x(t), y(t))$  such that  $(y(t))^2 = f(x(t))$ , where  $t = y$  is the local parameter.

INPUT:

- $P$  – a finite Weierstrass point on self
- `prec` – desired precision of the local coordinates
- `name` – gen of the power series ring (default:  $t$ )

OUTPUT:

$(x(t), y(t))$  such that  $y(t)^2 = f(x(t))$  and  $t = y$  is the local parameter at  $P$

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^5-23*x^3+18*x^2+40*x)
sage: A = H(4, 0)
sage: x, y = H.local_coordinates_at_weierstrass(A, prec=7)
sage: x
4 + 1/360*t^2 - 191/23328000*t^4 + 7579/188956800000*t^6 + O(t^7)
sage: y
t + O(t^7)
sage: B = H(-5, 0)
sage: x, y = H.local_coordinates_at_weierstrass(B, prec=5)
sage: x
-5 + 1/1260*t^2 + 887/2000376000*t^4 + O(t^5)
sage: y
t + O(t^5)
```

AUTHOR:

- Jennifer Balakrishnan (2007-12)
- Francis Clarke (2012-08-26)

`monsky_washnitzer_gens()`

`odd_degree_model()`

Return an odd degree model of self, or raise `ValueError` if one does not exist over the field of definition.

EXAMPLES:

```
sage: x = QQ['x'].gen()
sage: H = HyperellipticCurve((x^2 + 2)*(x^2 + 3)*(x^2 + 5)); H
Hyperelliptic Curve over Rational Field defined by y^2 = x^6 + 10*x^4 + 31*x^2 + 30
sage: H.odd_degree_model()
Traceback (most recent call last):
...
ValueError: No odd degree model exists over field of definition

sage: K2 = QuadraticField(-2, 'a')
sage: Hp2 = H.change_ring(K2).odd_degree_model(); Hp2
Hyperelliptic Curve over Number Field in a with defining polynomial x^2 + 2
defined by y^2 = 6*a*x^5 - 29*x^4 - 20*x^2 + 6*a*x + 1

sage: K3 = QuadraticField(-3, 'b')
sage: Hp3 = H.change_ring(QuadraticField(-3, 'b')).odd_degree_model(); Hp3
Hyperelliptic Curve over Number Field in b with defining polynomial x^2 + 3
defined by y^2 = -4*b*x^5 - 14*x^4 - 20*b*x^3 - 35*x^2 + 6*b*x + 1
```

Of course, `Hp2` and `Hp3` are isomorphic over the composite extension. One consequence of this is that odd degree models

reduced over "different" fields should have the same number of points on their reductions. 43 and 67 split completely in the compositum, so when we reduce we find:

```
sage: P2 = K2.factor(43)[0][0]
sage: P3 = K3.factor(43)[0][0]
sage: Hp2.change_ring(K2.residue_field(P2)).frobenius_polynomial()
x^4 - 16*x^3 + 134*x^2 - 688*x + 1849
sage: Hp3.change_ring(K3.residue_field(P3)).frobenius_polynomial()
x^4 - 16*x^3 + 134*x^2 - 688*x + 1849
sage: H.change_ring(GF(43)).odd_degree_model().frobenius_polynomial()
x^4 - 16*x^3 + 134*x^2 - 688*x + 1849

sage: P2 = K2.factor(67)[0][0]
sage: P3 = K3.factor(67)[0][0]
sage: Hp2.change_ring(K2.residue_field(P2)).frobenius_polynomial()
x^4 - 8*x^3 + 150*x^2 - 536*x + 4489
sage: Hp3.change_ring(K3.residue_field(P3)).frobenius_polynomial()
x^4 - 8*x^3 + 150*x^2 - 536*x + 4489
sage: H.change_ring(GF(67)).odd_degree_model().frobenius_polynomial()
x^4 - 8*x^3 + 150*x^2 - 536*x + 4489
```

sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.**is\_HyperellipticCurve**(C)  
EXAMPLES:

```
sage: R.<x> = QQ[]; C = HyperellipticCurve(x^3 + x - 1); C
Hyperelliptic Curve over Rational Field defined by y^2 = x^3 + x - 1
sage: sage.schemes.hyperelliptic_curves.hyperelliptic_generic.is_
↪HyperellipticCurve(C)
True
```

## 16.3 Hyperelliptic curves over a finite field

AUTHORS:

- David Kohel (2006)
- Robert Bradshaw (2007)
- Alyson Deines, Marina Gresham, Gagan Sekhon, (2010)
- Daniel Krenn (2011)
- Jean-Pierre Flori, Jan Tuitman (2013)
- Kiran Kedlaya (2016)
- Dean Bisogno (2017): Fixed Hasse-Witt computation

EXAMPLES:

```
sage: K.<a> = GF(9, 'a')
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^7 - x^5 - 2, x^2 + a)
sage: C._points_fast_sqrt()
[(0 : 1 : 0), (a + 1 : a : 1), (a + 1 : a + 1 : 1), (2 : a + 1 : 1), (2*a : 2*a + 2 : ↪
↪1), (2*a : 2*a : 1), (1 : a + 1 : 1)]
```

**class** sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.**HyperellipticCurve\_finite**

Bases: *sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic*

**Cartier\_matrix()**

INPUT:

- **E** : Hyperelliptic Curve of the form  $y^2 = f(x)$  over a finite field,  $\mathbb{F}_q$

OUTPUT:

- **M**: The matrix  $M = (c_{pi-j})$ , where  $c_i$  are the coefficients of  $f(x)^{(p-1)/2} = \sum c_i x^i$

REFERENCES:

14. Yui. On the Jacobian varieties of hyperelliptic curves over fields of characteristic  $p > 2$ .

EXAMPLES:

```
sage: K.<x>=GF(9,'x') []
sage: C=HyperellipticCurve(x^7-1,0)
sage: C.Cartier_matrix()
[0 0 2]
[0 0 0]
[0 1 0]

sage: K.<x>=GF(49,'x') []
sage: C=HyperellipticCurve(x^5+1,0)
sage: C.Cartier_matrix()
[0 3]
[0 0]

sage: P.<x>=GF(9,'a') []
sage: E=HyperellipticCurve(x^29+1,0)
sage: E.Cartier_matrix()
[0 0 1 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 1 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 1 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 1 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 1 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[1 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 1 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 1 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 1 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 1 0 0 0 0 0]
```

**Hasse\_Witt()**

INPUT:

- **E** : Hyperelliptic Curve of the form  $y^2 = f(x)$  over a finite field,  $\mathbb{F}_q$

OUTPUT:

- **N** : The matrix  $N = MM^p \dots M^{p^{g-1}}$  where  $M = c_{pi-j}$ , and  $f(x)^{(p-1)/2} = \sum c_i x^i$



Reference-N. Yui. On the Jacobian varieties of hyperelliptic curves over fields of characteristic  $p > 2$ .

EXAMPLES:

```
sage: K.<x>=GF(9,'x') []
sage: C=HyperellipticCurve(x^7-1,0)
sage: C.Hasse_Witt()
[0 0 0]
[0 0 0]
[0 0 0]

sage: K.<x>=GF(49,'x') []
sage: C=HyperellipticCurve(x^5+1,0)
sage: C.Hasse_Witt()
[0 0]
[0 0]

sage: P.<x>=GF(9,'a') []
sage: E=HyperellipticCurve(x^29+1,0)
sage: E.Hasse_Witt()
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
[0 0 0 0 0 0 0 0 0 0 0 0 0 0]
```

**a\_number()**

INPUT:

- E: Hyperelliptic Curve of the form  $y^2 = f(x)$  over a finite field,  $\mathbb{F}_q$

OUTPUT:

- a : a-number

EXAMPLES:

```
sage: K.<x>=GF(49,'x') []
sage: C=HyperellipticCurve(x^5+1,0)
sage: C.a_number()
1

sage: K.<x>=GF(9,'x') []
sage: C=HyperellipticCurve(x^7-1,0)
sage: C.a_number()
1

sage: P.<x>=GF(9,'a') []
sage: E=HyperellipticCurve(x^29+1,0)
sage: E.a_number()
5
```

**cardinality** (*extension\_degree=1*)

Count points on a single extension of the base field.

EXAMPLES:

```

sage: K = GF(101)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + 3*t^5 + 5)
sage: H.cardinality()
106
sage: H.cardinality(15)
1160968955369992567076405831000
sage: H.cardinality(100)
27048138294215260932671947108075308336779383827810027768902010491171015143067392794394560143

sage: K = GF(37)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + 3*t^5 + 5)
sage: H.cardinality()
40
sage: H.cardinality(2)
1408
sage: H.cardinality(3)
50116

```

The following example shows that [trac ticket #20391](#) has been resolved:: sage: F=GF(23) sage: x=polygen(F) sage: C=HyperellipticCurve(x^8+1) sage: C.cardinality() 24

**cardinality\_exhaustive** (*extension\_degree=1, algorithm=None*)

Count points on a single extension of the base field by enumerating over x and solving the resulting quadratic equation for y.

EXAMPLES:

```

sage: K.<a> = GF(9, 'a')
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^7 - 1, x^2 + a)
sage: C.cardinality_exhaustive()
7

sage: K = GF(next_prime(1<<10))
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^7 + 3*t^5 + 5)
sage: H.cardinality_exhaustive()
1025

sage: P.<x> = PolynomialRing(GF(9, 'a'))
sage: H = HyperellipticCurve(x^5+x^2+1)
sage: H.count_points(5)
[18, 78, 738, 6366, 60018]

sage: F.<a> = GF(4); P.<x> = F[]
sage: H = HyperellipticCurve(x^5+a*x^2+1, x+a+1)
sage: H.count_points(6)
[2, 24, 74, 256, 1082, 4272]

```

**cardinality\_hypellfrob** (*extension\_degree=1, algorithm=None*)Count points on a single extension of the base field using the `hypellfrob` program.

EXAMPLES:

```
sage: K = GF(next_prime(1<<10))
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^7 + 3*t^5 + 5)
sage: H.cardinality_hypellfrob()
1025

sage: K = GF(49999)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^7 + 3*t^5 + 5)
sage: H.cardinality_hypellfrob()
50162
sage: H.cardinality_hypellfrob(3)
124992471088310
```

**count\_points** ( $n=1$ )

Count points over finite fields.

INPUT:

- $n$  – integer.

OUTPUT:

An integer. The number of points over  $\mathbf{F}_q, \dots, \mathbf{F}_{q^n}$  on a hyperelliptic curve over a finite field  $\mathbf{F}_q$ .

**Warning:** This is currently using exhaustive search for hyperelliptic curves over non-prime fields, which can be awfully slow.

EXAMPLES:

```
sage: P.<x> = PolynomialRing(GF(3))
sage: C = HyperellipticCurve(x^3+x^2+1)
sage: C.count_points(4)
[6, 12, 18, 96]
sage: C.base_extend(GF(9, 'a')).count_points(2)
[12, 96]

sage: K = GF(2**31-1)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + 3*t + 5)
sage: H.count_points() # long time, 2.4 sec on a Corei7
[2147464821]
sage: H.count_points(n=2) # long time, 30s on a Corei7
[2147464821, 4611686018988310237]

sage: K = GF(2**7-1)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^13 + 3*t^5 + 5)
sage: H.count_points(n=6)
[112, 16360, 2045356, 260199160, 33038302802, 4195868633548]

sage: P.<x> = PolynomialRing(GF(3))
sage: H = HyperellipticCurve(x^3+x^2+1)
sage: C1 = H.count_points(4); C1
[6, 12, 18, 96]
sage: C2 = sage.schemes.generic.scheme.Scheme.count_points(H,4); C2 # long
time, 2s on a Corei7
```

```
[6, 12, 18, 96]
sage: C1 == C2 # long time, because we need C2 to be defined
True

sage: P.<x> = PolynomialRing(GF(9,'a'))
sage: H = HyperellipticCurve(x^5+x^2+1)
sage: H.count_points(5)
[18, 78, 738, 6366, 60018]

sage: F.<a> = GF(4); P.<x> = F[]
sage: H = HyperellipticCurve(x^5+a*x^2+1, x+a+1)
sage: H.count_points(6)
[2, 24, 74, 256, 1082, 4272]
```

This example shows that [trac ticket #20391](#) is resolved:

```
sage: x = polygen(GF(4099))
sage: H = HyperellipticCurve(x^6 + x + 1)
sage: H.count_points(1)
[4106]
```

#### **count\_points\_exhaustive** (*n=1, naive=False*)

Count the number of points on the curve over the first  $n$  extensions of the base field by exhaustive search if  $n$  is smaller than  $g$ , the genus of the curve, and by computing the frobenius polynomial after performing exhaustive search on the first  $g$  extensions if  $n > g$  (unless `naive == True`).

EXAMPLES:

```
sage: K = GF(5)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + t^3 + 1)
sage: H.count_points_exhaustive(n=5)
[9, 27, 108, 675, 3069]
```

When  $n > g$ , the frobenius polynomial is computed from the numbers of points of the curve over the first  $g$  extension, so that computing the number of points on extensions of degree  $n > g$  is not much more expensive than for  $n == g$ :

```
sage: H.count_points_exhaustive(n=15)
[9,
 27,
 108,
 675,
 3069,
 16302,
 78633,
 389475,
 1954044,
 9768627,
 48814533,
 244072650,
 1220693769,
 6103414827,
 30517927308]
```

This behavior can be disabled by passing `naive=True`:

```
sage: H.count_points_exhaustive(n=6, naive=True) # long time, 7s on a Corei7
[9, 27, 108, 675, 3069, 16302]
```

**count\_points\_frobenius\_polynomial** ( $n=1, f=None$ )

Count the number of points on the curve over the first  $n$  extensions of the base field by computing the frobenius polynomial.

EXAMPLES:

```
sage: K = GF(49999)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^19 + t + 1)
```

The following computation takes a long time as the complete characteristic polynomial of the frobenius is computed:

```
sage: H.count_points_frobenius_polynomial(3) # long time, 20s on a Corei7
↪ (when computed before the following test of course)
[49491, 2500024375, 124992509154249]
```

As the polynomial is cached, further computations of number of points are really fast:

```
sage: H.count_points_frobenius_polynomial(19) # long time, because of the
↪ previous test
[49491,
2500024375,
124992509154249,
6249500007135192947,
312468751250758776051811,
15623125093747382662737313867,
781140631562281338861289572576257,
39056250437482500417107992413002794587,
1952773465623687539373429411200893147181079,
97636720507718753281169963459063147221761552935,
4881738388665429945305281187129778704058864736771824,
244082037694882831835318764490138139735446240036293092851,
12203857802706446708934102903106811520015567632046432103159713,
610180686277519628999996211052002771035439565767719719151141201339,
30508424133189703930370810556389262704405225546438978173388673620145499,
1525390698235352006814610157008906752699329454643826047826098161898351623931,
76268009521069364988723693240288328729528917832735078791261015331201838856825193,
↪
3813324208043947180071195938321176148147244128062172555558715783649006587868272993991,
↪
190662397077989315056379725720120486231213267083935859751911720230901597698389839098903847]
```

**count\_points\_hypellfrob** ( $n=1, N=None, algorithm=None$ )

Count the number of points on the curve over the first  $n$  extensions of the base field using the hypellfrob program.

This only supports prime fields of large enough characteristic.

EXAMPLES:

```
sage: K = GF(49999)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^21 + 3*t^5 + 5)
sage: H.count_points_hypellfrob()
```

```
[49804]
sage: H.count_points_hypellfrob(2)
[49804, 2499799038]

sage: K = GF(2**7-1)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^11 + 3*t^5 + 5)
sage: H.count_points_hypellfrob()
[127]
sage: H.count_points_hypellfrob(n=5)
[127, 16335, 2045701, 260134299, 33038098487]

sage: K = GF(2**7-1)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^13 + 3*t^5 + 5)
sage: H.count_points(n=6)
[112, 16360, 2045356, 260199160, 33038302802, 4195868633548]
```

The base field should be prime:

```
sage: K.<z> = GF(19**10)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + (z+1)*t^5 + 1)
sage: H.count_points_hypellfrob()
Traceback (most recent call last):
...
ValueError: hypellfrob does not support non-prime fields
```

and the characteristic should be large enough:

```
sage: K = GF(7)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + t^3 + 1)
sage: H.count_points_hypellfrob()
Traceback (most recent call last):
...
ValueError: p=7 should be greater than (2*g+1)(2*N-1)=27
```

**count\_points\_matrix\_traces** ( $n=1, M=None, N=None$ )

Count the number of points on the curve over the first  $n$  extensions of the base field by computing traces of powers of the frobenius matrix. This requires less  $p$ -adic precision than computing the charpoly of the matrix when  $n < g$  where  $g$  is the genus of the curve.

EXAMPLES:

```
sage: K = GF(49999)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^19 + t + 1)
sage: H.count_points_matrix_traces(3)
[49491, 2500024375, 124992509154249]
```

**frobenius\_matrix** ( $N=None, \text{algorithm}='hypellfrob'$ )

Compute  $p$ -adic frobenius matrix to precision  $p^N$ . If  $N$  not supplied, a default value is selected, which is the minimum needed to recover the charpoly unambiguously.

**Note:** Currently only implemented using `hypellfrob`, which means it only works over the prime field

$GF(p)$ , and requires  $p > (2g + 1)(2N - 1)$ .

EXAMPLES:

```
sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.frobenius_matrix()
[1258 + O(37^2)  925 + O(37^2)  132 + O(37^2)  587 + O(37^2)]
[1147 + O(37^2)  814 + O(37^2)  241 + O(37^2) 1011 + O(37^2)]
[1258 + O(37^2) 1184 + O(37^2) 1105 + O(37^2)  482 + O(37^2)]
[1073 + O(37^2)  999 + O(37^2)  772 + O(37^2)  929 + O(37^2)]
```

The hypellfrob program doesn't support non-prime fields:

```
sage: K.<z> = GF(37**3)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + z*t^3 + 1)
sage: H.frobenius_matrix(algorithm='hypellfrob')
Traceback (most recent call last):
...
NotImplementedError: Computation of Frobenius matrix only implemented for
↳hyperelliptic curves defined over prime fields.
```

nor too small characteristic:

```
sage: K = GF(7)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + t^3 + 1)
sage: H.frobenius_matrix(algorithm='hypellfrob')
Traceback (most recent call last):
...
ValueError: In the current implementation, p must be greater than (2g+1)(2N-
↳1) = 81
```

**frobenius\_matrix\_hypellfrob** ( $N=None$ )

Compute  $p$ -adic frobenius matrix to precision  $p^N$ . If  $N$  not supplied, a default value is selected, which is the minimum needed to recover the charpoly unambiguously.

**Note:** Implemented using hypellfrob, which means it only works over the prime field  $GF(p)$ , and requires  $p > (2g + 1)(2N - 1)$ .

EXAMPLES:

```
sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.frobenius_matrix_hypellfrob()
[1258 + O(37^2)  925 + O(37^2)  132 + O(37^2)  587 + O(37^2)]
[1147 + O(37^2)  814 + O(37^2)  241 + O(37^2) 1011 + O(37^2)]
[1258 + O(37^2) 1184 + O(37^2) 1105 + O(37^2)  482 + O(37^2)]
[1073 + O(37^2)  999 + O(37^2)  772 + O(37^2)  929 + O(37^2)]
```

The hypellfrob program doesn't support non-prime fields:

```
sage: K.<z> = GF(37**3)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + z*t^3 + 1)
```

```
sage: H.frobenius_matrix_hypellfrob()
Traceback (most recent call last):
...
NotImplementedError: Computation of Frobenius matrix only implemented for
↳ hyperelliptic curves defined over prime fields.
```

nor too small characteristic:

```
sage: K = GF(7)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + t^3 + 1)
sage: H.frobenius_matrix_hypellfrob()
Traceback (most recent call last):
...
ValueError: In the current implementation, p must be greater than (2g+1)(2N-
↳ 1) = 81
```

### **frobenius\_polynomial()**

Compute the charpoly of frobenius, as an element of  $\mathbf{Z}[x]$ .

EXAMPLES:

```
sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.frobenius_polynomial()
x^4 + x^3 - 52*x^2 + 37*x + 1369
```

A quadratic twist:

```
sage: H = HyperellipticCurve(2*t^5 + 2*t + 4)
sage: H.frobenius_polynomial()
x^4 - x^3 - 52*x^2 - 37*x + 1369
```

Slightly larger example:

```
sage: K = GF(2003)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^7 + 487*t^5 + 9*t + 1)
sage: H.frobenius_polynomial()
x^6 - 14*x^5 + 1512*x^4 - 66290*x^3 + 3028536*x^2 - 56168126*x + 8036054027
```

Curves defined over a non-prime field of odd characteristic, or an odd prime field which is too small compared to the genus, are supported via PARI:

```
sage: K.<z> = GF(23**3)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^3 + z*t + 4)
sage: H.frobenius_polynomial()
x^2 - 15*x + 12167

sage: K.<z> = GF(3**3)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + z*t + z**3)
sage: H.frobenius_polynomial()
x^4 - 3*x^3 + 10*x^2 - 81*x + 729
```

Over prime fields of odd characteristic,  $h$  may be non-zero:



```

sage: K = GF(101)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + 27*t + 3, t)
sage: H.frobenius_polynomial()
x^4 + 2*x^3 - 58*x^2 + 202*x + 10201

```

Over prime fields of odd characteristic,  $f$  may have even degree:

```

sage: H = HyperellipticCurve(t^6 + 27*t + 3)
sage: H.frobenius_polynomial()
x^4 + 25*x^3 + 322*x^2 + 2525*x + 10201

```

In even characteristic, the naive algorithm could cover all cases because we can easily check for squareness in quotient rings of polynomial rings over finite fields but these rings unfortunately do not support iteration:

```

sage: K.<z> = GF(2**5)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + z*t + z**3, t)
sage: H.frobenius_polynomial()
x^4 - x^3 + 16*x^2 - 32*x + 1024

```

#### **frobenius\_polynomial\_cardinalities** ( $a=None$ )

Compute the charpoly of frobenius, as an element of  $\mathbb{Z}[x]$ , by computing the number of points on the curve over  $g$  extensions of the base field where  $g$  is the genus of the curve.

**Warning:** This is highly inefficient when the base field or the genus of the curve are large.

EXAMPLES:

```

sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.frobenius_polynomial_cardinalities()
x^4 + x^3 - 52*x^2 + 37*x + 1369

```

A quadratic twist:

```

sage: H = HyperellipticCurve(2*t^5 + 2*t + 4)
sage: H.frobenius_polynomial_cardinalities()
x^4 - x^3 - 52*x^2 - 37*x + 1369

```

Curve over a non-prime field:

```

sage: K.<z> = GF(7**2)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + z*t + z^2)
sage: H.frobenius_polynomial_cardinalities()
x^4 + 8*x^3 + 70*x^2 + 392*x + 2401

```

This method may actually be useful when *hypellfrob* does not work:

```

sage: K = GF(7)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + t^3 + 1)
sage: H.frobenius_polynomial_matrix(algorithm='hypellfrob')
Traceback (most recent call last):
...

```

```

ValueError: In the current implementation, p must be greater than (2g+1)(2N-
↪1) = 81
sage: H.frobenius_polynomial_cardinalities()
x^8 - 5*x^7 + 7*x^6 + 36*x^5 - 180*x^4 + 252*x^3 + 343*x^2 - 1715*x + 2401

```

**frobenius\_polynomial\_matrix** ( $M=None$ ,  $algorithm='hypellfrob'$ )

Compute the charpoly of frobenius, as an element of  $\mathbf{Z}[x]$ , by computing the charpoly of the frobenius matrix.

This is currently only supported when the base field is prime and large enough using the `hypellfrob` library.

EXAMPLES:

```

sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.frobenius_polynomial_matrix()
x^4 + x^3 - 52*x^2 + 37*x + 1369

```

A quadratic twist:

```

sage: H = HyperellipticCurve(2*t^5 + 2*t + 4)
sage: H.frobenius_polynomial_matrix()
x^4 - x^3 - 52*x^2 - 37*x + 1369

```

Curves defined over larger prime fields:

```

sage: K = GF(49999)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + t^5 + 1)
sage: H.frobenius_polynomial_matrix()
x^8 + 281*x^7 + 55939*x^6 + 14144175*x^5 + 3156455369*x^4 + 707194605825*x^3 +
↪ 139841906155939*x^2 + 35122892542149719*x + 6249500014999800001
sage: H = HyperellipticCurve(t^15 + t^5 + 1)
sage: H.frobenius_polynomial_matrix() # long time, 8s on a Corei7
x^14 - 76*x^13 + 220846*x^12 - 12984372*x^11 + 24374326657*x^10 -
↪ 1203243210304*x^9 + 1770558798515792*x^8 - 74401511415210496*x^7 +
↪ 88526169366991084208*x^6 - 3007987702642212810304*x^5 +
↪ 3046608028331197124223343*x^4 - 81145833008762983138584372*x^3 +
↪ 69007473838551978905211279154*x^2 - 1187357507124810002849977200076*x +
↪ 781140631562281254374947500349999

```

This `hypellfrob` program doesn't support non-prime fields:

```

sage: K.<z> = GF(37**3)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^9 + z*t^3 + 1)
sage: H.frobenius_polynomial_matrix(algorithm='hypellfrob')
Traceback (most recent call last):
...
NotImplementedError: Computation of Frobenius matrix only implemented for
↪ hyperelliptic curves defined over prime fields.

```

**frobenius\_polynomial\_pari** ()

Compute the charpoly of frobenius, as an element of  $\mathbf{Z}[x]$ , by calling the PARI function `hyperellcharpoly`.

EXAMPLES:

```
sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.frobenius_polynomial_pari()
x^4 + x^3 - 52*x^2 + 37*x + 1369
```

A quadratic twist:

```
sage: H = HyperellipticCurve(2*t^5 + 2*t + 4)
sage: H.frobenius_polynomial_pari()
x^4 - x^3 - 52*x^2 - 37*x + 1369
```

Slightly larger example:

```
sage: K = GF(2003)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^7 + 487*t^5 + 9*t + 1)
sage: H.frobenius_polynomial_pari()
x^6 - 14*x^5 + 1512*x^4 - 66290*x^3 + 3028536*x^2 - 56168126*x + 8036054027
```

Curves defined over a non-prime field are supported as well:

```
sage: K.<a> = GF(7^2)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + a*t + 1)
sage: H.frobenius_polynomial_pari()
x^4 + 4*x^3 + 84*x^2 + 196*x + 2401

sage: K.<z> = GF(23^3)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^3 + z*t + 4)
sage: H.frobenius_polynomial_pari()
x^2 - 15*x + 12167
```

Over prime fields of odd characteristic,  $h$  may be non-zero:

```
sage: K = GF(101)
sage: R.<t> = PolynomialRing(K)
sage: H = HyperellipticCurve(t^5 + 27*t + 3, t)
sage: H.frobenius_polynomial_pari()
x^4 + 2*x^3 - 58*x^2 + 202*x + 10201
```

**p\_rank()**

INPUT:

- $E$  : Hyperelliptic Curve of the form  $y^2 = f(x)$  over a finite field,  $\mathbb{F}_q$

OUTPUT:

- `pr` :p-rank

EXAMPLES:

```
sage: K.<x>=GF(49, 'x') []
sage: C=HyperellipticCurve(x^5+1,0)
sage: C.p_rank()
0

sage: K.<x>=GF(9, 'x') []
sage: C=HyperellipticCurve(x^7-1,0)
```

```

sage: C.p_rank()
0

sage: P.<x>=GF(9, 'a') []
sage: E=HyperellipticCurve(x^29+1, 0)
sage: E.p_rank()
0

```

**points()**

All the points on this hyperelliptic curve.

EXAMPLES:

```

sage: x = polygen(GF(7))
sage: C = HyperellipticCurve(x^7 - x^2 - 1)
sage: C.points()
[(0 : 1 : 0), (2 : 5 : 1), (2 : 2 : 1), (3 : 0 : 1), (4 : 6 : 1), (4 : 1 : 1),
↪ (5 : 0 : 1), (6 : 5 : 1), (6 : 2 : 1)]

```

```

sage: x = polygen(GF(121, 'a'))
sage: C = HyperellipticCurve(x^5 + x - 1, x^2 + 2)
sage: len(C.points())
122

```

Conics are allowed (the issue reported at [trac ticket #11800](#) has been resolved):

```

sage: R.<x> = GF(7) []
sage: H = HyperellipticCurve(3*x^2 + 5*x + 1)
sage: H.points()
[(0 : 6 : 1), (0 : 1 : 1), (1 : 4 : 1), (1 : 3 : 1), (2 : 4 : 1), (2 : 3 : 1),
↪ (3 : 6 : 1), (3 : 1 : 1)]

```

The method currently lists points on the plane projective model, that is the closure in  $\mathbb{P}^2$  of the curve defined by  $y^2 + hy = f$ . This means that one point  $(0 : 1 : 0)$  at infinity is returned if the degree of the curve is at least 4 and  $\deg(f) > \deg(h) + 1$ . This point is a singular point of the plane model. Later implementations may consider a smooth model instead since that would be a more relevant object. Then, for a curve whose only singularity is at  $(0 : 1 : 0)$ , the point at infinity would be replaced by a number of rational points of the smooth model. We illustrate this with an example of a genus 2 hyperelliptic curve:

```

sage: R.<x>=GF(11) []
sage: H = HyperellipticCurve(x*(x+1)*(x+2)*(x+3)*(x+4)*(x+5))
sage: H.points()
[(0 : 1 : 0), (0 : 0 : 1), (1 : 7 : 1), (1 : 4 : 1), (5 : 7 : 1), (5 : 4 : 1),
↪ (6 : 0 : 1), (7 : 0 : 1), (8 : 0 : 1), (9 : 0 : 1), (10 : 0 : 1)]

```

The plane model of the genus 2 hyperelliptic curve in the above example is the curve in  $\mathbb{P}^2$  defined by  $y^2 z^4 = g(x, z)$  where  $g(x, z) = x(x+z)(x+2z)(x+3z)(x+4z)(x+5z)$ . This model has one point at infinity  $(0 : 1 : 0)$  which is also the only singular point of the plane model. In contrast, the hyperelliptic curve is smooth and imbeds via the equation  $y^2 = g(x, z)$  into weighted projected space  $\mathbb{P}(1, 3, 1)$ . The latter model has two points at infinity:  $(1 : 1 : 0)$  and  $(1 : -1 : 0)$ .

**zeta\_function()**

Compute the zeta function of the hyperelliptic curve.

EXAMPLES:

```

sage: F = GF(2); R.<t> = F[]
sage: H = HyperellipticCurve(t^9 + t, t^4)
sage: H.zeta_function()
(16*x^8 + 8*x^7 + 8*x^6 + 4*x^5 + 6*x^4 + 2*x^3 + 2*x^2 + x + 1)/(2*x^2 - 3*x_
↪ + 1)

sage: F.<a> = GF(4); R.<t> = F[]
sage: H = HyperellipticCurve(t^5 + t^3 + t^2 + t + 1, t^2 + t + 1)
sage: H.zeta_function()
(16*x^4 + 8*x^3 + x^2 + 2*x + 1)/(4*x^2 - 5*x + 1)

sage: F.<a> = GF(9); R.<t> = F[]
sage: H = HyperellipticCurve(t^5 + a*t)
sage: H.zeta_function()
(81*x^4 + 72*x^3 + 32*x^2 + 8*x + 1)/(9*x^2 - 10*x + 1)

sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(t^5 + t + 2)
sage: H.zeta_function()
(1369*x^4 + 37*x^3 - 52*x^2 + x + 1)/(37*x^2 - 38*x + 1)

```

A quadratic twist:

```

sage: R.<t> = PolynomialRing(GF(37))
sage: H = HyperellipticCurve(2*t^5 + 2*t + 4)
sage: H.zeta_function()
(1369*x^4 - 37*x^3 - 52*x^2 - x + 1)/(37*x^2 - 38*x + 1)

```

## 16.4 Hyperelliptic curves over a p-adic field.

**class** sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic

Bases: *sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic*

**P\_to\_S**(*P*, *S*)

Given a finite Weierstrass point *P* and a point *S* in the same disc, computes the Coleman integrals  $\{\int_P^S x^i dx/2y\}_{i=0}^{2g-1}$

INPUT:

- *P*: finite Weierstrass point
- *S*: point in disc of *P*

OUTPUT:

Coleman integrals  $\{\int_P^S x^i dx/2y\}_{i=0}^{2g-1}$

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,4)

```

```

sage: HK = H.change_ring(K)
sage: P = HK(1,0)
sage: HJ = HK.curve_over_ram_extn(10)
sage: S = HK.get_boundary_point(HJ,P)
sage: HK.P_to_S(P, S)
(2*a + 4*a^3 + 2*a^11 + 4*a^13 + 2*a^17 + 2*a^19 + a^21 + 4*a^23 + a^25 + 2*a^
↪ 27 + 2*a^29 + 3*a^31 + 4*a^33 + O(a^35), a^-5 + 2*a + 2*a^3 + a^7 + 3*a^11,
↪ a^13 + 3*a^15 + 3*a^17 + 2*a^19 + 4*a^21 + 4*a^23 + 4*a^25 + 2*a^27 + a^
↪ 29 + a^31 + O(a^33))

```

AUTHOR:

- Jennifer Balakrishnan

**S\_to\_Q**( $S, Q$ )

Given  $S$  a point on self over an extension field, computes the Coleman integrals  $\{\int_S^Q x^i dx/2y\}_{i=0}^{2g-1}$

one should be able to feed ‘S,Q’ into `coleman_integral`, but currently that segfaults

INPUT:

- $S$ : a point with coordinates in an extension of  $\mathbf{Q}_p$  (with unif.  $a$ )
- $Q$ : a non-Weierstrass point defined over  $\mathbf{Q}_p$

OUTPUT:

the Coleman integrals  $\{\int_S^Q x^i dx/2y\}_{i=0}^{2g-1}$  in terms of  $a$

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,6)
sage: HK = H.change_ring(K)
sage: J.<a> = K.extension(x^20-5)
sage: HJ = H.change_ring(J)
sage: w = HK.invariant_differential()
sage: x,y = HK.monsky_washnitzer_gens()
sage: P = HK(1,0)
sage: Q = HK(0,3)
sage: S = HK.get_boundary_point(HJ,P)
sage: P_to_S = HK.P_to_S(P, S)
sage: S_to_Q = HJ.S_to_Q(S, Q)
sage: P_to_S + S_to_Q
(2*a^40 + a^80 + a^100 + O(a^105), a^20 + 2*a^40 + 4*a^60 + 2*a^80 + O(a^103))
sage: HK.coleman_integrals_on_basis(P,Q)
(2*5^2 + 5^4 + 5^5 + 3*5^6 + O(5^7), 5 + 2*5^2 + 4*5^3 + 2*5^4 + 5^6 + O(5^7))

```

AUTHOR:

- Jennifer Balakrishnan

**coleman\_integral**( $w, P, Q, \text{algorithm}='None'$ )

Returns the Coleman integral  $\int_P^Q w$

INPUT:

- $w$  differential (if one of  $P, Q$  is Weierstrass,  $w$  must be odd)
- $P$  point on self
- $Q$  point on self

- algorithm (optional) = None (uses Frobenius) or teichmuller (uses Teichmuller points)

OUTPUT:

the Coleman integral  $\int_P^Q w$

EXAMPLES:

Example of Leprevost from Kiran Kedlaya The first two should be zero as  $(P - Q) = 30(P - Q)$  in the Jacobian and  $dx/2y$  and  $xdx/2y$  are holomorphic.

```
sage: K = pAdicField(11, 6)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪16)
sage: P = C(-1, 1); P1 = C(-1, -1)
sage: Q = C(0, 1/4); Q1 = C(0, -1/4)
sage: x, y = C.monsky_washnitzer_gens()
sage: w = C.invariant_differential()
sage: w.coleman_integral(P, Q)
O(11^6)
sage: C.coleman_integral(x*w, P, Q)
O(11^6)
sage: C.coleman_integral(x^2*w, P, Q)
7*11 + 6*11^2 + 3*11^3 + 11^4 + 5*11^5 + O(11^6)
```

```
sage: p = 71; m = 4
sage: K = pAdicField(p, m)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪16)
sage: P = C(-1, 1); P1 = C(-1, -1)
sage: Q = C(0, 1/4); Q1 = C(0, -1/4)
sage: x, y = C.monsky_washnitzer_gens()
sage: w = C.invariant_differential()
sage: w.integrate(P, Q), (x*w).integrate(P, Q)
(O(71^4), O(71^4))
sage: R, R1 = C.lift_x(4, all=True)
sage: w.integrate(P, R)
21*71 + 67*71^2 + 27*71^3 + O(71^4)
sage: w.integrate(P, R) + w.integrate(P1, R1)
O(71^4)
```

A simple example, integrating dx:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^3-4*x+4)
sage: K = Qp(5, 10)
sage: EK = E.change_ring(K)
sage: P = EK(2, 2)
sage: Q = EK.teichmuller(P)
sage: x, y = EK.monsky_washnitzer_gens()
sage: EK.coleman_integral(x.diff(), P, Q)
5 + 2*5^2 + 5^3 + 3*5^4 + 4*5^5 + 2*5^6 + 3*5^7 + 3*5^9 + O(5^10)
sage: Q[0] - P[0]
5 + 2*5^2 + 5^3 + 3*5^4 + 4*5^5 + 2*5^6 + 3*5^7 + 3*5^9 + O(5^10)
```

Yet another example:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x*(x-1)*(x+9))
sage: K = Qp(7,10)
sage: HK = H.change_ring(K)
sage: import sage.schemes.hyperelliptic_curves.monsky_washnitzer as mw
sage: M_frob, forms = mw.matrix_of_frobenius_hyperelliptic(HK)
sage: w = HK.invariant_differential()
sage: x,y = HK.monsky_washnitzer_gens()
sage: f = forms[0]
sage: S = HK(9,36)
sage: Q = HK.teichmuller(S)
sage: P = HK(-1,4)
sage: b = x*w*w._coeff.parent()(f)
sage: HK.coleman_integral(b,P,Q)
7 + 7^2 + 4*7^3 + 5*7^4 + 3*7^5 + 7^6 + 5*7^7 + 3*7^8 + 4*7^9 + 4*7^10 + O(7^
↪11)

```

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3+1)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: w = HK.invariant_differential()
sage: P = HK(0,1)
sage: Q = HK.lift_x(5)
sage: x,y = HK.monsky_washnitzer_gens()
sage: (2*y*w).coleman_integral(P,Q)
5 + O(5^9)
sage: xloc,yloc,zloc = HK.local_analytic_interpolation(P,Q)
sage: I2 = (xloc.derivative()/(2*yloc)).integral()
sage: I2.polynomial()(1) - I2(0)
3*5 + 2*5^2 + 2*5^3 + 5^4 + 4*5^6 + 5^7 + O(5^9)
sage: HK.coleman_integral(w,P,Q)
3*5 + 2*5^2 + 2*5^3 + 5^4 + 4*5^6 + 5^7 + O(5^9)

```

Integrals involving Weierstrass points:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: S = HK(1,0)
sage: P = HK(0,3)
sage: negP = HK(0,-3)
sage: T = HK(0,1,0)
sage: w = HK.invariant_differential()
sage: x,y = HK.monsky_washnitzer_gens()
sage: HK.coleman_integral(w*x^3,S,T)
0
sage: HK.coleman_integral(w*x^3,T,S)
0
sage: HK.coleman_integral(w,S,P)
2*5^2 + 5^4 + 5^5 + 3*5^6 + 3*5^7 + 2*5^8 + O(5^9)
sage: HK.coleman_integral(w,T,P)
2*5^2 + 5^4 + 5^5 + 3*5^6 + 3*5^7 + 2*5^8 + O(5^9)
sage: HK.coleman_integral(w*x^3,T,P)
5^2 + 2*5^3 + 3*5^6 + 3*5^7 + O(5^8)
sage: HK.coleman_integral(w*x^3,S,P)
5^2 + 2*5^3 + 3*5^6 + 3*5^7 + O(5^8)

```



```

sage: HK.coleman_integral(w, P, negP, algorithm='teichmuller')
5^2 + 4*5^3 + 2*5^4 + 2*5^5 + 3*5^6 + 2*5^7 + 4*5^8 + O(5^9)
sage: HK.coleman_integral(w, P, negP)
5^2 + 4*5^3 + 2*5^4 + 2*5^5 + 3*5^6 + 2*5^7 + 4*5^8 + O(5^9)

```

AUTHORS:

- Robert Bradshaw (2007-03)
- Kiran Kedlaya (2008-05)
- Jennifer Balakrishnan (2010-02)

**coleman\_integral\_P\_to\_S**( $w, P, S$ )

Given a finite Weierstrass point  $P$  and a point  $S$  in the same disc, computes the Coleman integral  $\int_P^S w$

INPUT:

- $w$ : differential
- $P$ : Weierstrass point
- $S$ : point in the same disc of  $P$  ( $S$  is defined over an extension of  $\mathbf{Q}_p$ ; coordinates of  $S$  are given in terms of uniformizer  $a$ )

OUTPUT:

Coleman integral  $\int_P^S w$  in terms of  $a$

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,4)
sage: HK = H.change_ring(K)
sage: P = HK(1,0)
sage: J.<a> = K.extension(x^10-5)
sage: HJ = H.change_ring(J)
sage: S = HK.get_boundary_point(HJ,P)
sage: x,y = HK.monsky_washnitzer_gens()
sage: S[0]-P[0] == HK.coleman_integral_P_to_S(x.diff(),P,S)
True
sage: HK.coleman_integral_P_to_S(HK.invariant_differential(),P,S) == HK.P_to_
↪S(P,S)[0]
True

```

AUTHOR:

- Jennifer Balakrishnan

**coleman\_integral\_S\_to\_Q**( $w, S, Q$ )

Computes the Coleman integral  $\int_S^Q w$

**one should be able to feed ‘S,Q’ into coleman\_integral, but currently that segfaults**

INPUT:

- $w$ : a differential
- $S$ : a point with coordinates in an extension of  $\mathbf{Q}_p$
- $Q$ : a non-Weierstrass point defined over  $\mathbf{Q}_p$

OUTPUT:

the Coleman integral  $\int_S^Q w$

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,6)
sage: HK = H.change_ring(K)
sage: J.<a> = K.extension(x^20-5)
sage: HJ = H.change_ring(J)
sage: x,y = HK.monsky_washnitzer_gens()
sage: P = HK(1,0)
sage: Q = HK(0,3)
sage: S = HK.get_boundary_point(HJ,P)
sage: P_to_S = HK.coleman_integral_P_to_S(y.diff(),P,S)
sage: S_to_Q = HJ.coleman_integral_S_to_Q(y.diff(),S,Q)
sage: P_to_S + S_to_Q
3 + O(a^119)
sage: HK.coleman_integral(y.diff(),P,Q)
3 + O(5^6)
```

AUTHOR:

- Jennifer Balakrishnan

**coleman\_integral\_from\_weierstrass\_via\_boundary**( $w, P, Q, d$ )

Computes the Coleman integral  $\int_P^Q w$  via a boundary point in the disc of  $P$ , defined over a degree  $d$  extension

INPUT:

- $w$ : a differential
- $P$ : a Weierstrass point
- $Q$ : a non-Weierstrass point
- $d$ : degree of extension where coordinates of boundary point lie

OUTPUT:

the Coleman integral  $\int_P^Q w$ , written in terms of the uniformizer  $a$  of the degree  $d$  extension

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,6)
sage: HK = H.change_ring(K)
sage: P = HK(1,0)
sage: Q = HK(0,3)
sage: x,y = HK.monsky_washnitzer_gens()
sage: HK.coleman_integral_from_weierstrass_via_boundary(y.diff(),P,Q,20)
3 + O(a^119)
sage: HK.coleman_integral(y.diff(),P,Q)
3 + O(5^6)
sage: w = HK.invariant_differential()
sage: HK.coleman_integral_from_weierstrass_via_boundary(w,P,Q,20)
2*a^40 + a^80 + a^100 + O(a^105)
sage: HK.coleman_integral(w,P,Q)
2*5^2 + 5^4 + 5^5 + 3*5^6 + O(5^7)
```

AUTHOR:

- Jennifer Balakrishnan

**coleman\_integrals\_on\_basis** ( $P, Q, \text{algorithm}=\text{None}$ )

Computes the Coleman integrals  $\{\int_P^Q x^i dx/2y\}_{i=0}^{2g-1}$

INPUT:

- $P$  point on self
- $Q$  point on self
- `algorithm` (optional) = `None` (uses Frobenius) or `teichmuller` (uses Teichmuller points)

OUTPUT:

the Coleman integrals  $\{\int_P^Q x^i dx/2y\}_{i=0}^{2g-1}$

EXAMPLES:

```
sage: K = pAdicField(11, 5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪16)
sage: P = C.lift_x(2)
sage: Q = C.lift_x(3)
sage: C.coleman_integrals_on_basis(P, Q)
(10*11 + 6*11^3 + 2*11^4 + O(11^5), 11 + 9*11^2 + 7*11^3 + 9*11^4 + O(11^5), ↪
↪3 + 10*11 + 5*11^2 + 9*11^3 + 4*11^4 + O(11^5), 3 + 11 + 5*11^2 + 4*11^4 + ↪
↪O(11^5))
sage: C.coleman_integrals_on_basis(P, Q, algorithm='teichmuller')
(10*11 + 6*11^3 + 2*11^4 + O(11^5), 11 + 9*11^2 + 7*11^3 + 9*11^4 + O(11^5), ↪
↪3 + 10*11 + 5*11^2 + 9*11^3 + 4*11^4 + O(11^5), 3 + 11 + 5*11^2 + 4*11^4 + ↪
↪O(11^5))
```

```
sage: K = pAdicField(11,5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪16)
sage: P = C.lift_x(11^(-2))
sage: Q = C.lift_x(3*11^(-2))
sage: C.coleman_integrals_on_basis(P, Q)
(3*11^3 + 7*11^4 + 4*11^5 + 7*11^6 + 5*11^7 + O(11^8), 3*11 + 10*11^2 + 8*11^ ↪
↪3 + 9*11^4 + 7*11^5 + O(11^6), 4*11^-1 + 2 + 6*11 + 6*11^2 + 7*11^3 + O(11^ ↪
↪4), 11^-3 + 6*11^-2 + 2*11^-1 + 2 + O(11^2))
```

```
sage: R = C(0,1/4)
sage: a = C.coleman_integrals_on_basis(P,R) # long time (7s on sage.math, ↪
↪2011)
sage: b = C.coleman_integrals_on_basis(R,Q) # long time (9s on sage.math, ↪
↪2011)
sage: c = C.coleman_integrals_on_basis(P,Q) # long time
sage: a+b == c # long time
True
```

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
```

```

sage: HK = H.change_ring(K)
sage: S = HK(1, 0)
sage: P = HK(0, 3)
sage: T = HK(0, 1, 0)
sage: Q = HK.lift_x(5^-2)
sage: R = HK.lift_x(4*5^-2)
sage: HK.coleman_integrals_on_basis(S, P)
(2*5^2 + 5^4 + 5^5 + 3*5^6 + 3*5^7 + 2*5^8 + O(5^9), 5 + 2*5^2 + 4*5^3 + 2*5^4
↪ 4 + 3*5^6 + 4*5^7 + 2*5^8 + O(5^9))
sage: HK.coleman_integrals_on_basis(T, P)
(2*5^2 + 5^4 + 5^5 + 3*5^6 + 3*5^7 + 2*5^8 + O(5^9), 5 + 2*5^2 + 4*5^3 + 2*5^4
↪ 4 + 3*5^6 + 4*5^7 + 2*5^8 + O(5^9))
sage: HK.coleman_integrals_on_basis(P, S) == -HK.coleman_integrals_on_basis(S,
↪ P)
True
sage: HK.coleman_integrals_on_basis(S, Q)
(4*5 + 4*5^2 + 4*5^3 + O(5^4), 5^-1 + O(5^3))
sage: HK.coleman_integrals_on_basis(Q, R)
(4*5 + 2*5^2 + 2*5^3 + 2*5^4 + 5^5 + 5^6 + 5^7 + 3*5^8 + O(5^9), 2*5^-1 + 4 +
↪ 4*5 + 4*5^2 + 4*5^3 + 2*5^4 + 3*5^5 + 2*5^6 + O(5^7))
sage: HK.coleman_integrals_on_basis(S, R) == HK.coleman_integrals_on_basis(S,
↪ Q) + HK.coleman_integrals_on_basis(Q, R)
True
sage: HK.coleman_integrals_on_basis(T, T)
(0, 0)
sage: HK.coleman_integrals_on_basis(S, T)
(0, 0)

```

## AUTHORS:

- Robert Bradshaw (2007-03): non-Weierstrass points
- Jennifer Balakrishnan and Robert Bradshaw (2010-02): Weierstrass points

**coleman\_integrals\_on\_basis\_hyperelliptic** ( $P, Q, \text{algorithm=None}$ )

Computes the Coleman integrals  $\{\int_P^Q x^i dx/2y\}_{i=0}^{2g-1}$

## INPUT:

- $P$  point on self
- $Q$  point on self
- `algorithm` (optional) = None (uses Frobenius) or `teichmuller` (uses Teichmuller points)

## OUTPUT:

the Coleman integrals  $\{\int_P^Q x^i dx/2y\}_{i=0}^{2g-1}$

## EXAMPLES:

```

sage: K = pAdicField(11, 5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪ 16)
sage: P = C.lift_x(2)
sage: Q = C.lift_x(3)
sage: C.coleman_integrals_on_basis(P, Q)
(10*11 + 6*11^3 + 2*11^4 + O(11^5), 11 + 9*11^2 + 7*11^3 + 9*11^4 + O(11^5),
↪ 3 + 10*11 + 5*11^2 + 9*11^3 + 4*11^4 + O(11^5), 3 + 11 + 5*11^2 + 4*11^4 +
↪ O(11^5))

```

```
sage: C.coleman_integrals_on_basis(P, Q, algorithm='teichmuller')
(10*11 + 6*11^3 + 2*11^4 + O(11^5), 11 + 9*11^2 + 7*11^3 + 9*11^4 + O(11^5),
↪ 3 + 10*11 + 5*11^2 + 9*11^3 + 4*11^4 + O(11^5), 3 + 11 + 5*11^2 + 4*11^4 +
↪ O(11^5))
```

```
sage: K = pAdicField(11,5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪ 16)
sage: P = C.lift_x(11^(-2))
sage: Q = C.lift_x(3*11^(-2))
sage: C.coleman_integrals_on_basis(P, Q)
(3*11^3 + 7*11^4 + 4*11^5 + 7*11^6 + 5*11^7 + O(11^8), 3*11 + 10*11^2 + 8*11^
↪ 3 + 9*11^4 + 7*11^5 + O(11^6), 4*11^-1 + 2 + 6*11 + 6*11^2 + 7*11^3 + O(11^
↪ 4), 11^-3 + 6*11^-2 + 2*11^-1 + 2 + O(11^2))
```

```
sage: R = C(0,1/4)
sage: a = C.coleman_integrals_on_basis(P,R) # long time (7s on sage.math,
↪ 2011)
sage: b = C.coleman_integrals_on_basis(R,Q) # long time (9s on sage.math,
↪ 2011)
sage: c = C.coleman_integrals_on_basis(P,Q) # long time
sage: a+b == c # long time
True
```

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: S = HK(1,0)
sage: P = HK(0,3)
sage: T = HK(0,1,0)
sage: Q = HK.lift_x(5^-2)
sage: R = HK.lift_x(4*5^-2)
sage: HK.coleman_integrals_on_basis(S,P)
(2*5^2 + 5^4 + 5^5 + 3*5^6 + 3*5^7 + 2*5^8 + O(5^9), 5 + 2*5^2 + 4*5^3 + 2*5^
↪ 4 + 3*5^6 + 4*5^7 + 2*5^8 + O(5^9))
sage: HK.coleman_integrals_on_basis(T,P)
(2*5^2 + 5^4 + 5^5 + 3*5^6 + 3*5^7 + 2*5^8 + O(5^9), 5 + 2*5^2 + 4*5^3 + 2*5^
↪ 4 + 3*5^6 + 4*5^7 + 2*5^8 + O(5^9))
sage: HK.coleman_integrals_on_basis(P,S) == -HK.coleman_integrals_on_basis(S,
↪ P)
True
sage: HK.coleman_integrals_on_basis(S,Q)
(4*5 + 4*5^2 + 4*5^3 + O(5^4), 5^-1 + O(5^3))
sage: HK.coleman_integrals_on_basis(Q,R)
(4*5 + 2*5^2 + 2*5^3 + 2*5^4 + 5^5 + 5^6 + 5^7 + 3*5^8 + O(5^9), 2*5^-1 + 4 +
↪ 4*5 + 4*5^2 + 4*5^3 + 2*5^4 + 3*5^5 + 2*5^6 + O(5^7))
sage: HK.coleman_integrals_on_basis(S,R) == HK.coleman_integrals_on_basis(S,
↪ Q) + HK.coleman_integrals_on_basis(Q,R)
True
sage: HK.coleman_integrals_on_basis(T,T)
(0, 0)
sage: HK.coleman_integrals_on_basis(S,T)
(0, 0)
```

AUTHORS:

- Robert Bradshaw (2007-03): non-Weierstrass points
- Jennifer Balakrishnan and Robert Bradshaw (2010-02): Weierstrass points

**curve\_over\_ram\_extn**(deg)

Return self over  $\mathbf{Q}_p(p^{1/\text{deg}})$ .

INPUT:

- deg: the degree of the ramified extension

OUTPUT:

self over  $\mathbf{Q}_p(p^{1/\text{deg}})$

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^5-23*x^3+18*x^2+40*x)
sage: K = Qp(11,5)
sage: HK = H.change_ring(K)
sage: HL = HK.curve_over_ram_extn(2)
sage: HL
Hyperelliptic Curve over Eisenstein Extension in a defined by x^2 - 11 with
↳ capped relative precision 10 over 11-adic Field defined by (1 + O(a^10))*y^
↳ 2 = (1 + O(a^10))*x^5 + (10 + 8*a^2 + 10*a^4 + 10*a^6 + 10*a^8 + O(a^10))*x^
↳ 3 + (7 + a^2 + O(a^10))*x^2 + (7 + 3*a^2 + O(a^10))*x
```

AUTHOR:

- Jennifer Balakrishnan

**find\_char\_zero\_weier\_point**(Q)

Given  $Q$  a point on self in a Weierstrass disc, finds the center of the Weierstrass disc (if defined over self.base\_ring())

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: P = HK.lift_x(1 + 2*5^2)
sage: Q = HK.lift_x(5^-2)
sage: S = HK(1,0)
sage: T = HK(0,1,0)
sage: HK.find_char_zero_weier_point(P)
(1 + O(5^8) : 0 : 1 + O(5^8))
sage: HK.find_char_zero_weier_point(Q)
(0 : 1 + O(5^8) : 0)
sage: HK.find_char_zero_weier_point(S)
(1 + O(5^8) : 0 : 1 + O(5^8))
sage: HK.find_char_zero_weier_point(T)
(0 : 1 + O(5^8) : 0)
```

AUTHOR:

- Jennifer Balakrishnan

**frobenius**(P=None)

Returns the  $p$ -th power lift of Frobenius of  $P$

EXAMPLES:

```

sage: K = Qp(11, 5)
sage: R.<x> = K[]
sage: E = HyperellipticCurve(x^5 - 21*x - 20)
sage: P = E.lift_x(2)
sage: E.frobenius(P)
(2 + 10*11 + 5*11^2 + 11^3 + O(11^5) : 5 + 9*11 + 2*11^2 + 2*11^3 + O(11^5) :
↪ 1 + O(11^5))
sage: Q = E.teichmuller(P); Q
(2 + 10*11 + 4*11^2 + 9*11^3 + 11^4 + O(11^5) : 5 + 9*11 + 6*11^2 + 11^3 +
↪ 6*11^4 + O(11^5) : 1 + O(11^5))
sage: E.frobenius(Q)
(2 + 10*11 + 4*11^2 + 9*11^3 + 11^4 + O(11^5) : 5 + 9*11 + 6*11^2 + 11^3 +
↪ 6*11^4 + O(11^5) : 1 + O(11^5))

```

```

sage: R.<x> = QQ[]
sage: H = HyperellipticCurve(x^5-23*x^3+18*x^2+40*x)
sage: Q = H(0,0)
sage: u,v = H.local_coord(Q,prec=100)
sage: K = Qp(11,5)
sage: L.<a> = K.extension(x^20-11)
sage: HL = H.change_ring(L)
sage: S = HL(u(a),v(a))
sage: HL.frobenius(S)
(8*a^22 + 10*a^42 + 4*a^44 + 2*a^46 + 9*a^48 + 8*a^50 + a^52 + 7*a^54 +
7*a^56 + 5*a^58 + 9*a^62 + 5*a^64 + a^66 + 6*a^68 + a^70 + 6*a^74 +
2*a^76 + 2*a^78 + 4*a^82 + 5*a^84 + 2*a^86 + 7*a^88 + a^90 + 6*a^92 +
a^96 + 5*a^98 + 2*a^102 + 2*a^106 + 6*a^108 + 8*a^110 + 3*a^112 +
a^114 + 8*a^116 + 10*a^118 + 3*a^120 + O(a^122) :
a^11 + 7*a^33 + 7*a^35 + 4*a^37 + 6*a^39 + 9*a^41 + 8*a^43 + 8*a^45 +
a^47 + 7*a^51 + 4*a^53 + 5*a^55 + a^57 + 7*a^59 + 5*a^61 + 9*a^63 +
4*a^65 + 10*a^69 + 3*a^71 + 2*a^73 + 9*a^75 + 10*a^77 + 6*a^79 +
10*a^81 + 7*a^85 + a^87 + 4*a^89 + 8*a^91 + a^93 + 8*a^95 + 2*a^97 +
7*a^99 + a^101 + 3*a^103 + 6*a^105 + 7*a^107 + 4*a^109 + O(a^111) :
1 + O(a^100))

```

**AUTHORS:**

- Robert Bradshaw and Jennifer Balakrishnan (2010-02)

**get\_boundary\_point** (*curve\_over\_extn*, *P*)

Given self over an extension field, find a point in the disc of  $P$  near the boundary

**INPUT:**

- *curve\_over\_extn*: self over a totally ramified extension
- *P*: Weierstrass point

**OUTPUT:**

a point in the disc of  $P$  near the boundary

**EXAMPLES:**

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(3,6)
sage: HK = H.change_ring(K)
sage: P = HK(1,0)
sage: J.<a> = K.extension(x^30-3)

```

```

sage: HJ = H.change_ring(J)
sage: S = HK.get_boundary_point(HJ,P)
sage: S
(1 + 2*a^2 + 2*a^6 + 2*a^18 + a^32 + a^34 + a^36 + 2*a^38 + 2*a^40 + a^42 +
↪ 2*a^44 + a^48 + 2*a^50 + 2*a^52 + a^54 + a^56 + 2*a^60 + 2*a^62 + a^70 +
↪ 2*a^72 + a^76 + 2*a^78 + a^82 + a^88 + a^96 + 2*a^98 + 2*a^102 + a^104 +
↪ 2*a^106 + a^108 + 2*a^110 + a^112 + 2*a^116 + a^126 + 2*a^130 + 2*a^132 + a^
↪ 144 + 2*a^148 + 2*a^150 + a^152 + 2*a^154 + a^162 + a^164 + a^166 + a^168 +
↪ a^170 + a^176 + a^178 + O(a^180) : a + O(a^180) : 1 + O(a^180))

```

AUTHOR:

- Jennifer Balakrishnan

**is\_in\_weierstrass\_disc(*P*)**

Checks if *P* is in a Weierstrass disc

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: P = HK(0,3)
sage: HK.is_in_weierstrass_disc(P)
False
sage: Q = HK(0,1,0)
sage: HK.is_in_weierstrass_disc(Q)
True
sage: S = HK(1,0)
sage: HK.is_in_weierstrass_disc(S)
True
sage: T = HK.lift_x(1+3*5^2); T
(1 + 3*5^2 + O(5^8) : 2*5 + 4*5^3 + 3*5^4 + 5^5 + 3*5^6 + O(5^7) : 1 + O(5^8))
sage: HK.is_in_weierstrass_disc(T)
True

```

AUTHOR:

- Jennifer Balakrishnan (2010-02)

**is\_same\_disc(*P*, *Q*)**

Checks if *P*, *Q* are in same residue disc

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: P = HK.lift_x(1 + 2*5^2)
sage: Q = HK.lift_x(5^-2)
sage: S = HK(1,0)
sage: HK.is_same_disc(P,Q)
False
sage: HK.is_same_disc(P,S)
True
sage: HK.is_same_disc(Q,S)
False

```



**is\_weierstrass**( $P$ )

Checks if  $P$  is a Weierstrass point (i.e., fixed by the hyperelliptic involution)

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
sage: P = HK(0,3)
sage: HK.is_weierstrass(P)
False
sage: Q = HK(0,1,0)
sage: HK.is_weierstrass(Q)
True
sage: S = HK(1,0)
sage: HK.is_weierstrass(S)
True
sage: T = HK.lift_x(1+3*5^2); T
(1 + 3*5^2 + O(5^8) : 2*5 + 4*5^3 + 3*5^4 + 5^5 + 3*5^6 + O(5^7) : 1 + O(5^8))
sage: HK.is_weierstrass(T)
False
```

AUTHOR:

- Jennifer Balakrishnan (2010-02)

**local\_analytic\_interpolation**( $P, Q$ )

For points  $P, Q$  in the same residue disc, this constructs an interpolation from  $P$  to  $Q$  (in homogeneous coordinates) in a power series in the local parameter  $t$ , with precision equal to the  $p$ -adic precision of the underlying ring.

INPUT:

- $P$  and  $Q$  points on self in the same residue disc

OUTPUT:

Returns a point  $X(t) = (x(t) : y(t) : z(t))$  such that:

1.  $X(0) = P$  and  $X(1) = Q$  if  $P, Q$  are not in the infinite disc
2.  $X(P[0]^g/P[1]) = P$  and  $X(Q[0]^g/Q[1]) = Q$  if  $P, Q$  are in the infinite disc

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5,8)
sage: HK = H.change_ring(K)
```

A non-Weierstrass disc:

```
sage: P = HK(0,3)
sage: Q = HK(5, 3 + 3*5^2 + 2*5^3 + 3*5^4 + 2*5^5 + 2*5^6 + 3*5^7 + O(5^8))
sage: x,y,z, = HK.local_analytic_interpolation(P,Q)
sage: x(0) == P[0], x(1) == Q[0], y(0) == P[1], y.polynomial()(1) == Q[1]
(True, True, True, True)
```

A finite Weierstrass disc:

```

sage: P = HK.lift_x(1 + 2*5^2)
sage: Q = HK.lift_x(1 + 3*5^2)
sage: x,y,z = HK.local_analytic_interpolation(P,Q)
sage: x(0) == P[0], x.polynomial()(1) == Q[0], y(0) == P[1], y(1) == Q[1]
(True, True, True, True)

```

The infinite disc:

```

sage: P = HK.lift_x(5^-2)
sage: Q = HK.lift_x(4*5^-2)
sage: x,y,z = HK.local_analytic_interpolation(P,Q)
sage: x = x/z
sage: y = y/z
sage: x(P[0]/P[1]) == P[0]
True
sage: x(Q[0]/Q[1]) == Q[0]
True
sage: y(P[0]/P[1]) == P[1]
True
sage: y(Q[0]/Q[1]) == Q[1]
True

```

An error if points are not in the same disc:

```

sage: x,y,z = HK.local_analytic_interpolation(P, HK(1,0))
Traceback (most recent call last):
...
ValueError: (5^-2 + O(5^6) : 5^-3 + 4*5^2 + 5^3 + 3*5^4 + O(5^5) : 1 + O(5^
↪8)) and (1 + O(5^8) : 0 : 1 + O(5^8)) are not in the same residue disc

```

AUTHORS:

- Robert Bradshaw (2007-03)
- Jennifer Balakrishnan (2010-02)

**newton\_sqrt** (*f*, *x0*, *prec*)

Takes the square root of the power series *f* by Newton's method

NOTE:

this function should eventually be moved to *p*-adic power series ring

INPUT:

- *f* – power series with coefficients in  $\mathbb{Q}_p$  or an extension
- *x0* – seeds the Newton iteration
- *prec* – precision

OUTPUT: the square root of *f*

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^5-23*x^3+18*x^2+40*x)
sage: Q = H(0,0)
sage: u,v = H.local_coord(Q,prec=100)
sage: K = Qp(11,5)
sage: HK = H.change_ring(K)
sage: L.<a> = K.extension(x^20-11)

```

```

sage: HL = H.change_ring(L)
sage: S = HL(u(a), v(a))
sage: f = H.hyperelliptic_polynomials()[0]
sage: y = HK.newton_sqrt(f(u(a)^11), a^11, 5)
sage: y^2 - f(u(a)^11)
O(a^122)

```

AUTHOR:

- Jennifer Balakrishnan

**residue\_disc**( $P$ )

Gives the residue disc of  $P$

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: H = HyperellipticCurve(x^3-10*x+9)
sage: K = Qp(5, 8)
sage: HK = H.change_ring(K)
sage: P = HK.lift_x(1 + 2*5^2)
sage: HK.residue_disc(P)
(1 : 0 : 1)
sage: Q = HK(0, 3)
sage: HK.residue_disc(Q)
(0 : 3 : 1)
sage: S = HK.lift_x(5^-2)
sage: HK.residue_disc(S)
(0 : 1 : 0)
sage: T = HK(0, 1, 0)
sage: HK.residue_disc(T)
(0 : 1 : 0)

```

AUTHOR:

- Jennifer Balakrishnan

**teichmuller**( $P$ )

Find a Teichmüller point in the same residue class of  $P$ .

Because this lift of Frobenius acts as  $x \mapsto x^p$ , take the Teichmüller lift of  $x$  and then find a matching  $y$  from that.

EXAMPLES:

```

sage: K = pAdicField(7, 5)
sage: E = EllipticCurve(K, [-31/3, -2501/108]) # 11a
sage: P = E(K(14/3), K(11/2))
sage: E.frobenius(P) == P
False
sage: TP = E.teichmuller(P); TP
(0 : 2 + 3*7 + 3*7^2 + 3*7^4 + O(7^5) : 1 + O(7^5))
sage: E.frobenius(TP) == TP
True
sage: (TP[0] - P[0]).valuation() > 0, (TP[1] - P[1]).valuation() > 0
(True, True)

```

**tiny\_integrals**( $F, P, Q$ )

Evaluate the integrals of  $f_i dx/2y$  from  $P$  to  $Q$  for each  $f_i$  in  $F$  by formally integrating a power series in a local parameter  $t$

$P$  and  $Q$  MUST be in the same residue disc for this result to make sense.

INPUT:

- $F$  a list of functions  $f_i$
- $P$  a point on self
- $Q$  a point on self (in the same residue disc as  $P$ )

OUTPUT:

The integrals  $\int_P^Q f_i dx/2y$

EXAMPLES:

```
sage: K = pAdicField(17, 5)
sage: E = EllipticCurve(K, [-31/3, -2501/108]) # 11a
sage: P = E(K(14/3), K(11/2))
sage: TP = E.teichmuller(P);
sage: x,y = E.monsky_washnitzer_gens()
sage: E.tiny_integrals([1,x],P, TP) == E.tiny_integrals_on_basis(P,TP)
True
```

```
sage: K = pAdicField(11, 5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪16)
sage: P = C.lift_x(11^(-2))
sage: Q = C.lift_x(3*11^(-2))
sage: C.tiny_integrals([1],P,Q)
(3*11^3 + 7*11^4 + 4*11^5 + 7*11^6 + 5*11^7 + O(11^8))
```

Note that this fails if the points are not in the same residue disc:

```
sage: S = C(0,1/4)
sage: C.tiny_integrals([1,x,x^2,x^3],P,S)
Traceback (most recent call last):
...
ValueError: (11^-2 + O(11^3) : 11^-5 + 8*11^-2 + O(11^0) : 1 + O(11^5)) and
↪(0 : 3 + 8*11 + 2*11^2 + 8*11^3 + 2*11^4 + O(11^5) : 1 + O(11^5)) are not
↪in the same residue disc
```

**tiny\_integrals\_on\_basis** ( $P, Q$ )

Evaluate the integrals  $\{\int_P^Q x^i dx/2y\}_{i=0}^{2g-1}$  by formally integrating a power series in a local parameter  $t$ .  $P$  and  $Q$  MUST be in the same residue disc for this result to make sense.

INPUT:

- $P$  a point on self
- $Q$  a point on self (in the same residue disc as  $P$ )

OUTPUT:

The integrals  $\{\int_P^Q x^i dx/2y\}_{i=0}^{2g-1}$

EXAMPLES:

```
sage: K = pAdicField(17, 5)
sage: E = EllipticCurve(K, [-31/3, -2501/108]) # 11a
sage: P = E(K(14/3), K(11/2))
sage: TP = E.teichmuller(P);
```

```
sage: E.tiny_integrals_on_basis(P, TP)
(17 + 14*17^2 + 17^3 + 8*17^4 + O(17^5), 16*17 + 5*17^2 + 8*17^3 + 14*17^4 +
↪ O(17^5))
```

```
sage: K = pAdicField(11, 5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪ 16)
sage: P = C.lift_x(11^(-2))
sage: Q = C.lift_x(3*11^(-2))
sage: C.tiny_integrals_on_basis(P, Q)
(3*11^3 + 7*11^4 + 4*11^5 + 7*11^6 + 5*11^7 + O(11^8), 3*11 + 10*11^2 + 8*11^
↪ 3 + 9*11^4 + 7*11^5 + O(11^6), 4*11^-1 + 2 + 6*11 + 6*11^2 + 7*11^3 + O(11^
↪ 4), 11^-3 + 6*11^-2 + 2*11^-1 + 2 + O(11^2))
```

Note that this fails if the points are not in the same residue disc:

```
sage: S = C(0, 1/4)
sage: C.tiny_integrals_on_basis(P, S)
Traceback (most recent call last):
...
ValueError: (11^-2 + O(11^3) : 11^-5 + 8*11^-2 + O(11^0) : 1 + O(11^5)) and
↪ (0 : 3 + 8*11 + 2*11^2 + 8*11^3 + 2*11^4 + O(11^5) : 1 + O(11^5)) are not
↪ in the same residue disc
```

#### **weierstrass\_points()**

Return the Weierstrass points of self defined over self.base\_ring(), that is, the point at infinity and those points in the support of the divisor of  $y$

EXAMPLES:

```
sage: K = pAdicField(11, 5)
sage: x = polygen(K)
sage: C = HyperellipticCurve(x^5 + 33/16*x^4 + 3/4*x^3 + 3/8*x^2 - 1/4*x + 1/
↪ 16)
sage: C.weierstrass_points()
[(0 : 1 + O(11^5) : 0), (7 + 10*11 + 4*11^3 + O(11^5) : 0 : 1 + O(11^5))]
```

## 16.5 Hyperelliptic curves over the rationals

```
class sage.schemes.hyperelliptic_curves.hyperelliptic_rational_field.HyperellipticCurve_rat
```

Bases: `sage.schemes.hyperelliptic_curves.hyperelliptic_generic.HyperellipticCurve_generic`

**matrix\_of\_frobenius**( $p$ ,  $prec=20$ )

## 16.6 Mestre's algorithm

This file contains functions that:

- create hyperelliptic curves from the Igusa-Clebsch invariants (over  $\mathbb{Q}$  and finite fields)
- create Mestre's conic from the Igusa-Clebsch invariants

AUTHORS:

- Florian Bouyer
- Marco Streng

```
sage.schemes.hyperelliptic_curves.mestre.HyperellipticCurve_from_invariants(i,
                                                                              re-
                                                                              duced=True,
                                                                              pre-
                                                                              ci-
                                                                              sion=None,
                                                                              al-
                                                                              go-
                                                                              rithm='default')
```

Returns a hyperelliptic curve with the given Igusa-Clebsch invariants up to scaling.

The output is a curve over the field in which the Igusa-Clebsch invariants are given. The output curve is unique up to isomorphism over the algebraic closure. If no such curve exists over the given field, then raise a `ValueError`.

INPUT:

- `i` - list or tuple of length 4 containing the four Igusa-Clebsch invariants:  $I_2, I_4, I_6, I_{10}$ .
- `reduced` - Boolean (default = `True`) If `True`, tries to reduce the polynomial defining the hyperelliptic curve using the function `reduce_polynomial()` (see the `reduce_polynomial()` documentation for more details).
- `precision` - integer (default = `None`) Which precision for real and complex numbers should the reduction use. This only affects the reduction, not the correctness. If `None`, the algorithm uses the default 53 bit precision.
- `algorithm` - 'default' or 'magma'. If set to 'magma', uses Magma to parameterize Mestre's conic (needs Magma to be installed).

OUTPUT:

A hyperelliptic curve object.

EXAMPLES:

Examples over the rationals:

```
sage: HyperellipticCurve_from_invariants([3840, 414720, 491028480, 2437709561856])
Traceback (most recent call last):
...
NotImplementedError: Reduction of hyperelliptic curves not yet implemented. See
↳ trac #14755 and #14756.
sage: HyperellipticCurve_from_invariants([3840, 414720, 491028480, 2437709561856],
↳ reduced = False)
Hyperelliptic Curve over Rational Field defined by y^2 = -46656*x^6 + 46656*x^5 -
↳ 19440*x^4 + 4320*x^3 - 540*x^2 + 4410*x - 1
sage: HyperellipticCurve_from_invariants([21, 225/64, 22941/512, 1])
Traceback (most recent call last):
...
NotImplementedError: Reduction of hyperelliptic curves not yet implemented. See
↳ trac #14755 and #14756.
```

An example over a finite field:

```
sage: HyperellipticCurve_from_invariants([GF(13)(1), 3, 7, 5])
Hyperelliptic Curve over Finite Field of size 13 defined by  $y^2 = 8x^5 + 5x^4 + 5x^2 + 9x + 3$ 
```

An example over a number field:

```
sage: K = QuadraticField(353, 'a')
sage: H = HyperellipticCurve_from_invariants([21, 225/64, 22941/512, 1], reduced_
↳= false)
sage: f = K['x'](H.hyperelliptic_polynomials()[0])
```

If the Mestre Conic defined by the Igusa-Clebsch invariants has no rational points, then there exists no hyperelliptic curve over the base field with the given invariants.:

```
sage: HyperellipticCurve_from_invariants([1, 2, 3, 4])
Traceback (most recent call last):
...
ValueError: No such curve exists over Rational Field as there are no rational_
↳points on Projective Conic Curve over Rational Field defined by  $-2572155000u^2v - 317736000u^2w + 1250755459200v^2 + 2501510918400uw + 39276887040vw + 2736219686912w^2$ 
```

Mestre's algorithm only works for generic curves of genus two, so another algorithm is needed for those curves with extra automorphism. See also [trac ticket #12199](#):

```
sage: P.<x> = QQ[]
sage: C = HyperellipticCurve(x^6+1)
sage: i = C.igusa_clebsch_invariants()
sage: HyperellipticCurve_from_invariants(i)
Traceback (most recent call last):
...
TypeError: F (=0) must have degree 2
```

Igusa-Clebsch invariants also only work over fields of characteristic different from 2, 3, and 5, so another algorithm will be needed for fields of those characteristics. See also [trac ticket #12200](#):

```
sage: P.<x> = GF(3)[]
sage: HyperellipticCurve(x^6+x+1).igusa_clebsch_invariants()
Traceback (most recent call last):
...
NotImplementedError: Invariants of binary sextics/genus 2 hyperelliptic curves_
↳not implemented in characteristics 2, 3, and 5
sage: HyperellipticCurve_from_invariants([GF(5)(1), 1, 0, 1])
Traceback (most recent call last):
...
ZeroDivisionError: Inverse does not exist.
```

#### ALGORITHM:

This is Mestre's algorithm [\[M1991\]](#). Our implementation is based on the formulae on page 957 of [\[LY2001\]](#), cross-referenced with [\[W1999\]](#) to correct typos.

First construct Mestre's conic using the `Mestre_conic()` function. Parametrize the conic if possible. Let  $f_1, f_2, f_3$  be the three coordinates of the parametrization of the conic by the projective line, and change them into one variable by letting  $F_i = f_i(t, 1)$ . Note that each  $F_i$  has degree at most 2.

Then construct a sextic polynomial  $f = \sum_{0 \leq i, j, k \leq 3} c_{ijk} * F_i * F_j * F_k$ , where  $c_{ijk}$  are defined as rational functions in the invariants (see the source code for detailed formulae for  $c_{ijk}$ ). The output is the hyperelliptic

curve  $y^2 = f$ .

#### REFERENCES:

`sage.schemes.hyperelliptic_curves.mestre.Mestre_conic(i, xyz=False, names='u, v, w')`

Return the conic equation from Mestre's algorithm given the Igusa-Clebsch invariants.

It has a rational point if and only if a hyperelliptic curve corresponding to the invariants exists.

#### INPUT:

- `i` - list or tuple of length 4 containing the four Igusa-Clebsch invariants: I2, I4, I6, I10
- `xyz` - Boolean (default: False) if True, the algorithm also returns three invariants x,y,z used in Mestre's algorithm
- `names` (default: 'u,v,w') - the variable names for the Conic

#### OUTPUT:

A Conic object

#### EXAMPLES:

A standard example:

```
sage: Mestre_conic([1,2,3,4])
Projective Conic Curve over Rational Field defined by -2572155000*u^2 -
↪ 317736000*u*v + 1250755459200*v^2 + 2501510918400*u*w + 39276887040*v*w +
↪ 2736219686912*w^2
```

Note that the algorithm works over number fields as well:

```
sage: k = NumberField(x^2-41, 'a')
sage: a = k.an_element()
sage: Mestre_conic([1,2+a,a,4+a])
Projective Conic Curve over Number Field in a with defining polynomial x^2 - 41
↪ defined by (-801900000*a + 343845000)*u^2 + (855360000*a + 15795864000)*u*v +
↪ (312292800000*a + 1284808579200)*v^2 + (624585600000*a + 2569617158400)*u*w +
↪ (15799910400*a + 234573143040)*v*w + (2034199306240*a + 16429854656512)*w^2
```

And over finite fields:

```
sage: Mestre_conic([GF(7)(10), GF(7)(1), GF(7)(2), GF(7)(3)])
Projective Conic Curve over Finite Field of size 7 defined by -2*u*v - v^2 -
↪ 2*u*w + 2*v*w - 3*w^2
```

An example with xyz:

```
sage: Mestre_conic([5,6,7,8], xyz=True)
(Projective Conic Curve over Rational Field defined by -415125000*u^2 +
↪ 608040000*u*v + 33065136000*v^2 + 66130272000*u*w + 240829440*v*w +
↪ 10208835584*w^2, 232/1125, -1072/16875, 14695616/2109375)
```

#### ALGORITHM:

The formulas are taken from pages 956 - 957 of [LY2001] and based on pages 321 and 332 of [M1991].

See the code or [LY2001] for the detailed formulae defining x, y, z and L.



## 16.7 Computation of Frobenius matrix on Monsky-Washnitzer cohomology

The most interesting functions to be exported here are `matrix_of_frobenius()` and `adjusted_prec()`.

Currently this code is limited to the case  $p \geq 5$  (no  $GF(p^n)$  for  $n > 1$ ), and only handles the elliptic curve case (not more general hyperelliptic curves).

REFERENCES:

AUTHORS:

- David Harvey and Robert Bradshaw: initial code developed at the 2006 MSRI graduate workshop, working with Jennifer Balakrishnan and Liang Xiao
- David Harvey (2006-08): cleaned up, rewrote some chunks, lots more documentation, added Newton iteration method, added more complete ‘trace trick’, integrated better into Sage.
- David Harvey (2007-02): added algorithm with  $\sqrt{p}$  complexity (removed in May 2007 due to better C++ implementation)
- Robert Bradshaw (2007-03): keep track of exact form in reduction algorithms
- Robert Bradshaw (2007-04): generalization to hyperelliptic curves
- Julian Rueth (2014-05-09): improved caching

**class** `sage.schemes.hyperelliptic_curves.monsky_washnitzer.MonskyWashnitzerDifferential` (parent=`val=`  
offset=`off-`  
set=`set=`

Bases: `sage.structure.element.ModuleElement`

Create an element of the Monsky-Washnitzer ring of differentials, of the form  $Fdx/2y$ .

INPUT:

- `parent` – Monsky-Washnitzer differential ring (instance of class `MonskyWashnitzerDifferentialRing`)
- `val` – element of the base ring, or list of coefficients
- `offset` – if non-zero, shift `val` by  $y^{\text{offset}}$  (default 0)

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5 - 4*x + 4)
sage: x,y = C.monsky_washnitzer_gens()
sage: MW = C.invariant_differential().parent()
sage: sage.schemes.hyperelliptic_curves.monsky_washnitzer.
↳MonskyWashnitzerDifferential(MW, x)
x dx/2y
sage: sage.schemes.hyperelliptic_curves.monsky_washnitzer.
↳MonskyWashnitzerDifferential(MW, y)
y*1 dx/2y
sage: sage.schemes.hyperelliptic_curves.monsky_washnitzer.
↳MonskyWashnitzerDifferential(MW, x, 10)
y^10*x dx/2y
```

**coeff()**

Returns  $A$ , where this element is  $Adx/2y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: x,y = C.monsky_washnitzer_gens()
sage: w = C.invariant_differential()
sage: w
1 dx/2y
sage: w.coeff()
1
sage: (x*y*w).coeff()
y*x
```

**coeffs** (*R=None*)

Used to obtain the raw coefficients of a differential, see *SpecialHyperellipticQuotientElement.coeffs()*

INPUT:

- *R* – An (optional) base ring in which to cast the coefficients

OUTPUT:

The raw coefficients of *A* where self is  $Adx/2y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: x,y = C.monsky_washnitzer_gens()
sage: w = C.invariant_differential()
sage: w.coeffs()
[(1, 0, 0, 0, 0), 0]
sage: (x*w).coeffs()
[(0, 1, 0, 0, 0), 0]
sage: (y*w).coeffs()
[(0, 0, 0, 0, 0), (1, 0, 0, 0, 0), 0]
sage: (y^-2*w).coeffs()
[(1, 0, 0, 0, 0), (0, 0, 0, 0, 0), (0, 0, 0, 0, 0)], -2]
```

**coleman\_integral** (*P, Q*)

Computes the definite integral of self from *P* to *Q*.

INPUT:

- *P, Q* – Two points on the underlying curve

OUTPUT:

$\int_P^Q \text{self}$

EXAMPLES:

```
sage: K = pAdicField(5,7)
sage: E = EllipticCurve(K, [-31/3, -2501/108]) #11a
sage: P = E(K(14/3), K(11/2))
sage: w = E.invariant_differential()
sage: w.coleman_integral(P, 2*P)
O(5^6)

sage: Q = E([3, 58332])
sage: w.coleman_integral(P, Q)
```

```

2*5 + 4*5^2 + 3*5^3 + 4*5^4 + 3*5^5 + O(5^6)
sage: w.coleman_integral(2*P,Q)
2*5 + 4*5^2 + 3*5^3 + 4*5^4 + 3*5^5 + O(5^6)
sage: (2*w).colemant_integral(P, Q) == 2*(w.coleman_integral(P, Q))
True

```

**extract\_pow\_y(k)**

Returns the power of  $y$  in  $A$  where self is  $A dx/2y$ .

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-3*x+1)
sage: x,y = C.monsky_washnitzer_gens()
sage: A = y^5 - x*y^3
sage: A.extract_pow_y(5)
[1, 0, 0, 0, 0]
sage: (A * C.invariant_differential()).extract_pow_y(5)
[1, 0, 0, 0, 0]

```

**integrate(P, Q)**

Computes the definite integral of self from  $P$  to  $Q$ .

INPUT:

- $P, Q$  – Two points on the underlying curve

OUTPUT:

$$\int_P^Q \text{self}$$

EXAMPLES:

```

sage: K = pAdicField(5,7)
sage: E = EllipticCurve(K, [-31/3, -2501/108]) #11a
sage: P = E(K(14/3), K(11/2))
sage: w = E.invariant_differential()
sage: w.coleman_integral(P, 2*P)
O(5^6)

sage: Q = E([3, 58332])
sage: w.coleman_integral(P, Q)
2*5 + 4*5^2 + 3*5^3 + 4*5^4 + 3*5^5 + O(5^6)
sage: w.coleman_integral(2*P, Q)
2*5 + 4*5^2 + 3*5^3 + 4*5^4 + 3*5^5 + O(5^6)
sage: (2*w).colemant_integral(P, Q) == 2*(w.coleman_integral(P, Q))
True

```

**max\_pow\_y()**

Returns the maximum power of  $y$  in  $A$  where self is  $A dx/2y$ .

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-3*x+1)
sage: x,y = C.monsky_washnitzer_gens()
sage: w = y^5 * C.invariant_differential()
sage: w.max_pow_y()
5
sage: w = (x^2*y^4 + y^5) * C.invariant_differential()

```

```
sage: w.max_pow_y()
5
```

**min\_pow\_y()**

Returns the minimum power of  $y$  in  $A$  where self is  $Adx/2y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-3*x+1)
sage: x,y = C.monsky_washnitzer_gens()
sage: w = y^5 * C.invariant_differential()
sage: w.min_pow_y()
5
sage: w = (x^2*y^4 + y^5) * C.invariant_differential()
sage: w.min_pow_y()
4
```

**reduce()**

Use homology relations to find  $a$  and  $f$  such that this element is equal to  $a + df$ , where  $a$  is given in terms of the  $x^i dx/2y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: x,y = C.monsky_washnitzer_gens()
sage: w = (y*x).diff()
sage: w.reduce()
(y*x, 0 dx/2y)

sage: w = x^4 * C.invariant_differential()
sage: w.reduce()
(1/5*y*1, 4/5*1 dx/2y)

sage: w = sum(QQ.random_element() * x^i * y^j for i in [0..4] for j in [-3..
↪ 3]) * C.invariant_differential()
sage: f, a = w.reduce()
sage: f.diff() + a - w
0 dx/2y
```

**reduce\_fast** (*even\_degree\_only=False*)

Use homology relations to find  $a$  and  $f$  such that this element is equal to  $a + df$ , where  $a$  is given in terms of the  $x^i dx/2y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^3-4*x+4)
sage: x, y = E.monsky_washnitzer_gens()
sage: x.diff().reduce_fast()
(x, (0, 0))
sage: y.diff().reduce_fast()
(y*1, (0, 0))
sage: (y^-1).diff().reduce_fast()
((y^-1)*1, (0, 0))
sage: (y^-11).diff().reduce_fast()
((y^-11)*1, (0, 0))
```

```
sage: (x*y^2).diff().reduce_fast()
(y^2*x, (0, 0))
```

**reduce\_neg\_y()**

Use homology relations to eliminate negative powers of  $y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-3*x+1)
sage: x,y = C.monsky_washnitzer_gens()
sage: (y^-1).diff().reduce_neg_y()
((y^-1)*1, 0 dx/2y)
sage: (y^-5*x^2+y^-1*x).diff().reduce_neg_y()
((y^-1)*x + (y^-5)*x^2, 0 dx/2y)
```

**reduce\_neg\_y\_fast** (*even\_degree\_only=False*)

Use homology relations to eliminate negative powers of  $y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x, y = E.monsky_washnitzer_gens()
sage: (y^-1).diff().reduce_neg_y_fast()
((y^-1)*1, 0 dx/2y)
sage: (y^-5*x^2+y^-1*x).diff().reduce_neg_y_fast()
((y^-1)*x + (y^-5)*x^2, 0 dx/2y)
```

It leaves non-negative powers of  $y$  alone:

```
sage: y.diff()
(-3*1 + 5*x^4) dx/2y
sage: y.diff().reduce_neg_y_fast()
(0, (-3*1 + 5*x^4) dx/2y)
```

**reduce\_neg\_y\_faster** (*even\_degree\_only=False*)

Use homology relations to eliminate negative powers of  $y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-3*x+1)
sage: x,y = C.monsky_washnitzer_gens()
sage: (y^-1).diff().reduce_neg_y()
((y^-1)*1, 0 dx/2y)
sage: (y^-5*x^2+y^-1*x).diff().reduce_neg_y_faster()
((y^-1)*x + (y^-5)*x^2, 0 dx/2y)
```

**reduce\_pos\_y()**

Use homology relations to eliminate positive powers of  $y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^3-4*x+4)
sage: x,y = C.monsky_washnitzer_gens()
sage: (y^2).diff().reduce_pos_y()
(y^2*1, 0 dx/2y)
```

```

sage: (y^2*x).diff().reduce_pos_y()
(y^2*x, 0 dx/2y)
sage: (y^92*x).diff().reduce_pos_y()
(y^92*x, 0 dx/2y)
sage: w = (y^3 + x).diff()
sage: w += w.parent()(x)
sage: w.reduce_pos_y_fast()
(y^3+1 + x, x dx/2y)

```

**reduce\_pos\_y\_fast** (*even\_degree\_only=False*)

Use homology relations to eliminate positive powers of  $y$ .

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^3-4*x+4)
sage: x, y = E.monsky_washnitzer_gens()
sage: y.diff().reduce_pos_y_fast()
(y*1, 0 dx/2y)
sage: (y^2).diff().reduce_pos_y_fast()
(y^2+1, 0 dx/2y)
sage: (y^2*x).diff().reduce_pos_y_fast()
(y^2*x, 0 dx/2y)
sage: (y^92*x).diff().reduce_pos_y_fast()
(y^92*x, 0 dx/2y)
sage: w = (y^3 + x).diff()
sage: w += w.parent()(x)
sage: w.reduce_pos_y_fast()
(y^3+1 + x, x dx/2y)

```

**class** sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**MonskyWashnitzerDifferentialRing**  
 Bases: sage.structure.unique\_representation.UniqueRepresentation, sage.modules.module.Module

A ring of Monsky–Washnitzer differentials over `base_ring`.

**Q()**

Returns  $Q(x)$  where the model of the underlying hyperelliptic curve of self is given by  $y^2 = Q(x)$ .

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.Q()
x^5 - 4*x + 4

```

**base\_extend(R)**

Return a new differential ring which is self base-extended to  $R$

INPUT:

- $R$  – ring

OUTPUT:

Self, base-extended to  $R$ .

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.base_ring()
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = x^5 - 4*x + 4) over
↳Rational Field
sage: MW.base_extend(Qp(5,5)).base_ring()
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = (1 + O(5^5))*x^5 + (1 +
↳4*5 + 4*5^2 + 4*5^3 + 4*5^4 + O(5^5))*x + (4 + O(5^5))) over 5-adic Field
↳with capped relative precision 5

```

**change\_ring(*R*)**

Returns a new differential ring which is self with the coefficient ring changed to *R*.

INPUT:

- *R* – ring of coefficients

OUTPUT:

Self, with the coefficient ring changed to *R*.

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.base_ring()
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = x^5 - 4*x + 4) over
↳Rational Field
sage: MW.change_ring(Qp(5,5)).base_ring()
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = (1 + O(5^5))*x^5 + (1 +
↳4*5 + 4*5^2 + 4*5^3 + 4*5^4 + O(5^5))*x + (4 + O(5^5))) over 5-adic Field
↳with capped relative precision 5

```

**degree()**

Returns the degree of  $Q(x)$ , where the model of the underlying hyperelliptic curve of self is given by  $y^2 = Q(x)$ .

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.Q()
x^5 - 4*x + 4
sage: MW.degree()
5

```

**dimension()**

Returns the dimension of self.

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: K = Qp(7,5)
sage: CK = C.change_ring(K)
sage: MW = CK.invariant_differential().parent()

```

```
sage: MW.dimension()
4
```

**frob\_Q(p)**

Returns and caches  $Q(x^p)$ , which is used in computing the image of  $y$  under a  $p$ -power lift of Frobenius to  $A^\dagger$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.frob_Q(3)
-(60-48*y^2+12*y^4-y^6)*1 + (192-96*y^2+12*y^4)*x - (192-48*y^2)*x^2 + 60*x^3
sage: MW.Q()(MW.x_to_p(3))
-(60-48*y^2+12*y^4-y^6)*1 + (192-96*y^2+12*y^4)*x - (192-48*y^2)*x^2 + 60*x^3
sage: MW.frob_Q(11) is MW.frob_Q(11)
True
```

**frob\_basis\_elements(prec, p)**

Returns the action of a  $p$ -power lift of Frobenius on the basis

$$\{dx/2y, xdx/2y, \dots, x^{d-2}dx/2y\}$$

where  $d$  is the degree of the underlying hyperelliptic curve.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: prec = 1
sage: p = 5
sage: MW = C.invariant_differential().parent()
sage: MW.frob_basis_elements(prec, p)
[ ((92000*y^-14-74200*y^-12+32000*y^-10-8000*y^-8+1000*y^-6-50*y^-4)*1 -
↳ (194400*y^-14-153600*y^-12+57600*y^-10-9600*y^-8+600*y^-6)*x + (204800*y^-
↳ 14-153600*y^-12+38400*y^-10-3200*y^-8)*x^2 - (153600*y^-14-76800*y^-
↳ 12+9600*y^-10)*x^3 + (63950*y^-14-18550*y^-12+1600*y^-10-400*y^-8+50*y^-
↳ 6+5*y^-4)*x^4) dx/2y, (- (1391200*y^-14-941400*y^-12+302000*y^-10-76800*y^-
↳ 8+14400*y^-6-1320*y^-4+30*y^-2)*1 + (2168800*y^-14-1402400*y^-12+537600*y^-
↳ 10-134400*y^-8+16800*y^-6-720*y^-4)*x - (1596800*y^-14-1433600*y^-
↳ 12+537600*y^-10-89600*y^-8+5600*y^-6)*x^2 + (1433600*y^-14-1075200*y^-
↳ 12+268800*y^-10-22400*y^-8)*x^3 - (870200*y^-14-445350*y^-12+63350*y^-10-
↳ 3200*y^-8+600*y^-6-30*y^-4-5*y^-2)*x^4) dx/2y, ((19488000*y^-14-15763200*y^-
↳ 12+4944400*y^-10-913800*y^-8+156800*y^-6-22560*y^-4+1480*y^-2-10)*1 -
↳ (28163200*y^-14-18669600*y^-12+5774400*y^-10-1433600*y^-8+268800*y^-6-
↳ 25440*y^-4+760*y^-2)*x + (15062400*y^-14-12940800*y^-12+5734400*y^-10-
↳ 1433600*y^-8+179200*y^-6-8480*y^-4)*x^2 - (12121600*y^-14-11468800*y^-
↳ 12+4300800*y^-10-716800*y^-8+44800*y^-6)*x^3 + (9215200*y^-14-6952400*y^-
↳ 12+1773950*y^-10-165750*y^-8+5600*y^-6-720*y^-4+10*y^-2+5)*x^4) dx/2y, (-
↳ (225395200*y^-14-230640000*y^-12+91733600*y^-10-18347400*y^-8+2293600*y^-6-
↳ 280960*y^-4+31520*y^-2-1480-10*y^2)*1 + (338048000*y^-14-277132800*y^-
↳ 12+89928000*y^-10-17816000*y^-8+3225600*y^-6-472320*y^-4+34560*y^-2-720)*x -
↳ (172902400*y^-14-141504000*y^-12+58976000*y^-10-17203200*y^-8+3225600*y^-6-
↳ 314880*y^-4+11520*y^-2)*x^2 + (108736000*y^-14-109760000*y^-12+51609600*y^-
↳ 10-12902400*y^-8+1612800*y^-6-78720*y^-4)*x^3 - (85347200*y^-14-82900000*y^-
↳ 12+31251400*y^-10-5304150*y^-8+367350*y^-6-8480*y^-4+760*y^-2+10-5*y^2)*x^
↳ 4) dx/2y]
```



**frob\_invariant\_differential** (*prec*, *p*)

Kedlaya's algorithm allows us to calculate the action of Frobenius on the Monsky-Washnitzer cohomology. First we lift  $\phi$  to  $A^\dagger$  by setting

$$\phi(x) = x^p$$

$$\phi(y) = y^p \sqrt{1 + \frac{Q(x^p) - Q(x)^p}{Q(x)^p}}.$$

Pulling back the differential  $dx/2y$ , we get

$$\phi^*(dx/2y) = px^{p-1}y(\phi(y))^{-1}dx/2y = px^{p-1}y^{1-p}\sqrt{1 + \frac{Q(x^p) - Q(x)^p}{Q(x)^p}}dx/2y$$

Use Newton's method to calculate the square root.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: prec = 2
sage: p = 7
sage: MW = C.invariant_differential().parent()
sage: MW.frob_invariant_differential(prec,p)
((67894400*y^-20-81198880*y^-18+40140800*y^-16-10035200*y^-14+1254400*y^-12-
↪ 62720*y^-10)*1 - (119503944*y^-20-116064242*y^-18+43753472*y^-16-7426048*y^-
↪ 14+514304*y^-12-12544*y^-10+1568*y^-8-70*y^-6-7*y^-4)*x + (78905288*y^-20-
↪ 61014016*y^-18+16859136*y^-16-2207744*y^-14+250880*y^-12-37632*y^-10+3136*y^-
↪ 8-70*y^-6)*x^2 - (39452448*y^-20-26148752*y^-18+8085490*y^-16-2007040*y^-
↪ 14+376320*y^-12-37632*y^-10+1568*y^-8)*x^3 + (21102144*y^-20-18120592*y^-
↪ 18+8028160*y^-16-2007040*y^-14+250880*y^-12-12544*y^-10)*x^4) dx/2y
```

**helper\_matrix** ()

We use this to solve for the linear combination of  $x^i y^j$  needed to clear all terms with  $y^{j-1}$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.helper_matrix()
[ 256/2101  320/2101  400/2101  500/2101  625/2101]
[-625/8404  -64/2101  -80/2101 -100/2101 -125/2101]
[-125/2101 -625/8404  -64/2101  -80/2101 -100/2101]
[-100/2101 -125/2101 -625/8404  -64/2101  -80/2101]
[ -80/2101 -100/2101 -125/2101 -625/8404  -64/2101]
```

**invariant\_differential** ()

Returns  $dx/2y$  as an element of self.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.invariant_differential()
1 dx/2y
```

**x\_to\_p**( $p$ )

Returns and caches  $x^p$ , reduced via the relations coming from the defining polynomial of the hyperelliptic curve.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: C = HyperellipticCurve(x^5-4*x+4)
sage: MW = C.invariant_differential().parent()
sage: MW.x_to_p(3)
x^3
sage: MW.x_to_p(5)
-(4-y^2)*1 + 4*x
sage: MW.x_to_p(101) is MW.x_to_p(101)
True
```

sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**MonskyWashnitzerDifferentialRing\_class**  
alias of *MonskyWashnitzerDifferentialRing*

**class** sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**SpecialCubicQuotientRing**( $Q$ ,  
*lau-*  
*rent\_series*

Bases: sage.rings.ring.CommutativeAlgebra

Specialised class for representing the quotient ring  $R[x, T]/(T - x^3 - ax - b)$ , where  $R$  is an arbitrary commutative base ring (in which 2 and 3 are invertible),  $a$  and  $b$  are elements of that ring.

Polynomials are represented internally in the form  $p_0 + p_1x + p_2x^2$  where the  $p_i$  are polynomials in  $T$ . Multiplication of polynomials always reduces high powers of  $x$  (i.e. beyond  $x^2$ ) to powers of  $T$ .

Hopefully this ring is faster than a general quotient ring because it uses the special structure of this ring to speed multiplication (which is the dominant operation in the frobenius matrix calculation). I haven't actually tested this theory though...

**Todo:** Eventually we will want to run this in characteristic 3, so we need to: (a) Allow  $Q(x)$  to contain an  $x^2$  term, and (b) Remove the requirement that 3 be invertible. Currently this is used in the Toom-Cook algorithm to speed multiplication.

EXAMPLES:

```
sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: R
SpecialCubicQuotientRing over Ring of integers modulo 125 with polynomial T = x^3_
↪+ 124*x + 94
```

Get generators:

```
sage: x, T = R.gens()
sage: x
(0) + (1)*x + (0)*x^2
sage: T
(T) + (0)*x + (0)*x^2
```

Coercions:

```
sage: R(7)
(7) + (0)*x + (0)*x^2
```

Create elements directly from polynomials:

```
sage: A = R.poly_ring()
sage: A
Univariate Polynomial Ring in T over Ring of integers modulo 125
sage: z = A.gen()
sage: R.create_element(z^2, z+1, 3)
(T^2) + (T + 1)*x + (3)*x^2
```

Some arithmetic:

```
sage: x^3
(T + 31) + (1)*x + (0)*x^2
sage: 3 * x**15 * T**2 + x - T
(3*T^7 + 90*T^6 + 110*T^5 + 20*T^4 + 58*T^3 + 26*T^2 + 124*T) + (15*T^6 + 110*T^5 +
↪ 35*T^4 + 63*T^2 + 1)*x + (30*T^5 + 40*T^4 + 8*T^3 + 38*T^2)*x^2
```

Retrieve coefficients (output is zero-padded):

```
sage: x^10
(3*T^2 + 61*T + 8) + (T^3 + 93*T^2 + 12*T + 40)*x + (3*T^2 + 61*T + 9)*x^2
sage: (x^10).coeffs()
[[8, 61, 3, 0], [40, 12, 93, 1], [9, 61, 3, 0]]
```

**Todo:** write an example checking multiplication of these polynomials against Sage's ordinary quotient ring arithmetic. I can't seem to get the quotient ring stuff happening right now...

**create\_element** ( $p_0, p_1, p_2, \text{check}=\text{True}$ )

Creates the element  $p_0 + p_1 * x + p_2 * x^2$ , where the  $p_i$  are polynomials in  $T$ .

INPUT:

- **p0, p1, p2** – coefficients; must be coercible into `poly_ring()`
- **check** – bool (default `True`): whether to carry out coercion

EXAMPLES:

```
sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: A, z = R.poly_ring().objgen()
sage: R.create_element(z^2, z+1, 3)
(T^2) + (T + 1)*x + (3)*x^2
```

**gens** ()

Return a list  $[x, T]$  where  $x$  and  $T$  are the generators of the ring (as element *of this ring*).

**Note:** I have no idea if this is compatible with the usual Sage 'gens' interface.

EXAMPLES:

```
sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: x, T = R.gens()
sage: x
(0) + (1)*x + (0)*x^2
```

```
sage: T
(T) + (0)*x + (0)*x^2
```

**poly\_ring()**

Return the underlying polynomial ring in  $T$ .

EXAMPLES:

```
sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: R.poly_ring()
Univariate Polynomial Ring in T over Ring of integers modulo 125
```

**class** sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**SpecialCubicQuotientRingElement** (*p*)

Bases: sage.structure.element.CommutativeAlgebraElement

An element of a SpecialCubicQuotientRing.

**coeffs()**

Returns list of three lists of coefficients, corresponding to the  $x^0$ ,  $x^1$ ,  $x^2$  coefficients. The lists are zero padded to the same length. The list entries belong to the base ring.

EXAMPLES:

```
sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: p = R.create_element(t, t^2 - 2, 3)
sage: p.coeffs()
[[0, 1, 0], [123, 0, 1], [3, 0, 0]]
```

**scalar\_multiply**(*scalar*)

Multiplies this element by a scalar, i.e. just multiply each coefficient of  $x^j$  by the scalar.

INPUT:

- **scalar** – either an element of `base_ring`, or an element of `poly_ring`.

EXAMPLES:

```
sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: x, T = R.gens()
sage: f = R.create_element(2, t, t^2 - 3)
sage: f
(2) + (T)*x + (T^2 + 122)*x^2
sage: f.scalar_multiply(2)
(4) + (2*T)*x + (2*T^2 + 119)*x^2
sage: f.scalar_multiply(t)
(2*T) + (T^2)*x + (T^3 + 122*T)*x^2
```

**shift**(*n*)

Returns this element multiplied by  $T^n$ .

EXAMPLES:

```

sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: f = R.create_element(2, t, t^2 - 3)
sage: f
(2) + (T)*x + (T^2 + 122)*x^2
sage: f.shift(1)
(2*T) + (T^2)*x + (T^3 + 122*T)*x^2
sage: f.shift(2)
(2*T^2) + (T^3)*x + (T^4 + 122*T^2)*x^2

```

**square()**

EXAMPLES:

```

sage: B.<t> = PolynomialRing(Integers(125))
sage: R = monsky_washnitzer.SpecialCubicQuotientRing(t^3 - t + B(1/4))
sage: x, T = R.gens()

```

```

sage: f = R.create_element(1 + 2*t + 3*t^2, 4 + 7*t + 9*t^2, 3 + 5*t + 11*t^2)
sage: f.square()
(73*T^5 + 16*T^4 + 38*T^3 + 39*T^2 + 70*T + 120) + (121*T^5 + 113*T^4 + 73*T^
↪ 3 + 8*T^2 + 51*T + 61)*x + (18*T^4 + 60*T^3 + 22*T^2 + 108*T + 31)*x^2

```

**class** sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientElement

Bases: sage.structure.element.CommutativeAlgebraElement

Elements in the Hyperelliptic quotient ring

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-36*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: MW = x.parent()
sage: MW(x+x**2+y-77) # indirect doctest
-(77-y)*1 + x + x^2

```

**change\_ring(R)**

Return the same element after changing the base ring to R.

EXAMPLES:

```

sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-36*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: MW = x.parent()
sage: z = MW(x+x**2+y-77)
sage: z.change_ring(AA).parent()
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = x^5 - 36*x + 1) over_
↪ Algebraic Real Field

```

**coeffs(R=None)**

Returns the raw coefficients of this element.

INPUT:

- $R$  – an (optional) base-ring in which to cast the coefficients

OUTPUT:

- **coeffs** – a list of coefficients of powers of  $x$  for each power of  $y$
- **n** – an offset indicating the power of  $y$  of the first list element

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.coeffs()
[(0, 1, 0, 0, 0)], 0)
sage: y.coeffs()
[(0, 0, 0, 0, 0), (1, 0, 0, 0, 0)], 0)

sage: a = sum(n*x^n for n in range(5)); a
x + 2*x^2 + 3*x^3 + 4*x^4
sage: a.coeffs()
[(0, 1, 2, 3, 4)], 0)
sage: a.coeffs(Qp(7))
[(0, 1 + O(7^20), 2 + O(7^20), 3 + O(7^20), 4 + O(7^20))], 0)
sage: (a*y).coeffs()
[(0, 0, 0, 0, 0), (0, 1, 2, 3, 4)], 0)
sage: (a*y^-2).coeffs()
[(0, 1, 2, 3, 4), (0, 0, 0, 0, 0), (0, 0, 0, 0, 0)], -2)
```

Note that the coefficient list is transposed compared to how they are stored and printed:

```
sage: a*y^-2
(y^-2)*x + (2*y^-2)*x^2 + (3*y^-2)*x^3 + (4*y^-2)*x^4
```

A more complicated example:

```
sage: a = x^20*y^-3 - x^11*y^2; a
(y^-3-4*y^-1+6*y-4*y^3+y^5)*1 - (12*y^-3-36*y^-1+36*y+y^2-12*y^3-2*y^4+y^6)*x
↪ + (54*y^-3-108*y^-1+54*y+6*y^2-6*y^4)*x^2 - (108*y^-3-108*y^-1+9*y^2)*x^3 +
↪ (81*y^-3)*x^4
sage: raw, offset = a.coeffs()
sage: a.min_pow_y()
-3
sage: offset
-3
sage: raw
[(1, -12, 54, -108, 81),
 (0, 0, 0, 0, 0),
 (-4, 36, -108, 108, 0),
 (0, 0, 0, 0, 0),
 (6, -36, 54, 0, 0),
 (0, -1, 6, -9, 0),
 (-4, 12, 0, 0, 0),
 (0, 2, -6, 0, 0),
 (1, 0, 0, 0, 0),
 (0, -1, 0, 0, 0)]
sage: sum(c * x^i * y^(j+offset) for j, L in enumerate(raw) for i, c in
↪ enumerate(L)) == a
True
```

Can also be used to construct elements:

```
sage: a.parent()(raw, offset) == a
True
```

**diff()**

Return the differential of self

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: (x+3*y).diff()
(-(9-2*y)*1 + 15*x^4) dx/2y
```

**extract\_pow\_y(k)**

Return the coefficients of  $y^k$  in self as a list

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: (x+3*y+9*x*y).extract_pow_y(1)
[3, 9, 0, 0, 0]
```

**max\_pow\_y()**

Return the maximal degree of self w.r.t. y

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: (x+3*y).max_pow_y()
1
```

**min\_pow\_y()**

Return the minimal degree of self w.r.t. y

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: (x+3*y).min_pow_y()
0
```

**truncate\_neg(n)**

Return self minus its terms of degree less than  $n$  wrt  $y$ .

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: (x+3*y+7*x*2*y**4).truncate_neg(1)
3*y*1 + 14*y^4*x
```

```
class sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientRing
```

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.rings.ring.CommutativeAlgebra`

Initialization.

`Q()`

Return the defining polynomial of the underlying hyperelliptic curve.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-2*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().Q()
x^5 - 2*x + 1
```

`base_extend(R)`

Return the base extension of `self` to the ring `R` if possible.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().base_extend(UniversalCyclotomicField())
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = x^5 - 3*x + 1) over
↳Universal Cyclotomic Field
sage: x.parent().base_extend(ZZ)
Traceback (most recent call last):
...
TypeError: no such base extension
```

`change_ring(R)`

Return the analog of `self` over the ring `R`

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().change_ring(ZZ)
SpecialHyperellipticQuotientRing K[x,y,y^-1] / (y^2 = x^5 - 3*x + 1) over
↳Integer Ring
```

`curve()`

Return the underlying hyperelliptic curve.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().curve()
Hyperelliptic Curve over Rational Field defined by y^2 = x^5 - 3*x + 1
```



**degree()**

Return the degree of the underlying hyperelliptic curve.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().degree()
5
```

**gens()**

Return the generators of self

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().gens()
(x, y*1)
```

**is\_field(proof=True)**

Return False as self is not a field.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().is_field()
False
```

**monomial(i, j, b=None)**

Returns  $by^jx^i$ , computed quickly.

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().monomial(4, 5)
y^5*x^4
```

**monomial\_diff\_coeffs(i, j)**

The key here is that the formula for  $d(x^iy^j)$  is messy in terms of  $i$ , but varies nicely with  $j$ .

$$d(x^iy^j) = y^{j-1}(2ix^{i-1}y^2 + j(A_i(x) + B_i(x)y^2))\frac{dx}{2y}$$

Where  $A, B$  have degree at most  $n - 1$  for each  $i$ . Pre-compute  $A_i, B_i$  for each  $i$  the “hard” way, and the rest are easy.

**monomial\_diff\_coeffs\_matrices()****monskey\_washnitzer()****prime()****x()**

Return the generator  $x$  of self

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().x()
x
```

**y()**

Return the generator  $y$  of self

EXAMPLES:

```
sage: R.<x> = QQ['x']
sage: E = HyperellipticCurve(x^5-3*x+1)
sage: x,y = E.monsky_washnitzer_gens()
sage: x.parent().y()
y*1
```

sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**SpecialHyperellipticQuotientRing\_class**  
alias of *SpecialHyperellipticQuotientRing*

sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**adjusted\_prec**( $p$ ,  $prec$ )

Computes how much precision is required in `matrix_of_frobenius` to get an answer correct to  $prec$   $p$ -adic digits.

The issue is that the algorithm used in `matrix_of_frobenius()` sometimes performs divisions by  $p$ , so precision is lost during the algorithm.

The estimate returned by this function is based on Kedlaya's result (Lemmas 2 and 3 of [Ked2001]), which implies that if we start with  $M$   $p$ -adic digits, the total precision loss is at most  $1 + \lfloor \log_p(2M - 3) \rfloor$   $p$ -adic digits. (This estimate is somewhat less than the amount you would expect by naively counting the number of divisions by  $p$ .)

INPUT:

- $p$  – a prime = 5
- $prec$  – integer, desired output precision, = 1

OUTPUT: adjusted precision (usually slightly more than  $prec$ )

sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.**frobenius\_expansion\_by\_newton**( $Q$ ,  
 $p$ ,  
 $M$ )

Computes the action of Frobenius on  $dx/y$  and on  $xdx/y$ , using Newton's method (as suggested in Kedlaya's paper [Ked2001]).

(This function does *not* yet use the cohomology relations - that happens afterwards in the “reduction” step.)

More specifically, it finds  $F_0$  and  $F_1$  in the quotient ring  $R[x, T]/(T - Q(x))$ , such that

$$F(dx/y) = T^{-r} F_0 dx/y, \text{ and } F(xdx/y) = T^{-r} F_1 dx/y$$

where

$$r = ((2M - 3)p - 1)/2.$$

(Here  $T$  is  $y^2 = z^{-2}$ , and  $R$  is the coefficient ring of  $Q$ .)

$F_0$  and  $F_1$  are computed in the SpecialCubicQuotientRing associated to  $Q$ , so all powers of  $x^j$  for  $j \geq 3$  are reduced to powers of  $T$ .

INPUT:

- **Q** – cubic polynomial of the form  $Q(x) = x^3 + ax + b$ , whose coefficient ring is a  $\mathbb{Z}/(p^M)\mathbb{Z}$ -algebra
- $p$  – residue characteristic of the  $p$ -adic field
- **M** –  $p$ -adic precision of the coefficient ring (this will be used to determine the number of Newton iterations)

OUTPUT:

- $F_0, F_1$  - elements of `SpecialCubicQuotientRing(Q)`, as described above
- $r$  - non-negative integer, as described above

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.monsky_washnitzer import frobenius_
      ↪ expansion_by_newton
sage: R.<x> = Integers(5^3) ['x']
sage: Q = x^3 - x + R(1/4)
sage: frobenius_expansion_by_newton(Q, 5, 3)
((25*T^5 + 75*T^3 + 100*T^2 + 100*T + 100) + (5*T^6 + 80*T^5 + 100*T^3
+ 25*T + 50)*x + (55*T^5 + 50*T^4 + 75*T^3 + 25*T^2 + 25*T + 25)*x^2,
(5*T^8 + 15*T^7 + 95*T^6 + 10*T^5 + 25*T^4 + 25*T^3 + 100*T^2 + 50)
+ (65*T^7 + 55*T^6 + 70*T^5 + 100*T^4 + 25*T^2 + 100*T)*x
+ (15*T^6 + 115*T^5 + 75*T^4 + 100*T^3 + 50*T^2 + 75*T + 75)*x^2, 7)
```

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.frobenius_expansion_by_series(Q,`

$p,$   
 $M)$

Computes the action of Frobenius on  $dx/y$  and on  $x dx/y$ , using a series expansion.

(This function computes the same thing as `frobenius_expansion_by_newton()`, using a different method. Theoretically the Newton method should be asymptotically faster, when the precision gets large. However, in practice, this functions seems to be marginally faster for moderate precision, so I'm keeping it here until I figure out exactly why it is faster.)

(This function does *not* yet use the cohomology relations - that happens afterwards in the “reduction” step.)

More specifically, it finds  $F_0$  and  $F_1$  in the quotient ring  $R[x, T]/(T - Q(x))$ , such that  $F(dx/y) = T^{-r} F_0 dx/y$ , and  $F(x dx/y) = T^{-r} F_1 dx/y$  where  $r = ((2M - 3)p - 1)/2$ . (Here  $T$  is  $y^2 = z^{-2}$ , and  $R$  is the coefficient ring of  $Q$ .)

$F_0$  and  $F_1$  are computed in the `SpecialCubicQuotientRing` associated to  $Q$ , so all powers of  $x^j$  for  $j \geq 3$  are reduced to powers of  $T$ .

It uses the sum

$$F_0 = \sum_{k=0}^{M-2} \binom{-1/2}{k} p x^{p-1} E^k T^{(M-2-k)p}$$

and

$$F_1 = x^p F_0,$$

where  $E = Q(x^p) - Q(x)^p$ .

INPUT:

- **Q** – cubic polynomial of the form  $Q(x) = x^3 + ax + b$ , whose coefficient ring is a  $\mathbb{Z}/(p^M)\mathbb{Z}$ -algebra
- $p$  – residue characteristic of the  $p$ -adic field
- **M** –  $p$ -adic precision of the coefficient ring (this will be used to determine the number of terms in the series)

OUTPUT:

- $F_0, F_1$  - elements of `SpecialCubicQuotientRing(Q)`, as described above
- $r$  - non-negative integer, as described above

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.monsky_washnitzer import frobenius_
      ↪ expansion_by_series
sage: R.<x> = Integers(5^3) ['x']
sage: Q = x^3 - x + R(1/4)
sage: frobenius_expansion_by_series(Q, 5, 3)
((25*T^5 + 75*T^3 + 100*T^2 + 100*T + 100) + (5*T^6 + 80*T^5 + 100*T^3
+ 25*T + 50)*x + (55*T^5 + 50*T^4 + 75*T^3 + 25*T^2 + 25*T + 25)*x^2,
(5*T^8 + 15*T^7 + 95*T^6 + 10*T^5 + 25*T^4 + 25*T^3 + 100*T^2 + 50)
+ (65*T^7 + 55*T^6 + 70*T^5 + 100*T^4 + 25*T^2 + 100*T)*x
+ (15*T^6 + 115*T^5 + 75*T^4 + 100*T^3 + 50*T^2 + 75*T + 75)*x^2, 7)
```

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.helper_matrix(Q)`

Computes the (constant) matrix used to calculate the linear combinations of the  $d(x^i y^j)$  needed to eliminate the negative powers of  $y$  in the cohomology (i.e. in `reduce_negative()`).

INPUT:

- $Q$  – cubic polynomial

EXAMPLES:

```
sage: t = polygen(QQ, 't')
sage: from sage.schemes.hyperelliptic_curves.monsky_washnitzer import helper_
      ↪ matrix
sage: helper_matrix(t**3-4*t-691)
[ 64/12891731 -16584/12891731 4297329/12891731]
[ 6219/12891731 -32/12891731 8292/12891731]
[ -24/12891731 6219/12891731 -32/12891731]
```

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.lift(x)`

Tries to call `x.lift()`, presumably from the  $p$ -adics to  $\mathbb{Z}\mathbb{Z}$ .

If this fails, it assumes the input is a power series, and tries to lift it to a power series over  $\mathbb{Q}\mathbb{Q}$ .

This function is just a very kludgy solution to the problem of trying to make the reduction code (below) work over both  $\mathbb{Z}_p$  and  $\mathbb{Z}_p[[t]]$ .

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.monsky_washnitzer import lift
sage: l = lift(Qp(13)(131)); l
131
sage: l.parent()
Integer Ring

sage: x=PowerSeriesRing(Qp(17), 'x').gen()
sage: l = lift(4+5*x+17*x**6); l
4 + 5*t + 17*t^6
sage: l.parent()
Power Series Ring in t over Rational Field
```

```
sage.schemes.hyperelliptic_curves.monsky_washnitzer.matrix_of_frobenius(Q,
                                                                    p,
                                                                    M,
                                                                    trace=None,
                                                                    compute_exact_forms=False)
```

Computes the matrix of Frobenius on Monsky-Washnitzer cohomology, with respect to the basis  $(dx/y, xdx/y)$ .

INPUT:

- **Q – cubic polynomial**  $Q(x) = x^3 + ax + b$  defining an elliptic curve  $E$  by  $y^2 = Q(x)$ . The coefficient ring of  $Q$  should be a  $\mathbf{Z}/(p^M)\mathbf{Z}$ -algebra in which the matrix of Frobenius will be constructed.
- **p – prime = 5** for which  $E$  has good reduction
- **M – integer = 2; p -adic precision of** the coefficient ring
- **trace – (optional) the trace of the matrix, if** known in advance. This is easy to compute because it is just the  $a_p$  of the curve. If the trace is supplied, `matrix_of_frobenius` will use it to speed the computation (i.e. we know the determinant is  $p$ , so we have two conditions, so really only column of the matrix needs to be computed. it is actually a little more complicated than that, but that's the basic idea.) If `trace=None`, then both columns will be computed independently, and you can get a strong indication of correctness by verifying the trace afterwards.

**Warning:** THE RESULT WILL NOT NECESSARILY BE CORRECT TO M p-ADIC DIGITS. If you want `prec` digits of precision, you need to use the function `adjusted_prec()`, and then you need to reduce the answer mod  $p^{\text{prec}}$  at the end.

OUTPUT:

2x2 matrix of Frobenius on Monsky-Washnitzer cohomology, with entries in the coefficient ring of  $Q$ .

EXAMPLES:

A simple example:

```
sage: p = 5
sage: prec = 3
sage: M = monsky_washnitzer.adjusted_prec(p, prec)
sage: M
5
sage: R.<x> = PolynomialRing(Integers(p**M))
sage: A = monsky_washnitzer.matrix_of_frobenius(x^3 - x + R(1/4), p, M)
sage: A
[3090 187]
[2945 408]
```

But the result is only accurate to `prec` digits:

```
sage: B = A.change_ring(Integers(p**prec))
sage: B
[90 62]
[70 33]
```

Check trace ( $123 = -2 \bmod 125$ ) and determinant:

```
sage: B.det()
5
```

```
sage: B.trace()
123
sage: EllipticCurve([-1, 1/4]).ap(5)
-2
```

Try using the trace to speed up the calculation:

```
sage: A = monsky_washnitzer.matrix_of_frobenius(x^3 - x + R(1/4),
....:                                         p, M, -2)
sage: A
[2715  187]
[1445  408]
```

Hmmm... it looks different, but that's because the trace of our first answer was only  $-2$  modulo  $5^3$ , not  $-2$  modulo  $5^5$ . So the right answer is:

```
sage: A.change_ring(Integers(p**prec))
[90 62]
[70 33]
```

Check it works with only one digit of precision:

```
sage: p = 5
sage: prec = 1
sage: M = monsky_washnitzer.adjusted_prec(p, prec)
sage: R.<x> = PolynomialRing(Integers(p**M))
sage: A = monsky_washnitzer.matrix_of_frobenius(x^3 - x + R(1/4), p, M)
sage: A.change_ring(Integers(p))
[0 2]
[0 3]
```

Here is an example that is particularly badly conditioned for using the trace trick:

```
sage: p = 11
sage: prec = 3
sage: M = monsky_washnitzer.adjusted_prec(p, prec)
sage: R.<x> = PolynomialRing(Integers(p**M))
sage: A = monsky_washnitzer.matrix_of_frobenius(x^3 + 7*x + 8, p, M)
sage: A.change_ring(Integers(p**prec))
[1144  176]
[ 847  185]
```

The problem here is that the top-right entry is divisible by 11, and the bottom-left entry is divisible by  $11^2$ . So when you apply the trace trick, neither  $F(dx/y)$  nor  $F(xdx/y)$  is enough to compute the whole matrix to the desired precision, even if you try increasing the target precision by one. Nevertheless, `matrix_of_frobenius` knows how to get the right answer by evaluating  $F((x+1)dx/y)$  instead:

```
sage: A = monsky_washnitzer.matrix_of_frobenius(x^3 + 7*x + 8, p, M, -2)
sage: A.change_ring(Integers(p**prec))
[1144  176]
[ 847  185]
```

The running time is about  $O(p \cdot \text{prec}^2)$  (times some logarithmic factors), so it is feasible to run on fairly large primes, or precision (or both?!?!):

```
sage: p = 10007
sage: prec = 2
```

```

sage: M = monsky_washnitzer.adjusted_prec(p, prec)
sage: R.<x> = PolynomialRing(Integers(p**M))
sage: A = monsky_washnitzer.matrix_of_frobenius(           # long time
....:                                     x^3 - x + R(1/4), p, M) # long time
sage: B = A.change_ring(Integers(p**prec)); B             # long time
[74311982 57996908]
[95877067 25828133]
sage: B.det()                                             # long time
10007
sage: B.trace()                                           # long time
66
sage: EllipticCurve([-1, 1/4]).ap(10007)                 # long time
66

```

```

sage: p = 5
sage: prec = 300
sage: M = monsky_washnitzer.adjusted_prec(p, prec)
sage: R.<x> = PolynomialRing(Integers(p**M))
sage: A = monsky_washnitzer.matrix_of_frobenius(           # long time
....:                                     x^3 - x + R(1/4), p, M) # long time
sage: B = A.change_ring(Integers(p**prec))               # long time
sage: B.det()                                             # long time
5
sage: -B.trace()                                          # long time
2
sage: EllipticCurve([-1, 1/4]).ap(5)                     # long time
-2

```

Let us check consistency of the results for a range of precisions:

```

sage: p = 5
sage: max_prec = 60
sage: M = monsky_washnitzer.adjusted_prec(p, max_prec)
sage: R.<x> = PolynomialRing(Integers(p**M))
sage: A = monsky_washnitzer.matrix_of_frobenius(x^3 - x + R(1/4), p, M) # long time
↪long time
sage: A = A.change_ring(Integers(p**max_prec))           # long time
sage: result = []                                         # long time
sage: for prec in range(1, max_prec):                     # long time
....:     M = monsky_washnitzer.adjusted_prec(p, prec)   # long time
....:     R.<x> = PolynomialRing(Integers(p**M), 'x')     # long time
....:     B = monsky_washnitzer.matrix_of_frobenius(     # long time
....:                                     x^3 - x + R(1/4), p, M) # long time
....:     B = B.change_ring(Integers(p**prec))           # long time
....:     result.append(B == A.change_ring(               # long time
....:                                     Integers(p**prec))) # long time
sage: result == [True] * (max_prec - 1)                 # long time
True

```

The remaining examples discuss what happens when you take the coefficient ring to be a power series ring; i.e. in effect you're looking at a family of curves.

The code does in fact work...

```

sage: p = 11
sage: prec = 3
sage: M = monsky_washnitzer.adjusted_prec(p, prec)
sage: S.<t> = PowerSeriesRing(Integers(p**M), default_prec=4)

```

```

sage: a = 7 + t + 3*t^2
sage: b = 8 - 6*t + 17*t^2
sage: R.<x> = PolynomialRing(S)
sage: Q = x**3 + a*x + b
sage: A = monsky_washnitzer.matrix_of_frobenius(Q, p, M)      # long time
sage: B = A.change_ring(PowerSeriesRing(Integers(p**prec), 't', default_prec=4))
↪      # long time
sage: B
# long time
[1144 + 264*t + 841*t^2 + 1025*t^3 + O(t^4)  176 + 1052*t + 216*t^2 + 523*t^3 +
↪O(t^4)]
[  847 + 668*t + 81*t^2 + 424*t^3 + O(t^4)   185 + 341*t + 171*t^2 + 642*t^3 +
↪O(t^4)]

```

The trace trick should work for power series rings too, even in the badly- conditioned case. Unfortunately I don't know how to compute the trace in advance, so I'm not sure exactly how this would help. Also, I suspect the running time will be dominated by the expansion, so the trace trick won't really speed things up anyway. Another problem is that the determinant is not always  $p$ :

```

sage: B.det()
11 + 484*t^2 + 451*t^3 + O(t^4)
# long time

```

However, it appears that the determinant always has the property that if you substitute  $t - 11t$ , you do get the constant series  $p \pmod{p^{**prec}}$ . Similarly for the trace. And since the parameter only really makes sense when it is divisible by  $p$  anyway, perhaps this isn't a problem after all.

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.matrix_of_frobenius_hyperelliptic(Q,`  
 $p=$ Non  
 $prec=$ i  
 $M=$ No

Computes the matrix of Frobenius on Monsky-Washnitzer cohomology, with respect to the basis  $(dx/2y, xdx/2y, \dots, x^{d-2}dx/2y)$ , where  $d$  is the degree of  $Q$ .

INPUT:

- $Q$  – monic polynomial  $Q(x)$
- $p$  – prime  $\geq 5$  for which  $E$  has good reduction
- $prec$  – (optional)  $p$ -adic precision of the coefficient ring
- $M$  – (optional) adjusted  $p$ -adic precision of the coefficient ring

OUTPUT:

$(d-1) \times (d-1)$  matrix  $M$  of Frobenius on Monsky-Washnitzer cohomology, and list of differentials  $\{f_i\}$  such that

$$\phi^*(x^i dx/2y) = df_i + M[i] * \text{vec}(dx/2y, \dots, x^{d-2} dx/2y)$$

EXAMPLES:

```

sage: p = 5
sage: prec = 3
sage: R.<x> = QQ['x']
sage: A, f = monsky_washnitzer.matrix_of_frobenius_hyperelliptic(x^5 - 2*x + 3, p,
↪prec)
sage: A
[ 4*5 + O(5^3)      5 + 2*5^2 + O(5^3)  2 + 3*5 + 2*5^2 + O(5^3)  2
↪+ 5 + 5^2 + O(5^3)]
[ 3*5 + 5^2 + O(5^3)      3*5 + O(5^3)      4*5 + O(5^3)
↪ 2 + 5^2 + O(5^3)]

```



$[$	$4*5 + 4*5^2 + O(5^3)$	$3*5 + 2*5^2 + O(5^3)$	$5 + 3*5^2 + O(5^3)$	$\rightarrow$
$\rightarrow$	$2*5 + 2*5^2 + O(5^3)$			
$[$	$5^2 + O(5^3)$	$5 + 4*5^2 + O(5^3)$	$4*5 + 3*5^2 + O(5^3)$	$\rightarrow$
$\rightarrow$	$2*5 + O(5^3)$			

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.reduce_all(Q, p, coeffs, offset, compute_exact_form=False)`

Applies cohomology relations to reduce all terms to a linear combination of  $dx/y$  and  $x dx/y$ .

INPUT:

- $Q$  – cubic polynomial
- **coeffs** – list of length 3 lists. The  $i^{th}$  list  $[a, b, c]$  represents  $y^{2(i-offset)}(a + bx + cx^2)dx/y$ .
- **offset** – nonnegative integer

OUTPUT:

- $A, B$  - pair such that the input differential is cohomologous to  $(A + Bx) dx/y$ .

---

**Note:** The algorithm operates in-place, so the data in `coeffs` is destroyed.

---

EXAMPLES:

```
sage: R.<x> = Integers(5^3) ['x']
sage: Q = x^3 - x + R(1/4)
sage: coeffs = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
sage: coeffs = [[R.base_ring()(a) for a in row] for row in coeffs]
sage: monsky_washnitzer.reduce_all(Q, 5, coeffs, 1)
(21, 106)
```

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.reduce_negative(Q, p, coeffs, offset, exact_form=None)`

Applies cohomology relations to incorporate negative powers of  $y$  into the  $y^0$  term.

INPUT:

- $p$  – prime
- $Q$  – cubic polynomial
- **coeffs** – list of length 3 lists. The  $i^{th}$  list  $[a, b, c]$  represents  $y^{2(i-offset)}(a + bx + cx^2)dx/y$ .
- **offset** – nonnegative integer

OUTPUT: The reduction is performed in-place. The output is placed in `coeffs[offset]`. Note that `coeffs[i]` will be meaningless for  $i$  offset after this function is finished.

EXAMPLES:

```
sage: R.<x> = Integers(5^3) ['x']
sage: Q = x^3 - x + R(1/4)
sage: coeffs = [[10, 15, 20], [1, 2, 3], [4, 5, 6], [7, 8, 9]]
sage: coeffs = [[R.base_ring()(a) for a in row] for row in coeffs]
sage: monsky_washnitzer.reduce_negative(Q, 5, coeffs, 3)
```

```
sage: coeffs[3]
[28, 52, 9]
```

```
sage: R.<x> = Integers(7^3) ['x']
sage: Q = x^3 - x + R(1/4)
sage: coeffs = [[7, 14, 21], [1, 2, 3], [4, 5, 6], [7, 8, 9]]
sage: coeffs = [[R.base_ring()(a) for a in row] for row in coeffs]
sage: monsky_washnitzer.reduce_negative(Q, 7, coeffs, 3)
sage: coeffs[3]
[245, 332, 9]
```

```
sage.schemes.hyperelliptic_curves.monsky_washnitzer.reduce_positive(Q, p,
                                                                    coeffs,
                                                                    offset,
                                                                    ex-
                                                                    act_form=None)
```

Applies cohomology relations to incorporate positive powers of  $y$  into the  $y^0$  term.

INPUT:

- $Q$  – cubic polynomial
- **coeffs** – list of length 3 lists. The  $i^{th}$  list  $[a, b, c]$  represents  $y^{2(i-offset)}(a + bx + cx^2)dx/y$ .
- offset – nonnegative integer

OUTPUT: The reduction is performed in-place. The output is placed in `coeffs[offset]`. Note that `coeffs[i]` will be meaningless for  $i$  offset after this function is finished.

EXAMPLES:

```
sage: R.<x> = Integers(5^3) ['x']
sage: Q = x^3 - x + R(1/4)
```

```
sage: coeffs = [[1, 2, 3], [10, 15, 20]]
sage: coeffs = [[R.base_ring()(a) for a in row] for row in coeffs]
sage: monsky_washnitzer.reduce_positive(Q, 5, coeffs, 0)
sage: coeffs[0]
[16, 102, 88]
```

```
sage: coeffs = [[9, 8, 7], [10, 15, 20]]
sage: coeffs = [[R.base_ring()(a) for a in row] for row in coeffs]
sage: monsky_washnitzer.reduce_positive(Q, 5, coeffs, 0)
sage: coeffs[0]
[24, 108, 92]
```

```
sage.schemes.hyperelliptic_curves.monsky_washnitzer.reduce_zero(Q, coeffs,
                                                                offset, ex-
                                                                act_form=None)
```

Applies cohomology relation to incorporate  $x^2y^0$  term into  $x^0y^0$  and  $x^1y^0$  terms.

INPUT:

- $Q$  – cubic polynomial
- **coeffs** – list of length 3 lists. The  $i^{th}$  list  $[a, b, c]$  represents  $y^{2(i-offset)}(a + bx + cx^2)dx/y$ .
- offset – nonnegative integer

OUTPUT: The reduction is performed in-place. The output is placed in `coeffs[offset]`. This method completely ignores `coeffs[i]` for  $i \neq \text{offset}$ .

EXAMPLES:

```
sage: R.<x> = Integers(5^3) ['x']
sage: Q = x^3 - x + R(1/4)
sage: coeffs = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
sage: coeffs = [[R.base_ring()(a) for a in row] for row in coeffs]
sage: monsky_washnitzer.reduce_zero(Q, coeffs, 1)
sage: coeffs[1]
[6, 5, 0]
```

`sage.schemes.hyperelliptic_curves.monsky_washnitzer.transpose_list(input)`

INPUT:

- **input** – a list of lists, each list of the same length

OUTPUT:

- **output** – a list of lists such that `output[i][j] = input[j][i]`

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.monsky_washnitzer import transpose_
      ↪list
sage: L = [[1, 2], [3, 4], [5, 6]]
sage: transpose_list(L)
[[1, 3, 5], [2, 4, 6]]
```

## 16.8 Frobenius on Monsky-Washnitzer cohomology of a hyperelliptic curve over $\text{GF}(p)$ ,

for largish  $p$

This is a wrapper for the `matrix()` function in `hypellfrob.cpp`.

AUTHOR:

- David Harvey (2007-05)
- David Harvey (2007-12): rewrote for `hypellfrob` version 2.0

`sage.schemes.hyperelliptic_curves.hypellfrob.hypellfrob(p, N, Q)`

Compute the matrix of Frobenius acting on the Monsky-Washnitzer cohomology of a hyperelliptic curve  $y^2 = Q(x)$ , with respect to the basis  $x^i dx/y$ ,  $0 \leq i < 2g$ .

INPUT:

- $p$  – a prime
- $Q$  – a monic polynomial in  $\mathbb{Z}[x]$  of odd degree. Must have no multiple roots mod  $p$ .
- $N$  – precision parameter; the output matrix will be correct modulo  $p^N$ .

PRECONDITIONS:

Must have  $p > (2g + 1)(2N - 1)$ , where  $g = (\deg(Q) - 1)/2$  is the genus of the curve.

ALGORITHM:

Described in “Kedlaya’s algorithm in larger characteristic” by David Harvey. Running time is theoretically soft- $O(p^{1/2}N^{5/2}g^3)$ .

**Todo:** Remove the restriction on  $p$ . Probably by merging in Robert’s code, which eventually needs a fast C++/NTL implementation.

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.hypellfrob import hypellfrob
sage: R.<x> = PolynomialRing(ZZ)
sage: f = x^5 + 2*x^2 + x + 1; p = 101
sage: M = hypellfrob(p, 4, f); M
[ 91844754 + O(101^4)  38295665 + O(101^4)  44498269 + O(101^4)  11854028 + O(101^
↪4) ]
[ 93514789 + O(101^4)  48987424 + O(101^4)  53287857 + O(101^4)  61431148 + O(101^
↪4) ]
[ 77916046 + O(101^4)  60656459 + O(101^4)  101244586 + O(101^4)  56237448 + O(101^
↪4) ]
[ 58643832 + O(101^4)  81727988 + O(101^4)  85294589 + O(101^4)  70104432 + O(101^
↪4) ]
sage: -M.trace()
7 + O(101^4)
sage: sum([legendre_symbol(f(i), p) for i in range(p)])
7
sage: ZZ(M.det())
10201
sage: M = hypellfrob(p, 1, f); M
[ 0 + O(101)  0 + O(101)  93 + O(101)  62 + O(101) ]
[ 0 + O(101)  0 + O(101)  55 + O(101)  19 + O(101) ]
[ 0 + O(101)  0 + O(101)  65 + O(101)  42 + O(101) ]
[ 0 + O(101)  0 + O(101)  89 + O(101)  29 + O(101) ]
```

AUTHORS:

- David Harvey (2007-05)
- David Harvey (2007-12): updated for hypellfrob version 2.0

## 16.9 Jacobian of a General Hyperelliptic Curve

**class** sage.schemes.hyperelliptic\_curves.jacobian\_generic.**HyperellipticJacobian\_generic**(C)  
Bases: *sage.schemes.jacobians.abstract\_jacobian.Jacobian\_generic*

EXAMPLES:

```
sage: FF = FiniteField(2003)
sage: R.<x> = PolynomialRing(FF)
sage: f = x**5 + 1184*x**3 + 1846*x**2 + 956*x + 560
sage: C = HyperellipticCurve(f)
sage: J = C.jacobian()
sage: a = x**2 + 376*x + 245; b = 1015*x + 1368
sage: X = J(FF)
sage: D = X([a,b])
sage: D
(x^2 + 376*x + 245, y + 988*x + 635)
sage: J(0)
```

```
(1)
sage: D == J([a,b])
True
sage: D == D + J(0)
True
```

An more extended example, demonstrating arithmetic in  $J(\mathbb{Q}\mathbb{Q})$  and  $J(K)$  for a number field  $K/\mathbb{Q}\mathbb{Q}$ .

```
sage: P.<x> = PolynomialRing(QQ)
sage: f = x^5 - x + 1; h = x
sage: C = HyperellipticCurve(f,h,'u,v')
sage: C
Hyperelliptic Curve over Rational Field defined by v^2 + u*v = u^5 - u + 1
sage: PP = C.ambient_space()
sage: PP
Projective Space of dimension 2 over Rational Field
sage: C.defined_polynomial()
-x^0*x^5 + x^0*x^1*x^2^3 + x^1^2*x^2^3 + x^0*x^2^4 - x^2^5
sage: C(QQ)
Set of rational points of Hyperelliptic Curve over Rational Field defined by v^2 +
u*v = u^5 - u + 1
sage: K.<t> = NumberField(x^2-2)
sage: C(K)
Set of rational points of Hyperelliptic Curve over Number Field in t with
defining polynomial x^2 - 2 defined by v^2 + u*v = u^5 - u + 1
sage: P = C(QQ)(0,1,1); P
(0 : 1 : 1)
sage: P == C(0,1,1)
True
sage: C(0,1,1).parent()
Set of rational points of Hyperelliptic Curve over Rational Field defined by v^2 +
u*v = u^5 - u + 1
sage: P1 = C(K)(P)
sage: P2 = C(K)([2,4*t-1,1])
sage: P3 = C(K)([-1/2,1/8*(7*t+2),1])
sage: P1, P2, P3
((0 : 1 : 1), (2 : 4*t - 1 : 1), (-1/2 : 7/8*t + 1/4 : 1))
sage: J = C.jacobian()
sage: J
Jacobian of Hyperelliptic Curve over Rational Field defined by v^2 + u*v = u^5 -
u + 1
sage: Q = J(QQ)(P); Q
(u, v - 1)
sage: for i in range(6): Q*i
(1)
(u, v - 1)
(u^2, v + u - 1)
(u^2, v + 1)
(u, v + 1)
(1)
sage: Q1 = J(K)(P1); print("%s -> %s"%( P1, Q1 ))
(0 : 1 : 1) -> (u, v - 1)
sage: Q2 = J(K)(P2); print("%s -> %s"%( P2, Q2 ))
(2 : 4*t - 1 : 1) -> (u - 2, v - 4*t + 1)
sage: Q3 = J(K)(P3); print("%s -> %s"%( P3, Q3 ))
(-1/2 : 7/8*t + 1/4 : 1) -> (u + 1/2, v - 7/8*t - 1/4)
sage: R.<x> = PolynomialRing(K)
sage: Q4 = J(K)([x^2-t,R(1)])
```

```

sage: for i in range(4): Q4*i
(1)
(u^2 - t, v - 1)
(u^2 + (-3/4*t - 9/16)*u + 1/2*t + 1/4, v + (-1/32*t - 57/64)*u + 1/2*t + 9/16)
(u^2 + (1352416/247009*t - 1636930/247009)*u - 1156544/247009*t + 1900544/247009,
↪ v + (-2326345442/122763473*t + 3233153137/122763473)*u + 2439343104/122763473*t,
↪ - 3350862929/122763473)
sage: R2 = Q2*5; R2
(u^2 - 3789465233/116983808*u - 267915823/58491904, v + (-233827256513849/
↪ 1789384327168*t + 1/2)*u - 15782925357447/894692163584*t)
sage: R3 = Q3*5; R3
(u^2 + 5663300808399913890623/14426454798950909645952*u - 26531814176395676231273/
↪ 28852909597901819291904, v + (253155440321645614070860868199103/
↪ 2450498420175733688903836378159104*t + 1/2)*u +
↪ 2427708505064902611513563431764311/4900996840351467377807672756318208*t)
sage: R4 = Q4*5; R4
(u^2 - 3789465233/116983808*u - 267915823/58491904, v + (233827256513849/
↪ 1789384327168*t + 1/2)*u + 15782925357447/894692163584*t)
sage: # Thus we find the following identity:
sage: 5*Q2 + 5*Q4
(1)
sage: # Moreover the following relation holds in the 5-torsion subgroup:
sage: Q2 + Q4 == 2*Q1
True

```

**dimension()**

Return the dimension of this Jacobian.

**OUTPUT:** Integer

**EXAMPLES:**

```

sage: k.<a> = GF(9); R.<x> = k[]
sage: HyperellipticCurve(x^3 + x - 1, x+a).jacobian().dimension()
1
sage: g = HyperellipticCurve(x^6 + x - 1, x+a).jacobian().dimension(); g
2
sage: type(g)
<... 'sage.rings.integer.Integer'>

```

**point** (*mumford*, *check=True*)

## 16.10 Jacobian of a Hyperelliptic curve of Genus 2

```

class sage.schemes.hyperelliptic_curves.jacobian_g2.HyperellipticJacobian_g2(C)
    Bases: sage.schemes.hyperelliptic_curves.jacobian_generic.
            HyperellipticJacobian_generic
    kummer_surface()

```

## 16.11 Rational point sets on a Jacobian

**EXAMPLES:**

```

sage: x = QQ['x'].0
sage: f = x^5 + x + 1
sage: C = HyperellipticCurve(f); C
Hyperelliptic Curve over Rational Field defined by y^2 = x^5 + x + 1
sage: C(QQ)
Set of rational points of Hyperelliptic Curve over Rational Field defined by y^2 = x^
↪ 5 + x + 1
sage: P = C([0,1,1])
sage: J = C.jacobian(); J
Jacobian of Hyperelliptic Curve over Rational Field defined by y^2 = x^5 + x + 1
sage: Q = J(QQ)(P); Q
(x, y - 1)
sage: Q + Q
(x^2, y - 1/2*x - 1)
sage: Q*3
(x^2 - 1/64*x + 1/8, y + 255/512*x + 65/64)

```

```

sage: F.<a> = GF(3)
sage: R.<x> = F[]
sage: f = x^5-1
sage: C = HyperellipticCurve(f)
sage: J = C.jacobian()
sage: X = J(F)
sage: a = x^2-x+1
sage: b = -x +1
sage: c = x-1
sage: d = 0
sage: D1 = X([a,b])
sage: D1
(x^2 + 2*x + 1, y + x + 2)
sage: D2 = X([c,d])
sage: D2
(x + 2, y)
sage: D1+D2
(x^2 + 2*x + 2, y + 2*x + 1)

```

```

class sage.schemes.hyperelliptic_curves.jacobian_homset.JacobianHomset_divisor_classes(Y,
                                                                                       X,
                                                                                       **kw)

    Bases: sage.schemes.generic.homset.SchemeHomset_points

    base_extend(R)

    curve()

    value_ring()
        Returns S for a homset X(T) where T = Spec(S).

```

## 16.12 Jacobian ‘morphism’ as a class in the Picard group

This module implements the group operation in the Picard group of a hyperelliptic curve, represented as divisors in Mumford representation, using Cantor’s algorithm.

A divisor on the hyperelliptic curve  $y^2 + yh(x) = f(x)$  is stored in Mumford representation, that is, as two polynomials  $u(x)$  and  $v(x)$  such that:

- $u(x)$  is monic,

- $u(x)$  divides  $f(x) - h(x)v(x) - v(x)^2$ ,
- $\deg(v(x)) < \deg(u(x)) \leq g$ .

## REFERENCES:

A readable introduction to divisors, the Picard group, Mumford representation, and Cantor's algorithm:

- J. Scholten, F. Vercauteren. An Introduction to Elliptic and Hyperelliptic Curve Cryptography and the NTRU Cryptosystem. To appear in B. Preneel (Ed.) State of the Art in Applied Cryptography - COSIC '03, Lecture Notes in Computer Science, Springer 2004.

A standard reference in the field of cryptography:

- R. Avanzi, H. Cohen, C. Doche, G. Frey, T. Lange, K. Nguyen, and F. Vercauteren, Handbook of Elliptic and Hyperelliptic Curve Cryptography. CRC Press, 2005.

EXAMPLES: The following curve is the reduction of a curve whose Jacobian has complex multiplication.

```
sage: x = GF(37)['x'].gen()
sage: H = HyperellipticCurve(x^5 + 12*x^4 + 13*x^3 + 15*x^2 + 33*x); H
Hyperelliptic Curve over Finite Field of size 37 defined
by y^2 = x^5 + 12*x^4 + 13*x^3 + 15*x^2 + 33*x
```

At this time, Jacobians of hyperelliptic curves are handled differently than elliptic curves:

```
sage: J = H.jacobian(); J
Jacobian of Hyperelliptic Curve over Finite Field of size 37 defined
by y^2 = x^5 + 12*x^4 + 13*x^3 + 15*x^2 + 33*x
sage: J = J(J.base_ring()); J
Set of rational points of Jacobian of Hyperelliptic Curve over Finite Field
of size 37 defined by y^2 = x^5 + 12*x^4 + 13*x^3 + 15*x^2 + 33*x
```

Points on the Jacobian are represented by Mumford's polynomials. First we find a couple of points on the curve:

```
sage: P1 = H.lift_x(2); P1
(2 : 11 : 1)
sage: Q1 = H.lift_x(10); Q1
(10 : 18 : 1)
```

Observe that 2 and 10 are the roots of the polynomials in  $x$ , respectively:

```
sage: P = J(P1); P
(x + 35, y + 26)
sage: Q = J(Q1); Q
(x + 27, y + 19)
```

```
sage: P + Q
(x^2 + 25*x + 20, y + 13*x)
sage: (x^2 + 25*x + 20).roots(multiplicities=False)
[10, 2]
```

Frobenius satisfies

$$x^4 + 12 * x^3 + 78 * x^2 + 444 * x + 1369$$

on the Jacobian of this reduction and the order of the Jacobian is  $N = 1904$ .

```
sage: 1904*P
(1)
```



```
sage: 34*P == 0
True
sage: 35*P == P
True
sage: 33*P == -P
True
```

```
sage: Q*1904
(1)
sage: Q*238 == 0
True
sage: Q*239 == Q
True
sage: Q*237 == -Q
True
```

```
class sage.schemes.hyperelliptic_curves.jacobian_morphism.JacobianMorphism_divisor_class_f
```

Bases: `sage.structure.element.AdditiveGroupElement`, `sage.schemes.generic.morphism.SchemeMorphism`

An element of a Jacobian defined over a field, i.e. in  $J(K) = \text{Pic}_K^0(C)$ .

**scheme()**

Return the scheme this morphism maps to; or, where this divisor lives.

**Warning:** Although a pointset is defined over a specific field, the scheme returned may be over a different (usually smaller) field. The example below demonstrates this: the pointset is determined over a number field of absolute degree 2 but the scheme returned is defined over the rationals.

EXAMPLES:

```
sage: x = QQ['x'].gen()
sage: f = x^5 + x
sage: H = HyperellipticCurve(f)
sage: F.<a> = NumberField(x^2 - 2, 'a')
sage: J = H.jacobian()(F); J
Set of rational points of Jacobian of Hyperelliptic Curve over
Number Field in a with defining polynomial x^2 - 2 defined
by y^2 = x^5 + x
```

```
sage: P = J(H.lift_x(F(1)))
sage: P.scheme()
Jacobian of Hyperelliptic Curve over Rational Field defined by y^2 = x^5 + x
```

```
sage.schemes.hyperelliptic_curves.jacobian_morphism.cantor_composition(D1,
                                                                           D2,
                                                                           f, h,
                                                                           genus)
```

EXAMPLES:

```
sage: F.<a> = GF(7^2, 'a')
sage: x = F['x'].gen()
sage: f = x^7 + x^2 + a
```

```
sage: H = HyperellipticCurve(f, 2*x); H
Hyperelliptic Curve over Finite Field in a of size 7^2 defined by y^2 + 2*x*y = x^
↪7 + x^2 + a
sage: J = H.jacobian()(F); J
Set of rational points of Jacobian of Hyperelliptic Curve over
Finite Field in a of size 7^2 defined by y^2 + 2*x*y = x^7 + x^2 + a
```

```
sage: Q = J(H.lift_x(F(1))); Q
(x + 6, y + 2*a + 2)
sage: 10*Q # indirect doctest
(x^3 + (3*a + 1)*x^2 + (2*a + 5)*x + a + 5, y + (4*a + 5)*x^2 + (a + 1)*x + 6*a +
↪3)
sage: 7*8297*Q
(1)
```

```
sage: Q = J(H.lift_x(F(a+1))); Q
(x + 6*a + 6, y + 2*a)
sage: 7*8297*Q # indirect doctest
(1)

A test over a prime field:

sage: F = GF(next_prime(10^30))
sage: x = F['x'].gen()
sage: f = x^7 + x^2 + 1
sage: H = HyperellipticCurve(f, 2*x); H
Hyperelliptic Curve over Finite Field of size 10000000000000000000000000057
↪defined by y^2 + 2*x*y = x^7 + x^2 + 1
sage: J = H.jacobian()(F); J
verbose 0 (...: multi_polynomial_ideal.py, dimension) Warning: falling back to
↪very slow toy implementation.
Set of rational points of Jacobian of Hyperelliptic Curve over
Finite Field of size 10000000000000000000000000000057 defined
by y^2 + 2*x*y = x^7 + x^2 + 1
sage: Q = J(H.lift_x(F(1))); Q
(x + 100000000000000000000000000000056, y + 100000000000000000000000000056)
sage: 10*Q # indirect doctest
(x^3 + 150296037169838934997145567227*x^2 + 377701248971234560956743242408*x +
↪509456150352486043408603286615, y + 514451014495791237681619598519*x^2 +
↪875375621665039398768235387900*x + 861429240012590886251910326876)
sage: 7*8297*Q
(x^3 + 35410976139548567549919839063*x^2 + 26230404235226464545886889960*x +
↪681571430588959705539385624700, y + 999722365017286747841221441793*x^2 +
↪262703715994522725686603955650*x + 626219823403254233972118260890)
```

`sage.schemes.hyperelliptic_curves.jacobian_morphism.cantor_composition_simple` ( $D_1$ ,  $D_2$ ,  $f$ , *genus*)

Given  $D_1$  and  $D_2$  two reduced Mumford divisors on the Jacobian of the curve  $y^2 = f(x)$ , computes a representative  $D_1 + D_2$ .

**Warning:** The representative computed is NOT reduced! Use `cantor_reduction_simple()` to reduce it.

## EXAMPLES:

```
sage: x = QQ['x'].gen()
sage: f = x^5 + x
sage: H = HyperellipticCurve(f); H
Hyperelliptic Curve over Rational Field defined by y^2 = x^5 + x
```

```
sage: F.<a> = NumberField(x^2 - 2, 'a')
sage: J = H.jacobian()(F); J
Set of rational points of Jacobian of Hyperelliptic Curve over
Number Field in a with defining polynomial x^2 - 2 defined
by y^2 = x^5 + x
```

```
sage: P = J(H.lift_x(F(1))); P
(x - 1, y - a)
sage: Q = J(H.lift_x(F(0))); Q
(x, y)
sage: 2*P + 2*Q # indirect doctest
(x^2 - 2*x + 1, y - 3/2*a*x + 1/2*a)
sage: 2*(P + Q) # indirect doctest
(x^2 - 2*x + 1, y - 3/2*a*x + 1/2*a)
sage: 3*P # indirect doctest
(x^2 - 25/32*x + 49/32, y - 45/256*a*x - 315/256*a)
```

`sage.schemes.hyperelliptic_curves.jacobian_morphism.cantor_reduction`( $a$ ,  $b$ ,  $f$ ,  $h$ ,  $genus$ )

Return the unique reduced divisor linearly equivalent to  $(a, b)$  on the curve  $y^2 + yh(x) = f(x)$ .

See the docstring of `sage.schemes.hyperelliptic_curves.jacobian_morphism` for information about divisors, linear equivalence, and reduction.

## EXAMPLES:

```
sage: x = QQ['x'].gen()
sage: f = x^5 - x
sage: H = HyperellipticCurve(f, x); H
Hyperelliptic Curve over Rational Field defined by y^2 + x*y = x^5 - x
sage: J = H.jacobian()(QQ); J
Set of rational points of Jacobian of Hyperelliptic Curve over
Rational Field defined by y^2 + x*y = x^5 - x
```

The following point is 2-torsion:

```
sage: Q = J(H.lift_x(0)); Q
(x, y)
sage: 2*Q # indirect doctest
(1)
```

The next point is not 2-torsion:

```
sage: P = J(H.lift_x(-1)); P
(x + 1, y - 1)
sage: 2 * J(H.lift_x(-1)) # indirect doctest
(x^2 + 2*x + 1, y - 3*x - 4)
sage: 3 * J(H.lift_x(-1)) # indirect doctest
(x^2 - 487*x - 324, y - 10754*x - 7146)
```

```
sage.schemes.hyperelliptic_curves.jacobian_morphism.cantor_reduction_simple(a,
                                                                              b,
                                                                              f,
                                                                              genus)
```

Return the unique reduced divisor linearly equivalent to  $(a, b)$  on the curve  $y^2 = f(x)$ .

See the docstring of `sage.schemes.hyperelliptic_curves.jacobian_morphism` for information about divisors, linear equivalence, and reduction.

EXAMPLES:

```
sage: x = QQ['x'].gen()
sage: f = x^5 - x
sage: H = HyperellipticCurve(f); H
Hyperelliptic Curve over Rational Field defined by y^2 = x^5 - x
sage: J = H.jacobian()(QQ); J
Set of rational points of Jacobian of Hyperelliptic Curve over Rational Field
defined by y^2 = x^5 - x
```

The following point is 2-torsion:

```
sage: P = J(H.lift_x(-1)); P
(x + 1, y)
sage: 2 * P # indirect doctest
(1)
```

## 16.13 Hyperelliptic curves of genus 2 over a general ring

```
class sage.schemes.hyperelliptic_curves.hyperelliptic_g2_generic.HyperellipticCurve_g2_gen
```

Bases: `sage.schemes.hyperelliptic_curves.hyperelliptic_generic.HyperellipticCurve_generic`

**absolute\_igusa\_invariants\_kohel()**

Return the three absolute Igusa invariants used by Kohel [K].

See also:

`sage.schemes.hyperelliptic_curves.invariants()`

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: HyperellipticCurve(x^5 - 1).absolute_igusa_invariants_kohel()
(0, 0, 0)
sage: HyperellipticCurve(x^5 - x + 1, x^2).absolute_igusa_invariants_kohel()
(-1030567/178769, 259686400/178769, 20806400/178769)
sage: HyperellipticCurve((x^5 - x + 1)(3*x + 1), (x^2)(3*x + 1)).absolute_
↪ igusa_invariants_kohel()
(-1030567/178769, 259686400/178769, 20806400/178769)
```

**absolute\_igusa\_invariants\_wamelen()**

Return the three absolute Igusa invariants used by van Wamelen [W].

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: HyperellipticCurve(x^5 - 1).absolute_igusa_invariants_wamelen()
(0, 0, 0)
sage: HyperellipticCurve((x^5 - 1)(x - 2), (x^2)(x - 2)).absolute_igusa_
↪ invariants_wamelen()
(0, 0, 0)

```

**clebsch\_invariants()**

Return the Clebsch invariants  $(A, B, C, D)$  of Mestre, p 317, [M].

See also:

`sage.schemes.hyperelliptic_curves.invariants()`

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: f = x^5 - x^4 + 3
sage: HyperellipticCurve(f).clebsch_invariants()
(0, -2048/375, -4096/25, -4881645568/84375)
sage: HyperellipticCurve(f(2*x)).clebsch_invariants()
(0, -8388608/375, -1073741824/25, -5241627016305836032/84375)

sage: HyperellipticCurve(f, x).clebsch_invariants()
(-8/15, 17504/5625, -23162896/140625, -420832861216768/7119140625)
sage: HyperellipticCurve(f(2*x), 2*x).clebsch_invariants()
(-512/15, 71696384/5625, -6072014209024/140625, -451865844002031331704832/
↪ 7119140625)

```

**igusa\_clebsch\_invariants()**

Return the Igusa-Clebsch invariants  $I_2, I_4, I_6, I_{10}$  of Igusa and Clebsch [I].

See also:

`sage.schemes.hyperelliptic_curves.invariants()`

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: f = x^5 - x + 2
sage: HyperellipticCurve(f).igusa_clebsch_invariants()
(-640, -20480, 1310720, 52160364544)
sage: HyperellipticCurve(f(2*x)).igusa_clebsch_invariants()
(-40960, -83886080, 343597383680, 56006764965979488256)

sage: HyperellipticCurve(f, x).igusa_clebsch_invariants()
(-640, 17920, -1966656, 52409511936)
sage: HyperellipticCurve(f(2*x), 2*x).igusa_clebsch_invariants()
(-40960, 73400320, -515547070464, 56274284941110411264)

```

**is\_odd\_degree()**

Return True if the curve is an odd degree model.

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: f = x^5 - x^4 + 3
sage: HyperellipticCurve(f).is_odd_degree()
True

```

**jacobian()**

Return the Jacobian of the hyperelliptic curve.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: f = x^5 - x^4 + 3
sage: HyperellipticCurve(f).jacobian()
Jacobian of Hyperelliptic Curve over Rational Field defined by  $y^2 = x^5 - x^4 + 3$ 
```

**kummer\_morphism()**

Return the morphism of an odd degree hyperelliptic curve to the Kummer surface of its Jacobian.

This could be extended to an even degree model if a prescribed embedding in its Jacobian is fixed.

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: f = x^5 - x^4 + 3
sage: HyperellipticCurve(f).kummer_morphism() # not tested
```

## 16.14 Hyperelliptic curves of genus 2 over a finite field

**class** sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_finite\_field.**HyperellipticCurve\_g2\_finite\_field**

Bases: *sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic, sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field*

## 16.15 Hyperelliptic curves of genus 2 over a p-adic field

**class** sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_padic\_field.**HyperellipticCurve\_g2\_padic\_field**

Bases: *sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic, sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field*

## 16.16 Hyperelliptic curves of genus 2 over the rationals

**class** sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_rational\_field.**HyperellipticCurve\_g2\_rational\_field**

Bases: *sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic*

`HyperellipticCurve_g2_generic,` `sage.schemes.hyperelliptic_curves.hyperelliptic_rational_field.HyperellipticCurve_rational_field`

## 16.17 Compute invariants of quintics and sextics via ‘Ueberschiebung’.

REFERENCES:

Todo:

- Implement invariants in small positive characteristic.
- Cardona-Quer and additional invariants for classifying automorphism groups.

AUTHOR:

- Nick Alexander

`sage.schemes.hyperelliptic_curves.invariants.Ueberschiebung(f, g, k)`

Return the differential operator  $(fg)_k$ .

This is defined by Mestre on page 315 [M]:

$$(fg)_k = \frac{(m-k)!(n-k)!}{m!n!} \left( \frac{\partial f}{\partial x} \frac{\partial g}{\partial y} - \frac{\partial f}{\partial y} \frac{\partial g}{\partial x} \right)^k.$$

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.invariants import Ueberschiebung as ub
      ↪ ub
sage: R.<x, y> = QQ[]
sage: ub(x, y, 0)
x*y
sage: ub(x^5 + 1, x^5 + 1, 1)
0
sage: ub(x^5 + 5*x + 1, x^5 + 5*x + 1, 0)
x^10 + 10*x^6 + 2*x^5 + 25*x^2 + 10*x + 1
```

`sage.schemes.hyperelliptic_curves.invariants.absolute_igusa_invariants_kohel(f)`

Given a sextic form  $f$ , return the three absolute Igusa invariants used by Kohel [K].

$f$  may be homogeneous in two variables or inhomogeneous in one.

REFERENCES:

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: absolute_igusa_invariants_kohel(x^5 - 1)
(0, 0, 0)
sage: absolute_igusa_invariants_kohel(x^5 - x)
(100, -20000, -2000)
```

The following example can be checked against Kohel’s database [K]

```

sage: i1, i2, i3 = absolute_igusa_invariants_kohel(-x^5 + 3*x^4 + 2*x^3 - 6*x^2 -
↪ 3*x + 1)
sage: list(map(factor, (i1, i2, i3)))
[2^2 * 3^5 * 5 * 31, 2^5 * 3^11 * 5, 2^4 * 3^9 * 31]
sage: list(map(factor, (150660, 28343520, 9762768)))
[2^2 * 3^5 * 5 * 31, 2^5 * 3^11 * 5, 2^4 * 3^9 * 31]

```

`sage.schemes.hyperelliptic_curves.invariants.absolute_igusa_invariants_wamelen(f)`  
 Given a sextic form  $f$ , return the three absolute Igusa invariants used by van Wamelen [W].

$f$  may be homogeneous in two variables or inhomogeneous in one.

REFERENCES:

EXAMPLES:

```

sage: R.<x> = QQ[]
sage: absolute_igusa_invariants_wamelen(x^5 - 1)
(0, 0, 0)

```

The following example can be checked against van Wamelen's paper:

```

sage: i1, i2, i3 = absolute_igusa_invariants_wamelen(-x^5 + 3*x^4 + 2*x^3 - 6*x^2 -
↪ 3*x + 1)
sage: list(map(factor, (i1, i2, i3)))
[2^7 * 3^15, 2^5 * 3^11 * 5, 2^4 * 3^9 * 31]

```

`sage.schemes.hyperelliptic_curves.invariants.clebsch_invariants(f)`  
 Given a sextic form  $f$ , return the Clebsch invariants  $(A, B, C, D)$  of Mestre, p 317, [M].

$f$  may be homogeneous in two variables or inhomogeneous in one.

EXAMPLES:

```

sage: R.<x, y> = QQ[]
sage: clebsch_invariants(x^6 + y^6)
(2, 2/3, -2/9, 0)
sage: R.<x> = QQ[]
sage: clebsch_invariants(x^6 + x^5 + x^4 + x^2 + 2)
(62/15, 15434/5625, -236951/140625, 229930748/791015625)

sage: magma(x^6 + 1).ClebschInvariants() # optional - magma
[ 2, 2/3, -2/9, 0 ]
sage: magma(x^6 + x^5 + x^4 + x^2 + 2).ClebschInvariants() # optional - magma
[ 62/15, 15434/5625, -236951/140625, 229930748/791015625 ]

```

`sage.schemes.hyperelliptic_curves.invariants.clebsch_to_igusa(A, B, C, D)`  
 Convert Clebsch invariants  $A, B, C, D$  to Igusa invariants  $I_2, I_4, I_6, I_{10}$ .

EXAMPLES:

```

sage: from sage.schemes.hyperelliptic_curves.invariants import clebsch_to_igusa,
↪ igusa_to_clebsch
sage: clebsch_to_igusa(2, 3, 4, 5)
(-240, 17370, 231120, -103098906)
sage: igusa_to_clebsch(*clebsch_to_igusa(2, 3, 4, 5))
(2, 3, 4, 5)

sage: Cs = tuple(map(GF(31), (2, 3, 4, 5))); Cs
(2, 3, 4, 5)

```



```
sage: clebsch_to_igusa(*Cs)
(8, 10, 15, 26)
sage: igusa_to_clebsch(*clebsch_to_igusa(*Cs))
(2, 3, 4, 5)
```

`sage.schemes.hyperelliptic_curves.invariants.differential_operator(f, g, k)`  
Return the differential operator  $(fg)_k$  symbolically in the polynomial ring in `dfdx`, `dfdy`, `dgdx`, `dgdy`.

This is defined by Mestre on p 315 [M]:

$$(fg)_k = \frac{(m-k)!(n-k)!}{m!n!} \left( \frac{\partial f}{\partial x} \frac{\partial g}{\partial y} - \frac{\partial f}{\partial y} \frac{\partial g}{\partial x} \right)^k.$$

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.invariants import differential_
      ↪operator
sage: R.<x, y> = QQ[]
sage: differential_operator(x, y, 0)
1
sage: differential_operator(x, y, 1)
-dfdy*dgdx + dfdx*dgdy
sage: differential_operator(x*y, x*y, 2)
1/4*dfdy^2*dgdx^2 - 1/2*dfdx*dfdy*dgdx*dgdy + 1/4*dfdx^2*dgdy^2
sage: differential_operator(x^2*y, x*y^2, 2)
1/36*dfdy^2*dgdx^2 - 1/18*dfdx*dfdy*dgdx*dgdy + 1/36*dfdx^2*dgdy^2
sage: differential_operator(x^2*y, x*y^2, 4)
1/576*dfdy^4*dgdx^4 - 1/144*dfdx*dfdy^3*dgdx^3*dgdy + 1/96*dfdx^2*dfdy^2*dgdx^
      ↪2*dgdy^2 - 1/144*dfdx^3*dfdy*dgdx*dgdy^3 + 1/576*dfdx^4*dgdy^4
```

`sage.schemes.hyperelliptic_curves.invariants.diffsymb(U, f, g)`  
Given a differential operator  $U$  in `dfdx`, `dfdy`, `dgdx`, `dgdy`, represented symbolically by `U`, apply it to  $f$ ,  $g$ .

EXAMPLES:

```
sage: from sage.schemes.hyperelliptic_curves.invariants import diffsymb
sage: R.<x, y> = QQ[]
sage: S.<dfdx, dfdy, dgdx, dgdy> = QQ[]
sage: [ diffsymb(dd, x^2, y*0 + 1) for dd in S.gens() ]
[2*x, 0, 0, 0]
sage: [ diffsymb(dd, x*0 + 1, y^2) for dd in S.gens() ]
[0, 0, 0, 2*y]
sage: [ diffsymb(dd, x^2, y^2) for dd in S.gens() ]
[2*x*y^2, 0, 0, 2*x^2*y]

sage: diffsymb(dfdx + dfdy*dgdy, y*x^2, y^3)
2*x*y^4 + 3*x^2*y^2
```

`sage.schemes.hyperelliptic_curves.invariants.diffxy(f, x, xtimes, y, ytimes)`  
Differentiate a polynomial  $f$ ,  $xtimes$  with respect to  $x$ , and  $ytimes$  with respect to  $y$ .

EXAMPLES:

```
sage: R.<u, v> = QQ[]
sage: sage.schemes.hyperelliptic_curves.invariants.diffxy(u^2*v^3, u, 0, v, 0)
u^2*v^3
sage: sage.schemes.hyperelliptic_curves.invariants.diffxy(u^2*v^3, u, 2, v, 1)
6*v^2
```

```

sage: sage.schemes.hyperelliptic_curves.invariants.diffxy(u^2*v^3, u, 2, v, 2)
12*v
sage: sage.schemes.hyperelliptic_curves.invariants.diffxy(u^2*v^3 + u^4*v^4, u, 2,
↪ v, 2)
144*u^2*v^2 + 12*v

```

`sage.schemes.hyperelliptic_curves.invariants.igusa_clebsch_invariants(f)`  
 Given a sextic form  $f$ , return the Igusa-Clebsch invariants  $I_2, I_4, I_6, I_{10}$  of Igusa and Clebsch [I].

$f$  may be homogeneous in two variables or inhomogeneous in one.

EXAMPLES:

```

sage: R.<x, y> = QQ[]
sage: igusa_clebsch_invariants(x^6 + y^6)
(-240, 1620, -119880, -46656)
sage: R.<x> = QQ[]
sage: igusa_clebsch_invariants(x^6 + x^5 + x^4 + x^2 + 2)
(-496, 6220, -955932, -1111784)

sage: magma(x^6 + 1).IgusaClebschInvariants() # optional - magma
[ -240, 1620, -119880, -46656 ]
sage: magma(x^6 + x^5 + x^4 + x^2 + 2).IgusaClebschInvariants() # optional - magma
[ -496, 6220, -955932, -1111784 ]

```

`sage.schemes.hyperelliptic_curves.invariants.igusa_to_clebsch(I2, I4, I6, I10)`  
 Convert Igusa invariants  $I_2, I_4, I_6, I_{10}$  to Clebsch invariants  $A, B, C, D$ .

EXAMPLES:

```

sage: from sage.schemes.hyperelliptic_curves.invariants import clebsch_to_igusa, ↪
↪ igusa_to_clebsch
sage: igusa_to_clebsch(-2400, 173700, 23112000, -10309890600)
(20, 342/5, 2512/5, 43381012/1125)
sage: clebsch_to_igusa(*igusa_to_clebsch(-2400, 173700, 23112000, -10309890600))
(-2400, 173700, 23112000, -10309890600)

sage: Is = tuple(map(GF(31), (-2400, 173700, 23112000, -10309890600))); Is
(18, 7, 12, 27)
sage: igusa_to_clebsch(*Is)
(20, 25, 25, 12)
sage: clebsch_to_igusa(*igusa_to_clebsch(*Is))
(18, 7, 12, 27)

```

`sage.schemes.hyperelliptic_curves.invariants.ubs(f)`  
 Given a sextic form  $f$ , return a dictionary of the invariants of Mestre, p 317 [M].

$f$  may be homogeneous in two variables or inhomogeneous in one.

EXAMPLES:

```

sage: from sage.schemes.hyperelliptic_curves.invariants import ubs
sage: x = QQ['x'].0
sage: ubs(x^6 + 1)
{'A': 2,
 'B': 2/3,
 'C': -2/9,
 'D': 0,
 'Delta': -2/3*x^2*h^2,

```

```

'f': x^6 + h^6,
'i': 2*x^2*h^2,
'y1': 0,
'y2': 0,
'y3': 0}

sage: R.<u, v> = QQ[]
sage: ubs(u^6 + v^6)
{'A': 2,
 'B': 2/3,
 'C': -2/9,
 'D': 0,
 'Delta': -2/3*u^2*v^2,
 'f': u^6 + v^6,
 'i': 2*u^2*v^2,
 'y1': 0,
 'y2': 0,
 'y3': 0}

sage: R.<t> = GF(31)[]
sage: ubs(t^6 + 2*t^5 + t^2 + 3*t + 1)
{'A': 0,
 'B': -12,
 'C': -15,
 'D': -15,
 'Delta': -10*t^4 + 12*t^3*h + 7*t^2*h^2 - 5*t*h^3 + 2*h^4,
 'f': t^6 + 2*t^5*h + t^2*h^4 + 3*t*h^5 + h^6,
 'i': -4*t^4 + 10*t^3*h + 2*t^2*h^2 - 9*t*h^3 - 7*h^4,
 'y1': 4*t^2 - 10*t*h - 13*h^2,
 'y2': 6*t^2 - 4*t*h + 2*h^2,
 'y3': 4*t^2 - 4*t*h - 9*h^2}

```

## 16.18 Kummer surfaces over a general ring

**class** sage.schemes.hyperelliptic\_curves.kummer\_surface.**KummerSurface**(*J*)  
 Bases: sage.schemes.projective.projective\_subscheme.AlgebraicScheme\_subscheme\_projective

## 16.19 Conductor and Reduction Types for Genus 2 Curves

AUTHORS:

- Qing Liu and Henri Cohen (1994-1998): wrote genus2reduction C program
- William Stein (2006-03-05): wrote Sage interface to genus2reduction
- Jeroen Demeyer (2014-09-17): replace genus2reduction program by PARI library call ([trac ticket #15808](#))

ACKNOWLEDGMENT: (From Liu's website:) Many thanks to Henri Cohen who started writing this program. After this program is available, many people pointed out to me (mathematical as well as programming) bugs : B. Poonen, E. Schaefer, C. Stahlke, M. Stoll, F. Villegas. So thanks to all of them. Thanks also go to Ph. Depouilly who help me to compile the program.

Also Liu has given me explicit permission to include genus2reduction with Sage and for people to modify the C source code however they want.

**class** sage.interfaces.genus2reduction.**Genus2reduction**

Bases: sage.structure.sage\_object.SageObject

Conductor and Reduction Types for Genus 2 Curves.

Use  $R = \text{genus2reduction}(Q, P)$  to obtain reduction information about the Jacobian of the projective smooth curve defined by  $y^2 + Q(x)y = P(x)$ . Type `R?` for further documentation and a description of how to interpret the local reduction data.

EXAMPLES:

```
sage: x = QQ['x'].0
sage: R = genus2reduction(x^3 - 2*x^2 - 2*x + 1, -5*x^5)
sage: R.conductor
1416875
sage: factor(R.conductor)
5^4 * 2267
```

This means that only the odd part of the conductor is known.

```
sage: R.prime_to_2_conductor_only
True
```

The discriminant is always minimal away from 2, but possibly not at 2.

```
sage: factor(R.minimal_disc)
2^3 * 5^5 * 2267
```

Printing `R` summarizes all the information computed about the curve

```
sage: R
Reduction data about this proper smooth genus 2 curve:
  y^2 + (x^3 - 2*x^2 - 2*x + 1)*y = -5*x^5
A Minimal Equation (away from 2):
  y^2 = x^6 - 240*x^4 - 2550*x^3 - 11400*x^2 - 24100*x - 19855
Minimal Discriminant (away from 2): 56675000
Conductor (away from 2): 1416875
Local Data:
  p=2
  (potential) stable reduction: (II), j=1
  p=5
  (potential) stable reduction: (I)
  reduction at p: [V] page 156, (3), f=4
  p=2267
  (potential) stable reduction: (II), j=432
  reduction at p: [I{1-0-0}] page 170, (1), f=1
```

Here are some examples of curves with modular Jacobians:

```
sage: R = genus2reduction(x^3 + x + 1, -2*x^5 - 3*x^2 + 2*x - 2)
sage: factor(R.conductor)
23^2
sage: factor(genus2reduction(x^3 + 1, -x^5 - 3*x^4 + 2*x^2 + 2*x - 2).conductor)
29^2
sage: factor(genus2reduction(x^3 + x + 1, x^5 + 2*x^4 + 2*x^3 + x^2 - x - 1).
↪conductor)
5^6
```

EXAMPLES:

```

sage: genus2reduction(0, x^6 + 3*x^3 + 63)
Reduction data about this proper smooth genus 2 curve:
      y^2 = x^6 + 3*x^3 + 63
A Minimal Equation (away from 2):
      y^2 = x^6 + 3*x^3 + 63
Minimal Discriminant (away from 2): 10628388316852992
Conductor (away from 2): 2893401
Local Data:
  p=2
  (potential) stable reduction: (V), j1+j2=0, j1*j2=0
  p=3
  (potential) stable reduction: (I)
  reduction at p: [III{9}] page 184, (3)^2, f=10
  p=7
  (potential) stable reduction: (V), j1+j2=0, j1*j2=0
  reduction at p: [I{0}-II-0] page 159, (1), f=2

```

In the above example, Liu remarks that in fact at  $p = 2$ , the reduction is [II-II-0] page 163, (1),  $f = 8$ . So the conductor of  $J(C)$  is actually  $2 \cdot 2893401 = 5786802$ .

#### A MODULAR CURVE:

Consider the modular curve  $X_1(13)$  defined by an equation

$$y^2 + (x^3 - x^2 - 1)y = x^2 - x.$$

We have:

```

sage: genus2reduction(x^3-x^2-1, x^2 - x)
Reduction data about this proper smooth genus 2 curve:
      y^2 + (x^3 - x^2 - 1)*y = x^2 - x
A Minimal Equation (away from 2):
      y^2 = x^6 + 58*x^5 + 1401*x^4 + 18038*x^3 + 130546*x^2 + 503516*x + 808561
Minimal Discriminant (away from 2): 169
Conductor: 169
Local Data:
  p=13
  (potential) stable reduction: (V), j1+j2=0, j1*j2=0
  reduction at p: [I{0}-II-0] page 159, (1), f=2

```

So the curve has good reduction at 2. At  $p = 13$ , the stable reduction is union of two elliptic curves, and both of them have 0 as modular invariant. The reduction at 13 is of type [I\_0-II-0] (see Namikawa-Ueno, page 159). It is an elliptic curve with a cusp. The group of connected components of the Neron model of  $J(C)$  is trivial, and the exponent of the conductor of  $J(C)$  at 13 is  $f = 2$ . The conductor of  $J(C)$  is  $13^2$ . (Note: It is a theorem of Conrad-Edixhoven-Stein that the component group of  $J(X_1(p))$  is trivial for all primes  $p$ .)

#### raw( $Q, P$ )

Return a string emulating the raw output of running the old `genus2reduction` program on the hyperelliptic curve  $y^2 + Q(x)y = P(x)$ .

INPUT:

- $Q$  - something coercible to a univariate polynomial over  $\mathbb{Q}$ .
- $P$  - something coercible to a univariate polynomial over  $\mathbb{Q}$ .

OUTPUT:

- string - raw output
- $\mathbb{Q}$  - what  $Q$  was actually input to auxiliary `genus2reduction` program

- P - what P was actually input to auxiliary genus2reduction program

EXAMPLES:

```
sage: x = QQ['x'].0
sage: print(genus2reduction.raw(x^3 - 2*x^2 - 2*x + 1, -5*x^5)[0])
doctest:...: DeprecationWarning: the raw() method is provided for backwards
↳ compatibility only, use the result of the genus2reduction() call instead of
↳ parsing strings
See http://trac.sagemath.org/15808 for details.
a minimal equation over Z[1/2] is :
y^2 = x^6-240*x^4-2550*x^3-11400*x^2-24100*x-19855

factorization of the minimal (away from 2) discriminant :
[2,3;5,5;2267,1]

p=2
(potential) stable reduction : (II), j=1
p=5
(potential) stable reduction : (I)
reduction at p : [V] page 156, (3), f=4
p=2267
(potential) stable reduction : (II), j=432
reduction at p : [I{1-0-0}] page 170, (1), f=1

the prime to 2 part of the conductor is 1416875
in factorized form : [5,4;2267,1]
```

```
class sage.interfaces.genus2reduction.ReductionData(pari_result, P, Q, minimal_equation, minimal_disc,
                                                    local_data, conductor,
                                                    prime_to_2_conductor_only)
```

Bases: sage.structure.sage\_object.SageObject

Reduction data for a genus 2 curve.

How to read `local_data` attribute, i.e., if this class is `R`, then the following is the meaning of `R.local_data[p]`.

For each prime number  $p$  dividing the discriminant of  $y^2 + Q(x)y = P(x)$ , there are two lines.

The first line contains information about the stable reduction after field extension. Here are the meanings of the symbols of stable reduction :

(I) The stable reduction is smooth (i.e. the curve has potentially good reduction).

(II) The stable reduction is an elliptic curve  $E$  with an ordinary double point.  $j \bmod p$  is the modular invariant of  $E$ .

(III) The stable reduction is a projective line with two ordinary double points.

(IV) The stable reduction is two projective lines crossing transversally at three points.

(V) The stable reduction is the union of two elliptic curves  $E_1$  and  $E_2$  intersecting transversally at one point. Let  $j_1, j_2$  be their modular invariants, then  $j_1 + j_2$  and  $j_1 j_2$  are computed (they are numbers mod  $p$ ).

(VI) The stable reduction is the union of an elliptic curve  $E$  and a projective line which has an ordinary double point. These two components intersect transversally at one point.  $j \bmod p$  is the modular invariant of  $E$ .

(VII) The stable reduction is as above, but the two components are both singular.

In the cases (I) and (V), the Jacobian  $J(C)$  has potentially good reduction. In the cases (III), (IV) and (VII),  $J(C)$  has potentially multiplicative reduction. In the two remaining cases, the (potential) semi-abelian reduction

of  $J(C)$  is extension of an elliptic curve (with modular invariant  $j \bmod p$ ) by a torus.

The second line contains three data concerning the reduction at  $p$  without any field extension.

1. The first symbol describes the REDUCTION AT  $p$  of  $C$ . We use the symbols of Namikawa-Ueno for the type of the reduction (Namikawa, Ueno: "The complete classification of fibers in pencils of curves of genus two", Manuscripta Math., vol. 9, (1973), pages 143-186.) The reduction symbol is followed by the corresponding page number (or just an indication) in the above article. The lower index is printed by , for instance, [I2-II-5] means [I\_2-II-5]. Note that if  $K$  and  $K'$  are Kodaira symbols for singular fibers of elliptic curves,  $[K-K'-m]$  and  $[K'-K-m]$  are the same type. Finally,  $[K-K'-1]$  (not the same as  $[K-K'-1]$ ) is  $[K'-K-\alpha]$  in the notation of Namikawa-Ueno. The figure [2I\_0-m] in Namikawa-Ueno, page 159 must be denoted by [2I\_0-(m+1)].
2. The second datum is the GROUP OF CONNECTED COMPONENTS (over an ALGEBRAIC CLOSURE (!) of  $\mathbb{F}_p$ ) of the Neron model of  $J(C)$ . The symbol (n) means the cyclic group with n elements. When  $n=0$ , (0) is the trivial group (1).  $H_n$  is isomorphic to  $(2) \times (2)$  if  $n$  is even and to  $(4)$  otherwise.

Note - The set of rational points of  $\Phi$  can be computed using Theorem 1.17 in S. Bosch and Q. Liu "Rational points of the group of components of a Neron model", Manuscripta Math. 98 (1999), 275-293.

3. Finally,  $f$  is the exponent of the conductor of  $J(C)$  at  $p$ .

**Warning:** Be careful regarding the formula:

$$\text{valuation of the naive minimal discriminant} = f + n - 1 + 11c(X).$$

(Q. Liu : "Conducteur et discriminant minimal de courbes de genre 2", Compositio Math. 94 (1994) 51-79, Theoreme 2) is valid only if the residual field is algebraically closed as stated in the paper. So this equality does not hold in general over  $\mathbb{Q}_p$ . The fact is that the minimal discriminant may change after unramified extension. One can show however that, at worst, the change will stabilize after a quadratic unramified extension (Q. Liu : "Modeles entiers de courbes hyperelliptiques sur un corps de valuation discrete", Trans. AMS 348 (1996), 4577-4610, Section 7.2, Proposition 4).

`sage.interfaces.genus2reduction.divisors_to_string(divs)`

Convert a list of numbers (representing the orders of cyclic groups in the factorization of a finite abelian group) to a string according to the format shown in the examples.

INPUT:

- `divs` – a (possibly empty) list of numbers

OUTPUT: a string representation of these numbers

EXAMPLES:

```
sage: from sage.interfaces.genus2reduction import divisors_to_string
sage: print(divisors_to_string([]))
(1)
sage: print(divisors_to_string([5]))
(5)
sage: print(divisors_to_string([5]*6))
(5)^6
sage: print(divisors_to_string([2,3,4]))
(2)x(3)x(4)
sage: print(divisors_to_string([6,2,2]))
(6)x(2)^2
```





## INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)



## BIBLIOGRAPHY

- [Hartshorne] R. Hartshorne. Algebraic Geometry. Springer-Verlag, New York, 1977.
- [Fulton89] W. Fulton. Algebraic curves: an introduction to algebraic geometry. Addison-Wesley, Redwood City CA (1989).
- [HC2006] Mark van Hoeij and John Cremona, Solving Conics over function fields. J. Théor. Nombres Bordeaux, 2006.
- [ACKERMANS2016] Lennart Ackermans, Oplosbaarheid van Kegelsneden. <http://www.math.leidenuniv.nl/nl/theses/Bachelor/>.
- [WpJacobianVariety] [Wikipedia article Jacobian\\_variety](#)
- [HSV] Hess, Smart, Vercauteren, “The Eta Pairing Revisited”, IEEE Trans. Information Theory, 52(10): 4595-4602, 2006.
- [Mil04] Victor S. Miller, “The Weil pairing, and its efficient calculation”, J. Cryptol., 17(4):235-261, 2004
- [Cre] John Cremona, Algorithms for Modular Elliptic Curves. Cambridge University Press, 1997.
- [Sil1988] Joseph H. Silverman, Computing heights on elliptic curves. Mathematics of Computation, Vol. 51, No. 183 (Jul., 1988), pp. 339-358.
- [SilBook] Joseph H. Silverman, The Arithmetic of Elliptic Curves. Second edition. Graduate Texts in Mathematics, 106. Springer, 2009.
- [MazurTate1991] Mazur, B., & Tate, J. (1991). The  $p$ -adic sigma function. Duke Mathematical Journal, 62(3), 663-688.
- [K96] Kohel, “Endomorphism Rings of Elliptic Curves over Finite Fields”, UC Berkeley PhD thesis 1996.
- [BMSS] Boston, Morain, Salvy, Schost, “Fast Algorithms for Isogenies.”
- [M09] Moody, “The Diffie-Hellman Problem and Generalization of Verheul’s Theorem”
- [S72] Stark, “Class-numbers of complex quadratic fields.”
- [CW2005] J. E. Cremona and M. Watkins. Computing isogenies of elliptic curves. preprint, 2005.
- [KT2013] K. Tsukazaki, Explicit Isogenies of Elliptic Curves, PhD thesis, University of Warwick, 2013.
- [PZGH] Petho A., Zimmer H.G., Gebel J. and Herrmann E., Computing all  $S$ -integral points on elliptic curves Math. Proc. Camb. Phil. Soc. (1999), 127, 383-402
- [Bob13] J.W. Bober. Conditionally bounding analytic ranks of elliptic curves. ANTS 10. <http://msp.org/obs/2013/1-1/obs-v1-n1-p07-s.pdf>
- [GrossZagier] B. Gross and D. Zagier, *Heegner points and derivatives of  $L$ -series*. Invent. Math. 84 (1986), no. 2, 225-320.

- [Cha] B. Cha. Vanishing of some cohomology groups and bounds for the Shafarevich-Tate groups of elliptic curves. *J. Number Theory*, 111:154–178, 2005.
- [Jetchev] D. Jetchev. Global divisibility of Heegner points and Tamagawa numbers. *Compos. Math.* 144 (2008), no. 4, 811–826.
- [Kato] K. Kato.  $p$ -adic Hodge theory and values of zeta functions of modular forms. *Astérisque*, (295):ix, 117–290, 2004.
- [Kolyvagin] V. A. Kolyvagin. On the structure of Shafarevich-Tate groups. *Algebraic geometry*, 94–121, Lecture Notes in Math., 1479, Springer, Berlin, 1991.
- [LawsonWuthrich] T. Lawson and C. Wuthrich, Vanishing of some Galois cohomology groups for elliptic curves, [Arxiv 1505.02940](#)
- [LumStein] A. Lum, W. Stein. Verification of the Birch and Swinnerton-Dyer Conjecture for Elliptic Curves with Complex Multiplication (unpublished)
- [Mazur] B. Mazur. Modular curves and the Eisenstein ideal. *Inst. Hautes Études Sci. Publ. Math.* No. 47 (1977), 33–186 (1978).
- [Rubin] K. Rubin. The “main conjectures” of Iwasawa theory for imaginary quadratic fields. *Invent. Math.* 103 (1991), no. 1, 25–68.
- [SteinWuthrich] W. Stein and C. Wuthrich, Algorithms for the Arithmetic of Elliptic Curves using Iwasawa Theory *Mathematics of Computation* 82 (2013), 1757–1792.
- [SteinEtAl] G. Grigorov, A. Jorza, S. Patrikis, W. Stein, C. Tarniță. Computational verification of the Birch and Swinnerton-Dyer conjecture for individual elliptic curves. *Math. Comp.* 78 (2009), no. 268, 2397–2425.
- [CS] J.E.Cremona, and S. Siksek, Computing a Lower Bound for the Canonical Height on Elliptic Curves over  $\mathbf{Q}$ , ANTS VII Proceedings: F.Hess, S.Pauli and M.Pohst (eds.), ANTS VII, Lecture Notes in Computer Science 4076 (2006), pages 275–286.
- [TT] T. Thongjunthug, Computing a lower bound for the canonical height on elliptic curves over number fields, *Math. Comp.* 79 (2010), pages 2431–2449.
- [CPS] J.E. Cremona, M. Prickett and S. Siksek, Height Difference Bounds For Elliptic Curves over Number Fields, *Journal of Number Theory* 116(1) (2006), pages 42–68.
- [Se1] Jean-Pierre Serre, Propriétés galoisiennes des points d’ordre fini des courbes elliptiques. *Invent. Math.* 15 (1972), no. 4, 259–331.
- [Se2] Jean-Pierre Serre, Sur les représentations modulaires de degré 2 de  $\text{Gal}(\bar{\mathbf{Q}}/\mathbf{Q})$ . *Duke Math. J.* 54 (1987), no. 1, 179–230.
- [Co] Alina Carmen Cojocaru, On the surjectivity of the Galois representations associated to non-CM elliptic curves. With an appendix by Ernst Kani. *Canad. Math. Bull.* 48 (2005), no. 1, 16–31.
- [Serre72] Serre. Propriétés galoisiennes des points d’ordre fini des courbes elliptiques. *Inventiones mathematicae*, 1972.
- [Sutherland12] Sutherland. A local-global principle for rational isogenies of prime degree. *Journal de Théorie des Nombres de Bordeaux*, 2012.
- [M78] B. Mazur. Rational Isogenies of Prime Degree. *Inventiones mathematicae* 44,129–162 (1978).
- [MTT] B. Mazur, J. Tate, and J. Teitelbaum, On  $p$ -adic analogues of the conjectures of Birch and Swinnerton-Dyer, *Inventiones mathematicae* 84, (1986), 1–48.
- [BP] Dominique Bernardi and Bernadette Perrin-Riou, Variante  $p$ -adique de la conjecture de Birch et Swinnerton-Dyer (le cas supersingulier), *C. R. Acad. Sci. Paris, Sér I. Math.*, 317 (1993), no. 3, 227–232.

- [Ka] Kayuza Kato,  $p$ -adic Hodge theory and values of zeta functions of modular forms, *Cohomologies  $p$ -adiques et applications arithmétiques III*, Astérisque vol 295, SMF, Paris, 2004.
- [Gri] G. Grigorov, Kato's Euler System and the Main Conjecture, Harvard Ph.D. Thesis (2005).
- [GJPST] G. Grigorov, A. Jorza, S. Patrikis, W. A. Stein, and C. Tarniță, Computational verification of the Birch and Swinnerton-Dyer conjecture for individual elliptic curves, *Math. Comp.* 78 (2009), 2397-2425.
- [SW] William Stein and Christian Wuthrich, Algorithms for the Arithmetic of Elliptic Curves using Iwasawa Theory *Mathematics of Computation* 82 (2013), 1757-1792.
- [Wu] Christian Wuthrich, On the integrality of modular symbols and Kato's Euler system for elliptic curves. *Doc. Math.* 19 (2014), 381-402.
- [SU] Christopher Skinner and Eric Urban, The Iwasawa main conjectures for  $GL_2$ . *Invent. Math.* 195 (2014), no. 1, 1-277.
- [Col] Pierre Colmez, Invariant  $\mathcal{L}$  et derivees de valeurs propres de Frobenius, preprint, 2004.
- [Wer] Annette Werner, Local heights on abelian varieties and rigid analytic uniformization, *Doc. Math.* 3 (1998), 301-319.
- [CT] J. E. Cremona and T. Thongjunthug, The Complex AGM, periods of elliptic curves over  $\mathbb{C}$  and complex elliptic logarithms. *Journal of Number Theory* Volume 133, Issue 8, August 2013, pages 2813-2841.
- [T] T. Thongjunthug, Computing a lower bound for the canonical height on elliptic curves over number fields, *Math. Comp.* 79 (2010), pages 2431-2449.
- [MaTaTe] B. Mazur, J. Tate, and J. Teitelbaum, On  $p$ -adic analogues of the conjectures of Birch and Swinnerton-Dyer, *Inventiones mathematicae* 84, (1986), 1-48.
- [Crem97] John Cremona, Algorithms for modular elliptic curves, Cambridge University Press, 1997.
- [StWu] William Stein and Christian Wuthrich, Algorithms for the Arithmetic of Elliptic Curves using Iwasawa Theory, *Mathematics of Computation* 82 (2013), 1757-1792.
- [SteinToward] Stein, "Toward a Generalization of the Gross-Zagier Conjecture", *Int Math Res Notices* (2011), doi:10.1093/imrn/rnq075
- [LY2001] K. Lauter and T. Yang, "Computing genus 2 curves from invariants on the Hilbert moduli space", *Journal of Number Theory* 131 (2011), pages 936 - 958
- [M1991] J.-F. Mestre, "Construction de courbes de genre 2 a partir de leurs modules", in *Effective methods in algebraic geometry* (Castiglione, 1990), volume 94 of *Progr. Math.*, pages 313 - 334
- [W1999] P. van Wamelen, Pari-GP code, section "thecubic" <https://www.math.lsu.edu/~wamelen/Genus2/FindCurve/igusa2curve.gp>
- [Ked2001] Kedlaya, K., "Counting points on hyperelliptic curves using Monsky-Washnitzer cohomology", *J. Ramanujan Math. Soc.* 16 (2001) no 4, 323-338
- [Edix] Edixhoven, B., "Point counting after Kedlaya", EIDMA-Stieltjes graduate course, Lieden (lecture notes?).
- [M] Mestre, Jean-Francois. *Construction de courbes de genre 2 a partir de leurs modules*. *Effective methods in algebraic geometry* (Castiglione, 1990), 313-334, *Progr. Math.*, 94, Birkhauser Boston, Boston, MA, 1991.
- [I] Igusa, Jun-ichi. *Arithmetic variety of moduli for genus two*. *Ann. of Math.* (2) 72 1960 612-649.
- [K] Kohel, David. ECHIDNA: Databases for Elliptic Curves and Higher Dimensional Analogues. Available at <http://echidna.maths.usyd.edu.au/~kohel/dbs/>
- [W] van Wamelen, Paul. *Examples of genus two CM curves defined over the rationals*. *Math. Comp.* 68 (1999), no. 225, 307-320.



## PYTHON MODULE INDEX

### i

`sage.interfaces.genus2reduction`, 679

### S

`sage.schemes.curves.affine_curve`, 5  
`sage.schemes.curves.constructor`, 1  
`sage.schemes.curves.curve`, 43  
`sage.schemes.curves.point`, 49  
`sage.schemes.curves.projective_curve`, 23  
`sage.schemes.elliptic_curves.cm`, 443  
`sage.schemes.elliptic_curves.constructor`, 91  
`sage.schemes.elliptic_curves.descent_two_isogeny`, 582  
`sage.schemes.elliptic_curves.ec_database`, 341  
`sage.schemes.elliptic_curves.ell_curve_isogeny`, 202  
`sage.schemes.elliptic_curves.ell_egros`, 584  
`sage.schemes.elliptic_curves.ell_field`, 164  
`sage.schemes.elliptic_curves.ell_finite_field`, 177  
`sage.schemes.elliptic_curves.ell_generic`, 140  
`sage.schemes.elliptic_curves.ell_local_data`, 448  
`sage.schemes.elliptic_curves.ell_modular_symbols`, 501  
`sage.schemes.elliptic_curves.ell_number_field`, 342  
`sage.schemes.elliptic_curves.ell_padic_field`, 589  
`sage.schemes.elliptic_curves.ell_point`, 108  
`sage.schemes.elliptic_curves.ell_rational_field`, 253  
`sage.schemes.elliptic_curves.ell_tate_curve`, 457  
`sage.schemes.elliptic_curves.ell_torsion`, 408  
`sage.schemes.elliptic_curves.ell_wp`, 474  
`sage.schemes.elliptic_curves.formal_group`, 195  
`sage.schemes.elliptic_curves.gal_reps`, 411  
`sage.schemes.elliptic_curves.gal_reps_number_field`, 422  
`sage.schemes.elliptic_curves.gp_simon`, 589  
`sage.schemes.elliptic_curves.heegner`, 514  
`sage.schemes.elliptic_curves.height`, 389  
`sage.schemes.elliptic_curves.isogeny_class`, 427  
`sage.schemes.elliptic_curves.isogeny_small_degree`, 231  
`sage.schemes.elliptic_curves.jacobian`, 106  
`sage.schemes.elliptic_curves.kodaira_symbol`, 456

`sage.schemes.elliptic_curves.lseries_ell`, 506  
`sage.schemes.elliptic_curves.mod5family`, 590  
`sage.schemes.elliptic_curves.modular_parametrization`, 499  
`sage.schemes.elliptic_curves.padic_lseries`, 568  
`sage.schemes.elliptic_curves.padics`, 461  
`sage.schemes.elliptic_curves.period_lattice`, 477  
`sage.schemes.elliptic_curves.period_lattice_region`, 495  
`sage.schemes.elliptic_curves.saturation`, 406  
`sage.schemes.elliptic_curves.sha_tate`, 432  
`sage.schemes.elliptic_curves.weierstrass_morphism`, 200  
`sage.schemes.elliptic_curves.weierstrass_transform`, 590  
`sage.schemes.hyperelliptic_curves.constructor`, 595  
`sage.schemes.hyperelliptic_curves.hypellfrob`, 663  
`sage.schemes.hyperelliptic_curves.hyperelliptic_finite_field`, 603  
`sage.schemes.hyperelliptic_curves.hyperelliptic_g2_finite_field`, 674  
`sage.schemes.hyperelliptic_curves.hyperelliptic_g2_generic`, 672  
`sage.schemes.hyperelliptic_curves.hyperelliptic_g2_padic_field`, 674  
`sage.schemes.hyperelliptic_curves.hyperelliptic_g2_rational_field`, 674  
`sage.schemes.hyperelliptic_curves.hyperelliptic_generic`, 597  
`sage.schemes.hyperelliptic_curves.hyperelliptic_padic_field`, 617  
`sage.schemes.hyperelliptic_curves.hyperelliptic_rational_field`, 633  
`sage.schemes.hyperelliptic_curves.invariants`, 675  
`sage.schemes.hyperelliptic_curves.jacobian_g2`, 666  
`sage.schemes.hyperelliptic_curves.jacobian_generic`, 664  
`sage.schemes.hyperelliptic_curves.jacobian_homset`, 666  
`sage.schemes.hyperelliptic_curves.jacobian_morphism`, 667  
`sage.schemes.hyperelliptic_curves.kummer_surface`, 679  
`sage.schemes.hyperelliptic_curves.mestre`, 633  
`sage.schemes.hyperelliptic_curves.monsky_washnitzer`, 637  
`sage.schemes.jacobians.abstract_jacobian`, 87  
`sage.schemes.plane_conics.con_field`, 57  
`sage.schemes.plane_conics.con_finite_field`, 79  
`sage.schemes.plane_conics.con_number_field`, 71  
`sage.schemes.plane_conics.con_prime_finite_field`, 81  
`sage.schemes.plane_conics.con_rational_field`, 75  
`sage.schemes.plane_conics.con_rational_function_field`, 83  
`sage.schemes.plane_conics.constructor`, 55  
`sage.schemes.plane_quartics.quartic_constructor`, 89  
`sage.schemes.plane_quartics.quartic_generic`, 89



## A

- `a1()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 141
- `a2()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 141
- `a3()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 141
- `a4()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 141
- `a6()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 142
- `a_invariants()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 142
- `a_number()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 605
- `abelian_group()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 178
- `abelian_variety()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 258
- `absolute_degree()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 552
- `absolute_igusa_invariants_kohel()` (in module sage.schemes.hyperelliptic\_curves.invariants), 675
- `absolute_igusa_invariants_kohel()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic method), 672
- `absolute_igusa_invariants_wamelen()` (in module sage.schemes.hyperelliptic\_curves.invariants), 676
- `absolute_igusa_invariants_wamelen()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic method), 672
- `additive_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 111
- `additive_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_finite\_field method), 123
- `additive_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 127
- `adjusted_prec()` (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 654
- `affine_patch()` (sage.schemes.curves.projective\_curve.ProjectiveCurve method), 24
- `AffineCurve` (class in sage.schemes.curves.affine\_curve), 5
- `AffineCurvePoint_field` (class in sage.schemes.curves.point), 49
- `AffinePlaneCurve` (class in sage.schemes.curves.affine\_curve), 14
- `AffinePlaneCurve_finite_field` (class in sage.schemes.curves.affine\_curve), 20
- `AffinePlaneCurve_prime_finite_field` (class in sage.schemes.curves.affine\_curve), 21
- `AffinePlaneCurvePoint_field` (class in sage.schemes.curves.point), 50
- `AffinePlaneCurvePoint_finite_field` (class in sage.schemes.curves.point), 51
- `ainvs()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 142
- `alpha()` (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphismQuadraticForm method), 517
- `alpha()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 392
- `alpha()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseries method), 570
- `an()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 259
- `an()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 434
- `an_numerical()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 436

`an_padic()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 437  
`analytic_rank()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 259  
`analytic_rank_upper_bound()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 260  
`anlist()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 263  
`antilogarithm()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 263  
`ap()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 264  
`aplist()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 264  
`archimedean_local_height()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 128  
`archimedian_local_height()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 129  
`are_projectively_equivalent()` (in module sage.schemes.elliptic\_curves.constructor), 104  
`arithmetic_genus()` (sage.schemes.curves.projective\_curve.ProjectiveCurve method), 24  
`arithmetic_genus()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 28  
`at1()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 507  
`ate_pairing()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 111  
`atkin_lehner_act()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnX0N method), 529  
`automorphisms()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 143

## B

`B()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 389  
`b2()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 143  
`b4()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 143  
`b6()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 144  
`b8()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 144  
`b_invariants()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 144  
`bad_reduction_type()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 450  
`base_extend()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 144  
`base_extend()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 343  
`base_extend()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 598  
`base_extend()` (sage.schemes.hyperelliptic\_curves.jacobian\_homset.JacobianHomset\_divisor\_classes method), 667  
`base_extend()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 642  
`base_extend()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 652  
`base_extend()` (sage.schemes.jacobians.abstract\_jacobian.Jacobian\_generic method), 87  
`base_extend()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 57  
`base_field()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 164  
`base_field()` (sage.schemes.elliptic\_curves.heegner.GaloisGroup method), 519  
`base_field()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 392  
`base_ring()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 145  
`base_ring()` (sage.schemes.elliptic\_curves.ell\_modular\_symbols.ModularSymbol method), 502  
`baseWI` (class in sage.schemes.elliptic\_curves.weierstrass\_morphism), 201  
`basis()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 479  
`basis_matrix()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 480  
`bernardi_sigma_function()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 579  
`beta()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 546  
`betas()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc\_cond method), 534  
`blowup()` (sage.schemes.curves.affine\_curve.AffineCurve method), 5  
`border()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 495  
`bound()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 438

`bound_kato()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 438  
`bound_kolyvagin()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 439  
`brandt_module()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 536

## C

`c4()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 145  
`c6()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 145  
`c_invariants()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 145  
`cache_point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 57  
`cantor_composition()` (in module sage.schemes.hyperelliptic\_curves.jacobian\_morphism), 669  
`cantor_composition_simple()` (in module sage.schemes.hyperelliptic\_curves.jacobian\_morphism), 670  
`cantor_reduction()` (in module sage.schemes.hyperelliptic\_curves.jacobian\_morphism), 671  
`cantor_reduction_simple()` (in module sage.schemes.hyperelliptic\_curves.jacobian\_morphism), 671  
`cardinality()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 180  
`cardinality()` (sage.schemes.elliptic\_curves.heegner.GaloisGroup method), 519  
`cardinality()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 606  
`cardinality_bsgs()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 181  
`cardinality_exhaustive()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 181  
`cardinality_exhaustive()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 606  
`cardinality_hypellfrob()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 606  
`cardinality_pari()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 182  
`Cartier_matrix()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 604  
`change_ring()` (sage.schemes.curves.curve.Curve\_generic method), 43  
`change_ring()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 146  
`change_ring()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 598  
`change_ring()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 643  
`change_ring()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientElement method), 649  
`change_ring()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 652  
`change_ring()` (sage.schemes.jacobians.abstract\_jacobian.Jacobian\_generic method), 87  
`change_weierstrass_model()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 146  
`check_prime()` (in module sage.schemes.elliptic\_curves.ell\_local\_data), 455  
`chord_and_tangent()` (in module sage.schemes.elliptic\_curves.constructor), 104  
`class_number()` (in module sage.schemes.elliptic\_curves.heegner), 556  
`clebsch_invariants()` (in module sage.schemes.hyperelliptic\_curves.invariants), 676  
`clebsch_invariants()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic method), 673  
`clebsch_to_igusa()` (in module sage.schemes.hyperelliptic\_curves.invariants), 676  
`cm_discriminant()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 344  
`cm_discriminant()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 264  
`cm_j_invariants()` (in module sage.schemes.elliptic\_curves.cm), 443  
`cm_j_invariants_and_orders()` (in module sage.schemes.elliptic\_curves.cm), 443  
`cm_orders()` (in module sage.schemes.elliptic\_curves.cm), 444  
`codomain()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 546

`coeff()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferential method), 637

`coefficients()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 58

`coefficients_from_j()` (in module sage.schemes.elliptic\_curves.constructor), 105

`coefficients_from_Weierstrass_polynomial()` (in module sage.schemes.elliptic\_curves.constructor), 104

`coeffs()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferential method), 638

`coeffs()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialCubicQuotientRingElement method), 648

`coeffs()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientElement method), 649

`coleman_integral()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 618

`coleman_integral()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferential method), 638

`coleman_integral_from_weierstrass_via_boundary()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 622

`coleman_integral_P_to_S()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 621

`coleman_integral_S_to_Q()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 621

`coleman_integrals_on_basis()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 623

`coleman_integrals_on_basis_hyperelliptic()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 624

`complex_area()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 481

`complex_conjugation()` (sage.schemes.elliptic\_curves.heegner.GaloisGroup method), 520

`complex_intersection_is_empty()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 392

`compute_codomain_formula()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 220

`compute_codomain_kohel()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 220

`compute_intermediate_curves()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 221

`compute_isogeny_kernel_polynomial()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 222

`compute_isogeny_starks()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 223

`compute_sequence_of_maps()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 224

`compute_vw_kohel_even_deg1()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 226

`compute_vw_kohel_even_deg3()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 226

`compute_vw_kohel_odd()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 227

`compute_wp_fast()` (in module sage.schemes.elliptic\_curves.ell\_wp), 475

`compute_wp_pari()` (in module sage.schemes.elliptic\_curves.ell\_wp), 475

`compute_wp_quadratic()` (in module sage.schemes.elliptic\_curves.ell\_wp), 475

`conductor()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 344

`conductor()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 265

`conductor()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoint method), 521

`conductor()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc\_cond method), 534

`conductor()` (sage.schemes.elliptic\_curves.heegner.KolyvaginCohomologyClass method), 547

`conductor()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 553

`conductor_valuation()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 450

`congruence_number()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 265

`Conic()` (in module sage.schemes.plane\_conics.constructor), 55

`conjugate()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 546

`conjugates_over_K()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 523

`contract()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 496

`coordinates()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 481

`copy()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC\_NumberField method), 430

`copy()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC\_Rational method), 431  
`count_points()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 182  
`count_points()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 607  
`count_points()` (sage.schemes.plane\_conics.con\_finite\_field.ProjectiveConic\_finite\_field method), 79  
`count_points_exhaustive()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 608  
`count_points_frobenius_polynomial()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 609  
`count_points_hypellfrob()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 609  
`count_points_matrix_traces()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 610  
`CPS_height_bound()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 254  
`create_element()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialCubicQuotientRing method), 647  
`create_key_and_extra_args()` (sage.schemes.elliptic\_curves.constructor.EllipticCurveFactory method), 93  
`create_object()` (sage.schemes.elliptic\_curves.constructor.EllipticCurveFactory method), 95  
`cremona_curves()` (in module sage.schemes.elliptic\_curves.ell\_rational\_field), 339  
`cremona_label()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 266  
`cremona_optimal_curves()` (in module sage.schemes.elliptic\_curves.ell\_rational\_field), 339  
`Curve()` (in module sage.schemes.curves.constructor), 1  
`curve()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 114  
`curve()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 458  
`curve()` (sage.schemes.elliptic\_curves.ell\_torsion.EllipticCurveTorsionSubgroup method), 410  
`curve()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 195  
`curve()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 523  
`curve()` (sage.schemes.elliptic\_curves.heegner.KolyvaginPoint method), 549  
`curve()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 393  
`curve()` (sage.schemes.elliptic\_curves.modular\_parametrization.ModularParameterization method), 499  
`curve()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 482  
`curve()` (sage.schemes.hyperelliptic\_curves.jacobian\_homset.JacobianHomset\_divisor\_classes method), 667  
`curve()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 652  
`curve()` (sage.schemes.jacobians.abstract\_jacobian.Jacobian\_generic method), 88  
`Curve_generic` (class in sage.schemes.curves.curve), 43  
`curve_key()` (in module sage.schemes.elliptic\_curves.ell\_egros), 585  
`curve_over_ram_extn()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 626  
`cyclic_subideal_p1()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 536

## D

`data` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion attribute), 496  
`database_attributes()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 267  
`database_curve()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 267  
`DE()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 390  
`defining_polynomial()` (sage.schemes.curves.curve.Curve\_generic method), 43  
`deg_one_primes_iter()` (in module sage.schemes.elliptic\_curves.gal\_reps\_number\_field), 426  
`degree()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 29  
`degree()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 209  
`degree()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 643  
`degree()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 652



`degree_over_H()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 553  
`degree_over_K()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 554  
`degree_over_Q()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 554  
`deriv_at1()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 508  
`derivative_matrix()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 58  
`descend_to()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 164  
`determinant()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 58  
`diagonal_matrix()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 59  
`diagonalization()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 59  
`diff()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientElement method), 651  
`differential()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 195  
`differential_operator()` (in module sage.schemes.hyperelliptic\_curves.invariants), 677  
`diffsymb()` (in module sage.schemes.hyperelliptic\_curves.invariants), 677  
`diffxy()` (in module sage.schemes.hyperelliptic\_curves.invariants), 677  
`dimension()` (sage.schemes.hyperelliptic\_curves.jacobian\_generic.HyperellipticJacobian\_generic method), 666  
`dimension()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 643  
`discrete_log()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_finite\_field method), 125  
`discriminant()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 146  
`discriminant()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoint method), 521  
`discriminant()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc method), 532  
`discriminant_of_K()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 554  
`discriminant_valuation()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 451  
`discriminants()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level method), 531  
`discriminants_with_bounded_class_number()` (in module sage.schemes.elliptic\_curves.cm), 445  
`division_field()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 345  
`division_points()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 114  
`division_polynomial()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 147  
`division_polynomial_0()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 148  
`divisor()` (sage.schemes.curves.curve.Curve\_generic method), 44  
`divisor_group()` (sage.schemes.curves.curve.Curve\_generic method), 44  
`divisor_of_function()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 14  
`divisor_of_function()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 29  
`divisors_to_string()` (in module sage.interfaces.genus2reduction), 683  
`dokchitser()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 509  
`domain()` (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphism method), 516  
`domain()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 546  
`domain_conductor()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 547  
`domain_gen()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 547  
`Dp_valued_height()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 577  
`Dp_valued_regulator()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 578  
`Dp_valued_series()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 578  
`ds()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 496  
`dual()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 209

## E

`E2()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 457  
`e_log_RC()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 482  
`e_p()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 393  
`egros_from_j()` (in module sage.schemes.elliptic\_curves.ell\_egros), 586

egros\_from\_j\_0() (in module sage.schemes.elliptic\_curves.ell\_egros), 586  
 egros\_from\_j\_1728() (in module sage.schemes.elliptic\_curves.ell\_egros), 587  
 egros\_from\_jlist() (in module sage.schemes.elliptic\_curves.ell\_egros), 587  
 egros\_get\_j() (in module sage.schemes.elliptic\_curves.ell\_egros), 588  
 ei() (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 484  
 ell() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 536  
 ell\_heegner\_discriminants() (in module sage.schemes.elliptic\_curves.heegner), 556  
 ell\_heegner\_discriminants\_list() (in module sage.schemes.elliptic\_curves.heegner), 556  
 ell\_heegner\_point() (in module sage.schemes.elliptic\_curves.heegner), 556  
 elliptic\_curve() (sage.schemes.elliptic\_curves.ell\_modular\_symbols.ModularSymbol method), 502  
 elliptic\_curve() (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 412  
 elliptic\_curve() (sage.schemes.elliptic\_curves.gal\_reps\_number\_field.GaloisRepresentation method), 423  
 elliptic\_curve() (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 510  
 elliptic\_curve() (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseries method), 570  
 elliptic\_curve\_congruence\_graph() (in module sage.schemes.elliptic\_curves.ell\_rational\_field), 340  
 elliptic\_exponential() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 267  
 elliptic\_exponential() (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 484  
 elliptic\_logarithm() (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 129  
 elliptic\_logarithm() (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 486  
 EllipticCurve\_field (class in sage.schemes.elliptic\_curves.ell\_field), 164  
 EllipticCurve\_finite\_field (class in sage.schemes.elliptic\_curves.ell\_finite\_field), 177  
 EllipticCurve\_from\_c4c6() (in module sage.schemes.elliptic\_curves.constructor), 95  
 EllipticCurve\_from\_cubic() (in module sage.schemes.elliptic\_curves.constructor), 96  
 EllipticCurve\_from\_j() (in module sage.schemes.elliptic\_curves.constructor), 101  
 EllipticCurve\_from\_plane\_curve() (in module sage.schemes.elliptic\_curves.constructor), 102  
 EllipticCurve\_from\_Weierstrass\_polynomial() (in module sage.schemes.elliptic\_curves.constructor), 95  
 EllipticCurve\_generic (class in sage.schemes.elliptic\_curves.ell\_generic), 141  
 EllipticCurve\_number\_field (class in sage.schemes.elliptic\_curves.ell\_number\_field), 343  
 EllipticCurve\_padic\_field (class in sage.schemes.elliptic\_curves.ell\_padic\_field), 589  
 EllipticCurve\_rational\_field (class in sage.schemes.elliptic\_curves.ell\_rational\_field), 254  
 EllipticCurveCanonicalHeight (class in sage.schemes.elliptic\_curves.height), 389  
 EllipticCurveFactory (class in sage.schemes.elliptic\_curves.constructor), 91  
 EllipticCurveFormalGroup (class in sage.schemes.elliptic\_curves.formal\_group), 195  
 EllipticCurveIsogeny (class in sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 203  
 EllipticCurveLocalData (class in sage.schemes.elliptic\_curves.ell\_local\_data), 449  
 EllipticCurvePoint (class in sage.schemes.elliptic\_curves.ell\_point), 110  
 EllipticCurvePoint\_field (class in sage.schemes.elliptic\_curves.ell\_point), 110  
 EllipticCurvePoint\_finite\_field (class in sage.schemes.elliptic\_curves.ell\_point), 123  
 EllipticCurvePoint\_number\_field (class in sage.schemes.elliptic\_curves.ell\_point), 127  
 EllipticCurves (class in sage.schemes.elliptic\_curves.ec\_database), 341  
 EllipticCurves\_with\_good\_reduction\_outside\_S() (in module sage.schemes.elliptic\_curves.constructor), 102  
 EllipticCurveTorsionSubgroup (class in sage.schemes.elliptic\_curves.ell\_torsion), 408  
 eps() (in module sage.schemes.elliptic\_curves.height), 404  
 eval\_modular\_form() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 269  
 excellent\_position() (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 29  
 expand() (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 496  
 extended\_agm\_iteration() (in module sage.schemes.elliptic\_curves.period\_lattice), 493  
 extract\_pow\_y() (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 639  
 extract\_pow\_y() (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.SpecialHyperellipticQuotientElement

method), 651

## F

field() (sage.schemes.elliptic\_curves.heegner.GaloisGroup method), 520

fill\_isogeny\_matrix() (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 227

find\_char\_zero\_weier\_point() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 626

find\_point() (sage.schemes.plane\_conics.con\_rational\_function\_field.ProjectiveConic\_rational\_function\_field method), 83

finite\_endpoints() (sage.schemes.elliptic\_curves.height.UnionOfIntervals method), 402

fk\_intervals() (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 394

formal() (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 211

formal() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 150

formal\_group() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 150

Fricke\_module() (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 231

Fricke\_polynomial() (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 232

frob\_basis\_elements() (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 644

frob\_invariant\_differential() (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 644

frob\_Q() (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 644

frobenius() (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 182

frobenius() (sage.schemes.elliptic\_curves.ell\_padic\_field.EllipticCurve\_padic\_field method), 589

frobenius() (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 579

frobenius() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 626

frobenius\_expansion\_by\_newton() (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 654

frobenius\_expansion\_by\_series() (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 655

frobenius\_matrix() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 610

frobenius\_matrix\_hypellfrob() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 611

frobenius\_order() (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 183

frobenius\_polynomial() (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 183

frobenius\_polynomial() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 612

frobenius\_polynomial\_cardinalities() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 613

frobenius\_polynomial\_matrix() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 614

frobenius\_polynomial\_pari() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 614

full (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion attribute), 497

full\_p\_saturation() (in module sage.schemes.elliptic\_curves.saturation), 406

fundamental\_group() (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 15

fundamental\_group() (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 31

## G

galois\_group() (sage.schemes.elliptic\_curves.heegner.RingClassField method), 554

galois\_group\_over\_hilbert\_class\_field() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 537

galois\_group\_over\_quadratic\_field() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 537



`galois_orbit_over_K()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnX0N method), 529  
`galois_representation()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 347  
`galois_representation()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 269  
`GaloisAutomorphism` (class in sage.schemes.elliptic\_curves.heegner), 516  
`GaloisAutomorphismComplexConjugation` (class in sage.schemes.elliptic\_curves.heegner), 516  
`GaloisAutomorphismQuadraticForm` (class in sage.schemes.elliptic\_curves.heegner), 517  
`GaloisGroup` (class in sage.schemes.elliptic\_curves.heegner), 518  
`GaloisRepresentation` (class in sage.schemes.elliptic\_curves.gal\_reps), 412  
`GaloisRepresentation` (class in sage.schemes.elliptic\_curves.gal\_reps\_number\_field), 423  
`gen()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 150  
`gens()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 184  
`gens()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 151  
`gens()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 348  
`gens()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 269  
`gens()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialCubicQuotientRing method), 647  
`gens()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 653  
`gens()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 60  
`gens_certain()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 270  
`gens_quadratic()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 349  
`genus()` (sage.schemes.curves.curve.Curve\_generic method), 44  
`genus()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 165  
`genus()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 598  
`genus()` (sage.schemes.plane\_quartics.quartic\_generic.QuarticCurve\_generic method), 89  
`Genus2reduction` (class in sage.interfaces.genus2reduction), 679  
`geometric_genus()` (sage.schemes.curves.curve.Curve\_generic method), 44  
`get_boundary_point()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 627  
`get_post_isomorphism()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 211  
`get_pre_isomorphism()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 212  
`global_integral_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 350  
`global_integral_model()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 271  
`global_minimal_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 351  
`global_minimality_class()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 353  
`graph()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC method), 427  
`group_law()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 196

## H

`has_additive_reduction()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 451  
`has_additive_reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 353  
`has_bad_reduction()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 451  
`has_bad_reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 354  
`has_cm()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 354  
`has_cm()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 271  
`has_finite_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 116  
`has_finite_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_finite\_field method), 125  
`has_finite_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 131  
`has_global_minimal_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 355  
`has_good_reduction()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 451  
`has_good_reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 355

`has_good_reduction()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 131

`has_good_reduction_outside_S()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 271

`has_infinite_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 116

`has_infinite_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 132

`has_multiplicative_reduction()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 452

`has_multiplicative_reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 356

`has_nonsplit_multiplicative_reduction()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 452

`has_nonsplit_multiplicative_reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 356

`has_odd_degree_model()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 598

`has_rational_cm()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 356

`has_rational_cm()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 272

`has_rational_point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 61

`has_rational_point()` (sage.schemes.plane\_conics.con\_finite\_field.ProjectiveConic\_finite\_field method), 79

`has_rational_point()` (sage.schemes.plane\_conics.con\_number\_field.ProjectiveConic\_number\_field method), 71

`has_rational_point()` (sage.schemes.plane\_conics.con\_rational\_field.ProjectiveConic\_rational\_field method), 75

`has_rational_point()` (sage.schemes.plane\_conics.con\_rational\_function\_field.ProjectiveConic\_rational\_function\_field method), 84

`has_singular_point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 61

`has_split_multiplicative_reduction()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 452

`has_split_multiplicative_reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 358

`Hasse_bounds()` (in module sage.schemes.curves.projective\_curve), 23

`hasse_invariant()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 165

`Hasse_Witt()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 604

`heegner_conductors()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 537

`heegner_discriminants()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 273

`heegner_discriminants()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 538

`heegner_discriminants_list()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 273

`heegner_divisor()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 538

`heegner_index()` (in module sage.schemes.elliptic\_curves.heegner), 557

`heegner_index()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 273

`heegner_index_bound()` (in module sage.schemes.elliptic\_curves.heegner), 559

`heegner_index_bound()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 275

`heegner_point()` (in module sage.schemes.elliptic\_curves.heegner), 560

`heegner_point()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 275

`heegner_point()` (sage.schemes.elliptic\_curves.heegner.KolyvaginCohomologyClass method), 548

`heegner_point()` (sage.schemes.elliptic\_curves.heegner.KolyvaginPoint method), 549

`heegner_point_height()` (in module sage.schemes.elliptic\_curves.heegner), 560

`heegner_point_height()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 276

`heegner_point_on_X0N()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 524

`heegner_points()` (in module sage.schemes.elliptic\_curves.heegner), 561

`heegner_sha_an()` (in module sage.schemes.elliptic\_curves.heegner), 561

`heegner_sha_an()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 277

[HeegnerPoint](#) (class in `sage.schemes.elliptic_curves.heegner`), [521](#)  
[HeegnerPointOnEllipticCurve](#) (class in `sage.schemes.elliptic_curves.heegner`), [523](#)  
[HeegnerPointOnX0N](#) (class in `sage.schemes.elliptic_curves.heegner`), [528](#)  
[HeegnerPoints](#) (class in `sage.schemes.elliptic_curves.heegner`), [531](#)  
[HeegnerPoints\\_level](#) (class in `sage.schemes.elliptic_curves.heegner`), [531](#)  
[HeegnerPoints\\_level\\_disc](#) (class in `sage.schemes.elliptic_curves.heegner`), [532](#)  
[HeegnerPoints\\_level\\_disc\\_cond](#) (class in `sage.schemes.elliptic_curves.heegner`), [533](#)  
[HeegnerQuatAlg](#) (class in `sage.schemes.elliptic_curves.heegner`), [536](#)  
[HeegnerQuatAlgEmbedding](#) (class in `sage.schemes.elliptic_curves.heegner`), [546](#)  
[height\(\)](#) (`sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_number_field` method), [132](#)  
[height\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [278](#)  
[height\\_function\(\)](#) (`sage.schemes.elliptic_curves.ell_number_field.EllipticCurve_number_field` method), [358](#)  
[height\\_pairing\\_matrix\(\)](#) (`sage.schemes.elliptic_curves.ell_number_field.EllipticCurve_number_field` method), [358](#)  
[helper\\_matrix\(\)](#) (in module `sage.schemes.hyperelliptic_curves.monsky_washnitzer`), [656](#)  
[helper\\_matrix\(\)](#) (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.MonskyWashnitzerDifferentialRing` method), [645](#)  
[hilbert\\_class\\_polynomial\(\)](#) (in module `sage.schemes.elliptic_curves.cm`), [446](#)  
[hom\(\)](#) (`sage.schemes.plane_conics.con_field.ProjectiveConic_field` method), [62](#)  
[hypellfrob\(\)](#) (in module `sage.schemes.hyperelliptic_curves.hypellfrob`), [663](#)  
[hyperelliptic\\_polynomials\(\)](#) (`sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic` method), [151](#)  
[hyperelliptic\\_polynomials\(\)](#) (`sage.schemes.hyperelliptic_curves.hyperelliptic_generic.HyperellipticCurve_generic` method), [599](#)  
[HyperellipticCurve\(\)](#) (in module `sage.schemes.hyperelliptic_curves.constructor`), [595](#)  
[HyperellipticCurve\\_finite\\_field](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_finite_field`), [603](#)  
[HyperellipticCurve\\_from\\_invariants\(\)](#) (in module `sage.schemes.hyperelliptic_curves.mestre`), [634](#)  
[HyperellipticCurve\\_g2\\_finite\\_field](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_g2_finite_field`), [674](#)  
[HyperellipticCurve\\_g2\\_generic](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_g2_generic`), [672](#)  
[HyperellipticCurve\\_g2\\_padic\\_field](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_g2_padic_field`), [674](#)  
[HyperellipticCurve\\_g2\\_rational\\_field](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_g2_rational_field`), [674](#)  
[HyperellipticCurve\\_generic](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_generic`), [597](#)  
[HyperellipticCurve\\_padic\\_field](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_padic_field`), [617](#)  
[HyperellipticCurve\\_rational\\_field](#) (class in `sage.schemes.hyperelliptic_curves.hyperelliptic_rational_field`), [633](#)  
[HyperellipticJacobian\\_g2](#) (class in `sage.schemes.hyperelliptic_curves.jacobian_g2`), [666](#)  
[HyperellipticJacobian\\_generic](#) (class in `sage.schemes.hyperelliptic_curves.jacobian_generic`), [664](#)

**I**

[ideal\(\)](#) (`sage.schemes.elliptic_curves.heegner.GaloisAutomorphismQuadraticForm` method), [517](#)  
[igusa\\_clebsch\\_invariants\(\)](#) (in module `sage.schemes.hyperelliptic_curves.invariants`), [678](#)  
[igusa\\_clebsch\\_invariants\(\)](#) (`sage.schemes.hyperelliptic_curves.hyperelliptic_g2_generic.HyperellipticCurve_g2_generic` method), [673](#)  
[igusa\\_to\\_clebsch\(\)](#) (in module `sage.schemes.hyperelliptic_curves.invariants`), [678](#)  
[image\\_classes\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [413](#)  
[image\\_type\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [414](#)  
[index\(\)](#) (`sage.schemes.elliptic_curves.heegner.KolyvaginPoint` method), [549](#)  
[index\(\)](#) (`sage.schemes.elliptic_curves.isogeny_class.IsogenyClass_EC` method), [428](#)  
[inf\\_max\\_abs\(\)](#) (in module `sage.schemes.elliptic_curves.height`), [404](#)  
[init\(\)](#) (in module `sage.schemes.elliptic_curves.gp_simon`), [589](#)  
[innermost\\_point\(\)](#) (`sage.schemes.elliptic_curves.period_lattice_region.PeriodicRegion` method), [497](#)  
[integral\\_model\(\)](#) (`sage.schemes.elliptic_curves.ell_number_field.EllipticCurve_number_field` method), [359](#)

`integral_model()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 279

`integral_points()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 279

`integral_points_with_bounded_mw_coeffs()` (in module sage.schemes.elliptic\_curves.ell\_rational\_field), 340

`integral_short_weierstrass_model()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 281

`integral_weierstrass_model()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 281

`integral_x_coords_in_interval()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 281

`integrate()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 639

`intersection()` (sage.schemes.elliptic\_curves.height.UnionOfIntervals class method), 402

`intersection_points()` (sage.schemes.curves.curve.Curve\_generic method), 45

`intersects_at()` (sage.schemes.curves.curve.Curve\_generic method), 45

`intervals()` (sage.schemes.elliptic\_curves.height.UnionOfIntervals method), 402

`invariant_differential()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 599

`invariant_differential()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferentialRing method), 645

`inverse()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 197

`inverse()` (sage.schemes.elliptic\_curves.weierstrass\_transform.WeierstrassTransformationWithInverse\_class method), 593

`is_cm_j_invariant()` (in module sage.schemes.elliptic\_curves.cm), 447

`is_complete_intersection()` (sage.schemes.curves.projective\_curve.ProjectiveCurve method), 25

`is_crystalline()` (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 416

`is_diagonal()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 63

`is_divisible_by()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 117

`is_EllipticCurve()` (in module sage.schemes.elliptic\_curves.ell\_generic), 164

`is_empty()` (sage.schemes.elliptic\_curves.height.UnionOfIntervals method), 403

`is_empty()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 497

`is_field()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.SpecialHyperellipticQuotientRing method), 653

`is_finite_order()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 117

`is_global_integral_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 360

`is_global_integral_model()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 281

`is_global_minimal_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 360

`is_good()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 282

`is_HyperellipticCurve()` (in module sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic), 603

`is_identity()` (sage.schemes.elliptic\_curves.weierstrass\_morphism.baseWI method), 201

`is_in_weierstrass_disc()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 628

`is_inert()` (in module sage.schemes.elliptic\_curves.heegner), 562

`is_injective()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 212

`is_integral()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 282

`is_irreducible()` (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 417

`is_isogenous()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 166

`is_isogenous()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 185

`is_isogenous()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 361

`is_isogenous()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 282

`is_isomorphic()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 151

`is_j_supersingular()` (in module sage.schemes.elliptic\_curves.ell\_finite\_field), 194

[is\\_Jacobian\(\)](#) (in module `sage.schemes.jacobians.abstract_jacobian`), [88](#)  
[is\\_kolyvagin\(\)](#) (`sage.schemes.elliptic_curves.heegner.GaloisGroup` method), [520](#)  
[is\\_kolyvagin\\_conductor\(\)](#) (in module `sage.schemes.elliptic_curves.heegner`), [562](#)  
[is\\_local\\_integral\\_model\(\)](#) (`sage.schemes.elliptic_curves.ell_number_field.EllipticCurve_number_field` method), [362](#)  
[is\\_local\\_integral\\_model\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [283](#)  
[is\\_locally\\_solvable\(\)](#) (`sage.schemes.plane_conics.con_number_field.ProjectiveConic_number_field` method), [72](#)  
[is\\_locally\\_solvable\(\)](#) (`sage.schemes.plane_conics.con_rational_field.ProjectiveConic_rational_field` method), [76](#)  
[is\\_minimal\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [283](#)  
[is\\_normalized\(\)](#) (`sage.schemes.elliptic_curves.ell_curve_isogeny.EllipticCurveIsogeny` method), [213](#)  
[is\\_odd\\_degree\(\)](#) (`sage.schemes.hyperelliptic_curves.hyperelliptic_g2_generic.HyperellipticCurve_g2_generic` method), [673](#)  
[is\\_on\\_curve\(\)](#) (`sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic` method), [152](#)  
[is\\_on\\_identity\\_component\(\)](#) (`sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_number_field` method), [136](#)  
[is\\_ordinary\(\)](#) (`sage.schemes.elliptic_curves.ell_finite_field.EllipticCurve_finite_field` method), [186](#)  
[is\\_ordinary\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [283](#)  
[is\\_ordinary\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [417](#)  
[is\\_ordinary\(\)](#) (`sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesOrdinary` method), [573](#)  
[is\\_ordinary\(\)](#) (`sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesSupersingular` method), [579](#)  
[is\\_ordinary\\_singularity\(\)](#) (`sage.schemes.curves.affine_curve.AffinePlaneCurve` method), [15](#)  
[is\\_ordinary\\_singularity\(\)](#) (`sage.schemes.curves.point.AffinePlaneCurvePoint_field` method), [50](#)  
[is\\_ordinary\\_singularity\(\)](#) (`sage.schemes.curves.point.ProjectivePlaneCurvePoint_field` method), [51](#)  
[is\\_ordinary\\_singularity\(\)](#) (`sage.schemes.curves.projective_curve.ProjectivePlaneCurve` method), [31](#)  
[is\\_p\\_integral\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [284](#)  
[is\\_p\\_minimal\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [284](#)  
[is\\_possible\\_j\(\)](#) (in module `sage.schemes.elliptic_curves.ell_egros`), [588](#)  
[is\\_potentially\\_crystalline\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [417](#)  
[is\\_potentially\\_semistable\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [418](#)  
[is\\_quadratic\\_twist\(\)](#) (`sage.schemes.elliptic_curves.ell_field.EllipticCurve_field` method), [167](#)  
[is\\_quartic\\_twist\(\)](#) (`sage.schemes.elliptic_curves.ell_field.EllipticCurve_field` method), [168](#)  
[is\\_QuarticCurve\(\)](#) (in module `sage.schemes.plane_quartics.quartic_generic`), [90](#)  
[is\\_quasi\\_unipotent\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [418](#)  
[is\\_ramified\(\)](#) (in module `sage.schemes.elliptic_curves.heegner`), [563](#)  
[is\\_real\(\)](#) (`sage.schemes.elliptic_curves.period_lattice.PeriodLattice_ell` method), [489](#)  
[is\\_rectangular\(\)](#) (`sage.schemes.elliptic_curves.period_lattice.PeriodLattice_ell` method), [489](#)  
[is\\_reducible\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [418](#)  
[is\\_same\\_disc\(\)](#) (`sage.schemes.hyperelliptic_curves.hyperelliptic_padic_field.HyperellipticCurve_padic_field` method), [628](#)  
[is\\_semistable\(\)](#) (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), [284](#)  
[is\\_semistable\(\)](#) (`sage.schemes.elliptic_curves.gal_reps.GaloisRepresentation` method), [419](#)  
[is\\_separable\(\)](#) (`sage.schemes.elliptic_curves.ell_curve_isogeny.EllipticCurveIsogeny` method), [214](#)  
[is\\_sextic\\_twist\(\)](#) (`sage.schemes.elliptic_curves.ell_field.EllipticCurve_field` method), [169](#)  
[is\\_singular\(\)](#) (`sage.schemes.curves.curve.Curve_generic` method), [46](#)  
[is\\_singular\(\)](#) (`sage.schemes.curves.point.AffineCurvePoint_field` method), [49](#)  
[is\\_singular\(\)](#) (`sage.schemes.curves.point.ProjectiveCurvePoint_field` method), [51](#)  
[is\\_singular\(\)](#) (`sage.schemes.curves.projective_curve.ProjectivePlaneCurve` method), [32](#)  
[is\\_singular\(\)](#) (`sage.schemes.hyperelliptic_curves.hyperelliptic_generic.HyperellipticCurve_generic` method), [599](#)  
[is\\_smooth\(\)](#) (`sage.schemes.hyperelliptic_curves.hyperelliptic_generic.HyperellipticCurve_generic` method), [599](#)  
[is\\_smooth\(\)](#) (`sage.schemes.plane_conics.con_field.ProjectiveConic_field` method), [63](#)  
[is\\_split\(\)](#) (in module `sage.schemes.elliptic_curves.heegner`), [563](#)  
[is\\_split\(\)](#) (`sage.schemes.elliptic_curves.ell_tate_curve.TateCurve` method), [458](#)



`is_subfield()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 555

`is_supersingular()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 186

`is_supersingular()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 285

`is_supersingular()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesOrdinary method), 573

`is_supersingular()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 579

`is_surjective()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 214

`is_surjective()` (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 419

`is_surjective()` (sage.schemes.elliptic\_curves.gal\_reps\_number\_field.GaloisRepresentation method), 423

`is_transverse()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 16

`is_transverse()` (sage.schemes.curves.point.AffinePlaneCurvePoint\_field method), 50

`is_transverse()` (sage.schemes.curves.point.ProjectivePlaneCurvePoint\_field method), 52

`is_transverse()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 33

`is_unipotent()` (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 420

`is_unramified()` (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 421

`is_weierstrass()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 628

`is_x_coord()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 152

`is_zero()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 215

`isogenies()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC method), 428

`isogenies_13_0()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 233

`isogenies_13_1728()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 235

`isogenies_2()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 236

`isogenies_3()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 237

`isogenies_5_0()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 237

`isogenies_5_1728()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 238

`isogenies_7_0()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 239

`isogenies_7_1728()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 241

`isogenies_prime_degree()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 242

`isogenies_prime_degree()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 169

`isogenies_prime_degree()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 363

`isogenies_prime_degree()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 285

`isogenies_prime_degree_general()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 244

`isogenies_prime_degree_genus_0()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 246

`isogenies_prime_degree_genus_plus_0()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 247

`isogenies_prime_degree_genus_plus_0_j0()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 249

`isogenies_prime_degree_genus_plus_0_j1728()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 251

`isogenies_sporadic_Q()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 252

`isogeny()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 172

`isogeny_bound()` (sage.schemes.elliptic\_curves.gal\_reps\_number\_field.GaloisRepresentation method), 424

`isogeny_class()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 363

`isogeny_class()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 286

`isogeny_codomain()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 174

`isogeny_codomain_from_kernel()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 228

`isogeny_degree()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 368

`isogeny_degree()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 288

`isogeny_determine_algorithm()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 228

`isogeny_graph()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 290

`IsogenyClass_EC` (class in sage.schemes.elliptic\_curves.isogeny\_class), 427

`IsogenyClass_EC_NumberField` (class in sage.schemes.elliptic\_curves.isogeny\_class), 430

`IsogenyClass_EC_Rational` (class in sage.schemes.elliptic\_curves.isogeny\_class), 430

isomorphism\_to() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 153

isomorphisms() (in module sage.schemes.elliptic\_curves.weierstrass\_morphism), 201

isomorphisms() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 153

## J

j\_invariant() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 154

Jacobian() (in module sage.schemes.elliptic\_curves.jacobian), 106

Jacobian() (in module sage.schemes.jacobians.abstract\_jacobian), 87

jacobian() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic method), 673

jacobian() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 600

Jacobian\_generic (class in sage.schemes.jacobians.abstract\_jacobian), 87

Jacobian\_of\_curve() (in module sage.schemes.elliptic\_curves.jacobian), 107

Jacobian\_of\_equation() (in module sage.schemes.elliptic\_curves.jacobian), 107

JacobianHomset\_divisor\_classes (class in sage.schemes.hyperelliptic\_curves.jacobian\_homset), 667

JacobianMorphism\_divisor\_class\_field (class in sage.schemes.hyperelliptic\_curves.jacobian\_morphism), 669

join() (sage.schemes.elliptic\_curves.height.UnionOfIntervals static method), 403

## K

kernel\_polynomial() (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 215

kodaira\_symbol() (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 453

kodaira\_symbol() (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 369

kodaira\_symbol() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 291

kodaira\_type() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 291

kodaira\_type\_old() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 291

KodairaSymbol() (in module sage.schemes.elliptic\_curves.kodaira\_symbol), 456

KodairaSymbol\_class (class in sage.schemes.elliptic\_curves.kodaira\_symbol), 456

kolyvagin\_cohomology\_class() (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 524

kolyvagin\_cohomology\_class() (sage.schemes.elliptic\_curves.heegner.KolyvaginPoint method), 549

kolyvagin\_conductors() (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc method), 533

kolyvagin\_cyclic\_subideals() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 538

kolyvagin\_generator() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 539

kolyvagin\_generators() (sage.schemes.elliptic\_curves.heegner.GaloisGroup method), 520

kolyvagin\_generators() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 540

kolyvagin\_point() (in module sage.schemes.elliptic\_curves.heegner), 564

kolyvagin\_point() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 292

kolyvagin\_point() (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 524

kolyvagin\_point() (sage.schemes.elliptic\_curves.heegner.KolyvaginCohomologyClass method), 548

kolyvagin\_point\_on\_curve() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 540

kolyvagin\_reduction\_data() (in module sage.schemes.elliptic\_curves.heegner), 564

kolyvagin\_sigma\_operator() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 540

KolyvaginCohomologyClass (class in sage.schemes.elliptic\_curves.heegner), 547

KolyvaginCohomologyClassEn (class in sage.schemes.elliptic\_curves.heegner), 548

KolyvaginPoint (class in sage.schemes.elliptic\_curves.heegner), 548

kummer\_morphism() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_g2\_generic.HyperellipticCurve\_g2\_generic method), 674

kummer\_surface() (sage.schemes.hyperelliptic\_curves.jacobian\_g2.HyperellipticJacobian\_g2 method), 666

KummerSurface (class in sage.schemes.hyperelliptic\_curves.kummer\_surface), 679

## L

`L1_vanishes()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 506

`L_invariant()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 457

`L_ratio()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 506

`label()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 292

`Lambda()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 255

`largest_fundamental_disc_with_class_number()` (in module sage.schemes.elliptic\_curves.cm), 447

`left_orders()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 542

`level()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoint method), 522

`level()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints method), 531

`level()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 542

`lift()` (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 656

`lift()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 458

`lift_of_hilbert_class_field_galois_group()` (sage.schemes.elliptic\_curves.heegner.GaloisGroup method), 521

`lift_x()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 154

`lift_x()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 600

`lml_reduce()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 369

`lmfdb_page()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 293

`local_analytic_interpolation()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 629

`local_coord()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 600

`local_coordinates()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 17

`local_coordinates()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 34

`local_coordinates_at_infinity()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 600

`local_coordinates_at_nonweierstrass()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 601

`local_coordinates_at_weierstrass()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 601

`local_data()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 371

`local_integral_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 372

`local_integral_model()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 293

`local_minimal_model()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 373

`local_obstructions()` (sage.schemes.plane\_conics.con\_number\_field.ProjectiveConic\_number\_field method), 73

`local_obstructions()` (sage.schemes.plane\_conics.con\_rational\_field.ProjectiveConic\_rational\_field method), 76

`log()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 197

`lseries()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 293

`Lseries_ell` (class in sage.schemes.elliptic\_curves.lseries\_ell), 506

`lseries_gross_zagier()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 293

## M

`make_monoid()` (in module sage.schemes.elliptic\_curves.heegner), 566

`manin_constant()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 294

`map_to_complex_numbers()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 524

`map_to_complex_numbers()` (sage.schemes.elliptic\_curves.modular\_parametrization.ModularParameterization method), 500

`map_to_curve()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnX0N method), 530

`matrix()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlgEmbedding method), 547

`matrix()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC method), 428

`matrix()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 64



`matrix_of_frobenius()` (in module `sage.schemes.elliptic_curves.padics`), 461  
`matrix_of_frobenius()` (in module `sage.schemes.hyperelliptic_curves.monsky_washnitzer`), 656  
`matrix_of_frobenius()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 294  
`matrix_of_frobenius()` (`sage.schemes.hyperelliptic_curves.hyperelliptic_rational_field.HyperellipticCurve_rational_field` method), 633  
`matrix_of_frobenius_hyperelliptic()` (in module `sage.schemes.hyperelliptic_curves.monsky_washnitzer`), 660  
`max_pow_y()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.MonskyWashnitzerDifferential` method), 639  
`max_pow_y()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientElement` method), 651  
`ME()` (`sage.schemes.elliptic_curves.height.EllipticCurveCanonicalHeight` method), 390  
`measure()` (`sage.schemes.elliptic_curves.padic_lseries.pAdicLseries` method), 570  
`Mestre_conic()` (in module `sage.schemes.hyperelliptic_curves.mestre`), 636  
`min()` (`sage.schemes.elliptic_curves.height.EllipticCurveCanonicalHeight` method), 395  
`min_gr()` (`sage.schemes.elliptic_curves.height.EllipticCurveCanonicalHeight` method), 396  
`min_on_disk()` (in module `sage.schemes.elliptic_curves.height`), 405  
`min_pow_y()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.MonskyWashnitzerDifferential` method), 640  
`min_pow_y()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientElement` method), 651  
`minimal_discriminant_ideal()` (`sage.schemes.elliptic_curves.ell_number_field.EllipticCurve_number_field` method), 373  
`minimal_model()` (`sage.schemes.elliptic_curves.ell_local_data.EllipticCurveLocalData` method), 453  
`minimal_model()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 295  
`minimal_quadratic_twist()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 296  
`mod()` (`sage.schemes.elliptic_curves.heegner.KolyvaginPoint` method), 550  
`mod5family()` (in module `sage.schemes.elliptic_curves.mod5family`), 590  
`mod5family()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 296  
`modp_dual_elliptic_curve_factor()` (`sage.schemes.elliptic_curves.heegner.HeegnerQuatAlg` method), 542  
`modp_splitting_data()` (`sage.schemes.elliptic_curves.heegner.HeegnerQuatAlg` method), 542  
`modp_splitting_map()` (`sage.schemes.elliptic_curves.heegner.HeegnerQuatAlg` method), 543  
`modular_degree()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 297  
`modular_form()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 298  
`modular_parametrization()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 299  
`modular_symbol()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 299  
`modular_symbol()` (`sage.schemes.elliptic_curves.padic_lseries.pAdicLseries` method), 571  
`modular_symbol_numerical()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 301  
`modular_symbol_space()` (in module `sage.schemes.elliptic_curves.ell_modular_symbols`), 505  
`modular_symbol_space()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 302  
`ModularParameterization` (class in `sage.schemes.elliptic_curves.modular_parametrization`), 499  
`ModularSymbol` (class in `sage.schemes.elliptic_curves.ell_modular_symbols`), 502  
`ModularSymbolECLIB` (class in `sage.schemes.elliptic_curves.ell_modular_symbols`), 502  
`ModularSymbolSage` (class in `sage.schemes.elliptic_curves.ell_modular_symbols`), 504  
`monomial()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientRing` method), 653  
`monomial_diff_coeffs()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientRing` method), 653  
`monomial_diff_coeffs_matrices()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientRing` method), 653  
`monsky_washnitzer()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialHyperellipticQuotientRing` method), 653  
`monsky_washnitzer_gens()` (`sage.schemes.hyperelliptic_curves.hyperelliptic_generic.HyperellipticCurve_generic`

method), 602

MonskyWashnitzerDifferential (class in sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 637

MonskyWashnitzerDifferentialRing (class in sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 642

MonskyWashnitzerDifferentialRing\_class (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 646

mult\_by\_n() (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 197

multiplication\_by\_m() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 157

multiplication\_by\_m\_isogeny() (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 158

multiplicity() (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 17

multiplicity() (sage.schemes.curves.point.AffinePlaneCurvePoint\_field method), 50

multiplicity() (sage.schemes.curves.point.ProjectivePlaneCurvePoint\_field method), 52

mwrnk() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 302

mwrnk\_curve() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 303

## N

n() (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 216

n() (sage.schemes.elliptic\_curves.heegner.KolyvaginCohomologyClass method), 548

nearby\_rational\_poly() (in module sage.schemes.elliptic\_curves.heegner), 566

newform() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 303

newton\_sqrt() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 630

ngens() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 304

non\_archimedean\_local\_height() (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 137

non\_minimal\_primes() (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 374

non\_surjective() (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 421

non\_surjective() (sage.schemes.elliptic\_curves.gal\_reps\_number\_field.GaloisRepresentation method), 425

nonarchimedian\_local\_height() (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 138

nonneg\_region() (in module sage.schemes.elliptic\_curves.height), 405

normalise\_periods() (in module sage.schemes.elliptic\_curves.period\_lattice), 494

normalised\_basis() (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 490

Np() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 255

numerical\_approx() (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 525

numerical\_approx() (sage.schemes.elliptic\_curves.heegner.KolyvaginPoint method), 550

## O

odd\_degree\_model() (sage.schemes.hyperelliptic\_curves.hyperelliptic\_generic.HyperellipticCurve\_generic method), 602

omega() (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 490

optimal\_curve() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 304

optimal\_embeddings() (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 544

order() (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 187

order() (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 118

order() (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_finite\_field method), 125

order() (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 138

order() (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphismComplexConjugation method), 516

order() (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphismQuadraticForm method), 518

order\_of\_vanishing() (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseries method), 572

ordinary\_model() (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 34

ordinary\_primes() (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 305

`original_curve()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 459

## P

`p1_element()` (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphismQuadraticForm method), 518

`p_primary_bound()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 440

`p_primary_order()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 442

`p_rank()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 615

`p_saturation()` (in module sage.schemes.elliptic\_curves.saturation), 407

`P_to_S()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 617

`padic_E2()` (in module sage.schemes.elliptic\_curves.padics), 462

`padic_E2()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 305

`padic_elliptic_logarithm()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 138

`padic_height()` (in module sage.schemes.elliptic\_curves.padics), 464

`padic_height()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 308

`padic_height()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 459

`padic_height_pairing_matrix()` (in module sage.schemes.elliptic\_curves.padics), 466

`padic_height_pairing_matrix()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 309

`padic_height_via_multiply()` (in module sage.schemes.elliptic\_curves.padics), 467

`padic_height_via_multiply()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 310

`padic_lseries` (in module sage.schemes.elliptic\_curves.padics), 468

`padic_lseries()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 312

`padic_regulator()` (in module sage.schemes.elliptic\_curves.padics), 470

`padic_regulator()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 313

`padic_regulator()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 459

`padic_sigma()` (in module sage.schemes.elliptic\_curves.padics), 471

`padic_sigma()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 314

`padic_sigma_truncated()` (in module sage.schemes.elliptic\_curves.padics), 473

`padic_sigma_truncated()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 316

`pAdicLseries` (class in sage.schemes.elliptic\_curves.padic\_lseries), 568

`pAdicLseriesOrdinary` (class in sage.schemes.elliptic\_curves.padic\_lseries), 573

`pAdicLseriesSupersingular` (class in sage.schemes.elliptic\_curves.padic\_lseries), 577

`parameter()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 460

`parametrisation_onto_original_curve()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 460

`parametrisation_onto_tate_curve()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 460

`parametrization()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 64

`parametrization()` (sage.schemes.plane\_conics.con\_rational\_field.ProjectiveConic\_rational\_field method), 77

`parent()` (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphism method), 516

`pari_curve()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 158

`pari_curve()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 317

`pari_mincurve()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 318

`period_lattice()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 375

`period_lattice()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 319

`PeriodicRegion` (class in sage.schemes.elliptic\_curves.period\_lattice\_region), 495

`PeriodLattice` (class in sage.schemes.elliptic\_curves.period\_lattice), 479

`PeriodLattice_ell` (class in sage.schemes.elliptic\_curves.period\_lattice), 479

`plane_projection()` (sage.schemes.curves.affine\_curve.AffineCurve method), 9

`plane_projection()` (sage.schemes.curves.projective\_curve.ProjectiveCurve method), 25

`plot()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 18

`plot()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 36

`plot()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 188

`plot()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 159

`plot()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 118

`plot()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnX0N method), 530

`plot()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc\_cond method), 534

`plot()` (sage.schemes.elliptic\_curves.heegner.KolyvaginPoint method), 551

`plot()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 498

`point()` (sage.schemes.hyperelliptic\_curves.jacobian\_generic.HyperellipticJacobian\_generic method), 666

`point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 65

`point_exact()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 526

`point_exact()` (sage.schemes.elliptic\_curves.heegner.KolyvaginPoint method), 551

`point_search()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 319

`points()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 188

`points()` (sage.schemes.elliptic\_curves.ell\_torsion.EllipticCurveTorsionSubgroup method), 410

`points()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc\_cond method), 535

`points()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 616

`pollack_stevens_modular_symbol()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 320

`poly_ring()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialCubicQuotientRing method), 648

`possible_isogeny_degrees()` (in module sage.schemes.elliptic\_curves.isogeny\_class), 431

`post_compose()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 216

`post_rescaling()` (sage.schemes.elliptic\_curves.weierstrass\_transform.WeierstrassTransformation method), 592

`power_series()` (sage.schemes.elliptic\_curves.modular\_parametrization.ModularParameterization method), 500

`power_series()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesOrdinary method), 573

`power_series()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseriesSupersingular method), 579

`pre_compose()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 216

`prime()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 454

`prime()` (sage.schemes.elliptic\_curves.ell\_tate\_curve.TateCurve method), 461

`prime()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseries method), 572

`prime()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 653

`projection()` (sage.schemes.curves.affine\_curve.AffineCurve method), 9

`projection()` (sage.schemes.curves.projective\_curve.ProjectiveCurve method), 26

`projective_closure()` (sage.schemes.curves.affine\_curve.AffineCurve method), 11

`projective_point()` (in module sage.schemes.elliptic\_curves.constructor), 105

`ProjectiveConic_field` (class in sage.schemes.plane\_conics.con\_field), 57

`ProjectiveConic_finite_field` (class in sage.schemes.plane\_conics.con\_finite\_field), 79

`ProjectiveConic_number_field` (class in sage.schemes.plane\_conics.con\_number\_field), 71

`ProjectiveConic_prime_finite_field` (class in sage.schemes.plane\_conics.con\_prime\_finite\_field), 81

`ProjectiveConic_rational_field` (class in sage.schemes.plane\_conics.con\_rational\_field), 75

`ProjectiveConic_rational_function_field` (class in sage.schemes.plane\_conics.con\_rational\_function\_field), 83

`ProjectiveCurve` (class in sage.schemes.curves.projective\_curve), 23

`ProjectiveCurvePoint_field` (class in sage.schemes.curves.point), 51

`ProjectivePlaneCurve` (class in sage.schemes.curves.projective\_curve), 28

`ProjectivePlaneCurve_finite_field` (class in sage.schemes.curves.projective\_curve), 39

`ProjectivePlaneCurve_prime_finite_field` (class in sage.schemes.curves.projective\_curve), 41

`ProjectivePlaneCurvePoint_field` (class in sage.schemes.curves.point), 51

`ProjectivePlaneCurvePoint_finite_field` (class in sage.schemes.curves.point), 53

`prove_BSD()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 320

`Psi()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 232

`psi()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 397

`Psi2()` (in module sage.schemes.elliptic\_curves.isogeny\_small\_degree), 232

## Q

`Q()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 642

`Q()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 652

`q_eigenform()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 323

`q_expansion()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 323

`qf_matrix()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC method), 429

`quadratic_field()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoint method), 522

`quadratic_field()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc method), 533

`quadratic_field()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 544

`quadratic_field()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 555

`quadratic_form()` (sage.schemes.elliptic\_curves.heegner.GaloisAutomorphismQuadraticForm method), 518

`quadratic_form()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 527

`quadratic_form()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnX0N method), 530

`quadratic_order()` (in module sage.schemes.elliptic\_curves.heegner), 566

`quadratic_order()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoint method), 522

`quadratic_transform()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 37

`quadratic_twist()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 174

`quadratic_twist()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 324

`quartic_twist()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 175

`QuarticCurve()` (in module sage.schemes.plane\_quartics.quartic\_constructor), 89

`QuarticCurve_generic` (class in sage.schemes.plane\_quartics.quartic\_generic), 89

`quaternion_algebra()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 544

## R

`ramified_primes()` (sage.schemes.elliptic\_curves.heegner.RingClassField method), 555

`random_element()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 189

`random_point()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 190

`random_rational_point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 65

`rank()` (sage.schemes.elliptic\_curves.ec\_database.EllipticCurves method), 341

`rank()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 376

`rank()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 324

`rank_bound()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 325

`rank_bounds()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 377

`rat_term_CIF()` (in module sage.schemes.elliptic\_curves.height), 406

`rational_kolyvagin_divisor()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 544

`rational_maps()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 216

`rational_parameterization()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 18

`rational_parameterization()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 37

`rational_point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 66

`rational_points()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve\_finite\_field method), 20

`rational_points()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve\_prime\_finite\_field method), 21

`rational_points()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve\_finite\_field method), 39

`rational_points()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve\_prime\_finite\_field method), 41

`rational_points()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 191

`rational_points_iterator()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve\_finite\_field method), 40

`raw()` (sage.interfaces.genus2reduction.Genus2reduction method), 681

`real_components()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 325



`real_intersection_is_empty()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 398

`real_period()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 491

`reduce()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 492

`reduce()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 640

`reduce_all()` (in module sage.schemes.hyperelliptic\_curves.monkey\_washnitzer), 661

`reduce_fast()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 640

`reduce_mod()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level method), 532

`reduce_neg_y()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 641

`reduce_neg_y_fast()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 641

`reduce_neg_y_faster()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 641

`reduce_negative()` (in module sage.schemes.hyperelliptic\_curves.monkey\_washnitzer), 661

`reduce_pos_y()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 641

`reduce_pos_y_fast()` (sage.schemes.hyperelliptic\_curves.monkey\_washnitzer.MonkeyWashnitzerDifferential method), 642

`reduce_positive()` (in module sage.schemes.hyperelliptic\_curves.monkey\_washnitzer), 662

`reduce_tau()` (in module sage.schemes.elliptic\_curves.period\_lattice), 494

`reduce_zero()` (in module sage.schemes.hyperelliptic\_curves.monkey\_washnitzer), 662

`reduced_quadratic_form()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnXON method), 530

`reducible_primes()` (sage.schemes.elliptic\_curves.gal\_reps.GaloisRepresentation method), 422

`reducible_primes()` (sage.schemes.elliptic\_curves.gal\_reps\_number\_field.GaloisRepresentation method), 426

`reduction()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 378

`reduction()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_number\_field method), 139

`reduction()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 326

`ReductionData` (class in sage.interfaces.genus2reduction), 682

`refine()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 498

`regulator()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 326

`regulator_of_points()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 378

`reorder()` (sage.schemes.elliptic\_curves.isogeny\_class.IsogenyClass\_EC method), 429

`residue_disc()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 631

`resolution_of_singularities()` (sage.schemes.curves.affine\_curve.AffineCurve method), 12

`riemann_roch_basis()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve\_prime\_finite\_field method), 21

`riemann_roch_basis()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve\_prime\_finite\_field method), 42

`riemann_surface()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 19

`riemann_surface()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 38

`right_ideals()` (sage.schemes.elliptic\_curves.heegner.HeegnerQuatAlg method), 545

`ring_class_field()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoint method), 522

`ring_class_field()` (sage.schemes.elliptic\_curves.heegner.HeegnerPoints\_level\_disc\_cond method), 535

`RingClassField` (class in sage.schemes.elliptic\_curves.heegner), 552

`root_number()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 327

`rst_transform()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 160

## S

`S()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 390

`S_integral_points()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 256

`S_to_Q()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 618

`sage.interfaces.genus2reduction` (module), 679

`sage.schemes.curves.affine_curve` (module), 5

[sage.schemes.curves.constructor \(module\)](#), 1  
[sage.schemes.curves.curve \(module\)](#), 43  
[sage.schemes.curves.point \(module\)](#), 49  
[sage.schemes.curves.projective\\_curve \(module\)](#), 23  
[sage.schemes.elliptic\\_curves.cm \(module\)](#), 443  
[sage.schemes.elliptic\\_curves.constructor \(module\)](#), 91  
[sage.schemes.elliptic\\_curves.descent\\_two\\_isogeny \(module\)](#), 582  
[sage.schemes.elliptic\\_curves.ec\\_database \(module\)](#), 341  
[sage.schemes.elliptic\\_curves.ell\\_curve\\_isogeny \(module\)](#), 202  
[sage.schemes.elliptic\\_curves.ell\\_egros \(module\)](#), 584  
[sage.schemes.elliptic\\_curves.ell\\_field \(module\)](#), 164  
[sage.schemes.elliptic\\_curves.ell\\_finite\\_field \(module\)](#), 177  
[sage.schemes.elliptic\\_curves.ell\\_generic \(module\)](#), 140  
[sage.schemes.elliptic\\_curves.ell\\_local\\_data \(module\)](#), 448  
[sage.schemes.elliptic\\_curves.ell\\_modular\\_symbols \(module\)](#), 501  
[sage.schemes.elliptic\\_curves.ell\\_number\\_field \(module\)](#), 342  
[sage.schemes.elliptic\\_curves.ell\\_padic\\_field \(module\)](#), 589  
[sage.schemes.elliptic\\_curves.ell\\_point \(module\)](#), 108  
[sage.schemes.elliptic\\_curves.ell\\_rational\\_field \(module\)](#), 253  
[sage.schemes.elliptic\\_curves.ell\\_tate\\_curve \(module\)](#), 457  
[sage.schemes.elliptic\\_curves.ell\\_torsion \(module\)](#), 408  
[sage.schemes.elliptic\\_curves.ell\\_wp \(module\)](#), 474  
[sage.schemes.elliptic\\_curves.formal\\_group \(module\)](#), 195  
[sage.schemes.elliptic\\_curves.gal\\_reps \(module\)](#), 411  
[sage.schemes.elliptic\\_curves.gal\\_reps\\_number\\_field \(module\)](#), 422  
[sage.schemes.elliptic\\_curves.gp\\_simon \(module\)](#), 589  
[sage.schemes.elliptic\\_curves.heegner \(module\)](#), 514  
[sage.schemes.elliptic\\_curves.height \(module\)](#), 389  
[sage.schemes.elliptic\\_curves.isogeny\\_class \(module\)](#), 427  
[sage.schemes.elliptic\\_curves.isogeny\\_small\\_degree \(module\)](#), 231  
[sage.schemes.elliptic\\_curves.jacobian \(module\)](#), 106  
[sage.schemes.elliptic\\_curves.kodaira\\_symbol \(module\)](#), 456  
[sage.schemes.elliptic\\_curves.lseries\\_ell \(module\)](#), 506  
[sage.schemes.elliptic\\_curves.mod5family \(module\)](#), 590  
[sage.schemes.elliptic\\_curves.modular\\_parametrization \(module\)](#), 499  
[sage.schemes.elliptic\\_curves.padic\\_lseries \(module\)](#), 568  
[sage.schemes.elliptic\\_curves.padics \(module\)](#), 461  
[sage.schemes.elliptic\\_curves.period\\_lattice \(module\)](#), 477  
[sage.schemes.elliptic\\_curves.period\\_lattice\\_region \(module\)](#), 495  
[sage.schemes.elliptic\\_curves.saturation \(module\)](#), 406  
[sage.schemes.elliptic\\_curves.sha\\_tate \(module\)](#), 432  
[sage.schemes.elliptic\\_curves.weierstrass\\_morphism \(module\)](#), 200  
[sage.schemes.elliptic\\_curves.weierstrass\\_transform \(module\)](#), 590  
[sage.schemes.hyperelliptic\\_curves.constructor \(module\)](#), 595  
[sage.schemes.hyperelliptic\\_curves.hypellfrob \(module\)](#), 663  
[sage.schemes.hyperelliptic\\_curves.hyperelliptic\\_finite\\_field \(module\)](#), 603  
[sage.schemes.hyperelliptic\\_curves.hyperelliptic\\_g2\\_finite\\_field \(module\)](#), 674  
[sage.schemes.hyperelliptic\\_curves.hyperelliptic\\_g2\\_generic \(module\)](#), 672  
[sage.schemes.hyperelliptic\\_curves.hyperelliptic\\_g2\\_padic\\_field \(module\)](#), 674  
[sage.schemes.hyperelliptic\\_curves.hyperelliptic\\_g2\\_rational\\_field \(module\)](#), 674

`sage.schemes.hyperelliptic_curves.hyperelliptic_generic` (module), 597  
`sage.schemes.hyperelliptic_curves.hyperelliptic_padic_field` (module), 617  
`sage.schemes.hyperelliptic_curves.hyperelliptic_rational_field` (module), 633  
`sage.schemes.hyperelliptic_curves.invariants` (module), 675  
`sage.schemes.hyperelliptic_curves.jacobian_g2` (module), 666  
`sage.schemes.hyperelliptic_curves.jacobian_generic` (module), 664  
`sage.schemes.hyperelliptic_curves.jacobian_homset` (module), 666  
`sage.schemes.hyperelliptic_curves.jacobian_morphism` (module), 667  
`sage.schemes.hyperelliptic_curves.kummer_surface` (module), 679  
`sage.schemes.hyperelliptic_curves.mestre` (module), 633  
`sage.schemes.hyperelliptic_curves.monsky_washnitzer` (module), 637  
`sage.schemes.jacobians.abstract_jacobian` (module), 87  
`sage.schemes.plane_conics.con_field` (module), 57  
`sage.schemes.plane_conics.con_finite_field` (module), 79  
`sage.schemes.plane_conics.con_number_field` (module), 71  
`sage.schemes.plane_conics.con_prime_finite_field` (module), 81  
`sage.schemes.plane_conics.con_rational_field` (module), 75  
`sage.schemes.plane_conics.con_rational_function_field` (module), 83  
`sage.schemes.plane_conics.constructor` (module), 55  
`sage.schemes.plane_quartics.quartic_constructor` (module), 89  
`sage.schemes.plane_quartics.quartic_generic` (module), 89  
`satisfies_heegner_hypothesis()` (in module `sage.schemes.elliptic_curves.heegner`), 567  
`satisfies_heegner_hypothesis()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 327  
`satisfies_heegner_hypothesis()` (`sage.schemes.elliptic_curves.heegner.HeegnerQuatAlg` method), 545  
`satisfies_kolyvagin_hypothesis()` (`sage.schemes.elliptic_curves.heegner.HeegnerPointOnEllipticCurve` method), 527  
`satisfies_kolyvagin_hypothesis()` (`sage.schemes.elliptic_curves.heegner.HeegnerPoints_level_disc_cond` method), 535  
`satisfies_kolyvagin_hypothesis()` (`sage.schemes.elliptic_curves.heegner.KolyvaginPoint` method), 552  
`satisfies_weak_heegner_hypothesis()` (in module `sage.schemes.elliptic_curves.heegner`), 567  
`saturation()` (`sage.schemes.elliptic_curves.ell_number_field.EllipticCurve_number_field` method), 380  
`saturation()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 328  
`scalar_multiply()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialCubicQuotientRingElement` method), 648  
`scale_curve()` (`sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic` method), 161  
`scheme()` (`sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_field` method), 118  
`scheme()` (`sage.schemes.hyperelliptic_curves.jacobian_morphism.JacobianMorphism_divisor_class_field` method), 669  
`selmer_rank()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 328  
`series()` (`sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesOrdinary` method), 575  
`series()` (`sage.schemes.elliptic_curves.padic_lseries.pAdicLseriesSupersingular` method), 580  
`set_order()` (`sage.schemes.elliptic_curves.ell_finite_field.EllipticCurve_finite_field` method), 192  
`set_order()` (`sage.schemes.elliptic_curves.ell_point.EllipticCurvePoint_field` method), 119  
`set_post_isomorphism()` (`sage.schemes.elliptic_curves.ell_curve_isogeny.EllipticCurveIsogeny` method), 217  
`set_pre_isomorphism()` (`sage.schemes.elliptic_curves.ell_curve_isogeny.EllipticCurveIsogeny` method), 217  
`sextic_twist()` (`sage.schemes.elliptic_curves.ell_field.EllipticCurve_field` method), 176  
`Sha` (class in `sage.schemes.elliptic_curves.sha_tate`), 433  
`sha()` (`sage.schemes.elliptic_curves.ell_rational_field.EllipticCurve_rational_field` method), 329  
`shift()` (`sage.schemes.hyperelliptic_curves.monsky_washnitzer.SpecialCubicQuotientRingElement` method), 648  
`short_weierstrass_model()` (`sage.schemes.elliptic_curves.ell_generic.EllipticCurve_generic` method), 161



`sigma()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 199  
`sigma()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 492  
`sign()` (sage.schemes.elliptic\_curves.ell\_modular\_symbols.ModularSymbol method), 502  
`silverman_height_bound()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 329  
`simon_two_descent()` (in module sage.schemes.elliptic\_curves.gp\_simon), 589  
`simon_two_descent()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 381  
`simon_two_descent()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 330  
`simplest_rational_poly()` (in module sage.schemes.elliptic\_curves.heegner), 567  
`singular_point()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 68  
`singular_points()` (sage.schemes.curves.curve.Curve\_generic method), 47  
`singular_subscheme()` (sage.schemes.curves.curve.Curve\_generic method), 47  
`Sn()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 391  
`solve_linear_differential_system()` (in module sage.schemes.elliptic\_curves.ell\_wp), 476  
`SpecialCubicQuotientRing` (class in sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 646  
`SpecialCubicQuotientRingElement` (class in sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 648  
`SpecialHyperellipticQuotientElement` (class in sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 649  
`SpecialHyperellipticQuotientRing` (class in sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 651  
`SpecialHyperellipticQuotientRing_class` (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 654  
`split_kernel_polynomial()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 229  
`square()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialCubicQuotientRingElement method), 649  
`supersingular_j_polynomial()` (in module sage.schemes.elliptic\_curves.ell\_finite\_field), 195  
`supersingular_primes()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 332  
`switch_sign()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 218  
`symmetric_matrix()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 68  
`sympow()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 510  
`sympow_derivs()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 511

## T

`tamagawa_exponent()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 454  
`tamagawa_exponent()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 384  
`tamagawa_exponent()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 332  
`tamagawa_number()` (sage.schemes.elliptic\_curves.ell\_local\_data.EllipticCurveLocalData method), 454  
`tamagawa_number()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 384  
`tamagawa_number()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 333  
`tamagawa_number_old()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 333  
`tamagawa_numbers()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 385  
`tamagawa_product()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 333  
`tamagawa_product_bsd()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 385  
`tangent_at_smooth_point()` (in module sage.schemes.elliptic\_curves.constructor), 105  
`tangents()` (sage.schemes.curves.affine\_curve.AffinePlaneCurve method), 19  
`tangents()` (sage.schemes.curves.point.AffinePlaneCurvePoint\_field method), 51  
`tangents()` (sage.schemes.curves.point.ProjectivePlaneCurvePoint\_field method), 52  
`tangents()` (sage.schemes.curves.projective\_curve.ProjectivePlaneCurve method), 38  
`tate_curve()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 333  
`tate_pairing()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 120  
`TateCurve` (class in sage.schemes.elliptic\_curves.ell\_tate\_curve), 457  
`tau()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 527  
`tau()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnXON method), 531  
`tau()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 398  
`tau()` (sage.schemes.elliptic\_curves.period\_lattice.PeriodLattice\_ell method), 493

`taylor_series()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 511

`teichmuller()` (sage.schemes.elliptic\_curves.padic\_lseries.pAdicLseries method), 573

`teichmuller()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 631

`test_els()` (in module sage.schemes.elliptic\_curves.descent\_two\_isogeny), 582

`test_mu()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 399

`test_padic_square()` (in module sage.schemes.elliptic\_curves.descent\_two\_isogeny), 582

`test_qpls()` (in module sage.schemes.elliptic\_curves.descent\_two\_isogeny), 582

`test_valuation()` (in module sage.schemes.elliptic\_curves.descent\_two\_isogeny), 582

`three_selmer_rank()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 334

`tiny_integrals()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 631

`tiny_integrals_on_basis()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 632

`torsion_order()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 386

`torsion_order()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 334

`torsion_points()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 386

`torsion_points()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 335

`torsion_polynomial()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 162

`torsion_subgroup()` (sage.schemes.elliptic\_curves.ell\_number\_field.EllipticCurve\_number\_field method), 388

`torsion_subgroup()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 336

`trace_of_frobenius()` (sage.schemes.elliptic\_curves.ell\_finite\_field.EllipticCurve\_finite\_field method), 193

`trace_to_real_numerical()` (sage.schemes.elliptic\_curves.heegner.KolyaginPoint method), 552

`transpose_list()` (in module sage.schemes.hyperelliptic\_curves.monsky\_washnitzer), 663

`truncate_neg()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientElement method), 651

`tuple()` (sage.schemes.elliptic\_curves.weierstrass\_morphism.baseWI method), 201

`twist_values()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 512

`twist_zeros()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 512

`two_descent()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 337

`two_descent_by_two_isogeny()` (in module sage.schemes.elliptic\_curves.descent\_two\_isogeny), 583

`two_descent_by_two_isogeny_work()` (in module sage.schemes.elliptic\_curves.descent\_two\_isogeny), 584

`two_descent_simon()` (sage.schemes.elliptic\_curves.ell\_rational\_field.EllipticCurve\_rational\_field method), 337

`two_division_polynomial()` (sage.schemes.elliptic\_curves.ell\_generic.EllipticCurve\_generic method), 163

`two_selmer_bound()` (sage.schemes.elliptic\_curves.sha\_tate.Sha method), 442

`two_torsion_part()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 230

`two_torsion_rank()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 176

## U

`ubs()` (in module sage.schemes.hyperelliptic\_curves.invariants), 678

`Ueberschiebung()` (in module sage.schemes.hyperelliptic\_curves.invariants), 675

`unfill_isogeny_matrix()` (in module sage.schemes.elliptic\_curves.ell\_curve\_isogeny), 230

`union()` (sage.schemes.curves.curve.Curve\_generic method), 48

`union()` (sage.schemes.elliptic\_curves.height.UnionOfIntervals class method), 403

`UnionOfIntervals` (class in sage.schemes.elliptic\_curves.height), 401

`upper_triangular_matrix()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 68

## V

`value_ring()` (sage.schemes.hyperelliptic\_curves.jacobian\_homset.JacobianHomset\_divisor\_classes method), 667

`values_along_line()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 513

`variable_names()` (sage.schemes.plane\_conics.con\_field.ProjectiveConic\_field method), 69

`verify()` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion method), 498

## W

`w()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 199

`w1` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion attribute), 499

`w2` (sage.schemes.elliptic\_curves.period\_lattice\_region.PeriodicRegion attribute), 499

`weierstrass_p()` (in module sage.schemes.elliptic\_curves.ell\_wp), 476

`weierstrass_p()` (sage.schemes.elliptic\_curves.ell\_field.EllipticCurve\_field method), 177

`weierstrass_points()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_padic\_field.HyperellipticCurve\_padic\_field method), 633

WeierstrassIsomorphism (class in sage.schemes.elliptic\_curves.weierstrass\_morphism), 201

WeierstrassTransformation (class in sage.schemes.elliptic\_curves.weierstrass\_transform), 591

WeierstrassTransformationWithInverse() (in module sage.schemes.elliptic\_curves.weierstrass\_transform), 592

WeierstrassTransformationWithInverse\_class (class in sage.schemes.elliptic\_curves.weierstrass\_transform), 593

`weil_pairing()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 122

`wp_c()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 400

`wp_intervals()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 400

`wp_on_grid()` (sage.schemes.elliptic\_curves.height.EllipticCurveCanonicalHeight method), 401

## X

`x()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 200

`x()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 653

`x_poly_exact()` (sage.schemes.elliptic\_curves.heegner.HeegnerPointOnEllipticCurve method), 527

`x_rational_map()` (sage.schemes.elliptic\_curves.ell\_curve\_isogeny.EllipticCurveIsogeny method), 219

`x_to_p()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.MonskyWashnitzerDifferentialRing method), 645

`xy()` (sage.schemes.elliptic\_curves.ell\_point.EllipticCurvePoint\_field method), 123

## Y

`y()` (sage.schemes.elliptic\_curves.formal\_group.EllipticCurveFormalGroup method), 200

`y()` (sage.schemes.hyperelliptic\_curves.monsky\_washnitzer.SpecialHyperellipticQuotientRing method), 654

## Z

`zero_sums()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 513

`zeros()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 513

`zeros_in_interval()` (sage.schemes.elliptic\_curves.lseries\_ell.Lseries\_ell method), 514

`zeta_function()` (sage.schemes.hyperelliptic\_curves.hyperelliptic\_finite\_field.HyperellipticCurve\_finite\_field method), 616