
Sage 9.2 Reference Manual: Algebraic Function Fields

Release 9.2

The Sage Development Team

Oct 25, 2020

CONTENTS

1	Function Fields	3
2	Elements of function fields	49
3	Orders of function fields	61
4	Ideals of function fields	81
5	Places of function fields	105
6	Divisors of function fields	111
7	Differentials of function fields	117
8	Valuation rings of function fields	123
9	Morphisms of function fields	127
10	Factories to construct function fields	137
11	Indices and Tables	141
	Python Module Index	143
	Index	145

Sage allows basic computations with elements and ideals in orders of algebraic function fields over arbitrary constant fields. Advanced computations, like computing the genus or a basis of the Riemann-Roch space of a divisor, are available for function fields over finite fields, number fields, and $\overline{\mathbb{Q}}$.

A reference for the basic theory of algebraic function fields is [Stich2009].

FUNCTION FIELDS

A function field (of one variable) is a finitely generated field extension of transcendence degree one. In Sage, a function field can be a rational function field or a finite extension of a function field.

EXAMPLES:

We create a rational function field:

```
sage: K.<x> = FunctionField(GF(5^2, 'a')); K
Rational function field in x over Finite Field in a of size 5^2
sage: K.genus()
0
sage: f = (x^2 + x + 1) / (x^3 + 1)
sage: f
(x^2 + x + 1)/(x^3 + 1)
sage: f^3
(x^6 + 3*x^5 + x^4 + 2*x^3 + x^2 + 3*x + 1)/(x^9 + 3*x^6 + 3*x^3 + 1)
```

Then we create an extension of the rational function field, and do some simple arithmetic in it:

```
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^3 - (x^3 + 2*x*y + 1/x)); L
Function field in y defined by y^3 + 3*x*y + (4*x^4 + 4)/x
sage: y^2
y^2
sage: y^3
2*x*y + (x^4 + 1)/x
sage: a = 1/y; a
(x/(x^4 + 1))*y^2 + 3*x^2/(x^4 + 1)
sage: a * y
1
```

We next make an extension of the above function field, illustrating that arithmetic with a tower of three fields is fully supported:

```
sage: S.<t> = L[]
sage: M.<t> = L.extension(t^2 - x*y)
sage: M
Function field in t defined by t^2 + 4*x*y
sage: t^2
x*y
sage: 1/t
((1/(x^4 + 1))*y^2 + 3*x/(x^4 + 1))*t
sage: M.base_field()
Function field in y defined by y^3 + 3*x*y + (4*x^4 + 4)/x
```

(continues on next page)

(continued from previous page)

```
sage: M.base_field().base_field()
Rational function field in x over Finite Field in a of size 5^2
```

It is also possible to construct function fields over an imperfect base field:

```
sage: N.<u> = FunctionField(K)
```

and inseparable extension function fields:

```
sage: J.<x> = FunctionField(GF(5)); J
Rational function field in x over Finite Field of size 5
sage: T.<v> = J[]
sage: O.<v> = J.extension(v^5 - x); O
Function field in v defined by v^5 + 4*x
```

Function fields over the rational field are supported:

```
sage: F.<x> = FunctionField(QQ)
sage: R.<Y> = F[]
sage: L.<y> = F.extension(Y^2 - x^8 - 1)
sage: O = L.maximal_order()
sage: I = O.ideal(x, y - 1)
sage: P = I.place()
sage: D = P.divisor()
sage: D.basis_function_space()
[1]
sage: (2*D).basis_function_space()
[1]
sage: (3*D).basis_function_space()
[1]
sage: (4*D).basis_function_space()
[1, 1/x^4*y + 1/x^4]

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor()
2*Place (x, y, (1/(x^3 + x^2 + x))*y^2)
+ 2*Place (x^2 + x + 1, y, (1/(x^3 + x^2 + x))*y^2)

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor()
- Place (x, x*y)
+ Place (x^2 + 1, x*y)
```

Function fields over the algebraic field are supported:

```
sage: K.<x> = FunctionField(QQbar); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor()
```

(continues on next page)

(continued from previous page)

```

Place (x - I, x*y)
- Place (x, x*y)
+ Place (x + I, x*y)
sage: pl = I.divisor().support()[0]
sage: m = L.completion(pl, prec=5)
sage: m(x)
I + s + O(s^5)
sage: m(y)
-2*s + (-4 - I)*s^2 + (-15 - 4*I)*s^3 + (-75 - 23*I)*s^4 + (-413 - 154*I)*s^5 + O(s^6)
sage: m(y)^2 + m(y) + m(x) + 1/m(x)
O(s^5)

```

1.1 Global function fields

A global function field in Sage is an extension field of a rational function field over a *finite* constant field by an irreducible separable polynomial over the rational function field.

EXAMPLES:

A fundamental computation for a global or any function field is to get a basis of its maximal order and maximal infinite order, and then do arithmetic with ideals of those maximal orders:

```

sage: K.<x> = FunctionField(GF(3)); _.<t> = K[]
sage: L.<y> = K.extension(t^4 + t - x^5)
sage: O = L.maximal_order()
sage: O.basis()
(1, y, 1/x*y^2 + 1/x*y, 1/x^3*y^3 + 2/x^3*y^2 + 1/x^3*y)
sage: I = O.ideal(x, y); I
Ideal (x, y) of Maximal order of Function field in y defined by y^4 + y + 2*x^5
sage: J = I^-1
sage: J.basis_matrix()
[ 1  0  0  0]
[1/x 1/x  0  0]
[ 0  0  1  0]
[ 0  0  0  1]
sage: L.maximal_order_infinite().basis()
(1, 1/x^2*y, 1/x^3*y^2, 1/x^4*y^3)

```

As an example of the most sophisticated computations that Sage can do with a global function field, we compute all the Weierstrass places of the Klein quartic over \mathbf{F}_2 and gap numbers for ordinary places:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: L.genus()
3
sage: L.weierstrass_places()
[Place (1/x, 1/x^3*y^2 + 1/x),
 Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1),
 Place (x, y),
 Place (x + 1, (x^3 + 1)*y + x + 1),
 Place (x^3 + x + 1, y + 1),
 Place (x^3 + x + 1, y + x^2),
 Place (x^3 + x + 1, y + x^2 + 1),
 Place (x^3 + x^2 + 1, y + x),

```

(continues on next page)

(continued from previous page)

```

Place (x^3 + x^2 + 1, y + x^2 + 1),
Place (x^3 + x^2 + 1, y + x^2 + x + 1)]
sage: L.gaps()
[1, 2, 3]

```

The gap numbers for Weierstrass places are of course not ordinary:

```

sage: p1,p2,p3 = L.weierstrass_places()[ :3]
sage: p1.gaps()
[1, 2, 4]
sage: p2.gaps()
[1, 2, 4]
sage: p3.gaps()
[1, 2, 4]

```

AUTHORS:

- William Stein (2010): initial version
- Robert Bradshaw (2010-05-30): added `is_finite()`
- Julian R  th (2011-06-08, 2011-09-14, 2014-06-23, 2014-06-24, 2016-11-13): fixed `hom()`, `extension()`; use `@cached_method`; added `derivation()`; added support for relative vector spaces; fixed conversion to base fields
- Maarten Derickx (2011-09-11): added doctests
- Syed Ahmad Lavasani (2011-12-16): added `genus()`, `is_RationalFunctionField()`
- Simon King (2014-10-29): Use the same generator names for a function field extension and the underlying polynomial ring.
- Kwankyu Lee (2017-04-30): added global function fields
- Brent Baccala (2019-12-20): added function fields over number fields and $\mathbb{Q}\bar{\mathbb{Q}}$

```

class sage.rings.function_field.function_field.FunctionField(base_field, names,
                                                             category=Category
                                                             of function fields)

```

Bases: `sage.rings.ring.Field`

Abstract base class for all function fields.

INPUT:

- `base_field` – field; the base of this function field
- `names` – string that gives the name of the generator

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: K
Rational function field in x over Rational Field

```

`characteristic()`

Return the characteristic of the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: K.characteristic()
0

```

(continues on next page)

(continued from previous page)

```

sage: K.<x> = FunctionField(QQbar)
sage: K.characteristic()
0
sage: K.<x> = FunctionField(GF(7))
sage: K.characteristic()
7
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: L.characteristic()
7

```

completion (*place*, *name=None*, *prec=None*, *gen_name=None*)

Return the completion of the function field at the place.

INPUT:

- *place* – place
- *name* – string; name of the series variable
- *prec* – positive integer; default precision
- *gen_name* – string; name of the generator of the residue field; used only when the place is non-rational

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: m = L.completion(p); m
Completion map:
  From: Function field in y defined by y^2 + y + (x^2 + 1)/x
  To:   Laurent Series Ring in s over Finite Field of size 2
sage: m(x, 10)
s^2 + s^3 + s^4 + s^5 + s^7 + s^8 + s^9 + s^10 + O(s^12)
sage: m(y, 10)
s^-1 + 1 + s^3 + s^5 + s^7 + O(s^9)

sage: K.<x> = FunctionField(GF(2)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: m = L.completion(p); m
Completion map:
  From: Function field in y defined by y^2 + y + (x^2 + 1)/x
  To:   Laurent Series Ring in s over Finite Field of size 2
sage: m(x, 10)
s^2 + s^3 + s^4 + s^5 + s^7 + s^8 + s^9 + s^10 + O(s^12)
sage: m(y, 10)
s^-1 + 1 + s^3 + s^5 + s^7 + O(s^9)

sage: K.<x> = FunctionField(GF(2))
sage: p = K.places_finite()[0]; p
Place (x)
sage: m = K.completion(p); m
Completion map:
  From: Rational function field in x over Finite Field of size 2
  To:   Laurent Series Ring in s over Finite Field of size 2
sage: m(1/(x+1))

```

(continues on next page)

(continued from previous page)

```

1 + s + s^2 + s^3 + s^4 + s^5 + s^6 + s^7 + s^8 + s^9 + s^10 + s^11 + s^12
+ s^13 + s^14 + s^15 + s^16 + s^17 + s^18 + s^19 + O(s^20)

sage: p = K.place_infinite(); p
Place (1/x)
sage: m = K.completion(p); m
Completion map:
  From: Rational function field in x over Finite Field of size 2
  To:   Laurent Series Ring in s over Finite Field of size 2
sage: m(x)
s^-1 + O(s^19)

sage: m = K.completion(p, prec=infinity); m
Completion map:
  From: Rational function field in x over Finite Field of size 2
  To:   Lazy Laurent Series Ring in s over Finite Field of size 2
sage: f = m(x); f
s^-1 + ...
sage: f.coefficient(100)
0

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 - x)
sage: O = L.maximal_order()
sage: decomp = O.decomposition(K.maximal_order().ideal(x - 1))
sage: pls = (decomp[0][0].place(), decomp[1][0].place())
sage: m = L.completion(pls[0]); m
Completion map:
  From: Function field in y defined by y^2 - x
  To:   Laurent Series Ring in s over Rational Field
sage: xe = m(x)
sage: ye = m(y)
sage: ye^2 - xe == 0
True

sage: decomp2 = O.decomposition(K.maximal_order().ideal(x^2 + 1))
sage: pls2 = decomp2[0][0].place()
sage: m = L.completion(pls2); m
Completion map:
  From: Function field in y defined by y^2 - x
  To:   Laurent Series Ring in s over Number Field in a with defining_
  ↪ polynomial x^4 + 2*x^2 + 4*x + 2
sage: xe = m(x)
sage: ye = m(y)
sage: ye^2 - xe == 0
True

```

divisor_group()

Return the group of divisors attached to the function field.

EXAMPLES:

```

sage: K.<t> = FunctionField(QQ)
sage: K.divisor_group()
Divisor group of Rational function field in t over Rational Field

sage: _.<Y> = K[]

```

(continues on next page)

(continued from previous page)

```

sage: L.<y> = K.extension(Y^3 - (t^3 - 1)/(t^3 - 2))
sage: L.divisor_group()
Divisor group of Function field in y defined by y^3 + (-t^3 + 1)/(t^3 - 2)

sage: K.<x> = FunctionField(GF(5)); L.<y> = K[]
sage: L.<y> = K.extension(Y^3 - (x^3 - 1)/(x^3 - 2))
sage: L.divisor_group()
Divisor group of Function field in y defined by y^3 + (4*x^3 + 1)/(x^3 + 3)

```

extension (*f*, *names=None*)

Create an extension $K(y)$ of this function field K extended with a root y of the univariate polynomial f over K .

INPUT:

- f – univariate polynomial over K
- *names* – string or tuple of length 1 that names the variable y

OUTPUT:

- a function field

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: K.extension(y^5 - x^3 - 3*x + x*y)
Function field in y defined by y^5 + x*y - x^3 - 3*x

```

A nonintegral defining polynomial:

```

sage: K.<t> = FunctionField(QQ); R.<y> = K[]
sage: K.extension(y^3 + (1/t)*y + t^3/(t+1), 'z')
Function field in z defined by z^3 + 1/t*z + t^3/(t + 1)

```

The defining polynomial need not be monic or integral:

```

sage: K.extension(t*y^3 + (1/t)*y + t^3/(t+1))
Function field in y defined by t*y^3 + 1/t*y + t^3/(t + 1)

```

is_finite ()

Return whether the function field is finite, which is false.

EXAMPLES:

```

sage: R.<t> = FunctionField(QQ)
sage: R.is_finite()
False
sage: R.<t> = FunctionField(GF(7))
sage: R.is_finite()
False

```

is_global ()

Return whether the function field is global, that is, whether the constant field is finite.

EXAMPLES:

```

sage: R.<t> = FunctionField(QQ)
sage: R.is_global()

```

(continues on next page)

(continued from previous page)

```
False
sage: R.<t> = FunctionField(QQbar)
sage: R.is_global()
False
sage: R.<t> = FunctionField(GF(7))
sage: R.is_global()
True
```

is_perfect()

Return whether the field is perfect, i.e., its characteristic p is zero or every element has a p -th root.

EXAMPLES:

```
sage: FunctionField(QQ, 'x').is_perfect()
True
sage: FunctionField(GF(2), 'x').is_perfect()
False
```

order(x, check=True)

Return the order generated by x over the base maximal order.

INPUT:

- x – element or list of elements of the function field
- *check* – boolean; if *True*, check that x really generates an order

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^3 + x^3 + 4*x + 1)
sage: O = L.order(y); O
Order in Function field in y defined by y^3 + x^3 + 4*x + 1
sage: O.basis()
(1, y, y^2)

sage: Z = K.order(x); Z
Order in Rational function field in x over Rational Field
sage: Z.basis()
(1,)
```

Orders with multiple generators are not yet supported:

```
sage: Z = K.order([x, x^2]); Z
Traceback (most recent call last):
...
NotImplementedError
```

order_infinite(x, check=True)

Return the order generated by x over the maximal infinite order.

INPUT:

- x – element or a list of elements of the function field
- *check* – boolean; if *True*, check that x really generates an order

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^3 + x^3 + 4*x + 1)
sage: L.order_infinite(y) # todo: not implemented

sage: Z = K.order(x); Z
Order in Rational function field in x over Rational Field
sage: Z.basis()
(1,)

```

Orders with multiple generators, not yet supported:

```

sage: Z = K.order_infinite([x, x^2]); Z
Traceback (most recent call last):
...
NotImplementedError

```

order_infinite_with_basis (*basis*, *check=True*)

Return the order with given basis over the maximal infinite order of the base field.

INPUT:

- *basis* – list of elements of the function field
- *check* – boolean (default: True); if True, check that the basis is really linearly independent and that the module it spans is closed under multiplication, and contains the identity element.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^3 + x^3 + 4*x + 1)
sage: O = L.order_infinite_with_basis([1, 1/x*y, 1/x^2*y^2]); O
Infinite order in Function field in y defined by y^3 + x^3 + 4*x + 1
sage: O.basis()
(1, 1/x*y, 1/x^2*y^2)

```

Note that 1 does not need to be an element of the basis, as long it is in the module spanned by it:

```

sage: O = L.order_infinite_with_basis([1+1/x*y, 1/x*y, 1/x^2*y^2]); O
Infinite order in Function field in y defined by y^3 + x^3 + 4*x + 1
sage: O.basis()
(1/x*y + 1, 1/x*y, 1/x^2*y^2)

```

The following error is raised when the module spanned by the basis is not closed under multiplication:

```

sage: O = L.order_infinite_with_basis([1, y, 1/x^2*y^2]); O
Traceback (most recent call last):
...
ValueError: the module generated by basis (1, y, 1/x^2*y^2) must be closed_
↳ under multiplication

```

and this happens when the identity is not in the module spanned by the basis:

```

sage: O = L.order_infinite_with_basis([1/x, 1/x*y, 1/x^2*y^2])
Traceback (most recent call last):
...
ValueError: the identity element must be in the module spanned by basis (1/x, _
↳ 1/x*y, 1/x^2*y^2)

```

order_with_basis (*basis*, *check=True*)

Return the order with given basis over the maximal order of the base field.

INPUT:

- *basis* – list of elements of this function field
- *check* – boolean (default: `True`); if `True`, check that the basis is really linearly independent and that the module it spans is closed under multiplication, and contains the identity element.

OUTPUT:

- an order in the function field

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]; L.<y> = K.extension(y^3 + x^3 + 4*x + 1)
sage: O = L.order_with_basis([1, y, y^2]); O
Order in Function field in y defined by y^3 + x^3 + 4*x + 1
sage: O.basis()
(1, y, y^2)
```

Note that 1 does not need to be an element of the basis, as long it is in the module spanned by it:

```
sage: O = L.order_with_basis([1+y, y, y^2]); O
Order in Function field in y defined by y^3 + x^3 + 4*x + 1
sage: O.basis()
(y + 1, y, y^2)
```

The following error is raised when the module spanned by the basis is not closed under multiplication:

```
sage: O = L.order_with_basis([1, x^2 + x*y, (2/3)*y^2]); O
Traceback (most recent call last):
...
ValueError: the module generated by basis (1, x*y + x^2, 2/3*y^2) must be
closed under multiplication
```

and this happens when the identity is not in the module spanned by the basis:

```
sage: O = L.order_with_basis([x, x^2 + x*y, (2/3)*y^2])
Traceback (most recent call last):
...
ValueError: the identity element must be in the module spanned by basis (x,
x*y + x^2, 2/3*y^2)
```

place_set ()

Return the set of all places of the function field.

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(7))
sage: K.place_set()
Set of places of Rational function field in t over Finite Field of size 7

sage: K.<t> = FunctionField(QQ)
sage: K.place_set()
Set of places of Rational function field in t over Rational Field

sage: K.<x> = FunctionField(GF(2)); L.<y> = K[]
```

(continues on next page)

(continued from previous page)

```

sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: L.place_set()
Set of places of Function field in y defined by  $y^2 + y + (x^2 + 1)/x$ 

```

rational_function_field()

Return the rational function field from which this field has been created as an extension.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: K.rational_function_field()
Rational function field in x over Rational Field

sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2-x)
sage: L.rational_function_field()
Rational function field in x over Rational Field

sage: R.<z> = L[]
sage: M.<z> = L.extension(z^2-y)
sage: M.rational_function_field()
Rational function field in x over Rational Field

```

some_elements()

Return some elements in this function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: K.some_elements()
[1,
 x,
 2*x,
 x/(x^2 + 2*x + 1),
 1/x^2,
 x/(x^2 - 1),
 x/(x^2 + 1),
 1/2*x/(x^2 + 1),
 0,
 1/x,
 ...]

```

```

sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: L.some_elements()
[1,
 y,
 1/x*y,
 ((x + 1)/(x^2 - 2*x + 1))*y - 2*x/(x^2 - 2*x + 1),
 1/x,
 (1/(x - 1))*y,
 (1/(x + 1))*y,
 (1/2/(x + 1))*y,
 0,
 ...]

```

space_of_differentials()

Return the space of differentials attached to the function field.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: K.space_of_differentials()
Space of differentials of Rational function field in t over Rational Field

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 - (x^3 - 1)/(x^3 - 2))
sage: L.space_of_differentials()
Space of differentials of Function field in y defined by y^3 + (4*x^3 + 1)/(x^
↪ 3 + 3)
```

valuation (*prime*)

Return the discrete valuation on this function field defined by *prime*.

INPUT:

- *prime* – a place of the function field, a valuation on a subring, or a valuation on another function field together with information for isomorphisms to and from that function field

EXAMPLES:

We create valuations that correspond to finite rational places of a function field:

```
sage: K.<x> = FunctionField(QQ)
sage: v = K.valuation(1); v
(x - 1)-adic valuation
sage: v(x)
0
sage: v(x - 1)
1
```

A place can also be specified with an irreducible polynomial:

```
sage: v = K.valuation(x^2 - 1); v
(x^2 - 1)-adic valuation
```

Similarly, for a finite non-rational place:

```
sage: v = K.valuation(x^2 + 1); v
(x^2 + 1)-adic valuation
sage: v(x^2 + 1)
1
sage: v(x)
0
```

Or for the infinite place:

```
sage: v = K.valuation(1/x); v
Valuation at the infinite place
sage: v(x)
-1
```

Instead of specifying a generator of a place, we can define a valuation on a rational function field by giving a discrete valuation on the underlying polynomial ring:

```

sage: R.<x> = QQ[]
sage: w = valuations.GaussValuation(R, valuations.TrivialValuation(QQ)).
↪augmentation(x - 1, 1)
sage: v = K.valuation(w); v
(x - 1)-adic valuation

```

Note that this allows us to specify valuations which do not correspond to a place of the function field:

```

sage: w = valuations.GaussValuation(R, QQ.valuation(2))
sage: v = K.valuation(w); v
2-adic valuation

```

The same is possible for valuations with $v(1/x) > 0$ by passing in an extra pair of parameters, an isomorphism between this function field and an isomorphic function field. That way you can, for example, indicate that the valuation is to be understood as a valuation on $K[1/x]$, i.e., after applying the substitution $x \mapsto 1/x$ (here, the inverse map is also $x \mapsto 1/x$):

```

sage: w = valuations.GaussValuation(R, QQ.valuation(2)).augmentation(x, 1)
sage: w = K.valuation(w)
sage: v = K.valuation((w, K.hom([~K.gen()], K.hom([~K.gen()]))) ); v
Valuation on rational function field induced by [ Gauss valuation induced by ↪
↪2-adic valuation, v(x) = 1 ] (in Rational function field in x over Rational ↪
↪Field after x |--> 1/x)

```

Note that classical valuations at finite places or the infinite place are always normalized such that the uniformizing element has valuation 1:

```

sage: K.<t> = FunctionField(GF(3))
sage: M.<x> = FunctionField(K)
sage: v = M.valuation(x^3 - t)
sage: v(x^3 - t)
1

```

However, if such a valuation comes out of a base change of the ground field, this is not the case anymore. In the example below, the unique extension of v to L still has valuation 1 on $x^3 - t$ but it has valuation $1/3$ on its uniformizing element $x - w$:

```

sage: R.<w> = K[]
sage: L.<w> = K.extension(w^3 - t)
sage: N.<x> = FunctionField(L)
sage: w = v.extension(N) # missing factorization, :trac:`16572`
Traceback (most recent call last):
...
NotImplementedError
sage: w(x^3 - t) # not tested
1
sage: w(x - w) # not tested
1/3

```

There are several ways to create valuations on extensions of rational function fields:

```

sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x); L
Function field in y defined by y^2 - x

```

A place that has a unique extension can just be defined downstairs:

```
sage: v = L.valuation(x); v
(x)-adic valuation
```

```
class sage.rings.function_field.function_field.FunctionField_char_zero (polynomial,
                                                                           names,
                                                                           cat-
                                                                           e-
                                                                           gory=None)
```

Bases: `sage.rings.function_field.function_field.FunctionField_simple`

Function fields of characteristic zero.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 - (x^3 - 1)/(x^3 - 2))
sage: L
Function field in y defined by y^3 + (-x^3 + 1)/(x^3 - 2)
sage: L.characteristic()
0
```

higher_derivation()

Return the higher derivation (also called the Hasse-Schmidt derivation) for the function field.

The higher derivation of the function field is uniquely determined with respect to the separating element x of the base rational function field $k(x)$.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 - (x^3 - 1)/(x^3 - 2))
sage: L.higher_derivation()
Higher derivation map:
  From: Function field in y defined by y^3 + (-x^3 + 1)/(x^3 - 2)
  To:   Function field in y defined by y^3 + (-x^3 + 1)/(x^3 - 2)
```

```
class sage.rings.function_field.function_field.FunctionField_char_zero_integral (polynomial,
                                                                           names,
                                                                           cat-
                                                                           e-
                                                                           gory=None)
```

Bases: `sage.rings.function_field.function_field.FunctionField_char_zero`,
`sage.rings.function_field.function_field.FunctionField_integral`

Function fields of characteristic zero, defined by an irreducible and separable polynomial, integral over the maximal order of the base rational function field with a finite constant field.

```
class sage.rings.function_field.function_field.FunctionField_global (polynomial,
                                                                           names)
```

Bases: `sage.rings.function_field.function_field.FunctionField_simple`

Global function fields.

INPUT:

- `polynomial` – monic irreducible and separable polynomial
- `names` – name of the generator of the function field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 - (x^3 - 1)/(x^3 - 2))
sage: L
Function field in y defined by y^3 + (4*x^3 + 1)/(x^3 + 3)

```

The defining equation needs not be monic:

```

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension((1 - x)*Y^7 - x^3)
sage: L.gaps()
[1, 2, 3]

```

or may define a trivial extension:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: L.<y> = K.extension(Y-1)
sage: L.genus()
0

```

L_polynomial (*name='t'*)

Return the L-polynomial of the function field.

INPUT:

- *name* – (default: *t*) name of the variable of the polynomial

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: F.L_polynomial()
2*t^2 + t + 1

```

gaps ()

Return the gaps of the function field.

These are the gaps at the ordinary places, that is, places which are not Weierstrass places.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3 * Y + x)
sage: L.gaps()
[1, 2, 3]

```

get_place (*degree*)

Return a place of degree.

INPUT:

- *degree* – a positive integer

OUTPUT: a place of degree if any exists; otherwise None

EXAMPLES:

```

sage: F.<a> = GF(2)
sage: K.<x> = FunctionField(F)
sage: R.<Y> = PolynomialRing(K)
sage: L.<y> = K.extension(Y^4 + Y - x^5)

```

(continues on next page)

(continued from previous page)

```

sage: L.get_place(1)
Place (x, y)
sage: L.get_place(2)
Place (x, y^2 + y + 1)
sage: L.get_place(3)
Place (x^3 + x^2 + 1, y + x^2 + x)
sage: L.get_place(4)
Place (x + 1, x^5 + 1)
sage: L.get_place(5)
Place (x^5 + x^3 + x^2 + x + 1, y + x^4 + 1)
sage: L.get_place(6)
Place (x^3 + x^2 + 1, y^2 + y + x^2)
sage: L.get_place(7)
Place (x^7 + x + 1, y + x^6 + x^5 + x^4 + x^3 + x)
sage: L.get_place(8)

```

higher_derivation()

Return the higher derivation (also called the Hasse-Schmidt derivation) for the function field.

The higher derivation of the function field is uniquely determined with respect to the separating element x of the base rational function field $k(x)$.

EXAMPLES:

```

sage: K.<x>=FunctionField(GF(5)); _.<Y>=K[]
sage: L.<y>=K.extension(Y^3 - (x^3 - 1)/(x^3 - 2))
sage: L.higher_derivation()
Higher derivation map:
  From: Function field in y defined by y^3 + (4*x^3 + 1)/(x^3 + 3)
  To:   Function field in y defined by y^3 + (4*x^3 + 1)/(x^3 + 3)

```

maximal_order()

Return the maximal order of the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2));
sage: R.<t> = PolynomialRing(K);
sage: F.<y> = K.extension(t^4 + x^12*t^2 + x^18*t + x^21 + x^18);
sage: O = F.maximal_order()
sage: O.basis()
(1, 1/x^4*y, 1/x^11*y^2 + 1/x^2, 1/x^15*y^3 + 1/x^6*y)

```

number_of_rational_places(r=l)

Return the number of rational places of the function field whose constant field extended by degree r .

INPUT:

- r – positive integer (default: 1)

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: F.number_of_rational_places()
4
sage: [F.number_of_rational_places(r) for r in [1..10]]
[4, 8, 4, 16, 44, 56, 116, 288, 508, 968]

```

places (*degree=1*)

Return a list of the places with degree.

INPUT:

- degree – positive integer (default: 1)

EXAMPLES:

```
sage: F.<a> = GF(2)
sage: K.<x> = FunctionField(F)
sage: R.<t> = PolynomialRing(K)
sage: L.<y> = K.extension(t^4 + t - x^5)
sage: L.places(1)
[Place (1/x, 1/x^4*y^3), Place (x, y), Place (x, y + 1)]
```

places_finite (*degree=1*)

Return a list of the finite places with degree.

INPUT:

- degree – positive integer (default: 1)

EXAMPLES:

```
sage: F.<a> = GF(2)
sage: K.<x> = FunctionField(F)
sage: R.<t> = PolynomialRing(K)
sage: L.<y> = K.extension(t^4+t-x^5)
sage: L.places_finite(1)
[Place (x, y), Place (x, y + 1)]
```

places_infinite (*degree=1*)

Return a list of the infinite places with degree.

INPUT:

- degree – positive integer (default: 1)

EXAMPLES:

```
sage: F.<a> = GF(2)
sage: K.<x> = FunctionField(F)
sage: R.<t> = PolynomialRing(K)
sage: L.<y> = K.extension(t^4+t-x^5)
sage: L.places_infinite(1)
[Place (1/x, 1/x^4*y^3)]
```

weierstrass_places ()

Return all Weierstrass places of the function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); L.<y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3 * Y + x)
sage: L.weierstrass_places()
[Place (1/x, 1/x^3*y^2 + 1/x),
 Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1),
 Place (x, y),
 Place (x + 1, (x^3 + 1)*y + x + 1),
 Place (x^3 + x + 1, y + 1),
```

(continues on next page)

(continued from previous page)

```
Place (x^3 + x + 1, y + x^2),
Place (x^3 + x + 1, y + x^2 + 1),
Place (x^3 + x^2 + 1, y + x),
Place (x^3 + x^2 + 1, y + x^2 + 1),
Place (x^3 + x^2 + 1, y + x^2 + x + 1)]
```

class sage.rings.function_field.function_field.**FunctionField_global_integral** (*polynomial, names*)

Bases: *sage.rings.function_field.function_field.FunctionField_global, sage.rings.function_field.function_field.FunctionField_integral*

Global function fields, defined by an irreducible and separable polynomial, integral over the maximal order of the base rational function field with a finite constant field.

class sage.rings.function_field.function_field.**FunctionField_integral** (*polynomial, names, category=None*)

Bases: *sage.rings.function_field.function_field.FunctionField_simple*

Integral function fields.

A function field is integral if it is defined by an irreducible separable polynomial, which is integral over the maximal order of the base rational function field.

equation_order()

Return the equation order of the function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: F.equation_order()
Order in Function field in y defined by y^3 + x^6 + x^4 + x^2

sage: K.<x> = FunctionField(QQ); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: F.equation_order()
Order in Function field in y defined by y^3 - x^6 - 2*x^5 - 3*x^4 - 2*x^3 - x^2
↪2
```

equation_order_infinite()

Return the infinite equation order of the function field.

This is by definition $o[b]$ where b is the primitive integral element from *primitive_integral_element_infinite()* and o is the maximal infinite order of the base rational function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: F.equation_order_infinite()
Infinite order in Function field in y defined by y^3 + x^6 + x^4 + x^2

sage: K.<x> = FunctionField(QQ); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: F.equation_order_infinite()
Infinite order in Function field in y defined by y^3 - x^6 - 2*x^5 - 3*x^4 -
↪2*x^3 - x^2
```

(continues on next page)

(continued from previous page)

primitive_integral_element_infinite()

Return a primitive integral element over the base maximal infinite order.

This element is integral over the maximal infinite order of the base rational function field and the function field is a simple extension by this element over the base order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: b = F.primitive_integral_element_infinite(); b
1/x^2*y
sage: b.minimal_polynomial('t')
t^3 + (x^4 + x^2 + 1)/x^4
```

class sage.rings.function_field.function_field.**FunctionField_polymod**(*polynomial*,
names,
cate-
gory=None)

Bases: *sage.rings.function_field.function_field.FunctionField*

Function fields defined by a univariate polynomial, as an extension of the base field.

INPUT:

- *polynomial* – univariate polynomial over a function field
- *names* – tuple of length 1 or string; variable names
- *category* – category (default: category of function fields)

EXAMPLES:

We make a function field defined by a degree 5 polynomial over the rational function field over the rational numbers:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x)); L
Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
```

We next make a function field over the above nontrivial function field L:

```
sage: S.<z> = L[]
sage: M.<z> = L.extension(z^2 + y*z + y); M
Function field in z defined by z^2 + y*z + y
sage: 1/z
((-x/(x^4 + 1))*y^4 + 2*x^2/(x^4 + 1))*z - 1
sage: z * (1/z)
1
```

We drill down the tower of function fields:

```
sage: M.base_field()
Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
sage: M.base_field().base_field()
Rational function field in x over Rational Field
sage: M.base_field().base_field().constant_field()
```

(continues on next page)

(continued from previous page)

```
Rational Field
sage: M.constant_base_field()
Rational Field
```

Warning: It is not checked if the polynomial used to define the function field is irreducible. Hence it is not guaranteed that this object really is a field! This is illustrated below.

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(x^2 - y^2)
sage: (y - x)*(y + x)
0
sage: 1/(y - x)
1
sage: y - x == 0; y + x == 0
False
False
```

Element

alias of `sage.rings.function_field.element.FunctionFieldElement_polymod`

base_field()

Return the base field of the function field. This function field is presented as $L = K[y]/(f(y))$, and the base field is by definition the field K .

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.base_field()
Rational function field in x over Rational Field
```

change_variable_name(name)

Return a field isomorphic to this field with variable(s) name.

INPUT:

- name – a string or a tuple consisting of a strings, the names of the new variables starting with a generator of this field and going down to the rational function field.

OUTPUT:

A triple F, f, ι where F is a function field, f is an isomorphism from F to this field, and ι is the inverse of f .

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: R.<z> = L[]
sage: M.<z> = L.extension(z^2 - y)

sage: M.change_variable_name('zz')
(Function field in zz defined by zz^2 - y,
Function Field morphism:
```

(continues on next page)

(continued from previous page)

```

From: Function field in zz defined by zz^2 - y
To:   Function field in z defined by z^2 - y
Defn: zz |--> z
      y |--> y
      x |--> x,
Function Field morphism:
From: Function field in z defined by z^2 - y
To:   Function field in zz defined by zz^2 - y
Defn: z |--> zz
      y |--> y
      x |--> x)
sage: M.change_variable_name(('zz','yy'))
(Function field in zz defined by zz^2 - yy, Function Field morphism:
From: Function field in zz defined by zz^2 - yy
To:   Function field in z defined by z^2 - y
Defn: zz |--> z
      yy |--> y
      x |--> x, Function Field morphism:
From: Function field in z defined by z^2 - y
To:   Function field in zz defined by zz^2 - yy
Defn: z |--> zz
      y |--> yy
      x |--> x)
sage: M.change_variable_name(('zz','yy','xx'))
(Function field in zz defined by zz^2 - yy,
Function Field morphism:
From: Function field in zz defined by zz^2 - yy
To:   Function field in z defined by z^2 - y
Defn: zz |--> z
      yy |--> y
      xx |--> x,
Function Field morphism:
From: Function field in z defined by z^2 - y
To:   Function field in zz defined by zz^2 - yy
Defn: z |--> zz
      y |--> yy
      x |--> xx)

```

constant_base_field()

Return the base constant field of the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x)); L
Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
sage: L.constant_base_field()
Rational Field
sage: S.<z> = L[]
sage: M.<z> = L.extension(z^2 - y)
sage: M.constant_base_field()
Rational Field

```

constant_field()

Return the algebraic closure of the constant field of the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^5 - x)
sage: L.constant_field()
Traceback (most recent call last):
...
NotImplementedError

```

degree (*base=None*)

Return the degree of the function field over the function field *base*.

INPUT:

- *base* – a function field (default: *None*), a function field from which this field has been constructed as a finite extension.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x)); L
Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
sage: L.degree()
5
sage: L.degree(L)
1

sage: R.<z> = L[]
sage: M.<z> = L.extension(z^2 - y)
sage: M.degree(L)
2
sage: M.degree(K)
10

```

derivation ()

Return a generator of the space of derivations over the constant base ring of this function field *K*.

A derivation on *K* is map $K \rightarrow K$ with $D(\alpha + \beta) = D(\alpha) + D(\beta)$ and $D(\alpha\beta) = \beta D(\alpha) + \alpha D(\beta)$ for all $\alpha, \beta \in K$.

If the base field *k* of *K* is perfect, then the derivations on *K* form a one-dimensional *K*-vector space. (More generally, this is true if *K* is separable over *k*, or in other words if the corresponding curve is geometrically reduced over *k*; this is automatically the case if *k* is perfect.) We apply the techniques from [GT1996] to find a generator of this one-dimensional vector space, which is then returned by the algorithm.

ALGORITHM:

If *K* is a separable extension of another function field *F* between *K* and *k*, then Proposition 11 of [GT1996] describes how to compute the unique extension of a derivation on *F* to *K*; we then apply this algorithm to the generator of the space of derivations on *F*, which we may calculate inductively. If *K* is not given as a separable extension of another function field, then we find a field isomorphic to *K* that is a separable extension of a rational function field over *k* by using `separable_model()`. This part of the algorithm uses the assumption that *k* is perfect.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(3))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: d = L.derivation(); d

```

(continues on next page)

(continued from previous page)

```

Derivation map:
  From: Function field in y defined by y^2 + 2*x
  To:   Function field in y defined by y^2 + 2*x
  Defn: y |--> 2/x*y
        x |--> 1
sage: d(x)
1
sage: d(x^3)
0
sage: d(x*y)
0
sage: d(y)
2/x*y

```

This also works for inseparable extensions:

```

sage: R.<y> = K[]
sage: L.<y> = K.extension(y^3 - x)
sage: d = L.derivation(); d
Derivation map:
  From: Function field in y defined by y^3 + 2*x
  To:   Function field in y defined by y^3 + 2*x
  Defn: y |--> 1
        x |--> 0
sage: d(x^2)
0
sage: d(y^2)
2*y
sage: d(x*y)
x

```

different()

Return the different of the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: F.different()
2*Place (x, (1/(x^3 + x^2 + x))*y^2)
+ 2*Place (x^2 + x + 1, (1/(x^3 + x^2 + x))*y^2)

```

equation_order()

Return the equation order of the function field.

If we view the function field as being presented as $K[y]/(f(y))$, then the order generated by the class of y is returned. If f is not monic, then `_make_monic_integral()` is called, and instead we get the order generated by some integral multiple of a root of f .

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: O = L.equation_order()
sage: O.basis()
(1, x*y, x^2*y^2, x^3*y^3, x^4*y^4)

```

We try an example, in which the defining polynomial is not monic and is not integral:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(x^2*y^5 - 1/x); L
Function field in y defined by x^2*y^5 - 1/x
sage: O = L.equation_order()
sage: O.basis()
(1, x^3*y, x^6*y^2, x^9*y^3, x^12*y^4)

```

free_module (*base=None, basis=None, map=True*)

Return a vector space and isomorphisms from the field to and from the vector space.

This function allows us to identify the elements of this field with elements of a vector space over the base field, which is useful for representation and arithmetic with orders, ideals, etc.

INPUT:

- *base* – a function field (default: `None`), the returned vector space is over this subfield R , which defaults to the base field of this function field.
- *basis* – a basis for this field over the base.
- *maps* – boolean (default `True`), whether to return R -linear maps to and from V .

OUTPUT:

- a vector space over the base function field
- an isomorphism from the vector space to the field (if requested)
- an isomorphism from the field to the vector space (if requested)

EXAMPLES:

We define a function field:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x)); L
Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x

```

We get the vector spaces, and maps back and forth:

```

sage: V, from_V, to_V = L.free_module()
sage: V
Vector space of dimension 5 over Rational function field in x over Rational
↪Field
sage: from_V
Isomorphism:
  From: Vector space of dimension 5 over Rational function field in x over
↪Rational Field
  To:   Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
sage: to_V
Isomorphism:
  From: Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
  To:   Vector space of dimension 5 over Rational function field in x over
↪Rational Field

```

We convert an element of the vector space back to the function field:

```

sage: from_V(V.1)
y

```

We define an interesting element of the function field:

```
sage: a = 1/L.0; a
(x/(x^4 + 1))*y^4 - 2*x^2/(x^4 + 1)
```

We convert it to the vector space, and get a vector over the base field:

```
sage: to_V(a)
(-2*x^2/(x^4 + 1), 0, 0, 0, x/(x^4 + 1))
```

We convert to and back, and get the same element:

```
sage: from_V(to_V(a)) == a
True
```

In the other direction:

```
sage: v = x*V.0 + (1/x)*V.1
sage: to_V(from_V(v)) == v
True
```

And we show how it works over an extension of an extension field:

```
sage: R2.<z> = L[]; M.<z> = L.extension(z^2 - y)
sage: M.free_module()
(Vector space of dimension 2 over Function field in y defined by y^5 - 2*x*y
↪ + (-x^4 - 1)/x, Isomorphism:
  From: Vector space of dimension 2 over Function field in y defined by y^5 -
↪ 2*x*y + (-x^4 - 1)/x
  To: Function field in z defined by z^2 - y, Isomorphism:
  From: Function field in z defined by z^2 - y
  To: Vector space of dimension 2 over Function field in y defined by y^5 -
↪ 2*x*y + (-x^4 - 1)/x)
```

We can also get the vector space of M over K:

```
sage: M.free_module(K)
(Vector space of dimension 10 over Rational function field in x over Rational
↪ Field, Isomorphism:
  From: Vector space of dimension 10 over Rational function field in x over
↪ Rational Field
  To: Function field in z defined by z^2 - y, Isomorphism:
  From: Function field in z defined by z^2 - y
  To: Vector space of dimension 10 over Rational function field in x over
↪ Rational Field)
```

gen ($n=0$)

Return the n -th generator of the function field. By default, n is 0; any other value of n leads to an error. The generator is the class of y , if we view the function field as being presented as $K[y]/(f(y))$.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.gen()
y
sage: L.gen(1)
Traceback (most recent call last):
...
IndexError: there is only one generator
```

genus()

Return the genus of the function field.

For now, the genus is computed using Singular.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^3 - (x^3 + 2*x*y + 1/x))
sage: L.genus()
3
```

hom(im_gens, base_morphism=None)

Create a homomorphism from the function field to another function field.

INPUT:

- `im_gens` – list of images of the generators of the function field and of successive base rings.
- `base_morphism` – homomorphism of the base ring, after the `im_gens` are used. Thus if `im_gens` has length 2, then `base_morphism` should be a morphism from the base ring of the base ring of the function field.

EXAMPLES:

We create a rational function field, and a quadratic extension of it:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
```

We make the field automorphism that sends y to $-y$:

```
sage: f = L.hom(-y); f
Function Field endomorphism of Function field in y defined by y^2 - x^3 - 1
Defn: y |--> -y
```

Evaluation works:

```
sage: f(y*x - 1/x)
-x*y - 1/x
```

We try to define an invalid morphism:

```
sage: f = L.hom(y+1)
Traceback (most recent call last):
...
ValueError: invalid morphism
```

We make a morphism of the base rational function field:

```
sage: phi = K.hom(x+1); phi
Function Field endomorphism of Rational function field in x over Rational_
Field
Defn: x |--> x + 1
sage: phi(x^3 - 3)
x^3 + 3*x^2 + 3*x - 2
sage: (x+1)^3-3
x^3 + 3*x^2 + 3*x - 2
```

We make a morphism by specifying where the generators and the base generators go:


```
sage: L.hom([-y, x])
Function Field endomorphism of Function field in y defined by  $y^2 - x^3 - 1$ 
Defn: y |--> -y
      x |--> x
```

You can also specify a morphism on the base:

```
sage: R1.<q> = K[]
sage: L1.<q> = K.extension(q^2 - (x+1)^3 - 1)
sage: L.hom(q, base_morphism=phi)
Function Field morphism:
From: Function field in y defined by  $y^2 - x^3 - 1$ 
To:   Function field in q defined by  $q^2 - x^3 - 3x^2 - 3x - 2$ 
Defn: y |--> q
      x |--> x + 1
```

We make another extension of a rational function field:

```
sage: K2.<t> = FunctionField(QQ); R2.<w> = K2[]
sage: L2.<w> = K2.extension((4*w)^2 - (t+1)^3 - 1)
```

We define a morphism, by giving the images of generators:

```
sage: f = L.hom([4*w, t+1]); f
Function Field morphism:
From: Function field in y defined by  $y^2 - x^3 - 1$ 
To:   Function field in w defined by  $16w^2 - t^3 - 3t^2 - 3t - 2$ 
Defn: y |--> 4*w
      x |--> t + 1
```

Evaluation works, as expected:

```
sage: f(y+x)
4*w + t + 1
sage: f(x*y + x/(x^2+1))
(4*t + 4)*w + (t + 1)/(t^2 + 2*t + 2)
```

We make another extension of a rational function field:

```
sage: K3.<yy> = FunctionField(QQ); R3.<xx> = K3[]
sage: L3.<xx> = K3.extension(yy^2 - xx^3 - 1)
```

This is the function field L with the generators exchanged. We define a morphism to L:

```
sage: g = L3.hom([x,y]); g
Function Field morphism:
From: Function field in xx defined by  $-xx^3 + yy^2 - 1$ 
To:   Function field in y defined by  $y^2 - x^3 - 1$ 
Defn: xx |--> x
      yy |--> y
```

is_separable (*base=None*)

Return whether this is a separable extension of base.

INPUT:

- base – a function field from which this field has been created as an extension or None (default: None); if None, then return whether this is a separable extension over its base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: L.is_separable()
False
sage: R.<z> = L[]
sage: M.<z> = L.extension(z^3 - y)
sage: M.is_separable()
True
sage: M.is_separable(K)
False

sage: K.<x> = FunctionField(GF(5))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.is_separable()
True

sage: K.<x> = FunctionField(GF(5))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - 1)
sage: L.is_separable()
False
```

maximal_order()

Return the maximal order of the function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.maximal_order()
Maximal order of Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x
```

maximal_order_infinite()

Return the maximal infinite order of the function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.maximal_order_infinite()
Maximal infinite order of Function field in y defined by y^5 - 2*x*y + (-x^4 - 1)/x

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: F.maximal_order_infinite()
Maximal infinite order of Function field in y defined by y^3 + x^6 + x^4 + x^2

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: L.maximal_order_infinite()
Maximal infinite order of Function field in y defined by y^2 + y + (x^2 + 1)/x
```

monic_integral_model(names=None)

Return a function field isomorphic to this field but which is an extension of a rational function field with

defining polynomial that is monic and integral over the constant base field.

INPUT:

- `names` – a string or a tuple of up to two strings (default: `None`), the name of the generator of the field, and the name of the generator of the underlying rational function field (if a tuple); if not given, then the names are chosen automatically.

OUTPUT:

A triple (F, f, ι) where F is a function field, f is an isomorphism from F to this field, and ι is the inverse of f .

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(x^2*y^5 - 1/x); L
Function field in y defined by x^2*y^5 - 1/x
sage: A, from_A, to_A = L.monic_integral_model('z')
sage: A
Function field in z defined by z^5 - x^12
sage: from_A
Function Field morphism:
  From: Function field in z defined by z^5 - x^12
  To:   Function field in y defined by x^2*y^5 - 1/x
  Defn: z |--> x^3*y
        x |--> x
sage: to_A
Function Field morphism:
  From: Function field in y defined by x^2*y^5 - 1/x
  To:   Function field in z defined by z^5 - x^12
  Defn: y |--> 1/x^3*z
        x |--> x
sage: to_A(y)
1/x^3*z
sage: from_A(to_A(y))
y
sage: from_A(to_A(1/y))
x^3*y^4
sage: from_A(to_A(1/y)) == 1/y
True
```

This also works for towers of function fields:

```
sage: R.<z> = L[]
sage: M.<z> = L.extension(z^2*y - 1/x)
sage: M.monic_integral_model()
(Function field in z_ defined by z_^10 - x^18, Function Field morphism:
  From: Function field in z_ defined by z_^10 - x^18
  To:   Function field in z defined by y*z^2 - 1/x
  Defn: z_ |--> x^2*z
        x |--> x, Function Field morphism:
  From: Function field in z defined by y*z^2 - 1/x
  To:   Function field in z_ defined by z_^10 - x^18
  Defn: z |--> 1/x^2*z_
        y |--> 1/x^15*z_^8
        x |--> x)
```

`ngens()`

Return the number of generators of the function field over its base field. This is by definition 1.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.ngens()
1
```

polynomial()

Return the univariate polynomial that defines the function field, that is, the polynomial $f(y)$ so that the function field is of the form $K[y]/(f(y))$.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.polynomial()
y^5 - 2*x*y + (-x^4 - 1)/x
```

polynomial_ring()

Return the polynomial ring used to represent elements of the function field. If we view the function field as being presented as $K[y]/(f(y))$, then this function returns the ring $K[y]$.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.polynomial_ring()
Univariate Polynomial Ring in y over Rational function field in x over
↪Rational Field
```

primitive_element()

Return a primitive element over the underlying rational function field.

If this is a finite extension of a rational function field $K(x)$ with K perfect, then this is a simple extension of $K(x)$, i.e., there is a primitive element y which generates this field over $K(x)$. This method returns such an element y .

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2-x)
sage: R.<z> = L[]
sage: M.<z> = L.extension(z^2-y)
sage: R.<z> = L[]
sage: N.<u> = L.extension(z^2-x-1)
sage: N.primitive_element()
u + y
sage: M.primitive_element()
z
sage: L.primitive_element()
y
```

This also works for inseparable extensions:

```
sage: K.<x> = FunctionField(GF(2))
sage: R.<Y> = K[]
```

(continues on next page)

(continued from previous page)

```

sage: L.<y> = K.extension(Y^2-x)
sage: R.<Z> = L[]
sage: M.<z> = L.extension(Z^2-y)
sage: M.primitive_element()
z

```

random_element (*args, **kws)

Create a random element of the function field. Parameters are passed onto the random_element method of the base_field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - (x^2 + x))
sage: L.random_element() # random
((x^2 - x + 2/3)/(x^2 + 1/3*x - 1))*y^2 + ((-1/4*x^2 + 1/2*x - 1)/(-5/2*x + 2/
↪ 3))*y
+ (-1/2*x^2 - 4)/(-12*x^2 + 1/2*x - 1/95)

```

separable_model (names=None)

Return a function field isomorphic to this field which is a separable extension of a rational function field.

INPUT:

- names – a tuple of two strings or None (default: None); the second entry will be used as the variable name of the rational function field, the first entry will be used as the variable name of its separable extension. If None, then the variable names will be chosen automatically.

OUTPUT:

A triple (F, f, t) where F is a function field, f is an isomorphism from F to this function field, and t is the inverse of f .

ALGORITHM:

Suppose that the constant base field is perfect. If this is a monic integral inseparable extension of a rational function field, then the defining polynomial is separable if we swap the variables (Proposition 4.8 in Chapter VIII of [Lan2002].) The algorithm reduces to this case with `monic_integral_model()`.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3)
sage: L.separable_model(('t', 'w'))
(Function field in t defined by t^3 + w^2,
Function Field morphism:
  From: Function field in t defined by t^3 + w^2
  To:   Function field in y defined by y^2 + x^3
  Defn: t |--> x
        w |--> y,
Function Field morphism:
  From: Function field in y defined by y^2 + x^3
  To:   Function field in t defined by t^3 + w^2
  Defn: y |--> w
        x |--> t)

```

This also works for non-integral polynomials:

```

sage: K.<x> = FunctionField(GF(2))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2/x - x^2)
sage: L.separable_model()
(Function field in y_ defined by y_3 + x_2,
Function Field morphism:
  From: Function field in y_ defined by y_3 + x_2
  To:   Function field in y defined by 1/x*y^2 + x^2
  Defn: y_ |--> x
        x_ |--> y,
Function Field morphism:
  From: Function field in y defined by 1/x*y^2 + x^2
  To:   Function field in y_ defined by y_3 + x_2
  Defn: y |--> x_
        x |--> y_)

```

If the base field is not perfect this is only implemented in trivial cases:

```

sage: k.<t> = FunctionField(GF(2))
sage: k.is_perfect()
False
sage: K.<x> = FunctionField(k)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^3 - t)
sage: L.separable_model()
(Function field in y defined by y^3 + t,
Function Field endomorphism of Function field in y defined by y^3 + t
  Defn: y |--> y
        x |--> x,
Function Field endomorphism of Function field in y defined by y^3 + t
  Defn: y |--> y
        x |--> x)

```

Some other cases for which a separable model could be constructed are not supported yet:

```

sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - t)
sage: L.separable_model()
Traceback (most recent call last):
...
NotImplementedError: constructing a separable model is only implemented for
↳function fields over a perfect constant base field

```

simple_model (name=None)

Return a function field isomorphic to this field which is a simple extension of a rational function field.

INPUT:

- name – a string (default: None), the name of generator of the simple extension. If None, then the name of the generator will be the same as the name of the generator of this function field.

OUTPUT:

A triple (F, f, t) where F is a field isomorphic to this field, f is an isomorphism from F to this function field and t is the inverse of f .

EXAMPLES:

A tower of four function fields:

```

sage: K.<x> = FunctionField(QQ); R.<z> = K[]
sage: L.<z> = K.extension(z^2-x); R.<u> = L[]
sage: M.<u> = L.extension(u^2-z); R.<v> = M[]
sage: N.<v> = M.extension(v^2-u)

```

The fields N and M as simple extensions of K:

```

sage: N.simple_model()
(Function field in v defined by v^8 - x,
Function Field morphism:
  From: Function field in v defined by v^8 - x
  To:   Function field in v defined by v^2 - u
  Defn: v |--> v,
Function Field morphism:
  From: Function field in v defined by v^2 - u
  To:   Function field in v defined by v^8 - x
  Defn: v |--> v
        u |--> v^2
        z |--> v^4
        x |--> x)
sage: M.simple_model()
(Function field in u defined by u^4 - x,
Function Field morphism:
  From: Function field in u defined by u^4 - x
  To:   Function field in u defined by u^2 - z
  Defn: u |--> u,
Function Field morphism:
  From: Function field in u defined by u^2 - z
  To:   Function field in u defined by u^4 - x
  Defn: u |--> u
        z |--> u^2
        x |--> x)

```

An optional parameter name can be used to set the name of the generator of the simple extension:

```

sage: M.simple_model(name='t')
(Function field in t defined by t^4 - x, Function Field morphism:
  From: Function field in t defined by t^4 - x
  To:   Function field in u defined by u^2 - z
  Defn: t |--> u, Function Field morphism:
  From: Function field in u defined by u^2 - z
  To:   Function field in t defined by t^4 - x
  Defn: u |--> t
        z |--> t^2
        x |--> x)

```

An example with higher degrees:

```

sage: K.<x> = FunctionField(GF(3)); R.<y> = K[]
sage: L.<y> = K.extension(y^5-x); R.<z> = L[]
sage: M.<z> = L.extension(z^3-x)
sage: M.simple_model()
(Function field in z defined by z^15 + x*z^12 + x^2*z^9 + 2*x^3*z^6 + 2*x^4*z^
↪ 3 + 2*x^5 + 2*x^3,
Function Field morphism:
  From: Function field in z defined by z^15 + x*z^12 + x^2*z^9 + 2*x^3*z^6 +
↪ 2*x^4*z^3 + 2*x^5 + 2*x^3

```

(continues on next page)

(continued from previous page)

```

To:    Function field in z defined by  $z^3 + 2x$ 
Defn:   $z \mapsto z + y$ ,
Function Field morphism:
From:  Function field in z defined by  $z^3 + 2x$ 
To:    Function field in z defined by  $z^{15} + xz^{12} + x^2z^9 + 2x^3z^6 + 2x^4z^3 + 2x^5 + 2x^3$ 
Defn:   $z \mapsto 2/xz^6 + 2z^3 + z + 2x$ 
        $y \mapsto 1/xz^6 + z^3 + x$ 
        $x \mapsto x$ )

```

This also works for inseparable extensions:

```

sage: K.<x> = FunctionField(GF(2)); R.<y> = K[]
sage: L.<y> = K.extension(y^2-x); R.<z> = L[]
sage: M.<z> = L.extension(z^2-y)
sage: M.simple_model()
(Function field in z defined by  $z^4 + x$ , Function Field morphism:
  From: Function field in z defined by  $z^4 + x$ 
  To:    Function field in z defined by  $z^2 + y$ 
  Defn:   $z \mapsto z$ , Function Field morphism:
  From: Function field in z defined by  $z^2 + y$ 
  To:    Function field in z defined by  $z^4 + x$ 
  Defn:   $z \mapsto z$ 
         $y \mapsto z^2$ 
         $x \mapsto x$ )

```

class sage.rings.function_field.function_field.**FunctionField_simple** (*polynomial, names, category=None*)

Bases: *sage.rings.function_field.function_field.FunctionField_polymod*

Function fields defined by irreducible and separable polynomials over rational function fields.

constant_field()

Return the algebraic closure of the base constant field in the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(3)); L.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: L.constant_field()
Finite Field of size 3

```

exact_constant_field (*name='t'*)

Return the exact constant field and its embedding into the function field.

INPUT:

- *name* – *name* (default: *t*) of the generator of the exact constant field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(3)); L.<y> = K[]
sage: f = Y^2 - x*Y + x^2 + 1 # irreducible but not absolutely irreducible
sage: L.<y> = K.extension(f)
sage: L.genus()
0

```

(continues on next page)

(continued from previous page)

```

sage: L.exact_constant_field()
(Finite Field in t of size 3^2, Ring morphism:
  From: Finite Field in t of size 3^2
  To:   Function field in y defined by y^2 + 2*x*y + x^2 + 1
  Defn: t |--> y + x)
sage: (y+x).divisor()
0

```

genus()

Return the genus of the function field.

EXAMPLES:

```

sage: F.<a> = GF(16)
sage: K.<x> = FunctionField(F); K
Rational function field in x over Finite Field in a of size 2^4
sage: R.<t> = PolynomialRing(K)
sage: L.<y> = K.extension(t^4+t-x^5)
sage: L.genus()
6

```

The genus is computed by the Hurwitz genus formula.

places_above(p)

Return places lying above p.

INPUT:

- p – place of the base rational function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: all(q.place_below() == p for p in K.places() for q in F.places_above(p))
True

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: O = K.maximal_order()
sage: pls = [O.ideal(x-c).place() for c in [-2, -1, 0, 1, 2]]
sage: all(q.place_below() == p for p in pls for q in F.places_above(p))
True

sage: K.<x> = FunctionField(QQbar); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: O = K.maximal_order()
sage: pls = [O.ideal(x-QQbar(sqrt(c))).place() for c in [-2, -1, 0, 1, 2]]
sage: all(q.place_below() == p for p in pls for q in F.places_above(p))
True

```

residue_field(place, name=None)

Return the residue field associated with the place along with the maps from and to the residue field.

INPUT:

- place – place of the function field
- name – string; name of the generator of the residue field

The domain of the map to the residue field is the discrete valuation ring associated with the place.

The discrete valuation ring is defined as the ring of all elements of the function field with nonnegative valuation at the place. The maximal ideal is the set of elements of positive valuation. The residue field is then the quotient of the discrete valuation ring by its maximal ideal.

If an element not in the valuation ring is applied to the map, an exception `TypeError` is raised.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: R, fr_R, to_R = L.residue_field(p)
sage: R
Finite Field of size 2
sage: f = 1 + y
sage: f.valuation(p)
-1
sage: to_R(f)
Traceback (most recent call last):
...
TypeError: ...
sage: (1+1/f).valuation(p)
0
sage: to_R(1 + 1/f)
1
sage: [fr_R(e) for e in R]
[0, 1]
```

```
class sage.rings.function_field.function_field.RationalFunctionField(constant_field,
                                                                    names,
                                                                    cate-
                                                                    gory=None)
```

Bases: `sage.rings.function_field.function_field.FunctionField`

Rational function field in one variable, over an arbitrary base field.

INPUT:

- `constant_field` – arbitrary field
- `names` – string or tuple of length 1

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(3)); K
Rational function field in t over Finite Field of size 3
sage: K.gen()
t
sage: 1/t + t^3 + 5
(t^4 + 2*t + 1)/t

sage: K.<t> = FunctionField(QQ); K
Rational function field in t over Rational Field
sage: K.gen()
t
sage: 1/t + t^3 + 5
(t^4 + 5*t + 1)/t
```

There are various ways to get at the underlying fields and rings associated to a rational function field:

```

sage: K.<t> = FunctionField(GF(7))
sage: K.base_field()
Rational function field in t over Finite Field of size 7
sage: K.field()
Fraction Field of Univariate Polynomial Ring in t over Finite Field of size 7
sage: K.constant_field()
Finite Field of size 7
sage: K.maximal_order()
Maximal order of Rational function field in t over Finite Field of size 7

sage: K.<t> = FunctionField(QQ)
sage: K.base_field()
Rational function field in t over Rational Field
sage: K.field()
Fraction Field of Univariate Polynomial Ring in t over Rational Field
sage: K.constant_field()
Rational Field
sage: K.maximal_order()
Maximal order of Rational function field in t over Rational Field

```

We define a morphism:

```

sage: K.<t> = FunctionField(QQ)
sage: L = FunctionField(QQ, 'tbar') # give variable name as second input
sage: K.hom(L.gen())
Function Field morphism:
  From: Rational field in t over Rational Field
  To:   Rational function field in tbar over Rational Field
  Defn: t |--> tbar

```

Here are some calculations over a number field:

```

sage: R.<x> = FunctionField(QQ)
sage: L.<y> = R[]
sage: F.<y> = R.extension(y^2 - (x^2+1))
sage: (y/x).divisor()
- Place (x, y - 1)
- Place (x, y + 1)
+ Place (x^2 + 1, y)

sage: A.<z> = QQ[]
sage: NF.<i> = NumberField(z^2+1)
sage: R.<x> = FunctionField(NF)
sage: L.<y> = R[]
sage: F.<y> = R.extension(y^2 - (x^2+1))

sage: (x/y*x.differential()).divisor()
-2*Place (1/x, 1/x*y - 1)
- 2*Place (1/x, 1/x*y + 1)
+ Place (x, y - 1)
+ Place (x, y + 1)

sage: (x/y).divisor()
- Place (x - i, y)
+ Place (x, y - 1)
+ Place (x, y + 1)
- Place (x + i, y)

```

Element

alias of `sage.rings.function_field.element.FunctionFieldElement_rational`

base_field()

Return the base field of the rational function field, which is just the function field itself.

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(7))
sage: K.base_field()
Rational function field in t over Finite Field of size 7
```

change_variable_name (*name*)

Return a field isomorphic to this field with variable *name*.

INPUT:

- *name* – a string or a tuple consisting of a single string, the name of the new variable

OUTPUT:

A triple F, f, t where F is a rational function field, f is an isomorphism from F to this field, and t is the inverse of f .

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: L,f,t = K.change_variable_name('y')
sage: L,f,t
(Rational function field in y over Rational Field,
Function Field morphism:
  From: Rational function field in y over Rational Field
  To:   Rational function field in x over Rational Field
  Defn: y |--> x,
Function Field morphism:
  From: Rational function field in x over Rational Field
  To:   Rational function field in y over Rational Field
  Defn: x |--> y)
sage: L.change_variable_name('x')[0] is K
True
```

constant_base_field()

Return the field of which the rational function field is a transcendental extension.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: K.constant_base_field()
Rational Field
```

constant_field()

Return the field of which the rational function field is a transcendental extension.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: K.constant_base_field()
Rational Field
```

degree (*base=None*)

Return the degree over the base field of the rational function field. Since the base field is the rational

function field itself, the degree is 1.

INPUT:

- `base` – the base field of the vector space; must be the function field itself (the default)

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: K.degree()
1
```

derivation()

Return a derivation of the rational function field over the constant base field.

The derivation maps the generator of the rational function field to 1.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(3))
sage: m = K.derivation(); m
Derivation map:
  From: Rational function field in x over Finite Field of size 3
  To:   Rational function field in x over Finite Field of size 3
  Defn: x |--> 1
sage: m(x)
1
```

different()

Return the different of the rational function field.

For a rational function field, the different is simply the zero divisor.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: K.different()
0
```

equation_order()

Return the maximal order of the function field.

Since this is a rational function field it is of the form $K(t)$, and the maximal order is by definition $K[t]$, where K is the constant field.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: K.maximal_order()
Maximal order of Rational function field in t over Rational Field
sage: K.equation_order()
Maximal order of Rational function field in t over Rational Field
```

equation_order_infinite()

Return the maximal infinite order of the function field.

By definition, this is the valuation ring of the degree valuation of the rational function field.

EXAMPLES:

```

sage: K.<t> = FunctionField(QQ)
sage: K.maximal_order_infinite()
Maximal infinite order of Rational function field in t over Rational Field
sage: K.equation_order_infinite()
Maximal infinite order of Rational function field in t over Rational Field

```

extension (*f*, *names=None*)

Create an extension $L = K[y]/(f(y))$ of the rational function field.

INPUT:

- *f* – univariate polynomial over self
- *names* – string or length-1 tuple

OUTPUT:

- a function field

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: K.extension(y^5 - x^3 - 3*x + x*y)
Function field in y defined by y^5 + x*y - x^3 - 3*x

```

A nonintegral defining polynomial:

```

sage: K.<t> = FunctionField(QQ); R.<y> = K[]
sage: K.extension(y^3 + (1/t)*y + t^3/(t+1))
Function field in y defined by y^3 + 1/t*y + t^3/(t + 1)

```

The defining polynomial need not be monic or integral:

```

sage: K.extension(t*y^3 + (1/t)*y + t^3/(t+1))
Function field in y defined by t*y^3 + 1/t*y + t^3/(t + 1)

```

field()

Return the underlying field, forgetting the function field structure.

EXAMPLES:

```

sage: K.<t> = FunctionField(GF(7))
sage: K.field()
Fraction Field of Univariate Polynomial Ring in t over Finite Field of size 7

```

See also:

`sage.rings.fraction_field.FractionField_1poly_field.function_field()`

free_module (*base=None*, *basis=None*, *map=True*)

Return a vector space V and isomorphisms from the field to V and from V to the field.

This function allows us to identify the elements of this field with elements of a one-dimensional vector space over the field itself. This method exists so that all function fields (rational or not) have the same interface.

INPUT:

- *base* – the base field of the vector space; must be the function field itself (the default)
- *basis* – (ignored) a basis for the vector space
- *map* – (default `True`), whether to return maps to and from the vector space

OUTPUT:

- a vector space V over base field
- an isomorphism from V to the field
- the inverse isomorphism from the field to V

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: K.free_module()
(Vector space of dimension 1 over Rational function field in x over Rational
↪Field, Isomorphism:
  From: Vector space of dimension 1 over Rational function field in x over
↪Rational Field
  To:   Rational function field in x over Rational Field, Isomorphism:
  From: Rational function field in x over Rational Field
  To:   Vector space of dimension 1 over Rational function field in x over
↪Rational Field)
```

gen ($n=0$)

Return the n -th generator of the function field. If n is not 0, then an `IndexError` is raised.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ); K.gen()
t
sage: K.gen().parent()
Rational function field in t over Rational Field
sage: K.gen(1)
Traceback (most recent call last):
...
IndexError: Only one generator.
```

genus ()

Return the genus of the function field, namely 0.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: K.genus()
0
```

hom ($im_gens, base_morphism=None$)

Create a homomorphism from `self` to another ring.

INPUT:

- `im_gens` – exactly one element of some ring. It must be invertible and transcendental over the image of `base_morphism`; this is not checked.
- `base_morphism` – a homomorphism from the base field into the other ring. If `None`, try to use a coercion map.

OUTPUT:

- a map between function fields

EXAMPLES:

We make a map from a rational function field to itself:

```

sage: K.<x> = FunctionField(GF(7))
sage: K.hom( (x^4 + 2)/x)
Function Field endomorphism of Rational function field in x over Finite Field
↳ of size 7
Defn: x |--> (x^4 + 2)/x

```

We construct a map from a rational function field into a non-rational extension field:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^3 + 6*x^3 + x)
sage: f = K.hom(y^2 + y + 2); f
Function Field morphism:
  From: Rational function field in x over Finite Field of size 7
  To:   Function field in y defined by y^3 + 6*x^3 + x
  Defn: x |--> y^2 + y + 2
sage: f(x)
y^2 + y + 2
sage: f(x^2)
5*y^2 + (x^3 + 6*x + 4)*y + 2*x^3 + 5*x + 4

```

maximal_order()

Return the maximal order of the function field.

Since this is a rational function field it is of the form $K(t)$, and the maximal order is by definition $K[t]$, where K is the constant field.

EXAMPLES:

```

sage: K.<t> = FunctionField(QQ)
sage: K.maximal_order()
Maximal order of Rational function field in t over Rational Field
sage: K.equation_order()
Maximal order of Rational function field in t over Rational Field

```

maximal_order_infinite()

Return the maximal infinite order of the function field.

By definition, this is the valuation ring of the degree valuation of the rational function field.

EXAMPLES:

```

sage: K.<t> = FunctionField(QQ)
sage: K.maximal_order_infinite()
Maximal infinite order of Rational function field in t over Rational Field
sage: K.equation_order_infinite()
Maximal infinite order of Rational function field in t over Rational Field

```

ngens()

Return the number of generators, which is 1.

EXAMPLES:

```

sage: K.<t> = FunctionField(QQ)
sage: K.ngens()
1

```

polynomial_ring(var='x')

Return a polynomial ring in one variable over the rational function field.

INPUT:

- `var` – string; name of the variable

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: K.polynomial_ring()
Univariate Polynomial Ring in x over Rational function field in x over
↳Rational Field
sage: K.polynomial_ring('T')
Univariate Polynomial Ring in T over Rational function field in x over
↳Rational Field
```

random_element (*args, **kws)

Create a random element of the rational function field.

Parameters are passed to the `random_element` method of the underlying fraction field.

EXAMPLES:

```
sage: FunctionField(QQ, 'alpha').random_element() # random
(-1/2*alpha^2 - 4)/(-12*alpha^2 + 1/2*alpha - 1/95)
```

residue_field (place, name=None)

Return the residue field of the place along with the maps from and to it.

INPUT:

- `place` – place of the function field
- `name` – string; name of the generator of the residue field

EXAMPLES:

```
sage: F.<x> = FunctionField(GF(5))
sage: p = F.places_finite(2)[0]
sage: R, fr_R, to_R = F.residue_field(p)
sage: R
Finite Field in z2 of size 5^2
sage: to_R(x) in R
True
```

class `sage.rings.function_field.function_field.RationalFunctionField_char_zero` (*constant_field*,
names,
cat-
e-
gory=None)

Bases: `sage.rings.function_field.function_field.RationalFunctionField`

Rational function fields of characteristic zero.

higher_derivation ()

Return the higher derivation for the function field.

This is also called the Hasse-Schmidt derivation.

EXAMPLES:

```
sage: F.<x> = FunctionField(QQ)
sage: d = F.higher_derivation()
sage: [d(x^5,i) for i in range(10)]
[x^5, 5*x^4, 10*x^3, 10*x^2, 5*x, 1, 0, 0, 0, 0]
```

(continues on next page)

(continued from previous page)

```
sage: [d(x^9,i) for i in range(10)]
[x^9, 9*x^8, 36*x^7, 84*x^6, 126*x^5, 126*x^4, 84*x^3, 36*x^2, 9*x, 1]
```

class sage.rings.function_field.function_field.**RationalFunctionField_global** (*constant_field,*
names,
cat-
e-
gory=None)

Bases: *sage.rings.function_field.function_field.RationalFunctionField*

Rational function field over finite fields.

get_place (*degree*)

Return a place of degree.

INPUT:

- degree – a positive integer

EXAMPLES:

```
sage: F.<a> = GF(2)
sage: K.<x> = FunctionField(F)
sage: K.get_place(1)
Place (x)
sage: K.get_place(2)
Place (x^2 + x + 1)
sage: K.get_place(3)
Place (x^3 + x + 1)
sage: K.get_place(4)
Place (x^4 + x + 1)
sage: K.get_place(5)
Place (x^5 + x^2 + 1)
```

higher_derivation ()

Return the higher derivation for the function field.

This is also called the Hasse-Schmidt derivation.

EXAMPLES:

```
sage: F.<x> = FunctionField(GF(5))
sage: d = F.higher_derivation()
sage: [d(x^5,i) for i in range(10)]
[x^5, 0, 0, 0, 0, 1, 0, 0, 0, 0]
sage: [d(x^7,i) for i in range(10)]
[x^7, 2*x^6, x^5, 0, 0, x^2, 2*x, 1, 0, 0]
```

place_infinite ()

Return the unique place at infinity.

EXAMPLES:

```
sage: F.<x> = FunctionField(GF(5))
sage: F.place_infinite()
Place (1/x)
```

places (*degree=1*)

Return all places of the degree.

INPUT:

- degree – (default: 1) a positive integer

EXAMPLES:

```
sage: F.<x> = FunctionField(GF(5))
sage: F.places()
[Place (1/x),
 Place (x),
 Place (x + 1),
 Place (x + 2),
 Place (x + 3),
 Place (x + 4)]
```

places_finite(*degree=1*)

Return the finite places of the degree.

INPUT:

- degree – (default: 1) a positive integer

EXAMPLES:

```
sage: F.<x> = FunctionField(GF(5))
sage: F.places_finite()
[Place (x), Place (x + 1), Place (x + 2), Place (x + 3), Place (x + 4)]
```

`sage.rings.function_field.function_field.is_FunctionField(x)`

Return True if x is a function field.

EXAMPLES:

```
sage: from sage.rings.function_field.function_field import is_FunctionField
sage: is_FunctionField(QQ)
False
sage: is_FunctionField(FunctionField(QQ, 't'))
True
```


ELEMENTS OF FUNCTION FIELDS

Sage provides arithmetic with elements of function fields.

EXAMPLES:

Arithmetic with rational functions:

```
sage: K.<t> = FunctionField(QQ)
sage: f = t - 1
sage: g = t^2 - 3
sage: h = f^2/g^3
sage: h.valuation(t-1)
2
sage: h.valuation(t)
0
sage: h.valuation(t^2 - 3)
-3
```

Derivatives of elements in separable extensions:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (y^3 + x).derivative()
((x^2 + 1)/x^2)*y + (x^4 + x^3 + 1)/x^3
```

The divisor of an element of a global function field:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: y.divisor()
- Place (1/x, 1/x*y)
- Place (x, x*y)
+ 2*Place (x + 1, x*y)
```

AUTHORS:

- William Stein: initial version
- Robert Bradshaw (2010-05-27): cythonize function field elements
- Julian Rueth (2011-06-28): treat zero correctly
- Maarten Derickx (2011-09-11): added doctests, fixed pickling
- Kwankyu Lee (2017-04-30): added elements for global function fields

```
class sage.rings.function_field.element.FunctionFieldElement
    Bases: sage.structure.element.FieldElement
```

Abstract base class for function field elements.

EXAMPLES:

```
sage: t = FunctionField(QQ, 't').gen()
sage: isinstance(t, sage.rings.function_field.element.FunctionFieldElement)
True
```

characteristic_polynomial (*args, **kws)

Return the characteristic polynomial of the element. Give an optional input string to name the variable in the characteristic polynomial.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3); R.<z> = L[]
sage: M.<z> = L.extension(z^3 - y^2*z + x)
sage: x.characteristic_polynomial('W')
W - x
sage: y.characteristic_polynomial('W')
W^2 - x*W + 4*x^3
sage: z.characteristic_polynomial('W')
W^3 + (-x*y + 4*x^3)*W + x
```

charpoly (*args, **kws)

Return the characteristic polynomial of the element. Give an optional input string to name the variable in the characteristic polynomial.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3); R.<z> = L[]
sage: M.<z> = L.extension(z^3 - y^2*z + x)
sage: x.characteristic_polynomial('W')
W - x
sage: y.characteristic_polynomial('W')
W^2 - x*W + 4*x^3
sage: z.characteristic_polynomial('W')
W^3 + (-x*y + 4*x^3)*W + x
```

derivative ()

Return the derivative of the element.

The derivative is with respect to the generator of the base rational function field, over which the function field is a separable extension.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = (t + 1) / (t^2 - 1/3)
sage: f.derivative()
(-t^2 - 2*t - 1/3) / (t^4 - 2/3*t^2 + 1/9)

sage: K.<x> = FunctionField(GF(4)); L.<y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (y^3 + x).derivative()
((x^2 + 1)/x^2)*y + (x^4 + x^3 + 1)/x^3
```

differential ()

Return the differential dx where x is the element.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = 1 / t
sage: f.differential()
(-1/t^2) d(t)

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (y^3 + x).differential()
(((x^2 + 1)/x^2)*y + (x^4 + x^3 + 1)/x^3) d(x)
```

divisor()

Return the divisor of the element.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2))
sage: f = 1/(x^3 + x^2 + x)
sage: f.divisor()
3*Place (1/x)
- Place (x)
- Place (x^2 + x + 1)
```

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: y.divisor()
- Place (1/x, 1/x*y)
- Place (x, x*y)
+ 2*Place (x + 1, x*y)
```

divisor_of_poles()

Return the divisor of poles for the element.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2))
sage: f = 1/(x^3 + x^2 + x)
sage: f.divisor_of_poles()
Place (x)
+ Place (x^2 + x + 1)
```

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (x/y).divisor_of_poles()
Place (1/x, 1/x*y) + 2*Place (x + 1, x*y)
```

divisor_of_zeros()

Return the divisor of zeros for the element.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2))
sage: f = 1/(x^3 + x^2 + x)
sage: f.divisor_of_zeros()
3*Place (1/x)
```

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (x/y).divisor_of_zeros()
3*Place (x, x*y)
```

evaluate (*place*)

Return the value of the element at the place.

INPUT:

- *place* – a function field place

OUTPUT:

If the element is in the valuation ring at the place, then an element in the residue field at the place is returned. Otherwise, `ValueError` is raised.

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(5))
sage: p = K.place_infinite()
sage: f = 1/t^2 + 3
sage: f.evaluate(p)
3
```

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p, = L.places_infinite()
sage: p, = L.places_infinite()
sage: (y + x).evaluate(p)
Traceback (most recent call last):
...
ValueError: has a pole at the place
sage: (y/x + 1).evaluate(p)
1
```

higher_derivative (*i*, *separating_element=None*)

Return the *i*-th derivative of the element with respect to the separating element.

INPUT:

- *i* – nonnegative integer
- *separating_element* – a separating element of the function field; the default is the generator of the rational function field

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(2))
sage: f = t^2
sage: f.higher_derivative(2)
1
```

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (y^3 + x).higher_derivative(2)
1/x^3*y + (x^6 + x^4 + x^3 + x^2 + x + 1)/x^5
```

is_integral ()

Determine if the element is integral over the maximal order of the base field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: y.is_integral()
True
sage: (y/x).is_integral()
True
sage: (y/x)^2 - (y/x) + 4*x
0
sage: (y/x^2).is_integral()
False
sage: (y/x).minimal_polynomial('W')
W^2 - W + 4*x

```

matrix (base=None)

Return the matrix of multiplication by this element, interpreting this element as an element of a vector space over base.

INPUT:

- base – a function field (default: None), if None, then the matrix is formed over the base field of this function field.

EXAMPLES:

A rational function field:

```

sage: K.<t> = FunctionField(QQ)
sage: t.matrix()
[t]
sage: (1/(t+1)).matrix()
[1/(t + 1)]

```

Now an example in a nontrivial extension of a rational function field:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: y.matrix()
[ 0      1]
[-4*x^3   x]
sage: y.matrix().charpoly('Z')
Z^2 - x*Z + 4*x^3

```

An example in a relative extension, where neither function field is rational:

```

sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: M.<T> = L[]
sage: Z.<alpha> = L.extension(T^3 - y^2*T + x)
sage: alpha.matrix()
[ 0      1      0]
[ 0      0      1]
[-x x*y - 4*x^3  0]
sage: alpha.matrix(K)
[ 0      0      1      0      0      0]
↪ 0]
[ 0      0      0      1      0      0]
↪ 0]

```

(continues on next page)

(continued from previous page)

```

[      0      0      0      0      1
↪0]
[      0      0      0      0      0
↪1]
[     -x      0    -4*x^3      x      0
↪0]
[      0     -x   -4*x^4 -4*x^3 + x^2      0
↪0]
sage: alpha.matrix(Z)
[alpha]

```

We show that this matrix does indeed work as expected when making a vector space from a function field:

```

sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: V, from_V, to_V = L.vector_space()
sage: y5 = to_V(y^5); y5
((x^4 + 1)/x, 2*x, 0, 0, 0)
sage: y4y = to_V(y^4) * y.matrix(); y4y
((x^4 + 1)/x, 2*x, 0, 0, 0)
sage: y5 == y4y
True

```

minimal_polynomial (*args, **kws)

Return the minimal polynomial of the element. Give an optional input string to name the variable in the characteristic polynomial.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3); R.<z> = L[]
sage: M.<z> = L.extension(z^3 - y^2*z + x)
sage: x.minimal_polynomial('W')
W - x
sage: y.minimal_polynomial('W')
W^2 - x*W + 4*x^3
sage: z.minimal_polynomial('W')
W^3 + (-x*y + 4*x^3)*W + x

```

minpoly (*args, **kws)

Return the minimal polynomial of the element. Give an optional input string to name the variable in the characteristic polynomial.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3); R.<z> = L[]
sage: M.<z> = L.extension(z^3 - y^2*z + x)
sage: x.minimal_polynomial('W')
W - x
sage: y.minimal_polynomial('W')
W^2 - x*W + 4*x^3
sage: z.minimal_polynomial('W')
W^3 + (-x*y + 4*x^3)*W + x

```

norm ()

Return the norm of the element.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: y.norm()
4*x^3
```

The norm is relative:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3); R.<z> = L[]
sage: M.<z> = L.extension(z^3 - y^2*z + x)
sage: z.norm()
-x
sage: z.norm().parent()
Function field in y defined by y^2 - x*y + 4*x^3
```

poles()

Return the list of the poles of the element.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2))
sage: f = 1/(x^3 + x^2 + x)
sage: f.poles()
[Place (x), Place (x^2 + x + 1)]
```

```
sage: K.<x> = FunctionField(GF(4)); L.<y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (x/y).poles()
[Place (1/x, 1/x*y), Place (x + 1, x*y)]
```

trace()

Return the trace of the element.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: y.trace()
x
```

valuation(place)

Return the valuation of the element at the place.

INPUT:

- place – a place of the function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); L.<y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_infinite()[0]
sage: y.valuation(p)
-1
```

```

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: p = O.ideal(x-1).place()
sage: y.valuation(p)
0

```

zeros()

Return the list of the zeros of the element.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: f = 1/(x^3 + x^2 + x)
sage: f.zeros()
[Place (1/x)]

```

```

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: (x/y).zeros()
[Place (x, x*y)]

```

class sage.rings.function_field.element.**FunctionFieldElement_polymod**

Bases: *sage.rings.function_field.element.FunctionFieldElement*

Elements of a finite extension of a function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: x*y + 1/x^3
x*y + 1/x^3

```

element()

Return the underlying polynomial that represents the element.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<T> = K[]
sage: L.<y> = K.extension(T^2 - x*T + 4*x^3)
sage: f = y/x^2 + x/(x^2+1); f
1/x^2*y + x/(x^2 + 1)
sage: f.element()
1/x^2*y + x/(x^2 + 1)

```

list()

Return the list of the coefficients representing the element.

If the function field is $K[y]/(f(y))$, then return the coefficients of the reduced presentation of the element as a polynomial in $K[y]$.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: a = ~(2*y + 1/x); a
(-1/8*x^2/(x^5 + 1/8*x^2 + 1/16))*y + (1/8*x^3 + 1/16*x)/(x^5 + 1/8*x^2 + 1/
↪ 16)

```

(continues on next page)

(continued from previous page)

```
sage: a.list()
[(1/8*x^3 + 1/16*x)/(x^5 + 1/8*x^2 + 1/16), -1/8*x^2/(x^5 + 1/8*x^2 + 1/16)]
sage: (x*y).list()
[0, x]
```

class sage.rings.function_field.element.**FunctionFieldElement_rational**

Bases: *sage.rings.function_field.element.FunctionFieldElement*

Elements of a rational function field.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ); K
Rational function field in t over Rational Field
sage: t^2 + 3/2*t
t^2 + 3/2*t
sage: FunctionField(QQ, 't').gen()^3
t^3
```

denominator()

Return the denominator of the rational function.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = (t+1) / (t^2 - 1/3); f
(t + 1)/(t^2 - 1/3)
sage: f.denominator()
t^2 - 1/3
```

element()

Return the underlying fraction field element that represents the element.

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(7))
sage: t.element()
t
sage: type(t.element())
<... 'sage.rings.fraction_field_FpT.FpTElement'>

sage: K.<t> = FunctionField(GF(131101))
sage: t.element()
t
sage: type(t.element())
<... 'sage.rings.fraction_field_element.FractionFieldElement_1poly_field'>
```

factor()

Factor the rational function.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = (t+1) / (t^2 - 1/3)
sage: f.factor()
(t + 1) * (t^2 - 1/3)^-1
sage: (7*f).factor()
(7) * (t + 1) * (t^2 - 1/3)^-1
```

(continues on next page)

(continued from previous page)

```
sage: ((7*f).factor()).unit()
7
sage: (f^3).factor()
(t + 1)^3 * (t^2 - 1/3)^-3
```

inverse_mod(I)

Return an inverse of the element modulo the integral ideal I , if I and the element together generate the unit ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order(); I = O.ideal(x^2+1)
sage: t = O(x+1).inverse_mod(I); t
-1/2*x + 1/2
sage: (t*(x+1) - 1) in I
True
```

is_square()

Return whether the element is a square.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: t.is_square()
False
sage: (t^2/4).is_square()
True
sage: f = 9 * (t+1)^6 / (t^2 - 2*t + 1); f.is_square()
True

sage: K.<t> = FunctionField(GF(5))
sage: (-t^2).is_square()
True
sage: (-t^2).sqrt()
2*t
```

list()

Return a list with just the element.

The list represents the element when the rational function field is viewed as a (one-dimensional) vector space over itself.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: t.list()
[t]
```

numerator()

Return the numerator of the rational function.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = (t+1) / (t^2 - 1/3); f
(t + 1)/(t^2 - 1/3)
```

(continues on next page)

(continued from previous page)

```
sage: f.numerator()
t + 1
```

sqrt (*all=False*)

Return the square root of the rational function.

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = t^2 - 2 + 1/t^2; f.sqrt()
(t^2 - 1)/t
sage: f = t^2; f.sqrt(all=True)
[t, -t]
```

valuation (*place*)

Return the valuation of the rational function at the place.

Rational function field places are associated with irreducible polynomials.

INPUT:

- *place* – a place or an irreducible polynomial

EXAMPLES:

```
sage: K.<t> = FunctionField(QQ)
sage: f = (t - 1)^2*(t + 1)/(t^2 - 1/3)^3
sage: f.valuation(t - 1)
2
sage: f.valuation(t)
0
sage: f.valuation(t^2 - 1/3)
-3

sage: K.<x> = FunctionField(GF(2))
sage: p = K.places_finite()[0]
sage: (1/x^2).valuation(p)
-2
```

sage.rings.function_field.element.is_FunctionFieldElement (*x*)Return True if *x* is any type of function field element.

EXAMPLES:

```
sage: t = FunctionField(QQ, 't').gen()
sage: sage.rings.function_field.element.is_FunctionFieldElement(t)
True
sage: sage.rings.function_field.element.is_FunctionFieldElement(0)
False
```

sage.rings.function_field.element.make_FunctionFieldElement (*parent*, *element_class*, *representing_element*)

Used for unpickling FunctionFieldElement objects (and subclasses).

EXAMPLES:

```
sage: from sage.rings.function_field.element import make_FunctionFieldElement
sage: K.<x> = FunctionField(QQ)
```

(continues on next page)

(continued from previous page)

```
sage: make_FunctionFieldElement(K, K.element_class, (x+1)/x)
(x + 1)/x
```


ORDERS OF FUNCTION FIELDS

An order of a function field is a subring that is, as a module over the base maximal order, finitely generated and of maximal rank n , where n is the extension degree of the function field. All orders are subrings of maximal orders.

A rational function field has two maximal orders: maximal finite order o and maximal infinite order o_∞ . The maximal order of a rational function field over constant field k is just the polynomial ring $o = k[x]$. The maximal infinite order is the set of rational functions whose denominator has degree greater than or equal to that of the numerator.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: I = O.ideal(1/x); I
Ideal (1/x) of Maximal order of Rational function field in x over Rational Field
sage: 1/x in O
False
sage: Oinf = K.maximal_order_infinite()
sage: 1/x in Oinf
True
```

In an extension of a rational function field, an order over the maximal finite order is called a finite order while an order over the maximal infinite order is called an infinite order. Thus a function field has one maximal finite order O and one maximal infinite order O_∞ . There are other non-maximal orders such as equation orders:

```
sage: K.<x> = FunctionField(GF(3)); R.<y> = K[]
sage: L.<y> = K.extension(y^3-y-x)
sage: O = L.equation_order()
sage: 1/y in O
False
sage: x/y in O
True
```

Sage provides an extensive functionality for computations in maximal orders of function fields. For example, you can decompose a prime ideal of a rational function field in an extension:

```
sage: K.<x> = FunctionField(GF(2)); L.<t> = K[]
sage: o = K.maximal_order()
sage: p = o.ideal(x+1)
sage: p.is_prime()
True

sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: O.decomposition(p)
[(Ideal (x + 1, y + 1) of Maximal order
```

(continues on next page)

(continued from previous page)

```

of Function field in y defined by y^3 + x^6 + x^4 + x^2, 1, 1),
(Ideal (x + 1, (1/(x^3 + x^2 + x))*y^2 + y + 1) of Maximal order
of Function field in y defined by y^3 + x^6 + x^4 + x^2, 2, 1)]

sage: p1.relative_degree,ramification_index = O.decomposition(p)[1]
sage: p1.parent()
Monoid of ideals of Maximal order of Function field in y
defined by y^3 + x^6 + x^4 + x^2
sage: relative_degree
2
sage: ramification_index
1

```

When the base constant field is the algebraic field $\overline{\mathbb{Q}}$, the only prime ideals of the maximal order of the rational function field are linear polynomials.

```

sage: K.<x> = FunctionField(QQbar)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - (x^3-x^2))
sage: p = K.maximal_order().ideal(x)
sage: L.maximal_order().decomposition(p)
[(Ideal (1/x*y - I) of Maximal order of Function field in y defined by y^2 - x^3 + x^
↪2,
  1,
  1),
 (Ideal (1/x*y + I) of Maximal order of Function field in y defined by y^2 - x^3 + x^
↪2,
  1,
  1)]

```

AUTHORS:

- William Stein (2010): initial version
- Maarten Derickx (2011-09-14): fixed `ideal_with_gens_over_base()` for rational function fields
- Julian Rueth (2011-09-14): added check in `_element_constructor_`
- Kwankyu Lee (2017-04-30): added maximal orders of global function fields
- Brent Baccala (2019-12-20): support orders in characteristic zero

```

class sage.rings.function_field.order.FunctionFieldMaximalOrder (field,
                                                                ideal_class=<class
                                                                'sage.rings.function_field.ideal.Function
                                                                cate-
                                                                gory=None)

```

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.rings.function_field.order.FunctionFieldOrder`

Base class of maximal orders of function fields.

```

class sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite (field,
                                                                ideal_class=<class
                                                                'sage.rings.function_field.ia
                                                                cat-
                                                                e-
                                                                gory=None)

```

Bases: `sage.rings.function_field.order.FunctionFieldMaximalOrder`, `sage.rings.`

function_field.order.FunctionFieldOrderInfinite

Base class of maximal infinite orders of function fields.

class sage.rings.function_field.order.**FunctionFieldMaximalOrderInfinite_polymod**(*field*,
cat-
e-
gory=None)

Bases: *sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite*

Maximal infinite orders of function fields.

INPUT:

- *field* – function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: F.maximal_order_infinite()
Maximal infinite order of Function field in y defined by y^3 + x^6 + x^4 + x^2

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: L.maximal_order_infinite()
Maximal infinite order of Function field in y defined by y^2 + y + (x^2 + 1)/x
```

basis ()

Return a basis of this order as a module over the maximal order of the base function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: L.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.basis()
(1, 1/x^2*y, (1/(x^4 + x^3 + x^2))*y^2)
```

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.basis()
(1, 1/x*y)
```

coordinate_vector (*e*)

Return the coordinates of *e* with respect to the basis of the order.

INPUT:

- *e* – element of the function field

The returned coordinates are in the base maximal infinite order if and only if the element is in the order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: f = 1/y^2
sage: f in Oinf
```

(continues on next page)

(continued from previous page)

```
True
sage: Oinf.coordinate_vector(f)
((x^3 + x^2 + x)/(x^4 + 1), x^3/(x^4 + 1))
```

decomposition()

Return prime ideal decomposition of pO_∞ where p is the unique prime ideal of the maximal infinite order of the rational function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = F.maximal_order_infinite()
sage: Oinf.decomposition()
[(Ideal ((1/(x^4 + x^3 + x^2))*y^2 + 1) of Maximal infinite order
of Function field in y defined by y^3 + x^6 + x^4 + x^2, 1, 1),
 (Ideal ((1/(x^4 + x^3 + x^2))*y^2 + 1/x^2*y + 1) of Maximal infinite order
of Function field in y defined by y^3 + x^6 + x^4 + x^2, 2, 1)]
```

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.decomposition()
[(Ideal (1/x*y) of Maximal infinite order of Function field in y
defined by y^2 + y + (x^2 + 1)/x, 1, 2)]
```

```
sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = F.maximal_order_infinite()
sage: Oinf.decomposition()
[(Ideal (1/x^2*y - 1) of Maximal infinite order
of Function field in y defined by y^3 - x^6 - 2*x^5 - 3*x^4 - 2*x^3 - x^2, 1,
↪ 1),
 (Ideal ((1/(x^4 + x^3 + x^2))*y^2 + 1/x^2*y + 1) of Maximal infinite order
of Function field in y defined by y^3 - x^6 - 2*x^5 - 3*x^4 - 2*x^3 - x^2, 2,
↪ 1)]
```

```
sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.decomposition()
[(Ideal (1/x*y) of Maximal infinite order of Function field in y
defined by y^2 + y + (x^2 + 1)/x, 1, 2)]
```

different()

Return the different ideal of the maximal infinite order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.different()
Ideal (1/x) of Maximal infinite order of Function field in y
defined by y^2 + y + (x^2 + 1)/x
```

gen (*n=0*)Return the *n*-th generator of the order.

The basis elements of the order are generators.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: L.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.gen()
1
sage: Oinf.gen(1)
1/x^2*y
sage: Oinf.gen(2)
(1/(x^4 + x^3 + x^2))*y^2
sage: Oinf.gen(3)
Traceback (most recent call last):
...
IndexError: there are only 3 generators

```

ideal (**gens*)Return the ideal generated by *gens*.

INPUT:

- *gens* – tuple of elements of the function field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(x,y); I
Ideal (y) of Maximal infinite order of Function field
in y defined by y^3 + x^6 + x^4 + x^2

```

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(x,y); I
Ideal (x) of Maximal infinite order of Function field in y defined by y^2 + y
↪+ (x^2 + 1)/x

```

ideal_with_gens_over_base (*gens*)Return the ideal generated by *gens* as a module.

INPUT:

- *gens* – tuple of elements of the function field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = F.maximal_order_infinite()
sage: Oinf.ideal_with_gens_over_base((x^2, y, (1/(x^2 + x + 1))*y^2))
Ideal (y) of Maximal infinite order of Function field in y
defined by y^3 + x^6 + x^4 + x^2

```

ngens()

Return the number of generators of the order.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: L.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = L.maximal_order_infinite()
sage: Oinf.ngens()
3

```

class sage.rings.function_field.order.**FunctionFieldMaximalOrderInfinite_rational** (*field*, *cat*, *e*, *gory=None*)

Bases: *sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite*

Maximal infinite orders of rational function fields.

INPUT:

- *field* – a rational function field

EXAMPLES:

```

sage: K.<t> = FunctionField(GF(19)); K
Rational function field in t over Finite Field of size 19
sage: R = K.maximal_order_infinite(); R
Maximal infinite order of Rational function field in t over Finite Field of size 19
↪ 19

```

basis()

Return the basis (=1) of the order as a module over the polynomial ring.

EXAMPLES:

```

sage: K.<t> = FunctionField(GF(19))
sage: O = K.maximal_order()
sage: O.basis()
(1,)

```

gen (*n=0*)Return the *n*-th generator of self. Since there is only one generator *n* must be 0.

EXAMPLES:

```

sage: O = FunctionField(QQ, 'y').maximal_order()
sage: O.gen()
y
sage: O.gen(1)
Traceback (most recent call last):
...
IndexError: there is only one generator

```

ideal (**gens*)Return the fractional ideal generated by *gens*.

INPUT:

- *gens* – elements of the function field

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order_infinite()
sage: O.ideal(x)
Ideal (x) of Maximal infinite order of Rational function field in x over
↳Rational Field
sage: O.ideal([x,1/x]) == O.ideal(x,1/x) # multiple generators may be given
↳as a list
True
sage: O.ideal(x^3+1,x^3+6)
Ideal (x^3) of Maximal infinite order of Rational function field in x over
↳Rational Field
sage: I = O.ideal((x^2+1)*(x^3+1),(x^3+6)*(x^2+1)); I
Ideal (x^5) of Maximal infinite order of Rational function field in x over
↳Rational Field
sage: O.ideal(I)
Ideal (x^5) of Maximal infinite order of Rational function field in x over
↳Rational Field

```

ngens()

Return 1 the number of generators of the order.

EXAMPLES:

```

sage: FunctionField(QQ,'y').maximal_order().ngens()
1

```

prime_ideal()

Return the unique prime ideal of the order.

EXAMPLES:

```

sage: K.<t> = FunctionField(GF(19))
sage: O = K.maximal_order_infinite()
sage: O.prime_ideal()
Ideal (1/t) of Maximal infinite order of Rational function field in t
over Finite Field of size 19

```

class sage.rings.function_field.order.**FunctionFieldMaximalOrder_global** (*field*)
 Bases: *sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod*

Maximal orders of global function fields.

INPUT:

- *field* – function field to which this maximal order belongs

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: L.maximal_order()
Maximal order of Function field in y defined by y^4 + x*y + 4*x + 1

```

decomposition (*ideal*)

Return the decomposition of the prime ideal.

INPUT:

- *ideal* – prime ideal of the base maximal order

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: o = K.maximal_order()
sage: O = F.maximal_order()
sage: p = o.ideal(x+1)
sage: O.decomposition(p)
[(Ideal (x + 1, y + 1) of Maximal order
  of Function field in y defined by y^3 + x^6 + x^4 + x^2, 1, 1),
 (Ideal (x + 1, (1/(x^3 + x^2 + x))*y^2 + y + 1) of Maximal order
  of Function field in y defined by y^3 + x^6 + x^4 + x^2, 2, 1)]

```

p_radical (*prime*)

Return the prime-radical of the maximal order.

INPUT:

- *prime* – prime ideal of the maximal order of the base rational function field

The algorithm is outlined in Section 6.1.3 of [Coh1993].

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2 * (x^2 + x + 1)^2)
sage: o = K.maximal_order()
sage: O = F.maximal_order()
sage: p = o.ideal(x+1)
sage: O.p_radical(p)
Ideal (x + 1) of Maximal order of Function field in y
defined by y^3 + x^6 + x^4 + x^2

```

class sage.rings.function_field.order.**FunctionFieldMaximalOrder_polymod** (*field*,
ideal_class=<class 'sage.rings.function_field.ia

Bases: *sage.rings.function_field.order.FunctionFieldMaximalOrder*

Maximal orders of extensions of function fields.

basis ()

Return a basis of the order over the maximal order of the base function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.basis()
(1, y, y^2, y^3)

sage: K.<x> = FunctionField(QQ)
sage: R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^4 + x^12*t^2 + x^18*t + x^21 + x^18)
sage: O = F.maximal_order()
sage: O.basis()
(1, 1/x^4*y, 1/x^9*y^2, 1/x^13*y^3)

```

codifferent ()

Return the codifferent ideal of the function field.

EXAMPLES:


```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.maximal_order()
sage: O.codifferent()
Ideal (1, (1/(x^4 + 4*x^3 + 3*x^2 + 6*x + 4))*y^3
+ ((5*x^3 + 6*x^2 + x + 6)/(x^4 + 4*x^3 + 3*x^2 + 6*x + 4))*y^2
+ ((x^3 + 2*x^2 + 2*x + 2)/(x^4 + 4*x^3 + 3*x^2 + 6*x + 4))*y
+ 6*x/(x^4 + 4*x^3 + 3*x^2 + 6*x + 4)) of Maximal order of Function field
in y defined by y^4 + x*y + 4*x + 1

```

coordinate_vector (*e*)

Return the coordinates of *e* with respect to the basis of this order.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.maximal_order()
sage: O.coordinate_vector(y)
(0, 1, 0, 0)
sage: O.coordinate_vector(x*y)
(0, x, 0, 0)

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: f = (x + y)^3
sage: O.coordinate_vector(f)
(x^3, 3*x^2, 3*x, 1)

```

decomposition (*ideal*)

Return the decomposition of the prime ideal.

INPUT:

- *ideal* – prime ideal of the base maximal order

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: o = K.maximal_order()
sage: O = F.maximal_order()
sage: p = o.ideal(x+1)
sage: O.decomposition(p)
[(Ideal (x + 1, y + 1) of Maximal order
of Function field in y defined by y^3 + x^6 + x^4 + x^2, 1, 1),
 (Ideal (x + 1, (1/(x^3 + x^2 + x))*y^2 + y + 1) of Maximal order
of Function field in y defined by y^3 + x^6 + x^4 + x^2, 2, 1)]

```

ALGORITHM:

In principle, we're trying to compute a primary decomposition of the extension of *ideal* in *self* (an order, and therefore a ring). However, while we have primary decomposition methods for polynomial rings, we lack any such method for an order. Therefore, we construct *self mod ideal* as a finite-dimensional algebra, a construct for which we do support primary decomposition.

See <https://trac.sagemath.org/attachment/ticket/28094/decomposition.pdf>

Todo: Use Kummer's theorem to shortcut this code if possible, like as done in `FunctionFieldMaximalOrder_global.decomposition()`

different()

Return the different ideal of the function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.maximal_order()
sage: O.different()
Ideal (y^3 + 2*x)
of Maximal order of Function field in y defined by y^4 + x*y + 4*x + 1
```

free_module()

Return the free module formed by the basis over the maximal order of the base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.maximal_order()
sage: O.free_module()
Free module of degree 4 and rank 4 over Maximal order of Rational function_
↪field in x over Finite Field of size 7
User basis matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
```

gen(n=0)

Return the n-th generator of the order.

The basis elements of the order are generators.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: L.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: O = L.maximal_order()
sage: O.gen()
1
sage: O.gen(1)
y
sage: O.gen(2)
(1/(x^3 + x^2 + x))*y^2
sage: O.gen(3)
Traceback (most recent call last):
...
IndexError: there are only 3 generators
```

ideal(*gens, **kwargs)

Return the fractional ideal generated by the elements in gens.

INPUT:

- gens – list of generators

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: O = K.maximal_order()
sage: I = O.ideal(x^2-4)
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: S = L.maximal_order()
sage: S.ideal(1/y)
Ideal ((1/(x^3 + 1))*y) of Maximal order of Function field
in y defined by y^2 + 6*x^3 + 6
sage: I2 = S.ideal(x^2-4); I2
Ideal (x^2 + 3) of Maximal order of Function field in y defined by y^2 + 6*x^
↪ 3 + 6
sage: I2 == S.ideal(I)
True

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: O = K.maximal_order()
sage: I = O.ideal(x^2-4)
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: S = L.maximal_order()
sage: S.ideal(1/y)
Ideal ((1/(x^3 + 1))*y) of Maximal order of Function field in y defined by y^
↪ 2 - x^3 - 1
sage: I2 = S.ideal(x^2-4); I2
Ideal (x^2 - 4) of Maximal order of Function field in y defined by y^2 - x^3 -
↪ 1
sage: I2 == S.ideal(I)
True

```

ideal_with_gens_over_base (*gens*)

Return the fractional ideal with basis gens over the maximal order of the base field.

INPUT:

- gens – list of elements that generates the ideal over the maximal order of the base field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.maximal_order(); O
Maximal order of Function field in y defined by y^2 + 6*x^3 + 6
sage: I = O.ideal_with_gens_over_base([1, y]); I
Ideal (1) of Maximal order of Function field in y defined by y^2 + 6*x^3 + 6
sage: I.module()
Free module of degree 2 and rank 2 over Maximal order of Rational function_
↪ field in x over Finite Field of size 7
Echelon basis matrix:
[1 0]
[0 1]

```

There is no check if the resulting object is really an ideal:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal_with_gens_over_base([y]); I
Ideal (y) of Order in Function field in y defined by y^2 + 6*x^3 + 6

```

(continues on next page)

(continued from previous page)

```
sage: y in I
True
sage: y^2 in I
False
```

ngens()

Return the number of generators of the order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); L.<t> = K[]
sage: L.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: Oinf = L.maximal_order()
sage: Oinf.ngens()
3
```

polynomial()

Return the defining polynomial of the function field of which this is an order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.polynomial()
y^4 + x*y + 4*x + 1

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.polynomial()
y^4 + x*y + 4*x + 1
```

class sage.rings.function_field.order.**FunctionFieldMaximalOrder_rational** (*field*)Bases: *sage.rings.function_field.order.FunctionFieldMaximalOrder*

Maximal orders of rational function fields.

INPUT:

- *field* – a function field

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(19)); K
Rational function field in t over Finite Field of size 19
sage: R = K.maximal_order(); R
Maximal order of Rational function field in t over Finite Field of size 19
```

basis()

Return the basis (=1) of the order as a module over the polynomial ring.

EXAMPLES:

```
sage: K.<t> = FunctionField(GF(19))
sage: O = K.maximal_order()
sage: O.basis()
(1,)
```

gen ($n=0$)Return the n -th generator of the order. Since there is only one generator n must be 0.

EXAMPLES:

```

sage: O = FunctionField(QQ, 'y').maximal_order()
sage: O.gen()
y
sage: O.gen(1)
Traceback (most recent call last):
...
IndexError: there is only one generator

```

ideal (*gens)

Return the fractional ideal generated by gens.

INPUT:

- gens – elements of the function field

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: O.ideal(x)
Ideal (x) of Maximal order of Rational function field in x over Rational Field
sage: O.ideal([x, 1/x]) == O.ideal(x, 1/x) # multiple generators may be given
↪ as a list
True
sage: O.ideal(x^3+1, x^3+6)
Ideal (1) of Maximal order of Rational function field in x over Rational Field
sage: I = O.ideal((x^2+1)*(x^3+1), (x^3+6)*(x^2+1)); I
Ideal (x^2 + 1) of Maximal order of Rational function field in x over
↪ Rational Field
sage: O.ideal(I)
Ideal (x^2 + 1) of Maximal order of Rational function field in x over
↪ Rational Field

```

ideal_with_gens_over_base (gens)

Return the fractional ideal with generators gens.

INPUT:

- gens – elements of the function field

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: O.ideal_with_gens_over_base([x^3+1, -y])
Ideal (x^3 + 1, -y) of Order in Function field in y defined by y^2 - x^3 - 1

```

ngens ()

Return 1 the number of generators of the order.

EXAMPLES:

```

sage: FunctionField(QQ, 'y').maximal_order().ngens()
1

```

```
class sage.rings.function_field.order.FunctionFieldOrder (field, ideal_class=<class
                                                    'sage.rings.function_field.ideal.FunctionFieldIdea
                                                    category=None)
    Bases: sage.rings.function_field.order.FunctionFieldOrder_base
```

Base class for orders in function fields.

```
class sage.rings.function_field.order.FunctionFieldOrderInfinite (field,
                                                    ideal_class=<class
                                                    'sage.rings.function_field.ideal.Functi
                                                    cate-
                                                    gory=None)
```

Bases: *sage.rings.function_field.order.FunctionFieldOrder_base*

Base class for infinite orders in function fields.

```
class sage.rings.function_field.order.FunctionFieldOrderInfinite_basis (basis,
                                                    check=True)
```

Bases: *sage.rings.function_field.order.FunctionFieldOrderInfinite*

Order given by a basis over the infinite maximal order of the base field.

INPUT:

- `basis` – elements of the function field
- `check` – boolean (default: `True`); if `True`, check the basis generates an order

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order_infinite(); O
Infinite order in Function field in y defined by y^4 + x*y + 4*x + 1
```

The basis only defines an order if the module it generates is closed under multiplication and contains the identity element (only checked when `check` is `True`):

```
sage: O = L.order_infinite_with_basis([1, y, 1/x^2*y^2, y^3]); O
Traceback (most recent call last):
...
ValueError: the module generated by basis (1, y, 1/x^2*y^2, y^3) must be closed_
↳under multiplication
```

The basis also has to be linearly independent and of the same rank as the degree of the function field of its elements (only checked when `check` is `True`):

```
sage: O = L.order_infinite_with_basis([1, y, 1/x^2*y^2, 1 + y]); O
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

Note that `1` does not need to be an element of the basis, as long as it is in the module spanned by it:

```
sage: O = L.order_infinite_with_basis([1 + 1/x*y, 1/x*y, 1/x^2*y^2, 1/x^3*y^3]); O
Infinite order in Function field in y defined by y^4 + x*y + 4*x + 1
sage: O.basis()
(1/x*y + 1, 1/x*y, 1/x^2*y^2, 1/x^3*y^3)
```

basis()

Return a basis of this order over the maximal order of the base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.basis()
(1, y, y^2, y^3)
```

free_module()

Return the free module formed by the basis over the maximal order of the base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.free_module()
Free module of degree 4 and rank 4 over Maximal order of Rational
function field in x over Finite Field of size 7
Echelon basis matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
```

ideal(*gens)

Return the fractional ideal generated by the elements in gens.

INPUT:

- gens – list of generators or an ideal in a ring which coerces to this order

EXAMPLES:

```
sage: K.<y> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: O.ideal(y)
Ideal (y) of Maximal order of Rational function field in y over Rational Field
sage: O.ideal([y, 1/y]) == O.ideal(y, 1/y) # multiple generators may be given,
↳ as a list
True
```

A fractional ideal of a nontrivial extension:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: O = K.maximal_order_infinite()
sage: I = O.ideal(x^2-4)
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: S = L.order_infinite_with_basis([1, 1/x^2*y])
```

ideal_with_gens_over_base(gens)

Return the fractional ideal with basis gens over the maximal order of the base field.

It is not checked that gens really generates an ideal.

INPUT:

- gens – list of elements that are a basis for the ideal over the maximal order of the base field

EXAMPLES:

We construct an ideal in a rational function field:

```

sage: K.<y> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: I = O.ideal([y]); I
Ideal (y) of Maximal order of Rational function field in y over Rational Field
sage: I*I
Ideal (y^2) of Maximal order of Rational function field in y over Rational
↪Field

```

We construct some ideals in a nontrivial function field:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order(); O
Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: I = O.ideal_with_gens_over_base([1, y]); I
Ideal (1) of Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: I.module()
Free module of degree 2 and rank 2 over Maximal order of Rational function
↪field in x over Finite Field of size 7
Echelon basis matrix:
[1 0]
[0 1]

```

There is no check if the resulting object is really an ideal:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal_with_gens_over_base([y]); I
Ideal (y) of Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: y in I
True
sage: y^2 in I
False

```

`polynomial()`

Return the defining polynomial of the function field of which this is an order.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.polynomial()
y^4 + x*y + 4*x + 1

```

```

class sage.rings.function_field.order.FunctionFieldOrder_base(field,
                                                                ideal_class=<class
                                                                'sage.rings.function_field.ideal.FunctionFi
                                                                category=None>)

```

Bases: `sage.structure.unique_representation.CachedRepresentation`, `sage.structure.parent.Parent`

Base class for orders in function fields.

INPUT:

- `field` – function field

EXAMPLES:


```
sage: F = FunctionField(QQ, 'y')
sage: F.maximal_order()
Maximal order of Rational function field in y over Rational Field
```

fraction_field()

Return the function field to which the order belongs.

EXAMPLES:

```
sage: FunctionField(QQ, 'y').maximal_order().function_field()
Rational function field in y over Rational Field
```

function_field()

Return the function field to which the order belongs.

EXAMPLES:

```
sage: FunctionField(QQ, 'y').maximal_order().function_field()
Rational function field in y over Rational Field
```

ideal_monoid()

Return the monoid of ideals of the order.

EXAMPLES:

```
sage: FunctionField(QQ, 'y').maximal_order().ideal_monoid()
Monoid of ideals of Maximal order of Rational function field in y over
↪ Rational Field
```

is_field(*proof=True*)

Return False since orders are never fields.

EXAMPLES:

```
sage: FunctionField(QQ, 'y').maximal_order().is_field()
False
```

is_noetherian()

Return True since orders in function fields are noetherian.

EXAMPLES:

```
sage: FunctionField(QQ, 'y').maximal_order().is_noetherian()
True
```

is_subring(*other*)

Return True if the order is a subring of the other order.

INPUT:

- *other* – order of the function field or the field itself

EXAMPLES:

```
sage: F = FunctionField(QQ, 'y')
sage: O = F.maximal_order()
sage: O.is_subring(F)
True
```

class sage.rings.function_field.order.**FunctionFieldOrder_basis** (*basis*,
check=True)
 Bases: *sage.rings.function_field.order.FunctionFieldOrder*

Order given by a basis over the maximal order of the base field.

INPUT:

- *basis* – list of elements of the function field
- *check* – (default: True) if True, check whether the module that *basis* generates forms an order

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order(); O
Order in Function field in y defined by y^4 + x*y + 4*x + 1
```

The basis only defines an order if the module it generates is closed under multiplication and contains the identity element:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - (x^3 + 2*x*y + 1/x))
sage: y.is_integral()
False
sage: L.order(y)
Traceback (most recent call last):
...
ValueError: the module generated by basis (1, y, y^2, y^3, y^4) must be closed_
↳under multiplication
```

The basis also has to be linearly independent and of the same rank as the degree of the function field of its elements (only checked when *check* is True):

```
sage: L.order(L(x))
Traceback (most recent call last):
...
ValueError: basis (1, x, x^2, x^3, x^4) is not linearly independent
sage: sage.rings.function_field.order.FunctionFieldOrder_basis((y,y,y^3,y^4,y^5))
Traceback (most recent call last):
...
ValueError: basis (y, y, y^3, y^4, 2*x*y + (x^4 + 1)/x) is not linearly_
↳independent
```

basis()

Return a basis of the order over the maximal order of the base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.basis()
(1, y, y^2, y^3)
```

coordinate_vector (*e*)

Return the coordinates of *e* with respect to the basis of the order.

INPUT:

- e – element of the order or the function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: f = (x + y)^3
sage: O.coordinate_vector(f)
(x^3, 3*x^2, 3*x, 1)
```

free_module()

Return the free module formed by the basis over the maximal order of the base function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.free_module()
Free module of degree 4 and rank 4 over Maximal order of Rational
function field in x over Finite Field of size 7
Echelon basis matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
```

ideal(*gens)

Return the fractional ideal generated by the elements in gens.

INPUT:

- gens – list of generators or an ideal in a ring which coerces to this order

EXAMPLES:

```
sage: K.<y> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: O.ideal(y)
Ideal (y) of Maximal order of Rational function field in y over Rational Field
sage: O.ideal([y, 1/y]) == O.ideal(y, 1/y) # multiple generators may be given
↪ as a list
True
```

A fractional ideal of a nontrivial extension:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: O = K.maximal_order()
sage: I = O.ideal(x^2-4)
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: S = L.equation_order()
sage: S.ideal(1/y)
Ideal (1, (6/(x^3 + 1))*y) of Order in Function field in y defined by y^2 +
↪ 6*x^3 + 6
sage: I2 = S.ideal(x^2-4); I2
Ideal (x^2 + 3) of Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: I2 == S.ideal(I)
True
```

ideal_with_gens_over_base (*gens*)

Return the fractional ideal with basis *gens* over the maximal order of the base field.

It is not checked that the *gens* really generates an ideal.

INPUT:

- *gens* – list of elements of the function field

EXAMPLES:

We construct an ideal in a rational function field:

```
sage: K.<y> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: I = O.ideal([y]); I
Ideal (y) of Maximal order of Rational function field in y over Rational Field
sage: I*I
Ideal (y^2) of Maximal order of Rational function field in y over Rational_
↪Field
```

We construct some ideals in a nontrivial function field:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order(); O
Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: I = O.ideal_with_gens_over_base([1, y]); I
Ideal (1) of Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: I.module()
Free module of degree 2 and rank 2 over Maximal order of Rational function_
↪field in x over Finite Field of size 7
Echelon basis matrix:
[1 0]
[0 1]
```

There is no check if the resulting object is really an ideal:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal_with_gens_over_base([y]); I
Ideal (y) of Order in Function field in y defined by y^2 + 6*x^3 + 6
sage: y in I
True
sage: y^2 in I
False
```

polynomial ()

Return the defining polynomial of the function field of which this is an order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^4 + x*y + 4*x + 1)
sage: O = L.equation_order()
sage: O.polynomial()
y^4 + x*y + 4*x + 1
```

IDEALS OF FUNCTION FIELDS

Ideals of an order of a function field include all fractional ideals of the order. Sage provides basic arithmetic with fractional ideals.

The fractional ideals of the maximal order of a global function field forms a multiplicative monoid. Sage allows advanced arithmetic with the fractional ideals. For example, an ideal of the maximal order can be factored into a product of prime ideals.

EXAMPLES:

Ideals in the maximal order of a rational function field:

```
sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: I = O.ideal(x^3 + 1); I
Ideal (x^3 + 1) of Maximal order of Rational function field in x over Rational Field
sage: I^2
Ideal (x^6 + 2*x^3 + 1) of Maximal order of Rational function field in x over
↳Rational Field
sage: ~I
Ideal (1/(x^3 + 1)) of Maximal order of Rational function field in x over Rational
↳Field
sage: ~I * I
Ideal (1) of Maximal order of Rational function field in x over Rational Field
```

Ideals in the equation order of an extension of a rational function field:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(y); I
Ideal (x^3 + 1, -y) of Order in Function field in y defined by y^2 - x^3 - 1
sage: I^2
Ideal (x^3 + 1, (-x^3 - 1)*y) of Order in Function field in y defined by y^2 - x^3 - 1
```

Ideals in the maximal order of a global function field:

```
sage: K.<x> = FunctionField(GF(2)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3*y - x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I^2
Ideal (x) of Maximal order of Function field in y defined by y^2 + x^3*y + x
sage: ~I
Ideal (1/(x*y)) of Maximal order of Function field in y defined by y^2 + x^3*y + x
sage: ~I * I
```

(continues on next page)

(continued from previous page)

```

Ideal (1) of Maximal order of Function field in y defined by y^2 + x^3*y + x

sage: J = O.ideal(x+y) * I
sage: J.factor()
(Ideal (y) of Maximal order of Function field in y defined by y^2 + x^3*y + x)^2 *
(Ideal (x^3 + x + 1, y + x) of Maximal order of Function field in y defined by y^2 +
↪ x^3*y + x)

```

Ideals in the maximal infinite order of a global function field:

```

sage: K.<x> = FunctionField(GF(3^2)); R.<t> = K[]
sage: F.<y> = K.extension(t^3 + t^2 - x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(1/y)
sage: I + I == I
True
sage: I^2
Ideal (1/x^4*y) of Maximal infinite order of Function field in y defined by y^3 + y^2
↪ + 2*x^4
sage: ~I
Ideal (y) of Maximal infinite order of Function field in y defined by y^3 + y^2 + 2*x^
↪ 4
sage: ~I * I
Ideal (1) of Maximal infinite order of Function field in y defined by y^3 + y^2 + 2*x^
↪ 4
sage: I.factor()
(Ideal (1/x^3*y^2) of Maximal infinite order of Function field in y defined by y^3 +
↪ y^2 + 2*x^4)^4

```

AUTHORS:

- William Stein (2010): initial version
- Maarten Derickx (2011-09-14): fixed `ideal_with_gens_over_base()`
- Kwankyu Lee (2017-04-30): added ideals for global function fields

class `sage.rings.function_field.ideal.FunctionFieldIdeal` (*ring*)
 Bases: `sage.structure.element.Element`

Base class of fractional ideals of function fields.

INPUT:

- `ring` – ring of the ideal

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7))
sage: O = K.equation_order()
sage: O.ideal(x^3+1)
Ideal (x^3 + 1) of Maximal order of Rational function field in x over Finite
↪ Field of size 7

```

base_ring()

Return the base ring of this ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(x^2 + 1)
sage: I.base_ring()
Order in Function field in y defined by y^2 - x^3 - 1

```

divisor()

Return the divisor corresponding to the ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x*(x + 1)^2/(x^2 + x + 1))
sage: I.divisor()
Place (x) + 2*Place (x + 1) - Place (x + z2) - Place (x + z2 + 1)

sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x + 1)/(x^3 + 1))
sage: I.divisor()
2*Place (1/x)

sage: K.<x> = FunctionField(GF(2)); _.<T> = PolynomialRing(K)
sage: F.<y> = K.extension(T^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor()
2*Place (x, (1/(x^3 + x^2 + x))*y^2)
+ 2*Place (x^2 + x + 1, (1/(x^3 + x^2 + x))*y^2)

sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(y)
sage: I.divisor()
-2*Place (1/x, 1/x^4*y^2 + 1/x^2*y + 1)
- 2*Place (1/x, 1/x^2*y + 1)

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor()
- Place (x, x*y)
+ 2*Place (x + 1, x*y)

sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(y)
sage: I.divisor()
- Place (1/x, 1/x*y)

```

divisor_of_poles()

Return the divisor of poles corresponding to the ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x*(x + 1)^2/(x^2 + x + 1))

```

(continues on next page)

(continued from previous page)

```

sage: I.divisor_of_poles()
Place (x + z2) + Place (x + z2 + 1)

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x + 1)/(x^3 + 1))
sage: I.divisor_of_poles()
0

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor_of_poles()
Place (x, x*y)

```

divisor_of_zeros()

Return the divisor of zeros corresponding to the ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x*(x + 1)^2/(x^2 + x + 1))
sage: I.divisor_of_zeros()
Place (x) + 2*Place (x + 1)

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x + 1)/(x^3 + 1))
sage: I.divisor_of_zeros()
2*Place (1/x)

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I.divisor_of_zeros()
2*Place (x + 1, x*y)

```

factor()

Return the factorization of this ideal.

Subclass of this class should define `_factor()` method that returns a list of prime ideal and multiplicity pairs.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x^3*(x + 1)^2)
sage: I.factor()
(Ideal (x) of Maximal order of Rational function field in x
over Finite Field in z2 of size 2^2)^3 *
(Ideal (x + 1) of Maximal order of Rational function field in x
over Finite Field in z2 of size 2^2)^2

```

(continues on next page)

(continued from previous page)

```

sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x + 1)/(x^3 + 1))
sage: I.factor()
(Ideal (1/x) of Maximal infinite order of Rational function field in x
over Finite Field in z2 of size 2^2)^2

sage: K.<x> = FunctionField(GF(2)); _.<T> = PolynomialRing(K)
sage: F.<y> = K.extension(T^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: I == I.factor().prod()
True

sage: Oinf = F.maximal_order_infinite()
sage: f = 1/x
sage: I = Oinf.ideal(f)
sage: I.factor()
(Ideal ((1/(x^4 + x^3 + x^2))*y^2 + 1/x^2*y + 1) of Maximal infinite order
of Function field in y defined by y^3 + x^6 + x^4 + x^2) *
(Ideal ((1/(x^4 + x^3 + x^2))*y^2 + 1) of Maximal infinite order
of Function field in y defined by y^3 + x^6 + x^4 + x^2)

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: I == I.factor().prod()
True

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I == I.factor().prod()
True

```

gens_reduced()

Return reduced generators.

For now, this method just looks at the generators and sees if any can be removed without changing the ideal. It prefers principal representations (a single generator) over all others, and otherwise picks the generator set with the shortest print representation.

This method is provided so that ideals in function fields have the method `gens_reduced()`, just like ideals of number fields. Sage linear algebra machinery sometimes requires this.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7))
sage: O = K.equation_order()
sage: I = O.ideal(x, x^2, x^2+x)
sage: I.gens_reduced()
(x,)

```

place()

Return the place associated with this prime ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x^2 + x + 1)
sage: I.place()
Traceback (most recent call last):
...
TypeError: not a prime ideal
sage: I = O.ideal(x^3+x+1)
sage: I.place()
Place (x^3 + x + 1)

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x + 1)/(x^3 + 1))
sage: p = I.factor()[0][0]
sage: p.place()
Place (1/x)

sage: K.<x> = FunctionField(GF(2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: [f.place() for f,_ in I.factor()]
[Place (x, (1/(x^3 + x^2 + x))*y^2),
 Place (x^2 + x + 1, (1/(x^3 + x^2 + x))*y^2)]

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: [f.place() for f,_ in I.factor()]
[Place (x, x*y), Place (x + 1, x*y)]

sage: K.<x> = FunctionField(GF(3^2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3 + t^2 - x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(1/x)
sage: I.factor()
(Ideal (1/x^3*y^2) of Maximal infinite order of Function field
in y defined by y^3 + y^2 + 2*x^4)^3
sage: J = I.factor()[0][0]
sage: J.is_prime()
True
sage: J.place()
Place (1/x, 1/x^3*y^2)

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(1/x)
sage: I.factor()
(Ideal (1/x*y) of Maximal infinite order of Function field in y
defined by y^2 + y + (x^2 + 1)/x)^2
sage: J = I.factor()[0][0]
sage: J.is_prime()
True
sage: J.place()
Place (1/x, 1/x*y)

```

ring()

Return the ring to which this ideal belongs.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7))
sage: O = K.equation_order()
sage: I = O.ideal(x, x^2, x^2+x)
sage: I.ring()
Maximal order of Rational function field in x over Finite Field of size 7
```

class sage.rings.function_field.ideal.**FunctionFieldIdealInfinite**(ring)

Bases: *sage.rings.function_field.ideal.FunctionFieldIdeal*

Base class of ideals of maximal infinite orders

class sage.rings.function_field.ideal.**FunctionFieldIdealInfinite_module**(ring, module)

Bases: *sage.rings.function_field.ideal.FunctionFieldIdealInfinite*, *sage.rings.ideal.Ideal_generic*

A fractional ideal specified by a finitely generated module over the integers of the base field.

INPUT:

- ring – order in a function field
- module – module

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: O.ideal(y)
Ideal (x^3 + 1, -y) of Order in Function field in y defined by y^2 - x^3 - 1
```

module()

Return the module over the maximal order of the base field that underlies this ideal.

The formation of the module is compatible with the vector space corresponding to the function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7))
sage: O = K.maximal_order(); O
Maximal order of Rational function field in x over Finite Field of size 7
sage: K.polynomial_ring()
Univariate Polynomial Ring in x over Rational function field in x over Finite_
↪Field of size 7
sage: I = O.ideal([x^2 + 1, x*(x^2+1)])
sage: I.gens()
(x^2 + 1,)
sage: I.module()
Free module of degree 1 and rank 1 over Maximal order of Rational function_
↪field in x over Finite Field of size 7
Echelon basis matrix:
[x^2 + 1]
sage: V, from_V, to_V = K.vector_space(); V
Vector space of dimension 1 over Rational function field in x over Finite_
↪Field of size 7
```

(continues on next page)

(continued from previous page)

```
sage: I.module().is_submodule(V)
True
```

class sage.rings.function_field.ideal.**FunctionFieldIdealInfinite_polymod**(*ring*,
ideal)

Bases: *sage.rings.function_field.ideal.FunctionFieldIdealInfinite*

Ideals of the infinite maximal order of an algebraic function field.

INPUT:

- ring – infinite maximal order of the function field
- ideal – ideal in the inverted function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(3^2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3+t^2-x^4)
sage: Oinf = F.maximal_order_infinite()
sage: Oinf.ideal(1/y)
Ideal (1/x^4*y^2) of Maximal infinite order of Function field
in y defined by y^3 + y^2 + 2*x^4
```

gens()

Return a set of generators of this ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(3^2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3+t^2-x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(x+y)
sage: I.gens()
(x, y, 1/x^2*y^2)

sage: K.<x> = FunctionField(GF(2)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(x+y)
sage: I.gens()
(x, y)
```

gens_over_base()

Return a set of generators of this ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(3^2)); L.<t> = K[]
sage: F.<y> = K.extension(t^3 + t^2 - x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(x + y)
sage: I.gens_over_base()
(x, y, 1/x^2*y^2)
```

gens_two()

Return a set of at most two generators of this ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(3^2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3+t^2-x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(x+y)
sage: I.gens_two()
(x, y)

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2+Y+x+1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(x+y)
sage: I.gens_two()
(x, )

```

ideal_below()

Return a set of generators of this ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(3^2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 + t^2 - x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(1/y^2)
sage: I.ideal_below()
Ideal (x^3) of Maximal order of Rational function field
in x over Finite Field in z2 of size 3^2

```

is_prime()

Return True if this ideal is a prime ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(3^2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3 + t^2 - x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(1/x)
sage: I.factor()
(Ideal (1/x^3*y^2) of Maximal infinite order of Function field
in y defined by y^3 + y^2 + 2*x^4)^3
sage: I.is_prime()
False
sage: J = I.factor()[0][0]
sage: J.is_prime()
True

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(1/x)
sage: I.factor()
(Ideal (1/x*y) of Maximal infinite order of Function field in y
defined by y^2 + y + (x^2 + 1)/x)^2
sage: I.is_prime()
False
sage: J = I.factor()[0][0]
sage: J.is_prime()
True

```

prime_below()

Return the prime of the base order that underlies this prime ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(3^2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3+t^2-x^4)
sage: Oinf = F.maximal_order_infinite()
sage: I = Oinf.ideal(1/x)
sage: I.factor()
(Ideal (1/x^3*y^2) of Maximal infinite order of Function field
in y defined by y^3 + y^2 + 2*x^4)^3
sage: J = I.factor()[0][0]
sage: J.is_prime()
True
sage: J.prime_below()
Ideal (1/x) of Maximal infinite order of Rational function field
in x over Finite Field in z2 of size 3^2

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(1/x)
sage: I.factor()
(Ideal (1/x*y) of Maximal infinite order of Function field in y
defined by y^2 + y + (x^2 + 1)/x)^2
sage: J = I.factor()[0][0]
sage: J.is_prime()
True
sage: J.prime_below()
Ideal (1/x) of Maximal infinite order of Rational function field in x
over Finite Field of size 2
```

valuation (*ideal*)

Return the valuation of *ideal* with respect to this prime ideal.

INPUT:

- *ideal* – fractional ideal

EXAMPLES:

```
sage: K.<x>=FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y>=K.extension(Y^2 + Y + x + 1/x)
sage: Oinf = L.maximal_order_infinite()
sage: I = Oinf.ideal(y)
sage: [f.valuation(I) for f,_ in I.factor()]
[-1]
```

class sage.rings.function_field.ideal.**FunctionFieldIdealInfinite_rational** (*ring*, *gen*)

Bases: *sage.rings.function_field.ideal.FunctionFieldIdealInfinite*

Fractional ideal of the maximal order of rational function field.

INPUT:

- *ring* – infinite maximal order
- *gen* – generator

Note that the infinite maximal order is a principal ideal domain.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: Oinf.ideal(x)
Ideal (x) of Maximal infinite order of Rational function field in x over Finite_
↪Field of size 2

```

gen()

Return the generator of this principal ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x+1)/(x^3+x), (x^2+1)/x^4)
sage: I.gen()
1/x^2

```

gens()

Return the generator of this principal ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x+1)/(x^3+x), (x^2+1)/x^4)
sage: I.gens()
(1/x^2,)

```

gens_over_base()

Return the generator of this ideal as a rank one module over the infinite maximal order.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal((x+1)/(x^3+x), (x^2+1)/x^4)
sage: I.gens_over_base()
(1/x^2,)

```

is_prime()

Return True if this ideal is a prime ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: Oinf = K.maximal_order_infinite()
sage: I = Oinf.ideal(x/(x^2 + 1))
sage: I.is_prime()
True

```

valuation(ideal)

Return the valuation of *ideal* at this prime ideal.

INPUT:

- *ideal* – fractional ideal

EXAMPLES:

```

sage: F.<x> = FunctionField(QQ)
sage: O = F.maximal_order_infinite()
sage: p = O.ideal(1/x)
sage: p.valuation(O.ideal(x/(x+1)))
0
sage: p.valuation(O.ideal(0))
+Infinity

```

class sage.rings.function_field.ideal.**FunctionFieldIdeal_global**(ring, hnf, denominator=1)

Bases: *sage.rings.function_field.ideal.FunctionFieldIdeal_polymod*

Fractional ideals of canonical function fields

INPUT:

- ring – order in a function field
- hnf – matrix in hermite normal form
- denominator – denominator

The rows of hnf is a basis of the ideal, which itself is denominator times the fractional ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3*y - x)
sage: O = L.maximal_order()
sage: O.ideal(y)
Ideal (y) of Maximal order of Function field in y defined by y^2 + x^3*y + x

```

gens()

Return a set of generators of this ideal.

This provides whatever set of generators as quickly as possible.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^2 - x^3*Y - x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)
sage: I.gens()
(x^4 + x^2 + x, y + x)

sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)
sage: I.gens()
(x^3 + 1, y + x)

```

gens_two()

Return two generators of this fractional ideal.

If the ideal is principal, one generator *may* be returned.

ALGORITHM:

At most two generators are required to generate ideals in Dedekind domains.

Lemma 4.7.9, algorithm 4.7.10, and exercise 4.29 of [Coh1993] tell us that for an integral ideal I in a number field, if we pick a such that $\gcd(N(I), N(a)/N(I)) = 1$, then a and $N(I)$ generate the ideal. $N()$ is the norm, and this result (presumably) generalizes to function fields.

After computing $N(I)$, we search exhaustively to find a .

Todo: Always return a single generator for a principal ideal.

Testing for principality is not trivial. Algorithm 6.5.10 of [Coh1993] could probably be adapted for function fields.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: I # indirect doctest
Ideal (y) of Maximal order of Function field
in y defined by y^3 + x^6 + x^4 + x^2
sage: ~I # indirect doctest
Ideal ((1/(x^6 + x^4 + x^2))*y^2) of Maximal order of Function field
in y defined by y^3 + x^6 + x^4 + x^2

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: I # indirect doctest
Ideal (y) of Maximal order of Function field in y
defined by y^2 + y + (x^2 + 1)/x
sage: ~I # indirect doctest
Ideal ((x/(x^2 + 1))*y + x/(x^2 + 1)) of Maximal order
of Function field in y defined by y^2 + y + (x^2 + 1)/x
```

```
class sage.rings.function_field.ideal.FunctionFieldIdeal_module(ring, module)
Bases: sage.rings.function_field.ideal.FunctionFieldIdeal, sage.rings.ideal.
Ideal_generic
```

A fractional ideal specified by a finitely generated module over the integers of the base field.

INPUT:

- ring – an order in a function field
- module – a module of the order

EXAMPLES:

An ideal in an extension of a rational function field:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(y)
sage: I
Ideal (x^3 + 1, -y) of Order in Function field in y defined by y^2 - x^3 - 1
sage: I^2
Ideal (x^3 + 1, (-x^3 - 1)*y) of Order in Function field in y defined by y^2 - x^
-3 - 1
```

(continues on next page)

(continued from previous page)

gen (*i*)Return the *i*-th generator in the current basis of this ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(x^2 + 1)
sage: I.gen(1)
(x^2 + 1)*y

```

gens ()

Return a set of generators of this ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(x^2 + 1)
sage: I.gens()
(x^2 + 1, (x^2 + 1)*y)

```

intersection (*other*)Return the intersection of this ideal and *other*.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(y^3); J = O.ideal(y^2)
sage: Z = I.intersection(J); Z
Ideal (x^6 + 2*x^3 + 1, (-x^3 - 1)*y) of Order in Function field in y defined_
↳by y^2 - x^3 - 1
sage: y^2 in Z
False
sage: y^3 in Z
True

```

module ()

Return the module over the maximal order of the base field that underlies this ideal.

The formation of the module is compatible with the vector space corresponding to the function field.

OUTPUT:

- a module over the maximal order of the base field of the ideal

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order(); O
Order in Function field in y defined by y^2 - x^3 - 1
sage: I = O.ideal(x^2 + 1)

```

(continues on next page)

(continued from previous page)

```

sage: I.gens()
(x^2 + 1, (x^2 + 1)*y)
sage: I.module()
Free module of degree 2 and rank 2 over Maximal order of Rational function
↪field in x over Rational Field
Echelon basis matrix:
[x^2 + 1      0]
[      0 x^2 + 1]
sage: V, from_V, to_V = L.vector_space(); V
Vector space of dimension 2 over Rational function field in x over Rational
↪Field
sage: I.module().is_submodule(V)
True

```

ngens()

Return the number of generators in the basis.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.equation_order()
sage: I = O.ideal(x^2 + 1)
sage: I.ngens()
2

```

class sage.rings.function_field.ideal.**FunctionFieldIdeal_polymod**(ring, hnf, denominator=1)

Bases: *sage.rings.function_field.ideal.FunctionFieldIdeal*

Fractional ideals of algebraic function fields

INPUT:

- ring – order in a function field
- hnf – matrix in hermite normal form
- denominator – denominator

The rows of hnf is a basis of the ideal, which itself is denominator times the fractional ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3*y - x)
sage: O = L.maximal_order()
sage: O.ideal(y)
Ideal (y) of Maximal order of Function field in y defined by y^2 + x^3*y + x

```

basis_matrix()

Return the matrix of basis vectors of this ideal as a module.

The basis matrix is by definition the hermite norm form of the ideal divided by the denominator.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)

```

(continues on next page)

(continued from previous page)

```

sage: O = F.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.denominator() * I.basis_matrix() == I.hnf()
True

```

denominator()

Return the denominator of this fractional ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.maximal_order()
sage: I = O.ideal(y/(y+1))
sage: d = I.denominator(); d
x^3
sage: d in O
True

```

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.maximal_order()
sage: I = O.ideal(y/(y+1))
sage: d = I.denominator(); d
x^3
sage: d in O
True

```

gens()

Return a set of generators of this ideal.

This provides whatever set of generators as quickly as possible.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); L.<y> = K[]
sage: L.<y> = K.extension(Y^2 - x^3*Y - x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)
sage: I.gens()
(x^4 + x^2 + x, y + x)

sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)
sage: I.gens()
(x^3 + 1, y + x)

```

gens_over_base()

Return the generators of this ideal as a module over the maximal order of the base rational function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); L.<y> = K[]
sage: L.<y> = K.extension(Y^2 - x^3*Y - x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)

```

(continues on next page)

(continued from previous page)

```

sage: I.gens_over_base()
(x^4 + x^2 + x, y + x)

sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)
sage: I.gens_over_base()
(x^3 + 1, y + x)

```

hnf()

Return the matrix in hermite normal form representing this ideal.

See also *denominator()*

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.maximal_order()
sage: I = O.ideal(y*(y+1)); I.hnf()
[x^6 + x^3      0]
[ x^3 + 1      1]

```

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x^3 - 1)
sage: O = L.maximal_order()
sage: I = O.ideal(y*(y+1)); I.hnf()
[x^6 + x^3      0]
[ x^3 + 1      1]

```

ideal_below()

Return the ideal below this ideal.

This is defined only for integral ideals.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.ideal_below()
Traceback (most recent call last):
...
TypeError: not an integral ideal
sage: J = I.denominator() * I
sage: J.ideal_below()
Ideal (x^3 + x^2 + x) of Maximal order of Rational function field
in x over Finite Field of size 2

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.ideal_below()
Traceback (most recent call last):
...

```

(continues on next page)

(continued from previous page)

```

TypeError: not an integral ideal
sage: J = I.denominator() * I
sage: J.ideal_below()
Ideal (x^3 + x) of Maximal order of Rational function field
in x over Finite Field of size 2

sage: K.<x> = FunctionField(QQ); _.<t> = K[]
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.ideal_below()
Traceback (most recent call last):
...
TypeError: not an integral ideal
sage: J = I.denominator() * I
sage: J.ideal_below()
Ideal (x^3 + x^2 + x) of Maximal order of Rational function field
in x over Rational Field

```

intersect (*other*)

Intersect this ideal with the other ideal as fractional ideals.

INPUT:

- *other* – ideal

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 - x^3*Y - x)
sage: O = L.maximal_order()
sage: I = O.ideal(x+y)
sage: J = O.ideal(x)
sage: I.intersect(J) == I * J * (I + J)^-1
True

```

is_integral ()

Return True if this is an integral ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.is_integral()
False
sage: J = I.denominator() * I
sage: J.is_integral()
True

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.is_integral()
False
sage: J = I.denominator() * I

```

(continues on next page)

(continued from previous page)

```

sage: J.is_integral()
True

sage: K.<x> = FunctionField(QQ); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.is_integral()
False
sage: J = I.denominator() * I
sage: J.is_integral()
True

```

is_prime()

Return True if this ideal is a prime ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: [f.is_prime() for f,_ in I.factor()]
[True, True]

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: [f.is_prime() for f,_ in I.factor()]
[True, True]

sage: K.<x> = FunctionField(QQ); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: [f.is_prime() for f,_ in I.factor()]
[True, True]

```

module()

Return the module, that is the ideal viewed as a module over the base maximal order.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: F.<y> = K.extension(y^2 - x^3 - 1)
sage: O = F.maximal_order()
sage: I = O.ideal(x, 1/y)
sage: I.module()
Free module of degree 2 and rank 2 over Maximal order
of Rational function field in x over Finite Field of size 7
Echelon basis matrix:
[      1      0]
[      0 1/(x^3 + 1)]

```

norm()

Return the norm of this fractional ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^3-x^2*(x^2+x+1)^2)
sage: O = F.maximal_order()
sage: i1 = O.ideal(x)
sage: i2 = O.ideal(y)
sage: i3 = i1 * i2
sage: i3.norm() == i1.norm() * i2.norm()
True
sage: i1.norm()
x^3
sage: i1.norm() == x ** F.degree()
True
sage: i2.norm()
x^6 + x^4 + x^2
sage: i2.norm() == y.norm()
True

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: i1 = O.ideal(x)
sage: i2 = O.ideal(y)
sage: i3 = i1 * i2
sage: i3.norm() == i1.norm() * i2.norm()
True
sage: i1.norm()
x^2
sage: i1.norm() == x ** L.degree()
True
sage: i2.norm()
(x^2 + 1)/x
sage: i2.norm() == y.norm()
True

```

prime_below()

Return the prime lying below this prime ideal.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: [f.prime_below() for f, _ in I.factor()]
[Ideal (x) of Maximal order of Rational function field in x
over Finite Field of size 2, Ideal (x^2 + x + 1) of Maximal order
of Rational function field in x over Finite Field of size 2]

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: [f.prime_below() for f, _ in I.factor()]
[Ideal (x) of Maximal order of Rational function field in x over Finite Field
↳ of size 2,
Ideal (x + 1) of Maximal order of Rational function field in x over Finite
↳ Field of size 2]

```

(continues on next page)

(continued from previous page)

```

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(y)
sage: [f.prime_below() for f,_ in I.factor()]
[Ideal (x) of Maximal order of Rational function field in x over Rational
↪Field,
 Ideal (x^2 + x + 1) of Maximal order of Rational function field in x over
↪Rational Field]

```

valuation (*ideal*)Return the valuation of *ideal* at this prime ideal.

INPUT:

- *ideal* – fractional ideal

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: O = F.maximal_order()
sage: I = O.ideal(x, (1/(x^3 + x^2 + x))*y^2)
sage: I.is_prime()
True
sage: J = O.ideal(y)
sage: I.valuation(J)
2

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: O = L.maximal_order()
sage: I = O.ideal(y)
sage: [f.valuation(I) for f,_ in I.factor()]
[-1, 2]

```

The method closely follows Algorithm 4.8.17 of [Coh1993].

class sage.rings.function_field.ideal.**FunctionFieldIdeal_rational** (*ring*, *gen*)Bases: *sage.rings.function_field.ideal.FunctionFieldIdeal*

Fractional ideals of the maximal order of a rational function field.

INPUT:

- *ring* – the maximal order of the rational function field.
- *gen* – generator of the ideal, an element of the function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: I = O.ideal(1/(x^2+x)); I
Ideal (1/(x^2 + x)) of Maximal order of Rational function field in x over
↪Rational Field

```

denominator ()

Return the denominator of this fractional ideal.

EXAMPLES:

```
sage: F.<x> = FunctionField(QQ)
sage: O = F.maximal_order()
sage: I = O.ideal(x/(x^2+1))
sage: I.denominator()
x^2 + 1
```

gen()

Return the unique generator of this ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x^2+x)
sage: I.gen()
x^2 + x
```

gens()

Return the tuple of the unique generator of this ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x^2+x)
sage: I.gens()
(x^2 + x,)
```

gens_over_base()

Return the generator of this ideal as a rank one module over the maximal order.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4))
sage: O = K.maximal_order()
sage: I = O.ideal(x^2+x)
sage: I.gens_over_base()
(x^2 + x,)
```

is_prime()

Return True if this is a prime ideal.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order()
sage: I = O.ideal(x^3+x^2)
sage: [f.is_prime() for f,m in I.factor()]
[True, True]
```

module()

Return the module, that is the ideal viewed as a module over the ring.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: O = K.maximal_order()
```

(continues on next page)

(continued from previous page)

```

sage: I = O.ideal(x^3+x^2)
sage: I.module()
Free module of degree 1 and rank 1 over Maximal order of Rational
function field in x over Rational Field
Echelon basis matrix:
[x^3 + x^2]
sage: J = 0*I
sage: J.module()
Free module of degree 1 and rank 0 over Maximal order of Rational
function field in x over Rational Field
Echelon basis matrix:
[]

```

valuation (*ideal*)

Return the valuation of the ideal at this prime ideal.

INPUT:

- ideal – fractional ideal

EXAMPLES:

```

sage: F.<x> = FunctionField(QQ)
sage: O = F.maximal_order()
sage: I = O.ideal(x^2*(x^2+x+1)^3)
sage: [f.valuation(I) for f,_ in I.factor()]
[2, 3]

```

class sage.rings.function_field.ideal.IdealMonoid(*R*)

Bases: sage.structure.unique_representation.UniqueRepresentation, sage.structure.parent.Parent

The monoid of ideals in orders of function fields.

INPUT:

- R – order

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: O = K.maximal_order()
sage: M = O.ideal_monoid(); M
Monoid of ideals of Maximal order of Rational function field in x over Finite_
↪Field of size 2

```

ring ()

Return the ring of which this is the ideal monoid.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2))
sage: O = K.maximal_order()
sage: M = O.ideal_monoid(); M.ring() is O
True

```


PLACES OF FUNCTION FIELDS

The places of a function field correspond, one-to-one, to valuation rings of the function field, each of which defines a discrete valuation for the elements of the function field. “Finite” places are in one-to-one correspondence with the prime ideals of the finite maximal order while places “at infinity” are in one-to-one correspondence with the prime ideals of the infinite maximal order.

EXAMPLES:

All rational places of a function field can be computed:

```
sage: K.<x> = FunctionField(GF(2)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: L.places()
[Place (1/x, 1/x^3*y^2 + 1/x),
 Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1),
 Place (x, y)]
```

The residue field associated with a place is given as an extension of the constant field:

```
sage: F.<x> = FunctionField(GF(2))
sage: O = F.maximal_order()
sage: p = O.ideal(x^2 + x + 1).place()
sage: k, fr_k, to_k = p.residue_field()
sage: k
Finite Field in z2 of size 2^2
```

The homomorphisms are between the valuation ring and the residue field:

```
sage: fr_k
Ring morphism:
  From: Finite Field in z2 of size 2^2
  To:   Valuation ring at Place (x^2 + x + 1)
sage: to_k
Ring morphism:
  From: Valuation ring at Place (x^2 + x + 1)
  To:   Finite Field in z2 of size 2^2
```

AUTHORS:

- Kwankyu Lee (2017-04-30): initial version
- Brent Baccala (2019-12-20): function fields of characteristic zero

```
class sage.rings.function_field.place.FunctionFieldPlace(parent, prime)
```

```
  Bases: sage.structure.element.Element
```

```
  Places of function fields.
```

INPUT:

- `field` – function field
- `prime` – prime ideal associated with the place

EXAMPLES:

```
sage: K.<x>=FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y>=K.extension(Y^3 + x + x^3*Y)
sage: L.places_finite()[0]
Place (x, y)
```

divisor (*multiplicity=1*)

Return the prime divisor corresponding to the place.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(5)); R.<t> = PolynomialRing(K)
sage: F.<y> = K.extension(t^2-x^3-1)
sage: O = F.maximal_order()
sage: I = O.ideal(x+1,y)
sage: P = I.place()
sage: P.divisor()
Place (x + 1, y)
```

function_field()

Return the function field to which the place belongs.

EXAMPLES:

```
sage: K.<x>=FunctionField(GF(2)); _.<Y>=K[]
sage: L.<y>=K.extension(Y^3+x+x^3*Y)
sage: p = L.places()[0]
sage: p.function_field() == L
True
```

prime_ideal()

Return the prime ideal associated with the place.

EXAMPLES:

```
sage: K.<x>=FunctionField(GF(2)); _.<Y>=K[]
sage: L.<y>=K.extension(Y^3+x+x^3*Y)
sage: p = L.places()[0]
sage: p.prime_ideal()
Ideal (1/x^3*y^2 + 1/x) of Maximal infinite order of Function field
in y defined by y^3 + x^3*y + x
```

class `sage.rings.function_field.place.FunctionFieldPlace_polymod` (*parent*, *prime*)

Bases: `sage.rings.function_field.place.FunctionFieldPlace`

Places of extensions of function fields.

degree()

Return the degree of the place.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: OK = L.maximal_order()
sage: OL = L.maximal_order()
sage: p = OK.ideal(x^2 + x + 1)
sage: dec = OL.decomposition(p)
sage: q = dec[0][0].place()
sage: q.degree()
2

```

gaps()

Return the gap sequence for the place.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: O = L.maximal_order()
sage: p = O.ideal(x,y).place()
sage: p.gaps() # a Weierstrass place
[1, 2, 4]

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3 * Y + x)
sage: [p.gaps() for p in L.places()]
[[1, 2, 4], [1, 2, 4], [1, 2, 4]]

```

is_infinite_place()

Return True if the place is above the unique infinite place of the underlying rational function field.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: pls = L.places()
sage: [p.is_infinite_place() for p in pls]
[True, True, False]
sage: [p.place_below() for p in pls]
[Place (1/x), Place (1/x), Place (x)]

```

local_uniformizer()

Return an element of the function field that has a simple zero at the place.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: pls = L.places()
sage: [p.local_uniformizer().valuation(p) for p in pls]
[1, 1, 1, 1, 1]

```

place_below()

Return the place lying below the place.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)

```

(continues on next page)

(continued from previous page)

```

sage: OK = K.maximal_order()
sage: OL = L.maximal_order()
sage: p = OK.ideal(x^2 + x + 1)
sage: dec = OL.decomposition(p)
sage: q = dec[0][0].place()
sage: q.place_below()
Place (x^2 + x + 1)

```

relative_degree()

Return the relative degree of the place.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: OK = K.maximal_order()
sage: OL = L.maximal_order()
sage: p = OK.ideal(x^2 + x + 1)
sage: dec = OL.decomposition(p)
sage: q = dec[0][0].place()
sage: q.relative_degree()
1

```

residue_field(name=None)

Return the residue field of the place.

INPUT:

- name – string; name of the generator of the residue field

OUTPUT:

- a field isomorphic to the residue field
- a ring homomorphism from the valuation ring to the field
- a ring homomorphism from the field to the valuation ring

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: k, fr_k, to_k = p.residue_field()
sage: k
Finite Field of size 2
sage: fr_k
Ring morphism:
  From: Finite Field of size 2
  To:   Valuation ring at Place (x, x*y)
sage: to_k
Ring morphism:
  From: Valuation ring at Place (x, x*y)
  To:   Finite Field of size 2
sage: to_k(y)
Traceback (most recent call last):
...
TypeError: y fails to convert into the map's domain
Valuation ring at Place (x, x*y)...

```

(continues on next page)

(continued from previous page)

```

sage: to_k(1/y)
0
sage: to_k(y/(1+y))
1

```

valuation_ring()

Return the valuation ring at the place.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: p.valuation_ring()
Valuation ring at Place (x, x*y)

```

class sage.rings.function_field.place.**FunctionFieldPlace_rational** (*parent*,
prime)

Bases: *sage.rings.function_field.place.FunctionFieldPlace*

Places of rational function fields.

degree()

Return the degree of the place.

EXAMPLES:

```

sage: F.<x> = FunctionField(GF(2))
sage: O = F.maximal_order()
sage: i = O.ideal(x^2+x+1)
sage: p = i.place()
sage: p.degree()
2

```

is_infinite_place()

Return True if the place is at infinite.

EXAMPLES:

```

sage: F.<x> = FunctionField(GF(2))
sage: F.places()
[Place (1/x), Place (x), Place (x + 1)]
sage: [p.is_infinite_place() for p in F.places()]
[True, False, False]

```

local_uniformizer()

Return a local uniformizer of the place.

EXAMPLES:

```

sage: F.<x> = FunctionField(GF(2))
sage: F.places()
[Place (1/x), Place (x), Place (x + 1)]
sage: [p.local_uniformizer() for p in F.places()]
[1/x, x, x + 1]

```

residue_field (*name=None*)

Return the residue field of the place.

EXAMPLES:

```
sage: F.<x> = FunctionField(GF(2))
sage: O = F.maximal_order()
sage: p = O.ideal(x^2 + x + 1).place()
sage: k, fr_k, to_k = p.residue_field()
sage: k
Finite Field in z2 of size 2^2
sage: fr_k
Ring morphism:
  From: Finite Field in z2 of size 2^2
  To:   Valuation ring at Place (x^2 + x + 1)
sage: to_k
Ring morphism:
  From: Valuation ring at Place (x^2 + x + 1)
  To:   Finite Field in z2 of size 2^2
```

valuation_ring()

Return the valuation ring at the place.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: p.valuation_ring()
Valuation ring at Place (x, x*y)
```

class sage.rings.function_field.place.**PlaceSet** (*field*)

Bases: sage.structure.unique_representation.UniqueRepresentation, sage.structure.parent.Parent

Sets of Places of function fields.

INPUT:

- *field* – function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: L.place_set()
Set of places of Function field in y defined by y^3 + x^3*y + x
```

Element

alias of *FunctionFieldPlace*

DIVISORS OF FUNCTION FIELDS

Sage allows extensive computations with divisors on function fields.

EXAMPLES:

The divisor of an element of the function field is the formal sum of poles and zeros of the element with multiplicities:

```
sage: K.<x> = FunctionField(GF(2)); R.<t> = K[]
sage: L.<y> = K.extension(t^3 + x^3*t + x)
sage: f = x/(y+1)
sage: f.divisor()
- Place (1/x, 1/x^3*y^2 + 1/x)
+ Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1)
+ 3*Place (x, y)
- Place (x^3 + x + 1, y + 1)
```

The Riemann-Roch space of a divisor can be computed. We can get a basis of the space as a vector space over the constant field:

```
sage: p = L.places_finite()[0]
sage: q = L.places_infinite()[0]
sage: (3*p + 2*q).basis_function_space()
[1/x*y^2 + x^2, 1, 1/x]
```

We verify the Riemann-Roch theorem:

```
sage: D = 3*p - q
sage: index_of_speciality = len(D.basis_differential_space())
sage: D.dimension() == D.degree() - L.genus() + 1 + index_of_speciality
True
```

AUTHORS:

- Kwankyu Lee (2017-04-30): initial version

```
class sage.rings.function_field.divisor.DivisorGroup(field)
    Bases:      sage.structure.unique_representation.UniqueRepresentation,      sage.
               structure.parent.Parent
```

Groups of divisors of function fields.

INPUT:

- field – function field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 - x^3 - 1)
sage: F.divisor_group()
Divisor group of Function field in y defined by y^2 + 4*x^3 + 4

```

Element

alias of *FunctionFieldDivisor*

function_field()

Return the function field to which the divisor group is attached.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 - x^3 - 1)
sage: G = F.divisor_group()
sage: G.function_field()
Function field in y defined by y^2 + 4*x^3 + 4

```

class sage.rings.function_field.divisor.**FunctionFieldDivisor** (*parent, data*)

Bases: *sage.structure.element.ModuleElement*

Divisors of function fields.

INPUT:

- *parent* – divisor group
- *data* – dict of place and multiplicity pairs

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^3 - x^2*(x^2 + x + 1)^2)
sage: f = x/(y + 1)
sage: f.divisor()
Place (1/x, 1/x^4*y^2 + 1/x^2*y + 1)
+ Place (1/x, 1/x^2*y + 1)
+ 3*Place (x, (1/(x^3 + x^2 + x))*y^2)
- 6*Place (x + 1, y + 1)

```

basis_differential_space()

Return a basis of the space of differentials $\Omega(D)$ for the divisor D .

EXAMPLES:

We check the Riemann-Roch theorem:

```

sage: K.<x>=FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y>=K.extension(Y^3 + x^3*Y + x)
sage: d = 3*L.places()[0]
sage: l = len(d.basis_function_space())
sage: i = len(d.basis_differential_space())
sage: l == d.degree() + 1 - L.genus() + i
True

```

basis_function_space()

Return a basis of the Riemann-Roch space of the divisor.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 - x^3 - 1)
sage: O = F.maximal_order()
sage: I = O.ideal(x - 2)
sage: D = I.divisor()
sage: D.basis_function_space()
[x/(x + 3), 1/(x + 3)]

```

degree()

Return the degree of the divisor.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: p1, p2 = L.places()[1:2]
sage: D = 2*p1 - 3*p2
sage: D.degree()
-1

```

dict()

Return the dictionary representing the divisor.

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: f = x/(y + 1)
sage: D = f.divisor()
sage: D.dict()
{Place (1/x, 1/x^3*y^2 + 1/x): -1,
 Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1): 1,
 Place (x, y): 3,
 Place (x^3 + x + 1, y + 1): -1}

```

differential_space()

Return the vector space of the differential space $\Omega(D)$ of the divisor D .

OUTPUT:

- a vector space isomorphic to $\Omega(D)$
- an isomorphism from the vector space to the differential space
- the inverse of the isomorphism

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 - x^3 - 1)
sage: O = F.maximal_order()
sage: I = O.ideal(x - 2)
sage: P1 = I.divisor().support()[0]
sage: Pinf = F.places_infinite()[0]
sage: D = -3*Pinf + P1
sage: V, from_V, to_V = D.differential_space()
sage: all(to_V(from_V(e)) == e for e in V)
True

```

dimension()

Return the dimension of the Riemann-Roch space of the divisor.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2 - x^3 - 1)
sage: O = F.maximal_order()
sage: I = O.ideal(x - 2)
sage: P1 = I.divisor().support()[0]
sage: Pinf = F.places_infinite()[0]
sage: D = 3*Pinf + 2*P1
sage: D.dimension()
5
```

function_space()

Return the vector space of the Riemann-Roch space of the divisor.

OUTPUT:

- a vector space, an isomorphism from the vector space to the Riemann-Roch space, and its inverse.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: F.<y> = K.extension(Y^2-x^3-1)
sage: O = F.maximal_order()
sage: I = O.ideal(x - 2)
sage: D = I.divisor()
sage: V, from_V, to_V = D.function_space()
sage: all(to_V(from_V(e)) == e for e in V)
True
```

list()

Return the list of place and multiplicity pairs of the divisor.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: f = x/(y + 1)
sage: D = f.divisor()
sage: D.list()
[(Place (1/x, 1/x^3*y^2 + 1/x), -1),
 (Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1), 1),
 (Place (x, y), 3),
 (Place (x^3 + x + 1, y + 1), -1)]
```

multiplicity(place)

Return the multiplicity of the divisor at the place.

INPUT:

- place – place of a function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: p1, p2 = L.places()[2:]
```

(continues on next page)

(continued from previous page)

```
sage: D = 2*p1 - 3*p2
sage: D.multiplicity(p1)
2
sage: D.multiplicity(p2)
-3
```

support ()

Return the support of the divisor.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: f = x/(y + 1)
sage: D = f.divisor()
sage: D.support()
[Place (1/x, 1/x^3*y^2 + 1/x),
 Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1),
 Place (x, y),
 Place (x^3 + x + 1, y + 1)]
```

valuation (place)

Return the multiplicity of the divisor at the place.

INPUT:

- place – place of a function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: p1, p2 = L.places()[2:]
sage: D = 2*p1 - 3*p2
sage: D.multiplicity(p1)
2
sage: D.multiplicity(p2)
-3
```

`sage.rings.function_field.divisor.divisor (field, data)`

Construct a divisor from the data.

INPUT:

- field – function field
- data – dictionary of place and multiplicity pairs

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); R.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: from sage.rings.function_field.divisor import divisor
sage: p, q, r = F.places()
sage: divisor(F, {p: 1, q: 2, r: 3})
Place (1/x, 1/x^2*y + 1)
+ 2*Place (x, (1/(x^3 + x^2 + x))*y^2)
+ 3*Place (x + 1, y + 1)
```

`sage.rings.function_field.divisor.prime_divisor` (*field*, *place*, *m=1*)
Construct a prime divisor from the place.

INPUT:

- *field* – function field
- *place* – place of the function field
- *m* – (default: 1) a positive integer; multiplicity at the place

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); R.<t> = K[]
sage: F.<y> = K.extension(t^3 - x^2*(x^2 + x + 1)^2)
sage: p = F.places()[0]
sage: from sage.rings.function_field.divisor import prime_divisor
sage: d = prime_divisor(F, p)
sage: 3 * d == prime_divisor(F, p, 3)
True
```


DIFFERENTIALS OF FUNCTION FIELDS

Sage provides arithmetic with differentials of function fields.

EXAMPLES:

The module of differentials on a function field forms an one-dimensional vector space over the function field:

```
sage: K.<x> = FunctionField(GF(4)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: f = x + y
sage: g = 1 / y
sage: df = f.differential()
sage: dg = g.differential()
sage: dfdg = f.derivative() / g.derivative()
sage: df == dfdg * dg
True
sage: df
(x*y^2 + 1/x*y + 1) d(x)
sage: df.parent()
Space of differentials of Function field in y defined by y^3 + x^3*y + x
```

We can compute a canonical divisor:

```
sage: k = df.divisor()
sage: k.degree()
4
sage: k.degree() == 2 * L.genus() - 2
True
```

Exact differentials vanish and logarithmic differentials are stable under the Cartier operation:

```
sage: df.cartier()
0
sage: w = 1/f * df
sage: w.cartier() == w
True
```

AUTHORS:

- Kwankyu Lee (2017-04-30): initial version

```
class sage.rings.function_field.differential.DifferentialsSpace(field, cate-  
                                                                gory=None)  
    Bases: sage.structure.unique_representation.UniqueRepresentation, sage.  
            structure.parent.Parent
```

Space of differentials of a function field.

INPUT:

- field – function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: L.space_of_differentials()
Space of differentials of Function field in y defined by y^3 + x^3*y + x
```

The space of differentials is a one-dimensional module over the function field. So a base differential is chosen to represent differentials. Usually the generator of the base rational function field is a separating element and used to generate the base differential. Otherwise a separating element is automatically found and used to generate the base differential relative to which other differentials are denoted:

```
sage: K.<x> = FunctionField(GF(5))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^5 - 1/x)
sage: L(x).differential()
0
sage: y.differential()
d(y)
sage: (y^2).differential()
(2*y) d(y)
```

Element

alias of *FunctionFieldDifferential*

basis()

Return a basis.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: S = L.space_of_differentials()
sage: S.basis()
Family (d(x),)
```

function_field()

Return the function field to which the space of differentials is attached.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: S = L.space_of_differentials()
sage: S.function_field()
Function field in y defined by y^3 + x^3*y + x
```

class sage.rings.function_field.differential.DifferentialsSpaceInclusion

Bases: *sage.categories.morphism.Morphism*

Inclusion morphisms for extensions of function fields.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
```

(continues on next page)

(continued from previous page)

```

sage: OK = K.space_of_differentials()
sage: OL = L.space_of_differentials()
sage: OL.coerce_map_from(OK)
Inclusion morphism:
  From: Space of differentials of Rational function field in x over Rational Field
  To:   Space of differentials of Function field in y defined by  $y^2 - xy + 4x^3$ 

```

is_injective()

Return True, since the inclusion morphism is injective.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: OK = K.space_of_differentials()
sage: OL = L.space_of_differentials()
sage: OL.coerce_map_from(OK).is_injective()
True

```

is_surjective()

Return True if the inclusion morphism is surjective.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: OK = K.space_of_differentials()
sage: OL = L.space_of_differentials()
sage: OL.coerce_map_from(OK).is_surjective()
False
sage: S.<z> = L[]
sage: M.<z> = L.extension(z - 1)
sage: OM = M.space_of_differentials()
sage: OM.coerce_map_from(OL).is_surjective()
True

```

class sage.rings.function_field.differential.DifferentialsSpace_global (*field*,
cat-
e-
gory=None)

Bases: *sage.rings.function_field.differential.DifferentialsSpace*

Space of differentials of a global function field.

INPUT:

- *field* – function field

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(4)); L.<y> = K[]
sage: L.<y> = K.extension(Y^3 + x^3*Y + x)
sage: L.space_of_differentials()
Space of differentials of Function field in y defined by  $y^3 + x^3y + x$ 

```

Elementalias of *FunctionFieldDifferential_global*

```
class sage.rings.function_field.differential.FunctionFieldDifferential (parent,
                                                                    f,
                                                                    t=None)
```

Bases: `sage.structure.element.ModuleElement`

Base class for differentials on function fields.

INPUT:

- f – element of the function field
- t – element of the function field; if t is not specified, the generator of the base differential is assumed

EXAMPLES:

```
sage: F.<x>=FunctionField(QQ)
sage: f = x/(x^2 + x + 1)
sage: f.differential()
((-x^2 + 1)/(x^4 + 2*x^3 + 3*x^2 + 2*x + 1)) d(x)
```

```
sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: L(x).differential()
d(x)
sage: y.differential()
((21/4*x/(x^7 + 27/4))*y^2 + ((3/2*x^7 + 9/4)/(x^8 + 27/4*x))*y + 7/2*x^4/(x^7 +
↪27/4)) d(x)
```

divisor()

Return the divisor of the differential.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(5)); _.<Y>=K[]
sage: L.<y> = K.extension(Y^3+x+x^3*Y)
sage: w = (1/y) * y.differential()
sage: w.divisor()
- Place (1/x, 1/x^3*y^2 + 1/x)
- Place (1/x, 1/x^3*y^2 + 1/x^2*y + 1)
- Place (x, y)
+ Place (x + 2, y + 3)
+ Place (x^6 + 3*x^5 + 4*x^4 + 2*x^3 + x^2 + 3*x + 4, y + x^5)
```

```
sage: F.<x> = FunctionField(QQ)
sage: w = (1/x).differential()
sage: w.divisor()
-2*Place (x)
```

monomial_coefficients (*copy=True*)

Return a dictionary whose keys are indices of basis elements in the support of `self` and whose values are the corresponding coefficients.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(5)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3+x+x^3*Y)
sage: d = y.differential()
sage: d
((4*x/(x^7 + 3))*y^2 + ((4*x^7 + 1)/(x^8 + 3*x))*y + x^4/(x^7 + 3)) d(x)
```

(continues on next page)

(continued from previous page)

```
sage: d.monomial_coefficients()
{0: (4*x/(x^7 + 3))*y^2 + ((4*x^7 + 1)/(x^8 + 3*x))*y + x^4/(x^7 + 3)}
```

residue (*place*)

Return the residue of the differential at the place.

INPUT:

- *place* – a place of the function field

OUTPUT:

- an element of the residue field of the place

EXAMPLES:

We verify the residue theorem in a rational function field:

```
sage: F.<x> = FunctionField(GF(4))
sage: f = 0
sage: while f == 0:
....:     f = F.random_element()
sage: w = 1/f * f.differential()
sage: d = f.divisor()
sage: s = d.support()
sage: sum([w.residue(p).trace() for p in s])
0
```

and in an extension field:

```
sage: K.<x> = FunctionField(GF(7)); L.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: f = 0
sage: while f == 0:
....:     f = L.random_element()
sage: w = 1/f * f.differential()
sage: d = f.divisor()
sage: s = d.support()
sage: sum([w.residue(p).trace() for p in s])
0
```

and also in a function field of characteristic zero:

```
sage: R.<x> = FunctionField(QQ)
sage: L.<Y> = R[]
sage: F.<y> = R.extension(Y^2 - x^4 - 4*x^3 - 2*x^2 - 1)
sage: a = 6*x^2 + 5*x + 7
sage: b = 2*x^6 + 8*x^5 + 3*x^4 - 4*x^3 - 1
sage: w = y*a/b*x.differential()
sage: d = w.divisor()
sage: sum([QQ(w.residue(p)) for p in d.support()])
0
```

valuation (*place*)

Return the valuation of the differential at the place.

INPUT:

- *place* – a place of the function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(5)); _.<Y>=K[]
sage: L.<y> = K.extension(Y^3+x+x^3*Y)
sage: w = (1/y) * y.differential()
sage: [w.valuation(p) for p in L.places()]
[-1, -1, -1, 0, 1, 0]
```

```
class sage.rings.function_field.differential.FunctionFieldDifferential_global (parent,
                                                                              f,
                                                                              t=None)
```

Bases: *sage.rings.function_field.differential.FunctionFieldDifferential*

Differentials on global function fields.

EXAMPLES:

```
sage: F.<x>=FunctionField(GF(7))
sage: f = x/(x^2 + x + 1)
sage: f.differential()
((6*x^2 + 1)/(x^4 + 2*x^3 + 3*x^2 + 2*x + 1)) d(x)
```

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: y.differential()
(x*y^2 + 1/x*y) d(x)
```

cartier()

Return the image of the differential by the Cartier operator.

The Cartier operator operates on differentials. Let x be a separating element of the function field. If a differential ω is written in prime-power representation $\omega = (f_0^p + f_1^p x + \cdots + f_{p-1}^p x^{p-1})dx$, then the Cartier operator maps ω to $f_{p-1}dx$. It is known that this definition does not depend on the choice of x .

The Cartier operator has interesting properties. Notably, the set of exact differentials is precisely the kernel of the Cartier operator and logarithmic differentials are stable under the Cartier operation.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(4)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: f = x/y
sage: w = 1/f*f.differential()
sage: w.cartier() == w
True
```

```
sage: F.<x> = FunctionField(GF(4))
sage: f = x/(x^2 + x + 1)
sage: w = 1/f*f.differential()
sage: w.cartier() == w
True
```

VALUATION RINGS OF FUNCTION FIELDS

A valuation ring of a function field is associated with a place of the function field. The valuation ring consists of all elements of the function field that have nonnegative valuation at the place.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: p
Place (x, x*y)
sage: R = p.valuation_ring()
sage: R
Valuation ring at Place (x, x*y)
sage: R.place() == p
True
```

Thus any nonzero element or its inverse of the function field lies in the valuation ring, as shown in the following example:

```
sage: f = y/(1+y)
sage: f in R
True
sage: f not in R
False
sage: f.valuation(p)
0
```

The residue field at the place is defined as the quotient ring of the valuation ring modulo its unique maximal ideal. The method `residue_field()` of the valuation ring returns an extension field of the constant base field, isomorphic to the residue field, along with lifting and evaluation homomorphisms:

```
sage: k, phi, psi = R.residue_field()
sage: k
Finite Field of size 2
sage: phi
Ring morphism:
  From: Finite Field of size 2
  To:   Valuation ring at Place (x, x*y)
sage: psi
Ring morphism:
  From: Valuation ring at Place (x, x*y)
  To:   Finite Field of size 2
sage: psi(f) in k
True
```

AUTHORS:

- Kwankyu Lee (2017-04-30): initial version

```
class sage.rings.function_field.valuation_ring.FunctionFieldValuationRing (field,  
                                                                    place,  
                                                                    cat-  
                                                                    e-  
                                                                    gory=None)  
sage.
```

Bases: `sage.structure.unique_representation.UniqueRepresentation`,
`structure.parent.Parent`

Base class for valuation rings of function fields.

INPUT:

- `field` – function field
- `place` – place of the function field

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]  
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)  
sage: p = L.places_finite()[0]  
sage: p.valuation_ring()  
Valuation ring at Place (x, x*y)
```

place()

Return the place associated with the valuation ring.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]  
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)  
sage: p = L.places_finite()[0]  
sage: R = p.valuation_ring()  
sage: p == R.place()  
True
```

residue_field (*name=None*)

Return the residue field of the valuation ring together with the maps from and to it.

INPUT:

- `name` – string; name of the generator of the field

OUTPUT:

- a field isomorphic to the residue field
- a ring homomorphism from the valuation ring to the field
- a ring homomorphism from the field to the valuation ring

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]  
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)  
sage: p = L.places_finite()[0]  
sage: R = p.valuation_ring()  
sage: k, fr_k, to_k = R.residue_field()  
sage: k
```

(continues on next page)

(continued from previous page)

```
Finite Field of size 2
sage: fr_k
Ring morphism:
  From: Finite Field of size 2
  To:   Valuation ring at Place (x, x*y)
sage: to_k
Ring morphism:
  From: Valuation ring at Place (x, x*y)
  To:   Finite Field of size 2
sage: to_k(1/y)
0
sage: to_k(y/(1+y))
1
```


MORPHISMS OF FUNCTION FIELDS

Maps and morphisms useful for computations with function fields.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: K.hom(1/x)
Function Field endomorphism of Rational function field in x over Rational Field
Defn: x |--> 1/x
sage: L.<y> = K.extension(y^2 - x)
sage: K.hom(y)
Function Field morphism:
From: Rational function field in x over Rational Field
To:   Function field in y defined by y^2 - x
Defn: x |--> y
sage: L.hom([y,x])
Function Field endomorphism of Function field in y defined by y^2 - x
Defn: y |--> y
      x |--> x
sage: L.hom([x,y])
Traceback (most recent call last):
...
ValueError: invalid morphism
```

For global function fields, which have positive characteristics, the higher derivation is available:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y>=K[]
sage: L.<y> = K.extension(Y^3+x+x^3*Y)
sage: h = L.higher_derivation()
sage: h(y^2, 2)
((x^7 + 1)/x^2)*y^2 + x^3*y
```

AUTHORS:

- William Stein (2010): initial version
- Julian R  th (2011-09-14, 2014-06-23, 2017-08-21): refactored class hierarchy; added derivation classes; morphisms to/from fraction fields
- Kwankyu Lee (2017-04-30): added higher derivations and completions

class sage.rings.function_field.maps.**FractionFieldToFunctionField**
 Bases: *sage.rings.function_field.maps.FunctionFieldVectorSpaceIsomorphism*
 Isomorphism from a fraction field of a polynomial ring to the isomorphic function field.

EXAMPLES:

```

sage: K = QQ['x'].fraction_field()
sage: L = K.function_field()
sage: f = L.coerce_map_from(K); f
Isomorphism:
  From: Fraction Field of Univariate Polynomial Ring in x over Rational Field
  To:   Rational function field in x over Rational Field

```

See also:

FunctionFieldToFractionField

section()

Return the inverse map of this isomorphism.

EXAMPLES:

```

sage: K = QQ['x'].fraction_field()
sage: L = K.function_field()
sage: f = L.coerce_map_from(K)
sage: f.section()
Isomorphism:
  From: Rational function field in x over Rational Field
  To:   Fraction Field of Univariate Polynomial Ring in x over Rational_
↪Field

```

```

class sage.rings.function_field.maps.FunctionFieldCompletion (field,      place,
                                                             name=None,
                                                             prec=None,
                                                             gen_name=None)

```

Bases: `sage.categories.map.Map`

Completions on function fields.

INPUT:

- `field` – function field
- `place` – place of the function field
- `name` – string for the name of the series variable
- `prec` – positive integer; default precision
- `gen_name` – string; name of the generator of the residue field; used only when `place` is non-rational

EXAMPLES:

```

sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: m = L.completion(p)
sage: m
Completion map:
  From: Function field in y defined by y^2 + y + (x^2 + 1)/x
  To:   Laurent Series Ring in s over Finite Field of size 2
sage: m(x)
s^2 + s^3 + s^4 + s^5 + s^7 + s^8 + s^9 + s^10 + s^12 + s^13
+ s^15 + s^16 + s^17 + s^19 + O(s^22)
sage: m(y)
s^-1 + 1 + s^3 + s^5 + s^7 + s^9 + s^13 + s^15 + s^17 + O(s^19)
sage: m(x*y) == m(x) * m(y)

```

(continues on next page)

(continued from previous page)

```
True
sage: m(x+y) == m(x) + m(y)
True
```

The variable name of the series can be supplied. If the place is not rational such that the residue field is a proper extension of the constant field, you can also specify the generator name of the extension:

```
sage: p2 = L.places_finite(2)[0]
sage: p2
Place (x^2 + x + 1, x*y + 1)
sage: m2 = L.completion(p2, 't', gen_name='b')
sage: m2(x)
(b + 1) + t + t^2 + t^4 + t^8 + t^16 + O(t^20)
sage: m2(y)
b + b*t + b*t^3 + b*t^4 + (b + 1)*t^5 + (b + 1)*t^7 + b*t^9 + b*t^11
+ b*t^12 + b*t^13 + b*t^15 + b*t^16 + (b + 1)*t^17 + (b + 1)*t^19 + O(t^20)
```

default_precision()

Return the default precision.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^2 + Y + x + 1/x)
sage: p = L.places_finite()[0]
sage: m = L.completion(p)
sage: m.default_precision()
20
```

class sage.rings.function_field.maps.**FunctionFieldConversionToConstantBaseField**(parent)

Bases: sage.categories.map.Map

Conversion map from the function field to its constant base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: QQ.convert_map_from(K)
Conversion map:
  From: Rational function field in x over Rational Field
  To:   Rational Field
```

class sage.rings.function_field.maps.**FunctionFieldDerivation**(K)

Bases: sage.categories.map.Map

Base class for derivations on function fields.

A derivation on R is a map $R \rightarrow R$ with $D(\alpha + \beta) = D(\alpha) + D(\beta)$ and $D(\alpha\beta) = \beta D(\alpha) + \alpha D(\beta)$ for all $\alpha, \beta \in R$.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: d = K.derivation()
sage: d
Derivation map:
  From: Rational function field in x over Rational Field
  To:   Rational function field in x over Rational Field
  Defn: x |--> 1
```

is_injective()

Return False since a derivation is never injective.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: d = K.derivation()
sage: d.is_injective()
False
```

class sage.rings.function_field.maps.**FunctionFieldDerivation_inseparable**(*L*)
 Bases: *sage.rings.function_field.maps.FunctionFieldDerivation*

A generator of the space of derivations on *L*.

INPUT:

- *L* – a function field which is an inseparable extension of its base field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: d = L.derivation()
```

This also works for iterated non-monic extensions:

```
sage: K.<x> = FunctionField(GF(2))
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - 1/x)
sage: R.<z> = L[]
sage: M.<z> = L.extension(z^2*y - x^3)
sage: M.derivation()
Derivation map:
  From: Function field in z defined by y*z^2 + x^3
  To:   Function field in z defined by y*z^2 + x^3
  Defn: z |--> 1
        y |--> 0
        x |--> 0
```

class sage.rings.function_field.maps.**FunctionFieldDerivation_rational**(*K, u*)
 Bases: *sage.rings.function_field.maps.FunctionFieldDerivation*

Derivations on rational function fields.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: K.derivation()
Derivation map:
  From: Rational function field in x over Rational Field
  To:   Rational function field in x over Rational Field
  Defn: x |--> 1
```

class sage.rings.function_field.maps.**FunctionFieldDerivation_separable**(*L, d*)
 Bases: *sage.rings.function_field.maps.FunctionFieldDerivation*

Derivations of separable extensions.

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x)
sage: L.derivation()
Derivation map:
  From: Function field in y defined by y^2 - x
  To:   Function field in y defined by y^2 - x
  Defn: y |--> 1/2/x*y
        x |--> 1

```

class sage.rings.function_field.maps.**FunctionFieldHigherDerivation** (*field*)

Bases: `sage.categories.map.Map`

Base class of higher derivations on function fields.

INPUT:

- *field* – function field on which the derivation operates

EXAMPLES:

```

sage: F.<x> = FunctionField(GF(2))
sage: F.higher_derivation()
Higher derivation map:
  From: Rational function field in x over Finite Field of size 2
  To:   Rational function field in x over Finite Field of size 2

```

class sage.rings.function_field.maps.**FunctionFieldHigherDerivation_char_zero** (*field*)

Bases: `sage.rings.function_field.maps.FunctionFieldHigherDerivation`

Higher derivations of function fields of characteristic zero.

INPUT:

- *field* – function field on which the derivation operates

EXAMPLES:

```

sage: K.<x> = FunctionField(QQ); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: h = L.higher_derivation()
sage: h
Higher derivation map:
  From: Function field in y defined by y^3 + x^3*y + x
  To:   Function field in y defined by y^3 + x^3*y + x
sage: h(y,1) == -(3*x^2*y+1)/(3*y^2+x^3)
True
sage: h(y^2,1) == -2*y*(3*x^2*y+1)/(3*y^2+x^3)
True
sage: e = L.random_element()
sage: h(h(e,1),1) == 2*h(e,2)
True
sage: h(h(h(e,1),1),1) == 3*2*h(e,3)
True

```

class sage.rings.function_field.maps.**FunctionFieldHigherDerivation_global** (*field*)

Bases: `sage.rings.function_field.maps.FunctionFieldHigherDerivation`

Higher derivations of global function fields.

INPUT:

- `field` – function field on which the derivation operates

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(2)); _.<Y> = K[]
sage: L.<y> = K.extension(Y^3 + x + x^3*Y)
sage: h = L.higher_derivation()
sage: h
Higher derivation map:
  From: Function field in y defined by y^3 + x^3*y + x
  To:   Function field in y defined by y^3 + x^3*y + x
sage: h(y^2, 2)
((x^7 + 1)/x^2)*y^2 + x^3*y
```

class `sage.rings.function_field.maps.FunctionFieldLinearMap`

Bases: `sage.categories.morphism.SetMorphism`

Linear map to function fields.

class `sage.rings.function_field.maps.FunctionFieldLinearMapSection`

Bases: `sage.categories.morphism.SetMorphism`

Section of linear map from function fields.

class `sage.rings.function_field.maps.FunctionFieldMorphism` (*parent*, *im_gen*,
base_morphism)

Bases: `sage.rings.morphism.RingHomomorphism`

Base class for morphisms between function fields.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: f = K.hom(1/x); f
Function Field endomorphism of Rational function field in x over Rational Field
Defn: x |--> 1/x
```

class `sage.rings.function_field.maps.FunctionFieldMorphism_polymod` (*parent*,
im_gen,
base_morphism)

Bases: `sage.rings.function_field.maps.FunctionFieldMorphism`

Morphism from a finite extension of a function field to a function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(GF(7)); R.<y> = K[]
sage: L.<y> = K.extension(y^3 + 6*x^3 + x)
sage: f = L.hom(y^2); f
Function Field endomorphism of Function field in y defined by y^3 + 6*x^3 + x
Defn: y |--> 2*y
sage: factor(L.polynomial())
y^3 + 6*x^3 + x
sage: f(y).charpoly('y')
y^3 + 6*x^3 + x
```

class `sage.rings.function_field.maps.FunctionFieldMorphism_rational` (*parent*,
im_gen,
base_morphism)

Bases: `sage.rings.function_field.maps.FunctionFieldMorphism`

Morphism from a rational function field to a function field.

class sage.rings.function_field.maps.**FunctionFieldRingMorphism**

Bases: *sage.categories.morphism.SetMorphism*

Ring homomorphism.

class sage.rings.function_field.maps.**FunctionFieldToFractionField**

Bases: *sage.rings.function_field.maps.FunctionFieldVectorSpaceIsomorphism*

Isomorphism from rational function field to the isomorphic fraction field of a polynomial ring.

EXAMPLES:

```
sage: K = QQ['x'].fraction_field()
sage: L = K.function_field()
sage: f = K.coerce_map_from(L); f
Isomorphism:
  From: Rational function field in x over Rational Field
  To:   Fraction Field of Univariate Polynomial Ring in x over Rational Field
```

See also:

FractionFieldToFunctionField

section()

Return the inverse map of this isomorphism.

EXAMPLES:

```
sage: K = QQ['x'].fraction_field()
sage: L = K.function_field()
sage: f = K.coerce_map_from(L)
sage: f.section()
Isomorphism:
  From: Fraction Field of Univariate Polynomial Ring in x over Rational
  ↪Field
  To:   Rational function field in x over Rational Field
```

class sage.rings.function_field.maps.**FunctionFieldVectorSpaceIsomorphism**

Bases: *sage.categories.morphism.Morphism*

Base class for isomorphisms between function fields and vector spaces.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space()
sage: isinstance(f, sage.rings.function_field.maps.
  ↪FunctionFieldVectorSpaceIsomorphism)
True
```

is_injective()

Return True, since the isomorphism is injective.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space()
sage: f.is_injective()
True
```

is_surjective()

Return True, since the isomorphism is surjective.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space()
sage: f.is_surjective()
True
```

class sage.rings.function_field.maps.**MapFunctionFieldToVectorSpace**(K, V)

Bases: *sage.rings.function_field.maps.FunctionFieldVectorSpaceIsomorphism*

Isomorphism from a function field to a vector space.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space(); t
Isomorphism:
  From: Function field in y defined by y^2 - x*y + 4*x^3
  To:   Vector space of dimension 2 over Rational function field in x over_
↪Rational Field
```

class sage.rings.function_field.maps.**MapVectorSpaceToFunctionField**(V, K)

Bases: *sage.rings.function_field.maps.FunctionFieldVectorSpaceIsomorphism*

Isomorphism from a vector space to a function field.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space(); f
Isomorphism:
  From: Vector space of dimension 2 over Rational function field in x over_
↪Rational Field
  To:   Function field in y defined by y^2 - x*y + 4*x^3
```

codomain()

Return the function field which is the codomain of the isomorphism.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space()
sage: f.codomain()
Function field in y defined by y^2 - x*y + 4*x^3
```

domain()

Return the vector space which is the domain of the isomorphism.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); R.<y> = K[]
sage: L.<y> = K.extension(y^2 - x*y + 4*x^3)
sage: V, f, t = L.vector_space()
```

(continues on next page)

(continued from previous page)

```

sage: f.domain()
Vector space of dimension 2 over Rational function field in x over Rational_
↪Field

```

class sage.rings.function_field.maps.**RationalFunctionFieldHigherDerivation_global** (*field*)
 Bases: *sage.rings.function_field.maps.FunctionFieldHigherDerivation*

Higher derivations of rational function fields over finite fields.

INPUT:

- `field` – function field on which the derivation operates

EXAMPLES:

```

sage: F.<x> = FunctionField(GF(2))
sage: h = F.higher_derivation()
sage: h
Higher derivation map:
  From: Rational function field in x over Finite Field of size 2
  To:   Rational function field in x over Finite Field of size 2
sage: h(x^2, 2)
1

```


FACTORIES TO CONSTRUCT FUNCTION FIELDS

This module provides factories to construct function fields. These factories are only for internal use.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); K
Rational function field in x over Rational Field
sage: L.<x> = FunctionField(QQ); L
Rational function field in x over Rational Field
sage: K is L
True
```

AUTHORS:

- William Stein (2010): initial version
- Maarten Derickx (2011-09-11): added `FunctionField_polymod_Constructor`, use `@cached_function`
- Julian Rueth (2011-09-14): replaced `@cached_function` with `UniqueFactory`

class `sage.rings.function_field.constructor.FunctionFieldExtensionFactory`

Bases: `sage.structure.factory.UniqueFactory`

Create a function field defined as an extension of another function field by adjoining a root of a univariate polynomial. The returned function field is unique in the sense that if you call this function twice with an equal polynomial and names it returns the same python object in both calls.

INPUT:

- `polynomial` – univariate polynomial over a function field
- `names` – variable names (as a tuple of length 1 or string)
- `category` – category (defaults to category of function fields)

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y>=K[]
sage: y2 = y*1
sage: y2 is y
False
sage: L.<w>=K.extension(x - y^2)
sage: M.<w>=K.extension(x - y2^2)
sage: L is M
True
```

create_key (*polynomial, names*)

Given the arguments and keywords, create a key that uniquely determines this object.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<w> = K.extension(x - y^2) # indirect doctest
```

create_object (*version, key, **extra_args*)

Create the object from the key and extra arguments. This is only called if the object was not found in the cache.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ)
sage: R.<y> = K[]
sage: L.<w> = K.extension(x - y^2) # indirect doctest
sage: y2 = y*1
sage: M.<w> = K.extension(x - y2^2) # indirect doctest
sage: L is M
True
```

class sage.rings.function_field.constructor.**FunctionFieldFactory**

Bases: `sage.structure.factory.UniqueFactory`

Return the function field in one variable with constant field F . The function field returned is unique in the sense that if you call this function twice with the same base field and name then you get the same python object back.

INPUT:

- F – field
- names – name of variable as a string or a tuple containing a string

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ); K
Rational function field in x over Rational Field
sage: L.<y> = FunctionField(GF(7)); L
Rational function field in y over Finite Field of size 7
sage: R.<z> = L[]
sage: M.<z> = L.extension(z^7-z-y); M
Function field in z defined by  $z^7 + 6z + 6y$ 
```

create_key (F , *names*)

Given the arguments and keywords, create a key that uniquely determines this object.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ) # indirect doctest
```

create_object (*version, key, **extra_args*)

Create the object from the key and extra arguments. This is only called if the object was not found in the cache.

EXAMPLES:

```
sage: K.<x> = FunctionField(QQ) # indirect doctest
sage: L.<x> = FunctionField(QQ) # indirect doctest
```

(continues on next page)

(continued from previous page)

```
sage: K is L
True
```


INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

r

- `sage.rings.function_field.constructor`, 137
- `sage.rings.function_field.differential`, 117
- `sage.rings.function_field.divisor`, 111
- `sage.rings.function_field.element`, 49
- `sage.rings.function_field.function_field`, 3
- `sage.rings.function_field.ideal`, 81
- `sage.rings.function_field.maps`, 127
- `sage.rings.function_field.order`, 61
- `sage.rings.function_field.place`, 105
- `sage.rings.function_field.valuation_ring`, 123

B

`base_field()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 22
`base_field()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 40
`base_ring()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 82
`basis()` (*sage.rings.function_field.differential.DifferentialsSpace method*), 118
`basis()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 68
`basis()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_rational method*), 72
`basis()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 63
`basis()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_rational method*), 66
`basis()` (*sage.rings.function_field.order.FunctionFieldOrder_basis method*), 78
`basis()` (*sage.rings.function_field.order.FunctionFieldOrderInfinite_basis method*), 74
`basis_differential_space()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 112
`basis_function_space()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 112
`basis_matrix()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 95

C

`cartier()` (*sage.rings.function_field.differential.FunctionFieldDifferential_global method*), 122
`change_variable_name()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 22
`change_variable_name()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 40
`characteristic()` (*sage.rings.function_field.function_field.FunctionField method*), 6
`characteristic_polynomial()` (*sage.rings.function_field.element.FunctionFieldElement method*), 50
`charpoly()` (*sage.rings.function_field.element.FunctionFieldElement method*), 50
`codifferent()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 68
`codomain()` (*sage.rings.function_field.maps.MapVectorSpaceToFunctionField method*), 134
`completion()` (*sage.rings.function_field.function_field.FunctionField method*), 7
`constant_base_field()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 23
`constant_base_field()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 40
`constant_field()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 23
`constant_field()` (*sage.rings.function_field.function_field.FunctionField_simple method*), 36
`constant_field()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 40
`coordinate_vector()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 69
`coordinate_vector()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 63
`coordinate_vector()` (*sage.rings.function_field.order.FunctionFieldOrder_basis method*), 78
`create_key()` (*sage.rings.function_field.constructor.FunctionFieldExtensionFactory method*), 137
`create_key()` (*sage.rings.function_field.constructor.FunctionFieldFactory method*), 138
`create_object()` (*sage.rings.function_field.constructor.FunctionFieldExtensionFactory method*), 138

`create_object()` (*sage.rings.function_field.constructor.FunctionFieldFactory method*), 138

D

`decomposition()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_global method*), 67
`decomposition()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 69
`decomposition()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 64
`default_precision()` (*sage.rings.function_field.maps.FunctionFieldCompletion method*), 129
`degree()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 113
`degree()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 24
`degree()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 40
`degree()` (*sage.rings.function_field.place.FunctionFieldPlace_polymod method*), 106
`degree()` (*sage.rings.function_field.place.FunctionFieldPlace_rational method*), 109
`denominator()` (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 57
`denominator()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 96
`denominator()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_rational method*), 101
`derivation()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 24
`derivation()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 41
`derivative()` (*sage.rings.function_field.element.FunctionFieldElement method*), 50
`dict()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 113
`different()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 25
`different()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 41
`different()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 70
`different()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 64
`differential()` (*sage.rings.function_field.element.FunctionFieldElement method*), 50
`differential_space()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 113
`DifferentialsSpace` (*class in sage.rings.function_field.differential*), 117
`DifferentialsSpace_global` (*class in sage.rings.function_field.differential*), 119
`DifferentialsSpaceInclusion` (*class in sage.rings.function_field.differential*), 118
`dimension()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 113
`divisor()` (*in module sage.rings.function_field.divisor*), 115
`divisor()` (*sage.rings.function_field.differential.FunctionFieldDifferential method*), 120
`divisor()` (*sage.rings.function_field.element.FunctionFieldElement method*), 51
`divisor()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 83
`divisor()` (*sage.rings.function_field.place.FunctionFieldPlace method*), 106
`divisor_group()` (*sage.rings.function_field.function_field.FunctionField method*), 8
`divisor_of_poles()` (*sage.rings.function_field.element.FunctionFieldElement method*), 51
`divisor_of_poles()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 83
`divisor_of_zeros()` (*sage.rings.function_field.element.FunctionFieldElement method*), 51
`divisor_of_zeros()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 84
`DivisorGroup` (*class in sage.rings.function_field.divisor*), 111
`domain()` (*sage.rings.function_field.maps.MapVectorSpaceToFunctionField method*), 134

E

`Element` (*sage.rings.function_field.differential.DifferentialsSpace attribute*), 118
`Element` (*sage.rings.function_field.differential.DifferentialsSpace_global attribute*), 119
`Element` (*sage.rings.function_field.divisor.DivisorGroup attribute*), 112
`Element` (*sage.rings.function_field.function_field.FunctionField_polymod attribute*), 22
`Element` (*sage.rings.function_field.function_field.RationalFunctionField attribute*), 39
`Element` (*sage.rings.function_field.place.PlaceSet attribute*), 110
`element()` (*sage.rings.function_field.element.FunctionFieldElement_polymod method*), 56

`element()` (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 57
`equation_order()` (*sage.rings.function_field.function_field.FunctionField_integral method*), 20
`equation_order()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 25
`equation_order()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 41
`equation_order_infinite()` (*sage.rings.function_field.function_field.FunctionField_integral method*), 20
`equation_order_infinite()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 41
`evaluate()` (*sage.rings.function_field.element.FunctionFieldElement method*), 52
`exact_constant_field()` (*sage.rings.function_field.function_field.FunctionField_simple method*), 36
`extension()` (*sage.rings.function_field.function_field.FunctionField method*), 9
`extension()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 42

F

`factor()` (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 57
`factor()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 84
`field()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 42
`fraction_field()` (*sage.rings.function_field.order.FunctionFieldOrder_base method*), 77
`FractionFieldToFunctionField` (*class in sage.rings.function_field.maps*), 127
`free_module()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 26
`free_module()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 42
`free_module()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 70
`free_module()` (*sage.rings.function_field.order.FunctionFieldOrder_basis method*), 79
`free_module()` (*sage.rings.function_field.order.FunctionFieldOrderInfinite_basis method*), 75
`function_field()` (*sage.rings.function_field.differential.DifferentialsSpace method*), 118
`function_field()` (*sage.rings.function_field.divisor.DivisorGroup method*), 112
`function_field()` (*sage.rings.function_field.order.FunctionFieldOrder_base method*), 77
`function_field()` (*sage.rings.function_field.place.FunctionFieldPlace method*), 106
`function_space()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 114
`FunctionField` (*class in sage.rings.function_field.function_field*), 6
`FunctionField_char_zero` (*class in sage.rings.function_field.function_field*), 16
`FunctionField_char_zero_integral` (*class in sage.rings.function_field.function_field*), 16
`FunctionField_global` (*class in sage.rings.function_field.function_field*), 16
`FunctionField_global_integral` (*class in sage.rings.function_field.function_field*), 20
`FunctionField_integral` (*class in sage.rings.function_field.function_field*), 20
`FunctionField_polymod` (*class in sage.rings.function_field.function_field*), 21
`FunctionField_simple` (*class in sage.rings.function_field.function_field*), 36
`FunctionFieldCompletion` (*class in sage.rings.function_field.maps*), 128
`FunctionFieldConversionToConstantBaseField` (*class in sage.rings.function_field.maps*), 129
`FunctionFieldDerivation` (*class in sage.rings.function_field.maps*), 129
`FunctionFieldDerivation_inseparable` (*class in sage.rings.function_field.maps*), 130
`FunctionFieldDerivation_rational` (*class in sage.rings.function_field.maps*), 130
`FunctionFieldDerivation_separable` (*class in sage.rings.function_field.maps*), 130
`FunctionFieldDifferential` (*class in sage.rings.function_field.differential*), 119
`FunctionFieldDifferential_global` (*class in sage.rings.function_field.differential*), 122
`FunctionFieldDivisor` (*class in sage.rings.function_field.divisor*), 112
`FunctionFieldElement` (*class in sage.rings.function_field.element*), 49
`FunctionFieldElement_polymod` (*class in sage.rings.function_field.element*), 56
`FunctionFieldElement_rational` (*class in sage.rings.function_field.element*), 57
`FunctionFieldExtensionFactory` (*class in sage.rings.function_field.constructor*), 137
`FunctionFieldFactory` (*class in sage.rings.function_field.constructor*), 138
`FunctionFieldHigherDerivation` (*class in sage.rings.function_field.maps*), 131

`FunctionFieldHigherDerivation_char_zero` (class in `sage.rings.function_field.maps`), 131
`FunctionFieldHigherDerivation_global` (class in `sage.rings.function_field.maps`), 131
`FunctionFieldIdeal` (class in `sage.rings.function_field.ideal`), 82
`FunctionFieldIdeal_global` (class in `sage.rings.function_field.ideal`), 92
`FunctionFieldIdeal_module` (class in `sage.rings.function_field.ideal`), 93
`FunctionFieldIdeal_polymod` (class in `sage.rings.function_field.ideal`), 95
`FunctionFieldIdeal_rational` (class in `sage.rings.function_field.ideal`), 101
`FunctionFieldIdealInfinite` (class in `sage.rings.function_field.ideal`), 87
`FunctionFieldIdealInfinite_module` (class in `sage.rings.function_field.ideal`), 87
`FunctionFieldIdealInfinite_polymod` (class in `sage.rings.function_field.ideal`), 88
`FunctionFieldIdealInfinite_rational` (class in `sage.rings.function_field.ideal`), 90
`FunctionFieldLinearMap` (class in `sage.rings.function_field.maps`), 132
`FunctionFieldLinearMapSection` (class in `sage.rings.function_field.maps`), 132
`FunctionFieldMaximalOrder` (class in `sage.rings.function_field.order`), 62
`FunctionFieldMaximalOrder_global` (class in `sage.rings.function_field.order`), 67
`FunctionFieldMaximalOrder_polymod` (class in `sage.rings.function_field.order`), 68
`FunctionFieldMaximalOrder_rational` (class in `sage.rings.function_field.order`), 72
`FunctionFieldMaximalOrderInfinite` (class in `sage.rings.function_field.order`), 62
`FunctionFieldMaximalOrderInfinite_polymod` (class in `sage.rings.function_field.order`), 63
`FunctionFieldMaximalOrderInfinite_rational` (class in `sage.rings.function_field.order`), 66
`FunctionFieldMorphism` (class in `sage.rings.function_field.maps`), 132
`FunctionFieldMorphism_polymod` (class in `sage.rings.function_field.maps`), 132
`FunctionFieldMorphism_rational` (class in `sage.rings.function_field.maps`), 132
`FunctionFieldOrder` (class in `sage.rings.function_field.order`), 73
`FunctionFieldOrder_base` (class in `sage.rings.function_field.order`), 76
`FunctionFieldOrder_basis` (class in `sage.rings.function_field.order`), 77
`FunctionFieldOrderInfinite` (class in `sage.rings.function_field.order`), 74
`FunctionFieldOrderInfinite_basis` (class in `sage.rings.function_field.order`), 74
`FunctionFieldPlace` (class in `sage.rings.function_field.place`), 105
`FunctionFieldPlace_polymod` (class in `sage.rings.function_field.place`), 106
`FunctionFieldPlace_rational` (class in `sage.rings.function_field.place`), 109
`FunctionFieldRingMorphism` (class in `sage.rings.function_field.maps`), 132
`FunctionFieldToFractionField` (class in `sage.rings.function_field.maps`), 133
`FunctionFieldValuationRing` (class in `sage.rings.function_field.valuation_ring`), 124
`FunctionFieldVectorSpaceIsomorphism` (class in `sage.rings.function_field.maps`), 133

G

`gaps()` (`sage.rings.function_field.function_field.FunctionField_global` method), 17
`gaps()` (`sage.rings.function_field.place.FunctionFieldPlace_polymod` method), 107
`gen()` (`sage.rings.function_field.function_field.FunctionField_polymod` method), 27
`gen()` (`sage.rings.function_field.function_field.RationalFunctionField` method), 43
`gen()` (`sage.rings.function_field.ideal.FunctionFieldIdeal_module` method), 94
`gen()` (`sage.rings.function_field.ideal.FunctionFieldIdeal_rational` method), 102
`gen()` (`sage.rings.function_field.ideal.FunctionFieldIdealInfinite_rational` method), 91
`gen()` (`sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod` method), 70
`gen()` (`sage.rings.function_field.order.FunctionFieldMaximalOrder_rational` method), 72
`gen()` (`sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod` method), 64
`gen()` (`sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_rational` method), 66
`gens()` (`sage.rings.function_field.ideal.FunctionFieldIdeal_global` method), 92
`gens()` (`sage.rings.function_field.ideal.FunctionFieldIdeal_module` method), 94

`gens()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 96
`gens()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_rational method*), 102
`gens()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod method*), 88
`gens()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_rational method*), 91
`gens_over_base()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 96
`gens_over_base()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_rational method*), 102
`gens_over_base()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod method*), 88
`gens_over_base()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_rational method*), 91
`gens_reduced()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 85
`gens_two()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_global method*), 92
`gens_two()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod method*), 88
`genus()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 27
`genus()` (*sage.rings.function_field.function_field.FunctionField_simple method*), 37
`genus()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 43
`get_place()` (*sage.rings.function_field.function_field.FunctionField_global method*), 17
`get_place()` (*sage.rings.function_field.function_field.RationalFunctionField_global method*), 46

H

`higher_derivation()` (*sage.rings.function_field.function_field.FunctionField_char_zero method*), 16
`higher_derivation()` (*sage.rings.function_field.function_field.FunctionField_global method*), 18
`higher_derivation()` (*sage.rings.function_field.function_field.RationalFunctionField_char_zero method*), 45
`higher_derivation()` (*sage.rings.function_field.function_field.RationalFunctionField_global method*), 46
`higher_derivative()` (*sage.rings.function_field.element.FunctionFieldElement method*), 52
`hnf()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 97
`hom()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 28
`hom()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 43

I

`ideal()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 70
`ideal()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_rational method*), 73
`ideal()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 65
`ideal()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_rational method*), 66
`ideal()` (*sage.rings.function_field.order.FunctionFieldOrder_basis method*), 79
`ideal()` (*sage.rings.function_field.order.FunctionFieldOrderInfinite_basis method*), 75
`ideal_below()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 97
`ideal_below()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod method*), 89
`ideal_monoid()` (*sage.rings.function_field.order.FunctionFieldOrder_base method*), 77
`ideal_with_gens_over_base()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 71
`ideal_with_gens_over_base()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_rational method*), 73
`ideal_with_gens_over_base()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 65
`ideal_with_gens_over_base()` (*sage.rings.function_field.order.FunctionFieldOrder_basis method*), 79
`ideal_with_gens_over_base()` (*sage.rings.function_field.order.FunctionFieldOrderInfinite_basis method*), 75
`IdealMonoid` (*class in sage.rings.function_field.ideal*), 103
`intersect()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 98
`intersection()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_module method*), 94
`inverse_mod()` (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 58

`is_field()` (*sage.rings.function_field.order.FunctionFieldOrder_base* method), 77
`is_finite()` (*sage.rings.function_field.function_field.FunctionField* method), 9
`is_FunctionField()` (in module *sage.rings.function_field.function_field*), 47
`is_FunctionFieldElement()` (in module *sage.rings.function_field.element*), 59
`is_global()` (*sage.rings.function_field.function_field.FunctionField* method), 9
`is_infinite_place()` (*sage.rings.function_field.place.FunctionFieldPlace_polymod* method), 107
`is_infinite_place()` (*sage.rings.function_field.place.FunctionFieldPlace_rational* method), 109
`is_injective()` (*sage.rings.function_field.differential.DifferentialsSpaceInclusion* method), 119
`is_injective()` (*sage.rings.function_field.maps.FunctionFieldDerivation* method), 129
`is_injective()` (*sage.rings.function_field.maps.FunctionFieldVectorSpaceIsomorphism* method), 133
`is_integral()` (*sage.rings.function_field.element.FunctionFieldElement* method), 52
`is_integral()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod* method), 98
`is_noetherian()` (*sage.rings.function_field.order.FunctionFieldOrder_base* method), 77
`is_perfect()` (*sage.rings.function_field.function_field.FunctionField* method), 10
`is_prime()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod* method), 99
`is_prime()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_rational* method), 102
`is_prime()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod* method), 89
`is_prime()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_rational* method), 91
`is_separable()` (*sage.rings.function_field.function_field.FunctionField_polymod* method), 29
`is_square()` (*sage.rings.function_field.element.FunctionFieldElement_rational* method), 58
`is_subring()` (*sage.rings.function_field.order.FunctionFieldOrder_base* method), 77
`is_surjective()` (*sage.rings.function_field.differential.DifferentialsSpaceInclusion* method), 119
`is_surjective()` (*sage.rings.function_field.maps.FunctionFieldVectorSpaceIsomorphism* method), 133

L

`L_polynomial()` (*sage.rings.function_field.function_field.FunctionField_global* method), 17
`list()` (*sage.rings.function_field.divisor.FunctionFieldDivisor* method), 114
`list()` (*sage.rings.function_field.element.FunctionFieldElement_polymod* method), 56
`list()` (*sage.rings.function_field.element.FunctionFieldElement_rational* method), 58
`local_uniformizer()` (*sage.rings.function_field.place.FunctionFieldPlace_polymod* method), 107
`local_uniformizer()` (*sage.rings.function_field.place.FunctionFieldPlace_rational* method), 109

M

`make_FunctionFieldElement()` (in module *sage.rings.function_field.element*), 59
`MapFunctionFieldToVectorSpace` (class in *sage.rings.function_field.maps*), 134
`MapVectorSpaceToFunctionField` (class in *sage.rings.function_field.maps*), 134
`matrix()` (*sage.rings.function_field.element.FunctionFieldElement* method), 53
`maximal_order()` (*sage.rings.function_field.function_field.FunctionField_global* method), 18
`maximal_order()` (*sage.rings.function_field.function_field.FunctionField_polymod* method), 30
`maximal_order()` (*sage.rings.function_field.function_field.RationalFunctionField* method), 44
`maximal_order_infinite()` (*sage.rings.function_field.function_field.FunctionField_polymod* method), 30
`maximal_order_infinite()` (*sage.rings.function_field.function_field.RationalFunctionField* method), 44
`minimal_polynomial()` (*sage.rings.function_field.element.FunctionFieldElement* method), 54
`minpoly()` (*sage.rings.function_field.element.FunctionFieldElement* method), 54
module
 sage.rings.function_field.constructor, 137
 sage.rings.function_field.differential, 117
 sage.rings.function_field.divisor, 111
 sage.rings.function_field.element, 49
 sage.rings.function_field.function_field, 3

`sage.rings.function_field.ideal`, 81
`sage.rings.function_field.maps`, 127
`sage.rings.function_field.order`, 61
`sage.rings.function_field.place`, 105
`sage.rings.function_field.valuation_ring`, 123
`module()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_module method*), 94
`module()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 99
`module()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_rational method*), 102
`module()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_module method*), 87
`monic_integral_model()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 30
`monomial_coefficients()` (*sage.rings.function_field.differential.FunctionFieldDifferential method*), 120
`multiplicity()` (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 114

N

`ngens()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 31
`ngens()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 44
`ngens()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_module method*), 95
`ngens()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 72
`ngens()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_rational method*), 73
`ngens()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_polymod method*), 65
`ngens()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_rational method*), 67
`norm()` (*sage.rings.function_field.element.FunctionFieldElement method*), 54
`norm()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 99
`number_of_rational_places()` (*sage.rings.function_field.function_field.FunctionField_global method*), 18
`numerator()` (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 58

O

`order()` (*sage.rings.function_field.function_field.FunctionField method*), 10
`order_infinite()` (*sage.rings.function_field.function_field.FunctionField method*), 10
`order_infinite_with_basis()` (*sage.rings.function_field.function_field.FunctionField method*), 11
`order_with_basis()` (*sage.rings.function_field.function_field.FunctionField method*), 11

P

`p_radical()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_global method*), 68
`place()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 85
`place()` (*sage.rings.function_field.valuation_ring.FunctionFieldValuationRing method*), 124
`place_below()` (*sage.rings.function_field.place.FunctionFieldPlace_polymod method*), 107
`place_infinite()` (*sage.rings.function_field.function_field.RationalFunctionField_global method*), 46
`place_set()` (*sage.rings.function_field.function_field.FunctionField method*), 12
`places()` (*sage.rings.function_field.function_field.FunctionField_global method*), 18
`places()` (*sage.rings.function_field.function_field.RationalFunctionField_global method*), 46
`places_above()` (*sage.rings.function_field.function_field.FunctionField_simple method*), 37
`places_finite()` (*sage.rings.function_field.function_field.FunctionField_global method*), 19
`places_finite()` (*sage.rings.function_field.function_field.RationalFunctionField_global method*), 47
`places_infinite()` (*sage.rings.function_field.function_field.FunctionField_global method*), 19
`PlaceSet` (class in *sage.rings.function_field.place*), 110
`poles()` (*sage.rings.function_field.element.FunctionFieldElement method*), 55
`polynomial()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 32
`polynomial()` (*sage.rings.function_field.order.FunctionFieldMaximalOrder_polymod method*), 72
`polynomial()` (*sage.rings.function_field.order.FunctionFieldOrder_basis method*), 80

`polynomial()` (*sage.rings.function_field.order.FunctionFieldOrderInfinite_basis method*), 76
`polynomial_ring()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 32
`polynomial_ring()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 44
`prime_below()` (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 100
`prime_below()` (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod method*), 89
`prime_divisor()` (*in module sage.rings.function_field.divisor*), 115
`prime_ideal()` (*sage.rings.function_field.order.FunctionFieldMaximalOrderInfinite_rational method*), 67
`prime_ideal()` (*sage.rings.function_field.place.FunctionFieldPlace method*), 106
`primitive_element()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 32
`primitive_integral_element_infinite()` (*sage.rings.function_field.function_field.FunctionField_integral method*), 21

R

`random_element()` (*sage.rings.function_field.function_field.FunctionField_polymod method*), 33
`random_element()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 45
`rational_function_field()` (*sage.rings.function_field.function_field.FunctionField method*), 13
`RationalFunctionField` (*class in sage.rings.function_field.function_field*), 38
`RationalFunctionField_char_zero` (*class in sage.rings.function_field.function_field*), 45
`RationalFunctionField_global` (*class in sage.rings.function_field.function_field*), 46
`RationalFunctionFieldHigherDerivation_global` (*class in sage.rings.function_field.maps*), 135
`relative_degree()` (*sage.rings.function_field.place.FunctionFieldPlace_polymod method*), 108
`residue()` (*sage.rings.function_field.differential.FunctionFieldDifferential method*), 121
`residue_field()` (*sage.rings.function_field.function_field.FunctionField_simple method*), 37
`residue_field()` (*sage.rings.function_field.function_field.RationalFunctionField method*), 45
`residue_field()` (*sage.rings.function_field.place.FunctionFieldPlace_polymod method*), 108
`residue_field()` (*sage.rings.function_field.place.FunctionFieldPlace_rational method*), 109
`residue_field()` (*sage.rings.function_field.valuation_ring.FunctionFieldValuationRing method*), 124
`ring()` (*sage.rings.function_field.ideal.FunctionFieldIdeal method*), 86
`ring()` (*sage.rings.function_field.ideal.IdealMonoid method*), 103

S

`sage.rings.function_field.constructor`
 module, 137
`sage.rings.function_field.differential`
 module, 117
`sage.rings.function_field.divisor`
 module, 111
`sage.rings.function_field.element`
 module, 49
`sage.rings.function_field.function_field`
 module, 3
`sage.rings.function_field.ideal`
 module, 81
`sage.rings.function_field.maps`
 module, 127
`sage.rings.function_field.order`
 module, 61
`sage.rings.function_field.place`
 module, 105
`sage.rings.function_field.valuation_ring`

module, 123

section() (*sage.rings.function_field.maps.FractionFieldToFunctionField method*), 128

section() (*sage.rings.function_field.maps.FunctionFieldToFractionField method*), 133

separable_model() (*sage.rings.function_field.function_field.FunctionField_polymod method*), 33

simple_model() (*sage.rings.function_field.function_field.FunctionField_polymod method*), 34

some_elements() (*sage.rings.function_field.function_field.FunctionField method*), 13

space_of_differentials() (*sage.rings.function_field.function_field.FunctionField method*), 13

sqrt() (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 59

support() (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 115

T

trace() (*sage.rings.function_field.element.FunctionFieldElement method*), 55

V

valuation() (*sage.rings.function_field.differential.FunctionFieldDifferential method*), 121

valuation() (*sage.rings.function_field.divisor.FunctionFieldDivisor method*), 115

valuation() (*sage.rings.function_field.element.FunctionFieldElement method*), 55

valuation() (*sage.rings.function_field.element.FunctionFieldElement_rational method*), 59

valuation() (*sage.rings.function_field.function_field.FunctionField method*), 14

valuation() (*sage.rings.function_field.ideal.FunctionFieldIdeal_polymod method*), 101

valuation() (*sage.rings.function_field.ideal.FunctionFieldIdeal_rational method*), 103

valuation() (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_polymod method*), 90

valuation() (*sage.rings.function_field.ideal.FunctionFieldIdealInfinite_rational method*), 91

valuation_ring() (*sage.rings.function_field.place.FunctionFieldPlace_polymod method*), 109

valuation_ring() (*sage.rings.function_field.place.FunctionFieldPlace_rational method*), 110

W

weierstrass_places() (*sage.rings.function_field.function_field.FunctionField_global method*), 19

Z

zeros() (*sage.rings.function_field.element.FunctionFieldElement method*), 56