Sage Reference Manual: The Sage Command Line

Release 8.5

The Sage Development Team

CONTENTS

1	Runnir	
		nvoking Sage
		Sage startup scripts
	1.3 E	Environment variables used by Sage
		Relevant environment variables for other packages
	1.5 I	nteractively tracing execution of a command
2	Prepar	
	2.1 T	The Sage Preparser
3	Loadin	ng and attaching files 25
	3.1 L	Load Python, Sage, Cython, Fortran and Magma files in Sage
	3.2 k	Keep track of attached files
4	Pretty	Printing 35
		Python Displayhook Formatters
		The Sage pretty printer
		Representations of objects
		Utility functions for pretty-printing
5 Di	Display	y Backend Infrastructure 45
		Display Manager
		Display Preferences
	5.3	Output Buffer
	5.4 E	Basic Output Types
		Graphics Output Types
		Three-Dimensional Graphics Output Types
		Video Output Types
		Catalog of all available output container types
		Base Class for Backends
		Test Backend
		The backend used for doctests
		Python Backend for the Sage Rich Output System
	5.13 S	SageNB Backend for the Sage Rich Output System
	Miscell	
		Extra Readline Commands
		Sage's IPython Modifications
		Sage's IPython Extension
		Magics for each of the Sage interfaces
	6.5 I	nteracts for the Sage Jupyter notebook

n	dex		141			
у	Python Module Index					
7	Indices and Tables					
	6.13	The Sage Input Hook	134			
	6.12	Sage Wrapper for Bitmap Images	131			
	6.11	HTML Generator for JSmol	129			
	6.10	Tests for the IPython integration	127			
	6.9	The Sage ZMQ Kernel	126			
	6.8	Installing the SageMath Jupyter Kernel and Extensions	123			
	6.7	Functions to construct widgets, based on the old SageNB interface	118			
	6.6	Widgets to be used for the Sage Jupyter notebook	113			

The Sage Read-Eval-Print-Loop (REPL) is based on IPython. In this document, you'll find how the IPython integration works. You should also be familiar with the documentation for IPython.

For more details about using the Sage command line, see the Sage tutorial.

CONTENTS 1

2 CONTENTS

CHAPTER

ONE

RUNNING SAGE

1.1 Invoking Sage

To run Sage, you basically just need to type sage from the command-line prompt to start the Sage interpreter. See the Sage Installation Guide for information about making sure your \$PATH is set correctly, etc.

1.1.1 Command-line options for Sage

Running Sage, the most common options

- file.[sage|py|spyx] run the given .sage, .py or .spyx files (as in sage my_file.sage)
- -h, -?, --help print a short help message
- -v, --version print the Sage version
- --advanced print (essentially this) list of Sage options
- -c cmd-evaluate cmd as sage code. For example, sage -c 'print (factor (35)) ' will print "5 * 7".

Running Sage, other options

- --preparse file.sage preparse file.sage, a file of Sage code, and produce the corresponding Python file file.sage.py. See the Sage tutorial for more about preparsing and the differences between Sage and Python.
- -q quiet; start with no banner
- --grep [options] <string> grep through all the Sage library code for string. Any options will get passed to the "grep" command; for example, sage --grep -i epstein will search for epstein, and the -i flag tells grep to ignore case when searching. Note that while running Sage, you can also use the function search_src to accomplish the same thing.
- --grepdoc [options] <string> grep through all the Sage documentation for string. Note that while running Sage, you can also use the function search_doc to accomplish the same thing.
- --min [...] do not populate global namespace (must be first option)
- -gthread, -qthread, -q4thread, -wthread, -pylab pass the option through to IPython
- --nodotsage run Sage without using the user's .sage directory: create and use a temporary .sage directory instead. Warning: notebooks are stored in the .sage directory, so any notebooks created while running with --nodotsage will be temporary also.

Running the notebook

- -n [...], --notebook=[...] start the notebook, valid options are default, sagenb, jupyter and export (see the output of sage --notebook --help for more details and examples of how to pass optional arguments)
- -bn [...], --build-and-notebook [...] build the Sage library (as by running sage -b) then start the Sage notebook
- --inotebook [...] start the insecure Sage notebook

Running external programs and utilities

- --cython [...] run Cython with the given arguments
- --ecl [...], --lisp [...] run Sage's copy of ECL (Embeddable Common Lisp) with the given arguments
- --gap [...] run Sage's Gap with the given arguments
- --git [...] run Sage's Git with the given arguments
- --gp [...] run Sage's PARI/GP calculator with the given arguments
- --ipython [...] -run Sage's IPython using the default environment (not Sage), passing additional options to IPython
- -- kash [...] run Sage's Kash with the given arguments
- --M2 [...] run Sage's Macaulay2 with the given arguments
- --maxima [...] run Sage's Maxima with the given arguments
- --mwrank [...] run Sage's mwrank with the given arguments
- --python [...], --python2 [...] run the Python 2 interpreter
- --python3 [...] run the Python 3 interpreter
- $\neg R$ [...] run Sage's R with the given arguments
- --scons [...] -run Sage's scons
- --singular [...] run Sage's singular with the given arguments
- --twistd [...] run Twisted server
- --sh [...] run a shell with Sage environment variables set
- -- gdb run Sage under the control of gdb
- --qdb-ipython run Sage's IPython under the control of gdb
- --cleaner run the Sage cleaner. This cleans up after Sage, removing temporary directories and spawned processes. (This gets run by Sage automatically, so it is usually not necessary to run it separately.)

Installing packages and upgrading

- -i [options] [packages] install the given Sage packages (unless they are already installed); if no packages are given, print a list of all installed packages. Options:
 - -c run the packages' test suites, overriding the settings of SAGE_CHECK and SAGE_CHECK_PACKAGES.

- −f − force build: install the packages even if they are already installed.
- -s do not delete the spkg/build directories after a successful build useful for debugging.
- -f [options] [packages] shortcut for -i -f: force build of the given Sage packages.
- --info [packages] display the SPKG.txt file of the given Sage packages.
- --standard list all standard packages that can be installed
- --optional list all optional packages that can be installed
- --experimental list all experimental packages that can be installed
- --upgrade [url] download, build and install standard packages from given url. If url not given, automatically selects a suitable mirror. If url='ask', it lets you select the mirror.

Building and testing the Sage library

- --root print the Sage root directory
- -b build Sage library do this if you have modified any source code files in \$SAGE_ROOT/src/sage/.
- -ba same as -b, but rebuild *all* Cython code. This could take a while, so you will be asked if you want to proceed.
- -ba-force same as -ba, but don't query before rebuilding
- --br build and run Sage
- -t [options] <files|dir> test examples in .py, .pyx, .sage or .tex files. Options:
 - --long include lines with the phrase 'long time'
 - --verbose print debugging output during the test
 - --optional also test all examples labeled # optional
 - --only-optional[=tags] if no tags are specified, only run blocks of tests containing a line labeled # optional. If a comma separated list of tags is specified, only run blocks containing a line labeled # optional tag for any of the tags given and in these blocks only run the lines which are unlabeled or labeled #optional or labeled #optional tag for any of the tags given.
 - --randorder[=seed] randomize order of tests
 - --short [=seconds] run as many doctests as possible in about 300 seconds (or the number of seconds given.) This runs the tests for each module from the top of the file and skips tests once it exceeds the budget allocated for that file.
- -tnew [...] like -t above, but only tests files modified since last commit
- -tp <N> [...] like -t above, but tests in parallel using N threads with 0 interpreted as minimum(8, cpu_count())
- --testall [options] test all source files, docs, and examples; options are the same as for -t.
- -bt [...] build and test, options like -t above
- -btp <N> [...] build and test in parallel, options like -tp above
- -btnew [...] build and test modified files, options like -tnew
- --fixdoctests file.py [output_file] [--long] writes a new version of file.py to output_file (default: file.py.out) that will pass the doctests. With the optional --long argument the long time tests are also checked. A patch for the new file is printed to stdout.

1.1. Invoking Sage 5

- --startuptime [module] display how long each component of Sage takes to start up. Optionally specify a module (e.g., "sage.rings.qqbar") to get more details about that particular module.
- --coverage <files> give information about doctest coverage of files
- --coverageall give summary info about doctest coverage of all files in the Sage library

Documentation

- --docbuild [options] document (format | command) build or return information about the Sage documentation.
 - document name of the document to build
 - format document output format
 - command document-specific command

A document and either a format or a command are required, unless a list of one or more of these is requested.

Options:

- help, -h, --help print a help message
- -H, --help-all print an extended help message, including the output from the options -h, -D, -F, -C all, and a short list of examples.
- -D, --documents list all available documents
- ¬F, ¬¬formats − list all output formats
- -C DOC, --commands=DOC list all commands for document DOC; use -C all to list all
- -i, --inherited include inherited members in reference manual; may be slow, may fail for PDF output
- -u, --underscore include variables prefixed with _ in reference manual; may be slow, may fail for PDF output
- -j, --jsmath render math using jsMath; formats: html, json, pickle, web
- --no-pdf-links-do not include PDF links in document website; formats: html, json, pickle, web
- --check-nested-check picklability of nested classes in document reference
- N, --no-colors do not color output; does not affect children
- -q, --quiet work quietly; same as --verbose=0
- -v LEVEL, --verbose=LEVEL report progress at level 0 (quiet), 1 (normal), 2 (info), or 3 (debug);
 does not affect children

Advanced – use these options with care:

- -S OPTS, --sphinx-opts=OPTS pass comma-separated OPTS to sphinx-build
- U, --update-mtimes before building reference manual, update modification times for autogenerated ReST files

Making Sage packages or distributions

- --pkg dir create the Sage package dir.spkg from the directory dir
- --pkq_nc dir as --pkq, but do not compress the package
- --merge run Sage's automatic merge and test script
- --sdist build a source distribution of Sage

Valgrind memory debugging

- --cachegrind run Sage using Valgrind's cachegrind tool
- --callgrind run Sage using Valgrind's callgrind tool
- --massif run Sage using Valgrind's massif tool
- --memcheck run Sage using Valgrind's memcheck tool
- -- omega run Sage using Valgrind's omega tool
- --valgrind this is an alias for --memcheck

1.2 Sage startup scripts

There are two kinds of startup scripts that Sage reads when starting:

1.2.1 The sagerc shell script

The bash shell script <code>\$DOT_SAGE/sagerc</code> (with the default value of <code>DOT_SAGE</code>, this is ~/.sage/sagerc) is read by <code>\$SAGE_ROOT/spkg/bin/sage-env</code> after Sage has set its environment variables. It can be used to override some of the environment variables determined by Sage, or it can contain other shell commands like creating directories. This script is sourced not only when running Sage itself, but also when running any of the subcommands (like <code>sage --python</code>, <code>sage -b</code> or <code>sage -i <package></code>). In particular, setting <code>PS1</code> here overrides the default prompt for the Sage shell <code>sage --sh</code>.

Note: This script is run with the Sage directories in its PATH, so executing git for example will run the Git inside Sage.

The default location of this file can be changed using the environment variable SAGE RC FILE.

1.2.2 The init.sage script

The Sage script \$DOT_SAGE/init.sage (with the default value of DOT_SAGE, this is ~/.sage/init.sage) contains Sage commands to be executed every time Sage starts. If you want symbolic variables y and z in every Sage session, you could put

```
var('y, z')
```

in this file.

The default location of this file can be changed using the environment variable SAGE STARTUP FILE.

1.3 Environment variables used by Sage

Sage uses several environment variables when running. These all have sensible default values, so many users won't need to set any of these. (There are also variables used to compile Sage; see the Sage Installation Guide for more about those.)

- DOT_SAGE this is the directory, to which the user has read and write access, where Sage stores a number of files. The default location is ~/.sage/, but you can change that by setting this variable.
- SAGE_RC_FILE a shell script which is sourced after Sage has determined its environment variables. This script is executed before starting Sage or any of its subcommands (like sage -i <package>). The default value is \$DOT_SAGE/sagerc.
- SAGE_STARTUP_FILE a file including commands to be executed every time Sage starts. The default value is \$DOT_SAGE/init.sage.
- SAGE_SERVER only used for installing packages. Alternative mirror from which to download sources, see
 the Installation Guide for details.
- SAGE_PATH a colon-separated list of directories which Sage searches when trying to locate Python libraries.
- BROWSER on most platforms, Sage will detect the command to run a web browser, but if this doesn't seem to work on your machine, set this variable to the appropriate command.

1.4 Relevant environment variables for other packages

This is a non-exhaustive list of environment variables which influence some package contained within the SageMath distribution.

In many cases, SageMath uses a custom default value if the variable is not set, which is not the same default that the system-wide package would use. So, if you would like to use your system-wide configuration, you need to explicitly set the environment variable to the system-wide default.

- IPYTHONDIR directory where the configuration of IPython is stored. By default, this is some directory inside DOT_SAGE. See http://ipython.readthedocs.io/en/stable/development/config.html for more information.
- JUPYTER_CONFIG_DIR directory where the configuration of Jupyter is stored. By default, this is some directory inside DOT_SAGE. See http://jupyter.readthedocs.io/en/latest/projects/jupyter-directories.html for more information.
- MPLCONFIGDIR directory where the configuration of Matplotlib is stored. See https://matplotlib.org/faq/environment_variables_faq.html#envvar-MPLCONFIGDIR By default, this is some directory inside DOT SAGE.

1.5 Interactively tracing execution of a command

sage.misc.trace.trace(code, preparse=True)

Evaluate Sage code using the interactive tracer and return the result. The string code must be a valid expression enclosed in quotes (no assignments - the result of the expression is returned). In the Sage notebook this just raises a NotImplementedException.

INPUT:

- code str
- preparse bool (default: True); if True, run expression through the Sage preparser.

REMARKS: This function is extremely powerful! For example, if you want to step through each line of execution of, e.g., factor (100), type

```
sage: trace("factor(100)") # not tested
```

then at the (Pdb) prompt type s (or step), then press return over and over to step through every line of Python that is called in the course of the above computation. Type? at any time for help on how to use the debugger (e.g., 1 lists 11 lines around the current line; bt gives a back trace, etc.).

Setting a break point: If you have some code in a file and would like to drop into the debugger at a given point, put the following code at that point in the file:

```
import pdb; pdb.set_trace()
```

For an article on how to use the Python debugger, see http://www.onlamp.com/pub/a/python/2005/09/01/debugger.html

TWO

PREPARSING

Sage commands are "preparsed" to valid Python syntax. This allows for example to support the R.<x> = QQ[] syntax.

2.1 The Sage Preparser

AUTHORS:

- William Stein (2006-02-19)
 - Fixed bug when loading .py files.
- William Stein (2006-03-09)
 - Fixed crash in parsing exponentials.
 - Precision of real literals now determined by digits of input (like Mathematica).
- Joe Wetherell (2006-04-14)
 - Added MAGMA-style constructor preparsing.
- Bobby Moretti (2007-01-25)
 - Added preliminary function assignment notation.
- Robert Bradshaw (2007-09-19)
 - Added strip_string_literals, containing_block utility functions. Arrr!
 - Added [1,2,..,n] notation.
- Robert Bradshaw (2008-01-04)
 - Implicit multiplication (off by default).
- Robert Bradshaw (2008-09-23)
 - Factor out constants.
- Robert Bradshaw (2000-01)
 - Simplify preparser by making it modular and using regular expressions.
 - Bug fixes, complex numbers, and binary input.

EXAMPLES:

Preparsing:

```
sage: preparse('2/3')
'Integer(2)/Integer(3)'
sage: preparse('2.5')
"RealNumber('2.5')"
sage: preparse('2^3')
'Integer(2)**Integer(3)'
sage: preparse('a^b')
                                 # exponent
sage: preparse('a**b')
'a**b'
sage: preparse('G.0')
                                  # generator
'G.gen(0)'
sage: preparse('a = 939393R')
                                  # raw
'a = 939393'
sage: implicit_multiplication(True)
sage: preparse('a b c in L')
                                 # implicit multiplication
'a*b*c in L'
sage: preparse('2e3x + 3exp(y)')
"RealNumber('2e3')*x + Integer(3)*exp(y)"
```

A string with escaped quotes in it (the point here is that the preparser doesn't get confused by the internal quotes):

```
sage: ""Yes," he said."
'"Yes," he said.'
sage: s = "\"; s
'\'
```

A hex literal:

```
sage: preparse('0x2e3')
'Integer(0x2e3)'
sage: 0xA
10
sage: 0xe
```

Raw and hex work correctly:

```
sage: type(0xa1)
<type 'sage.rings.integer.Integer'>
sage: type(0xa1r)
<type 'int'>
sage: type(0Xa1R)
<type 'int'>
```

In Sage, methods can also be called on integer and real literals (note that in pure Python this would be a syntax error):

```
sage: 16.sqrt()
4
sage: 87.factor()
3 * 29
sage: 15.10.sqrt()
3.88587184554509
sage: preparse('87.sqrt()')
'Integer(87).sqrt()'
sage: preparse('15.10.sqrt()')
"RealNumber('15.10').sqrt()"
```

Note that calling methods on int literals in pure Python is a syntax error, but Sage allows this for Sage integers and reals, because users frequently request it:

```
sage: eval('4.__add__(3)')
Traceback (most recent call last):
...
SyntaxError: invalid syntax
```

Symbolic functional notation:

```
sage: a=10; f(theta, beta) = theta + beta; b = x^2 + theta
sage: f
(theta, beta) |--> beta + theta
sage: a
10
sage: b
x^2 + theta
sage: f(theta, theta)
2*theta

sage: a = 5; f(x,y) = x*y*sqrt(a)
sage: f
(x, y) |--> sqrt(5)*x*y
```

This involves an =-, but should still be turned into a symbolic expression:

```
sage: preparse('a(x) =- 5')
'__tmp__evar("x"); a = symbolic_expression(- Integer(5)).function(x)'
sage: f(x)=-x
sage: f(10)
-10
```

This involves -=, which should not be turned into a symbolic expression (of course a(x) isn't an identifier, so this will never be valid):

```
sage: preparse('a(x) -= 5')
'a(x) -= Integer(5)'
```

Raw literals:

Raw literals are not preparsed, which can be useful from an efficiency point of view. Just like Python ints are denoted by an L, in Sage raw integer and floating literals are followed by an"r" (or "R") for raw, meaning not preparsed.

We create a raw integer:

```
sage: a = 393939r
sage: a
393939
sage: type(a)
<type 'int'>
```

We create a raw float:

```
sage: z = 1.5949r
sage: z
1.5949
sage: type(z)
<type 'float'>
```

You can also use an upper case letter:

```
sage: z = 3.1415R
sage: z
3.1415
sage: type(z)
<type 'float'>
```

This next example illustrates how raw literals can be very useful in certain cases. We make a list of even integers up to 10000:

```
sage: v = [2*i \text{ for } i \text{ in } range(10000)]
```

This takes a noticeable fraction of a second (e.g., 0.25 seconds). After preparsing, what Python is really executing is the following:

```
sage: preparse('v = [ 2*i for i in range(10000)]')
'v = [ Integer(2)*i for i in range(Integer(10000))]'
```

If instead we use a raw 2 we get execution that is *instant* (0.00 seconds):

```
sage: v = [ 2r * i for i in range(10000r)]
```

Behind the scenes what happens is the following:

```
sage: preparse('v = [ 2r * i for i in range(10000r)]')
'v = [ 2 * i for i in range(10000)]'
```

Warning: The results of the above two expressions are different. The first one computes a list of Sage integers, whereas the second creates a list of Python integers. Python integers are typically much more efficient than Sage integers when they are very small; large Sage integers are much more efficient than Python integers, since they are implemented using the GMP C library.

```
sage.repl.preparse.containing_block(code, idx, delimiters=['()', '[]', '{}'], re-
quire delim=True)
```

Find the code block given by balanced delimiters that contains the position idx.

INPUT:

- code a string
- idx an integer; a starting position
- delimiters a list of strings (default: ['()', '[]', '{}']); the delimiters to balance. A delimiter must be a single character and no character can at the same time be opening and closing delimiter.
- require_delim a boolean (default: True); whether to raise a SyntaxError if delimiters are present. If the delimiters are unbalanced, an error will be raised in any case.

OUTPUT:

- a 2-tuple (a,b) of integers, such that code[a:b] is delimited by balanced delimiters, a <= idx <b, and a is maximal and b is minimal with that property. If that does not exist, a SyntaxError is raised.
- If require_delim is false and a, b as above can not be found, then 0, len(code) is returned.

EXAMPLES:

```
sage: from sage.repl.preparse import containing_block
sage: s = "factor(next_prime(L[5]+1))"
sage: s[22]
'+'
sage: start, end = containing_block(s, 22)
sage: start, end
(17, 25)
sage: s[start:end]
'(L[5]+1)'
sage: s[20]
'5'
sage: start, end = containing_block(s, 20); s[start:end]
'[5]'
sage: start, end = containing_block(s, 20, delimiters=['()']); s[start:end]
'(L[5]+1)'
sage: start, end = containing_block(s, 10); s[start:end]
'(next_prime(L[5]+1))'
```

sage.repl.preparse.extract_numeric_literals(code)

Pulls out numeric literals and assigns them to global variables. This eliminates the need to re-parse and create the literals, e.g., during every iteration of a loop.

INPUT:

• code - a string; a block of code

OUTPUT:

• a (string, string:string dictionary) 2-tuple; the block with literals replaced by variable names and a mapping from names to the new variables

EXAMPLES:

$\verb|sage.repl.preparse.handle_encoding_declaration| (\textit{contents}, \textit{out})$

Find a PEP 263-style Python encoding declaration in the first or second line of contents. If found, output it to out and return contents without the encoding line; otherwise output a default UTF-8 declaration and return contents.

EXAMPLES:

```
sage: from sage.repl.preparse import handle_encoding_declaration
sage: import sys
sage: c1='# -*- coding: latin-1 -*-\nimport os, sys\n...'
```

```
sage: c2='# -*- coding: iso-8859-15 -*-\nimport os, sys\n...'
sage: c3='# -*- coding: ascii -*-\nimport os, sys\n...'
sage: c4='import os, sys\n...'
sage: handle_encoding_declaration(c1, sys.stdout)
# -*- coding: latin-1 -*-
'import os, sys\n...'
sage: handle_encoding_declaration(c2, sys.stdout)
# -*- coding: iso-8859-15 -*-
'import os, sys\n...'
sage: handle_encoding_declaration(c3, sys.stdout)
# -*- coding: ascii -*-
'import os, sys\n...'
sage: handle_encoding_declaration(c4, sys.stdout)
# -*- coding: utf-8 -*-
'import os, sys\n...'
```

Note:

- PEP 263 says that Python will interpret a UTF-8 byte order mark as a declaration of UTF-8 encoding, but I don't think we do that; this function only sees a Python string so it can't account for a BOM.
- We default to UTF-8 encoding even though PEP 263 says that Python files should default to ASCII.
- Also see https://docs.python.org/ref/encodings.html.

AUTHORS:

- · Lars Fischer
- Dan Drake (2010-12-08, rewrite for trac ticket #10440)

```
sage.repl.preparse.implicit_mul(code, level=5)
Inserts *'s to make implicit multiplication explicit.
```

INPUT:

- code a string; the code with missing *'s
- level an integer (default: 5); how aggressive to be in placing *'s
 - 0 Do nothing
 - 1 Numeric followed by alphanumeric
 - 2 Closing parentheses followed by alphanumeric
 - 3 Spaces between alphanumeric
 - 10 Adjacent parentheses (may mangle call statements)

OUTPUT:

· a string

EXAMPLES:

```
sage: from sage.repl.preparse import implicit_mul
sage: implicit_mul('(2x^2-4x+3)a0')
'(2*x^2-4*x+3)*a0'
sage: implicit_mul('a b c in L')
'a*b*c in L'
(continues on next rese)
```

```
sage: implicit_mul('1r + 1e3 + 5exp(2)')
'1r + 1e3 + 5*exp(2)'
sage: implicit_mul('f(a)(b)', level=10)
'f(a)*(b)'
```

sage.repl.preparse.implicit_multiplication(level=None)

Turns implicit multiplication on or off, optionally setting a specific level. Returns the current level if no argument is given.

INPUT:

• level - an integer (default: None); see implicit_mul() for a list

EXAMPLES:

```
sage: implicit_multiplication(True)
sage: implicit_multiplication()
5
sage: preparse('2x')
'Integer(2)*x'
sage: implicit_multiplication(False)
sage: preparse('2x')
'2x'
```

```
sage.repl.preparse.in_quote()
sage.repl.preparse.isalphadigit (s)
```

Return True if s is a non-empty string of alphabetic characters or a non-empty string of digits or just a single

EXAMPLES:

```
sage: from sage.repl.preparse import isalphadigit_
sage: isalphadigit_('abc')
True
sage: isalphadigit_('123')
True
sage: isalphadigit_('_')
True
sage: isalphadigit_('a123')
False
```

sage.repl.preparse.parse_ellipsis (code, preparse_step=True)

Preparses [0,2,..,n] notation.

INPUT:

- code a string
- preparse_step a boolean (default: True)

OUTPUT:

· a string

EXAMPLES:

```
sage: from sage.repl.preparse import parse_ellipsis
sage: parse_ellipsis("[1,2,..,n]")
'(ellipsis_range(1,2,Ellipsis,n))'
```

```
sage: parse_ellipsis("for i in (f(x) .. L[10]):")
'for i in (ellipsis_iter(f(x) ,Ellipsis, L[10])):'
sage: [1.0..2.0]
[1.00000000000000, 2.000000000000]
```

sage.repl.preparse.preparse(line, reset=True, do_time=False, ignore_prompts=False, numeric_literals=True)

Preparses a line of input.

INPUT:

- line a string
- reset a boolean (default: True)
- do_time a boolean (default: False)
- ignore_prompts a boolean (default: False)
- numeric_literals a boolean (default: True)

OUTPUT:

• a string

EXAMPLES:

```
sage: preparse("ZZ.<x> = ZZ['x']")
"ZZ = ZZ['x']; (x,) = ZZ._first_ngens(1)"
sage: preparse("ZZ.<x> = ZZ['y']")
"ZZ = ZZ['y']; (x,) = ZZ._first_ngens(1)"
sage: preparse ("ZZ.<x,y>=ZZ[]")
"ZZ = ZZ['x, y']; (x, y,) = ZZ._first_ngens(2)"
sage: preparse("ZZ.\langle x, y \rangle = ZZ['u, v']")
"ZZ = ZZ['u,v']; (x, y,) = ZZ._first_ngens(2)"
sage: preparse ("ZZ.\langle x \rangle = QQ[2^{(1/3)}]")
'ZZ = QQ[Integer(2)**(Integer(1)/Integer(3))]; (x,) = ZZ._first_ngens(1)'
sage: QQ[2^{(1/3)}]
Number Field in a with defining polynomial x^3 - 2
sage: preparse("a^b")
'a**b'
sage: preparse("a^^b")
'a^b'
sage: 8^1
sage: 8^^1
sage: 9^^1
sage: preparse("A \\ B")
'A * BackslashOperator() * B'
sage: preparse("A^2 \\ B + C")
'A**Integer(2) * BackslashOperator() * B + C'
sage: preparse("a \\ b \\") # There is really only one backslash here, it's just_
⇒being escaped.
'a * BackslashOperator() * b \\'
```

sage.repl.preparse.preparse_calculus (code)

Supports calculus-like function assignment, e.g., transforms:

```
f(x,y,z) = \sin(x^3 - 4*y) + y^x
```

into:

AUTHORS:

- · Bobby Moretti
 - Initial version 02/2007
- · William Stein
 - Make variables become defined if they aren't already defined.
- · Robert Bradshaw
 - Rewrite using regular expressions (01/2009)

EXAMPLES:

```
sage: preparse("f(x) = x^3-x")
'__tmp__=var("x"); f = symbolic_expression(x**Integer(3)-x).function(x)'
sage: preparse("f(u,v) = u - v")
'__tmp__=var("u,v"); f = symbolic_expression(u - v).function(u,v)'
sage: preparse("f(x) =-5")
'__tmp__=var("x"); f = symbolic_expression(-Integer(5)).function(x)'
sage: preparse("f(x) -= 5")
'f(x) -= Integer(5)'
sage: preparse("f(x_1, x_2) = x_1^2 - x_2^2")
'__tmp__=var("x_1,x_2"); f = symbolic_expression(x_1**Integer(2) - x_
-2**Integer(2)).function(x_1,x_2)'
```

For simplicity, this function assumes all statements begin and end with a semicolon:

```
sage: from sage.repl.preparse import preparse_calculus
sage: preparse_calculus(";f(t,s)=t^2;")
';__tmp__=var("t,s"); f = symbolic_expression(t^2).function(t,s);'
sage: preparse_calculus(";f(t,s) = t^2;")
';__tmp__=var("t,s"); f = symbolic_expression(t^2).function(t,s);'
```

sage.repl.preparse.**preparse_file** (*contents*, *globals=None*, *numeric_literals=True*)
Preparses input, attending to numeric literals and load/attach file directives.

Note: Temporarily, if @parallel is in the input, then numeric_literals is always set to False.

INPUT:

- contents a string
- globals dict or None (default: None); if given, then arguments to load/attach are evaluated in the namespace of this dict.
- numeric_literals bool (default: True), whether to factor out wrapping of integers and floats, so they don't get created repeatedly inside loops

OUTPUT:

· a string

```
sage.repl.preparse.preparse_file_named(name)
```

Preparse file named code{name} (presumably a .sage file), outputting to a temporary file. Returns name of temporary file.

```
sage.repl.preparse.preparse_file_named_to_stream(name, out)
```

Preparse file named code{name} (presumably a .sage file), outputting to stream code{out}.

```
sage.repl.preparse.preparse_generators(code)
```

Parses generator syntax, converting:

```
obj.<gen0,gen1,...,genN> = objConstructor(...)
```

into:

```
obj = objConstructor(..., names=("gen0", "gen1", ..., "genN"))
(gen0, gen1, ..., genN,) = obj.gens()
```

and:

```
obj.<gen0,gen1,...,genN> = R[interior]
```

into:

```
obj = R[interior]; (gen0, gen1, ..., genN,) = obj.gens()
```

INPUT:

• code - a string

OUTPUT:

· a string

LIMITATIONS:

• The entire constructor *must* be on one line.

AUTHORS:

- 2006-04-14: Joe Wetherell (jlwether@alum.mit.edu)
 - Initial version.
- 2006-04-17: William Stein
 - Improvements to allow multiple statements.
- 2006-05-01: William
 - Fix bug that Joe found.
- 2006-10-31: William
 - Fix so obj doesn't have to be mutated.

- 2009-01-27: Robert Bradshaw
 - Rewrite using regular expressions

```
sage.repl.preparse_preparse_numeric_literals(code, extract=False)
```

This preparses numerical literals into their Sage counterparts, e.g. Integer, RealNumber, and ComplexNumber.

INPUT:

- code a string; a code block to preparse
- extract a boolean (default: False); whether to create names for the literals and return a dictionary of name-construction pairs

OUTPUT:

• a string or (string, string:string dictionary) 2-tuple; the preparsed block and, if extract is True, the name-construction mapping

EXAMPLES:

```
sage: from sage.repl.preparse import preparse_numeric_literals
sage: preparse_numeric_literals("5")
'Integer (5)'
sage: preparse_numeric_literals("5j")
"ComplexNumber(0, '5')"
sage: preparse_numeric_literals("5jr")
'5J'
sage: preparse_numeric_literals("51")
'51'
sage: preparse_numeric_literals("5L")
'5L'
sage: preparse_numeric_literals("1.5")
"RealNumber('1.5')"
sage: preparse_numeric_literals("1.5j")
"ComplexNumber(0, '1.5')"
sage: preparse_numeric_literals(".5j")
"ComplexNumber(0, '.5')"
sage: preparse_numeric_literals("5e9j")
"ComplexNumber(0, '5e9')"
sage: preparse numeric literals("5.")
"RealNumber('5.')"
sage: preparse_numeric_literals("5.j")
"ComplexNumber(0, '5.')"
sage: preparse_numeric_literals("5.foo()")
'Integer(5).foo()'
sage: preparse numeric literals("5.5.foo()")
"RealNumber('5.5').foo()"
sage: preparse_numeric_literals("5.5j.foo()")
"ComplexNumber(0, '5.5').foo()"
sage: preparse_numeric_literals("5j.foo()")
"ComplexNumber(0, '5').foo()"
sage: preparse_numeric_literals("1.exp()")
'Integer(1).exp()'
sage: preparse_numeric_literals("1e+10")
"RealNumber('1e+10')"
sage: preparse_numeric_literals("0x0af")
'Integer (0x0af)'
sage: preparse_numeric_literals("0x10.sqrt()")
'Integer (0x10).sqrt()'
sage: preparse_numeric_literals('0o100')
```

```
'Integer(0o100)'
sage: preparse_numeric_literals('0b111001')
'Integer(0b111001)'
sage: preparse_numeric_literals('0xe')
'Integer(0xe)'
sage: preparse_numeric_literals('0xEAR')
'0xEA'
sage: preparse_numeric_literals('0x1012Fae')
'Integer(0x1012Fae)'
```

sage.repl.preparse.strip_prompts(line)

Removes leading sage: and >>> prompts so that pasting of examples from the documentation works.

INPUT:

• line - a string to process

OUTPUT:

• a string stripped of leading prompts

EXAMPLES:

```
sage: from sage.repl.preparse import strip_prompts
sage: strip_prompts("sage: 2 + 2")
'2 + 2'
sage: strip_prompts(">>> 3 + 2")
'3 + 2'
sage: strip_prompts(" 2 + 4")
' 2 + 4'
```

sage.repl.preparse.strip_string_literals(code, state=None)

Returns a string with all literal quotes replaced with labels and a dictionary of labels for re-substitution. This makes parsing easier.

INPUT:

- code a string; the input
- state a 2-tuple (default: None); state with which to continue processing, e.g., across multiple calls to this function

OUTPUT:

a 3-tuple of the processed code, the dictionary of labels, and any accumulated state

EXAMPLES:

```
sage: from sage.repl.preparse import strip_string_literals
sage: s, literals, state = strip_string_literals(r'''['a', "b", 'c', "d\""]''')
sage: s
'[%(L1)s, %(L2)s, %(L3)s, %(L4)s]'
sage: literals
{'L1': "'a'", 'L2': '"b"', 'L3': "'c'", 'L4': '"d\\""'}
sage: print(s % literals)
['a', "b", 'c', "d\""]
sage: print(strip_string_literals(r'-"\\\""-"\\""-"\\""-")[0])
-%(L1)s-%(L2)s-
```

Triple-quotes are handled as well:

```
sage: s, literals, state = strip_string_literals("[a, '''b''', c, '']")
sage: s
'[a, %(L1)s, c, %(L2)s]'
sage: print(s % literals)
[a, '''b''', c, '']
```

Comments are substitute too:

```
sage: s, literals, state = strip_string_literals("code '#' # ccc 't'"); s
'code %(L1)s #%(L2)s'
sage: s % literals
"code '#' # ccc 't'"
```

A state is returned so one can break strings across multiple calls to this function:

```
sage: s, literals, state = strip_string_literals('s = "some'); s
's = %(L1)s'
sage: s, literals, state = strip_string_literals('thing" * 5', state); s
'%(L1)s * 5'
```

LOADING AND ATTACHING FILES

Sage or Python files can be loaded (similar to Python's execfile) in a Sage session. Attaching is similar, except that the attached file is reloaded whenever it is changed.

3.1 Load Python, Sage, Cython, Fortran and Magma files in Sage

```
sage.repl.load.is_loadable_filename (filename)
```

Returns whether a file can be loaded into Sage. This checks only whether its name ends in one of the supported extensions .py, .pyx, .sage, .spyx, .f, .f90 and .m. Note: load() assumes the latter signifies a Magma file.

INPUT:

• filename - a string

OUTPUT:

· a boolean

EXAMPLES:

```
sage: sage.repl.load.is_loadable_filename('foo.bar')
False
sage: sage.repl.load.is_loadable_filename('foo.c')
False
sage: sage.repl.load.is_loadable_filename('foo.sage')
True
sage: sage.repl.load.is_loadable_filename('FOO.F9O')
True
sage: sage.repl.load.is_loadable_filename('foo.m')
```

sage.repl.load.load(filename, globals, attach=False)

Executes a file in the scope given by globals. If the name starts with http://, it is treated as a URL and downloaded.

Note: For Cython files, the situation is more complicated – the module is first compiled to a temporary module t and executed via:

```
from t import *
```

INPUT:

- filename a string denoting a filename or URL.
- globals a string:object dictionary; the context in which to execute the file contents.
- attach a boolean (default: False); whether to add the file to the list of attached files.

EXAMPLES:

Note that .py files are *not* preparsed:

A . sage file is preparsed:

Cython files are *not* preparsed:

If the file isn't a Cython, Python, or a Sage file, a ValueError is raised:

We load a file given at a remote URL:

We can load files using secure http (https):

We attach a file:

You can't attach remote URLs (yet):

The default search path for loading and attaching files is the current working directory, i.e., '.'. But you can modify the path with <code>load_attach_path()</code>:

or by setting the environment variable SAGE_LOAD_ATTACH_PATH to a colon-separated list before starting Sage:

```
$ export SAGE_LOAD_ATTACH_PATH="/path/to/my/library:/path/to/utils"
$ sage
sage: load_attach_path()  # not tested
['.', '/path/to/my/library', '/path/to/utils']
```

sage.repl.load.load_cython(name)

Helper function to load a Cython file.

INPUT:

• name – filename of the Cython file

OUTPUT:

• A string with Python code to import the names from the compiled module.

```
sage.repl.load.load_wrap (filename, attach=False)
```

Encodes a load or attach command as valid Python code.

INPUT:

- filename a string; the argument to the load or attach command
- attach a boolean (default: False); whether to attach filename, instead of loading it

OUTPUT:

a string

EXAMPLES:

```
sage: sage.repl.load.load_wrap('foo.py', True)
'sage.repl.load.load(sage.repl.load.base64.b64decode("Zm9vLnB5"),globals(),True)'
sage: sage.repl.load.load_wrap('foo.sage')
'sage.repl.load.load(sage.repl.load.base64.b64decode("Zm9vLnNhZ2U="),globals(),
→False)'
sage: m = sage.repl.load.base64.b64decode("Zm9vLnNhZ2U=")
sage: m == b'foo.sage'
True
```

3.2 Keep track of attached files

```
sage.repl.attach.add_attached_file(filename)
```

Add to the list of attached files

This is a callback to be used from <code>load()</code> after evaluating the attached file the first time.

INPUT:

• filename – string, the fully qualified file name.

EXAMPLES:

```
sage: import sage.repl.attach as af
sage: af.reset()
sage: t = tmp_filename(ext='.py')
sage: af.add_attached_file(t)
sage: af.attached_files()
['/.../tmp_....py']
sage: af.detach(t)
sage: af.attached_files()
[]
```

```
sage.repl.attach.attach(*files)
```

Attach a file or files to a running instance of Sage and also load that file.

Note: Attaching files uses the Python inputhook, which will conflict with other inputhook users. This generally includes GUI main loop integrations, for example tkinter. So you can only use tkinter or attach, but not both at the same time.

INPUT:

• files – a list of filenames (strings) to attach.

OUTPUT

Each file is read in and added to an internal list of watched files. The meaning of reading in a file depends on the file type:

• .py files are read in with no preparsing (so, e.g., 2^3 is 2 bit-xor 3);

- . sage files are preparsed, then the result is read in;
- .pyx files are not preparsed, but rather are compiled to a module m and then from m import * is executed.

The contents of the file are then loaded, which means they are read into the running Sage session. For example, if foo.sage contains x=5, after attaching foo.sage the variable x will be set to 5. Moreover, any time you change foo.sage, before you execute a command, the attached file will be re-read automatically (with no intervention on your part).

See also:

load () is the same as attach (), but doesn't automatically reload a file when it changes.

EXAMPLES:

You attach a file, e.g., foo. sage or foo.py or foo.pyx, to a running Sage session by typing:

```
sage: attach('foo.sage') # not tested
```

Here we test attaching multiple files at once:

```
sage: sage.repl.attach.reset()
sage: t1 = tmp_filename(ext='.py')
sage: _ = open(t1,'w').write("print('hello world')")
sage: t2 = tmp_filename(ext='.py')
sage: _ = open(t2,'w').write("print('hi there xxx')")
sage: attach(t1, t2)
hello world
hi there xxx
sage: set(attached_files()) == set([t1,t2])
True
```

See also:

- attached_files() returns a list of all currently attached files.
- detach () instructs Sage to remove a file from the internal list of watched files.
- load_attach_path() allows you to get or modify the current search path for loading and attaching files

```
sage.repl.attach.attached_files()
```

Returns a list of all files attached to the current session with attach().

OUTPUT:

The filenames in a sorted list of strings.

EXAMPLES:

```
sage: sage.repl.attach.reset()
sage: t = tmp_filename(ext='.py')
sage: _ = open(t,'w').write("print('hello world')")
sage: attach(t)
hello world
sage: attached_files()
['/....py']
sage: attached_files() == [t]
True
```

```
sage.repl.attach.detach(filename)
Detach a file.
```

This is the counterpart to attach().

INPUT:

• filename – a string, or a list of strings, or a tuple of strings.

EXAMPLES:

```
sage: sage.repl.attach.reset()
sage: t = tmp_filename(ext='.py')
sage: _ = open(t,'w').write("print('hello world')")
sage: attach(t)
hello world
sage: attached_files() == [t]
sage: detach(t)
sage: attached_files()
[]
sage: sage.repl.attach.reset(); reset_load_attach_path()
sage: load_attach_path()
['.']
sage: t_dir = tmp_dir()
sage: fullpath = os.path.join(t_dir, 'test.py')
sage: _ = open(fullpath, 'w').write("print(37 * 3)")
sage: load_attach_path(t_dir)
sage: attach('test.py')
111
sage: attached_files() == [os.path.normpath(fullpath)]
sage: detach('test.py')
sage: attached_files()
sage: attach('test.py')
111
sage: fullpath = os.path.join(t_dir, 'test2.py')
sage: _ = open(fullpath, 'w').write("print(3)")
sage: attach('test2.py')
sage: detach(attached_files())
sage: attached_files()
[]
```

sage.repl.attach.load_attach_mode (load_debug=None, attach_debug=None)

Get or modify the current debug mode for the behavior of load() and attach() on .sage files.

In debug mode, loaded or attached .sage files are preparsed through a file to make their tracebacks more informative. If not in debug mode, then .sage files are preparsed in memory only for performance.

At startup, debug mode is True for attaching and False for loading.

Note: This function should really be deprecated and code executed from memory should raise proper tracebacks.

INPUT:

- load_debug boolean or None (default); if not None, then set a new value for the debug mode for loading files.
- attach_debug boolean or None (default); same as load_debug, but for attaching files.

OUTPUT:

If all input values are None, returns a tuple giving the current modes for loading and attaching.

EXAMPLES:

```
sage: load_attach_mode()
(False, True)
sage: load_attach_mode(attach_debug=False)
sage: load_attach_mode()
(False, False)
sage: load_attach_mode(load_debug=True)
sage: load_attach_mode()
(True, False)
sage: load_attach_mode(load_debug=False, attach_debug=True)
```

sage.repl.attach.load_attach_path(path=None, replace=False)

Get or modify the current search path for load () and attach ().

INPUT:

- path string or list of strings (default: None); path(s) to append to or replace the current path.
- replace boolean (default: False); if path is not None, whether to *replace* the search path instead of *appending* to it.

OUTPUT:

None or a *reference* to the current search paths.

EXAMPLES:

First, we extend the example given in load () 's docstring:

```
sage: sage.repl.attach.reset(); reset_load_attach_path()
sage: load_attach_path()
['.']
sage: t_dir = tmp_dir()
sage: fullpath = os.path.join(t_dir, 'test.py')
sage: _ = open(fullpath, 'w').write("print(37 * 3)")
sage: attach('test.py')
Traceback (most recent call last):
IOError: did not find file 'test.py' to load or attach
sage: load_attach_path(t_dir)
sage: attach('test.py')
111
sage: attached_files() == [fullpath]
sage: sage.repl.attach.reset(); reset_load_attach_path()
sage: load_attach_path() == ['.']
sage: load('test.py')
Traceback (most recent call last):
IOError: did not find file 'test.py' to load or attach
```

The function returns a reference to the path list:

```
sage: reset_load_attach_path(); load_attach_path()
['.']
sage: load_attach_path('/path/to/my/sage/scripts'); load_attach_path()
['.', '/path/to/my/sage/scripts']
sage: load_attach_path(['good', 'bad', 'ugly'], replace=True)
sage: load_attach_path()
['good', 'bad', 'ugly']
sage: p = load_attach_path(); p.pop()
'ugly'
sage: p[0] = 'weird'; load_attach_path()
['weird', 'bad']
sage: reset_load_attach_path(); load_attach_path()
['.']
```

```
sage.repl.attach.modified_file_iterator()
```

Iterate over the changed files

As a side effect the stored time stamps are updated with the actual time stamps. So if you iterate over the attached files in order to reload them and you hit an error then the subsequent files are not marked as read.

Files that are in the process of being saved are excluded.

EXAMPLES:

```
sage: sage.repl.attach.reset()
sage: t = tmp_filename(ext='.py')
sage: attach(t)
sage: from sage.repl.attach import modified_file_iterator
sage: list(modified_file_iterator())
[]
sage: sleep(1)  # filesystem mtime granularity
sage: _ = open(t, 'w').write('1')
sage: list(modified_file_iterator())
[('/.../tmp_....py', time.struct_time(...))]
```

sage.repl.attach.reload_attached_files_if_modified()

Reload attached files that have been modified

This is the internal implementation of the attach mechanism.

EXAMPLES:

```
sage: sage.repl.attach.reset()
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: tmp = tmp_filename(ext='.py')
sage: _ = open(tmp, 'w').write('a = 2\n')
sage: shell.run_cell('attach({0})'.format(repr(tmp)))
sage: shell.run_cell('a')
2
sage: sleep(1) # filesystem mtime granularity
sage: _ = open(tmp, 'w').write('a = 3\n')
```

Note that the doctests are never really at the command prompt where the automatic reload is triggered. So we have to do it manually:

```
sage.repl.attach.reset()
```

Remove all the attached files from the list of attached files.

EXAMPLES:

```
sage: sage.repl.attach.reset()
sage: t = tmp_filename(ext='.py')
sage: _ = open(t,'w').write("print('hello world')")
sage: attach(t)
hello world
sage: attached_files() == [t]
True
sage: sage.repl.attach.reset()
sage: attached_files()
[]
```

```
sage.repl.attach.reset_load_attach_path()
```

Resets the current search path for load () and attach ().

The default path is '.' plus any paths specified in the environment variable SAGE_LOAD_ATTACH_PATH.

EXAMPLES:

```
sage: load_attach_path()
['.']
sage: t_dir = tmp_dir()
sage: load_attach_path(t_dir)
sage: t_dir in load_attach_path()
True
sage: reset_load_attach_path(); load_attach_path()
['.']
```

At startup, Sage adds colon-separated paths in the environment variable SAGE_LOAD_ATTACH_PATH:

```
sage: reset_load_attach_path(); load_attach_path()
['.']
sage: os.environ['SAGE_LOAD_ATTACH_PATH'] = '/veni/vidi:vici:'
sage: import imp
sage: imp.reload(sage.repl.attach)  # Simulate startup
<module 'sage.repl.attach' from '...'>
sage: load_attach_path()
['.', '/veni/vidi', 'vici']
sage: del os.environ['SAGE_LOAD_ATTACH_PATH']
sage: imp.reload(sage.repl.preparse)  # Simulate startup
<module 'sage.repl.preparse' from '...'>
sage: reset_load_attach_path(); load_attach_path()
['.']
```

Sage Reference Manual: The Sage Command Line, Release 8.5		

PRETTY PRINTING

In addition to making input nicer, we also modify how results are printed. This again builds on how IPython formats output. Technically, this works using a modified displayhook in Python.

4.1 IPython Displayhook Formatters

The classes in this module can be used as IPython displayhook formatters. It has two main features, by default the displayhook contains a new facility for displaying lists of matrices in an easier to read format:

This facility uses _repr_() (and a simple string) to try do a nice read format (see sage.structure.parent. Parent._repr_option() for details).

With this displayhook there exists an other way for displaying object and more generally, all sage expression as an ASCII art object:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('%display ascii_art')
sage: shell.run_cell('integral(x^2/pi^x, x)')
  -x / 2
-pi * x * log (pi) + 2*x* log (pi) + 2/
              3
            log (pi)
sage: shell.run_cell("i = var('i')")
sage: shell.run_cell('sum(i*x^i, i, 0, 10)')
  10 9 8 7 6 5
10*x + 9*x + 8*x + 7*x + 6*x + 5*x + 4*x + 3*x + 2*x + x
sage: shell.run_cell('StandardTableaux(4).list()')
[
               1 3 4 1 2 4 1 2 3 1 3
               2 , 3 ,
                                  4 ,
                1 ]
```

(continues on next page)

(continued from previous page)

```
1 3 1 2 2 ]
2 3 3 ]
4 , 4 , 4 ]
sage: shell.run_cell('*display default')
sage: shell.quit()
```

This other facility uses a simple AsciiArt object (see and sage.structure.sage_object.SageObject._ascii_art_()).

```
class sage.repl.display.formatter.SageDisplayFormatter(*args, **kwds)
    Bases: IPython.core.formatters.DisplayFormatter
```

This is where the Sage rich objects are translated to IPython

INPUT/OUTPUT:

See the IPython documentation.

EXAMPLES:

This is part of how Sage works with the IPython output system. It cannot be used in doctests:

```
sage: from sage.repl.display.formatter import SageDisplayFormatter
sage: fmt = SageDisplayFormatter()
Traceback (most recent call last):
...
RuntimeError: check failed: current backend is invalid
```

default_mime()

Return the default mime output(s)

If these are the only output mime types from the Sage rich output machinery, then format () will try to fall back to IPythons internal formatting.

OUTPUT:

List of mime type strings. Usually just text/plain, though possibly more depending on display manager preferences.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: from sage.repl.rich_output.backend_ipython import BackendIPython
sage: backend = BackendIPython()
sage: shell = get_test_shell()
sage: backend.install(shell=shell)
sage: shell.run_cell('get_ipython().display_formatter.default_mime()')
[u'text/plain']
sage: shell.run_cell('%display latex') # indirect doctest
sage: shell.run_cell('get_ipython().display_formatter.default_mime()')
\newcommand{\Bold}[1]{\mathbf{#1}}\left[\verb|text/plain|, \verb|text/
\right]\right]
sage: shell.run_cell('%display default')
sage: shell.run_cell('%display default')
sage: shell.quit()
```

format (obj, include=None, exclude=None)

Use the Sage rich output instead of IPython

INPUT/OUTPUT:

See the IPython documentation.

EXAMPLES:

```
sage: [identity_matrix(i) for i in range(3,7)]
                                   [1 0 0 0 0 0]
                     [1 0 0 0 0] [0 1 0 0 0 0]
         [1 0 0 0] [0 1 0 0 0] [0 0 1 0 0 0]
[1\ 0\ 0] \quad [0\ 1\ 0\ 0] \quad [0\ 0\ 1\ 0\ 0] \quad [0\ 0\ 0\ 1\ 0\ 0]
[0\ 1\ 0]\quad [0\ 0\ 1\ 0]\quad [0\ 0\ 0\ 1\ 0]\quad [0\ 0\ 0\ 0\ 1\ 0]
[0 0 1], [0 0 0 1], [0 0 0 0 1], [0 0 0 0 0 1]
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('%display ascii_art') # indirect doctest
sage: shell.run_cell("i = var('i')")
sage: shell.run_cell('sum(i*x^i, i, 0, 10)')
                        7
         9 8
                                  6
                                                 4
     + 9*x + 8*x + 7*x + 6*x + 5*x + 4*x + 3*x + 2*x + x
sage: shell.run_cell('%display default')
sage: shell.quit()
```

class sage.repl.display.formatter.SagePlainTextFormatter(*args, **kwds)

Bases: IPython.core.formatters.PlainTextFormatter

Improved plain text IPython formatter.

In particular, it correctly print lists of matrices or other objects (see sage.structure.parent.Parent._repr_option()).

Warning: This IPython formatter is NOT used. You could use it to enable Sage formatting in IPython, but Sage uses its own rich output system that is more flexible and supports different backends.

INPUT/OUTPUT:

See the IPython documentation.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.display_formatter.formatters['text/plain']
<IPython.core.formatters.PlainTextFormatter object at 0x...>
sage: shell.quit()
```

4.2 The Sage pretty printer

Any transformation to a string goes through here. In other words, the SagePlainTextFormatter is entirely implemented via SagePrettyPrinter. Other formatters may or may not use SagePrettyPrinter to generate text output.

AUTHORS:

- Bill Cauchois (2009): initial version
- Jean-Baptiste Priez <jbp@kerios.fr> (2013): ASCII art
- Volker Braun (2013): refactored into DisplayHookBase

Bases: IPython.lib.pretty.PrettyPrinter

Pretty print Sage objects for the commandline

INPUT:

See IPython documentation.

EXAMPLES:

```
sage: 123
123
```

IPython pretty printers:

```
sage: set({1, 2, 3})
{1, 2, 3}
sage: dict(zzz=123, aaa=99, xab=10) # sorted by keys
{'aaa': 99, 'xab': 10, 'zzz': 123}
```

These are overridden in IPython in a way that we feel is somewhat confusing, and we prefer to print them like plain Python which is more informative. See trac ticket #14466

```
sage: 'this is a string'
'this is a string'
sage: type(123)
<type 'sage.rings.integer.Integer'>
sage: type
<... 'type'>
sage: import types
sage: type('name', (), {})
<class '__main__.name'>
sage: types.BuiltinFunctionType
<type 'builtin_function_or_method'>

sage: def foo(): pass
sage: foo
<function foo at 0x...>
```

pretty(obj)

Pretty print obj

This is the only method that outside code should invoke.

INPUT:

• obj - anything.

OUTPUT:

String representation for object.

```
sage: from sage.repl.display.pretty_print import SagePrettyPrinter
sage: from six import StringIO
sage: stream = StringIO()
sage: SagePrettyPrinter(stream, 78, '\n').pretty([type, 123, 'foo'])
sage: stream.getvalue()
"[<... 'type'>,"
```

toplevel()

Return whether we are currently at the top level.

OUTPUT:

Boolean. Whether we are currently pretty-printing an object at the outermost level (True), or whether the object is inside a container (False).

EXAMPLES:

```
sage: from sage.repl.display.pretty_print import SagePrettyPrinter
sage: from six import StringIO
sage: stream = StringIO()
sage: spp = SagePrettyPrinter(stream, 78, '\n')
sage: spp.toplevel()
True
```

4.3 Representations of objects.

```
class sage.repl.display.fancy_repr.LargeMatrixHelpRepr
Bases: sage.repl.display.fancy_repr.ObjectReprABC
```

Representation including help for large Sage matrices

```
__call__ (obj, p, cycle)
Format matrix.
```

INPUT:

- obj anything. Object to format.
- p PrettyPrinter instance.
- cycle boolean. Whether there is a cycle.

OUTPUT:

Boolean. Whether the representer is applicable to obj. If True, the string representation is appended to p.

EXAMPLES:

Leads to:

```
class sage.repl.display.fancy_repr.ObjectReprABC
    Bases: object
```

The abstract base class of an object representer.

```
__call__ (obj, p, cycle)
Format object.
```

INPUT:

- obj anything. Object to format.
- p PrettyPrinter instance.
- cycle boolean. Whether there is a cycle.

OUTPUT:

Boolean. Whether the representer is applicable to obj. If True, the string representation is appended to p.

EXAMPLES:

```
sage: from sage.repl.display.fancy_repr import ObjectReprABC
sage: ObjectReprABC().format_string(123) # indirect doctest
'Error: ObjectReprABC.__call__ is abstract'
```

format string (obj)

For doctesting only: Directly return string.

INPUT:

• obj – anything. Object to format.

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.display.fancy_repr import ObjectReprABC
sage: ObjectReprABC().format_string(123)
'Error: ObjectReprABC.__call__ is abstract'
```

${\bf class} \ {\tt sage.repl.display.fancy_repr.PlainPythonRepr}$

Bases: sage.repl.display.fancy_repr.ObjectReprABC

The ordinary Python representation

```
\_\_\mathtt{call}\_\_(obj, p, cycle)
```

Format matrix.

INPUT:

- ob j anything. Object to format.
- p PrettyPrinter instance.
- cycle boolean. Whether there is a cycle.

OUTPUT:

Boolean. Whether the representer is applicable to obj. If True, the string representation is appended to p.

```
sage: from sage.repl.display.fancy_repr import PlainPythonRepr
sage: pp = PlainPythonRepr()
sage: pp.format_string(type(1))
"<type 'sage.rings.integer.Integer'>"
```

Do not swallow a trailing newline at the end of the output of a custom representer. Note that it is undesirable to have a trailing newline, and if we don't display it you can't fix it:

```
class sage.repl.display.fancy_repr.SomeIPythonRepr
```

Bases: sage.repl.display.fancy_repr.ObjectReprABC

Some selected representers from IPython

EXAMPLES:

```
sage: from sage.repl.display.fancy_repr import SomeIPythonRepr
sage: SomeIPythonRepr()
SomeIPythonRepr pretty printer
```

```
__call__(obj, p, cycle)
```

Format object.

INPUT:

- ob j anything. Object to format.
- p PrettyPrinter instance.
- cycle boolean. Whether there is a cycle.

OUTPUT:

Boolean. Whether the representer is applicable to obj. If True, the string representation is appended to p.

EXAMPLES:

```
sage: from sage.repl.display.fancy_repr import SomeIPythonRepr
sage: pp = SomeIPythonRepr()
sage: pp.format_string(set([1, 2, 3]))
'{1, 2, 3}'
```

```
class sage.repl.display.fancy_repr.TallListRepr
```

Bases: sage.repl.display.fancy_repr.ObjectReprABC

Special representation for lists with tall entries (e.g. matrices)

```
___call___(obj, p, cycle)
Format list/tuple.
```

INPUT:

- ob j anything. Object to format.
- p PrettyPrinter instance.
- cycle boolean. Whether there is a cycle.

OUTPUT:

Boolean. Whether the representer is applicable to obj. If True, the string representation is appended to p.

EXAMPLES:

Check that trac ticket #18743 is fixed:

```
sage: class Foo(object):
....: def __repr__(self):
       return '''BBB AA
                            RRR
....: B B A A R R
....: BBB AAAA RRR
....: B B A A R R
....: BBB A A R R'''
....: def _repr_option(self, key):
       return key == 'ascii_art'
sage: F = Foo()
sage: [F, F]
Γ
    AA RRR
             BBB AA RRR
BBB
B B A A R R B B A A R R
              BBB AAAA RRR
BBB AAAA RRR
B B A A R R B B A A R R
   AAR R, BBB AAR R
```

4.4 Utility functions for pretty-printing

These utility functions are used in the implementations of <code>_repr_</code> methods elsewhere.

```
class sage.repl.display.util.TallListFormatter
    Bases: object

Special representation for lists with tall entries (e.g. matrices)

__call__(the_list)
    Return "tall list" string representation.

See also try_format().

INPUT:
```

• the_list - list or tuple.

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.display.util import format_list
sage: format_list(['not', 'tall'])
"['not', 'tall']"
```

try_format (the_list)

First check whether a list is "tall" – whether the reprs of the elements of the list will span multiple lines and cause the list to be printed awkwardly. If not, this function returns None and does nothing; you should revert back to the normal method for printing an object (its repr). If so, return the string in the special format. Note that the special format isn't just for matrices. Any object with a multiline repr will be formatted.

INPUT:

• the_list - The list (or a tuple).

OUTPUT:

String or None. The latter is returned if the list is not deemed to be tall enough and another formatter should be used.

Sage Reference Manual: The Sage Command Line, Release 8.5		

CHAPTER

FIVE

DISPLAY BACKEND INFRASTRUCTURE

5.1 Display Manager

This is the heart of the rich output system, the display manager arbitrates between

- Backend capabilities: what can be displayed
- · Backend preferences: what gives good quality on the backend
- Sage capabilities: every Sage object can only generate certain representations, and
- User preferences: typeset vs. plain text vs. ascii art, etc.

The display manager is a singleton class, Sage always has exactly one instance of it. Use get_display_manager() to obtain it.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager(); dm
The Sage display manager using the doctest backend
```

```
exception sage.repl.rich_output.display_manager.DisplayException
Bases: exceptions.Exception
```

Base exception for all rich output-related exceptions.

EXAMPLES:

```
sage: from sage.repl.rich_output.display_manager import DisplayException
sage: raise DisplayException('foo')
Traceback (most recent call last):
...
DisplayException: foo
```

```
class sage.repl.rich_output.display_manager.DisplayManager
    Bases: sage.structure.sage_object.SageObject
```

The Display Manager

Used to decide what kind of rich output is best.

```
sage: from sage.repl.rich_output import get_display_manager
sage: get_display_manager()
The Sage display manager using the doctest backend
```

check backend class(backend class)

Check that the current backend is an instance of backend class.

This is, for example, used by the Sage IPython display formatter to ensure that the IPython backend is in use.

INPUT:

• backend_class - type of a backend class.

OUTPUT:

This method returns nothing. A RuntimeError is raised if backend_class is not the type of the current backend.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendSimple
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.check_backend_class(BackendSimple)
Traceback (most recent call last):
...
RuntimeError: check failed: current backend is invalid
```

display_immediately (obj, **rich_repr_kwds)

Show output without going back to the command line prompt.

This method must be called to create rich output from an object when we are not returning to the command line prompt, for example during program execution. Typically, it is being called by sage.plot.graphics.Graphics.show().

INPUT:

- obj anything. The object to be shown.
- rich_repr_kwds optional keyword arguments that are passed through to obj._rich_repr_.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.display_immediately(1/2)
1/2
```

displayhook (obj)

Implementation of the displayhook

Every backend must pass the value of the last statement of a line / cell to this method. See also <code>display_immediately()</code> if you want do display rich output while a program is running.

INPUT:

• ob j – anything. The object to be shown.

OUTPUT:

Returns whatever the backend's displayhook method returned.

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.displayhook(1/2)
1/2
```

classmethod get_instance()

Get the singleton instance.

This class method is equivalent to get_display_manager().

OUTPUT:

The display manager singleton.

EXAMPLES:

```
sage: from sage.repl.rich_output.display_manager import DisplayManager
sage: DisplayManager.get_instance()
The Sage display manager using the doctest backend
```

Helper to construct graphics.

This method can be used to simplify the implementation of a _rich_repr_ method of a graphics object if there is already a function to save graphics to a file.

INPUT:

- save_function callable that can save graphics to a file and accepts options like sage.plot. graphics.Graphics.save().
- save kwds dictionary. Keyword arguments that are passed to the save function.
- file_extension string starting with '.'. The file extension of the graphics file.
- output_container subclass of sage.repl.rich_output.output_basic. OutputBase. The output container to use. Must be one of the types in supported_output().
- figsize pair of integers (optional). The desired graphics size in pixels. Suggested, but need not be respected by the output.
- dpi integer (optional). The desired resolution in dots per inch. Suggested, but need not be respected by the output.

OUTPUT:

Return an instance of output_container.

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: plt = plot(sin)
sage: out = dm.graphics_from_save(plt.save, dict(), '.png', dm.types.

OutputImagePng)
sage: out
OutputImagePng container
sage: out.png.get().startswith(b'\x89PNG')
True
sage: out.png.filename() # random
'/home/user/.sage/temp/localhost.localdomain/23903/tmp_pu5woK.png'
```

is in terminal()

Test whether the UI is meant to run in a terminal

When this method returns True, you can assume that it is possible to use raw_input or launch external programs that take over the input.

Otherwise, you should assume that the backend runs remotely or in a pty controlled by another program. Then you should not launch external programs with a (text or graphical) UI.

This is used to enable/disable interpreter consoles.

OUTPUT:

Boolean.

preferences

Return the preferences.

OUTPUT:

The display preferences as instance of <code>DisplayPreferences</code>.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.preferences
Display preferences:
* graphics is not specified
* supplemental_plot = never
* text is not specified
```

supported_output()

Return the output container classes that can be used.

OUTPUT:

Frozen set of subclasses of OutputBase. If the backend defines derived container classes, this method will always return their base classes.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.types.OutputPlainText in dm.supported_output()
True
sage: type(dm.supported_output())
<... 'frozenset'>
```

switch backend(backend, **kwds)

Switch to a new backend

INPUT:

- backend instance of BackendBase.
- kwds optional keyword arguments that are passed on to the *install()* method.

OUTPUT:

The previous backend.

```
sage: from sage.repl.rich_output.backend_base import BackendSimple
sage: simple = BackendSimple()
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager(); dm
The Sage display manager using the doctest backend

sage: previous = dm.switch_backend(simple)
sage: dm
The Sage display manager using the simple backend
```

Restore the doctest backend:

```
sage: dm.switch_backend(previous) is simple
True
```

threejs_scripts(online)

Return Three.js script tags for the current backend.

INPUT:

• online - Boolean determining script usage context

OUTPUT:

String containing script tags

Note: This base method handles online=True case only, serving CDN script tags. Location of scripts for offline usage is backend-specific.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: get_display_manager().threejs_scripts(online=True)
'...<script src="https://cdn.rawgit.com/mrdoob/three.js/...'
sage: get_display_manager().threejs_scripts(online=False)
Traceback (most recent call last):
...
ValueError: current backend does not support
offline threejs graphics</pre>
```

types

Catalog of all output container types.

Note that every output type must be registered in sage.repl.rich_output.output_catalog.

OUTPUT:

Returns the sage.repl.rich_output.output_catalog module.

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.types.OutputPlainText
<class 'sage.repl.rich_output.output_basic.OutputPlainText'>
```

```
exception sage.repl.rich_output.display_manager.OutputTypeException Bases: sage.repl.rich_output.display_manager.DisplayException
```

Wrong Output container.

The output containers are the subclasses of OutputBase that contain the entire output. The display backends must create output containers of a suitable type depending on the displayed Python object. This exception indicates that there is a mistake in the backend and it returned the wrong type of output container.

EXAMPLES:

```
sage: from sage.repl.rich_output.display_manager import OutputTypeException
sage: raise OutputTypeException('foo')
Traceback (most recent call last):
...
OutputTypeException: foo
```

```
exception sage.repl.rich_output.display_manager.RichReprWarning
Bases: exceptions.UserWarning
```

Warning that is throws if a call to _rich_repr_ fails.

If an object implements _rich_repr_ then it must return a value, possibly None to indicate that no rich output can be generated. But it may not raise an exception as it is very confusing for the user if the displayhook fails.

EXAMPLES:

```
sage: from sage.repl.rich_output.display_manager import RichReprWarning
sage: raise RichReprWarning('foo')
Traceback (most recent call last):
...
RichReprWarning: foo
```

Context manager to temporarily restrict the accepted output types

In the context, the output is restricted to the output container types listed in output_classes. Additionally, display preferences are changed not to show graphics.

INPUT:

- display_manager the display manager.
- output_classes iterable of output container types.

EXAMPLES:

```
sage: from sage.repl.rich_output.display_manager import (
...:     get_display_manager, restricted_output)
sage: dm = get_display_manager()
sage: restricted_output(dm, [dm.types.OutputPlainText])
<sage.repl.rich_output.display_manager.restricted_output object at 0x...>
```

5.2 Display Preferences

This class is used to express display preferences that are not simply a choice of a particular output format. For example, whether to prefer vector over raster graphics. By convention, the value None is always a valid value for a preference

and means no particular preference.

EXAMPLES:

```
sage: from sage.repl.rich_output.preferences import DisplayPreferences
sage: prefs = DisplayPreferences()
sage: prefs.available_options()
(graphics, supplemental_plot, text)
sage: prefs.text is None
True
sage: prefs.text = 'ascii_art'
sage: prefs.text
'ascii_art'
sage: prefs
Display preferences:
* graphics is not specified
* supplemental_plot is not specified
* text = ascii_art
```

Properties can be unset by deleting them or by assigning None:

```
sage: prefs.text = 'ascii_art'
sage: del prefs.text
sage: prefs.text is None
True

sage: prefs.text = 'ascii_art'
sage: prefs.text = None
sage: prefs.text = None
True
```

Properties have documentation attached:

```
sage: import pydoc
sage: doc = pydoc.render_doc(prefs)
sage: assert ' graphics' in doc
sage: assert ' Preferred graphics format' in doc
sage: assert ' text' in doc
sage: assert ' Which textual representation is preferred' in doc
```

Values can also be specified as keyword arguments to the constructor:

```
sage: DisplayPreferences(text='latex')
Display preferences:
  * graphics is not specified
  * supplemental_plot is not specified
  * text = latex
```

Todo: A value-checking preference system should be used elsewhere in Sage, too. The class here is just a simple implementation, a proper implementation would use a metaclass to construct the preference items.

```
class sage.repl.rich_output.preferences.DisplayPreferences(*args, **kwds)
    Bases: sage.repl.rich_output.preferences.PreferencesABC
    graphics
    Preferred graphics format
    Allowed values:
```

- None (default): no preference
- · 'disable'
- · 'vector'
- · 'raster'

supplemental plot

Whether to graphically display graphs and other graph-like objects that implement rich output. When not specified small objects are show graphically and large objects as textual overview.

Allowed values:

- None (default): no preference
- · 'always'
- · 'never'

text

Which textual representation is preferred

Allowed values:

- None (default): no preference
- · 'plain'
- · 'ascii art'
- · 'unicode art'
- · 'latex'

Preferences for displaying graphics

These can be preferences expressed by the user or by the display backend. They are specified as keyword arguments.

INPUT:

- *args* positional arguments are preferences instances. The property values will be inherited from left to right, that is, later parents override values from earlier parents.
- **kwds keyword arguments. Will be used to initialize properties, and override inherited values if necessary.

EXAMPLES:

```
sage: from sage.repl.rich_output.preferences import DisplayPreferences
sage: p1 = DisplayPreferences(graphics='vector')
sage: p2 = DisplayPreferences(graphics='raster')
sage: DisplayPreferences(p1, p2)
Display preferences:
  * graphics = raster
  * supplemental_plot is not specified
  * text is not specified
```

If specified in the opposite order, the setting from p1 is inherited:

```
sage: DisplayPreferences(p2, p1)
Display preferences:
  * graphics = vector
  * supplemental_plot is not specified
  * text is not specified
```

Further keywords override:

```
sage: DisplayPreferences(p2, p1, graphics='disable')
Display preferences:
  * graphics = disable
  * supplemental_plot is not specified
  * text is not specified
```

available_options()

Return the available options

OUTPUT:

Tuple of the preference items as instances of *Property*.

EXAMPLES:

```
sage: from sage.repl.rich_output.preferences import DisplayPreferences
sage: DisplayPreferences().available_options()
(graphics, supplemental_plot, text)
```

 $\textbf{class} \ \, \texttt{sage.repl.rich_output.preferences.Property} \, (\textit{name}, \textit{allowed_values}, \textit{doc=None}) \\$

Bases: property

Preference item

INPUT:

- name string. The name of the property.
- allowed_values list/tuple/iterable of allowed values.
- doc string (optional). The docstring of the property.

EXAMPLES:

```
sage: from sage.repl.rich_output.preferences import Property
sage: prop = Property('foo', [0, 1, 2], 'The Foo Property')
sage: prop.__doc__
'The Foo Property\n\nAllowed values:\n\n* ``None`` (default): no preference\n\n*_
\[
\to 0\n\n* 1\n\n* 2'
\]
sage: prop.allowed_values
(0, 1, 2)
```

deleter (prefs)

Delete the current value of the property

INPUT:

• prefs – the *PreferencesABC* instance that the property is bound to.

EXAMPLES:

```
sage: from sage.repl.rich_output.preferences import Property, PreferencesABC
sage: prop = Property('foo', [0, 1, 2], 'The Foo Property')
```

(continues on next page)

(continued from previous page)

```
sage: prefs = PreferencesABC()
sage: prop.getter(prefs) is None
True
sage: prop.setter(prefs, 1)
sage: prop.deleter(prefs)
sage: prop.getter(prefs) is None
True
```

getter (prefs)

Get the current value of the property

INPUT:

• prefs – the *PreferencesABC* instance that the property is bound to.

OUTPUT

One of the allowed values or None if not set.

EXAMPLES:

```
sage: from sage.repl.rich_output.preferences import Property, PreferencesABC
sage: prop = Property('foo', [0, 1, 2], 'The Foo Property')
sage: prefs = PreferencesABC()
sage: prop.getter(prefs) is None
True
sage: prop.setter(prefs, 1)
sage: prop.getter(prefs)
1
```

setter (prefs, value)

Get the current value of the property

INPUT:

- prefs the *PreferencesABC* instance that the property is bound to.
- value anything. The new value of the property. Setting a property to None is equivalent to deleting the value.

OUTPUT:

This method does not return anything. A ValueError is raised if the given value is not one of the allowed values.

```
sage: from sage.repl.rich_output.preferences import Property, PreferencesABC
sage: prop = Property('foo', [0, 1, 2], 'The Foo Property')
sage: prefs = PreferencesABC()
sage: prop.getter(prefs) is None
True
sage: prop.setter(prefs, 1)
sage: prop.getter(prefs)
1
sage: prop.setter(prefs, None)
sage: prop.getter(prefs) is None
True
```

5.3 Output Buffer

This is the fundamental unit of rich output, a single immutable buffer (either in-memory or as a file). Rich output always consists of one or more buffers. Ideally, the Sage library always uses the buffer object as an in-memory buffer. But you can also ask it for a filename, and it will save the data to a file if necessary. Either way, the buffer object presents the same interface for getting the content of an in-memory buffer or a temporary file. So any rich output backends do not need to know where the buffer content is actually stored.

EXAMPLES:

```
sage: from sage.repl.rich_output.buffer import OutputBuffer
sage: buf = OutputBuffer('this is the buffer content'); buf
buffer containing 26 bytes
sage: buf.get().decode('ascii')
u'this is the buffer content'
sage: type(buf.get()) is bytes
True
```

```
class sage.repl.rich_output.buffer.OutputBuffer(data)
    Bases: sage.structure.sage_object.SageObject
```

Data stored either in memory or as a file

This class is an abstraction for "files", in that they can either be defined by a bytes array (Python 3) or string (Python 2) or by a file (see from_file()).

INPUT:

• data – bytes. The data that is stored in the buffer.

EXAMPLES:

```
sage: from sage.repl.rich_output.buffer import OutputBuffer
sage: buf = OutputBuffer('this is the buffer content'); buf
buffer containing 26 bytes

sage: buf2 = OutputBuffer(buf); buf2
buffer containing 26 bytes

sage: buf.get_str()
'this is the buffer content'
sage: buf.filename(ext='.txt')
'/....txt'
```

filename (ext=None)

Return the filename.

INPUT:

• ext – string. The file extension.

OUTPUT:

Name of a file, most likely a temporary file. If ext is specified, the filename will have that extension.

You must not modify the returned file. Its permissions are set to readonly to help with that.

EXAMPLES:

5.3. Output Buffer 55

```
sage: from sage.repl.rich_output.buffer import OutputBuffer
sage: buf = OutputBuffer('test')
sage: buf.filename()  # random output
'/home/user/.sage/temp/hostname/26085/tmp_RNSfAc'

sage: os.path.isfile(buf.filename())
True
sage: buf.filename(ext='txt')  # random output
'/home/user/.sage/temp/hostname/26085/tmp_Rjjp4V.txt'
sage: buf.filename(ext='txt').endswith('.txt')
True
```

classmethod from_file(filename)

Construct buffer from data in file.

Warning: The buffer assumes that the file content remains the same during the lifetime of the Sage session. To communicate this to the user, the file permissions will be changed to read only.

INPUT:

• filename - string. The filename under which the data is stored.

OUTPUT:

String containing the buffer data.

EXAMPLES:

get()

Return the buffer content

OUTPUT:

Bytes. A string in Python 2.x.

```
sage: from sage.repl.rich_output.buffer import OutputBuffer
sage: c = OutputBuffer('test1234').get(); c.decode('ascii')
u'test1234'
sage: type(c) is bytes
True
sage: c = OutputBuffer(u'été').get()
sage: type(c) is bytes
True
```

get_str()

Return the buffer content as a str object for the current Python version.

That is, returns a Python 2-style encoding-agnostic str on Python 2, and returns a unicode str on Python 3 with the buffer content decoded from UTF-8. In other words, this is equivalent to OutputBuffer.get on Python 2 and OutputBuffer.get_unicode on Python 3. This is useful in some cases for cross-compatible code.

OUTPUT:

A str object.

EXAMPLES:

```
sage: from sage.repl.rich_output.buffer import OutputBuffer
sage: c = OutputBuffer('test1234').get_str(); c
'test1234'
sage: type(c) is str
True
sage: c = OutputBuffer(u'été').get_str()
sage: type(c) is str
True
```

get_unicode()

Return the buffer content as string

OUTPUT:

String. Unicode in Python 2.x. Raises a UnicodeEncodeError if the data is not valid utf-8.

EXAMPLES:

```
sage: from sage.rep1.rich_output.buffer import OutputBuffer
sage: OutputBuffer('test1234').get().decode('ascii')
u'test1234'
sage: OutputBuffer('test1234').get_unicode()
u'test1234'
```

save_as (filename)

Save a copy of the buffer content.

You may edit the returned file, unlike the file returned by filename ().

INPUT:

• filename – string. The file name to save under.

EXAMPLES:

```
sage: from sage.repl.rich_output.buffer import OutputBuffer
sage: buf = OutputBuffer('test')
sage: buf.filename(ext='txt') # random output
sage: tmp = tmp_dir()
sage: filename = os.path.join(tmp, 'foo.txt')
sage: buf.save_as(filename)
sage: with open(filename, 'r') as f:
....: f.read()
```

5.3. Output Buffer 57

5.4 Basic Output Types

The Sage rich representation system requires a special container class to hold the data for each type of rich output. They all inherit from <code>OutputBase</code>, though a more typical example is <code>OutputPlainText</code>. Some output classes consist of more than one data buffer, for example jmol or certain animation formats. The output class is independent of user preferences and of the display backend.

The display backends can define derived classes to attach backend-specific display functionality to, for example how to launch a viewer. But they must not change how the output container is created. To enforce this, the Sage _rich_repr_ magic method will only ever see the output class defined here. The display manager will promote it to a backend-specific subclass if necessary prior to displaying it.

To create new types of output, you must create your own subclass of OutputBase and register it in sage.repl.rich_output.output_catalog.

Warning: All rich output data in sublasses of *OutputBase* must be contained in *OutputBuffer* instances. You must never reference any files on the local file system, as there is no guarantee that the notebook server and the worker process are on the same computer. Or even share a common file system.

```
class sage.repl.rich_output.output_basic.OutputAsciiArt (ascii_art)
    Bases: sage.repl.rich_output.output_basic.OutputBase
    ASCII Art Output
```

INPUT:

• ascii_art - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. Ascii art rendered into a string.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputAsciiArt
sage: OutputAsciiArt(':-}')
OutputAsciiArt container
```

classmethod example()

Construct a sample ascii art output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputAsciiArt.

EXAMPLES:

```
print_to_stdout()
```

Write the data to stdout.

This is just a convenience method to help with debugging.

```
class sage.repl.rich_output.output_basic.OutputBase
```

Bases: sage.structure.sage_object.SageObject

Base class for all rich output containers.

classmethod example()

Construct a sample instance

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of the OutputBase subclass.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_basic import OutputBase
sage: OutputBase.example()
Traceback (most recent call last):
...
NotImplementedError: derived classes must implement this class method
```

```
class sage.repl.rich_output.output_basic.OutputLatex(latex)
```

Bases: sage.repl.rich_output.output_basic.OutputBase

LaTeX Output

Note: The LaTeX commands will only use a subset of LaTeX that can be displayed by MathJax.

INPUT:

• latex - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. String containing the latex equation code. Excludes the surrounding dollar signs / LaTeX equation environment. Also excludes the surrounding MathJax <html> tag.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputLatex
sage: OutputLatex('<html><script type="math/tex; mode=display">1</script></html>')
OutputLatex container
```

display_equation()

Return the LaTeX code for a display equation

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputLatex
sage: rich_output = OutputLatex('1')
sage: rich_output.latex
```

(continues on next page)

(continued from previous page)

```
buffer containing 1 bytes
sage: rich_output.latex.get_str()
'1'
sage: rich_output.display_equation()
'\\begin{equation}\n1\n\\end{equation}'
```

classmethod example()

Construct a sample LaTeX output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputLatex.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputLatex
sage: OutputLatex.example()
OutputLatex container
sage: OutputLatex.example().latex.get_str()
'\\newcommand{\\Bold}[1]{\\mathbf{#1}}\\int \\sin\\left(x\\right)\\,{d x}'
```

inline_equation()

Return the LaTeX code for an inline equation

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputLatex
sage: rich_output = OutputLatex('1')
sage: rich_output.latex
buffer containing 1 bytes
sage: rich_output.latex.get_str()
'1'
sage: rich_output.inline_equation()
'\\begin{math}\n1\n\\end{math}'
```

mathjax (display=True)

Return the LaTeX with a surrounding MathJax HTML code.

INPUT:

• display - boolean. Whether to return display (as opposed to inline) TeX.

```
sage: from sage.repl.rich_output.output_catalog import OutputLatex
sage: rich_output = OutputLatex('1')
sage: rich_output.latex
buffer containing 1 bytes
sage: rich_output.latex.get_str()
'1'
sage: rich_output.mathjax()
'<html><script type="math/tex; mode=display">1</script></html>'
sage: rich_output.mathjax(display=False)
'<html><script type="math/tex">1</script></html>'
```

print_to_stdout()

Write the data to stdout.

This is just a convenience method to help with debugging.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputLatex
sage: rich_output = OutputLatex.example()
sage: rich_output.print_to_stdout()
\newcommand{\Bold}[1]{\mathbf{#1}}\int \sin\left(x\right)\,{d x}
```

```
class sage.repl.rich_output.output_basic.OutputPlainText (plain_text)
```

```
Bases: sage.repl.rich output.output basic.OutputBase
```

Plain Text Output

INPUT:

• plain_text - OutputBuffer. Alternatively, a bytes (string in Python 2.x) or string (unicode in Python 2.x) can be passed directly which will then be converted into an OutputBuffer. The plain text output.

This should always be exactly the same as the (non-rich) output from the <code>_repr_</code> method. Every backend object must support plain text output as fallback.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputPlainText
sage: OutputPlainText('foo')
OutputPlainText container
```

classmethod example()

Construct a sample plain text output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputPlainText.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputPlainText
sage: OutputPlainText.example()
OutputPlainText container
sage: OutputPlainText.example().text.get_str()
'Example plain text output'
```

print_to_stdout()

Write the data to stdout.

This is just a convenience method to help with debugging.

```
sage: from sage.repl.rich_output.output_catalog import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: plain_text.print_to_stdout()
Example plain text output
```

```
class sage.repl.rich_output.output_basic.OutputUnicodeArt (unicode_art)
```

```
Bases: sage.repl.rich_output.output_basic.OutputBase
```

Unicode Art Output

Similar to OutputAsciiArt but using the entire unicode range.

INPUT:

• unicode_art - OutputBuffer. Alternatively, a string (unicode in Python 2.x) can be passed directly which will then be converted into an OutputBuffer. Unicode art rendered into a string.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputUnicodeArt
sage: OutputUnicodeArt (u':-}')
OutputUnicodeArt container
```

classmethod example()

Construct a sample unicode art output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputUnicodeArt.

EXAMPLES:

print_to_stdout()

Write the data to stdout.

This is just a convenience method to help with debugging.

EXAMPLES:

5.5 Graphics Output Types

This module defines the rich output types for 2-d images, both vector and raster graphics.

```
class sage.repl.rich_output.output_graphics.OutputImageDvi (dvi)
    Bases: sage.repl.rich_output.output_basic.OutputBase
    DVI Image
    INPUT:
```

• dvi - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. The DVI data.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageDvi
sage: OutputImageDvi.example() # indirect doctest
OutputImageDvi container
```

classmethod example()

Construct a sample DVI output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of Output ImageDvi.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageDvi
sage: OutputImageDvi.example()
OutputImageDvi container
sage: OutputImageDvi.example().dvi
buffer containing 212 bytes
sage: b'TeX output' in OutputImageDvi.example().dvi.get()
True
```

```
\textbf{class} \texttt{ sage.repl.rich\_output.output\_graphics.OutputImageGif} (\textit{gif})
```

Bases: sage.repl.rich_output.output_basic.OutputBase

GIF Image (possibly animated)

INPUT:

• gif - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. The GIF image data.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageGif
sage: OutputImageGif.example() # indirect doctest
OutputImageGif container
```

classmethod example()

Construct a sample GIF output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of Output ImageGif.

```
sage: from sage.repl.rich_output.output_catalog import OutputImageGif
sage: OutputImageGif.example()
OutputImageGif container
sage: OutputImageGif.example().gif
buffer containing 408 bytes
sage: OutputImageGif.example().gif.get().startswith(b'GIF89a')
True
```

html fragment()

Return a self-contained HTML fragment displaying the image

This is a workaround for the Jupyter notebook which doesn't support GIF directly.

OUTPUT:

String. HTML fragment for displaying the GIF image.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageGif
sage: OutputImageGif.example().html_fragment()
'<img src="...zd3t/g4eLj50VDQQA7"/>'
```

```
\verb|class| sage.repl.rich_output.output_graphics.OutputImageJpg|(jpg)|
```

```
Bases: sage.repl.rich_output.output_basic.OutputBase
```

JPEG Image

INPUT:

• jpg - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. The JPEG image data.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageJpg
sage: OutputImageJpg.example() # indirect doctest
OutputImageJpg container
```

classmethod example()

Construct a sample JPEG output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputImageJpg.

EXAMPLES:

```
class sage.repl.rich_output.output_graphics.OutputImagePdf(pdf)
```

```
Bases: sage.repl.rich_output.output_basic.OutputBase
```

PDF Image

INPUT:

• pdf – OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. The PDF data.

```
sage: from sage.repl.rich_output.output_catalog import OutputImagePdf
sage: OutputImagePdf.example() # indirect doctest
OutputImagePdf container
```

classmethod example()

Construct a sample PDF output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputImagePdf.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImagePdf
sage: OutputImagePdf.example()
OutputImagePdf container
sage: OutputImagePdf.example().pdf
buffer containing 4285 bytes
sage: OutputImagePdf.example().pdf.get().startswith(b'%PDF-1.4')
True
```

```
\verb|class| sage.repl.rich_output.output_graphics.OutputImagePng| (png)
```

Bases: sage.repl.rich_output.output_basic.OutputBase

PNG Image

Note: Every backend that is capable of displaying any kind of graphics is supposed to support the PNG format at least.

INPUT:

• png - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. The PNG image data.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImagePng
sage: OutputImagePng.example() # indirect doctest
OutputImagePng container
```

classmethod example()

Construct a sample PNG output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of Output ImagePng.

```
sage: from sage.repl.rich_output.output_catalog import OutputImagePng
sage: OutputImagePng.example()
OutputImagePng container
sage: OutputImagePng.example().png
buffer containing 608 bytes
sage: OutputImagePng.example().png.get().startswith(b'\x89PNG')
True
```

```
class sage.repl.rich_output.output_graphics.OutputImageSvg(svg)
    Bases: sage.repl.rich_output.output_basic.OutputBase
    SVG Image
```

• svg - OutputBuffer. Alternatively, a string (bytes) can be passed directly which will then be converted into an OutputBuffer. The SVG image data.

EXAMPLES:

INPUT:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageSvg
sage: OutputImageSvg.example() # indirect doctest
OutputImageSvg container
```

classmethod example()

Construct a sample SVG output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputImageSvg.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputImageSvg
sage: OutputImageSvg.example()
OutputImageSvg container
sage: OutputImageSvg.example().svg
buffer containing 1422 bytes
sage: b'</svg>' in OutputImageSvg.example().svg.get()
True
```

5.6 Three-Dimensional Graphics Output Types

This module defines the rich output types for 3-d scenes.

```
class sage.repl.rich_output.output_graphics3d.OutputSceneCanvas3d(canvas3d)
    Bases: sage.repl.rich_output.output_basic.OutputBase
```

Canvas3d Scene

INPUT:

• canvas3d - string/bytes. The canvas3d data.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneCanvas3d
sage: OutputSceneCanvas3d.example()
OutputSceneCanvas3d container
```

classmethod example()

Construct a sample Canvas3D output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputSceneCanvas3d.

EXAMPLES:

Bases: sage.repl.rich_output.output_basic.OutputBase

JMol Scene

By our (Sage) convention, the actual scene is called SCENE inside the zip archive.

INPUT:

- scene_zip string/bytes. The jmol scene (a zip archive).
- preview_png string/bytes. Preview as png file.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneJmol
sage: OutputSceneJmol.example()
OutputSceneJmol container
```

classmethod example()

Construct a sample Jmol output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputSceneJmol.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneJmol
sage: rich_output = OutputSceneJmol.example(); rich_output
OutputSceneJmol container

sage: rich_output.scene_zip
buffer containing 654 bytes
sage: rich_output.scene_zip.get().startswith(b'PK')
True

sage: rich_output.preview_png
buffer containing 608 bytes
sage: rich_output.preview_png.get().startswith(b'\x89PNG')
True
```

launch_script_filename()

Return a launch script suitable to display the scene.

This method saves the scene to disk and creates a launch script. The latter contains an absolute path to the scene file. The launch script is often necessary to make jmol render the 3d scene.

OUTPUT:

String. The file name of a suitable launch script.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneJmol
sage: rich_output = OutputSceneJmol.example(); rich_output
OutputSceneJmol container
sage: filename = rich_output.launch_script_filename(); filename
'/.../scene.spt'
sage: with open(filename) as fobj:
....: print(fobj.read())
set defaultdirectory "/.../scene.spt.zip"
script SCRIPT
```

class sage.repl.rich_output.output_graphics3d.OutputSceneThreejs(html)

Bases: sage.repl.rich_output.output_basic.OutputBase

Three.js Scene

INPUT:

• html - string/bytes. The Three.js HTML data.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneThreejs
sage: OutputSceneThreejs('<html>')
OutputSceneThreejs container
```

Wavefront *.obj Scene

The Wavefront format consists of two files, an .obj file defining the geometry data (mesh points, normal vectors, ...) together with a .mtl file defining texture data.

INPUT:

- ob j bytes. The Wavefront obj file format describing the mesh shape.
- mtl bytes. The Wavefront mtl file format describing textures.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneWavefront
sage: OutputSceneWavefront.example()
OutputSceneWavefront container
```

classmethod example()

Construct a sample Canvas3D output container

This static method is meant for doctests, so they can easily construct an example.

OUTPUT:

An instance of OutputSceneCanvas3d.

mtllib()

Return the mtllib filename

The mtllib line in the Wavefront file format (*.obj) is the name of the separate texture file.

OUTPUT:

String. The filename under which mtl is supposed to be saved.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneWavefront
sage: rich_output = OutputSceneWavefront.example()
sage: rich_output.mtllib()
'scene.mtl'
```

obj_filename()

Return the file name of the .obj file

This method saves the object and texture to separate files in a temporary directory and returns the object file name. This is often used to launch a 3d viewer.

OUTPUT:

String. The file name (absolute path) of the saved obj file.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputSceneWavefront
sage: rich_output = OutputSceneWavefront.example(); rich_output
OutputSceneWavefront container
sage: obj = rich_output.obj_filename(); obj
'/.../scene.obj'
sage: with open(obj) as fobj:
....:     print(fobj.read())
mtllib scene.mtl
g obj_1
...
f 3 2 6 8

sage: path = os.path.dirname(obj)
sage: mtl = os.path.join(path, 'scene.mtl'); mtl
'/.../scene.mtl'
sage: os.path.exists(mtl)
```

```
True
sage: os.path.dirname(obj) == os.path.dirname(mtl)
True
sage: with open(mtl) as fobj:
....:     print(fobj.read())
newmtl texture177
Ka 0.2 0.2 0.5
...
d 1
```

5.7 Video Output Types

This module defines the rich output types for video formats.

```
class sage.repl.rich_output.output_video.OutputVideoAvi (video, loop=True)
    Bases: sage.repl.rich_output.output_video.OutputVideoBase
    AVI video
```

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoAvi
sage: OutputVideoAvi.example()
OutputVideoAvi container
```

```
class sage.repl.rich_output.output_video.OutputVideoBase(video, loop=True)
    Bases: sage.repl.rich_output.output_basic.OutputBase
```

Abstract base class for rich video output

INPUT:

- video OutputBuffer. The video data.
- loop boolean. Whether to repeat the video in an endless loop.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoOgg
sage: OutputVideoOgg.example() # indirect doctest
OutputVideoOgg container
```

classmethod example()

Construct a sample video output container

This static method is meant for doctests, so they can easily construct an example. The method is implemented in the abstract <code>OutputVideoBase</code> class, but should get invoked on a concrete subclass for which an actual example can exist.

OUTPUT:

An instance of the class on which this method is called.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoOgg
sage: OutputVideoOgg.example()
OutputVideoOgg container
```

```
sage: OutputVideoOgg.example().video
buffer containing 5612 bytes
sage: OutputVideoOgg.example().ext
'.ogv'
sage: OutputVideoOgg.example().mimetype
'video/ogg'
```

html fragment(url, link attrs=")

Construct a HTML fragment for embedding this video

INPUT:

- url string. The URL where the data of this video can be found.
- link_attrs string. Can be used to style the fallback link which is presented to the user if the video is not supported.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoOgg
sage: print (OutputVideoOgg.example().html_fragment
....: ('foo', 'class="bar"').replace('><','>\n<'))
<video autoplay="autoplay" controls="controls" loop="loop">
<source src="foo" type="video/ogg" />

<a target="_new" href="foo" class="bar">Download video/ogg video</a>

</video>
```

class sage.repl.rich_output.output_video.OutputVideoFlash(video, loop=True)

Bases: sage.repl.rich_output.output_video.OutputVideoBase

Flash video

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoFlash
sage: OutputVideoFlash.example()
OutputVideoFlash container
```

class sage.repl.rich_output.output_video.OutputVideoMatroska(video, loop=True)

Bases: sage.repl.rich_output.output_video.OutputVideoBase

Matroska Video

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoMatroska
sage: OutputVideoMatroska.example()
OutputVideoMatroska container
```

```
class sage.repl.rich_output.output_video.OutputVideoMp4 (video, loop=True)
```

Bases: sage.repl.rich_output.output_video.OutputVideoBase

MPEG 4 video

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoMp4
sage: OutputVideoMp4.example()
OutputVideoMp4 container
```

```
\textbf{class} \  \, \texttt{sage.repl.rich\_output.output\_video.OutputVideoOgg} \, (\textit{video}, loop=True) \, \\
```

Bases: sage.repl.rich output.output video.OutputVideoBase

Ogg video, Ogg Theora in particular

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoOgg
sage: OutputVideoOgg.example()
OutputVideoOgg container
```

```
class sage.repl.rich_output.output_video.OutputVideoQuicktime(video,
```

loop=True)

Bases: sage.repl.rich output.output video.OutputVideoBase

Quicktime video

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoQuicktime
sage: OutputVideoQuicktime.example()
OutputVideoQuicktime container
```

```
class sage.repl.rich_output.output_video.OutputVideoWebM(video, loop=True)
```

Bases: sage.repl.rich_output.output_video.OutputVideoBase

WebM video

The video can be encoded using VP8, VP9 or an even more recent codec.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoWebM
sage: OutputVideoWebM.example()
OutputVideoWebM container
```

```
class sage.repl.rich_output.output_video.OutputVideoWmv (video, loop=True)
```

Bases: sage.repl.rich_output.output_video.OutputVideoBase

Windows Media Video

EXAMPLES:

```
sage: from sage.repl.rich_output.output_catalog import OutputVideoWmv
sage: OutputVideoWmv.example()
OutputVideoWmv container
```

5.8 Catalog of all available output container types.

If you define another output type then you must add it to the imports here.

5.9 Base Class for Backends

The display backends are the commandline, the SageNB notebook, the IPython notebook, the Emacs sage mode, the Sage doctester, All of these have different capabilities for what they can display.

To implement a new display backend, you need to subclass <code>BackendBase</code>. All backend-specific handlig of rich output should be in <code>displayhook()</code> and <code>display_immediately()</code>. See <code>BackendSimple</code> for an absolutely minimal example of a functioning backend.

You declare the types of rich output that your backend can handle in <code>supported_output()</code>. There are two ways to then display specific output types in your own backend.

- Directly use one of the existing output containers listed in sage.repl.rich_output. output_catalog. That is, test for the rich output type in display_immediately() and handle it.
- Subclass the rich output container to attach your backend-specific functionality. Then <code>display_immediately()</code> will receive instances of your subclass. See <code>BackendTest</code> for an example of how this is done.

You can also mix both ways of implementing different rich output types.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendSimple
sage: backend = BackendSimple()
sage: plain_text = backend.plain_text_formatter(list(range(10))); plain_text
OutputPlainText container
sage: backend.displayhook(plain_text, plain_text)
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

```
class sage.repl.rich_output.backend_base.BackendBase
    Bases: sage.structure.sage_object.SageObject
```

ascii_art_formatter(obj, **kwds)

Hook to override how ascii art is being formatted.

INPUT:

- obj anything.
- **kwds optional keyword arguments to control the formatting. Supported are:
 - concatenate boolean (default: False). If True, the argument obj must be iterable and
 its entries will be concatenated. There is a single whitespace between entries.

OUTPUT:

Instance of OutputAsciiArt containing the ascii art string representation of the object.

EXAMPLES:

```
22, 23, 24, 25, 26, 27, 28, 29 ]

sage: backend.ascii_art_formatter([1,2,3], concatenate=False).ascii_art.get_

str()
'[ 1, 2, 3 ]'

sage: backend.ascii_art_formatter([1,2,3], concatenate=True).ascii_art.get_

str()
'1 2 3'
```

default_preferences()

Return the backend's display preferences

Override this method to change the default preferences when using your backend.

OUTPUT:

Instance of DisplayPreferences.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.default_preferences()
Display preferences:
  * graphics is not specified
  * supplemental_plot is not specified
  * text is not specified
```

display_immediately (plain_text, rich_output)

Show output without going back to the command line prompt.

This method is similar to the rich output <code>displayhook()</code>, except that it can be invoked at any time. Typically, it ends up being called by <code>sage.plot.graphics.Graphics.show()</code>.

Derived classes must implement this method.

INPUT:

Same as displayhook().

OUTPUT:

This method may return something so you can implement <code>displayhook()</code> by calling this method. However, when called by the display manager any potential return value is discarded: There is no way to return anything without returning to the command prompt.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_basic import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.display_immediately(plain_text, plain_text)
Traceback (most recent call last):
...
NotImplementedError: derived classes must implement this method
```

displayhook (plain_text, rich_output)

Backend implementation of the displayhook

The value of the last statement on a REPL input line or notebook cell are usually handed to the Python displayhook and shown on screen. By overriding this method you define how your backend handles output. The difference to the usual displayhook is that Sage already converted the value to the most suitable rich output container.

Derived classes must implement this method.

INPUT:

- plain_text instance of OutputPlainText. The plain text version of the output.
- rich_output instance of an output container class (subclass of OutputBase). Guaranteed to be one of the output containers returned from supported_output(), possibly the same as plain_text.

OUTPUT:

This method may return something, which is then returned from the display manager's <code>displayhook()</code> method.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_basic import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.displayhook(plain_text, plain_text)
Traceback (most recent call last):
...
NotImplementedError: derived classes must implement this method
```

get_display_manager()

Return the display manager singleton

This is a convenience method to access the display manager singleton.

OUTPUT:

The unique DisplayManager instance.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.get_display_manager()
The Sage display manager using the doctest backend
```

install(**kwds)

Hook that will be called once before the backend is used for the first time.

The default implementation does nothing.

INPUT:

• kwds – optional keyword arguments that are passed through by the switch_backend() method.

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.install()
```

is in terminal()

Test whether the UI is meant to run in a terminal

```
See sage.repl.rich_output.display_manager.DisplayManager.is_in_terminal() for details.
```

OUTPUT:

Defaults to False.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.is_in_terminal()
False
```

latex_formatter (obj, **kwds)

Hook to override how Latex is being formatted.

INPUT:

- ob j anything.
- **kwds optional keyword arguments to control the formatting. Supported are:
 - concatenate boolean (default: False). If True, the argument obj must be iterable and its entries will be concatenated. There is a single whitespace between entries.

OUTPUT:

Instance of OutputLatex containing the latex string representation of the object.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: out = backend.latex_formatter(1/2)
sage: out
OutputLatex container
sage: out.latex
buffer containing 45 bytes
sage: out.latex.get_str()
'\newcommand{\\Bold}[1]{\\mathbf\{#1\}}\\frac\{1\}{2}'
sage: out.mathjax()
'<html><script type="math/tex; mode=display">\\newcommand{\\Bold}[1]{\\mathbf{
→#1}}\\frac{1}{2}</script></html>'
sage: out = backend.latex_formatter([1/2, x, 3/4, ZZ], concatenate=False)
sage: out.latex.get_str()
'\ \\newcommand{\\Bold}[1]{\\mathbf{#1}}\\left[\\frac{1}{2}, x, \\frac{3}{4}, \_
→\\Bold{Z}\\right]'
sage: out = backend.latex_formatter([1/2, x, 3/4, ZZ], concatenate=True)
sage: out.latex.get_str()
\label{eq:local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_local_command_loca
```

max_width()

Return the number of characters that fit into one output line

OUTPUT:

Integer.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.max_width()
79
```

newline()

Return the newline string.

OUTPUT:

String for starting a new line of output.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.newline()
'\n'
```

plain_text_formatter (obj, **kwds)

Hook to override how plain text is being formatted.

If the object does not have a _rich_repr_ method, or if it does not return a rich output object (OutputBase), then this method is used to generate plain text output.

INPUT:

- ob j anything.
- **kwds optional keyword arguments to control the formatting. Supported are:
 - concatenate boolean (default: False). If True, the argument obj must be iterable and its entries will be concatenated. There is a single whitespace between entries.

OUTPUT:

Instance of OutputPlainText containing the string representation of the object.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: out = backend.plain_text_formatter(list(range(30)))
sage: out
OutputPlainText container
sage: out.text
buffer containing 139 bytes
sage: out.text.get_str()
'[0,\n 1,\n 2,\n 3,\n 4,\n 5,\n 6,\n 7,\n 8,\n 9,\n
10,\n 11,\n 12,\n 13,\n 14,\n 15,\n 16,\n 17,\n 18,\n
19,\n 20,\n 21,\n 22,\n 23,\n 24,\n 25,\n 26,\n 27,\n
28,\n 29]'
sage: out = backend.plain_text_formatter(list(range(20)), concatenate=True)
sage: out.text.get_str()
'0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19'
```

$\mathtt{set_underscore_variable}\ (obj)$

Set the builtin variable.

By default, this sets the special _ variable. Backends that organize the history differently (e.g. IPython) can override this method.

INPUT:

• ob j – result of the most recent evaluation.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.set_underscore_variable(123)
sage: _
123

sage: 'foo'
'foo'
sage: _ # indirect doctest
'foo'
```

supported_output()

Return the outputs that are supported by the backend.

Subclasses must implement this method.

OUTPUT:

Iterable of output container classes, that is, subclass of OutputBase). May be a list/tuple/set/frozenset. The order is ignored. Only used internally by the display manager.

You may return backend-specific subclasses of existing output containers. This allows you to attach backend-specific functionality to the output container.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.supported_output()
Traceback (most recent call last):
...
NotImplementedError: derived classes must implement this method
```

unicode_art_formatter(obj, **kwds)

Hook to override how unicode art is being formatted.

INPUT:

- ob j anything.
- **kwds optional keyword arguments to control the formatting. Supported are:
 - concatenate boolean (default: False). If True, the argument obj must be iterable and its entries will be concatenated. There is a single whitespace between entries.

OUTPUT:

Instance of OutputUnicodeArt containing the unicode art string representation of the object.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: out = backend.unicode_art_formatter(list(range(30)))
```

uninstall()

Hook that will be called once right before the backend is removed.

The default implementation does nothing.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendBase
sage: backend = BackendBase()
sage: backend.uninstall()
```

class sage.repl.rich_output.backend_base.BackendSimple

Bases: sage.repl.rich_output.backend_base.BackendBase

Simple Backend

This backend only supports plain text.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendSimple
sage: BackendSimple()
simple
```

display_immediately (plain_text, rich_output)

Show output without going back to the command line prompt.

INPUT:

Same as displayhook().

OUTPUT:

This backend returns nothing, it just prints to stdout.

```
sage: from sage.repl.rich_output.output_basic import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: from sage.repl.rich_output.backend_base import BackendSimple
sage: backend = BackendSimple()
sage: backend.display_immediately(plain_text, plain_text)
Example plain text output
```

supported output()

Return the outputs that are supported by the backend.

OUTPUT:

Iterable of output container classes, that is, subclass of OutputBase). This backend only supports the plain text output container.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_base import BackendSimple
sage: backend = BackendSimple()
sage: backend.supported_output()
{<class 'sage.repl.rich_output.output_basic.OutputPlainText'>}
```

5.10 Test Backend

This backend is only for doctesting purposes.

EXAMPLES:

We switch to the test backend for the remainder of this file:

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: from sage.repl.rich_output.backend_test import BackendTest, TestObject
sage: doctest_backend = dm.switch_backend(BackendTest())
sage: dm
The Sage display manager using the test backend
sage: dm._output_promotions
{<class 'sage.repl.rich_output.output_basic.OutputPlainText'>:
<class 'sage.repl.rich_output.backend_test.TestOutputPlainText'>}
sage: dm.displayhook(1/2)
1/2 [TestOutputPlainText]
TestOutputPlainText container
sage: test = TestObject()
sage: test
called the _repr_ method
sage: dm.displayhook(test)
called the _rich_repr_ method [TestOutputPlainText]
TestOutputPlainText container
```

```
class sage.repl.rich_output.backend_test.BackendTest
```

Bases: sage.repl.rich_output.backend_base.BackendBase

display_immediately (plain_text, rich_output)

Show output without going back to the command line prompt.

INPUT:

Same as displayhook().

OUTPUT

This method returns the rich output for doctesting convenience. The actual display framework ignores the return value.

```
sage: from sage.repl.rich_output.output_basic import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: from sage.repl.rich_output.backend_test import BackendTest
sage: backend = BackendTest()
sage: backend.display_immediately(plain_text, plain_text)
Example plain text output
OutputPlainText container
```

supported_output()

Return the outputs that are supported by the backend.

OUTPUT

Iterable of output container classes. Only the TestOutputPlainText output container is supported by the test backend.

EXAMPLES:

```
sage: display_manager = sage.repl.rich_output.get_display_manager()
sage: backend = display_manager._backend
sage: list(backend.supported_output())
[<class 'sage.repl.rich_output.backend_test.TestOutputPlainText'>]
```

The output of this method is used by the display manager to set up the actual supported outputs. Compare:

```
sage: list(display_manager.supported_output())
[<class 'sage.repl.rich_output.output_basic.OutputPlainText'>]
```

```
class sage.repl.rich_output.backend_test.TestObject
    Bases: sage.structure.sage_object.SageObject

Test object with both _repr_() and _rich_repr_()

class sage.repl.rich_output.backend_test.TestOutputPlainText(*args, **kwds)
    Bases: sage.repl.rich_output.output_basic.OutputPlainText
```

Backend-specific subclass of the plain text output container.

Backends must not influence how the display system constructs output containers, they can only control how the output container is displayed. In particular, we cannot override the constructor (only the <code>OutputPlainText</code> constructor is used).

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_test import TestOutputPlainText
sage: TestOutputPlainText()
Traceback (most recent call last):
AssertionError: cannot override constructor
```

print_to_stdout()

Write the data to stdout.

This is just a convenience method to help with debugging.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: test_output = dm.displayhook(123)
123 [TestOutputPlainText]
```

(continues on next page)

5.10. Test Backend 81

```
sage: type(test_output)
<class 'sage.repl.rich_output.backend_test.TestOutputPlainText'>
sage: test_output.print_to_stdout()
123 [TestOutputPlainText]
```

5.11 The backend used for doctests

This backend is active during doctests. It should mimic the behavior of the IPython command line as close as possible. Without actually launching image viewers, of course.

EXAMPLES:

```
sage: from sage.repl.rich_output import get_display_manager
sage: get_display_manager()
The Sage display manager using the doctest backend
```

```
class sage.repl.rich_output.backend_doctest.BackendDoctest
    Bases: sage.repl.rich_output.backend_base.BackendBase
    default_preferences()
```

Return the backend's display preferences

Matches the IPython command line display preferences to keep the differences between that and the doctests to a minimum.

OUTPUT:

Instance of DisplayPreferences.

EXAMPLES:

display_immediately (plain_text, rich_output)

Display object immediately

INPUT:

Same as displayhook().

EXAMPLES:

The following example does not call the displayhook. More precisely, the <code>show()</code> method returns <code>None</code> which is ignored by the displayhook. When running the example on a Sage display backend capable of displaying graphics outside of the displayhook, the plot is still shown. Nothing is shown during doctests:

```
sage: plt = plot(sin)
sage: plt
Graphics object consisting of 1 graphics primitive
sage: plt.show()
```

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.display_immediately(plt) # indirect doctest
```

displayhook (plain_text, rich_output)

Display object from displayhook

INPUT:

- plain_text instance of OutputPlainText. The plain text version of the output.
- rich_output instance of an output container class (subclass of OutputBase). Guaranteed to be one of the output containers returned from supported_output(), possibly the same as plain text.

EXAMPLES:

This ends up calling the displayhook:

```
sage: plt = plot(sin)
sage: plt
Graphics object consisting of 1 graphics primitive
sage: plt.show()

sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: dm.displayhook(plt)  # indirect doctest
Graphics object consisting of 1 graphics primitive
```

install(**kwds)

Switch to the doctest backend.

This method is being called from within switch_backend(). You should never call it by hand.

INPUT:

None of the optional keyword arguments are used in the doctest backend.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_doctest import BackendDoctest
sage: backend = BackendDoctest()
sage: backend.install()
sage: backend.uninstall()
```

supported_output()

Return the supported output types

OUTPUT:

Set of subclasses of OutputBase, the supported output container types.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_doctest import BackendDoctest
sage: from sage.repl.rich_output.output_catalog import *
sage: backend = BackendDoctest()
sage: OutputPlainText in backend.supported_output()
True
```

```
sage: OutputSceneJmol in backend.supported_output()
True
```

uninstall()

Switch away from the doctest backend

This method is being called from within switch_backend(). You should never call it by hand.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_doctest import BackendDoctest
sage: backend = BackendDoctest()
sage: backend.install()
sage: backend.uninstall()
```

validate(rich_output)

Perform checks on rich_output

INPUT:

• rich output - instance of a subclass of OutputBase.

OUTPUT:

An assertion is triggered if rich_output is invalid.

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: invalid = dm.types.OutputImagePng('invalid')
sage: backend = dm._backend; backend
sage: backend.validate(invalid)
Traceback (most recent call last):
AssertionError
sage: backend.validate(dm.types.OutputPlainText.example())
sage: backend.validate(dm.types.OutputAsciiArt.example())
sage: backend.validate(dm.types.OutputLatex.example())
sage: backend.validate(dm.types.OutputImagePng.example())
sage: backend.validate(dm.types.OutputImageGif.example())
sage: backend.validate(dm.types.OutputImageJpg.example())
sage: backend.validate(dm.types.OutputImageSvg.example())
sage: backend.validate(dm.types.OutputImagePdf.example())
sage: backend.validate(dm.types.OutputImageDvi.example())
sage: backend.validate(dm.types.OutputSceneJmol.example())
sage: backend.validate(dm.types.OutputSceneWavefront.example())
sage: backend.validate(dm.types.OutputSceneCanvas3d.example())
sage: backend.validate(dm.types.OutputVideoOgg.example())
sage: backend.validate(dm.types.OutputVideoWebM.example())
sage: backend.validate(dm.types.OutputVideoMp4.example())
sage: backend.validate(dm.types.OutputVideoFlash.example())
sage: backend.validate(dm.types.OutputVideoMatroska.example())
sage: backend.validate(dm.types.OutputVideoAvi.example())
sage: backend.validate(dm.types.OutputVideoWmv.example())
sage: backend.validate(dm.types.OutputVideoQuicktime.example())
```

5.12 IPython Backend for the Sage Rich Output System

This module defines the IPython backends for sage.repl.rich_output.

Common base for the IPython UIs

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_ipython import BackendIPython
sage: BackendIPython()._repr_()
Traceback (most recent call last):
NotImplementedError: derived classes must implement this method
```

display_immediately (plain_text, rich_output)

Show output immediately.

This method is similar to the rich output displayhook (), except that it can be invoked at any time.

INPUT:

Same as displayhook().

OUTPUT:

This method does not return anything.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_basic import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: from sage.repl.rich_output.backend_ipython import BackendIPythonNotebook
sage: backend = BackendIPythonNotebook()
sage: _ = backend.display_immediately(plain_text, plain_text)
Example plain text output
```

install(**kwds)

Switch the Sage rich output to the IPython backend

INPUT:

• shell – keyword argument. The IPython shell.

No tests since switching away from the doctest rich output backend will break the doctests.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: from sage.repl.rich_output.backend_ipython import BackendIPython
sage: backend = BackendIPython()
sage: shell = get_test_shell()
sage: backend.install(shell=shell)
sage: shell.run_cell('1+1')
2
```

$set_underscore_variable(obj)$

Set the builtin variable.

Since IPython handles the history itself, this does nothing.

INPUT:

• ob j - anything.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: from sage.repl.rich_output.backend_ipython import BackendIPython
sage: backend = BackendIPython()
sage: backend.set_underscore_variable(123)
sage: _
0
```

class sage.repl.rich_output.backend_ipython.BackendIPythonCommandline

Bases: sage.repl.rich_output.backend_ipython.BackendIPython

Backend for the IPython Command Line

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_ipython import BackendIPythonCommandline
sage: BackendIPythonCommandline()
IPython command line
```

default_preferences()

Return the backend's display preferences

The default for the commandline is to not plot graphs since the launching of an external viewer is considered too disruptive.

OUTPUT:

Instance of DisplayPreferences.

EXAMPLES:

display_immediately (plain_text, rich_output)

Show output without going back to the command line prompt.

This method is similar to the rich output displayhook(), except that it can be invoked at any time. On the Sage command line it launches viewers just like displayhook().

INPUT:

Same as displayhook().

OUTPUT:

This method does not return anything.

EXAMPLES:

```
sage: backend = BackendIPythonCommandline()
sage: backend.display_immediately(plain_text, plain_text)
Example plain text output
```

displayhook (plain_text, rich_output)

Backend implementation of the displayhook

INPUT:

- plain_text instance of OutputPlainText. The plain text version of the output.
- rich_output instance of an output container class (subclass of OutputBase). Guaranteed to be one of the output containers returned from supported_output(), possibly the same as plain_text.

OUTPUT:

The IPython commandline display hook returns the IPython display data, a pair of dictionaries. The first dictionary contains mime types as keys and the respective output as value. The second dictionary is metadata.

EXAMPLES:

is_in_terminal()

Test whether the UI is meant to run in a terminal

```
See sage.repl.rich_output.display_manager.DisplayManager.is_in_terminal() for details.
```

OUTPUT:

True for the IPython commandline.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_ipython import_

→BackendIPythonCommandline
sage: backend = BackendIPythonCommandline()
sage: backend.is_in_terminal()
True
```

launch_jmol (output_jmol, plain_text)

Launch the stand-alone jmol viewer

INPUT:

- output_jmol OutputSceneJmol. The scene to launch Jmol with.
- plain_text string. The plain text representation.

OUTPUT:

String. Human-readable message indicating that the viewer was launched.

EXAMPLES:

launch_viewer (image_file, plain_text)

Launch external viewer for the graphics file.

INPUT:

- image_file string. File name of the image file.
- plain_text string. The plain text representation of the image file.

OUTPUT:

String. Human-readable message indicating whether the viewer was launched successfully.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_ipython import_

→BackendIPythonCommandline
sage: backend = BackendIPythonCommandline()
sage: backend.launch_viewer('/path/to/foo.bar', 'Graphics object')
'Launched bar viewer for Graphics object'
```

supported_output()

Return the outputs that are supported by the IPython commandline backend.

OUTPUT:

Iterable of output container classes, that is, subclass of OutputBase). The order is ignored.

EXAMPLES:

threejs_offline_scripts()

Three.js scripts for the IPython command line

OUTPUT:

String containing script tags

EXAMPLES:

```
sage: backend.threejs_offline_scripts()
'...<script ...</pre>
```

class sage.repl.rich_output.backend_ipython.BackendIPythonNotebook

Bases: sage.repl.rich_output.backend_ipython.BackendIPython

Backend for the IPython Notebook

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_ipython import BackendIPythonNotebook
sage: BackendIPythonNotebook()
IPython notebook
```

displayhook (plain_text, rich_output)

Backend implementation of the displayhook

INPUT:

- plain_text instance of OutputPlainText. The plain text version of the output.
- rich_output instance of an output container class (subclass of OutputBase). Guaranteed to be one of the output containers returned from supported_output(), possibly the same as plain_text.

OUTPUT:

The IPython notebook display hook returns the IPython display data, a pair of dictionaries. The first dictionary contains mime types as keys and the respective output as value. The second dictionary is metadata.

EXAMPLES:

```
sage: from sage.repl.rich_output.output_basic import OutputPlainText
sage: plain_text = OutputPlainText.example()
sage: from sage.repl.rich_output.backend_ipython import BackendIPythonNotebook
sage: backend = BackendIPythonNotebook()
sage: backend.displayhook(plain_text, plain_text)
({u'text/plain': u'Example plain text output'}, {})
```

supported_output()

Return the outputs that are supported by the IPython notebook backend.

OUTPUT:

Iterable of output container classes, that is, subclass of OutputBase). The order is ignored.

EXAMPLES:

```
sage: OutputImageGif in supp
True
```

threejs_offline_scripts()

Three.js scripts for the IPython notebook

OUTPUT:

String containing script tags

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_ipython import BackendIPythonNotebook
sage: backend = BackendIPythonNotebook()
sage: backend.threejs_offline_scripts()
'...<script src="/nbextensions/threejs/three.min...<\/script>...'
```

5.13 SageNB Backend for the Sage Rich Output System

This module defines the IPython backends for sage.repl.rich_output.

EXAMPLES:

Install the SageNB displayhook while doctesting for the rest of this file. This somewhat odd incantation is how SageNB installed its displayhook before:

```
sage: from sage.misc.displayhook import DisplayHook
sage: import sys
sage: sys.displayhook = DisplayHook()

sage: from sage.repl.rich_output import get_display_manager
sage: get_display_manager()
The Sage display manager using the SageNB backend
```

We also enable the SageNB magic global variable:

```
sage: import sage.plot.plot
sage: sage.plot.plot.EMBEDDED_MODE = True
```

And switch to a temporary directory so our current directory will not get cluttered with temporary files:

```
sage: os.chdir(tmp_dir())
```

The SageNB notebook is based on saving data files with predictable filenames:

```
sage: os.path.exists('sage0.png')
False
sage: Graphics()
sage: os.path.exists('sage0.png')
True
sage: os.remove('sage0.png')
```

Tables are typeset as html in SageNB:

class sage.repl.rich_output.backend_sagenb.BackendSageNB

Bases: sage.repl.rich_output.backend_base.BackendBase

display_immediately (plain_text, rich_output)

Show output without waiting for the prompt.

INPUT:

- plain_text instance of OutputPlainText. The plain text version of the output.
- rich_output instance of an output container class (subclass of OutputBase). Guaranteed to be one of the output containers returned from supported_output(), possibly the same as plain_text.

OUTPUT:

This method does not return anything.

EXAMPLES:

embed_image (output_buffer, file_ext)

Embed Image in the SageNB worksheet

SageNB scans per-cell directories for image files, so all we have to do here is to save the image at the right place.

INPUT:

- output_buffer Buffer. A buffer holding the image data.
- file_ext string. The file extension to use for saving the image.

OUTPUT:

Nothing is returned. The image file is saved in the appropriate place for SageNB.

```
sage: from sage.repl.rich_output import get_display_manager
sage: dm = get_display_manager()
sage: rich_output = dm.types.OutputImagePng.example()
sage: os.path.exists('sage0.png')
False
sage: dm._backend.embed_image(rich_output.png, '.png')
sage: os.path.exists('sage0.png')
True
```

embed video (video output)

supported output()

Return the outputs that are supported by the SageNB backend.

OUTPUT:

Iterable of output container classes, that is, subclass of OutputBase). The order is ignored.

EXAMPLES:

threejs_offline_scripts()

Three.js scripts for the Sage notebook

OUTPUT:

String containing script tags

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import BackendSageNB
sage: backend = BackendSageNB()
sage: backend.threejs_offline_scripts()
'...<script ...</script>...'
```

view_png)

Bases: sage.repl.rich_output.output_graphics3d.OutputSceneJmol

Adapt Jmol rich output container for SageNB.

For legacy reasons, SageNB expects Jmol files saved under strange names. This class takes care of that.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: SageNbOutputSceneJmol.example()
SageNbOutputSceneJmol container
```

embed()

Save all files necessary to embed jmol

EXAMPLES:

Switch to a new empty temporary directory:

```
sage: os.chdir(tmp_dir())

sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: j = SageNbOutputSceneJmol.example()
sage: j.embed() # py2 - requires sagenb
sage: sorted(os.listdir('.')) # py2
['.jmol_images', 'sage0-size32-...jmol.zip', 'sage0-size32.jmol']
sage: sorted(os.listdir('.jmol_images')) # py2
['sage0-size32.jmol.png']
```

preview_filename()

Return the filename for the png preview

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: j = SageNbOutputSceneJmol.example()
sage: j.preview_filename()
'./.jmol_images/sage0-size32.jmol.png'
```

sagenb_launch_script_filename()

Return the launch script filename used by SageNB

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: j = SageNbOutputSceneJmol.example()
sage: j.sagenb_launch_script_filename()
'sage0-size32.jmol'
```

save_launch_script()

Save the Jmol launch script

See sagenb_launch_script_filename().

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: j = SageNbOutputSceneJmol.example()
sage: os.path.exists('sage0-size32.jmol')
False
sage: j.save_launch_script() # py2: requires sagenb
sage: os.path.exists('sage0-size32.jmol') # py2
True
```

save_preview()

Save the preview PNG image

See preview_filename().

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: j = SageNbOutputSceneJmol.example()
sage: import shutil
sage: shutil.rmtree('.jmol_images', ignore_errors=True)
sage: j.save_preview()
sage: os.listdir('.jmol_images') # py2
['sage1-size32.jmol.png']
```

scene_zip_filename()

Return the filename for the scene zip archive

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.rich_output.backend_sagenb import SageNbOutputSceneJmol
sage: j = SageNbOutputSceneJmol.example()
sage: j.scene_zip_filename()
'sage0-size32-....jmol.zip'
```

sage.repl.rich_output.backend_sagenb.world_readable(filename)

All SageNB temporary files must be world-readable.

Discussion of this design choice can be found at trac ticket #17743.

EXAMPLES:

```
sage: import os, stat
sage: f = tmp_filename()
```

At least on a sane system the temporary files are only readable by the user, but not by others in the group or total strangers:

```
sage: mode = os.stat(f).st_mode
sage: bool(mode & stat.S_IRUSR), bool(mode & stat.S_IRGRP), bool(mode & stat.S_
→IROTH) # random output
(True, False, False)
```

This function disables that protection:

CHAPTER

SIX

MISCELLANEOUS

6.1 Extra Readline Commands

Warning: The feature described here is no longer available in Sage, as IPython upon which Sage's command line interface is based adopted prompt_toolkit as a replacement of readline as of IPython version 5.0

The following extra readline commands are available in Sage:

- operate-and-get-next
- history-search-backward-and-save
- history-search-forward-and-save

The operate-and-get-next command accepts the input line and fetches the next line from the history. This is the same command with the same name in the Bash shell.

The history-search-backward-and-save command searches backward in the history for the string of characters from the start of the input line to the current cursor position, and fetches the first line found. If the cursor is at the start of the line, the previous line is fetched. The position of the fetched line is saved internally, and the next search begins at the saved position.

The history-search-forward-and-save command behaves similarly but forward.

The previous two commands is best used in tandem to fetch a block of lines from the history, by searching backward the first line of the block and then issuing the forward command as many times as needed. They are intended to replace the history-search-backward command and the history-search-forward command provided by the GNU readline library used in Sage.

To bind these commands with keys, insert the relevant lines into the IPython configuration file <code>\$DOT_SAGE/ipython-*/profile_default/ipython_config.py</code>. Note that <code>\$DOT_SAGE</code> is <code>\$HOME/.sage</code> by default. For example,

```
c = get_config()
c.InteractiveShell.readline_parse_and_bind = [
    '"\C-o": operate-and-get-next',
    '"\e[A": history-search-backward-and-save',
    '"\e[B": history-search-forward-and-save'
]
```

binds the three commands with the control-o key, the up arrow key, and the down arrow key, respectively. Warning: Sometimes, these keys may be bound to do other actions by the terminal and does not reach to the readline properly (check this by running stty -a and reading the cchars section). Then you may need to turn off these bindings

before the new readline commands work fine . A prominent case is when control-o is bound to discard by the terminal. You can turn this off by running stty discard undef.

AUTHORS:

- Kwankyu Lee (2010-11-23): initial version
- Kwankyu Lee (2013-06-05): updated for the new IPython configuration format.

6.2 Sage's IPython Modifications

This module contains all of Sage's customizations to the IPython interpreter. These changes consist of the following major components:

- SageTerminalApp
- SageInteractiveShell
- SageTerminalInteractiveShell
- interface shell embed()

6.2.1 SageTerminalApp

This is the main application object. It is used by the \$SAGE_LOCAL/bin/sage-ipython script to start the Sage command-line. It's primary purpose is to

- Initialize the SageTerminalInteractiveShell.
- Provide default configuration options for the shell, and its subcomponents. These work with (and can be overridden by) IPython's configuration system.
- Load the Sage ipython extension (which does things like preparsing, add magics, etc.).
- Provide a custom SageCrashHandler to give the user instructions on how to report the crash to the Sage support mailing list.

6.2.2 SageInteractiveShell

The SageInteractiveShell object is the object responsible for accepting input from the user and evaluating it. From the command-line, this object can be retrieved by running:

```
sage: shell = get_ipython() # not tested
```

Any input is preprocessed and evaluated inside the shell.run_cell method. If the command line processing does not do what you want it to do, you can step through it in the debugger:

```
sage: %debug shell.run_cell('?') # not tested
```

The SageInteractiveShell provides the following customizations:

• Modify the libraries before calling system commands. See system_raw().

6.2.3 SageTerminalInteractiveShell

The SageTerminalInteractiveShell is a close relative of SageInteractiveShell that is specialized for running in a terminal. In particular, running commands like !ls will directly write to stdout. Technically, the system attribute will point to system_raw instead of system_piped.

6.2.4 Interface Shell

The function <code>interface_shell_embed()</code> takes a <code>Interface</code> object and returns an embeddable IPython shell which can be used to directly interact with that shell. The bulk of this functionality is provided through <code>InterfaceShellTransformer</code>.

```
class sage.repl.interpreter.InterfaceShellTransformer(*args, **kwds)
    Bases: IPython.core.prefilter.PrefilterTransformer
    Initialize this class. All of the arguments get passed to PrefilterTransformer.__init__().
```

temporary_objects

a list of hold onto interface objects and keep them from being garbage collected

See also:

interface_shell_embed()

EXAMPLES:

```
sage: from sage.repl.interpreter import interface_shell_embed
sage: shell = interface_shell_embed(maxima)
sage: ift = shell.prefilter_manager.transformers[0]
sage: ift.temporary_objects
set()
sage: ift._sage_import_re.findall('sage(a) + maxima(b)')
['a', 'b']
```

preparse_imports_from_sage (line)

Finds occurrences of strings such as sage (object) in *line*, converts object to shell.interface, and replaces those strings with their identifier in the new system. This also works with strings such as maxima (object) if shell.interface is maxima.

Parameters line (string) – the line to transform

Warning: This does not parse nested parentheses correctly. Thus, lines like sage (a.foo()) will not work correctly. This can't be done in generality with regular expressions.

EXAMPLES:

transform(line, continue_prompt)

Evaluates line in shell.interface and returns a string representing the result of that evaluation.

Parameters

- line (string) the line to be transformed and evaluated
- continue_prompt (bool) is this line a continuation in a sequence of multiline input?

EXAMPLES:

```
sage: from sage.repl.interpreter import interface_shell_embed,...
→InterfaceShellTransformer
sage: shell = interface_shell_embed(maxima)
sage: ift = InterfaceShellTransformer(shell=shell, config=shell.config,...
→prefilter_manager=shell.prefilter_manager)
sage: ift.transform('2+2', False) # note: output contains triple quotation.
→marks
'sage.misc.all.logstr("""4""")'
sage: ift.shell.ex('a = 4')
sage: ift.transform(r'sage(a)+4', False)
'sage.misc.all.logstr("""8""")'
sage: ift.temporary_objects
set()
sage: shell = interface_shell_embed(gap)
sage: ift = InterfaceShellTransformer(shell=shell, config=shell.config,_
→prefilter_manager=shell.prefilter_manager)
sage: ift.transform('2+2', False)
'sage.misc.all.logstr("""4""")'
```

class sage.repl.interpreter.SageCrashHandler(app)

Bases: IPython.terminal.ipapp.IPAppCrashHandler

A custom CrashHandler which gives the user instructions on how to post the problem to sage-support.

```
sage: from sage.repl.interpreter import SageTerminalApp, SageCrashHandler
sage: app = SageTerminalApp.instance()
sage: sch = SageCrashHandler(app); sch
<sage.repl.interpreter.SageCrashHandler object at 0x...>
sage: sorted(sch.info.items())
[('app_name', u'Sage'),
    ('bug_tracker', 'http://trac.sagemath.org'),
    ('contact_email', 'sage-support@googlegroups.com'),
    ('contact_name', 'sage-support'),
    ('crash_report_fname', u'Crash_report_Sage.txt')]
```

IPython Shell for the Sage IPython Notebook

The doctests are not tested since they would change the current rich output backend away from the doctest rich output backend.

EXAMPLES:

```
sage: from sage.repl.interpreter import SageNotebookInteractiveShell
sage: SageNotebookInteractiveShell() # not tested
<sage.repl.interpreter.SageNotebookInteractiveShell object at 0x...>
```

init_display_formatter()

Switch to the Sage IPython notebook rich output backend

EXAMPLES:

```
sage: from sage.repl.interpreter import SageNotebookInteractiveShell
sage: SageNotebookInteractiveShell().init_display_formatter() # not tested
```

 $\verb|sage.repl.interpreter.SagePreparseTransformer(**kwargs)|$

EXAMPLES:

```
sage: from sage.repl.interpreter import SagePreparseTransformer
sage: spt = SagePreparseTransformer()
sage: spt.push('1+1r+2.3^2.3r')
"Integer(1)+1+RealNumber('2.3')**2.3"
sage: preparser(False)
sage: spt.push('2.3^2')
'2.3^2'
```

sage.repl.interpreter.SagePromptTransformer(**kwargs)

Strip the sage:/...: prompts of Sage.

EXAMPLES:

```
sage: from sage.repl.interpreter import SagePromptTransformer
sage: spt = SagePromptTransformer()
sage: spt.push("sage: 2 + 2")
'2 + 2'
sage: spt.push('')
''
sage: spt.push("...: 2+2")
'2+2'
```

This should strip multiple prompts: see trac ticket #16297:

```
sage: spt.push("sage: sage: 2+2")
'2+2'
sage: spt.push(" sage: ....: 2+2")
'2+2'
```

The prompt contains a trailing space. Extra spaces between the last prompt and the remainder should not be stripped:

```
sage: spt.push(" sage: ...: 2+2")
' 2+2'
```

We test that the input transformer is enabled on the Sage command line:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('sage: a = 123')  # single line
sage: shell.run_cell('sage: a = [\n... 123]')  # old-style multi-line
sage: shell.run_cell('sage: a = [\n...: 123]')  # new-style multi-line
```

We test that trac ticket #16196 is resolved:

```
sage: shell.run_cell(' sage: 1+1')
2
sage: shell.quit()
```

```
{\bf class} \ {\tt sage.repl.interpreter.SageShellOverride}
```

Bases: object

Mixin to override methods in IPython's [Terminal]InteractiveShell classes.

```
show_usage()
```

Print the basic Sage usage.

This method ends up being called when you enter? and nothing else on the command line.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('?')
Welcome to Sage ...
sage: shell.quit()
```

system_raw(cmd)

Run a system command.

This is equivalent to the sage-native-execute shell script.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.system_raw('false')
sage: shell.user_ns['_exit_code'] > 0
True
sage: shell.system_raw('true')
sage: shell.user_ns['_exit_code']
0
sage: shell.system_raw('R --version')
R version ...
sage: shell.user_ns['_exit_code']
0
sage: shell.user_ns['_exit_code']
```

```
class sage.repl.interpreter.SageTerminalApp (**kwargs)
```

Bases: IPython.terminal.ipapp.TerminalIPythonApp

crash handler class

alias of SageCrashHandler

init_shell()

Initialize the SageInteractiveShell instance.

Note: This code is based on TerminalIPythonApp.init_shell().

EXAMPLES:

```
sage: from sage.repl.interpreter import SageTerminalApp
sage: app = SageTerminalApp.instance()
sage: app.shell
<sage.repl.interpreter.SageTestShell object at 0x...>
```

load_config_file(*args, **kwds)

Merges a config file with the default sage config.

Note: This code is based on Application.update_config().

shell class

A trait whose value must be a subclass of a specified class.

test shell

A boolean (True, False) trait.

```
class sage.repl.interpreter.SageTerminalInteractiveShell(*args, **kwargs)
```

Bases: sage.repl.interpreter.SageShellOverride, IPython.terminal.interactiveshell.TerminalInteractiveShell

IPython Shell for the Sage IPython Commandline Interface

The doctests are not tested since they would change the current rich output backend away from the doctest rich output backend.

EXAMPLES:

```
sage: from sage.repl.interpreter import SageTerminalInteractiveShell
sage: SageTerminalInteractiveShell() # not tested
<sage.repl.interpreter.SageNotebookInteractiveShell object at 0x...>
```

init_display_formatter()

Switch to the Sage IPython commandline rich output backend

EXAMPLES:

```
sage: from sage.repl.interpreter import SageTerminalInteractiveShell
sage: SageTerminalInteractiveShell().init_display_formatter() # not tested
```

```
class sage.repl.interpreter.SageTestShell(*args, **kwargs)
```

Bases: sage.repl.interpreter.SageShellOverride, IPython.terminal.interactiveshell.TerminalInteractiveShell

Test Shell

Care must be taken in these doctests to quit the test shell in order to switch back the rich output display backend to the doctest backend.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell(); shell
<sage.repl.interpreter.SageTestShell object at 0x...>
sage: shell.quit()
```

init_display_formatter()

Switch to the Sage IPython commandline rich output backend

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell(); shell
<sage.repl.interpreter.SageTestShell object at 0x...>
sage: shell.quit()
sage: shell.init_display_formatter()
sage: shell.quit()
```

quit()

Quit the test shell.

To make the test shell as realistic as possible, we switch to the <code>BackendIPythonCommandline</code> display backend. This method restores the previous display backend, which is the <code>BackendDoctest</code> during doctests.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: from sage.repl.rich_output import get_display_manager
sage: get_display_manager()
The Sage display manager using the doctest backend

sage: shell = get_test_shell()
sage: get_display_manager()
The Sage display manager using the IPython command line backend

sage: shell.quit()
sage: get_display_manager()
The Sage display manager using the doctest backend
```

run_cell(*args, **kwds)

Run IPython cell

Starting with IPython-3.0, this returns an success/failure information. Since it is more convenient for doctests, we ignore it.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: rc = shell.run_cell('2^50')
1125899906842624
sage: rc is None
True
sage: shell.quit()
```

```
sage.repl.interpreter.embedded()
```

Returns True if Sage is being run from the notebook.

EXAMPLES:

```
sage: from sage.repl.interpreter import embedded
sage: embedded()
False
```

```
sage.repl.interpreter.get_test_shell()
```

Returns a IPython shell that can be used in testing the functions in this module.

OUTPUT:

An IPython shell

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell(); shell
<sage.repl.interpreter.SageTestShell object at 0x...>
sage: shell.parent.shell_class
<class 'sage.repl.interpreter.SageTestShell'>
sage: shell.parent.test_shell
True
sage: shell.quit()
```

sage.repl.interpreter.interface_shell_embed(interface)

Returns an IPython shell which uses a Sage interface on the backend to perform the evaluations. It uses InterfaceShellTransformer to transform the input into the appropriate interface.eval(...) input.

INPUT:

• interface - A Sage PExpect interface instance.

EXAMPLES:

sage.repl.interpreter.preparser(on=True)

Turn on or off the Sage preparser.

Parameters on (bool) – if True turn on preparsing; if False, turn it off.

```
sage: 2/3
2/3
sage: preparser(False)
sage: 2/3 # not tested since doctests are always preparsed
0
sage: preparser(True)
sage: 2^3
8
```

6.3 Sage's IPython Extension

A Sage extension which adds sage-specific features:

```
· magics
```

- %crun
- %runfile
- %attach
- %display
- %mode (like %maxima, etc.)
- %%cython
- %%fortran
- · preparsing of input
- loading Sage library
- running init.sage
- · changing prompt to Sage prompt
- · Display hook

```
\begin{tabular}{ll} \textbf{class} & \texttt{sage.repl.ipython\_extension.SageCustomizations} \ (\textit{shell=None}) \\ & \textbf{Bases: object} \end{tabular}
```

Initialize the Sage plugin.

```
static all_globals()
```

Return a Python module containing all globals which should be made available to the user.

EXAMPLES:

```
sage: from sage.repl.ipython_extension import SageCustomizations
sage: SageCustomizations.all_globals()
<module 'sage.all_cmdline' ...>
```

```
init_environment()
```

Set up Sage command-line environment

```
init_inspector()
```

```
init_line_transforms()
```

Set up transforms (like the preparser).

```
register_interface_magics()
```

Register magics for each of the Sage interfaces

```
run_init()
```

Run Sage's initial startup file.

```
set_quit_hook()
```

Set the exit hook to cleanly exit Sage.

```
class sage.repl.ipython_extension.SageJupyterCustomizations(shell=None)
```

Bases: sage.repl.ipython_extension.SageCustomizations

static all globals()

Return a Python module containing all globals which should be made available to the user when running the Jupyter notebook.

EXAMPLES:

```
sage: from sage.repl.ipython_extension import SageJupyterCustomizations
sage: SageJupyterCustomizations.all_globals()
<module 'sage.repl.ipython_kernel.all_jupyter' ...>
```

class sage.repl.ipython_extension.SageMagics(shell=None, **kwargs)
 Bases: IPython.core.magic.Magics

attach(s)

Attach the code contained in the file s.

This is designed to be used from the command line as %attach /path/to/file.

• s – string. The file to be attached

EXAMPLES:

```
sage: import os
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: tmp = os.path.normpath(os.path.join(SAGE_TMP, 'run_cell.py'))
sage: f = open(tmp, 'w'); _ = f.write('a = 2\n'); f.close()
sage: shell.run_cell('%attach ' + tmp)
sage: shell.run_cell('a')
2
sage: sleep(1) # filesystem timestamp granularity
sage: f = open(tmp, 'w'); _ = f.write('a = 3\n'); f.close()
```

Note that the doctests are never really at the command prompt, so we call the input hook manually:

$\mathtt{crun}(s)$

Profile C function calls

INPUT:

• s – string. Sage command to profile.

EXAMPLES:

(continues on next page)

```
PROFILE: interrupts/evictions/bytes = ...
Using local file ...
Using local file ...
sage: shell.quit()
```

cython (line, cell)

Cython cell magic

This is syntactic sugar on the cython_compile() function.

INPUT:

- line ignored.
- cell string. The Cython source code to process.

OUTPUT:

None. The Cython code is compiled and loaded.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('''
...: %%cython
...: def f():
...: print('test')
...: '''')
sage: f()
test
```

display (args)

A magic command to switch between simple display and ASCII art display.

• args - string. See sage.misc.display_hook.DisplayHookBase.set_display() for allowed values. If the mode is ascii_art, it can optionally be followed by a width.

How to use: if you want activate the ASCII art mod:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('%display ascii_art')
```

That means you don't have to use ascii_art() to get an ASCII art output:

Then when you want return in 'textual mode':

```
sage: shell.run_cell('%display text plain')
sage: shell.run_cell('%display plain')  # shortcut for "text plain"
sage: shell.run_cell('sum(i^2*x^i, i, 0, 10)')
100*x^10 + 81*x^9 + 64*x^8 + 49*x^7 + 36*x^6 + 25*x^5 + 16*x^4 + 9*x^3 + 4*x^4 + 2 + x
```

Sometime you could have to use a special output width and you could specify it:

```
sage: shell.run_cell('%display ascii_art')
sage: shell.run_cell('StandardTableaux(4).list()')
                                                      1 4
[
              1 3 4 1 2 4 1 2 3 1 3 1 2 2
[
 1 2 3 4, 2
                           , 4
                                         2 4, 3 4,
                     3
                                                     3
               1 ]
  1 3 1 2
             2 ]
        3
               3 1
        4 ,
             4 ]
sage: shell.run_cell('%display ascii_art 50')
sage: shell.run_cell('StandardTableaux(4).list()')
[
              1 3 4
                       1 2 4
                                1 2 3
[
  1 2 3 4,
              2
                                4
                       3
                                  1 ]
                    1 3
                           1 2
              1
                                  2]
       1 2
              2
                     2
                           3
                                  3 ]
      3 4,
              3
                    4
                          4
                                4 ]
```

As yet another option, typeset mode. This is used in the emacs interface:

```
sage: shell.run_cell('%display text latex')
sage: shell.run_cell('1/2')
\newcommand{\Bold}[1]{\mathbf{#1}}\frac{1}{2}
```

Switch back:

```
sage: shell.run_cell('%display default')
```

Switch graphics to default to vector or raster graphics file formats:

```
sage: shell.run_cell('%display graphics vector')
```

fortran (line, cell)

Fortran cell magic.

This is syntactic sugar on the fortran () function.

INPUT:

- line ignored.
- cell string. The Cython source code to process.

OUTPUT:

None. The Fortran code is compiled and loaded.

EXAMPLES:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('''
...: %%fortran
...: C FILE: FIB1.F
...: SUBROUTINE FIB(A,N)
```

(continues on next page)

```
....: C
....: C
            CALCULATE FIRST N FIBONACCI NUMBERS
....: C
           INTEGER N
. . . . :
. . . . :
           REAL*8 A(N)
           DO I=1, N
. . . . :
              IF (I.EQ.1) THEN
. . . . :
. . . . :
                 A(I) = 0.0D0
              ELSEIF (I.EQ.2) THEN
. . . . :
                A(I) = 1.0D0
. . . . :
              ELSE
                A(I) = A(I-1) + A(I-2)
              ENDIF
. . . . :
           ENDDO
           END
. . . . :
....: C END FILE FIB1.F
...: ''')
sage: fib
<fortran object>
sage: from numpy import array
sage: a = array(range(10), dtype=float)
sage: fib(a, 10)
sage: a
array([ 0., 1., 1., 2., 3., 5., 8., 13., 21., 34.])
```

iload(args)

A magic command to interactively load a file as in MAGMA.

• args – string. The file to be interactively loaded

Note: Currently, this cannot be completely doctested as it relies on raw_input().

EXAMPLES:

runfile(s)

Execute the code contained in the file s.

This is designed to be used from the command line as %runfile /path/to/file.

• s – string. The file to be loaded.

EXAMPLES:

```
sage: import os
sage: from sage.repl.interpreter import get_test_shell
sage: from sage.misc.all import tmp_dir
sage: shell = get_test_shell()
sage: tmp = os.path.join(tmp_dir(), 'run_cell.py')
sage: f = open(tmp, 'w'); _ = f.write('a = 2\n'); f.close()
```

(continues on next page)

```
sage: shell.run_cell('%runfile '+tmp)
sage: shell.run_cell('a')
2
sage: shell.quit()
```

sage.repl.ipython_extension.load_ipython_extension(*args, **kwargs)
Load the extension in IPython.

```
sage.repl.ipython_extension.run_once (func)
Runs a function (successfully) only once.
```

The running can be reset by setting the has_run attribute to False

6.4 Magics for each of the Sage interfaces

This module defines magic functions for interpreters. As an example, consider the GAP interpreter which can evaluate a gap command given as a string:

```
sage: gap('SymmetricGroup(4)') # not tested
SymmetricGroup([ 1 .. 4 ] )
```

Magics are syntactic sugar to avoid writing the Python string. They are either called as line magics:

```
sage: %gap SymmetricGroup(4) # not tested
```

or as cell magics, that is, spanning multiple lines:

```
sage: %%gap # not tested
....: G := SymmetricGroup(4);
....: Display(G);
```

Note that the cell magic needs semicolons, this is required by the GAP language to separate multiple commands.

```
class sage.repl.interface_magic.InterfaceMagic(name, interface)
    Bases: object
```

Interface Magic

This class is a wrapper around interface objects to provide them with magics.

INPUT:

- name string. The interface name
- interface sage.interfaces.expect.Expect. The interface to wrap.

EXAMPLES:

```
sage: from sage.repl.interface_magic import InterfaceMagic
sage: InterfaceMagic.find('gap')
<sage.repl.interface_magic.InterfaceMagic object at 0x...>
```

```
classmethod all iter()
```

Iterate over the available interfaces

```
sage: from sage.repl.interface_magic import InterfaceMagic
sage: next(InterfaceMagic.all_iter())
<sage.repl.interface_magic.InterfaceMagic object at 0x...>
```

cell_magic_factory()

Factory for cell magic

OUTPUT:

A function suitable to be used as cell magic.

EXAMPLES:

```
sage: from sage.repl.interface_magic import InterfaceMagic
sage: cell_magic = InterfaceMagic.find('gap').cell_magic_factory()
sage: output = cell_magic('', '1+1;')
2
sage: output is None
True
sage: cell_magic('foo', '1+1;')
Traceback (most recent call last):
...
SyntaxError: Interface magics have no options, got "foo"
```

This is how the built cell magic is used in practice:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('%%gap\nG:=SymmetricGroup(5);\n1+1;Order(G);')
Sym([1..5])
2
120
sage: shell.run_cell('%%gap foo\n1+1;\n')
File "<string>", line unknown
SyntaxError: Interface magics have no options, got "foo"

sage: shell.run_cell('%%gap?')
Docstring:
Interact with gap

The cell magic %%gap sends multiple lines to the gap interface.
...
```

classmethod find(name)

Find a particular magic by name

This method is for doctesting purposes only.

INPUT:

• name – string. The name of the interface magic to search for.

OUTPUT:

The corresponding InterfaceMagic instance.

```
sage: from sage.repl.interface_magic import InterfaceMagic
sage: InterfaceMagic.find('gap')
<sage.repl.interface_magic.InterfaceMagic object at 0x...>
```

```
line_magic_factory()
```

Factory for line magic

OUTPUT:

A function suitable to be used as line magic.

EXAMPLES:

```
sage: from sage.repl.interface_magic import InterfaceMagic
sage: line_magic = InterfaceMagic.find('gap').line_magic_factory()
sage: output = line_magic('1+1')
sage: output
2
sage: type(output)
<class 'sage.interfaces.gap.GapElement'>
```

This is how the built line magic is used in practice:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell('%gap 1+1')
2
sage: shell.run_cell('%gap?')
Docstring:
Interact with gap
The line magic %gap sends a single line to the gap interface.
...
```

classmethod register_all(shell=None)

Register all available interfaces

EXAMPLES:

```
sage: class MockShell():
....: magics = set()
        def register_magic_function(self, fn, magic_name, magic_kind):
. . . . :
             self.magics.add(magic_name)
            print (magic_name, magic_kind)
sage: from sage.repl.interface_magic import InterfaceMagic
sage: InterfaceMagic.register_all(MockShell())
                                                # random output
('gp', 'line')
('gp', 'cell')
('mwrank', 'line')
('mwrank', 'cell')
('maxima', 'line')
('maxima', 'cell')
sage: 'gap' in MockShell.magics
sage: 'maxima' in MockShell.magics
True
```

6.5 Interacts for the Sage Jupyter notebook

This is mostly the same as the stock ipywidgets.interact, but with some customizations for Sage.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.interact import interact
sage: @interact
....: def f(x=(0,10)):
....: pass
Interactive function <function f at ...> with 1 widget
    x: IntSlider(value=5, description=u'x', max=10)
sage: f.widget.children
(IntSlider(value=5, description=u'x', max=10), Output())
```

```
class sage.repl.ipython_kernel.interact.sage_interactive(*args, **kwds)
```

 $Bases: \verb"ipywidgets.widgets." interaction. \verb"interactive" \\$

Wrapper around the ipywidgets interactive which handles some SageNB specifics.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.interact import sage_interactive
sage: def myfunc(x=10, y="hello", z=None): pass
sage: sage_interactive(myfunc, x=(0,100), z=["one", "two", "three"])
Interactive function <function myfunc at ...> with 3 widgets
    x: IntSlider(value=10, description=u'x')
    y: Text(value=u'hello', description=u'y')
    z: Dropdown(description=u'z', options=('one', 'two', 'three'), value=None)
```

signature()

Return the fixed signature of the interactive function (after a possible auto_update parameter was removed).

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.interact import sage_interactive
sage: def myfunc(x=[1,2,3], auto_update=False): pass
sage: sage_interactive(myfunc).signature().parameters # py2
OrderedDict([('x', <Parameter ... 'x'>)])
sage: sage_interactive(myfunc).signature().parameters # py3
mappingproxy({'x': <Parameter "x=[1, 2, 3]">})
```

classmethod widget_from_iterable(abbrev, *args, **kwds)

Convert an unspecified iterable to a widget.

This behaves like in ipywidgets, except that an iterator (like a generator object) becomes a SelectionSlider.

```
sage: from sage.repl.ipython_kernel.interact import sage_interactive
sage: sage_interactive.widget_from_iterable([1..5])
Dropdown(options=(1, 2, 3, 4, 5), value=1)
sage: sage_interactive.widget_from_iterable(iter([1..5]))
SelectionSlider(options=(1, 2, 3, 4, 5), value=1)
sage: sage_interactive.widget_from_iterable((1..5))
SelectionSlider(options=(1, 2, 3, 4, 5), value=1)
sage: sage_interactive.widget_from_iterable(x for x in [1..5])
SelectionSlider(options=(1, 2, 3, 4, 5), value=1)
sage: def gen():
...:     yield 1; yield 2; yield 3; yield 4; yield 5
sage: sage_interactive.widget_from_iterable(gen())
SelectionSlider(options=(1, 2, 3, 4, 5), value=1)
```

classmethod widget_from_single_value(abbrev, *args, **kwds)

Convert a single value (i.e. a non-iterable) to a widget.

This supports the Sage Color class. Any unknown type is changed to a string for evaluating. This is meant to support symbolic expressions like sin(x).

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.interact import sage_interactive
sage: sage_interactive.widget_from_single_value("sin(x)")
Text(value=u'sin(x)')
sage: sage_interactive.widget_from_single_value(sin(x))
EvalText(value=u'sin(x)')
sage: from sage.plot.colors import Color
sage: sage_interactive.widget_from_single_value(Color('cornflowerblue'))
SageColorPicker(value='#6495ed')
```

classmethod widget_from_tuple (abbrev, *args, **kwds)

Convert a tuple to a widget.

This supports two SageNB extensions: (description, abbrev) if description is a string and (default, abbrev) if abbrev is not a single value.

Symbolic expressions are changed to a floating-point number.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.interact import sage_interactive
sage: sage_interactive.widget_from_tuple( (0, 10) )
IntSlider(value=5, max=10)
sage: sage_interactive.widget_from_tuple( ("number", (0, 10)) )
IntSlider(value=5, description=u'number', max=10)
sage: sage_interactive.widget_from_tuple( (3, (0, 10)) )
IntSlider(value=3, max=10)
sage: sage_interactive.widget_from_tuple( (2, dict(one=1, two=2, three=3)) )
Dropdown(index=1, options={'three': 3, 'two': 2, 'one': 1}, value=2)
sage: sage_interactive.widget_from_tuple( (sqrt(2), pi) )
FloatSlider(value=2.277903107981444, max=3.141592653589793, min=1.

$\times 4142135623730951)$
```

6.6 Widgets to be used for the Sage Jupyter notebook

These are all based on widgets from ipywidgets, changing or combining existing widgets.

A ipywidgets. Text widget which evaluates (using sage_eval()) its contents and applies an optional transformation.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import EvalText
sage: w = EvalText(value="pi", transform=lambda x: x^2)
sage: w
EvalText(value=u'pi')
```

(continues on next page)

```
sage: w.get_interact_value()
pi^2
```

A ipywidgets. Textarea widget which evaluates (using $sage_eval()$) its contents and applies an optional transformation.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import EvalTextarea
sage: w = EvalTextarea(value="pi", transform=lambda x: x^2)
sage: w
EvalTextarea(value=u'pi')
sage: w.get_interact_value()
pi^2
```

```
class sage.repl.ipython_kernel.widgets.EvalWidget(*args, **kwds)
    Bases: sage.repl.ipython_kernel.widgets.TransformWidget
```

A mixin class for a widget to evaluate (using sage_eval()) the widget value and possibly transform it like TransformWidget.

EXAMPLES:

```
sage: from ipywidgets import ToggleButtons
sage: from sage.repl.ipython_kernel.widgets import EvalWidget
sage: class EvalToggleButtons(EvalWidget, ToggleButtons): pass
sage: w = EvalToggleButtons(options=["pi", "e"], transform=lambda x: x+x)
sage: w
EvalToggleButtons(options=('pi', 'e'), value='pi')
sage: w.get_interact_value()
2*pi
```

get value()

Evaluate the bare widget value using sage_eval().

EXAMPLES:

```
sage: from ipywidgets import Dropdown
sage: from sage.repl.ipython_kernel.widgets import EvalWidget
sage: class EvalDropdown(EvalWidget, Dropdown): pass
sage: w = EvalDropdown(options=["the_answer"], transform=RR)
sage: w
EvalDropdown(options=('the_answer',), value='the_answer')
sage: the_answer = 42
sage: w.get_value()
42
sage: w.get_interact_value()
42.0000000000000
```

Bases: sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widgets.widgets.ValueWidget

A square grid of widgets whose value is a list of lists of the values of the individual widgets.

This is usually created using the input_grid() function.

EXAMPLES:

description

A trait for unicode strings.

value

An instance of a Python list.

```
class sage.repl.ipython_kernel.widgets.HTMLText(value=None, **kwargs)
Bases: ipywidgets.widgets.widget string.HTML
```

A HTML widget whose description is always empty.

This is used to display arbitrary HTML text in interacts without a label. The text_control() function from SageNB is an alias of HTMLText.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import HTMLText
sage: w = HTMLText("Hello")
sage: w.description
u''
sage: w.description = "text"
sage: w.description
u''
```

description

Always return empty string.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import HTMLText
sage: w = HTMLText("Hello")
sage: w.description
u''
```

```
class sage.repl.ipython_kernel.widgets.SageColorPicker(**kwargs)
```

Bases: ipywidgets.widgets.widget_color.ColorPicker

A color picker widget returning a Sage Color.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import SageColorPicker
sage: SageColorPicker()
SageColorPicker(value='black')
```

```
get_interact_value()
```

Return a Sage Color corresponding to the value of this widget.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import SageColorPicker
sage: SageColorPicker().get_interact_value()
RGB color (0.0, 0.0, 0.0)
```

 ${\bf class} \ \, {\tt sage.repl.ipython_kernel.widgets.TransformFloatRangeSlider} \, (\, {\tt *args}, \, \, {\tt repl.ipython_kernel.widgets.TransformFloatRangeSlider} \, (\, {\tt *args}, \, {\tt *args}, \,$

***kwds*)

Bases: sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widgets.widgets.float.FloatRangeSlider

An ipywidgets.FloatRangeSlider widget with an optional transformation.

EXAMPLES:

class sage.repl.ipython_kernel.widgets.TransformFloatSlider(*args, **kwds)

 $Bases: sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widgets.transformWidget, ipywidgets.widgets.widgets.widgets.widgets.transformWidget, ipywidgets.widgets.widgets.transformWidget, ipywidgets.widgets.widgets.transformWidget, ipywidgets.$

A ipywidgets.FloatSlider widget with an optional transformation.

EXAMPLES:

class sage.repl.ipython_kernel.widgets.TransformIntRangeSlider(*args, **kwds)

Bases: sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widget int.IntRangeSlider

An ipywidgets. IntRangeSlider widget with an optional transformation.

EXAMPLES:

```
class sage.repl.ipython_kernel.widgets.TransformIntSlider(*args, **kwds)
```

 $Bases: \ sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widgets.transformWidget, ipywidgets.wi$

An ipywidgets. IntSlider widget with an optional transformation.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import TransformIntSlider
sage: w = TransformIntSlider(min=0, max=100, value=7, transform=lambda x: x^2)
sage: w
TransformIntSlider(value=7)
sage: w.get_interact_value()
49
```

class sage.repl.ipython_kernel.widgets.TransformText(*args, **kwds)

Bases: sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widgets.widgets.widgets.widgets.tring.Text

A ipywidgets. Text widget with an optional transformation.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import TransformText
sage: w = TransformText(value="hello", transform=lambda x: x+x)
sage: w
TransformText(value=u'hello')
sage: w.get_interact_value()
u'hellohello'
```

```
class sage.repl.ipython kernel.widgets.TransformTextarea(*args, **kwds)
```

Bases: sage.repl.ipython_kernel.widgets.TransformWidget, ipywidgets.widgets.widget string.Textarea

A ipywidgets. Textarea widget with an optional transformation.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets import TransformTextarea
sage: w = TransformTextarea(value="hello", transform=lambda x: x+x)
sage: w
TransformTextarea(value=u'hello')
sage: w.get_interact_value()
u'hellohello'
```

A mixin class for a widget to transform the bare widget value for use in interactive functions.

INPUT:

- transform a one-argument function which transforms the value of the widget for use by an interactive function.
- other arguments are passed to the base class

```
sage: from ipywidgets import ToggleButtons
sage: from sage.repl.ipython_kernel.widgets import TransformWidget
sage: class TransformToggleButtons(TransformWidget, ToggleButtons): pass
sage: w = TransformToggleButtons(options=["pi", "e"], transform=lambda x: x+x)
sage: w
TransformToggleButtons(options=('pi', 'e'), value='pi')
sage: w.get_interact_value()
'pipi'
```

get interact value()

Return the transformed value of this widget, by calling the transform function.

EXAMPLES:

```
sage: from ipywidgets import Checkbox
sage: from sage.repl.ipython_kernel.widgets import TransformWidget
sage: class TransformCheckbox(TransformWidget, Checkbox): pass
sage: w = TransformCheckbox(value=True, transform=int); w
TransformCheckbox(value=True)
sage: w.get_interact_value()
1
```

get_value()

Return self.value.

This is meant to be overridden by sub-classes to change the input of the transform function.

FXAMPI FS.

```
sage: from ipywidgets import ColorPicker
sage: from sage.repl.ipython_kernel.widgets import TransformWidget
sage: class TransformColorPicker(TransformWidget, ColorPicker): pass
sage: TransformColorPicker(value="red").get_value()
'red'
```

6.7 Functions to construct widgets, based on the old SageNB interface.

These should ensure mostly backwards compatibility with SageNB.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.widgets_sagenb import text_control
sage: text_control("Hello World!")
HTMLText(value=u'Hello World!')
```

sage.repl.ipython_kernel.widgets_sagenb.checkbox(default=True, label=None)
A checkbox widget.

INPUT:

- default (boolean) initial value
- label optional label

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.all_jupyter import checkbox
sage: checkbox(label="toggle me")
Checkbox(value=True, description=u'toggle me')
sage: checkbox(default=0)
Checkbox(value=False)
```

```
sage.repl.ipython\_kernel.widgets\_sagenb.\textbf{color\_selector}(\textit{default}=(0, 0, 1), la-bel=None, widget=None, hide\_box=False)
```

A widget for choosing a color.

INPUT:

- default initial value
- label optional label
- hide_box (boolean) if True, do not show the textbox

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.all_jupyter import color_selector
sage: w = color_selector("orange", label="color me"); w
SageColorPicker(value='#ffa500', description=u'color me')
sage: w.get_interact_value()
RGB color (1.0, 0.6470588235294118, 0.0)
sage: color_selector(Color(0.1, 0.2, 0.3))
SageColorPicker(value='#19334c')
```

```
sage.repl.ipython_kernel.widgets_sagenb.input_box(default=None, label=None, type=None, width=80, height=1)
```

A textbox widget.

INPUT:

- default initial value
- label optional label
- type function of one variable or None. if type is str, the value of this widget for interactive functions is just the text as str. Otherwise, the text is evaluated using sage_eval(), type is called on it and the result is used as value. Except if type is None, then the evaluated text is used as value.
- width width of the box
- height if height > 1, create a textarea instead of a single-line textbox.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.all_jupyter import input_box
```

The most basic usage is when type=str:

Without type, the text is evaluated:

```
sage: w = input_box("4+5")
sage: w
EvalText(value=u'4+5', layout=Layout(max_width=u'81em'))
sage: w.get_interact_value()
9
```

With a different type, the text is evaluated and type is called on it:

```
sage: w = input_box("4+5", type=float) sage: w EvalText(value=u'4+5', layout=Layout(max_width=u'81em')) sage: w.get_interact_value() 9.0
```

Despite the keyword name, type does not need to be a type:

```
sage: w = input_box("4+5", type=sqrt)
sage: w
EvalText(value=u'4+5', layout=Layout(max_width=u'81em'))
sage: w.get_interact_value()
3
```

When height > 1, a textarea is returned:

```
sage: w = input_box("4+5", width=100, height=1)
sage: w
EvalText(value=u'4+5', layout=Layout(max_width=u'101em'))
sage: w = input_box("4+5", width=100, height=5)
sage: w
EvalTextarea(value=u'4+5', layout=Layout(max_width=u'101em'))
```

A widget consisting of a grid (matrix) of textboxes.

The values entered in the textboxes are evaluated (using sage_eval()). These are stored as a list of lists on the value attribute. The value of this widget for an interactive function is the result of calling to_value on this list of lists.

INPUT:

- nrows, ncols number of rows and columns in the grid
- default initial value (given as a list of lists, a single constant value or a flat list)
- label optional label
- to_value function to be called to get the value for interactive functions
- width width of each textbox

```
sage: from sage.repl.ipython_kernel.all_jupyter import input_grid
sage: input_grid(2, 2, default=42, label="answers")
Grid(value=[[42, 42], [42, 42]], children=(Label(value=u'answers'),_
→VBox(children=(EvalText(value=u'42', layout=Layout(max_width=u'5em')),,
→EvalText(value=u'42', layout=Layout(max_width=u'5em')))),...
→VBox(children=(EvalText(value=u'42', layout=Layout(max_width=u'5em')), _
→EvalText(value=u'42', layout=Layout(max_width=u'5em'))))))
sage: w = input_grid(2, 2, default=[[cos(x), sin(x)], [-sin(x), cos(x)]], to_
→value=matrix); w
Grid(value=[[cos(x), sin(x)], [-sin(x), cos(x)]], children=(Label(value=u''), _
→VBox(children=(EvalText(value=u'cos(x)', layout=Layout(max_width=u'5em')),...
→EvalText(value=u'-sin(x)', layout=Layout(max_width=u'5em')))),,
→VBox(children=(EvalText(value=u'sin(x)', layout=Layout(max_width=u'5em')),_
→EvalText(value=u'cos(x)', layout=Layout(max_width=u'5em'))))))
sage: w.get_interact_value()
[\cos(x) \sin(x)]
[-\sin(x) \cos(x)]
sage: w = input\_qrid(2, 2, default=[1, x, x^2, x^3], to\_value=lambda x: x[1][1]);
Grid(value=[[1, x], [x^2, x^3]), children=(Label(value=u''), [x^2, x^3])
→VBox(children=(EvalText(value=u'1', layout=Layout(max_width=u'5em')),_
→EvalText(value=u'x^2', layout=Layout(max_width=u'5em')))),
→VBox (children=(EvalText(value=u'x', layout=Layout(max_width=u'5em')) (continues on next page)
→EvalText(value=u'x^3', layout=Layout(max_width=u'5em'))))))
```

```
sage: w.get_interact_value()
x^3
```

sage.repl.ipython_kernel.widgets_sagenb.range_slider(*args, **kwds)
A slider widget to select a range of values.

INPUT:

- vmin, vmax minimum and maximum value
- step_size the step size
- default initial value, given as a 2-tuple
- label optional label
- display_value (boolean) if True, display the current value.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.all_jupyter import range_slider
sage: range_slider(5, label="slide me")
TransformIntRangeSlider(value=(28, 76), description=u'slide me', min=5)
sage: range_slider(5, 20)
TransformIntRangeSlider(value=(8, 16), max=20, min=5)
sage: range_slider(5, 20, 0.5)
TransformFloatRangeSlider(value=(8.75, 16.25), max=20.0, min=5.0, step=0.5)
sage: range_slider(5, 20, default=(12,15))
TransformIntRangeSlider(value=(12, 15), max=20, min=5)
```

The parent of the inputs determines the parent of the value:

```
sage: w = range_slider(5); w
TransformIntRangeSlider(value=(28, 76), min=5)
sage: [parent(x) for x in w.get_interact_value()]
[Integer Ring, Integer Ring]
sage: w = range_slider(int(5)); w
IntRangeSlider(value=(28, 76), min=5)
sage: [parent(x) for x in w.get_interact_value()]
[<... 'int'>, <... 'int'>]
sage: w = range_slider(5, 20, step_size=RDF("0.1")); w
TransformFloatRangeSlider(value=(8.75, 16.25), max=20.0, min=5.0)
sage: [parent(x) for x in w.get_interact_value()]
[Real Double Field, Real Double Field]
```

Unfortunately, rational numbers are not supported:

```
sage: w = range_slider(5, 20, step_size=10/3); w
Traceback (most recent call last):
...
NotImplementedError: range_slider does not support rational numbers
```

```
sage.repl.ipython\_kernel.widgets\_sagenb.\textbf{selector}(values,\ label=None,\ default=None,\ nrows=None,\ ncols=None,\ width=None,\ buttons=False)
```

A widget to select a value from a given list of values.

This is rendered as a dropdown box (if buttons is False) or as a list of buttons (if buttons is True).

INPUT:

- values a list of values to choose from (see examples below for the accepted formats for this)
- label optional label
- default initial value
- buttons (boolean) if True, display buttons instead of a dropdown box

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.all_jupyter import selector
sage: selector(range(5), label="choose one")
Dropdown(description=u'choose one', options=(0, 1, 2, 3, 4), value=0)
sage: selector(range(5), buttons=True, default=4)
ToggleButtons(index=4, options=(0, 1, 2, 3, 4), value=4)
```

Apart from a simple list, values can be given as a list of 2-tuples (value, label):

```
sage: selector([(1,"one"), (2,"two"), (3,"three")])
Dropdown(options=(('one', 1), ('two', 2), ('three', 3)), value=1)
sage: selector([(1,"one"), (2,"two"), (3,"three")], buttons=True)
ToggleButtons(options=(('one', 1), ('two', 2), ('three', 3)), value=1)
```

A dict of label:value pairs is also allowed. Since a dict is not ordered, it is better to use an OrderedDict:

The values can be any kind of object:

sage: selector($[\sin(x^2), GF(29), EllipticCurve('37a1')]$) Dropdown(options= $(\sin(x^2), Finite Field of size 29, Elliptic Curve defined by <math>y^2 + y = x^3 - x$ over Rational Field), value= $\sin(x^2)$

```
sage.repl.ipython\_kernel.widgets\_sagenb. \textbf{slider} (\textit{vmin}, \textit{vmax}=None, \textit{step\_size}=None, \\ \textit{default}=None, & \textit{label}=None, & \textit{display\_value}=True, \_range=False)
```

A slider widget.

INPUT:

For a numeric slider (select a value from a range):

- vmin, vmax minimum and maximum value
- step_size the step size

For a selection slider (select a value from a list of values):

• vmin – a list of possible values for the slider

For all sliders:

- default initial value
- label optional label
- display_value (boolean) if True, display the current value.

```
sage: from sage.repl.ipython_kernel.all_jupyter import slider
sage: slider(5, label="slide me")
TransformIntSlider(value=5, description=u'slide me', min=5)
sage: slider(5, 20)
TransformIntSlider(value=5, max=20, min=5)
sage: slider(5, 20, 0.5)
TransformFloatSlider(value=5.0, max=20.0, min=5.0, step=0.5)
sage: slider(5, 20, default=12)
TransformIntSlider(value=12, max=20, min=5)
```

The parent of the inputs determines the parent of the value:

```
sage: w = slider(5); w
TransformIntSlider(value=5, min=5)
sage: parent(w.get_interact_value())
Integer Ring
sage: w = slider(int(5)); w
IntSlider(value=5, min=5)
sage: parent(w.get_interact_value())
<... 'int'>
sage: w = slider(5, 20, step_size=RDF("0.1")); w
TransformFloatSlider(value=5.0, max=20.0, min=5.0)
sage: parent(w.get_interact_value())
Real Double Field
sage: w = slider(5, 20, step_size=10/3); w
SelectionSlider(index=2, options=(5, 25/3, 35/3, 15, 55/3), value=35/3)
sage: parent(w.get_interact_value())
Rational Field
```

Symbolic input is evaluated numerically:

For a selection slider, the default is adjusted to one of the possible values:

```
sage: slider(range(10), default=17/10)
SelectionSlider(index=2, options=(0, 1, 2, 3, 4, 5, 6, 7, 8, 9), value=2)
```

6.8 Installing the SageMath Jupyter Kernel and Extensions

Kernels have to register themselves with Jupyter so that they appear in the Jupyter notebook's kernel drop-down. This is done by SageKernelSpec.

Note: The doctests in this module run in a temporary directory as the involved directories might be different during runs of the tests and actual installation and because we might be lacking write permission to places such as /usr/share.

```
class sage.repl.ipython_kernel.install.SageKernelSpec(prefix=None)
    Bases: object
```

Utility to manage SageMath kernels and extensions

INPUT:

• prefix – (optional, default: sys.prefix) directory for the installation prefix

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: prefix = tmp_dir()
sage: spec = SageKernelSpec(prefix=prefix)
sage: spec._display_name # random output
'SageMath 6.9'
sage: spec.kernel_dir == SageKernelSpec(prefix=prefix).kernel_dir
True
```

classmethod identifier()

Internal identifier for the SageMath kernel

OUTPUT: the string "sagemath".

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: SageKernelSpec.identifier()
'sagemath'
```

kernel_spec()

Return the kernel spec as Python dictionary

OUTPUT:

A dictionary. See the Jupyter documentation for details.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: spec = SageKernelSpec(prefix=tmp_dir())
sage: spec.kernel_spec()
{'argv': ..., 'display_name': 'SageMath ...'}
```

symlink (src, dst)

Symlink src to dst

This is not an atomic operation.

Already-existing symlinks will be deleted, already existing non-empty directories will be kept.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: spec = SageKernelSpec(prefix=tmp_dir())
sage: path = tmp_dir()
sage: spec.symlink(os.path.join(path, 'a'), os.path.join(path, 'b'))
sage: os.listdir(path)
['b']
```

classmethod update(*args, **kwds)

Configure the Jupyter notebook for the SageMath kernel

This method does everything necessary to use the SageMath kernel, you should never need to call any of the other methods directly.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: SageKernelSpec.update(prefix=tmp_dir())
```

use_local_jsmol()

Symlink ismol to the Jupyter notebook.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: spec = SageKernelSpec(prefix=tmp_dir())
sage: spec.use_local_jsmol()
sage: jsmol = os.path.join(spec.nbextensions_dir, 'jsmol')
sage: os.path.isdir(jsmol)
True
sage: os.path.isfile(os.path.join(jsmol, "JSmol.min.js"))
True
```

use_local_mathjax()

Symlink SageMath's Mathjax install to the Jupyter notebook.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: spec = SageKernelSpec(prefix=tmp_dir())
sage: spec.use_local_mathjax()
sage: mathjax = os.path.join(spec.nbextensions_dir, 'mathjax')
sage: os.path.isdir(mathjax)
True
```

use_local_threejs()

Symlink three is to the Jupyter notebook.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.install import SageKernelSpec
sage: spec = SageKernelSpec(prefix=tmp_dir())
sage: spec.use_local_threejs()
sage: threejs = os.path.join(spec.nbextensions_dir, 'threejs')
sage: os.path.isdir(threejs)
True
```

sage.repl.ipython_kernel.install.have_prerequisites(debug=True)

Check that we have all prerequisites to run the Jupyter notebook.

In particular, the Jupyter notebook requires OpenSSL whether or not you are using https. See trac ticket #17318.

INPUT:

debug – boolean (default: True). Whether to print debug information in case that prerequisites are missing.

OUTPUT:

Boolean.

```
sage: from sage.repl.ipython_kernel.install import have_prerequisites
sage: have_prerequisites(debug=False) in [True, False]
True
```

6.9 The Sage ZMQ Kernel

Version of the Jupyter kernel when running Sage inside the Jupyter notebook or remote Jupyter sessions.

```
class sage.repl.ipython_kernel.kernel.SageKernel(**kwds)
    Bases: ipykernel.ipkernel.IPythonKernel
```

The Sage Jupyter Kernel

INPUT:

See the Jupyter documentation

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.kernel import SageKernel
sage: SageKernel.__new__(SageKernel)
<sage.repl.ipython_kernel.kernel.SageKernel object at 0x...>
```

banner

The Sage Banner

The value of this property is displayed in the Jupyter notebook.

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.kernel import SageKernel
sage: sk = SageKernel.__new__(SageKernel)
sage: print(sk.banner)
+...SageMath version...
```

help_links

Help in the Jupyter Notebook

OUTPUT:

See the Jupyter documentation.

Note: Urls starting with "kernelspecs" are prepended by the browser with the appropriate path.

EXAMPLES:

```
sage: from sage.repl.ipython_kernel.kernel import SageKernel
sage: sk = SageKernel.__new__(SageKernel)
sage: sk.help_links
[{'text': 'Sage Documentation',
    'url': 'kernelspecs/sagemath/doc/index.html'},
    ...]
```

pre_handler_hook()

Restore the signal handlers to their default values at Sage startup, saving the old handler at the saved_sigint_handler attribute. This is needed because Jupyter needs to change the SIGINT handler.

See trac ticket #19135.

shell class

A trait whose value must be a subclass of a specified class.

6.10 Tests for the IPython integration

First, test the pinfo magic for Python code. This is what IPython calls when you ask for the single-questionmark help, like *foo*?

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell(u'from sage.repl.ipython_tests import dummy')
sage: shell.run_cell(u'%pinfo dummy')
Signature:
               dummy(argument, optional=None)
Docstring:
  Dummy Docstring Title
  Dummy docstring explanation.
  INPUT:
   * "argument" -- anything. Dummy argument.
   * "optional" -- anything (optional). Dummy optional.
  EXAMPLES:
Init docstring: x.__init__(...) initializes x; see help(type(x)) for signature
               .../sage/repl/ipython_tests.py
File:
                function
Type:
```

Next, test the pinfo magic for Cython code:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell(u'from sage.tests.stl_vector import stl_int_vector')
sage: shell.run_cell(u'%pinfo stl_int_vector')
Docstring:
    Example class wrapping an STL vector

EXAMPLES:
...
Init docstring: x.__init__(...) initializes x; see help(type(x)) for signature
```

(continues on next page)

```
File: .../sage/tests/stl_vector.pyx
Type: type
```

Next, test the pinfo2 magic for Python code. This is what IPython calls when you ask for the double-questionmark help, like foo??

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell(u'from sage.repl.ipython_tests import dummy')
sage: shell.run_cell(u'%pinfo2 dummy')
Signature: dummy(argument, optional=None)
Source:
def dummy(argument, optional=None):
   Dummy Docstring Title
   Dummy docstring explanation.
   INPUT:
   - ``argument`` -- anything. Dummy argument.
   - ``optional`` -- anything (optional). Dummy optional.
   EXAMPLES::
   return 'Source code would be here'
File: .../sage/repl/ipython_tests.py
Type:
          function
```

Next, test the pinfo2 magic for Cython code:

```
sage: from sage.repl.interpreter import get_test_shell
sage: shell = get_test_shell()
sage: shell.run_cell(u'from sage.tests.stl_vector import stl_int_vector')
sage: shell.run_cell(u'%pinfo2 stl_int_vector')
Source:
cdef class stl_int_vector(SageObject):
    """
    Example class wrapping an STL vector

    EXAMPLES::
...

"""
    cdef vector[int] *data
    cdef string *name

    def __cinit__(self):
        """
        The Cython constructor.

EXAMPLES::
```

(continues on next page)

```
File: .../sage/tests/stl_vector.pyx
Type: type
```

Test that there are no warnings being ignored internally:

```
sage: import warnings
sage: warnings.simplefilter('error'); get_test_shell()
<sage.repl.interpreter.SageTestShell object at 0x...>
```

sage.repl.ipython_tests.dummy (argument, optional=None)
Dummy Docstring Title

Dummy docstring explanation.

INPUT:

- argument anything. Dummy argument.
- optional anything (optional). Dummy optional.

EXAMPLES:

```
sage: from sage.repl.ipython_tests import dummy
sage: dummy(1)
'Source code would be here'
```

6.11 HTML Generator for JSmol

This is all an evil iframe hack to get JSmol to display 3-d graphics while separating JSmol's j2s machinery from your actual web page.

There are some caveats for how to load JSmol, in particular it cannot just load its code from a file:// uri. To use a html file generated by this module, you need

- A web server,
- The JSmol directory tree must be served by your web server,
- The output of <code>JSMolHtml.inner_html()</code> or <code>JSMolHtml.outer_html()</code> must be served by the same web server.

See https://github.com/phetsims/molecule-polarity/issues/6 for a discussion of loading JSMol.

- jmol 3-d graphics or sage.repl.rich_output.output_graphics3d. OutputSceneJmol instance. The 3-d scene to show.
- path_to_jsmol string (optional, default is '/nbextensions/jsmol'). The path (relative or absolute) where JSmol.min.js is served on the web server.
- width integer or string (optional, default: '100%'). The width of the JSmol applet using CSS dimensions.

• height - integer or string (optional, default: '100%'). The height of the JSmol applet using CSS dimensions.

EXAMPLES:

```
sage: from sage.repl.display.jsmol_iframe import JSMolHtml
sage: JSMolHtml(sphere(), width=500, height=300)
JSmol Window 500x300
```

iframe()

Return HTML iframe

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.display.jsmol_iframe import JSMolHtml
sage: from sage.repl.rich_output.output_graphics3d import OutputSceneJmol
sage: jmol = JSMolHtml(OutputSceneJmol.example())
sage: print(jmol.iframe())
<iframe srcdoc="
...
</iframe>
```

inner html()

Return a HTML document containing a JSmol applet

EXAMPLES:

js_script()

The script () as Javascript string.

Since the many shortcomings of Javascript include multi-line strings, this actually returns Javascript code to reassemble the script from a list of strings.

OUTPUT:

String. Javascript code that evaluates to script () as Javascript string.

EXAMPLES:

```
sage: from sage.repl.display.jsmol_iframe import JSMolHtml
sage: from sage.repl.rich_output.output_graphics3d import OutputSceneJmol
sage: jsmol = JSMolHtml(OutputSceneJmol.example(), width=500, height=300)
sage: print(jsmol.js_script())
[
```

(continues on next page)

```
'data "model list"',
...
'isosurface fullylit; pmesh o* fullylit; set antialiasdisplay on;',
].join('\n');
```

outer_html()

Return a HTML document containing an iframe with a JSmol applet

OUTPUT:

String

EXAMPLES:

script()

Return the JMol script file.

This method extracts the Jmol script from the Jmol spt file (a zip archive) and inlines meshes.

OUTPUT:

String.

EXAMPLES:

```
sage: from sage.repl.display.jsmol_iframe import JSMolHtml
sage: from sage.repl.rich_output.output_graphics3d import OutputSceneJmol
sage: jsmol = JSMolHtml(OutputSceneJmol.example(), width=500, height=300)
sage: jsmol.script()
'data "model list"\n10\nempt...aliasdisplay on;\n'
```

6.12 Sage Wrapper for Bitmap Images

Some computations in Sage return bitmap images, for example matrices can be turned into bitmaps directly. Note that this is different from all plotting functionality, the latter can equally produce vector graphics. This module is about bitmaps only, and a shallow wrapper around PIL.Image. The only difference is that *Image* is displayed as graphics by the Sage if the UI can.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: img = Image('RGB', (256, 256), 'white')
```

(continues on next page)

```
class sage.repl.image.Image (mode, size, color='white')
    Bases: sage.structure.sage object.SageObject
```

Creates a new image with the given mode and size.

INPUT:

- mode string. The mode to use for the new image. Valid options are:
 - '1' (1-bit pixels, black and white, stored with one pixel per byte)
 - 'L' (8-bit pixels, black and white)
 - 'P' (8-bit pixels, mapped to any other mode using a color palette)
 - 'RGB' (3x8-bit pixels, true color)
 - 'RGBA' (4x8-bit pixels, true color with transparency mask)
 - 'CMYK' (4x8-bit pixels, color separation)
 - 'YCbCr' (3x8-bit pixels, color video format)
 - 'LAB' (3x8-bit pixels, the L*a*b color space)
 - 'HSV' (3x8-bit pixels, Hue, Saturation, Value color space)
 - 'I' (32-bit signed integer pixels)
 - 'F' (32-bit floating point pixels)
- size 2-tuple, containing (width, height) in pixels.
- color string or tuple of numeric. What colour to use for the image. Default is black. If given, this should be a a tuple with one value per band. When creating RGB images, you can also use colour strings as supported by the ImageColor module. If the colour is None, the image is not initialised.

OUTPUT:

A new Image object.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: Image('P', (16, 16), (13,))
16x16px 8-bit Color image
```

height()

Return the vertical dimension in pixels

OUTPUT:

Integer.

```
sage: from sage.repl.image import Image
sage: img = Image('1', (12, 34), 'white')
sage: img.width()
12
sage: img.height()
34
```

mode()

Return the color mode

OUTPUT:

String. As given when constructing the image.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: img = Image('YCbCr', (16, 16), 'white')
sage: img.mode()
'YCbCr'
```

pil

Access the wrapped PIL(low) Image

OUTPUT:

The underlying PIL. Image. Image object.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: img = Image('RGB', (16, 16), 'white')
sage: img.pil
<PIL.Image.Image image mode=RGB size=16x16 at 0x...>
```

pixels()

Return the pixel map

OUTPUT:

The PIL PixelAccess object that allows you to get/set the pixel data.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: img = Image('RGB', (16, 16), 'white')
sage: img.pixels()
<PixelAccess object at 0x...>
```

save (filename)

Save the bitmap image

INPUT:

• filename – string. The filename to save as. The given extension automatically determines the image file type.

```
sage: from sage.repl.image import Image
sage: img = Image('P', (12, 34), (13,))
sage: filename = tmp_filename(ext='.png')
sage: img.save(filename)
sage: with open(filename, 'rb') as f:
....: f.read(4) == b'\x89PNG'
True
```

show()

Show this image immediately.

This method attempts to display the graphics immediately, without waiting for the currently running code (if any) to return to the command line. Be careful, calling it from within a loop will potentially launch a large number of external viewer programs.

OUTPUT:

This method does not return anything. Use save () if you want to save the figure as an image.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: img = Image('1', (12, 34), 'white')
sage: img.show()
```

width()

Return the horizontal dimension in pixels

OUTPUT:

Integer.

EXAMPLES:

```
sage: from sage.repl.image import Image
sage: img = Image('1', (12, 34), 'white')
sage: img.width()
12
sage: img.height()
34
```

6.13 The Sage Input Hook

This lets us perform actions while IPython is sitting at the terminal input prompt. We use it to reload attached files if they have changed.

```
sage: from sage.repl.inputhook import install
sage: install()
```

```
sage.repl.inputhook.sage_inputhook(context)
sage.repl.inputhook.uninstall()
     Uninstall the Sage input hook
```

```
sage: from sage.repl.inputhook import uninstall
sage: uninstall()
```

Sage Reference Manual: The Sage Command Line, Release 8.5	
<u> </u>	

CHAPTER

SEVEN

INDICES AND TABLES

- Index
- Module Index
- Search Page

PYTHON MODULE INDEX

```
m
sage.misc.trace, 8
r
sage.repl.attach, 28
sage.repl.display.fancy_repr, 39
sage.repl.display.formatter, 35
sage.repl.display.jsmol_iframe, 129
sage.repl.display.pretty_print,37
sage.repl.display.util,42
sage.repl.image, 131
sage.repl.inputhook, 134
sage.repl.interface magic, 109
sage.repl.interpreter,96
sage.repl.ipython_extension, 104
sage.repl.ipython_kernel.install, 123
sage.repl.ipython_kernel.interact,111
sage.repl.ipython_kernel.kernel, 126
sage.repl.ipython_kernel.widgets, 113
sage.repl.ipython_kernel.widgets_sagenb, 118
sage.repl.ipython_tests, 127
sage.repl.load, 25
sage.repl.preparse, 11
sage.repl.readline extra commands, 95
sage.repl.rich_output.backend_base,73
sage.repl.rich_output.backend_doctest,82
sage.repl.rich_output.backend_ipython, 85
sage.repl.rich_output.backend_sagenb, 90
sage.repl.rich_output.backend_test,80
sage.repl.rich_output.buffer,55
sage.repl.rich_output.display_manager,45
sage.repl.rich_output.output_basic,58
sage.repl.rich_output.output_catalog,72
sage.repl.rich_output.output_graphics,62
sage.repl.rich_output.output_graphics3d,66
sage.repl.rich_output.output_video,70
sage.repl.rich_output.preferences,50
```

140 Python Module Index

INDEX

Symbols \$PATH. 3 __call__() (sage.repl.display.fancy_repr.LargeMatrixHelpRepr method), 39 __call__() (sage.repl.display.fancy_repr.ObjectReprABC method), 40 __call__() (sage.repl.display.fancy_repr.PlainPythonRepr method), 40 __call__() (sage.repl.display.fancy_repr.SomeIPythonRepr method), 41 __call__() (sage.repl.display.fancy_repr.TallListRepr method), 41 __call__() (sage.repl.display.util.TallListFormatter method), 42 Α add_attached_file() (in module sage.repl.attach), 28 all_globals() (sage.repl.ipython_extension.SageCustomizations static method), 104 all_globals() (sage.repl.ipython_extension.SageJupyterCustomizations static method), 104 all_iter() (sage.repl.interface_magic.InterfaceMagic class method), 109 ascii art formatter() (sage.repl.rich output.backend base.BackendBase method), 73 attach() (in module sage.repl.attach), 28 attach() (sage.repl.ipython_extension.SageMagics method), 105 attached files() (in module sage.repl.attach), 29 available_options() (sage.repl.rich_output.preferences.PreferencesABC method), 53 В BackendBase (class in sage.repl.rich_output.backend_base), 73 BackendDoctest (class in sage.repl.rich_output.backend_doctest), 82 BackendIPython (class in sage.repl.rich_output.backend_ipython), 85 BackendIPythonCommandline (class in sage.repl.rich_output.backend_ipython), 86 BackendIPythonNotebook (class in sage.repl.rich_output.backend_ipython), 89 BackendSageNB (class in sage.repl.rich_output.backend_sagenb), 91 BackendSimple (class in sage.repl.rich_output.backend_base), 79 BackendTest (class in sage.repl.rich output.backend test), 80 banner (sage.repl.ipython_kernel.kernel.SageKernel attribute), 126 BROWSER, 8 C cell magic factory() (sage.repl.interface magic.InterfaceMagic method), 110 check_backend_class() (sage.repl.rich_output.display_manager.DisplayManager method), 45

checkbox() (in module sage.repl.ipython_kernel.widgets_sagenb), 118 color selector() (in module sage.repl.ipython_kernel.widgets_sagenb), 118

```
containing block() (in module sage.repl.preparse), 14
crash_handler_class (sage.repl.interpreter.SageTerminalApp attribute), 100
crun() (sage.repl.ipython_extension.SageMagics method), 105
cython() (sage.repl.ipython extension.SageMagics method), 106
D
default_mime() (sage.repl.display.formatter.SageDisplayFormatter method), 36
default_preferences() (sage.repl.rich_output.backend_base.BackendBase method), 74
default preferences() (sage.repl.rich output.backend doctest.BackendDoctest method), 82
default_preferences() (sage.repl.rich_output.backend_ipython.BackendIPythonCommandline method), 86
deleter() (sage.repl.rich_output.preferences.Property method), 53
description (sage.repl.ipython kernel.widgets.Grid attribute), 115
description (sage.repl.ipython_kernel.widgets.HTMLText attribute), 115
detach() (in module sage.repl.attach), 29
display() (sage.repl.ipython extension.SageMagics method), 106
display equation() (sage.repl.rich output.output basic.OutputLatex method), 59
display immediately() (sage.repl.rich output.backend base.BackendBase method), 74
display_immediately() (sage.repl.rich_output.backend_base.BackendSimple method), 79
display_immediately() (sage.repl.rich_output.backend_doctest.BackendDoctest method), 82
display immediately() (sage.repl.rich output.backend ipython.BackendIPython method), 85
display_immediately() (sage.repl.rich_output.backend_ipython.BackendIPythonCommandline method), 86
display_immediately() (sage.repl.rich_output.backend_sagenb.BackendSageNB method), 91
display immediately() (sage.repl.rich output.backend test.BackendTest method), 80
display_immediately() (sage.repl.rich_output.display_manager.DisplayManager method), 46
DisplayException, 45
displayhook() (sage.repl.rich output.backend base.BackendBase method), 74
displayhook() (sage.repl.rich output.backend doctest.BackendDoctest method), 83
displayhook() (sage.repl.rich_output.backend_ipython.BackendIPythonCommandline method), 87
displayhook() (sage.repl.rich_output.backend_ipython.BackendIPythonNotebook method), 89
displayhook() (sage.repl.rich output.display manager.DisplayManager method), 46
DisplayManager (class in sage.repl.rich output.display manager), 45
DisplayPreferences (class in sage.repl.rich_output.preferences), 51
DOT_SAGE, 7, 8
dummy() (in module sage.repl.ipython tests), 129
F
embed() (sage.repl.rich_output.backend_sagenb.SageNbOutputSceneJmol method), 92
embed_image() (sage.repl.rich_output.backend_sagenb.BackendSageNB method), 91
embed video() (sage.repl.rich output.backend sagenb.BackendSageNB method), 92
embedded() (in module sage.repl.interpreter), 102
environment variable
    $PATH, 3
    BROWSER, 8
    DOT_SAGE, 7, 8
    IPYTHONDIR, 8
    JUPYTER_CONFIG_DIR, 8
    MPLCONFIGDIR, 8
    PATH, 7
    SAGE_CHECK, 4
    SAGE CHECK PACKAGES, 4
```

```
SAGE PATH, 8
    SAGE_RC_FILE, 7, 8
    SAGE SERVER, 8
    SAGE STARTUP FILE, 7, 8
EvalText (class in sage.repl.ipython_kernel.widgets), 113
EvalTextarea (class in sage.repl.ipython_kernel.widgets), 114
EvalWidget (class in sage.repl.ipython kernel.widgets), 114
example() (sage.repl.rich output.output basic.OutputAsciiArt class method), 58
example() (sage.repl.rich_output.output_basic.OutputBase class method), 59
example() (sage.repl.rich output.output basic.OutputLatex class method), 60
example() (sage.repl.rich output.output basic.OutputPlainText class method), 61
example() (sage.repl.rich output.output basic.OutputUnicodeArt class method), 62
example() (sage.repl.rich_output.output_graphics.OutputImageDvi class method), 63
example() (sage.repl.rich_output.output_graphics.OutputImageGif class method), 63
example() (sage.repl.rich output.output graphics.OutputImageJpg class method), 64
example() (sage.repl.rich_output.output_graphics.OutputImagePdf class method), 65
example() (sage.repl.rich_output.output_graphics.OutputImagePng class method), 65
example() (sage.repl.rich output.output graphics.OutputImageSvg class method), 66
example() (sage.repl.rich output.output graphics3d.OutputSceneCanvas3d class method), 66
example() (sage.repl.rich_output.output_graphics3d.OutputSceneJmol class method), 67
example() (sage.repl.rich output.output graphics3d.OutputSceneWavefront class method), 68
example() (sage.repl.rich output.output video.OutputVideoBase class method), 70
extract_numeric_literals() (in module sage.repl.preparse), 15
F
filename() (sage.repl.rich output.buffer.OutputBuffer method), 55
find() (sage.repl.interface magic.InterfaceMagic class method), 110
format() (sage.repl.display.formatter.SageDisplayFormatter method), 36
format string() (sage.repl.display.fancy repr.ObjectReprABC method), 40
fortran() (sage.repl.ipython extension.SageMagics method), 107
from file() (sage.repl.rich output.buffer.OutputBuffer class method), 56
G
get() (sage.repl.rich output.buffer.OutputBuffer method), 56
get_display_manager (in module sage.repl.rich_output.display_manager), 50
get display manager() (sage.repl.rich output.backend base.BackendBase method), 75
get instance() (sage.repl.rich output.display manager.DisplayManager class method), 47
get_interact_value() (sage.repl.ipython_kernel.widgets.SageColorPicker method), 115
get_interact_value() (sage.repl.ipython_kernel.widgets.TransformWidget method), 117
get_str() (sage.repl.rich_output.buffer.OutputBuffer method), 56
get test shell() (in module sage.repl.interpreter), 103
get unicode() (sage.repl.rich output.buffer.OutputBuffer method), 57
get value() (sage.repl.ipvthon kernel.widgets.EvalWidget method), 114
get_value() (sage.repl.ipython_kernel.widgets.TransformWidget method), 118
getter() (sage.repl.rich output.preferences.Property method), 54
graphics (sage.repl.rich output.preferences.DisplayPreferences attribute), 51
graphics_from_save() (sage.repl.rich_output.display_manager.DisplayManager method), 47
Grid (class in sage.repl.ipython_kernel.widgets), 114
```

Н handle encoding declaration() (in module sage.repl.preparse), 15 have prerequisites() (in module sage.repl.ipython kernel.install), 125 height() (sage.repl.image.Image method), 132 help links (sage.repl.ipython kernel.kernel.SageKernel attribute), 126 html_fragment() (sage.repl.rich_output.output_graphics.OutputImageGif method), 63 html_fragment() (sage.repl.rich_output.output_video.OutputVideoBase method), 71 HTMLText (class in sage.repl.ipython_kernel.widgets), 115 identifier() (sage.repl.ipython kernel.install.SageKernelSpec class method), 124 iframe() (sage.repl.display.jsmol_iframe.JSMolHtml method), 130 iload() (sage.repl.ipython_extension.SageMagics method), 108 Image (class in sage.repl.image), 132 implicit mul() (in module sage.repl.preparse), 16 implicit multiplication() (in module sage.repl.preparse), 17 in_quote() (in module sage.repl.preparse), 17 init_display_formatter() (sage.repl.interpreter.SageNotebookInteractiveShell method), 99 init display formatter() (sage.repl.interpreter.SageTerminalInteractiveShell method), 101 init_display_formatter() (sage.repl.interpreter.SageTestShell method), 102 init_environment() (sage.repl.ipython_extension.SageCustomizations method), 104 init_inspector() (sage.repl.ipython_extension.SageCustomizations method), 104 init_line_transforms() (sage.repl.ipython_extension.SageCustomizations method), 104 init shell() (sage.repl.interpreter.SageTerminalApp method), 101 inline_equation() (sage.repl.rich_output.output_basic.OutputLatex method), 60 inner html() (sage.repl.display.jsmol iframe.JSMolHtml method), 130 input box() (in module sage.repl.ipython kernel.widgets sagenb), 119 input grid() (in module sage.repl.ipython kernel.widgets sagenb), 120 install() (in module sage.repl.inputhook), 134 install() (sage.repl.rich output.backend base.BackendBase method), 75 install() (sage.repl.rich output.backend doctest.BackendDoctest method), 83 install() (sage.repl.rich_output.backend_ipython.BackendIPython method), 85 interface_shell_embed() (in module sage.repl.interpreter), 103 InterfaceMagic (class in sage.repl.interface magic), 109 InterfaceShellTransformer (class in sage.repl.interpreter), 97 IPYTHONDIR, 8 is in terminal() (sage.repl.rich output.backend base.BackendBase method), 75 is in terminal() (sage.repl.rich output.backend ipython.BackendIPythonCommandline method), 87 is_in_terminal() (sage.repl.rich_output.display_manager.DisplayManager method), 47 is_loadable_filename() (in module sage.repl.load), 25 isalphadigit () (in module sage.repl.preparse), 17 J is script() (sage.repl.display.jsmol iframe.JSMolHtml method), 130 JSMolHtml (class in sage.repl.display.jsmol_iframe), 129 JUPYTER CONFIG DIR, 8

K

kernel_spec() (sage.repl.ipython_kernel.install.SageKernelSpec method), 124

```
L
LargeMatrixHelpRepr (class in sage.repl.display.fancy repr), 39
latex formatter() (sage.repl.rich output.backend base.BackendBase method), 76
launch_jmol() (sage.repl.rich_output.backend_ipython.BackendIPythonCommandline method), 87
launch_script_filename() (sage.repl.rich_output.output_graphics3d.OutputSceneJmol method), 67
launch viewer() (sage.repl.rich output.backend ipython.BackendIPythonCommandline method), 88
line_magic_factory() (sage.repl.interface_magic.InterfaceMagic method), 110
load() (in module sage.repl.load), 25
load_attach_mode() (in module sage.repl.attach), 30
load_attach_path() (in module sage.repl.attach), 31
load config file() (sage.repl.interpreter.SageTerminalApp method), 101
load cython() (in module sage.repl.load), 27
load_ipython_extension() (in module sage.repl.ipython_extension), 109
load wrap() (in module sage.repl.load), 27
M
mathjax() (sage.repl.rich_output.output_basic.OutputLatex method), 60
max width() (sage.repl.rich output.backend base.BackendBase method), 76
mode() (sage.repl.image.Image method), 133
modified file iterator() (in module sage.repl.attach), 32
MPLCONFIGDIR, 8
mtllib() (sage.repl.rich output.output graphics3d.OutputSceneWavefront method), 69
Ν
newline() (sage.repl.rich output.backend base.BackendBase method), 77
obj filename() (sage.repl.rich output.output graphics3d.OutputSceneWavefront method), 69
ObjectReprABC (class in sage.repl.display.fancy_repr), 39
outer_html() (sage.repl.display.jsmol_iframe.JSMolHtml method), 131
OutputAsciiArt (class in sage.repl.rich output.output basic), 58
OutputBase (class in sage.repl.rich output.output basic), 59
OutputBuffer (class in sage.repl.rich output.buffer), 55
OutputImageDvi (class in sage.repl.rich_output.output_graphics), 62
OutputImageGif (class in sage.repl.rich output.output graphics), 63
OutputImageJpg (class in sage.repl.rich output.output graphics), 64
OutputImagePdf (class in sage.repl.rich_output.output_graphics), 64
OutputImagePng (class in sage.repl.rich_output.output_graphics), 65
OutputImageSvg (class in sage.repl.rich output.output graphics), 65
OutputLatex (class in sage.repl.rich_output.output_basic), 59
OutputPlainText (class in sage.repl.rich_output.output_basic), 61
OutputSceneCanvas3d (class in sage.repl.rich output.output graphics3d), 66
OutputSceneJmol (class in sage.repl.rich_output.output_graphics3d), 67
OutputSceneThreejs (class in sage.repl.rich_output.output_graphics3d), 68
OutputSceneWavefront (class in sage.repl.rich_output.output_graphics3d), 68
OutputTypeException, 49
OutputUnicodeArt (class in sage.repl.rich output.output basic), 61
OutputVideoAvi (class in sage.repl.rich_output.output_video), 70
OutputVideoBase (class in sage.repl.rich_output.output_video), 70
OutputVideoFlash (class in sage.repl.rich output.output video), 71
```

```
OutputVideoMatroska (class in sage.repl.rich output.output video), 71
OutputVideoMp4 (class in sage.repl.rich_output.output_video), 71
OutputVideoOgg (class in sage.repl.rich_output.output_video), 72
OutputVideoQuicktime (class in sage.repl.rich output.output video), 72
OutputVideoWebM (class in sage.repl.rich_output.output_video), 72
OutputVideoWmv (class in sage.repl.rich_output.output_video), 72
Р
parse ellipsis() (in module sage.repl.preparse), 17
PATH, 7
pil (sage.repl.image.Image attribute), 133
pixels() (sage.repl.image.Image method), 133
plain text formatter() (sage.repl.rich output.backend base.BackendBase method), 77
PlainPythonRepr (class in sage.repl.display.fancy_repr), 40
pre_handler_hook() (sage.repl.ipython_kernel.kernel.SageKernel method), 126
preferences (sage.repl.rich output.display manager.DisplayManager attribute), 48
Preferences ABC (class in sage.repl.rich output.preferences), 52
preparse() (in module sage.repl.preparse), 18
preparse calculus() (in module sage.repl.preparse), 19
preparse file() (in module sage.repl.preparse), 19
preparse_file_named() (in module sage.repl.preparse), 20
preparse_file_named_to_stream() (in module sage.repl.preparse), 20
preparse generators() (in module sage.repl.preparse), 20
preparse imports from sage() (sage.repl.interpreter.InterfaceShellTransformer method), 97
preparse_numeric_literals() (in module sage.repl.preparse), 21
preparser() (in module sage.repl.interpreter), 103
pretty() (sage.repl.display.pretty print.SagePrettyPrinter method), 38
preview_filename() (sage.repl.rich_output.backend_sagenb.SageNbOutputSceneJmol method), 93
print_to_stdout() (sage.repl.rich_output.backend_test.TestOutputPlainText method), 81
print to stdout() (sage.repl.rich output.output basic.OutputAsciiArt method), 58
print to stdout() (sage.repl.rich output.output basic.OutputLatex method), 60
print_to_stdout() (sage.repl.rich_output.output_basic.OutputPlainText method), 61
print_to_stdout() (sage.repl.rich_output.output_basic.OutputUnicodeArt method), 62
Property (class in sage.repl.rich output.preferences), 53
Python Enhancement Proposals
    PEP 263, 16
Q
quit() (sage.repl.interpreter.SageTestShell method), 102
R
range slider() (in module sage.repl.ipython kernel.widgets sagenb), 121
register_all() (sage.repl.interface_magic.InterfaceMagic class method), 111
register_interface_magics() (sage.repl.ipython_extension.SageCustomizations method), 104
reload_attached_files_if_modified() (in module sage.repl.attach), 32
reset() (in module sage.repl.attach), 33
reset load attach path() (in module sage.repl.attach), 33
restricted_output (class in sage.repl.rich_output.display_manager), 50
RichReprWarning, 50
run cell() (sage.repl.interpreter.SageTestShell method), 102
```

```
run init() (sage.repl.ipython extension.SageCustomizations method), 104
run_once() (in module sage.repl.ipython_extension), 109
runfile() (sage.repl.ipython_extension.SageMagics method), 108
S
sage.misc.trace (module), 8
sage.repl.attach (module), 28
sage.repl.display.fancy_repr (module), 39
sage.repl.display.formatter (module), 35
sage.repl.display.jsmol iframe (module), 129
sage.repl.display.pretty_print (module), 37
sage.repl.display.util (module), 42
sage.repl.image (module), 131
sage.repl.inputhook (module), 134
sage.repl.interface magic (module), 109
sage.repl.interpreter (module), 96
sage.repl.ipython extension (module), 104
sage.repl.ipython kernel.install (module), 123
sage.repl.ipython_kernel.interact (module), 111
sage.repl.ipython_kernel.kernel (module), 126
sage.repl.ipython kernel.widgets (module), 113
sage.repl.ipython_kernel.widgets_sagenb (module), 118
sage.repl.ipython_tests (module), 127
sage.repl.load (module), 25
sage.repl.preparse (module), 11
sage.repl.readline extra commands (module), 95
sage.repl.rich output.backend base (module), 73
sage.repl.rich_output.backend_doctest (module), 82
sage.repl.rich output.backend ipython (module), 85
sage.repl.rich_output.backend_sagenb (module), 90
sage.repl.rich output.backend test (module), 80
sage.repl.rich_output.buffer (module), 55
sage.repl.rich_output.display_manager (module), 45
sage.repl.rich output.output basic (module), 58
sage.repl.rich_output.output_catalog (module), 72
sage.repl.rich_output.output_graphics (module), 62
sage.repl.rich output.output graphics3d (module), 66
sage.repl.rich output.output video (module), 70
sage.repl.rich_output.preferences (module), 50
SAGE CHECK, 4
SAGE CHECK PACKAGES, 4
sage_inputhook() (in module sage.repl.inputhook), 134
sage_interactive (class in sage.repl.ipython_kernel.interact), 112
SAGE_PATH, 8
SAGE RC FILE, 7, 8
SAGE SERVER, 8
SAGE STARTUP FILE, 7, 8
SageColorPicker (class in sage.repl.ipython kernel.widgets), 115
SageCrashHandler (class in sage.repl.interpreter), 98
```

SageCustomizations (class in sage.repl.ipython_extension), 104

```
SageDisplayFormatter (class in sage.repl.display.formatter), 36
SageJupyterCustomizations (class in sage.repl.ipython_extension), 104
SageKernel (class in sage.repl.ipython kernel.kernel), 126
SageKernelSpec (class in sage.repl.ipython kernel.install), 123
SageMagics (class in sage.repl.ipython_extension), 105
sagenb_launch_script_filename() (sage.repl.rich_output.backend_sagenb.SageNbOutputSceneJmol method), 93
SageNbOutputSceneJmol (class in sage.repl.rich output.backend sagenb), 92
SageNotebookInteractiveShell (class in sage.repl.interpreter), 98
SagePlainTextFormatter (class in sage.repl.display.formatter), 37
SagePreparseTransformer() (in module sage.repl.interpreter), 99
SagePrettyPrinter (class in sage.repl.display.pretty print), 38
SagePromptTransformer() (in module sage.repl.interpreter), 99
SageShellOverride (class in sage.repl.interpreter), 100
SageTerminalApp (class in sage.repl.interpreter), 100
SageTerminalInteractiveShell (class in sage.repl.interpreter), 101
SageTestShell (class in sage.repl.interpreter), 101
SageZMQInteractiveShell (class in sage.repl.ipython_kernel.kernel), 127
save() (sage.repl.image.Image method), 133
save as() (sage.repl.rich output.buffer.OutputBuffer method), 57
save_launch_script() (sage.repl.rich_output.backend_sagenb.SageNbOutputSceneJmol method), 93
save preview() (sage.repl.rich output.backend sagenb.SageNbOutputSceneJmol method), 93
scene zip filename() (sage.repl.rich output.backend sagenb.SageNbOutputSceneJmol method), 94
script() (sage.repl.display.jsmol_iframe.JSMolHtml method), 131
selector() (in module sage.repl.ipython kernel.widgets sagenb), 121
set_quit_hook() (sage.repl.ipython_extension.SageCustomizations method), 104
set underscore variable() (sage.repl.rich output.backend base.BackendBase method), 77
set_underscore_variable() (sage.repl.rich_output.backend_ipython.BackendIPython method), 85
setter() (sage.repl.rich_output.preferences.Property method), 54
shell class (sage.repl.interpreter.SageTerminalApp attribute), 101
shell class (sage.repl.ipython kernel.kernel.SageKernel attribute), 126
show() (sage.repl.image.Image method), 134
show usage() (sage.repl.interpreter.SageShellOverride method), 100
signature() (sage.repl.ipython kernel.interact.sage interactive method), 112
slider() (in module sage.repl.ipython_kernel.widgets_sagenb), 122
SomeIPythonRepr (class in sage.repl.display.fancy repr), 41
strip_prompts() (in module sage.repl.preparse), 22
strip_string_literals() (in module sage.repl.preparse), 22
supplemental plot (sage.repl.rich output.preferences.DisplayPreferences attribute), 52
supported_output() (sage.repl.rich_output.backend_base.BackendBase method), 78
supported output() (sage.repl.rich output.backend base.BackendSimple method), 79
supported output() (sage.repl.rich output.backend doctest.BackendDoctest method), 83
supported_output() (sage.repl.rich_output.backend_ipython.BackendIPythonCommandline method), 88
supported_output() (sage.repl.rich_output.backend_ipython.BackendIPythonNotebook method), 89
supported output() (sage.repl.rich output.backend sagenb.BackendSageNB method), 92
supported_output() (sage.repl.rich_output.backend_test.BackendTest method), 81
supported output() (sage.repl.rich output.display manager.DisplayManager method), 48
switch_backend() (sage.repl.rich_output.display_manager.DisplayManager method), 48
symlink() (sage.repl.ipython_kernel.install.SageKernelSpec method), 124
system raw() (sage.repl.interpreter.SageShellOverride method), 100
```

Т

```
TallListFormatter (class in sage.repl.display.util), 42
TallListRepr (class in sage.repl.display.fancy repr), 41
temporary_objects (sage.repl.interpreter.InterfaceShellTransformer attribute), 97
test shell (sage.repl.interpreter.SageTerminalApp attribute), 101
TestObject (class in sage.repl.rich output.backend test), 81
TestOutputPlainText (class in sage.repl.rich_output.backend_test), 81
text (sage.repl.rich output.preferences.DisplayPreferences attribute), 52
threejs_offline_scripts() (sage.repl.rich_output.backend_ipython.BackendIPythonCommandline method), 88
threejs_offline_scripts() (sage.repl.rich_output.backend_ipython.BackendIPythonNotebook method), 90
threejs offline scripts() (sage.repl.rich output.backend sagenb.BackendSageNB method), 92
threejs_scripts() (sage.repl.rich_output.display_manager.DisplayManager method), 49
toplevel() (sage.repl.display.pretty_print.SagePrettyPrinter method), 38
trace() (in module sage.misc.trace), 8
transform() (sage.repl.interpreter.InterfaceShellTransformer method), 98
TransformFloatRangeSlider (class in sage.repl.ipython_kernel.widgets), 116
TransformFloatSlider (class in sage.repl.ipython_kernel.widgets), 116
TransformIntRangeSlider (class in sage.repl.ipython_kernel.widgets), 116
TransformIntSlider (class in sage.repl.ipython kernel.widgets), 116
TransformText (class in sage.repl.ipython_kernel.widgets), 117
TransformTextarea (class in sage.repl.ipython kernel.widgets), 117
TransformWidget (class in sage.repl.ipython kernel.widgets), 117
try format() (sage.repl.display.util.TallListFormatter method), 43
types (sage.repl.rich_output.display_manager.DisplayManager attribute), 49
U
unicode art formatter() (sage.repl.rich output.backend base.BackendBase method), 78
uninstall() (in module sage.repl.inputhook), 134
uninstall() (sage.repl.rich_output.backend_base.BackendBase method), 79
uninstall() (sage.repl.rich output.backend doctest.BackendDoctest method), 84
update() (sage.repl.ipython kernel.install.SageKernelSpec class method), 124
use_local_ismol() (sage.repl.ipython_kernel.install.SageKernelSpec method), 125
use_local_mathjax() (sage.repl.ipython_kernel.install.SageKernelSpec method), 125
use_local_threejs() (sage.repl.ipython_kernel.install.SageKernelSpec method), 125
V
validate() (sage.repl.rich_output.backend_doctest.BackendDoctest method), 84
value (sage.repl.ipython_kernel.widgets.Grid attribute), 115
W
widget_from_iterable() (sage.repl.ipython_kernel.interact.sage_interactive class method), 112
widget_from_single_value() (sage.repl.ipython_kernel.interact.sage_interactive class method), 112
widget from tuple() (sage.repl.ipython kernel.interact.sage interactive class method), 113
width() (sage.repl.image.Image method), 134
world_readable() (in module sage.repl.rich_output.backend_sagenb), 94
```