
Modules

Release 9.7

The Sage Development Team

Sep 20, 2022

CONTENTS

1	Tutorial: Using free modules and vector spaces	3
1.1	Construction, arithmetic, and basic usage	3
1.2	Manipulating free module elements	5
1.3	Manipulating free modules	6
1.4	Review	7
2	Free modules, submodules, and quotients	9
2.1	Abstract base class for modules	9
2.2	Free modules	12
2.3	Elements of free modules	76
2.4	Submodules and subquotients of free modules	126
2.5	Quotients of free modules	129
3	Modules with basis	137
3.1	Concrete classes related to modules with a distinguished basis	137
3.2	Cell modules	137
3.3	An element in an indexed free module	140
3.4	Invariant modules	142
3.5	Morphisms of modules with a basis	150
3.6	Quotients of modules with basis	164
3.7	Representations of a semigroup	168
4	Finitely generated modules over a PID	175
4.1	Finitely generated modules over a PID	175
4.2	Elements of finitely generated modules over a PID	193
4.3	Morphisms between finitely generated modules over a PID	195
5	Finitely presented graded modules	199
5.1	Finitely generated free graded left modules over connected graded algebras	199
5.2	Elements of finitely generated free graded left modules	211
5.3	Homomorphisms of finitely generated free graded left modules	214
5.4	Homsets of finitely generated free graded left modules	215
5.5	Finitely presented graded modules	216
5.6	Elements of finitely presented graded modules	230
5.7	Homomorphisms of finitely presented graded modules	233
5.8	Homsets of finitely presented graded modules	247
5.9	Finitely presented graded modules over the Steenrod algebra	249
5.10	Homomorphisms of finitely presented modules over the Steenrod algebra	253
6	Special modules	259
6.1	Discrete subgroups of \mathbb{Z}^n	259

6.2	Free quadratic modules	268
6.3	Integral lattices	280
6.4	Finite \mathbf{Z} -modules with bilinear and quadratic forms	301
6.5	\mathbf{Z} -filtered vector spaces	313
6.6	Multiple \mathbf{Z} -graded filtrations of a single vector space	324
7	Morphisms	333
7.1	Space of morphisms of vector spaces (linear transformations)	333
7.2	Morphisms of vector spaces (linear transformations)	336
7.3	Homspaces between free modules	348
7.4	Morphisms of free modules	351
7.5	Morphisms defined by a matrix	362
8	Vectors	381
8.1	Vectors with integer entries	381
8.2	Vectors with elements in \mathbf{F}_2	382
8.3	Vectors with integer mod n entries, with small n	383
8.4	Vectors with rational entries	384
8.5	Vectors over the symbolic ring	385
8.6	Vectors over callable symbolic rings	392
8.7	Dense vectors using a NumPy backend	392
8.8	Dense real double vectors using a NumPy backend	398
8.9	Dense complex double vectors using a NumPy backend	399
8.10	Pickling for the old CDF vector class	400
8.11	Pickling for the old RDF vector class	400
9	Misc	401
9.1	Diamond cutting implementation	401
9.2	Helper classes to implement tensor operations	403
9.3	Iterators over finite submodules of a \mathbf{Z} -module	408
9.4	Miscellaneous module-related functions	410
10	Indices and Tables	413
	Python Module Index	415
	Index	417

Sage provides modules of various kinds over various base rings.

TUTORIAL: USING FREE MODULES AND VECTOR SPACES

AUTHOR: Jason Bandlow

In this tutorial, we show how to construct and manipulate free modules and vector spaces and their elements.

Sage currently provides two implementations of free modules: *FreeModule* and *CombinatorialFreeModule*. The distinction between the two is mostly an accident in history. The latter allows for the basis to be indexed by any kind of objects, instead of just $0, 1, 2, \dots$. They also differ by feature set and efficiency. Eventually, both implementations will be merged under the name *FreeModule*. In the mean time, we focus here on *CombinatorialFreeModule*. We recommend to start by browsing its documentation:

```
sage: CombinatorialFreeModule? # not tested
```

1.1 Construction, arithmetic, and basic usage

We begin with a minimal example:

```
sage: G = Zmod(5)
sage: F = CombinatorialFreeModule(ZZ, G)
sage: F.an_element()
2*B[0] + 2*B[1] + 3*B[2]
```

F is the free module over the ring integers \mathbb{Z} whose canonical basis is indexed by the set of integers modulo 5.

We can use any set, finite or not, to index the basis, as long as its elements are immutable. Here are some \mathbb{Z} -free modules; what is the indexing set for the basis in each example below?

```
sage: F = CombinatorialFreeModule(ZZ, CC); F.an_element()
B[1.0000000000000000*I]
sage: F = CombinatorialFreeModule(ZZ, Partitions(NonNegativeIntegers(), max_part=3)); F.
↪an_element()
2*B[[]] + 2*B[[1]] + 3*B[[2]]
sage: F = CombinatorialFreeModule(ZZ, ['spam', 'eggs', '42']); F.an_element()
3*B['42'] + 2*B['eggs'] + 2*B['spam']
```

Note that we use '42' (and not the number 42) in order to ensure that all objects are comparable in a deterministic way, which allows the elements to be printed in a predictable manner. It is not mandatory that indices have such a stable ordering, but if they do not, then the elements may be displayed in some random order.

Lists are not hashable, and thus cannot be used to index the basis; instead one can use tuples:

```
sage: F = CombinatorialFreeModule(ZZ, ([1],[2],[3])); F.an_element()
Traceback (most recent call last):
...
TypeError: unhashable type: 'list'

sage: F = CombinatorialFreeModule(ZZ, ((1,),(2,),(3,))); F.an_element()
2*B[(1,)] + 2*B[(2,)] + 3*B[(3,)]
```

The name of the basis can be customized:

```
sage: F = CombinatorialFreeModule(ZZ, Zmod(5), prefix='a'); F.an_element()
2*a[0] + 2*a[1] + 3*a[2]
```

Let us do some arithmetic with elements of A :

```
sage: f = F.an_element(); f
2*a[0] + 2*a[1] + 3*a[2]

sage: 2*f
4*a[0] + 4*a[1] + 6*a[2]

sage: 2*f - f
2*a[0] + 2*a[1] + 3*a[2]
```

Inputting elements as they are output does not work by default:

```
sage: a[0] + 3*a[1]
Traceback (most recent call last):
...
NameError: name 'a' is not defined
```

To enable this, we must first get the *canonical basis* for the module:

```
sage: a = F.basis(); a
Lazy family (Term map from Ring of integers modulo 5 to Free module generated by Ring of
↳ integers modulo 5 over Integer Ring(i))_{i in Ring of integers modulo 5}
```

This gadget models the family $(B_i)_{i \in \mathbb{Z}_5}$. In particular, one can run through its elements:

```
sage: list(a)
[a[0], a[1], a[2], a[3], a[4]]
```

recover its indexing set:

```
sage: a.keys()
Ring of integers modulo 5
```

or construct an element from the corresponding index:

```
sage: a[2]
a[2]
```

So now we can do:


```
sage: a[0] + 3*a[1]
a[0] + 3*a[1]
```

which enables copy-pasting outputs as long as the prefix matches the name of the basis:

```
sage: 2*a[0] + 2*a[1] + 3*a[2] == f
True
```

Be careful that the input is currently *not* checked:

```
sage: a['is'] + a['this'] + a['a'] + a['bug']
a['a'] + a['bug'] + a['is'] + a['this']
```

1.2 Manipulating free module elements

The elements of our module come with many methods for exploring and manipulating them:

```
sage: f.<tab>                                # not tested
```

Some definitions:

- A *monomial* is an element of the basis B_i ;
- A *term* is an element of the basis multiplied by a non zero *coefficient*: cB_i ;
- The support of that term is i .
- The corresponding *item* is the tuple (i, c) .
- The *support* of an element f is the collection of indices i such that B_i appears in f with non zero coefficient.
- The *monomials*, *terms*, *items*, and *coefficients* of an element f are defined accordingly.
- *Leading/trailing* refers to the *greatest/least* index. Elements are printed starting with the *least* index (for lexicographic order by default).

Let us investigate those definitions on our example:

```
sage: f
2*a[0] + 2*a[1] + 3*a[2]
sage: f.leading_term()
3*a[2]
sage: f.leading_monomial()
a[2]
sage: f.leading_support()
2
sage: f.leading_coefficient()
3
sage: f.leading_item()
(2, 3)

sage: f.support()
[0, 1, 2]
sage: f.monomials()
[a[0], a[1], a[2]]
```

(continues on next page)

(continued from previous page)

```
sage: f.coefficients()
[2, 2, 3]
```

We can iterate through the items of an element:

```
sage: for index, coeff in f:
.....:     print("The coefficient of a_{%s} is %s"%(index, coeff))
The coefficient of a_{0} is 2
The coefficient of a_{1} is 2
The coefficient of a_{2} is 3
```

This element can be thought of as a dictionary index→coefficient:

```
sage: f[0], f[1], f[2]
(2, 2, 3)
```

This dictionary can be accessed explicitly with the `monomial_coefficients` method:

```
sage: f.monomial_coefficients()
{0: 2, 1: 2, 2: 3}
```

The map methods are useful to transform elements:

```
sage: f
2*a[0] + 2*a[1] + 3*a[2]
sage: f.map_support(lambda i: i+1)
2*a[1] + 2*a[2] + 3*a[3]
sage: f.map_coefficients(lambda c: c-3)
-a[0] - a[1]
sage: f.map_item(lambda i,c: (i+1,c-3))
-a[1] - a[2]
```

Note: this last function should be called `map_items`!

1.3 Manipulating free modules

The free module itself (A in our example) has several utility methods for constructing elements:

```
sage: F.zero()
0
sage: F.term(1)
a[1]
sage: F.sum_of_monomials(i for i in Zmod(5) if i > 2)
a[3] + a[4]
sage: F.sum_of_terms((i+1,i) for i in Zmod(5) if i > 2)
4*a[0] + 3*a[4]
sage: F.sum(ZZ(i)*a[i+1] for i in Zmod(5) if i > 2) # Note coeff is not (currently)
↳implicitly coerced
4*a[0] + 3*a[4]
```

Is safer to use `F.sum()` than to use `sum()`: in case the input is an empty iterable, it makes sure the zero of A is returned, and not a plain 0:

```
sage: F.sum([], parent(F.sum([]))  
(0, Free module generated by Ring of integers modulo 5 over Integer Ring)  
sage: sum([], parent(sum([]))  
(0, <... 'int'>)
```

Todo: Introduce echelon forms, submodules, quotients in the finite dimensional case

1.4 Review

In this tutorial we have seen how to construct vector spaces and free modules with a basis indexed by any kind of objects.

To learn how to endow such free modules with additional structure, define morphisms, or implement modules with several distinguished basis, see the [Implementing Algebraic Structures](#) thematic tutorial.

FREE MODULES, SUBMODULES, AND QUOTIENTS

2.1 Abstract base class for modules

AUTHORS:

- William Stein: initial version
- Julian Rueth (2014-05-10): category parameter for Module, doc cleanup

EXAMPLES:

A minimal example of a module:

```
sage: from sage.structure.richcmp import richcmp
sage: class MyElement(sage.structure.element.ModuleElement):
.....:     def __init__(self, parent, x):
.....:         self.x = x
.....:         sage.structure.element.ModuleElement.__init__(self, parent=parent)
.....:     def _lmul_(self, c):
.....:         return self.parent()(c*self.x)
.....:     def _add_(self, other):
.....:         return self.parent()(self.x + other.x)
.....:     def _richcmp_(self, other, op):
.....:         return richcmp(self.x, other.x, op)
.....:     def __hash__(self):
.....:         return hash(self.x)
.....:     def _repr_(self):
.....:         return repr(self.x)

sage: class MyModule(sage.modules.module.Module):
.....:     Element = MyElement
.....:     def _element_constructor_(self, x):
.....:         if isinstance(x, MyElement): x = x.x
.....:         return self.element_class(self, self.base_ring()(x))
.....:     def __eq__(self, other):
.....:         if not isinstance(other, MyModule): return False
.....:         return self.base_ring() == other.base_ring()
.....:     def __hash__(self):
.....:         return hash(self.base_ring())

sage: M = MyModule(QQ)
sage: M(1)
```

(continues on next page)

(continued from previous page)

```
1
sage: import __main__
sage: __main__.MyModule = MyModule
sage: __main__.MyElement = MyElement
sage: TestSuite(M).run()
```

class sage.modules.module.**Module**
 Bases: sage.structure.parent.Parent

Generic module class.

INPUT:

- **base** – a ring. The base ring of the module.
- **category** – a category (default: None), the category for this module. If None, then this is set to the category of modules/vector spaces over base.
- **names** – names of generators

EXAMPLES:

```
sage: from sage.modules.module import Module
sage: M = Module(ZZ)
sage: M.base_ring()
Integer Ring
sage: M.category()
Category of modules over Integer Ring
```

Normally the category is set to the category of modules over base. If base is a field, then the category is the category of vector spaces over base:

```
sage: M_QQ = Module(QQ)
sage: M_QQ.category()
Category of vector spaces over Rational Field
```

The category parameter can be used to set a more specific category:

```
sage: N = Module(ZZ, category=FiniteDimensionalModulesWithBasis(ZZ))
sage: N.category()
Category of finite dimensional modules with basis over Integer Ring
```

base_extend(R)

Return the base extension of self to R .

This is the same as `self.change_ring(R)` except that a `TypeError` is raised if there is no canonical coerce map from the base ring of self to R .

INPUT:

- **R** – ring

EXAMPLES:

```
sage: V = ZZ^7
sage: V.base_extend(QQ)
Vector space of dimension 7 over Rational Field
```

change_ring(*R*)

Return the base change of self to *R*.

EXAMPLES:

```
sage: sage.modular.modform.space.ModularFormsSpace(Gamma0(11), 2,
↳ DirichletGroup(1)[0], QQ).change_ring(GF(7))
Traceback (most recent call last):
...
NotImplementedError: the method change_ring() has not yet been implemented
```

endomorphism_ring()

Return the endomorphism ring of this module in its category.

EXAMPLES:

```
sage: from sage.modules.module import Module
sage: M = Module(ZZ)
sage: M.endomorphism_ring()
Set of Morphisms from <sage.modules.module.Module object at ...> to <sage.
↳ modules.module.Module object at ...> in Category of modules over Integer Ring
```

sage.modules.module.is_Module(*x*)

Return True if *x* is a module, False otherwise.

INPUT:

- *x* – anything.

EXAMPLES:

```
sage: from sage.modules.module import is_Module
sage: M = FreeModule(RationalField(), 30)
sage: is_Module(M)
True
sage: is_Module(10)
False
```

sage.modules.module.is_VectorSpace(*x*)

Return True if *x* is a vector space, False otherwise.

INPUT:

- *x* – anything.

EXAMPLES:

```
sage: from sage.modules.module import is_Module, is_VectorSpace
sage: M = FreeModule(RationalField(), 30)
sage: is_VectorSpace(M)
True
sage: M = FreeModule(IntegerRing(), 30)
sage: is_Module(M)
True
sage: is_VectorSpace(M)
False
```

2.2 Free modules

Sage supports computation with free modules over an arbitrary commutative ring. Nontrivial functionality is available over \mathbf{Z} , fields, and some principal ideal domains (e.g. $\mathbf{Q}[x]$ and rings of integers of number fields). All free modules over an integral domain are equipped with an embedding in an ambient vector space and an inner product, which you can specify and change.

Create the free module of rank n over an arbitrary commutative ring R using the command `FreeModule(R,n)`. Equivalently, `R^n` also creates that free module.

The following example illustrates the creation of both a vector space and a free module over the integers and a submodule of it. Use the functions `FreeModule`, `span` and member functions of free modules to create free modules. *Do not use the `FreeModule_XXX` constructors directly.*

EXAMPLES:

```
sage: V = VectorSpace(QQ,3)
sage: W = V.subspace([[1,2,7], [1,1,0]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -7]
[ 0  1  7]
sage: C = VectorSpaces(FiniteField(7))
sage: C
Category of vector spaces over Finite Field of size 7
sage: C(W)
Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0 0]
[0 1 0]
```

```
sage: M = ZZ^3
sage: C = VectorSpaces(FiniteField(7))
sage: C(M)
Vector space of dimension 3 over Finite Field of size 7
sage: W = M.submodule([[1,2,7], [8,8,0]])
sage: C(W)
Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0 0]
[0 1 0]
```

We illustrate the exponent notation for creation of free modules.

```
sage: ZZ^4
Ambient free module of rank 4 over the principal ideal domain Integer Ring
sage: QQ^2
Vector space of dimension 2 over Rational Field
sage: RR^3
Vector space of dimension 3 over Real Field with 53 bits of precision
```

Base ring:


```
sage: R.<x,y> = QQ[]
sage: M = FreeModule(R,2)
sage: M.base_ring()
Multivariate Polynomial Ring in x, y over Rational Field
```

```
sage: VectorSpace(QQ, 10).base_ring()
Rational Field
```

Enumeration of \mathbb{Z}^n happens in order of increasing 1-norm primarily and increasing ∞ -norm secondarily:

```
sage: print([v for _,v in zip(range(31), ZZ^3)])
[(0, 0, 0),
 (1, 0, 0), (-1, 0, 0), (0, 1, 0), (0, -1, 0), (0, 0, 1), (0, 0, -1),
 (1, 1, 0), (-1, 1, 0), (1, -1, 0), (-1, -1, 0), (1, 0, 1), (-1, 0, 1), (1, 0, -1), (-1,
 ↪ 0, -1), (0, 1, 1), (0, -1, 1), (0, 1, -1), (0, -1, -1),
 (2, 0, 0), (-2, 0, 0), (0, 2, 0), (0, -2, 0), (0, 0, 2), (0, 0, -2),
 (1, 1, 1), (-1, 1, 1), (1, -1, 1), (-1, -1, 1), (1, 1, -1), ...]
```

For other infinite enumerated base rings (i.e., rings which are objects of the category `InfiniteEnumeratedSets`), a free module of rank r is enumerated by applying `FreeModule_ambient.linear_combination_of_basis()` to all vectors in \mathbb{Z}^r , enumerated in the way shown above.

AUTHORS:

- William Stein (2005, 2007)
- David Kohel (2007, 2008)
- Niles Johnson (2010-08): ([trac ticket #3893](#)) `random_element()` should pass on `*args` and `**kwds`.
- Simon King (2010-12): ([trac ticket #8800](#)) fixed a bug in `denominator()`.
- Simon King (2010-12), Peter Bruin (June 2014): ([trac ticket #10513](#)) new coercion model and category framework.

```
class sage.modules.free_module.ComplexDoubleVectorSpace_class(n)
```

Bases: `sage.modules.free_module.FreeModule_ambient_field`

`coordinates(v)`

```
class sage.modules.free_module.EchelonMatrixKey(obj)
```

Bases: `object`

A total ordering on free modules for sorting.

This class orders modules by their ambient spaces, then by dimension, then in order by their echelon matrices. If a function returns a list of free modules, this can be used to sort the output and thus render it deterministic.

INPUT:

- `obj` – a free module

EXAMPLES:

```
sage: V = span([[1,2,3], [5,6,7], [8,9,10]], QQ)
sage: W = span([[5,6,7], [8,9,10]], QQ)
sage: X = span([[5,6,7]], ZZ).scale(1/11)
sage: Y = CC^3
sage: Z = ZZ^2
sage: modules = [V,W,X,Y,Z]
```

(continues on next page)

(continued from previous page)

```

sage: modules_sorted = [Z,X,V,W,Y]
sage: from sage.modules.free_module import EchelonMatrixKey
sage: modules.sort(key=EchelonMatrixKey)
sage: modules == modules_sorted
True

```

```

sage.modules.free_module.FreeModule(base_ring, rank_or_basis_keys, sparse, inner_product_matrix,
                                     with_basis=None, rank=False, basis_keys=None, **args)

```

Create a free module over the given commutative `base_ring`

`FreeModule` can be called with the following positional arguments:

- `FreeModule(base_ring, rank, ...)`
- `FreeModule(base_ring, basis_keys, ...)`

INPUT:

- `base_ring` – a commutative ring
- `rank` – a nonnegative integer
- `basis_keys` – a finite or enumerated family of arbitrary objects
- `sparse` – boolean (default `False`)
- `inner_product_matrix` – the inner product matrix (default `None`)
- `with_basis` – either "standard" (the default), in which case a free module with the standard basis as the distinguished basis is created; or `None`, in which case a free module without distinguished basis is created.
- further options may be accepted by various implementation classes

OUTPUT: a free module

This factory function creates instances of various specialized classes depending on the input. Not all combinations of options are implemented.

- If the parameter `basis_keys` is provided, it must be a finite or enumerated family of objects, and an instance of `CombinatorialFreeModule` is created.

EXAMPLES:

```

sage: CombinatorialFreeModule(QQ, ['a','b','c'])
Free module generated by {'a', 'b', 'c'} over Rational Field

```

It has a distinguished standard basis that is indexed by the provided `basis_keys`. See the documentation of `CombinatorialFreeModule` for more examples and details, including its `UniqueRepresentation` semantics.

- If the parameter `with_basis` is set to `None`, then a free module of the given `rank` without distinguished basis is created. It is represented by an instance of `FiniteRankFreeModule`.

EXAMPLES:

```

sage: FiniteRankFreeModule(ZZ, 3, name='M')
Rank-3 free module M over the Integer Ring

```

See the documentation of `FiniteRankFreeModule` for more options, examples, and details.

- If rank is provided and the option `with_basis` is left at its default value, "standard", then a free ambient module with distinguished standard basis indexed by `range(rank)` is created. There is only one dense and one sparse free ambient module of given rank over `base_ring`.

EXAMPLES:

```
sage: FreeModule(Integers(8), 10)
Ambient free module of rank 10 over Ring of integers modulo 8
```

The remainder of this documentation discusses this case of free ambient modules.

EXAMPLES:

First we illustrate creating free modules over various base fields. The base field affects the free module that is created. For example, free modules over a field are vector spaces, and free modules over a principal ideal domain are special in that more functionality is available for them than for completely general free modules.

```
sage: FreeModule(QQ, 10)
Vector space of dimension 10 over Rational Field
sage: FreeModule(ZZ, 10)
Ambient free module of rank 10 over the principal ideal domain Integer Ring
sage: FreeModule(FiniteField(5), 10)
Vector space of dimension 10 over Finite Field of size 5
sage: FreeModule(Integers(7), 10)
Vector space of dimension 10 over Ring of integers modulo 7
sage: FreeModule(PolynomialRing(QQ, 'x'), 5)
Ambient free module of rank 5 over the principal ideal domain Univariate Polynomial_
↳Ring in x over Rational Field
sage: FreeModule(PolynomialRing(ZZ, 'x'), 5)
Ambient free module of rank 5 over the integral domain Univariate Polynomial Ring_
↳in x over Integer Ring
```

Of course we can make rank 0 free modules:

```
sage: FreeModule(RealField(100), 0)
Vector space of dimension 0 over Real Field with 100 bits of precision
```

Next we create a free module with sparse representation of elements. Functionality with sparse modules is *identical* to dense modules, but they may use less memory and arithmetic may be faster (or slower!).

```
sage: M = FreeModule(ZZ, 200, sparse=True)
sage: M.is_sparse()
True
sage: type(M.0)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
```

The default is dense.

```
sage: M = ZZ^200
sage: type(M.0)
<class 'sage.modules.vector_integer_dense.Vector_integer_dense'>
```

Note that matrices associated in some way to sparse free modules are sparse by default:

```
sage: M = FreeModule(Integers(8), 2)
sage: A = M.basis_matrix()
```

(continues on next page)

(continued from previous page)

```
sage: A.is_sparse()
False
sage: Ms = FreeModule(Integers(8), 2, sparse=True)
sage: M == Ms # as mathematical objects they are equal
True
sage: Ms.basis_matrix().is_sparse()
True
```

We can also specify an inner product matrix, which is used when computing inner products of elements.

```
sage: A = MatrixSpace(ZZ,2)([[1,0],[0,-1]])
sage: M = FreeModule(ZZ,2,inner_product_matrix=A)
sage: v, w = M.gens()
sage: v.inner_product(w)
0
sage: v.inner_product(v)
1
sage: w.inner_product(w)
-1
sage: (v+2*w).inner_product(w)
-2
```

You can also specify the inner product matrix by giving anything that coerces to an appropriate matrix. This is only useful if the inner product matrix takes values in the base ring.

```
sage: FreeModule(ZZ,2,inner_product_matrix=1).inner_product_matrix()
[1 0]
[0 1]
sage: FreeModule(ZZ,2,inner_product_matrix=[1,2,3,4]).inner_product_matrix()
[1 2]
[3 4]
sage: FreeModule(ZZ,2,inner_product_matrix=[[1,2],[3,4]]).inner_product_matrix()
[1 2]
[3 4]
```

Todo: Refactor modules such that it only counts what category the base ring belongs to, but not what is its Python class.

EXAMPLES:

```
sage: FreeModule(QQ, ['a', 'b', 'c'])
Free module generated by {'a', 'b', 'c'} over Rational Field
sage: _.category()
Category of finite dimensional vector spaces with basis over Rational Field

sage: FreeModule(QQ, 3, with_basis=None)
3-dimensional vector space over the Rational Field
sage: _.category()
Category of finite dimensional vector spaces over Rational Field

sage: FreeModule(QQ, [1, 2, 3, 4], with_basis=None)
```

(continues on next page)

(continued from previous page)

```
4-dimensional vector space over the Rational Field
sage: _.category()
Category of finite dimensional vector spaces over Rational Field
```

class sage.modules.free_module.FreeModuleFactory

Bases: [sage.structure.factory.UniqueFactory](#)

Factory class for the finite-dimensional free modules with standard basis

create_key(*base_ring*, *rank*, *sparse=False*, *inner_product_matrix=None*)

create_object(*version*, *key*)

class sage.modules.free_module.FreeModule_ambient(*base_ring*, *rank*, *sparse=False*,
coordinate_ring=None)

Bases: [sage.modules.free_module.FreeModule_generic](#)

Ambient free module over a commutative ring.

ambient_module()

Return self, since self is ambient.

EXAMPLES:

```
sage: A = QQ^5; A.ambient_module()
Vector space of dimension 5 over Rational Field
sage: A = ZZ^5; A.ambient_module()
Ambient free module of rank 5 over the principal ideal domain Integer Ring
```

basis()

Return a basis for this ambient free module.

OUTPUT:

- Sequence - an immutable sequence with universe this ambient free module

EXAMPLES:

```
sage: A = ZZ^3; B = A.basis(); B
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
sage: B.universe()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

change_ring(*R*)

Return the ambient free module over *R* of the same rank as self.

EXAMPLES:

```
sage: A = ZZ^3; A.change_ring(QQ)
Vector space of dimension 3 over Rational Field
sage: A = ZZ^3; A.change_ring(GF(5))
Vector space of dimension 3 over Finite Field of size 5
```

For ambient modules any change of rings is defined.

```
sage: A = GF(5)**3; A.change_ring(QQ)
Vector space of dimension 3 over Rational Field
```

coordinate_vector(*v*, *check=True*)

Write *v* in terms of the standard basis for *self* and return the resulting coefficients in a vector over the fraction field of the base ring.

Returns a vector *c* such that if *B* is the basis for *self*, then

$$\sum c_i B_i = v.$$

If *v* is not in *self*, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = Integers(16)^3
sage: v = V.coordinate_vector([1,5,9]); v
(1, 5, 9)
sage: v.parent()
Ambient free module of rank 3 over Ring of integers modulo 16
```

echelon_coordinate_vector(*v*, *check=True*)

Same as `self.coordinate_vector(v)`, since *self* is an ambient free module.

INPUT:

- *v* - vector
- *check* - boolean (default: `True`); if `True`, also verify that *v* is really in *self*.

OUTPUT: list

EXAMPLES:

```
sage: V = QQ^4
sage: v = V([-1/2, 1/2, -1/2, 1/2])
sage: v
(-1/2, 1/2, -1/2, 1/2)
sage: V.coordinate_vector(v)
(-1/2, 1/2, -1/2, 1/2)
sage: V.echelon_coordinate_vector(v)
(-1/2, 1/2, -1/2, 1/2)
sage: W = V.submodule_with_basis([[1/2, 1/2, 1/2, 1/2], [1, 0, 1, 0]])
sage: W.coordinate_vector(v)
(1, -1)
sage: W.echelon_coordinate_vector(v)
(-1/2, 1/2)
```

echelon_coordinates(*v*, *check=True*)

Returns the coordinate vector of *v* in terms of the echelon basis for *self*.

EXAMPLES:

```
sage: U = VectorSpace(QQ, 3)
sage: [ U.coordinates(v) for v in U.basis() ]
[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
sage: [ U.echelon_coordinates(v) for v in U.basis() ]
```

(continues on next page)

(continued from previous page)

```

[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
sage: V = U.submodule([[1,1,0],[0,1,1]])
sage: V
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  1]
sage: [ V.coordinates(v) for v in V.basis() ]
[[1, 0], [0, 1]]
sage: [ V.echelon_coordinates(v) for v in V.basis() ]
[[1, 0], [0, 1]]
sage: W = U.submodule_with_basis([[1,1,0],[0,1,1]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 1 0]
[0 1 1]
sage: [ W.coordinates(v) for v in W.basis() ]
[[1, 0], [0, 1]]
sage: [ W.echelon_coordinates(v) for v in W.basis() ]
[[1, 1], [0, 1]]

```

echelonized_basis()

Return a basis for this ambient free module in echelon form.

EXAMPLES:

```

sage: A = ZZ^3; A.echelonized_basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]

```

echelonized_basis_matrix()

The echelonized basis matrix of self.

EXAMPLES:

```

sage: V = ZZ^4
sage: W = V.submodule([ V.gen(i)-V.gen(0) for i in range(1,4) ])
sage: W.basis_matrix()
[ 1  0  0 -1]
[ 0  1  0 -1]
[ 0  0  1 -1]
sage: W.echelonized_basis_matrix()
[ 1  0  0 -1]
[ 0  1  0 -1]
[ 0  0  1 -1]
sage: U = V.submodule_with_basis([ V.gen(i)-V.gen(0) for i in range(1,4) ])
sage: U.basis_matrix()
[-1  1  0  0]
[-1  0  1  0]

```

(continues on next page)

(continued from previous page)

```

[-1  0  0  1]
sage: U.echelonized_basis_matrix()
[ 1  0  0 -1]
[ 0  1  0 -1]
[ 0  0  1 -1]

```

gen(*i*=0)Return the *i*-th generator for **self**.Here *i* is between 0 and rank - 1, inclusive.

INPUT:

- *i* – an integer (default 0)

OUTPUT: *i*-th basis vector for **self**.

EXAMPLES:

```

sage: n = 5
sage: V = QQ^n
sage: B = [V.gen(i) for i in range(n)]
sage: B
[(1, 0, 0, 0, 0),
 (0, 1, 0, 0, 0),
 (0, 0, 1, 0, 0),
 (0, 0, 0, 1, 0),
 (0, 0, 0, 0, 1)]
sage: V.gens() == tuple(B)
True

```

is_ambient()

Return True since this module is an ambient module.

EXAMPLES:

```

sage: A = QQ^5; A.is_ambient()
True
sage: A = (QQ^5).span([[1,2,3,4,5]]); A.is_ambient()
False

```

linear_combination_of_basis(*v*)Return the linear combination of the basis for **self** obtained from the elements of the list *v*.

INPUT:

- *v* - list

EXAMPLES:

```

sage: V = span([[1,2,3], [4,5,6]], ZZ)
sage: V
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]

```

(continues on next page)

(continued from previous page)

```
sage: V.linear_combination_of_basis([1,1])
(1, 5, 9)
```

This should raise an error if the resulting element is not in self:

```
sage: W = span([[2,4]], ZZ)
sage: W.linear_combination_of_basis([1/2])
Traceback (most recent call last):
...
TypeError: element [1, 2] is not in free module
```

random_element(*prob=1.0*, **args*, ***kws*)

Returns a random element of self.

INPUT:

- **prob** - float. Each coefficient will be set to zero with probability $1 - \text{prob}$. Otherwise coefficients will be chosen randomly from base ring (and may be zero).
- ***args**, ****kws** - passed on to **random_element** function of base ring.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.random_element().parent() is M
True
```

Passes extra positional or keyword arguments through:

```
sage: all(i in range(5, 10) for i in M.random_element(1.0, 5, 10))
True
```

```
sage: M = FreeModule(ZZ, 16)
sage: M.random_element().parent() is M
True

sage: def add_sample(**kws):
....:     global total, zeros
....:     v = M.random_element(**kws)
....:     total += M.rank()
....:     zeros += sum(i == 0 for i in v)

sage: total = 0
sage: zeros = 0
sage: add_sample()
sage: expected = 1/5
sage: while abs(zeros/total - expected) > 0.01:
....:     add_sample()

sage: total = 0
sage: zeros = 0
sage: add_sample(prob=0.3)
sage: expected = 1/5 * 3/10 + 7/10
sage: while abs(zeros/total - expected) > 0.01:
```

(continues on next page)

(continued from previous page)

```

.....:      add_sample(prob=0.3)

sage: total = 0
sage: zeros = 0
sage: add_sample(prob=0.7)
sage: expected = 1/5 * 7/10 + 3/10
sage: while abs(zeros/total - expected) > 0.01:
.....:      add_sample(prob=0.7)

```

class sage.modules.free_module.FreeModule_ambient_domain(*base_ring*, *rank*, *sparse=False*,
coordinate_ring=None)

Bases: *sage.modules.free_module.FreeModule_generic_domain*, *sage.modules.free_module.FreeModule_ambient*

Ambient free module over an integral domain.

EXAMPLES:

```

sage: FreeModule(PolynomialRing(GF(5),'x'), 3)
Ambient free module of rank 3 over the principal ideal domain
Univariate Polynomial Ring in x over Finite Field of size 5

```

ambient_vector_space()

Return the ambient vector space, which is this free module tensored with its fraction field.

EXAMPLES:

```

sage: M = ZZ^3
sage: V = M.ambient_vector_space(); V
Vector space of dimension 3 over Rational Field

```

If an inner product on the module is specified, then this is preserved on the ambient vector space.

```

sage: N = FreeModule(ZZ,4,inner_product_matrix=1)
sage: U = N.ambient_vector_space()
sage: U
Ambient quadratic space of dimension 4 over Rational Field
Inner product matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
sage: P = N.submodule_with_basis([[1,-1,0,0],[0,1,-1,0],[0,0,1,-1]])
sage: P.gram_matrix()
[ 2 -1  0]
[-1  2 -1]
[ 0 -1  2]
sage: U == N.ambient_vector_space()
True
sage: U == V
False

```

coordinate_vector(*v*, *check=True*)

Write *v* in terms of the standard basis for self and return the resulting coefficients in a vector over the fraction field of the base ring.

INPUT:

- v – vector
- **check** – boolean (default: True); if True, also verify that v is really in self.

OUTPUT: list

The output is a vector c such that if B is the basis for self, then

$$\sum c_i B_i = v.$$

If v is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = ZZ^3
sage: v = V.coordinate_vector([1,5,9]); v
(1, 5, 9)
sage: v.parent()
Vector space of dimension 3 over Rational Field
```

vector_space(*base_field=None*)

Returns the vector space obtained from self by tensoring with the fraction field of the base ring and extending to the field.

EXAMPLES:

```
sage: M = ZZ^3; M.vector_space()
Vector space of dimension 3 over Rational Field
```

class `sage.modules.free_module.FreeModule_ambient_field`(*base_field, dimension, sparse=False*)
 Bases: `sage.modules.free_module.FreeModule_generic_field`, `sage.modules.free_module.FreeModule_ambient_pid`

ambient_vector_space()

Returns self as the ambient vector space.

EXAMPLES:

```
sage: M = QQ^3
sage: M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
```

base_field()

Returns the base field of this vector space.

EXAMPLES:

```
sage: M = QQ^3
sage: M.base_field()
Rational Field
```

class `sage.modules.free_module.FreeModule_ambient_pid`(*base_ring, rank, sparse=False, coordinate_ring=None*)
 Bases: `sage.modules.free_module.FreeModule_generic_pid`, `sage.modules.free_module.FreeModule_ambient_domain`

Ambient free module over a principal ideal domain.

```
class sage.modules.free_module.FreeModule_generic(base_ring, rank, degree, sparse=False,  
                                                    coordinate_ring=None, category=None)
```

Bases: `sage.modules.free_module.Module_free_ambient`

Base class for all free modules.

INPUT:

- `base_ring` – a commutative ring
- `rank` – a non-negative integer
- `degree` – a non-negative integer
- `sparse` – boolean (default: `False`)
- `coordinate_ring` – a ring containing `base_ring` (default: equal to `base_ring`)
- `category` – category (default: `None`)

If `base_ring` is a field, then the default category is the category of finite-dimensional vector spaces over that field; otherwise it is the category of finite-dimensional free modules over that ring. In addition, the category is intersected with the category of finite enumerated sets if the ring is finite or the rank is 0.

EXAMPLES:

```
sage: PolynomialRing(QQ,3,'x')^3
Ambient free module of rank 3 over the integral domain Multivariate Polynomial Ring
↳in x0, x1, x2 over Rational Field

sage: FreeModule(GF(7),3).category()
Category of enumerated finite dimensional vector spaces with basis over
(finite enumerated fields and subquotients of monoids and quotients of semigroups)

sage: V = QQ^4; V.category()
Category of finite dimensional vector spaces with basis over
(number fields and quotient fields and metric spaces)

sage: V = GF(5)**20; V.category()
Category of enumerated finite dimensional vector spaces with basis over (finite
↳enumerated fields and subquotients of monoids and quotients of semigroups)

sage: FreeModule(ZZ,3).category()
Category of finite dimensional modules with basis over
(euclidean domains and infinite enumerated sets
and metric spaces)

sage: (QQ^0).category()
Category of finite enumerated finite dimensional vector spaces with basis
over (number fields and quotient fields and metric spaces)
```

```
are_linearly_dependent(vecs)
```

Return `True` if the vectors `vecs` are linearly dependent and `False` otherwise.

EXAMPLES:

```
sage: M = QQ^3
sage: vecs = [M([1,2,3]), M([4,5,6])]
sage: M.are_linearly_dependent(vecs)
False
sage: vecs.append(M([3,3,3]))
sage: M.are_linearly_dependent(vecs)
True
```

(continues on next page)

(continued from previous page)

```

sage: R.<x> = QQ[]
sage: M = FreeModule(R, 2)
sage: vecs = [M([x^2+1, x+1]), M([x+2, 2*x+1])]
sage: M.are_linearly_dependent(vecs)
False
sage: vecs.append(M([-2*x+1, -2*x^2+1]))
sage: M.are_linearly_dependent(vecs)
True

```

base_field()

Return the base field, which is the fraction field of the base ring of this module.

EXAMPLES:

```

sage: FreeModule(GF(3), 2).base_field()
Finite Field of size 3
sage: FreeModule(ZZ, 2).base_field()
Rational Field
sage: FreeModule(PolynomialRing(GF(7), 'x'), 2).base_field()
Fraction Field of Univariate Polynomial Ring in x over Finite Field of size 7

```

basis()

Return the basis of this module.

EXAMPLES:

```

sage: FreeModule(Integers(12), 3).basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]

```

basis_matrix(ring=None)

Return the matrix whose rows are the basis for this free module.

INPUT:

- `ring` – (default: `self.coordinate_ring()`) a ring over which the matrix is defined

EXAMPLES:

```

sage: FreeModule(Integers(12), 3).basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]

```

```

sage: M = FreeModule(GF(7), 3).span([[2, 3, 4], [1, 1, 1]]); M
Vector space of degree 3 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0 6]
[0 1 2]
sage: M.basis_matrix()

```

(continues on next page)

(continued from previous page)

```
[1 0 6]
[0 1 2]
```

```
sage: M = FreeModule(GF(7), 3).span_of_basis([[2, 3, 4], [1, 1, 1]])
sage: M.basis_matrix()
[2 3 4]
[1 1 1]
```

```
sage: M = FreeModule(QQ, 2).span_of_basis([[1, -1], [1, 0]]); M
Vector space of degree 2 and dimension 2 over Rational Field
User basis matrix:
[ 1 -1]
[ 1  0]
sage: M.basis_matrix()
[ 1 -1]
[ 1  0]
```

cardinality()

Return the cardinality of the free module.

OUTPUT:

Either an integer or +Infinity.

EXAMPLES:

```
sage: k.<a> = FiniteField(9)
sage: V = VectorSpace(k, 3)
sage: V.cardinality()
729
sage: W = V.span([[1, 2, 1], [0, 1, 1]])
sage: W.cardinality()
81
sage: R = IntegerModRing(12)
sage: M = FreeModule(R, 2)
sage: M.cardinality()
144
sage: (QQ^3).cardinality()
+Infinity
```

codimension()

Return the codimension of this free module, which is the dimension of the ambient space minus the dimension of this free module.

EXAMPLES:

```
sage: M = Matrix(3, 4, range(12))
sage: V = M.left_kernel(); V
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 1 -2  1]
sage: V.dimension()
1
```

(continues on next page)

(continued from previous page)

```
sage: V.codimension()
2
```

The codimension of an ambient space is always zero:

```
sage: (QQ^10).codimension()
0
```

construction()

The construction functor and base ring for self.

EXAMPLES:

```
sage: R = PolynomialRing(QQ,3,'x')
sage: V = R^5
sage: V.construction()
(VectorFunctor, Multivariate Polynomial Ring in x0, x1, x2 over Rational Field)
```

coordinate_module(V)

Suppose V is a submodule of `self` (or a module commensurable with `self`), and that `self` is a free module over R of rank n . Let ϕ be the map from `self` to R^n that sends the basis vectors of `self` in order to the standard basis of R^n . This function returns the image $\phi(V)$.

Warning: If there is no integer d such that dV is a submodule of `self`, then this function will give total nonsense.

EXAMPLES:

We illustrate this function with some \mathbf{Z} -submodules of \mathbf{Q}^3 :

```
sage: V = (ZZ^3).span([[1/2,3,5], [0,1,-3]])
sage: W = (ZZ^3).span([[1/2,4,2]])
sage: V.coordinate_module(W)
Free module of degree 2 and rank 1 over Integer Ring
User basis matrix:
[1 4]
sage: V.0 + 4*V.1
(1/2, 4, 2)
```

In this example, the coordinate module isn't even in \mathbf{Z}^3 :

```
sage: W = (ZZ^3).span([[1/4,2,1]])
sage: V.coordinate_module(W)
Free module of degree 2 and rank 1 over Integer Ring
User basis matrix:
[1/2 2]
```

The following more elaborate example illustrates using this function to write a submodule in terms of integral cuspidal modular symbols:

```
sage: M = ModularSymbols(54)
sage: S = M.cuspidal_subspace()
sage: K = S.integral_structure(); K
```

(continues on next page)

(continued from previous page)

```

Free module of degree 19 and rank 8 over Integer Ring
Echelon basis matrix:
[ 0  1  0  0 -1  0  0  0  0  0  0  0  0  0  0  0  0  0]
...
sage: L = M[0].integral_structure(); L
Free module of degree 19 and rank 2 over Integer Ring
Echelon basis matrix:
[ 0  1  1  0 -2  1 -1  1 -1 -2  2  0  0  0  0  0  0  0]
[ 0  0  3  0 -3  2 -1  2 -1 -4  2 -1 -2  1  2  0  0 -1  1]
sage: K.coordinate_module(L)
Free module of degree 8 and rank 2 over Integer Ring
User basis matrix:
[ 1  1  1 -1  1 -1  0  0]
[ 0  3  2 -1  2 -1 -1 -2]
sage: K.coordinate_module(L).basis_matrix() * K.basis_matrix()
[ 0  1  1  0 -2  1 -1  1 -1 -2  2  0  0  0  0  0  0  0]
[ 0  0  3  0 -3  2 -1  2 -1 -4  2 -1 -2  1  2  0  0 -1  1]

```

coordinate_ring()

Return the ring over which the entries of the vectors are defined.

This is the same as `base_ring()` unless an explicit basis was given over the fraction field.

EXAMPLES:

```

sage: M = ZZ^2
sage: M.coordinate_ring()
Integer Ring

```

```

sage: M = (ZZ^2) * (1/2)
sage: M.base_ring()
Integer Ring
sage: M.coordinate_ring()
Rational Field

```

```

sage: R.<x> = QQ[]
sage: L = R^2
sage: L.coordinate_ring()
Univariate Polynomial Ring in x over Rational Field
sage: L.span([(x,0), (1,x)]).coordinate_ring()
Univariate Polynomial Ring in x over Rational Field
sage: L.span([(x,0), (1,1/x)]).coordinate_ring()
Fraction Field of Univariate Polynomial Ring in x over Rational Field
sage: L.span([]).coordinate_ring()
Univariate Polynomial Ring in x over Rational Field

```

coordinate_vector(*v*, *check=True*)

Return the vector whose coefficients give *v* as a linear combination of the basis for self.

INPUT:

- *v* – vector
- *check* – boolean (default: **True**); if **True**, also verify that *v* is really in self.

OUTPUT: list

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2); M0,M1=M.gens()
sage: W = M.submodule([M0 + M1, M0 - 2*M1])
sage: W.coordinate_vector(2*M0 - M1)
(2, -1)
```

coordinates(*v*, *check=True*)

Write *v* in terms of the basis for self.

INPUT:

- *v* – vector
- **check** – boolean (default: **True**); if **True**, also verify that *v* is really in self.

OUTPUT: list

Returns a list *c* such that if *B* is the basis for self, then

$$\sum c_i B_i = v.$$

If *v* is not in self, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2); M0,M1=M.gens()
sage: W = M.submodule([M0 + M1, M0 - 2*M1])
sage: W.coordinates(2*M0-M1)
[2, -1]
```

dense_module()

Return corresponding dense module.

EXAMPLES:

We first illustrate conversion with ambient spaces:

```
sage: M = FreeModule(QQ, 3)
sage: S = FreeModule(QQ, 3, sparse=True)
sage: M.sparse_module()
Sparse vector space of dimension 3 over Rational Field
sage: S.dense_module()
Vector space of dimension 3 over Rational Field
sage: M.sparse_module() == S
True
sage: S.dense_module() == M
True
sage: M.dense_module() == M
True
sage: S.sparse_module() == S
True
```

Next we create a subspace:

```
sage: M = FreeModule(QQ, 3, sparse=True)
sage: V = M.span([ [1,2,3] ] ); V
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
sage: V.sparse_module()
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
```

dimension()

Return the dimension of this free module.

EXAMPLES:

```
sage: M = FreeModule(FiniteField(19), 100)
sage: W = M.submodule([M.gen(50)])
sage: W.dimension()
1
```

direct_sum(*other*)

Return the direct sum of *self* and *other* as a free module.

EXAMPLES:

```
sage: V = (ZZ^3).span([[1/2,3,5], [0,1,-3]]); V
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1/2  0  14]
[  0  1  -3]
sage: W = (ZZ^3).span([[1/2,4,2]]); W
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1/2  4  2]
sage: V.direct_sum(W)
Free module of degree 6 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  14  0  0  0]
[  0  1  -3  0  0  0]
[  0  0  0  1/2  4  2]
```

discriminant()

Return the discriminant of this free module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.discriminant()
1
sage: W = M.span([[1,2,3]])
sage: W.discriminant()
14
sage: W2 = M.span([[1,2,3], [1,1,1]])
sage: W2.discriminant()
6
```

echelonized_basis_matrix()

The echelonized basis matrix (not implemented for this module).

This example works because M is an ambient module. Submodule creation should exist for generic modules.

EXAMPLES:

```
sage: R = IntegerModRing(12)
sage: S.<x,y> = R[]
sage: M = FreeModule(S,3)
sage: M.echelonized_basis_matrix()
[1 0 0]
[0 1 0]
[0 0 1]
```

free_module()

Return this free module. (This is used by the `FreeModule` functor, and simply returns self.)

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.free_module()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

gen($i=0$)

Return the i -th generator for self.

Here i is between 0 and rank - 1, inclusive.

INPUT:

- i – an integer (default 0)

OUTPUT: i -th basis vector for self.

EXAMPLES:

```
sage: n = 5
sage: V = QQ^n
sage: B = [V.gen(i) for i in range(n)]
sage: B
[(1, 0, 0, 0, 0),
 (0, 1, 0, 0, 0),
 (0, 0, 1, 0, 0),
 (0, 0, 0, 1, 0),
 (0, 0, 0, 0, 1)]
sage: V.gens() == tuple(B)
True
```

gens()

Return a tuple of basis elements of self.

EXAMPLES:

```
sage: FreeModule(Integers(12),3).gens()
((1, 0, 0), (0, 1, 0), (0, 0, 1))
```

gram_matrix()

Return the gram matrix associated to this free module, defined to be $G = B * A * B.transpose()$, where A is the inner product matrix (induced from the ambient space), and B the basis matrix.

EXAMPLES:

```
sage: V = VectorSpace(QQ,4)
sage: u = V([1/2,1/2,1/2,1/2])
sage: v = V([0,1,1,0])
sage: w = V([0,0,1,1])
sage: M = span([u,v,w], ZZ)
sage: M.inner_product_matrix() == V.inner_product_matrix()
True
sage: L = M.submodule_with_basis([u,v,w])
sage: L.inner_product_matrix() == M.inner_product_matrix()
True
sage: L.gram_matrix()
[1 1 1]
[1 2 1]
[1 1 2]
```

has_user_basis()

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.subspace([[2, '1/2', 1]])
sage: W.has_user_basis()
False
sage: W = V.subspace_with_basis([[2, '1/2', 1]])
sage: W.has_user_basis()
True
```

hom(im_gens, codomain=None, **kws)

Override the hom method to handle the case of morphisms given by left-multiplication of a matrix and the codomain is not given.

EXAMPLES:

```
sage: W = ZZ^2; W.hom(matrix(1, [1, 2]), side="right")
Free module morphism defined as left-multiplication by the matrix
[1 2]
Domain: Ambient free module of rank 2 over the principal ideal domain Integer_
↳Ring
Codomain: Ambient free module of rank 1 over the principal ideal domain Integer_
↳Ring
sage: V = QQ^2; V.hom(identity_matrix(2), side="right")
Vector space morphism represented as left-multiplication by the matrix:
[1 0]
[0 1]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
```

inner_product_matrix()

Return the default identity inner product matrix associated to this module.

By definition this is the inner product matrix of the ambient space, hence may be of degree greater than the rank of the module.

TODO: Differentiate the image ring of the inner product from the base ring of the module and/or ambient space. E.g. On an integral module over $\mathbb{Z}\mathbb{Z}$ the inner product pairing could naturally take values in $\mathbb{Z}\mathbb{Z}$, $\mathbb{Q}\mathbb{Q}$, $\mathbb{R}\mathbb{R}$, or $\mathbb{C}\mathbb{C}$.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.inner_product_matrix()
[1 0 0]
[0 1 0]
[0 0 1]
```

is_ambient()

Returns False since this is not an ambient free module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3).span([[1,2,3]]); M
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1 2 3]
sage: M.is_ambient()
False
sage: M = (ZZ^2).span([[1,0], [0,1]])
sage: M
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1 0]
[0 1]
sage: M.is_ambient()
False
sage: M == M.ambient_module()
True
```

is_dense()

Return True if the underlying representation of this module uses dense vectors, and False otherwise.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_dense()
True
sage: FreeModule(ZZ, 2, sparse=True).is_dense()
False
```

is_finite()

Returns True if the underlying set of this free module is finite.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_finite()
False
```

(continues on next page)

(continued from previous page)

```
sage: FreeModule(Integers(8), 2).is_finite()
True
sage: FreeModule(ZZ, 0).is_finite()
True
```

is_full()

Return True if the rank of this module equals its degree.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_full()
True
sage: M = FreeModule(ZZ, 2).span([[1,2]])
sage: M.is_full()
False
```

is_submodule(*other*)

Return True if self is a submodule of other.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: V = M.ambient_vector_space()
sage: X = V.span([[1/2, 1/2, 0], [1/2, 0, 1/2]], ZZ)
sage: Y = V.span([[1, 1, 1]], ZZ)
sage: N = X + Y
sage: M.is_submodule(X)
False
sage: M.is_submodule(Y)
False
sage: Y.is_submodule(M)
True
sage: N.is_submodule(M)
False
sage: M.is_submodule(N)
True

sage: M = FreeModule(ZZ, 2)
sage: M.is_submodule(M)
True
sage: N = M.scale(2)
sage: N.is_submodule(M)
True
sage: M.is_submodule(N)
False
sage: N = M.scale(1/2)
sage: N.is_submodule(M)
False
sage: M.is_submodule(N)
True
```

Since `basis()` is not implemented in general, submodule testing does not work for all PID's. However, trivial cases are already used (and useful) for coercion, e.g.:

```
sage: QQ(1/2) * vector(ZZ['x']['y'], [1, 2, 3, 4])
(1/2, 1, 3/2, 2)
sage: vector(ZZ['x']['y'], [1, 2, 3, 4]) * QQ(1/2)
(1/2, 1, 3/2, 2)
```

matrix()

Return the basis matrix of this module, which is the matrix whose rows are a basis for this module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2)
sage: M.matrix()
[1 0]
[0 1]
sage: M.submodule([M.gen(0) + M.gen(1), M.gen(0) - 2*M.gen(1)]).matrix()
[1 1]
[0 3]
```

ngens()

Returns the number of basis elements of this free module.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).ngens()
2
sage: FreeModule(ZZ, 0).ngens()
0
sage: FreeModule(ZZ, 2).span([[1, 1]]).ngens()
1
```

nonembedded_free_module()

Returns an ambient free module that is isomorphic to this free module.

Thus if this free module is of rank n over a ring R , then this function returns R^n , as an ambient free module.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).span([[1, 1]]).nonembedded_free_module()
Ambient free module of rank 1 over the principal ideal domain Integer Ring
```

random_element(*prob=1.0, *args, **kws*)

Returns a random element of self.

INPUT:

- **prob** - float. Each coefficient will be set to zero with probability $1 - \text{prob}$. Otherwise coefficients will be chosen randomly from base ring (and may be zero).
- ***args, **kws** - passed on to `random_element()` function of base ring.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2).span([[1, 1]])
sage: v = M.random_element()
sage: v.parent() is M
True
sage: v in M
True
```

Small entries are likely:

```
sage: for i in [-2, -1, 0, 1, 2]:
.....:     while vector([i, i]) != M.random_element():
.....:         pass
```

Large entries appear as well:

```
sage: while abs(M.random_element()[0]) < 100:
.....:     pass
```

Passes extra positional or keyword arguments through:

```
sage: all(i in range(5, 10) for i in M.random_element(1.0, 5, 10))
True
```

rank()

Return the rank of this free module.

EXAMPLES:

```
sage: FreeModule(Integers(6), 100000000).rank()
100000000
sage: FreeModule(ZZ, 2).span([[1,1], [2,2], [3,4]]).rank()
2
```

relations()

Return the module of relations of self.

EXAMPLES:

```
sage: V = GF(2)^2
sage: V.relations() == V.zero_submodule()
True
sage: W = V.subspace([[1, 0]])
sage: W.relations() == V.zero_submodule()
True

sage: Q = V / W
sage: Q.relations() == W
True
```

scale(*other*)

Return the product of this module by the number *other*, which is the module spanned by *other* times each basis vector.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.scale(2)
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[2 0 0]
[0 2 0]
[0 0 2]
```



```

sage: a = QQ('1/3')
sage: M.scale(a)
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/3  0  0]
[  0 1/3  0]
[  0  0 1/3]

```

`sparse_module()`

Return the corresponding sparse module with the same defining data.

EXAMPLES:

We first illustrate conversion with ambient spaces:

```

sage: M = FreeModule(Integers(8),3)
sage: S = FreeModule(Integers(8),3, sparse=True)
sage: M.sparse_module()
Ambient sparse free module of rank 3 over Ring of integers modulo 8
sage: S.dense_module()
Ambient free module of rank 3 over Ring of integers modulo 8
sage: M.sparse_module() is S
True
sage: S.dense_module() is M
True
sage: M.dense_module() is M
True
sage: S.sparse_module() is S
True

```

Next we convert a subspace:

```

sage: M = FreeModule(QQ,3)
sage: V = M.span([ [1,2,3] ] ); V
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
sage: V.sparse_module()
Sparse vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]

```

`uses_ambient_inner_product()`

Return True if the inner product on this module is the one induced by the ambient inner product.

EXAMPLES:

```

sage: M = FreeModule(ZZ, 2)
sage: W = M.submodule([[1,2]])
sage: W.uses_ambient_inner_product()
True
sage: W.inner_product_matrix()
[1 0]
[0 1]

```

```
sage: W.gram_matrix()
[5]
```

```
class sage.modules.free_module.FreeModule_generic_domain(base_ring, rank, degree, sparse=False,
                                                           coordinate_ring=None)
```

Bases: `sage.modules.free_module.FreeModule_generic`

Base class for free modules over an integral domain.

```
class sage.modules.free_module.FreeModule_generic_field(base_field, dimension, degree,
                                                         sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_generic_pid`

Base class for all free modules over fields.

complement()

Return the complement of self in the `ambient_vector_space()`.

EXAMPLES:

```
sage: V = QQ^3
sage: V.complement()
Vector space of degree 3 and dimension 0 over Rational Field
Basis matrix:
[]
sage: V == V.complement().complement()
True
sage: W = V.span([[1, 0, 1]])
sage: X = W.complement(); X
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  0]
sage: X.complement() == W
True
sage: X + W == V
True
```

Even though we construct a subspace of a subspace, the orthogonal complement is still done in the ambient vector space \mathbb{Q}^3 :

```
sage: V = QQ^3
sage: W = V.subspace_with_basis([[1,0,1],[-1,1,0]])
sage: X = W.subspace_with_basis([[1,0,1]])
sage: X.complement()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  0]
```

All these complements are only done with respect to the inner product in the usual basis. Over finite fields, this means we can get complements which are only isomorphic to a vector space decomposition complement.

```
sage: F2 = GF(2, x)
sage: V = F2^6
```

(continues on next page)

(continued from previous page)

```

sage: W = V.span([[1,1,0,0,0,0]])
sage: W
Vector space of degree 6 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 1 0 0 0 0]
sage: W.complement()
Vector space of degree 6 and dimension 5 over Finite Field of size 2
Basis matrix:
[1 1 0 0 0 0]
[0 0 1 0 0 0]
[0 0 0 1 0 0]
[0 0 0 0 1 0]
[0 0 0 0 0 1]
sage: W.intersection(W.complement())
Vector space of degree 6 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 1 0 0 0 0]

```

echelonized_basis_matrix()

Return basis matrix for self in row echelon form.

EXAMPLES:

```

sage: V = FreeModule(QQ, 3).span_of_basis([[1,2,3],[4,5,6]])
sage: V.basis_matrix()
[1 2 3]
[4 5 6]
sage: V.echelonized_basis_matrix()
[ 1  0 -1]
[ 0  1  2]

```

intersection(*other*)

Return the intersection of self and other, which must be R-submodules of a common ambient vector space.

EXAMPLES:

```

sage: V = VectorSpace(QQ,3)
sage: W1 = V.submodule([V.gen(0), V.gen(0) + V.gen(1)])
sage: W2 = V.submodule([V.gen(1), V.gen(2)])
sage: W1.intersection(W2)
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[0 1 0]
sage: W2.intersection(W1)
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[0 1 0]
sage: V.intersection(W1)
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]
[0 1 0]
sage: W1.intersection(V)

```

(continues on next page)

(continued from previous page)

```

Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]
[0 1 0]
sage: Z = V.submodule([])
sage: W1.intersection(Z)
Vector space of degree 3 and dimension 0 over Rational Field
Basis matrix:
[]

```

is_subspace(*other*)

True if this vector space is a subspace of *other*.

EXAMPLES:

```

sage: V = VectorSpace(QQ,3)
sage: W = V.subspace([V.gen(0), V.gen(0) + V.gen(1)])
sage: W2 = V.subspace([V.gen(1)])
sage: W.is_subspace(V)
True
sage: W2.is_subspace(V)
True
sage: W.is_subspace(W2)
False
sage: W2.is_subspace(W)
True

```

linear_dependence(*vectors*, *zeros*='left', *check*=True)

Returns a list of vectors giving relations of linear dependence for the input list of vectors. Can be used to check linear independence of a set of vectors.

INPUT:

- **vectors** – A list of vectors, all from the same vector space.
- **zeros** – default: 'left' - 'left' or 'right' as a general preference for where zeros are located in the returned coefficients
- **check** – default: True - if True each item in the list **vectors** is checked for membership in **self**. Set to False if you can be certain the vectors come from the vector space.

OUTPUT:

Returns a list of vectors. The scalar entries of each vector provide the coefficients for a linear combination of the input vectors that will equal the zero vector in **self**. Furthermore, the returned list is linearly independent in the vector space over the same base field with degree equal to the length of the list **vectors**.

The linear independence of **vectors** is equivalent to the returned list being empty, so this provides a test - see the examples below.

The returned vectors are always independent, and with **zeros** set to 'left' they have 1's in their first non-zero entries and a qualitative disposition to having zeros in the low-index entries. With **zeros** set to 'right' the situation is reversed with a qualitative disposition for zeros in the high-index entries.

If the vectors in **vectors** are made the rows of a matrix V and the returned vectors are made the rows of a matrix R , then the matrix product RV is a zero matrix of the proper size. And R is a matrix of full rank. This routine uses kernels of matrices to compute these relations of linear dependence, but handles

all the conversions between sets of vectors and matrices. If speed is important, consider working with the appropriate matrices and kernels instead.

EXAMPLES:

We begin with two linearly independent vectors, and add three non-trivial linear combinations to the set. We illustrate both types of output and check a selected relation of linear dependence.

```
sage: v1 = vector(QQ, [2, 1, -4, 3])
sage: v2 = vector(QQ, [1, 5, 2, -2])
sage: V = QQ^4
sage: V.linear_dependence([v1,v2])
[
]

sage: v3 = v1 + v2
sage: v4 = 3*v1 - 4*v2
sage: v5 = -v1 + 2*v2
sage: L = [v1, v2, v3, v4, v5]

sage: relations = V.linear_dependence(L, zeros='left')
sage: relations
[
(1, 0, 0, -1, -2),
(0, 1, 0, -1/2, -3/2),
(0, 0, 1, -3/2, -7/2)
]
sage: v2 + (-1/2)*v4 + (-3/2)*v5
(0, 0, 0, 0)

sage: relations = V.linear_dependence(L, zeros='right')
sage: relations
[
(-1, -1, 1, 0, 0),
(-3, 4, 0, 1, 0),
(1, -2, 0, 0, 1)
]
sage: z = sum([relations[2][i]*L[i] for i in range(len(L))])
sage: z == zero_vector(QQ, 4)
True
```

A linearly independent set returns an empty list, a result that can be tested.

```
sage: v1 = vector(QQ, [0,1,-3])
sage: v2 = vector(QQ, [4,1,0])
sage: V = QQ^3
sage: relations = V.linear_dependence([v1, v2]); relations
[
]
sage: relations == []
True
```

Exact results result from exact fields. We start with three linearly independent vectors and add in two linear

combinations to make a linearly dependent set of five vectors.

```
sage: F = FiniteField(17)
sage: v1 = vector(F, [1, 2, 3, 4, 5])
sage: v2 = vector(F, [2, 4, 8, 16, 15])
sage: v3 = vector(F, [1, 0, 0, 0, 1])
sage: (F^5).linear_dependence([v1, v2, v3]) == []
True
sage: L = [v1, v2, v3, 2*v1+v2, 3*v2+6*v3]
sage: (F^5).linear_dependence(L)
[
(1, 0, 16, 8, 3),
(0, 1, 2, 0, 11)
]
sage: v1 + 16*v3 + 8*(2*v1+v2) + 3*(3*v2+6*v3)
(0, 0, 0, 0, 0)
sage: v2 + 2*v3 + 11*(3*v2+6*v3)
(0, 0, 0, 0, 0)
sage: (F^5).linear_dependence(L, zeros='right')
[
(15, 16, 0, 1, 0),
(0, 14, 11, 0, 1)
]
```

quotient(*sub*, *check=True*)

Return the quotient of *self* by the given subspace *sub*.

INPUT:

- *sub* – a submodule of *self*, or something that can be turned into one via *self.submodule(sub)*
- *check* – (default: True) whether or not to check that *sub* is a submodule

EXAMPLES:

```
sage: A = QQ^3; V = A.span([[1,2,3], [4,5,6]])
sage: Q = V.quotient( [V.0 + V.1] ); Q
Vector space quotient V/W of dimension 1 over Rational Field where
V: Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
W: Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 1 1]
sage: Q(V.0 + V.1)
(0)
```

We illustrate that the base rings must be the same:

```
sage: (QQ^2)/(ZZ^2)
Traceback (most recent call last):
...
ValueError: base rings must be the same
```

quotient_abstract(*sub*, *check=True*, ***kws*)

Return an ambient free module isomorphic to the quotient space of *self* modulo *sub*, together with maps

from `self` to the quotient, and a lifting map in the other direction.

Use `self.quotient(sub)` to obtain the quotient module as an object equipped with natural maps in both directions, and a canonical coercion.

INPUT:

- `sub` – a submodule of `self` or something that can be turned into one via `self.submodule(sub)`
- `check` – (default: `True`) whether or not to check that `sub` is a submodule
- further named arguments, that are currently ignored.

OUTPUT:

- `U` – the quotient as an abstract *ambient* free module
- `pi` – projection map to the quotient
- `lift` – lifting map back from quotient

EXAMPLES:

```
sage: V = GF(19)^3
sage: W = V.span_of_basis([ [1,2,3], [1,0,1] ])
sage: U,pi,lift = V.quotient_abstract(W)
sage: pi(V.2)
(18)
sage: pi(V.0)
(1)
sage: pi(V.0 + V.2)
(0)
```

Another example involving a quotient of one subspace by another:

```
sage: A = matrix(QQ,4,4,[0,1,0,0, 0,0,1,0, 0,0,0,1, 0,0,0,0])
sage: V = (A^3).kernel()
sage: W = A.kernel()
sage: U, pi, lift = V.quotient_abstract(W)
sage: [pi(v) == 0 for v in W.gens()]
[True]
sage: [pi(lift(b)) == b for b in U.basis()]
[True, True]
```

scale(*other*)

Return the product of `self` by the number `other`, which is the module spanned by `other` times each basis vector. Since `self` is a vector space this product equals `self` if `other` is nonzero, and is the zero vector space if `other` is 0.

EXAMPLES:

```
sage: V = QQ^4
sage: V.scale(5)
Vector space of dimension 4 over Rational Field
sage: V.scale(0)
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]
```

```

sage: W = V.span([[1,1,1,1]])
sage: W.scale(2)
Vector space of degree 4 and dimension 1 over Rational Field
Basis matrix:
[1 1 1 1]
sage: W.scale(0)
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

```

```

sage: V = QQ^4; V
Vector space of dimension 4 over Rational Field
sage: V.scale(3)
Vector space of dimension 4 over Rational Field
sage: V.scale(0)
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

```

span_of_basis(*basis*, *base_ring=None*, *check=True*, *already_echelonized=False*)

Return the free K-module with the given basis, where K is the base field of *self* or user specified *base_ring*.

Note that this span is a subspace of the ambient vector space, but need not be a subspace of *self*.

INPUT:

- *basis* - list of vectors
- *check* - boolean (default: *True*): whether or not to coerce entries of gens into base field
- *already_echelonized* - boolean (default: *False*): set this if you know the gens are already in echelon form

EXAMPLES:

```

sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span_of_basis([[2,2,2], [3,3,0]])
Vector space of degree 3 and dimension 2 over Finite Field of size 7
User basis matrix:
[2 2 2]
[3 3 0]

```

The basis vectors must be linearly independent or a *ValueError* exception is raised:

```

sage: W.span_of_basis([[2,2,2], [3,3,3]])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.

```

subspace(*gens*, *check=True*, *already_echelonized=False*)

Return the subspace of *self* spanned by the elements of *gens*.

INPUT:

- `gens` - list of vectors
- `check` - boolean (default: `True`) verify that gens are all in `self`.
- `already_echelonized` - boolean (default: `False`) set to `True` if you know the gens are in Echelon form.

EXAMPLES:

First we create a 1-dimensional vector subspace of an ambient 3-dimensional space over the finite field of order 7:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
```

Next we create an invalid subspace, but it's allowed since `check=False`. This is just equivalent to computing the span of the element:

```
sage: W.subspace([[1,1,0]], check=False)
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 1 0]
```

With `check=True` (the default) the mistake is correctly detected and reported with an `ArithmeticError` exception:

```
sage: W.subspace([[1,1,0]], check=True)
Traceback (most recent call last):
...
ArithmeticError: argument gens (= [[1, 1, 0]]) does not generate a submodule of self
↪self
```

`subspace_with_basis`(*gens*, *check=True*, *already_echelonized=False*)

Same as `self.submodule_with_basis(...)`.

EXAMPLES:

We create a subspace with a user-defined basis.

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace_with_basis([[2,2,2], [1,2,3]]); W
Vector space of degree 3 and dimension 2 over Finite Field of size 7
User basis matrix:
[2 2 2]
[1 2 3]
```

We then create a subspace of the subspace with user-defined basis.

```
sage: W1 = W.subspace_with_basis([[3,4,5]]); W1
Vector space of degree 3 and dimension 1 over Finite Field of size 7
User basis matrix:
[3 4 5]
```

Notice how the basis for the same subspace is different if we merely use the `subspace` command.

```
sage: W2 = W.subspace([[3,4,5]]); W2
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 6 4]
```

Nonetheless the two subspaces are equal (as mathematical objects):

```
sage: W1 == W2
True
```

subspaces(*dim*)

Iterate over all subspaces of dimension *dim*.

INPUT:

- *dim* - int, dimension of subspaces to be generated

EXAMPLES:

```
sage: V = VectorSpace(GF(3), 5)
sage: len(list(V.subspaces(0)))
1
sage: len(list(V.subspaces(1)))
121
sage: len(list(V.subspaces(2)))
1210
sage: len(list(V.subspaces(3)))
1210
sage: len(list(V.subspaces(4)))
121
sage: len(list(V.subspaces(5)))
1
```

```
sage: V = VectorSpace(GF(3), 5)
sage: V = V.subspace([V([1,1,0,0,0]),V([0,0,1,1,0])])
sage: list(V.subspaces(1))
[Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[1 1 0 0 0],
Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[1 1 1 1 0],
Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[1 1 2 2 0],
Vector space of degree 5 and dimension 1 over Finite Field of size 3
Basis matrix:
[0 0 1 1 0]]
```

vector_space(*base_field=None*)

Return the vector space associated to self. Since *self* is a vector space this function simply returns self, unless the base field is different.

EXAMPLES:

```

sage: V = span([[1,2,3]],QQ); V
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
sage: V.vector_space()
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]

```

zero_submodule()

Return the zero submodule of self.

EXAMPLES:

```

sage: (QQ^4).zero_submodule()
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

```

zero_subspace()

Return the zero subspace of self.

EXAMPLES:

```

sage: (QQ^4).zero_subspace()
Vector space of degree 4 and dimension 0 over Rational Field
Basis matrix:
[]

```

```

class sage.modules.free_module.FreeModule_generic_pid(base_ring, rank, degree, sparse=False,
                                                         coordinate_ring=None)

```

Bases: *sage.modules.free_module.FreeModule_generic_domain*

Base class for all free modules over a PID.

denominator()

The denominator of the basis matrix of `self` (i.e. the LCM of the coordinate entries with respect to the basis of the ambient space).

EXAMPLES:

```

sage: V = QQ^3
sage: L = V.span([[1,1/2,1/3], [-1/5,2/3,3]],ZZ)
sage: L
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1/5 19/6 37/3]
[   0 23/6 46/3]
sage: L.denominator()
30

```

index_in(*other*)

Return the lattice index [`other`:`self`] of `self` in `other`, as an element of the base field. When `self` is contained in `other`, the lattice index is the usual index. If the index is infinite, then this function returns infinity.

EXAMPLES:

```
sage: L1 = span([[1,2]], ZZ)
sage: L2 = span([[3,6]], ZZ)
sage: L2.index_in(L1)
3
```

Note that the free modules being compared need not be integral.

```
sage: L1 = span([[1/2', '1/3']], [4,5], ZZ)
sage: L2 = span([[1,2], [3,4]], ZZ)
sage: L2.index_in(L1)
12/7
sage: L1.index_in(L2)
7/12
sage: L1.discriminant() / L2.discriminant()
49/144
```

The index of a lattice of infinite index is infinite.

```
sage: L1 = FreeModule(ZZ, 2)
sage: L2 = span([[1,2]], ZZ)
sage: L2.index_in(L1)
+Infinity
```

index_in_saturation()

Return the index of this module in its saturation, i.e., its intersection with R^n .

EXAMPLES:

```
sage: W = span([[2,4,6]], ZZ)
sage: W.index_in_saturation()
2
sage: W = span([[1/2, 1/3]], ZZ)
sage: W.index_in_saturation()
1/6
```

intersection(*other*)

Return the intersection of **self** and **other**.

EXAMPLES:

We intersect two submodules one of which is clearly contained in the other:

```
sage: A = ZZ^2
sage: M1 = A.span([[1,1]])
sage: M2 = A.span([[3,3]])
sage: M1.intersection(M2)
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[3 3]
sage: M1.intersection(M2) is M2
True
```

We intersect two submodules of \mathbb{Z}^3 of rank 2, whose intersection has rank 1:

```

sage: A = ZZ^3
sage: M1 = A.span([[1,1,1], [1,2,3]])
sage: M2 = A.span([[2,2,2], [1,0,0]])
sage: M1.intersection(M2)
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[2 2 2]

```

We compute an intersection of two \mathbf{Z} -modules that are not submodules of \mathbf{Z}^2 :

```

sage: A = ZZ^2
sage: M1 = A.span([[1,2]]).scale(1/6)
sage: M2 = A.span([[1,2]]).scale(1/15)
sage: M1.intersection(M2)
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[1/3 2/3]

```

We intersect a \mathbf{Z} -module with a \mathbf{Q} -vector space:

```

sage: A = ZZ^3
sage: L = ZZ^3
sage: V = QQ^3
sage: W = L.span([[1/2,0,1/2]])
sage: K = V.span([[1,0,1], [0,0,1]])
sage: W.intersection(K)
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1/2  0 1/2]
sage: K.intersection(W)
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1/2  0 1/2]

```

We intersect two modules over the ring of integers of a number field:

```

sage: L.<w> = NumberField(x^2 - x + 2)
sage: OL = L.ring_of_integers()
sage: V = L**3
sage: W1 = V.span([[0,w/5,0], [1,0,-1/17]], OL)
sage: W2 = V.span([[0,(1-w)/5,0]], OL)
sage: W1.intersection(W2)
Free module of degree 3 and rank 1 over Maximal Order in
Number Field in w with defining polynomial x^2 - x + 2
Echelon basis matrix:
[ 0 2/5  0]

```

quotient(*sub*, *check=True*, ***kws*)

Return the quotient of *self* by the given submodule *sub*.

INPUT:

- *sub* – a submodule of *self*, or something that can be turned into one via *self.submodule(sub)*
- *check* – (default: *True*) whether or not to check that *sub* is a submodule

- further named arguments, that are passed to the constructor of the quotient space

EXAMPLES:

```
sage: A = ZZ^3; V = A.span([[1,2,3], [4,5,6]])
sage: Q = V.quotient( [V.0 + V.1] ); Q
Finitely generated module V/W over Integer Ring with invariants (0)
```

saturation()

Return the saturated submodule of R^n that spans the same vector space as self.

EXAMPLES:

We create a 1-dimensional lattice that is obviously not saturated and saturate it.

```
sage: L = span([[9,9,6]], ZZ); L
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[9 9 6]
sage: L.saturation()
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[3 3 2]
```

We create a lattice spanned by two vectors, and saturate. Computation of discriminants shows that the index of lattice in its saturation is 3, which is a prime of congruence between the two generating vectors.

```
sage: L = span([[1,2,3], [4,5,6]], ZZ)
sage: L.saturation()
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: L.discriminant()
54
sage: L.saturation().discriminant()
6
```

Notice that the saturation of a non-integral lattice L is defined, but the result is integral hence does not contain L :

```
sage: L = span(['1/2', 1, 3], ZZ)
sage: L.saturation()
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[1 2 6]
```

span_of_basis(basis, base_ring=None, check=True, already_echelonized=False)

Return the free R-module with the given basis, where R is the base ring of self or user specified base_ring.

Note that this R-module need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: W = M.span_of_basis([M([1,2,3])])
```

Next we create two free \mathbf{Z} -modules, neither of which is a submodule of W .

```
sage: W.span_of_basis([M([2,4,0])])
Free module of degree 3 and rank 1 over Integer Ring
User basis matrix:
[2 4 0]
```

The following module isn't in the ambient module \mathbf{Z}^3 but is contained in the ambient vector space \mathbf{Q}^3 :

```
sage: V = M.ambient_vector_space()
sage: W.span_of_basis([ V([1/5,2/5,0]), V([1/7,1/7,0]) ])
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1/5 2/5 0]
[1/7 1/7 0]
```

Of course the input basis vectors must be linearly independent:

```
sage: W.span_of_basis([ [1,2,0], [2,4,0] ])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

submodule_with_basis(*basis*, *check=True*, *already_echelonized=False*)

Create the R -submodule of the ambient vector space with given basis, where R is the base ring of self.

INPUT:

- **basis** – a list of linearly independent vectors
- **check** – whether or not to verify that each gen is in the ambient vector space

OUTPUT:

- **FreeModule** – the R -submodule with given basis

EXAMPLES:

First we create a submodule of \mathbf{ZZ}^3 :

```
sage: M = FreeModule(ZZ, 3)
sage: B = M.basis()
sage: N = M.submodule_with_basis([B[0]+B[1], 2*B[1]-B[2]])
sage: N
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  1  0]
[ 0  2 -1]
```

A list of vectors in the ambient vector space may fail to generate a submodule.

```
sage: V = M.ambient_vector_space()
sage: X = M.submodule_with_basis([ V(B[0]+B[1])/2, V(B[1]-B[2])/2 ])
Traceback (most recent call last):
...
ArithmeticError: The given basis does not generate a submodule of self.
```

However, we can still determine the R-span of vectors in the ambient space, or over-ride the submodule check by setting check to False.

```
sage: X = V.span([ V(B[0]+B[1])/2, V(B[1]-B[2])/2 ], ZZ)
sage: X
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1/2  0  1/2]
[  0  1/2 -1/2]
sage: Y = M.submodule([ V(B[0]+B[1])/2, V(B[1]-B[2])/2 ], check=False)
sage: X == Y
True
```

Next we try to create a submodule of a free module over the principal ideal domain $\mathbb{Q}[x]$, using our general Hermite normal form implementation:

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: M = FreeModule(R, 3)
sage: B = M.basis()
sage: W = M.submodule_with_basis([x*B[0], 2*B[0]-x*B[2]]); W
Free module of degree 3 and rank 2 over Univariate Polynomial Ring in x over
↳Rational Field
User basis matrix:
[ x  0  0]
[ 2  0 -x]
```

`vector_space_span(gens, check=True)`

Create the vector subspace of the ambient vector space with given generators.

INPUT:

- gens - a list of vector in self
- check - whether or not to verify that each gen is in the ambient vector space

OUTPUT: a vector subspace

EXAMPLES:

We create a 2-dimensional subspace of \mathbb{Q}^3 .

```
sage: V = VectorSpace(QQ, 3)
sage: B = V.basis()
sage: W = V.vector_space_span([B[0]+B[1], 2*B[1]-B[2]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0  1/2]
[ 0  1 -1/2]
```

We create a subspace of a vector space over $\mathbb{Q}(i)$.

```
sage: R.<x> = QQ[]
sage: K = NumberField(x^2 + 1, 'a'); a = K.gen()
sage: V = VectorSpace(K, 3)
sage: V.vector_space_span([2*V.gen(0) + 3*V.gen(2)])
Vector space of degree 3 and dimension 1 over Number Field in a with defining
↳polynomial x^2 + 1
```

(continues on next page)

(continued from previous page)

```
Basis matrix:
[ 1  0 3/2]
```

We use the `vector_space_span` command to create a vector subspace of the ambient vector space of a submodule of \mathbb{Z}^3 .

```
sage: M = FreeModule(ZZ, 3)
sage: W = M.submodule([M([1, 2, 3])])
sage: W.vector_space_span([M([2, 3, 4])])
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 3/2  2]
```

`vector_space_span_of_basis(basis, check=True)`

Create the vector subspace of the ambient vector space with given basis.

INPUT:

- **basis** – a list of linearly independent vectors
- **check** – whether or not to verify that each gen is in the ambient vector space

OUTPUT: a vector subspace with user-specified basis

EXAMPLES:

```
sage: V = VectorSpace(QQ, 3)
sage: B = V.basis()
sage: W = V.vector_space_span_of_basis([B[0]+B[1], 2*B[1]-B[2]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  2 -1]
```

`zero_submodule()`

Return the zero submodule of this module.

EXAMPLES:

```
sage: V = FreeModule(ZZ, 2)
sage: V.zero_submodule()
Free module of degree 2 and rank 0 over Integer Ring
Echelon basis matrix:
[]
```

```
class sage.modules.free_module.FreeModule_submodule_field(ambient, gens, check=True,
                                                           already_echelonized=False)
```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_field`

An embedded vector subspace with echelonized basis.

EXAMPLES:

Since this is an embedded vector subspace with echelonized basis, the `echelon_coordinates()` and `user_coordinates()` agree:

```

sage: V = QQ^3
sage: W = V.span([[1,2,3],[4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]

```

```

sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.basis_matrix()
(1, 5, 9)
sage: v = V([1,5,9])
sage: W.coordinates(v)
[1, 5]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)

```

coordinate_vector(*v*, *check=True*)

Write *v* in terms of the user basis for *self*.

INPUT:

- *v* – vector
- **check** – boolean (default: **True**); if **True**, also verify that *v* is really in *self*

OUTPUT: list

The output is a list *c* such that if *B* is the basis for *self*, then

$$\sum c_i B_i = v.$$

If *v* is not in *self*, raise an `ArithmeticError` exception.

EXAMPLES:

```

sage: V = QQ^3
sage: W = V.span([[1,2,3],[4,5,6]]); W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: v = V([1,5,9])
sage: W.coordinate_vector(v)
(1, 5)
sage: W.coordinates(v)
[1, 5]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)

```

```

sage: V = VectorSpace(QQ,5, sparse=True)
sage: W = V.subspace([[0,1,2,0,0], [0,-1,0,0,-1/2]])
sage: W.coordinate_vector([0,0,2,0,-1/2])
(0, 2)

```

echelon_coordinates(v , *check=True*)

Write v in terms of the echelonized basis of `self`.

INPUT:

- v – vector
- *check* – boolean (default: `True`); if `True`, also verify that v is really in `self`

OUTPUT: list

The output is a list c such that if B is the basis for `self`, then

$$\sum c_i B_i = v.$$

If v is not in `self`, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.span([[1,2,3],[4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
```

```
sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

has_user_basis()

Return `True` if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.subspace([[2,'1/2', 1]])
sage: W.has_user_basis()
False
sage: W = V.subspace_with_basis([[2,'1/2',1]])
sage: W.has_user_basis()
True
```

class `sage.modules.free_module.FreeModule_submodule_pid`(*ambient*, *gens*, *check=True*,
already_echelonized=False)

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_pid`

An R -submodule of K^n where K is the fraction field of a principal ideal domain R .

EXAMPLES:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,19]]); W
Free module of degree 3 and rank 2 over Integer Ring
```

(continues on next page)

(continued from previous page)

```
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

Generic tests, including saving and loading submodules and elements:

```
sage: TestSuite(W).run()
sage: v = W.0 + W.1
sage: TestSuite(v).run()
```

coordinate_vector(*v*, *check=True*)

Write *v* in terms of the user basis for *self*.

INPUT:

- *v* – vector
- **check** – boolean (default: True); if True, also verify that *v* is really in *self*.

OUTPUT: list

The output is a list *c* such that if *B* is the basis for *self*, then

$$\sum c_i B_i = v.$$

If *v* is not in *self*, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: V = ZZ^3
sage: W = V.span_of_basis([[1,2,3],[4,5,6]])
sage: W.coordinate_vector([1,5,9])
(5, -1)
```

has_user_basis()

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```
sage: A = ZZ^3; A
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: A.has_user_basis()
False
sage: W = A.span_of_basis([[2,'1/2',1]])
sage: W.has_user_basis()
True
sage: W = A.span([[2,'1/2',1]])
sage: W.has_user_basis()
False
```

```
class sage.modules.free_module.FreeModule_submodule_with_basis_field(ambient, basis,
                                                                    check=True,
                                                                    echelonize=False,
                                                                    echelonized_basis=None,
                                                                    al-
                                                                    ready_echelonized=False)
Bases: sage.modules.free_module.FreeModule_generic_field, sage.modules.free_module.
```

FreeModule_submodule_with_basis_pid

An embedded vector subspace with a distinguished user basis.

EXAMPLES:

```
sage: M = QQ^3; W = M.submodule_with_basis([[1,2,3], [4,5,19]]); W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

Since this is an embedded vector subspace with a distinguished user basis possibly different than the echelonized basis, the `echelon_coordinates()` and `user coordinates()` do not agree:

```
sage: V = QQ^3
```

```
sage: W = V.submodule_with_basis([[1,2,3], [4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 2 3]
[4 5 6]
```

```
sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.echelonized_basis_matrix()
(1, 5, 9)
```

```
sage: v = V([1,5,9])
sage: W.coordinates(v)
[5, -1]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

Generic tests, including saving and loading submodules and elements:

```
sage: TestSuite(W).run()

sage: K.<x> = FractionField(PolynomialRing(QQ, 'x'))
sage: M = K^3; W = M.span_of_basis([[1,1,x]])
sage: TestSuite(W).run()
```

is_ambient()

Return False since this is not an ambient module.

EXAMPLES:

```
sage: V = QQ^3
sage: V.is_ambient()
True
sage: W = V.span_of_basis([[1,2,3], [4,5,6]])
sage: W.is_ambient()
False
```

```
class sage.modules.free_module.FreeModule_submodule_with_basis_pid(ambient, basis, check=True,
                                                                    echelonize=False,
                                                                    echelonized_basis=None,
                                                                    already_echelonized=False)
```

Bases: `sage.modules.free_module.FreeModule_generic_pid`

Construct a submodule of a free module over PID with a distinguished basis.

INPUT:

- **ambient** – ambient free module over a principal ideal domain R , i.e. R^n ;
- **basis** – list of elements of K^n , where K is the fraction field of R . These elements must be linearly independent and will be used as the default basis of the constructed submodule;
- **check** – (default: True) if False, correctness of the input will not be checked and type conversion may be omitted, use with care;
- **echelonize** – (default: False) if True, basis will be echelonized and the result will be used as the default basis of the constructed submodule;
- **echelonized_basis** – (default: None) if not None, must be the echelonized basis spanning the same submodule as **basis**;
- **already_echelonized** – (default: False) if True, basis must be already given in the echelonized form.

OUTPUT:

- R -submodule of K^n with the user-specified basis.

EXAMPLES:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,6]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1 2 3]
[4 5 6]
```

Now we create a submodule of the ambient vector space, rather than **M** itself:

```
sage: W = M.span_of_basis([[1,2,3/2],[4,5,6]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2 3/2]
[ 4  5  6]
```

ambient_module()

Return the ambient module related to the R -module **self**, which was used when creating this module, and is of the form R^n . Note that **self** need not be contained in the ambient module, though **self** will be contained in the ambient vector space.

EXAMPLES:

```
sage: A = ZZ^3
sage: M = A.span_of_basis([[1,2,'3/7'],[4,5,6]])
sage: M
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2 3/7]
```

(continues on next page)

(continued from previous page)

```
[ 4 5 6]
sage: M.ambient_module()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: M.is_submodule(M.ambient_module())
False
```

ambient_vector_space()

Return the ambient vector space in which this free module is embedded.

EXAMPLES:

```
sage: M = ZZ^3; M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
```

```
sage: N = M.span_of_basis([[1,2,'1/5']])
sage: N
Free module of degree 3 and rank 1 over Integer Ring
User basis matrix:
[ 1 2 1/5]
sage: M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
sage: M.ambient_vector_space() is N.ambient_vector_space()
True
```

If an inner product on the module is specified, then this is preserved on the ambient vector space.

```
sage: M = FreeModule(ZZ,4,inner_product_matrix=1)
sage: V = M.ambient_vector_space()
sage: V
Ambient quadratic space of dimension 4 over Rational Field
Inner product matrix:
[1 0 0 0]
[0 1 0 0]
[0 0 1 0]
[0 0 0 1]
sage: N = M.submodule([[1,-1,0,0],[0,1,-1,0],[0,0,1,-1]])
sage: N.gram_matrix()
[2 1 1]
[1 2 1]
[1 1 2]
sage: V == N.ambient_vector_space()
True
```

basis()

Return the user basis for this free module.

EXAMPLES:

```
sage: V = ZZ^3
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
```

(continues on next page)

(continued from previous page)

```
(0, 0, 1)
]
sage: M = V.span_of_basis([[1/8, 2, 1]])
sage: M.basis()
[
(1/8, 2, 1)
]
```

change_ring(*R*)

Return the free module over R obtained by coercing each element of the basis of `self` into a vector over the fraction field of R , then taking the resulting R -module.

INPUT:

- R - a principal ideal domain

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.subspace([[2, 1/2, 1]])
sage: W.change_ring(GF(7))
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 2 4]
```

```
sage: M = (ZZ^2) * (1/2)
sage: N = M.change_ring(QQ)
sage: N
Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]
sage: N = M.change_ring(QQ['x'])
sage: N
Free module of degree 2 and rank 2 over Univariate Polynomial Ring in x over
↳ Rational Field
Echelon basis matrix:
[1/2 0]
[0 1/2]
sage: N.coordinate_ring()
Univariate Polynomial Ring in x over Rational Field
```

The ring must be a principal ideal domain:

```
sage: M.change_ring(ZZ['x'])
Traceback (most recent call last):
...
TypeError: the new ring Univariate Polynomial Ring in x over Integer Ring
↳ should be a principal ideal domain
```

construction()

Returns the functorial construction of `self`, namely, the subspace of the ambient module spanned by the given basis.

EXAMPLES:


```

sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,6]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1 2 3]
[4 5 6]
sage: c, V = W.construction()
sage: c(V) == W
True

```

coordinate_vector(v , *check=True*)

Write v in terms of the user basis for `self`.

INPUT:

- v – vector
- **check** – boolean (default: **True**); if **True**, also verify that v is really in `self`.

OUTPUT: list

The output is a vector c such that if B is the basis for `self`, then

$$\sum c_i B_i = v.$$

If v is not in `self`, raise an `ArithmeticError` exception.

EXAMPLES:

```

sage: V = ZZ^3
sage: M = V.span_of_basis([[1/8,2,1]])
sage: M.coordinate_vector([1,16,8])
(8)

```

echelon_coordinate_vector(v , *check=True*)

Write v in terms of the echelonized basis for `self`.

INPUT:

- v - vector
- **check** - boolean (default: **True**); if **True**, also verify that v is really in `self`.

Returns a list c such that if B is the echelonized basis for `self`, then

$$\sum c_i B_i = v.$$

If v is not in `self`, raise an `ArithmeticError` exception.

EXAMPLES:

```

sage: V = ZZ^3
sage: M = V.span_of_basis([[1/2,3,1], [0,1/6,0]])
sage: B = M.echelonized_basis(); B
[
(1/2, 0, 1),
(0, 1/6, 0)
]
sage: M.echelon_coordinate_vector([1/2, 3, 1])
(1, 18)

```

echelon_coordinates(v , *check=True*)

Write v in terms of the echelonized basis for `self`.

INPUT:

- v - vector
- *check* - boolean (default: `True`); if `True`, also verify that v is really in `self`.

OUTPUT: list

Returns a list c such that if B is the basis for `self`, then

$$\sum c_i B_i = v.$$

If v is not in `self`, raise an `ArithmeticError` exception.

EXAMPLES:

```
sage: A = ZZ^3
sage: M = A.span_of_basis([[1,2,'3/7'],[4,5,6]])
sage: M.coordinates([8,10,12])
[0, 2]
sage: M.echelon_coordinates([8,10,12])
[8, -2]
sage: B = M.echelonized_basis(); B
[
(1, 2, 3/7),
(0, 3, -30/7)
]
sage: 8*B[0] - 2*B[1]
(8, 10, 12)
```

We do an example with a sparse vector space:

```
sage: V = VectorSpace(QQ,5, sparse=True)
sage: W = V.subspace_with_basis([[0,1,2,0,0], [0,-1,0,0,-1/2]])
sage: W.echelonized_basis()
[
(0, 1, 0, 0, 1/2),
(0, 0, 1, 0, -1/4)
]
sage: W.echelon_coordinates([0,0,2,0,-1/2])
[0, 2]
```

echelon_to_user_matrix()

Return matrix that transforms the echelon basis to the user basis of `self`. This is a matrix A such that if v is a vector written with respect to the echelon basis for `self` then vA is that vector written with respect to the user basis of `self`.

EXAMPLES:

```
sage: V = QQ^3
sage: W = V.span_of_basis([[1,2,3],[4,5,6]])
sage: W.echelonized_basis()
[
(1, 0, -1),
(0, 1, 2)
```

(continues on next page)

(continued from previous page)

```

]
sage: A = W.echelon_to_user_matrix(); A
[-5/3  2/3]
[ 4/3 -1/3]

```

The vector $(1, 1, 1)$ has coordinates $v = (1, 1)$ with respect to the echelonized basis for self. Multiplying vA we find the coordinates of this vector with respect to the user basis.

```

sage: v = vector(QQ, [1,1]); v
(1, 1)
sage: v * A
(-1/3, 1/3)
sage: u0, u1 = W.basis()
sage: (-u0 + u1)/3
(1, 1, 1)

```

echelonized_basis()

Return the basis for self in echelon form.

EXAMPLES:

```

sage: V = ZZ^3
sage: M = V.span_of_basis([[1/2, 3, 1], [0, 1/6, 0]])
sage: M.basis()
[
(1/2, 3, 1),
(0, 1/6, 0)
]
sage: B = M.echelonized_basis(); B
[
(1/2, 0, 1),
(0, 1/6, 0)
]
sage: V.span(B) == M
True

```

echelonized_basis_matrix()

Return basis matrix for self in row echelon form.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 3).span_of_basis([[1,2,3],[4,5,6]])
sage: V.basis_matrix()
[1 2 3]
[4 5 6]
sage: V.echelonized_basis_matrix()
[1 2 3]
[0 3 6]

```

has_user_basis()

Return True if the basis of this free module is specified by the user, as opposed to being the default echelon form.

EXAMPLES:

```

sage: V = ZZ^3; V.has_user_basis()
False
sage: M = V.span_of_basis([[1,3,1]]); M.has_user_basis()
True
sage: M = V.span([[1,3,1]]); M.has_user_basis()
False

```

linear_combination_of_basis(v)

Return the linear combination of the basis for `self` obtained from the coordinates of `v`.

INPUT:

- `v` - list

EXAMPLES:

```

sage: V = span([[1,2,3], [4,5,6]], ZZ); V
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]
sage: V.linear_combination_of_basis([1,1])
(1, 5, 9)

```

This should raise an error if the resulting element is not in `self`:

```

sage: W = (QQ**2).span([[2, 0], [0, 8]], ZZ)
sage: W.linear_combination_of_basis([1, -1/2])
Traceback (most recent call last):
...
TypeError: element [2, -4] is not in free module

```

relations()

Return the submodule defining the relations of `self` as a subquotient (considering the ambient module as a quotient module).

EXAMPLES:

```

sage: V = GF(2)^2
sage: W = V.subspace([[1, 0]])
sage: W.relations() == V.zero_submodule()
True

sage: Q = V / W
sage: Q.relations() == W
True
sage: Q.zero_submodule().relations() == W
True

```

user_to_echelon_matrix()

Return matrix that transforms a vector written with respect to the user basis of `self` to one written with respect to the echelon basis. The matrix acts from the right, as is usual in Sage.

EXAMPLES:

```

sage: A = ZZ^3
sage: M = A.span_of_basis([[1,2,3],[4,5,6]])
sage: M.echelonized_basis()
[
(1, 2, 3),
(0, 3, 6)
]
sage: M.user_to_echelon_matrix()
[ 1  0]
[ 4 -1]

```

The vector $v = (5, 7, 9)$ in M is $(1, 1)$ with respect to the user basis. Multiplying the above matrix on the right by this vector yields $(5, -1)$, which has components the coordinates of v with respect to the echelon basis.

```

sage: v0,v1 = M.basis(); v = v0+v1
sage: e0,e1 = M.echelonized_basis()
sage: v
(5, 7, 9)
sage: 5*e0 + (-1)*e1
(5, 7, 9)

```

vector_space(*base_field=None*)

Return the vector space associated to this free module via tensor product with the fraction field of the base ring.

EXAMPLES:

```

sage: A = ZZ^3; A
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: A.vector_space()
Vector space of dimension 3 over Rational Field
sage: M = A.span_of_basis([[1/3,2,3/7],[4,5,6]]); M
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1/3  2 3/7]
[ 4   5  6]
sage: M.vector_space()
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1/3  2 3/7]
[ 4   5  6]

```

```

class sage.modules.free_module.Module_free_ambient(base_ring, degree, sparse=False,
                                                    category=None)

```

Bases: [sage.modules.module.Module](#)

Base class for modules with elements represented by elements of a free module.

Modules whose elements are represented by elements of a free module (such as submodules, quotients, and subquotients of a free module) should be either a subclass of this class or [FreeModule_generic](#), which itself is a subclass of this class. If the modules have bases and ranks, then use [FreeModule_generic](#). Otherwise, use this class.

INPUT:

- `base_ring` – a commutative ring
- `degree` – a non-negative integer; degree of the ambient free module
- `sparse` – boolean (default: `False`)
- `category` – category (default: `None`)

If `base_ring` is a field, then the default category is the category of finite-dimensional vector spaces over that field; otherwise it is the category of finite-dimensional free modules over that ring. In addition, the category is intersected with the category of finite enumerated sets if the ring is finite or the rank is 0.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N.gens()
[
(x - y, z),
(y*z, x*z)
]
sage: N.degree()
2
```

`coordinate_ring()`

Return the ring over which the entries of the vectors are defined.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N.coordinate_ring()
Multivariate Polynomial Ring in x, y, z over Rational Field
```

`degree()`

Return the degree of this free module. This is the dimension of the ambient vector space in which it is embedded.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 10)
sage: W = M.submodule([M.gen(0), 2*M.gen(3) - M.gen(0), M.gen(0) + M.gen(3)])
sage: W.degree()
10
sage: W.rank()
2
```

`is_sparse()`

Return `True` if the underlying representation of this module uses sparse vectors, and `False` otherwise.

EXAMPLES:

```
sage: FreeModule(ZZ, 2).is_sparse()
False
sage: FreeModule(ZZ, 2, sparse=True).is_sparse()
True
```

is_submodule(*other*)

Return True if *self* is a submodule of *other*.

EXAMPLES:

Submodule testing over general rings is not guaranteed to work in all cases. However, it will raise an error when it is unable to determine containment.

The zero module can always be tested:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: N.zero_submodule().is_submodule(M)
True
sage: N.zero_submodule().is_submodule(N)
True
sage: M.zero_submodule().is_submodule(N)
True
```

It also respects which module it is constructed from:

```
sage: Q = M.quotient_module(N)
sage: Q.zero_submodule().is_submodule(M)
False
sage: Q.zero_submodule().is_submodule(N)
False
sage: M.zero_submodule().is_submodule(Q)
False
sage: N.zero_submodule().is_submodule(Q)
False
```

quotient(*sub*, *check=True*)

Return the quotient of *self* by the given subspace *sub*.

INPUT:

- *sub* – a submodule of *self* or something that can be turned into one via *self.submodule(sub)*
- *check* – (default: True) whether or not to check that *sub* is a submodule

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: M.quotient(N)
Quotient module by Submodule of Ambient free module of rank 2 over
the integral domain Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y      z]
[ y*z     x*z]
```

quotient_module(*sub*, *check=True*)

Return the quotient of *self* by the given subspace *sub*.

INPUT:

- *sub* – a submodule of *self* or something that can be turned into one via *self.submodule(sub)*

- `check` – (default: `True`) whether or not to check that `sub` is a submodule

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: M.quotient(N)
Quotient module by Submodule of Ambient free module of rank 2 over
the integral domain Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y      z]
[ y*z     x*z]
```

`relations_matrix()`

Return the matrix of relations of `self`.

EXAMPLES:

```
sage: V = GF(2)^2
sage: V.relations_matrix()
[]
sage: W = V.subspace([[1, 0]])
sage: W.relations_matrix()
[]

sage: Q = V / W
sage: Q.relations_matrix()
[1 0]

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: M.relations_matrix()
[]

sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
sage: Q.relations_matrix()
[x - y      z]
[ y*z     x*z]
```

`some_elements()`

Return some elements of this free module.

See [TestSuite](#) for a typical use case.

OUTPUT:

An iterator.

EXAMPLES:

```
sage: F = FreeModule(ZZ, 2)
sage: tuple(F.some_elements())
((1, 0),
 (1, 1),
 (0, 1),
```

(continues on next page)

(continued from previous page)

```

(-1, 2),
(-2, 3),
...
(-49, 50))

sage: F = FreeModule(QQ, 3)
sage: tuple(F.some_elements())
((1, 0, 0),
 (1/2, 1/2, 1/2),
 (1/2, -1/2, 2),
 (-2, 0, 1),
 (-1, 42, 2/3),
 (-2/3, 3/2, -3/2),
 (4/5, -4/5, 5/4),
 ...
 (46/103823, -46/103823, 103823/46))

sage: F = FreeModule(SR, 2)
sage: tuple(F.some_elements())
((1, 0), (some_variable, some_variable))

```

span(gens, base_ring=None, check=True, already_echelonized=False)

Return the R -span of gens, where R is the base_ring.

The default R is the base ring of `self`. Note that this span need not be a submodule of `self`, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R .

INPUT:

- gens – a list of vectors
- base_ring – (optional) a ring
- check – boolean (default: True): whether or not to coerce entries of gens into base field
- already_echelonized – boolean (default: False); set this if you know the gens are already in echelon form

EXAMPLES:

```

sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span([[1,1,1]])
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 1 1]

```

Over a general ring:

```

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: M.span([vector([x - y, z]), vector([y*z, x*z])])

```

(continues on next page)

(continued from previous page)

```
Submodule of Ambient free module of rank 2 over the integral domain.
↳Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y      z]
[ y*z    x*z]
```

Over a PID:

```
sage: V = FreeModule(ZZ, 3)
sage: W = V.submodule([V.gen(0)])
sage: W.span([V.gen(1)])
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[0 1 0]
sage: W.submodule([V.gen(1)])
Traceback (most recent call last):
...
ArithmeticError: argument gens (= [(0, 1, 0)]) does not generate a submodule of.
↳self
sage: V.span([[1,0,0],[1/5,4,0],[6,3/4,0]])
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1/5  0  0]
[  0 1/4  0]
```

It also works with other things than integers:

```
sage: R.<x>=QQ[]
sage: L=R^1
sage: a=L.span([(1/x,)])
sage: a
Free module of degree 1 and rank 1 over Univariate Polynomial Ring in x over
↳Rational Field
Echelon basis matrix:
[1/x]
sage: b=L.span([(1/x,)])
sage: a(b.gens()[0])
(1/x)
sage: L2 = R^2
sage: L2.span([(x^2+x)/(x^2-3*x+2),1/5],[(x^2+2*x)/(x^2-4*x+3),x])
Free module of degree 2 and rank 2 over Univariate Polynomial Ring in x over
↳Rational Field
Echelon basis matrix:
[x/(x^3 - 6*x^2 + 11*x - 6)  2/15*x^2 - 17/75*x - 1/75]
[ 0 x^3 - 11/5*x^2 - 3*x + 4/5]
```

Note that the `base_ring` can make a huge difference. We repeat the previous example over the fraction field of R and get a simpler vector space.

```
sage: L2.span([(x^2+x)/(x^2-3*x+2),1/5],[(x^2+2*x)/(x^2-4*x+3),x],base_ring=R.
↳fraction_field())
Vector space of degree 2 and dimension 2 over Fraction Field of Univariate
↳Polynomial Ring in x over Rational Field
```

(continues on next page)

(continued from previous page)

```
Basis matrix:
[1 0]
[0 1]
```

submodule(gens, check=True, already_echelonized=False)

Create the R -submodule of the ambient module with given generators, where R is the base ring of **self**.

INPUT:

- **gens** – a list of free module elements or a free module
- **check** – (default: True) whether or not to verify that the gens are in **self**

OUTPUT:

The submodule spanned by the vectors in the list **gens**. The basis for the subspace is always put in reduced row echelon form (if possible).

EXAMPLES:

We create a submodule of \mathbf{Z}^3 :

```
sage: M = FreeModule(ZZ, 3)
sage: B = M.basis()
sage: W = M.submodule([B[0]+B[1], 2*B[1]-B[2]])
sage: W
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  1  0]
[ 0  2 -1]
```

We create a submodule of a submodule:

```
sage: W.submodule([3*B[0] + 3*B[1]])
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[3 3 0]
```

We try to create a submodule that isn't really a submodule, which results in an **ArithmeticError** exception:

```
sage: W.submodule([B[0] - B[1]])
Traceback (most recent call last):
...
ArithmeticError: argument gens (= [(1, -1, 0)]) does not generate a submodule
↳ of self
```

Next we create a submodule of a free module over the principal ideal domain $\mathbf{Q}[x]$, which uses the general Hermite normal form functionality:

```
sage: R = PolynomialRing(QQ, 'x'); x = R.gen()
sage: M = FreeModule(R, 3)
sage: B = M.basis()
sage: W = M.submodule([x*B[0], 2*B[1]-x*B[2]]); W
Free module of degree 3 and rank 2 over Univariate Polynomial Ring in x over
↳ Rational Field
```

(continues on next page)

(continued from previous page)

```
Echelon basis matrix:
[ x  0  0]
[ 0  2 -x]
sage: W.ambient_module()
Ambient free module of rank 3 over the principal ideal domain Univariate_
↳Polynomial Ring in x over Rational Field
```

Over a generic ring:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: A = S**2
sage: A.submodule([vector([x - y,z]), vector([y*z, x*z])])
Submodule of Ambient free module of rank 2 over the integral domain_
↳Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y    z]
[ y*z   x*z]
```

zero()

Return the zero vector in this module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2)
sage: M.zero()
(0, 0)
sage: M.span([[1,1]]).zero()
(0, 0)
sage: M.zero_submodule().zero()
(0, 0)
sage: M.zero_submodule().zero().is_mutable()
False
```

zero_submodule()

Return the zero submodule of this module.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: M.zero_submodule()
Submodule of Ambient free module of rank 2 over the integral domain_
↳Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[]
```

zero_vector()

Return the zero vector in this module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 2)
sage: M.zero_vector()
(0, 0)
```

(continues on next page)

(continued from previous page)

```

sage: M(0)
(0, 0)
sage: M.span([[1,1]]).zero_vector()
(0, 0)
sage: M.zero_submodule().zero_vector()
(0, 0)

```

class sage.modules.free_module.RealDoubleVectorSpace_class(*n*)

Bases: *sage.modules.free_module.FreeModule_ambient_field*

coordinates(*v*)

sage.modules.free_module.VectorSpace(*K, dimension_or_basis_keys, sparse, inner_product_matrix, with_basis=None, dimension=False, basis_keys=None, **args*)

EXAMPLES:

The base can be complicated, as long as it is a field.

```

sage: V = VectorSpace(FractionField(PolynomialRing(ZZ, 'x')), 3)
sage: V
Vector space of dimension 3 over Fraction Field of Univariate Polynomial Ring in x
↳ over Integer Ring
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]

```

The base must be a field or a `TypeError` is raised.

```

sage: VectorSpace(ZZ, 5)
Traceback (most recent call last):
...
TypeError: Argument K (= Integer Ring) must be a field.

```

sage.modules.free_module.basis_seq(*V, vecs*)

This converts a list *vecs* of vectors in *V* to an Sequence of immutable vectors.

Should it? I.e. in most other parts of the system the return type of `basis` or `generators` is a tuple.

EXAMPLES:

```

sage: V = VectorSpace(QQ, 2)
sage: B = V.gens()
sage: B
((1, 0), (0, 1))
sage: v = B[0]
sage: v[0] = 0 # immutable
Traceback (most recent call last):
...
ValueError: vector is immutable; please change a copy instead (use copy())
sage: sage.modules.free_module.basis_seq(V, V.gens())
[
(1, 0),

```

(continues on next page)

(continued from previous page)

```
(0, 1)
]
```

`sage.modules.free_module.element_class(R, is_sparse)`

The class of the vectors (elements of a free module) with base ring `R` and boolean `is_sparse`.

EXAMPLES:

```
sage: FF = FiniteField(2)
sage: P = PolynomialRing(FF, 'x')
sage: sage.modules.free_module.element_class(QQ, is_sparse=True)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(QQ, is_sparse=False)
<class 'sage.modules.vector_rational_dense.Vector_rational_dense'>
sage: sage.modules.free_module.element_class(ZZ, is_sparse=True)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(ZZ, is_sparse=False)
<class 'sage.modules.vector_integer_dense.Vector_integer_dense'>
sage: sage.modules.free_module.element_class(FF, is_sparse=True)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(FF, is_sparse=False)
<class 'sage.modules.vector_mod2_dense.Vector_mod2_dense'>
sage: sage.modules.free_module.element_class(GF(7), is_sparse=False)
<class 'sage.modules.vector_modn_dense.Vector_modn_dense'>
sage: sage.modules.free_module.element_class(P, is_sparse=True)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: sage.modules.free_module.element_class(P, is_sparse=False)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_dense'>
```

`sage.modules.free_module.is_FreeModule(M)`

Return True if `M` inherits from `FreeModule_generic`.

EXAMPLES:

```
sage: from sage.modules.free_module import is_FreeModule
sage: V = ZZ^3
sage: is_FreeModule(V)
True
sage: W = V.span([ V.random_element() for i in range(2) ])
sage: is_FreeModule(W)
True
```

`sage.modules.free_module.span(gens, base_ring=None, check=True, already_echelonized=False)`

Return the span of the vectors in `gens` using scalars from `base_ring`.

INPUT:

- `gens` - a list of either vectors or lists of ring elements used to generate the span
- `base_ring` - default: `None` - a principal ideal domain for the ring of scalars
- `check` - default: `True` - passed to the `span()` method of the ambient module
- `already_echelonized` - default: `False` - set to `True` if the vectors form the rows of a matrix in echelon form, in order to skip the computation of an echelonized basis for the span.

OUTPUT:

A module (or vector space) that is all the linear combinations of the free module elements (or vectors) with scalars from the ring (or field) given by `base_ring`. See the examples below describing behavior when the base ring is not specified and/or the module elements are given as lists that do not carry explicit base ring information.

EXAMPLES:

The vectors in the list of generators can be given as lists, provided a base ring is specified and the elements of the list are in the ring (or the fraction field of the ring). If the base ring is a field, the span is a vector space.

```
sage: V = span([[1,2,5], [2,2,2]], QQ); V
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -3]
[ 0  1  4]

sage: span([V.gen(0)], QuadraticField(-7,'a'))
Vector space of degree 3 and dimension 1 over Number Field in a with defining
↳ polynomial x^2 + 7 with a = 2.645751311064591?I
Basis matrix:
[ 1  0 -3]

sage: span([[1,2,3], [2,2,2], [1,2,5]], GF(2))
Vector space of degree 3 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 0 1]
```

If the base ring is not a field, then a module is created. The entries of the vectors can lie outside the ring, if they are in the fraction field of the ring.

```
sage: span([[1,2,5], [2,2,2]], ZZ)
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  0 -3]
[ 0  2  8]

sage: span([[1,1,1], [1,1/2,1]], ZZ)
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 1  0  1]
[ 0 1/2  0]

sage: R.<x> = QQ[]
sage: M= span( [x, x^2+1], [1/x, x^3]], R); M
Free module of degree 2 and rank 2 over
Univariate Polynomial Ring in x over Rational Field
Echelon basis matrix:
[      1/x      x^3]
[      0 x^5 - x^2 - 1]
sage: M.basis()[0][0].parent()
Fraction Field of Univariate Polynomial Ring in x over Rational Field
```

A base ring can be inferred if the generators are given as a list of vectors.

```
sage: span([vector(QQ, [1,2,3]), vector(QQ, [4,5,6])])
Vector space of degree 3 and dimension 2 over Rational Field
```

(continues on next page)

(continued from previous page)

```

Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: span([vector(QQ, [1,2,3]), vector(ZZ, [4,5,6])])
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: span([vector(ZZ, [1,2,3]), vector(ZZ, [4,5,6])])
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[1 2 3]
[0 3 6]

```

2.3 Elements of free modules

AUTHORS:

- William Stein
- Josh Kantor
- Thomas Feulner (2012-11): Added `FreeModuleElement.hamming_weight()` and `FreeModuleElement_generic_sparse.hamming_weight()`
- Jeroen Demeyer (2015-02-24): Implement fast Cython methods `get_unsafe` and `set_unsafe` similar to other places in Sage ([trac ticket #17562](#))

EXAMPLES: We create a vector space over \mathbb{Q} and a subspace of this space.

```

sage: V = QQ^5
sage: W = V.span([V.1, V.2])

```

Arithmetic operations always return something in the ambient space, since there is a canonical map from W to V but not from V to W .

```

sage: parent(W.0 + V.1)
Vector space of dimension 5 over Rational Field
sage: parent(V.1 + W.0)
Vector space of dimension 5 over Rational Field
sage: W.0 + V.1
(0, 2, 0, 0, 0)
sage: W.0 - V.0
(-1, 1, 0, 0, 0)

```

Next we define modules over \mathbb{Z} and a finite field.

```

sage: K = ZZ^5
sage: M = GF(7)^5

```

Arithmetic between the \mathbb{Q} and \mathbb{Z} modules is defined, and the result is always over \mathbb{Q} , since there is a canonical coercion map to \mathbb{Q} .


```
sage: K.0 + V.1
(1, 1, 0, 0, 0)
sage: parent(K.0 + V.1)
Vector space of dimension 5 over Rational Field
```

Since there is no canonical coercion map to the finite field from \mathbb{Q} the following arithmetic is not defined:

```
sage: V.0 + M.0
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for +: 'Vector space of dimension 5 over
↳ Rational Field' and 'Vector space of dimension 5 over Finite Field of size 7'
```

However, there is a map from \mathbb{Z} to the finite field, so the following is defined, and the result is in the finite field.

```
sage: w = K.0 + M.0; w
(2, 0, 0, 0, 0)
sage: parent(w)
Vector space of dimension 5 over Finite Field of size 7
sage: parent(M.0 + K.0)
Vector space of dimension 5 over Finite Field of size 7
```

Matrix vector multiply:

```
sage: MS = MatrixSpace(QQ,3)
sage: A = MS([0,1,0,1,0,0,0,0,1])
sage: V = QQ^3
sage: v = V([1,2,3])
sage: v * A
(2, 1, 3)
```

class sage.modules.free_module_element.FreeModuleElement

Bases: sage.structure.element.Vector

An element of a generic free module.

Mod(p)

EXAMPLES:

```
sage: V = vector(ZZ, [5, 9, 13, 15])
sage: V.Mod(7)
(5, 2, 6, 1)
sage: parent(V.Mod(7))
Vector space of dimension 4 over Ring of integers modulo 7
```

additive_order()

Return the additive order of self.

EXAMPLES:

```
sage: v = vector(Integers(4), [1,2])
sage: v.additive_order()
4
```

```
sage: v = vector([1,2,3])
sage: v.additive_order()
+Infinity
```

```
sage: v = vector(Integers(30), [6, 15]); v
(6, 15)
sage: v.additive_order()
10
sage: 10*v
(0, 0)
```

apply_map(*phi*, *R=None*, *sparse=None*)

Apply the given map *phi* (an arbitrary Python function or callable object) to this free module element. If *R* is not given, automatically determine the base ring of the resulting element.

INPUT:

sparse – True or False will control whether the result is sparse. By default, the result is sparse iff self is sparse.

- *phi* - arbitrary Python function or callable object
- *R* - (optional) ring

OUTPUT: a free module element over *R*

EXAMPLES:

```
sage: m = vector([1,x,sin(x+1)])
sage: m.apply_map(lambda x: x^2)
(1, x^2, sin(x + 1)^2)
sage: m.apply_map(sin)
(sin(1), sin(x), sin(sin(x + 1)))
```

```
sage: m = vector(ZZ, 9, range(9))
sage: k.<a> = GF(9)
sage: m.apply_map(k)
(0, 1, 2, 0, 1, 2, 0, 1, 2)
```

In this example, we explicitly specify the codomain.

```
sage: s = GF(3)
sage: f = lambda x: s(x)
sage: n = m.apply_map(f, k); n
(0, 1, 2, 0, 1, 2, 0, 1, 2)
sage: n.parent()
Vector space of dimension 9 over Finite Field in a of size 3^2
```

If your map sends 0 to a non-zero value, then your resulting vector is not mathematically sparse:

```
sage: v = vector([0] * 6 + [1], sparse=True); v
(0, 0, 0, 0, 0, 0, 1)
sage: v2 = v.apply_map(lambda x: x+1); v2
(1, 1, 1, 1, 1, 1, 2)
```

but it's still represented with a sparse data type:

```
sage: parent(v2)
Ambient sparse free module of rank 7 over the principal ideal domain Integer_
↪Ring
```

This data type is inefficient for dense vectors, so you may want to specify `sparse=False`:

```
sage: v2 = v.apply_map(lambda x: x+1, sparse=False); v2
(1, 1, 1, 1, 1, 1, 2)
sage: parent(v2)
Ambient free module of rank 7 over the principal ideal domain Integer Ring
```

Or if you have a map that will result in mostly zeroes, you may want to specify `sparse=True`:

```
sage: v = vector(srange(10))
sage: v2 = v.apply_map(lambda x: 0 if x else 1, sparse=True); v2
(1, 0, 0, 0, 0, 0, 0, 0, 0, 0)
sage: parent(v2)
Ambient sparse free module of rank 10 over the principal ideal domain Integer_
↪Ring
```

`change_ring(R)`

Change the base ring of this vector.

EXAMPLES:

```
sage: v = vector(QQ['x,y'], [1..5]); v.change_ring(GF(3))
(1, 2, 0, 1, 2)
```

`column()`

Return a matrix with a single column and the same entries as the vector `self`.

OUTPUT:

A matrix over the same ring as the vector (or free module element), with a single column. The entries of the column are identical to those of the vector, and in the same order.

EXAMPLES:

```
sage: v = vector(ZZ, [1,2,3])
sage: w = v.column(); w
[1]
[2]
[3]
sage: w.parent()
Full MatrixSpace of 3 by 1 dense matrices over Integer Ring

sage: x = vector(FiniteField(13), [2,4,8,16])
sage: x.column()
[2]
[4]
[8]
[3]
```

There is more than one way to get one-column matrix from a vector. The `column` method is about equally

efficient to making a row and then taking a transpose. Notice that supplying a vector to the matrix constructor demonstrates Sage's preference for rows.

```
sage: x = vector(RDF, [sin(i*pi/20) for i in range(10)])
sage: x.column() == matrix(x).transpose()
True
sage: x.column() == x.row().transpose()
True
```

Sparse or dense implementations are preserved.

```
sage: d = vector(RR, [1.0, 2.0, 3.0])
sage: s = vector(CDF, {2:5.0+6.0*I})
sage: dm = d.column()
sage: sm = s.column()
sage: all([d.is_dense(), dm.is_dense(), s.is_sparse(), sm.is_sparse()])
True
```

`conjugate()`

Returns a vector where every entry has been replaced by its complex conjugate.

OUTPUT:

A vector of the same length, over the same ring, but with each entry replaced by the complex conjugate, as implemented by the `conjugate()` method for elements of the base ring, which is presently always complex conjugation.

EXAMPLES:

```
sage: v = vector(CDF, [2.3 - 5.4*I, -1.7 + 3.6*I])
sage: w = v.conjugate(); w
(2.3 + 5.4*I, -1.7 - 3.6*I)
sage: w.parent()
Vector space of dimension 2 over Complex Double Field
```

Even if conjugation seems nonsensical over a certain ring, this method for vectors cooperates silently.

```
sage: u = vector(ZZ, range(6))
sage: u.conjugate()
(0, 1, 2, 3, 4, 5)
```

Sage implements a few specialized subfields of the complex numbers, such as the cyclotomic fields. This example uses such a field containing a primitive 7-th root of unity named `a`.

```
sage: F.<a> = CyclotomicField(7)
sage: v = vector(F, [a^i for i in range(7)])
sage: v
(1, a, a^2, a^3, a^4, a^5, -a^5 - a^4 - a^3 - a^2 - a - 1)
sage: v.conjugate()
(1, -a^5 - a^4 - a^3 - a^2 - a - 1, a^5, a^4, a^3, a^2, a)
```

Sparse vectors are returned as such.

```
sage: v = vector(CC, {1: 5 - 6*I, 3: -7*I}); v
(0.0000000000000000, 5.000000000000000 - 6.000000000000000*I, 0.0000000000000000, -
↪ 7.000000000000000*I)
```

(continues on next page)

(continued from previous page)

```

sage: v.is_sparse()
True
sage: vc = v.conjugate(); vc
(0.0000000000000000, 5.000000000000000 + 6.000000000000000*I, 0.000000000000000, 7.
↪ 0000000000000000*I)
sage: vc.conjugate()
(0.0000000000000000, 5.000000000000000 - 6.000000000000000*I, 0.000000000000000, -
↪ 7.000000000000000*I)

```

coordinate_ring()

Return the ring from which the coefficients of this vector come.

This is different from `base_ring()`, which returns the ring of scalars.

EXAMPLES:

```

sage: M = (ZZ^2) * (1/2)
sage: v = M([0, 1/2])
sage: v.base_ring()
Integer Ring
sage: v.coordinate_ring()
Rational Field

```

cross_product(right)

Return the cross product of self and right, which is only defined for vectors of length 3 or 7.

INPUT:

- `right` - A vector of the same size as `self`, either degree three or degree seven.

OUTPUT:

The cross product (vector product) of `self` and `right`, a vector of the same size of `self` and `right`.

This product is performed under the assumption that the basis vectors are orthonormal. See the method `cross_product()` of vector fields for more general cases.

EXAMPLES:

```

sage: v = vector([1, 2, 3]); w = vector([0, 5, -9])
sage: v.cross_product(v)
(0, 0, 0)
sage: u = v.cross_product(w); u
(-33, 9, 5)
sage: u.dot_product(v)
0
sage: u.dot_product(w)
0

```

The cross product is defined for degree seven vectors as well: see [Wikipedia article Cross_product](#). The 3-D cross product is achieved using the quaternions, whereas the 7-D cross product is achieved using the octonions.

```

sage: u = vector(QQ, [1, -1/3, 57, -9, 56/4, -4, 1])
sage: v = vector(QQ, [37, 55, -99/57, 9, -12, 11/3, 4/98])
sage: u.cross_product(v)
(1394815/2793, -2808401/2793, 39492/49, -48737/399, -9151880/2793, 62513/2793, -
↪ 326603/171)

```

(continues on next page)

(continued from previous page)

The degree seven cross product is anticommutative.

```
sage: u.cross_product(v) + v.cross_product(u)
(0, 0, 0, 0, 0, 0, 0)
```

The degree seven cross product is distributive across addition.

```
sage: v = vector([-12, -8/9, 42, 89, -37, 60/99, 73])
sage: u = vector([31, -42/7, 97, 80, 30/55, -32, 64])
sage: w = vector([-25/4, 40, -89, -91, -72/7, 79, 58])
sage: v.cross_product(u + w) - (v.cross_product(u) + v.cross_product(w))
(0, 0, 0, 0, 0, 0, 0)
```

The degree seven cross product respects scalar multiplication.

```
sage: v = vector([2, 17, -11/5, 21, -6, 2/17, 16])
sage: u = vector([-8, 9, -21, -6, -5/3, 12, 99])
sage: (5*v).cross_product(u) - 5*(v.cross_product(u))
(0, 0, 0, 0, 0, 0, 0)
sage: v.cross_product(5*u) - 5*(v.cross_product(u))
(0, 0, 0, 0, 0, 0, 0)
sage: (5*v).cross_product(u) - (v.cross_product(5*u))
(0, 0, 0, 0, 0, 0, 0)
```

The degree seven cross product respects the scalar triple product.

```
sage: v = vector([2, 6, -7/4, -9/12, -7, 12, 9])
sage: u = vector([22, -7, -9/11, 12, 15, 15/7, 11])
sage: w = vector([-11, 17, 19, -12/5, 44, 21/56, -8])
sage: v.dot_product(u.cross_product(w)) - w.dot_product(v.cross_product(u))
0
```

AUTHOR:

Billy Wonderly (2010-05-11), Added 7-D Cross Product

cross_product_matrix()

Return the matrix which describes a cross product between `self` and some other vector.

This operation is sometimes written using the hat operator: see [Wikipedia article Hat_operator#Cross_product](#). It is only defined for vectors of length 3 or 7. For a vector v the cross product matrix \hat{v} is a matrix which satisfies $\hat{v} \cdot w = v \times w$ and also $w \cdot \hat{v} = w \times v$ for all vectors w . The basis vectors are assumed to be orthonormal.

OUTPUT:

The cross product matrix of this vector.

EXAMPLES:

```
sage: v = vector([1, 2, 3])
sage: vh = v.cross_product_matrix()
sage: vh
[ 0 -3  2]
```

(continues on next page)

(continued from previous page)

```

[ 3  0 -1]
[-2  1  0]
sage: w = random_vector(3, x=1, y=100)
sage: v*h*w == v.cross_product(w)
True
sage: w*v*h == w.cross_product(v)
True
sage: v.h.is_alternating()
True

```

curl(variables=None)

Return the curl of this two-dimensional or three-dimensional vector function.

EXAMPLES:

```

sage: R.<x,y,z> = QQ[]
sage: vector([-y, x, 0]).curl()
(0, 0, 2)
sage: vector([y, -x, x*y*z]).curl()
(x*z, -y*z, -2)
sage: vector([y^2, 0, 0]).curl()
(0, 0, -2*y)
sage: (R^3).random_element().curl().div()
0

```

For rings where the variable order is not well defined, it must be defined explicitly:

```

sage: v = vector(SR, [-y, x, 0])
sage: v.curl()
Traceback (most recent call last):
...
ValueError: Unable to determine ordered variable names for Symbolic Ring
sage: v.curl([x, y, z])
(0, 0, 2)

```

Note that callable vectors have well defined variable orderings:

```

sage: v(x, y, z) = (-y, x, 0)
sage: v.curl()
(x, y, z) |--> (0, 0, 2)

```

In two-dimensions, this returns a scalar value:

```

sage: R.<x,y> = QQ[]
sage: vector([-y, x]).curl()
2

```

See also:

`curl()` of vector fields on Euclidean spaces (and more generally pseudo-Riemannian manifolds), in particular for computing the curl in curvilinear coordinates.

degree()

Return the degree of this vector, which is simply the number of entries.

EXAMPLES:

```
sage: sage.modules.free_module_element.FreeModuleElement(QQ^389).degree()
389
sage: vector([1, 2/3, 8]).degree()
3
```

denominator()

Return the least common multiple of the denominators of the entries of self.

EXAMPLES:

```
sage: v = vector([1/2, 2/5, 3/14])
sage: v.denominator()
70
sage: 2*5*7
70
```

```
sage: M = (ZZ^2)*(1/2)
sage: M.basis()[0].denominator()
2
```

dense_vector()

Return dense version of self. If self is dense, just return self; otherwise, create and return correspond dense vector.

EXAMPLES:

```
sage: vector([-1, 0, 3, 0, 0, 0]).dense_vector().is_dense()
True
sage: vector([-1, 0, 3, 0, 0, 0], sparse=True).dense_vector().is_dense()
True
sage: vector([-1, 0, 3, 0, 0, 0], sparse=True).dense_vector()
(-1, 0, 3, 0, 0, 0)
```

derivative(*args)

Derivative with respect to variables supplied in args.

Multiple variables and iteration counts may be supplied; see documentation for the global derivative() function for more details.

diff() is an alias of this function.

EXAMPLES:

```
sage: v = vector([1, x, x^2])
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v = vector([1, x, x^2], sparse=True)
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v.derivative(x, x)
(0, 0, 2)
```


dict(*copy=True*)Return dictionary of nonzero entries of *self*.

More precisely, this returns a dictionary whose keys are indices of basis elements in the support of *self* and whose values are the corresponding coefficients.

INPUT:

- *copy* – (default: `True`) if *self* is internally represented by a dictionary *d*, then make a copy of *d*; if `False`, then this can cause undesired behavior by mutating *d*

OUTPUT:

- Python dictionary

EXAMPLES:

```
sage: v = vector([0,0,0,0,1/2,0,3/14])
sage: v.dict()
{4: 1/2, 6: 3/14}
sage: sorted(v.support())
[4, 6]
```

In some cases, when *copy=False*, we get back a dangerous reference:

```
sage: v = vector({0:5, 2:3/7}, sparse=True)
sage: v.dict(copy=False)
{0: 5, 2: 3/7}
sage: v.dict(copy=False)[0] = 18
sage: v
(18, 0, 3/7)
```

diff(**args*)Derivative with respect to variables supplied in *args*.

Multiple variables and iteration counts may be supplied; see documentation for the `global derivative()` function for more details.

`diff()` is an alias of this function.

EXAMPLES:

```
sage: v = vector([1,x,x^2])
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v = vector([1,x,x^2], sparse=True)
sage: v.derivative(x)
(0, 1, 2*x)
sage: type(v.derivative(x)) == type(v)
True
sage: v.derivative(x,x)
(0, 0, 2)
```

div(*variables=None*)

Return the divergence of this vector function.

EXAMPLES:

```

sage: R.<x,y,z> = QQ[]
sage: vector([x, y, z]).div()
3
sage: vector([x*y, y*z, z*x]).div()
x + y + z

sage: R.<x,y,z,w> = QQ[]
sage: vector([x*y, y*z, z*x]).div([x, y, z])
x + y + z
sage: vector([x*y, y*z, z*x]).div([z, x, y])
0
sage: vector([x*y, y*z, z*x]).div([x, y, w])
y + z

sage: vector(SR, [x*y, y*z, z*x]).div()
Traceback (most recent call last):
...
ValueError: Unable to determine ordered variable names for Symbolic Ring
sage: vector(SR, [x*y, y*z, z*x]).div([x, y, z])
x + y + z

```

See also:

[divergence\(\)](#) of vector fields on Euclidean spaces (and more generally pseudo-Riemannian manifolds), in particular for computing the divergence in curvilinear coordinates.

dot_product(*right*)

Return the dot product of *self* and *right*, which is the sum of the product of the corresponding entries.

INPUT:

- *right* – a vector of the same degree as *self*. It does not need to belong to the same parent as *self*, so long as the necessary products and sums are defined.

OUTPUT:

If *self* and *right* are the vectors \vec{x} and \vec{y} , of degree n , then this method returns

$$\sum_{i=1}^n x_i y_i$$

Note: The [inner_product\(\)](#) is a more general version of this method, and the [hermitian_inner_product\(\)](#) method may be more appropriate if your vectors have complex entries.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 3)
sage: v = V([1,2,3])
sage: w = V([4,5,6])
sage: v.dot_product(w)
32

```

```

sage: R.<x> = QQ[]
sage: v = vector([x,x^2,3*x]); w = vector([2*x,x,3+x])
sage: v*w
x^3 + 5*x^2 + 9*x
sage: (x^2*x) + (x^2*x) + (3*x*(3+x))
x^3 + 5*x^2 + 9*x
sage: w*v
x^3 + 5*x^2 + 9*x

```

The vectors may be from different vector spaces, provided the necessary operations make sense. Notice that coercion will generate a result of the same type, even if the order of the arguments is reversed.:

```

sage: v = vector(ZZ, [1,2,3])
sage: w = vector(FiniteField(3), [0,1,2])
sage: ip = w.dot_product(v); ip
2
sage: ip.parent()
Finite Field of size 3

sage: ip = v.dot_product(w); ip
2
sage: ip.parent()
Finite Field of size 3

```

The dot product of a vector with itself is the 2-norm, squared.

```

sage: v = vector(QQ, [3, 4, 7])
sage: v.dot_product(v) - v.norm()^2
0

```

element()

Simply returns self. This is useful, since for many objects, self.element() returns a vector corresponding to self.

EXAMPLES:

```

sage: v = vector([1/2,2/5,0]); v
(1/2, 2/5, 0)
sage: v.element()
(1/2, 2/5, 0)

```

get(i)

Like `__getitem__` but without bounds checking: *i* must satisfy $0 \leq i < \text{self.degree}$.

EXAMPLES:

```

sage: vector(SR, [1/2,2/5,0]).get(0)
1/2

```

hamming_weight()

Return the number of positions *i* such that `self[i] != 0`.

EXAMPLES:

```

sage: vector([-1,0,3,0,0,0,0.01]).hamming_weight()
3

```

hermitian_inner_product(*right*)

Returns the dot product, but with the entries of the first vector conjugated beforehand.

INPUT:

- *right* - a vector of the same degree as *self*

OUTPUT:

If *self* and *right* are the vectors \vec{x} and \vec{y} of degree n then this routine computes

$$\sum_{i=1}^n \overline{x_i} y_i$$

where the bar indicates complex conjugation.

Note: If your vectors do not contain complex entries, then `dot_product()` will return the same result without the overhead of conjugating elements of *self*.

If you are not computing a weighted inner product, and your vectors do not have complex entries, then the `dot_product()` will return the same result.

EXAMPLES:

```
sage: v = vector(CDF, [2+3*I, 5-4*I])
sage: w = vector(CDF, [6-4*I, 2+3*I])
sage: v.hermitian_inner_product(w)
-2.0 - 3.0*I
```

Sage implements a few specialized fields over the complex numbers, such as cyclotomic fields and quadratic number fields. So long as the base rings have a conjugate method, then the Hermitian inner product will be available.

```
sage: Q.<a> = QuadraticField(-7)
sage: a^2
-7
sage: v = vector(Q, [3+a, 5-2*a])
sage: w = vector(Q, [6, 4+3*a])
sage: v.hermitian_inner_product(w)
17*a - 4
```

The Hermitian inner product should be additive in each argument (we only need to test one), linear in each argument (with conjugation on the first scalar), and anti-commutative.

```
sage: alpha = CDF(5.0 + 3.0*I)
sage: u = vector(CDF, [2+4*I, -3+5*I, 2-7*I])
sage: v = vector(CDF, [-1+3*I, 5+4*I, 9-2*I])
sage: w = vector(CDF, [8+3*I, -4+7*I, 3-6*I])
sage: (u+v).hermitian_inner_product(w) == u.hermitian_inner_product(w) + v.
hermitian_inner_product(w)
True
sage: (alpha*u).hermitian_inner_product(w) == alpha.conjugate()*u.hermitian_
inner_product(w)
True
sage: u.hermitian_inner_product(alpha*w) == alpha*u.hermitian_inner_product(w)
```

(continues on next page)

(continued from previous page)

```
True
sage: u.hermitian_inner_product(v) == v.hermitian_inner_product(u).conjugate()
True
```

For vectors with complex entries, the Hermitian inner product has a more natural relationship with the 2-norm (which is the default for the `norm()` method). The norm squared equals the Hermitian inner product of the vector with itself.

```
sage: v = vector(CDF, [-0.66+0.47*I, -0.60+0.91*I, -0.62-0.87*I, 0.53+0.32*I])
sage: abs(v.norm())^2 - v.hermitian_inner_product(v) < 1.0e-10
True
```

`inner_product(right)`

Returns the inner product of `self` and `right`, possibly using an inner product matrix from the parent of `self`.

INPUT:

- `right` - a vector of the same degree as `self`

OUTPUT:

If the parent vector space does not have an inner product matrix defined, then this is the usual dot product (`dot_product()`). If `self` and `right` are considered as single column matrices, \vec{x} and \vec{y} , and A is the inner product matrix, then this method computes

$$(\vec{x})^t A \vec{y}$$

where t indicates the transpose.

Note: If your vectors have complex entries, the `hermitian_inner_product()` may be more appropriate for your purposes.

EXAMPLES:

```
sage: v = vector(QQ, [1,2,3])
sage: w = vector(QQ, [-1,2,-3])
sage: v.inner_product(w)
-6
sage: v.inner_product(w) == v.dot_product(w)
True
```

The vector space or free module that is the parent to `self` can have an inner product matrix defined, which will be used by this method. This matrix will be passed through to subspaces.

```
sage: ipm = matrix(ZZ, [[2,0,-1], [0,2,0], [-1,0,6]])
sage: M = FreeModule(ZZ, 3, inner_product_matrix = ipm)
sage: v = M([1,0,0])
sage: v.inner_product(v)
2
sage: K = M.span_of_basis([[0/2,-1/2,-1/2], [0,1/2,-1/2],[2,0,0]])
sage: (K.0).inner_product(K.0)
2
sage: w = M([1,3,-1])
```

(continues on next page)

(continued from previous page)

```
sage: v = M([2,-4,5])
sage: w.row()*ipm*v.column() == w.inner_product(v)
True
```

Note that the inner product matrix comes from the parent of `self`. So if a vector is not an element of the correct parent, the result could be a source of confusion.

```
sage: V = VectorSpace(QQ, 2, inner_product_matrix=[[1,2],[2,1]])
sage: v = V([12, -10])
sage: w = vector(QQ, [10,12])
sage: v.inner_product(w)
88
sage: w.inner_product(v)
0
sage: w = V(w)
sage: w.inner_product(v)
88
```

Note: The use of an inner product matrix makes no restrictions on the nature of the matrix. In particular, in this context it need not be Hermitian and positive-definite (as it is in the example above).

integral(*args, **kws)

Returns a symbolic integral of the vector, component-wise.

`integrate()` is an alias of the function.

EXAMPLES:

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: r.integral(t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: integrate(r,t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: r.integrate(t,0,1)
(1/2, 1/3, -cos(1) + 1)
```

integrate(*args, **kws)

Returns a symbolic integral of the vector, component-wise.

`integrate()` is an alias of the function.

EXAMPLES:

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: r.integral(t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: integrate(r,t)
(1/2*t^2, 1/3*t^3, -cos(t))
sage: r.integrate(t,0,1)
(1/2, 1/3, -cos(1) + 1)
```

is_dense()

Return True if this is a dense vector, which is just a statement about the data structure, not the number of nonzero entries.

EXAMPLES:

```
sage: vector([1/2, 2/5, 0]).is_dense()
True
sage: vector([1/2, 2/5, 0], sparse=True).is_dense()
False
```

is_sparse()

Return True if this is a sparse vector, which is just a statement about the data structure, not the number of nonzero entries.

EXAMPLES:

```
sage: vector([1/2, 2/5, 0]).is_sparse()
False
sage: vector([1/2, 2/5, 0], sparse=True).is_sparse()
True
```

is_vector()

Return True, since this is a vector.

EXAMPLES:

```
sage: vector([1/2, 2/5, 0]).is_vector()
True
```

items()

Return an iterator over self.

EXAMPLES:

```
sage: v = vector([1, 2/3, pi])
sage: v.items()
<generator object at ...>
sage: list(v.items())
[(0, 1), (1, 2/3), (2, pi)]
```

iteritems()

Return an iterator over self.

EXAMPLES:

```
sage: v = vector([1, 2/3, pi])
sage: v.items()
<generator object at ...>
sage: list(v.items())
[(0, 1), (1, 2/3), (2, pi)]
```

lift()

Lift self to the cover ring.

OUTPUT:

Return a lift of self to the covering ring of the base ring R , which is by definition the ring returned by calling `cover_ring()` on R , or just R itself if the `cover_ring()` method is not defined.

EXAMPLES:

```
sage: V = vector(Integers(7), [5, 9, 13, 15]) ; V
(5, 2, 6, 1)
sage: V.lift()
(5, 2, 6, 1)
sage: parent(V.lift())
Ambient free module of rank 4 over the principal ideal domain Integer Ring
```

If the base ring does not have a cover method, return a copy of the vector:

```
sage: W = vector(QQ, [1, 2, 3])
sage: W1 = W.lift()
sage: W is W1
False
sage: parent(W1)
Vector space of dimension 3 over Rational Field
```

lift_centered()

Lift to a congruent, centered vector.

INPUT:

- self A vector with coefficients in $\text{Integers}(n)$.

OUTPUT:

- The unique integer vector v such that for each i , $\text{Mod}(v[i], n) = \text{Mod}(\text{self}[i], n)$ and $-n/2 < v[i] \leq n/2$.

EXAMPLES:

```
sage: V = vector(Integers(7), [5, 9, 13, 15]) ; V
(5, 2, 6, 1)
sage: V.lift_centered()
(-2, 2, -1, 1)
sage: parent(V.lift_centered())
Ambient free module of rank 4 over the principal ideal domain Integer Ring
```

list(copy=True)

Return list of elements of self.

INPUT:

- copy – bool, whether returned list is a copy that is safe to change, is ignored.

EXAMPLES:

```
sage: P.<x,y,z> = QQ[]
sage: v = vector([x,y,z], sparse=True)
sage: type(v)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: a = v.list(); a
[x, y, z]
sage: a[0] = x*y; v
(x, y, z)
```

The optional argument copy is ignored:


```
sage: a = v.list(copy=False); a
[x, y, z]
sage: a[0] = x*y; v
(x, y, z)
```

list_from_positions(*positions*)

Return list of elements chosen from this vector using the given positions of this vector.

INPUT:

- *positions* – iterable of ints

EXAMPLES:

```
sage: v = vector([1,2/3,pi])
sage: v.list_from_positions([0,0,0,2,1])
[1, 1, 1, pi, 2/3]
```

monic()

Return this vector divided through by the first nonzero entry of this vector.

EXAMPLES:

```
sage: v = vector(QQ, [0, 4/3, 5, 1, 2])
sage: v.monic()
(0, 1, 15/4, 3/4, 3/2)
sage: v = vector(QQ, [])
sage: v.monic()
()
```

monomial_coefficients(*copy=True*)

Return dictionary of nonzero entries of *self*.

More precisely, this returns a dictionary whose keys are indices of basis elements in the support of *self* and whose values are the corresponding coefficients.

INPUT:

- *copy* – (default: `True`) if *self* is internally represented by a dictionary *d*, then make a copy of *d*; if `False`, then this can cause undesired behavior by mutating *d*

OUTPUT:

- Python dictionary

EXAMPLES:

```
sage: v = vector([0,0,0,0,1/2,0,3/14])
sage: v.dict()
{4: 1/2, 6: 3/14}
sage: sorted(v.support())
[4, 6]
```

In some cases, when *copy=False*, we get back a dangerous reference:

```
sage: v = vector({0:5, 2:3/7}, sparse=True)
sage: v.dict(copy=False)
{0: 5, 2: 3/7}
```

(continues on next page)

(continued from previous page)

```
sage: v.dict(copy=False)[0] = 18
sage: v
(18, 0, 3/7)
```

nintegral(*args, **kws)

Returns a numeric integral of the vector, component-wise, and the result of the nintegral command on each component of the input.

`nintegrate()` is an alias of the function.

EXAMPLES:

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: vec,answers=r.nintegral(t,0,1)
sage: vec
(0.5, 0.3333333333333334, 0.4596976941318602)
sage: type(vec)
<class 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: answers
[(0.5, 5.55111512312578...e-15, 21, 0), (0.333333333333333..., 3.70074341541719...
↪e-15, 21, 0), (0.45969769413186..., 5.10366964392284...e-15, 21, 0)]

sage: r=vector([t,0,1], sparse=True)
sage: r.nintegral(t,0,1)
((0.5, 0.0, 1.0), {0: (0.5, 5.55111512312578...e-15, 21, 0), 2: (1.0, 1.
↪11022302462515...e-14, 21, 0)})
```

nintegrate(*args, **kws)

Returns a numeric integral of the vector, component-wise, and the result of the nintegral command on each component of the input.

`nintegrate()` is an alias of the function.

EXAMPLES:

```
sage: t=var('t')
sage: r=vector([t,t^2,sin(t)])
sage: vec,answers=r.nintegral(t,0,1)
sage: vec
(0.5, 0.3333333333333334, 0.4596976941318602)
sage: type(vec)
<class 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: answers
[(0.5, 5.55111512312578...e-15, 21, 0), (0.333333333333333..., 3.70074341541719...
↪e-15, 21, 0), (0.45969769413186..., 5.10366964392284...e-15, 21, 0)]

sage: r=vector([t,0,1], sparse=True)
sage: r.nintegral(t,0,1)
((0.5, 0.0, 1.0), {0: (0.5, 5.55111512312578...e-15, 21, 0), 2: (1.0, 1.
↪11022302462515...e-14, 21, 0)})
```

nonzero_positions()

Return the sorted list of integers i such that $\text{self}[i] \neq 0$.

EXAMPLES:

```
sage: vector([-1,0,3,0,0,0,0.01]).nonzero_positions()
[0, 2, 6]
```

norm($p='_two_'$)

Return the p -norm of self.

INPUT:

- p - default: 2 - p can be a real number greater than 1, infinity (oo or Infinity), or a symbolic expression.
 - $p = 1$: the taxicab (Manhattan) norm
 - $p = 2$: the usual Euclidean norm (the default)
 - $p = \infty$: the maximum entry (in absolute value)

Note: See also `sage.misc.functional.norm()`

EXAMPLES:

```
sage: v = vector([1,2,-3])
sage: v.norm(5)
276^(1/5)
```

The default is the usual Euclidean norm.

```
sage: v.norm()
sqrt(14)
sage: v.norm(2)
sqrt(14)
```

The infinity norm is the maximum size (in absolute value) of the entries.

```
sage: v.norm(Infinity)
3
sage: v.norm(oo)
3
```

Real or symbolic values may be used for p .

```
sage: v=vector(RDF,[1,2,3])
sage: v.norm(5)
3.077384885394063
sage: v.norm(pi/2)      #abs tol 1e-15
4.216595864704748
sage: _=var('a b c d p'); v=vector([a, b, c, d])
sage: v.norm(p)
(abs(a)^p + abs(b)^p + abs(c)^p + abs(d)^p)^(1/p)
```

Notice that the result may be a symbolic expression, owing to the necessity of taking a square root (in the default case). These results can be converted to numerical values if needed.

```
sage: v = vector(ZZ, [3,4])
sage: nrm = v.norm(); nrm
```

(continues on next page)

(continued from previous page)

```

5
sage: nrm.parent()
Rational Field

sage: v = vector(QQ, [3, 5])
sage: nrm = v.norm(); nrm
sqrt(34)
sage: nrm.parent()
Symbolic Ring
sage: numeric = N(nrm); numeric
5.83095189484...
sage: numeric.parent()
Real Field with 53 bits of precision

```

normalized(*p*='__two__')

Return the input vector divided by the p-norm.

INPUT:

- “p” - default: 2 - p value for the norm

EXAMPLES:

```

sage: v = vector(QQ, [4, 1, 3, 2])
sage: v.normalized()
(2/15*sqrt(30), 1/30*sqrt(30), 1/10*sqrt(30), 1/15*sqrt(30))
sage: sum(v.normalized(1))
1

```

Note that normalizing the vector may change the base ring:

```

sage: v.base_ring() == v.normalized().base_ring()
False
sage: u = vector(RDF, [-3, 4, 6, 9])
sage: u.base_ring() == u.normalized().base_ring()
True

```

numerical_approx(*prec*=None, *digits*=None, *algorithm*=None)

Return a numerical approximation of *self* with *prec* bits (or decimal *digits*) of precision, by approximating all entries.

INPUT:

- *prec* – precision in bits
- *digits* – precision in decimal digits (only used if *prec* is not given)
- *algorithm* – which algorithm to use to compute the approximation of the entries (the accepted algorithms depend on the object)

If neither *prec* nor *digits* is given, the default precision is 53 bits (roughly 16 digits).

EXAMPLES:

```

sage: v = vector(RealField(212), [1,2,3])
sage: v.n()
(1.000000000000000, 2.000000000000000, 3.000000000000000)

```

(continues on next page)

(continued from previous page)

```

sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: numerical_approx(v)
(1.000000000000000, 2.000000000000000, 3.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.000000000000000000000000000000000, 2.000000000000000000000000000000000, 3.000000000000000000000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 75 bits of precision
sage: numerical_approx(v, digits=3)
(1.00, 2.00, 3.00)
sage: _.parent()
Vector space of dimension 3 over Real Field with 14 bits of precision

```

Both functional and object-oriented usage is possible.

```

sage: u = vector(QQ, [1/2, 1/3, 1/4])
sage: u.n()
(0.5000000000000000, 0.3333333333333333, 0.2500000000000000)
sage: u.numerical_approx()
(0.5000000000000000, 0.3333333333333333, 0.2500000000000000)
sage: n(u)
(0.5000000000000000, 0.3333333333333333, 0.2500000000000000)
sage: N(u)
(0.5000000000000000, 0.3333333333333333, 0.2500000000000000)
sage: numerical_approx(u)
(0.5000000000000000, 0.3333333333333333, 0.2500000000000000)

```

Precision (bits) and digits (decimal) may be specified. When both are given, `prec` wins.

```

sage: u = vector(QQ, [1/2, 1/3, 1/4])
sage: n(u, prec=15)
(0.5000, 0.3333, 0.2500)
sage: n(u, digits=5)
(0.50000, 0.33333, 0.25000)
sage: n(u, prec=30, digits=100)
(0.500000000, 0.33333333, 0.250000000)

```

These are some legacy doctests that were part of various specialized versions of the numerical approximation routine that were removed as part of [trac ticket #12195](#).

```

sage: v = vector(ZZ, [1,2,3])
sage: v.n()
(1.000000000000000, 2.000000000000000, 3.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.000000000000000000000000000000000, 2.000000000000000000000000000000000, 3.000000000000000000000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 75 bits of precision
sage: v = vector(RDF, [1,2,3])

```

(continues on next page)

(continued from previous page)

```

sage: v.n()
(1.000000000000000, 2.000000000000000, 3.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v = vector(CDF, [1,2,3])
sage: v.n()
(1.000000000000000, 2.000000000000000, 3.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Complex Field with 53 bits of precision

sage: v = vector(Integers(8), [1,2,3])
sage: v.n()
(1.000000000000000, 2.000000000000000, 3.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.000000000000000000000000000000000, 2.000000000000000000000000000000000, 3.000000000000000000000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 75 bits of precision

sage: v = vector(QQ, [1,2,3])
sage: v.n()
(1.000000000000000, 2.000000000000000, 3.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.000000000000000000000000000000000, 2.000000000000000000000000000000000, 3.000000000000000000000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 75 bits of precision

```

```

sage: v = vector(GF(2), [1,2,3])
sage: v.n()
(1.000000000000000, 0.000000000000000, 1.000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.000000000000000000000000000000000, 0.000000000000000000000000000000000, 1.000000000000000000000000000000000)
sage: _.parent()
Vector space of dimension 3 over Real Field with 75 bits of precision

```

numpy(dtype='object')
Convert self to a numpy array.

INPUT:

- **dtype** – the **numpy dtype** of the returned array

EXAMPLES:

```

sage: v = vector([1,2,3])
sage: v.numpy()
array([1, 2, 3], dtype=object)
sage: v.numpy() * v.numpy()

```

(continues on next page)

(continued from previous page)

```
array([1, 4, 9], dtype=object)

sage: vector(QQ, [1, 2, 5/6]).numpy()
array([1, 2, 5/6], dtype=object)
```

By default the object `dtype` is used. Alternatively, the desired dtype can be passed in as a parameter:

```
sage: v = vector(QQ, [1, 2, 5/6])
sage: v.numpy()
array([1, 2, 5/6], dtype=object)
sage: v.numpy(dtype=float)
array([1., 2., 0.83333333])
sage: v.numpy(dtype=int)
array([1, 2, 0])
sage: import numpy
sage: v.numpy(dtype=numpy.uint8)
array([1, 2, 0], dtype=uint8)
```

Passing a dtype of `None` will let numpy choose a native type, which can be more efficient but may have unintended consequences:

```
sage: v.numpy(dtype=None)
array([1., 2., 0.83333333])

sage: w = vector(ZZ, [0, 1, 2^63 - 1]); w
(0, 1, 9223372036854775807)
sage: wn = w.numpy(dtype=None); wn
array([0, 1, 9223372036854775807]...)
sage: wn.dtype
dtype('int64')
sage: w.dot_product(w)
85070591730234615847396907784232501250
sage: wn.dot(wn) # overflow
2
```

Numpy can give rather obscure errors; we wrap these to give a bit of context:

```
sage: vector([1, 1/2, QQ['x'].0]).numpy(dtype=float)
Traceback (most recent call last):
...
ValueError: Could not convert vector over Univariate Polynomial Ring in x over
↳ Rational Field to numpy array of type <... 'float'>: setting an array element
↳ with a sequence.
```

outer_product(*right*)

Returns a matrix, the outer product of two vectors `self` and `right`.

INPUT:

- `right` - a vector (or free module element) of any size, whose elements are compatible (with regard to multiplication) with the elements of `self`.

OUTPUT:

The outer product of two vectors x and y (respectively `self` and `right`) can be described several ways. If

we interpret x as a $m \times 1$ matrix and interpret y as a $1 \times n$ matrix, then the outer product is the $m \times n$ matrix from the usual matrix product xy . Notice how this is the “opposite” in some ways from an inner product (which would require $m = n$).

If we just consider vectors, use each entry of x to create a scalar multiples of the vector y and use these vectors as the rows of a matrix. Or use each entry of y to create a scalar multiples of x and use these vectors as the columns of a matrix.

EXAMPLES:

```
sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.outer_product(v)
[ 30  90 300]
[ 20  60 200]
[ 15  45 150]
[ 12  36 120]
sage: M = v.outer_product(u); M
[ 30  20  15  12]
[ 90  60  45  36]
[300 200 150 120]
sage: M.parent()
Full MatrixSpace of 3 by 4 dense matrices over Rational Field
```

The more general `sage.matrix.matrix2.tensor_product()` is an operation on a pair of matrices. If we construct a pair of vectors as a column vector and a row vector, then an outer product and a tensor product are identical. Thus *tensor_pproduct* is a synonym for this method.

```
sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.tensor_product(v) == (u.column()).tensor_product(v.row())
True
```

The result is always a dense matrix, no matter if the two vectors are, or are not, dense.

```
sage: d = vector(ZZ, [4,5], sparse=False)
sage: s = vector(ZZ, [1,2,3], sparse=True)
sage: dd = d.outer_product(d)
sage: ds = d.outer_product(s)
sage: sd = s.outer_product(d)
sage: ss = s.outer_product(s)
sage: all([dd.is_dense(), ds.is_dense(), sd.is_dense(), ss.is_dense()])
True
```

Vectors with no entries do the right thing.

```
sage: v = vector(ZZ, [])
sage: z = v.outer_product(v)
sage: z.parent()
Full MatrixSpace of 0 by 0 dense matrices over Integer Ring
```

There is a fair amount of latitude in the value of the `right` vector, and the matrix that results can have entries from a new ring large enough to contain the result. If you know better, you can sometimes bring the result down to a less general ring.


```

sage: R.<t> = ZZ[]
sage: v = vector(R, [12, 24*t])
sage: w = vector(QQ, [1/2, 1/3, 1/4])
sage: op = v.outer_product(w)
sage: op
[ 6  4  3]
[12*t 8*t 6*t]
sage: op.base_ring()
Univariate Polynomial Ring in t over Rational Field
sage: m = op.change_ring(R); m
[ 6  4  3]
[12*t 8*t 6*t]
sage: m.base_ring()
Univariate Polynomial Ring in t over Integer Ring

```

But some inputs are not compatible, even if vectors.

```

sage: w = vector(GF(5), [1,2])
sage: v = vector(GF(7), [1,2,3,4])
sage: z = w.outer_product(v)
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *: 'Full MatrixSpace of 2 by 1
└─dense matrices over Finite Field of size 5' and 'Full MatrixSpace of 1 by 4
└─dense matrices over Finite Field of size 7'

```

And some inputs don't make any sense at all.

```

sage: w=vector(QQ, [5,10])
sage: z=w.outer_product(6)
Traceback (most recent call last):
...
TypeError: right operand in an outer product must be a vector, not an element
└─of Integer Ring

```

pairwise_product(*right*)

Return the pairwise product of self and right, which is a vector of the products of the corresponding entries.

INPUT:

- *right* - vector of the same degree as self. It need not be in the same vector space as self, as long as the coefficients can be multiplied.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 3)
sage: v = V([1,2,3])
sage: w = V([4,5,6])
sage: v.pairwise_product(w)
(4, 10, 18)
sage: sum(v.pairwise_product(w)) == v.dot_product(w)
True

```

```

sage: W = VectorSpace(GF(3), 3)
sage: w = W([0,1,2])

```

(continues on next page)

(continued from previous page)

```
sage: w.pairwise_product(v)
(0, 2, 0)
sage: w.pairwise_product(v).parent()
Vector space of dimension 3 over Finite Field of size 3
```

Implicit coercion is well defined (regardless of order), so we get 2 even if we do the dot product in the other order.

```
sage: v.pairwise_product(w).parent()
Vector space of dimension 3 over Finite Field of size 3
```

plot(*plot_type=None, start=None, **kws*)

INPUT:

- **plot_type** - (default: 'arrow' if *v* has 3 or fewer components, otherwise 'step') type of plot. Options are:
 - 'arrow' to draw an arrow
 - 'point' to draw a point at the coordinates specified by the vector
 - 'step' to draw a step function representing the coordinates of the vector.

Both 'arrow' and 'point' raise exceptions if the vector has more than 3 dimensions.

- **start** - (default: origin in correct dimension) may be a tuple, list, or vector.

EXAMPLES:

The following both plot the given vector:

```
sage: v = vector(RDF, (1,2))
sage: A = plot(v)
sage: B = v.plot()
sage: A+B # should just show one vector
Graphics object consisting of 2 graphics primitives
```

Examples of the plot types:

```
sage: A = plot(v, plot_type='arrow')
sage: B = plot(v, plot_type='point', color='green', size=20)
sage: C = plot(v, plot_type='step') # calls v.plot_step()
sage: A+B+C
Graphics object consisting of 3 graphics primitives
```

You can use the optional arguments for *plot_step()*:

```
sage: eps = 0.1
sage: plot(v, plot_type='step', eps=eps, xmax=5, hue=0)
Graphics object consisting of 1 graphics primitive
```

Three-dimensional examples:

```
sage: v = vector(RDF, (1,2,1))
sage: plot(v) # defaults to an arrow plot
Graphics3d Object
```

```
sage: plot(v, plot_type='arrow')
Graphics3d Object
```

```
sage: from sage.plot.plot3d.shapes2 import frame3d
sage: plot(v, plot_type='point')+frame3d((0,0,0), v.list())
Graphics3d Object
```

```
sage: plot(v, plot_type='step') # calls v.plot_step()
Graphics object consisting of 1 graphics primitive
```

```
sage: plot(v, plot_type='step', eps=eps, xmax=5, hue=0)
Graphics object consisting of 1 graphics primitive
```

With greater than three coordinates, it defaults to a step plot:

```
sage: v = vector(RDF, (1,2,3,4))
sage: plot(v)
Graphics object consisting of 1 graphics primitive
```

One dimensional vectors are plotted along the horizontal axis of the coordinate plane:

```
sage: plot(vector([1]))
Graphics object consisting of 1 graphics primitive
```

An optional start argument may also be specified by a tuple, list, or vector:

```
sage: u = vector([1,2]); v = vector([2,5])
sage: plot(u, start=v)
Graphics object consisting of 1 graphics primitive
```

plot_step(*xmin=0, xmax=1, eps=None, res=None, connect=True, **kws*)

INPUT:

- **xmin** - (default: 0) start x position to start plotting
- **xmax** - (default: 1) stop x position to stop plotting
- **eps** - (default: determined by xmax) we view this vector as defining a function at the points x_{min} , $x_{min} + \text{eps}$, $x_{min} + 2*\text{eps}$, ...
- **res** - (default: all points) total number of points to include in the graph
- **connect** - (default: True) if True draws a line; otherwise draw a list of points.

EXAMPLES:

```
sage: eps=0.1
sage: v = vector(RDF, [sin(n*eps) for n in range(100)])
sage: v.plot_step(eps=eps, xmax=5, hue=0)
Graphics object consisting of 1 graphics primitive
```

row()

Return a matrix with a single row and the same entries as the vector `self`.

OUTPUT:

A matrix over the same ring as the vector (or free module element), with a single row. The entries of the row are identical to those of the vector, and in the same order.

EXAMPLES:

```
sage: v = vector(ZZ, [1,2,3])
sage: w = v.row(); w
[1 2 3]
sage: w.parent()
Full MatrixSpace of 1 by 3 dense matrices over Integer Ring

sage: x = vector(FiniteField(13), [2,4,8,16])
sage: x.row()
[2 4 8 3]
```

There is more than one way to get one-row matrix from a vector, but the `row` method is more efficient than making a column and then taking a transpose. Notice that supplying a vector to the matrix constructor demonstrates Sage's preference for rows.

```
sage: x = vector(RDF, [sin(i*pi/20) for i in range(10)])
sage: x.row() == matrix(x)
True
sage: x.row() == x.column().transpose()
True
```

Sparse or dense implementations are preserved.

```
sage: d = vector(RR, [1.0, 2.0, 3.0])
sage: s = vector(CDF, {2:5.0+6.0*I})
sage: dm = d.row()
sage: sm = s.row()
sage: all([d.is_dense(), dm.is_dense(), s.is_sparse(), sm.is_sparse()])
True
```

set(*i*, *value*)

Like `__setitem__` but without type or bounds checking: *i* must satisfy $0 \leq i < \text{self.degree}$ and *value* must be an element of the coordinate ring.

EXAMPLES:

```
sage: v = vector(SR, [1/2, 2/5, 0]); v
(1/2, 2/5, 0)
sage: v.set(2, pi); v
(1/2, 2/5, pi)
```

sparse_vector()

Return sparse version of self. If self is sparse, just return self; otherwise, create and return correspond sparse vector.

EXAMPLES:

```
sage: vector([-1,0,3,0,0,0]).sparse_vector().is_sparse()
True
sage: vector([-1,0,3,0,0,0]).sparse_vector().is_sparse()
True
sage: vector([-1,0,3,0,0,0]).sparse_vector()
(-1, 0, 3, 0, 0, 0)
```

subs(*in_dict=None, **kws*)

EXAMPLES:

```
sage: var('a,b,d,e')
(a, b, d, e)
sage: v = vector([a, b, d, e])
sage: v.substitute(a=1)
(1, b, d, e)
sage: v.subs(a=b, b=d)
(b, d, d, e)
```

support()

Return the integers i such that $\text{self}[i] \neq 0$. This is the same as the `nonzero_positions` function.

EXAMPLES:

```
sage: vector([-1,0,3,0,0,0,0.01]).support()
[0, 2, 6]
```

tensor_product(*right*)

Returns a matrix, the outer product of two vectors `self` and `right`.

INPUT:

- `right` - a vector (or free module element) of any size, whose elements are compatible (with regard to multiplication) with the elements of `self`.

OUTPUT:

The outer product of two vectors x and y (respectively `self` and `right`) can be described several ways. If we interpret x as a $m \times 1$ matrix and interpret y as a $1 \times n$ matrix, then the outer product is the $m \times n$ matrix from the usual matrix product xy . Notice how this is the “opposite” in some ways from an inner product (which would require $m = n$).

If we just consider vectors, use each entry of x to create a scalar multiples of the vector y and use these vectors as the rows of a matrix. Or use each entry of y to create a scalar multiples of x and use these vectors as the columns of a matrix.

EXAMPLES:

```
sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.outer_product(v)
[ 30  90 300]
[ 20  60 200]
[ 15  45 150]
[ 12  36 120]
sage: M = v.outer_product(u); M
[ 30  20  15  12]
[ 90  60  45  36]
[300 200 150 120]
sage: M.parent()
Full MatrixSpace of 3 by 4 dense matrices over Rational Field
```

The more general `sage.matrix.matrix2.tensor_product()` is an operation on a pair of matrices. If we construct a pair of vectors as a column vector and a row vector, then an outer product and a tensor product are identical. Thus *tensor_product* is a synonym for this method.

```
sage: u = vector(QQ, [1/2, 1/3, 1/4, 1/5])
sage: v = vector(ZZ, [60, 180, 600])
sage: u.tensor_product(v) == (u.column()).tensor_product(v.row())
True
```

The result is always a dense matrix, no matter if the two vectors are, or are not, dense.

```
sage: d = vector(ZZ, [4, 5], sparse=False)
sage: s = vector(ZZ, [1, 2, 3], sparse=True)
sage: dd = d.outer_product(d)
sage: ds = d.outer_product(s)
sage: sd = s.outer_product(d)
sage: ss = s.outer_product(s)
sage: all([dd.is_dense(), ds.is_dense(), sd.is_dense(), ss.is_dense()])
True
```

Vectors with no entries do the right thing.

```
sage: v = vector(ZZ, [])
sage: z = v.outer_product(v)
sage: z.parent()
Full MatrixSpace of 0 by 0 dense matrices over Integer Ring
```

There is a fair amount of latitude in the value of the `right` vector, and the matrix that results can have entries from a new ring large enough to contain the result. If you know better, you can sometimes bring the result down to a less general ring.

```
sage: R.<t> = ZZ[]
sage: v = vector(R, [12, 24*t])
sage: w = vector(QQ, [1/2, 1/3, 1/4])
sage: op = v.outer_product(w)
sage: op
[ 6 4 3]
[12*t 8*t 6*t]
sage: op.base_ring()
Univariate Polynomial Ring in t over Rational Field
sage: m = op.change_ring(R); m
[ 6 4 3]
[12*t 8*t 6*t]
sage: m.base_ring()
Univariate Polynomial Ring in t over Integer Ring
```

But some inputs are not compatible, even if vectors.

```
sage: w = vector(GF(5), [1, 2])
sage: v = vector(GF(7), [1, 2, 3, 4])
sage: z = w.outer_product(v)
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *: 'Full MatrixSpace of 2 by 1
└─dense matrices over Finite Field of size 5' and 'Full MatrixSpace of 1 by 4
└─dense matrices over Finite Field of size 7'
```

And some inputs don't make any sense at all.

```

sage: w=vector(QQ, [5,10])
sage: z=w.outer_product(6)
Traceback (most recent call last):
...
TypeError: right operand in an outer product must be a vector, not an element_
↳ of Integer Ring

```

class sage.modules.free_module_element.FreeModuleElement_generic_dense

Bases: *sage.modules.free_module_element.FreeModuleElement*

A generic dense element of a free module.

function(*args)

Return a vector over a callable symbolic expression ring.

EXAMPLES:

```

sage: x,y=var('x,y')
sage: v=vector([x,y,x*sin(y)])
sage: w=v.function([x,y]); w
(x, y) |--> (x, y, x*sin(y))
sage: w.coordinate_ring()
Callable function ring with arguments (x, y)
sage: w(1,2)
(1, 2, sin(2))
sage: w(2,1)
(2, 1, 2*sin(1))
sage: w(y=1,x=2)
(2, 1, 2*sin(1))

```

```

sage: x,y=var('x,y')
sage: v=vector([x,y,x*sin(y)])
sage: w=v.function([x]); w
x |--> (x, y, x*sin(y))
sage: w.coordinate_ring()
Callable function ring with argument x
sage: w(4)
(4, y, 4*sin(y))

```

list(copy=True)

Return list of elements of self.

INPUT:

- copy – bool, return list of underlying entries

EXAMPLES:

```

sage: P.<x,y,z> = QQ[]
sage: v = vector([x,y,z])
sage: type(v)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_dense'>
sage: a = v.list(); a
[x, y, z]
sage: a[0] = x*y; v
(x, y, z)

```

(continues on next page)

(continued from previous page)

```
sage: a = v.list(copy=False); a
[x, y, z]
sage: a[0] = x*y; v
(x*y, y, z)
```

class `sage.modules.free_module_element.FreeModuleElement_generic_sparse`

Bases: `sage.modules.free_module_element.FreeModuleElement`

A generic sparse free module element is a dictionary with keys ints i and entries in the base ring.

denominator()

Return the least common multiple of the denominators of the entries of `self`.

EXAMPLES:

```
sage: v = vector([1/2, 2/5, 3/14], sparse=True)
sage: v.denominator()
70
```

dict(`copy=True`)

Return dictionary of nonzero entries of `self`.

More precisely, this returns a dictionary whose keys are indices of basis elements in the support of `self` and whose values are the corresponding coefficients.

INPUT:

- `copy` – (default: `True`) if `self` is internally represented by a dictionary `d`, then make a copy of `d`; if `False`, then this can cause undesired behavior by mutating `d`

OUTPUT:

- Python dictionary

EXAMPLES:

```
sage: v = vector([0, 0, 0, 0, 1/2, 0, 3/14], sparse=True)
sage: v.dict()
{4: 1/2, 6: 3/14}
sage: sorted(v.support())
[4, 6]
```

hamming_weight()

Returns the number of positions i such that `self[i] != 0`.

EXAMPLES:

```
sage: v = vector({1: 1, 3: -2})
sage: w = vector({1: 4, 3: 2})
sage: v+w
(0, 5, 0, 0)
sage: (v+w).hamming_weight()
1
```

items()

Return an iterator over the entries of `self`.

EXAMPLES:


```
sage: v = vector([1,2/3,pi], sparse=True)
sage: next(v.items())
(0, 1)
sage: list(v.items())
[(0, 1), (1, 2/3), (2, pi)]
```

iteritems()

Return an iterator over the entries of `self`.

EXAMPLES:

```
sage: v = vector([1,2/3,pi], sparse=True)
sage: next(v.items())
(0, 1)
sage: list(v.items())
[(0, 1), (1, 2/3), (2, pi)]
```

list(*copy=True*)

Return list of elements of `self`.

INPUT:

- `copy` – ignored for sparse vectors

EXAMPLES:

```
sage: R.<x> = QQ[]
sage: M = FreeModule(R, 3, sparse=True) * (1/x)
sage: v = M([-x^2, 3/x, 0])
sage: type(v)
<class 'sage.modules.free_module_element.FreeModuleElement_generic_sparse'>
sage: a = v.list()
sage: a
[-x^2, 3/x, 0]
sage: [parent(c) for c in a]
[Fraction Field of Univariate Polynomial Ring in x over Rational Field,
 Fraction Field of Univariate Polynomial Ring in x over Rational Field,
 Fraction Field of Univariate Polynomial Ring in x over Rational Field]
```

monomial_coefficients(*copy=True*)

Return dictionary of nonzero entries of `self`.

More precisely, this returns a dictionary whose keys are indices of basis elements in the support of `self` and whose values are the corresponding coefficients.

INPUT:

- `copy` – (default: `True`) if `self` is internally represented by a dictionary `d`, then make a copy of `d`; if `False`, then this can cause undesired behavior by mutating `d`

OUTPUT:

- Python dictionary

EXAMPLES:

```
sage: v = vector([0,0,0,0,1/2,0,3/14], sparse=True)
sage: v.dict()
```

(continues on next page)

(continued from previous page)

```
{4: 1/2, 6: 3/14}
sage: sorted(v.support())
[4, 6]
```

nonzero_positions()

Returns the list of numbers `i` such that `self[i] != 0`.

EXAMPLES:

```
sage: v = vector({1: 1, 3: -2})
sage: w = vector({1: 4, 3: 2})
sage: v+w
(0, 5, 0, 0)
sage: (v+w).nonzero_positions()
[1]
```

```
numerical_approx(prec=None, digits=None, algorithm=None)
```

Return a numerical approximation of `self` with `prec` bits (or decimal digits) of precision, by approximating all entries.

INPUT:

- **prec** – precision in bits
- **digits** – precision in decimal digits (only used if **prec** is not given)
- **algorithm** – which algorithm to use to compute the approximation of the entries (the accepted algorithms depend on the object)

If neither `prec` nor `digits` is given, the default precision is 53 bits (roughly 16 digits).

EXAMPLES:

```
sage: v = vector(RealField(200), [1,2,3], sparse=True)
sage: v.n()
(1.0000000000000000, 2.0000000000000000, 3.0000000000000000)
sage: _.parent()
Sparse vector space of dimension 3 over Real Field with 53 bits of precision
sage: v.n(prec=75)
(1.0000000000000000000000000000000000, 2.0000000000000000000000000000000000, 3.0000000000000000000000000000000000)
sage: _.parent()
Sparse vector space of dimension 3 over Real Field with 75 bits of precision
```

[illegible]

Return a vector or free module element with specified entries.

CALL FORMATS:

This constructor can be called in several different ways. In each case, `sparse=True` or `sparse=False` as well as `immutable=True` or `immutable=False` can be supplied as an option. `free_module_element()` is an alias for `vector()`.

1. `vector(object)`
2. `vector(ring, object)`
3. `vector(object, ring)`
4. `vector(ring, degree, object)`

5. `vector(ring, degree)`

INPUT:

- `object` – a list, dictionary, or other iterable containing the entries of the vector, including any object that is palatable to the Sequence constructor
- `ring` – a base ring (or field) for the vector space or free module, which contains all of the elements
- `degree` – an integer specifying the number of entries in the vector or free module element
- `sparse` – boolean, whether the result should be a sparse vector
- `immutable` – boolean (default: `False`); whether the result should be an immutable vector

In call format 4, an error is raised if the `degree` does not match the length of `object` so this call can provide some safeguards. Note however that using this format when `object` is a dictionary is unlikely to work properly.

OUTPUT:

An element of the ambient vector space or free module with the given base ring and implied or specified dimension or rank, containing the specified entries and with correct degree.

In call format 5, no entries are specified, so the element is populated with all zeros.

If the `sparse` option is not supplied, the output will generally have a dense representation. The exception is if `object` is a dictionary, then the representation will be sparse.

EXAMPLES:

```
sage: v = vector([1,2,3]); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: v = vector([1,2,3/5]); v
(1, 2, 3/5)
sage: v.parent()
Vector space of dimension 3 over Rational Field
```

All entries must *canonically* coerce to some common ring:

```
sage: v = vector([17, GF(11)(5), 19/3]); v
Traceback (most recent call last):
...
TypeError: unable to find a common ring for all elements
```

```
sage: v = vector([17, GF(11)(5), 19]); v
(6, 5, 8)
sage: v.parent()
Vector space of dimension 3 over Finite Field of size 11
sage: v = vector([17, GF(11)(5), 19], QQ); v
(17, 5, 19)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector((1,2,3), QQ); v
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(QQ, (1,2,3)); v
```

(continues on next page)

(continued from previous page)

```
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(vector([1,2,3])); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

You can also use `free_module_element`, which is the same as `vector`.

```
sage: free_module_element([1/3, -4/5])
(1/3, -4/5)
```

We make a vector mod 3 out of a vector over \mathbb{Z} .

```
sage: vector(vector([1,2,3]), GF(3))
(1, 2, 0)
```

The degree of a vector may be specified:

```
sage: vector(QQ, 4, [1,1/2,1/3,1/4])
(1, 1/2, 1/3, 1/4)
```

But it is an error if the degree and size of the list of entries are mismatched:

```
sage: vector(QQ, 5, [1,1/2,1/3,1/4])
Traceback (most recent call last):
...
ValueError: incompatible degrees in vector constructor
```

Providing no entries populates the vector with zeros, but of course, you must specify the degree since it is not implied. Here we use a finite field as the base ring.

```
sage: w = vector(FiniteField(7), 4); w
(0, 0, 0, 0)
sage: w.parent()
Vector space of dimension 4 over Finite Field of size 7
```

The fastest method to construct a zero vector is to call the `zero_vector()` method directly on a free module or vector space, since `vector(...)` must do a small amount of type checking. Almost as fast as the `zero_vector()` method is the `zero_vector()` constructor, which defaults to the integers.

```
sage: vector(ZZ, 5)           # works fine
(0, 0, 0, 0, 0)
sage: (ZZ^5).zero_vector()    # very tiny bit faster
(0, 0, 0, 0, 0)
sage: zero_vector(ZZ, 5)      # similar speed to vector(...)
(0, 0, 0, 0, 0)
sage: z = zero_vector(5); z
(0, 0, 0, 0, 0)
sage: z.parent()
Ambient free module of rank 5 over
the principal ideal domain Integer Ring
```

Here we illustrate the creation of sparse vectors by using a dictionary:

```
sage: vector({1:1.1, 3:3.14})
(0.0000000000000000, 1.1000000000000000, 0.0000000000000000, 3.1400000000000000)
```

With no degree given, a dictionary of entries implicitly declares a degree by the largest index (key) present. So you can provide a terminal element (perhaps a zero?) to set the degree. But it is probably safer to just include a degree in your construction.

```
sage: v = vector(QQ, {0:1/2, 4:-6, 7:0}); v
(1/2, 0, 0, 0, -6, 0, 0, 0)
sage: v.degree()
8
sage: v.is_sparse()
True
sage: w = vector(QQ, 8, {0:1/2, 4:-6})
sage: w == v
True
```

It is an error to specify a negative degree.

```
sage: vector(RR, -4, [1.0, 2.0, 3.0, 4.0])
Traceback (most recent call last):
...
ValueError: cannot specify the degree of a vector as a negative integer (-4)
```

It is an error to create a zero vector but not provide a ring as the first argument.

```
sage: vector('junk', 20)
Traceback (most recent call last):
...
TypeError: first argument must be base ring of zero vector, not junk
```

And it is an error to specify an index in a dictionary that is greater than or equal to a requested degree.

```
sage: vector(ZZ, 10, {3:4, 7:-2, 10:637})
Traceback (most recent call last):
...
ValueError: dictionary of entries has a key (index) exceeding the requested degree
```

A 1-dimensional numpy array of type float or complex may be passed to vector. Unless an explicit ring is given, the result will be a vector in the appropriate dimensional vector space over the real double field or the complex double field. The data in the array must be contiguous, so column-wise slices of numpy matrices will raise an exception.

```
sage: import numpy
sage: x = numpy.random.randn(10)
sage: y = vector(x)
sage: parent(y)
Vector space of dimension 10 over Real Double Field
sage: parent(vector(RDF, x))
Vector space of dimension 10 over Real Double Field
sage: parent(vector(CDF, x))
Vector space of dimension 10 over Complex Double Field
```

(continues on next page)

(continued from previous page)

```
sage: parent(vector(RR, x))
Vector space of dimension 10 over Real Field with 53 bits of precision
sage: v = numpy.random.randn(10) * complex(0,1)
sage: w = vector(v)
sage: parent(w)
Vector space of dimension 10 over Complex Double Field
```

Multi-dimensional arrays are not supported:

```
sage: import numpy as np
sage: a = np.array([[1, 2, 3], [4, 5, 6]], np.float64)
sage: vector(a)
Traceback (most recent call last):
...
TypeError: cannot convert 2-dimensional array to a vector
```

If any of the arguments to `vector` have Python type `int`, `long`, `real`, or `complex`, they will first be coerced to the appropriate Sage objects. This fixes [trac ticket #3847](#).

```
sage: v = vector([int(0)]); v
(0)
sage: v[0].parent()
Integer Ring
sage: v = vector(range(10)); v
(0, 1, 2, 3, 4, 5, 6, 7, 8, 9)
sage: v[3].parent()
Integer Ring
sage: v = vector([float(23.4), int(2), complex(2+7*I), 1]); v
(23.4, 2.0, 2.0 + 7.0*I, 1.0)
sage: v[1].parent()
Complex Double Field
```

If the argument is a vector, it doesn't change the base ring. This fixes [trac ticket #6643](#):

```
sage: K.<sqrt3> = QuadraticField(3)
sage: u = vector(K, (1/2, sqrt3/2) )
sage: vector(u).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3 with sqrt3 = 1.
↪ 732050807568878?
sage: v = vector(K, (0, 1) )
sage: vector(v).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3 with sqrt3 = 1.
↪ 732050807568878?
```

Constructing a vector from a numpy array behaves as expected:

```
sage: import numpy
sage: a=numpy.array([1,2,3])
sage: v=vector(a); v
(1, 2, 3)
sage: parent(v)
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

Complex numbers can be converted naturally to a sequence of length 2. And then to a vector.

```
sage: c = CDF(2 + 3*I)
sage: v = vector(c); v
(2.0, 3.0)
```

A generator, or other iterable, may also be supplied as input. Anything that can be converted to a Sequence is a possible input.

```
sage: type(i^2 for i in range(3))
<... 'generator'>
sage: v = vector(i^2 for i in range(3)); v
(0, 1, 4)
```

An empty list, without a ring given, will default to the integers.

```
sage: x = vector([]); x
()
sage: x.parent()
Ambient free module of rank 0 over the principal ideal domain Integer Ring
```

The `immutable` switch allows to create an immutable vector.

```
sage: v = vector(QQ, {0:1/2, 4:-6, 7:0}, immutable=True); v
(1/2, 0, 0, 0, -6, 0, 0, 0)
sage: v.is_immutable()
True
```

The `immutable` switch works regardless of the type of valid input to the constructor.

```
sage: v = vector(ZZ, 4, immutable=True)
sage: v.is_immutable()
True
sage: w = vector(ZZ, [1,2,3])
sage: v = vector(w, ZZ, immutable=True)
sage: v.is_immutable()
True
sage: v = vector(QQ, w, immutable=True)
sage: v.is_immutable()
True
sage: import numpy as np
sage: w = np.array([1, 2, pi], float)
sage: v = vector(w, immutable=True)
sage: v.is_immutable()
True
sage: w = np.array([i, 2, 3], complex)
sage: v = vector(w, immutable=True)
sage: v.is_immutable()
True
```

`sage.modules.free_module_element.is_FreeModuleElement(x)`

EXAMPLES:

```
sage: sage.modules.free_module_element.is_FreeModuleElement(0)
False
```

(continues on next page)

(continued from previous page)

```
sage: sage.modules.free_module_element.is_FreeModuleElement(vector([1,2,3]))
True
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_dense(parent, entries, degree)`
EXAMPLES:

```
sage: sage.modules.free_module_element.make_FreeModuleElement_generic_dense(QQ^3,
↪ [1,2,-3/7], 3)
(1, 2, -3/7)
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_dense_v1(parent, entries, degree, is_mutable)`

EXAMPLES:

```
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_dense_
↪ v1(QQ^3, [1,2,-3/7], 3, True); v
(1, 2, -3/7)
sage: v[0] = 10; v
(10, 2, -3/7)
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_dense_
↪ v1(QQ^3, [1,2,-3/7], 3, False); v
(1, 2, -3/7)
sage: v[0] = 10
Traceback (most recent call last):
...
ValueError: vector is immutable; please change a copy instead (use copy())
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_sparse(parent, entries, degree)`
EXAMPLES:

```
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_sparse(QQ^
↪ 3, {2:5/2}, 3); v
(0, 0, 5/2)
```

`sage.modules.free_module_element.make_FreeModuleElement_generic_sparse_v1(parent, entries, degree, is_mutable)`

EXAMPLES:

```
sage: v = sage.modules.free_module_element.make_FreeModuleElement_generic_sparse_
↪ v1(QQ^3, {2:5/2}, 3, False); v
(0, 0, 5/2)
sage: v.is_mutable()
False
```

`sage.modules.free_module_element.prepare(v, R, degree=None)`
Converts an object describing elements of a vector into a list of entries in a common ring.

INPUT:

- `v` - a dictionary with non-negative integers as keys, or a list or other object that can be converted by the Sequence constructor
- `R` - a ring containing all the entries, possibly given as `None`
- `degree` - a requested size for the list when the input is a dictionary, otherwise ignored

OUTPUT:

A pair.

The first item is a list of the values specified in the object `v`. If the object is a dictionary, entries are placed in the list according to the indices that were their keys in the dictionary, and the remainder of the entries are zero. The value of `degree` is assumed to be larger than any index provided in the dictionary and will be used as the number of entries in the returned list.

The second item returned is a ring that contains all of the entries in the list. If `R` is given, the entries are coerced in. Otherwise a common ring is found. For more details, see the Sequence object. When `v` has no elements and `R` is `None`, the ring returned is the integers.

EXAMPLES:

```
sage: from sage.modules.free_module_element import prepare
sage: prepare([1,2/3,5],None)
([1, 2/3, 5], Rational Field)

sage: prepare([1,2/3,5],RR)
([1.000000000000000, 0.666666666666667, 5.000000000000000], Real Field with 53 bits
↳ of precision)

sage: prepare({1:4, 3:-2}, ZZ, 6)
([0, 4, 0, -2, 0, 0], Integer Ring)

sage: prepare({3:1, 5:3}, QQ, 6)
([0, 0, 0, 1, 0, 3], Rational Field)

sage: prepare([1,2/3,'10',5],RR)
([1.000000000000000, 0.666666666666667, 10.000000000000000, 5.000000000000000], Real
↳ Field with 53 bits of precision)

sage: prepare({},QQ, 0)
([], Rational Field)

sage: prepare([1,2/3,'10',5],None)
Traceback (most recent call last):
...
TypeError: unable to find a common ring for all elements
```

Some objects can be converted to sequences even if they are not always thought of as sequences.

```
sage: c = CDF(2+3*I)
sage: prepare(c, None)
([2.0, 3.0], Real Double Field)
```

This checks a bug listed at [trac ticket #10595](#). Without good evidence for a ring, the default is the integers.

```
sage: prepare([], None)
([], Integer Ring)
```

`sage.modules.free_module_element.random_vector(ring, degree=None, *args, **kws)`
Returns a vector (or module element) with random entries.

INPUT:

- `ring` – default: `ZZ` - the base ring for the entries

- degree – a non-negative integer for the number of entries in the vector
- sparse – default: False - whether to use a sparse implementation
- args, kwds - additional arguments and keywords are passed to the `random_element()` method of the ring

OUTPUT:

A vector, or free module element, with degree elements from ring, chosen randomly from the ring according to the ring's `random_element()` method.

Note: See below for examples of how random elements are generated by some common base rings.

EXAMPLES:

First, module elements over the integers. The default distribution is tightly clustered around -1, 0, 1. Uniform distributions can be specified by giving bounds, though the upper bound is never met. See `sage.rings.integer_ring.IntegerRing_class.random_element()` for several other variants.

```
sage: random_vector(10).parent()
Ambient free module of rank 10 over the principal ideal domain Integer Ring
sage: random_vector(20).parent()
Ambient free module of rank 20 over the principal ideal domain Integer Ring

sage: v = random_vector(ZZ, 20, x=4)
sage: all(i in range(4) for i in v)
True

sage: v = random_vector(ZZ, 20, x=-20, y=100)
sage: all(i in range(-20, 100) for i in v)
True
```

If the ring is not specified, the default is the integers, and parameters for the random distribution may be passed without using keywords. This is a random vector with 20 entries uniformly distributed between -20 and 100.

```
sage: random_vector(20, -20, 100).parent()
Ambient free module of rank 20 over the principal ideal domain Integer Ring
```

Now over the rationals. Note that bounds on the numerator and denominator may be specified. See `sage.rings.rational_field.RationalField.random_element()` for documentation.

```
sage: random_vector(QQ, 10).parent()
Vector space of dimension 10 over Rational Field

sage: v = random_vector(QQ, 10, num_bound=15, den_bound=5)
sage: v.parent()
Vector space of dimension 10 over Rational Field
sage: all(q.numerator() <= 15 and q.denominator() <= 5 for q in v)
True
```

Inexact rings may be used as well. The reals have uniform distributions, with the range $(-1, 1)$ as the default. More at: `sage.rings.real_mpfr.RealField_class.random_element()`

```
sage: v = random_vector(RR, 5)
sage: v.parent()
```

(continues on next page)

(continued from previous page)

```

Vector space of dimension 5 over Real Field with 53 bits of precision
sage: all(-1 <= r <= 1 for r in v)
True

sage: v = random_vector(RR, 5, min=8, max=14)
sage: v.parent()
Vector space of dimension 5 over Real Field with 53 bits of precision
sage: all(8 <= r <= 14 for r in v)
True

```

Any ring with a `random_element()` method may be used.

```

sage: F = FiniteField(23)
sage: hasattr(F, 'random_element')
True
sage: v = random_vector(F, 10)
sage: v.parent()
Vector space of dimension 10 over Finite Field of size 23

```

The default implementation is a dense representation, equivalent to setting `sparse=False`.

```

sage: v = random_vector(10)
sage: v.is_sparse()
False

sage: w = random_vector(ZZ, 20, sparse=True)
sage: w.is_sparse()
True

```

The elements are chosen using the ring's `random_element` method:

```

sage: from sage.misc.randstate import current_randstate
sage: seed = current_randstate().seed()
sage: set_random_seed(seed)
sage: v1 = random_vector(ZZ, 20, distribution="1/n")
sage: v2 = random_vector(ZZ, 15, x=-1000, y=1000)
sage: v3 = random_vector(QQ, 10)
sage: v4 = random_vector(FiniteField(17), 10)
sage: v5 = random_vector(RR, 10)
sage: set_random_seed(seed)
sage: w1 = vector(ZZ.random_element(distribution="1/n") for _ in range(20))
sage: w2 = vector(ZZ.random_element(x=-1000, y=1000) for _ in range(15))
sage: w3 = vector(QQ.random_element() for _ in range(10))
sage: w4 = vector(FiniteField(17).random_element() for _ in range(10))
sage: w5 = vector(RR.random_element() for _ in range(10))
sage: [v1, v2, v3, v4, v5] == [w1, w2, w3, w4, w5]
True

```

Inputs get checked before constructing the vector.

```

sage: random_vector('junk')
Traceback (most recent call last):
...

```

(continues on next page)

(continued from previous page)

```

TypeError: degree of a random vector must be an integer, not None

sage: random_vector('stuff', 5)
Traceback (most recent call last):
...
TypeError: elements of a vector, or module element, must come from a ring, not stuff

sage: random_vector(ZZ, -9)
Traceback (most recent call last):
...
ValueError: degree of a random vector must be non-negative, not -9

```

`sage.modules.free_module_element.vector`(*arg0*, *arg1=None*, *arg2=None*, *sparse=None*, *immutable=False*)
 Return a vector or free module element with specified entries.

CALL FORMATS:

This constructor can be called in several different ways. In each case, `sparse=True` or `sparse=False` as well as `immutable=True` or `immutable=False` can be supplied as an option. `free_module_element()` is an alias for `vector()`.

1. `vector(object)`
2. `vector(ring, object)`
3. `vector(object, ring)`
4. `vector(ring, degree, object)`
5. `vector(ring, degree)`

INPUT:

- `object` – a list, dictionary, or other iterable containing the entries of the vector, including any object that is palatable to the Sequence constructor
- `ring` – a base ring (or field) for the vector space or free module, which contains all of the elements
- `degree` – an integer specifying the number of entries in the vector or free module element
- `sparse` – boolean, whether the result should be a sparse vector
- `immutable` – boolean (default: `False`); whether the result should be an immutable vector

In call format 4, an error is raised if the `degree` does not match the length of `object` so this call can provide some safeguards. Note however that using this format when `object` is a dictionary is unlikely to work properly.

OUTPUT:

An element of the ambient vector space or free module with the given base ring and implied or specified dimension or rank, containing the specified entries and with correct degree.

In call format 5, no entries are specified, so the element is populated with all zeros.

If the `sparse` option is not supplied, the output will generally have a dense representation. The exception is if `object` is a dictionary, then the representation will be sparse.

EXAMPLES:

```

sage: v = vector([1,2,3]); v
(1, 2, 3)
sage: v.parent()

```

(continues on next page)

(continued from previous page)

```
Ambient free module of rank 3 over the principal ideal domain Integer Ring
sage: v = vector([1,2,3/5]); v
(1, 2, 3/5)
sage: v.parent()
Vector space of dimension 3 over Rational Field
```

All entries must *canonically* coerce to some common ring:

```
sage: v = vector([17, GF(11)(5), 19/3]); v
Traceback (most recent call last):
...
TypeError: unable to find a common ring for all elements
```

```
sage: v = vector([17, GF(11)(5), 19]); v
(6, 5, 8)
sage: v.parent()
Vector space of dimension 3 over Finite Field of size 11
sage: v = vector([17, GF(11)(5), 19], QQ); v
(17, 5, 19)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector((1,2,3), QQ); v
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(QQ, (1,2,3)); v
(1, 2, 3)
sage: v.parent()
Vector space of dimension 3 over Rational Field
sage: v = vector(vector([1,2,3])); v
(1, 2, 3)
sage: v.parent()
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

You can also use `free_module_element`, which is the same as `vector`.

```
sage: free_module_element([1/3, -4/5])
(1/3, -4/5)
```

We make a vector mod 3 out of a vector over \mathbf{Z} .

```
sage: vector(vector([1,2,3]), GF(3))
(1, 2, 0)
```

The degree of a vector may be specified:

```
sage: vector(QQ, 4, [1,1/2,1/3,1/4])
(1, 1/2, 1/3, 1/4)
```

But it is an error if the degree and size of the list of entries are mismatched:

```
sage: vector(QQ, 5, [1,1/2,1/3,1/4])
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: incompatible degrees in vector constructor
```

Providing no entries populates the vector with zeros, but of course, you must specify the degree since it is not implied. Here we use a finite field as the base ring.

```
sage: w = vector(FiniteField(7), 4); w
(0, 0, 0, 0)
sage: w.parent()
Vector space of dimension 4 over Finite Field of size 7
```

The fastest method to construct a zero vector is to call the `zero_vector()` method directly on a free module or vector space, since `vector(...)` must do a small amount of type checking. Almost as fast as the `zero_vector()` method is the `zero_vector()` constructor, which defaults to the integers.

```
sage: vector(ZZ, 5)           # works fine
(0, 0, 0, 0, 0)
sage: (ZZ^5).zero_vector()    # very tiny bit faster
(0, 0, 0, 0, 0)
sage: zero_vector(ZZ, 5)      # similar speed to vector(...)
(0, 0, 0, 0, 0)
sage: z = zero_vector(5); z
(0, 0, 0, 0, 0)
sage: z.parent()
Ambient free module of rank 5 over
the principal ideal domain Integer Ring
```

Here we illustrate the creation of sparse vectors by using a dictionary:

```
sage: vector({1:1.1, 3:3.14})
(0.0000000000000000, 1.1000000000000000, 0.0000000000000000, 3.1400000000000000)
```

With no degree given, a dictionary of entries implicitly declares a degree by the largest index (key) present. So you can provide a terminal element (perhaps a zero?) to set the degree. But it is probably safer to just include a degree in your construction.

```
sage: v = vector(QQ, {0:1/2, 4:-6, 7:0}); v
(1/2, 0, 0, 0, -6, 0, 0, 0)
sage: v.degree()
8
sage: v.is_sparse()
True
sage: w = vector(QQ, 8, {0:1/2, 4:-6})
sage: w == v
True
```

It is an error to specify a negative degree.

```
sage: vector(RR, -4, [1.0, 2.0, 3.0, 4.0])
Traceback (most recent call last):
...
ValueError: cannot specify the degree of a vector as a negative integer (-4)
```

It is an error to create a zero vector but not provide a ring as the first argument.

```
sage: vector('junk', 20)
Traceback (most recent call last):
...
TypeError: first argument must be base ring of zero vector, not junk
```

And it is an error to specify an index in a dictionary that is greater than or equal to a requested degree.

```
sage: vector(ZZ, 10, {3:4, 7:-2, 10:637})
Traceback (most recent call last):
...
ValueError: dictionary of entries has a key (index) exceeding the requested degree
```

A 1-dimensional numpy array of type float or complex may be passed to vector. Unless an explicit ring is given, the result will be a vector in the appropriate dimensional vector space over the real double field or the complex double field. The data in the array must be contiguous, so column-wise slices of numpy matrices will raise an exception.

```
sage: import numpy
sage: x = numpy.random.randn(10)
sage: y = vector(x)
sage: parent(y)
Vector space of dimension 10 over Real Double Field
sage: parent(vector(RDF, x))
Vector space of dimension 10 over Real Double Field
sage: parent(vector(CDF, x))
Vector space of dimension 10 over Complex Double Field
sage: parent(vector(RR, x))
Vector space of dimension 10 over Real Field with 53 bits of precision
sage: v = numpy.random.randn(10) * complex(0,1)
sage: w = vector(v)
sage: parent(w)
Vector space of dimension 10 over Complex Double Field
```

Multi-dimensional arrays are not supported:

```
sage: import numpy as np
sage: a = np.array([[1, 2, 3], [4, 5, 6]], np.float64)
sage: vector(a)
Traceback (most recent call last):
...
TypeError: cannot convert 2-dimensional array to a vector
```

If any of the arguments to vector have Python type int, long, real, or complex, they will first be coerced to the appropriate Sage objects. This fixes [trac ticket #3847](#).

```
sage: v = vector([int(0)]); v
(0)
sage: v[0].parent()
Integer Ring
sage: v = vector(range(10)); v
(0, 1, 2, 3, 4, 5, 6, 7, 8, 9)
sage: v[3].parent()
Integer Ring
```

(continues on next page)

(continued from previous page)

```
sage: v = vector([float(23.4), int(2), complex(2+7*I), 1]); v
(23.4, 2.0, 2.0 + 7.0*I, 1.0)
sage: v[1].parent()
Complex Double Field
```

If the argument is a vector, it doesn't change the base ring. This fixes [trac ticket #6643](#):

```
sage: K.<sqrt3> = QuadraticField(3)
sage: u = vector(K, (1/2, sqrt3/2) )
sage: vector(u).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3 with sqrt3 = 1.
↪ 732050807568878?
sage: v = vector(K, (0, 1) )
sage: vector(v).base_ring()
Number Field in sqrt3 with defining polynomial x^2 - 3 with sqrt3 = 1.
↪ 732050807568878?
```

Constructing a vector from a numpy array behaves as expected:

```
sage: import numpy
sage: a=numpy.array([1,2,3])
sage: v=vector(a); v
(1, 2, 3)
sage: parent(v)
Ambient free module of rank 3 over the principal ideal domain Integer Ring
```

Complex numbers can be converted naturally to a sequence of length 2. And then to a vector.

```
sage: c = CDF(2 + 3*I)
sage: v = vector(c); v
(2.0, 3.0)
```

A generator, or other iterable, may also be supplied as input. Anything that can be converted to a Sequence is a possible input.

```
sage: type(i^2 for i in range(3))
<... 'generator'>
sage: v = vector(i^2 for i in range(3)); v
(0, 1, 4)
```

An empty list, without a ring given, will default to the integers.

```
sage: x = vector([]); x
()
sage: x.parent()
Ambient free module of rank 0 over the principal ideal domain Integer Ring
```

The `immutable` switch allows to create an immutable vector.

```
sage: v = vector(QQ, {0:1/2, 4:-6, 7:0}, immutable=True); v
(1/2, 0, 0, 0, -6, 0, 0, 0)
sage: v.is_immutable()
True
```


The `immutable` switch works regardless of the type of valid input to the constructor.

```
sage: v = vector(ZZ, 4, immutable=True)
sage: v.is_immutable()
True
sage: w = vector(ZZ, [1,2,3])
sage: v = vector(w, ZZ, immutable=True)
sage: v.is_immutable()
True
sage: v = vector(QQ, w, immutable=True)
sage: v.is_immutable()
True
sage: import numpy as np
sage: w = np.array([1, 2, pi], float)
sage: v = vector(w, immutable=True)
sage: v.is_immutable()
True
sage: w = np.array([i, 2, 3], complex)
sage: v = vector(w, immutable=True)
sage: v.is_immutable()
True
```

`sage.modules.free_module_element.zero_vector(arg0, arg1=None)`
Returns a vector or free module element with a specified number of zeros.

CALL FORMATS:

1. `zero_vector(degree)`
2. `zero_vector(ring, degree)`

INPUT:

- `degree` - the number of zero entries in the vector or free module element
- `ring` - default `ZZ` - the base ring of the vector space or module containing the constructed zero vector

OUTPUT:

A vector or free module element with `degree` entries, all equal to zero and belonging to the ring if specified. If no ring is given, a free module element over `ZZ` is returned.

EXAMPLES:

A zero vector over the field of rationals.

```
sage: v = zero_vector(QQ, 5); v
(0, 0, 0, 0, 0)
sage: v.parent()
Vector space of dimension 5 over Rational Field
```

A free module zero element.

```
sage: w = zero_vector(Integers(6), 3); w
(0, 0, 0)
sage: w.parent()
Ambient free module of rank 3 over Ring of integers modulo 6
```

If no ring is given, the integers are used.

```
sage: u = zero_vector(9); u
(0, 0, 0, 0, 0, 0, 0, 0, 0)
sage: u.parent()
Ambient free module of rank 9 over the principal ideal domain Integer Ring
```

Non-integer degrees produce an error.

```
sage: zero_vector(5.6)
Traceback (most recent call last):
...
TypeError: Attempt to coerce non-integral RealNumber to Integer
```

Negative degrees also give an error.

```
sage: zero_vector(-3)
Traceback (most recent call last):
...
ValueError: rank (=-3) must be nonnegative
```

Garbage instead of a ring will be recognized as such.

```
sage: zero_vector(x^2, 5)
Traceback (most recent call last):
...
TypeError: first argument must be a ring
```

2.4 Submodules and subquotients of free modules

Free modules and submodules of a free module (of finite rank) over a principal ideal domain have well-defined notion of rank, and they are implemented in `sage.modules.free_module`. Here submodules with no rank are implemented. For example, submodules of free modules over multivariate polynomial rings with more than one variables have no notion of rank.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N
Submodule of Ambient free module of rank 2 over the integral domain Multivariate_
Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y      z]
[ y*z     x*z]
```

AUTHORS:

- Kwankyu Lee (2022-05): initial version

```
class sage.modules.submodule.Submodule_free_ambient(ambient, gens, check=True,
                                                    already_echelonized=False)
```

Bases: `sage.modules.free_module.Module_free_ambient`

Base class of submodules of ambient modules.

The ambient module is either a free module or a quotient of a free module by a submodule.

Note that if the ambient module is a quotient module, submodules of the quotient module are called subquotients.

INPUT:

- `ambient` – an ambient module
- `gens` – vectors of the ambient free module generating this submodule
- `check` – boolean; if `True`, vectors in `gens` are checked whether they belong to the ambient free module
- `already_echelonized` – ignored; for compatibility with other submodules

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N
Submodule of Ambient free module of rank 2 over the integral domain
Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y      z]
[ y*z      x*z]
```

```
sage: M.coerce_map_from(N)
Coercion map:
  From: Submodule of Ambient free module of rank 2 over the integral domain
  Multivariate Polynomial Ring in x, y, z over Rational Field
  Generated by the rows of the matrix:
  [x - y      z]
  [ y*z      x*z]
  To:   Ambient free module of rank 2 over the integral domain
  Multivariate Polynomial Ring in x, y, z over Rational Field
```

`ambient_module()`

Return the ambient module of `self`.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N.ambient_module() is M
True
sage: N.zero_submodule().ambient_module() is M
True
sage: Q = M / N
sage: Q.zero_submodule().ambient_module() is Q
True
```

`gen(i=0)`

Return the i -th generator of this module.

EXAMPLES:

```

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: N.gen(0)
(x - y, z)

```

generators_matrix()

Return the matrix defining self.

EXAMPLES:

```

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: N.matrix()
[x - y      z]
[ y*z     x*z]

```

gens()

Return the generators of this submodule.

EXAMPLES:

```

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N.gens()
[
(x - y, z),
(y*z, x*z)
]

```

matrix()

Return the matrix defining self.

EXAMPLES:

```

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: N.matrix()
[x - y      z]
[ y*z     x*z]

```

relations()

Return the relations module of the ambient module.

If the ambient module is free, then the relations module is trivial.

EXAMPLES:

```

sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y * z, x * z])])
sage: N.relations() == M.zero_submodule()
True

```

(continues on next page)

(continued from previous page)

```
sage: Q = M.quotient(N)
sage: Q.zero_submodule().relations() == N
True
```

2.5 Quotients of free modules

AUTHORS:

- William Stein (2009): initial version
- Kwankyu Lee (2022-05): added quotient module over domain

```
class sage.modules.quotient_module.FreeModule_ambient_field_quotient(domain, sub,
                                                                    quotient_matrix,
                                                                    lift_matrix, inner_product_matrix=None)
```

Bases: `sage.modules.free_module.FreeModule_ambient_field`

A quotient V/W of two vector spaces as a vector space.

To obtain V or W use `self.V()` and `self.W()`.

EXAMPLES:

```
sage: k.<i> = QuadraticField(-1)
sage: A = k^3; V = A.span([[1,0,i], [2,i,0]])
sage: W = A.span([[3,i,i]])
sage: U = V/W; U
Vector space quotient V/W of dimension 1 over Number Field in i with defining
↳ polynomial x^2 + 1 with i = 1*I where
V: Vector space of degree 3 and dimension 2 over Number Field in i with defining
↳ polynomial x^2 + 1 with i = 1*I
Basis matrix:
[ 1  0  i]
[ 0  1 -2]
W: Vector space of degree 3 and dimension 1 over Number Field in i with defining
↳ polynomial x^2 + 1 with i = 1*I
Basis matrix:
[ 1 1/3*i 1/3*i]
sage: U.V()
Vector space of degree 3 and dimension 2 over Number Field in i with defining
↳ polynomial x^2 + 1 with i = 1*I
Basis matrix:
[ 1  0  i]
[ 0  1 -2]
sage: U.W()
Vector space of degree 3 and dimension 1 over Number Field in i with defining
↳ polynomial x^2 + 1 with i = 1*I
Basis matrix:
[ 1 1/3*i 1/3*i]
sage: U.quotient_map()
Vector space morphism represented by the matrix:
```

(continues on next page)

(continued from previous page)

```
[ 1]
[3*i]
Domain: Vector space of degree 3 and dimension 2 over Number Field in i with
↳defining polynomial  $x^2 + 1$  with  $i = 1*I$ 
Basis matrix:
[ 1 0 i]
[ 0 1 -2]
Codomain: Vector space quotient  $V/W$  of dimension 1 over Number Field in i with
↳defining polynomial  $x^2 + 1$  with  $i = 1*I$  where
V: Vector space of degree 3 and dimension 2 over Number Field in i with defining
↳polynomial  $x^2 + 1$  with  $i = 1*I$ 
Basis matrix:
[ 1 0 i]
[ 0 1 -2]
W: Vector space of degree 3 and dimension 1 over Number Field in i with defining
↳polynomial  $x^2 + 1$  with  $i = 1*I$ 
Basis matrix:
[ 1 1/3*i 1/3*i]
sage: Z = V.quotient(W)
sage: Z == U
True
```

We create three quotient spaces and compare them:

```
sage: A = QQ^2
sage: V = A.span_of_basis([[1,0], [1,1]])
sage: W0 = V.span([V.1, V.0])
sage: W1 = V.span([V.1])
sage: W2 = V.span([V.1])
sage: Q0 = V/W0
sage: Q1 = V/W1
sage: Q2 = V/W2

sage: Q0 == Q1
False
sage: Q1 == Q2
True
```

V()

Given this quotient space $Q = V/W$, return V .

EXAMPLES:

```
sage: M = QQ^10 / [list(range(10)), list(range(2,12))]
sage: M.cover()
Vector space of dimension 10 over Rational Field
```

W()

Given this quotient space $Q = V/W$, return W .

EXAMPLES:

```
sage: M = QQ^10 / [list(range(10)), list(range(2,12))]
sage: M.relations()
```

(continues on next page)

(continued from previous page)

```

Vector space of degree 10 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1 -2 -3 -4 -5 -6 -7 -8]
[ 0  1  2  3  4  5  6  7  8  9]

```

cover()

Given this quotient space $Q = V/W$, return V .

EXAMPLES:

```

sage: M = QQ^10 / [list(range(10)), list(range(2,12))]
sage: M.cover()
Vector space of dimension 10 over Rational Field

```

lift(x)

Lift element of this quotient V/W to V by applying the fixed lift homomorphism.

The lift is a fixed homomorphism.

EXAMPLES:

```

sage: M = QQ^3 / [[1,2,3]]
sage: M.lift(M.0)
(1, 0, 0)
sage: M.lift(M.1)
(0, 1, 0)
sage: M.lift(M.0 - 2*M.1)
(1, -2, 0)

```

lift_map()

Given this quotient space $Q = V/W$, return a fixed choice of linear homomorphism (a section) from Q to V .

EXAMPLES:

```

sage: M = QQ^3 / [[1,2,3]]
sage: M.lift_map()
Vector space morphism represented by the matrix:
[1 0 0]
[0 1 0]
Domain: Vector space quotient V/W of dimension 2 over Rational Field where
V: Vector space of dimension 3 over Rational Field
W: Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]
Codomain: Vector space of dimension 3 over Rational Field

```

quotient_map()

Given this quotient space $Q = V/W$, return the natural quotient map from V to Q .

EXAMPLES:

```

sage: M = QQ^3 / [[1,2,3]]
sage: M.quotient_map()
Vector space morphism represented by the matrix:

```

(continues on next page)

(continued from previous page)

```
[ 1  0]
[ 0  1]
[-1/3 -2/3]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space quotient V/W of dimension 2 over Rational Field where
V: Vector space of dimension 3 over Rational Field
W: Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 2 3]

sage: M.quotient_map()( (QQ^3)([1,2,3]) )
(0, 0)
```

relations()

Given this quotient space $Q = V/W$, return W .

EXAMPLES:

```
sage: M = QQ^10 / [list(range(10)), list(range(2,12))]
sage: M.relations()
Vector space of degree 10 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1 -2 -3 -4 -5 -6 -7 -8]
[ 0  1  2  3  4  5  6  7  8  9]
```

class sage.modules.quotient_module.QuotientModule_free_ambient(module, sub)

Bases: [sage.modules.free_module.Module_free_ambient](#)

Quotients of ambient free modules by a submodule.

INPUT:

- module – an ambient free module
- sub – a submodule of module

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: M.quotient_module(N)
Quotient module by Submodule of Ambient free module of rank 2 over
the integral domain Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[x - y    z]
[ y*z    x*z]
```

V()

Given this quotient space $Q = V/W$, return V .

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
```

(continues on next page)

(continued from previous page)

```
sage: Q = M.quotient_module(N)
sage: Q.cover() is M
True
```

W()

Given this quotient space $Q = V/W$, return W

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
sage: Q.relations() is N
True
```

ambient_module()

Return self, since self is ambient.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
sage: Q.ambient_module() is Q
True
```

cover()

Given this quotient space $Q = V/W$, return V .

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
sage: Q.cover() is M
True
```

free_cover()

Given this quotient space $Q = V/W$, return the free module that covers V .

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M / N
sage: NQ = Q.submodule([Q([1,x])])
sage: QNQ = Q / NQ
sage: QNQ.free_cover() is Q.free_cover() is M
True
```

Note that this is different than the immediate cover:

```
sage: QNQ.cover() is Q
True
sage: QNQ.cover() is QNQ.free_cover()
False
```

free_relations()

Given this quotient space $Q = V/W$, return the submodule that generates all relations of Q .

When V is a free module, then this returns W . Otherwise this returns the union of W lifted to the cover of V and the relations of V (repeated until W is a submodule of a free module).

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M / N
sage: NQ = Q.submodule([Q([1, x])])
sage: QNQ = Q / NQ
sage: QNQ.free_relations()
Submodule of Ambient free module of rank 2 over the integral domain.
↳ Multivariate Polynomial Ring in x, y, z over Rational Field
Generated by the rows of the matrix:
[ 1      x]
[x - y   z]
[ y*z   x*z]
```

Note that this is different than the defining relations:

```
sage: QNQ.relations() is NQ
True
sage: QNQ.relations() == QNQ.free_relations()
False
```

gen($i=0$)

Return the i -th generator of this module.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
sage: Q.gen(0)
(1, 0)
```

gens()

Return the generators of this module.

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
```

(continues on next page)

(continued from previous page)

```
sage: Q.gens()
((1, 0), (0, 1))
```

relations()

Given this quotient space $Q = V/W$, return W

EXAMPLES:

```
sage: S.<x,y,z> = PolynomialRing(QQ)
sage: M = S**2
sage: N = M.submodule([vector([x - y, z]), vector([y*z, x*z])])
sage: Q = M.quotient_module(N)
sage: Q.relations() is N
True
```

See also `sage.tensor.modules.finite_rank_free_module`.

MODULES WITH BASIS

3.1 Concrete classes related to modules with a distinguished basis

This module provides concrete classes for various constructions related to modules with a distinguished basis:

- `morphism` – Concrete classes for morphisms of modules with basis

See also:

The category `ModulesWithBasis`

3.2 Cell modules

class `sage.modules.with_basis.cell_module.CellModule(A, mu, **kws)`

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

A cell module.

Let R be a commutative ring. Let A be a cellular R -algebra with cell datum (Λ, i, M, C) . A *cell module* $W(\lambda)$ is the R -module given by $R\{C_s \mid s \in M(\lambda)\}$ with an action of $a \in A$ given by $aC_s = \sum_{u \in M(\lambda)} r_a(u, s)C_u$, where $r_a(u, s)$ is the same as those given by the cellular condition:

$$aC_{st}^\lambda = \sum_{u \in M(\lambda)} r_a(u, s)C_{ut}^\lambda + \sum_{\substack{\mu < \lambda \\ x, y \in M(\mu)}} RC_{xy}^\mu.$$

INPUT:

- A – a cellular algebra
- μ – an element of the cellular poset of A

See also:

`CellularBasis`

AUTHORS:

- Travis Scrimshaw (2015-11-5): Initial version

REFERENCES:

- [GrLe1996]
- [KX1998]
- [Mat1999]

- [Wikipedia article Cellular_algebra](#)
- <http://webusers.imj-prg.fr/~bernhard.keller/ictp2006/lecturenotes/xi.pdf>

class Element

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

bilinear_form(*x*, *y*)

Return the bilinear form on *x* and *y*.

The cell module $W(\lambda)$ has a canonical bilinear form $\Phi_\lambda : W(\lambda) \times W(\lambda) \rightarrow W(\lambda)$ given by

$$C_{ss}^\lambda C_{tt}^\lambda = \Phi_\lambda(C_s, C_t) C_{st}^\lambda + \sum_{\substack{\mu < \lambda \\ x, y \in M(\mu)}} RC_{xy}^\mu.$$

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
sage: elt = W.an_element(); elt
2*W[[1, 2], [3]] + 2*W[[1, 3], [2]]
sage: W.bilinear_form(elt, elt)
8
```

bilinear_form_matrix(*ordering=None*)

Return the matrix corresponding to the bilinear form of *self*.

INPUT:

- *ordering* – (optional) an ordering of the indices

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
sage: W.bilinear_form_matrix()
[1 0]
[0 1]
```

cellular_algebra()

Return the cellular algebra of *self*.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
sage: W.cellular_algebra() is S.cellular_basis()
True
sage: S.has_coerce_map_from(W.cellular_algebra())
True
```

nonzero_bilinear_form()

Return True if the bilinear form of *self* is non-zero.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
```

(continues on next page)

(continued from previous page)

```
sage: W.nonzero_bilinear_form()
True
```

radical()

Return the radical of `self`.

Let $W(\lambda)$ denote a cell module. The *radical* of $W(\lambda)$ is defined as

$$\text{rad}(\lambda) := \{x \in W(\lambda) \mid \Phi_\lambda(x, y)\},$$

and note that it is a submodule of $W(\lambda)$.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
sage: R = W.radical(); R
Radical of Cell module indexed by [2, 1] of Cellular basis of
Symmetric group algebra of order 3 over Rational Field
sage: R.basis()
Finite family {}
```

radical_basis()

Return a basis of the radical of `self`.

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
sage: W.radical_basis()
()
```

simple_module()

Return the corresponding simple module of `self`.

Let $W(\lambda)$ denote a cell module. The simple module $L(\lambda)$ is defined as $W(\lambda)/\text{rad}(\lambda)$, where $\text{rad}(\lambda)$ is the radical of the bilinear form Φ_λ .

See also:

[*radical\(\)*](#)

EXAMPLES:

```
sage: S = SymmetricGroupAlgebra(QQ, 3)
sage: W = S.cell_module([2,1])
sage: L = W.simple_module(); L
Simple module indexed by [2, 1] of Cellular basis of
Symmetric group algebra of order 3 over Rational Field
sage: L.has_coerce_map_from(W)
True
```

class `sage.modules.with_basis.cell_module.SimpleModule(submodule)`

Bases: `sage.modules.with_basis.subquotient.QuotientModuleWithBasis`

A simple module of a cellular algebra.

Let $W(\lambda)$ denote a cell module. The simple module $L(\lambda)$ is defined as $W(\lambda)/\text{rad}(\lambda)$, where $\text{rad}(\lambda)$ is the radical of the bilinear form Φ_λ .

```
class Element
```

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

3.3 An element in an indexed free module

AUTHORS:

- Travis Scrimshaw (03-2017): Moved code from `sage.combinat.free_module`.
- Travis Scrimshaw (29-08-2022): Implemented copy as the identity map.

```
class sage.modules.with_basis.indexed_element.IndexedFreeModuleElement
```

Bases: `sage.structure.element.ModuleElement`

Create a combinatorial module element. This should never be called directly, but only through the parent combinatorial free module's `__call__()` method.

```
monomial_coefficients(copy=True)
```

Return the internal dictionary which has the combinatorial objects indexing the basis as keys and their corresponding coefficients as values.

INPUT:

- `copy` – (default: `True`) if `self` is internally represented by a dictionary `d`, then make a copy of `d`; if `False`, then this can cause undesired behavior by mutating `d`

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a','b','c'])
sage: B = F.basis()
sage: f = B['a'] + 3*B['c']
sage: d = f.monomial_coefficients()
sage: d['a']
1
sage: d['c']
3
```

To run through the monomials of an element, it is better to use the idiom:

```
sage: for (t,c) in f:
....:     print("{} {}".format(t,c))
a 1
c 3
```

```
sage: s = SymmetricFunctions(QQ).schur()
sage: a = s([2,1])+2*s([3,2])
sage: d = a.monomial_coefficients()
sage: type(d)
<... 'dict'>
sage: d[ Partition([2,1]) ]
1
sage: d[ Partition([3,2]) ]
2
```

```
to_vector(new_base_ring=None, order=None, sparse=False)
```

Return `self` as a vector.

INPUT:

- `new_base_ring` – a ring (default: `None`)
- `order` – (optional) an ordering of the support of `self`
- `sparse` – (default: `False`) whether to return a sparse vector or a dense vector

OUTPUT: a `FreeModule()` vector

Warning: This will crash/run forever if `self` is infinite dimensional!

See also:

- `vector()`
- `CombinatorialFreeModule.get_order()`
- `CombinatorialFreeModule.from_vector()`
- `CombinatorialFreeModule._dense_free_module()`

EXAMPLES:

```
sage: F = CombinatorialFreeModule(QQ, ['a', 'b', 'c'])
sage: B = F.basis()
sage: f = B['a'] - 3*B['c']
sage: f._vector_()
(1, 0, -3)
```

One can use equivalently:

```
sage: f.to_vector()
(1, 0, -3)
sage: vector(f)
(1, 0, -3)
```

More examples:

```
sage: QS3 = SymmetricGroupAlgebra(QQ, 3)
sage: a = 2*QS3([1,2,3]) + 4*QS3([3,2,1])
sage: a._vector_()
(2, 0, 0, 0, 0, 4)
sage: a.to_vector()
(2, 0, 0, 0, 0, 4)
sage: vector(a)
(2, 0, 0, 0, 0, 4)
sage: a == QS3.from_vector(a.to_vector())
True
sage: a.to_vector(sparse=True)
(2, 0, 0, 0, 0, 4)
```

If `new_base_ring` is specified, then a vector over `new_base_ring` is returned:

```
sage: a._vector_(RDF)
(2.0, 0.0, 0.0, 0.0, 0.0, 4.0)
```

Note: [trac ticket #13406](#): the current implementation has been optimized, at the price of breaking the encapsulation for FreeModule elements creation, with the following use case as metric, on a 2008' Macbook Pro:

```
sage: F = CombinatorialFreeModule(QQ, range(10))
sage: f = F.an_element()
sage: %timeit f._vector_() # not tested
625 loops, best of 3: 17.5 micros per loop
```

Other use cases may call for different or further optimizations.

3.4 Invariant modules

```
class sage.modules.with_basis.invariant.FiniteDimensionalInvariantModule(M, S,
                                                                    action=<built-in
                                                                    function mul>,
                                                                    side='left', *args,
                                                                    **kwargs)
```

Bases: `sage.modules.with_basis.subquotient.SubmoduleWithBasis`

The invariant submodule under a semigroup action.

When a semigroup S acts on a module M , the invariant module is the set of elements $m \in M$ such that $s \cdot m = m$ for all $s \in S$:

$$M^S := \{m \in M : s \cdot m = m, \forall s \in S\}.$$

INPUT:

- M – a module in the category of `FiniteDimensionalModulesWithBasis`
- S – a semigroup in the category of `FinitelyGeneratedSemigroups`
- `action` – (default: `operator.mul`) the action of S on M
- `side` – (default: `'left'`) the side on which S acts

EXAMPLES:

First, we create the invariant defined by the cyclic group action on the free module with basis $\{1, 2, 3\}$:

```
sage: G = CyclicPermutationGroup(3)
sage: M = CombinatorialFreeModule(QQ, [1,2,3], prefix='M')
sage: action = lambda g, m: M.monomial(g(m)) # cyclically permute coordinates
```

In order to give the module an action of G , we create a *Representation*:

```
sage: from sage.modules.with_basis.representation import Representation
sage: R = Representation(G, M, action)
sage: I = R.invariant_module()
```

Then we can lift the basis from the invariant to the original module:

```
sage: [I.lift(b) for b in I.basis()]
[M[1] + M[2] + M[3]]
```

The we could also have the action be a right-action, instead of the default left-action:

```
sage: def rt_action(g, m): return M.monomial(g(m)) # cyclically permute coordinates
sage: R = Representation(G, M, rt_action, side='right') # same as last but on right
sage: g = G.an_element(); g
(1,2,3)
sage: r = R.an_element(); r
2*M[1] + 2*M[2] + 3*M[3]
sage: R.side()
'right'
```

So now we can see that multiplication with g on the right sends $M[1]$ to $M[2]$ and so on:

```
sage: r * g
3*M[1] + 2*M[2] + 2*M[3]
sage: I = R.invariant_module()
sage: [I.lift(b) for b in I.basis()]
[M[1] + M[2] + M[3]]
```

Now we will take the regular representation of the symmetric group on three elements to be the module, and compute its invariant submodule:

```
sage: G = SymmetricGroup(3)
sage: R = G.regular_representation(QQ)
sage: I = R.invariant_module()
sage: [I.lift(b).to_vector() for b in I.basis()]
[(1, 1, 1, 1, 1, 1)]
```

We can also check the scalar multiplication by elements of the base ring (for this example, the rational field):

```
sage: [I.lift(3*b).to_vector() for b in I.basis()]
[(3, 3, 3, 3, 3, 3)]
```

A more subtle example is the invariant submodule of a skew-commutative module, for example the exterior algebra $E[x_0, x_1, x_2]$ generated by three elements:

```
sage: G = CyclicPermutationGroup(3)
sage: M = algebras.Exterior(QQ, 'x', 3)
sage: def cyclic_ext_action(g, m):
.....:     # cyclically permute generators
.....:     return M.prod([M.monomial(FrozenBitset([g(j+1)-1])) for j in m])
```

If you care about being able to exploit the algebra structure of the exterior algebra (i.e. if you want to multiply elements together), you should make sure the representation knows it is also an algebra with the semigroup action being by algebra endomorphisms:

```
sage: cat = Algebras(QQ).WithBasis().FiniteDimensional()
sage: R = Representation(G, M, cyclic_ext_action, category=cat)
sage: I = R.invariant_module()
```

We can express the basis in the ambient algebra ($E[x_0, x_1, x_2]$):

```
sage: [I.lift(b) for b in I.basis()]
[1, x0 + x1 + x2, x0*x1 - x0*x2 + x1*x2, x0*x1*x2]
```

or we can express the basis intrinsically to the invariant I :

```
sage: B = I.basis()
sage: m = 3*B[0] + 2*B[1] + 7*B[3]
```

This lifts to the exterior algebra:

```
sage: I.lift(m)
3 + 2*x0 + 7*x0*x1*x2 + 2*x1 + 2*x2
```

We can also check using the invariant element m that arithmetic works:

```
sage: m^2
9*B[0] + 12*B[1] + 42*B[3]
sage: m+m
6*B[0] + 4*B[1] + 14*B[3]
```

To see the actual elements expressed in the exterior algebra, we lift them again:

```
sage: I.lift(m+m)
6 + 4*x0 + 14*x0*x1*x2 + 4*x1 + 4*x2
sage: 7*m
21*B[0] + 14*B[1] + 49*B[3]
sage: I.lift(7*m)
21 + 14*x0 + 49*x0*x1*x2 + 14*x1 + 14*x2
```

The classic example of an invariant module is the module of symmetric functions, which is the invariant module of polynomials whose variables are acted upon by permutation. We can create a module isomorphic to the homogeneous component of a polynomial ring in n variable of a fixed degree d by looking at weak compositions of d of length n , which we consider as the exponent vector. For example, $x^2yz \in \mathbf{Q}[x, y, z]$ would have the exponent vector $(2, 1, 1)$. The vector $(2, 1, 1)$ is a weak composition of 4, with length 3, and so we can think of it as being in the degree-4 homogeneous component of a polynomial ring in three variables:

```
sage: C = IntegerVectors(4, length=3, min_part=0) # representing degree-4 monomials
sage: M = CombinatorialFreeModule(QQ, C) # isomorphic to deg-4 homog. polynomials
sage: G = SymmetricGroup(3)
sage: def perm_action(g,x): return M.monomial(C(g(list(x))))
sage: perm_action(G((1,2,3)), C([4,3,2]))
B[[3, 2, 4]]
sage: R = Representation(G, M, perm_action)
sage: I = R.invariant_module()
sage: [I.lift(b) for b in I.basis()]
[B[[0, 0, 4]] + B[[0, 4, 0]] + B[[4, 0, 0]],
 B[[0, 1, 3]] + B[[0, 3, 1]] + B[[1, 0, 3]]
 + B[[1, 3, 0]] + B[[3, 0, 1]] + B[[3, 1, 0]],
 B[[0, 2, 2]] + B[[2, 0, 2]] + B[[2, 2, 0]],
 B[[1, 1, 2]] + B[[1, 2, 1]] + B[[2, 1, 1]]]
```

These are the monomial symmetric functions, which are a well-known basis for the symmetric functions. For comparison:

```

sage: Sym = SymmetricFunctions(QQ)
sage: m = Sym.monomial()
sage: [m[mu].expand(3) for mu in Partitions(4)]
[x0^4 + x1^4 + x2^4,
 x0^3*x1 + x0*x1^3 + x0^3*x2 + x1^3*x2 + x0*x2^3 + x1*x2^3,
 x0^2*x1^2 + x0^2*x2^2 + x1^2*x2^2,
 x0^2*x1*x2 + x0*x1^2*x2 + x0*x1*x2^2,
 0]

```

Note: The current implementation works when S is a finitely-generated semigroup, and when M is a finite-dimensional free module with a distinguished basis.

Todo: Extend this to have multiple actions, including actions on both sides.

Todo: Extend when M does not have a basis and S is a permutation group using:

- [arXiv 0812.3082](https://arxiv.org/abs/0812.3082)
- <https://www.dmtcs.org/pdfpapers/dmAA0123.pdf>

class `Element`

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

semigroup()

Return the semigroup S whose action `self` is invariant under.

EXAMPLES:

```

sage: G = SymmetricGroup(3)
sage: M = CombinatorialFreeModule(QQ, [1,2,3], prefix='M')
sage: def action(g,x): return M.monomial(g(x))
sage: I = M.invariant_module(G, action_on_basis=action)
sage: I.semigroup()
Symmetric group of order 3! as a permutation group

```

semigroup_representation()

Return the ambient space of `self`.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(3)); x = X.basis()
sage: Y = X.submodule((x[0]-x[1], x[1]-x[2]))
sage: Y.ambient() is X
True

```

```

class sage.modules.with_basis.invariant.FiniteDimensionalTwistedInvariantModule(M, G, chi,
                                                                                   action=<built-
                                                                                   in function
                                                                                   mul>,
                                                                                   side='left',
                                                                                   **kwargs)

```

Bases: `sage.modules.with_basis.subquotient.SubmoduleWithBasis`

Construct the χ -twisted invariant submodule of M .

When a group G acts on a module M , the χ -twisted invariant submodule of M is the isotypic component of the representation M corresponding to the irreducible character χ .

For more information, see [Sta1979].

INPUT:

- M – a module in the category of `FiniteDimensionalModulesWithBasis` and whose base ring contains all the values passed to `chi` and $1/|G|$
- G – a finitely generated group
- `chi` – list/tuple of the character values of the irreducible representation onto which you want to project. The order of values of `chi` must agree with the order of `G.conjugacy_classes()`
- `action` – (default: `operator.mul`) the action of G on M
- `side` – (default: `'left'`) the side on which G acts

Warning: The current implementation does not check if `chi` is irreducible. Passing character values of non-irreducible representations may lead to mathematically incorrect results.

EXAMPLES:

Suppose that the symmetric group S_3 acts on a four dimensional vector space by permuting the first three coordinates only:

```
sage: M = CombinatorialFreeModule(QQ, [1,2,3,4], prefix='M')
sage: G = SymmetricGroup(3)
sage: action = lambda g,x: M.term(g(x))
```

The trivial representation corresponds to the usual invariant module, so trying to create the twisted invariant module when there is no twist returns a `FiniteDimensionalInvariantModule`:

```
sage: chi = ClassFunction(G, (1,1,1))
sage: T = M.twisted_invariant_module(G, chi, action_on_basis=action)
sage: type(T)
<class 'sage.modules.with_basis.invariant.FiniteDimensionalInvariantModule_with_
↪category'>
```

In this case, there are two copies of the trivial representation, one coming from the first three coordinates and the other coming from the fact that S_3 does not touch the fourth coordinate:

```
sage: T.basis()
Finite family {0: B[0], 1: B[1]}
sage: [T.lift(b) for b in T.basis()]
[M[1] + M[2] + M[3], M[4]]
```

The character values of the standard representation are $2, 0, -1$:

```
sage: chi = ClassFunction(G, [2,0,-1])
sage: T = M.twisted_invariant_module(G, chi, action_on_basis=action)
sage: type(T)
<class 'sage.modules.with_basis.invariant.FiniteDimensionalTwistedInvariantModule_
↪with_category'>
```

(continues on next page)

(continued from previous page)

```

sage: T.basis()
Finite family {0: B[0], 1: B[1]}
sage: [T.lift(b) for b in T.basis()]
[M[1] - M[3], M[2] - M[3]]

```

The permutation representation is the direct sum of the standard representation with the trivial representation, and the action on the basis element B[4] is itself a copy of the trivial representation, so the sign representation does not appear in the decomposition:

```

sage: T = M.twisted_invariant_module(G, [1,-1,1], action_on_basis=action)
sage: T.basis()
Finite family {}

```

We can also get two copies of the standard representation by looking at two copies of the permutation representation, found by reduction modulo three on the indices of a six-dimensional module:

```

sage: M = CombinatorialFreeModule(QQ, [0,1,2,3,4,5], prefix='M')
sage: action = lambda g,x: M.term(g(x%3 + 1)-1 + (x>=3)*3)
sage: T = M.twisted_invariant_module(G, [2,0,-1], action_on_basis=action)
sage: T.basis()
Finite family {0: B[0], 1: B[1], 2: B[2], 3: B[3]}
sage: [T.lift(b) for b in T.basis()]
[M[0] - M[2], M[1] - M[2], M[3] - M[5], M[4] - M[5]]

sage: T = M.twisted_invariant_module(G, [1,1,1], action_on_basis=action)
sage: T.basis()
Finite family {0: B[0], 1: B[1]}
sage: [T.lift(b) for b in T.basis()]
[M[0] + M[1] + M[2], M[3] + M[4] + M[5]]

```

There are still no copies of the sign representation:

```

sage: T = M.twisted_invariant_module(G, [1,-1,1], action_on_basis=action)
sage: T.basis()
Finite family {}

```

The trivial representation also contains no copies of the sign representation:

```

sage: R = G.trivial_representation(QQ)
sage: T = R.twisted_invariant_module([1,-1,1])
sage: T.basis()
Finite family {}

```

The regular representation contains two copies of the standard representation and one copy each of the trivial and the sign:

```

sage: R = G.regular_representation(QQ)
sage: std = R.twisted_invariant_module([2,0,-1])
sage: std.basis()
Finite family {0: B[0], 1: B[1], 2: B[2], 3: B[3]}
sage: [std.lift(b) for b in std.basis()]
[(1,2,3), -(1,2,3) + (1,3,2), (2,3) - (1,2), -(1,2) + (1,3)]

```

(continues on next page)

(continued from previous page)

```

sage: triv = R.twisted_invariant_module([1,1,1])
sage: triv.basis()
Finite family {0: B[0]}
sage: [triv.lift(b) for b in triv.basis()]
[(0) + (2,3) + (1,2) + (1,2,3) + (1,3,2) + (1,3)]

sage: sgn = R.twisted_invariant_module([1,-1,1])
sage: sgn.basis()
Finite family {0: B[0]}
sage: [sgn.lift(b) for b in sgn.basis()]
[(0) - (2,3) - (1,2) + (1,2,3) + (1,3,2) - (1,3)]

```

For the next example, we construct a twisted invariant by the character for the 2 dimensional representation of S_3 on the natural action on the exterior algebra. While S_3 acts by automorphisms, the twisted invariants do not form an algebra in this case:

```

sage: G = SymmetricGroup(3); G.rename('S3')
sage: E = algebras.Exterior(QQ, 'x', 3); E.rename('E')
sage: def action(g,m): return E.prod([E.monomial(FrozenBitset([g(j+1)-1])) for j in
    ↪ m])
sage: from sage.modules.with_basis.representation import Representation
sage: EA = Representation(G, E, action, category=Algebras(QQ).WithBasis().
    ↪ FiniteDimensional())
sage: T = EA.twisted_invariant_module([2,0,-1])
sage: t = T.an_element(); t
2*B[0] + 2*B[1] + 3*B[2]

```

We can still get meaningful information about the product by taking the product in the ambient space:

```

sage: T.lift(t) * T.lift(t)
-36*x0*x1*x2

```

We can see this does not lie in this twisted invariant algebra:

```

sage: T.retract(T.lift(t) * T.lift(t))
Traceback (most recent call last):
...
ValueError: -36*x0*x1*x2 is not in the image

sage: [T.lift(b) for b in T.basis()]
[x0 - x2, x1 - x2, x0*x1 - x1*x2, x0*x2 + x1*x2]

```

It happens to be in the trivial isotypic component (equivalently in the usual invariant algebra) but Sage does not know this.

```

sage: G.rename(); E.rename() # reset the names

```

Todo:

- Replace G by S in `FinitelyGeneratedSemigroups`
- Allow for chi to be a `Representation`
- Add check for irreducibility of chi

class Element

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

project(x)

Project x in the ambient module onto self.

EXAMPLES:

The standard representation is the orthogonal complement of the trivial representation inside of the permutation representation, so the basis for the trivial representation projects to 0:

```
sage: M = CombinatorialFreeModule(QQ, [1,2,3]); M.rename('M')
sage: B = M.basis()
sage: G = SymmetricGroup(3); G.rename('S3')
sage: def action(g,x): return M.term(g(x))
sage: T = M.twisted_invariant_module(G, [2,0,-1], action_on_basis=action)
sage: m = B[1] + B[2] + B[3]
sage: parent(m)
M
sage: t = T.project(m); t
0
sage: parent(t)
Twist of (S3)-invariant submodule of M by character [2, 0, -1]

sage: G.rename(); M.rename() # reset names
```

project_ambient(x)

Project x in the ambient representation onto the submodule of the ambient representation to which self is isomorphic as a module.

Note: The image of `self.project_ambient` is not in `self` but rather is in `self.ambient()`.

EXAMPLES:

```
sage: M = CombinatorialFreeModule(QQ, [1,2,3]); M.rename('M')
sage: B = M.basis()
sage: G = SymmetricGroup(3); G.rename('S3')
sage: def action(g,x): return M.term(g(x))
sage: T = M.twisted_invariant_module(G, [2,0,-1], action_on_basis=action)
```

To compare with `self.project`, we can inspect the parents. The image of `self.project` is in `self`, while the image of `self.project_ambient` is in `self._ambient`:

```
sage: t = T.project(B[1] + B[2] + B[3]); t
0
sage: parent(t)
Twist of (S3)-invariant submodule of M by character [2, 0, -1]
sage: s = T.project_ambient(B[1] + B[2] + B[3]); s
0
sage: parent(s)
Representation of S3 indexed by {1, 2, 3} over Rational Field
```

Note that because of the construction of `T`, `self._ambient` is an instance of `Representation`, but you still may pass elements of `M`, which is an instance of `CombinatorialFreeModule`, because the underlying

Representation is built off of `M` and we can canonically construct elements of the Representation from elements of `M`.

```
sage: G.rename(); M.rename() # reset names
```

`projection_matrix()`

Return the matrix defining the projection map from the ambient representation onto `self`.

EXAMPLES:

```
sage: M = CombinatorialFreeModule(QQ, [1,2,3])
sage: def action(g,x): return(M.term(g(x)))
sage: G = SymmetricGroup(3)
```

If the matrix A has columns form a basis for the subspace onto which we are trying to project, then we can find the projection matrix via the formula $P = A(A^T A)^{-1} A^T$. Recall that the standard representation twisted invariant has basis $(B[1] - B[3], B[2] - B[3])$, hence:

```
sage: A = Matrix([[1,0],[0,1],[-1,-1]])
sage: P = A*(A.transpose()*A).inverse()*A.transpose()
sage: T = M.twisted_invariant_module(G, [2,0,-1], action_on_basis=action)
sage: P == T.projection_matrix()
True
```

Moreover, since there is no component of the sign representation in this representation, the projection matrix is just the zero matrix:

```
sage: T = M.twisted_invariant_module(G, [1,-1,1], action_on_basis=action)
sage: T.projection_matrix()
[0 0 0]
[0 0 0]
[0 0 0]
```

3.5 Morphisms of modules with a basis

This module contains a hierarchy of classes for morphisms of modules with a basis (category `Modules.WithBasis`):

- `ModuleMorphism`
- `ModuleMorphismByLinearity`
- `ModuleMorphismFromMatrix`
- `ModuleMorphismFromFunction`
- `TriangularModuleMorphism`
- `TriangularModuleMorphismByLinearity`
- `TriangularModuleMorphismFromFunction`

These are internal classes; it is recommended *not* to use them directly, and instead to construct morphisms through the `ModulesWithBasis.ParentMethods.module_morphism()` method of the domain, or through the `homset`. See the former for an overview of the possible arguments.

EXAMPLES:

We construct a morphism through the method `ModulesWithBasis.ParentMethods.module_morphism()`, by specifying the image of each element of the distinguished basis:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4]); y = Y.basis()
sage: on_basis = lambda i: Y.monomial(i) + 2*Y.monomial(i+1)

sage: phi1 = X.module_morphism(on_basis, codomain=Y)
sage: phi1(x[1])
B[1] + 2*B[2]

sage: phi1
Generic morphism:
  From: Free module generated by {1, 2, 3} over Rational Field
  To:   Free module generated by {1, 2, 3, 4} over Rational Field
sage: phi1.parent()
Set of Morphisms from Free module generated by {1, 2, 3} over Rational Field to Free_
↳ module generated by {1, 2, 3, 4} over Rational Field in Category of finite dimensional_
↳ vector spaces with basis over Rational Field
sage: phi1.__class__
<class 'sage.modules.with_basis.morphism.ModuleMorphismByLinearity_with_category'>
```

Constructing the same morphism from the homset:

```
sage: H = Hom(X,Y)
sage: phi2 = H(on_basis=on_basis)
sage: phi1 == phi2
True
```

Constructing the same morphism directly using the class; no backward compatibility is guaranteed in this case:

```
sage: from sage.modules.with_basis.morphism import ModuleMorphismByLinearity
sage: phi3 = ModuleMorphismByLinearity(X, on_basis, codomain=Y)
sage: phi3 == phi1
True
```

Warning: The hierarchy of classes implemented in this module is one of the first non-trivial hierarchies of classes for morphisms. It is hitting a couple scaling issues:

- There are many independent properties from which module morphisms can get code (being defined by linearity, from a matrix, or a function; being triangular, being diagonal, ...). How to mitigate the class hierarchy growth?

This will become even more stringent as more properties are added (e.g. being defined from generators for an algebra morphism, ...)

Categories, whose primary purpose is to provide infrastructure for handling such large hierarchy of classes, can't help at this point: there is no category whose morphisms are triangular morphisms, and it's not clear such a category would be sensible.

- How to properly handle `__init__` method calls and multiple inheritance?
- Who should be in charge of setting the default category: the classes themselves, or `ModulesWithBasis.ParentMethods.module_morphism()`?

Because of this, the hierarchy of classes, and the specific APIs, is likely to be refactored as better infrastructure and best practices emerge.

AUTHORS:

- Nicolas M. Thiery (2008-2015)
- Jason Bandlow and Florent Hivert (2010): Triangular Morphisms
- Christian Stump (2010): [trac ticket #9648](#) module_morphism's to a wider class of codomains

Before [trac ticket #8678](#), this hierarchy of classes used to be in `sage.categories.modules_with_basis`; see [trac ticket #8678](#) for the complete log.

class `sage.modules.with_basis.morphism.DiagonalModuleMorphism`(*domain*, *diagonal*,
codomain=None, *category=None*)

Bases: `sage.modules.with_basis.morphism.ModuleMorphismByLinearity`

A class for diagonal module morphisms.

See `ModulesWithBasis.ParentMethods.module_morphism()`.

INPUT:

- `domain`, `codomain` – two modules with basis F and G , respectively
- `diagonal` – a function d

Assumptions:

- `domain` and `codomain` have the same base ring R ,
- their respective bases F and G have the same index set I ,
- d is a function $I \rightarrow R$.

Return the diagonal module morphism from `domain` to `codomain` sending $F(i) \mapsto d(i)G(i)$ for all $i \in I$.

By default, `codomain` is currently assumed to be `domain`. (Todo: make a consistent choice with `*ModuleMorphism`.)

Todo:

- Implement an optimized `_call_()` function.
 - Generalize to a `mapcoeffs`.
 - Generalize to a `mapterms`.
-

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X")
sage: phi = X.module_morphism(diagonal=factorial, codomain=X)
sage: x = X.basis()
sage: phi(x[1]), phi(x[2]), phi(x[3])
(B[1], 2*B[2], 6*B[3])
```

class `sage.modules.with_basis.morphism.ModuleMorphism`(*domain*, *codomain=None*, *category=None*,
affine=False)

Bases: `sage.categories.morphism.Morphism`

The top abstract base class for module with basis morphisms.

INPUT:

- `domain` – a parent in `ModulesWithBasis(...)`
- `codomain` – a parent in `Modules(...)`;
- `category` – a category or `None` (default: `None`)
- `affine` – whether we define an affine module morphism (default: `False`).

Construct a module morphism from `domain` to `codomain` in the category `category`. By default, the category is the first of `Modules(R).WithBasis().FiniteDimensional()`, `Modules(R).WithBasis()`, `Modules(R)`, `CommutativeAdditiveMonoids()` that contains both the domain and the codomain. If initializing an affine morphism, then `Sets()` is used instead.

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

The role of this class is minimal: it provides an `__init__()` method which:

- handles the choice of the default category
- handles the proper inheritance from categories by updating the class of `self` upon construction.

```
class sage.modules.with_basis.morphism.ModuleMorphismByLinearity(domain, on_basis=None,
                                                                    codomain=None,
                                                                    category=None, position=0,
                                                                    zero=None)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphism`

A class for module morphisms obtained by extending a function by linearity.

INPUT:

- `domain`, `codomain`, `category` – as for `ModuleMorphism`
- `on_basis` – a function which accepts indices of the basis of `domain` as `position`-th argument
- `codomain` – a parent in `Modules(...)` (default: `on_basis.codomain()`)
- `position` – a non-negative integer (default: 0)
- `zero` – the zero of the codomain (defaults: `codomain.zero()`)

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

Note: `on_basis` may alternatively be provided in derived classes by passing `None` as argument, and implementing or setting the attribute `_on_basis`

on_basis()

Return the action of this morphism on basis elements, as per `ModulesWithBasis.Homsets.ElementMethods.on_basis()`.

OUTPUT:

- a function from the indices of the basis of the domain to the codomain

EXAMPLES:

```
sage: X = CombinatorialFreeModule(ZZ, [-2, -1, 1, 2])
sage: Y = CombinatorialFreeModule(ZZ, [1, 2])
sage: phi_on_basis = Y.monomial * abs
sage: phi = sage.modules.with_basis.morphism.ModuleMorphismByLinearity(X, on_
↳ basis = phi_on_basis, codomain=Y)
sage: x = X.basis()
sage: phi.on_basis()(-2)
B[2]
sage: phi.on_basis() == phi_on_basis
True
```

```
class sage.modules.with_basis.morphism.ModuleMorphismFromFunction(domain, function,
                                                                    codomain=None,
                                                                    category=None)

Bases: sage.modules.with_basis.morphism.ModuleMorphism, sage.categories.morphism.
SetMorphism
```

A class for module morphisms implemented by a plain function.

INPUT:

- domain, codomain, category – as for *ModuleMorphism*
- function – any function or callable from domain to codomain

See also:

- *ModulesWithBasis.ParentMethods.module_morphism()* for usage information and examples;
- *sage.modules.with_basis.morphism* for a technical overview of the classes for module morphisms;
- *ModuleMorphismFromFunction* and *TriangularModuleMorphism*.

```
class sage.modules.with_basis.morphism.ModuleMorphismFromMatrix(domain, matrix,
                                                                    codomain=None,
                                                                    category=None, side='left')
```

Bases: *sage.modules.with_basis.morphism.ModuleMorphismByLinearity*

A class for module morphisms built from a matrix in the distinguished bases of the domain and codomain.

See also:

- *ModulesWithBasis.ParentMethods.module_morphism()*
- *ModulesWithBasis.FiniteDimensional.MorphismMethods.matrix()*

INPUT:

- domain, codomain – two finite dimensional modules over the same base ring R with basis F and G , respectively
- matrix – a matrix with base ring R and dimensions matching that of F and G , respectively
- side – “left” or “right” (default: “left”)

If side is “left”, this morphism is considered as acting on the left; i.e. each column of the matrix represents the image of an element of the basis of the domain.

- `category` – a category or None (default: None)

EXAMPLES:

```
sage: X = CombinatorialFreeModule(ZZ, [1,2]); X.rename("X"); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [3,4]); Y.rename("Y"); y = Y.basis()
sage: m = matrix([[1,2],[3,5]])
sage: phi = X.module_morphism(matrix=m, codomain=Y)
sage: phi.parent()
Set of Morphisms from X to Y in Category of finite dimensional modules with basis_
↳over Integer Ring
sage: phi.__class__
<class 'sage.modules.with_basis.morphism.ModuleMorphismFromMatrix_with_category'>
sage: phi(x[1])
B[3] + 3*B[4]
sage: phi(x[2])
2*B[3] + 5*B[4]

sage: m = matrix([[1,2],[3,5]])
sage: phi = X.module_morphism(matrix=m, codomain=Y, side="right",
.....:                        category=Modules(ZZ).WithBasis())
sage: phi.parent()
Set of Morphisms from X to Y
in Category of modules with basis over Integer Ring
sage: phi(x[1])
B[3] + 2*B[4]
sage: phi(x[2])
3*B[3] + 5*B[4]
```

Todo: Possibly implement rank, addition, multiplication, matrix, etc, from the stored matrix.

class `sage.modules.with_basis.morphism.PointwiseInverseFunction(f)`

Bases: `sage.structure.sage_object.SageObject`

A class for pointwise inverse functions.

The pointwise inverse function of a function f is the function sending every x to $1/f(x)$.

EXAMPLES:

```
sage: from sage.modules.with_basis.morphism import PointwiseInverseFunction
sage: f = PointwiseInverseFunction(factorial)
sage: f(0), f(1), f(2), f(3)
(1, 1, 1/2, 1/6)
```

`pointwise_inverse()`

```
class sage.modules.with_basis.morphism.TriangularModuleMorphism(triangular='upper',
                                                                    unitriangular=False, key=None,
                                                                    inverse=None,
                                                                    inverse_on_support=<built-in
                                                                    function identity>,
                                                                    invertible=None)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphism`

An abstract class for triangular module morphisms

Let X and Y be modules over the same base ring, with distinguished bases F indexed by I and G indexed by J , respectively.

A module morphism ϕ from X to Y is *triangular* if its representing matrix in the distinguished bases of X and Y is upper triangular (echelon form).

More precisely, ϕ is *upper triangular* w.r.t. a total order $<$ on J if, for any $j \in J$, there exists at most one index $i \in I$ such that the leading support of $\phi(F_i)$ is j (see `leading_support()`). We denote by $r(j)$ this index, setting $r(j)$ to `None` if it does not exist.

Lower triangular morphisms are defined similarly, taking the trailing support instead (see `trailing_support()`).

A triangular morphism is *unitriangular* if all its pivots (i.e. coefficient of j in each $\phi(F[r(j)])$) are 1.

INPUT:

- `domain` – a module with basis X
- `codomain` – a module with basis Y (default: X)
- `category` – a category, as for `ModuleMorphism`
- `triangular` – "upper" or "lower" (default: "upper")
- `unitriangular` – boolean (default: `False`) As a shorthand, one may use `unitriangular="lower"` for `triangular="lower"`, `unitriangular=True`.
- `key` – a comparison key on J (default: the usual comparison of elements of J)
- `inverse_on_support` – a function $J \rightarrow I \cup \{None\}$ implementing r (default: the identity function). If set to "compute", the values of $r(j)$ are precomputed by running through the index set I of the basis of the domain. This of course requires the domain to be finite dimensional.
- `invertible` – a boolean or `None` (default: `None`); can be set to specify that ϕ is known to be (or not to be) invertible. If the domain and codomain share the same indexing set, this is by default automatically set to `True` if `inverse_on_support` is the identity, or in the finite dimensional case.

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

OUTPUT:

A morphism from X to Y .

Warning: This class is meant to be used as a complement for a concrete morphism class. In particular, the `__init__()` method focuses on setting up the data structure describing the triangularity of the morphism. It purposely does *not* call `ModuleMorphism.__init__()` which should be called (directly or indirectly) beforehand.

EXAMPLES:

We construct and invert an upper unitriangular module morphism between two free \mathbb{Q} -modules:

```
sage: I = range(1,200)
sage: X = CombinatorialFreeModule(QQ, I); X.rename("X"); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, I); Y.rename("Y"); y = Y.basis()
sage: ut = Y.sum_of_monomials * divisors # This * is map composition.
sage: phi = X.module_morphism(ut, unitriangular="upper", codomain=Y)
sage: phi(x[2])
B[1] + B[2]
sage: phi(x[6])
B[1] + B[2] + B[3] + B[6]
sage: phi(x[30])
B[1] + B[2] + B[3] + B[5] + B[6] + B[10] + B[15] + B[30]
sage: phi.preimage(y[2])
-B[1] + B[2]
sage: phi.preimage(y[6])
B[1] - B[2] - B[3] + B[6]
sage: phi.preimage(y[30])
-B[1] + B[2] + B[3] + B[5] - B[6] - B[10] - B[15] + B[30]
sage: (phi^-1)(y[30])
-B[1] + B[2] + B[3] + B[5] - B[6] - B[10] - B[15] + B[30]
```

A lower triangular (but not unitriangular) morphism:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def lt(i): return sum(j*x[j] for j in range(i,4))
sage: phi = X.module_morphism(lt, triangular="lower", codomain=X)
sage: phi(x[2])
2*B[2] + 3*B[3]
sage: phi.preimage(x[2])
1/2*B[2] - 1/2*B[3]
sage: phi(phi.preimage(x[2]))
B[2]
```

Using the key keyword, we can use triangularity even if the map becomes triangular only after a permutation of the basis:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def ut(i): return (x[1] + x[2] if i == 1 else x[2] + (x[3] if i == 3 else 0))
sage: perm = [0, 2, 1, 3]
sage: phi = X.module_morphism(ut, triangular="upper", codomain=X,
.....:                       key=lambda a: perm[a])
sage: [phi(x[i]) for i in range(1, 4)]
[B[1] + B[2], B[2], B[2] + B[3]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[B[1] - B[2], B[2], -B[2] + B[3]]
```

The same works in the lower-triangular case:

```
sage: def lt(i): return (x[1] + x[2] + x[3] if i == 2 else x[i])
sage: phi = X.module_morphism(lt, triangular="lower", codomain=X,
.....:                        key=lambda a: perm[a])
sage: [phi(x[i]) for i in range(1, 4)]
[B[1], B[1] + B[2] + B[3], B[3]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[B[1], -B[1] + B[2] - B[3], B[3]]
```

An injective but not surjective morphism cannot be inverted, but the `inverse_on_support` keyword allows Sage to find a partial inverse:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i+1,6) )
sage: phi = X.module_morphism(ult, unitriangular="lower", codomain=Y,
.....:                        inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi(x[2])
B[3] + B[4] + B[5]
sage: phi.preimage(y[3])
B[2] - B[3]
```

The `inverse_on_support` keyword can also be used if the bases of the domain and the codomain are identical but one of them has to be permuted in order to render the morphism triangular. For example:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def ut(i):
.....:     return (x[3] if i == 1 else x[1] if i == 2
.....:             else x[1] + x[2])
sage: def perm(i):
.....:     return (2 if i == 1 else 3 if i == 2 else 1)
sage: phi = X.module_morphism(ut, triangular="upper", codomain=X,
.....:                        inverse_on_support=perm)
sage: [phi(x[i]) for i in range(1, 4)]
[B[3], B[1], B[1] + B[2]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[B[2], -B[2] + B[3], B[1]]
```

The same works if the permutation induces lower triangularity:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X"); x = X.basis()
sage: def lt(i):
.....:     return (x[3] if i == 1 else x[2] if i == 2
.....:             else x[1] + x[2])
sage: def perm(i):
.....:     return 4 - i
sage: phi = X.module_morphism(lt, triangular="lower", codomain=X,
.....:                        inverse_on_support=perm)
sage: [phi(x[i]) for i in range(1, 4)]
[B[3], B[2], B[1] + B[2]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[-B[2] + B[3], B[2], B[1]]
```

In the finite dimensional case, one can ask Sage to recover `inverse_on_support` by a precomputation:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4]); y = Y.basis()
sage: ut = lambda i: sum( y[j] for j in range(1,i+2) )
sage: phi = X.module_morphism(ut, triangular="upper", codomain=Y,
.....:                        inverse_on_support="compute")
sage: tx = "{} {} {}"
sage: for j in Y.basis().keys():
.....:     i = phi._inverse_on_support(j)
.....:     print(tx.format(j, i, phi(x[i]) if i is not None else None))
1 None None
2 1 B[1] + B[2]
3 2 B[1] + B[2] + B[3]
4 3 B[1] + B[2] + B[3] + B[4]

```

The `inverse_on_basis` and key keywords can be combined:

```

sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); X.rename("X")
sage: x = X.basis()
sage: def ut(i):
.....:     return (2*x[2] + 3*x[3] if i == 1
.....:             else x[1] + x[2] + x[3] if i == 2
.....:             else 4*x[2])
sage: def perm(i):
.....:     return (2 if i == 1 else 3 if i == 2 else 1)
sage: perverse_key = lambda a: (a - 2) % 3
sage: phi = X.module_morphism(ut, triangular="upper", codomain=X,
.....:                        inverse_on_support=perm, key=perverse_key)
sage: [phi(x[i]) for i in range(1, 4)]
[2*B[2] + 3*B[3], B[1] + B[2] + B[3], 4*B[2]]
sage: [phi.preimage(x[i]) for i in range(1, 4)]
[-1/3*B[1] + B[2] - 1/12*B[3], 1/4*B[3], 1/3*B[1] - 1/6*B[3]]

```

`cokernel_basis_indices()`

Return the indices of the natural monomial basis of the cokernel of `self`.

INPUT:

- `self` – a triangular morphism over a field or a unitriangular morphism over a ring, with a finite dimensional codomain.

OUTPUT:

A list E of indices of the basis $(B_e)_e$ of the codomain of `self` so that $(B_e)_{e \in E}$ forms a basis of a supplementary of the image set of `self`.

Thinking of this triangular morphism as a row echelon matrix, this returns the complementary of the characteristic columns. Namely E is the set of indices which do not appear as leading support of some element of the image set of `self`.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(ZZ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [1,2,3,4,5]); y = Y.basis()
sage: uut = lambda i: sum( y[j] for j in range(i+1,6) ) # uni-upper
sage: phi = X.module_morphism(uut, unitriangular="upper", codomain=Y,
.....:                        inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)

```

(continues on next page)

(continued from previous page)

```

sage: phi.cokernel_basis_indices()
[1, 5]

sage: phi = X.module_morphism(uut, triangular="upper", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi.cokernel_basis_indices()
Traceback (most recent call last):
...
NotImplementedError: cokernel_basis_indices for a triangular but not
↳ unitriangular morphism over a ring

sage: Y = CombinatorialFreeModule(ZZ, NN); y = Y.basis()
sage: phi = X.module_morphism(uut, unitriangular="upper", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi.cokernel_basis_indices()
Traceback (most recent call last):
...
NotImplementedError: cokernel_basis_indices implemented only for morphisms with
↳ a finite dimensional codomain

```

cokernel_projection(category=None)

Return a projection on the co-kernel of self.

INPUT:

- category – the category of the result

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i+1,6) ) # lower
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phipro = phi.cokernel_projection()
sage: phipro(y[1] + y[2])
B[1]
sage: all(phipro(phi(x)).is_zero() for x in X.basis())
True
sage: phipro(y[1])
B[1]
sage: phipro(y[4])
-B[5]
sage: phipro(y[5])
B[5]

```

coreduced(y)Return y reduced w.r.t. the image of self.

INPUT:

- self – a triangular morphism over a field, or a unitriangular morphism over a ring
- y – an element of the codomain of self

Suppose that self is a morphism from X to Y . Then, for any $y \in Y$, the call self.coreduced(y)

returns a normal form for y in the quotient Y/I where I is the image of `self`.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i+1,6) )
sage: phi = X.module_morphism(ult, unitriangular="lower", codomain=Y,
.....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi(v) for v in X.basis()]
[B[2] + B[3] + B[4] + B[5],
 B[3] + B[4] + B[5],
 B[4] + B[5]]
sage: [phi.coreduced(y[1]-2*y[4])]
[B[1] + 2*B[5]]
sage: [phi.coreduced(v) for v in y]
[B[1], 0, 0, -B[5], B[5]]
```

Now with a non unitriangular morphism:

```
sage: lt = lambda i: sum( j*y[j] for j in range(i+1,6) )
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
.....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi(v) for v in X.basis()]
[2*B[2] + 3*B[3] + 4*B[4] + 5*B[5],
 3*B[3] + 4*B[4] + 5*B[5],
 4*B[4] + 5*B[5]]
sage: [phi.coreduced(y[1]-2*y[4])]
[B[1] + 5/2*B[5]]
sage: [phi.coreduced(v) for v in y]
[B[1], 0, 0, -5/4*B[5], B[5]]
```

For general rings, this method is only implemented for unitriangular morphisms:

```
sage: X = CombinatorialFreeModule(ZZ, [1,2,3]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [1,2,3,4,5]); y = Y.basis()
sage: phi = X.module_morphism(ult, unitriangular="lower", codomain=Y,
.....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi.coreduced(y[1]-2*y[4])]
[B[1] + 2*B[5]]
sage: [phi.coreduced(v) for v in y]
[B[1], 0, 0, -B[5], B[5]]

sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
.....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: [phi.coreduced(v) for v in y]
Traceback (most recent call last):
...
NotImplementedError: coreduce for a triangular but not unitriangular morphism.
↳ over a ring
```

Note: Before [trac ticket #8678](#) this method used to be called `co_reduced`.

preimage(*f*)

Return the preimage of *f* under self.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i,4) ) # uni-lower
sage: phi = X.module_morphism(ult, triangular="lower", codomain=Y)
sage: phi.preimage(y[1] + y[2])
B[1] - B[3]
```

The morphism need not be surjective. In the following example, the codomain is of larger dimension than the domain:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i,5) )
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y)
sage: phi.preimage(y[1] + y[2])
B[1] - B[3]
```

Here are examples using `inverse_on_support` to handle a morphism that shifts the leading indices by 1:

```
sage: X = CombinatorialFreeModule(QQ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(QQ, [1, 2, 3, 4, 5]); y = Y.basis()
sage: lt = lambda i: sum( y[j] for j in range(i+1,6) ) # lower
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y,
.....:     inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: phi(x[1])
B[2] + B[3] + B[4] + B[5]
sage: phi(x[3])
B[4] + B[5]
sage: phi.preimage(y[2] + y[3])
B[1] - B[3]
sage: phi(phi.preimage(y[2] + y[3])) == y[2] + y[3]
True
sage: el = x[1] + 3*x[2] + 2*x[3]
sage: phi.preimage(phi(el)) == el
True

sage: phi.preimage(y[1])
Traceback (most recent call last):
...
ValueError: B[1] is not in the image
sage: phi.preimage(y[4])
Traceback (most recent call last):
...
ValueError: B[4] is not in the image
```

Over a base ring like \mathbb{Z} , the morphism need not be surjective even when the dimensions match:

```
sage: X = CombinatorialFreeModule(ZZ, [1, 2, 3]); x = X.basis()
sage: Y = CombinatorialFreeModule(ZZ, [1, 2, 3]); y = Y.basis()
sage: lt = lambda i: sum( 2* y[j] for j in range(i,4) ) # lower
```

(continues on next page)

(continued from previous page)

```
sage: phi = X.module_morphism(lt, triangular="lower", codomain=Y)
sage: phi.preimage(2*y[1] + 2*y[2])
B[1] - B[3]
```

The error message in case of failure could be more specific though:

```
sage: phi.preimage(y[1] + y[2])
Traceback (most recent call last):
...
TypeError: no conversion of this rational to integer
```

section()

Return the section (partial inverse) of self.

Return a partial triangular morphism which is a section of self. The section morphism raise a `ValueError` if asked to apply on an element which is not in the image of self.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, [1,2,3]); x = X.basis()
sage: X.rename('X')
sage: Y = CombinatorialFreeModule(QQ, [1,2,3,4,5]); y = Y.basis()
sage: ult = lambda i: sum( y[j] for j in range(i+1,6) ) # uni-lower
sage: phi = X.module_morphism(ult, triangular="lower", codomain=Y,
.....:      inverse_on_support=lambda i: i-1 if i in [2,3,4] else None)
sage: ~phi
Traceback (most recent call last):
...
ValueError: Morphism not known to be invertible;
see the invertible option of module_morphism
sage: phiinv = phi.section()
sage: list(map(phiinv*phi, X.basis().list())) == X.basis().list()
True
sage: phiinv(Y.basis()[1])
Traceback (most recent call last):
...
ValueError: B[1] is not in the image
```

```
class sage.modules.with_basis.morphism.TriangularModuleMorphismByLinearity(domain, on_basis,
                                                                              codomain=None,
                                                                              category=None,
                                                                              **keywords)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphismByLinearity`, `sage.modules.with_basis.morphism.TriangularModuleMorphism`

A concrete class for triangular module morphisms obtained by extending a function by linearity.

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismByLinearity` and `TriangularModuleMorphism`.

```
class sage.modules.with_basis.morphism.TriangularModuleMorphismFromFunction(domain, function,
                                                                              codomain=None,
                                                                              category=None,
                                                                              **keywords)
```

Bases: `sage.modules.with_basis.morphism.ModuleMorphismFromFunction`, `sage.modules.with_basis.morphism.TriangularModuleMorphism`

A concrete class for triangular module morphisms implemented by a function.

See also:

- `ModulesWithBasis.ParentMethods.module_morphism()` for usage information and examples;
- `sage.modules.with_basis.morphism` for a technical overview of the classes for module morphisms;
- `ModuleMorphismFromFunction` and `TriangularModuleMorphism`.

```
sage.modules.with_basis.morphism.pointwise_inverse_function(f)
```

Return the function $x \mapsto 1/f(x)$.

INPUT:

- `f` – a function

EXAMPLES:

```
sage: from sage.modules.with_basis.morphism import pointwise_inverse_function
sage: def f(x): return x
sage: g = pointwise_inverse_function(f)
sage: g(1), g(2), g(3)
(1, 1/2, 1/3)
```

`pointwise_inverse_function()` is an involution:

```
sage: f is pointwise_inverse_function(g)
True
```

Todo: This has nothing to do here!!! Should there be a library for pointwise operations on functions somewhere in Sage?

3.6 Quotients of modules with basis

```
class sage.modules.with_basis.subquotient.QuotientModuleWithBasis(submodule, category)
```

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

A class for quotients of a module with basis by a submodule.

INPUT:

- `submodule` – a submodule of `self`
- `category` – a category (default: `ModulesWithBasis(submodule.base_ring())`)

`submodule` should be a free submodule admitting a basis in unitriangular echelon form. Typically `submodule` is a `SubmoduleWithBasis` as returned by `Modules.WithBasis.ParentMethods.submodule()`.

The `lift` method should have a method `.cokernel_basis_indices` that computes the indexing set of a subset B of the basis of `self` that spans some supplementary of submodule in `self` (typically the non characteristic columns of the aforementioned echelon form). `submodule` should further implement a `submodule.reduce(x)` method that returns the unique element in the span of B which is equivalent to x modulo submodule.

This is meant to be constructed via `Modules.WithBasis.FiniteDimensional.ParentMethods.quotient_module()`

This differs from `sage.rings.quotient_ring.QuotientRing` in the following ways:

- `submodule` needs not be an ideal. If it is, the transportation of the ring structure is taken care of by the `Subquotients` categories.
- Thanks to `.cokernel_basis_indices`, we know the indices of a basis of the quotient, and elements are represented directly in the free module spanned by those indices rather than by wrapping elements of the ambient space.

There is room for sharing more code between those two implementations and generalizing them. See [trac ticket #18204](#).

See also:

- `Modules.WithBasis.ParentMethods.submodule()`
- `Modules.WithBasis.FiniteDimensional.ParentMethods.quotient_module()`
- [SubmoduleWithBasis](#)
- `sage.rings.quotient_ring.QuotientRing`

ambient()

Return the ambient space of `self`.

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.quotient_module((x[0]-x[1], x[1]-x[2]))
sage: Y.ambient() is X
True
```

lift(x)

Lift x to the ambient space of `self`.

INPUT:

- x – an element of `self`

EXAMPLES:

```
sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.quotient_module((x[0]-x[1], x[1]-x[2])); y = Y.basis()
sage: Y.lift(y[2])
x[2]
```

retract(x)

Retract an element of the ambient space by projecting it back to `self`.

INPUT:

- x – an element of the ambient space of `self`

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.quotient_module((x[0]-x[1], x[1]-x[2])); y = Y.basis()
sage: Y.print_options(prefix='y')
sage: Y.retract(x[0])
y[2]
sage: Y.retract(x[1])
y[2]
sage: Y.retract(x[2])
y[2]

```

class `sage.modules.with_basis.subquotient.SubmoduleWithBasis`(*basis*, *support_order*, *ambient*, *unitriangular*, *category*, **args*, ***opts*)

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

A base class for submodules of a `ModuleWithBasis` spanned by a (possibly infinite) basis in echelon form.

INPUT:

- *basis* – a family of elements in echelon form in some `module with basis` *V*, or data that can be converted into such a family
- *support_order* – an ordering of the support of basis expressed in *ambient* given as a list
- *unitriangular* – if the lift morphism is unitriangular
- *ambient* – the ambient space *V*
- *category* – a category

Further arguments are passed down to `CombinatorialFreeModule`.

This is meant to be constructed via `Modules.WithBasis.ParentMethods.submodule()`.

See also:

- `Modules.WithBasis.ParentMethods.submodule()`
- `QuotientModuleWithBasis`

ambient()

Return the ambient space of `self`.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(3)); x = X.basis()
sage: Y = X.submodule((x[0]-x[1], x[1]-x[2]))
sage: Y.ambient() is X
True

```

is_submodule(*other*)

Return whether `self` is a submodule of *other*.

INPUT:

- *other* – another submodule of the same ambient module, or the ambient module itself

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(4)); x = X.basis()
sage: F = X.submodule([x[0]-x[1], x[1]-x[2], x[2]-x[3]])
sage: G = X.submodule([x[0]-x[2]])
sage: H = X.submodule([x[0]-x[1], x[2]])
sage: F.is_submodule(X)
True
sage: G.is_submodule(F)
True
sage: H.is_submodule(F)
False

```

lift()

The lift (embedding) map from self to the ambient space.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.
↳basis()
sage: Y = X.submodule([x[0]-x[1], x[1]-x[2]], already_echelonized=True); y = Y.
↳basis()
sage: Y.lift
Generic morphism:
  From: Free module generated by {0, 1} over Rational Field
  To:   Free module generated by {0, 1, 2} over Rational Field
sage: [ Y.lift(u) for u in y ]
[x[0] - x[1], x[1] - x[2]]
sage: (y[0] + y[1]).lift()
x[0] - x[2]

```

reduce()

The reduce map.

This map reduces elements of the ambient space modulo this submodule.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.submodule([x[0]-x[1], x[1]-x[2]], already_echelonized=True)
sage: Y.reduce
Generic endomorphism of Free module generated by {0, 1, 2} over Rational Field
sage: Y.reduce(x[1])
x[2]
sage: Y.reduce(2*x[0] + x[1])
3*x[2]

```

retract()

The retract map from the ambient space.

EXAMPLES:

```

sage: X = CombinatorialFreeModule(QQ, range(3), prefix="x"); x = X.basis()
sage: Y = X.submodule([x[0]-x[1], x[1]-x[2]], already_echelonized=True)
sage: Y.print_options(prefix='y')
sage: Y.retract
Generic morphism:

```

(continues on next page)

(continued from previous page)

```

From: Free module generated by {0, 1, 2} over Rational Field
To:   Free module generated by {0, 1} over Rational Field
sage: Y.retract(x[0] - x[2])
y[0] + y[1]

```

3.7 Representations of a semigroup

AUTHORS:

- Travis Scrimshaw (2015-11-21): initial version
- Siddharth Singh (2020-03-21): signed representation

class sage.modules.with_basis.representation.**RegularRepresentation**(*semigroup*, *base_ring*, *side*='left')

Bases: [sage.modules.with_basis.representation.Representation](#)

The regular representation of a semigroup.

The left regular representation of a semigroup S over a commutative ring R is the semigroup ring $R[S]$ equipped with the left S -action $xb_y = b_{xy}$, where $(b_z)_{z \in S}$ is the natural basis of $R[S]$ and $x, y \in S$.

INPUT:

- *semigroup* – a semigroup
- *base_ring* – the base ring for the representation
- *side* – (default: "left") whether this is a "left" or "right" representation

REFERENCES:

- [Wikipedia article Regular representation](#)

class sage.modules.with_basis.representation.**Representation**(*semigroup*, *module*, *on_basis*, *side*='left', ***kwargs*)

Bases: [sage.modules.with_basis.representation.Representation_abstract](#)

Representation of a semigroup.

INPUT:

- *semigroup* – a semigroup
- *module* – a module with a basis
- *on_basis* – function which takes as input g, m , where g is an element of the semigroup and m is an element of the indexing set for the basis, and returns the result of g acting on m
- *side* – (default: "left") whether this is a "left" or "right" representation

EXAMPLES:

We construct the sign representation of a symmetric group:

```

sage: G = SymmetricGroup(4)
sage: M = CombinatorialFreeModule(QQ, ['v'])
sage: from sage.modules.with_basis.representation import Representation
sage: on_basis = lambda g,m: M.term(m, g.sign())
sage: R = Representation(G, M, on_basis)

```

(continues on next page)

(continued from previous page)

```

sage: x = R.an_element(); x
2*B['v']
sage: c,s = G.gens()
sage: c,s
((1,2,3,4), (1,2))
sage: c * x
-2*B['v']
sage: s * x
-2*B['v']
sage: c * s * x
2*B['v']
sage: (c * s) * x
2*B['v']

```

This extends naturally to the corresponding group algebra:

```

sage: A = G.algebra(QQ)
sage: s,c = A.algebra_generators()
sage: c,s
((1,2,3,4), (1,2))
sage: c * x
-2*B['v']
sage: s * x
-2*B['v']
sage: c * s * x
2*B['v']
sage: (c * s) * x
2*B['v']
sage: (c + s) * x
-4*B['v']

```

REFERENCES:

- [Wikipedia article Group_representation](#)

class Element

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

product_by_coercion(left, right)

Return the product of left and right by passing to `self._module` and then building a new element of `self`.

EXAMPLES:

```

sage: G = groups.permutation.KleinFour()
sage: E = algebras.Exterior(QQ, 'e', 4)
sage: on_basis = lambda g,m: E.monomial(m) # the trivial representation
sage: from sage.modules.with_basis.representation import Representation
sage: R = Representation(G, E, on_basis)
sage: r = R.an_element(); r
1 + 2*e0 + 3*e1 + e1*e2
sage: g = G.an_element();
sage: g*r == r
True

```

(continues on next page)

(continued from previous page)

```

sage: r*r
Traceback (most recent call last):
...
TypeError: unsupported operand parent(s) for *:
'Representation of The Klein 4 group of order 4, as a permutation
group indexed by Subsets of {0,1,...,3} over Rational Field' and
'Representation of The Klein 4 group of order 4, as a permutation
group indexed by Subsets of {0,1,...,3} over Rational Field'

sage: from sage.categories.algebras import Algebras
sage: category = Algebras(QQ).FiniteDimensional().WithBasis()
sage: T = Representation(G, E, on_basis, category=category)
sage: t = T.an_element(); t
1 + 2*e0 + 3*e1 + e1*e2
sage: g*t == t
True
sage: t*t
1 + 4*e0 + 4*e0*e1*e2 + 6*e1 + 2*e1*e2

```

side()

Return whether `self` is a left or a right representation.

OUTPUT:

- the string "left" or "right"

EXAMPLES:

```

sage: G = groups.permutation.Dihedral(4)
sage: R = G.regular_representation()
sage: R.side()
'left'
sage: S = G.regular_representation(side="right")
sage: S.side()
'right'

```

class `sage.modules.with_basis.representation.Representation_abstract`(*semigroup*, *base_ring*,
args*, *opts*)

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

Abstract base class for representations of semigroups.

INPUT:

- `semigroup` – a semigroup
- `base_ring` – a commutative ring

invariant_module(*S=None*, ***kwargs*)

Return the submodule of `self` invariant under the action of `S`.

For a semigroup S acting on a module M , the invariant submodule is given by

$$M^S = \{m \in M : s \cdot m = m \forall s \in S\}.$$

INPUT:

- `S` – a finitely-generated semigroup (default: the semigroup this is a representation of)

- `action` – a function (default: `operator.mul`)
- `side` – 'left' or 'right' (default: `side()`); which side of `self` the elements of `S` acts

Note: Two sided actions are considered as left actions for the invariant module.

OUTPUT:

- `FiniteDimensionalInvariantModule`

EXAMPLES:

```
sage: S3 = SymmetricGroup(3)
sage: M = S3.regular_representation()
sage: I = M.invariant_module()
sage: [I.lift(b) for b in I.basis()]
[(1) + (2,3) + (1,2) + (1,2,3) + (1,3,2) + (1,3)]
```

We build the D_4 -invariant representation inside of the regular representation of S_4 :

```
sage: D4 = groups.permutation.Dihedral(4)
sage: S4 = SymmetricGroup(4)
sage: R = S4.regular_representation()
sage: I = R.invariant_module(D4)
sage: [I.lift(b) for b in I.basis()]
[(1) + (2,4) + (1,2)(3,4) + (1,2,3,4) + (1,3) + (1,3)(2,4) + (1,4,3,2) + (1,4)(2,
↪3),
(3,4) + (2,3,4) + (1,2) + (1,2,4) + (1,3,2) + (1,3,2,4) + (1,4,3) + (1,4,2,3),
(2,3) + (2,4,3) + (1,2,3) + (1,2,4,3) + (1,3,4,2) + (1,3,4) + (1,4,2) + (1,4)]
```

semigroup()

Return the semigroup whose representation `self` is.

EXAMPLES:

```
sage: G = SymmetricGroup(4)
sage: M = CombinatorialFreeModule(QQ, ['v'])
sage: from sage.modules.with_basis.representation import Representation
sage: on_basis = lambda g,m: M.term(m, g.sign())
sage: R = Representation(G, M, on_basis)
sage: R.semigroup()
Symmetric group of order 4! as a permutation group
```

semigroup_algebra()

Return the semigroup algebra whose representation `self` is.

EXAMPLES:

```
sage: G = SymmetricGroup(4)
sage: M = CombinatorialFreeModule(QQ, ['v'])
sage: from sage.modules.with_basis.representation import Representation
sage: on_basis = lambda g,m: M.term(m, g.sign())
sage: R = Representation(G, M, on_basis)
sage: R.semigroup_algebra()
Symmetric group algebra of order 4 over Rational Field
```

side()

Return whether `self` is a left, right, or two-sided representation.

OUTPUT:

- the string "left", "right", or "twosided"

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)
sage: R = G.regular_representation()
sage: R.side()
'left'
```

twisted_invariant_module(*chi*, *G=None*, *kwargs*)**

Create the isotypic component of the action of `G` on `self` with irreducible character given by `chi`.

See also:

- [*FiniteDimensionalTwistedInvariantModule*](#)

INPUT:

- `chi` – a list/tuple of character values or an instance of [`ClassFunction_gap`](#)
- `G` – a finitely-generated semigroup (default: the semigroup this is a representation of)

This also accepts the group to be the first argument to be the group.

OUTPUT:

- [*FiniteDimensionalTwistedInvariantModule*](#)

EXAMPLES:

```
sage: G = SymmetricGroup(3)
sage: R = G.regular_representation(QQ)
sage: T = R.twisted_invariant_module([2,0,-1])
sage: T.basis()
Finite family {0: B[0], 1: B[1], 2: B[2], 3: B[3]}
sage: [T.lift(b) for b in T.basis()]
[(C) - (1,2,3), -(1,2,3) + (1,3,2), (2,3) - (1,2), -(1,2) + (1,3)]
```

We check the different inputs work

```
sage: R.twisted_invariant_module([2,0,-1], G) is T True
sage: R.twisted_invariant_module(G, [2,0,-1]) is T True
```

```
class sage.modules.with_basis.representation.SignRepresentationCoxeterGroup(group, base_ring,
                                                                                   sign_function=None)
```

Bases: [*sage.modules.with_basis.representation.SignRepresentation_abstract*](#)

The sign representation for a Coxeter group.

EXAMPLES:

```
sage: G = WeylGroup(["A", 1, 1])
sage: V = G.sign_representation()
sage: TestSuite(V).run()
```



```
class sage.modules.with_basis.representation.SignRepresentationMatrixGroup(group, base_ring,
                                                                    sign_function=None)
    Bases: sage.modules.with_basis.representation.SignRepresentation_abstract
```

The sign representation for a matrix group.

EXAMPLES:

```
sage: G = groups.permutation.PGL(2, 3)
sage: V = G.sign_representation()
sage: TestSuite(V).run()
```

```
class sage.modules.with_basis.representation.SignRepresentationPermgroupe(group, base_ring,
                                                                    sign_function=None)
    Bases: sage.modules.with_basis.representation.SignRepresentation_abstract
```

The sign representation for a permutation group.

EXAMPLES:

```
sage: G = groups.permutation.PGL(2, 3)
sage: V = G.sign_representation()
sage: TestSuite(V).run()
```

```
class sage.modules.with_basis.representation.SignRepresentation_abstract(group, base_ring,
                                                                    sign_function=None)
    Bases: sage.modules.with_basis.representation.Representation_abstract
```

Generic implementation of a sign representation.

The sign representation of a semigroup S over a commutative ring R is the 1-dimensional R -module on which every element of S acts by 1 if order of element is even (including 0) or -1 if order of element if odd.

This is simultaneously a left and right representation.

INPUT:

- `permgroupe` – a permgroupe
- `base_ring` – the base ring for the representation
- `sign_function` – a function which returns 1 or -1 depending on the elements sign

REFERENCES:

- [Wikipedia article Representation_theory_of_the_symmetric_group](#)

```
class Element
```

```
    Bases: sage.modules.with_basis.indexed_element.IndexedFreeModuleElement
```

```
side()
```

Return that `self` is a two-sided representation.

OUTPUT:

- the string "twosided"

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)
sage: R = G.sign_representation()
sage: R.side()
'twosided'
```

```
class sage.modules.with_basis.representation.TrivialRepresentation(semigroup, base_ring)  
    Bases: sage.modules.with_basis.representation.Representation_abstract
```

The trivial representation of a semigroup.

The trivial representation of a semigroup S over a commutative ring R is the 1-dimensional R -module on which every element of S acts by the identity.

This is simultaneously a left and right representation.

INPUT:

- `semigroup` – a semigroup
- `base_ring` – the base ring for the representation

REFERENCES:

- [Wikipedia article Trivial_representation](#)

```
class Element
```

```
    Bases: sage.modules.with_basis.indexed_element.IndexedFreeModuleElement
```

```
side()
```

Return that `self` is a two-sided representation.

OUTPUT:

- the string "twosided"

EXAMPLES:

```
sage: G = groups.permutation.Dihedral(4)  
sage: R = G.trivial_representation()  
sage: R.side()  
'twosided'
```

FINITELY GENERATED MODULES OVER A PID

4.1 Finitely generated modules over a PID

You can use Sage to compute with finitely generated modules (FGM's) over a principal ideal domain R presented as a quotient V/W , where V and W are free.

Note: Currently this is only enabled over $R=\mathbb{Z}$, since it has not been tested and debugged over more general PIDs. All algorithms make sense whenever there is a Hermite form implementation. In theory the obstruction to extending the implementation is only that one has to decide how elements print.

We represent $M = V / W$ as a pair (V, W) with W contained in V , and we internally represent elements of M non-canonically as elements x of V . We also fix independent generators $g[i]$ for M in V , and when we print out elements of V we print their coordinates with respect to the $g[i]$; over \mathbb{Z} this is canonical, since each coefficient is reduce modulo the additive order of $g[i]$. To obtain the vector in V corresponding to x in M , use $x.lift()$.

Morphisms between finitely generated R modules are well supported. You create a homomorphism by simply giving the images of generators of M_0 in M_1 . Given a morphism $\phi: M_0 \rightarrow M_1$, you can compute the image of ϕ , the kernel of ϕ , and using $y = \phi.lift(x)$ you can lift an elements x in M_1 to an element y in M_0 , if such a y exists.

TECHNICAL NOTE: For efficiency, we introduce a notion of optimized representation for quotient modules. The optimized representation of $M=V/W$ is the quotient V'/W' where V' has as basis lifts of the generators $g[i]$ for M . We internally store a morphism from $M_0=V_0/W_0$ to $M_1=V_1/W_1$ by giving a morphism from the optimized representation V_0' of M_0 to V_1 that sends W_0 into W_1 .

The following TUTORIAL illustrates several of the above points.

First we create free modules V_0 and W_0 and the quotient module M_0 . Notice that everything works fine even though V_0 and W_0 are not contained inside \mathbb{Z}^n , which is extremely convenient.

```
sage: V0 = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W0 = V0.span([V0.0+2*V0.1, 9*V0.
↪0+2*V0.1, 4*V0.2])
sage: M0 = V0/W0; M0
Finitely generated module V/W over Integer Ring with invariants (4, 16)
```

The invariants are computed using the Smith normal form algorithm, and determine the structure of this finitely generated module.

You can get the V and W used in constructing the quotient module using $V()$ and $W()$ methods:

```
sage: M0.V()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
```

(continues on next page)

(continued from previous page)

```
[1/2  0  0]
[  0  2  0]
[  0  0  1]
sage: M0.W()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  4  0]
[  0 32  0]
[  0  0  4]
```

We note that the optimized representation of M_0 , mentioned above in the technical note has a V that need not be equal to V_0 , in general.

```
sage: M0.optimized()[0].V()
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 0  8  1]
[ 0 -2  0]
```

Create elements of M_0 either by coercing in elements of V_0 , getting generators, or coercing in a list or tuple or coercing in 0. Finally, one can express an element as a linear combination of the smith form generators

```
sage: M0(V0.0)
(0, 2)
sage: M0(V0.0 + W0.0) # no difference modulo W0
(0, 2)
sage: M0.linear_combination_of_smith_form_gens([3,20])
(3, 4)
sage: 3*M0.0 + 20*M0.1
(3, 4)
```

We make an element of M_0 by taking a difference of two generators, and lift it. We also illustrate making an element from a list, which coerces to V_0 , then take the equivalence class modulo W_0 .

```
sage: x = M0.0 - M0.1; x
(1, 15)
sage: x.lift()
(0, 10, 1)
sage: M0(vector([1/2,0,0]))
(0, 2)
sage: x.additive_order()
16
```

Similarly, we construct V_1 and W_1 , and the quotient M_1 , in a completely different 2-dimensional ambient space.

```
sage: V1 = span([1/2,0],[3/2,2],ZZ); W1 = V1.span([2*V1.0, 3*V1.1])
sage: M1 = V1/W1; M1
Finitely generated module V/W over Integer Ring with invariants (6)
```

We create the homomorphism from M_0 to M_1 that sends both generators of M_0 to 3 times the generator of M_1 . This is well defined since 3 times the generator has order 2.

```
sage: f = M0.hom([3*M1.0, 3*M1.0]); f
Morphism from module over Integer Ring with invariants (4, 16) to module with invariants
↪(6,) that sends the generators to [(3), (3)]
```

We evaluate the homomorphism on our element x of the domain, and on the first generator of the domain. We also evaluate at an element of $V0$, which is coerced into $M0$.

```
sage: f(x)
(0)
sage: f(M0.0)
(3)
sage: f(V0.1)
(3)
```

Here we illustrate lifting an element of the image of f , i.e., finding an element of $M0$ that maps to a given element of $M1$:

```
sage: y = f.lift(3*M1.0)
sage: y # random
(0, 13)
sage: f(y)
(3)
```

We compute the kernel of f , i.e., the submodule of elements of $M0$ that map to 0. Note that the kernel is not explicitly represented as a submodule, but as another quotient V/W where V is contained in $V0$. You can explicitly coerce elements of the kernel into $M0$ though.

```
sage: K = f.kernel(); K
Finitely generated module V/W over Integer Ring with invariants (2, 16)

sage: M0(K.0)
(2, 8)
sage: M0(K.1)
(1, 5)
sage: f(M0(K.0))
(0)
sage: f(M0(K.1))
(0)
```

We compute the image of f .

```
sage: f.image()
Finitely generated module V/W over Integer Ring with invariants (2)
```

Notice how the elements of the image are written as (0) and (1), despite the image being naturally a submodule of $M1$, which has elements (0), (1), (2), (3), (4), (5). However, below we coerce the element (1) of the image into the codomain, and get (3):

```
sage: list(f.image())
[(0), (1)]
sage: list(M1)
[(0), (1), (2), (3), (4), (5)]
sage: x = f.image().0; x
(1)
```

(continues on next page)

(continued from previous page)

```
sage: M1(x)
(3)
```

AUTHOR:

- William Stein, 2009

```
sage.modules.fg_pid.fgp_module.FGP_Module(V, W, check=True)
```

INPUT:

- V – a free R -module
- W – a free R -submodule of V
- `check` – bool (default: `True`); if `True`, more checks on correctness are performed; in particular, we check the data types of V and W , and that W is a submodule of V with the same base ring.

OUTPUT:

- the quotient V / W as a finitely generated R -module

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪ 0+12*V.1, 4*V.2])
sage: import sage.modules.fg_pid.fgp_module
sage: Q = sage.modules.fg_pid.fgp_module.FGP_Module(V, W)
sage: type(Q)
<class 'sage.modules.fg_pid.fgp_module.FGP_Module_class_with_category'>
sage: Q is sage.modules.fg_pid.fgp_module.FGP_Module(V, W, check=False)
True
```

```
class sage.modules.fg_pid.fgp_module.FGP_Module_class(V, W, check=True)
```

Bases: `sage.modules.module.Module`

A finitely generated module over a PID presented as a quotient V / W .

INPUT:

- V – an R -module
- W – an R -submodule of V
- `check` – bool (default: `True`)

EXAMPLES:

```
sage: A = (ZZ^1)/span([[100]], ZZ); A
Finitely generated module V/W over Integer Ring with invariants (100)
sage: A.V()
Ambient free module of rank 1 over the principal ideal domain Integer Ring
sage: A.W()
Free module of degree 1 and rank 1 over Integer Ring
Echelon basis matrix:
[100]

sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ)
sage: W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
```

(continues on next page)

(continued from previous page)

```
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: type(Q)
<class 'sage.modules.fg_pid.fgp_module.FGP_Module_class_with_category'>
```

Element

alias of `sage.modules.fg_pid.fgp_element.FGP_Element`

V()

If this module was constructed as a quotient V/W , return V .

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.V()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  0]
[ 0  1  0]
[ 0  0  1]
```

W()

If this module was constructed as a quotient V/W , return W .

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.W()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  8  0]
[ 0  12  0]
[ 0  0  4]
```

annihilator()

Return the ideal of the base ring that annihilates `self`. This is precisely the ideal generated by the LCM of the invariants of `self` if `self` is finite, and is 0 otherwise.

EXAMPLES:

```
sage: V = span([[1/2, 0, 0], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([V.0+2*V.1, 9*V.
↪ 0+2*V.1, 4*V.2])
sage: Q = V/W; Q.annihilator()
Principal ideal (16) of Integer Ring
sage: Q.annihilator().gen()
16

sage: Q = V/V.span([V.0]); Q
Finitely generated module V/W over Integer Ring with invariants (0, 0)
sage: Q.annihilator()
Principal ideal (0) of Integer Ring
```

We check that [trac ticket #22720](#) is resolved:

```
sage: H=AdditiveAbelianGroup([])
sage: H.annihilator()
Principal ideal (1) of Integer Ring
```

base_ring()

Return the base ring of self.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.base_ring()
Integer Ring
```

cardinality()

Return the cardinality of this module as a set.

EXAMPLES:

```
sage: V = ZZ^2; W = V.span([[1,2],[3,4]]); A = V/W; A
Finitely generated module V/W over Integer Ring with invariants (2)
sage: A.cardinality()
2
sage: V = ZZ^2; W = V.span([[1,2]]); A = V/W; A
Finitely generated module V/W over Integer Ring with invariants (0)
sage: A.cardinality()
+Infinity
sage: V = QQ^2; W = V.span([[1,2]]); A = V/W; A
Vector space quotient V/W of dimension 1 over Rational Field where
V: Vector space of dimension 2 over Rational Field
W: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]
sage: A.cardinality()
+Infinity
```

construction()

The construction functor and ambient module for self.

EXAMPLES:

```
sage: W = ZZ^2
sage: A1 = W.submodule([[1,0]])
sage: B1 = W.submodule([[2,0]])
sage: T1 = A1 / B1
sage: T1.construction()
(QuotientModuleFunctor,
 Free module of degree 2 and rank 1 over Integer Ring
 Echelon basis matrix:
 [1 0])
```

coordinate_vector(x, reduce=False)

Return coordinates of x with respect to the optimized representation of self.

INPUT:

- x – element of self
- `reduce` – (default: False); if True, reduce coefficients modulo invariants; this is ignored if the base ring is not ZZ.

OUTPUT:

The coordinates as a vector. That is, the same type as `self.V()`, but in general with fewer entries.

EXAMPLES:

```
sage: V = span([[1/4,0,0],[3/4,4,2],[0,0,2]],ZZ); W = V.span([4*V.0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 0, 0)
sage: Q.coordinate_vector(-Q.0)
(-1, 0, 0)
sage: Q.coordinate_vector(-Q.0, reduce=True)
(3, 0, 0)
```

If x is not in self, it is coerced in:

```
sage: Q.coordinate_vector(V.0)
(1, -3, 0)
sage: Q.coordinate_vector(Q(V.0))
(1, -3, 0)
```

cover()

If this module was constructed as V/W , return the cover module V .

This is the same as `self.V()`.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.V()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  0  0]
[  0  1  0]
[  0  0  1]
```

gen(i)

Return the i -th generator of self.

INPUT:

- i – integer

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↪ 0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.gen(0)
```

(continues on next page)

(continued from previous page)

```
(1, 0)
sage: Q.gen(1)
(0, 1)
sage: Q.gen(2)
Traceback (most recent call last):
...
ValueError: Generator 2 not defined
sage: Q.gen(-1)
Traceback (most recent call last):
...
ValueError: Generator -1 not defined
```

gens()

Returns tuple of elements g_0, \dots, g_n of self such that the module generated by the g_i is isomorphic to the direct sum of $R/e_i R$, where e_i are the invariants of self and R is the base ring.

Note that these are not generally uniquely determined, and depending on how Smith normal form is implemented for the base ring, they may not even be deterministic.

This can safely be overridden in all derived classes.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.gens()
((1, 0), (0, 1))
sage: Q.0
(1, 0)
```

gens_to_smith()

Return the transformation matrix from the user to Smith form generators.

To go in the other direction use [smith_to_gens\(\)](#).

OUTPUT:

- a matrix over the base ring

EXAMPLES:

```
sage: L2 = IntegralLattice(3 * matrix([[ -2, 0, 0], [0, 1, 0], [0, 0, -4]]))
sage: D = L2.discriminant_group().normal_form()
sage: D
Finite quadratic module over Integer Ring with invariants (3, 6, 12)
Gram matrix of the quadratic form with values in Q/Z:
[1/2  0  0  0  0]
[ 0 1/4  0  0  0]
[ 0  0 1/3  0  0]
[ 0  0  0 1/3  0]
[ 0  0  0  0 2/3]
sage: D.gens_to_smith()
[0 3 0]
[0 0 3]
[0 4 0]
```

(continues on next page)

(continued from previous page)

```

[1 2 0]
[0 0 4]
sage: T = D.gens_to_smith()*D.smith_to_gens()
sage: T
[ 3  0  3  0  0]
[ 0 33  0  0  3]
[ 4  0  4  0  0]
[ 2  0  3  1  0]
[ 0 44  0  0  4]

```

The matrix T now satisfies a certain congruence:

```

sage: for i in range(T.nrows()):
.....:     T[:,i] = T[:,i] % D.gens()[i].order()
sage: T
[1 0 0 0 0]
[0 1 0 0 0]
[0 0 1 0 0]
[0 0 0 1 0]
[0 0 0 0 1]

```

gens_vector(x , *reduce=False*)

Return coordinates of x with respect to the generators.

INPUT:

- x – element of self
- *reduce* – (default: False); if True, reduce coefficients modulo invariants; this is ignored if the base ring is not \mathbb{Z}

EXAMPLES:

We create a derived class and overwrite `gens()`:

```

sage: from sage.modules.fg_pid.fgp_module import FGP_Module_class
sage: W = ZZ^3
sage: V = W.span(matrix.diagonal([1/6, 1/3, 1/12]))
sage: class FGP_with_gens(FGP_Module_class):
.....:     def __init__(self, V, W, gens):
.....:         FGP_Module_class.__init__(self, V, W)
.....:         self._gens = tuple([self(g) for g in gens])
.....:     def gens(self):
.....:         return self._gens
sage: gens = [(1/2, 0, 0), (0, 0, 1/4), (1/3, 0, 0), (0, 1/3, 0), (0, 0, 2/3)]
sage: gens = [V(g) for g in gens]
sage: D = FGP_with_gens(V, W, gens)
sage: D.gens()
((0, 3, 0), (0, 0, 3), (0, 4, 0), (1, 2, 0), (0, 0, 8))

```

We create some element of D :

```

sage: x = D.linear_combination_of_smith_form_gens((1,2,3))
sage: x
(1, 2, 3)

```

In our generators:

```
sage: v = D.gens_vector(x)
sage: v
(2, 9, 3, 1, 33)
```

The output can be further reduced:

```
sage: D.gens_vector(x, reduce=True)
(0, 1, 0, 1, 0)
```

Let us check:

```
sage: x == sum(v[i]*D.gen(i) for i in range(len(D.gens())))
True
```

`has_canonical_map_to(A)`

Return True if `self` has a canonical map to `A`, relative to the given presentation of `A`.

This means that `A` is a finitely generated quotient module, `self.V()` is a submodule of `A.V()` and `self.W()` is a submodule of `A.W()`, i.e., that there is a natural map induced by inclusion of the `V`'s. Note that we do *not* require that this natural map be injective; for this use `is_submodule()`.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: A = Q.submodule((Q.0, Q.0 + 3*Q.1)); A
Finitely generated module V/W over Integer Ring with invariants (4, 4)
sage: A.has_canonical_map_to(Q)
True
sage: Q.has_canonical_map_to(A)
False
```

`hom(im_gens, codomain=None, check=True)`

Homomorphism defined by giving the images of `self.gens()` in some fixed fg R-module.

Note: We do not assume that the generators given by `self.gens()` are the same as the Smith form generators, since this may not be true for a general derived class.

INPUT:

- `im_gens` – a list of the images of `self.gens()` in some R-module

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2])
sage: Q = V/W
sage: phi = Q.hom([3*Q.1, Q.0])
sage: phi
Morphism from module over Integer Ring with invariants (4, 12) to module with
↪invariants (4, 12) that sends the generators to [(0, 3), (1, 0)]
```

(continues on next page)

(continued from previous page)

```
sage: phi(Q.0)
(0, 3)
sage: phi(Q.1)
(1, 0)
sage: Q.0 == phi(Q.1)
True
```

This example illustrates creating a morphism to a free module. The free module is turned into an FGP module (i.e., quotient V/W with $W=0$), and the morphism is constructed:

```
sage: V = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (2, 0, 0)
sage: phi = Q.hom([0,V.0,V.1]); phi
Morphism from module over Integer Ring with invariants (2, 0, 0) to module with
↳ invariants (0, 0, 0) that sends the generators to [(0, 0, 0), (1, 0, 0), (0,
↳ 1, 0)]
sage: phi.domain()
Finitely generated module V/W over Integer Ring with invariants (2, 0, 0)
sage: phi.codomain()
Finitely generated module V/W over Integer Ring with invariants (0, 0, 0)
sage: phi(Q.0)
(0, 0, 0)
sage: phi(Q.1)
(1, 0, 0)
sage: phi(Q.2) == V.1
True
```

Constructing two zero maps from the zero module:

```
sage: A = (ZZ^2)/(ZZ^2); A
Finitely generated module V/W over Integer Ring with invariants ()
sage: A.hom([])
Morphism from module over Integer Ring with invariants () to module with
↳ invariants () that sends the generators to []
sage: A.hom([]).codomain() is A
True
sage: B = (ZZ^3)/(ZZ^3)
sage: A.hom([],codomain=B)
Morphism from module over Integer Ring with invariants () to module with
↳ invariants () that sends the generators to []
sage: phi = A.hom([],codomain=B); phi
Morphism from module over Integer Ring with invariants () to module with
↳ invariants () that sends the generators to []
sage: phi(A(0))
()
sage: phi(A(0)) == B(0)
True
```

A degenerate case:

```
sage: A = (ZZ^2)/(ZZ^2)
sage: phi = A.hom([]); phi
```

(continues on next page)

(continued from previous page)

```
Morphism from module over Integer Ring with invariants () to module with
↳ invariants () that sends the generators to []
sage: phi(A(0))
()
```

The code checks that the morphism is valid. In the example below we try to send a generator of order 2 to an element of order 14:

```
sage: V = span([[1/14, 3/14], [0, 1/2]], ZZ); W = ZZ^2
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (2, 14)
sage: Q.linear_combination_of_smith_form_gens([1, 11]).additive_order()
14
sage: f = Q.hom([Q.linear_combination_of_smith_form_gens([1, 11]), Q.linear_
↳ combination_of_smith_form_gens([1, 3])]); f
Traceback (most recent call last):
...
ValueError: phi must send optimized submodule of M.W() into N.W()
```

invariants(include_ones=False)

Return the diagonal entries of the smith form of the relative matrix that defines `self` (see `_relative_matrix()`) padded with zeros, excluding 1's by default. Thus if `v` is the list of integers returned, then `self` is abstractly isomorphic to the product of cyclic groups Z/nZ where n is in `v`.

INPUT:

- `include_ones` – bool (default: False); if True, also include 1's in the output list.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↳ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.invariants()
(4, 12)
```

An example with 1 and 0 rows:

```
sage: V = ZZ^3; W = V.span([[1, 2, 0], [0, 1, 0], [0, 2, 0]]); Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (0)
sage: Q.invariants()
(0,)
sage: Q.invariants(include_ones=True)
(1, 1, 0)
```

is_finite()

Return True if `self` is finite and False otherwise.

EXAMPLES:

```
sage: V = span([[1/2, 0, 0], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([V.0+2*V.1, 9*V.
↳ 0+2*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 16)
sage: Q.is_finite()
```

(continues on next page)

(continued from previous page)

```

True
sage: Q = V/V.zero_submodule(); Q
Finitely generated module V/W over Integer Ring with invariants (0, 0, 0)
sage: Q.is_finite()
False

```

is_submodule(A)

Return True if self is a submodule of A.

More precisely, this returns True if `self.V()` is a submodule of `A.V()`, with `self.W()` equal to `A.W()`.

Compare [`has_canonical_map_to\(\)`](#).

EXAMPLES:

```

sage: V = ZZ^2; W = V.span([[1,2]]); W2 = W.scale(2)
sage: A = V/W; B = W/W2
sage: B.is_submodule(A)
False
sage: A = V/W2; B = W/W2
sage: B.is_submodule(A)
True

```

This example illustrates that this command works in a subtle cases.:

```

sage: A = ZZ^1
sage: Q3 = A / A.span([[3]])
sage: Q6 = A / A.span([[6]])
sage: Q6.is_submodule(Q3)
False
sage: Q6.has_canonical_map_to(Q3)
True
sage: Q = A.span([[2]]) / A.span([[6]])
sage: Q.is_submodule(Q6)
True

```

linear_combination_of_smith_form_gens(x)

Compute a linear combination of the optimised generators of this module as returned by [`smith_form_gens\(\)`](#).

EXAMPLES:

```

sage: X = ZZ**2 / span([[3,0],[0,2]], ZZ)
sage: X.linear_combination_of_smith_form_gens([1])
(1)

```

list()

Return a list of the elements of self.

EXAMPLES:

```

sage: V = ZZ^2; W = V.span([[1,2],[3,4]])
sage: list(V/W)
[(0), (1)]

```

ngens()

Return the number of generators of `self`.

(Note for developers: This is just the length of `gens()`, rather than of the minimal set of generators as returned by `smith_form_gens()`; these are the same in the `FGP_Module_class`, but not necessarily in derived classes.)

EXAMPLES:

```
sage: A = (ZZ**2) / span([[4,0],[0,3]], ZZ)
sage: A.ngens()
1
```

This works (but please do not do it in production code!)

```
sage: A.gens = lambda: [1,2,"Barcelona!"]
sage: A.ngens()
3
```

optimized()

Return a module isomorphic to this one, but with `V` replaced by a submodule of `V` such that the generators of `self` all lift trivially to generators of `V`. Replace `W` by the intersection of `V` and `W`. This has the advantage that `V` has small dimension and any homomorphism from `self` trivially extends to a homomorphism from `V`.

OUTPUT:

- `Q` – an optimized quotient V_0/W_0 with V_0 a submodule of V such that $\text{phi}: V_0/W_0 \rightarrow V/W$ is an isomorphism
- `Z` – matrix such that if x is in `self.V()` and c gives the coordinates of x in terms of the basis for `self.V()`, then $c*Z$ is in V_0 and $c*Z$ maps to x via phi above.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  0+12*V.1, 4*V.2])
sage: Q = V/W
sage: O, X = Q.optimized(); O
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: O.V()
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 0  3  1]
[ 0 -1  0]
sage: O.W()
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[ 0 12  0]
[ 0  0  4]
sage: X          # random
[0 4 0]
[0 1 0]
[0 0 1]
sage: OV = O.V()
sage: Q(OV([0,-8,0])) == V.0
True
```

(continues on next page)

(continued from previous page)

```
sage: Q(OV([0,1,0])) == V.1
True
sage: Q(OV([0,0,1])) == V.2
True
```

quotient_map()

Given this quotient space $Q = V/W$, return the natural quotient map from V to Q .

EXAMPLES:

```
sage: A = (ZZ**2) / span([[4,0],[0,3]], ZZ)
sage: A.quotient_map()
Coercion map:
  From: Ambient free module of rank 2 over the principal ideal domain Integer_
  ↪ Ring
  To:   Finitely generated module V/W over Integer Ring with invariants (12)
```

random_element(*args, **kws)

Create a random element of $\text{self} = V/W$, by creating a random element of V and reducing it modulo W .

All arguments are passed onto the method `random_element()` of V .

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.random_element().parent() is Q
True
sage: Q.cardinality()
48
sage: S = set()
sage: while len(S) < 48:
.....:     S.add(Q.random_element())
```

relations()

If self was constructed as V / W , return the relations module W .

This is the same as `self.W()`.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]], ZZ)
sage: W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V / W
sage: Q.relations()
Free module of degree 3 and rank 3 over Integer Ring
Echelon basis matrix:
[1/2  8  0]
[ 0 12  0]
[ 0  0  4]
```

smith_form_gen(i)

Return the i -th generator of self .

This is a separate method so we can freely override `gen()` in derived classes.

INPUT:

- i – integer

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ)
sage: W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.smith_form_gen(0)
(1, 0)
sage: Q.smith_form_gen(1)
(0, 1)
```

smith_form_gens()

Return a set of generators for self which are in Smith normal form.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.0+12*V.1, 4*V.2])
sage: Q = V/W
sage: Q.smith_form_gens()
((1, 0), (0, 1))
sage: [x.lift() for x in Q.smith_form_gens()]
[(0, 3, 1), (0, -1, 0)]
```

smith_to_gens()

Return the transformation matrix from Smith form to user generators.

To go in the other direction use [gens_to_smith\(\)](#).

OUTPUT:

- a matrix over the base ring

EXAMPLES:

```
sage: L2 = IntegralLattice(3 * matrix([[-2, 0, 0], [0, 1, 0], [0, 0, -4]]))
sage: D = L2.discriminant_group().normal_form()
sage: D
Finite quadratic module over Integer Ring with invariants (3, 6, 12)
Gram matrix of the quadratic form with values in Q/Z:
[1/2  0  0  0  0]
[ 0 1/4  0  0  0]
[ 0  0 1/3  0  0]
[ 0  0  0 1/3  0]
[ 0  0  0  0 2/3]
sage: D.smith_to_gens()
[ 0  0  1  1  0]
[ 1  0  1  0  0]
[ 0 11  0  0  1]
sage: T = D.smith_to_gens()*D.gens_to_smith()
sage: T
[ 1  6  0]
[ 0  7  0]
[ 0  0 37]
```

This matrix satisfies the congruence:

```
sage: for i in range(T.ncols()):
.....:     T[:, i] = T[:, i] % D.smith_form_gens()[i].order()
sage: T
[1 0 0]
[0 1 0]
[0 0 1]
```

We create some element of our FGP module:

```
sage: x = D.linear_combination_of_smith_form_gens((1,2,3))
sage: x
(1, 2, 3)
```

and want to know some (it is not unique) linear combination of the user defined generators that is x:

```
sage: x.vector() * D.smith_to_gens()
(2, 33, 3, 1, 3)
```

submodule(x)

Return the submodule defined by x.

INPUT:

- x – list, tuple, or FGP module

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↪ 0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.gens()
((1, 0), (0, 1))
```

We create submodules generated by a list or tuple of elements:

```
sage: Q.submodule([Q.0])
Finitely generated module V/W over Integer Ring with invariants (4)
sage: Q.submodule([Q.1])
Finitely generated module V/W over Integer Ring with invariants (12)
sage: Q.submodule((Q.0, Q.0 + 3*Q.1))
Finitely generated module V/W over Integer Ring with invariants (4, 4)
```

A submodule defined by a submodule:

```
sage: A = Q.submodule((Q.0, Q.0 + 3*Q.1)); A
Finitely generated module V/W over Integer Ring with invariants (4, 4)
sage: Q.submodule(A)
Finitely generated module V/W over Integer Ring with invariants (4, 4)
```

Inclusion is checked:

```
sage: A.submodule(Q)
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: x.V() must be contained in self's V.
```

`sage.modules.fg_pid.fgp_module.is_FGP_Module(x)`

Return True if x is an FGP module, i.e., a finitely generated module over a PID represented as a quotient of finitely generated free modules over a PID.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2]); Q = V/W
sage: sage.modules.fg_pid.fgp_module.is_FGP_Module(V)
False
sage: sage.modules.fg_pid.fgp_module.is_FGP_Module(Q)
True
```

`sage.modules.fg_pid.fgp_module.random_fgp_module(n, R=Integer Ring, finite=False)`

Return a random FGP module inside a rank n free module over R .

INPUT:

- n – nonnegative integer
- R – base ring (default: \mathbb{Z})
- finite – bool (default: True); if True, make the random module finite.

EXAMPLES:

```
sage: import sage.modules.fg_pid.fgp_module as fgp
sage: fgp.random_fgp_module(4)
Finitely generated module V/W over Integer Ring with invariants (...)
```

In most cases the cardinality is small or infinite:

```
sage: for g in (1, 2, 3, +Infinity):
.....:     while fgp.random_fgp_module(4).cardinality() != 1:
.....:         pass
```

One can force a finite module:

```
sage: fgp.random_fgp_module(4, finite=True).is_finite()
True
```

Larger finite modules appear:

```
sage: while fgp.random_fgp_module(4, finite=True).cardinality() < 100:
.....:     pass
```

`sage.modules.fg_pid.fgp_module.random_fgp_morphism_0(*args, **kws)`

Construct a random fgp module using `random_fgp_module()`, then construct a random morphism that sends each generator to a random multiple of itself.

Inputs are the same as to `random_fgp_module()`.

EXAMPLES:

```
sage: import sage.modules.fg_pid.fgp_module as fgp
sage: mor = fgp.random_fgp_morphism_0(4)
sage: mor.domain() == mor.codomain()
True
sage: fgp.is_FGP_Module(mor.domain())
True
```

Each generator is sent to a random multiple of itself:

```
sage: gens = mor.domain().gens()
sage: im_gens = mor.im_gens()
sage: all(im_gens[i] == sum(im_gens[i])*gens[i] for i in range(len(gens)))
True
```

4.2 Elements of finitely generated modules over a PID

AUTHOR:

- William Stein, 2009

class sage.modules.fg_pid.fgp_element.FGP_Element(*parent, x, check=True*)

Bases: sage.structure.element.ModuleElement

An element of a finitely generated module over a PID.

INPUT:

- *parent* – parent module *M*
- *x* – element of *M.V()*

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪ 0+12*V.1, 4*V.2])
sage: Q = V/W
sage: x = Q(V.0-V.1); x #indirect doctest
(0, 9)
sage: isinstance(x, sage.modules.fg_pid.fgp_element.FGP_Element)
True
sage: type(x)
<class 'sage.modules.fg_pid.fgp_module.FGP_Module_class_with_category.element_class
↪ '>
sage: x is Q(x)
True
sage: x.parent() is Q
True
```

additive_order()

Return the additive order of this element.

EXAMPLES:

```

sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↳ 0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.0.additive_order()
4
sage: Q.1.additive_order()
12
sage: (Q.0+Q.1).additive_order()
12
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↳ 0+12*V.1])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (12, 0)
sage: Q.0.additive_order()
12
sage: type(Q.0.additive_order())
<class 'sage.rings.integer.Integer'>
sage: Q.1.additive_order()
+Infinity

```

lift()

Lift self to an element of V , where the parent of self is the quotient module V/W .

EXAMPLES:

```

sage: V = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↳ 0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.0
(1, 0)
sage: Q.1
(0, 1)
sage: Q.0.lift()
(0, 6, 1)
sage: Q.1.lift()
(0, -2, 0)
sage: x = Q(V.0); x
(0, 8)
sage: x.lift()
(1/2, 0, 0)
sage: x == 8*Q.1
True
sage: x.lift().parent() == V
True

```

A silly version of the integers modulo 100:

```

sage: A = (ZZ^1)/span([[100]], ZZ); A
Finitely generated module V/W over Integer Ring with invariants (100)
sage: x = A([5]); x
(5)
sage: v = x.lift(); v

```

(continues on next page)

(continued from previous page)

```
(5)
sage: v.parent()
Ambient free module of rank 1 over the principal ideal domain Integer Ring
```

vector()

EXAMPLES:

```
sage: V = span([[1/2,0,0],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: x = Q.0 + 3*Q.1; x
(1, 3)
sage: x.vector()
(1, 3)
sage: tuple(x)
(1, 3)
sage: list(x)
[1, 3]
sage: x.vector().parent()
Ambient free module of rank 2 over the principal ideal domain Integer Ring
```

4.3 Morphisms between finitely generated modules over a PID

AUTHOR:

- William Stein, 2009

```
sage.modules.fg_pid.fgp_morphism.FGP_Homset(X, Y)
```

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2]); Q = V/W
sage: Q.Hom(Q) # indirect doctest
Set of Morphisms from Finitely generated module V/W over Integer Ring with
↪invariants (4, 12) to Finitely generated module V/W over Integer Ring with
↪invariants (4, 12) in Category of modules over Integer Ring
sage: True # Q.Hom(Q) is Q.Hom(Q)
True
sage: type(Q.Hom(Q))
<class 'sage.modules.fg_pid.fgp_morphism.FGP_Homset_class_with_category'>
```

```
class sage.modules.fg_pid.fgp_morphism.FGP_Homset_class(X, Y, category=None)
```

Bases: `sage.categories.homset.Homset`Homsets of *FGP_Module***Element**alias of *FGP_Morphism*

```
class sage.modules.fg_pid.fgp_morphism.FGP_Morphism(parent, phi, check=True)
```

Bases: `sage.categories.morphism.Morphism`

A morphism between finitely generated modules over a PID.

EXAMPLES:

An endomorphism:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: phi = Q.hom([Q.0+3*Q.1, -Q.1]); phi
Morphism from module over Integer Ring with invariants (4, 12) to module with
↪invariants (4, 12) that sends the generators to [(1, 3), (0, 11)]
sage: phi(Q.0) == Q.0 + 3*Q.1
True
sage: phi(Q.1) == -Q.1
True
```

A morphism between different modules $V_1/W_1 \rightarrow V_2/W_2$ in different ambient spaces:

```
sage: V1 = ZZ^2; W1 = V1.span([[1,2],[3,4]]); A1 = V1/W1
sage: V2 = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W2 = V2.span([2*V2.0+4*V2.1,
↪9*V2.0+12*V2.1, 4*V2.2]); A2=V2/W2
sage: A1
Finitely generated module V/W over Integer Ring with invariants (2)
sage: A2
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: phi = A1.hom([2*A2.0])
sage: phi(A1.0)
(2, 0)
sage: 2*A2.0
(2, 0)
sage: phi(2*A1.0)
(0, 0)
```

im_gens()

Return tuple of the images of the generators of the domain under this morphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2]); Q = V/W
sage: phi = Q.hom([Q.0,Q.0 + 2*Q.1])
sage: phi.im_gens()
((1, 0), (1, 2))
sage: phi.im_gens() is phi.im_gens()
True
```

image()

Compute the image of this homomorphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
↪0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
```

(continues on next page)

(continued from previous page)

```
sage: Q.hom([Q.0+3*Q.1, -Q.1]).image()
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.hom([3*Q.1, Q.1]).image()
Finitely generated module V/W over Integer Ring with invariants (12)
```

inverse_image(A)

Given a submodule A of the codomain of this morphism, return the inverse image of A under this morphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↪ 0+12*V.1, 4*V.2]); Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: phi = Q.hom([0, Q.1])
sage: phi.inverse_image(Q.submodule([]))
Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi.kernel()
Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi.inverse_image(phi.codomain())
Finitely generated module V/W over Integer Ring with invariants (4, 12)

sage: phi.inverse_image(Q.submodule([Q.0]))
Finitely generated module V/W over Integer Ring with invariants (4)
sage: phi.inverse_image(Q.submodule([Q.1]))
Finitely generated module V/W over Integer Ring with invariants (4, 12)

sage: phi.inverse_image(ZZ^3)
Traceback (most recent call last):
...
TypeError: A must be a finitely generated quotient module
sage: phi.inverse_image(ZZ^3 / W.scale(2))
Traceback (most recent call last):
...
ValueError: A must be a submodule of the codomain
```

kernel()

Compute the kernel of this homomorphism.

EXAMPLES:

```
sage: V = span([[1/2,1,1],[3/2,2,1],[0,0,1]],ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↪ 0+12*V.1, 4*V.2])
sage: Q = V/W; Q
Finitely generated module V/W over Integer Ring with invariants (4, 12)
sage: Q.hom([0, Q.1]).kernel()
Finitely generated module V/W over Integer Ring with invariants (4)
sage: A = Q.hom([Q.0, 0]).kernel(); A
Finitely generated module V/W over Integer Ring with invariants (12)
sage: Q.1 in A
True
sage: phi = Q.hom([Q.0-3*Q.1, Q.0+Q.1])
sage: A = phi.kernel(); A
Finitely generated module V/W over Integer Ring with invariants (4)
```

(continues on next page)

(continued from previous page)

```
sage: phi(A)
Finitely generated module V/W over Integer Ring with invariants ()
```

lift(x)

Given an element x in the codomain of self, if possible find an element y in the domain such that $\text{self}(y) == x$. Raise a `ValueError` if no such y exists.

INPUT:

- x – element of the codomain of self.

EXAMPLES:

```
sage: V = span([[1/2, 1, 1], [3/2, 2, 1], [0, 0, 1]], ZZ); W = V.span([2*V.0+4*V.1, 9*V.
  ↳ 0+12*V.1, 4*V.2])
sage: Q=V/W; phi = Q.hom([2*Q.0, Q.1])
sage: phi.lift(Q.1)
(0, 1)
sage: phi.lift(Q.0)
Traceback (most recent call last):
...
ValueError: no lift of element to domain
sage: phi.lift(2*Q.0)
(1, 0)
sage: phi.lift(2*Q.0+Q.1)
(1, 1)
sage: V = span([[5, -1/2]], ZZ); W = span([2*0, -2], ZZ); Q = V/W; phi=Q.hom([2*Q.
  ↳ 0])
sage: x = phi.image().0; phi(phi.lift(x)) == x
True
```

FINITELY PRESENTED GRADED MODULES

5.1 Finitely generated free graded left modules over connected graded algebras

Let A be a connected graded algebra. Some methods here require in addition that A be an algebra over a field or a PID and that Sage has a description of a basis for A .

For example, let p be a prime number. The mod p Steenrod algebra A_p is a connected algebra over the finite field of p elements. Many of the modules presented here will be defined over A_p , or one of its sub-Hopf algebras. E.g.:

```
sage: A = SteenrodAlgebra(p=2)
```

However, the current implementation can use any connected graded algebra that has a graded basis where each graded part is finite dimensional. Another good family is the exterior algebras:

```
sage: E.<x,y,z> = ExteriorAlgebra(QQ)
```

A free module is defined by the graded algebra and an ordered tuple of degrees for the generators:

```
sage: M = A.free_graded_module(generator_degrees=(0,1))
sage: M
Free graded left module on 2 generators over
mod 2 Steenrod algebra, milnor basis

sage: F.<a,b,c> = E.free_graded_module((0,3,6))
sage: F
Free graded left module on 3 generators over
The exterior algebra of rank 3 over Rational Field
```

The resulting free modules will have generators in the degrees as specified:

```
sage: M.generator_degrees()
(0, 1)
sage: F.generator_degrees()
(0, 3, 6)
```

The default names for the generators are $g[\text{degree}]$ if they are in distinct degrees, $g[\text{degree}, i]$ otherwise. They can be given other names, as was done when creating the module F :

```
sage: M.generators()
(g[0], g[1])
```

(continues on next page)

(continued from previous page)

```
sage: F.generators()
(a, b, c)
```

The connectivity of a module over a connected graded algebra is the minimum degree of all its module generators. Thus, if the module is non-trivial, the connectivity is an integer:

```
sage: M.connectivity()
0
```

5.1.1 Module elements

For an A -module with generators $\{g_i\}_{i=1}^N$, any homogeneous element of degree n has the form

$$x = \sum_{i=1}^N a_i \cdot g_i,$$

where $a_i \in A_{n-\deg(g_i)}$ for all i . The ordered set $\{a_i\}$ is referred to as the coefficients of x .

You can produce module elements from a given set of coefficients:

```
sage: coeffs = [Sq(5), Sq(1,1)]
sage: x = M(coeffs); x
Sq(5)*g[0] + Sq(1,1)*g[1]
```

You can also use the module action:

```
sage: Sq(2) * x
(Sq(4,1)+Sq(7))*g[0] + Sq(3,1)*g[1]
```

Each non-zero element has a well-defined degree:

```
sage: x.degree()
5
```

However the zero element does not:

```
sage: zero = M.zero(); zero
0
sage: zero.degree()
Traceback (most recent call last):
...
ValueError: the zero element does not have a well-defined degree
```

Any two elements can be added as long as they are in the same degree:

```
sage: y = M.an_element(5); y
Sq(2,1)*g[0] + Sq(4)*g[1]
sage: x + y
(Sq(2,1)+Sq(5))*g[0] + (Sq(1,1)+Sq(4))*g[1]
```

or when at least one of them is zero:

```
sage: x + zero == x
True
```

Finally, additive inverses exist:

```
sage: x - x
0
```

For every integer n , the set of module elements of degree n form a free module over the ground ring k . A basis for this free module can be computed:

```
sage: M.basis_elements(5)
(Sq(2,1)*g[0], Sq(5)*g[0], Sq(1,1)*g[1], Sq(4)*g[1])
```

together with a corresponding free module presentation:

```
sage: M.vector_presentation(5)
Vector space of dimension 4 over Finite Field of size 2
```

Given any element, its coordinates with respect to this basis can be computed:

```
sage: v = x.vector_presentation(); v
(0, 1, 1, 0)
```

Going the other way, any element can be constructed by specifying its coordinates:

```
sage: x_ = M.element_from_coordinates((0,1,1,0), 5)
sage: x_
Sq(5)*g[0] + Sq(1,1)*g[1]
sage: x_ == x
True
```

5.1.2 Module homomorphisms

Homomorphisms of free graded A -modules $M \rightarrow N$ are linear maps of their underlying free k -module which commute with the A -module structure.

To create a homomorphism, first create the object modeling the set of all such homomorphisms using the free function `Hom`:

```
sage: M = A.free_graded_module((0,1))
sage: N.<c2> = A.free_graded_module((2,))
sage: homspace = Hom(M, N); homspace
Set of Morphisms from Free graded left module on 2 generators
over mod 2 Steenrod algebra, milnor basis
to Free graded left module on 1 generator
over mod 2 Steenrod algebra, milnor basis
in Category of finite dimensional graded modules with basis
over mod 2 Steenrod algebra, milnor basis
```

Just as module elements, homomorphisms are created using the `homspace` object. The only argument is a list of module elements in the codomain, corresponding to the module generators of the domain:

```
sage: values = [Sq(2)*c2, Sq(2)*Sq(1)*c2]
sage: f = homspace(values)
```

The resulting homomorphism is the one sending the i -th generator of the domain to the i -th codomain value given:

```
sage: f
Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor basis
  To:   Free graded left module on 1 generator over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> Sq(2)*c2
        g[1] |--> (Sq(0,1)+Sq(3))*c2
```

Convenience methods exist for creating the trivial morphism:

```
sage: homspace.zero()
Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor basis
  To:   Free graded left module on 1 generator over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> 0
        g[1] |--> 0
```

as well as the identity endomorphism:

```
sage: Hom(M, M).identity()
Module endomorphism of Free graded left module on 2 generators over mod 2 Steenrod
↪ algebra, milnor basis
  Defn: g[0] |--> g[0]
        g[1] |--> g[1]
```

Homomorphisms can be evaluated on elements of the domain module:

```
sage: v1 = f(Sq(7)*M.generator(0)); v1
Sq(3,2)*c2

sage: v2 = f(Sq(17)*M.generator(1)); v2
(Sq(11,3)+Sq(13,0,1)+Sq(17,1))*c2
```

and they respect the module action:

```
sage: v1 == Sq(7)*f(M.generator(0))
True

sage: v2 == Sq(17)*f(M.generator(1))
True
```

Any non-trivial homomorphism has a well-defined degree:

```
sage: f.degree()
4
```

but just as module elements, the trivial homomorphism does not:

```
sage: zero_map = homspace.zero()
sage: zero_map.degree()
```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
ValueError: the zero morphism does not have a well-defined degree
```

Any two homomorphisms can be added as long as they are of the same degree:

```
sage: f2 = homspace([Sq(2)*c2, Sq(3)*c2])
sage: f + f2
Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor basis
  To:   Free graded left module on 1 generator over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> 0
        g[1] |--> Sq(0,1)*c2
```

or when at least one of them is zero:

```
sage: f + zero_map == f
True
```

Finally, additive inverses exist:

```
sage: f - f == 0
True
```

The restriction of a homomorphism to the free module of n -dimensional module elements is a linear transformation:

```
sage: f_4 = f.vector_presentation(4); f_4
Vector space morphism represented by the matrix:
[0 1 0]
[1 1 1]
[0 1 0]
[0 0 0]
Domain: Vector space of dimension 4 over Finite Field of size 2
Codomain: Vector space of dimension 3 over Finite Field of size 2
```

This is compatible with the vector presentations of its domain and codomain modules:

```
sage: f.domain() is M
True
sage: f.codomain() is N
True
sage: f_4.domain() is M.vector_presentation(4)
True
sage: f_4.codomain() is N.vector_presentation(4 + f.degree())
True
```

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

```
class sage.modules.fp_graded.free_module.FreeGradedModule(algebra, generator_degrees, category,
                                                         names=None, **kws)
```

Bases: `sage.combinat.free_module.CombinatorialFreeModule`

Create a finitely generated free graded module over a connected graded algebra, with generators in specified degrees.

INPUT:

- `algebra` – the graded connected algebra over which the module is defined; this algebra must be equipped with a graded basis
- `generator_degrees` – tuple of integers defining the number of generators of the module, and their degrees
- `names` – optional, the names of the generators. If `names` is a comma-separated string like 'a, b, c', then those will be the names. Otherwise, for example if `names` is `abc`, then the names will be `abc(d, i)`.

By default, if all generators are in distinct degrees, then the names of the generators will have the form `g_{d}` where `d` is the degree of the generator. If the degrees are not distinct, then the generators will be called `g_{d,i}` where `d` is the degree and `i` is its index in the list of generators in that degree.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: E.<x,y,z> = ExteriorAlgebra(QQ)
sage: M = FreeGradedModule(E, (-1,3))
sage: M
Free graded left module on 2 generators over
The exterior algebra of rank 3 over Rational Field
sage: M.generator_degrees()
(-1, 3)
sage: a, b = M.generators()
sage: (x*y*b).degree()
5
```

names of generators:

```
sage: M.generators()
(g[-1], g[3])
sage: FreeGradedModule(E, (0, 0, 2)).generators()
(g[0, 0], g[0, 1], g[2, 0])
sage: FreeGradedModule(E, (0, 0, 2), names='x, y, z').generators()
(x, y, z)
sage: FreeGradedModule(E, (0, 0, 2), names='xyz').generators()
(xyz[0, 0], xyz[0, 1], xyz[2, 0])
```

names can also be defined implicitly using Sage's `M.<...>` syntax:

```
sage: A = SteenrodAlgebra(2)
sage: M.<x,y,z> = FreeGradedModule(A, (-2,2,4))
sage: M
Free graded left module on 3 generators over
mod 2 Steenrod algebra, milnor basis
sage: M.gens()
(x, y, z)
```

Element

alias of `sage.modules.fp_graded.free_element.FreeGradedModuleElement`

an_element(*n=None*)

Return an element of `self`.

This function chooses deterministically an element of the module in the given degree.

INPUT:

- *n* – (optional) the degree of the element to construct

OUTPUT:

An element (of the given degree if specified).

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (0,2,4))
sage: M.an_element(172)
Sq(0,0,2,0,1,0,1)*g[0] + Sq(0,4,0,0,1,0,1)*g[2] + Sq(7,1,0,0,1,0,1)*g[4]
```

Zero is the only element in the trivial module:

```
sage: FreeGradedModule(A, ()).an_element()
0
```

basis_elements(*n*)

Return a basis for the free module of degree *n* module elements.

Note: Suppose `self` is a module over the graded algebra *A* with base ring *R*. This returns a basis as a free module over *R*, not a basis as a free module over *A*.

INPUT:

- *n* – an integer

OUTPUT:

A sequence of homogeneous module elements of degree *n*, which is a basis for the free module of all degree *n* module elements.

See also:

[`vector_presentation\(\)`](#), [`element_from_coordinates\(\)`](#)

EXAMPLES:

```
sage: A = SteenrodAlgebra(2)
sage: M.<m0, m2, m4> = A.free_graded_module((0,2,4))
sage: M.basis_elements(8)
(Sq(1,0,1)*m0,
 Sq(2,2)*m0,
 Sq(5,1)*m0,
 Sq(8)*m0,
 Sq(0,2)*m2,
 Sq(3,1)*m2,
 Sq(6)*m2,
 Sq(1,1)*m4,
 Sq(4)*m4)
```

change_ring(*algebra*)

Change the base ring of *self*.

INPUT:

- *algebra* – a connected graded algebra

OUTPUT:

The free graded module over *algebra* defined with the same number of generators of the same degrees as *self*.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))

sage: M = FreeGradedModule(A, [0,1])
sage: N = M.change_ring(A2); N
Free graded left module on 2 generators over sub-Hopf algebra of
mod 2 Steenrod algebra, milnor basis, profile function [3, 2, 1]
```

Changing back yields the original module:

```
sage: N.change_ring(A) is M
True
```

connectivity()

The connectivity of *self*.

OUTPUT:

An integer equal to the minimal degree of all the generators, if this module is non-trivial. Otherwise, $+\infty$.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (-2,2,4))
sage: M.connectivity()
-2
```

element_from_coordinates(*coordinates*, *n*)

The module element of degree *n* having the given coordinates with respect to the basis of module elements given by [*basis_elements\(\)*](#).

INPUT:

- *coordinates* – a sequence of elements of the ground ring
- *n* – an integer

OUTPUT:

A module element of degree *n*.

See also:

[*vector_presentation\(\)*](#), and [*basis_elements\(\)*](#).

EXAMPLES:

```

sage: A = SteenrodAlgebra(2)
sage: M = A.free_graded_module((0,1))
sage: x = M.element_from_coordinates((0,1,0,1), 5); x
Sq(5)*g[0] + Sq(4)*g[1]
sage: basis = M.basis_elements(5)
sage: y = 0*basis[0] + 1*basis[1] + 0*basis[2] + 1*basis[3]
sage: x == y
True

sage: M.element_from_coordinates((0,0,0,0), 5)
0

```

gen(*index*)

Return the module generator with the given index.

EXAMPLES:

```

sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (0,2,4))
sage: M.generator(0)
g[0]
sage: M.generator(1)
g[2]
sage: M.generator(2)
g[4]

```

generator(*index*)

Return the module generator with the given index.

EXAMPLES:

```

sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (0,2,4))
sage: M.generator(0)
g[0]
sage: M.generator(1)
g[2]
sage: M.generator(2)
g[4]

```

generator_degrees()

The degrees of the module generators.

OUTPUT:

A tuple containing the degrees of the generators for this module, in the order that the generators were given when `self` was constructed.

EXAMPLES:

```

sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (-2,2,4))

```

(continues on next page)

(continued from previous page)

```
sage: M.generator_degrees()
(-2, 2, 4)
```

generators()

Return all the module generators.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (-2,1))
sage: M.generators()
(g[-2], g[1])
```

has_relations()

Return False as this has no relations.

This is for compatibility with *FModule*.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: F = FreeGradedModule(A, (-2,2,4))
sage: F.has_relations()
False
```

is_trivial()

Return True if this module is trivial and False otherwise.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: FreeGradedModule(A, (-2,2,4)).is_trivial()
False
sage: FreeGradedModule(A, ()).is_trivial()
True
```

minimal_presentation(*top_dim=None, verbose=False*)

Return a minimal presentation of self.

OUTPUT:

The identity morphism as self is free.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FModule
sage: A2 = SteenrodAlgebra(2)

sage: M = A2.free_graded_module([0,1])
sage: M.minimal_presentation().is_identity()
True
```

relations()

Return the relations of self, which is ().

This is for compatibility with *FPModule*.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: F = FreeGradedModule(A, (-2,2,4))
sage: F.relations()
()
```

resolution(*k*, *top_dim*=None, *verbose*=False)

Return a free resolution of *self* of length *k*.

Since *self* is free, the initial map in the resolution will be the identity, and the rest of the maps will be zero.

INPUT:

- *k* – an non-negative integer
- *top_dim* – stop the computation at this degree. Ignored, for compatibility with `sage.modules.fp_graded.module.FPModule.resolution()`.
- *verbose* – (default: False) a boolean to control if log messages should be emitted

OUTPUT:

A list of homomorphisms $[1_M, 0, 0, \dots, 0]$ consisting of the identity map on this module followed by zero maps. Other than this module, the other modules in the resolution will be zero.

EXAMPLES:

```
sage: E.<x,y,z> = ExteriorAlgebra(QQ)
sage: M = E.free_graded_module((1,2))
sage: M.resolution(0)
[Module endomorphism of Free graded left module on 2 generators over The
↪ exterior algebra of rank 3 over Rational Field
  Defn: g[1] |--> g[1]
        g[2] |--> g[2]]
sage: M.resolution(1)
[Module endomorphism of Free graded left module on 2 generators over The
↪ exterior algebra of rank 3 over Rational Field
  Defn: g[1] |--> g[1]
        g[2] |--> g[2],
Module morphism:
  From: Free graded left module on 0 generators over The exterior algebra of
↪ rank 3 over Rational Field
  To:   Free graded left module on 2 generators over The exterior algebra of
↪ rank 3 over Rational Field]
sage: M.resolution(4)
[Module endomorphism of Free graded left module on 2 generators over The
↪ exterior algebra of rank 3 over Rational Field
  Defn: g[1] |--> g[1]
        g[2] |--> g[2],
Module morphism:
  From: Free graded left module on 0 generators over The exterior algebra of
↪ rank 3 over Rational Field
  To:   Free graded left module on 2 generators over The exterior algebra of
↪ rank 3 over Rational Field,
```

(continues on next page)

(continued from previous page)

```

Module endomorphism of Free graded left module on 0 generators over The_
↪ exterior algebra of rank 3 over Rational Field,
Module endomorphism of Free graded left module on 0 generators over The_
↪ exterior algebra of rank 3 over Rational Field,
Module endomorphism of Free graded left module on 0 generators over The_
↪ exterior algebra of rank 3 over Rational Field]

```

suspension(*t*)

Suspend `self` by the given degree `t`.

INPUT:

- `t` – an integer

OUTPUT:

A module which is isomorphic to this module by a shift of degrees by the integer `t`.

EXAMPLES:

```

sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (0,2,4))
sage: M.suspension(4).generator_degrees()
(4, 6, 8)
sage: M.suspension(-4).generator_degrees()
(-4, -2, 0)

```

vector_presentation(*n*)

Return a free module over the ground ring of the module algebra isomorphic to the degree `n` elements of `self`.

Let $\|$ be the ground ring of the algebra over this module is defined, and let M_n be the free module of module elements of degree `n`.

The return value of this function is the free module $\|^r$ where $r = \dim(M_n)$.

The isomorphism between k^r and M_n is given by the bijection taking the standard basis element e_i to the i -th element of the array returned by `basis_elements()`.

INPUT:

- `n` – an integer degree

OUTPUT:

A free module over the ground ring of the algebra over which `self` is defined, isomorphic to the free module of module elements of degree `n`.

See also:

`basis_elements()`, `element_from_coordinates()`

EXAMPLES:

```

sage: A1 = SteenrodAlgebra(2, profile=[2,1])
sage: M.<x> = A1.free_graded_module((0,))
sage: M.vector_presentation(3)
Vector space of dimension 2 over Finite Field of size 2
sage: M.basis_elements(3)

```

(continues on next page)

(continued from previous page)

```
(Sq(0,1)*x, Sq(3)*x)
sage: [M.vector_presentation(i).dimension() for i in range(-2, 9)]
[0, 0, 1, 1, 1, 2, 1, 1, 1, 0, 0]
```

5.2 Elements of finitely generated free graded left modules

For an overview, see the [free graded modules documentation](#).

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

class sage.modules.fp_graded.free_element.FreeGradedModuleElement

Bases: [sage.modules.with_basis.indexed_element.IndexedFreeModuleElement](#)

Create a module element of a finitely generated free graded left module over a connected graded algebra.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: M = FreeGradedModule(SteenrodAlgebra(2), (0, 1))

sage: M([0, 0])
0

sage: M([1, 0])
g[0]

sage: M([0, 1])
g[1]

sage: M([Sq(1), 1])
Sq(1)*g[0] + g[1]
```

degree()

The degree of self.

OUTPUT:

The integer degree of this element, or raise an error if this is the zero element.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import *
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (0,1))
sage: x = M.an_element(7); x
Sq(0,0,1)*g[0] + Sq(3,1)*g[1]
sage: x.degree()
7
```

The zero element has no degree:

```
sage: (x-x).degree()
Traceback (most recent call last):
...
ValueError: the zero element does not have a well-defined degree
```

Neither do non-homogeneous elements:

```
sage: y = M.an_element(4)
sage: (x+y).degree()
Traceback (most recent call last):
...
ValueError: this is a nonhomogeneous element, no well-defined degree
```

dense_coefficient_list(*order=None*)

Return a list of all coefficients of *self*.

INPUT:

- *order* – (optional) an ordering of the basis indexing set

Note that this includes *all* of the coefficients, not just the nonzero ones. By default they appear in the same order as the module generators.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M.<Y,Z> = FreeGradedModule(SteenrodAlgebra(2), (0, 1))
sage: x = M.an_element(7); x
Sq(0,0,1)*Y + Sq(3,1)*Z
sage: x.dense_coefficient_list()
[Sq(0,0,1), Sq(3,1)]
```

lift_to_free()

Return *self*.

It is provided for compatibility with the method of the same name for *sage.modules.fp_graded.module.FPModule*.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: M = FreeGradedModule(A, (0,1))
sage: x = M.an_element()
sage: x.lift_to_free() == x
True
sage: x.lift_to_free() is x
True
```

vector_presentation()

A coordinate vector representing *self* when it is a non-zero homogeneous element.

These are coordinates with respect to the basis chosen by *basis_elements()*. When the element is zero, it has no well defined degree, and this function returns *None*.

OUTPUT:

A vector of elements in the ground ring of the algebra for this module when this element is non-zero. Otherwise, the value None.

See also:

- `sage.modules.fp_graded.free_module.FreeGradedModule.vector_presentation()`
- `sage.modules.fp_graded.free_module.FreeGradedModule.basis_elements()`
- `sage.modules.fp_graded.free_module.FreeGradedModule.element_from_coordinates()`

EXAMPLES:

```
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: M = A2.free_graded_module((0,1))
sage: x = M.an_element(7)
sage: v = x.vector_presentation(); v
(1, 0, 0, 0, 0, 1, 0)
sage: type(v)
<class 'sage.modules.vector_mod2_dense.Vector_mod2_dense'>
sage: M.gen(0).vector_presentation()
(1)
sage: M.gen(1).vector_presentation()
(0, 1)

sage: V = M.vector_presentation(7)
sage: v in V
True

sage: M.element_from_coordinates(v, 7) == x
True
```

We can use the basis for the module elements in the degree of x , together with the coefficients v to recreate the element x :

```
sage: basis = M.basis_elements(7)
sage: x_ = sum( [c*b for (c,b) in zip(v, basis)] ); x_
Sq(0,0,1)*g[0] + Sq(3,1)*g[1]
sage: x__ = M.linear_combination(zip(basis, v)); x__
Sq(0,0,1)*g[0] + Sq(3,1)*g[1]
sage: x == x_ == x__
True
```

This is not defined for elements that are not homogeneous:

```
sage: sum(M.basis()).vector_presentation()
Traceback (most recent call last):
...
ValueError: this is a nonhomogeneous element, no well-defined degree
```

5.3 Homomorphisms of finitely generated free graded left modules

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

class `sage.modules.fp_graded.free_morphism.FreeGradedModuleMorphism`(*parent, values*)

Bases: `sage.modules.fp_graded.morphism.FPModuleMorphism`

Create a homomorphism from a finitely generated free graded module to a graded module.

INPUT:

- *parent* – a homspace in the category of finitely generated free modules
- *values* – a list of elements in the codomain; each element corresponds (by their ordering) to a module generator in the domain

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: F1 = FreeGradedModule(A, (4,5), names='b')
sage: F2 = FreeGradedModule(A, (3,4), names='c')
sage: F3 = FreeGradedModule(A, (2,3), names='d')
sage: H1 = Hom(F1, F2)
sage: H2 = Hom(F2, F3)
sage: f = H1((F2((Sq(4), 0)), F2((0, Sq(4)))))
sage: g = H2((F3((Sq(2), 0)), F3((Sq(3), Sq(2)))))
sage: g*f
Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor_
↳basis
  To:   Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor_
↳basis
  Defn: b[4] |--> (Sq(0,2)+Sq(3,1)+Sq(6))*d[2]
        b[5] |--> (Sq(1,2)+Sq(7))*d[2] + (Sq(0,2)+Sq(3,1)+Sq(6))*d[3]
```

degree()

The degree of *self*.

OUTPUT:

The degree of this homomorphism. Raise an error if this is the trivial homomorphism.

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: homspace = Hom(FreeGradedModule(A, (0,1)), FreeGradedModule(A, (0,)))
sage: N = homspace.codomain()
sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]
sage: f = homspace(values)
```

(continues on next page)

(continued from previous page)

```
sage: f.degree()
5
```

The zero homomorphism has no degree:

```
sage: homspace.zero().degree()
Traceback (most recent call last):
...
ValueError: the zero morphism does not have a well-defined degree
```

fp_module()

Create a finitely presented module from `self`.

OUTPUT:

The finitely presented module with presentation equal to `self`.

EXAMPLES:

```
sage: A = SteenrodAlgebra(2)
sage: F1 = A.free_graded_module([2])
sage: F2 = A.free_graded_module([0])
sage: v = F2([Sq(2)])
sage: pres = Hom(F1, F2)([v])
sage: M = pres.fp_module(); M
Finitely presented left module on 1 generator and 1 relation over
mod 2 Steenrod algebra, milnor basis
sage: M.generator_degrees()
(0,)
sage: M.relations()
(Sq(2)*g[0],)

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: F1 = A.free_graded_module((2,))
sage: F2 = FPMModule(A, (0,), [[Sq(4)]])
sage: v = F2([Sq(2)])
sage: pres = Hom(F1, F2)([v])
sage: pres.fp_module()
Traceback (most recent call last):
...
ValueError: this is not a morphism between free modules
```

5.4 Homsets of finitely generated free graded left modules

For an overview, see the [free graded modules documentation](#).

EXAMPLES:

```
sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: A = SteenrodAlgebra(2)
sage: F1 = FreeGradedModule(A, (1,3), names='g')
```

(continues on next page)

(continued from previous page)

```

sage: F2 = FreeGradedModule(A, (2,3), names='h')
sage: homset = Hom(F1, F2)
sage: homset
Set of Morphisms from Free graded left module on 2 generators ...
sage: homset([F2((Sq(1), 1)), F2((0, Sq(2)))])
Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor basis
  To:   Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor basis
  Defn: g[1] |--> Sq(1)*h[2] + h[3]
        g[3] |--> Sq(2)*h[3]
sage: TestSuite(homset).run()

```

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

```

class sage.modules.fp_graded.free_homspace.FreeGradedModuleHomspace(X, Y, category=None,
                                                                    base=None, check=True)

```

Bases: [sage.modules.fp_graded.homspace.FPModuleHomspace](#)

Homspace between two free graded modules.

Element

alias of [sage.modules.fp_graded.free_morphism.FreeGradedModuleMorphism](#)

5.5 Finitely presented graded modules

Let R be a connected graded algebra. A finitely presented module over R is a module isomorphic to the cokernel of an R -linear homomorphism $f : F_1 \rightarrow F_0$ of finitely generated free modules: the generators of F_0 correspond to the generators of the module, and the generators of F_1 correspond to its relations, via the map f .

This module class takes as input a set of generators and relations and uses them to construct a presentation, using the class [FreeGradedModuleMorphism](#). It also allows such a morphism as input.

This package was designed with homological algebra in mind, and its API focuses on maps rather than objects. A good example of this is the kernel function [sage.modules.fp_graded.morphism.FPModuleMorphism.kernel_inclusion\(\)](#), which computes the kernel of a homomorphism $f : M \rightarrow N$. Its return value is not an instance of the module class, but rather an injective homomorphism $i : K \rightarrow M$ with the property that $\text{im}(i) = \ker(f)$.

Note: Some methods here require in addition that R be an algebra over a field or a PID and that Sage has a description of a basis for R .

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

```
class sage.modules.fp_graded.module.FPModule(j, names)
```

Bases: `sage.structure.unique_representation.UniqueRepresentation`, `sage.structure.indexed_generators.IndexedGenerators`, `sage.modules.module.Module`

A finitely presented module over a connected graded algebra.

INPUT:

One of the following:

- `arg0` – a morphism such that the module is the cokernel, or a free graded module, in which case the output is the same module, viewed as finitely presented

Otherwise:

- `arg0` – the graded connected algebra over which the module is defined; this algebra must be equipped with a graded basis
- `generator_degrees` – tuple of integer degrees
- `relations` – tuple of relations; a relation is a tuple of coefficients (c_1, \dots, c_n) , ordered so that they correspond to the module generators, that is, such a tuple corresponds to the relation

$$c_1g_1 + \dots + c_ng_n = 0$$

if the generators are (g_1, \dots, g_n)

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPModule

sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: M = FPModule(E, [0, 1], [[x, 1]])
sage: a, b = M.generators()
sage: x*a + b == 0
True
sage: (x*a + b).normalize()
0

sage: A3 = SteenrodAlgebra(2, profile=(4,3,2,1))
sage: M = FPModule(A3, [0, 1], [[Sq(2), Sq(1)]])
sage: M.generators()
(g[0], g[1])
sage: M.relations()
(Sq(2)*g[0] + Sq(1)*g[1],)
sage: M.is_trivial()
False

sage: Z = FPModule(A3, [])
sage: Z.generators()
()
sage: Z.relations()
()
sage: Z.is_trivial()
True

sage: from sage.modules.fp_graded.free_module import FreeGradedModule
sage: F = FreeGradedModule(E, [0, 1])
```

(continues on next page)

(continued from previous page)

```

sage: one = Hom(F, F).identity()
sage: Z = FPMModule(one)
sage: Z.is_trivial()
True

sage: FPMModule(E.free_graded_module([0, 1]))
Free graded left module on 2 generators over The exterior algebra of rank 2 over
↪ Rational Field

```

Elementalias of `sage.modules.fp_graded.element.FPElement`**an_element**(*n=None*)

An element of this module.

This function chooses deterministically an element, i.e. the output depends only on the module and its input *n*.

INPUT:

- *n* – (optional) the degree of the element to construct

OUTPUT:

A module element of the given degree.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: M = FPMModule(A2, [0,2,4], [[0, Sq(5), Sq(3)], [Sq(7), 0, Sq(2)*Sq(1)]]

sage: [M.an_element(i) for i in range(10)]
[g[0],
 Sq(1)*g[0],
 Sq(2)*g[0] + g[2],
 Sq(0,1)*g[0] + Sq(1)*g[2],
 Sq(1,1)*g[0] + Sq(2)*g[2] + g[4],
 Sq(2,1)*g[0] + Sq(0,1)*g[2] + Sq(1)*g[4],
 Sq(0,2)*g[0] + Sq(1,1)*g[2] + Sq(2)*g[4],
 Sq(0,0,1)*g[0] + Sq(2,1)*g[2] + Sq(0,1)*g[4],
 Sq(1,0,1)*g[0] + Sq(6)*g[2] + Sq(1,1)*g[4],
 Sq(2,0,1)*g[0] + Sq(4,1)*g[2] + Sq(2,1)*g[4]]

```

basis_elements(*n, verbose=False*)Return a basis for the free module of degree *n* module elements.

Note: Suppose `self` is a module over the graded algebra *A* with base ring *R*. This returns a basis as a free module over *R*.

INPUT:

- *n* – an integer
- *verbose* – (default: `False`) a boolean to control if log messages should be emitted

OUTPUT:

A list of homogeneous module elements of degree n which is a basis for the free module of all degree n module elements.

See also:

`vector_presentation()`, `element_from_coordinates()`

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: M.<m0,m2> = FPMModule(A2, [0,2], [[Sq(4), Sq(2)], [0, Sq(6)]])

sage: M.basis_elements(4)
(Sq(1,1)*m0, Sq(4)*m0)

sage: M.basis_elements(5)
(Sq(2,1)*m0, Sq(5)*m0, Sq(0,1)*m2)

sage: M.basis_elements(25)
()

sage: M.basis_elements(0)
(m0,)

sage: M.basis_elements(2)
(Sq(2)*m0, m2)
```

change_ring(*algebra*)

Change the base ring of self.

INPUT:

- *algebra* – a connected graded algebra

OUTPUT:

The finitely presented module over *algebra* defined with the exact same number of generators of the same degrees and relations as self.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))

sage: M = FPMModule(A, [0,1], [[Sq(2), Sq(1)]])
sage: N = M.change_ring(A2); N
Finitely presented left module on 2 generators and 1 relation over
sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3,
↪2, 1]
```

Changing back yields the original module:

```
sage: N.change_ring(A) is M
True
```

connectivity()

The connectivity of self.

Since a finitely presented module over a connected algebra is in particular bounded below, the connectivity is an integer when the module is non-trivial, and $+\infty$ when the module is trivial.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)

sage: M = FPMModule(A, [0,2,4], [[0, Sq(5), Sq(3)], [Sq(7), 0, Sq(2)*Sq(1)]])
sage: M.connectivity()
0

sage: G = FPMModule(A, [0,2], [[1,0]])
sage: G.connectivity()
2
```

`defining_homomorphism()`

Return the homomorphism defining self.

self is a finitely presented module defined as the cokernel of a map $j : F_0 \otimes F_1$ of free modules, and this returns that map.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: E.<x,y> = ExteriorAlgebra(QQ)
sage: M = FPMModule(E, [0, 1], [[x, 1]])
sage: M.defining_homomorphism()
Module morphism:
  From: Free graded left module on 1 generator over The exterior algebra of
↳rank 2 over Rational Field
  To:   Free graded left module on 2 generators over The exterior algebra of
↳rank 2 over Rational Field
  Defn: g[1] |--> x*g[0] + g[1]
```

`element_from_coordinates(coordinates, n)`

Return the module element in degree n having the given coordinates with respect to the basis returned by `basis_elements()`.

This function is inverse to `sage.modules.fp_graded.element.FPElement.vector_presentation()`.

INPUT:

- `coordinates` – a vector of coordinates
- `n` – the degree of the element to construct

OUTPUT:

A module element of degree n having the given coordinates with respect to the basis returned by `basis_elements()`.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0], [[Sq(4)], [Sq(7)], [Sq(4)*Sq(9)]])
```

(continues on next page)

(continued from previous page)

```
sage: M.vector_presentation(12).dimension()
3
sage: x = M.element_from_coordinates((0,1,0), 12); x
Sq(0,4)*g[0]
```

Applying the inverse function brings us back to the coordinate form:

```
sage: x.vector_presentation()
(0, 1, 0)
```

See also:

sage.modules.fp_graded.module.FPModule.vector_presentation()

gen(*index*)

Return the module generator with the given index.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))

sage: M = FPModule(A4, [0,2,3])
sage: M.generator(0)
g[0]

sage: N = FPModule(A4, [0, 1], [[Sq(2), Sq(1)]], names='h')
sage: N.generator(1)
h[1]
```

generator(*index*)

Return the module generator with the given index.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))

sage: M = FPModule(A4, [0,2,3])
sage: M.generator(0)
g[0]

sage: N = FPModule(A4, [0, 1], [[Sq(2), Sq(1)]], names='h')
sage: N.generator(1)
h[1]
```

generator_degrees()

Return the degrees of the generators for self.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))
sage: N = FPModule(A4, [0, 1], [[Sq(2), Sq(1)]])
```

(continues on next page)

(continued from previous page)

```
sage: N.generator_degrees()
(0, 1)
```

generators()

Return the generators of self.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))

sage: M = FPMModule(A4, [0,0,2,3])
sage: M.generators()
(g[0, 0], g[0, 1], g[2, 0], g[3, 0])

sage: N = FPMModule(A4, [0, 1], [[Sq(2), Sq(1)]], names='h')
sage: N.generators()
(h[0], h[1])

sage: Z = FPMModule(A4, [])
sage: Z.generators()
()
```

gens()

Return the generators of self.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))

sage: M = FPMModule(A4, [0,0,2,3])
sage: M.generators()
(g[0, 0], g[0, 1], g[2, 0], g[3, 0])

sage: N = FPMModule(A4, [0, 1], [[Sq(2), Sq(1)]], names='h')
sage: N.generators()
(h[0], h[1])

sage: Z = FPMModule(A4, [])
sage: Z.generators()
()
```

has_relations()

Return True if no relations are defined, and False otherwise.

Note: This module is free if this function returns False, but a free module can have (redundant) relations.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
```

(continues on next page)

(continued from previous page)

```

sage: F = FPMModule(A2, [1,2])
sage: F.has_relations()
False

sage: M = FPMModule(A2, [1,2], [[Sq(2), Sq(1)]])
sage: M.has_relations()
True

```

A free module constructed with a redundant generator and relation:

```

sage: N = FPMModule(A2, [0, 0], [[0, 1]])
sage: N.has_relations()
True
sage: # Computing a minimal presentation reveals an
..... # isomorphic module with no relations.
sage: N_min = N.minimal_presentation().domain()
sage: N_min.has_relations()
False

```

is_trivial()

Return True if self is isomorphic to the trivial module and False otherwise.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))

sage: M = FPMModule(A2, [])
sage: M.is_trivial()
True

sage: N = FPMModule(A, [1,2])
sage: N.is_trivial()
False

sage: P = FPMModule(A, [1,2], [[1,0], [0,1]])
sage: P.is_trivial()
True

```

minimal_presentation(top_dim=None, verbose=False)

Return a minimal presentation of self.

OUTPUT:

An isomorphism $M \rightarrow S$, where M has minimal presentation and S is self.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))

sage: M = FPMModule(A2, [0,1], [[Sq(2), Sq(1)], [0, Sq(2)], [Sq(3), 0]])
sage: i = M.minimal_presentation()
sage: M_min = i.domain()

```

i is an isomorphism between M_{\min} and M :

```
sage: i.codomain() is M
True
sage: i.is_injective()
True
sage: i.is_surjective()
True
```

There are more relations in M than in M_{\min} :

```
sage: M.relations()
(Sq(2)*g[0] + Sq(1)*g[1], Sq(2)*g[1], Sq(3)*g[0])
sage: M_min.relations()
(Sq(2)*g[0] + Sq(1)*g[1], Sq(2)*g[1])
```

monomial()

Return the basis element indexed by i .

INPUT:

- i – an element of the index set

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: M = FPMModule(SteenrodAlgebra(2), [0,1], [[Sq(4), Sq(3)]])
sage: M.monomial(0)
g[0]
sage: M.monomial(1)
g[1]
```

relation(index)

Return the module relation of the given index.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))
sage: N = FPMModule(A4, [0, 1], [[Sq(2), Sq(1)]])
sage: N.relation(0)
Sq(2)*g[0] + Sq(1)*g[1]
```

relations()

Return the relations of self.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A4 = SteenrodAlgebra(2, profile=(4,3,2,1))

sage: M = FPMModule(A4, [0,2,3])
sage: M.relations()
()

sage: N = FPMModule(A4, [0, 1], [[Sq(2), Sq(1)]])
sage: N.relations()
```

(continues on next page)

(continued from previous page)

```
(Sq(2)*g[0] + Sq(1)*g[1],)
```

```
sage: Z = FPMModule(A4, [])
```

```
sage: Z.relations()
```

```
()
```

resolution(*k*, *top_dim=None*, *verbose=False*)

Return a free resolution of this module of length *k*.

INPUT:

- *k* – an non-negative integer
- *top_dim* – stop the computation at this degree (optional, default *None*, but required if the algebra is not finite-dimensional)
- *verbose* – (default: *False*) a boolean to control if log messages should be emitted

OUTPUT:

A list of homomorphisms $[\epsilon, f_1, \dots, f_k]$ such that

$$f_i : F_i \rightarrow F_{i-1} \text{ for } 1 \leq i \leq k, \quad \epsilon : F_0 \rightarrow M,$$

where each F_i is a finitely generated free module, and the sequence

$$F_k \xrightarrow{f_k} F_{k-1} \xrightarrow{f_{k-1}} \dots \rightarrow F_0 \xrightarrow{\epsilon} M \rightarrow 0$$

is exact. Note that the 0th element in this list is the map ϵ , and the rest of the maps are between free modules.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
```

```
sage: E.<x,y> = ExteriorAlgebra(QQ)
```

```
sage: M = FPMModule(E, [0], [[x], [y]])
```

```
sage: res = M.resolution(3); res
```

```
[Module morphism:
```

```
  From: Free graded left module on 1 generator over The exterior algebra of
  rank 2 over Rational Field
```

```
  To:   Finitely presented left module on 1 generator and 2 relations over The
  exterior algebra of rank 2 over Rational Field
```

```
  Defn: g[0] |--> g[0],
```

```
Module morphism:
```

```
  From: Free graded left module on 2 generators over The exterior algebra of
  rank 2 over Rational Field
```

```
  To:   Free graded left module on 1 generator over The exterior algebra of
  rank 2 over Rational Field
```

```
  Defn: g[1, 0] |--> x*g[0]
        g[1, 1] |--> y*g[0],
```

```
Module morphism:
```

```
  From: Free graded left module on 3 generators over The exterior algebra of
  rank 2 over Rational Field
```

```
  To:   Free graded left module on 2 generators over The exterior algebra of
  rank 2 over Rational Field
```

```
  Defn: g[2, 0] |--> x*g[1, 0]
```

(continues on next page)

(continued from previous page)

```

    g[2, 1] |--> y*g[1, 0] + x*g[1, 1]
    g[2, 2] |--> y*g[1, 1],
Module morphism:
  From: Free graded left module on 4 generators over The exterior algebra of
↳rank 2 over Rational Field
  To:   Free graded left module on 3 generators over The exterior algebra of
↳rank 2 over Rational Field
  Defn: g[3, 0] |--> x*g[2, 0]
        g[3, 1] |--> y*g[2, 0] + x*g[2, 1]
        g[3, 2] |--> y*g[2, 1] + x*g[2, 2]
        g[3, 3] |--> y*g[2, 2]]
sage: all((res[i] * res[i+1]).is_zero() for i in range(len(res)-1))
True

sage: e = SymmetricFunctions(QQ).e()
sage: M = FPMModule(e, [0], [[e[2]+e[1,1]], [e[1,1]]])
sage: res = M.resolution(3, top_dim=10)
sage: all((res[i] * res[i+1]).is_zero() for i in range(2))
True
sage: res[-1].domain().is_trivial()
True
sage: M = FPMModule(e, [0,2], [[e[2]+e[1,1], 0], [e[2,1], e[1]], [0, e[1,1]]])
sage: res = M.resolution(3, top_dim=10)
sage: all((res[i] * res[i+1]).is_zero() for i in range(2))
True
sage: res[-1].domain().is_trivial()
True

sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: M = FPMModule(A2, [0,1], [[Sq(2), Sq(1)]])
sage: M.resolution(0)
[Module morphism:
  From: Free graded left module on 2 generators over sub-Hopf algebra of mod 2
↳Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Finitely presented left module on 2 generators and 1 relation over sub-
↳Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3, 2,
↳1]
  Defn: g[0] |--> g[0]
        g[1] |--> g[1]]
sage: res = M.resolution(4, verbose=True)
Computing f_1 (1/4)
Computing f_2 (2/4)
Computing using the profile:
(2, 1)
Resolving the kernel in the range of dimensions [2, 8]: 2 3 4 5 6 7 8.
Computing f_3 (3/4)
Computing using the profile:
(2, 1)
Resolving the kernel in the range of dimensions [8, 14]: 8 9 10 11 12 13 14.
Computing f_4 (4/4)
Computing using the profile:
(2, 1)

```

(continues on next page)

(continued from previous page)

```

Resolving the kernel in the range of dimensions [9, 16]: 9 10 11 12 13 14 15 16.
sage: len(res)
5
sage: res
[Module morphism:
  From: Free graded left module on 2 generators over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Finitely presented left module on 2 generators and 1 relation over sub-
  ↪Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3, 2, ↪
  ↪1]
  Defn: g[0] |--> g[0]
        g[1] |--> g[1],
Module morphism:
  From: Free graded left module on 1 generator over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Free graded left module on 2 generators over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  Defn: g[2] |--> Sq(2)*g[0] + Sq(1)*g[1],
Module morphism:
  From: Free graded left module on 1 generator over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Free graded left module on 1 generator over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  Defn: g[8] |--> Sq(3,1)*g[2],
Module morphism:
  From: Free graded left module on 2 generators over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Free graded left module on 1 generator over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  Defn: g[9] |--> Sq(1)*g[8]
        g[10] |--> Sq(2)*g[8],
Module morphism:
  From: Free graded left module on 2 generators over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Free graded left module on 2 generators over sub-Hopf algebra of mod 2_
  ↪Steenrod algebra, milnor basis, profile function [3, 2, 1]
  Defn: g[10] |--> Sq(1)*g[9]
        g[12] |--> Sq(0,1)*g[9] + Sq(2)*g[10]]
sage: for i in range(len(res)-1):
.....:     assert (res[i] * res[i+1]).is_zero(), 'the result is not a complex'

```

We construct F_3 as a \mathbf{Z} -module (with trivial grading concentrated in degree 0) and compute its resolution:

```

sage: E = ExteriorAlgebra(ZZ, 0)
sage: M = FPMModule(E, [0], [[3]])
sage: res = M.resolution(3)
sage: res
[Module morphism:
  From: Free graded left module on 1 generator over The exterior algebra of_
  ↪rank 0 over Integer Ring
  To:   Finitely presented left module on 1 generator and 1 relation over The_
  ↪exterior algebra of rank 0 over Integer Ring

```

(continues on next page)

(continued from previous page)

```

Defn: g[0] |--> g[0],
Module endomorphism of Free graded left module on 1 generator over The_
↳ exterior algebra of rank 0 over Integer Ring
Defn: g[0] |--> 3*g[0],
Module morphism:
From: Free graded left module on 0 generators over The exterior algebra of_
↳ rank 0 over Integer Ring
To: Free graded left module on 1 generator over The exterior algebra of_
↳ rank 0 over Integer Ring,
Module endomorphism of Free graded left module on 0 generators over The_
↳ exterior algebra of rank 0 over Integer Ring]

```

submodule_inclusion(*spanning_elements*)

Return the inclusion morphism of the submodule of `self` spanned by the given elements.

INPUT:

- `spanning_elements` – an iterable of elements

OUTPUT:

The inclusion of the submodule into this module.

Because a submodule of a finitely presented module need not be finitely presented, this method will only work if the underlying algebra is finite-dimensional. Indeed, the current implementation only works if the algebra has a `top_class` method, which gets used in `sage.modules.fp_graded.morphism._resolve_kernel()`.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))

sage: M = FPMModule(A2, [0,1], [[Sq(2),Sq(1)]])
sage: i = M.submodule_inclusion([M.generator(0)])
sage: i.codomain() is M
True
sage: i.is_injective()
True
sage: i.domain().generator_degrees()
(0,)
sage: i.domain().relations()
(Sq(3)*g[0],)

```

suspension(*t*)

Return the suspension of `self` by degree `t`.

INPUT:

- `t` – an integer degree by which the module is suspended

OUTPUT:

A module which is identical to this module by a shift of degrees by the integer `t`.

EXAMPLES:


```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))

sage: Y = FPMModule(A2, [0], [[Sq(1)]])
sage: X = Y.suspension(4)
sage: X.generator_degrees()
(4,)
sage: X.relations()
(Sq(1)*g[4],)

sage: M = FPMModule(A, [2,3], [[Sq(2), Sq(1)], [0, Sq(2)]])
sage: Q = M.suspension(1)
sage: Q.generator_degrees()
(3, 4)
sage: Q.relations()
(Sq(2)*g[3] + Sq(1)*g[4], Sq(2)*g[4])
sage: Q = M.suspension(-3)
sage: Q.generator_degrees()
(-1, 0)
sage: Q = M.suspension(0)
sage: Q.generator_degrees()
(2, 3)

```

vector_presentation(*n*, *verbose=False*)

Return a free module isomorphic to the free module of module elements of degree *n*.

INPUT:

- *n* – the degree of the presentation

OUTPUT:

A vector space.

See also:

[*basis_elements\(\)*](#), [*element_from_coordinates\(\)*](#)

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0,2,4], [[Sq(4),Sq(2),0]])

sage: V = M.vector_presentation(4)
sage: V.dimension()
3

sage: len(M.basis_elements(4))
3

```

zero()

Return the zero element.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FModule
sage: M = FModule(SteenrodAlgebra(2), [0,1], [[Sq(4), Sq(3)]])
sage: M.zero()
0
```

5.6 Elements of finitely presented graded modules

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

class `sage.modules.fp_graded.element.FPElement`

Bases: `sage.modules.with_basis.indexed_element.IndexedFreeModuleElement`

A module element of a finitely presented graded module over a connected graded algebra.

degree()

The degree of `self`.

OUTPUT:

The integer degree of `self` or raise an error if the zero element.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FModule
sage: M = FModule(SteenrodAlgebra(2), [0,1], [[Sq(4), Sq(3)]])
sage: x = M.an_element(7)

sage: x
Sq(0,0,1)*g[0] + Sq(3,1)*g[1]
sage: x.degree()
7
```

The zero element has no degree:

```
sage: (x-x).degree()
Traceback (most recent call last):
...
ValueError: the zero element does not have a well-defined degree
```

dense_coefficient_list(*order=None*)

Return a list of all coefficients of `self`.

INPUT:

- `order` – (optional) an ordering of the basis indexing set

Note that this includes *all* of the coefficients, not just the nonzero ones. By default they appear in the same order as the module generators.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra()
sage: M = FPMModule(SteenrodAlgebra(2), [0,1], [[Sq(4), Sq(3)]])
sage: x = M([Sq(1), 1])
sage: x.dense_coefficient_list()
[Sq(1), 1]
sage: y = Sq(2) * M.generator(1)
sage: y.dense_coefficient_list()
[0, Sq(2)]

```

lift_to_free()

Return the lift of `self` to the free module `F`, where `self` is in a quotient of `F`.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: M = FPMModule(SteenrodAlgebra(2), [0,1], [[Sq(4), Sq(3)]])
sage: x = M([Sq(1), 1])
sage: x
Sq(1)*g[0] + g[1]
sage: x.parent()
Finitely presented left module on 2 generators and 1 relation over mod 2
↳ Steenrod algebra, milnor basis
sage: x.lift_to_free()
Sq(1)*g[0] + g[1]
sage: x.lift_to_free().parent()
Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor
↳ basis

```

normalize()

A normalized form of `self`.

OUTPUT:

An instance representing the same module element as `self` in normalized form.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: M.<a0,b2,c4> = FPMModule(SteenrodAlgebra(2), [0,2,4], [[Sq(4),Sq(2),0]])

sage: m = M((Sq(6), 0, Sq(2))); m
Sq(6)*a0 + Sq(2)*c4
sage: m.normalize()
Sq(6)*a0 + Sq(2)*c4
sage: m == m.normalize()
True

sage: n = M((Sq(4), Sq(2), 0)); n
Sq(4)*a0 + Sq(2)*b2
sage: n.normalize()
0
sage: n == n.normalize()
True

```

vector_presentation()

A coordinate vector representing `self` when it is non-zero.

These are coordinates with respect to the basis chosen by `basis_elements()`. When the element is zero, it has no well defined degree, and this function returns `None`.

OUTPUT:

A vector of elements in the ground ring of the algebra for this module when this element is non-zero. Otherwise, the value `None`.

See also:

- `sage.modules.fp_graded.module.FPModule.vector_presentation()`
- `sage.modules.fp_graded.module.FPModule.basis_elements()`
- `sage.modules.fp_graded.module.FPModule.element_from_coordinates()`

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: M.<m0,m1> = FPModule(A2, (0,1))

sage: x = M.an_element(7)
sage: v = x.vector_presentation(); v
(1, 0, 0, 0, 0, 1, 0)
sage: type(v)
<class 'sage.modules.vector_mod2_dense.Vector_mod2_dense'>

sage: V = M.vector_presentation(7)
sage: v in V
True

sage: M.element_from_coordinates(v, 7) == x
True
```

We can use the basis for the module elements in the degree of x , together with the coefficients v to recreate the element x :

```
sage: basis = M.basis_elements(7)
sage: x_ = sum( [c*b for (c,b) in zip(v, basis)] ); x_
Sq(0,0,1)*m0 + Sq(3,1)*m1
sage: x__ = M.linear_combination(zip(basis, v)); x__
Sq(0,0,1)*m0 + Sq(3,1)*m1
sage: x == x_ == x__
True
```

5.7 Homomorphisms of finitely presented graded modules

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

class `sage.modules.fp_graded.morphism.FPModuleMorphism`(*parent, values, check=True*)

Bases: `sage.categories.morphism.Morphism`

Create a homomorphism between finitely presented graded modules.

INPUT:

- *parent* – a homspace of finitely presented graded modules
- *values* – a list of elements in the codomain; each element corresponds to a module generator in the domain
- *check* – boolean (default: True); if True, check that the morphism is well-defined

change_ring(*algebra*)

Change the base ring of *self*.

INPUT:

- *algebra* – a graded algebra

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: A3 = SteenrodAlgebra(2, profile=(4,3,2,1))
sage: M = FPMModule(A2, [0], relations=[[Sq(1)]])
sage: N = FPMModule(A2, [0], relations=[[Sq(4)],[Sq(1)]])

sage: f = Hom(M,N)([A2.Sq(3)*N.generator(0)]); f
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3, 2,
↳ 1]
  To:   Finitely presented left module on 1 generator and 2 relations over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3, 2,
↳ 1]
  Defn: g[0] |--> Sq(3)*g[0]

sage: f.base_ring()
sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3,
↳ 2, 1]

sage: g = f.change_ring(A3)
sage: g.base_ring()
sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [4,
↳ 3, 2, 1]
```

cokernel_projection()

Return the map to the cokernel of *self*.

OUTPUT:

The natural projection from the codomain of this homomorphism to its cokernel.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A1 = SteenrodAlgebra(2, profile=(2,1))
sage: M = FPMModule(A1, [0], [[Sq(2)]])
sage: F = FPMModule(A1, [0])

sage: r = Hom(F, M)([A1.Sq(1)*M.generator(0)])
sage: co = r.cokernel_projection(); co
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [2, 1]
  To:   Finitely presented left module on 1 generator and 2 relations over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [2, 1]
  Defn: g[0] |--> g[0]

sage: co.domain().is_trivial()
False
```

degree()

The degree of `self`.

OUTPUT:

The integer degree of `self`.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import *
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0,1], [[Sq(2), Sq(1)]])
sage: N = FPMModule(A, [2], [[Sq(4)]])
sage: homspace = Hom(M, N)

sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]
sage: f = homspace(values)
sage: f.degree()
7
```

The trivial homomorphism has no degree:

```
sage: homspace.zero().degree()
Traceback (most recent call last):
...
ValueError: the zero morphism does not have a well-defined degree
```

fp_module()

Create a finitely presented module from `self`.

OUTPUT:

The finitely presented module having presentation equal to `self` as long as the domain and codomain are free.

EXAMPLES:

We construct examples with free modules that are presented with a redundant relation:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: F1 = FPMModule(A, (2,), [[0]])
sage: F2 = FPMModule(A, (0,), [[0]])
sage: v = F2([Sq(2)])
sage: pres = Hom(F1, F2)([v])
sage: M = pres.fp_module(); M
Finitely presented left module on 1 generator and 1 relation over
mod 2 Steenrod algebra, milnor basis
sage: M.generator_degrees()
(0,)
sage: M.relations()
(Sq(2)*g[0],)

sage: F2 = A.free_graded_module((0,))
sage: v = F2([Sq(2)])
sage: pres = Hom(F1, F2)([v])
sage: M = pres.fp_module(); M
Finitely presented left module on 1 generator and 1 relation over
mod 2 Steenrod algebra, milnor basis
sage: M.generator_degrees()
(0,)
sage: M.relations()
(Sq(2)*g[0],)

sage: F3 = FPMModule(A, (0,), [[Sq(4)]])
sage: v = F3([Sq(2)])
sage: pres = Hom(F1, F3)([v])
sage: pres.fp_module()
Traceback (most recent call last):
...
ValueError: this is not a morphism between free modules
```

homology(*f*, *top_dim=None*, *verbose=False*)

Compute the sub-quotient module of $H(\text{self}, f) = \ker(\text{self}) / \text{im}(f)$ in a range of degrees.

For a pair of composable morphisms $f : M \rightarrow N$ and $g : N \rightarrow Q$ of finitely presented modules, the homology module is a finitely presented quotient of the kernel sub module $\ker(g) \subset N$.

INPUT:

- *f* – a homomorphism with codomain equal to the domain of *self* and image contained in the kernel of this homomorphism
- *top_dim* – integer (optional); used by this function to stop the computation at the given degree
- *verbose* – boolean (default: False); enable progress messages

OUTPUT:

A quotient homomorphism $\ker(\text{self}) \rightarrow H$, where H is isomorphic to $H(\text{self}, f)$ in degrees less than or equal to *top_dim*.

Note: If the algebra for this module is finite, then no *top_dim* needs to be specified in order to ensure that

this function terminates.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2, profile=(3,2,1))
sage: M = FPMModule(A, [0], [[Sq(3)]])
sage: N = FPMModule(A, [0], [[Sq(2,2)]])
sage: F = FPMModule(A, [0])
sage: f = Hom(M,N)([A.Sq(2)*N.generator(0)])
sage: g = Hom(F, M)([A.Sq(4)*A.Sq(1,2)*M.generator(0)])
sage: ho = f.homology(g)
sage: ho.codomain()
Finitely presented left module on 1 generator and 5 relations over
sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [3,
↪2, 1]
sage: ho.codomain().is_trivial()
False
```

image(*top_dim=None, verbose=False*)
Compute the image of *self*.

INPUT:

- *top_dim* – integer (optional); used by this function to stop the computation at the given degree
- *verbose* – boolean (default: `False`); enable progress messages

OUTPUT:

A homomorphism into $\text{im}(\text{self})$ that is an isomorphism in degrees less than or equal to *top_dim*

Note: If the algebra for this module is finite, then no *top_dim* needs to be specified in order to ensure that this function terminates.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A3 = SteenrodAlgebra(2, profile=(4,3,2,1))
sage: F = FPMModule(A3, [1,3]);
sage: L = FPMModule(A3, [2,3], [[Sq(2),Sq(1)], [0,Sq(2)]]);
sage: H = Hom(F, L);

sage: H([L((A3.Sq(1), 1)), L((0, A3.Sq(2)))]).image() # long time
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over sub-
↪Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [4, 3,
↪2, 1]
  To:   Finitely presented left module on 2 generators and 2 relations over sub-
↪Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [4, 3,
↪2, 1]
  Defn: g[3] |--> Sq(1)*g[2] + g[3]

sage: M = FPMModule(A3, [0,7], [[Sq(1), 0], [Sq(2), 0], [Sq(4), 0], [Sq(8),
↪Sq(1)], [0, Sq(7)], [0, Sq(0,1,1)+Sq(4,2)]])
```

(continues on next page)

(continued from previous page)

```

sage: F2 = FPMModule(A3, [0], [[Sq(1)], [Sq(2)], [Sq(4)], [Sq(8)], [Sq(15)]]])
sage: H = Hom(M, F2)
sage: f = H([F2([1]), F2([0])])
sage: K = f.image(verbose=True, top_dim=17)
1. Computing the generators of the image presentation:
Resolving the image in the range of dimensions [0, 17]:
  0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17.
2. Computing the relations of the image presentation:
Computing using the profile:
(4, 3, 2, 1)
Resolving the kernel in the range of dimensions [0, 17]:
  0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17.

sage: K.is_injective() # long time
True
sage: K.domain().generator_degrees()
(0,)
sage: K.domain().relations()
(Sq(1)*g[0], Sq(2)*g[0], Sq(4)*g[0], Sq(8)*g[0])
sage: K.domain().is_trivial()
False

```

is_identity()

Decide if self is the identity endomorphism.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import *
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0,1], [[Sq(2), Sq(1)]]])
sage: N = FPMModule(A, [2], [[Sq(4)]]])
sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]

sage: f = Hom(M, N)(values)
sage: f.is_identity()
False

sage: one = Hom(M, M)(M.generators()); one
Module endomorphism of Finitely presented left module on 2 generators and 1
relation over mod 2 Steenrod algebra, milnor basis
Defn: g[0] |--> g[0]
      g[1] |--> g[1]

sage: one.is_identity()
True

sage: M = A.free_graded_module((0,1))
sage: N = A.free_graded_module((2,))
sage: v = N.generator(0)
sage: values = [Sq(5)*v, Sq(3,1)*v]
sage: f = Hom(M, N)(values)
sage: f.is_identity()
False

```

(continues on next page)

(continued from previous page)

```

sage: one = Hom(M, M)(M.generators()); one
Module endomorphism of Free graded left module on 2 generators over mod 2
↳ Steenrod algebra, milnor basis
Defn: g[0] |--> g[0]
      g[1] |--> g[1]
sage: one.is_identity()
True

```

is_injective(*top_dim=None, verbose=False*)

Return True if and only if *self* has a trivial kernel.

INPUT:

- *top_dim* – integer (optional); used by this function to stop the computation at the given degree
- *verbose* – boolean (default: False); enable progress messages

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)

sage: K = FPMModule(A, [2], [[Sq(2)]])
sage: HZ = FPMModule(A, [0], [[Sq(1)]])

sage: f = Hom(K, HZ)([Sq(2)*HZ([1])])
sage: f.is_injective(top_dim=23)
True

```

is_surjective()

Return True if and only if *self* has a trivial cokernel.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: F = FPMModule(A, [0])

sage: f = Hom(F, F)([Sq(1)*F.generator(0)])
sage: f.is_surjective()
False

```

is_zero()

Decide if *self* is the zero homomorphism.

OUTPUT:

The boolean value True if *self* is trivial and False otherwise.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0,1], [[Sq(2), Sq(1)]])
sage: N = FPMModule(A, [2], [[Sq(4)]])
sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]

```

(continues on next page)

(continued from previous page)

```

sage: f = Hom(M, N)(values)
sage: f.is_zero()
False

sage: (f-f).is_zero()
True

sage: M = A.free_graded_module((0,1))
sage: N = A.free_graded_module((2,))
sage: v = N.generator(0)
sage: values = [Sq(5)*v, Sq(3,1)*v]
sage: f = Hom(M, N)(values)
sage: f.is_zero()
False
sage: (f-f).is_zero()
True

```

kernel_inclusion(*top_dim=None, verbose=False*)

Return the kernel of *self*.

INPUT:

- *top_dim* – integer (optional); used by this function to stop the computation at the given degree
- *verbose* – boolean (default: `False`); enable progress messages

OUTPUT:

A homomorphism into $\ker(\text{self})$ which is an isomorphism in degrees less than or equal to *top_dim*.

Note: If the algebra for this module is finite, then no *top_dim* needs to be specified in order to ensure that this function terminates.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A3 = SteenrodAlgebra(2, profile=(4,3,2,1))
sage: F = FPMModule(A3, [1,3]);
sage: L = FPMModule(A3, [2,3], [[Sq(2),Sq(1)], [0,Sq(2)]]);
sage: H = Hom(F, L);

sage: H([L((A3.Sq(1), 1)), L((0, A3.Sq(2)))]).kernel_inclusion() # long time
Module morphism:
  From: Finitely presented left module on 2 generators and 1 relation over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [4, 3,
↳ 2, 1]
  To: Free graded left module on 2 generators over sub-Hopf algebra of mod 2
↳ Steenrod algebra, milnor basis, profile function [4, 3, 2, 1]
  Defn: g[3] |--> g[3]
        g[4] |--> Sq(0,1)*g[1]

sage: M = FPMModule(A3, [0,7], [[Sq(1), 0], [Sq(2), 0], [Sq(4), 0], [Sq(8),
↳ Sq(1)], [0, Sq(7)], [0, Sq(0,1,1)+Sq(4,2)]]

```

(continues on next page)

(continued from previous page)

```

sage: F2 = FPMModule(A3, [0], [[Sq(1)], [Sq(2)], [Sq(4)], [Sq(8)], [Sq(15)]]])
sage: H = Hom(M, F2)
sage: f = H([F2([1]), F2([0])])

sage: K = f.kernel_inclusion(verbose=True, top_dim=17)
1. Computing the generators of the kernel presentation:
Resolving the kernel in the range of dimensions [0, 17]:
  0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17.
2. Computing the relations of the kernel presentation:
Computing using the profile:
(4, 3, 2, 1)
Resolving the kernel in the range of dimensions [7, 17]:
  7 8 9 10 11 12 13 14 15 16 17.

sage: K.domain().generators()
(g[7],)
sage: K.domain().relations()
((Sq(0,1)+Sq(3))*g[7],
 (Sq(0,0,1)+Sq(1,2)+Sq(4,1))*g[7],
 Sq(9)*g[7],
 (Sq(0,1,1)+Sq(4,2))*g[7])

sage: K
Module morphism:
  From: Finitely presented left module on 1 generator and 4 relations over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [4, 3,
↳ 2, 1]
  To:   Finitely presented left module on 2 generators and 6 relations over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [4, 3,
↳ 2, 1]
  Defn: g[7] |--> g[7]

```

lift(*f*, *verbose=False*)Return a lift of this homomorphism over the given homomorphism *f*.

INPUT:

- *f* – a homomorphism with codomain equal to the codomain of *self*
- *verbose* – boolean (default: False); enable progress messages

OUTPUT:

A homomorphism *g* with the property that *self* equals *f* ∘ *g*. If no lift exist, None is returned.

ALGORITHM:

Let *s* be this homomorphism with *L* the domain of *s*. Choose x_1, \dots, x_N such that $f(x_i) = s(g_i)$, where the g_i 's are the module generators of *L*.

The linear function sending g_i to x_i for every *i* is well defined if and only if the vector $x = (x_1, \dots, x_N)$ lies in the nullspace of the coefficient matrix $R = (r_{ij})$ given by the relations of *L*.

Let $k \in \ker(f)$ solve the matrix equation:

$$R \cdot k = R \cdot x.$$

Define a module homomorphism by sending the generators of L to $x_1 - k_1, \dots, x_N - k_N$. This is well defined, and is also a lift of this homomorphism over f .

Note that it does not matter how we choose the initial elements x_i : If x' is another choice then $x' - x \in \ker(f)$ and $R \cdot k = R \cdot x$ if and only if $R \cdot (k + x' - x) = R \cdot x'$.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
```

Lifting a map from a free module is always possible:

```
sage: M = FPMModule(A, [0], [[Sq(3)]]])
sage: N = FPMModule(A, [0], [[Sq(2,2)]]])
sage: F = FPMModule(A, [0])
sage: f = Hom(M,N)([Sq(2)*N.generator(0)])
sage: k = Hom(F,N)([Sq(1)*Sq(2)*N.generator(0)])
sage: f_ = k.lift(f)
sage: f*f_ == k
True
sage: f_
Module morphism:
  From: Free graded left module on 1 generator over mod 2 Steenrod algebra,
↪milnor basis
  To:   Finitely presented left module on 1 generator and 1 relation over mod 2
↪Steenrod algebra, milnor basis
  Defn: g[0] |--> Sq(1)*g[0]
```

A split projection:

```
sage: A_plus_HZ = FPMModule(A, [0,0], [[0, Sq(1)]]])
sage: HZ = FPMModule(A, [0], [[Sq(1)]]])
sage: q = Hom(A_plus_HZ, HZ)([HZ([1]), HZ([1])])
sage: # We can construct a splitting of `q` manually:
sage: split = Hom(HZ,A_plus_HZ)([A_plus_HZ.generator(1)])
sage: (q*split).is_identity()
True
```

Thus, lifting the identity homomorphism over q should be possible:

```
sage: one = Hom(HZ,HZ).identity()
sage: j = one.lift(q); j
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over mod 2
↪Steenrod algebra, milnor basis
  To:   Finitely presented left module on 2 generators and 1 relation over mod 2
↪2 Steenrod algebra, milnor basis
  Defn: g[0] |--> g[0, 1]
sage: q*j
Module endomorphism of Finitely presented left module on 1 generator and 1
↪relation over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> g[0]
```

Lifting over the inclusion of the image sub module:

```

sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0], relations=[[Sq(0,1)]])
sage: f = Hom(M,M)([Sq(2)*M.generator(0)])
sage: im = f.image(top_dim=10)
sage: f.lift(im)
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over mod 2
  ↪ Steenrod algebra, milnor basis
  To:   Finitely presented left module on 1 generator and 2 relations over mod 2
  ↪ 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> g[2]

```

When a lift cannot be found, the `None` value is returned. By setting the `verbose` argument to `True`, an explanation of why the lifting failed will be displayed:

```

sage: F2 = FPMModule(A, [0,0])
sage: non_surjection = Hom(F2, F2)([F2([1, 0]), F2([0, 0])])
sage: lift = Hom(F2, F2).identity().lift(non_surjection, verbose=True)
The generators of the domain of this homomorphism do not map into
the image of the homomorphism we are lifting over.
sage: lift is None
True

```

See also:

[`split\(\)`](#)

`solve(x)`

Return an element in the inverse image of `x`.

INPUT:

- `x` – an element of the codomain of this morphism

OUTPUT:

An element of the domain which maps to `x` under this morphism or `None` if `x` was not in the image of this morphism.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0], [[Sq(3)]])
sage: N = FPMModule(A, [0], [[Sq(2,2)]])
sage: f = Hom(M, N)([Sq(2)*N.generator(0)])
sage: y = Sq(1,1)*N.generator(0); y
Sq(1,1)*g[0]
sage: x = f.solve(y); x
Sq(2)*g[0]
sage: y == f(x)
True

```

Trying to lift an element which is not in the image results in a `None` value:

```
sage: z = f.solve(Sq(1)*N.generator(0))
sage: z is None
True
```

split(*verbose=False*)

Return a split of self.

INPUT:

- *verbose* – boolean (default: False); enable progress messages

OUTPUT:

A homomorphism with the property that the composite homomorphism $S \circ f = id$, where S is self, is The identity homomorphism If no such split exist, None is returned.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0,0], [[0, Sq(1)]])
sage: N = FPMModule(A, [0], [[Sq(1)]])
sage: p = Hom(M, N)([N.generator(0), N.generator(0)])
sage: s = p.split(); s
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over mod 2
  ↪ Steenrod algebra, milnor basis
  To:   Finitely presented left module on 2 generators and 1 relation over mod
  ↪ 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> g[0, 1]
sage: # Verify that `s` is a splitting:
sage: p*s
Module endomorphism of Finitely presented left module on 1 generator and 1
  ↪ relation over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> g[0]
```

See also:

[*lift\(\)*](#)

suspension(*t*)

The suspension of this morphism by the given degree *t*.

INPUT:

- *t* – an integer by which the morphism is suspended

OUTPUT:

The morphism which is the suspension of self by the degree *t*.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: F1 = FPMModule(A, [4,5])
sage: F2 = FPMModule(A, [5])
sage: f = Hom(F1, F2)( ( F2([Sq(4)]), F2([Sq(5)]) ) ); f
```

(continues on next page)

(continued from previous page)

```

Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra,
  ↪milnor basis
  To:   Free graded left module on 1 generator over mod 2 Steenrod algebra,
  ↪milnor basis
  Defn: g[4] |--> Sq(4)*g[5]
        g[5] |--> Sq(5)*g[5]

sage: e1 = F1([1, 0])
sage: e2 = F1([0, 1])
sage: f(e1)
Sq(4)*g[5]
sage: f(e2)
Sq(5)*g[5]

sage: sf = f.suspension(4); sf
Module morphism:
  From: Free graded left module on 2 generators over mod 2 Steenrod algebra,
  ↪milnor basis
  To:   Free graded left module on 1 generator over mod 2 Steenrod algebra,
  ↪milnor basis
  Defn: g[8] |--> Sq(4)*g[9]
        g[9] |--> Sq(5)*g[9]

sage: sf.domain() is f.domain().suspension(4)
True

sage: sf.codomain() is f.codomain().suspension(4)
True

```

values()

The values under `self` of the module generators of the domain module.

OUTPUT:

A sequence of module elements of the codomain.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: M = FPMModule(A, [0,1], [[Sq(2), Sq(1)]])
sage: N = FPMModule(A, [2], [[Sq(4)]])
sage: homspace = Hom(M, N)

sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]
sage: f = homspace(values)

sage: f.values()
(Sq(5)*g[2], Sq(3,1)*g[2])

sage: homspace.zero().values()
(0, 0)

```

(continues on next page)

(continued from previous page)

```

sage: homspace = Hom(A.free_graded_module((0,1)), A.free_graded_module((2,)))
sage: N = homspace.codomain()
sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]
sage: f = homspace(values)
sage: f.values()
(Sq(5)*g[2], Sq(3,1)*g[2])
sage: homspace.zero().values()
(0, 0)

```

vector_presentation(*n*)

Return the restriction of `self` to the domain module elements of degree `n`.

The restriction of a non-zero module homomorphism to the free module of module elements of degree n is a linear function into the free module of elements of degree $n + d$ belonging to the codomain. Here d is the degree of this homomorphism.

When this homomorphism is zero, it has no well defined degree so the function cannot be presented since we do not know the degree of its codomain. In this case, an error is raised.

INPUT:

- `n` – an integer degree

OUTPUT:

A linear function of finite dimensional free modules over the ground ring of the algebra for this module. The domain is isomorphic to the free module of domain elements of degree `n` of `self` via the choice of basis given by `basis_elements()`. If the morphism is zero, an error is raised.

See also:

- `sage.modules.fp_graded.module.FPModule.vector_presentation()`
- `sage.modules.fp_graded.module.FPModule.basis_elements()`
- `sage.modules.fp_graded.free_module.FreeGradedModule.vector_presentation()`
- `sage.modules.fp_graded.free_module.FreeGradedModule.basis_elements()`

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FPModule
sage: A = SteenrodAlgebra(2)
sage: M = FPModule(A, [0,1], [[Sq(2), Sq(1)]])
sage: N = FPModule(A, [2], [[Sq(4)]])
sage: values = [Sq(5)*N.generator(0), Sq(3,1)*N.generator(0)]
sage: f = Hom(M, N)(values)
sage: f.vector_presentation(0)
Vector space morphism represented by the matrix:
[0]
Domain: Vector space quotient V/W of dimension 1 over Finite Field of size 2
↳ where
V: Vector space of dimension 1 over Finite Field of size 2
W: Vector space of degree 1 and dimension 0 over Finite Field of size 2
Basis matrix:
[]
Codomain: Vector space quotient V/W of dimension 1 over Finite Field of size 2
↳ where

```

(continues on next page)

(continued from previous page)

```

V: Vector space of dimension 2 over Finite Field of size 2
W: Vector space of degree 2 and dimension 1 over Finite Field of size 2
Basis matrix:
[0 1]
sage: f.vector_presentation(1)
Vector space morphism represented by the matrix:
[0 0]
[0 1]
Domain: Vector space quotient V/W of dimension 2 over Finite Field of size 2
↳where
V: Vector space of dimension 2 over Finite Field of size 2
W: Vector space of degree 2 and dimension 0 over Finite Field of size 2
Basis matrix:
[]
Codomain: Vector space quotient V/W of dimension 2 over Finite Field of size 2
↳where
V: Vector space of dimension 3 over Finite Field of size 2
W: Vector space of degree 3 and dimension 1 over Finite Field of size 2
Basis matrix:
[0 1 1]
sage: f.vector_presentation(2)
Vector space morphism represented by the matrix:
[0 0]
Domain: Vector space quotient V/W of dimension 1 over Finite Field of size 2
↳where
V: Vector space of dimension 2 over Finite Field of size 2
W: Vector space of degree 2 and dimension 1 over Finite Field of size 2
Basis matrix:
[1 1]
Codomain: Vector space quotient V/W of dimension 2 over Finite Field of size 2
↳where
V: Vector space of dimension 4 over Finite Field of size 2
W: Vector space of degree 4 and dimension 2 over Finite Field of size 2
Basis matrix:
[0 0 1 0]
[0 0 0 1]

sage: M = A.free_graded_module((0,1))
sage: N = A.free_graded_module((2,))
sage: v = N.generator(0)
sage: values = [Sq(5)*v, Sq(3,1)*v]
sage: f = Hom(M, N)(values)
sage: f.vector_presentation(0)
Vector space morphism represented by the matrix:
[0 1]
Domain: Vector space of dimension 1 over Finite Field of size 2
Codomain: Vector space of dimension 2 over Finite Field of size 2
sage: f.vector_presentation(1)
Vector space morphism represented by the matrix:
[0 0 0]
[0 1 0]
Domain: Vector space of dimension 2 over Finite Field of size 2

```

(continues on next page)

(continued from previous page)

```

Codomain: Vector space of dimension 3 over Finite Field of size 2
sage: f.vector_presentation(2)
Vector space morphism represented by the matrix:
[0 0 1 1]
[0 0 0 0]
Domain: Vector space of dimension 2 over Finite Field of size 2
Codomain: Vector space of dimension 4 over Finite Field of size 2

```

5.8 Homsets of finitely presented graded modules

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

```

class sage.modules.fp_graded.homspace.FPModuleHomspace(X, Y, category=None, base=None,
                                                         check=True)

```

Bases: `sage.categories.homset.Homset`

Element

alias of `sage.modules.fp_graded.morphism.FPModuleMorphism`

an_element(*n=0*)

Create a homomorphism belonging to self.

INPUT:

- *n* – (default: 0) an integer degree

OUTPUT:

A module homomorphism of degree *n*.

EXAMPLES:

```

sage: from sage.modules.fp_graded.module import FModule
sage: A = SteenrodAlgebra(2)
sage: HZ = FModule(A, [0], relations=[[Sq(1)]])

sage: Hom(HZ, HZ).an_element(3)
Module endomorphism of Finitely presented left module on 1 generator and 1
relation over mod 2 Steenrod algebra, milnor basis
Defn: g[0] |--> Sq(0,1)*g[0]

```

basis_elements(*n*)

Return a basis for the free module of degree *n* morphisms.

INPUT:

- *n* – an integer degree

OUTPUT:

A basis for the set of all module homomorphisms of degree *n*.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A = SteenrodAlgebra(2)
sage: Hko = FPMModule(A, [0], relations=[[Sq(2)], [Sq(1)]])

sage: Hom(Hko, Hko).basis_elements(21)
[Module endomorphism of Finitely presented left module on 1 generator and 2
↪relations over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> (Sq(0,0,3)+Sq(0,2,0,1))*g[0],
Module endomorphism of Finitely presented left module on 1 generator and 2
↪relations over mod 2 Steenrod algebra, milnor basis
  Defn: g[0] |--> Sq(8,2,1)*g[0]]
```

identity()

Return the identity homomorphism.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: L = FPMModule(A2, [2,3], [[Sq(2),Sq(1)], [0,Sq(2)]])

sage: one = Hom(L, L).identity(); one
Module endomorphism of Finitely presented left module on 2 generators and 2
↪relations over sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis,
↪profile function [3, 2, 1]
  Defn: g[2] |--> g[2]
        g[3] |--> g[3]

sage: e = L.an_element(5)
sage: e == one(e)
True
```

It is an error to call this function when the homset is not a set of endomorphisms:

```
sage: F = FPMModule(A2, [1,3])
sage: Hom(F,L).identity()
Traceback (most recent call last):
...
TypeError: this homspace does not consist of endomorphisms
```

An example with free graded modules:

```
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: L = A2.free_graded_module((2,3))
sage: H = Hom(L, L)
sage: H.identity()
Module endomorphism of Free graded left module on 2 generators
over sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile
↪function [3, 2, 1]
  Defn: g[2] |--> g[2]
        g[3] |--> g[3]
```

zero()

Create the trivial homomorphism in self.

EXAMPLES:

```
sage: from sage.modules.fp_graded.module import FPMModule
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: F = FPMModule(A2, [1,3])
sage: L = FPMModule(A2, [2,3], [[Sq(2),Sq(1)], [0,Sq(2)]])

sage: z = Hom(F, L).zero()
sage: z(F.an_element(5))
0
sage: z(F.an_element(23))
0
```

Example with free modules:

```
sage: A2 = SteenrodAlgebra(2, profile=(3,2,1))
sage: F = A2.free_graded_module((1,3))
sage: L = A2.free_graded_module((2,3))
sage: H = Hom(F, L)
sage: H.zero()
Module morphism:
  From: Free graded left module on 2 generators over sub-Hopf algebra of mod 2
  ↪ Steenrod algebra, milnor basis, profile function [3, 2, 1]
  To:   Free graded left module on 2 generators over sub-Hopf algebra of mod 2
  ↪ Steenrod algebra, milnor basis, profile function [3, 2, 1]
Defn: g[1] |--> 0
      g[3] |--> 0
```

5.9 Finitely presented graded modules over the Steenrod algebra

This package allows the user to define finitely presented modules over the mod p Steenrod algebra, elements of them, and morphisms between them. Methods are provided for doing basic homological algebra, e.g. computing kernels and images of homomorphisms, and finding free resolutions of modules.

Theoretical background

The category of finitely presented graded modules over an arbitrary non-Noetherian graded ring R is not abelian in general, since kernels of homomorphisms are not necessarily finitely presented.

The mod p Steenrod algebra is non-Noetherian, but it is the union of a countable set of finite sub-Hopf algebras ([Mar1983] Ch. 15, Sect. 1, Prop 7). It is therefore an example of a P -algebra ([Mar1983] Ch. 13).

Any finitely presented module over the Steenrod algebra is defined over one of these finite sub-Hopf algebras. Similarly, any homomorphism between finitely presented modules over the Steenrod algebra is defined over a finite sub-Hopf algebra of the Steenrod algebra. Further, tensoring up from the category of modules over a sub-Hopf algebra is an exact functor, since the Steenrod algebra is free over any sub-Hopf algebra.

It follows that kernels, cokernels, images, and, more generally, any finite limits or colimits can be computed in the category of modules over the Steenrod algebra by working in the category of modules over an appropriate finite sub-Hopf algebra.

It is also the case that presentations of modules and the images of the generators of the domain of a homomorphism are the same over the sub-Hopf algebra and over the whole Steenrod algebra, so that the tensoring up is entirely implicit and requires no computation.

The definitions and computations carried out by this package are thus done as follows. First, find a small finite sub-Hopf algebra over which the computation can be done. Then, carry out the calculation there, where it is a finite problem and can be reduced to linear algebra over a finite prime field.

For examples, see the [Steenrod algebra modules](#) thematic tutorial.

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

class `sage.modules.fp_graded.steenrod.module.SteenrodFPModule(j, names)`

Bases: `sage.modules.fp_graded.module.FPModule`, `sage.modules.fp_graded.steenrod.module.SteenrodModuleMixin`

Create a finitely presented module over the Steenrod algebra.

See also:

The thematic tutorial on [Steenrod algebra modules](#).

INPUT:

One of the following:

- `arg0` – a morphism such that the module is the cokernel, or a free graded module, in which case the output is the same module, viewed as finitely presented

Otherwise:

- `arg0` – the graded connected algebra over which the module is defined; this algebra must be equipped with a graded basis
- `generator_degrees` – tuple of integer degrees
- `relations` – tuple of relations; a relation is a tuple of coefficients (c_1, \dots, c_n) , ordered so that they correspond to the module generators, that is, such a tuple corresponds to the relation

$$c_1 g_1 + \dots + c_n g_n = 0$$

if the generators are (g_1, \dots, g_n)

resolution(`k`, `top_dim=None`, `verbose=False`)

A free resolution of `self` of the given length.

INPUT:

- `k` – non-negative integer
- `top_dim` – (optional) stop the computation at this degree
- `verbose` – (default: `False`) whether log messages are printed

OUTPUT:

A list of homomorphisms $[\epsilon, f_1, \dots, f_k]$ such that

$$\begin{aligned} f_i : F_i &\rightarrow F_{i-1} \text{ for } 1 \leq i \leq k, \\ \epsilon : F_0 &\rightarrow M, \end{aligned}$$

where each F_i is a finitely generated free module, and the sequence

$$F_k \xrightarrow{f_k} F_{k-1} \xrightarrow{f_{k-1}} \dots \rightarrow F_0 \xrightarrow{\epsilon} M \rightarrow 0$$

is exact. Note that the 0th element in this list is the map ϵ , and the rest of the maps are between free modules.

EXAMPLES:

```
sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPMModule
sage: A = SteenrodAlgebra(2)
sage: Hko = SteenrodFPMModule(A, [0], [[Sq(1)], [Sq(2)]]])

sage: res = Hko.resolution(5, verbose=True)
Computing f_1 (1/5)
Computing f_2 (2/5)
Computing using the profile:
(2, 1)
Resolving the kernel in the range of dimensions [1, 8]: 1 2 3 4 5 6 7 8.
Computing f_3 (3/5)
Computing using the profile:
(2, 1)
Resolving the kernel in the range of dimensions [2, 10]: 2 3 4 5 6 7 8 9 10.
Computing f_4 (4/5)
Computing using the profile:
(2, 1)
Resolving the kernel in the range of dimensions [3, 13]: 3 4 5 6 7 8 9 10 11 12 ↵
↵13.
Computing f_5 (5/5)
Computing using the profile:
(2, 1)
Resolving the kernel in the range of dimensions [4, 18]: 4 5 6 7 8 9 10 11 12 ↵
↵13 14 15 16 17 18.
sage: [x.domain() for x in res]
[Free graded left module on 1 generator over mod 2 Steenrod algebra, milnor ↵
↵basis,
Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor ↵
↵basis,
Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor ↵
↵basis,
Free graded left module on 2 generators over mod 2 Steenrod algebra, milnor ↵
↵basis,
Free graded left module on 3 generators over mod 2 Steenrod algebra, milnor ↵
↵basis,
Free graded left module on 4 generators over mod 2 Steenrod algebra, milnor ↵
↵basis]
```

When there are no relations, the resolution is trivial:

```
sage: M = SteenrodFPMModule(A, [0])
sage: M.resolution(4)
[Module endomorphism of Free graded left module on 1 generator over mod 2 ↵
↵Steenrod algebra, milnor basis
Defn: g[0] |--> g[0],
Module morphism:
From: Free graded left module on 0 generators over mod 2 Steenrod algebra, ↵
↵milnor basis
```

(continues on next page)

(continued from previous page)

```

    To:   Free graded left module on 1 generator over mod 2 Steenrod algebra,
    ↪milnor basis,
    Module endomorphism of Free graded left module on 0 generators over mod 2
    ↪Steenrod algebra, milnor basis,
    Module endomorphism of Free graded left module on 0 generators over mod 2
    ↪Steenrod algebra, milnor basis,
    Module endomorphism of Free graded left module on 0 generators over mod 2
    ↪Steenrod algebra, milnor basis]

```

```

class sage.modules.fp_graded.steenrod.module.SteenrodFreeModule(algebra, generator_degrees,
                                                                category, names=None, **kws)
    Bases: sage.modules.fp_graded.free_module.FreeGradedModule, sage.modules.fp_graded.
            steenrod.module.SteenrodModuleMixin

```

```

class sage.modules.fp_graded.steenrod.module.SteenrodModuleMixin
    Bases: object

```

Mixin class for common methods of the Steenrod algebra modules.

```

export_module_definition(powers_of_two_only=True)

```

Return the module to the input `format` used by R. Bruner's Ext software as a string.

INPUT:

- `powers_of_two_only` – boolean (default: `True`); if the output should contain the action of all Steenrod squaring operations (restricted by the profile), or only the action of the operations of degree equal to a power of two

EXAMPLES:

```

sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPModule
sage: A1 = algebra=SteenrodAlgebra(p=2, profile=[2,1])
sage: M = SteenrodFPModule(A1, [0])
sage: print(M.export_module_definition())
8 0 1 2 3 3 4 5 6
0 1 1 1
2 1 1 4
3 1 1 5
6 1 1 7
0 2 1 2
1 2 2 3 4
2 2 1 5
3 2 1 6
4 2 1 6
5 2 1 7
sage: N = SteenrodFPModule(A1, [0], [[Sq(1)]])
sage: print(N.export_module_definition())
4 0 2 3 5
1 1 1 2
0 2 1 1
2 2 1 3
sage: print(N.export_module_definition(powers_of_two_only=False))
4 0 2 3 5
1 1 1 2
0 2 1 1

```

(continues on next page)

(continued from previous page)

```

2 2 1 3
0 3 1 2
sage: A2 = SteenrodAlgebra(p=2, profile=[3,2,1])
sage: Hko = SteenrodFPMModule(A2, [0], [[Sq(1)], [Sq(2)]]])
sage: print(Hko.export_module_definition())
8 0 4 6 7 10 11 13 17
2 1 1 3
4 1 1 5
1 2 1 2
5 2 1 6
0 4 1 1
2 4 1 4
3 4 1 5
6 4 1 7

```

profile()

Return a finite profile over which `self` can be defined.

Any finitely presented module over the Steenrod algebra can be defined over a finite-dimensional sub-Hopf algebra, and this method identifies such a sub-Hopf algebra and returns its profile function.

Note: The profile produced by this function is reasonably small but is not guaranteed to be minimal.

EXAMPLES:

```

sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPMModule
sage: A = SteenrodAlgebra(2)
sage: M = SteenrodFPMModule(A, [0,1], [[Sq(2),Sq(1)], [0,Sq(2)], [Sq(3),0]])
sage: M.profile()
(2, 1)

```

5.10 Homomorphisms of finitely presented modules over the Steenrod algebra

This class implements construction and basic manipulation of homomorphisms between *finitely presented graded modules* over the mod p Steenrod algebra.

AUTHORS:

- Robert R. Bruner, Michael J. Catanzaro (2012): Initial version.
- Sverre Lunoe-Nielsen and Koen van Woerden (2019-11-29): Updated the original software to Sage version 8.9.
- Sverre Lunoe-Nielsen (2020-07-01): Refactored the code and added new documentation and tests.

```
class sage.modules.fp_graded.steenrod.morphism.SteenrodFPMModuleMorphism(parent, values,
                                                                           check=True)
```

Bases: `sage.modules.fp_graded.morphism.FPMModuleMorphism`

cokernel_projection(*verbose=False*)

Compute the map to the cokernel of `self`.

INPUT:

- `verbose` – (default: `False`) whether log messages are printed

OUTPUT:

The natural projection from the codomain of this homomorphism to its cokernel.

EXAMPLES:

```
sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPMModule
sage: A1 = SteenrodAlgebra(2, profile=(2,1))
sage: M = SteenrodFPMModule(A1, [0], [[Sq(2)]])
sage: F = SteenrodFPMModule(A1, [0])

sage: r = Hom(F, M)([A1.Sq(1)*M.generator(0)])
sage: co = r.cokernel_projection(); co
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [2, 1]
  To:   Finitely presented left module on 1 generator and 2 relations over sub-
↳ Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [2, 1]
  Defn: g[0] |--> g[0]

sage: co.domain().is_trivial()
False
```

image(*top_dim=None, verbose=False*)

Return the image of `self`.

INPUT:

- `top_dim` – integer (optional); used by this function to stop the computation at the given degree
- `verbose` – (default: `False`) whether log messages are printed

OUTPUT:

An injective homomorphism into the codomain of `self` which is onto the image of `self`.

EXAMPLES:

```
sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPMModule
sage: A = SteenrodAlgebra(2)
sage: M = SteenrodFPMModule(A, [0,1], [[Sq(2),Sq(1)], [0,Sq(2)]])
sage: S = SteenrodFPMModule(A, [0], [[Sq(2)]])
sage: f = Hom(S, M)([M([0,1])])
sage: f.is_injective()
True
sage: i = f.image(); i
Module morphism:
  From: Finitely presented left module on 1 generator and 1 relation over mod 2_
↳ Steenrod algebra, milnor basis
  To:   Finitely presented left module on 2 generators and 2 relations over mod_
↳ 2 Steenrod algebra, milnor basis
  Defn: g[1] |--> g[1]
sage: i.codomain() is M
True
```

Lift the map f over the inclusion i :

```
sage: f_ = f.lift(i)
sage: f_.is_injective()
True
sage: f_.is_surjective()
True

sage: g = Hom(S, M)([M([Sq(3),Sq(2)])])
sage: j = g.image(); j
Module morphism:
  From: Free graded left module on 0 generators over mod 2 Steenrod algebra,
  ↪milnor basis
  To:   Finitely presented left module on 2 generators and 2 relations over mod_
  ↪2 Steenrod algebra, milnor basis
```

So g had to be trivial:

```
sage: g.is_zero()
True
```

is_injective(*top_dim=None, verbose=False*)

Return True if *self* is injective.

INPUT:

- *top_dim* – (optional) stop the computation at this degree; if not specified, this is determined using [profile\(\)](#)
- *verbose* – (default: False) whether log messages are printed

EXAMPLES:

```
sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPModule
sage: A = SteenrodAlgebra(2)
sage: M = SteenrodFPModule(A, [0,1], [[Sq(2),Sq(1)], [0,Sq(2)]])
sage: S = SteenrodFPModule(A, [0], [[Sq(2)]])
sage: f = Hom(S, M)([M([0,1])])
sage: f.is_injective()
True
sage: g = Hom(S, M).zero()
sage: g.is_injective()
False
sage: z = Hom(SteenrodFPModule(A, []), M).zero()
sage: z.is_injective()
True
sage: z.is_zero()
True
```

kernel_inclusion(*top_dim=None, verbose=False*)

Return the kernel of *self* as a morphism.

INPUT:

- *top_dim* – (optional) stop the computation at this degree; if not specified, this is determined using [profile\(\)](#)
- *verbose* – (default: False) whether log messages are printed

OUTPUT: An injective homomorphism into the domain `self` which is onto the kernel of this homomorphism.

EXAMPLES:

```
sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPMModule
sage: A = SteenrodAlgebra(2)
sage: M = SteenrodFPMModule(A, [0,1], [[Sq(2),Sq(1)], [0,Sq(2)]])
sage: S = SteenrodFPMModule(A, [0], [[Sq(2)]])
sage: f = Hom(S, M)([M([0,1])])
sage: f.is_injective()
True
sage: k = f.kernel_inclusion()
sage: k == 0
True
```

Since `k` is both trivial and injective, its domain should be the zero module:

```
sage: k.domain().is_trivial()
True
sage: g = Hom(S, M)([M([Sq(3),Sq(2)])])
sage: h = g.kernel_inclusion()
sage: h.is_identity()
True
sage: ker = h.domain();
sage: ker is S
True
```

So `g` had to be trivial:

```
sage: g.is_zero()
True
```

`profile()`

Return a finite profile over which `self` can be defined.

This is in some ways the key method for these morphisms. As discussed in the “Theoretical background” section of [sage.modules.fp_graded.steenrod.module](#), any homomorphism of finitely presented modules over the Steenrod algebra can be defined over a finite-dimensional sub-Hopf algebra, and this method identifies such a sub-Hopf algebra and returns its profile function.

EXAMPLES:

```
sage: from sage.modules.fp_graded.steenrod.module import SteenrodFPMModule
sage: A = SteenrodAlgebra(2)
sage: M = SteenrodFPMModule(A, [0,1], [[Sq(2),Sq(1)], [0,Sq(2)]])
sage: one = Hom(M,M).identity()
sage: one.profile()
(2, 1)
sage: zero = Hom(M,M).zero()
sage: zero.profile()
(2, 1)
sage: A_fin = SteenrodAlgebra(2, profile=(2,1))
sage: M_fin = M.change_ring(A_fin)
```

Change the ring of the module M:

```
sage: M_fin.change_ring(A) is M
True
```

We can change rings to the finite sub-Hopf algebra defined by the profile we just computed:

```
sage: one_fin = one.change_ring(A_fin)
sage: one_fin.domain()
Finitely presented left module on 2 generators and 2 relations over
sub-Hopf algebra of mod 2 Steenrod algebra, milnor basis, profile function [2, ↪
↪ 1]
```

If we change back to the full Steenrod algebra, we are back where we started:

```
sage: one_fin.change_ring(A) == one
True
```

```
class sage.modules.fp_graded.steenrod.morphism.SteenrodFreeModuleMorphism(parent, values)
Bases: sage.modules.fp_graded.free_morphism.FreeGradedModuleMorphism, sage.modules.
fp_graded.steenrod.morphism.SteenrodFPModuleMorphism
```


SPECIAL MODULES

6.1 Discrete subgroups of \mathbb{Z}^n

AUTHORS:

- Martin Albrecht (2014-03): initial version
- Jan Pöschko (2012-08): some code in this module was taken from Jan Pöschko's 2012 GSoC project

```
class sage.modules.free_module_integer.FreeModule_submodule_with_basis_integer(ambient,
                                                                              basis,
                                                                              check=True,
                                                                              echelo-
                                                                              nize=False,
                                                                              echelo-
                                                                              nized_basis=None,
                                                                              al-
                                                                              ready_echelonized=False,
                                                                              lll_reduce=True)
```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_pid`

This class represents submodules of \mathbb{Z}^n with a distinguished basis.

However, most functionality in excess of standard submodules over PID is for these submodules considered as discrete subgroups of \mathbb{Z}^n , i.e. as lattices. That is, this class provides functions for computing LLL and BKZ reduced bases for this free module with respect to the standard Euclidean norm.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice(sage.crypto.gen_lattice(type='modular', m=10, seed=1337,
↳ dual=True)); L
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[-1  1  2 -2  0  1  0 -1  2  1]
[ 1  0  0 -1 -2  1 -2  3 -1  0]
[ 1  2  0  2 -1  1 -2  2  2  0]
[ 1  0 -1  0  2  3  0  0 -1 -2]
[ 1 -3  0  0  2  1 -2 -1  0  0]
[-3  0 -1  0 -1  2 -2  0  0  2]
[ 0  0  0  1  0  2 -3 -3 -2 -1]
[ 0 -1 -4 -1 -1  1  2 -1  0  1]
[ 1  1 -2  1  1  2  1  1 -2  3]
```

(continues on next page)

(continued from previous page)

```
[ 2 -1  1  2 -3  2  2  1  0  1]
sage: L.shortest_vector()
(-1, 1, 2, -2, 0, 1, 0, -1, 2, 1)
```

BKZ(*args, **kws)Return a Block Korkine-Zolotareff reduced basis for `self`.

INPUT:

- `*args` – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.BKZ()`
- `*kws` – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.BKZ()`

OUTPUT:

An integer matrix which is a BKZ-reduced basis for this lattice.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='random', n=1, m=60, q=2^60, seed=42)
sage: L = IntegerLattice(A, lll_reduce=False)
sage: min(v.norm().n() for v in L.reduced_basis)
4.17330740711759e15

sage: L.LLL()
60 x 60 dense matrix over Integer Ring (use the '.str()' method to see the
↳ entries)

sage: min(v.norm().n() for v in L.reduced_basis)
5.19615242270663

sage: L.BKZ(block_size=10)
60 x 60 dense matrix over Integer Ring (use the '.str()' method to see the
↳ entries)

sage: min(v.norm().n() for v in L.reduced_basis)
4.12310562561766
```

Note: If `block_size == L.rank()` where `L` is this lattice, then this function performs Hermite-Korkine-Zolotareff (HKZ) reduction.

HKZ(*args, **kws)

Hermite-Korkine-Zolotarev (HKZ) reduce the basis.

A basis B of a lattice L , with orthogonalized basis B^* such that $B = M \cdot B^*$ is HKZ reduced, if and only if, the following properties are satisfied:

1. The basis B is size-reduced, i.e., all off-diagonal coefficients of M satisfy $|\mu_{i,j}| \leq 1/2$
2. The vector b_1 realizes the first minimum $\lambda_1(L)$.
3. The projection of the vectors b_2, \dots, b_r orthogonally to b_1 form an HKZ reduced basis.

Note: This is realized by calling `sage.modules.free_module_integer.FreeModule_submodule_with_basis_integer.BKZ()` with `block_size == self.rank()`.

INPUT:

- `*args` – passed through to `BKZ()`
- `*kwds` – passed through to `BKZ()`

OUTPUT:

An integer matrix which is a HKZ-reduced basis for this lattice.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = sage.crypto.gen_lattice(type='random', n=1, m=40, q=2^60, seed=1337,
↳ lattice=True)
sage: L.HKZ()
40 x 40 dense matrix over Integer Ring (use the '.str()' method to see the
↳ entries)

sage: L.reduced_basis[0]
(0, 0, -1, -1, 0, 0, -1, 1, 0, 0, -1, 1, 1, 0, 0, 1, 1, 1, -1, 0, 0, 1, -1, 0,
↳ 0, -1, 0, 0, 1, 0, 0, -1, 0, 0, 0, 1, 1, 0, 0, -2)
```

LLL(`*args`, `**kwds`)

Return an LLL reduced basis for `self`.

A lattice basis (b_1, b_2, \dots, b_d) is (δ, η) -LLL-reduced if the two following conditions hold:

- For any $i > j$, we have $|\mu_{i,j}| \leq \eta$.
- For any $i < d$, we have $\delta |b_i^*|^2 \leq |b_{i+1}^* + \mu_{i+1,i} b_i^*|^2$,

where $\mu_{i,j} = \langle b_i, b_j^* \rangle / \langle b_j^*, b_j^* \rangle$ and b_i^* is the i -th vector of the Gram-Schmidt orthogonalisation of (b_1, b_2, \dots, b_d) .

The default reduction parameters are $\delta = 3/4$ and $\eta = 0.501$.

The parameters δ and η must satisfy: $0.25 < \delta \leq 1.0$ and $0.5 \leq \eta < \sqrt{\delta}$. Polynomial time complexity is only guaranteed for $\delta < 1$.

INPUT:

- `*args` – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.LLL()`
- `**kwds` – passed through to `sage.matrix.matrix_integer_dense.Matrix_integer_dense.LLL()`

OUTPUT:

An integer matrix which is an LLL-reduced basis for this lattice.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = random_matrix(ZZ, 10, 10, x=-2000, y=2000)
sage: while A.rank() < 10:
```

(continues on next page)

(continued from previous page)

```

.....: A = random_matrix(ZZ, 10, 10)
sage: L = IntegerLattice(A, lll_reduce=False); L
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
...
sage: L.reduced_basis == A
True
sage: old = L.reduced_basis[0].norm().n()
sage: _ = L.LLL()
sage: new = L.reduced_basis[0].norm().n()
sage: new <= old
True

```

closest_vector(*t*)

Compute the closest vector in the embedded lattice to a given vector.

INPUT:

- *t* – the target vector to compute the closest vector to

OUTPUT:

The vector in the lattice closest to *t*.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[1, 0], [0, 1]])
sage: L.closest_vector((-6, 5/3))
(-6, 2)

```

ALGORITHM:

Uses the algorithm from [MV2010].

discriminant()

Return $|\det(G)|$, i.e. the absolute value of the determinant of the Gram matrix $B \cdot B^T$ for any basis B .

OUTPUT:

An integer.

EXAMPLES:

```

sage: L = sage.crypto.gen_lattice(m=10, seed=1337, lattice=True)
sage: L.discriminant()
214358881

```

is_unimodular()

Return True if this lattice is unimodular.

OUTPUT:

A boolean.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[1, 0], [0, 1]])

```

(continues on next page)

(continued from previous page)

```

sage: L.is_unimodular()
True
sage: IntegerLattice([[2, 0], [0, 3]]).is_unimodular()
False

```

reduced_basis

This attribute caches the currently best known reduced basis for `self`, where “best” is defined by the Euclidean norm of the first row vector.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: M = random_matrix(ZZ, 10, 10)
sage: while M.rank() < 10:
.....:     M = random_matrix(ZZ, 10, 10)
sage: L = IntegerLattice(M, lll_reduce=False)
sage: L.reduced_basis == M
True

sage: LLL = L.LLL()
sage: LLL == L.reduced_basis or bool(LLL[0].norm() >= M[0].norm())
True

```

shortest_vector(*update_reduced_basis=True, algorithm='fplll', *args, **kwds*)

Return a shortest vector.

INPUT:

- `update_reduced_basis` – (default: `True`) set this flag if the found vector should be used to improve the basis
- `algorithm` – (default: `"fplll"`) either `"fplll"` or `"pari"`
- `*args` – passed through to underlying implementation
- `**kwds` – passed through to underlying implementation

OUTPUT:

A shortest non-zero vector for this lattice.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='random', n=1, m=30, q=2^40, seed=42)
sage: L = IntegerLattice(A, lll_reduce=False)
sage: min(v.norm().n() for v in L.reduced_basis)
6.038907567000000e10

sage: L.shortest_vector().norm().n()
3.74165738677394

sage: L = IntegerLattice(A, lll_reduce=False)
sage: min(v.norm().n() for v in L.reduced_basis)
6.038907567000000e10

sage: L.shortest_vector(algorithm="pari").norm().n()

```

(continues on next page)

(continued from previous page)

```

3.74165738677394

sage: L = IntegerLattice(A, lll_reduce=True)
sage: L.shortest_vector(algorithm="pari").norm().n()
3.74165738677394

```

update_reduced_basis(*w*)

Inject the vector *w* and run LLL to update the basis.

INPUT:

- *w* – a vector

OUTPUT:

Nothing is returned but the internal state is modified.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='random', n=1, m=30, q=2^40, seed=42)
sage: L = IntegerLattice(A)
sage: B = L.reduced_basis
sage: v = L.shortest_vector(update_reduced_basis=False)
sage: L.update_reduced_basis(v)
sage: bool(L.reduced_basis[0].norm() < B[0].norm())
True

```

volume()

Return $\text{vol}(L)$ which is $\sqrt{\det(B \cdot B^T)}$ for any basis *B*.

OUTPUT:

An integer.

EXAMPLES:

```

sage: L = sage.crypto.gen_lattice(m=10, seed=1337, lattice=True)
sage: L.volume()
14641

```

voronoi_cell(*radius=None*)

Compute the Voronoi cell of a lattice, returning a Polyhedron.

INPUT:

- *radius* – (default: automatic determination) radius of ball containing considered vertices

OUTPUT:

The Voronoi cell as a Polyhedron instance.

The result is cached so that subsequent calls to this function return instantly.

EXAMPLES:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[1, 0], [0, 1]])
sage: V = L.voronoi_cell()

```

(continues on next page)

(continued from previous page)

```
sage: V.Vrepresentation()
(A vertex at (1/2, -1/2), A vertex at (1/2, 1/2), A vertex at (-1/2, 1/2), A
↪ vertex at (-1/2, -1/2))
```

The volume of the Voronoi cell is the square root of the discriminant of the lattice:

```
sage: L = IntegerLattice(Matrix(ZZ, 4, 4, [[0,0,1,-1],[1,-1,2,1],[-6,0,3,3],[-
↪ 6,-24,-6,-5]])); L
Free module of degree 4 and rank 4 over Integer Ring
User basis matrix:
[ 0  0  1 -1]
[ 1 -1  2  1]
[-6  0  3  3]
[-6 -24 -6 -5]
sage: V = L.voronoi_cell() # long time
sage: V.volume()           # long time
678
sage: sqrt(L.discriminant())
678
```

Lattices not having full dimension are handled as well:

```
sage: L = IntegerLattice([[2, 0, 0], [0, 2, 0]])
sage: V = L.voronoi_cell()
sage: V.Hrepresentation()
(An inequality (-1, 0, 0) x + 1 >= 0, An inequality (0, -1, 0) x + 1 >= 0, An
↪ inequality (1, 0, 0) x + 1 >= 0, An inequality (0, 1, 0) x + 1 >= 0)
```

ALGORITHM:

Uses parts of the algorithm from [VB1996].

voronoi_relevant_vectors()

Compute the embedded vectors inducing the Voronoi cell.

OUTPUT:

The list of Voronoi relevant vectors.

EXAMPLES:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: L = IntegerLattice([[3, 0], [4, 0]])
sage: L.voronoi_relevant_vectors()
[(-1, 0), (1, 0)]
```

`sage.modules.free_module_integer.IntegerLattice(basis, lll_reduce=True)`

Construct a new integer lattice from basis.

INPUT:

- **basis** – can be one of the following:
 - a list of vectors
 - a matrix over the integers
 - an element of an absolute order

- `lll_reduce` – (default: `True`) run LLL reduction on the basis on construction.

EXAMPLES:

We construct a lattice from a list of rows:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: IntegerLattice([[1,0,3], [0,2,1], [0,2,7]])
Free module of degree 3 and rank 3 over Integer Ring
User basis matrix:
[-2  0  0]
[ 0  2  1]
[ 1 -2  2]
```

Sage includes a generator for hard lattices from cryptography:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: A = sage.crypto.gen_lattice(type='modular', m=10, seed=1337, dual=True)
sage: IntegerLattice(A)
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[-1  1  2 -2  0  1  0 -1  2  1]
[ 1  0  0 -1 -2  1 -2  3 -1  0]
[ 1  2  0  2 -1  1 -2  2  2  0]
[ 1  0 -1  0  2  3  0  0 -1 -2]
[ 1 -3  0  0  2  1 -2 -1  0  0]
[-3  0 -1  0 -1  2 -2  0  0  2]
[ 0  0  0  1  0  2 -3 -3 -2 -1]
[ 0 -1 -4 -1 -1  1  2 -1  0  1]
[ 1  1 -2  1  1  2  1  1 -2  3]
[ 2 -1  1  2 -3  2  2  1  0  1]
```

You can also construct the lattice directly:

```
sage: from sage.modules.free_module_integer import IntegerLattice
sage: sage.crypto.gen_lattice(type='modular', m=10, seed=1337, dual=True,
↪ lattice=True)
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[-1  1  2 -2  0  1  0 -1  2  1]
[ 1  0  0 -1 -2  1 -2  3 -1  0]
[ 1  2  0  2 -1  1 -2  2  2  0]
[ 1  0 -1  0  2  3  0  0 -1 -2]
[ 1 -3  0  0  2  1 -2 -1  0  0]
[-3  0 -1  0 -1  2 -2  0  0  2]
[ 0  0  0  1  0  2 -3 -3 -2 -1]
[ 0 -1 -4 -1 -1  1  2 -1  0  1]
[ 1  1 -2  1  1  2  1  1 -2  3]
[ 2 -1  1  2 -3  2  2  1  0  1]
```

We construct an ideal lattice from an element of an absolute order:

```
sage: K.<a> = CyclotomicField(17)
sage: O = K.ring_of_integers()
sage: f = O(-a^15 + a^13 + 4*a^12 - 12*a^11 - 256*a^10 + a^9 - a^7 - 4*a^6 + a^5 +
↪ 210*a^4 + 2*a^3 - 2*a^2 + 2*a - 2)
```

(continues on next page)

(continued from previous page)

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: IntegerLattice(f)
Free module of degree 16 and rank 16 over Integer Ring
User basis matrix:
[ -2   2  -2   2  210   1  -4  -1   0   1 -256 -12   4   1   0  -1]
[ 33  48  44  48 256 -209  28  51  45  49  -1  35  44  48  44  48]
[  1  -1   3  -1   3 211   2  -3   0   1   2 -255 -11   5   2   1]
[-223  34  50  47 258   0  29  45  46  47   2 -11  33  48  44  48]
[ -13  31  46  42  46  -2 -225  32  48  45 256  -2  27  43  44  45]
[ -16  33  42  46 254   1 -19  32  44  45   0 -13 -225  32  48  45]
[ -15 -223  30  50 255   1 -20  32  42  47  -2 -11 -15  33  44  44]
[ -11 -11  33  48 256   3 -17 -222  32  53   1  -9 -14  35  44  48]
[ -12 -13  32  45 257   0 -16 -13  32  48  -1 -10 -14 -222  31  51]
[  -9 -13 -221  32  52   1 -11 -12  33  46 258   1 -15 -12  33  49]
[  -5  -2  -1   0 -257 -13   3   0  -1  -2  -1  -3   1  -3   1 209]
[ -15 -11 -15  33 256  -1 -17 -14 -225  33   4 -12 -13 -14  31  44]
[ 11  11  11  11 -245  -3  17  10  13 220  12   5  12   9  14 -35]
[ -18 -15 -20  29 250  -3 -23 -16 -19  30  -4 -17 -17 -17 -229  28]
[ -15 -11 -15 -223 242   5 -18 -12 -16  34  -2 -11 -15 -11 -15  33]
[ 378 120  92 147 152 462 136  96  99 144 -52 412 133  91 -107 138]

```

We construct \mathbb{Z}^n :

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: IntegerLattice(ZZ^10)
Free module of degree 10 and rank 10 over Integer Ring
User basis matrix:
[1 0 0 0 0 0 0 0 0 0]
[0 1 0 0 0 0 0 0 0 0]
[0 0 1 0 0 0 0 0 0 0]
[0 0 0 1 0 0 0 0 0 0]
[0 0 0 0 1 0 0 0 0 0]
[0 0 0 0 0 1 0 0 0 0]
[0 0 0 0 0 0 1 0 0 0]
[0 0 0 0 0 0 0 1 0 0]
[0 0 0 0 0 0 0 0 1 0]
[0 0 0 0 0 0 0 0 0 1]

```

Sage also interfaces with fpylll's lattice generator:

```

sage: from sage.modules.free_module_integer import IntegerLattice
sage: from fpylll import IntegerMatrix
sage: A = IntegerMatrix.random(8, "simdioph", bits=20, bits2=10)
sage: A = A.to_matrix(matrix(ZZ, 8, 8))
sage: IntegerLattice(A, lll_reduce=False)
Free module of degree 8 and rank 8 over Integer Ring
User basis matrix:
[ 1024 829556 161099 11567 521155 769480 639201 689979]
[      0 1048576      0      0      0      0      0]
[      0      0 1048576      0      0      0      0]
[      0      0      0 1048576      0      0      0]
[      0      0      0      0 1048576      0      0]

```

(continues on next page)

(continued from previous page)

[0	0	0	0	0	1048576	0	0]
[0	0	0	0	0	0	1048576	0]
[0	0	0	0	0	0	0	1048576]

6.2 Free quadratic modules

Sage supports computation with free quadratic modules over an arbitrary commutative ring. Nontrivial functionality is available over \mathbb{Z} and fields. All free modules over an integral domain are equipped with an embedding in an ambient vector space and an inner product, which you can specify and change.

Create the free module of rank n over an arbitrary commutative ring R using the command `FreeModule(R,n)` with a given `inner_product_matrix`.

The following example illustrates the creation of both a vector spaces and a free module over the integers and a submodule of it. Use the functions `FreeModule`, `span` and member functions of free modules to create free modules. “Do not use the `FreeModule_XXX` constructors directly.”

EXAMPLES:

```
sage: M = Matrix(QQ,[[2,1,0],[1,2,1],[0,1,2]])
sage: V = VectorSpace(QQ,3,inner_product_matrix=M)
sage: type(V)
<class 'sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_field_with_
↳category'>
sage: V.inner_product_matrix()
[2 1 0]
[1 2 1]
[0 1 2]
sage: W = V.subspace([[1,2,7],[1,1,0]])
sage: type(W)
<class 'sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_field_with_
↳category'>
sage: W
Quadratic space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -7]
[ 0  1  7]
Inner product matrix:
[2 1 0]
[1 2 1]
[0 1 2]
sage: W.gram_matrix()
[ 100 -104]
[-104  114]
```

AUTHORS:

- David Kohel (2008-06): First created (based on `free_module.py`)

`sage.modules.free_quadratic_module.FreeQuadraticModule`(*base_ring*, *rank*, *inner_product_matrix*,
sparse=False, *inner_product_ring=None*)

Create the free quadratic module over the given commutative ring of the given rank.

INPUT:

- `base_ring` – a commutative ring
- `rank` – a nonnegative integer
- `inner_product_matrix` – the inner product matrix
- `sparse` – bool; (default False)
- `inner_product_ring` – the inner product codomain ring; (default None)

OUTPUT:

A free quadratic module (with given inner product matrix).

Note: In Sage it is the case that there is only one dense and one sparse free ambient quadratic module of rank n over R and given inner product matrix.

EXAMPLES:

```
sage: M2 = FreeQuadraticModule(ZZ,2,inner_product_matrix=[1,2,3,4])
sage: M2 is FreeQuadraticModule(ZZ,2,inner_product_matrix=[1,2,3,4])
True
sage: M2.inner_product_matrix()
[1 2]
[3 4]
sage: M3 = FreeModule(ZZ,2,inner_product_matrix=[[1,2],[3,4]])
sage: M3 is M2
True
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient(base_ring, rank,
                                                                    inner_product_matrix,
                                                                    sparse=False)

Bases: sage.modules.free_module.FreeModule_ambient, sage.modules.free_quadratic_module.
FreeQuadraticModule_generic
```

Ambient free module over a commutative ring.

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_domain(base_ring, rank,
                                                                              in-
                                                                              ner_product_matrix,
                                                                              sparse=False)

Bases: sage.modules.free_module.FreeModule_ambient_domain, sage.modules.
free_quadratic_module.FreeQuadraticModule_ambient
```

Ambient free quadratic module over an integral domain.

ambient_vector_space()

Returns the ambient vector space, which is this free module tensored with its fraction field.

EXAMPLES:

```
sage: M = ZZ^3; M.ambient_vector_space()
Vector space of dimension 3 over Rational Field
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_field(base_field,
                                                                              dimension, in-
                                                                              ner_product_matrix,
                                                                              sparse=False)

Bases: sage.modules.free_module.FreeModule_ambient_field, sage.modules.
```

```
free_quadratic_module.FreeQuadraticModule_generic_field, sage.modules.  
free_quadratic_module.FreeQuadraticModule_ambient_pid
```

Create the ambient vector space of given dimension over the given field.

INPUT:

- `base_field` – a field
- `dimension` – a non-negative integer
- `sparse` – bool (default: False)

EXAMPLES:

```
sage: VectorSpace(QQ,3,inner_product_matrix=[[2,1,0],[1,2,0],[0,1,2]])  
Ambient quadratic space of dimension 3 over Rational Field  
Inner product matrix:  
[2 1 0]  
[1 2 0]  
[0 1 2]
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_pid(base_ring, rank, inner_product_matrix,  
                                                                           sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_ambient_pid`, `sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid`, `sage.modules.free_quadratic_module.FreeQuadraticModule_ambient_domain`

Ambient free quadratic module over a principal ideal domain.

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_generic(base_ring, rank, degree,  
                                                                       inner_product_matrix,  
                                                                       sparse=False)
```

Bases: `sage.modules.free_module.FreeModule_generic`

Base class for all free quadratic modules.

Modules are ordered by inclusion in the same ambient space.

ambient_module()

Return the ambient module associated to this module.

EXAMPLES:

```
sage: R.<x,y> = QQ[]  
sage: M = FreeModule(R,2)  
sage: M.ambient_module()  
Ambient free module of rank 2 over the integral domain Multivariate Polynomial  
Ring in x, y over Rational Field  
  
sage: V = FreeModule(QQ, 4).span([[1,2,3,4], [1,0,0,0]]); V  
Vector space of degree 4 and dimension 2 over Rational Field  
Basis matrix:  
[ 1  0  0  0]  
[ 0  1 3/2  2]  
sage: V.ambient_module()  
Vector space of dimension 4 over Rational Field
```

determinant()

Return the determinant of this free module.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3, inner_product_matrix=1)
sage: M.determinant()
1
sage: N = M.span([[1,2,3]])
sage: N.determinant()
14
sage: P = M.span([[1,2,3], [1,1,1]])
sage: P.determinant()
6
```

discriminant()

Return the discriminant of this free module, defined to be $(-1)^r$ of the determinant, where $r = n/2$ (n even) or $(n-1)/2$ (n odd) for a module of rank n .

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.discriminant()
1
sage: N = M.span([[1,2,3]])
sage: N.discriminant()
14
sage: P = M.span([[1,2,3], [1,1,1]])
sage: P.discriminant()
6
```

gram_matrix()

Return the gram matrix associated to this free module, defined to be $G = B \cdot A \cdot B.\text{transpose}()$, where A is the inner product matrix (induced from the ambient space), and B the basis matrix.

EXAMPLES:

```
sage: V = VectorSpace(QQ,4)
sage: u = V([1/2,1/2,1/2,1/2])
sage: v = V([0,1,1,0])
sage: w = V([0,0,1,1])
sage: M = span([u,v,w], ZZ)
sage: M.inner_product_matrix() == V.inner_product_matrix()
True
sage: L = M.submodule_with_basis([u,v,w])
sage: L.inner_product_matrix() == M.inner_product_matrix()
True
sage: L.gram_matrix()
[1 1 1]
[1 2 1]
[1 1 2]
```

inner_product_matrix()

Return the inner product matrix associated to this module. By definition this is the inner product matrix of the ambient space, hence may be of degree greater than the rank of the module.

N.B. The inner product does not have to be symmetric (see examples).

TODO: Differentiate the image ring of the inner product from the base ring of the module and/or ambient space. E.g. On an integral module over $\mathbb{Z}\mathbb{Z}$ the inner product pairing could naturally take values in $\mathbb{Z}\mathbb{Z}$, $\mathbb{Q}\mathbb{Q}$, $\mathbb{R}\mathbb{R}$, or $\mathbb{C}\mathbb{C}$.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: M.inner_product_matrix()
[1 0 0]
[0 1 0]
[0 0 1]
```

The inner product does not have to be symmetric or definite:

```
sage: N = FreeModule(ZZ, 2, inner_product_matrix=[[1, -1], [2, 5]])
sage: N.inner_product_matrix()
[ 1 -1]
[ 2  5]
sage: u, v = N.basis()
sage: u.inner_product(v)
-1
sage: v.inner_product(u)
2
```

The inner product matrix is defined with respect to the ambient space.

```
sage: V = QQ^3 sage: u = V([1/2, 1, 1]) sage: v = V([1, 1/2]) sage: M = span([u, v], ZZ)
sage: M.inner_product_matrix() [1 0 0] [0 1 0] [0 0 1] sage: M.inner_product_matrix() ==
V.inner_product_matrix() True sage: M.gram_matrix() [ 1/2 -3/4] [-3/4 13/4]
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_generic_field(base_field,
                                                                              dimension, degree,
                                                                              in-
                                                                              ner_product_matrix,
                                                                              sparse=False)
Bases: sage.modules.free_module.FreeModule_generic_field, sage.modules.
free_quadratic_module.FreeQuadraticModule_generic_pid
```

Base class for all free modules over fields.

span(gens, check=True, already_echelonized=False)

Return the K -span of the given list of gens, where K is the base field of self. Note that this span is a subspace of the ambient vector space, but need not be a subspace of self.

INPUT:

- gens – list of vectors
- check – bool (default: True): whether or not to coerce entries of gens into base field
- already_echelonized – bool (default: False): set this if you know the gens are already in echelon form

EXAMPLES:

```
sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2, 3, 4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
```

(continues on next page)

(continued from previous page)

```

sage: W.span([[1,1,1]])
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 1 1]

```

span_of_basis(*basis*, *check=True*, *already_echelonized=False*)

Return the free K-module with the given basis, where K is the base field of self. Note that this span is a subspace of the ambient vector space, but need not be a subspace of self.

INPUT:

- *basis* – list of vectors
- *check* – bool (default: True): whether or not to coerce entries of gens into base field
- *already_echelonized* – bool (default: False): set this if you know the gens are already in echelon form

EXAMPLES:

```

sage: V = VectorSpace(GF(7), 3)
sage: W = V.subspace([[2,3,4]]); W
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 5 2]
sage: W.span_of_basis([[2,2,2], [3,3,0]])
Vector space of degree 3 and dimension 2 over Finite Field of size 7
User basis matrix:
[2 2 2]
[3 3 0]

```

The basis vectors must be linearly independent or a `ValueError` exception is raised:

```

sage: W.span_of_basis([[2,2,2], [3,3,3]])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.

```

```

class sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid(base_ring, rank,
                                                                           degree, inner_product_matrix,
                                                                           sparse=False)
Bases:      sage.modules.free_module.FreeModule_generic_pid,      sage.modules.
free_quadratic_module.FreeQuadraticModule_generic

```

Class of all free modules over a PID.

span(*gens*, *check=True*, *already_echelonized=False*)

Return the R-span of the given list of gens, where R is the base ring of self. Note that this span need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```

sage: V = FreeModule(ZZ, 3)
sage: W = V.submodule([V.gen(0)])
sage: W.span([V.gen(1)])

```

(continues on next page)

(continued from previous page)

```
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[0 1 0]
sage: W.submodule([V.gen(1)])
Traceback (most recent call last):
...
ArithmeticError: argument gens (= [(0, 1, 0)]) does not generate a submodule of_
↳self
```

span_of_basis(basis, check=True, already_echelonized=False)

Return the free R-module with the given basis, where R is the base ring of self. Note that this R-module need not be a submodule of self, nor even of the ambient space. It must, however, be contained in the ambient vector space, i.e., the ambient space tensored with the fraction field of R.

EXAMPLES:

```
sage: M = FreeModule(ZZ, 3)
sage: W = M.span_of_basis([M([1, 2, 3])])
```

Next we create two free \mathbf{Z} -modules, neither of which is a submodule of W :

```
sage: W.span_of_basis([M([2, 4, 0])])
Free module of degree 3 and rank 1 over Integer Ring
User basis matrix:
[2 4 0]
```

The following module is not even in the ambient space:

```
sage: Q = QQ
sage: W.span_of_basis([ Q('1/5')*M([1, 2, 0]), Q('1/7')*M([1, 1, 0]) ])
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[1/5 2/5 0]
[1/7 1/7 0]
```

Of course the input basis vectors must be linearly independent:

```
sage: W.span_of_basis([ [1, 2, 0], [2, 4, 0] ])
Traceback (most recent call last):
...
ValueError: The given basis vectors must be linearly independent.
```

zero_submodule()

Return the zero submodule of this module.

EXAMPLES:

```
sage: V = FreeModule(ZZ, 2)
sage: V.zero_submodule()
Free module of degree 2 and rank 0 over Integer Ring
Echelon basis matrix:
[]
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_field(ambient, gens,
                                                                           inner_product_matrix,
                                                                           check=True, already_echelonized=False)
    sage.modules.
```

Bases: `sage.modules.free_module.FreeModule_submodule_field`,
`free_quadratic_module.FreeQuadraticModule_submodule_with_basis_field`

An embedded vector subspace with echelonized basis.

EXAMPLES:

Since this is an embedded vector subspace with echelonized basis, the `echelon_coordinates()` and `user_coordinates()` agree:

```
sage: V = QQ^3
sage: W = V.span([[1,2,3],[4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]

sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.basis_matrix()
(1, 5, 9)

sage: v = V([1,5,9])
sage: W.coordinates(v)
[1, 5]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)
```

```
class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_pid(ambient, gens, inner_product_matrix,
                                                                           check=True, already_echelonized=False)
    sage.modules.
```

Bases: `sage.modules.free_module.FreeModule_submodule_pid`,
`free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid`

An R -submodule of K^n where K is the fraction field of a principal ideal domain R .

EXAMPLES:

```
sage: M = ZZ^3
sage: W = M.span_of_basis([[1,2,3],[4,5,19]]); W
Free module of degree 3 and rank 2 over Integer Ring
User basis matrix:
[ 1  2  3]
[ 4  5 19]
```

We can save and load submodules and elements:

```

sage: loads(W.dumps()) == W
True
sage: v = W.0 + W.1
sage: loads(v.dumps()) == v
True

```

```

class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_field(ambient,
                                                                                          ba-
                                                                                          sis,
                                                                                          in-
                                                                                          ner_product_matrix,
                                                                                          check=True,
                                                                                          ech-
                                                                                          e-
                                                                                          l-
                                                                                          o-
                                                                                          nize=False,
                                                                                          ech-
                                                                                          e-
                                                                                          l-
                                                                                          o-
                                                                                          nized_basis=None,
                                                                                          al-
                                                                                          ready_echelonized=
Bases:      sage.modules.free_module.FreeModule_submodule_with_basis_field,      sage.
modules.free_quadratic_module.FreeQuadraticModule_generic_field,      sage.modules.
free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid

```

An embedded vector subspace with a distinguished user basis.

EXAMPLES:

```

sage: M = QQ^3; W = M.submodule_with_basis([[1,2,3], [4,5,19]]); W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  2  3]
[ 4  5 19]

```

Since this is an embedded vector subspace with a distinguished user basis possibly different than the echelonized basis, the `echelon_coordinates()` and `user_coordinates()` do not agree:

```

sage: V = QQ^3
sage: W = V.submodule_with_basis([[1,2,3], [4,5,6]])
sage: W
Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 2 3]
[4 5 6]

sage: v = V([1,5,9])
sage: W.echelon_coordinates(v)
[1, 5]
sage: vector(QQ, W.echelon_coordinates(v)) * W.echelonized_basis_matrix()
(1, 5, 9)

```

(continues on next page)

(continued from previous page)

```

sage: v = V([1,5,9])
sage: W.coordinates(v)
[5, -1]
sage: vector(QQ, W.coordinates(v)) * W.basis_matrix()
(1, 5, 9)

```

We can load and save submodules:

```

sage: loads(W.dumps()) == W
True

sage: K.<x> = FractionField(PolynomialRing(QQ, 'x'))
sage: M = K^3; W = M.span_of_basis([[1,1,x]])
sage: loads(W.dumps()) == W
True

```

```

class sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid(ambient,
                                                                                          ba-
                                                                                          sis,
                                                                                          in-
                                                                                          ner_product_matrix,
                                                                                          check=True,
                                                                                          ech-
                                                                                          elo-
                                                                                          nize=False,
                                                                                          ech-
                                                                                          elo-
                                                                                          nized_basis=None,
                                                                                          al-
                                                                                          ready_echelonized=False)

```

Bases: `sage.modules.free_module.FreeModule_submodule_with_basis_pid`, `sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid`

An R -submodule of K^n with distinguished basis, where K is the fraction field of a principal ideal domain R .

Modules are ordered by inclusion.

EXAMPLES:

First we compare two equal vector spaces:

```

sage: A = FreeQuadraticModule(QQ,3,2*matrix.identity(3))
sage: V = A.span([[1,2,3], [5,6,7], [8,9,10]])
sage: W = A.span([[5,6,7], [8,9,10]])
sage: V == W
True

```

Next we compare a one dimensional space to the two dimensional space defined above:

```

sage: M = A.span([[5,6,7]])
sage: V == M
False
sage: M < V
True

```

(continues on next page)

(continued from previous page)

```
sage: V < M
False
```

We compare a \mathbf{Z} -module to the one-dimensional space above:

```
sage: V = A.span([[5,6,7]])
sage: V = V.change_ring(ZZ).scale(1/11)
sage: V < M
True
sage: M < V
False
```

change_ring(*R*)

Return the free module over R obtained by coercing each element of self into a vector over the fraction field of R , then taking the resulting R -module. Raises a `TypeError` if coercion is not possible.

INPUT:

- R – a principal ideal domain

EXAMPLES:

Changing rings preserves the inner product and the user basis:

```
sage: V = QQ^3
sage: W = V.subspace([[2, '1/2', 1]]); W
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 1/4 1/2]
sage: W.change_ring(GF(7))
Vector space of degree 3 and dimension 1 over Finite Field of size 7
Basis matrix:
[1 2 4]

sage: N = FreeModule(ZZ, 2, inner_product_matrix=[[1,-1],[2,5]])
sage: N.inner_product_matrix()
[ 1 -1]
[ 2  5]
sage: Np = N.change_ring(RDF)
sage: Np.inner_product_matrix()
[ 1.0 -1.0]
[ 2.0  5.0]
```

`sage.modules.free_quadratic_module.InnerProductSpace(K, dimension, inner_product_matrix, sparse=False)`

EXAMPLES:

The base can be complicated, as long as it is a field:

```
sage: F.<x> = FractionField(PolynomialRing(ZZ,'x'))
sage: D = diagonal_matrix([x,x-1,x+1])
sage: V = QuadraticSpace(F,3,D)
sage: V
Ambient quadratic space of dimension 3 over Fraction Field of Univariate Polynomial
↪ Ring in x over Integer Ring
```

(continues on next page)

(continued from previous page)

```
Inner product matrix:
```

```
[  x      0      0]
[  0 x - 1      0]
[  0      0 x + 1]
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
```

The base must be a field or a `TypeError` is raised:

```
sage: QuadraticSpace(ZZ,5,identity_matrix(ZZ,2))
Traceback (most recent call last):
...
TypeError: Argument K (= Integer Ring) must be a field.
```

```
sage.modules.free_quadratic_module.QuadraticSpace(K, dimension, inner_product_matrix,
                                                    sparse=False)
```

EXAMPLES:

The base can be complicated, as long as it is a field:

```
sage: F.<x> = FractionField(PolynomialRing(ZZ,'x'))
sage: D = diagonal_matrix([x,x-1,x+1])
sage: V = QuadraticSpace(F,3,D)
sage: V
Ambient quadratic space of dimension 3 over Fraction Field of Univariate Polynomial
↪Ring in x over Integer Ring
Inner product matrix:
[  x      0      0]
[  0 x - 1      0]
[  0      0 x + 1]
sage: V.basis()
[
(1, 0, 0),
(0, 1, 0),
(0, 0, 1)
]
```

The base must be a field or a `TypeError` is raised:

```
sage: QuadraticSpace(ZZ,5,identity_matrix(ZZ,2))
Traceback (most recent call last):
...
TypeError: Argument K (= Integer Ring) must be a field.
```

```
sage.modules.free_quadratic_module.is_FreeQuadraticModule(M)
```

Return True if M is a free quadratic module.

EXAMPLES:

```

sage: from sage.modules.free_quadratic_module import is_FreeQuadraticModule
sage: U = FreeModule(QQ, 3)
sage: is_FreeQuadraticModule(U)
False
sage: V = FreeModule(QQ, 3, inner_product_matrix=diagonal_matrix([1, 1, 1]))
sage: is_FreeQuadraticModule(V)
True
sage: W = FreeModule(QQ, 3, inner_product_matrix=diagonal_matrix([2, 3, 3]))
sage: is_FreeQuadraticModule(W)
True

```

6.3 Integral lattices

An integral lattice is a finitely generated free abelian group $L \cong \mathbb{Z}^r$ equipped with a non-degenerate, symmetric bilinear form $L \times L \rightarrow \mathbb{Z}$.

Here, lattices have an ambient quadratic space \mathbb{Q}^n and a distinguished basis.

EXAMPLES:

```

sage: M = Matrix(ZZ, [[0, 1], [1, 0]])
sage: IntegralLattice(M)
Lattice of degree 2 and rank 2 over Integer Ring
Standard basis
Inner product matrix:
[0 1]
[1 0]

```

A lattice can be defined by an inner product matrix of the ambient space and a basis:

```

sage: G = matrix.identity(3)
sage: basis = [[1, -1, 0], [0, 1, -1]]
sage: L = IntegralLattice(G, basis)
sage: L
Lattice of degree 3 and rank 2 over Integer Ring
Basis matrix:
[ 1 -1  0]
[ 0  1 -1]
Standard scalar product

sage: L.gram_matrix()
[ 2 -1]
[-1  2]

```

AUTHORS:

- Simon Brandhorst (2017-09): First created
- Paolo Menegatti (2018-03): Added `IntegralLatticeDirectSum`, `IntegralLatticeGluing`

class sage.modules.free_quadratic_module_integer_symmetric.**FreeQuadraticModule_integer_symmetric**(ambient
basis,
inner_pro
check=1
al-
ready_e

Bases: *sage.modules.free_quadratic_module.FreeQuadraticModule_submodule_with_basis_pid*

This class represents non-degenerate, integral, symmetric free quadratic \mathbf{Z} -modules.

INPUT:

- **ambient** – an ambient free quadratic module
- **basis** – a list of elements of ambient or a matrix
- **inner_product_matrix** – a symmetric matrix over the rationals

EXAMPLES:

```
sage: IntegralLattice("U",basis=[vector([1,1])])
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[1 1]
Inner product matrix:
[0 1]
[1 0]
```

LLL()

Return this lattice with an LLL reduced basis.

EXAMPLES:

```
sage: L = IntegralLattice('A2')
sage: L.lll() == L
True
sage: G = matrix(ZZ,3,[0,1,0, 1,0,0, 0,0,7])
sage: V = matrix(ZZ,3,[-14,-15,-15, -4,1,16, -5,-5,-4])
sage: L = IntegralLattice(V * G * V.T)
sage: L.lll().gram_matrix()
[0 0 1]
[0 7 0]
[1 0 0]
```

automorphisms(gens=None, is_finite=None)

Return the orthogonal group of this lattice as a matrix group.

The elements are isometries of the ambient vector space which preserve this lattice. They are represented by matrices with respect to the standard basis.

INPUT:

- **gens** – a list of matrices (default:None)
- **is_finite** – bool (default: None) If set to True, then the group is placed in the category of finite groups. Sage does not check this.

OUTPUT:

The matrix group generated by gens. If gens is not specified, then generators of the full orthogonal group of this lattice are computed. They are continued as the identity on the orthogonal complement of the lattice in its ambient space. Currently, we can only compute the orthogonal group for positive definite lattices.

EXAMPLES:

```
sage: A4 = IntegralLattice("A4")
sage: Aut = A4.orthogonal_group()
sage: Aut
Group of isometries with 5 generators (
[-1  0  0  0] [0 0 0 1] [-1 -1 -1  0] [ 1  0  0  0] [ 1  0  0  0]
[ 0 -1  0  0] [0 0 1 0] [ 0  0  0 -1] [-1 -1 -1 -1] [ 0  1  0  0]
[ 0  0 -1  0] [0 1 0 0] [ 0  0  1  1] [ 0  0  0  1] [ 0  0  1  1]
[ 0  0  0 -1], [1 0 0 0], [ 0  1  0  0], [ 0  0  1  0], [ 0  0  0 -1]
)
```

The group acts from the right on the lattice and its discriminant group:

```
sage: x = A4.an_element()
sage: g = Aut.an_element()
sage: g
[ 1  1  1  0]
[ 0  0 -1  0]
[ 0  0  1  1]
[ 0 -1 -1 -1]
sage: x*g
(1, 1, 1, 0)
sage: (x*g).parent()==A4
True
sage: (g*x).parent()
Vector space of dimension 4 over Rational Field
sage: y = A4.discriminant_group().an_element()
sage: y*g
(1)
```

If the group is finite we can compute the usual things:

```
sage: Aut.order()
240
sage: conj = Aut.conjugacy_classes_representatives()
sage: len(conj)
14
sage: Aut.structure_description()
'C2 x S5'
```

The lattice can live in a larger ambient space:

```
sage: A2 = IntegralLattice(matrix.identity(3), Matrix(ZZ, 2, 3, [1, -1, 0, 0, 1, -1]))
sage: A2.orthogonal_group()
Group of isometries with 3 generators (
[-1/3  2/3  2/3] [ 2/3  2/3 -1/3] [1 0 0]
[ 2/3 -1/3  2/3] [ 2/3 -1/3  2/3] [0 0 1]
[ 2/3  2/3 -1/3], [-1/3  2/3  2/3], [0 1 0]
)
```

It can be negative definite as well:

```
sage: A2m = IntegralLattice(-Matrix(ZZ,2,[2,1,1,2]))
sage: G = A2m.orthogonal_group()
sage: G.order()
12
```

If the lattice is indefinite, sage does not know how to compute generators. Can you teach it?:

```
sage: U = IntegralLattice(Matrix(ZZ,2,[0,1,1,0]))
sage: U.orthogonal_group()
Traceback (most recent call last):
...
NotImplementedError: currently, we can only compute generators for orthogonal_
groups over definite lattices.
```

But we can define subgroups:

```
sage: S = IntegralLattice(Matrix(ZZ,2,[2, 3, 3, 2]))
sage: f = Matrix(ZZ,2,[0,1,-1,3])
sage: S.orthogonal_group([f])
Group of isometries with 1 generator (
[ 0  1]
[-1  3]
)
```

direct_sum(*M*)

Return the direct sum of this lattice with *M*.

INPUT:

- *M* – a module over \mathbb{Z}

EXAMPLES:

```
sage: A = IntegralLattice(1)
sage: A.direct_sum(A)
Lattice of degree 2 and rank 2 over Integer Ring
Standard basis
Standard scalar product
```

discriminant_group(*s=0*)

Return the discriminant group L^\vee/L of this lattice.

INPUT:

- *s* – an integer (default: 0)

OUTPUT:

The *s* primary part of the discriminant group. If *s* = 0, returns the whole discriminant group.

EXAMPLES:

```
sage: L = IntegralLattice(Matrix(ZZ,2,2,[2,1,1,-2])*2)
sage: L.discriminant_group()
Finite quadratic module over Integer Ring with invariants (2, 10)
Gram matrix of the quadratic form with values in Q/2Z:
```

(continues on next page)

(continued from previous page)

```
[ 1 1/2]
[1/2 1/5]
sage: L.discriminant_group(2)
Finite quadratic module over Integer Ring with invariants (2, 2)
Gram matrix of the quadratic form with values in Q/2Z:
[ 1 1/2]
[1/2 1]
sage: L.discriminant_group(5)
Finite quadratic module over Integer Ring with invariants (5,)
Gram matrix of the quadratic form with values in Q/2Z:
[4/5]
```

dual_lattice()

Return the dual lattice as a *FreeQuadraticModule*

Let L be a lattice. Its dual lattice is

$$L^\vee = \{x \in L \otimes \mathbf{Q} : (x, l) \in \mathbf{Z} \forall l \in L\}.$$

EXAMPLES:

```
sage: L = IntegralLattice("A2")
sage: Ldual=L.dual_lattice()
sage: Ldual
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1/3 2/3]
[ 0 1]
```

Since our lattices are always integral, a lattice is contained in its dual:

```
sage: L.is_submodule(Ldual)
True
```

genus()

Return the genus of this lattice.

EXAMPLES:

```
sage: L = IntegralLattice("U")
sage: L.genus()
Genus of
[0 1]
[1 0]
Signature: (1, 1)
Genus symbol at 2: 1^2
```

is_even()

Return whether the diagonal entries of the Gram matrix are even.

EXAMPLES:

```
sage: G = Matrix(ZZ,2,2,[-1,1,1,2])
sage: L = IntegralLattice(G)
```

(continues on next page)

(continued from previous page)

```

sage: L.is_even()
False
sage: L = IntegralLattice("A2")
sage: L.is_even()
True

```

is_primitive(M)

Return whether M is a primitive submodule of this lattice.

A \mathbf{Z} -submodule M of a \mathbf{Z} -module L is called primitive if the quotient L/M is torsion free.

INPUT:

- M – a submodule of this lattice

EXAMPLES:

```

sage: U = IntegralLattice("U")
sage: L1 = U.span([vector([1,1])])
sage: L2 = U.span([vector([1,-1])])
sage: U.is_primitive(L1)
True
sage: U.is_primitive(L2)
True
sage: U.is_primitive(L1+L2)
False

```

We can also compute the index:

```

sage: (L1+L2).index_in(U)
2

```

lll()

Return this lattice with an LLL reduced basis.

EXAMPLES:

```

sage: L = IntegralLattice('A2')
sage: L.lll() == L
True
sage: G = matrix(ZZ,3,[0,1,0, 1,0,0, 0,0,7])
sage: V = matrix(ZZ,3,[-14,-15,-15, -4,1,16, -5,-5,-4])
sage: L = IntegralLattice(V * G * V.T)
sage: L.lll().gram_matrix()
[0 0 1]
[0 7 0]
[1 0 0]

```

max()

Return the maximum of this lattice.

$$\max\{x^2 \mid x \in L \setminus \{0\}\}$$

EXAMPLES:

```
sage: L = IntegralLattice('A2')
sage: L.maximum()
+Infinity
sage: L.twist(-1).maximum()
-2
```

maximal_overlattice(*p=None*)

Return a maximal even integral overlattice of this lattice.

INPUT:

- *p* – (default:None) if given return an overlattice M of this lattice L that is maximal at p and the completions $M_q = L_q$ are equal for all primes $q \neq p$.

If p is 2 or None, then the lattice must be even.

EXAMPLES:

```
sage: L = IntegralLattice("A4").twist(25*89)
sage: L.maximal_overlattice().determinant()
5
sage: L.maximal_overlattice(89).determinant().factor()
5^9
sage: L.maximal_overlattice(5).determinant().factor()
5 * 89^4
```

maximum()

Return the maximum of this lattice.

$$\max\{x^2 | x \in L \setminus \{0\}\}$$

EXAMPLES:

```
sage: L = IntegralLattice('A2')
sage: L.maximum()
+Infinity
sage: L.twist(-1).maximum()
-2
```

min()

Return the minimum of this lattice.

$$\min\{x^2 | x \in L \setminus \{0\}\}$$

EXAMPLES:

```
sage: L = IntegralLattice('A2')
sage: L.minimum()
2
sage: L.twist(-1).minimum()
-Infinity
```

minimum()

Return the minimum of this lattice.

$$\min\{x^2 | x \in L \setminus \{0\}\}$$

EXAMPLES:

```

sage: L = IntegralLattice('A2')
sage: L.minimum()
2
sage: L.twist(-1).minimum()
-Infinity

```

orthogonal_complement(*M*)

Return the orthogonal complement of *M* in this lattice.

INPUT:

- *M* – a module in the same ambient space or a list of elements of the ambient space

EXAMPLES:

```

sage: H5 = Matrix(ZZ,2,[2,1,1,-2])
sage: L = IntegralLattice(H5)
sage: S = L.span([vector([1,1])])
sage: L.orthogonal_complement(S)
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[1 3]
Inner product matrix:
[ 2  1]
[ 1 -2]

sage: L = IntegralLattice(2)
sage: L.orthogonal_complement([vector(ZZ,[1,0])])
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[0 1]
Standard scalar product

```

orthogonal_group(*gens=None, is_finite=None*)

Return the orthogonal group of this lattice as a matrix group.

The elements are isometries of the ambient vector space which preserve this lattice. They are represented by matrices with respect to the standard basis.

INPUT:

- *gens* – a list of matrices (default:None)
- *is_finite* – bool (default: None) If set to True, then the group is placed in the category of finite groups. Sage does not check this.

OUTPUT:

The matrix group generated by *gens*. If *gens* is not specified, then generators of the full orthogonal group of this lattice are computed. They are continued as the identity on the orthogonal complement of the lattice in its ambient space. Currently, we can only compute the orthogonal group for positive definite lattices.

EXAMPLES:

```

sage: A4 = IntegralLattice("A4")
sage: Aut = A4.orthogonal_group()
sage: Aut
Group of isometries with 5 generators (

```

(continues on next page)

(continued from previous page)

```

[-1  0  0  0] [0 0 0 1] [-1 -1 -1  0] [ 1  0  0  0] [ 1  0  0  0]
[ 0 -1  0  0] [0 0 1 0] [ 0  0  0 -1] [-1 -1 -1 -1] [ 0  1  0  0]
[ 0  0 -1  0] [0 1 0 0] [ 0  0  1  1] [ 0  0  0  1] [ 0  0  1  1]
[ 0  0  0 -1], [1 0 0 0], [ 0  1  0  0], [ 0  0  1  0], [ 0  0  0 -1]
)

```

The group acts from the right on the lattice and its discriminant group:

```

sage: x = A4.an_element()
sage: g = Aut.an_element()
sage: g
[ 1  1  1  0]
[ 0  0 -1  0]
[ 0  0  1  1]
[ 0 -1 -1 -1]
sage: x*g
(1, 1, 1, 0)
sage: (x*g).parent()==A4
True
sage: (g*x).parent()
Vector space of dimension 4 over Rational Field
sage: y = A4.discriminant_group().an_element()
sage: y*g
(1)

```

If the group is finite we can compute the usual things:

```

sage: Aut.order()
240
sage: conj = Aut.conjugacy_classes_representatives()
sage: len(conj)
14
sage: Aut.structure_description()
'C2 x S5'

```

The lattice can live in a larger ambient space:

```

sage: A2 = IntegralLattice(matrix.identity(3), Matrix(ZZ, 2, 3, [1, -1, 0, 0, 1, -1]))
sage: A2.orthogonal_group()
Group of isometries with 3 generators (
[-1/3  2/3  2/3] [ 2/3  2/3 -1/3] [1 0 0]
[ 2/3 -1/3  2/3] [ 2/3 -1/3  2/3] [0 0 1]
[ 2/3  2/3 -1/3], [-1/3  2/3  2/3], [0 1 0]
)

```

It can be negative definite as well:

```

sage: A2m = IntegralLattice(-Matrix(ZZ, 2, [2, 1, 1, 2]))
sage: G = A2m.orthogonal_group()
sage: G.order()
12

```

If the lattice is indefinite, sage does not know how to compute generators. Can you teach it?:

```

sage: U = IntegralLattice(Matrix(ZZ,2,[0,1,1,0]))
sage: U.orthogonal_group()
Traceback (most recent call last):
...
NotImplementedError: currently, we can only compute generators for orthogonal_
↳groups over definite lattices.

```

But we can define subgroups:

```

sage: S = IntegralLattice(Matrix(ZZ,2,[2, 3, 3, 2]))
sage: f = Matrix(ZZ,2,[0,1,-1,3])
sage: S.orthogonal_group([f])
Group of isometries with 1 generator (
[ 0  1]
[-1  3]
)

```

overlattice(*gens*)

Return the lattice spanned by this lattice and *gens*.

INPUT:

- *gens* – a list of elements or a rational matrix

EXAMPLES:

```

sage: L = IntegralLattice(Matrix(ZZ,2,2,[2,0,0,2]))
sage: M = L.overlattice([vector([1,1])/2])
sage: M.gram_matrix()
[1 1]
[1 2]

```

quadratic_form()

Return the quadratic form given by $q(x) = (x, x)$.

EXAMPLES:

```

sage: L = IntegralLattice("A2")
sage: q = L.quadratic_form()
sage: q
Quadratic form in 2 variables over Integer Ring with coefficients:
[ 2 -2 ]
[ * 2 ]

```

short_vectors(*n*, *kwargs*)**

Return the short vectors of length $< n$.

INPUT:

- *n* – an integer
- further key word arguments are passed on to `sage.quadratic_forms.short_vector_list_up_to_length()`.

OUTPUT:

- a list *L* where *L*[*k*] is the list of vectors of lengths *k*

EXAMPLES:

```

sage: A2 = IntegralLattice('A2')
sage: A2.short_vectors(3)
[[ (0, 0), [], [(1, 1), (-1, -1), (0, 1), (0, -1), (1, 0), (-1, 0)]]
sage: A2.short_vectors(3, up_to_sign_flag=True)
[[ (0, 0), [], [(1, 1), (0, 1), (1, 0)]]

```

signature()

Return the signature of this lattice, which is defined as the difference between the number of positive eigenvalues and the number of negative eigenvalues in the Gram matrix.

EXAMPLES:

```

sage: U = IntegralLattice("U")
sage: U.signature()
0

```

signature_pair()

Return the signature tuple (n_+, n_-) of this lattice.

Here n_+ (resp. n_-) is the number of positive (resp. negative) eigenvalues of the Gram matrix.

EXAMPLES:

```

sage: A2 = IntegralLattice("A2")
sage: A2.signature_pair()
(2, 0)

```

sublattice(*basis*)

Return the sublattice spanned by *basis*.

INPUT:

- *basis* – A list of elements of this lattice.

EXAMPLES:

```

sage: U = IntegralLattice("U")
sage: S = U.sublattice([vector([1,1])])
sage: S
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[1 1]
Inner product matrix:
[0 1]
[1 0]
sage: U.sublattice([vector([1,-1])/2])
Traceback (most recent call last):
...
ValueError: lattices must be integral; use FreeQuadraticModule instead
sage: S.sublattice([vector([1,-1])])
Traceback (most recent call last):
...
ValueError: the basis (= [(1, -1)]) does not span a submodule

```

tensor_product(*other*, *discard_basis=False*)

Return the tensor product of *self* and *other*.

INPUT:

- **other** – an integral lattice
- **discard_basis** – a boolean (default: `False`). If `True`, then the lattice returned is equipped with the standard basis.

EXAMPLES:

```
sage: L = IntegralLattice("D3", [[1,-1,0], [0,1,-1]])
sage: L1 = L.tensor_product(L)
sage: L2 = L.tensor_product(L, True)
sage: L1
Lattice of degree 9 and rank 4 over Integer Ring
Basis matrix:
[ 1 -1  0 -1  1  0  0  0  0]
[ 0  1 -1  0 -1  1  0  0  0]
[ 0  0  0  1 -1  0 -1  1  0]
[ 0  0  0  0  1 -1  0 -1  1]
Inner product matrix:
[ 4 -2 -2 -2  1  1 -2  1  1]
[-2  4  0  1 -2  0  1 -2  0]
[-2  0  4  1  0 -2  1  0 -2]
[-2  1  1  4 -2 -2  0  0  0]
[ 1 -2  0 -2  4  0  0  0  0]
[ 1  0 -2 -2  0  4  0  0  0]
[-2  1  1  0  0  0  4 -2 -2]
[ 1 -2  0  0  0  0 -2  4  0]
[ 1  0 -2  0  0  0 -2  0  4]
sage: L1.gram_matrix()
[ 36 -12 -12  4]
[-12  24  4 -8]
[-12  4  24 -8]
[ 4 -8 -8 16]
sage: L2
Lattice of degree 4 and rank 4 over Integer Ring
Standard basis
Inner product matrix:
[ 36 -12 -12  4]
[-12  24  4 -8]
[-12  4  24 -8]
[ 4 -8 -8 16]
```

twist(*s*, *discard_basis=False*)

Return the lattice with inner product matrix scaled by *s*.

INPUT:

- **s** – a nonzero integer
- **discard_basis** – a boolean (default: `False`). If `True`, then the lattice returned is equipped with the standard basis.

EXAMPLES:

```
sage: L = IntegralLattice("A4")
sage: L.twist(3)
Lattice of degree 4 and rank 4 over Integer Ring
Standard basis
```

(continues on next page)

(continued from previous page)

```

Inner product matrix:
[ 6 -3  0  0]
[-3  6 -3  0]
[ 0 -3  6 -3]
[ 0  0 -3  6]
sage: L = Integrallattice(3,[[2,1,0],[0,1,1]])
sage: L
Lattice of degree 3 and rank 2 over Integer Ring
Basis matrix:
[2 1 0]
[0 1 1]
Standard scalar product
sage: L.twist(1)
Lattice of degree 3 and rank 2 over Integer Ring
Basis matrix:
[2 1 0]
[0 1 1]
Standard scalar product
sage: L.twist(1, True)
Lattice of degree 2 and rank 2 over Integer Ring
Standard basis
Inner product matrix:
[5 1]
[1 2]

```

`sage.modules.free_quadratic_module_integer_symmetric.Integrallattice(data, basis=None)`

Return the integral lattice spanned by basis in the ambient space.

A lattice is a finitely generated free abelian group $L \cong \mathbf{Z}^r$ equipped with a non-degenerate, symmetric bilinear form $L \times L: \rightarrow \mathbf{Z}$. Here, lattices have an ambient quadratic space \mathbf{Q}^n and a distinguished basis.

INPUT:

The input is a descriptor of the lattice and a (optional) basis. - data – can be one of the following:

- a symmetric matrix over the rationals – the inner product matrix
- an integer – the dimension for an Euclidean lattice
- a symmetric Cartan type or anything recognized by `CartanMatrix` (see also `Cartan types`) – for a root lattice
- the string "U" or "H" – for hyperbolic lattices
- basis – (optional) a matrix whose rows form a basis of the lattice, or a list of module elements forming a basis

OUTPUT:

A lattice in the ambient space defined by the inner_product_matrix. Unless specified, the basis of the lattice is the standard basis.

EXAMPLES:

```

sage: H5 = Matrix(ZZ, 2, [2,1,1,-2])
sage: Integrallattice(H5)
Lattice of degree 2 and rank 2 over Integer Ring

```

(continues on next page)

(continued from previous page)

```
Standard basis
Inner product matrix:
[ 2  1]
[ 1 -2]
```

A basis can be specified too:

```
sage: IntegralLattice(H5, Matrix([1,1]))
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[1 1]
Inner product matrix:
[ 2  1]
[ 1 -2]
```

We can define an Euclidean lattice just by its dimension:

```
sage: IntegralLattice(3)
Lattice of degree 3 and rank 3 over Integer Ring
Standard basis
Standard scalar product
```

Here is an example of the A_2 root lattice in Euclidean space:

```
sage: basis = Matrix([[1,-1,0], [0,1,-1]])
sage: A2 = IntegralLattice(3, basis)
sage: A2
Lattice of degree 3 and rank 2 over Integer Ring
Basis matrix:
[ 1 -1  0]
[ 0  1 -1]
Standard scalar product
sage: A2.gram_matrix()
[ 2 -1]
[-1  2]
```

We use "U" or "H" for defining a hyperbolic lattice:

```
sage: L1 = IntegralLattice("U")
sage: L1
Lattice of degree 2 and rank 2 over Integer Ring
Standard basis
Inner product matrix:
[0 1]
[1 0]
sage: L1 == IntegralLattice("H")
True
```

We can construct root lattices by specifying their type (see [Cartan types](#) and [CartanMatrix](#)):

```
sage: IntegralLattice(["E", 7])
Lattice of degree 7 and rank 7 over Integer Ring
Standard basis
```

(continues on next page)

(continued from previous page)

```

Inner product matrix:
[ 2  0 -1  0  0  0  0]
[ 0  2  0 -1  0  0  0]
[-1  0  2 -1  0  0  0]
[ 0 -1 -1  2 -1  0  0]
[ 0  0  0 -1  2 -1  0]
[ 0  0  0  0 -1  2 -1]
[ 0  0  0  0  0 -1  2]
sage: IntegralLattice(["A", 2])
Lattice of degree 2 and rank 2 over Integer Ring
Standard basis
Inner product matrix:
[ 2 -1]
[-1  2]
sage: IntegralLattice("D3")
Lattice of degree 3 and rank 3 over Integer Ring
Standard basis
Inner product matrix:
[ 2 -1 -1]
[-1  2  0]
[-1  0  2]
sage: IntegralLattice(["D", 4])
Lattice of degree 4 and rank 4 over Integer Ring
Standard basis
Inner product matrix:
[ 2 -1  0  0]
[-1  2 -1 -1]
[ 0 -1  2  0]
[ 0 -1  0  2]

```

We can specify a basis as well:

```

sage: G = Matrix(ZZ, 2, [0,1,1,0])
sage: B = [vector([1,1])]
sage: IntegralLattice(G, basis=B)
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[1 1]
Inner product matrix:
[0 1]
[1 0]
sage: IntegralLattice(["A", 3], [[1,1,1]])
Lattice of degree 3 and rank 1 over Integer Ring
Basis matrix:
[1 1 1]
Inner product matrix:
[ 2 -1  0]
[-1  2 -1]
[ 0 -1  2]
sage: IntegralLattice(4, [[1,1,1,1]])
Lattice of degree 4 and rank 1 over Integer Ring
Basis matrix:

```

(continues on next page)

(continued from previous page)

```

[1 1 1 1]
Standard scalar product
sage: Integrallattice("A2", [[1,1]])
Lattice of degree 2 and rank 1 over Integer Ring
Basis matrix:
[1 1]
Inner product matrix:
[ 2 -1]
[-1  2]

```

`sage.modules.free_quadratic_module_integer_symmetric.IntegrallatticeDirectSum(Lattices, return_embeddings=False)`

Return the direct sum of the lattices contained in the list `Lattices`.

INPUT:

- `Lattices` – a list of lattices $[L_1, \dots, L_n]$
- `return_embeddings` – (default: `False`) a boolean

OUTPUT:

The direct sum of the L_i if `return_embeddings` is `False` or the tuple $[L, \text{phi}]$ where L is the direct sum of L_i and `phi` is the list of embeddings from L_i to L .

EXAMPLES:

```

sage: from sage.modules.free_quadratic_module_integer_symmetric import
↪ IntegrallatticeDirectSum
sage: L1 = Integrallattice("D4")
sage: L2 = Integrallattice("A3", [[1, 1, 2]])
sage: L3 = Integrallattice("A4", [[0, 1, 1, 2], [1, 2, 3, 1]])
sage: Lattices = [L1, L2, L3]
sage: IntegrallatticeDirectSum([L1, L2, L3])
Lattice of degree 11 and rank 7 over Integer Ring
Basis matrix:
[1 0 0 0 0 0 0 0 0 0 0]
[0 1 0 0 0 0 0 0 0 0 0]
[0 0 1 0 0 0 0 0 0 0 0]
[0 0 0 1 0 0 0 0 0 0 0]
[0 0 0 0 1 1 2 0 0 0 0]
[0 0 0 0 0 0 0 0 1 1 2]
[0 0 0 0 0 0 0 1 2 3 1]
Inner product matrix:
[ 2 -1  0  0  0  0  0  0  0  0  0]
[-1  2 -1 -1  0  0  0  0  0  0  0]
[ 0 -1  2  0  0  0  0  0  0  0  0]
[ 0 -1  0  2  0  0  0  0  0  0  0]
[ 0  0  0  0  2 -1  0  0  0  0  0]
[ 0  0  0  0 -1  2 -1  0  0  0  0]
[ 0  0  0  0  0 -1  2  0  0  0  0]
[ 0  0  0  0  0  0  0  2 -1  0  0]
[ 0  0  0  0  0  0  0 -1  2 -1  0]
[ 0  0  0  0  0  0  0  0 -1  2 -1]
[ 0  0  0  0  0  0  0  0  0 -1  2]

```

(continues on next page)

(continued from previous page)

```

sage: [L, phi] = IntegralLatticeDirectSum([L1, L2, L3], True)
sage: LL3 = L.sublattice(phi[2].image().basis_matrix())
sage: L3.discriminant() == LL3.discriminant()
True
sage: x = L3([1, 2, 3, 1])
sage: phi[2](x).inner_product(phi[2](x)) == x.inner_product(x)
True

```

sage.modules.free_quadratic_module_integer_symmetric.**IntegralLatticeGluing**(*Lattices, glue, return_embeddings=False*)

Return an overlattice of the direct sum as defined by glue.

INPUT:

- *Lattices* – a list of lattices $[L_1, \dots, L_n]$
- *glue* – a list where the elements are lists in the form $[g_1, \dots, g_n]$; here g_i is an element of the discriminant group of L_i
- *return_embeddings* – (default: False) a boolean

OUTPUT:

The glued lattice given by L_i and glue if *return_embeddings* is False or the tuple $[L, \text{phi}]$ where L is the glued lattice and phi the list of embeddings from L_i to L

EXAMPLES:

A single lattice can be glued. This is the same as taking an overlattice:

```

sage: from sage.modules.free_quadratic_module_integer_symmetric import
↳ IntegralLatticeGluing
sage: L1 = IntegralLattice(matrix([[4]]))
sage: g1 = L1.discriminant_group().gens()[0]
sage: glue = [[2 * g1]]
sage: L = IntegralLatticeGluing([L1], glue)
sage: L
Lattice of degree 1 and rank 1 over Integer Ring
Basis matrix:
[1/2]
Inner product matrix:
[4]
sage: L.gram_matrix()
[1]
sage: IntegralLatticeGluing([L1], glue, return_embeddings=True)
[Lattice of degree 1 and rank 1 over Integer Ring
Basis matrix:
[1/2]
Inner product matrix:
[4], [Free module morphism defined by the matrix
[2]
Domain: Lattice of degree 1 and rank 1 over Integer Ring
Standard basis
Inner product matrix:
[4]
Codomain: Lattice of degree 1 and rank 1 over Integer Ring

```

(continues on next page)

(continued from previous page)

```

Basis matrix:
[1/2]
Inner product matrix:
[4]]

sage: L1 = IntegralLattice([[2]])
sage: L2 = IntegralLattice([[2]])
sage: AL1 = L1.discriminant_group()
sage: AL2 = L2.discriminant_group()
sage: AL1
Finite quadratic module over Integer Ring with invariants (2,)
Gram matrix of the quadratic form with values in Q/2Z:
[1/2]
sage: g1 = L1.discriminant_group().gens()[0]
sage: g2 = L2.discriminant_group().gens()[0]
sage: glue = [[g1, g2]]
sage: IntegralLatticeGluing([L1, L2], glue)
Lattice of degree 2 and rank 2 over Integer Ring
Basis matrix:
[1/2 1/2]
[ 0 1]
Inner product matrix:
[2 0]
[0 2]

sage: L1 = IntegralLattice("A4")
sage: L2 = IntegralLattice("A4")
sage: g1 = L1.discriminant_group().gens()[0]
sage: g2 = L2.discriminant_group().gens()[0]
sage: glue = [[g1, 2 * g2]]
sage: [V, phi] = IntegralLatticeGluing([L1, L2], glue, True)
sage: V
Lattice of degree 8 and rank 8 over Integer Ring
Basis matrix:
[1/5 2/5 3/5 4/5 2/5 4/5 1/5 3/5]
[ 0 1 0 0 0 0 0 0]
[ 0 0 1 0 0 0 0 0]
[ 0 0 0 1 0 0 0 0]
[ 0 0 0 0 1 0 0 0]
[ 0 0 0 0 0 1 0 0]
[ 0 0 0 0 0 0 1 0]
[ 0 0 0 0 0 0 0 1]
Inner product matrix:
[ 2 -1 0 0 0 0 0 0]
[-1 2 -1 0 0 0 0 0]
[ 0 -1 2 -1 0 0 0 0]
[ 0 0 -1 2 0 0 0 0]
[ 0 0 0 0 2 -1 0 0]
[ 0 0 0 0 -1 2 -1 0]
[ 0 0 0 0 0 -1 2 -1]
[ 0 0 0 0 0 0 -1 2]
sage: V.sublattice(phi[0].image()).basis_matrix()

```

(continues on next page)

(continued from previous page)

Lattice of degree 8 and rank 4 over Integer Ring

Basis matrix:

 $[1 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[0 \ 1 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[0 \ 0 \ 1 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[0 \ 0 \ 0 \ 1 \ 0 \ 0 \ 0 \ 0]$

Inner product matrix:

 $[\ 2 \ -1 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[-1 \ 2 \ -1 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[\ 0 \ -1 \ 2 \ -1 \ 0 \ 0 \ 0 \ 0]$ $[\ 0 \ 0 \ -1 \ 2 \ 0 \ 0 \ 0 \ 0]$ $[\ 0 \ 0 \ 0 \ 0 \ 2 \ -1 \ 0 \ 0]$ $[\ 0 \ 0 \ 0 \ 0 \ -1 \ 2 \ -1 \ 0]$ $[\ 0 \ 0 \ 0 \ 0 \ 0 \ -1 \ 2 \ -1]$ $[\ 0 \ 0 \ 0 \ 0 \ 0 \ 0 \ -1 \ 2]$

Different gluings can be composed:

sage: D4 = IntegralLattice("D4")**sage:** D4.discriminant_group()

Finite quadratic module over Integer Ring with invariants (2, 2)

Gram matrix of the quadratic form with values in $\mathbb{Q}/2\mathbb{Z}$: $[\ 1 \ 1/2]$ $[1/2 \ 1]$ **sage:** L2 = IntegralLattice(2 * matrix.identity(2))**sage:** L2.discriminant_group()

Finite quadratic module over Integer Ring with invariants (2, 2)

Gram matrix of the quadratic form with values in $\mathbb{Q}/2\mathbb{Z}$: $[1/2 \ 0]$ $[\ 0 \ 1/2]$ **sage:** g1 = D4.discriminant_group().gens()[0]**sage:** g2 = L2.discriminant_group().gens()[0] + L2.discriminant_group().gens()[1]**sage:** D6, phi = IntegralLatticeGluing([D4, L2], [[g1, g2]], **True**)**sage:** AD6 = D6.discriminant_group()**sage:** AD6.normal_form()

Finite quadratic module over Integer Ring with invariants (2, 2)

Gram matrix of the quadratic form with values in $\mathbb{Q}/2\mathbb{Z}$: $[3/2 \ 0]$ $[\ 0 \ 3/2]$ **sage:** f1, g1 = AD6.normal_form().gens()**sage:** f2, g2 = L2.discriminant_group().gens()**sage:** E8, psi = IntegralLatticeGluing([D6, L2], [[f1, f2], [g1, g2]], **True**)**sage:** D4embed = E8.sublattice(psi[0](phi[0].image()).basis_matrix())**sage:** x = D4([1, 0, 0, 0])**sage:** psi[0](phi[0](x)).inner_product(psi[0](phi[0](x)))==x.inner_product(x)

True

sage: D4embed

Lattice of degree 8 and rank 4 over Integer Ring

Basis matrix:

 $[1 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[0 \ 1 \ 0 \ 0 \ 0 \ 0 \ 0 \ 0]$ $[0 \ 0 \ 1 \ 0 \ 0 \ 0 \ 0 \ 0]$

(continues on next page)

(continued from previous page)

```
[0 0 0 1 0 0 0 0]
Inner product matrix:
[ 2 -1  0  0  0  0  0  0]
[-1  2 -1 -1  0  0  0  0]
[ 0 -1  2  0  0  0  0  0]
[ 0 -1  0  2  0  0  0  0]
[ 0  0  0  0  2  0  0  0]
[ 0  0  0  0  0  2  0  0]
[ 0  0  0  0  0  0  2  0]
[ 0  0  0  0  0  0  0  2]
```

The input may be a list of three or more lattices:

```
sage: A7 = IntegralLattice("A7")
sage: D5 = IntegralLattice("D5")
sage: gA7 = A7.discriminant_group().gens()[0]
sage: gD5 = D5.discriminant_group().gens()[0]
sage: [L, phi] = IntegralLatticeGluing([A7, A7, D5, D5],
.....:                               [[gA7, gA7, gD5, 2 * gD5],
.....:                               [gA7, 7 * gA7, 2 * gD5, gD5]], True)
sage: L.determinant()
1
sage: B = phi[0].matrix()
sage: B*L.gram_matrix()*B.transpose()==A7.gram_matrix()
True
```

The gluing takes place in the direct sum of the respective ambient spaces:

```
sage: L1 = IntegralLattice("D4", [[1, 1, 0, 0], [0, 1, 1, 0]])
sage: L2 = IntegralLattice("E6", [[0, 2, 0, 0, 0, 0], [0, 0, 0, 0, 1, 1]])
sage: [f1, f2] = L1.discriminant_group().gens()
sage: [g1, g2] = L2.discriminant_group().gens()
sage: [L, phi] = IntegralLatticeGluing([L1, L2], [[f1, g1], [f2, 2 * g2]], True)
sage: phi[0]
Free module morphism defined by the matrix
[ 2  2 -2 -1]
[ 0  2 -1  0]
Domain: Lattice of degree 4 and rank 2 over Integer Ring
Basis matrix:
[1 1 0 0]
[0 1 1 0]
Inner product matrix:
[ 2 -1  0  0]
[-1  2 -1 -1]
[ 0 -1  2  0]
[ 0 -1  0  2]
Codomain: Lattice of degree 10 and rank 4 over Integer Ring
Basis matrix:
[ 1/2  0 -1/2  0  0  1/2  0  0  1/2  1/2]
[  0  1/2  1/2  0  0  1/2  0  0  0  0]
[  0  0  0  0  0  1  0  0  0  0]
[  0  0  0  0  0  0  0  0  1  1]
```

(continues on next page)

(continued from previous page)

```

Inner product matrix:
[ 2 -1  0  0  0  0  0  0  0  0]
[-1  2 -1 -1  0  0  0  0  0  0]
[ 0 -1  2  0  0  0  0  0  0  0]
[ 0 -1  0  2  0  0  0  0  0  0]
[ 0  0  0  0  2  0 -1  0  0  0]
[ 0  0  0  0  0  2  0 -1  0  0]
[ 0  0  0  0 -1  0  2 -1  0  0]
[ 0  0  0  0  0 -1 -1  2 -1  0]
[ 0  0  0  0  0  0  0 -1  2 -1]
[ 0  0  0  0  0  0  0  0 -1  2]
sage: B = phi[0].matrix()
sage: B * L.gram_matrix() * B.transpose()==L1.gram_matrix()
True

```

`sage.modules.free_quadratic_module_integer_symmetric.local_modification($M, G, p, check=True$)`
 Return a local modification of M that matches G at p .

INPUT:

- M – a \mathbb{Z}_p -maximal lattice
- G – the gram matrix of a lattice isomorphic to M over \mathbb{Q}_p
- p – a prime number

OUTPUT:

an integral lattice M' in the ambient space of M such that M and M' are locally equal at all completions except at p where M' is locally equivalent to the lattice with gram matrix G

EXAMPLES:

```

sage: from sage.modules.free_quadratic_module_integer_symmetric import local_
      ↪modification
sage: L = IntegralLattice("A3").twist(15)
sage: M = L.maximal_overlattice()
sage: for p in prime_divisors(L.determinant()):
.....:     M = local_modification(M, L.gram_matrix(), p)
sage: M.genus() == L.genus()
True
sage: L = IntegralLattice("D4").twist(3*4)
sage: M = L.maximal_overlattice()
sage: local_modification(M, L.gram_matrix(), 2)
Lattice of degree 4 and rank 4 over Integer Ring
Basis matrix:
[1/3  0 2/3 2/3]
[ 0 1/3  0 2/3]
[ 0  0  1  0]
[ 0  0  0  1]
Inner product matrix:
[ 24 -12  0  0]
[-12  24 -12 -12]
[  0 -12  24  0]
[  0 -12  0  24]

```


6.4 Finite \mathbb{Z} -modules with bilinear and quadratic forms

AUTHORS:

- Simon Brandhorst (2017-09): First created

`sage.modules.torsion_quadratic_module.TorsionQuadraticForm(q)`

Create a torsion quadratic form module from a rational matrix.

The resulting quadratic form takes values in \mathbb{Q}/\mathbb{Z} or $\mathbb{Q}/2\mathbb{Z}$ (depending on q). If it takes values modulo 2, then it is non-degenerate. In any case the bilinear form is non-degenerate.

INPUT:

- q – a symmetric rational matrix

EXAMPLES:

```
sage: q1 = Matrix(QQ,2,[1,1/2,1/2,1])
sage: TorsionQuadraticForm(q1)
Finite quadratic module over Integer Ring with invariants (2, 2)
Gram matrix of the quadratic form with values in Q/2Z:
[ 1 1/2]
[1/2  1]
```

In the following example the quadratic form is degenerate. But the bilinear form is still non-degenerate:

```
sage: q2 = diagonal_matrix(QQ,[1/4,1/3])
sage: TorsionQuadraticForm(q2)
Finite quadratic module over Integer Ring with invariants (12,)
Gram matrix of the quadratic form with values in Q/Z:
[7/12]
```

`class sage.modules.torsion_quadratic_module.TorsionQuadraticModule(V, W, gens, modulus, modulus_qf)`

Bases: `sage.modules.fg_pid.fgp_module.FGP_Module_class`, `sage.structure.unique_representation.CachedRepresentation`

Finite quotients with a bilinear and a quadratic form.

Let V be a symmetric FreeQuadraticModule and $W \subseteq V$ a submodule of the same rank as V . The quotient V/W is a torsion quadratic module. It inherits a bilinear form b and a quadratic form q .

$b: V \times V \rightarrow \mathbb{Q}/m\mathbb{Z}$, where $m\mathbb{Z} = (V, W)$ and $b(x, y) = (x, y) + m\mathbb{Z}$

$q: V \rightarrow \mathbb{Q}/n\mathbb{Z}$, where $n\mathbb{Z} = 2(V, W) + \mathbb{Z}\{(w, w) | w \in W\}$

INPUT:

- V – a *FreeModule* with a symmetric inner product matrix
- W – a submodule of V of the same rank as V
- `check` – bool (default: True)
- `modulus` – a rational number dividing m (default: m); the inner product b is defined in $\mathbb{Q}/\text{modulus}\mathbb{Z}$
- `modulus_qf` – a rational number dividing n (default: n); the quadratic form q is defined in $\mathbb{Q}/\text{modulus_qf}\mathbb{Z}$

EXAMPLES:

```

sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = FreeModule(ZZ, 3)
sage: T = TorsionQuadraticModule(V, 5*V)
sage: T
Finite quadratic module over Integer Ring with invariants (5, 5, 5)
Gram matrix of the quadratic form with values in Q/5Z:
[1 0 0]
[0 1 0]
[0 0 1]

```

Element

alias of *TorsionQuadraticModuleElement*

all_submodules()

Return a list of all submodules of *self*.

Warning: This method creates all submodules in memory. The number of submodules grows rapidly with the number of generators. For example consider a vector space of dimension n over a finite field of prime order p . The number of subspaces is (very) roughly $p^{(n^2-n)/2}$.

EXAMPLES:

```

sage: D = Integrallattice("D4").discriminant_group()
sage: D.all_submodules()
[Finite quadratic module over Integer Ring with invariants ()
  Gram matrix of the quadratic form with values in Q/2Z:
  [],
Finite quadratic module over Integer Ring with invariants (2,)
  Gram matrix of the quadratic form with values in Q/2Z:
  [1],
Finite quadratic module over Integer Ring with invariants (2,)
  Gram matrix of the quadratic form with values in Q/2Z:
  [1],
Finite quadratic module over Integer Ring with invariants (2,)
  Gram matrix of the quadratic form with values in Q/2Z:
  [1],
Finite quadratic module over Integer Ring with invariants (2, 2)
  Gram matrix of the quadratic form with values in Q/2Z:
  [ 1 1/2]
  [1/2 1]]

```

brown_invariant()

Return the Brown invariant of this torsion quadratic form.

Let (D, q) be a torsion quadratic module with values in $\mathbf{Q}/2\mathbf{Z}$. The Brown invariant $Br(D, q) \in \mathbf{Z}/8\mathbf{Z}$ is defined by the equation

$$\exp\left(\frac{2\pi i}{8} Br(q)\right) = \frac{1}{\sqrt{D}} \sum_{x \in D} \exp(i\pi q(x)).$$

The Brown invariant is additive with respect to direct sums of torsion quadratic modules.

OUTPUT:

- an element of $\mathbf{Z}/8\mathbf{Z}$

EXAMPLES:

```
sage: L = IntegralLattice("D4")
sage: D = L.discriminant_group()
sage: D.brown_invariant()
4
```

We require the quadratic form to be defined modulo $2\mathbb{Z}$:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = FreeQuadraticModule(ZZ, 3, matrix.identity(3))
sage: T = TorsionQuadraticModule((1/10)*V, V)
sage: T.brown_invariant()
Traceback (most recent call last):
...
ValueError: the torsion quadratic form must have values in QQ / 2 ZZ
```

gens()

Return generators of self.

There is no assumption on the generators except that they generate the module.

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = FreeModule(ZZ, 3)
sage: T = TorsionQuadraticModule(V, 5*V)
sage: T.gens()
((1, 0, 0), (0, 1, 0), (0, 0, 1))
```

genus(signature_pair)

Return the genus defined by self and the signature_pair.

If no such genus exists, raise a ValueError.

REFERENCES:

[Nik1977] Corollary 1.9.4 and 1.16.3.

EXAMPLES:

```
sage: L = IntegralLattice("D4").direct_sum(IntegralLattice("A2"))
sage: D = L.discriminant_group()
sage: genus = D.genus(L.signature_pair())
sage: genus
Genus of
None
Signature: (6, 0)
Genus symbol at 2: 1^4:2^-2
Genus symbol at 3: 1^-5 3^-1
sage: genus == L.genus()
True
```

Let H be an even unimodular lattice of signature $(9, 1)$. Then $L = D_4 + A_2$ is primitively embedded in H . We compute the discriminant form of the orthogonal complement of L in H :

```
sage: DK = D.twist(-1)
sage: DK
Finite quadratic module over Integer Ring with invariants (2, 6)
Gram matrix of the quadratic form with values in Q/2Z:
[ 1 1/2]
[1/2 1/3]
```

We know that K has signature $(5, 1)$ and thus we can compute the genus of K as:

```
sage: DK.genus((3,1))
Genus of
None
Signature: (3, 1)
Genus symbol at 2: 1^2:2^-2
Genus symbol at 3: 1^-3 3^1
```

We can also compute the genus of an odd lattice from its discriminant form:

```
sage: L = IntegralLattice(matrix.diagonal(range(1,5)))
sage: D = L.discriminant_group()
sage: D.genus((4,0))
Genus of
None
Signature: (4, 0)
Genus symbol at 2: [1^-2 2^1 4^1]_6
Genus symbol at 3: 1^-3 3^1
```

gram_matrix_bilinear()

Return the Gram matrix with respect to the generators.

OUTPUT:

A rational matrix G with $G[i, j]$ given by the inner product of the i -th and j -th generator. Its entries are only well defined mod (V, W) .

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = FreeQuadraticModule(ZZ, 3, matrix.identity(3)*5)
sage: T = TorsionQuadraticModule((1/5)*V, V)
sage: T.gram_matrix_bilinear()
[1/5  0  0]
[  0 1/5  0]
[  0  0 1/5]
```

gram_matrix_quadratic()

The Gram matrix of the quadratic form with respect to the generators.

OUTPUT:

- a rational matrix G_q with $G_q[i, j] = \text{gens}[i] * \text{gens}[j]$ and $G[i, i] = \text{gens}[i].q()$

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: D4_gram = Matrix(ZZ, [[2,0,0,-1],[0,2,0,-1],[0,0,2,-1],[-1,-1,-1,2]])
```

(continues on next page)

(continued from previous page)

```

sage: D4 = FreeQuadraticModule(ZZ, 4, D4_gram)
sage: D4dual = D4.span(D4_gram.inverse())
sage: discrForm = TorsionQuadraticModule(D4dual, D4)
sage: discrForm.gram_matrix_quadratic()
[ 1 1/2]
[1/2 1]
sage: discrForm.gram_matrix_bilinear()
[ 0 1/2]
[1/2 0]

```

is_genus(signature_pair, even=True)

Return True if there is a lattice with this signature and discriminant form.

Todo: implement the same for odd lattices

INPUT:

- signature_pair – a tuple of non negative integers (s_plus, s_minus)
- even – bool (default: True)

EXAMPLES:

```

sage: L = IntegralLattice("D4").direct_sum(IntegralLattice(3 * Matrix(ZZ, 2, [2, 1,
↪ 1, 2])))
sage: D = L.discriminant_group()
sage: D.is_genus((6, 0))
True

```

Let us see if there is a lattice in the genus defined by the same discriminant form but with a different signature:

```

sage: D.is_genus((4, 2))
False
sage: D.is_genus((16, 2))
True

```

normal_form(partial=False)

Return the normal form of this torsion quadratic module.

Two torsion quadratic modules are isomorphic if and only if they have the same value modules and the same normal form.

A torsion quadratic module (T, q) with values in $\mathbf{Q}/n\mathbf{Z}$ is in normal form if the rescaled quadratic module $(T, q/n)$ with values in \mathbf{Q}/\mathbf{Z} is in normal form.

For the definition of normal form see [MirMor2009] IV Definition 4.6. Below are some of its properties. Let p be odd and u be the smallest non-square modulo p . The normal form is a diagonal matrix with diagonal entries either p^n or up^n .

If $p = 2$ is even, then the normal form consists of 1×1 blocks of the form

$$(0), \quad 2^n(1), \quad 2^n(3), \quad 2^n(5), \quad 2^n(7)$$

or of 2×2 blocks of the form

$$2^n \begin{pmatrix} 2 & 1 \\ 1 & 2 \end{pmatrix}, \quad 2^n \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}.$$

The blocks are ordered by their valuation.

INPUT:

- `partial - bool` (default: `False`) return only a partial normal form it is not unique but still useful to extract invariants

OUTPUT:

- a torsion quadratic module

EXAMPLES:

```
sage: L1=IntegralLattice(matrix([[ -2,0,0],[0,1,0],[0,0,4]]))
sage: L1.discriminant_group().normal_form()
Finite quadratic module over Integer Ring with invariants (2, 4)
Gram matrix of the quadratic form with values in Q/Z:
[1/2  0]
[ 0 1/4]
sage: L2=IntegralLattice(matrix([[ -2,0,0],[0,1,0],[0,0,-4]]))
sage: L2.discriminant_group().normal_form()
Finite quadratic module over Integer Ring with invariants (2, 4)
Gram matrix of the quadratic form with values in Q/Z:
[1/2  0]
[ 0 1/4]
```

We check that [trac ticket #24864](#) is fixed:

```
sage: L1=IntegralLattice(matrix([[ -4,0,0],[0,4,0],[0,0,-2]]))
sage: AL1=L1.discriminant_group()
sage: L2=IntegralLattice(matrix([[ -4,0,0],[0,-4,0],[0,0,2]]))
sage: AL2=L2.discriminant_group()
sage: AL1.normal_form()
Finite quadratic module over Integer Ring with invariants (2, 4, 4)
Gram matrix of the quadratic form with values in Q/2Z:
[1/2  0  0]
[ 0 1/4  0]
[ 0  0 5/4]
sage: AL2.normal_form()
Finite quadratic module over Integer Ring with invariants (2, 4, 4)
Gram matrix of the quadratic form with values in Q/2Z:
[1/2  0  0]
[ 0 1/4  0]
[ 0  0 5/4]
```

Some exotic cases:

```
sage: from sage.modules.torsion_quadratic_module import _
↪ TorsionQuadraticModule
sage: D4_gram = Matrix(ZZ,4,4,[2,0,0,-1,0,2,0,-1,0,0,2,-1,-1,-1,2])
sage: D4 = FreeQuadraticModule(ZZ,4,D4_gram)
```

(continues on next page)

(continued from previous page)

```

sage: D4dual = D4.span(D4_gram.inverse())
sage: T = TorsionQuadraticModule((1/6)*D4dual,D4)
sage: T
Finite quadratic module over Integer Ring with invariants (6, 6, 12, 12)
Gram matrix of the quadratic form with values in Q/(1/3)Z:
[ 1/18  1/12  5/36  1/36]
[ 1/12   1/6  1/36   1/9]
[ 5/36  1/36  1/36 11/72]
[ 1/36   1/9 11/72  1/36]
sage: T.normal_form()
Finite quadratic module over Integer Ring with invariants (6, 6, 12, 12)
Gram matrix of the quadratic form with values in Q/(1/3)Z:
[ 1/6 1/12  0  0  0  0  0  0]
[1/12 1/6  0  0  0  0  0  0]
[  0  0 1/12 1/24  0  0  0  0]
[  0  0 1/24 1/12  0  0  0  0]
[  0  0  0  0 1/9  0  0  0]
[  0  0  0  0  0 1/9  0  0]
[  0  0  0  0  0  0 1/9  0]
[  0  0  0  0  0  0  0 1/9]

```

orthogonal_group(gens=None, check=False)

Orthogonal group of the associated torsion quadratic form.

Warning: This is can be smaller than the orthogonal group of the bilinear form.

INPUT:

- **gens** – a list of generators, for instance square matrices, something that acts on self, or an automorphism of the underlying abelian group
- **check** – perform additional checks on the generators

EXAMPLES:

You can provide generators to obtain a subgroup of the full orthogonal group:

```

sage: D = TorsionQuadraticForm(matrix.identity(2)/2)
sage: f = matrix(2,[0,1,1,0])
sage: D.orthogonal_group(gens=[f]).order()
2

```

If no generators are given a slow brute force approach is used to calculate the full orthogonal group:

```

sage: D = TorsionQuadraticForm(matrix.identity(3)/2)
sage: OD = D.orthogonal_group()
sage: OD.order()
6
sage: fd = D.hom([D.1,D.0,D.2])
sage: OD(fd)
[0 1 0]
[1 0 0]
[0 0 1]

```

We compute the kernel of the action of the orthogonal group of L on the discriminant group.

```
sage: L = IntegralLattice('A4') sage: O = L.orthogonal_group() sage: D = L.discriminant_group()
sage: Obar = D.orthogonal_group(O.gens()) sage: O.order() 240 sage: Obar.order() 2 sage: phi
= O.hom(Obar.gens()) sage: phi.kernel().order() 120
```

orthogonal_submodule_to(S)

Return the submodule orthogonal to S .

INPUT:

- S – a submodule, list, or tuple of generators

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = FreeModule(ZZ, 10)
sage: T = TorsionQuadraticModule(V, 3*V)
sage: S = T.submodule(T.gens()[5])
sage: O = T.orthogonal_submodule_to(S)
sage: O
Finite quadratic module over Integer Ring with invariants (3, 3, 3, 3, 3)
Gram matrix of the quadratic form with values in Q/3Z:
[1 0 0 0 0]
[0 1 0 0 0]
[0 0 1 0 0]
[0 0 0 1 0]
[0 0 0 0 1]
sage: O.V() + S.V() == T.V()
True
```

primary_part(m)

Return the m -primary part of this torsion quadratic module as a submodule.

INPUT:

- m – an integer

OUTPUT:

- a submodule

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: T = TorsionQuadraticModule((1/6)*ZZ^3, ZZ^3)
sage: T
Finite quadratic module over Integer Ring with invariants (6, 6, 6)
Gram matrix of the quadratic form with values in Q/(1/3)Z:
[1/36 0 0]
[0 1/36 0]
[0 0 1/36]
sage: T.primary_part(2)
Finite quadratic module over Integer Ring with invariants (2, 2, 2)
Gram matrix of the quadratic form with values in Q/(1/3)Z:
[1/4 0 0]
[0 1/4 0]
[0 0 1/4]
```


submodule_with_gens(gens)

Return a submodule with generators given by gens.

INPUT:

- gens – a list of generators that convert into self

OUTPUT:

- a submodule with the specified generators

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = FreeQuadraticModule(ZZ,3,matrix.identity(3)*10)
sage: T = TorsionQuadraticModule((1/10)*V, V)
sage: g = T.gens()
sage: new_gens = [2*g[0], 5*g[0]]
sage: T.submodule_with_gens(new_gens)
Finite quadratic module over Integer Ring with invariants (10,)
Gram matrix of the quadratic form with values in Q/2Z:
[2/5  0]
[ 0 1/2]
```

The generators do not need to be independent:

```
sage: new_gens = [g[0], 2*g[1], g[0], g[1]]
sage: T.submodule_with_gens(new_gens)
Finite quadratic module over Integer Ring with invariants (10, 10)
Gram matrix of the quadratic form with values in Q/2Z:
[1/10  0 1/10  0]
[ 0 2/5  0 1/5]
[1/10  0 1/10  0]
[ 0 1/5  0 1/10]
```

twist(s)

Return the torsion quadratic module with quadratic form scaled by s.

If the old form was defined modulo n , then the new form is defined modulo ns .

INPUT:

- s - a rational number

EXAMPLES:

```
sage: q = TorsionQuadraticForm(matrix.diagonal([3/9, 1/9]))
sage: q.twist(-1)
Finite quadratic module over Integer Ring with invariants (3, 9)
Gram matrix of the quadratic form with values in Q/Z:
[2/3  0]
[ 0 8/9]
```

This form is defined modulo 3:

```
sage: q.twist(3)
Finite quadratic module over Integer Ring with invariants (3, 9)
Gram matrix of the quadratic form with values in Q/3Z:
```

(continues on next page)

(continued from previous page)

```
[ 1  0]
[ 0 1/3]
```

The next form is defined modulo 4:

```
sage: q.twist(4)
Finite quadratic module over Integer Ring with invariants (3, 9)
Gram matrix of the quadratic form with values in Q/4Z:
[4/3  0]
[ 0 4/9]
```

value_module()

Return $\mathbf{Q}/m\mathbf{Z}$ with $m = (V, W)$.

This is where the inner product takes values.

EXAMPLES:

```
sage: A2 = Matrix(ZZ, 2, 2, [2,-1,-1,2])
sage: L = IntegralLattice(2*A2)
sage: D = L.discriminant_group()
sage: D
Finite quadratic module over Integer Ring with invariants (2, 6)
Gram matrix of the quadratic form with values in Q/2Z:
[ 1 1/2]
[1/2 1/3]
sage: D.value_module()
Q/Z
```

value_module_qf()

Return $\mathbf{Q}/n\mathbf{Z}$ with $n\mathbf{Z} = (V, W) + \mathbf{Z}\{(w, w) | w \in W\}$.

This is where the torsion quadratic form takes values.

EXAMPLES:

```
sage: A2 = Matrix(ZZ, 2, 2, [2,-1,-1,2])
sage: L = IntegralLattice(2*A2)
sage: D = L.discriminant_group()
sage: D
Finite quadratic module over Integer Ring with invariants (2, 6)
Gram matrix of the quadratic form with values in Q/2Z:
[ 1 1/2]
[1/2 1/3]
sage: D.value_module_qf()
Q/2Z
```

class sage.modules.torsion_quadratic_module.TorsionQuadraticModuleElement(*parent, x,*
check=True)

Bases: *sage.modules.fg_pid.fgp_element.FGP_Element*

An element of a torsion quadratic module.

INPUT:

- parent – parent

- `x` – element of `parent.V()`
- `check` – bool (default: True)

b(*other*)

Compute the inner product of two elements.

OUTPUT:

- an element of $\mathbf{Q}/m\mathbf{Z}$ with $m\mathbf{Z} = (V, W)$

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = (1/2)*ZZ^2; W = ZZ^2
sage: T = TorsionQuadraticModule(V, W)
sage: g = T.gens()
sage: x = g[0]
sage: y = g[0] + g[1]
sage: x
(1, 0)
sage: x*y
1/4
```

The inner product has further aliases:

```
sage: x.inner_product(y)
1/4
sage: x.b(y)
1/4
```

inner_product(*other*)

Compute the inner product of two elements.

OUTPUT:

- an element of $\mathbf{Q}/m\mathbf{Z}$ with $m\mathbf{Z} = (V, W)$

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: V = (1/2)*ZZ^2; W = ZZ^2
sage: T = TorsionQuadraticModule(V, W)
sage: g = T.gens()
sage: x = g[0]
sage: y = g[0] + g[1]
sage: x
(1, 0)
sage: x*y
1/4
```

The inner product has further aliases:

```
sage: x.inner_product(y)
1/4
sage: x.b(y)
1/4
```

q()

Compute the quadratic_product of self.

OUTPUT:

- an element of $\mathbf{Q}/n\mathbf{Z}$ where $n\mathbf{Z} = 2(V, W) + \mathbf{Z}\{(w, w) | w \in W\}$

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: W = FreeQuadraticModule(ZZ, 2, 2*matrix.identity(2))
sage: V = (1/2) * W
sage: T = TorsionQuadraticModule(V, W)
sage: x = T.gen(0)
sage: x
(1, 0)
sage: x.quadratic_product()
1/2
sage: x.quadratic_product().parent()
Q/2Z
sage: x*x
1/2
sage: (x*x).parent()
Q/Z
```

quadratic_product()

Compute the quadratic_product of self.

OUTPUT:

- an element of $\mathbf{Q}/n\mathbf{Z}$ where $n\mathbf{Z} = 2(V, W) + \mathbf{Z}\{(w, w) | w \in W\}$

EXAMPLES:

```
sage: from sage.modules.torsion_quadratic_module import TorsionQuadraticModule
sage: W = FreeQuadraticModule(ZZ, 2, 2*matrix.identity(2))
sage: V = (1/2) * W
sage: T = TorsionQuadraticModule(V, W)
sage: x = T.gen(0)
sage: x
(1, 0)
sage: x.quadratic_product()
1/2
sage: x.quadratic_product().parent()
Q/2Z
sage: x*x
1/2
sage: (x*x).parent()
Q/Z
```

6.5 Z-filtered vector spaces

This module implements filtered vector spaces, that is, a descending sequence of vector spaces

$$\cdots \supset F_d \supset F_{d+1} \supset F_{d+2} \supset \cdots$$

with degrees $d \in \mathbf{Z}$. It is not required that F_d is the entire ambient space for $d \ll 0$ (see `is_exhaustive()`) nor that $F_d = 0$ for $d \gg 0$ (see `is_separating()`). To construct a filtered vector space, use the `FilteredVectorSpace()` command. It supports easy creation of simple filtrations, for example the trivial one:

```
sage: FilteredVectorSpace(2, base_ring=RDF)
RDF^2
```

The next-simplest filtration has a single non-trivial inclusion between V_d and V_{d+1} :

```
sage: d = 1
sage: V = FilteredVectorSpace(2, d); V
QQ^2 >= 0
sage: [V.get_degree(i).dimension() for i in range(0,4)]
[2, 2, 0, 0]
```

To construct general filtrations, you need to tell Sage about generating vectors for the nested subspaces. For example, a dictionary whose keys are the degrees and values are a list of generators:

```
sage: r1 = (1, 0, 5)
sage: r2 = (0, 1, 2)
sage: r3 = (1, 2, 1)
sage: V = FilteredVectorSpace({0:[r1, r2, r3], 1:[r1, r2], 3:[r1]}); V
QQ^3 >= QQ^2 >= QQ^1 >= QQ^1 >= 0
```

For degrees d that are not specified, the associated vector subspace is the same as the next-lower degree, that is, $V_d \simeq V_{d-1}$. In the above example, this means that

- $V_d \simeq \mathbf{Q}^3$ for $d < 0$
- $V_0 = \text{span}(r_1, r_2) \simeq \mathbf{Q}^2$
- $V_1 = V_2 = \text{span}(r_3) \simeq \mathbf{Q}$
- $V_d = 0$ for $d \geq 3$

That is:

```
sage: V.get_degree(0) == V
True
sage: V.get_degree(1) == V.span([r1, r2])
True
sage: V.get_degree(2) == V.get_degree(3) == V.span([r1])
True
sage: V.get_degree(4) == V.get_degree(5) == V.span([])
True
```

If you have many generators you can just pass the generators once and then refer to them by index:

```
sage: FilteredVectorSpace([r1, r2, r3], {0:[0,1,2], 1:[1,2], 3:[1]})
QQ^3 >= QQ^2 >= QQ^1 >= QQ^1 >= 0
```

Note that generators for the degree- d subspace of the filtration are automatically generators for all lower degrees. For example, here we do not have to specify the ray r_2 separately in degree 1:

```
sage: FilteredVectorSpace([r1, r2, r3], {0:[0 ], 1:[1]})
QQ^2 >= QQ^1 >= 0 in QQ^3
sage: FilteredVectorSpace([r1, r2, r3], {0:[0, 1], 1:[1]})
QQ^2 >= QQ^1 >= 0 in QQ^3
```

The degree can be infinite (plus infinity), this allows construction of filtered vector spaces that are not eventually zero in high degree:

```
sage: FilteredVectorSpace([r1, r2, r3], {0:[0,1], oo:[1]})
QQ^2 >= QQ^1 in QQ^3
```

Any field can be used as the vector space base. For example a finite field:

```
sage: F.<a> = GF(5^3)
sage: r1 = (a, 0, F(5)); r1
(a, 0, 0)
sage: FilteredVectorSpace([r1, r2, r3], {0:[0,1], oo:[1]}, base_ring=F)
GF(125)^2 >= GF(125)^1 in GF(125)^3
```

Or the algebraic field:

```
sage: r1 = (1, 0, 1+QQbar(I)); r1
(1, 0, I + 1)
sage: FilteredVectorSpace([r1, r2, r3], {0:[0,1], oo:[1]}, base_ring=QQbar)
Vector space of dimension 2 over Algebraic Field
>= Vector space of dimension 1 over Algebraic Field
in Vector space of dimension 3 over Algebraic Field
```

`sage.modules.filtered_vector_space.FilteredVectorSpace(arg1, arg2=None, base_ring=RationalField, check=True)`

Construct a filtered vector space.

INPUT:

This function accepts various input that determines the vector space and filtration.

- Just the dimension `FilteredVectorSpace(dimension)`: Return the trivial filtration (where all vector spaces are isomorphic).
- Dimension and maximal degree, see `constructor_from_dim_degree()` for arguments. Construct a filtration with only one non-trivial step $V \supset 0$ at the given cutoff degree.
- A dictionary containing the degrees as keys and a list of vector space generators as values, see `FilteredVectorSpace_from_generators()`
- Generators and a dictionary containing the degrees as keys and the indices of vector space generators as values, see `FilteredVectorSpace_from_generators_indices()`

In addition, the following keyword arguments are supported:

- `base_ring` – a field (optional, default \mathbb{Q}). The base field of the vector space. Must be a field.

EXAMPLES:

Just the dimension for the trivial filtration:

```
sage: FilteredVectorSpace(2)
QQ^2
```

Dimension and degree:

```
sage: FilteredVectorSpace(2, 1)
QQ^2 >= 0
```

Dictionary of generators:

```
sage: FilteredVectorSpace({1:[(1,0), (0,1)], 3:[(1,0)]})
QQ^2 >= QQ^1 >= QQ^1 >= 0
```

Generators and a dictionary referring to them by index:

```
sage: FilteredVectorSpace([(1,0), (0,1)], {1:[0,1], 3:[0]})
QQ^2 >= QQ^1 >= QQ^1 >= 0
```

class `sage.modules.filtered_vector_space.FilteredVectorSpace_class`(*base_ring*, *dim*, *generators*, *filtration*, *check=True*)

Bases: `sage.modules.free_module.FreeModule_ambient_field`

A descending filtration of a vector space

INPUT:

- `base_ring` – a field. The base field of the ambient vector space.
- `dim` – integer. The dimension of the ambient vector space.
- `generators` – tuple of generators for the ambient vector space. These will be used to span the subspaces of the filtration.
- `filtration` – a dictionary of filtration steps in ray index notation. See [construct_from_generators_indices\(\)](#) for details.
- `check` – boolean (optional; default: `True`). Whether to perform consistency checks.

ambient_vector_space()

Return the ambient (unfiltered) vector space.

OUTPUT:

A vector space.

EXAMPLES:

```
sage: V = FilteredVectorSpace(1, 0)
sage: V.ambient_vector_space()
Vector space of dimension 1 over Rational Field
```

change_ring(*base_ring*)

Return the same filtration over a different base ring.

INPUT:

- `base_ring` – a ring. The new base ring.

OUTPUT:

This method returns a new filtered vector space whose subspaces are defined by the same generators but over a different base ring.

EXAMPLES:

```
sage: V = FilteredVectorSpace(1, 0); V
QQ^1 >= 0
sage: V.change_ring(RDF)
RDF^1 >= 0
```

direct_sum(*other*)

Return the direct sum.

INPUT:

- *other* – a filtered vector space.

OUTPUT:

The direct sum as a filtered vector space.

EXAMPLES:

```
sage: V = FilteredVectorSpace(2, 0)
sage: W = FilteredVectorSpace({0:[(1,-1),(2,1)], 1:[(1,1)]})
sage: V.direct_sum(W)
QQ^4 >= QQ^1 >= 0
sage: V + W      # syntactic sugar
QQ^4 >= QQ^1 >= 0
sage: V + V == FilteredVectorSpace(4, 0)
True

sage: W = FilteredVectorSpace([(1,-1),(2,1)], {1:[0,1], 2:[1]})
sage: V + W
QQ^4 >= QQ^2 >= QQ^1 >= 0
```

A suitable base ring is chosen if they do not match:

```
sage: v = [(1,0), (0,1)]
sage: F1 = FilteredVectorSpace(v, {0:[0], 1:[1]}, base_ring=QQ)
sage: F2 = FilteredVectorSpace(v, {0:[0], 1:[1]}, base_ring=RDF)
sage: F1 + F2
RDF^4 >= RDF^2 >= 0
```

dual()

Return the dual filtered vector space.

OUTPUT:

The graded dual, that is, the dual of a degree- d subspace is a set of linear constraints in degree $-d + 1$. That is, the dual generators live in degree $-d$.

EXAMPLES:

```
sage: gens = identity_matrix(3).rows()
sage: F = FilteredVectorSpace(gens, {0:[0,1,2], 2:[0]}); F
QQ^3 >= QQ^1 >= QQ^1 >= 0
sage: F.support()
(0, 2)

sage: F.dual()
```

(continues on next page)

(continued from previous page)

```

QQ^3 >= QQ^2 >= QQ^2 >= 0
sage: F.dual().support()
(-2, 0)

```

exterior_power(*n*)

Return the n -th graded exterior power.

INPUT:

- n – integer. Exterior product of how many copies of `self`.

OUTPUT:

The graded exterior product, that is, the wedge product of a generator of degree d_1 with a generator in degree d_2 has degree $d_1 + d_2$.

EXAMPLES:

```

sage: F = FilteredVectorSpace(1, 1) + FilteredVectorSpace(1, 2); F
QQ^2 >= QQ^1 >= 0
sage: F.exterior_power(1)
QQ^2 >= QQ^1 >= 0
sage: F.exterior_power(2)
QQ^1 >= 0
sage: F.exterior_power(3)
0
sage: F.wedge(2)
QQ^1 >= 0

```

get_degree(*d*)

Return the degree- d entry of the filtration.

INPUT:

- d – Integer. The desired degree of the filtration.

OUTPUT:

The degree- d vector space in the filtration as subspace of the ambient space.

EXAMPLES:

```

sage: rays = [(1,0), (1,1), (1,2), (-1,-1)]
sage: F = FilteredVectorSpace(rays, {3:[1], 1:[1,2]})
sage: F.get_degree(2)
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 1]
sage: F.get_degree(0)
Vector space of degree 2 and dimension 0 over Rational Field
Basis matrix:
[]
sage: F.get_degree(-oo)
Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]

```

graded(*d*)

Return the associated graded vectorspace.

INPUT:

- *d* – integer. The degree.

OUTPUT:

The quotient $G_d = F_d/F_{d+1}$.

EXAMPLES:

```
sage: rays = [(1,0), (1,1), (1,2)]
sage: F = FilteredVectorSpace(rays, {3:[1], 1:[1,2]})
sage: F.graded(1)
Vector space quotient V/W of dimension 1 over Rational Field where
V: Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]
W: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 1]
```

is_constant()

Return whether the filtration is constant.

OUTPUT:

Boolean. Whether the filtered vector spaces are identical in all degrees.

EXAMPLES:

```
sage: V = FilteredVectorSpace(2); V
QQ^2
sage: V.is_constant()
True

sage: V = FilteredVectorSpace(1, 0); V
QQ^1 >= 0
sage: V.is_constant()
False

sage: V = FilteredVectorSpace({0:[(1,)]}); V
QQ^1 >= 0
sage: V.is_constant()
False
```

is_exhaustive()

Return whether the filtration is exhaustive.

A filtration $\{F_d\}$ in an ambient vector space V is exhaustive if $\cup F_d = V$. See also [is_separating\(\)](#).

OUTPUT:

Boolean.

EXAMPLES:

```

sage: F = FilteredVectorSpace({0:[(1,1)]}); F
QQ^1 >= 0 in QQ^2
sage: F.is_exhaustive()
False
sage: G = FilteredVectorSpace(2, 0); G
QQ^2 >= 0
sage: G.is_exhaustive()
True

```

is_separating()

Return whether the filtration is separating.

A filtration $\{F_d\}$ in an ambient vector space V is exhaustive if $\cap F_d = 0$. See also [is_exhaustive\(\)](#).

OUTPUT:

Boolean.

EXAMPLES:

```

sage: F = FilteredVectorSpace({0:[(1,1)]}); F
QQ^1 >= 0 in QQ^2
sage: F.is_separating()
True
sage: G = FilteredVectorSpace({0:[(1,1,0)], oo:[(0,0,1)]}); G
QQ^2 >= QQ^1 in QQ^3
sage: G.is_separating()
False

```

max_degree()

Return the highest degree of the filtration.

OUTPUT:

Integer or minus infinity. The smallest degree of the filtration such that the filtration is constant to the right.

EXAMPLES:

```

sage: FilteredVectorSpace(1, 3).max_degree()
4
sage: FilteredVectorSpace({0:[(1)]}).max_degree()
1
sage: FilteredVectorSpace(3).max_degree()
-Infinity

```

min_degree()

Return the lowest degree of the filtration.

OUTPUT:

Integer or plus infinity. The largest degree d of the (descending) filtration such that the filtered vector space F_d is still equal to $F_{-\infty}$.

EXAMPLES:

```

sage: FilteredVectorSpace(1, 3).min_degree()
3
sage: FilteredVectorSpace(2).min_degree()
+Infinity

```

presentation()

Return a presentation in term of generators of various degrees.

OUTPUT:

A pair consisting of generators and a filtration suitable as input to `construct_from_generators_indices()`.

EXAMPLES:

```
sage: rays = [(1,0), (1,1), (1,2), (-1,-1)]
sage: F = FilteredVectorSpace(rays, {0:[1, 2], 2:[3]}); F
QQ^2 >= QQ^1 >= QQ^1 >= 0
sage: F.presentation()
(((0, 1), (1, 0), (1, 1)), {0: (1, 0), 2: (2,), +Infinity: ()})
```

random_deformation(*epsilon=None*)

Return a random deformation

INPUT:

- *epsilon* – a number in the base ring.

OUTPUT:

A new filtered vector space where the generators of the subspaces are moved by *epsilon* times a random vector.

EXAMPLES:

```
sage: gens = identity_matrix(3).rows()
sage: F = FilteredVectorSpace(gens, {0:[0,1,2], 2:[0]}); F
QQ^3 >= QQ^1 >= QQ^1 >= 0
sage: F.get_degree(2)
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[1 0 0]
sage: G = F.random_deformation(1/50); G
QQ^3 >= QQ^1 >= QQ^1 >= 0
sage: D = G.get_degree(2)
sage: D.degree()
3
sage: v = D.basis_matrix()[0]
sage: v[0]
1
sage: while F.random_deformation(1/50).get_degree(2).matrix() == matrix([1, 0,
->0]):
.....:     pass
```

shift(*deg*)

Return a filtered vector space with degrees shifted by a constant.

EXAMPLES:

```
sage: gens = identity_matrix(3).rows()
sage: F = FilteredVectorSpace(gens, {0:[0,1,2], 2:[0]}); F
QQ^3 >= QQ^1 >= QQ^1 >= 0
```

(continues on next page)

(continued from previous page)

```
sage: F.support()
(0, 2)
sage: F.shift(-5).support()
(-5, -3)
```

support()

Return the degrees in which there are non-trivial generators.

OUTPUT:

A tuple of integers (and plus infinity) in ascending order. The last entry is plus infinity if and only if the filtration is not separating (see [is_separating\(\)](#)).

EXAMPLES:

```
sage: G = FilteredVectorSpace({0:[(1,1,0)], 3:[(0,1,0)]}); G
QQ^2 >= QQ^1 >= QQ^1 >= QQ^1 >= 0 in QQ^3
sage: G.support()
(0, 3)

sage: G = FilteredVectorSpace({0:[(1,1,0)], 3:[(0,1,0)], oo:[(0,0,1)]}); G
QQ^3 >= QQ^2 >= QQ^2 >= QQ^2 >= QQ^1
sage: G.support()
(0, 3, +Infinity)
```

symmetric_power(*n*)

Return the n -th graded symmetric power.

INPUT:

- *n* – integer. Symmetric product of how many copies of *self*.

OUTPUT:

The graded symmetric product, that is, the symmetrization of a generator of degree d_1 with a generator in degree d_2 has degree $d_1 + d_2$.

EXAMPLES:

```
sage: F = FilteredVectorSpace(1, 1) + FilteredVectorSpace(1, 2); F
QQ^2 >= QQ^1 >= 0
sage: F.symmetric_power(2)
QQ^3 >= QQ^2 >= QQ^1 >= 0
```

tensor_product(*other*)

Return the graded tensor product.

INPUT:

- *other* – a filtered vector space.

OUTPUT:

The graded tensor product, that is, the tensor product of a generator of degree d_1 with a generator in degree d_2 has degree $d_1 + d_2$.

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(1, 1)
sage: F2 = FilteredVectorSpace(1, 2)
sage: F1.tensor_product(F2)
QQ^1 >= 0
sage: F1 * F2
QQ^1 >= 0

sage: F1.min_degree()
1
sage: F2.min_degree()
2
sage: (F1*F2).min_degree()
3

```

A suitable base ring is chosen if they do not match:

```

sage: v = [(1,0), (0,1)]
sage: F1 = FilteredVectorSpace(v, {0:[0], 1:[1]}, base_ring=QQ)
sage: F2 = FilteredVectorSpace(v, {0:[0], 1:[1]}, base_ring=RDF)
sage: F1 * F2
RDF^4 >= RDF^3 >= RDF^1 >= 0

```

wedge(*n*)

Return the n -th graded exterior power.

INPUT:

- n – integer. Exterior product of how many copies of `self`.

OUTPUT:

The graded exterior product, that is, the wedge product of a generator of degree d_1 with a generator in degree d_2 has degree $d_1 + d_2$.

EXAMPLES:

```

sage: F = FilteredVectorSpace(1, 1) + FilteredVectorSpace(1, 2); F
QQ^2 >= QQ^1 >= 0
sage: F.exterior_power(1)
QQ^2 >= QQ^1 >= 0
sage: F.exterior_power(2)
QQ^1 >= 0
sage: F.exterior_power(3)
0
sage: F.wedge(2)
QQ^1 >= 0

```

`sage.modules.filtered_vector_space.construct_from_dim_degree(dim, max_degree, base_ring, check)`
Construct a filtered vector space.

INPUT:

- dim – integer. The dimension.
- max_degree – integer or infinity. The maximal degree where the vector subspace of the filtration is still the entire space.

EXAMPLES:

```

sage: V = FilteredVectorSpace(2, 5); V
QQ^2 >= 0
sage: V.get_degree(5)
Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]
sage: V.get_degree(6)
Vector space of degree 2 and dimension 0 over Rational Field
Basis matrix:
[]

sage: FilteredVectorSpace(2, oo)
QQ^2
sage: FilteredVectorSpace(2, -oo)
0 in QQ^2

```

`sage.modules.filtered_vector_space.construct_from_generators(filtration, base_ring, check)`
Construct a filtered vector space.

INPUT:

- `filtration` – a dictionary of filtration steps. Each filtration step is a pair consisting of an integer degree and a list/tuple/iterable of vector space generators. The integer degree stipulates that all filtration steps of degree higher or equal than degree (up to the next filtration step) are said subspace.

EXAMPLES:

```

sage: from sage.modules.filtered_vector_space import construct_from_generators
sage: r = [1, 2]
sage: construct_from_generators({1:[r]}, QQ, True)
QQ^1 >= 0 in QQ^2

```

`sage.modules.filtered_vector_space.construct_from_generators_indices(generators, filtration, base_ring, check)`
Construct a filtered vector space.

INPUT:

- `generators` – a list/tuple/iterable of vectors, or something convertible to them. The generators spanning various subspaces.
- `filtration` – a list or iterable of filtration steps. Each filtration step is a pair (degree, ray_indices). The ray_indices are a list or iterable of ray indices, which span a subspace of the vector space. The integer degree stipulates that all filtration steps of degree higher or equal than degree (up to the next filtration step) are said subspace.

EXAMPLES:

```

sage: from sage.modules.filtered_vector_space import construct_from_generators_
sage: gens = [(1,0), (0,1), (-1,-1)]
sage: V = construct_from_generators_indices(gens, {1:[0,1], 3:[1]}, QQ, True); V
QQ^2 >= QQ^1 >= QQ^1 >= 0

```

`sage.modules.filtered_vector_space.is_FilteredVectorSpace(X)`
Test whether X is a filtered vector space.

This function is for library use only.

INPUT:

- X – anything.

OUTPUT:

Boolean.

EXAMPLES:

```
sage: from sage.modules.filtered_vector_space import is_FilteredVectorSpace
sage: V = FilteredVectorSpace(2, 1)
sage: is_FilteredVectorSpace(V)
True
sage: is_FilteredVectorSpace('ceci n'est pas une pipe')
False
```

```
sage.modules.filtered_vector_space.normalize_degree(deg)
```

Normalized the degree

- deg – something that defines the degree (either integer or infinity).

OUTPUT:

Plus/minus infinity or a Sage integer.

EXAMPLES:

```
sage: from sage.modules.filtered_vector_space import normalize_degree
sage: type(normalize_degree(int(1)))
<class 'sage.rings.integer.Integer'>
sage: normalize_degree(oo)
+Infinity
```

6.6 Multiple Z-graded filtrations of a single vector space

See `filtered_vector_space` for simply graded vector spaces. This module implements the analog but for a collection of filtrations of the same vector space.

The basic syntax to use it is a dictionary whose keys are some arbitrary indexing set and values are `FilteredVectorSpace()`

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace({0:[(1,0)], 2:[(2,3)]})
sage: V = MultiFilteredVectorSpace({'first':F1, 'second':F2})
sage: V
Filtrations
  first: QQ^2 >= QQ^2 >= 0 >= 0
  second: QQ^2 >= QQ^1 >= QQ^1 >= 0

sage: V.index_set() # random output
{'second', 'first'}
sage: sorted(V.index_set())
['first', 'second']
```

(continues on next page)

(continued from previous page)

```

sage: V.get_filtration('first')
QQ^2 >= 0
sage: V.get_degree('second', 1)
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[ 1 3/2]

```

```

sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace(arg, base_ring=None,
                                                                    check=True)

```

Construct a multi-filtered vector space.

INPUT:

- *arg* – either a non-empty dictionary of filtrations or an integer. The latter is interpreted as the vector space dimension, and the indexing set of the filtrations is empty.
- *base_ring* – a field (optional, default 'None'). The base field of the vector space. Must be a field. If not specified, the base field is derived from the filtrations.
- *check* – boolean (optional; default: True). Whether to perform consistency checks.

EXAMPLES:

```

sage: MultiFilteredVectorSpace(3, QQ)
Unfiltered QQ^3

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2}); V
Filtrations
1: QQ^2 >= 0    >= 0    >= 0
2: QQ^2 >= QQ^2 >= QQ^2 >= 0

```

```

class sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class(base_ring,
                                                                              dim,
                                                                              filtrations,
                                                                              check=True)

```

Bases: *sage.modules.free_module.FreeModule_ambient_field*

Python constructor.

Warning: Use `MultiFilteredVectorSpace()` to construct multi-filtered vector spaces.

INPUT:

- *base_ring* – a ring. the base ring.
- *dim* – integer. The dimension of the ambient vector space.
- *filtrations* – a dictionary whose values are filtrations.
- *check* – boolean (optional). Whether to perform additional consistency checks.

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2}); V
Filtrations
  1: QQ^2 >= 0 >= 0 >= 0
  2: QQ^2 >= QQ^2 >= QQ^2 >= 0

```

ambient_vector_space()

Return the ambient (unfiltered) vector space.

OUTPUT:

A vector space.

EXAMPLES:

```

sage: V = FilteredVectorSpace(2, 0)
sage: W = FilteredVectorSpace(2, 2)
sage: F = MultiFilteredVectorSpace({'a':V, 'b':W})
sage: F.ambient_vector_space()
Vector space of dimension 2 over Rational Field

```

change_ring(*base_ring*)

Return the same multi-filtration over a different base ring.

INPUT:

- *base_ring* – a ring. The new base ring.

OUTPUT:

This method returns a new multi-filtered vector space whose subspaces are defined by the same generators but over a different base ring.

EXAMPLES:

```

sage: V = FilteredVectorSpace(2, 0)
sage: W = FilteredVectorSpace(2, 2)
sage: F = MultiFilteredVectorSpace({'a':V, 'b':W}); F
Filtrations
  a: QQ^2 >= 0 >= 0 >= 0
  b: QQ^2 >= QQ^2 >= QQ^2 >= 0
sage: F.change_ring(RDF)
Filtrations
  a: RDF^2 >= 0 >= 0 >= 0
  b: RDF^2 >= RDF^2 >= RDF^2 >= 0

sage: MultiFilteredVectorSpace(3, base_ring=QQ).change_ring(RR)
Unfiltered RR^3

```

direct_sum(*other*)

Return the direct sum.

INPUT:

- *other* – a multi-filtered vector space with the same [index_set\(\)](#).

OUTPUT:

The direct sum as a multi-filtered vector space. See [direct_sum\(\)](#).

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: G1 = FilteredVectorSpace(1, 1)
sage: G2 = FilteredVectorSpace(1, 3)
sage: W = MultiFilteredVectorSpace({'a':G1, 'b':G2})
sage: V.direct_sum(W)
Filtrations
  a: QQ^3 >= QQ^3 >= 0 >= 0 >= 0
  b: QQ^3 >= QQ^2 >= QQ^2 >= QQ^2 >= 0
sage: V + W # syntactic sugar
Filtrations
  a: QQ^3 >= QQ^3 >= 0 >= 0 >= 0
  b: QQ^3 >= QQ^2 >= QQ^2 >= QQ^2 >= 0
```

dual()

Return the dual.

OUTPUT:

The dual as a multi-filtered vector space. See [dual\(\)](#).

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: V.dual()
Filtrations
  a: QQ^2 >= QQ^2 >= QQ^2 >= 0 >= 0
  b: QQ^2 >= QQ^1 >= QQ^1 >= QQ^1 >= 0
```

exterior_power(n)

Return the n -th graded exterior power.

INPUT:

- n – integer. Exterior product of how many copies of `self`.

OUTPUT:

The exterior power as a multi-filtered vector space. See [exterior_power\(\)](#).

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: V.exterior_power(2) # long time
Filtrations
  a: QQ^1 >= 0 >= 0
  b: QQ^1 >= QQ^1 >= 0
```

get_degree(key, deg)

Return one filtered vector space.

INPUT:

- `key` – an element of the `index_set()`. Specifies which filtration.
- `d` – Integer. The desired degree of the filtration.

OUTPUT:

The vector space of degree `deg` in the filtration indexed by `key` as subspace of the ambient space.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.get_degree(2, 0)
Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]
```

get_filtration(*key*)

Return the filtration indexed by `key`.

OUTPUT:

A filtered vector space.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.get_filtration(2)
QQ^2 >= 0
```

graded(*key*, *deg*)

Return the associated graded vector space.

INPUT:

- `key` – an element of the `index_set()`. Specifies which filtration.
- `d` – Integer. The desired degree of the filtration.

OUTPUT:

The quotient $G_d = F_d/F_{d+1}$ of the filtration F corresponding to `key`.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.graded(2, 3)
Vector space quotient V/W of dimension 1 over Rational Field where
V: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 0]
W: Vector space of degree 2 and dimension 0 over Rational Field
Basis matrix:
[]
```

index_set()

Return the allowed indices for the different filtrations.

OUTPUT:

Set.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.index_set()
{1, 2}
```

is_constant()

Return whether the multi-filtration is constant.

OUTPUT:

Boolean. Whether the each filtration is constant, see [is_constant\(\)](#).

EXAMPLES:

```
sage: V = FilteredVectorSpace(2, 0)
sage: W = FilteredVectorSpace(2, 2)
sage: F = MultiFilteredVectorSpace({'a':V, 'b':W}); F
Filtrations
  a: QQ^2 >= 0    >= 0    >= 0
  b: QQ^2 >= QQ^2 >= QQ^2 >= 0
sage: F.is_constant()
False
```

is_exhaustive()

Return whether the multi-filtration is exhaustive.

A filtration $\{F_d\}$ in an ambient vector space V is exhaustive if $\cup F_d = V$. See also [is_separating\(\)](#).

OUTPUT:

Boolean. Whether each filtration is constant, see [is_exhaustive\(\)](#).

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.is_exhaustive()
True
```

is_separating()

Return whether the multi-filtration is separating.

A filtration $\{F_d\}$ in an ambient vector space V is exhaustive if $\cap F_d = 0$. See also [is_exhaustive\(\)](#).

OUTPUT:

Boolean. Whether each filtration is separating, see [is_separating\(\)](#).

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.is_separating()
True
```

max_degree()

Return the highest degree of the filtration.

OUTPUT:

Integer or minus infinity. The smallest degree of the filtrations such that the filtrations are constant to the right.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.max_degree()
4
```

min_degree()

Return the lowest degree of the filtration.

OUTPUT:

Integer or plus infinity. The largest degree d of the (descending) filtrations such that, for each individual filtration, the filtered vector space F_d still equal to $F_{-\infty}$.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.min_degree()
1
```

random_deformation(*epsilon=None*)

Return a random deformation

INPUT:

- *epsilon* – a number in the base ring.

OUTPUT:

A new multi-filtered vector space where the generating vectors of subspaces are moved by *epsilon* times a random vector.

EXAMPLES:

```
sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: V.get_degree('b',1)
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 0]
```

(continues on next page)

(continued from previous page)

```

sage: D = V.random_deformation(1/100).get_degree('b',1)
sage: D.degree()
2
sage: D.dimension()
1
sage: D.matrix()[0, 0]
1

sage: while V.random_deformation(1/100).get_degree('b',1).matrix() == matrix([1,
↪ 0]):
....:     pass

```

shift(*deg*)

Return a filtered vector space with degrees shifted by a constant.

OUTPUT:

The shift of `self`. See [shift\(\)](#).

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: V.support()
(0, 1, 3)
sage: V.shift(-5).support()
(-5, -4, -2)

```

support()

Return the degrees in which there are non-trivial generators.

OUTPUT:

A tuple of integers (and plus infinity) in ascending order. The last entry is plus infinity if and only if the filtration is not separating (see [is_separating\(\)](#)).

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(2, 3)
sage: V = MultiFilteredVectorSpace({1:F1, 2:F2})
sage: V.support()
(1, 3)

```

symmetric_power(*n*)

Return the n -th graded symmetric power.

INPUT:

- n – integer. Symmetric product of how many copies of `self`.

OUTPUT:

The symmetric power as a multi-filtered vector space. See [symmetric_power\(\)](#).

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: V.symmetric_power(2)
Filtrations
  a: QQ^3 >= QQ^3 >= QQ^3 >= 0 >= 0 >= 0 >= 0 >= 0
  b: QQ^3 >= QQ^2 >= QQ^2 >= QQ^2 >= QQ^1 >= QQ^1 >= QQ^1 >= 0

```

tensor_product(*other*)

Return the graded tensor product.

INPUT:

- *other* – a multi-filtered vector space with the same [index_set\(\)](#).

OUTPUT:

The tensor product of *self* and *other* as a multi-filtered vector space. See [tensor_product\(\)](#).

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: G1 = FilteredVectorSpace(1, 1)
sage: G2 = FilteredVectorSpace(1, 3)
sage: W = MultiFilteredVectorSpace({'a':G1, 'b':G2})
sage: V.tensor_product(W)
Filtrations
  a: QQ^2 >= 0 >= 0 >= 0 >= 0 >= 0
  b: QQ^2 >= QQ^2 >= QQ^1 >= QQ^1 >= QQ^1 >= 0
sage: V * W # syntactic sugar
Filtrations
  a: QQ^2 >= 0 >= 0 >= 0 >= 0 >= 0
  b: QQ^2 >= QQ^2 >= QQ^1 >= QQ^1 >= QQ^1 >= 0

```

wedge(*n*)

Return the *n*-th graded exterior power.

INPUT:

- *n* – integer. Exterior product of how many copies of *self*.

OUTPUT:

The exterior power as a multi-filtered vector space. See [exterior_power\(\)](#).

EXAMPLES:

```

sage: F1 = FilteredVectorSpace(2, 1)
sage: F2 = FilteredVectorSpace(1, 3) + FilteredVectorSpace(1,0)
sage: V = MultiFilteredVectorSpace({'a':F1, 'b':F2})
sage: V.exterior_power(2) # long time
Filtrations
  a: QQ^1 >= 0 >= 0
  b: QQ^1 >= QQ^1 >= 0

```


MORPHISMS

7.1 Space of morphisms of vector spaces (linear transformations)

AUTHOR:

- Rob Beezer: (2011-06-29)

A *VectorSpaceHomspace* object represents the set of all possible homomorphisms from one vector space to another. These mappings are usually known as linear transformations.

For more information on the use of linear transformations, consult the documentation for vector space morphisms at *sage.modules.vector_space_morphism*. Also, this is an extremely thin veneer on free module homspaces (*sage.modules.free_module_homspace*) and free module morphisms (*sage.modules.free_module_morphism*) - objects which might also be useful, and places where much of the documentation resides.

EXAMPLES:

Creation and basic examination is simple.

```
sage: V = QQ^3
sage: W = QQ^2
sage: H = Hom(V, W)
sage: H
Set of Morphisms (Linear Transformations) from
Vector space of dimension 3 over Rational Field to
Vector space of dimension 2 over Rational Field
sage: H.domain()
Vector space of dimension 3 over Rational Field
sage: H.codomain()
Vector space of dimension 2 over Rational Field
```

Homspaces have a few useful properties. A basis is provided by a list of matrix representations, where these matrix representatives are relative to the bases of the domain and codomain.

```
sage: K = Hom(GF(3)^2, GF(3)^2)
sage: B = K.basis()
sage: for f in B:
.....:     print(f)
.....:     print("\n")
Vector space morphism represented by the matrix:
[1 0]
[0 0]
Domain: Vector space of dimension 2 over Finite Field of size 3
```

(continues on next page)

(continued from previous page)

Codomain: Vector space of dimension 2 over Finite Field of size 3

Vector space morphism represented by the matrix:

$\begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix}$

Domain: Vector space of dimension 2 over Finite Field of size 3

Codomain: Vector space of dimension 2 over Finite Field of size 3

Vector space morphism represented by the matrix:

$\begin{bmatrix} 0 & 0 \\ 1 & 0 \end{bmatrix}$

Domain: Vector space of dimension 2 over Finite Field of size 3

Codomain: Vector space of dimension 2 over Finite Field of size 3

Vector space morphism represented by the matrix:

$\begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix}$

Domain: Vector space of dimension 2 over Finite Field of size 3

Codomain: Vector space of dimension 2 over Finite Field of size 3

The zero and identity mappings are properties of the space. The identity mapping will only be available if the domain and codomain allow for endomorphisms (equal vector spaces with equal bases).

```
sage: H = Hom(QQ^3, QQ^3)
sage: g = H.zero()
sage: g([1, 1/2, -3])
(0, 0, 0)
sage: f = H.identity()
sage: f([1, 1/2, -3])
(1, 1/2, -3)
```

The homspace may be used with various representations of a morphism in the space to create the morphism. We demonstrate three ways to create the same linear transformation between two two-dimensional subspaces of \mathbb{Q}^3 . The $V.n$ notation is a shortcut to the generators of each vector space, better known as the basis elements. Note that the matrix representations are relative to the bases, which are purposely fixed when the subspaces are created (“user bases”).

```
sage: U = QQ^3
sage: V = U.subspace_with_basis([U.0+U.1, U.1-U.2])
sage: W = U.subspace_with_basis([U.0, U.1+U.2])
sage: H = Hom(V, W)
```

First, with a matrix. Note that the matrix representation acts by matrix multiplication with the vector on the left. The input to the linear transformation, $(3, 1, 2)$, is converted to the coordinate vector $(3, -2)$, then matrix multiplication yields the vector $(-3, -2)$, which represents the vector $(-3, -2, -2)$ in the codomain.

```
sage: m = matrix(QQ, [[1, 2], [3, 4]])
sage: f1 = H(m)
sage: f1
Vector space morphism represented by the matrix:
[1 2]
[3 4]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
```

(continues on next page)

(continued from previous page)

```

User basis matrix:
[ 1  1  0]
[ 0  1 -1]
Codomain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 0 0]
[0 1 1]
sage: f1([3,1,2])
(-3, -2, -2)

```

Second, with a list of images of the domain's basis elements.

```

sage: img = [1*(U.0) + 2*(U.1+U.2), 3*U.0 + 4*(U.1+U.2)]
sage: f2 = H(img)
sage: f2
Vector space morphism represented by the matrix:
[1 2]
[3 4]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  1 -1]
Codomain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 0 0]
[0 1 1]
sage: f2([3,1,2])
(-3, -2, -2)

```

Third, with a linear function taking the domain to the codomain.

```

sage: g = lambda x: vector(QQ, [-2*x[0]+3*x[1], -2*x[0]+4*x[1], -2*x[0]+4*x[1]])
sage: f3 = H(g)
sage: f3
Vector space morphism represented by the matrix:
[1 2]
[3 4]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[ 1  1  0]
[ 0  1 -1]
Codomain: Vector space of degree 3 and dimension 2 over Rational Field
User basis matrix:
[1 0 0]
[0 1 1]
sage: f3([3,1,2])
(-3, -2, -2)

```

The three linear transformations look the same, and are the same.

```

sage: f1 == f2
True

```

(continues on next page)

(continued from previous page)

```
sage: f2 == f3
True
```

```
class sage.modules.vector_space_homspace.VectorSpaceHomspace(X, Y, category=None, check=True,
                                                                base=None)
```

Bases: `sage.modules.free_module_homspace.FreeModuleHomspace`

```
sage.modules.vector_space_homspace.is_VectorSpaceHomspace(x)
```

Return True if x is a vector space homspace.

INPUT:

x - anything

EXAMPLES:

To be a vector space morphism, the domain and codomain must both be vector spaces, in other words, modules over fields. If either set is just a module, then the Hom() constructor will build a space of free module morphisms.

```
sage: H = Hom(QQ^3, QQ^2)
sage: type(H)
<class 'sage.modules.vector_space_homspace.VectorSpaceHomspace_with_category'>
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace(H)
True

sage: K = Hom(QQ^3, ZZ^2)
sage: type(K)
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace(K)
False

sage: L = Hom(ZZ^3, QQ^2)
sage: type(L)
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace(L)
False

sage: sage.modules.vector_space_homspace.is_VectorSpaceHomspace('junk')
False
```

7.2 Morphisms of vector spaces (linear transformations)

AUTHOR:

- Rob Beezer: (2011-06-29)

A vector space morphism is a homomorphism between vector spaces, better known as a linear transformation. These are a specialization of Sage's free module homomorphisms. (A free module is like a vector space, but with scalars from a ring that may not be a field.) So references to free modules in the documentation or error messages should be understood as simply reflecting a more general situation.

7.2.1 Creation

The constructor `linear_transformation()` is designed to accept a variety of inputs that can define a linear transformation. See the documentation of the function for all the possibilities. Here we give two.

First a matrix representation. By default input matrices are understood to act on vectors placed to left of the matrix. Optionally, an input matrix can be described as acting on vectors placed to the right.

```
sage: A = matrix(QQ, [[-1, 2, 3], [4, 2, 0]])
sage: phi = linear_transformation(A)
sage: phi
Vector space morphism represented by the matrix:
[-1  2  3]
[ 4  2  0]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 3 over Rational Field
sage: phi([2, -3])
(-14, -2, 6)
```

A symbolic function can be used to specify the “rule” for a linear transformation, along with explicit descriptions of the domain and codomain.

```
sage: F = Integers(13)
sage: D = F^3
sage: C = F^2
sage: x, y, z = var('x y z')
sage: f(x, y, z) = [2*x + 3*y + 5*z, x + z]
sage: rho = linear_transformation(D, C, f)
sage: f(1, 2, 3)
(23, 4)
sage: rho([1, 2, 3])
(10, 4)
```

A “vector space homspace” is the set of all linear transformations between two vector spaces. Various input can be coerced into a homspace to create a linear transformation. See [sage.modules.vector_space_homspace](#) for more.

```
sage: D = QQ^4
sage: C = QQ^2
sage: hom_space = Hom(D, C)
sage: images = [[1, 3], [2, -1], [4, 0], [3, 7]]
sage: zeta = hom_space(images)
sage: zeta
Vector space morphism represented by the matrix:
[ 1  3]
[ 2 -1]
[ 4  0]
[ 3  7]
Domain: Vector space of dimension 4 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
```

A homomorphism may also be created via a method on the domain.

```
sage: F = QQ[sqrt(3)]
sage: a = F.gen(0)
```

(continues on next page)

(continued from previous page)

```

sage: D = F^2
sage: C = F^2
sage: A = matrix(F, [[a, 1], [2*a, 2]])
sage: psi = D.hom(A, C)
sage: psi
Vector space morphism represented by the matrix:
[  sqrt3      1]
[2*sqrt3      2]
Domain: Vector space of dimension 2 over Number Field in sqrt3 with defining polynomial_
↪ x^2 - 3 with sqrt3 = 1.732050807568878?
Codomain: Vector space of dimension 2 over Number Field in sqrt3 with defining_
↪ polynomial x^2 - 3 with sqrt3 = 1.732050807568878?
sage: psi([1, 4])
(9*sqrt3, 9)

```

7.2.2 Properties

Many natural properties of a linear transformation can be computed. Some of these are more general methods of objects in the classes `sage.modules.free_module_morphism.FreeModuleMorphism` and `sage.modules.matrix_morphism.MatrixMorphism`.

Values are computed in a natural way, an inverse image of an element can be computed with the `lift()` method, when the inverse image actually exists.

```

sage: A = matrix(QQ, [[1,2], [2,4], [3,6]])
sage: phi = linear_transformation(A)
sage: phi([1,2,0])
(5, 10)
sage: phi.lift([10, 20])
(10, 0, 0)
sage: phi.lift([100, 100])
Traceback (most recent call last):
...
ValueError: element is not in the image

```

Images and pre-images can be computed as vector spaces.

```

sage: A = matrix(QQ, [[1,2], [2,4], [3,6]])
sage: phi = linear_transformation(A)
sage: phi.image()
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]

sage: phi.inverse_image( (QQ^2).span([[1,2]]) )
Vector space of degree 3 and dimension 3 over Rational Field
Basis matrix:
[1 0 0]
[0 1 0]
[0 0 1]

```

(continues on next page)

(continued from previous page)

```
sage: phi.inverse_image( (QQ^2).span([[1,1]]) )
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[  1    0 -1/3]
[  0    1 -2/3]
```

Injectivity and surjectivity can be checked.

```
sage: A = matrix(QQ, [[1,2], [2,4], [3,6]])
sage: phi = linear_transformation(A)
sage: phi.is_injective()
False
sage: phi.is_surjective()
False
```

7.2.3 Restrictions and representations

It is possible to restrict the domain and codomain of a linear transformation to make a new linear transformation. We will use those commands to replace the domain and codomain by equal vector spaces, but with alternate bases. The point here is that the matrix representation used to represent linear transformations are relative to the bases of both the domain and codomain.

```
sage: A = graphs.PetersenGraph().adjacency_matrix()
sage: V = QQ^10
sage: phi = linear_transformation(V, V, A)
sage: phi
Vector space morphism represented by the matrix:
[0 1 0 0 1 1 0 0 0 0]
[1 0 1 0 0 0 1 0 0 0]
[0 1 0 1 0 0 0 1 0 0]
[0 0 1 0 1 0 0 0 1 0]
[1 0 0 1 0 0 0 0 0 1]
[1 0 0 0 0 0 0 1 1 0]
[0 1 0 0 0 0 0 0 1 1]
[0 0 1 0 0 1 0 0 0 1]
[0 0 0 1 0 1 1 0 0 0]
[0 0 0 0 1 0 1 1 0 0]
Domain: Vector space of dimension 10 over Rational Field
Codomain: Vector space of dimension 10 over Rational Field

sage: B1 = [V.gen(i) + V.gen(i+1) for i in range(9)] + [V.gen(9)]
sage: B2 = [V.gen(0)] + [-V.gen(i-1) + V.gen(i) for i in range(1,10)]
sage: D = V.subspace_with_basis(B1)
sage: C = V.subspace_with_basis(B2)
sage: rho = phi.restrict_codomain(C)
sage: zeta = rho.restrict_domain(D)
sage: zeta
Vector space morphism represented by the matrix:
[6 5 4 3 3 2 1 0 0 0]
[6 5 4 3 2 2 2 1 0 0]
[6 6 5 4 3 2 2 2 1 0]
```

(continues on next page)

(continued from previous page)

```

[6 5 5 4 3 2 2 2 2 1]
[6 4 4 4 3 3 3 3 2 1]
[6 5 4 4 4 4 4 4 3 1]
[6 6 5 4 4 4 3 3 3 2]
[6 6 6 5 4 4 2 1 1 1]
[6 6 6 6 5 4 3 1 0 0]
[3 3 3 3 3 2 2 1 0 0]
Domain: Vector space of degree 10 and dimension 10 over Rational Field
User basis matrix:
[1 1 0 0 0 0 0 0 0 0]
[0 1 1 0 0 0 0 0 0 0]
[0 0 1 1 0 0 0 0 0 0]
[0 0 0 1 1 0 0 0 0 0]
[0 0 0 0 1 1 0 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 0 1 1 0 0]
[0 0 0 0 0 0 0 1 1 0]
[0 0 0 0 0 0 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1]
Codomain: Vector space of degree 10 and dimension 10 over Rational Field
User basis matrix:
[ 1  0  0  0  0  0  0  0  0  0]
[-1  1  0  0  0  0  0  0  0  0]
[ 0 -1  1  0  0  0  0  0  0  0]
[ 0  0 -1  1  0  0  0  0  0  0]
[ 0  0  0 -1  1  0  0  0  0  0]
[ 0  0  0  0 -1  1  0  0  0  0]
[ 0  0  0  0  0 -1  1  0  0  0]
[ 0  0  0  0  0  0 -1  1  0  0]
[ 0  0  0  0  0  0  0 -1  1  0]
[ 0  0  0  0  0  0  0  0 -1  1]

```

An endomorphism is a linear transformation with an equal domain and codomain, and here each needs to have the same basis. We are using a matrix that has well-behaved eigenvalues, as part of showing that these do not change as the representation changes.

```

sage: A = graphs.PetersenGraph().adjacency_matrix()
sage: V = QQ^10
sage: phi = linear_transformation(V, V, A)
sage: phi.eigenvalues()
[3, -2, -2, -2, -2, 1, 1, 1, 1, 1]

sage: B1 = [V.gen(i) + V.gen(i+1) for i in range(9)] + [V.gen(9)]
sage: C = V.subspace_with_basis(B1)
sage: zeta = phi.restrict(C)
sage: zeta
Vector space morphism represented by the matrix:
[ 1  0  1 -1  2 -1  2 -2  2 -2]
[ 1  0  1  0  0  0  1  0  0  0]
[ 0  1  0  1  0  0  0  1  0  0]
[ 1 -1  2 -1  2 -2  2 -2  3 -2]
[ 2 -2  2 -1  1 -1  1  0  1  0]

```

(continues on next page)

(continued from previous page)

```
[ 1  0  0  0  0  0  0  1  1  0]
[ 0  1  0  0  0  1 -1  1  0  2]
[ 0  0  1  0  0  2 -1  1 -1  2]
[ 0  0  0  1  0  1  1  0  0  0]
[ 0  0  0  0  1 -1  2 -1  1 -1]
```

Domain: Vector space of degree 10 and dimension 10 over Rational Field

User basis matrix:

```
[1 1 0 0 0 0 0 0 0 0]
[0 1 1 0 0 0 0 0 0 0]
[0 0 1 1 0 0 0 0 0 0]
[0 0 0 1 1 0 0 0 0 0]
[0 0 0 0 1 1 0 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 0 1 1 0 0]
[0 0 0 0 0 0 0 1 1 0]
[0 0 0 0 0 0 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1]
```

Codomain: Vector space of degree 10 and dimension 10 over Rational Field

User basis matrix:

```
[1 1 0 0 0 0 0 0 0 0]
[0 1 1 0 0 0 0 0 0 0]
[0 0 1 1 0 0 0 0 0 0]
[0 0 0 1 1 0 0 0 0 0]
[0 0 0 0 1 1 0 0 0 0]
[0 0 0 0 0 1 1 0 0 0]
[0 0 0 0 0 0 1 1 0 0]
[0 0 0 0 0 0 0 1 1 0]
[0 0 0 0 0 0 0 0 1 1]
[0 0 0 0 0 0 0 0 0 1]
```

sage: zeta.eigenvalues()

```
[3, -2, -2, -2, -2, 1, 1, 1, 1, 1]
```

7.2.4 Equality

Equality of linear transformations is a bit nuanced. The equality operator `==` tests if two linear transformations have equal matrix representations, while we determine if two linear transformations are the same function with the `.is_equal_function()` method. Notice in this example that the function never changes, just the representations.

sage: `f = lambda x: vector(QQ, [x[1], x[0]+x[1], x[0]])`

sage: `H = Hom(QQ^2, QQ^3)`

sage: `phi = H(f)`

sage: `rho = linear_transformation(QQ^2, QQ^3, matrix(QQ,2, 3, [[0,1,1], [1,1,0]]))`

sage: `phi == rho`

True

sage: `U = (QQ^2).subspace_with_basis([[1, 2], [-3, 1]])`

sage: `V = (QQ^3).subspace_with_basis([[0, 1, 0], [2, 3, 1], [-1, 1, 6]])`

sage: `K = Hom(U, V)`

(continues on next page)

(continued from previous page)

```
sage: zeta = K(f)
```

```
sage: zeta == phi
```

```
False
```

```
sage: zeta.is_equal_function(phi)
```

```
True
```

```
sage: zeta.is_equal_function(rho)
```

```
True
```

class `sage.modules.vector_space_morphism.VectorSpaceMorphism(homspace, A, side='left')`

Bases: `sage.modules.free_module_morphism.FreeModuleMorphism`

Create a linear transformation, a morphism between vector spaces.

INPUT:

- `homspace` - a homspace (of vector spaces) to serve as a parent for the linear transformation and a home for the domain and codomain of the morphism
- `A` - a matrix representing the linear transformation, which will act on vectors placed to the left of the matrix

EXAMPLES:

Nominally, we require a homspace to hold the domain and codomain and a matrix representation of the morphism (linear transformation).

```
sage: from sage.modules.vector_space_homspace import VectorSpaceHomspace
sage: from sage.modules.vector_space_morphism import VectorSpaceMorphism
sage: H = VectorSpaceHomspace(QQ^3, QQ^2)
sage: A = matrix(QQ, 3, 2, range(6))
sage: zeta = VectorSpaceMorphism(H, A)
sage: zeta
```

Vector space morphism represented by the matrix:

```
[0 1]
```

```
[2 3]
```

```
[4 5]
```

Domain: Vector space of dimension 3 over Rational Field

Codomain: Vector space of dimension 2 over Rational Field

See the constructor, `sage.modules.vector_space_morphism.linear_transformation()` for another way to create linear transformations.

The `.hom()` method of a vector space will create a vector space morphism.

```
sage: V = QQ^3; W = V.subspace_with_basis([[1,2,3], [-1,2,5/3], [0,1,-1]])
sage: phi = V.hom(matrix(QQ, 3, range(9)), codomain=W) # indirect doctest
sage: type(phi)
<class 'sage.modules.vector_space_morphism.VectorSpaceMorphism'>
```

A matrix may be coerced into a vector space homspace to create a vector space morphism.

```
sage: from sage.modules.vector_space_homspace import VectorSpaceHomspace
sage: H = VectorSpaceHomspace(QQ^3, QQ^2)
sage: A = matrix(QQ, 3, 2, range(6))
sage: rho = H(A) # indirect doctest
```

(continues on next page)

(continued from previous page)

```
sage: type(rho)
<class 'sage.modules.vector_space_morphism.VectorSpaceMorphism'>
```

is_invertible()

Determines if the vector space morphism has an inverse.

OUTPUT:

True if the vector space morphism is invertible, otherwise False.

EXAMPLES:

If the dimension of the domain does not match the dimension of the codomain, then the morphism cannot be invertible.

```
sage: V = QQ^3
sage: U = V.subspace_with_basis([V.0 + V.1, 2*V.1 + 3*V.2])
sage: phi = V.hom([U.0, U.0 + U.1, U.0 - U.1], U)
sage: phi.is_invertible()
False
```

An invertible linear transformation.

```
sage: A = matrix(QQ, 3, [[-3, 5, -5], [4, -7, 7], [6, -8, 10]])
sage: A.determinant()
2
sage: H = Hom(QQ^3, QQ^3)
sage: rho = H(A)
sage: rho.is_invertible()
True
```

A non-invertible linear transformation, an endomorphism of a vector space over a finite field.

```
sage: F.<a> = GF(11^2)
sage: A = matrix(F, [[6*a + 3, 8*a + 2, 10*a + 3],
.....:               [2*a + 7, 4*a + 3, 2*a + 3],
.....:               [9*a + 2, 10*a + 10, 3*a + 3]])
sage: A.nullity()
1
sage: E = End(F^3)
sage: zeta = E(A)
sage: zeta.is_invertible()
False
```

sage.modules.vector_space_morphism.is_VectorSpaceMorphism(x)

Returns True if x is a vector space morphism (a linear transformation).

INPUT:

x - anything

OUTPUT:

True only if x is an instance of a vector space morphism, which are also known as linear transformations.

EXAMPLES:

```

sage: V = QQ^2; f = V.hom([V.1, -2*V.0])
sage: sage.modules.vector_space_morphism.is_VectorSpaceMorphism(f)
True
sage: sage.modules.vector_space_morphism.is_VectorSpaceMorphism('junk')
False

```

`sage.modules.vector_space_morphism.linear_transformation(arg0, arg1=None, arg2=None, side='left')`

Create a linear transformation from a variety of possible inputs.

FORMATS:

In the following, *D* and *C* are vector spaces over the same field that are the domain and codomain (respectively) of the linear transformation.

side is a keyword that is either 'left' or 'right'. When a matrix is used to specify a linear transformation, as in the first two call formats below, you may specify if the function is given by matrix multiplication with the vector on the left, or the vector on the right. The default is 'left'. The matrix representation may be obtained as either version, no matter how it is created.

- `linear_transformation(A, side='left')`

Where *A* is a matrix. The domain and codomain are inferred from the dimension of the matrix and the base ring of the matrix. The base ring must be a field, or have its fraction field implemented in Sage.

- `linear_transformation(D, C, A, side='left')`

A is a matrix that behaves as above. However, now the domain and codomain are given explicitly. The matrix is checked for compatibility with the domain and codomain. Additionally, the domain and codomain may be supplied with alternate ("user") bases and the matrix is interpreted as being a representation relative to those bases.

- `linear_transformation(D, C, f)`

f is any function that can be applied to the basis elements of the domain and that produces elements of the codomain. The linear transformation returned is the unique linear transformation that extends this mapping on the basis elements. *f* may come from a function defined by a Python `def` statement, or may be defined as a `lambda` function.

Alternatively, *f* may be specified by a callable symbolic function, see the examples below for a demonstration.

- `linear_transformation(D, C, images)`

images is a list, or tuple, of codomain elements, equal in number to the size of the basis of the domain. Each basis element of the domain is mapped to the corresponding element of the *images* list, and the linear transformation returned is the unique linear transformation that extends this mapping.

OUTPUT:

A linear transformation described by the input. This is a "vector space morphism", an object of the class `sage.modules.vector_space_morphism`.

EXAMPLES:

We can define a linear transformation with just a matrix, understood to act on a vector placed on one side or the other. The field for the vector spaces used as domain and codomain is obtained from the base ring of the matrix, possibly promoting to a fraction field.

```

sage: A = matrix(ZZ, [[1, -1, 4], [2, 0, 5]])
sage: phi = linear_transformation(A)
sage: phi
Vector space morphism represented by the matrix:
[ 1 -1  4]
[ 2  0  5]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 3 over Rational Field
sage: phi([1/2, 5])
(21/2, -1/2, 27)

sage: B = matrix(Integers(7), [[1, 2, 1], [3, 5, 6]])
sage: rho = linear_transformation(B, side='right')
sage: rho
Vector space morphism represented by the matrix:
[1 3]
[2 5]
[1 6]
Domain: Vector space of dimension 3 over Ring of integers modulo 7
Codomain: Vector space of dimension 2 over Ring of integers modulo 7
sage: rho([2, 4, 6])
(2, 6)

```

We can define a linear transformation with a matrix, while explicitly giving the domain and codomain. Matrix entries will be coerced into the common field of scalars for the vector spaces.

```

sage: D = QQ^3
sage: C = QQ^2
sage: A = matrix([[1, 7], [2, -1], [0, 5]])
sage: A.parent()
Full MatrixSpace of 3 by 2 dense matrices over Integer Ring
sage: zeta = linear_transformation(D, C, A)
sage: zeta.matrix().parent()
Full MatrixSpace of 3 by 2 dense matrices over Rational Field
sage: zeta
Vector space morphism represented by the matrix:
[ 1  7]
[ 2 -1]
[ 0  5]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

```

Matrix representations are relative to the bases for the domain and codomain.

```

sage: u = vector(QQ, [1, -1])
sage: v = vector(QQ, [2, 3])
sage: D = (QQ^2).subspace_with_basis([u, v])
sage: x = vector(QQ, [2, 1])
sage: y = vector(QQ, [-1, 4])
sage: C = (QQ^2).subspace_with_basis([x, y])
sage: A = matrix(QQ, [[2, 5], [3, 7]])
sage: psi = linear_transformation(D, C, A)
sage: psi

```

(continues on next page)

(continued from previous page)

```

Vector space morphism represented by the matrix:
[2 5]
[3 7]
Domain: Vector space of degree 2 and dimension 2 over Rational Field
User basis matrix:
[ 1 -1]
[ 2  3]
Codomain: Vector space of degree 2 and dimension 2 over Rational Field
User basis matrix:
[ 2  1]
[-1  4]
sage: psi(u) == 2*x + 5*y
True
sage: psi(v) == 3*x + 7*y
True

```

Functions that act on the domain may be used to compute images of the domain's basis elements, and this mapping can be extended to a unique linear transformation. The function may be a Python function (via `def` or `lambda`) or a Sage symbolic function.

```

sage: def g(x):
.....:     return vector(QQ, [2*x[0]+x[2], 5*x[1]])
sage: phi = linear_transformation(QQ^3, QQ^2, g)
sage: phi
Vector space morphism represented by the matrix:
[2 0]
[0 5]
[1 0]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

sage: f = lambda x: vector(QQ, [2*x[0]+x[2], 5*x[1]])
sage: rho = linear_transformation(QQ^3, QQ^2, f)
sage: rho
Vector space morphism represented by the matrix:
[2 0]
[0 5]
[1 0]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

sage: x, y, z = var('x y z')
sage: h(x, y, z) = [2*x + z, 5*y]
sage: zeta = linear_transformation(QQ^3, QQ^2, h)
sage: zeta
Vector space morphism represented by the matrix:
[2 0]
[0 5]
[1 0]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

```

(continues on next page)

(continued from previous page)

```
sage: phi == rho
True
sage: rho == zeta
True
```

We create a linear transformation relative to non-standard bases, and capture its representation relative to standard bases. With this, we can build functions that create the same linear transformation relative to the nonstandard bases.

```
sage: u = vector(QQ, [1, -1])
sage: v = vector(QQ, [2, 3])
sage: D = (QQ^2).subspace_with_basis([u, v])
sage: x = vector(QQ, [2, 1])
sage: y = vector(QQ, [-1, 4])
sage: C = (QQ^2).subspace_with_basis([x, y])
sage: A = matrix(QQ, [[2, 5], [3, 7]])
sage: psi = linear_transformation(D, C, A)
sage: rho = psi.restrict_codomain(QQ^2).restrict_domain(QQ^2)
sage: rho.matrix()
[ -4/5  97/5]
[  1/5 -13/5]

sage: f = lambda x: vector(QQ, [(-4/5)*x[0] + (1/5)*x[1], (97/5)*x[0] + (-13/
↪ 5)*x[1]])
sage: psi = linear_transformation(D, C, f)
sage: psi.matrix()
[2 5]
[3 7]

sage: s, t = var('s t')
sage: h(s, t) = [(-4/5)*s + (1/5)*t, (97/5)*s + (-13/5)*t]
sage: zeta = linear_transformation(D, C, h)
sage: zeta.matrix()
[2 5]
[3 7]
```

Finally, we can give an explicit list of images for the basis elements of the domain.

```
sage: x = polygen(QQ)
sage: F.<a> = NumberField(x^3+x+1)
sage: u = vector(F, [1, a, a^2])
sage: v = vector(F, [a, a^2, 2])
sage: w = u + v
sage: D = F^3
sage: C = F^3
sage: rho = linear_transformation(D, C, [u, v, w])
sage: rho.matrix()
[ 1      a      a^2]
[  a     a^2      2]
[ a + 1 a^2 + a a^2 + 2]
sage: C = (F^3).subspace_with_basis([u, v])
sage: D = (F^3).subspace_with_basis([u, v])
```

(continues on next page)

(continued from previous page)

```
sage: psi = linear_transformation(C, D, [u+v, u-v])
sage: psi.matrix()
[ 1  1]
[ 1 -1]
```

7.3 Homspaces between free modules

EXAMPLES:

We create $\text{End}(\mathbb{Z}^2)$ and compute a basis.

```
sage: M = FreeModule(IntegerRing(),2)
sage: E = End(M)
sage: B = E.basis()
sage: len(B)
4
sage: B[0]
Free module morphism defined by the matrix
[1 0]
[0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
```

We create $\text{Hom}(\mathbb{Z}^3, \mathbb{Z}^2)$ and compute a basis.

```
sage: V3 = FreeModule(IntegerRing(),3)
sage: V2 = FreeModule(IntegerRing(),2)
sage: H = Hom(V3,V2)
sage: H
Set of Morphisms from Ambient free module of rank 3 over
the principal ideal domain Integer Ring
to Ambient free module of rank 2
over the principal ideal domain Integer Ring
in Category of finite dimensional modules with basis over
(euclidean domains and infinite enumerated sets and metric spaces)
sage: B = H.basis()
sage: len(B)
6
sage: B[0]
Free module morphism defined by the matrix
[1 0]
[0 0]
[0 0]...
```

```
class sage.modules.free_module_homspace.FreeModuleHomspace(X, Y, category=None, check=True,
                                                            base=None)
```

Bases: `sage.categories.homset.HomsetWithBase`

basis(*side='left'*)

Return a basis for this space of free module homomorphisms.

INPUT:

- side – side of the vectors acted on by the matrix (default: left)

OUTPUT:

- tuple

EXAMPLES:

```
sage: H = Hom(ZZ^2, ZZ^1)
sage: H.basis()
(Free module morphism defined by the matrix
[1]
[0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 1 over the principal ideal domain ...,
Free module morphism defined by the matrix
[0]
[1]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 1 over the principal ideal domain ...)
sage: H.basis("right")
(Free module morphism defined as left-multiplication by the matrix
[1 0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 1 over the principal ideal domain ...,
Free module morphism defined as left-multiplication by the matrix
[0 1]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 1 over the principal ideal domain ...)
```

identity(side='left')

Return identity morphism in an endomorphism ring.

INPUT:

- side – side of the vectors acted on by the matrix (default: left)

EXAMPLES:

```
sage: V = FreeModule(ZZ, 5)
sage: H = V.Hom(V)
sage: H.identity()
Free module morphism defined by the matrix
[1 0 0 0 0]
[0 1 0 0 0]
[0 0 1 0 0]
[0 0 0 1 0]
[0 0 0 0 1]
Domain: Ambient free module of rank 5 over the principal ideal domain ...
Codomain: Ambient free module of rank 5 over the principal ideal domain ...
```

zero(side='left')

INPUT:

- side – side of the vectors acted on by the matrix (default: left)

EXAMPLES:

```

sage: E = ZZ^2
sage: F = ZZ^3
sage: H = Hom(E, F)
sage: f = H.zero()
sage: f
Free module morphism defined by the matrix
[0 0 0]
[0 0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain Integer_
↳Ring
Codomain: Ambient free module of rank 3 over the principal ideal domain Integer_
↳Ring
sage: f(E.an_element())
(0, 0, 0)
sage: f(E.an_element()) == F.zero()
True
sage: H.zero("right")
Free module morphism defined as left-multiplication by the matrix
[0 0]
[0 0]
[0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain Integer_
↳Ring
Codomain: Ambient free module of rank 3 over the principal ideal domain Integer_
↳Ring

```

`sage.modules.free_module_homspace.is_FreeModuleHomspace(x)`

Return True if x is a free module homspace.

Notice that every vector space is a free module, but when we construct a set of morphisms between two vector spaces, it is a `VectorSpaceHomspace`, which qualifies as a `FreeModuleHomspace`, since the former is special case of the latter.

EXAMPLES:

```

sage: H = Hom(ZZ^3, ZZ^2)
sage: type(H)
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(H)
True

sage: K = Hom(QQ^3, ZZ^2)
sage: type(K)
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(K)
True

sage: L = Hom(ZZ^3, QQ^2)
sage: type(L)
<class 'sage.modules.free_module_homspace.FreeModuleHomspace_with_category'>
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(L)
True

sage: P = Hom(QQ^3, QQ^2)

```

(continues on next page)

(continued from previous page)

```

sage: type(P)
<class 'sage.modules.vector_space_homspace.VectorSpaceHomspace_with_category'>
sage: sage.modules.free_module_homspace.is_FreeModuleHomspace(P)
True

sage: sage.modules.free_module_homspace.is_FreeModuleHomspace('junk')
False

```

7.4 Morphisms of free modules

AUTHORS:

- William Stein: initial version
- Miguel Marco (2010-06-19): added eigenvalues, eigenvectors and minpoly functions

class sage.modules.free_module_morphism.BaseIsomorphism1D

Bases: [sage.categories.morphism.Morphism](#)

An isomorphism between a ring and a free rank-1 module over the ring.

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: V, from_V, to_V = R.free_module(R)
sage: from_V
Isomorphism morphism:
  From: Ambient free module of rank 1 over the integral domain Multivariate_
  ↪ Polynomial Ring in x, y over Rational Field
  To:   Multivariate Polynomial Ring in x, y over Rational Field

```

is_injective()

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: V, from_V, to_V = R.free_module(R)
sage: from_V.is_injective()
True

```

is_surjective()

EXAMPLES:

```

sage: R.<x,y> = QQ[]
sage: V, from_V, to_V = R.free_module(R)
sage: from_V.is_surjective()
True

```

class sage.modules.free_module_morphism.BaseIsomorphism1D_from_FM(*parent, basis=None*)

Bases: [sage.modules.free_module_morphism.BaseIsomorphism1D](#)

An isomorphism to a ring from its 1-dimensional free module

INPUT:

- *parent* – the homset

- `basis` – (default 1) an invertible element of the ring

EXAMPLES:

```
sage: R.<x> = QQ[[[]]]
sage: V, from_V, to_V = R.free_module(R)
sage: v = to_V(1+x); v
(1 + x)
sage: from_V(v)
1 + x
sage: W, from_W, to_W = R.free_module(R, basis=(1-x))
sage: W is V
True
sage: w = to_W(1+x); w
(1 - x^2)
sage: from_W(w)
1 + x + O(x^20)
```

The basis vector has to be a unit so that the map is an isomorphism:

```
sage: W, from_W, to_W = R.free_module(R, basis=x)
Traceback (most recent call last):
...
ValueError: Basis element must be a unit
```

class `sage.modules.free_module_morphism.BaseIsomorphism1D_to_FM`(*parent, basis=None*)
 Bases: `sage.modules.free_module_morphism.BaseIsomorphism1D`

An isomorphism from a ring to its 1-dimensional free module

INPUT:

- `parent` – the homset
- `basis` – (default 1) an invertible element of the ring

EXAMPLES:

```
sage: R = Zmod(8)
sage: V, from_V, to_V = R.free_module(R)
sage: v = to_V(2); v
(2)
sage: from_V(v)
2
sage: W, from_W, to_W = R.free_module(R, basis=3)
sage: W is V
True
sage: w = to_W(2); w
(6)
sage: from_W(w)
2
```

The basis vector has to be a unit so that the map is an isomorphism:

```
sage: W, from_W, to_W = R.free_module(R, basis=4)
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: Basis element must be a unit
```

class `sage.modules.free_module_morphism.FreeModuleMorphism`(*parent*, *A*, *side*='left')
 Bases: `sage.modules.matrix_morphism.MatrixMorphism`

INPUT:

- *parent* - a homspace in a (sub) category of free modules
- *A* - matrix
- *side* – side of the vectors acted on by the matrix (default: "left")

EXAMPLES:

```
sage: V = ZZ^3; W = span([[1,2,3],[-1,2,8]], ZZ)
sage: phi = V.hom(matrix(ZZ,3,[1..9]))
sage: type(phi)
<class 'sage.modules.free_module_morphism.FreeModuleMorphism'>
```

change_ring(*R*)

Change the ring over which this morphism is defined. This changes the ring of the domain, codomain, and underlying matrix.

EXAMPLES:

```
sage: V0 = span([[0,0,1],[0,2,0]],ZZ); V1 = span([[1/2,0],[0,2]],ZZ); W =
↳ span([[1,0],[0,6]],ZZ)
sage: h = V0.hom([-3*V1.0-3*V1.1, -3*V1.0-3*V1.1])
sage: h.base_ring()
Integer Ring
sage: h
Free module morphism defined by the matrix
[-3 -3]
[-3 -3]...
sage: h.change_ring(QQ).base_ring()
Rational Field
sage: f = h.change_ring(QQ); f
Vector space morphism represented by the matrix:
[-3 -3]
[-3 -3]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[0 1 0]
[0 0 1]
Codomain: Vector space of degree 2 and dimension 2 over Rational Field
Basis matrix:
[1 0]
[0 1]
sage: f = h.change_ring(GF(7)); f
Vector space morphism represented by the matrix:
[4 4]
[4 4]
Domain: Vector space of degree 3 and dimension 2 over Finite Field of size 7
```

(continues on next page)

(continued from previous page)

```

Basis matrix:
[0 1 0]
[0 0 1]
Codomain: Vector space of degree 2 and dimension 2 over Finite Field of size 7
Basis matrix:
[1 0]
[0 1]

```

eigenspaces(*extend=True*)

Compute a list of subspaces formed by eigenvectors of *self*.

INPUT:

- *extend* – (default: *True*) determines if field extensions should be considered

OUTPUT:

- a list of pairs (*eigenvalue*, *eigenspace*)

EXAMPLES:

```

sage: V = QQ^3
sage: h = V.hom([[1,0,0],[0,0,1],[0,-1,0]], V)
sage: h.eigenspaces()
[(1,
  Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [1 0 0]),
 (-1*I,
  Vector space of degree 3 and dimension 1 over Algebraic Field
  Basis matrix:
  [ 0  1 1*I]),
 (1*I,
  Vector space of degree 3 and dimension 1 over Algebraic Field
  Basis matrix:
  [ 0  1 -1*I])]

sage: h.eigenspaces(extend=False)
[(1,
  Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [1 0 0])]

sage: h = V.hom([[2,1,0], [0,2,0], [0,0,-1]], V)
sage: h.eigenspaces()
[(-1, Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [0 0 1]),
 (2, Vector space of degree 3 and dimension 1 over Rational Field
  Basis matrix:
  [0 1 0])]

sage: h = V.hom([[2,1,0], [0,2,0], [0,0,2]], V)
sage: h.eigenspaces()
[(2, Vector space of degree 3 and dimension 2 over Rational Field

```

(continues on next page)

(continued from previous page)

```
Basis matrix:
[0 1 0]
[0 0 1]]]
```

```
sage: V = QQ^2; m = matrix(2, [1, 1, 0, 1])
sage: V.hom(m, side="right").eigenspaces()
[(1,
  Vector space of degree 2 and dimension 1 over Rational Field
  Basis matrix:
  [1 0]])]
sage: V.hom(m).eigenspaces()
[(1,
  Vector space of degree 2 and dimension 1 over Rational Field
  Basis matrix:
  [0 1]])]
```

eigenvalues(*extend=True*)

Returns a list with the eigenvalues of the endomorphism of vector spaces.

INPUT:

- **extend** – boolean (default: True) decides if base field extensions should be considered or not.

EXAMPLES:

We compute the eigenvalues of an endomorphism of \mathbb{Q}^3 :

```
sage: V=QQ^3
sage: H=V.endomorphism_ring()([[1,-1,0],[-1,1,1],[0,3,1]])
sage: H.eigenvalues()
[3, 1, -1]
```

Note the effect of the **extend** option:

```
sage: V=QQ^2
sage: H=V.endomorphism_ring()([[0,-1],[1,0]])
sage: H.eigenvalues()
[-1*I, 1*I]
sage: H.eigenvalues(extend=False)
[]
```

eigenvectors(*extend=True*)

Computes the subspace of eigenvectors of a given eigenvalue.

INPUT:

- **extend** – boolean (default: True) decides if base field extensions should be considered or not.

OUTPUT:

A sequence of tuples. Each tuple contains an eigenvalue, a sequence with a basis of the corresponding subspace of eigenvectors, and the algebraic multiplicity of the eigenvalue.

EXAMPLES:

```
sage: V=(QQ^4).subspace([[0,2,1,4],[1,2,5,0],[1,1,1,1]])
sage: H=(V.Hom(V))(matrix(QQ, [[0,1,0],[-1,0,0],[0,0,3]]))
```

(continues on next page)

(continued from previous page)

```

sage: H.eigenvectors()
[(3, [
(0, 0, 1, -6/7)
], 1), (-1*I, [
(1, 1*I, 0, -0.571428571428572? + 2.428571428571429?*I)
], 1), (1*I, [
(1, -1*I, 0, -0.571428571428572? - 2.428571428571429?*I)
], 1)]
sage: H.eigenvectors(extend=False)
[(3, [
(0, 0, 1, -6/7)
], 1)]
sage: H1=(V.Hom(V))(matrix(QQ, [[2,1,0],[0,2,0],[0,0,3]]))
sage: H1.eigenvectors()
[(3, [
(0, 0, 1, -6/7)
], 1), (2, [
(0, 1, 0, 17/7)
], 2)]
sage: H1.eigenvectors(extend=False)
[(3, [
(0, 0, 1, -6/7)
], 1), (2, [
(0, 1, 0, 17/7)
], 2)]

```

```

sage: V = QQ^2
sage: m = matrix(2, [1, 1, 0, 1])
sage: V.hom(m, side="right").eigenvectors()
[(1,
[
(1, 0)
],
2)]
sage: V.hom(m).eigenvectors()
[(1,
[
(0, 1)
],
2)]

```

inverse_image(V)

Given a submodule V of the codomain of self, return the inverse image of V under self, i.e., the biggest submodule of the domain of self that maps into V .

EXAMPLES:

We test computing inverse images over a field:

```

sage: V = QQ^3; W = span([[1,2,3],[-1,2,5/3]], QQ)
sage: phi = V.hom(matrix(QQ,3,[1..9]))
sage: phi.rank()
2

```

(continues on next page)

(continued from previous page)

```

sage: I = phi.inverse_image(W); I
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0  0]
[ 0  1 -1/2]
sage: phi(I.0) in W
True
sage: phi(I.1) in W
True
sage: W = phi.image()
sage: phi.inverse_image(W) == V
True

```

We test computing inverse images between two spaces embedded in different ambient spaces.:

```

sage: V0 = span([[0,0,1],[0,2,0]],ZZ); V1 = span([[1/2,0],[0,2]],ZZ); W = span
↳span([[1,0],[0,6]],ZZ)
sage: h = V0.hom([-3*V1.0-3*V1.1, -3*V1.0-3*V1.1])
sage: h.inverse_image(W)
Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[0 2 1]
[0 0 2]
sage: h(h.inverse_image(W)).is_submodule(W)
True
sage: h(h.inverse_image(W)).index_in(W)
+Infinity
sage: h(h.inverse_image(W))
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[ 3 12]

```

We test computing inverse images over the integers:

```

sage: V = QQ^3; W = V.span_of_basis([[2,2,3],[-1,2,5/3]], ZZ)
sage: phi = W.hom([W.0, W.0-W.1])
sage: Z = W.span([2*W.1]); Z
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 2 -4 -10/3]
sage: Y = phi.inverse_image(Z); Y
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 6 0 8/3]
sage: phi(Y) == Z
True

```

We test that [trac ticket #24590](#) is resolved:

```

sage: A = FreeQuadraticModule(ZZ,1,matrix([2]))
sage: f = A.Hom(A).an_element()
sage: f.inverse_image(A)
Free module of degree 1 and rank 1 over Integer Ring

```

(continues on next page)

(continued from previous page)

```
Echelon basis matrix:
[1]
```

We test that it respects the side:

```
sage: V = ZZ^2
sage: m = matrix(2, [1, 1, 0, 1])
sage: h = V.hom(m, side="right")
sage: h
Free module morphism defined as left-multiplication by the matrix
[1 1]
[0 1]...
sage: SV = V.span([V.0])
sage: h.inverse_image(SV)
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[1 0]
sage: V.hom(m).inverse_image(SV)
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[ 1 -1]
```

lift(x)

Given an element of the image, return an element of the codomain that maps onto it.

Note that `lift` and `preimage_representative` are equivalent names for this method, with the latter suggesting that the return value is a coset representative of the domain modulo the kernel of the morphism.

EXAMPLES:

```
sage: X = QQ**2
sage: V = X.span([[2, 0], [0, 8]], ZZ)
sage: W = (QQ**1).span([[1/12]], ZZ)
sage: f = V.hom([W([1/3]), W([1/2])], W)
sage: l=f.lift([1/3]); l # random
(8, -16)
sage: f(l)
(1/3)
sage: f(f.lift([1/2]))
(1/2)
sage: f(f.lift([1/6]))
(1/6)
sage: f.lift([1/12])
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: f.lift([1/24])
Traceback (most recent call last):
...
TypeError: element [1/24] is not in free module
```

This works for vector spaces, too:

```

sage: V = VectorSpace(GF(3), 2)
sage: W = VectorSpace(GF(3), 3)
sage: f = V.hom([W.1, W.1 - W.0])
sage: f.lift(W.1)
(1, 0)
sage: f.lift(W.2)
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: w = W((17, -2, 0))
sage: f(f.lift(w)) == w
True

```

This example illustrates the use of the `preimage_representative` as an equivalent name for this method.

```

sage: V = ZZ^3
sage: W = ZZ^2
sage: w = vector(ZZ, [1,2])
sage: f = V.hom([w, w, w], W)
sage: f.preimage_representative(vector(ZZ, [10, 20]))
(0, 0, 10)

```

```

sage: V = QQ^2; m = matrix(2, [1, 1, 0, 1])
sage: V.hom(m, side="right").lift(V.0+V.1)
(0, 1)
sage: V.hom(m).lift(V.0+V.1)
(1, 0)

```

`minimal_polynomial(var='x')`

Computes the minimal polynomial.

`minpoly()` and `minimal_polynomial()` are the same method.

INPUT:

- `var` - string (default: 'x') a variable name

OUTPUT:

polynomial in `var` - the minimal polynomial of the endomorphism.

EXAMPLES:

Compute the minimal polynomial, and check it.

```

sage: V=GF(7)^3
sage: H=V.Hom(V)([[0,1,2],[-1,0,3],[2,4,1]])
sage: H
Vector space morphism represented by the matrix:
[0 1 2]
[6 0 3]
[2 4 1]
Domain: Vector space of dimension 3 over Finite Field of size 7
Codomain: Vector space of dimension 3 over Finite Field of size 7

sage: H.minpoly()

```

(continues on next page)

(continued from previous page)

$$x^3 + 6x^2 + 6x + 1$$

sage: `H.minimal_polynomial()`

$$x^3 + 6x^2 + 6x + 1$$

sage: `H^3 + (H^2)*6 + H*6 + 1`

Vector space morphism represented by the matrix:

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Domain: Vector space of dimension 3 over Finite Field of size 7

Codomain: Vector space of dimension 3 over Finite Field of size 7

minpoly(*var*='x')

Computes the minimal polynomial.

`minpoly()` and `minimal_polynomial()` are the same method.

INPUT:

- **var** - string (default: 'x') a variable name

OUTPUT:

polynomial in *var* - the minimal polynomial of the endomorphism.

EXAMPLES:

Compute the minimal polynomial, and check it.

sage: `V=GF(7)^3`

sage: `H=V.Hom(V)([[0,1,2],[-1,0,3],[2,4,1]])`

sage: `H`

Vector space morphism represented by the matrix:

$$\begin{bmatrix} 0 & 1 & 2 \\ 6 & 0 & 3 \\ 2 & 4 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 1 & 2 \\ 6 & 0 & 3 \\ 2 & 4 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 1 & 2 \\ 6 & 0 & 3 \\ 2 & 4 & 1 \end{bmatrix}$$

Domain: Vector space of dimension 3 over Finite Field of size 7

Codomain: Vector space of dimension 3 over Finite Field of size 7

sage: `H.minpoly()`

$$x^3 + 6x^2 + 6x + 1$$

sage: `H.minimal_polynomial()`

$$x^3 + 6x^2 + 6x + 1$$

sage: `H^3 + (H^2)*6 + H*6 + 1`

Vector space morphism represented by the matrix:

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Domain: Vector space of dimension 3 over Finite Field of size 7

Codomain: Vector space of dimension 3 over Finite Field of size 7

preimage_representative(*x*)

Given an element of the image, return an element of the codomain that maps onto it.

Note that `lift` and `preimage_representative` are equivalent names for this method, with the latter suggesting that the return value is a coset representative of the domain modulo the kernel of the morphism.

EXAMPLES:

```
sage: X = QQ**2
sage: V = X.span([[2, 0], [0, 8]], ZZ)
sage: W = (QQ**1).span([[1/12]], ZZ)
sage: f = V.hom([W([1/3]), W([1/2])], W)
sage: l=f.lift([1/3]); l # random
(8, -16)
sage: f(l)
(1/3)
sage: f(f.lift([1/2]))
(1/2)
sage: f(f.lift([1/6]))
(1/6)
sage: f.lift([1/12])
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: f.lift([1/24])
Traceback (most recent call last):
...
TypeError: element [1/24] is not in free module
```

This works for vector spaces, too:

```
sage: V = VectorSpace(GF(3), 2)
sage: W = VectorSpace(GF(3), 3)
sage: f = V.hom([W.1, W.1 - W.0])
sage: f.lift(W.1)
(1, 0)
sage: f.lift(W.2)
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: w = W((17, -2, 0))
sage: f(f.lift(w)) == w
True
```

This example illustrates the use of the `preimage_representative` as an equivalent name for this method.

```
sage: V = ZZ^3
sage: W = ZZ^2
sage: w = vector(ZZ, [1,2])
sage: f = V.hom([w, w, w], W)
sage: f.preimage_representative(vector(ZZ, [10, 20]))
(0, 0, 10)
```

```
sage: V = QQ^2; m = matrix(2, [1, 1, 0, 1])
sage: V.hom(m, side="right").lift(V.0+V.1)
(0, 1)
sage: V.hom(m).lift(V.0+V.1)
```

(continues on next page)

(continued from previous page)

`(1, 0)`**pushforward(x)**

Compute the image of a sub-module of the domain.

EXAMPLES:

```

sage: V = QQ^3; W = span([[1,2,3],[-1,2,5/3]], QQ)
sage: phi = V.hom(matrix(QQ,3,[1..9]))
sage: phi.rank()
2
sage: phi(V) #indirect doctest
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]

```

We compute the image of a submodule of a ZZ-module embedded in a rational vector space:

```

sage: V = QQ^3; W = V.span_of_basis([[2,2,3],[-1,2,5/3]], ZZ)
sage: phi = W.hom([W.0, W.0-W.1]); phi
Free module morphism defined by the matrix
[ 1  0]
[ 1 -1]...
sage: phi(span([2*W.1],ZZ))
Free module of degree 3 and rank 1 over Integer Ring
Echelon basis matrix:
[ 6  0 8/3]
sage: phi(2*W.1)
(6, 0, 8/3)

```

`sage.modules.free_module_morphism.is_FreeModuleMorphism(x)`

EXAMPLES:

```

sage: V = ZZ^2; f = V.hom([V.1,-2*V.0])
sage: sage.modules.free_module_morphism.is_FreeModuleMorphism(f)
True
sage: sage.modules.free_module_morphism.is_FreeModuleMorphism(0)
False

```

7.5 Morphisms defined by a matrix

A matrix morphism is a morphism that is defined by multiplication by a matrix. Elements of domain must either have a method `vector()` that returns a vector that the defining matrix can hit from the left, or be coercible into vector space of appropriate dimension.

EXAMPLES:

```

sage: from sage.modules.matrix_morphism import MatrixMorphism, is_MatrixMorphism
sage: V = QQ^3
sage: T = End(V)
sage: M = MatrixSpace(QQ,3)

```

(continues on next page)

(continued from previous page)

```

sage: I = M.identity_matrix()
sage: m = MatrixMorphism(T, I); m
Morphism defined by the matrix
[1 0 0]
[0 1 0]
[0 0 1]
sage: is_MatrixMorphism(m)
True
sage: m.charpoly('x')
x^3 - 3*x^2 + 3*x - 1
sage: m.base_ring()
Rational Field
sage: m.det()
1
sage: m.fcp('x')
(x - 1)^3
sage: m.matrix()
[1 0 0]
[0 1 0]
[0 0 1]
sage: m.rank()
3
sage: m.trace()
3

```

AUTHOR:

- William Stein: initial versions
- David Joyner (2005-12-17): added examples
- William Stein (2005-01-07): added `__reduce__`
- Craig Citro (2008-03-18): refactored `MatrixMorphism` class
- Rob Beezer (2011-07-15): additional methods, bug fixes, documentation

```

class sage.modules.matrix_morphism.MatrixMorphism(parent, A, copy_matrix=True, side='left')
    Bases: sage.modules.matrix_morphism.MatrixMorphism_abstract

```

A morphism defined by a matrix.

INPUT:

- `parent` – a homspace
- `A` – matrix or a *MatrixMorphism_abstract* instance
- `copy_matrix` – (default: `True`) make an immutable copy of the matrix `A` if it is mutable; if `False`, then this makes `A` immutable

is_injective()

Tell whether `self` is injective.

EXAMPLES:

```

sage: V1 = QQ^2
sage: V2 = QQ^3
sage: phi = V1.hom(Matrix([[1,2,3],[4,5,6]]),V2)

```

(continues on next page)

(continued from previous page)

```

sage: phi.is_injective()
True
sage: psi = V2.hom(Matrix([[1,2],[3,4],[5,6]]),V1)
sage: psi.is_injective()
False

```

AUTHOR:

– Simon King (2010-05)

is_surjective()Tell whether `self` is surjective.

EXAMPLES:

```

sage: V1 = QQ^2
sage: V2 = QQ^3
sage: phi = V1.hom(Matrix([[1,2,3],[4,5,6]]), V2)
sage: phi.is_surjective()
False
sage: psi = V2.hom(Matrix([[1,2],[3,4],[5,6]]), V1)
sage: psi.is_surjective()
True

```

An example over a PID that is not \mathbb{Z} .

```

sage: R = PolynomialRing(QQ, 'x')
sage: A = R^2
sage: B = R^2
sage: H = A.hom([B([x^2-1, 1]), B([x^2, 1])])
sage: H.image()
Free module of degree 2 and rank 2 over Univariate Polynomial Ring in x over
Rational Field
Echelon basis matrix:
[ 1  0]
[ 0 -1]
sage: H.is_surjective()
True

```

This tests if [trac ticket #11552](#) is fixed.

```

sage: V = ZZ^2
sage: m = matrix(ZZ, [[1,2],[0,2]])
sage: phi = V.hom(m, V)
sage: phi.lift(vector(ZZ, [0, 1]))
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: phi.is_surjective()
False

```

AUTHORS:

- Simon King (2010-05)
- Rob Beezer (2011-06-28)

matrix(*side=None*)

Return a matrix that defines this morphism.

INPUT:

- *side* – (default: 'None') the side of the matrix where a vector is placed to effect the morphism (function)

OUTPUT:

A matrix which represents the morphism, relative to bases for the domain and codomain. If the modules are provided with user bases, then the representation is relative to these bases.

Internally, Sage represents a matrix morphism with the matrix multiplying a row vector placed to the left of the matrix. If the option *side='right'* is used, then a matrix is returned that acts on a vector to the right of the matrix. These two matrices are just transposes of each other and the difference is just a preference for the style of representation.

EXAMPLES:

```
sage: V = ZZ^2; W = ZZ^3
sage: m = column_matrix([3*V.0 - 5*V.1, 4*V.0 + 2*V.1, V.0 + V.1])
sage: phi = V.hom(m, W)
sage: phi.matrix()
[ 3  4  1]
[-5  2  1]

sage: phi.matrix(side='right')
[ 3 -5]
[ 4  2]
[ 1  1]
```

class sage.modules.matrix_morphism.**MatrixMorphism_abstract**(*parent, side='left'*)

Bases: sage.categories.morphism.Morphism

INPUT:

- *parent* - a homspace
- *A* - matrix

EXAMPLES:

```
sage: from sage.modules.matrix_morphism import MatrixMorphism
sage: T = End(ZZ^3)
sage: M = MatrixSpace(ZZ, 3)
sage: I = M.identity_matrix()
sage: A = MatrixMorphism(T, I)
sage: loads(A.dumps()) == A
True
```

base_ring()

Return the base ring of self, that is, the ring over which self is given by a matrix.

EXAMPLES:

```
sage: sage.modules.matrix_morphism.MatrixMorphism((ZZ**2).endomorphism_ring(),
↳Matrix(ZZ,2,[3..6])).base_ring()
Integer Ring
```

characteristic_polynomial(*var='x'*)

Return the characteristic polynomial of this endomorphism.

`characteristic_polynomial` and `char_poly` are the same method.

INPUT:

- `var` – variable

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.characteristic_polynomial()
x^2 - 3*x + 2
sage: phi.charpoly()
x^2 - 3*x + 2
sage: phi.matrix().charpoly()
x^2 - 3*x + 2
sage: phi.charpoly('T')
T^2 - 3*T + 2
```

charpoly(*var='x'*)

Return the characteristic polynomial of this endomorphism.

`characteristic_polynomial` and `char_poly` are the same method.

INPUT:

- `var` – variable

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.characteristic_polynomial()
x^2 - 3*x + 2
sage: phi.charpoly()
x^2 - 3*x + 2
sage: phi.matrix().charpoly()
x^2 - 3*x + 2
sage: phi.charpoly('T')
T^2 - 3*T + 2
```

decomposition(**args, **kws*)

Return decomposition of this endomorphism, i.e., sequence of subspaces obtained by finding invariant subspaces of self.

See the documentation for `self.matrix().decomposition` for more details. All inputs to this function are passed onto the matrix one.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.decomposition()
[
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[0 1],
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
```

(continues on next page)

(continued from previous page)

```
[ 1 -1]
]
sage: phi2 = V.hom(phi.matrix(), side="right")
sage: phi2.decomposition()
[
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[1 1],
Free module of degree 2 and rank 1 over Integer Ring
Echelon basis matrix:
[1 0]
]
```

det()

Return the determinant of this endomorphism.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.det()
2
```

fcp(*var*='x')

Return the factorization of the characteristic polynomial.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.fcp()
(x - 2) * (x - 1)
sage: phi.fcp('T')
(T - 2) * (T - 1)
```

image()

Compute the image of this morphism.

EXAMPLES:

```
sage: V = VectorSpace(QQ,3)
sage: phi = V.Hom(V)(matrix(QQ, 3, range(9)))
sage: phi.image()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[ 1  0 -1]
[ 0  1  2]
sage: hom(GF(7)^3, GF(7)^2, zero_matrix(GF(7), 3, 2)).image()
Vector space of degree 2 and dimension 0 over Finite Field of size 7
Basis matrix:
[]
sage: m = matrix(3, [1, 0, 0, 1, 0, 0, 0, 0, 1]); m
[1 0 0]
[1 0 0]
[0 0 1]
sage: f1 = V.hom(m)
```

(continues on next page)

(continued from previous page)

```

sage: f2 = V.hom(m, side="right")
sage: f1.image()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]
[0 0 1]
sage: f2.image()
Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 1 0]
[0 0 1]

```

Compute the image of the identity map on a ZZ-submodule:

```

sage: V = (ZZ^2).span([[1,2],[3,4]])
sage: phi = V.Hom(V)(identity_matrix(ZZ,2))
sage: phi(V.0) == V.0
True
sage: phi(V.1) == V.1
True
sage: phi.image()
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1 0]
[0 2]
sage: phi.image() == V
True

```

inverse()

Return the inverse of this matrix morphism, if the inverse exists.

Raises a `ZeroDivisionError` if the inverse does not exist.

EXAMPLES:

An invertible morphism created as a restriction of a non-invertible morphism, and which has an unequal domain and codomain.

```

sage: V = QQ^4
sage: W = QQ^3
sage: m = matrix(QQ, [[2, 0, 3], [-6, 1, 4], [1, 2, -4], [1, 0, 1]])
sage: phi = V.hom(m, W)
sage: rho = phi.restrict_domain(V.span([V.0, V.3]))
sage: zeta = rho.restrict_codomain(W.span([W.0, W.2]))
sage: x = vector(QQ, [2, 0, 0, -7])
sage: y = zeta(x); y
(-3, 0, -1)
sage: inv = zeta.inverse(); inv
Vector space morphism represented by the matrix:
[-1 3]
[ 1 -2]
Domain: Vector space of degree 3 and dimension 2 over Rational Field
Basis matrix:
[1 0 0]

```

(continues on next page)

(continued from previous page)

```
[0 0 1]
Codomain: Vector space of degree 4 and dimension 2 over Rational Field
Basis matrix:
[1 0 0 0]
[0 0 0 1]
sage: inv(y) == x
True
```

An example of an invertible morphism between modules, (rather than between vector spaces).

```
sage: M = ZZ^4
sage: p = matrix(ZZ, [[ 0, -1, 1, -2],
.....:               [ 1, -3, 2, -3],
.....:               [ 0, 4, -3, 4],
.....:               [-2, 8, -4, 3]])
sage: phi = M.hom(p, M)
sage: x = vector(ZZ, [1, -3, 5, -2])
sage: y = phi(x); y
(1, 12, -12, 21)
sage: rho = phi.inverse(); rho
Free module morphism defined by the matrix
[ -5  3 -1  1]
[ -9  4 -3  2]
[-20  8 -7  4]
[ -6  2 -2  1]
Domain: Ambient free module of rank 4 over the principal ideal domain ...
Codomain: Ambient free module of rank 4 over the principal ideal domain ...
sage: rho(y) == x
True
```

A non-invertible morphism, despite having an appropriate domain and codomain.

```
sage: V = QQ^2
sage: m = matrix(QQ, [[1, 2], [20, 40]])
sage: phi = V.hom(m, V)
sage: phi.is_bijective()
False
sage: phi.inverse()
Traceback (most recent call last):
...
ZeroDivisionError: matrix morphism not invertible
```

The matrix representation of this morphism is invertible over the rationals, but not over the integers, thus the morphism is not invertible as a map between modules. It is easy to notice from the definition that every vector of the image will have a second entry that is an even integer.

```
sage: V = ZZ^2
sage: q = matrix(ZZ, [[1, 2], [3, 4]])
sage: phi = V.hom(q, V)
sage: phi.matrix().change_ring(QQ).inverse()
[ -2  1]
[ 3/2 -1/2]
sage: phi.is_bijective()
```

(continues on next page)

(continued from previous page)

```

False
sage: phi.image()
Free module of degree 2 and rank 2 over Integer Ring
Echelon basis matrix:
[1 0]
[0 2]
sage: phi.lift(vector(ZZ, [1, 1]))
Traceback (most recent call last):
...
ValueError: element is not in the image
sage: phi.inverse()
Traceback (most recent call last):
...
ZeroDivisionError: matrix morphism not invertible

```

The unary invert operator (\sim , tilde, “wiggle”) is synonymous with the `inverse()` method (and a lot easier to type).

```

sage: V = QQ^2
sage: r = matrix(QQ, [[4, 3], [-2, 5]])
sage: phi = V.hom(r, V)
sage: rho = phi.inverse()
sage: zeta = ~phi
sage: rho.is_equal_function(zeta)
True

```

`is_bijective()`

Tell whether `self` is bijective.

EXAMPLES:

Two morphisms that are obviously not bijective, simply on considerations of the dimensions. However, each fulfills half of the requirements to be a bijection.

```

sage: V1 = QQ^2
sage: V2 = QQ^3
sage: m = matrix(QQ, [[1, 2, 3], [4, 5, 6]])
sage: phi = V1.hom(m, V2)
sage: phi.is_injective()
True
sage: phi.is_bijective()
False
sage: rho = V2.hom(m.transpose(), V1)
sage: rho.is_surjective()
True
sage: rho.is_bijective()
False

```

We construct a simple bijection between two one-dimensional vector spaces.

```

sage: V1 = QQ^3
sage: V2 = QQ^2
sage: phi = V1.hom(matrix(QQ, [[1, 2], [3, 4], [5, 6]]), V2)
sage: x = vector(QQ, [1, -1, 4])

```

(continues on next page)

(continued from previous page)

```

sage: y = phi(x); y
(18, 22)
sage: rho = phi.restrict_domain(V1.span([x]))
sage: zeta = rho.restrict_codomain(V2.span([y]))
sage: zeta.is_bijective()
True

```

AUTHOR:

- Rob Beezer (2011-06-28)

`is_equal_function(other)`

Determines if two morphisms are equal functions.

INPUT:

- `other` - a morphism to compare with `self`

OUTPUT:

Returns `True` precisely when the two morphisms have equal domains and codomains (as sets) and produce identical output when given the same input. Otherwise returns `False`.

This is useful when `self` and `other` may have different representations.

Sage's default comparison of matrix morphisms requires the domains to have the same bases and the codomains to have the same bases, and then compares the matrix representations. This notion of equality is more permissive (it will return `True` "more often"), but is more correct mathematically.

EXAMPLES:

Three morphisms defined by combinations of different bases for the domain and codomain and different functions. Two are equal, the third is different from both of the others.

```

sage: B = matrix(QQ, [[-3, 5, -4, 2],
.....:               [-1, 2, -1, 4],
.....:               [ 4, -6, 5, -1],
.....:               [-5, 7, -6, 1]])
sage: U = (QQ^4).subspace_with_basis(B.rows())
sage: C = matrix(QQ, [[-1, -6, -4],
.....:               [ 3, -5, 6],
.....:               [ 1, 2, 3]])
sage: V = (QQ^3).subspace_with_basis(C.rows())
sage: H = Hom(U, V)

sage: D = matrix(QQ, [[-7, -2, -5, 2],
.....:               [-5, 1, -4, -8],
.....:               [ 1, -1, 1, 4],
.....:               [-4, -1, -3, 1]])
sage: X = (QQ^4).subspace_with_basis(D.rows())
sage: E = matrix(QQ, [[ 4, -1, 4],
.....:               [ 5, -4, -5],
.....:               [-1, 0, -2]])
sage: Y = (QQ^3).subspace_with_basis(E.rows())
sage: K = Hom(X, Y)

sage: f = lambda x: vector(QQ, [x[0]+x[1], 2*x[1]-4*x[2], 5*x[3]])

```

(continues on next page)

(continued from previous page)

```

sage: g = lambda x: vector(QQ, [x[0]-x[2], 2*x[1]-4*x[2], 5*x[3]])

sage: rho = H(f)
sage: phi = K(f)
sage: zeta = H(g)

sage: rho.is_equal_function(phi)
True
sage: phi.is_equal_function(rho)
True
sage: zeta.is_equal_function(rho)
False
sage: phi.is_equal_function(zeta)
False

```

AUTHOR:

- Rob Beezer (2011-07-15)

is_identity()

Determines if this morphism is an identity function or not.

EXAMPLES:

A homomorphism that cannot possibly be the identity due to an unequal domain and codomain.

```

sage: V = QQ^3
sage: W = QQ^2
sage: m = matrix(QQ, [[1, 2], [3, 4], [5, 6]])
sage: phi = V.hom(m, W)
sage: phi.is_identity()
False

```

A bijection, but not the identity.

```

sage: V = QQ^3
sage: n = matrix(QQ, [[3, 1, -8], [5, -4, 6], [1, 1, -5]])
sage: phi = V.hom(n, V)
sage: phi.is_bijective()
True
sage: phi.is_identity()
False

```

A restriction that is the identity.

```

sage: V = QQ^3
sage: p = matrix(QQ, [[1, 0, 0], [5, 8, 3], [0, 0, 1]])
sage: phi = V.hom(p, V)
sage: rho = phi.restrict(V.span([V.0, V.2]))
sage: rho.is_identity()
True

```

An identity linear transformation that is defined with a domain and codomain with wildly different bases, so that the matrix representation is not simply the identity matrix.


```

sage: A = matrix(QQ, [[1, 1, 0], [2, 3, -4], [2, 4, -7]])
sage: B = matrix(QQ, [[2, 7, -2], [-1, -3, 1], [-1, -6, 2]])
sage: U = (QQ^3).subspace_with_basis(A.rows())
sage: V = (QQ^3).subspace_with_basis(B.rows())
sage: H = Hom(U, V)
sage: id = lambda x: x
sage: phi = H(id)
sage: phi([203, -179, 34])
(203, -179, 34)
sage: phi.matrix()
[ 1  0  1]
[-9 -18 -2]
[-17 -31 -5]
sage: phi.is_identity()
True

```

AUTHOR:

- Rob Beezer (2011-06-28)

is_zero()

Determines if this morphism is a zero function or not.

EXAMPLES:

A zero morphism created from a function.

```

sage: V = ZZ^5
sage: W = ZZ^3
sage: z = lambda x: zero_vector(ZZ, 3)
sage: phi = V.hom(z, W)
sage: phi.is_zero()
True

```

An image list that just barely makes a non-zero morphism.

```

sage: V = ZZ^4
sage: W = ZZ^6
sage: z = zero_vector(ZZ, 6)
sage: images = [z, z, W.5, z]
sage: phi = V.hom(images, W)
sage: phi.is_zero()
False

```

AUTHOR:

- Rob Beezer (2011-07-15)

kernel()

Compute the kernel of this morphism.

EXAMPLES:

```

sage: V = VectorSpace(QQ, 3)
sage: id = V.Hom(V)(identity_matrix(QQ, 3))
sage: null = V.Hom(V)(0*identity_matrix(QQ, 3))
sage: id.kernel()

```

(continues on next page)

(continued from previous page)

```

Vector space of degree 3 and dimension 0 over Rational Field
Basis matrix:
[]
sage: phi = V.hom(V)(matrix(QQ,3,range(9)))
sage: phi.kernel()
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 -2  1]
sage: hom(CC^2, CC^2, matrix(CC, [[1,0], [0,1]])).kernel()
Vector space of degree 2 and dimension 0 over Complex Field with 53 bits of
precision
Basis matrix:
[]
sage: m = matrix(3, [1, 0, 0, 1, 0, 0, 0, 0, 1]); m
[1 0 0]
[1 0 0]
[0 0 1]
sage: f1 = V.hom(m)
sage: f2 = V.hom(m, side="right")
sage: f1.kernel()
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[ 1 -1  0]
sage: f2.kernel()
Vector space of degree 3 and dimension 1 over Rational Field
Basis matrix:
[0 1 0]

```

matrix()

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom(V.basis())
sage: phi.matrix()
[1 0]
[0 1]
sage: sage.modules.matrix_morphism.MatrixMorphism_abstract.matrix(phi)
Traceback (most recent call last):
...
NotImplementedError: this method must be overridden in the extension class

```

nullity()

Returns the nullity of the matrix representing this morphism, which is the dimension of its kernel.

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom(V.basis())
sage: phi.nullity()
0
sage: V = ZZ^2; phi = V.hom([V.0, V.0])
sage: phi.nullity()
1

```

```

sage: m = matrix(2, [1, 2])
sage: V = ZZ^2
sage: h1 = V.hom(m)
sage: h1.nullity()
1
sage: W = ZZ^1
sage: h2 = W.hom(m, side="right")
sage: h2.nullity()
0

```

rank()

Returns the rank of the matrix representing this morphism.

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom(V.basis())
sage: phi.rank()
2
sage: V = ZZ^2; phi = V.hom([V.0, V.0])
sage: phi.rank()
1

```

restrict(*sub*)

Restrict this matrix morphism to a subspace *sub* of the domain.

The codomain and domain of the resulting matrix are both *sub*.

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom([3*V.0, 2*V.1])
sage: phi.restrict(V.span([V.0]))
Free module morphism defined by the matrix
[3]
Domain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...
Codomain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...

sage: V = (QQ^2).span_of_basis([[1,2],[3,4]])
sage: phi = V.hom([V.0+V.1, 2*V.1])
sage: phi(V.1) == 2*V.1
True
sage: W = span([V.1])
sage: phi(W)
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[ 1 4/3]
sage: psi = phi.restrict(W); psi
Vector space morphism represented by the matrix:
[2]
Domain: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[ 1 4/3]
Codomain: Vector space of degree 2 and dimension 1 over Rational Field

```

(continues on next page)

(continued from previous page)

```

Basis matrix:
[ 1 4/3]
sage: psi.domain() == W
True
sage: psi(W.0) == 2*W.0
True

```

```

sage: V = ZZ^3
sage: h1 = V.hom([V.0, V.1+V.2, -V.1+V.2])
sage: h2 = h1.side_switch()
sage: SV = V.span([2*V.1, 2*V.2])
sage: h1.restrict(SV)
Free module morphism defined by the matrix
[ 1 1]
[-1 1]
Domain: Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[0 2 0]
[0 0 2]
Codomain: Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[0 2 0]
[0 0 2]
sage: h2.restrict(SV)
Free module morphism defined as left-multiplication by the matrix
[ 1 -1]
[ 1 1]
Domain: Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[0 2 0]
[0 0 2]
Codomain: Free module of degree 3 and rank 2 over Integer Ring
Echelon basis matrix:
[0 2 0]
[0 0 2]

```

restrict_codomain(sub)

Restrict this matrix morphism to a subspace sub of the codomain.

The resulting morphism has the same domain as before, but a new codomain.

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom([4*(V.0+V.1), 0])
sage: W = V.span([2*(V.0+V.1)])
sage: phi
Free module morphism defined by the matrix
[4 4]
[0 0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
sage: psi = phi.restrict_codomain(W); psi
Free module morphism defined by the matrix

```

(continues on next page)

(continued from previous page)

```

[2]
[0]
Domain: Ambient free module of rank 2 over the principal ideal domain ...
Codomain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...
sage: phi2 = phi.side_switch(); phi2.restrict_codomain(W)
Free module morphism defined as left-multiplication by the matrix
[2 0]
Domain: Ambient free module of rank 2 over the principal ideal domain Integer_
  ↪ Ring
Codomain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...

```

An example in which the codomain equals the full ambient space, but with a different basis:

```

sage: V = QQ^2
sage: W = V.span_of_basis([[1,2],[3,4]])
sage: phi = V.hom(matrix(QQ,2,[1,0,2,0]),W)
sage: phi.matrix()
[1 0]
[2 0]
sage: phi(V.0)
(1, 2)
sage: phi(V.1)
(2, 4)
sage: X = V.span([[1,2]]); X
Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]
sage: phi(V.0) in X
True
sage: phi(V.1) in X
True
sage: psi = phi.restrict_codomain(X); psi
Vector space morphism represented by the matrix:
[1]
[2]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of degree 2 and dimension 1 over Rational Field
Basis matrix:
[1 2]
sage: psi(V.0)
(1, 2)
sage: psi(V.1)
(2, 4)
sage: psi(V.0).parent() is X
True

```

restrict_domain(*sub*)

Restrict this matrix morphism to a subspace *sub* of the domain. The subspace *sub* should have a `basis()` method and elements of the basis should be coercible into domain.

The resulting morphism has the same codomain as before, but a new domain.

EXAMPLES:

```
sage: V = ZZ^2; phi = V.hom([3*V.0, 2*V.1])
sage: phi.restrict_domain(V.span([V.0]))
Free module morphism defined by the matrix
[3 0]
Domain: Free module of degree 2 and rank 1 over Integer Ring
Echelon ...
Codomain: Ambient free module of rank 2 over the principal ideal domain ...
sage: phi.restrict_domain(V.span([V.1]))
Free module morphism defined by the matrix
[0 2]...
sage: m = matrix(2, range(1,5))
sage: f1 = V.hom(m); f2 = V.hom(m, side="right")
sage: SV = V.span([V.0])
sage: f1.restrict_domain(SV)
Free module morphism defined by the matrix
[1 2]...
sage: f2.restrict_domain(SV)
Free module morphism defined as left-multiplication by the matrix
[1]
[3]...
```

side()

Return the side of vectors acted on, relative to the matrix.

EXAMPLES:

```
sage: m = matrix(2, [1, 1, 0, 1])
sage: V = ZZ^2
sage: h1 = V.hom(m); h2 = V.hom(m, side="right")
sage: h1.side()
'left'
sage: h1([1, 0])
(1, 1)
sage: h2.side()
'right'
sage: h2([1, 0])
(1, 0)
```

side_switch()

Return the same morphism, acting on vectors on the opposite side

EXAMPLES:

```
sage: m = matrix(2, [1,1,0,1]); m
[1 1]
[0 1]
sage: V = ZZ^2
sage: h = V.hom(m); h.side()
'left'
sage: h2 = h.side_switch(); h2
Free module morphism defined as left-multiplication by the matrix
[1 0]
[1 1]
```

(continues on next page)

(continued from previous page)

```

Domain: Ambient free module of rank 2 over the principal ideal domain Integer
↳Ring
Codomain: Ambient free module of rank 2 over the principal ideal domain Integer
↳Ring
sage: h2.side()
'right'
sage: h2.side_switch().matrix()
[1 1]
[0 1]

```

trace()

Return the trace of this endomorphism.

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom([V.0+V.1, 2*V.1])
sage: phi.trace()
3

```

sage.modules.matrix_morphism.is_MatrixMorphism(x)

Return True if x is a Matrix morphism of free modules.

EXAMPLES:

```

sage: V = ZZ^2; phi = V.hom([3*V.0, 2*V.1])
sage: sage.modules.matrix_morphism.is_MatrixMorphism(phi)
True
sage: sage.modules.matrix_morphism.is_MatrixMorphism(3)
False

```


VECTORS

8.1 Vectors with integer entries

AUTHOR:

- William Stein (2007)

EXAMPLES:

```
sage: v = vector(ZZ,[1,2,3,4,5])
sage: v
(1, 2, 3, 4, 5)
sage: 3*v
(3, 6, 9, 12, 15)
sage: v*7
(7, 14, 21, 28, 35)
sage: -v
(-1, -2, -3, -4, -5)
sage: v - v
(0, 0, 0, 0, 0)
sage: v + v
(2, 4, 6, 8, 10)
sage: v * v # dot product.
55
```

We make a large zero vector:

```
sage: k = ZZ^100000; k
Ambient free module of rank 100000 over the principal ideal domain Integer Ring
sage: v = k(0)
sage: v[:10]
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

```
class sage.modules.vector_integer_dense.Vector_integer_dense
    Bases: sage.modules.free_module_element.FreeModuleElement
```

```
list(copy=True)
```

The list of entries of the vector.

INPUT:

- copy, ignored optional argument.

EXAMPLES:

```

sage: v = vector([1,2,3,4])
sage: a = v.list(copy=False); a
[1, 2, 3, 4]
sage: a[0] = 0
sage: v
(1, 2, 3, 4)

```

```
sage.modules.vector_integer_dense.unpickle_v0(parent, entries, degree)
```

```
sage.modules.vector_integer_dense.unpickle_v1(parent, entries, degree, is_mutable)
```

8.2 Vectors with elements in F_2

AUTHOR:

- Martin Albrecht (2009-12): initial implementation
- Thomas Feulner (2012-11): added `Vector_mod2_dense.hamming_weight()`

EXAMPLES:

```

sage: VS = GF(2)^3
sage: e = VS.random_element()
sage: e.parent() is VS
True
sage: S = set(vector(v, immutable=True) for v in VS)
sage: S1 = set()
sage: while S != S1:
.....:     S1.add(vector(VS.random_element(), immutable=True))

```

```

class sage.modules.vector_mod2_dense.Vector_mod2_dense
Bases: sage.modules.free_module_element.FreeModuleElement

```

EXAMPLES:

```

sage: VS = VectorSpace(GF(2), 3)
sage: VS((0,0,1/3))
(0, 0, 1)
sage: type(_)
<class 'sage.modules.vector_mod2_dense.Vector_mod2_dense'>
sage: VS((0,0,int(3)))
(0, 0, 1)
sage: VS((0,0,3))
(0, 0, 1)
sage: VS((0,0,GF(2)(1)))
(0, 0, 1)

```

hamming_weight()

Return the number of positions i such that `self[i] != 0`.

EXAMPLES:

```

sage: vector(GF(2), [1,1,0]).hamming_weight()
2

```

list(*copy=True*)

Return a list of entries in *self*.

INPUT:

- *copy* - always True

EXAMPLES:

```
sage: VS = VectorSpace(GF(2), 10)
sage: entries = [GF(2).random_element() for _ in range(10)]
sage: e = VS(entries)
sage: e.list() == entries
True
```

`sage.modules.vector_mod2_dense.unpickle_v0(parent, entries, degree, is_immutable)`

EXAMPLES:

```
sage: from sage.modules.vector_mod2_dense import unpickle_v0
sage: VS = VectorSpace(GF(2), 10)
sage: unpickle_v0(VS, [0, 1, 2, 3, 4, 5, 6, 7, 8, 9], 10, 0)
(0, 1, 0, 1, 0, 1, 0, 1, 0, 1)
```

8.3 Vectors with integer mod n entries, with small n

EXAMPLES:

```
sage: v = vector(Integers(8), [1, 2, 3, 4, 5])
sage: type(v)
<class 'sage.modules.vector_modn_dense.Vector_modn_dense'>
sage: v
(1, 2, 3, 4, 5)
sage: 3*v
(3, 6, 1, 4, 7)
sage: v*7
(7, 6, 5, 4, 3)
sage: -v
(7, 6, 5, 4, 3)
sage: v - v
(0, 0, 0, 0, 0)
sage: v + v
(2, 4, 6, 0, 2)
sage: v * v
7

sage: v = vector(Integers(8), [1, 2, 3, 4, 5])
sage: u = vector(Integers(8), [1, 2, 3, 4, 4])
sage: v - u
(0, 0, 0, 0, 1)
sage: u - v
(0, 0, 0, 0, 7)

sage: v = vector((Integers(5)(1), 2, 3, 4, 4))
```

(continues on next page)

(continued from previous page)

```
sage: u = vector((Integers(5)(1),2,3,4,3))
sage: v = u
(0, 0, 0, 0, 1)
sage: u - v
(0, 0, 0, 0, 4)
```

We make a large zero vector:

```
sage: k = Integers(8)^100000; k
Ambient free module of rank 100000 over Ring of integers modulo 8
sage: v = k(0)
sage: v[:10]
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

We multiply a vector by a matrix:

```
sage: a = (GF(97)^5)(range(5))
sage: m = matrix(GF(97),5,range(25))
sage: a*m
(53, 63, 73, 83, 93)
```

AUTHOR:

- William Stein (2007)

class sage.modules.vector_modn_dense.**Vector_modn_dense**

Bases: [sage.modules.free_module_element.FreeModuleElement](#)

sage.modules.vector_modn_dense.**unpickle_v0**(parent, entries, degree, p)

sage.modules.vector_modn_dense.**unpickle_v1**(parent, entries, degree, p, is_mutable)

8.4 Vectors with rational entries

AUTHOR:

- William Stein (2007)
- Soroosh Yazdani (2007)

EXAMPLES:

```
sage: v = vector(QQ,[1,2,3,4,5])
sage: v
(1, 2, 3, 4, 5)
sage: 3*v
(3, 6, 9, 12, 15)
sage: v/2
(1/2, 1, 3/2, 2, 5/2)
sage: -v
(-1, -2, -3, -4, -5)
sage: v - v
(0, 0, 0, 0, 0)
sage: v + v
```

(continues on next page)

(continued from previous page)

```
(2, 4, 6, 8, 10)
sage: v * v
55
```

We make a large zero vector:

```
sage: k = QQ^100000; k
Vector space of dimension 100000 over Rational Field
sage: v = k(0)
sage: v[:10]
(0, 0, 0, 0, 0, 0, 0, 0, 0, 0)
```

```
class sage.modules.vector_rational_dense.Vector_rational_dense
```

```
    Bases: sage.modules.free_module_element.FreeModuleElement
```

```
    list(copy=True)
```

The list of entries of the vector.

INPUT:

- copy, ignored optional argument.

EXAMPLES:

```
sage: v = vector(QQ, [1, 2, 3, 4])
sage: a = v.list(copy=False); a
[1, 2, 3, 4]
sage: a[0] = 0
sage: v
(1, 2, 3, 4)
```

```
sage.modules.vector_rational_dense.unpickle_v0(parent, entries, degree)
```

```
sage.modules.vector_rational_dense.unpickle_v1(parent, entries, degree, is_mutable)
```

8.5 Vectors over the symbolic ring

Implements vectors over the symbolic ring.

AUTHORS:

- Robert Bradshaw (2011-05-25): Added more element-wise simplification methods
- Joris Vankerschaver (2011-05-15): Initial version

EXAMPLES:

```
sage: x, y = var('x, y')
sage: u = vector([sin(x)^2 + cos(x)^2, log(2*y) + log(3*y)]); u
(cos(x)^2 + sin(x)^2, log(3*y) + log(2*y))
sage: type(u)
<class 'sage.modules.free_module.FreeModule_ambient_field_with_category.element_class'>
sage: u.simplify_full()
(1, log(3*y) + log(2*y))
```

class sage.modules.vector_symbolic_dense.Vector_symbolic_dense

Bases: [sage.modules.free_module_element.FreeModuleElement_generic_dense](#)

canonicalize_radical(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↳factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↳factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↳factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See Expression.canonicalize_radical() for optional arguments.

simplify(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↳factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↳factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↳factorial(x))
```

(continues on next page)

(continued from previous page)

```

sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.simplify()` for optional arguments.

simplify_factorial(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↪ factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↪ factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↪ factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.simplify_factorial()` for optional arguments.

simplify_full(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↪factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.simplify_full()` for optional arguments.

simplify_log(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↪factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
```

(continues on next page)

(continued from previous page)

```

sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See Expression.simplify_log() for optional arguments.

simplify_rational(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↪factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See Expression.simplify_rational() for optional arguments.

simplify_trig(*args, **kws)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↪factorial(x+1)/factorial(x)])

```

(continues on next page)

(continued from previous page)

```

sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))

```

See `Expression.simplify_trig()` for optional arguments.

trig_expand(*args, **kwds)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```

sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↪factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↪factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))

```

(continues on next page)

(continued from previous page)

```
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.expand_trig()` for optional arguments.

trig_reduce(*args, **kwargs)

Generic function used to implement common symbolic operations elementwise as methods of a vector.

EXAMPLES:

```
sage: var('x,y')
(x, y)
sage: v = vector([sin(x)^2 + cos(x)^2, log(x*y), sin(x/(x^2 + x)),
↳ factorial(x+1)/factorial(x)])
sage: v.simplify_trig()
(1, log(x*y), sin(1/(x + 1)), factorial(x + 1)/factorial(x))
sage: v.canonicalize_radical()
(cos(x)^2 + sin(x)^2, log(x) + log(y), sin(1/(x + 1)), factorial(x + 1)/
↳ factorial(x))
sage: v.simplify_rational()
(cos(x)^2 + sin(x)^2, log(x*y), sin(1/(x + 1)), factorial(x + 1)/
↳ factorial(x))
sage: v.simplify_factorial()
(cos(x)^2 + sin(x)^2, log(x*y), sin(x/(x^2 + x)), x + 1)
sage: v.simplify_full()
(1, log(x*y), sin(1/(x + 1)), x + 1)

sage: v = vector([sin(2*x), sin(3*x)])
sage: v.simplify_trig()
(2*cos(x)*sin(x), (4*cos(x)^2 - 1)*sin(x))
sage: v.simplify_trig(False)
(sin(2*x), sin(3*x))
sage: v.simplify_trig(expand=False)
(sin(2*x), sin(3*x))
```

See `Expression.reduce_trig()` for optional arguments.

`sage.modules.vector_symbolic_dense.apply_map(phi)`

Returns a function that applies `phi` to its argument.

EXAMPLES:

```
sage: from sage.modules.vector_symbolic_dense import apply_map
sage: v = vector([1,2,3])
sage: f = apply_map(lambda x: x+1)
sage: f(v)
(2, 3, 4)
```

8.6 Vectors over callable symbolic rings

AUTHOR: – Jason Grout (2010)

EXAMPLES:

```
sage: f(r, theta, z) = (r*cos(theta), r*sin(theta), z)
sage: f.parent()
Vector space of dimension 3 over Callable function ring with arguments (r, theta, z)
sage: f
(r, theta, z) |--> (r*cos(theta), r*sin(theta), z)
sage: f[0]
(r, theta, z) |--> r*cos(theta)
sage: f+f
(r, theta, z) |--> (2*r*cos(theta), 2*r*sin(theta), 2*z)
sage: 3*f
(r, theta, z) |--> (3*r*cos(theta), 3*r*sin(theta), 3*z)
sage: f*f # dot product
(r, theta, z) |--> r^2*cos(theta)^2 + r^2*sin(theta)^2 + z^2
sage: f.diff()(0,1,2) # the matrix derivative
[cos(1)      0      0]
[sin(1)      0      0]
[      0      0      1]
```

```
class sage.modules.vector_callable_symbolic_dense.Vector_callable_symbolic_dense
    Bases: sage.modules.free_module_element.FreeModuleElement_generic_dense
```

8.7 Dense vectors using a NumPy backend

This serves as a base class for dense vectors over Real Double Field and Complex Double Field

EXAMPLES:

```
sage: v = vector(CDF, [(1,-1), (2,pi), (3,5)])
sage: v
(1.0 - 1.0*I, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: type(v)
<class 'sage.modules.vector_complex_double_dense.Vector_complex_double_dense'>
sage: parent(v)
Vector space of dimension 3 over Complex Double Field
sage: v[0] = 5
sage: v
(5.0, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: loads(dumps(v)) == v
True
sage: v = vector(RDF, [1,2,3,4]); v
(1.0, 2.0, 3.0, 4.0)
sage: loads(dumps(v)) == v
True
```

AUTHORS:

- Jason Grout, Oct 2008: switch to numpy backend, factored out Vector_double_dense class

- Josh Kantor
- William Stein

class sage.modules.vector_double_dense.Vector_double_dense

Bases: sage.modules.vector_numpy_dense.Vector_numpy_dense

Base class for vectors over the Real Double Field and the Complex Double Field. These are supposed to be fast vector operations using C doubles. Most operations are implemented using numpy which will call the underlying BLAS, if needed, on the system.

This class cannot be instantiated on its own. The numpy vector creation depends on several variables that are set in the subclasses.

EXAMPLES:

```
sage: v = vector(RDF, [1,2,3,4]); v
(1.0, 2.0, 3.0, 4.0)
sage: v*v
30.0
```

complex_vector()

Return the associated complex vector, i.e., this vector but with coefficients viewed as complex numbers.

EXAMPLES:

```
sage: v = vector(RDF,4,range(4)); v
(0.0, 1.0, 2.0, 3.0)
sage: v.complex_vector()
(0.0, 1.0, 2.0, 3.0)
sage: v = vector(RDF,0)
sage: v.complex_vector()
()
```

fft(direction='forward', algorithm='radix2', inplace=False)

This performs a fast Fourier transform on the vector.

INPUT:

- direction – ‘forward’ (default) or ‘backward’

The algorithm and inplace arguments are ignored.

This function is fastest if the vector’s length is a power of 2.

EXAMPLES:

```
sage: v = vector(CDF, [1+2*I, 2, 3*I, 4])
sage: v.fft()
(7.0 + 5.0*I, 1.0 + 1.0*I, -5.0 + 5.0*I, 1.0 - 3.0*I)
sage: v.fft(direction='backward')
(1.75 + 1.25*I, 0.25 - 0.75*I, -1.25 + 1.25*I, 0.25 + 0.25*I)
sage: v.fft().fft(direction='backward')
(1.0 + 2.0*I, 2.0, 3.0*I, 4.0)
sage: v.fft().parent()
Vector space of dimension 4 over Complex Double Field
sage: v.fft(inplace=True)
sage: v
(7.0 + 5.0*I, 1.0 + 1.0*I, -5.0 + 5.0*I, 1.0 - 3.0*I)
```

(continues on next page)

(continued from previous page)

```

sage: v = vector(RDF, 4, range(4)); v
(0.0, 1.0, 2.0, 3.0)
sage: v.fft()
(6.0, -2.0 + 2.0*I, -2.0, -2.0 - 2.0*I)
sage: v.fft(direction='backward')
(1.5, -0.5 - 0.5*I, -0.5, -0.5 + 0.5*I)
sage: v.fft().fft(direction='backward')
(0.0, 1.0, 2.0, 3.0)
sage: v.fft().parent()
Vector space of dimension 4 over Complex Double Field
sage: v.fft(inplace=True)
Traceback (most recent call last):
...
ValueError: inplace can only be True for CDF vectors

```

inv_fft(algorithm='radix2', inplace=False)

This performs the inverse fast Fourier transform on the vector.

The Fourier transform can be done in place using the keyword inplace=True

This will be fastest if the vector's length is a power of 2.

EXAMPLES:

```

sage: v = vector(CDF, [1, 2, 3, 4])
sage: w = v.fft()
sage: max(v - w.inv_fft()) < 1e-12
True

```

mean()

Calculate the arithmetic mean of the vector.

EXAMPLES:

```

sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.mean()
4.0
sage: w.mean()
4.0 + 5.0*I

```

norm(p=2)

Returns the norm (or related computations) of the vector.

INPUT:

- p - default: 2 - controls which norm is computed, allowable values are any real number and positive and negative infinity. See output discussion for specifics.

OUTPUT:

Returned value is a double precision floating point value in RDF (or an integer when p=0). The default value of p = 2 is the “usual” Euclidean norm. For other values:

- p = Infinity or p = oo: the maximum of the absolute values of the entries, where the absolute value of the complex number $a + bi$ is $\sqrt{a^2 + b^2}$.

- $p = -\text{Infinity}$ or $p = -\infty$: the minimum of the absolute values of the entries.
- $p = 0$: the number of nonzero entries in the vector.
- p is any other real number: for a vector \vec{x} this method computes

$$\left(\sum_i x_i^p \right)^{1/p}$$

For $p < 0$ this function is not a norm, but the above computation may be useful for other purposes.

ALGORITHM:

Computation is performed by the `norm()` function of the SciPy/NumPy library.

EXAMPLES:

First over the reals.

```
sage: v = vector(RDF, range(9))
sage: v.norm()
14.28285685...
sage: v.norm(p=2)
14.28285685...
sage: v.norm(p=6)
8.744039097...
sage: v.norm(p=Infinity)
8.0
sage: v.norm(p=-oo)
0.0
sage: v.norm(p=0)
8.0
sage: v.norm(p=0.3)
4099.153615...
```

And over the complex numbers.

```
sage: w = vector(CDF, [3-4*I, 0, 5+12*I])
sage: w.norm()
13.9283882...
sage: w.norm(p=2)
13.9283882...
sage: w.norm(p=0)
2.0
sage: w.norm(p=4.2)
13.0555695...
sage: w.norm(p=oo)
13.0
```

Negative values of p are allowed and will provide the same computation as for positive values. A zero entry in the vector will raise a warning and return zero.

```
sage: v = vector(CDF, range(1,10))
sage: v.norm(p=-3.2)
0.953760808...
sage: w = vector(CDF, [-1,0,1])
sage: w.norm(p=-1.6)
```

(continues on next page)

(continued from previous page)

```
doctest:...: RuntimeWarning: divide by zero encountered in power
0.0
```

Return values are in RDF, or an integer when $p = 0$.

```
sage: v = vector(RDF, [1,2,4,8])
sage: v.norm() in RDF
True
sage: v.norm(p=0) in ZZ
True
```

Improper values of p are caught.

```
sage: w = vector(CDF, [-1,0,1])
sage: w.norm(p='junk')
Traceback (most recent call last):
...
ValueError: vector norm 'p' must be +/- infinity or a real number, not junk
```

prod()

Return the product of the entries of self.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.prod()
0.0
sage: w.prod()
57204225.0*I
```

standard_deviation(population=True)

Calculate the standard deviation of entries of the vector.

INPUT: population – If False, calculate the sample standard deviation.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.standard_deviation()
2.7386127875258306
sage: v.standard_deviation(population=False)
2.581988897471611
sage: w.standard_deviation()
3.872983346207417
sage: w.standard_deviation(population=False)
3.6514837167011076
```

stats_kurtosis()

Compute the kurtosis of a dataset.

Kurtosis is the fourth central moment divided by the square of the variance. Since we use Fisher's definition, 3.0 is subtracted from the result to give 0.0 for a normal distribution. (Paragraph from the `scipy.stats` docstring.)

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.stats_kurtosis() # rel tol 5e-15
-1.2300000000000000
sage: w.stats_kurtosis() # rel tol 5e-15
-1.2300000000000000
```

sum()

Return the sum of the entries of self.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.sum()
36.0
sage: w.sum()
36.0 + 45.0*I
```

variance(*population=True*)

Calculate the variance of entries of the vector.

INPUT:

- *population* – If False, calculate the sample variance.

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: w = vector(CDF, [k+(9-k)*I for k in range(9)])
sage: v.variance()
7.5
sage: v.variance(population=False)
6.666666666666667
sage: w.variance()
15.0
sage: w.variance(population=False)
13.333333333333334
```

zero_at(*eps*)

Returns a copy with small entries replaced by zeros.

This is useful for modifying output from algorithms which have large relative errors when producing zero elements, e.g. to create reliable doctests.

INPUT:

- *eps* - cutoff value

OUTPUT:

A modified copy of the vector. Elements smaller than or equal to *eps* are replaced with zeroes. For complex vectors, the real and imaginary parts are considered individually.

EXAMPLES:

```
sage: v = vector(RDF, [1.0, 2.0, 10^-10, 3.0])
sage: v.zero_at(1e-8)
(1.0, 2.0, 0.0, 3.0)
sage: v.zero_at(1e-12)
(1.0, 2.0, 1e-10, 3.0)
```

For complex numbers the real and imaginary parts are considered separately.

```
sage: w = vector(CDF, [10^-6 + 5*I, 5 + 10^-6*I, 5 + 5*I, 10^-6 + 10^-6*I])
sage: w.zero_at(1.0e-4)
(5.0*I, 5.0, 5.0 + 5.0*I, 0.0)
sage: w.zero_at(1.0e-8)
(1e-06 + 5.0*I, 5.0 + 1e-06*I, 5.0 + 5.0*I, 1e-06 + 1e-06*I)
```

8.8 Dense real double vectors using a NumPy backend

EXAMPLES:

```
sage: v = vector(RDF, [1, pi, sqrt(2)])
sage: v
(1.0, 3.141592653589793, 1.414213562373095)
sage: type(v)
<class 'sage.modules.vector_real_double_dense.Vector_real_double_dense'>
sage: parent(v)
Vector space of dimension 3 over Real Double Field
sage: v[0] = 5
sage: v
(5.0, 3.141592653589793, 1.414213562373095)
sage: loads(dumps(v)) == v
True
```

AUTHORS:

– Jason Grout, Oct 2008: switch to numpy backend, factored out `Vector_double_dense` class

class `sage.modules.vector_real_double_dense.Vector_real_double_dense`

Bases: `sage.modules.vector_double_dense.Vector_double_dense`

Vectors over the Real Double Field. These are supposed to be fast vector operations using C doubles. Most operations are implemented using numpy which will call the underlying BLAS, if needed, on the system.

EXAMPLES:

```
sage: v = vector(RDF, [1,2,3,4]); v
(1.0, 2.0, 3.0, 4.0)
sage: v*v
30.0
```

stats_skew()

Computes the skewness of a data set.

For normally distributed data, the skewness should be about 0. A skewness value > 0 means that there is more weight in the left tail of the distribution. (Paragraph from the `scipy.stats` docstring.)

EXAMPLES:

```
sage: v = vector(RDF, range(9))
sage: v.stats_skew()
0.0
```

`sage.modules.vector_real_double_dense.unpickle_v0(parent, entries, degree)`

Create a real double vector containing the entries.

EXAMPLES:

```
sage: v = vector(RDF, [1,2,3])
sage: w = sage.modules.vector_real_double_dense.unpickle_v0(v.parent(), list(v), v.
↳ degree())
sage: v == w
True
```

`sage.modules.vector_real_double_dense.unpickle_v1(parent, entries, degree, is_mutable=None)`

Create a real double vector with the given parent, entries, degree, and mutability.

EXAMPLES:

```
sage: v = vector(RDF, [1,2,3])
sage: w = sage.modules.vector_real_double_dense.unpickle_v1(v.parent(), list(v), v.
↳ degree(), v.is_immutable())
sage: v == w
True
```

8.9 Dense complex double vectors using a NumPy backend

EXAMPLES:

```
sage: v = vector(CDF, [(1,-1), (2,pi), (3,5)])
sage: v
(1.0 - 1.0*I, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: type(v)
<class 'sage.modules.vector_complex_double_dense.Vector_complex_double_dense'>
sage: parent(v)
Vector space of dimension 3 over Complex Double Field
sage: v[0] = 5
sage: v
(5.0, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: loads(dumps(v)) == v
True
```

AUTHORS:

– Jason Grout, Oct 2008: switch to NumPy backend, factored out `Vector_double_dense` class

class `sage.modules.vector_complex_double_dense.Vector_complex_double_dense`

Bases: `sage.modules.vector_double_dense.Vector_double_dense`

Vectors over the Complex Double Field. These are supposed to be fast vector operations using C doubles. Most operations are implemented using numpy which will call the underlying BLAS, if needed, on the system.

EXAMPLES:

```
sage: v = vector(CDF, [(1,-1), (2,pi), (3,5)])
sage: v
(1.0 - 1.0*I, 2.0 + 3.141592653589793*I, 3.0 + 5.0*I)
sage: v*v # rel tol 1e-15
-21.86960440108936 + 40.56637061435917*I
```

`sage.modules.vector_complex_double_dense.unpickle_v0(parent, entries, degree)`
Create a complex double vector containing the entries.

EXAMPLES:

```
sage: v = vector(CDF, [1,2,3])
sage: w = sage.modules.vector_complex_double_dense.unpickle_v0(v.parent(), list(v),
↳ v.degree())
sage: v == w
True
```

`sage.modules.vector_complex_double_dense.unpickle_v1(parent, entries, degree, is_mutable=None)`
Create a complex double vector with the given parent, entries, degree, and mutability.

EXAMPLES:

```
sage: v = vector(CDF, [1,2,3])
sage: w = sage.modules.vector_complex_double_dense.unpickle_v1(v.parent(), list(v),
↳ v.degree(), v.is_immutable())
sage: v == w
True
```

8.10 Pickling for the old CDF vector class

AUTHORS:

- Jason Grout

8.11 Pickling for the old RDF vector class

AUTHORS:

- Jason Grout

9.1 Diamond cutting implementation

AUTHORS:

- Jan Poeschko (2012-07-02): initial version

`sage.modules.diamond_cutting.calculate_voronoi_cell(basis, radius=None, verbose=False)`

Calculate the Voronoi cell of the lattice defined by basis

INPUT:

- **basis** – embedded basis matrix of the lattice
- **radius** – radius of basis vectors to consider
- **verbose** – whether to print debug information

OUTPUT:

A Polyhedron instance.

EXAMPLES:

```
sage: from sage.modules.diamond_cutting import calculate_voronoi_cell
sage: V = calculate_voronoi_cell(matrix([[1, 0], [0, 1]]))
sage: V.volume()
1
```

`sage.modules.diamond_cutting.diamond_cut(V, GM, C, verbose=False)`

Perform diamond cutting on polyhedron V with basis matrix GM and radius C.

INPUT:

- **V** – polyhedron to cut from
- **GM** – half of the basis matrix of the lattice
- **C** – radius to use in cutting algorithm
- **verbose** – (default: False) whether to print debug information

OUTPUT:

A Polyhedron instance.

EXAMPLES:

```

sage: from sage.modules.diamond_cutting import diamond_cut
sage: V = Polyhedron([[0], [2]])
sage: GM = matrix([2])
sage: V = diamond_cut(V, GM, 4)
sage: V.vertices()
(A vertex at (2), A vertex at (0))

```

`sage.modules.diamond_cutting.jacobi(M)`

Compute the upper-triangular part of the Cholesky/Jacobi decomposition of the symmetric matrix M .

Let M be a symmetric $n \times n$ -matrix over a field F . Let $m_{i,j}$ denote the (i,j) -th entry of M for any $1 \leq i \leq n$ and $1 \leq j \leq n$. Then, the upper-triangular part computed by this method is the upper-triangular $n \times n$ -matrix Q whose (i,j) -th entry $q_{i,j}$ satisfies

$$q_{i,j} = \begin{cases} \frac{1}{q_{i,i}} (m_{i,j} - \sum_{r < i} q_{r,i} q_{r,j}) & i < j, \\ m_{i,i} - \sum_{r < i} q_{r,i}^2 & i = j, \\ 0 & i > j, \end{cases}$$

for all $1 \leq i \leq n$ and $1 \leq j \leq n$. (These equalities determine the entries of Q uniquely by recursion.) This matrix Q is defined for all M in a certain Zariski-dense open subset of the set of all $n \times n$ -matrices.

Note: This should be a method of matrices.

EXAMPLES:

```

sage: from sage.modules.diamond_cutting import jacobi
sage: jacobi(identity_matrix(3) * 4)
[4 0 0]
[0 4 0]
[0 0 4]

sage: def testall(M):
.....:     Q = jacobi(M)
.....:     for j in range(3):
.....:         for i in range(j):
.....:             if Q[i,j] * Q[i,i] != M[i,j] - sum(Q[r,i] * Q[r,j] * Q[r,r] for
↪r in range(i)):
.....:                 return False
.....:     for i in range(3):
.....:         if Q[i,i] != M[i,i] - sum(Q[r,i] ** 2 * Q[r,r] for r in range(i)):
.....:             return False
.....:     for j in range(i):
.....:         if Q[i,j] != 0:
.....:             return False
.....:     return True

sage: M = Matrix(QQ, [[8,1,5], [1,6,0], [5,0,3]])
sage: Q = jacobi(M); Q
[ 8  1/8  5/8]
[ 0 47/8 -5/47]
[ 0  0 -9/47]
sage: testall(M)

```

(continues on next page)

(continued from previous page)

```
True

sage: M = Matrix(QQ, [[3,6,-1,7],[6,9,8,5],[-1,8,2,4],[7,5,4,0]])
sage: testall(M)
True
```

`sage.modules.diamond_cutting.plane_inequality(v)`

Return the inequality for points on the same side as the origin with respect to the plane through v normal to v .

EXAMPLES:

```
sage: from sage.modules.diamond_cutting import plane_inequality
sage: ieq = plane_inequality([1, -1]); ieq
[2, -1, 1]
sage: ieq[0] + vector(ieq[1:]) * vector([1, -1])
0
```

9.2 Helper classes to implement tensor operations

Warning: This module is not meant to be used directly. It just provides functionality for other classes to implement tensor operations.

The `VectorCollection` constructs the basis of tensor products (and symmetric/exterior powers) in terms of a chosen collection of vectors that generate the vector space(s).

EXAMPLES:

```
sage: from sage.modules.tensor_operations import VectorCollection, TensorOperation
sage: V = VectorCollection([(1,0), (-1, 0), (1,2)], QQ, 2)
sage: W = VectorCollection([(1,1), (1,-1), (-1, 1)], QQ, 2)
sage: VW = TensorOperation([V, W], operation='product')
```

Here is the tensor product of two vectors:

```
sage: V.vectors()[0]
(1, 0)
sage: W.vectors()[1]
(1, -1)
```

In a convenient choice of basis, the tensor product is $(a, b) \otimes (c, d) = (ac, ad, bc, bd)$. In this example, it is one of the vectors of the vector collection `VW`

```
sage: VW.index_map(0, 1)
1
sage: VW.vectors()[VW.index_map(0, 1)]
(1, -1, 0, 0)

sage: rows = []
sage: for i, j in cartesian_product((range(3), range(3))):
.....:     v = V.vectors()[i]
```

(continues on next page)

(continued from previous page)

```

.....: w = W.vectors()[j]
.....: i_tensor_j = VW.index_map(i, j)
.....: vw = VW.vectors()[i_tensor_j]
.....: rows.append([i, v, j, w, i_tensor_j, vw])
sage: table(rows)
0  (1, 0)  0  (1, 1)  0  (1, 1, 0, 0)
0  (1, 0)  1  (1, -1) 1  (1, -1, 0, 0)
0  (1, 0)  2  (-1, 1) 2  (-1, 1, 0, 0)
1  (-1, 0) 0  (1, 1)  3  (-1, -1, 0, 0)
1  (-1, 0) 1  (1, -1) 2  (-1, 1, 0, 0)
1  (-1, 0) 2  (-1, 1) 1  (1, -1, 0, 0)
2  (1, 2)  0  (1, 1)  4  (1, 1, 2, 2)
2  (1, 2)  1  (1, -1) 5  (1, -1, 2, -2)
2  (1, 2)  2  (-1, 1) 6  (-1, 1, -2, 2)

```

class sage.modules.tensor_operations.**TensorOperation**(vector_collections, operation='product')
 Bases: [sage.modules.tensor_operations.VectorCollection](#)

Auxiliary class to compute the tensor product of two [VectorCollection](#) objects.

Warning: This class is only used as a base class for filtered vector spaces. You should not use it yourself.

INPUT:

- vector_collections – a nonempty list/tuple/iterable of [VectorCollection](#) objects.
- operation – string. The tensor operation. Currently allowed values are product, symmetric, and antisymmetric.

Todo: More general tensor operations (specified by Young tableaux) should be implemented.

EXAMPLES:

```

sage: from sage.modules.tensor_operations import VectorCollection, TensorOperation
sage: R = VectorCollection([(1,0), (1,2), (-1,-2)], QQ, 2)
sage: S = VectorCollection([(1,), (-1,)], QQ, 1)
sage: R_tensor_S = TensorOperation([R, S])
sage: R_tensor_S.index_map(0, 0)
0
sage: matrix(ZZ, 3, 2, lambda i,j: R_tensor_S.index_map(i, j))
[0 1]
[2 3]
[3 2]
sage: R_tensor_S.vectors()
((1, 0), (-1, 0), (1, 2), (-1, -2))

```

codomain()

The codomain of the index map.

OUTPUT:

A list of integers. The image of [index_map\(\)](#).

EXAMPLES:


```

sage: from sage.modules.tensor_operations import      ....:
↳ VectorCollection, TensorOperation
sage: R = VectorCollection([(1,0), (0,1), (-2,-3)], QQ, 2)
sage: detR = TensorOperation([R]*2, 'antisymmetric')
sage: sorted(detR.preimage())
[(0, 1), (0, 2), (1, 2)]
sage: sorted(detR.codomain())
[0, 1, 2]

```

index_map(*i)

Return the result of the tensor operation.

INPUT:

- **i* – list of integers. The indices (in the corresponding factor of the tensor operation) of the domain vector.

OUTPUT:

The index (in `vectors()`) of the image of the tensor product/operation acting on the domain vectors indexed by *i*.

None is returned if the tensor operation maps the generators to zero (usually because of antisymmetry).

EXAMPLES:

```

sage: from sage.modules.tensor_operations import      ....:
↳ VectorCollection, TensorOperation
sage: R = VectorCollection([(1,0), (1,2), (-1,-2)], QQ, 2)
sage: Sym3_R = TensorOperation([R]*3, 'symmetric')

```

The symmetric product of the first vector (1,0), the second vector (1,2), and the third vector (-1,-2) equals the vector with index number 4 (that is, the fifth) in the symmetric product vector collection:

```

sage: Sym3_R.index_map(0, 1, 2)
4

```

In suitable coordinates, this is the vector:

```

sage: Sym3_R.vectors()[4]
(-1, -4, -4, 0)

```

The product is symmetric:

```

sage: Sym3_R.index_map(2, 0, 1)
4
sage: Sym3_R.index_map(2, 1, 0)
4

```

As another example, here is the rank-2 determinant:

```

sage: from sage.modules.tensor_operations import      ....:
↳ VectorCollection, TensorOperation
sage: R = VectorCollection([(1,0), (0,1), (-2,-3)], QQ, 2)
sage: detR = TensorOperation([R]*2, 'antisymmetric')
sage: detR.index_map(1, 0)
0

```

(continues on next page)

(continued from previous page)

```
sage: detR.index_map(0, 1)
0
```

preimage()

A choice of pre-image multi-indices.

OUTPUT:

A list of multi-indices (tuples of integers) whose image is the entire image under the *index_map()*.

EXAMPLES:

```
sage: from sage.modules.tensor_operations import VectorCollection, TensorOperation
sage: R = VectorCollection([(1,0), (0,1), (-2,-3)], QQ, 2)
sage: detR = TensorOperation([R]*2, 'antisymmetric')
sage: sorted(detR.preimage())
[(0, 1), (0, 2), (1, 2)]
sage: sorted(detR.codomain())
[0, 1, 2]
```

class sage.modules.tensor_operations.**VectorCollection**(*vector_collection*, *base_ring*, *dim*)

Bases: *sage.modules.free_module.FreeModule_ambient_field*

An ordered collection of generators of a vector space.

This is like a list of vectors, but with extra argument checking.

Warning: This class is only used as a base class for filtered vector spaces. You should not use it yourself.

INPUT:

- *dim* – integer. The dimension of the ambient vector space.
- *base_ring* – a field. The base field of the ambient vector space.
- *rays* – any list/iterable of things than can be converted into vectors of the ambient vector space. These will be used to span the subspaces of the filtration. Must span the ambient vector space.

EXAMPLES:

```
sage: from sage.modules.tensor_operations import VectorCollection
sage: R = VectorCollection([(1,0), (0,1), (1,2)], QQ, 2); R
Vector space of dimension 2 over Rational Field
```

n_vectors()

Return the number of vectors

OUTPUT:

Integer.

EXAMPLES:

```
sage: from sage.modules.tensor_operations import VectorCollection
sage: V = VectorCollection([(1,0), (0,1), (1,2)], QQ, 2)
sage: V.n_vectors()
3
```

vectors()

Return the collection of vectors

OUTPUT:

A tuple of vectors. The vectors that were specified in the constructor, in the same order.

EXAMPLES:

```
sage: from sage.modules.tensor_operations import VectorCollection
sage: V = VectorCollection([(1,0), (0,1), (1,2)], QQ, 2)
sage: V.vectors()
((1, 0), (0, 1), (1, 2))
```

`sage.modules.tensor_operations.antisymmetrized_coordinate_sums(dim, n)`

Return formal anti-symmetrized sum of multi-indices

INPUT:

- `dim` – integer. The dimension (range of each index).
- `n` – integer. The total number of indices.

OUTPUT:

An anti-symmetrized formal sum of multi-indices (tuples of integers)

EXAMPLES:

```
sage: from sage.modules.tensor_operations import antisymmetrized_coordinate_sums
sage: antisymmetrized_coordinate_sums(3, 2)
((0, 1) - (1, 0), (0, 2) - (2, 0), (1, 2) - (2, 1))
```

`sage.modules.tensor_operations.symmetrized_coordinate_sums(dim, n)`

Return formal symmetrized sum of multi-indices

INPUT:

- `dim` – integer. The dimension (range of each index).
- `n` – integer. The total number of indices.

OUTPUT:

A symmetrized formal sum of multi-indices (tuples of integers)

EXAMPLES:

```
sage: from sage.modules.tensor_operations import symmetrized_coordinate_sums
sage: symmetrized_coordinate_sums(2, 2)
((0, 0), (0, 1) + (1, 0), (1, 1))
```

9.3 Iterators over finite submodules of a \mathbb{Z} -module

We iterate over the elements of a finite \mathbb{Z} -module. The action of \mathbb{Z} must be the natural one.

This class is intended to provide optimizations for the `sage.free_module.FreeModule_generic.__iter__()` method.

AUTHORS:

- Thomas Feulner (2012-08-31): initial version
- Punarbasu Purkayastha (2012-11-09): replaced the loop with recursion
- Thomas Feulner (2012-11-09): added functionality to enumerate cosets, `FiniteFieldsubspace_projPoint_iterator`

EXAMPLES:

```
sage: from sage.modules.finite_submodule_iter import FiniteZZsubmodule_iterator
sage: F.<x,y,z> = FreeAlgebra(GF(3),3)
sage: iter = FiniteZZsubmodule_iterator([x,y], [3,3])
sage: list(iter)
[0, x, 2*x, y, x + y, 2*x + y, 2*y, x + 2*y, 2*x + 2*y]
```

There is a specialization for subspaces over finite fields:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: iter = FiniteFieldsubspace_iterator(A)
sage: len(list(iter))
1024
```

The module also allows the iteration over cosets:

```
sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: v = random_vector(GF(4, 'a'), 100)
sage: iter = FiniteFieldsubspace_iterator(A, v)
sage: len(list(iter))
1024
```

class `sage.modules.finite_submodule_iter.FiniteFieldsubspace_iterator`

Bases: `sage.modules.finite_submodule_iter.FiniteZZsubmodule_iterator`

This class implements an iterator over the subspace of a vector space over a finite field. The subspace is generated by basis.

INPUT:

- **basis** – a list of vectors or a matrix with elements over a finite field. If a matrix is provided then it is not checked whether the matrix is full ranked. Similarly, if a list of vectors is provided, then the linear independence of the vectors is not checked.
- **coset_rep** (optional) – a vector in the same ambient space, if one aims to compute a coset of the vector space given by basis.
- **immutable** (optional; default: `False`) – set it to `True` to return immutable vectors.

EXAMPLES:

```

sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator
sage: A = random_matrix(GF(2), 10, 100)
sage: iter = FiniteFieldsubspace_iterator(A)
sage: len(list(iter))
1024
sage: X = random_matrix(GF(4, 'a'), 7, 100).row_space()
sage: s = list(X) # long time (5s on sage.math, 2013)
sage: t = list(FiniteFieldsubspace_iterator(X.basis())) # takes 0.31s
sage: sorted(t) == sorted(s) # long time
True

```

class sage.modules.finite_submodule_iter.FiniteFieldsubspace_projPoint_iterator

Bases: object

This class implements an iterator over the projective points of a vector space over a finite field. The vector space is generated by basis and need not to be equal to the full ambient space.

A projective point (= one dimensional subspace) P will be represented by a generator p . To ensure that all p will be normalized you can set the optional argument `normalize` to `True`.

INPUT:

- `basis` – a list of vectors or a matrix with elements over a finite field. If a matrix is provided then it is not checked whether the matrix is full ranked. Similarly, if a list of vectors is provided, then the linear independence of the vectors is not checked.
- `normalize` (optional; default: `False`) – boolean which indicates if the returned vectors should be normalized, i.e. the first nonzero coordinate is equal to 1.
- `immutable` (optional; default: `False`) – set it to `True` to return immutable vectors.

EXAMPLES:

```

sage: from sage.modules.finite_submodule_iter import FiniteFieldsubspace_iterator,
↪FiniteFieldsubspace_projPoint_iterator
sage: A = random_matrix(GF(4, 'a'), 5, 100)
sage: a = len(list(FiniteFieldsubspace_iterator(A)))
sage: b = len(list(FiniteFieldsubspace_projPoint_iterator(A)))
sage: b == (a-1)/3
True

```

Prove that the option `normalize == True` will only return normalized vectors.

```
sage: all(x.monic() == x for x in FiniteFieldsubspace_projPoint_iterator(A, True)) True
```

class sage.modules.finite_submodule_iter.FiniteZZsubmodule_iterator

Bases: object

Let G be an abelian group and suppose that (g_0, \dots, g_n) is a list of elements of G , whose additive orders are equal to m_i and $\sum_{i=0}^n x_i g_i = 0$ for $x_i \in \mathbb{Z}_{m_i}$ for $i \in \{0, \dots, n\}$ implies $x_i = 0$ for all i .

This class implements an iterator over the \mathbb{Z} -submodule $M = \{\sum_{i=0}^n x_i g_i\}$. If the independence condition from above is not fulfilled, we can still use this iterator to run over the elements. In this case the elements will occur multiple times.

Getting from one element of the submodule to another is performed by one single addition in G .

INPUT:

- `basis` - the elements (g_0, \dots, g_n)

- `order` (optional) - the additive_orders m_i of g_i .
- `coset_rep` (optional) - an element of g , if one aims to compute a coset of the \mathbf{Z} -submodule M .
- `immutable` (optional; default: `False`) - set it to `True` to return immutable elements. Setting this to `True` makes sense if the elements are vectors. See [FiniteFieldsubspace_iterator](#) for examples.

EXAMPLES:

```
sage: from sage.modules.finite_submodule_iter import FiniteZZsubmodule_iterator
sage: F.<x,y,z> = FreeAlgebra(GF(3),3)
sage: iter = FiniteZZsubmodule_iterator([x,y], [3,3])
sage: list(iter)
[0, x, 2*x, y, x + y, 2*x + y, 2*y, x + 2*y, 2*x + 2*y]
sage: iter = FiniteZZsubmodule_iterator([x,y], [3,3], z)
sage: list(iter)
[z, x + z, 2*x + z, y + z, x + y + z, 2*x + y + z, 2*y + z, x + 2*y + z, 2*x + 2*y,
↪ + z]
```

9.4 Miscellaneous module-related functions

AUTHORS:

- William Stein (2007-11-18)

`sage.modules.misc.gram_schmidt(B)`

Return the Gram-Schmidt orthogonalization of the entries in the list `B` of vectors, along with the matrix `mu` of Gram-Schmidt coefficients.

Note that the output vectors need not have unit length. We do this to avoid having to extract square roots.

Note: Use of this function is discouraged. It fails on linearly dependent input and its output format is not as natural as it could be. Instead, see `sage.matrix.matrix2.Matrix2.gram_schmidt()` which is safer and more general-purpose.

EXAMPLES:

```
sage: B = [vector([1,2,1/5]), vector([1,2,3]), vector([-1,0,0])]
sage: from sage.modules.misc import gram_schmidt
sage: G, mu = gram_schmidt(B)
sage: G
[(1, 2, 1/5), (-1/9, -2/9, 25/9), (-4/5, 2/5, 0)]
sage: G[0] * G[1]
0
sage: G[0] * G[2]
0
sage: G[1] * G[2]
0
sage: mu
[ 0 0 0]
[ 10/9 0 0]
[-25/126 1/70 0]
sage: a = matrix([])
```

(continues on next page)

(continued from previous page)

```
sage: a.gram_schmidt()
([], [])
sage: a = matrix([[],[],[],[]])
sage: a.gram_schmidt()
([], [])
```

Linearly dependent input leads to a zero dot product in a denominator. This shows that [trac ticket #10791](#) is fixed.

```
sage: from sage.modules.misc import gram_schmidt
sage: V = [vector(ZZ,[1,1]), vector(ZZ,[2,2]), vector(ZZ,[1,2])]
sage: gram_schmidt(V)
Traceback (most recent call last):
...
ValueError: linearly dependent input for module version of Gram-Schmidt
```


INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

m

sage.modules.complex_double_vector, 400
sage.modules.diamond_cutting, 401
sage.modules.fg_pid.fgp_element, 193
sage.modules.fg_pid.fgp_module, 175
sage.modules.fg_pid.fgp_morphism, 195
sage.modules.filtered_vector_space, 313
sage.modules.finite_submodule_iter, 408
sage.modules.fp_graded.element, 230
sage.modules.fp_graded.free_element, 211
sage.modules.fp_graded.free_homspace, 215
sage.modules.fp_graded.free_module, 199
sage.modules.fp_graded.free_morphism, 214
sage.modules.fp_graded.homspace, 247
sage.modules.fp_graded.module, 216
sage.modules.fp_graded.morphism, 233
sage.modules.fp_graded.steenrod.module, 249
sage.modules.fp_graded.steenrod.morphism, 253
sage.modules.free_module, 12
sage.modules.free_module_element, 76
sage.modules.free_module_homspace, 348
sage.modules.free_module_integer, 259
sage.modules.free_module_morphism, 351
sage.modules.free_quadratic_module, 268
sage.modules.free_quadratic_module_integer_symmetric,
280
sage.modules.matrix_morphism, 362
sage.modules.misc, 410
sage.modules.module, 9
sage.modules.multi_filtered_vector_space, 324
sage.modules.quotient_module, 129
sage.modules.real_double_vector, 400
sage.modules.submodule, 126
sage.modules.tensor_operations, 403
sage.modules.torsion_quadratic_module, 301
sage.modules.tutorial_free_modules, 3
sage.modules.vector_callable_symbolic_dense,
392
sage.modules.vector_complex_double_dense, 399
sage.modules.vector_double_dense, 392
sage.modules.vector_integer_dense, 381
sage.modules.vector_mod2_dense, 382
sage.modules.vector_modn_dense, 383
sage.modules.vector_rational_dense, 384
sage.modules.vector_real_double_dense, 398
sage.modules.vector_space_homspace, 333
sage.modules.vector_space_morphism, 336
sage.modules.vector_symbolic_dense, 385
sage.modules.with_basis.__init__, 137
sage.modules.with_basis.cell_module, 137
sage.modules.with_basis.indexed_element, 140
sage.modules.with_basis.invariant, 142
sage.modules.with_basis.morphism, 150
sage.modules.with_basis.representation, 168
sage.modules.with_basis.subquotient, 164

A

`additive_order()` (*sage.modules.fg_pid.fgp_element.FGP_Element* method), 193
`additive_order()` (*sage.modules.free_module_element.FreeModuleElement* method), 77
`all_submodules()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 302
`ambient()` (*sage.modules.with_basis.subquotient.QuotientModuleWithBasis* method), 165
`ambient()` (*sage.modules.with_basis.subquotient.SubmoduleWithBasis* method), 166
`ambient_module()` (*sage.modules.free_module.FreeModule_ambient* method), 17
`ambient_module()` (*sage.modules.free_module.FreeModule_submodule_with_basis_pid* method), 58
`ambient_module()` (*sage.modules.free_quadratic_module.FreeQuadraticModule_generic* method), 270
`ambient_module()` (*sage.modules.quotient_module.QuotientModule_free_ambient* method), 133
`ambient_module()` (*sage.modules.submodule.Submodule_free_ambient* method), 127
`ambient_vector_space()` (*sage.modules.filtered_vector_space.FilteredVectorSpace_class* method), 315
`ambient_vector_space()` (*sage.modules.free_module.FreeModule_ambient_domain* method), 22
`ambient_vector_space()` (*sage.modules.free_module.FreeModule_ambient_free* method), 23
`ambient_vector_space()` (*sage.modules.free_module.FreeModule_submodule_with_basis_pid* method), 59
`ambient_vector_space()` (*sage.modules.free_quadratic_module.FreeQuadraticModule_ambient* method), 269
`ambient_vector_space()` (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 326
`an_element()` (*sage.modules.fp_graded.free_module.FreeGradedModule* method), 204
`an_element()` (*sage.modules.fp_graded.homspace.FPModuleHomspace* method), 247
`an_element()` (*sage.modules.fp_graded.module.FPModule* method), 218
`annihilator()` (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 179
`antisymmetrized_coordinate_sums()` (*sage.modules.tensor_operations*), 407
`apply_map()` (*sage.modules.vector_symbolic_dense*), 391
`apply_map()` (*sage.modules.free_module_element.FreeModuleElement* method), 78
`are_linearly_dependent()` (*sage.modules.free_module.FreeModule_generic* method), 24
`automorphisms()` (*sage.modules.free_quadratic_module_integer_symmetric* method), 281

B

`b()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModuleElement* method), 311
`base_extend()` (*sage.modules.module.Module* method), 10
`base_field()` (*sage.modules.free_module.FreeModule_ambient_field* method), 23
`base_field()` (*sage.modules.free_module.FreeModule_generic* method), 25
`base_ring()` (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 180
`base_ring()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 365
`BaseIsomorphism1D` (class in *sage.modules.free_module_morphism*), 351
`BaseIsomorphism1D_from_FM` (class in *sage.modules.free_module_morphism*), 351
`BaseIsomorphism1D_to_FM` (class in *sage.modules.free_module_morphism*), 352
`basis()` (*sage.modules.free_module.FreeModule_ambient* method), 17
`basis()` (*sage.modules.free_module.FreeModule_generic* method), 25
`basis()` (*sage.modules.free_module.FreeModule_submodule_with_basis_pid* method), 59

basis() (*sage.modules.free_module_homspace.FreeModuleHomSpace* method), 348
basis_elements() (*sage.modules.fp_graded.free_module.FreeGradedFreeModule* method), 205
basis_elements() (*sage.modules.fp_graded.homspace.FreeGradedHomSpace* method), 247
basis_elements() (*sage.modules.fp_graded.module.FPModule* method), 218
basis_matrix() (*sage.modules.free_module.FreeModule_generic* method), 25
basis_seq() (in module *sage.modules.free_module*), 73
bilinear_form() (*sage.modules.with_basis.cell_module.CellModule* method), 138
bilinear_form_matrix() (*sage.modules.with_basis.cell_module.CellModule* method), 138
BKZ() (*sage.modules.free_module_integer.FreeModule_submodule_with_basis.Integer* method), 260
brown_invariant() (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 302
C
calculate_voronoi_cell() (in module *sage.modules.diamond_cutting*), 401
canonicalize_radical() (*sage.modules.vector_symbolic_dense.Vector_symbolic_dense* method), 386
cardinality() (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 180
cardinality() (*sage.modules.free_module.FreeModule_generic* method), 26
CellModule (class in *sage.modules.with_basis.cell_module*), 137
CellModule.Element (class in *sage.modules.with_basis.cell_module*), 138
cellular_algebra() (*sage.modules.with_basis.cell_module.CellModule* method), 138
change_ring() (*sage.modules.filtered_vector_space.FilteredVectorSpace* method), 315
change_ring() (*sage.modules.fp_graded.free_module.FreeGradedFreeModule* method), 205
change_ring() (*sage.modules.fp_graded.module.FPModule* method), 219
change_ring() (*sage.modules.fp_graded.morphism.FPModuleMorphism* method), 233
change_ring() (*sage.modules.free_module.FreeModule_abstract* method), 17
change_ring() (*sage.modules.free_module.FreeModule_submodule_with_basis_pid* method), 60
change_ring() (*sage.modules.free_module_element.FreeModuleElement* method), 79
change_ring() (*sage.modules.free_module_morphism.FreeModuleMorphism* method), 353
change_ring() (*sage.modules.free_quadratic_module.FreeQuadraticModule* method), 278
change_ring() (*sage.modules.module.Module* method), 10
change_ring() (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace* method), 326
characteristic_polynomial() (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 365
charpoly() (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 366
call_module_vector() (*sage.modules.free_module_integer.FreeModule_submodule_with_basis_pid* method), 262
codimension() (*sage.modules.free_module.FreeModule_generic* method), 26
codomain() (*sage.modules.tensor_operations.TensorOperation* method), 40
cokernel_basis_indices() (*sage.modules.basis.morphism.TriangularModuleMorphism* method), 159
cokernel_projection() (*sage.modules.fp_graded.morphism.FPModuleMorphism* method), 233
cokernel_projection() (*sage.modules.fp_graded.steenrod.morphism.SteenrodFPModuleMorphism* method), 253
cokernel_projection() (*sage.modules.with_basis.morphism.TriangularModuleMorphism* method), 160
column() (*sage.modules.free_module_element.FreeModuleElement* method), 79
complement() (*sage.modules.free_module.FreeModule_generic_field* method), 38
complex_vector() (*sage.modules.vector_double_dense.Vector_double_dense* method), 393
ComplexDoubleVectorSpace_class (class in *sage.modules.free_module*), 13
conjugate() (*sage.modules.free_module_element.FreeModuleElement* method), 80
connectivity() (*sage.modules.fp_graded.free_module.FreeGradedFreeModule* method), 206
connectivity() (*sage.modules.fp_graded.module.FPModule* method), 219
construct_from_dim_degree() (in module *sage.modules.filtered_vector_space*), 322
construct_from_generators() (in module *sage.modules.filtered_vector_space*), 323
construct_from_generators_indices() (in module *sage.modules.filtered_vector_space*), 323
construction() (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 180
construction() (*sage.modules.free_module.FreeModule_generic* method), 27
construction() (*sage.modules.free_module.FreeModule_submodule_with_basis_pid* method), 60

`method`), 60
`coordinate_module()`
 (`sage.modules.free_module.FreeModule_generic`
 `method`), 27
`coordinate_ring()` (`sage.modules.free_module.FreeModule_generic`
 `method`), 28
`coordinate_ring()` (`sage.modules.free_module.Module_free_ambient`
 `method`), 66
`coordinate_ring()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 81
`coordinate_vector()`
 (`sage.modules.fg_pid.fgp_module.FGP_Module_class`
 `method`), 180
`coordinate_vector()`
 (`sage.modules.free_module.FreeModule_ambient`
 `method`), 18
`coordinate_vector()`
 (`sage.modules.free_module.FreeModule_ambient_algebra`
 `method`), 22
`coordinate_vector()`
 (`sage.modules.free_module.FreeModule_generic`
 `method`), 28
`coordinate_vector()`
 (`sage.modules.free_module.FreeModule_submodule_field`
 `method`), 54
`coordinate_vector()`
 (`sage.modules.free_module.FreeModule_submodule_pid`
 `method`), 56
`coordinate_vector()`
 (`sage.modules.free_module.FreeModule_submodule_with_basis_pid`
 `method`), 61
`coordinates()` (`sage.modules.free_module.ComplexDoubleVectorSpace_class`
 `method`), 13
`coordinates()` (`sage.modules.free_module.FreeModule_generic`
 `method`), 29
`coordinates()` (`sage.modules.free_module.RealDoubleVectorSpace_class`
 `method`), 73
`coreduced()` (`sage.modules.with_basis.morphism.TriangularModuleMorphism`
 `method`), 160
`cover()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class`
 `method`), 181
`cover()` (`sage.modules.quotient_module.FreeModule_ambient_field_quotient`
 `method`), 131
`cover()` (`sage.modules.quotient_module.QuotientModule_free_submodule`
 `method`), 133
`create_key()` (`sage.modules.free_module.FreeModuleFactor`
 `method`), 17
`create_object()` (`sage.modules.free_module.FreeModuleFactor`
 `method`), 17
`cross_product()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 81
`cross_product_matrix()`
 (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 82
`curl()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 83

D

`decomposition()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract`
 `method`), 366
`defining_homomorphism()`
 (`sage.modules.fp_graded.module.FPModule`
 `method`), 220
`degree()` (`sage.modules.fp_graded.element.FPElement`
 `method`), 230
`degree()` (`sage.modules.fp_graded.free_element.FreeGradedModuleElement`
 `method`), 211
`degree()` (`sage.modules.fp_graded.free_morphism.FreeGradedModuleMorphism`
 `method`), 214
`degree()` (`sage.modules.fp_graded.morphism.FPModuleMorphism`
 `method`), 234
`degree()` (`sage.modules.free_module.Module_free_ambient`
 `method`), 66
`degree()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 83
`denominator()` (`sage.modules.free_module.FreeModule_generic_pid`
 `method`), 47
`denominator()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 84
`denominator()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 108
`dense_coefficient_list()`
 (`sage.modules.fp_graded.element.FPElement`
 `method`), 230
`dense_coefficient_list()`
 (`sage.modules.fp_graded.free_element.FreeGradedModuleElement`
 `method`), 212
`dense_module()` (`sage.modules.free_module.FreeModule_generic`
 `method`), 29
`dense_vector()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 84
`derivate()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 84
`der()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract`
 `method`), 367
`determinant()` (`sage.modules.free_quadratic_module.FreeQuadraticModule`
 `method`), 270
`diagonal_module_morphism` (class in
 `sage.modules.with_basis.morphism`), 152
`diamond_cut()` (in module
 `sage.modules.diamond_cutting`), 401
`div()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 84
`div()` (`sage.modules.free_module_element.FreeModuleElement_generic`
 `method`), 108
`diff()` (`sage.modules.free_module_element.FreeModuleElement`
 `method`), 85

`dimension()` (`sage.modules.free_module.FreeModule_generic`
`method`), 30
`direct_sum()` (`sage.modules.filtered_vector_space.FilteredVectorSpace`
`method`), 316
`direct_sum()` (`sage.modules.free_module.FreeModule_generic`
`method`), 30
`direct_sum()` (`sage.modules.free_quadratic_module_integer_symmetric`
`method`), 283
`direct_sum()` (`sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace`
`method`), 326
`discriminant()` (`sage.modules.free_module.FreeModule_generic`
`method`), 30
`discriminant()` (`sage.modules.free_module_integer.FreeModule_submodule_with_basis_integer`
`method`), 262
`discriminant()` (`sage.modules.free_quadratic_module.FreeQuadraticModule_integer_free`
`method`), 271
`discriminant_group()`
`(sage.modules.free_quadratic_module_integer_symmetric`
`method`), 283
`div()` (`sage.modules.free_module_element.FreeModuleElement`
`method`), 85
`dot_product()` (`sage.modules.free_module_element.FreeModuleElement`
`method`), 86
`dual()` (`sage.modules.filtered_vector_space.FilteredVectorSpace`
`method`), 316
`dual()` (`sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace`
`method`), 327
`dual_lattice()` (`sage.modules.free_quadratic_module_integer_symmetric`
`method`), 284
E
`echelon_coordinate_vector()`
`(sage.modules.free_module.FreeModule_ambient`
`method`), 18
`echelon_coordinate_vector()`
`(sage.modules.free_module.FreeModule_submodule_with_basis_pid`
`method`), 61
`echelon_coordinates()`
`(sage.modules.free_module.FreeModule_ambient`
`method`), 18
`echelon_coordinates()`
`(sage.modules.free_module.FreeModule_submodule_field`
`method`), 54
`echelon_coordinates()`
`(sage.modules.free_module.FreeModule_submodule_with_basis_pid`
`method`), 61
`echelon_to_user_matrix()`
`(sage.modules.free_module.FreeModule_submodule_with_basis_pid`
`method`), 62
`echelonized_basis()`
`(sage.modules.free_module.FreeModule_ambient`
`method`), 19
`echelonized_basis()`
`(sage.modules.free_module.FreeModule_submodule_with_basis_pid`
`method`), 62

F

- `free_relations()` (*sage.modules.quotient_module.QuotientModule_free*
method), 134
- `fcg()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract*
method), 367
- `fft()` (*sage.modules.vector_double_dense.Vector_double_dense*
method), 393
- `FGP_Element` (class in *sage.modules.fg_pid.fgp_element*), 193
- `FGP_Homset()` (in module *sage.modules.fg_pid.fgp_morphism*), 195
- `FGP_Homset_class` (class in *sage.modules.fg_pid.fgp_morphism*), 195
- `FGP_Module()` (in module *sage.modules.fg_pid.fgp_module*), 178
- `FGP_Module_class` (class in *sage.modules.fg_pid.fgp_module*), 178
- `FGP_Morphism` (class in *sage.modules.fg_pid.fgp_morphism*), 195
- `FilteredVectorSpace()` (in module *sage.modules.filtered_vector_space*), 314
- `FilteredVectorSpace_class` (class in *sage.modules.filtered_vector_space*), 315
- `FiniteDimensionalInvariantModule` (class in *sage.modules.with_basis.invariant*), 142
- `FiniteDimensionalInvariantModule.Element`
 (class in *sage.modules.with_basis.invariant*), 145
- `FiniteDimensionalTwistedInvariantModule` (class
 in *sage.modules.with_basis.invariant*), 145
- `FiniteDimensionalTwistedInvariantModule.Element`
 (class in *sage.modules.with_basis.invariant*), 149
- `FiniteFieldsubspace_iterator` (class in *sage.modules.finite_submodule_iter*), 408
- `FiniteFieldsubspace_projPoint_iterator` (class
 in *sage.modules.finite_submodule_iter*), 409
- `FiniteZZsubmodule_iterator` (class in *sage.modules.finite_submodule_iter*), 409
- `fp_module()` (*sage.modules.fp_graded.free_morphism.FreeGradedModuleMorphism*
method), 215
- `fp_module()` (*sage.modules.fp_graded.morphism.FPModuleMorphism*
method), 234
- `FPElement` (class in *sage.modules.fp_graded.element*), 230
- `FPModule` (class in *sage.modules.fp_graded.module*), 216
- `FPModuleHomspace` (class in *sage.modules.fp_graded.homspace*), 247
- `FPModuleMorphism` (class in *sage.modules.fp_graded.morphism*), 233
- `free_cover()` (*sage.modules.quotient_module.QuotientModule_free*
method), 133
- `free_module()` (*sage.modules.free_module.FreeModule_generic*
method), 31
- `free_module_element()` (in module *sage.modules.free_module_element*), 110
- `FreeGradedModule` (class in *sage.modules.fp_graded.free_module*), 203
- `FreeGradedModuleElement` (class in *sage.modules.fp_graded.free_element*), 211
- `FreeGradedModuleHomspace` (class in *sage.modules.fp_graded.free_homspace*), 216
- `FreeGradedModuleMorphism` (class in *sage.modules.fp_graded.free_morphism*), 214
- `FreeModule()` (in module *sage.modules.free_module*), 14
- `FreeModule_ambient` (class in *sage.modules.free_module*), 17
- `FreeModule_ambient_domain` (class in *sage.modules.free_module*), 22
- `FreeModule_ambient_field` (class in *sage.modules.free_module*), 23
- `FreeModule_ambient_field_quotient` (class in *sage.modules.quotient_module*), 129
- `FreeModule_ambient_pid` (class in *sage.modules.free_module*), 23
- `FreeModule_generic` (class in *sage.modules.free_module*), 23
- `FreeModule_generic_domain` (class in *sage.modules.free_module*), 38
- `FreeModule_generic_field` (class in *sage.modules.free_module*), 38
- `FreeModule_generic_pid` (class in *sage.modules.free_module*), 47
- `FreeModule_submodule_field` (class in *sage.modules.free_module*), 53
- `FreeModule_submodule_pid` (class in *sage.modules.free_module*), 55
- `FreeModule_submodule_with_basis_field` (class in *sage.modules.free_module*), 56
- `FreeModule_submodule_with_basis_integer` (class
 in *sage.modules.free_module_integer*), 259
- `FreeModule_submodule_with_basis_pid` (class in *sage.modules.free_module*), 57
- `FreeModuleElement` (class in *sage.modules.free_module_element*), 77
- `FreeModuleElement_generic_dense` (class in *sage.modules.free_module_element*), 107
- `FreeModuleElement_generic_sparse` (class in *sage.modules.free_module_element*), 108
- `FreeModuleFactory` (class in *sage.modules.free_module*), 17
- `FreeModuleHomspace` (class in *sage.modules.free_module_homspace*), 348
- `FreeModuleMorphism` (class in *sage.modules.free_module_morphism*), 353

FreeQuadraticModule() (in module *sage.modules.free_quadratic_module*), 268

FreeQuadraticModule_ambient (class in *sage.modules.free_quadratic_module*), 269

FreeQuadraticModule_ambient_domain (class in *sage.modules.free_quadratic_module*), 269

FreeQuadraticModule_ambient_field (class in *sage.modules.free_quadratic_module*), 269

FreeQuadraticModule_ambient_pid (class in *sage.modules.free_quadratic_module*), 270

FreeQuadraticModule_generic (class in *sage.modules.free_quadratic_module*), 270

FreeQuadraticModule_generic_field (class in *sage.modules.free_quadratic_module*), 272

FreeQuadraticModule_generic_pid (class in *sage.modules.free_quadratic_module*), 273

FreeQuadraticModule_integer_symmetric (class in *sage.modules.free_quadratic_module_integer_symmetric*), 280

FreeQuadraticModule_submodule_field (class in *sage.modules.free_quadratic_module*), 274

FreeQuadraticModule_submodule_pid (class in *sage.modules.free_quadratic_module*), 275

FreeQuadraticModule_submodule_with_basis_field (class in *sage.modules.free_quadratic_module*), 276

FreeQuadraticModule_submodule_with_basis_pid (class in *sage.modules.free_quadratic_module*), 277

function() (*sage.modules.free_module_element.FreeModuleElement* method), 107

G

gen() (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 181

gen() (*sage.modules.fp_graded.free_module.FreeGradedModule* method), 207

gen() (*sage.modules.fp_graded.module.FPModule* method), 221

gen() (*sage.modules.free_module.FreeModule_ambient* method), 20

gen() (*sage.modules.free_module.FreeModule_generic* method), 31

gen() (*sage.modules.quotient_module.QuotientModule_free_ambient* method), 134

gen() (*sage.modules.submodule.Submodule_free_ambient* method), 127

generator() (*sage.modules.fp_graded.free_module.FreeGradedModule* method), 207

generator() (*sage.modules.fp_graded.module.FPModule* method), 221

generator_degrees() (*sage.modules.fp_graded.free_module.FreeGradedModule* method), 207

generator_degrees() (*sage.modules.fp_graded.module.FPModule* method), 221

generators() (*sage.modules.fp_graded.free_module.FreeGradedModule* method), 208

generators() (*sage.modules.fp_graded.module.FPModule* method), 222

generators_matrix() (*sage.modules.submodule.Submodule_free_ambient* method), 128

gens() (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 182

gens() (*sage.modules.fp_graded.module.FPModule* method), 222

gens() (*sage.modules.free_module.FreeModule_generic* method), 31

gens() (*sage.modules.quotient_module.QuotientModule_free_ambient* method), 134

gens() (*sage.modules.submodule.Submodule_free_ambient* method), 128

gens() (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 303

gens_to_smith() (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 182

gens_vector() (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 183

genus() (*sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric* method), 284

genus() (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 304

get() (*sage.modules.free_module_element.FreeModuleElement* method), 87

get_degree() (*sage.modules.filtered_vector_space.FilteredVectorSpace_class* method), 317

get_degree() (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 327

get_filtration() (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 328

graded() (*sage.modules.filtered_vector_space.FilteredVectorSpace_class* method), 317

graded() (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 328

gram_matrix() (*sage.modules.free_module.FreeModule_generic* method), 31

gram_matrix() (*sage.modules.free_quadratic_module.FreeQuadraticModule* method), 271

gram_matrix_bilinear() (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 304

gram_matrix_quadratic() (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 304

gram_schmidt() (in module *sage.modules.misc*), 410

H

`index_map()` (`sage.modules.tensor_operations.TensorOperation` method), 405
`index_set()` (`sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace` method), 87
`hamming_weight()` (`sage.modules.free_module_element.FreeModuleElement` method), 328
`hamming_weight()` (`sage.modules.free_module_element.FreeModuleElement_generic_sparse` method), 108
`hamming_weight()` (`sage.modules.vector_mod2_dense.Vector_mod2_dense` method), 382
`has_canonical_map_to()` (`sage.modules.free_module_element.FreeModuleElement` method), 89
`has_relations()` (`sage.modules.fp_graded.free_module.FreeGradedModule` method), 311
`has_relations()` (`sage.modules.fp_graded.module.FPModule` method), 208
`has_relations()` (`sage.modules.free_module.FreeModule_generic` method), 32
`has_user_basis()` (`sage.modules.free_module.FreeModule_generic` method), 32
`has_user_basis()` (`sage.modules.free_module.FreeModule_submodule_field` method), 271
`has_user_basis()` (`sage.modules.free_module.FreeModule_submodule_pid` method), 55
`has_user_basis()` (`sage.modules.free_module.FreeModule_submodule_pid` method), 56
`has_user_basis()` (`sage.modules.free_module.FreeModule_submodule_with_basis_pid` method), 63
`hermitian_inner_product()` (`sage.modules.free_module_element.FreeModuleElement` method), 87
`HKZ()` (`sage.modules.free_module_integer.FreeModule_submodule_with_basis_integer` method), 260
`hom()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 184
`hom()` (`sage.modules.free_module.FreeModule_generic` method), 32
`homology()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` method), 235

I
`identity()` (`sage.modules.fp_graded.homspace.FPModuleHomspace` method), 248
`identity()` (`sage.modules.free_module_homspace.FreeModuleHomspace` method), 349
`im_gens()` (`sage.modules.fg_pid.fgp_morphism.FGP_Morphism` method), 196
`image()` (`sage.modules.fg_pid.fgp_morphism.FGP_Morphism` method), 196
`image()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` method), 236
`image()` (`sage.modules.fp_graded.steenrod.morphism.SteenrodFPModuleMorphism` method), 254
`image()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 367
`index_in()` (`sage.modules.free_module.FreeModule_generic_pid` method), 47
`index_in_saturation()` (`sage.modules.free_module.FreeModule_generic_pid` method), 48
`inner_product()` (`sage.modules.free_module_element.FreeModuleElement` method), 89
`inner_product()` (`sage.modules.torsion_quadratic_module.TorsionQuadraticModule` method), 311
`inner_product_matrix()` (`sage.modules.free_module.FreeModule_generic` method), 32
`inner_product_matrix()` (`sage.modules.free_quadratic_module.FreeQuadraticModule_generic` method), 271
`InnerProductSpace()` (`sage.modules.free_quadratic_module` method), 278
`IntegerLattice()` (`sage.modules.free_module_integer` method), 265
`integral()` (`sage.modules.free_module_element.FreeModuleElement` method), 90
`IntegralLattice()` (`sage.modules.free_quadratic_module_integer_symmetric` method), 292
`IntegralLatticeDirectSum()` (`sage.modules.free_quadratic_module_integer_symmetric` method), 295
`IntegralLatticeGluing()` (`sage.modules.free_quadratic_module_integer_symmetric` method), 296
`integrate()` (`sage.modules.free_module_element.FreeModuleElement` method), 90
`intersection()` (`sage.modules.free_module.FreeModule_generic_field` method), 39
`intersection()` (`sage.modules.free_module.FreeModule_generic_pid` method), 48
`inv_fft()` (`sage.modules.vector_double_dense.Vector_double_dense` method), 394
`invariant_module()` (`sage.modules.with_basis.representation.Representation` method), 170
`invariants()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 186
`inverse()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 368
`inverse_image()` (`sage.modules.fg_pid.fgp_morphism.FGP_Morphism` method), 197
`inverse_image()` (`sage.modules.free_module_morphism.FreeModuleMorphism` method), 356
`is_ambient()` (`sage.modules.free_module.FreeModule_ambient` method), 20
`is_ambient()` (`sage.modules.free_module.FreeModule_generic_pid` method), 33

`is_ambient()` (*sage.modules.free_module.FreeModule_submodule_with_basis* method), 57
`is_bijjective()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 370
`is_constant()` (*sage.modules.filtered_vector_space.FilteredVectorSpace_class* method), 318
`is_constant()` (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 329
`is_dense()` (*sage.modules.free_module.FreeModule_generic* method), 33
`is_dense()` (*sage.modules.free_module_element.FreeModuleElement* method), 90
`is_equal_function()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 371
`is_even()` (*sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModule_integer_symmetric* method), 284
`is_exhaustive()` (*sage.modules.filtered_vector_space.FilteredVectorSpace_class* method), 318
`is_exhaustive()` (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 329
`is_FGP_Module()` (in module *sage.modules.fg_pid.fgp_module*), 192
`is_FilteredVectorSpace()` (in module *sage.modules.filtered_vector_space*), 323
`is_finite()` (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 186
`is_finite()` (*sage.modules.free_module.FreeModule_generic* method), 33
`is_FreeModule()` (in module *sage.modules.free_module*), 74
`is_FreeModuleElement()` (in module *sage.modules.free_module_element*), 115
`is_FreeModuleHomspace()` (in module *sage.modules.free_module_homspace*), 350
`is_FreeModuleMorphism()` (in module *sage.modules.free_module_morphism*), 362
`is_FreeQuadraticModule()` (in module *sage.modules.free_quadratic_module*), 279
`is_full()` (*sage.modules.free_module.FreeModule_generic* method), 34
`is_genus()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule* method), 305
`is_identity()` (*sage.modules.fp_graded.morphism.FPModuleMorphism* method), 237
`is_identity()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 372
`is_injective()` (*sage.modules.fp_graded.morphism.FPModuleMorphism* method), 238
`is_injective()` (*sage.modules.fp_graded.steenrod.morphism.SteenrodFPModuleMorphism* method), 255
`is_injective()` (*sage.modules.free_module_morphism.BaseIsomorphism* method), 351
`is_injective()` (*sage.modules.matrix_morphism.MatrixMorphism* method), 108
`is_invertible()` (*sage.modules.vector_space_morphism.VectorSpaceMorphism* method), 343
`is_MatrixMorphism()` (in module *sage.modules.matrix_morphism*), 379
`is_Module()` (in module *sage.modules.module*), 11
`is_multiplicative()` (*sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModule_integer_symmetric* method), 285
`is_separating()` (*sage.modules.filtered_vector_space.FilteredVectorSpace_class* method), 319
`is_separating()` (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class* method), 329
`is_sparse()` (*sage.modules.free_module.Module_free_ambient* method), 66
`is_sparse()` (*sage.modules.free_module_element.FreeModuleElement* method), 91
`is_submodule()` (*sage.modules.fg_pid.fgp_module.FGP_Module_class* method), 187
`is_submodule()` (*sage.modules.free_module.FreeModule_generic* method), 33
`is_submodule()` (*sage.modules.free_module.Module_free_ambient* method), 66
`is_submodule()` (*sage.modules.with_basis.subquotient.SubmoduleWithBasis* method), 166
`is_subspace()` (*sage.modules.free_module.FreeModule_generic_field* method), 40
`is_surjective()` (*sage.modules.fp_graded.morphism.FPModuleMorphism* method), 238
`is_surjective()` (*sage.modules.free_module_morphism.BaseIsomorphism* method), 351
`is_surjective()` (*sage.modules.matrix_morphism.MatrixMorphism* method), 364
`is_trivial()` (*sage.modules.fp_graded.free_module.FreeGradedModule* method), 208
`is_trivial()` (*sage.modules.fp_graded.module.FPModule* method), 223
`is_unimodular()` (*sage.modules.free_module_integer.FreeModule_submodule* method), 262
`is_vector()` (*sage.modules.free_module_element.FreeModuleElement* method), 91
`is_VectorSpace()` (in module *sage.modules.module*), 11
`is_VectorSpaceHomspace()` (in module *sage.modules.vector_space_homspace*), 336
`is_VectorSpaceMorphism()` (in module *sage.modules.vector_space_morphism*), 343
`is_zero()` (*sage.modules.fp_graded.morphism.FPModuleMorphism* method), 238
`is_zero()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract* method), 372
`items()` (*sage.modules.free_module_element.FreeModuleElement* method), 91
`items()` (*sage.modules.free_module_element.FreeModuleElement_generic* method), 108

`iteritems()` (`sage.modules.free_module_element.FreeModuleElement` method), 91
`iteritems()` (`sage.modules.free_module_element.FreeModuleElement` method), 109
J
`jacobi()` (in module `sage.modules.diamond_cutting`), 402
K
`kernel()` (`sage.modules.fg_pid.fgp_morphism.FGP_Morphism` method), 197
`kernel()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 373
`kernel_inclusion()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` method), 239
`kernel_inclusion()` (`sage.modules.fp_graded.steenrod.morphism.SteenrodFPModuleMorphism` method), 255
L
`lift()` (`sage.modules.fg_pid.fgp_element.FGP_Element` method), 194
`lift()` (`sage.modules.fg_pid.fgp_morphism.FGP_Morphism` method), 198
`lift()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` method), 240
`lift()` (`sage.modules.free_module_element.FreeModuleElement` method), 91
`lift()` (`sage.modules.free_module_morphism.FreeModuleMorphism` method), 358
`lift()` (`sage.modules.quotient_module.FreeModule_ambient_field_quotient` method), 131
`lift()` (`sage.modules.with_basis.subquotient.QuotientModuleWithBasis` method), 165
`lift()` (`sage.modules.with_basis.subquotient.SubmoduleWithBasis` method), 167
`lift_centered()` (`sage.modules.free_module_element.FreeModuleElement` method), 92
`lift_map()` (`sage.modules.quotient_module.FreeModule_ambient_field_quotient` method), 131
`lift_to_free()` (`sage.modules.fp_graded.element.FPElement` method), 231
`lift_to_free()` (`sage.modules.fp_graded.free_element.FreeGradedModuleElement` method), 212
`linear_combination_of_basis()` (`sage.modules.free_module.FreeModule_ambient` method), 20
`linear_combination_of_basis()` (`sage.modules.free_module.FreeModule_submodule_with_basis_pid` method), 64
`linear_combination_of_smith_form_gens()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 187
`linear_dependence()` (`sage.modules.free_module.FreeModule_generic_field` method), 40
`linear_transformation()` (in module `sage.modules.vector_space_morphism`), 344
`list()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 187
`list()` (`sage.modules.free_module_element.FreeModuleElement` method), 92
`list()` (`sage.modules.free_module_element.FreeModuleElement_generic` method), 107
`list()` (`sage.modules.free_module_element.FreeModuleElement_generic` method), 109
`list()` (`sage.modules.vector_integer_dense.Vector_integer_dense` method), 381
`list()` (`sage.modules.vector_mod2_dense.Vector_mod2_dense` method), 383
`list()` (`sage.modules.vector_rational_dense.Vector_rational_dense` method), 385
`list_from_positions()` (`sage.modules.free_module_element.FreeModuleElement` method), 93
`LLL()` (`sage.modules.free_module_integer.FreeModule_submodule_with_basis` method), 261
`LLL()` (`sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric` method), 281
`LLL()` (`sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric` method), 285
`local_modification()` (in module `sage.modules.free_quadratic_module_integer_symmetric`), 300
M
`make_FreeModuleElement_generic_dense()` (in module `sage.modules.free_module_element`), 116
`make_FreeModuleElement_generic_dense_v1()` (in module `sage.modules.free_module_element`), 116
`make_FreeModuleElement_generic_sparse()` (in module `sage.modules.free_module_element`), 116
`make_FreeModuleElement_generic_sparse_v1()` (in module `sage.modules.free_module_element`), 116
`matrix()` (`sage.modules.free_module.FreeModule_generic` method), 35
`matrix()` (`sage.modules.matrix_morphism.MatrixMorphism` method), 364
`matrix()` (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 374
`matrix()` (`sage.modules.submodule.Submodule_free_ambient` method), 128

MatrixMorphism	(class in sage.modules.matrix_morphism), 363
MatrixMorphism_abstract	(class in sage.modules.matrix_morphism), 365
max()	(<i>sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric</i> .method), 285
max_degree()	(<i>sage.modules.filtered_vector_space.FilteredVectorSpace</i> .method), 319
max_degree()	(<i>sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace</i> .method), 330
maximal_overlattice()	(<i>sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric</i> .method), 286
maximum()	(<i>sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric</i> .method), 286
mean()	(<i>sage.modules.vector_double_dense.VectorDoubleDense</i> .method), 394
min()	(<i>sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric</i> .method), 286
min_degree()	(<i>sage.modules.filtered_vector_space.FilteredVectorSpace</i> .method), 319
min_degree()	(<i>sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace</i> .method), 330
minimal_polynomial()	(<i>sage.modules.free_module_morphism.FreeModuleMorphism</i> .method), 359
minimal_presentation()	(<i>sage.modules.fp_graded.free_module.FreeGradedModuleFreeElement</i> .method), 208
minimal_presentation()	(<i>sage.modules.fp_graded.module.FPModule</i> .method), 223
minimum()	(<i>sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric</i> .method), 286
minpoly()	(<i>sage.modules.free_module_morphism.FreeModuleMorphism</i> .method), 360
Mod()	(<i>sage.modules.free_module_element.FreeModuleElement</i> .method), 77
module	<ul style="list-style-type: none">sage.modules.complex_double_vector, 400sage.modules.diamond_cutting, 401sage.modules.fg_pid.fgp_element, 193sage.modules.fg_pid.fgp_module, 175sage.modules.fg_pid.fgp_morphism, 195sage.modules.filtered_vector_space, 313sage.modules.finite_submodule_iter, 408sage.modules.fp graded.element, 230sage.modules.fp graded.free_element, 211sage.modules.fp graded.free_homspace, 215sage.modules.fp graded.free_module, 199sage.modules.fp graded.free_morphism, 214sage.modules.fp graded.homspace, 247sage.modules.fp graded.module, 216sage.modules.fp graded.morphism, 233
	<ul style="list-style-type: none">sage.modules.fp_graded.steenrod.module, 249sage.modules.fp_graded.steenrod.morphism, 253SageModulesFreeModuleSymmetric, 12sage.modules.free_module_element, 76sage.modules.free_module_homspace, 348sage.modules.free_module_integer, 259EdgeVertexSpaceFreeModuleMorphism, 351sage.modules.free_quadratic_module, 268sage.modules.free_quadratic_module_integer_symmetric, 280sage.modules.matrix_morphism, 362sage.modules.module, 9sage.modules.multi_filtered_vector_space, 324sage.modules.quadratic_integers_module, 400sage.modules.real_double_vector, 400sage.modules.submodule, 126sage.modules.tensor_operations, 403EdgeVertexSpaceFreeQuadraticModule, 301sage.modules.tutorial_free_modules, 3sage.modules.vector_callable_symbolic_dense, 392sage.modules.vector_complex_double_dense, 399sage.modules.vector_double_dense, 392sage.modules.vector_integer_dense, 381sage.modules.vector_mod2_dense, 382sage.modules.vector_modn_dense, 383sage.modules.vector_real_double_dense, 384sage.modules.with_basis.__init__, 137sage.modules.with_basis.cell_module, 137sage.modules.with_basis.indexed_element, 140sage.modules.with_basis.invariant, 142sage.modules.with_basis.morphism, 150sage.modules.with_basis.representation, 168sage.modules.with_basis.subquotient, 164Module (<i>class in sage.modules.module</i>), 10Module_free_ambient (<i>class in sage.modules.free_module</i>), 65ModuleMorphism (<i>class in sage.modules.with_basis.morphism</i>), 152ModuleMorphismByLinearity (<i>class in sage.modules.with_basis.morphism</i>), 153

ModuleMorphismFromFunction (class in `sage.modules.with_basis.morphism`), 154
ModuleMorphismFromMatrix (class in `sage.modules.with_basis.morphism`), 154
monic() (`sage.modules.free_module_element.FreeModuleElement` method), 93
monomial() (`sage.modules.fp_graded.module.FPModule` method), 224
monomial_coefficients() (`sage.modules.free_module_element.FreeModuleElement` method), 93
monomial_coefficients() (`sage.modules.free_module_element.FreeModuleElement` method), 109
monomial_coefficients() (`sage.modules.with_basis.indexed_element.IndexedFreeModuleElement` method), 140
MultiFilteredVectorSpace() (in `sage.modules.multi_filtered_vector_space`), 325
MultiFilteredVectorSpace_class (class in `sage.modules.multi_filtered_vector_space`), 325
N
n_vectors() (`sage.modules.tensor_operations.VectorCollection` method), 406
ngens() (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 187
ngens() (`sage.modules.free_module.FreeModule_generic` method), 35
nintegral() (`sage.modules.free_module_element.FreeModuleElement` method), 94
nintegrate() (`sage.modules.free_module_element.FreeModuleElement` method), 94
nonembedded_free_module() (`sage.modules.free_module.FreeModule_generic` method), 35
nonzero_bilinear_form() (`sage.modules.with_basis.cell_module.CellModule` method), 138
nonzero_positions() (`sage.modules.free_module_element.FreeModuleElement` method), 94
nonzero_positions() (`sage.modules.free_module_element.FreeModuleElement_generic_sparse` method), 110
norm() (`sage.modules.free_module_element.FreeModuleElement` method), 95
norm() (`sage.modules.vector_double_dense.Vector_double_dense` method), 394
normal_form() (`sage.modules.torsion_quadratic_module.TorsionQuadraticModule` method), 305
normalize() (`sage.modules.fp_graded.element.FPElement` method), 231
normalize_degree() (in `sage.modules.filtered_vector_space`), 324
normalized() (`sage.modules.free_module_element.FreeModuleElement` method), 96
nullity() (`sage.modules.matrix_morphism.MatrixMorphism_abstract` method), 374
numerical_approx() (`sage.modules.free_module_element.FreeModuleElement` method), 96
numerical_approx() (`sage.modules.free_module_element.FreeModuleElement` method), 110
numrank() (`sage.modules.free_module_element.FreeModuleElement` method), 98
O
on_basis() (`sage.modules.with_basis.morphism.ModuleMorphismByLine` method), 153
optimized() (`sage.modules.fg_pid.fgp_module.FGP_Module_class` method), 188
orthogonal_complement() (`sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric` method), 287
orthogonal_group() (`sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric` method), 287
orthogonal_group() (`sage.modules.torsion_quadratic_module.TorsionQuadraticModule` method), 307
orthogonal_submodule_to() (`sage.modules.torsion_quadratic_module.TorsionQuadraticModule` method), 308
outer_product() (`sage.modules.free_module_element.FreeModuleElement` method), 99
overlattice() (`sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric` method), 289
P
pairwise_product() (`sage.modules.free_module_element.FreeModuleElement` method), 101
plane_inequality() (in `sage.modules.diamond_cutting`), 403
plot() (`sage.modules.free_module_element.FreeModuleElement` method), 102
plot_step() (`sage.modules.free_module_element.FreeModuleElement` method), 103
pointwise_inverse() (`sage.modules.with_basis.morphism.PointwiseInverseFunction` method), 155
pointwise_inverse_function() (in `sage.modules.with_basis.morphism`), 164
PointwiseInverseFunction (class in `sage.modules.with_basis.morphism`), 155
preimage() (`sage.modules.tensor_operations.TensorOperation` method), 406

```

preimage() (sage.modules.with_basis.morphism.TriangularModuleMorphism
method), 161
preimage_representative() (sage.modules.free_module_morphism.FreeModuleMorphism
method), 360
prepare() (in module sage.modules.with_basis.subquotient), 164
presentation() (sage.modules.filtered_vector_space.FilteredVectorSpace_class
method), 319
primary_part() (sage.modules.torsion_quadratic_module.TorsionQuadraticModule
method), 308
prod() (sage.modules.vector_double_dense.Vector_double_dense
method), 396
product_by_coercion() (sage.modules.with_basis.representation.Representation
method), 169
profile() (sage.modules.fp_graded.steenrod.module.SteenrodModuleMixin
method), 253
profile() (sage.modules.fp_graded.steenrod.morphism.SteenrodFPMorphism
method), 256
project() (sage.modules.with_basis.invariant.FiniteDimensionalTwistedInvariantModule
method), 149
project_ambient() (sage.modules.with_basis.invariant.FiniteDimensionalTwistedInvariantModule
method), 149
projection_matrix() (sage.modules.with_basis.invariant.FiniteDimensionalTwistedInvariantModule
method), 150
pushforward() (sage.modules.free_module_morphism.FreeModuleMorphism
method), 362

```

Q

```

q() (sage.modules.torsion_quadratic_module.TorsionQuadraticModule
method), 311
quadratic_form() (sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModule_integer_symmetric
method), 289
quadratic_product() (sage.modules.torsion_quadratic_module.TorsionQuadraticModule
method), 312
QuadraticSpace() (in module sage.modules.free_quadratic_module), 279
quotient() (sage.modules.free_module.FreeModule_generic
method), 42
quotient() (sage.modules.free_module.FreeModule_generic_pid
method), 49
quotient() (sage.modules.free_module.Module_free_ambient
method), 67
quotient_abstract() (sage.modules.free_module.FreeModule_generic
method), 42
quotient_map() (sage.modules.fg_pid.fgp_module.FGP_Module_class
method), 189
quotient_map() (sage.modules.quotient_module.FreeModule_generic
method), 131

```

```

quotient_module() (sage.modules.free_module.Module_free_ambient
method), 67
QuotientModule_free_ambient (class in
sage.modules.quotient_module), 132
QuotientModuleWithBasis (class in
sage.modules.with_basis.subquotient), 164

```

R

```

radical() (sage.modules.with_basis.cell_module.CellModule
method), 319
radical_basis() (sage.modules.with_basis.cell_module.CellModule
method), 139
random_deformation() (sage.modules.filtered_vector_space.FilteredVectorSpace_class
method), 320
random_deformation() (sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace
method), 330
random_element() (sage.modules.fg_pid.fgp_module.FGP_Module_class
method), 189
random_element() (sage.modules.free_module.FreeModule_ambient
method), 21
random_element() (sage.modules.free_module.FreeModule_generic
method), 35
random_fgp_module() (in module sage.modules.fg_pid.fgp_module), 192
random_fgp_morphism() (in module sage.modules.fg_pid.fgp_module), 192
random_vector() (in module sage.modules.free_module_element), 117
rank() (sage.modules.free_module.FreeModule_generic
method), 86
rank() (sage.modules.matrix_morphism.MatrixMorphism_abstract
method), 7
RealDoubleVectorSpace_class (class in
sage.modules.free_module), 73
reduce() (sage.modules.with_basis.subquotient.SubmoduleWithBasis
method), 167
reduced_basis() (sage.modules.free_module_integer.FreeModule_submodule
attribute), 263
RegularRepresentation (class in
sage.modules.with_basis.representation), 168
relation() (sage.modules.fp_graded.module.FPModule
method), 224
relations() (sage.modules.fg_pid.fgp_module.FGP_Module_class
method), 189
relations() (sage.modules.fp_graded.free_module.FreeGradedModule
method), 208
relations() (sage.modules.fp_graded.module.FPModule
method), 224
relations() (sage.modules.free_module.FreeModule_generic
method), 36

```


`relations()` (`sage.modules.free_module.FreeModule_submodule`, `sage.modules.fp_graded.element`
 method), 64 module, 230
`relations()` (`sage.modules.quotient_module.FreeModule_submodule`, `sage.modules.fp_graded.free_element`
 method), 132 module, 211
`relations()` (`sage.modules.quotient_module.QuotientModule_submodule`, `sage.modules.fp_graded.free_homspace`
 method), 135 module, 215
`relations()` (`sage.modules.submodule.Submodule_free_and_rank`, `sage.modules.fp_graded.free_module`
 method), 128 module, 199
`relations_matrix()` (`sage.modules.free_module.Module_submodule`, `sage.modules.fp_graded.free_morphism`
 method), 68 module, 214
`Representation` (class in `sage.modules.fp_graded.homspace`
`sage.modules.with_basis.representation`), module, 247
 168 `sage.modules.fp_graded.module`
`Representation.Element` (class in module, 216
`sage.modules.with_basis.representation`), `sage.modules.fp_graded.morphism`
 169 module, 233
`Representation_abstract` (class in `sage.modules.fp_graded.steenrod.module`
`sage.modules.with_basis.representation`), module, 249
 170 `sage.modules.fp_graded.steenrod.morphism`
`resolution()` (`sage.modules.fp_graded.free_module.FreeGradedModule`, `sage.modules.free_module`
 method), 209 module, 12
`resolution()` (`sage.modules.fp_graded.module.FPModule`, `sage.modules.free_module_element`
 method), 225 module, 76
`resolution()` (`sage.modules.fp_graded.steenrod.module.SteenrodFPModule`, `sage.modules.free_module_homspace`
 method), 250 module, 348
`restrict()` (`sage.modules.matrix_morphism.MatrixMorphism`, `sage.modules.free_module_integer`
 method), 375 module, 259
`restrict_codomain()` (`sage.modules.matrix_morphism.MatrixMorphisms`, `sage.modules.free_module_morphism`
 method), 376 module, 351
`restrict_domain()` (`sage.modules.matrix_morphism.MatrixMorphisms`, `sage.modules.free_quadratic_module`
 method), 377 module, 268
`retract()` (`sage.modules.with_basis.subquotient.QuotientModuleWithBasis`, `sage.modules.free_quadratic_module_integer_symmetric`
 method), 165 module, 280
`retract()` (`sage.modules.with_basis.subquotient.SubmoduleWithBasis`, `sage.modules.matrix_morphism`
 method), 167 module, 362
`row()` (`sage.modules.free_module_element.FreeModuleElement`, `sage.modules.misc`
 method), 103 module, 410
`sage.modules.module`
 module, 9
`sage.modules.complex_double_vector` `sage.modules.multi_filtered_vector_space`
 module, 400 module, 324
`sage.modules.diamond_cutting` `sage.modules.quotient_module`
 module, 401 module, 129
`sage.modules.fg_pid.fgp_element` `sage.modules.real_double_vector`
 module, 193 module, 400
`sage.modules.fg_pid.fgp_module` `sage.modules.submodule`
 module, 175 module, 126
`sage.modules.fg_pid.fgp_morphism` `sage.modules.tensor_operations`
 module, 195 module, 403
`sage.modules.filtered_vector_space` `sage.modules.torsion_quadratic_module`
 module, 313 module, 301
`sage.modules.finite_submodule_iter` `sage.modules.tutorial_free_modules`
 module, 408 module, 3

[sage.modules.vector_callable_symbolic_dense_module](#), 392
[sage.modules.vector_complex_double_dense_module](#), 399
[sage.modules.vector_double_dense_module](#), 392
[sage.modules.vector_integer_dense_module](#), 381
[sage.modules.vector_mod2_dense_module](#), 382
[sage.modules.vector_modn_dense_module](#), 383
[sage.modules.vector_rational_dense_module](#), 384
[sage.modules.vector_real_double_dense_module](#), 398
[sage.modules.vector_space_homspace_module](#), 333
[sage.modules.vector_space_morphism_module](#), 336
[sage.modules.vector_symbolic_dense_module](#), 385
[sage.modules.with_basis.__init__ module](#), 137
[sage.modules.with_basis.cell_module module](#), 137
[sage.modules.with_basis.indexed_element module](#), 140
[sage.modules.with_basis.invariant module](#), 142
[sage.modules.with_basis.morphism module](#), 150
[sage.modules.with_basis.representation module](#), 168
[sage.modules.with_basis.subquotient module](#), 164
[saturation\(\)](#) ([sage.modules.free_module.FreeModule_generic_pid](#) method), 50
[scale\(\)](#) ([sage.modules.free_module.FreeModule_generic](#) method), 36
[scale\(\)](#) ([sage.modules.free_module.FreeModule_generic_free_module](#) method), 43
[section\(\)](#) ([sage.modules.with_basis.morphism.TriangularSimpleModule](#) method), 163
[semigroup\(\)](#) ([sage.modules.with_basis.invariant.FiniteDimensionalInvariantModuleElement](#) method), 145
[semigroup\(\)](#) ([sage.modules.with_basis.representation.Representation_abstract](#) method), 171
[semigroup_algebra\(\)](#) ([sage.modules.with_basis.representation.Representation_abstract](#) method), 171
[semigroup_representation\(\)](#) ([sage.modules.with_basis.invariant.FiniteDimensionalInvariantModuleElement](#) method), 145
[set\(\)](#) ([sage.modules.free_module_element.FreeModuleElement](#) method), 104
[shift\(\)](#) ([sage.modules.filtered_vector_space.FilteredVectorSpace_class](#) method), 320
[shift\(\)](#) ([sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace](#) method), 331
[short_vectors\(\)](#) ([sage.modules.free_quadratic_module_integer_symmetric](#) method), 289
[shortest_vector\(\)](#) ([sage.modules.free_module_integer.FreeModule_submodule](#) method), 263
[side\(\)](#) ([sage.modules.matrix_morphism.MatrixMorphism_abstract](#) method), 378
[side\(\)](#) ([sage.modules.with_basis.representation.Representation](#) method), 170
[side\(\)](#) ([sage.modules.with_basis.representation.Representation_abstract](#) method), 171
[side\(\)](#) ([sage.modules.with_basis.representation.SignRepresentation_abstract](#) method), 173
[side\(\)](#) ([sage.modules.with_basis.representation.TrivialRepresentation](#) method), 174
[side_switch\(\)](#) ([sage.modules.matrix_morphism.MatrixMorphism_abstract](#) method), 378
[signature\(\)](#) ([sage.modules.free_quadratic_module_integer_symmetric.FreeModuleElement](#) method), 290
[signature_pair\(\)](#) ([sage.modules.free_quadratic_module_integer_symmetric.FreeModuleElement](#) method), 290
[SignRepresentation_abstract](#) (class in [sage.modules.with_basis.representation](#)), 173
[SignRepresentation_abstract.Element](#) (class in [sage.modules.with_basis.representation](#)), 173
[SignRepresentationCoxeterGroup](#) (class in [sage.modules.with_basis.representation](#)), 172
[SignRepresentationMatrixGroup](#) (class in [sage.modules.with_basis.representation](#)), 173
[SignRepresentationPermgroupp](#) (class in [sage.modules.with_basis.representation](#)), 173
[simple_module\(\)](#) ([sage.modules.with_basis.cell_module.CellModule](#) method), 139
[SimpleModule](#) (class in [sage.modules.with_basis.cell_module](#)), 139
[SimpleModuleElement](#) (class in [sage.modules.with_basis.cell_module](#)), 139
[simplify\(\)](#) ([sage.modules.vector_symbolic_dense.Vector_symbolic_dense](#) method), 386
[simplify_factorial\(\)](#) ([sage.modules.vector_symbolic_dense.Vector_symbolic_dense](#) method), 387
[simplify_full\(\)](#) ([sage.modules.vector_symbolic_dense.Vector_symbolic_dense](#) method), 387
[simplify_log\(\)](#) ([sage.modules.vector_symbolic_dense.Vector_symbolic_dense](#) method), 387

`method`), 388
`simplify_rational()` (`sage.modules.vector_symbolic_dense.Vector_symbolic_dense` `method`), 389
`simplify_trig()` (`sage.modules.vector_symbolic_dense.Vector_symbolic_dense` `method`), 389
`smith_form_gen()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` `method`), 189
`smith_form_gens()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` `method`), 190
`smith_to_gens()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` `method`), 190
`solve()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` `method`), 242
`some_elements()` (`sage.modules.free_module.Module_free_ambient` `method`), 68
`span()` (in module `sage.modules.free_module`), 74
`span()` (`sage.modules.free_module.Module_free_ambient` `method`), 69
`span()` (`sage.modules.free_quadratic_module.FreeQuadraticModule` `method`), 272
`span()` (`sage.modules.free_quadratic_module.FreeQuadraticModule` `method`), 273
`span_of_basis()` (`sage.modules.free_module.FreeModule_generic_field` `method`), 44
`span_of_basis()` (`sage.modules.free_module.FreeModule_generic_pid` `method`), 50
`span_of_basis()` (`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_field` `method`), 273
`span_of_basis()` (`sage.modules.free_quadratic_module.FreeQuadraticModule_generic_pid` `method`), 274
`sparse_module()` (`sage.modules.free_module.FreeModule_generic_field` `method`), 37
`sparse_vector()` (`sage.modules.free_module_element.FreeModuleElement` `method`), 104
`split()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` `method`), 243
`standard_deviation()` (`sage.modules.vector_double_dense.Vector_double_dense` `method`), 396
`stats_kurtosis()` (`sage.modules.vector_double_dense.Vector_double_dense` `method`), 396
`stats_skew()` (`sage.modules.vector_real_double_dense.Vector_real_double_dense` `method`), 398
`SteenrodFPModule` (class in `sage.modules.fp_graded.steenrod.module`), 250
`SteenrodFPModuleMorphism` (class in `sage.modules.fp_graded.steenrod.morphism`), 253
`SteenrodFreeModule` (class in `sage.modules.fp_graded.steenrod.module`), 252
`SteenrodFreeModuleMorphism` (class in `sage.modules.fp_graded.steenrod.morphism`), 257
`SteenrodModuleMixin` (class in `sage.modules.fp_graded.steenrod.module`), 257
`sublattice()` (`sage.modules.free_quadratic_module_integer_symmetric_pid` `method`), 290
`submodule()` (`sage.modules.fg_pid.fgp_module.FGP_Module_class` `method`), 191
`submodule()` (`sage.modules.free_module.Module_free_ambient` `method`), 71
`Submodule_free_ambient` (class in `sage.modules.submodule`), 126
`submodule_inclusion()` (`sage.modules.fp_graded.module.FPModule` `method`), 228
`submodule_with_basis()` (`sage.modules.free_module.FreeModule_generic_pid` `method`), 51
`submodule_with_gens()` (`sage.modules.torsion_quadratic_module.TorsionQuadraticModule` `method`), 308
`SubmoduleWithBasis` (class in `sage.modules.with_basis.subquotient`), 166
`subs()` (`sage.modules.free_module_element.FreeModuleElement` `method`), 104
`subspace()` (`sage.modules.free_module.FreeModule_generic_field` `method`), 45
`subspace_with_basis()` (`sage.modules.free_module.FreeModule_generic_pid` `method`), 45
`subspaces()` (`sage.modules.free_module.FreeModule_generic_field` `method`), 46
`sum()` (`sage.modules.vector_double_dense.Vector_double_dense` `method`), 397
`support()` (`sage.modules.filtered_vector_space.FilteredVectorSpace_class` `method`), 321
`support()` (`sage.modules.free_module_element.FreeModuleElement` `method`), 105
`support()` (`sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class` `method`), 331
`suspension()` (`sage.modules.fp_graded.free_module.FreeGradedModule` `method`), 228
`suspension()` (`sage.modules.fp_graded.module.FPModule` `method`), 243
`suspension()` (`sage.modules.fp_graded.morphism.FPModuleMorphism` `method`), 243
`symmetric_power()` (`sage.modules.filtered_vector_space.FilteredVectorSpace_class` `method`), 321
`symmetric_power()` (`sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class` `method`), 331
`symmetrized_coordinate_sums()` (in module `sage.modules.tensor_operations`), 407

T

`tensor_product()` (*sage.modules.filtered_vector_space.FilteredVectorSpace_class*), 383
 method), 321
`tensor_product()` (*sage.modules.free_module_element.FreeModuleElement*), 384
 method), 105
`tensor_product()` (*sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric*), 385
 method), 290
`tensor_product()` (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace_class*), 399
 method), 332
TensorOperation (class in *sage.modules.tensor_operations*), 404
`to_vector()` (*sage.modules.with_basis.indexed_element.IndexedFreeModuleElement*), 400
 method), 140
TorsionQuadraticForm (in *sage.modules.torsion_quadratic_module*), 301
TorsionQuadraticModule (class in *sage.modules.torsion_quadratic_module*), 301
TorsionQuadraticModuleElement (class in *sage.modules.torsion_quadratic_module*), 310
`trace()` (*sage.modules.matrix_morphism.MatrixMorphism_abstract*), 264
 method), 379
TriangularModuleMorphism (class in *sage.modules.with_basis.morphism*), 155
TriangularModuleMorphismByLinearity (class in *sage.modules.with_basis.morphism*), 163
TriangularModuleMorphismFromFunction (class in *sage.modules.with_basis.morphism*), 163
`trig_expand()` (*sage.modules.vector_symbolic_dense.Vector_symbolic_dense*), 390
`trig_reduce()` (*sage.modules.vector_symbolic_dense.Vector_symbolic_dense*), 391
TrivialRepresentation (class in *sage.modules.with_basis.representation*), 173
TrivialRepresentation.Element (class in *sage.modules.with_basis.representation*), 174
`twist()` (*sage.modules.free_quadratic_module_integer_symmetric.FreeQuadraticModuleIntegerSymmetric*), 310
 method), 291
`twist()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule*), 310
 method), 309
`twisted_invariant_module()` (*sage.modules.with_basis.representation.Representation_abstract*), 397
 method), 172
`unpickle_v0()` (in *sage.modules.vector_complex_double_dense*), 400
`unpickle_v0()` (in *sage.modules.vector_integer_dense*), 382
`unpickle_v0()` (in *sage.modules.vector_mod2_dense*), 383
`unpickle_v0()` (in *sage.modules.vector_modn_dense*), 384
`unpickle_v0()` (in *sage.modules.vector_rational_dense*), 385
`unpickle_v0()` (in *sage.modules.vector_real_double_dense*), 399
`unpickle_v1()` (in *sage.modules.vector_complex_double_dense*), 400
`unpickle_v1()` (in *sage.modules.vector_integer_dense*), 382
`unpickle_v1()` (in *sage.modules.vector_modn_dense*), 384
`unpickle_v1()` (in *sage.modules.vector_rational_dense*), 385
`unpickle_v1()` (in *sage.modules.vector_real_double_dense*), 399
`update_reduced_basis()` (*sage.modules.free_module_integer.FreeModule_submodule_with_basis*), 64
user_to_echelon_matrix() (*sage.modules.free_module.FreeModule_submodule_with_basis*), 64
`uses_ambient_inner_product()` (*sage.modules.free_module.FreeModule_generic*), 37
`value_module()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule*), 310
`value_module_def()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule*), 310
`value_module_def()` (*sage.modules.fp_graded.morphism.FPModuleMorphism*), 244
`variance()` (*sage.modules.vector_double_dense.Vector_double_dense*), 397
`vector()` (in *sage.modules.free_module_element*), 120
`vector()` (*sage.modules.fg_pid.fgp_element.FGP_Element*), 195
Vector_callable_symbolic_dense (class in *sage.modules.vector_callable_symbolic_dense*), 392
Vector_complex_double_dense (class in *sage.modules.vector_complex_double_dense*), 400

U

`unpickle_v0()` (in *sage.modules.vector_complex_double_dense*), 400
`unpickle_v0()` (in *sage.modules.vector_integer_dense*), 382
`unpickle_v1()` (in *sage.modules.vector_complex_double_dense*), 400
`unpickle_v1()` (in *sage.modules.vector_integer_dense*), 382
`unpickle_v1()` (in *sage.modules.vector_mod2_dense*), 383
`unpickle_v1()` (in *sage.modules.vector_modn_dense*), 384
`unpickle_v1()` (in *sage.modules.vector_rational_dense*), 385
`unpickle_v1()` (in *sage.modules.vector_real_double_dense*), 399
`update_reduced_basis()` (*sage.modules.free_module_integer.FreeModule_submodule_with_basis*), 64
user_to_echelon_matrix() (*sage.modules.free_module.FreeModule_submodule_with_basis*), 64
`uses_ambient_inner_product()` (*sage.modules.free_module.FreeModule_generic*), 37
`value_module()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule*), 310
`value_module_def()` (*sage.modules.torsion_quadratic_module.TorsionQuadraticModule*), 310
`value_module_def()` (*sage.modules.fp_graded.morphism.FPModuleMorphism*), 244
`variance()` (*sage.modules.vector_double_dense.Vector_double_dense*), 397
`vector()` (in *sage.modules.free_module_element*), 120
`vector()` (*sage.modules.fg_pid.fgp_element.FGP_Element*), 195
Vector_callable_symbolic_dense (class in *sage.modules.vector_callable_symbolic_dense*), 392
Vector_complex_double_dense (class in *sage.modules.vector_complex_double_dense*), 400

sage.modules.vector_complex_double_dense),
 399
Vector_double_dense (class in
sage.modules.vector_double_dense), 393
Vector_integer_dense (class in
sage.modules.vector_integer_dense), 381
Vector_mod2_dense (class in
sage.modules.vector_mod2_dense), 382
Vector_modn_dense (class in
sage.modules.vector_modn_dense), 384
vector_presentation()
(sage.modules.fp_graded.element.FPElement
method), 231
vector_presentation()
(sage.modules.fp_graded.free_element.FreeGradedModuleElement
method), 212
vector_presentation()
(sage.modules.fp_graded.free_module.FreeGradedModule
method), 210
vector_presentation()
(sage.modules.fp_graded.module.FPModule
method), 229
vector_presentation()
(sage.modules.fp_graded.morphism.FPModuleMorphism
method), 245
Vector_rational_dense (class in
sage.modules.vector_rational_dense), 385
Vector_real_double_dense (class in
sage.modules.vector_real_double_dense),
 398
vector_space() (*sage.modules.free_module.FreeModule_ambient_domain*
method), 23
vector_space() (*sage.modules.free_module.FreeModule_generic_field*
method), 46
vector_space() (*sage.modules.free_module.FreeModule_submodule_with_basis_pid*
method), 65
vector_space_span()
(sage.modules.free_module.FreeModule_generic_pid
method), 52
vector_space_span_of_basis()
(sage.modules.free_module.FreeModule_generic_pid
method), 53
Vector_symbolic_dense (class in
sage.modules.vector_symbolic_dense), 385
VectorCollection (class in
sage.modules.tensor_operations), 406
vectors() (*sage.modules.tensor_operations.VectorCollection*
method), 406
VectorSpace() (in module *sage.modules.free_module*),
 73
VectorSpaceHomspace (class in
sage.modules.vector_space_homspace), 336
VectorSpaceMorphism (class in
sage.modules.vector_space_morphism), 342
volume() (*sage.modules.free_module_integer.FreeModule_submodule_with*
method), 264
voronoi_cell() (*sage.modules.free_module_integer.FreeModule_submodule*
method), 264
voronoi_relevant_vectors()
(sage.modules.free_module_integer.FreeModule_submodule_with
method), 265
W
W() (*sage.modules.fg_pid.fgp_module.FGP_Module_class*
method), 179
W() (*sage.modules.quotient_module.FreeModule_ambient_field_quotient*
method), 130
W() (*sage.modules.quotient_module.QuotientModule_free_ambient*
method), 133
wedge() (*sage.modules.filtered_vector_space.FilteredVectorSpace_class*
method), 322
wedge() (*sage.modules.multi_filtered_vector_space.MultiFilteredVectorSpace*
method), 332
Z
zero() (*sage.modules.fp_graded.homspace.FPModuleHomspace*
method), 248
zero() (*sage.modules.fp_graded.module.FPModule*
method), 229
zero() (*sage.modules.free_module.Module_free_ambient*
method), 72
zero() (*sage.modules.free_module_homspace.FreeModuleHomspace*
method), 349
zero_at() (*sage.modules.vector_double_dense.Vector_double_dense*
method), 397
zero_submodule() (*sage.modules.free_module.FreeModule_generic_field*
method), 47
zero_submodule() (*sage.modules.free_module.FreeModule_generic_pid*
method), 53
zero_submodule() (*sage.modules.free_module.Module_free_ambient*
method), 72
zero_submodule() (*sage.modules.free_quadratic_module.FreeQuadratic*
method), 274
zero_subspace() (*sage.modules.free_module.FreeModule_generic_field*
method), 47
zero_vector() (in module
sage.modules.free_module_element), 125
zero_vector() (*sage.modules.free_module.Module_free_ambient*
method), 72