

## Tree based methods II-a

### Classification Tree examples (using rpart)

STAT 32950-24620

Spring 2023 (5/16)

1 / 20

## Classification Tree

Building a **classification tree** is similar to building a regression tree.

**Regression Tree:** The response variable is continuous.

**Classification Tree:** The response variable is categorical.

```
library(rpart)           # better plots using rpart.plot
library(rpart.plot)      # better plots
#library(tree)           # alternative to rpart, concise summary
library(ISLR)
```

R library:

rpart — Recursive Partitioning And Regression Trees

cart — Classification and Regression Trees

tree — ...

2 / 20

## Example data

```
attach(Carseats)
str(Carseats)
```

```
## 'data.frame':   400 obs. of  11 variables:
## $ Sales       : num  9.5 11.22 10.06 7.4 4.15 ...
## $ CompPrice   : num  138 111 113 117 141 124 115 136 137
## $ Income      : num   73  48  35 100  64 113 105  81 110 113
## $ Advertising: num   11  16  10  4  3 13  0 15  0  0 ...
## $ Population : num  276 260 269 466 340 501 45 425 108
## $ Price       : num  120 83 80 97 128 72 108 120 124 124
## $ ShelfLoc    : Factor w/ 3 levels "Bad","Good","Medium"
## $ Age         : num   42  65  59  55  38  78  71  67  76  76 ...
## $ Education   : num   17  10 12 14 13 16 15 10 10 17 ...
## $ Urban       : Factor w/ 2 levels "No","Yes": 2 2 2 2 2
## $ US          : Factor w/ 2 levels "No","Yes": 2 2 2 2 2
```

3 / 20

## Create a binary response

For fitting a tree to predict High using all variables but Sales.

```
High=as.factor(ifelse(Sales<=8,"No","Yes"))
table(High) # No 236; Yes 164
```

```
## High
## No Yes
## 236 164
```

```
#table(ShelveLoc) # Bad 96    Good 85    Medium 219
Carseats=data.frame(Carseats,High) #'d.f': 400 obs 12 vars
colnames(Carseats)
```

```
## [1] "Sales"      "CompPrice"  "Income"     "Advertisi
## [6] "Price"      "ShelveLoc"  "Age"        "Educatio
## [11] "US"         "High"
```

4 / 20


## Fit a classification tree using library(rpart)

```
Rtree.carseats=rpart(High~.-Sales,Carseats)
attributes(Rtree.carseats)
```

```
## $names
## [1] "frame"           "where"           "call"
## [4] "terms"           "cptable"         "method"
## [7] "parms"           "control"         "function"
## [10] "numresp"         "splits"          "csplit"
## [13] "variable.importance" "y"              "ordered"
##
## $xlevels
## $xlevels$ShelveLoc
## [1] "Bad"    "Good"    "Medium"
##
## $xlevels$Urban
## [1] "No"    "Yes"
##
## $xlevels$US
7 / 20
```

## Plot a classification tree


```
# Plot classification tree using (rpart)
plot(Rtree.carseats,uniform=T)
text(Rtree.carseats,use.n=T,all=T,cex=.6)
```



6 / 20

## Plot a nicer tree using library(rpart.plot)


```
rpart.plot(Rtree.carseats) #rpart.plot(Rtree.carseats,extra
```



7 / 20

## Plot the tree with alternative style

```
rpart.plot(Rtree.carseats,extra=103, under=T,type=3)
```



8 / 20

## Notations at the nodes

### At each node

- Condition: splitting rule of a variable.  
E. g. Price  $\geq$  93
- Decision: Response variable classification rule.  
E. g. No when Price  $\geq$  143
- Ratio of the response variable (if given)  
E.g. 3/12:  
3 Yes, 9 No at the leave (will be ruled as No)  
(alternative common display: 3/12: 3 Yes, 12 No)

9 / 20

## Splitting nodes and ending nodes

### Splitting nodes

- Left branch: Condition in the label satisfied.  
E. g. Label: Price  $\geq$  93  
The left branch below have Price  $\geq$  93.
- Right branch: Condition in the label not satisfied.  
E. g. Label: Price  $\geq$  93  
The right branch below have Price  $<$  93.

### Ending nodes (leaves)

- Decision rule (Yes or No)

10 / 20

## Variable predictability

```
table(High,ShelveLoc);table(High,Urban);table(High,US)
```

```
##      ShelveLoc
## High  Bad Good Medium
##  No   82  19   135
##  Yes  14  66   84

##      Urban
## High  No Yes
##  No   64 172
##  Yes  54 110

##      US
## High  No Yes
##  No   101 135
##  Yes   41 123
```

11 / 20

## Examine the fit using summary(rpart(...),digits=3)

Call:

```
rpart(formula = High ~ . - Sales, data = Carseats)
n= 400
```

```
CP nsplit rel error xerror xstd
1 0.2866 0 1.000 1.000 0.0600
2 0.1098 1 0.713 0.713 0.0555
3 0.0457 2 0.604 0.683 0.0548
4 0.0366 4 0.512 0.720 0.0556
5 0.0274 5 0.476 0.713 0.0555
6 0.0244 7 0.421 0.695 0.0551
7 0.0122 8 0.396 0.652 0.0540
8 0.0100 10 0.372 0.622 0.0532
```

Variable importance

```
Price ShelveLoc Age Advertising CompPrice
34 25 11 11 5
Income Population Education
5 3 1
```

12 / 20

## Node details

Node index: 1-11; 16-19; 34, 35; 68, 69; 138, 139.

```
Node number 1: 400 observations, complexity param=0.287
  predicted class=No expected loss=0.41 P(node) =1
    class counts: 236 164
    probabilities: 0.590 0.410
  left son=2 (315 obs) right son=3 (85 obs)
Primary splits:
ShelveLoc splits as LRL, improve=29.00, (0 missi
Price < 92.5 to the right, improve=19.50, (0 missi
Advertising < 6.5 to the left, improve=17.30, (0 missi
Age < 61.5 to the right, improve= 9.26, (0 missi
Income < 60.5 to the left, improve= 7.25, (0 missi
... ..
Node number 139: 20 observations
  predicted class=Yes expected loss=0.4 P(node) =0.05
    class counts: 8 12
    probabilities: 0.400 0.600
```

13 / 20

## Training, testing, prediction error

Using all the data to fit one tree often results in overfit.

To avoid overfit, split data to training and testing sets.

```
set.seed(3)
train=sample(1:nrow(Carseats), 200)
Carseats.test=Carseats[-train,]
High.test=High[-train]
Rtree.carseats=rpart(High~.-Sales,Carseats,subset=train)
```

Check the fit on training data

14 / 20

## Check the fit on training data (summary output)

```
## Call:
## rpart(formula= High~.-Sales,data=Carseats,subset=train)
## n= 200
##      CP nsplit rel error xerror xstd
## 1 0.28000      0  1.0000 1.0000 0.09129
## 2 0.08000      1  0.7200 0.8267 0.08721
## 3 0.05333      3  0.5600 0.8400 0.08759
## 4 0.04000      4  0.5067 0.8267 0.08721
## 5 0.02667      5  0.4667 0.8267 0.08721
## 6 0.01333      6  0.4400 0.8400 0.08759
## 7 0.01000      7  0.4267 0.8667 0.08832
##
## Variable importance
##  ShelveLoc      Price Advertising  CompPrice
##      25         20         17         10
##   Age Population    US   Education    Income
##   10          7      6           4         3
```

15 / 20

## Check the fit on testing data

```
Rtree.pred=predict(Rtree.carseats,Carseats.test,
                    type="class")
table(Rtree.pred,High.test) # check the error rate
```

```
##           High.test
## Rtree.pred No  Yes
##           No  85  32
##           Yes 26  57
```

16 / 20

## Prune: use Cost Complexity (or Weakest Link)

```
Rtree.carseats$cptable # Using `rpart` to prune
```

```
##          CP nsplit rel error xerror   xstd
## 1 0.28000    0    1.0000 1.0000 0.09129
## 2 0.08000    1    0.7200 0.7200 0.08371
## 3 0.05333    3    0.5600 0.7600 0.08512
## 4 0.04000    4    0.5067 0.7733 0.08556
## 5 0.02667    5    0.4667 0.7467 0.08466
## 6 0.01333    6    0.4400 0.8133 0.08682
## 7 0.01000    7    0.4267 0.8000 0.08641
```


```
# which.min(Rtree.carseats$cptable[, "xerror"]); #2
Rtree.carseats$cptable[
  which.min(Rtree.carseats$cptable[, "xerror"]), "CP"]
```

```
## [1] 0.08
```

17 / 20

## Plot the min CP tree


```
pfit.min<- prune(Rtree.carseats, cp=Rtree.carseats$cptable[
  which.min(Rtree.carseats$cptable[, "xerror"]), "CP"])
rpart.plot(pfit.min)
```



18 / 20

## Pick a pruned tree


```
pfit2<- prune(Rtree.carseats, cp=0.05) #.1 -> 2 leaves
rpart.plot(pfit2)
```



19 / 20

## Pick another pruned tree

```
pfit3<- prune(Rtree.carseats, cp=0.01)
rpart.plot(pfit3)
```



20 / 20