

# Probabilistic graphical models

Kristian Wichmann

October 3, 2017

## 1 Bayesian networks

A group of graphical models are *Bayesian networks*, also known as *directed graphical models*.

### 1.1 An example

As an example, consider three random variables  $A, B$ , and  $C$  with a joint distribution  $p(a, b, c)$ . Then we can rewrite this as:

$$p(a, b, c) = p(c|a, b)p(a, b) \quad (1.1)$$

Using the same idea once more, this can be further rewritten:

$$p(a, b, c) = p(c|a, b)p(a, b) = p(c|a, b)p(b|a)p(a) \quad (1.2)$$

We can interpret this as  $c$  depending on  $a$  and  $b$ , and  $b$  depending on  $a$ . We will use directed *edges* to denote this dependency as shown in figure 1.

Do note, that we might as well have split the variables into dependency in another order! This graph is merely one way of viewing the joint distribution - in general a distribution can be represented by many different graphs.




Figure 1: A Bayesian network with three nodes




Figure 2: A less than fully connected Bayesian network

## 1.2 General case: Fully connected

Using the same scheme, we can decompose a joint distribution of  $K$  variables and split it into a form similar to equation 1.2 by applying the multiplication rule of probability  $K - 1$  times:

$$p(x_1, x_2, \dots, x_K) = p(x_K | x_1, \dots, x_{K-1}) \cdots p(x_2 | x_1) p(x_1) \quad (1.3)$$

This gives rise to a *fully connected* graph, as there will be edges between any two nodes.

## 1.3 Less than fully connected

However, in general we will be more interested in cases where some pairs of nodes will not have an edge between them. We will still require the graph to be *acyclical*, i.e. there must be no loops when following the directed edges.

As an example, consider the six-node graph in figure 2. The corresponding decomposition would be:

$$p(x_1, x_2, x_3, x_4, x_5, x_6) = p(x_6 | x_4, x_5) p(x_5 | x_3) p(x_4 | x_1, x_2, x_3) p(x_3) p(x_2) p(x_1) \quad (1.4)$$