



Red Hat

Support for mini-debuginfo in LLDB

How to read the `.gnu_debugdata` section

Konrad Kleine

February 2, 2020




Red Hat



Konrad Kleine

- Red Hat
- LLDB, C/C++, ELF, DWARF since 2019
- Before worked OpenShift since 2016

Reach out

-  <https://github.com/kwk/talks/>
-  <https://www.linkedin.com/in/konradkleine>
-  <https://developers.redhat.com/blog/author/kkleine/>

Improve LLDB for Fedora and RHEL binaries

- when no debug symbols installed
 - backtraces only show addresses
 - runtime symbols stored in special location

Approach

- make LLDB understand mini-debuginfo
 - that's where runtime symbols are stored


💡 Why was mini-debuginfo invented?

- without installing debug infos
 - be able to generate a backtrace for crashes with ABRT¹
 - have symbol table (.symtab)
 - have line information (.debug_line)
 - ➔ *more than two sections make an ELF file 😊*
- eventually only one relevant section
 - stripped .symtab
 - rest was too big
 - format remained
 - **no replacement** for separate full debug info
 - **not related** to DWARF
 - *just symbol tables*


¹Automatic Bug Reporting Tool

Symbol tables in an ELF file

regular ELF file



ELF file with mini-debuginfo



Where and since when is mini-debuginfo being used?

- RPM since 4.13.0-rc2 (2016)
- On by default since Fedora 18 (2013, Release Notes 4.2.4.1.)
- Red Hat Enterprise Linux (RHEL) since 7

Not focus on backtraces

- but make LLDB see mini-debuginfo
 - symbol awareness through
 - set and hit breakpoint
 - dump symbols (`(lldb) image dump symtab`)

Take existing Fedora binary (`/usr/bin/zip`)

- identify a symbol/function
- shootout: GDB vs. LLDB
- hurdles:
 - not from `.dynsym`
 - from within `.gnu_debugdata`

Extract and uncompress .gnu_debugdata section to zip.gdd

```
1 ~$ cp /usr/bin/zip .
2 ~$ objcopy --dump-section .gnu_debugdata=zip.gdd.xz zip
3 ~$ file zip.gdd.xz
4 zip.gdd.xz: XZ compressed data
5 ~$ xz --decompress --keep zip.gdd.xz
6 ~$ file zip.gdd
7 zip.gdd: ELF 64-bit LSB executable, x86-64, version 1 [...]
```


Identify symbol in zip.gdd but not in main binary

```
1  ~$ eu-readelf -s zip.gdd
2
3  Symbol table [28] '.symtab' contains 202 entries:
4  82 local symbols  String table: [29] '.strtab'
5
6  Num:          Value      Size Type   Bind   Vis      Ndx Name
7  0: 0000000000000000      0 NOTYPE LOCAL DEFAULT UNDEF
8  1: 0000000000408db0    494 FUNC   LOCAL DEFAULT   15 freeup
9  2: 0000000000408fa0   1015 FUNC   LOCAL DEFAULT   15 DisplayRunningStats
10 3: 00000000004093a0    128 FUNC   LOCAL DEFAULT   15 help
11 [...]
12
```

help looks promising².

```
11 ~$ eu-readelf --symbols /usr/bin/zip | grep help
12 ~$
```

²Promising as in: we may be able to trigger it with `/usr/bin/zip --help`.



Set and hit breakpoint on help with GDB 8.3³

```
1  -$ gdb --nx --args /usr/bin/zip --help
2  Reading symbols from /usr/bin/zip...
3  Reading symbols from .gnu_debugdata for /usr/bin/zip...
4  (No debugging symbols found in .gnu_debugdata for /usr/bin/zip)
5  Missing separate debuginfos, use: dnf debuginfo-install zip-3.0-25.fc31.x86_64
6  (gdb) b help
7  Breakpoint 1 at 0x4093a0
8  (gdb) r
9  Starting program: /usr/bin/zip --help
10
11  Breakpoint 1, 0x00000000004093a0 in help ()
12  (gdb)
```

Success and two things to note:

1. Symbols read from `.gnu_debugdata`
2. No debug symbols installed for zip

³GDB 8.3 is what ships with Fedora 31



Set and hit breakpoint on help with LLDB 9.0.0⁴

```
1 ~$ lldb -x /usr/bin/zip -- --help
2 (lldb) target create "/usr/bin/zip"
3 Current executable set to '/usr/bin/zip' (x86_64).
4 (lldb) settings set -- target.run-args "--help"
5 (lldb) b help
6 Breakpoint 1: no locations (pending).
7 WARNING: Unable to resolve breakpoint to any actual locations.
8 (lldb)
```



⁴LLDB 9.0.0 is what ships with Fedora 31

Symtab

- normally, `.dynsym` is subset
- **but** for mini-debuginfo `.dynsym` symbols are stripped⁵

Implications for LLDB (and other tools)

- parse `.dynsym` when
 - no `.symtab` found **or**
 - mini-debuginfo present and smuggled in

⁵<https://sourceware.org/gdb/current/onlinedocs/gdb/MiniDebugInfo.html>

✓ Show that LLDB can now find help symbol

```
1 $ lldb -x /usr/bin/zip -- --help
2 (lldb) target create "/usr/bin/zip"
3 Current executable set to '/usr/bin/zip' (x86_64).
4 (lldb) settings set -- target.run-args "--help"
5 (lldb) b help
6 Breakpoint 1: where = zip`help, address = 0x00000000004093a0
7 (lldb) r
8 Process 277525 launched: '/usr/bin/zip' (x86_64)
9 Process 277525 stopped
10 * thread #1, name = 'zip', stop reason = breakpoint 1.1
11   frame #0: 0x00000000004093a0 zip`help
12 zip`help:
13 -> 0x4093a0 <+0>:  pushq   %r12
14       0x4093a2 <+2>:  movq    0x2af6f(%rip), %rsi          ; + 4056
15       0x4093a9 <+9>:  movl    $0x1, %edi
16       0x4093ae <+14>: xorl    %eax, %eax
17 (lldb)
```

♡ shipping with LLVM 10



Ready to ship?

② What tests exists for mini-debuginfo?

- find symbol from `.gnu_debugdata`
- warning when decompressing `.gnu_debugdata` w/o LZMA support
- error when decompressing corrupted xz
- full example with compiled and modified code in accordance to gdb's documentation

 fell asleep yet?

</> Example test file in Shell test suite

lldb/test/Shell/Breakpoint/example.c:

```
1  // REQUIRES: system-linux, lzma, xz
2  // RUN: gcc -g -o %t %s
3  // RUN: %t 1 2 3 4 | FileCheck %s
4
5  #include <stdio.h>
6  int main(int argc, char* argv[]) {
7
8      // CHECK: Number of {{.*}}: 5
9      printf("Number of arguments: %d\n", argc);
10
11     return 0;
12 }
```

```
~/llvm-project$ llvm-lit lldb/test/Shell/Breakpoint/example.c
```

```
-- Testing: 1 tests, 1 workers --
```

```
PASS: lldb-shell :: Breakpoint/example.c (1 of 1)
```

```
Testing Time: 0.20s
```

```
Expected Passes      : 1
```

You might wonder...

- what was the hardest part?
 - polishing for upstream
 - dealing with tests
 - non-runable/sparse ELF files produced from some YAML
- set **and** hit a breakpoint
 - only possible with runnable ELF file



Thank you!

Please, share your feedback ★★★★★

<https://submission.fosdem.org/feedback/10393>