

SD-Wi-Fi-UART-BT-88W8987

Wi-Fi and Bluetooth Software Features for FreeRTOS



Contents

1.	Wi-Fi Features	4
1.1.	Wireless Client Features	4
1.1.1.	802.11 ac - Very High Throughput	4
1.1.2.	802.11n - High Throughput	4
1.1.3.	802.11 a/b/g Features	4
1.1.4.	802.11d	4
1.1.5.	802.11e – QoS	4
1.1.6.	802.11i - Security	4
1.1.7.	802.11w - Protected Management Frames(PMF).....	5
1.1.8.	Power Save Mode	5
1.1.9.	General Features.....	5
1.2.	Mobile AP Features.....	6
1.2.1.	802.11n - High Throughput	6
1.2.2.	802.11 b/g Features	6
1.2.3.	802.11d	6
1.2.4.	802.11i - Security	6
1.2.5.	802.11w - Protected Management Frames(PMF).....	6
1.2.6.	General Features.....	6
2.	Simultaneous AP-STA Operation (Same Channel)	7
3.	Bluetooth Features	8
3.1.	Bluetooth Classic Features.....	8
3.1.1.	General Features.....	8
3.1.2.	Bluetooth Packet Type Supported	8
3.1.3.	Bluetooth Profiles Supported	8
3.1.4.	Bluetooth Audio Features	8
3.2.	Bluetooth LE Features.....	9
3.2.1.	Generic Features	9
3.2.2.	Bluetooth LE Profile Support.....	9
3.2.3.	Bluetooth LE 4.0 Support	9
3.2.4.	Bluetooth LE 4.1 Support	9
3.2.5.	Bluetooth LE 4.2 Support	9
3.2.6.	Bluetooth LE 5.0 Support	9
4.	Bluetooth + Wi-Fi Coexistence	10
4.1.1.	Supported Bluetooth/Bluetooth LE Profile for Coexistence	10
4.1.2.	Timeshare Coex Mode	10
5.	Test Mode	11
5.1.1.	Wi-Fi	11
6.	Notes.....	12
7.	Acronyms & Abbreviations	13
8.	Legal Information	14
8.1.	Disclaimers.....	14
8.2.	Trademarks	14

Revision History

Table 1: Document revision history

Revision	Date	Change details
Rev. 1	19-Mar-2021	Initial release
Rev. 2	07-July-2021	Section 4 updated
Rev.3	09-Sept-2021	Section 1 updated
Rev.4	15-Mar-2022	Section 1.1.1 "802.11 ac - Very High Throughput" : Removed SU-AMPDU Aggregation Section 1.1.2 "802.11n - High Throughput" : Added 40MHz for 2.4GHz client and removed Explicit Beamformee Section 1.1.6 "802.11i - Security" : Removed WEP and WPA2 +WPA3 (SAE) mixed mode. Added WPA3 SAE (R3) Section 1.2.1 "802.11n - High Throughput" : Added 40MHz for 2.4G AP Section 1.2.2 "802.11 b/g Features" : Removed PS Poll and null data Section 1.2.4 "802.11i - Security" : Added WPA3 SAE (R3) and WPA2 +WPA3 (SAE) mixed mode Section 1.1.9 General Features : Added IPv6 Section 1.2.6 General Features : Added IPv6

1. Wi-Fi Features

1.1. Wireless Client Features

1.1.1. 802.11 ac - Very High Throughput

- 5GHz Band Operation
- 5 GHz band supported channel bandwidths: 20 MHz, 40 MHz, 80MHz
- 11ac Data rates - Up to 433.3 Mbps (MCS 0 to MCS 9)
- MU-MIMO Beamformee (Explicit and Implicit)
- RTS/CTS with BW Signaling
- Operation Mode Notification
- Backward Compatibility with non-VHT devices
- Tx VHT MCS Rate Adaptation

1.1.2. 802.11n - High Throughput

- 2.4 GHz and 5 GHz band operation
- 2.4 GHz band supported channel bandwidths : 20MHz, 40MHz
- 5 GHz band supported channel bandwidths : 20MHz, 40MHz
- Short/long guard interval (400 ns/800 ns)
- 1 spatial stream (1x1)
- 11n data rates – Up to 150 Mbit/s (MCS 0 to MCS 7)
- Aggregated MAC Protocol Data Unit(AMPDU) Rx support
- Aggregated MAC Service Data Unit(AMSDU)-4k Rx support
- HT protection mechanisms
- Tx MCS rate adaptation (BGN)
- RX Low Density Parity Check(LDPC)

1.1.3. 802.11 a/b/g Features

- 11 a/b/g data rates - Up to 54 Mbit/s
- Tx rate adaptation (BG)
- Fragmentation/defragmentation
- ERP protection, slot time, preamble

1.1.4. 802.11d

- 802.11d - Regulatory domain/operating class/country info

1.1.5. 802.11e – QoS

- EDCA[Enhanced Distributed Channel Access] / WMM (Wireless Multi-Media)

1.1.6. 802.11i - Security

- Embedded supplicant support
 - Open security
 - WPA-PSK, WPA2-PSK security (AES-CCMP encryption)
 - WPA + WPA2 mixed mode
 - WPA3 SAE (R3)

1.1.7. 802.11w - Protected Management Frames(PMF)

- PMF require and capable
- Unicast management frames - Encryption/decryption - using CCMP
- Broadcast management frames - Encryption/decryption - using BIP
- SA query request/response
- PMF support (embedded supplicant)

1.1.8. Power Save Mode

- Deep sleep
- IEEE power save

1.1.9. General Features

- Embedded MLME
- EU adaptivity support (ETSI cert)
- DFS radar detection in slave mode (Follow AP)
- IPv6

1.2. Mobile AP Features

1.2.1. 802.11n - High Throughput

- 2.4 GHz and 5 GHz band operation
- 2.4 GHz band supported channel bandwidths : 20MHz, 40MHz
- 5 GHz band supported channel bandwidths : 20MHz, 40MHz
- Short/long guard interval (400 ns/800 ns)
- 1 spatial stream (1x1)
- 11n data rates – Up to 150 Mbit/s (MCS0 to MCS7)
- Tx MCS rate adaptation (BGN)
- Aggregated MAC Protocol Data Unit(AMPDU) Rx support
- Aggregated MAC Service Data Unit(AMSDU)- 4k Rx support
- Max client support (up to 8 devices)
- HT protection mechanisms

1.2.2. 802.11 b/g Features

- 11 b/g data rates – Up to 54 Mbit/s
- Tx rate adaptation (BG)
- ERP protection, slot time, preamble
- Handling of associated STAs with IEEE PS

1.2.3. 802.11d

- 802.11d - Regulatory domain/operating class/country info

1.2.4. 802.11i - Security

- Embedded authenticator support
 - Open security
 - WPA2-PSK security (AES-CCMP encryption)
 - WPA2 +WPA3 (SAE) mixed mode
 - WPA3 SAE (R3)

1.2.5. 802.11w - Protected Management Frames(PMF)

- PMF require and capable
- Unicast management frames - Encryption/decryption - using CCMP
- Broadcast management frames - Encryption/decryption - using BIP
- SA query request/response

1.2.6. General Features

- Deep sleep
- Embedded MLME
- EU adaptivity support (ETSI Cert)
- Automatic channel selection (ACS)
- Extended channel switch announcement (ECSA)
- IPv6

2. Simultaneous AP-STA Operation (Same Channel)

- AP-STA functionality

3. Bluetooth Features

3.1. Bluetooth Classic Features

3.1.1. General Features

- Bluetooth Class 1.5 and Class 2 support
- Maximum of seven simultaneous ACL connections
- Automatic Packet Type Selection
- Bluetooth - Up to 5.0 Specification Support
- Maximum of one eSCO connection
- Secure Simple pairing
- BR/EDR Secure Connections
- Scatternet support
- Low power sniff

3.1.2. Bluetooth Packet Type Supported

- ACL (DM1, DH1, DM3, DH3, DM5, DH5, 2-DH1, 2-DH3, 2-DH5, 3-DH1, 3-DH3, 3-DH5)
- SCO (HV1, HV3)
- eSCO (EV3, EV4, EV5, 2EV3, 3EV3, 2EV5, 3EV5)

3.1.3. Bluetooth Profiles Supported

- A2DP Source
- A2DP Sink
- HFP Dev
- HFP GW
- SPP Server
- SPP Client
- RFCOMM

3.1.4. Bluetooth Audio Features

- PCM NBS (Bluetooth Controller role is Master)
- PCM WBS (Bluetooth Controller role is Master)

3.2. Bluetooth LE Features

3.2.1. Generic Features

- Maximum 16 Bluetooth LE connections (Master role)
- Bluetooth LE - 1Mbps Support
- Bluetooth LE - Up to 5.0 Specification Support
- Bluetooth LE FW Whitelist

3.2.2. Bluetooth LE Profile Support

- Proximity Reporter(PXR)/Proximity Monitor(PXM)
- IPSPN
- HPS
- HTP

3.2.3. Bluetooth LE 4.0 Support

- Low Energy Physical Layer
- Low Energy Link Layer
- Enhancements to HCI for Low Energy
- Low Energy Direct Test Mode

3.2.4. Bluetooth LE 4.1 Support

- Low duty Cycle Directed Advertising
- Bluetooth LE Dual Mode Topology
- Bluetooth LE Privacy v1.1
- Bluetooth LE Link Layer Topology

3.2.5. Bluetooth LE 4.2 Support

- Bluetooth LE secure connection
- Bluetooth LE Link Layer Privacy v1.2
- Bluetooth LE Data Length Extension
- Link Layer Extended Scanner Filter Policies

3.2.6. Bluetooth LE 5.0 Support

- Bluetooth LE 2 Mbps Support
- High Duty Cycle Directed Advertising

4. Bluetooth + Wi-Fi Coexistence

4.1.1. Supported Bluetooth/Bluetooth LE Profile for Coexistence

- A2DP Source
- A2DP Sink
- HFP Dev
- HFP GW
- SPP Client
- SPP Server
- Proximity Client
- Proximity Server
- RFCOMM
- IPSPN
- HPS
- HTP

4.1.2. Timeshare Coex Mode

- STA + Bluetooth Coex
- STA + Bluetooth LE Coex
- STA + Bluetooth + Bluetooth LE Coex
- AP + Bluetooth Coex
- AP + Bluetooth LE Coex
- AP + Bluetooth + Bluetooth LE Coex

Note: Timeshare Coex mode is not required when Wi-Fi is operating in 5GHz

5. Test Mode

5.1.1. Wi-Fi

- Wi-Fi transmit Continuous Wave (CW) mode
- Transmit standard 802.11 packets
- Wi-Fi receive mode

Refer to **Section: wifi_test_mode sample application** in the document: *UM11442-NXP Wi-Fi and Bluetooth Demo Applications for i.MX RT platforms User Guide* for more details.

6. Notes

None.

7. Acronyms & Abbreviations

Acronyms	Definitions
A2DP	Advanced audio distribution profile
AP	Access Point
HFP	Hands free profile
WPA	Wi-Fi protected access
MLME	Mac Layer Management Entity
STA	Station
HT	High Throughput
MCS	Modulation and Coding Scheme
ERP	Extended Rate Physical
SAE	Simultaneous Authentication of Equals
CCMP	Counter Mode CBC-MAC Protocol

8. Legal Information

8.1. Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors. In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products. NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Evaluation products — This product is provided on an "as is" and "with all faults" basis for evaluation purposes only. NXP Semiconductors, its affiliates and their suppliers expressly disclaim all warranties, whether express, implied or statutory, including but not limited to the implied warranties of non-infringement, merchantability and fitness for a particular purpose. The entire risk as to the quality, or arising out of the use or performance, of this product remains with customer. In no event shall NXP Semiconductors, its affiliates or their suppliers be liable to customer for any special, indirect, consequential, punitive or incidental damages (including without limitation damages for loss of business, business interruption, loss of use, loss of data or information, and the like) arising out of the use of or inability to use the product, whether or not based on tort (including

negligence), strict liability, breach of contract, breach of warranty or any other theory, even if advised of the possibility of such damages.

Notwithstanding any damages that customer might incur for any reason whatsoever (including without limitation, all damages referenced above and all direct or general damages), the entire liability of NXP Semiconductors, its affiliates and their suppliers and customer's exclusive remedy for all of the foregoing shall be limited to actual damages incurred by customer based on reasonable reliance up to the greater of the amount actually paid by customer for the product or five dollars (US\$5.00). The foregoing limitations, exclusions and disclaimers shall apply to the maximum extent permitted by applicable law, even if any remedy fails of its essential purpose.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

8.2. Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.