

SD-Wi-Fi-FP91-88W8801

Wi-Fi Software Features for FreeRTOS



Contents

1.	Wi-Fi Features	4
1.1.	Wireless Client Features	4
1.1.1.	802.11n - High Throughput	4
1.1.2.	802.11 b/g Features	4
1.1.3.	802.11d Features	4
1.1.4.	802.11i - Security	4
1.1.5.	802.11w - Protected Management Frames(PMF).....	4
1.1.6.	Power Save Mode	4
1.1.7.	General Features.....	4
1.2.	Mobile AP Features.....	5
1.2.1.	802.11n - High Throughput	5
1.2.2.	802.11 b/g Features	5
1.2.3.	802.11d Features	5
1.2.4.	802.11i - Security	5
1.2.5.	802.11w - Protected Management Frames(PMF).....	5
1.2.6.	General Features.....	5
2.	Simultaneous AP-STA Operation (Same Channel)	6
3.	Test Mode	7
3.1.1.	Wi-Fi	7
4.	Notes.....	8
5.	Acronyms & Abbreviations	9
6.	Legal Information	10
6.1.	Disclaimers	10
6.2.	Trademarks	10

Revision history

Table 1: Document revision history

Version	Date	Description
Rev. 1	17-Jul-2020	Initial version
Rev. 2	30-Nov-2020	Removed WLAN Certification and EU Conformance details and moved them to Release note document
Rev. 3	05-Jan-2021	Added Section for Wi-Fi Test Mode
Rev. 4	15-Mar-2021	Section 1.2.2 "802.11 b/g Features" : Removed PS Poll and null data Section 1.1.4 "802.11i - Security" : Added WPA3 SAE (R3) Section 1.2.4 "802.11i - Security" : Added WPA3 SAE (R3) and WPA2 +WPA3 (SAE) mixed mode Section 1.1.7 "General Features" : Added IPv6 Section 1.2.6 "General Features" : Added IPv6

1. Wi-Fi Features

1.1. Wireless Client Features

1.1.1. 802.11n - High Throughput

- 2.4 GHz band operation
- 2.4 GHz band supported channel bandwidths : 20 MHz
- Short/long guard interval (400 ns/800 ns)
- 1 Spatial stream (1x1)
- 11n data rates – Up to 72 Mbit/s (MCS0 to MCS7)
- Aggregated MAC Protocol Data Unit(AMPDU) Rx support
- Aggregated MAC Service Data Unit(AMSDU) -4k Rx support
- HT protection mechanisms
- Tx MCS rate adaptation (BGN)

1.1.2. 802.11 b/g Features

- 11 a/b/g data rates - Up to 54 Mbit/s
- Tx rate adaptation (BG)
- Fragmentation/defragmentation
- ERP protection, slot time, preamble

1.1.3. 802.11d Features

- 802.11d - Regulatory domain/operating class/country info

1.1.4. 802.11i - Security

- Embedded supplicant support
 - Open security
 - WPA-PSK, WPA2-PSK security (AES-CCMP encryption)
 - WPA + WPA2 mixed mode
 - WPA3 SAE (R3)

1.1.5. 802.11w - Protected Management Frames(PMF)

- PMF require and capable
- Unicast management frames - Encryption/decryption - using CCMP
- Broadcast management frames - Encryption/decryption - using BIP
- SA query request/response
- PMF support (embedded supplicant)

1.1.6. Power Save Mode

- Deep sleep
- IEEE power save

1.1.7. General Features

- Embedded MLME
- SW antenna diversity
- EU adaptivity support (ETSI cert)
- IPv6

1.2. Mobile AP Features

1.2.1. 802.11n - High Throughput

- 2.4 GHz band operation
- 2.4GHz band supported channel bandwidths : 20MHz
- Short/long guard Interval (400 ns/800 ns)
- 1 Spatial stream (1x1)
- 11n data rates - Up to 72 Mbit/s (MCS0 to MCS7)
- Tx MCS rate adaptation (BGN)
- Aggregated MAC Protocol Data Unit(AMPDU) Tx and Rx support
- Aggregated MAC Service Data Unit(AMSDU)- 4k Rx support
- HT protection mechanisms
- Max client support (up to 8 devices)

1.2.2. 802.11 b/g Features

- 11 b/g data rates - Up to 54 Mbit/s
- Tx rate adaptation (BG)
- ERP protection, slot time, preamble
- Handling associated STAs with IEEE PS

1.2.3. 802.11d Features

- 802.11d - Regulatory domain/operating class/country info

1.2.4. 802.11i - Security

- Embedded authenticator support
 - Open security
 - WPA2-PSK security (AES-CCMP encryption)
 - WPA2 +WPA3 (SAE) mixed mode
 - WPA3 SAE (R3)

1.2.5. 802.11w - Protected Management Frames(PMF)

- PMF require and capable
- Unicast management frames - Encryption/decryption - using CCMP
- Broadcast management frames - Encryption/decryption - using BIP
- SA query request/response

1.2.6. General Features

- Deep sleep
- SW antenna diversity
- Embedded MLME(MAC SubLayer Management Entity)
- EU adaptivity support (ETSI Cert)
- Automatic channel selection (ACS)
- Extended channel switch announcement (ECSA)
- IPv6

2. Simultaneous AP-STA Operation (Same Channel)

- AP-STA functionality

3. Test Mode

3.1.1. Wi-Fi

- Transmit Continuous Wave (CW) mode
- Transmit standard 802.11 packets
- Receive mode

Refer to **Section: wifi_test_mode sample application** in the document: *UM11442-NXP Wi-Fi and Bluetooth Demo Applications for i.MX RT platforms User Guide* for more details.

4. Notes

None.

5. Acronyms & Abbreviations

Acronyms	Definitions
AP	Access Point
WPA	Wi-Fi protected access
MLME	Mac Layer Management Entity
STA	Station
HT	High Throughput
MCS	Modulation and Coding Scheme
ERP	Extended Rate Physical
SAE	Simultaneous Authentication of Equals
CCMP	Counter Mode CBC-MAC Protocol

6. Legal Information

6.1. Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors. In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products. NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Evaluation products — This product is provided on an "as is" and "with all faults" basis for evaluation purposes only. NXP Semiconductors, its affiliates and their suppliers expressly disclaim all warranties, whether express, implied or statutory, including but not limited to the implied warranties of non-infringement, merchantability and fitness for a particular purpose. The entire risk as to the quality, or arising out of the use or performance, of this product remains with customer. In no event shall NXP Semiconductors, its affiliates or their suppliers be liable to customer for any special, indirect, consequential, punitive or incidental damages (including without limitation damages for loss of business, business interruption, loss of use, loss of data or information, and the like) arising out of the use of or inability to use the product, whether or not based on tort (including negligence), strict liability, breach of contract, breach of warranty or any other theory, even if advised of the possibility of such damages.

Notwithstanding any damages that customer might incur for any reason whatsoever (including without limitation, all damages referenced above and all direct or general damages), the entire liability of NXP Semiconductors, its affiliates and their suppliers and customer's exclusive remedy for all of the foregoing shall be limited to actual damages incurred by customer based on reasonable reliance up to the greater of the amount actually paid by customer for the product or five dollars (US\$5.00). The foregoing limitations, exclusions and disclaimers shall apply to the maximum extent permitted by applicable law, even if any remedy fails of its essential purpose.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

6.2. Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.