

by: NXP Semiconductors

1 Introduction

These release notes are for the motor-control middleware group of applications released together with the MCUXpresso SDK v2.12.0. This document provides a list of application examples, their notable features, supported hardware platforms, changes since the last MCUXpresso release, known issues, and links to further documentation. The latest documentation for the motor control SDK is available on http://www.nxp.com/motorcontrol_pmsm.

Contents

1	Introduction.....	1
2	Description.....	1
3	Examples.....	1
4	Supported platforms.....	2
5	What is new.....	2
6	Known issues.....	3
7	Feedback.....	3

2 Description

This motor-control middleware release contains application examples for the following three-phase electrical machine topologies:

- **AC Induction Motor (ACIM)**

The Field-Oriented Control (FOC) sensorless (machine model-based estimator algorithms are used to replace the position and speed sensor) application examples **mc_acim** were developed for the high-voltage development platform and Kinetis MCUs with a floating-point unit (see [Supported platforms](#) for exact platform support details). All examples integrate the Motor Identification (MID) software module and feature the Motor Control Application Tool (MCAT) to enable quick development.

See the user's guide in the *docs\MC* folder in your *SDK Documentation* package (see [Examples](#)) or the www.nxp.com/motorcontrol_acim web page for more details.

- **Permanent Magnet Synchronous Motor (PMSM)**

These FOC applications support both high- and low-voltage hardware platforms and various MCU types (see [Supported platforms](#) for exact platform support details). The following application types are available in the *mc_pmsm* folder of your SDK archive (see [Examples](#)):

- **pmsm_snsless** - Sensorless FOC examples utilizing both fractional and floating-point arithmetics. The Motor Identification (MID) software module in combination with the Motor Control Application Tool (MCAT) allow for rapid application development.
- **pmsm_enc** - This PMSM FOC application is identical to the **pmsm_snsless** example, except for the added option of acquiring the rotor position and speed from the encoder sensor.

See the user's guide in the *docs\MC* folder in your SDK Documentation package (see [Examples](#)) or the www.nxp.com/motorcontrol_pmsm web page.

All examples support the FreeMASTER interface for quick and simple application debugging, tuning, control, and monitoring. See www.nxp.com/freemaster and the application user's guide for more information.

3 Examples

The example projects are distributed only in the form of the MCUXpresso SDK Archive and the release documentation is available in the SDK Documentation package. To acquire both packages (specific to your development platform), use the online MCUXpresso SDK Builder tool and perform the following steps:

- Go to www.mcuxpresso.nxp.com.



- Click the **Select Development Board** button.
- Sign in or create the NXP account (if requested).
- Choose one of the supported platforms (see [Supported platforms](#) for the list of boards supported by this release).
- Click the **Build MCUXpresso SDK** button.
- Make sure that the **Motor Control** middleware is selected and click the **Download SDK** button.
- When the SDK Documentation and SDK Archive package build is done (you receive a notification email), it can be downloaded freely.

4 Supported platforms

The motor-control application examples were developed and tested with the following development tools:

- IAR Embedded Workbench IDE version 9.30.1
- Arm[®]-MDK - Keil[®] µVision[®] version 5.37
- MCUXpresso IDE version 11.6.0

FreeMASTER tool version 3.1.4 was used for application monitoring. See www.nxp.com/freemaster for the latest version.

The hardware platforms supported by this release are listed in the following table.

Table 1. Supported platforms

Board	mc_acim	pmsm_snsless	pmsm_enc
EVK-MIMXRT1170			✓ ^{fp, mid}
EVK-MIMXRT1160			✓ ^{fp, mid}
EVK-MIMXRT1064			✓ ^{fp, mid}
EVK-MIMXRT1060			✓ ^{fp, mid}
EVKB-MIMXRT1050			✓ ^{fp, mid}
EVK-MIMXRT1024			✓ ^{fp, mid}
EVK-MIMXRT1020			✓ ^{fp, mid}
EVK-MIMXRT1010		✓ ^{fp, mid}	
HVP-KV31F120M	✓ ^{fp, mid}	✓ ^{fp, mid}	
LPC55S69-EVK		✓ ^{fp, mid}	

^{fix} Fixed-point arithmetics.

^{fp} Floating-point arithmetics.

^{mid} Motor Identification (MID) software module is available.

^{reg_init} MCU peripherals initialized using MCUXpresso Config Tools.

5 What is new

This section describes all notable changes since the last motor-control middleware MCUXpresso SDK release v2.11.0.

1. New Motor Identification (MID)

Floating-point version of the **mc_pmsm** and **mc_pmsm_enc** examples features enhanced electrical parameters estimation algorithm which doesn't require characterized power stage and achieves higher estimation accuracy at motors with lower

electrical parameters. New MID was implemented to the devices, which were not supported in the MCUXpresso SDK release v2.11.0.

2. File management system add to the MCAT tool

Using file management system can be easily tuned and controlled motors with different parameters without any code recompilation. User has to choose required configuration file for the specific motor and load data to the target MCU using MCAT tool.

3. Updated documentation

Added chapter with step by step instructions how to replace TSA table with ELF file.

Equations for the calculation MCAT parameters and macros added to the documentation.

6 Known issues

This chapter contains the description of known issues or non-standard behavior of the released example.

1. User inputs are not generated in MCAT

After save mX_pmsm_appconfig.h file, macros defined by user are not generated or copied to the user section in the mX_pmsm_appconfig.h (marked by */* USER INPUT START */* and */* USER INPUT END */* comments).

7 Feedback

Your feedback is very important to us. Please feel free to leave a comment [here](#).

How To Reach Us

Home Page:

nxp.com

Web Support:

nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

While NXP has implemented advanced security features, all products may be subject to unidentified vulnerabilities. Customers are responsible for the design and operation of their applications and products to reduce the effect of these vulnerabilities on customer's applications and products, and NXP accepts no liability for any vulnerability that is discovered. Customers should implement appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, COOLFLUX, EMBRACE, GREENCHIP, HITAG, I2C BUS, ICODE, JCOP, LIFE VIBES, MIFARE, MIFARE CLASSIC, MIFARE DESFire, MIFARE PLUS, MIFARE FLEX, MANTIS, MIFARE ULTRALIGHT, MIFARE4MOBILE, MIGLO, NTAG, ROADLINK, SMARTLX, SMARTMX, STARPLUG, TOPFET, TRENCHMOS, UCODE, Freescale, the Freescale logo, Altivec, C-5, CodeTEST, CodeWarrior, ColdFire, ColdFire+, C-Ware, the Energy Efficient Solutions logo, Kinetis, Layerscape, MagniV, mobileGT, PEG, PowerQUICC, Processor Expert, QorIQ, QorIQ Qonverge, Ready Play, SafeAssure, the SafeAssure logo, StarCore, Symphony, VortiQa, Vybrid, Airfast, BeeKit, BeeStack, CoreNet, Flexis, MXC, Platform in a Package, QUICC Engine, SMARTMOS, Tower, TurboLink, UMEMS, EdgeScale, EdgeLock, eIQ, and Immersive3D are trademarks of NXP B.V. All other product or service names are the property of their respective owners. AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamiQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, μ Vision, Versatile are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

The ARM logo consists of the lowercase letters "arm" in a bold, blue, sans-serif font.

© NXP B.V. 2020.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 13 July 2022

Document identifier: MC2120RN