

Search the Arduino Website

Learning Examples (<http://arduino.cc/en/Tutorial/HomePage>) | Foundations (<http://arduino.cc/en/Tutorial/Foundations>) | Hacking (<http://arduino.cc/en/Hacking/HomePage>) | Links (<http://arduino.cc/en/Tutorial/Links>)

Writing a Library for Arduino

This document explains how to create a library for Arduino. It starts with a sketch for flashing Morse code and explains how to convert its functions into a library. This allows other people to easily use the code that you've written and to easily update it as you improve the library.

We start with a sketch that does simple Morse code:

```
int pin = 13;

void setup()
{
  pinMode(pin, OUTPUT);
}

void loop()
{
  dot(); dot(); dot();
  dash(); dash(); dash();
  dot(); dot(); dot();
  delay(3000);
}

void dot()
{
  digitalWrite(pin, HIGH);
  delay(250);
  digitalWrite(pin, LOW);
  delay(250);
}

void dash()
{
  digitalWrite(pin, HIGH);
  delay(1000);
  digitalWrite(pin, LOW);
  delay(250);
}
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=1>)

If you run this sketch, it will flash out the code for SOS (a distress call) on pin 13.

The sketch has a few different parts that we'll need to bring into our library. First, of course, we have the **dot()** and **dash()** functions that do the actual blinking. Second, there's the **ledPin** variable which the functions use to determine which pin to use. Finally, there's the call to **pinMode()** that initializes the pin as an output.

Let's start turning the sketch into a library!

You need at least two files for a library: a header file (w/ the extension .h) and the source file (w/ extension .cpp). The header file has definitions for the library: basically a listing of everything that's inside; while the source file has the actual code. We'll call our library "Morse", so our header file will be Morse.h. Let's take a look at what goes in it. It might seem a bit strange at first, but it will make more sense once you see the source file that goes with it.

The core of the header file consists of a line for each function in the library, wrapped up in a class along with any variables you need:

```
class Morse
{
public:
    Morse(int pin);
    void dot();
    void dash();
private:
    int _pin;
};
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=2>)

A class is simply a collection of functions and variables that are all kept together in one place. These functions and variables can be public, meaning that they can be accessed by people using your library, or private, meaning they can only be accessed from within the class itself. Each class has a special function known as a constructor, which is used to create an instance of the class. The constructor has the same name as the class, and no return type.

You need a couple of other things in the header file. One is an #include statement that gives you access to the standard types and constants of the Arduino language (this is automatically added to normal sketches, but not to libraries). It looks like this (and goes above the class definition given previously):

```
#include "Arduino.h"
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=3>)

Finally, it's common to wrap the whole header file up in a weird looking construct:

```
#ifndef Morse_h
#define Morse_h

// the #include statment and code go here...

#endif
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=4>)

Basically, this prevents problems if someone accidentally #include's your library twice.

Finally, you usually put a comment at the top of the library with its name, a short description of what it does, who wrote it, the date, and the license.

Let's take a look at the complete header file:

```
/*
Morse.h - Library for flashing Morse code.
Created by David A. Mellis, November 2, 2007.
Released into the public domain.
*/
#ifndef Morse_h
#define Morse_h

#include "Arduino.h"

class Morse
{
public:
    Morse(int pin);
    void dot();
    void dash();
private:
    int _pin;
};
```

```
};  
  
#endif
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=5>)

Now let's go through the various parts of the source file, Morse.cpp.

First comes a couple of #include statements. These give the rest of the code access to the standard Arduino functions, and to the definitions in your header file:

```
#include "Arduino.h"  
#include "Morse.h"
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=6>)

Then comes the constructor. Again, this explains what should happen when someone creates an instance of your class. In this case, the user specifies which pin they would like to use. We configure the pin as an output save it into a private variable for use in the other functions:

```
Morse::Morse(int pin)  
{  
    pinMode(pin, OUTPUT);  
    _pin = pin;  
}
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=7>)

There are a couple of strange things in this code. First is the **Morse::** before the name of the function. This says that the function is part of the **Morse** class. You'll see this again in the other functions in the class. The second unusual thing is the underscore in the name of our private variable, **_pin**. This variable can actually have any name you want, as long as it matches the definition in the header file. Adding an underscore to the start of the name is a common convention to make it clear which variables are private, and also to distinguish the name from that of the argument to the function (**pin** in this case).

Next comes the actual code from the sketch that you're turning into a library (finally!). It looks pretty much the same, except with **Morse::** in front of the names of the functions, and **_pin** instead of **pin**:

```
void Morse::dot()  
{  
    digitalWrite(_pin, HIGH);  
    delay(250);  
    digitalWrite(_pin, LOW);  
    delay(250);  
}  
  
void Morse::dash()  
{  
    digitalWrite(_pin, HIGH);  
    delay(1000);  
    digitalWrite(_pin, LOW);  
    delay(250);  
}
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=8>)

Finally, it's typical to include the comment header at the top of the source file as well. Let's see the whole thing:

```
/*  
Morse.cpp - Library for flashing Morse code.  
Created by David A. Mellis, November 2, 2007.  
Released into the public domain.  
*/  
  
#include "Arduino.h"  
#include "Morse.h"  
  
Morse::Morse(int pin)  
{  
    pinMode(pin, OUTPUT);  
    _pin = pin;  
}
```

```

void Morse::dot()
{
    digitalWrite(_pin, HIGH);
    delay(250);
    digitalWrite(_pin, LOW);
    delay(250);
}

void Morse::dash()
{
    digitalWrite(_pin, HIGH);
    delay(1000);
    digitalWrite(_pin, LOW);
    delay(250);
}

```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=9>)

And that's all you need (there's some other nice optional stuff, but we'll talk about that later). Let's see how you use the library.

First, make a **Morse** directory inside of the **libraries** sub-directory of your sketchbook directory. Copy or move the Morse.h and Morse.cpp files into that directory. Now launch the Arduino environment. If you open the **Sketch > Import Library** menu, you should see Morse inside. The library will be compiled with sketches that use it. If the library doesn't seem to build, make sure that the files really end in .cpp and .h (with no extra .pde or .txt extension, for example).

Let's see how we can replicate our old SOS sketch using the new library:

```

#include <Morse.h>

Morse morse(13);

void setup()
{
}

void loop()
{
    morse.dot(); morse.dot(); morse.dot();
    morse.dash(); morse.dash(); morse.dash();
    morse.dot(); morse.dot(); morse.dot();
    delay(3000);
}

```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=10>)

There are a few differences from the old sketch (besides the fact that some of the code has moved to a library).

First, we've added an `#include` statement to the top of the sketch. This makes the Morse library available to the sketch and includes it in the code sent to the board. That means if you no longer need a library in a sketch, you should delete the `#include` statement to save space.

Second, we now create an instance of the Morse class called **morse**:

```
Morse morse(13);
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=11>)

When this line gets executed (which actually happens even before the `setup()` function), the constructor for the Morse class will be called, and passed the argument you've given here (in this case, just 13).

Notice that our `setup()` is now empty; that's because the call to `pinMode()` happens inside the library (when the instance is constructed).

Finally, to call the `dot()` and `dash()` functions, we need to prefix them with **morse**. - the name of the instance we want to use. We could have multiple instances of the Morse class, each on their own pin stored in the `_pin` private variable of that instance. By calling a function on a particular instance, we specify which instance's variables should be used during that call to a function. That is, if we had both:

```
Morse morse(13);  
Morse morse2(12);
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=12>)

then inside a call to `morse2.dot()`, `_pin` would be 12.

If you tried the new sketch, you probably noticed that nothing from our library was recognized by the environment and highlighted in color. Unfortunately, the Arduino software can't automatically figure out what you've define in your library (though it would be a nice feature to have), so you have to give it a little help. To do this, create a file called **keywords.txt** in the Morse directory. It should look like this:

```
Morse    KEYWORD1  
dash     KEYWORD2  
dot      KEYWORD2
```

[Get Code] (<http://arduino.cc/en/Hacking/LibraryTutorial?action=sourceblock&num=13>)

Each line has the name of the keyword, followed by a tab (not spaces), followed by the kind of keyword. Classes should be KEYWORD1 and are colored orange; functions should be KEYWORD2 and will be brown. You'll have to restart the Arduino environment to get it to recognize the new keywords.

It's also nice to provide people with an example sketch that uses your library. To do this, create an **examples** directory inside the **Morse** directory. Then, move or copy the directory containing the sketch (let's call it **SOS**) we wrote above into the examples directory. (You can find the sketch using the **Sketch > Show Sketch Folder** command.) If you restart the Arduino environment (this is the last time, I promise) - you'll see a **Library-Morse** item inside the **File > Sketchbook > Examples** menu containing your example. You might want to add some comments that better explain how to use your library.

If you'd like to check out the complete library (with keywords and example), you can download it: Morse.zip (<http://arduino.cc/en/uploads/Hacking/Morse.zip>).

That's all for now but I'll probably write an advanced library tutorial soon. In the meantime, if you have any problems or suggestions, please post them to the Software Development forum (<http://www.arduino.cc/cgi-bin/yabb2/YaBB.pl?board=dev>).

Like { 62 Tweet { 19

635