

Big Data Analysis on Million Song Dataset (MSD)

ECE4721J: Methods and Tools for Big Data

Yiding Chang Yifan Shen Kexuan Huang Qinhang Wu


July 29, 2022




Overview

- Milestone 0: HDF5 Data Pre-process
- Milestone 1: Drill Database Query
- Milestone 2: Advanced Data Analysis

Workflow



Milestones



Section 1

Milestone 0: HDF5 Data Pre-process

Goals

1. Compact small hdf5 files into larger one
2. Read hdf5 file and extract the information
3. Convert hdf5 to Avro with Apache Avro

1. Compact small hdf5 files into larger one

\$ `python3 create_aggregate_file.py <IN> <OUT>`

- Input: a directory contains hdf5 song files
- Output: an aggregate hdf5 song file
- Example:

```
~/De/ECE4721J/p/p/m0 master !3 python3 src/create_aggregate_file.py MillionSongSubset/ data/compact.h5


need pg module and MBrainzDB folder of Python source code if you
want to use musicbrainz related functions, e.g. fill_hdf5_from_musicbrainz
found 10000 H5 files.
Aggregate file created, we start filling it.
17%|██████████          | 1721/10000 [02:06<08:55, 15.45it/s]
```

Figure 1: Compact 10000 hdf5 files into larger one

2. Read hdf5 files and extract the information

\$ `python3 display_song.py [FLAGS] <HDF5> <idx> <field>`

- Input: an hdf5 song file
- Output: specified field content
- Example:



```
~/De/ECE4721J/p/p/m0/src master !2 ?3 python3 display_song.py ../data/compact.h5 2 artist_name
artist_name: b'Casual'
DONE, showed song 2 / 2 in file: ../data/compact.h5
~/De/ECE4721J/p/p/m0/src master !2 ?3
```

The terminal output shows the command being executed and the resulting artist name 'Casual' for the second song in the file. A status bar at the bottom indicates the terminal is running 'base Py' at '07:23:34 PM'.

Figure 2: Get artist name of the second song in compacted hdf5 file

3. Convert hdf5 to Avro with Apache Avro

```
$ hdf5\_to\_avro.py [-h] -s <SCHEMA> -i <HDF5> -o <AVRO>
```

- Input:
 - an Avro schema file
 - an hdf5 song file to be converted
- Output: an Avro song file

Sample schema file in json format:

```
{  
  "namespace": "song.avro",  
  "type": "record",  
  "name": "Song",  
  "fields": [  
    {  
      "name": "artist_name",  
      "type": ["string", "null"]  
    },  
    {  
      "name": "title",  
      "type": ["string", "null"]  
    }  
  ]  
}
```

```

root@hadoop-master:/home/s/pj1/m0# python3 src/hdf5_to_avro.py -s schema/songs
.avsc -i data/compact.h5 -o data/output.avro
21:18:10 [Info] Convert a song file from hdf5 to Avro...
21:18:10 [Info] Avro schema path: schema/songs.avsc
21:18:10 [Info] hdf5 input path: data/compact.h5
21:18:10 [Info] Avro output path: data/output.avro
21:18:10 [Info] Avro schema file and hdf5 file exist
21:18:10 [Warning] Avro output file data/output.avro already exists
21:18:10 [Info] Parsing the Avro schema file...
21:18:10 [Info] Get the following fields:
        artist_hottnesss ["float", "null"]
        artist_id         ["string", "null"]
        artist_name       ["string", "null"]
        duration          ["float", "null"]
        energy            ["float", "null"]
        release           ["string", "null"]
        song_hottnesss    ["float", "null"]
        song_id           "string"
        tempo             ["float", "null"]
        title             ["string", "null"]
        track_id          ["string", "null"]
        year              ["int", "null"]
21:18:10 [Info] Found 10000 song(s)
21:18:10 [Info] Start converting hdf5 to Avro
21:18:10 Converting: 100%|██████████| 10000/10000 [00:22<00:00, 436.24it/s]

```

Figure 3: Convert compacted hdf5 file to Avro

Section 2

Milestone 1: Drill Database Query

Goals

Query Million Song Dataset (MSD) with Drill:

1. Find the range of dates covered by the songs in the dataset
2. Find the hottest song that is the shortest and shows highest energy with lowest tempo
3. Find the name of the album with the most tracks
4. Find the name of the band who recorded the longest song

1. The range of dates covered by the songs

- SQL:

```
-- Age of the oldest songs
```

```
SELECT 2022 - MAX(year) AS Age  
FROM hdfs.`/pj/m0/output.avro`;
```

```
-- Age of the youngest songs
```

```
SELECT 2022 - MIN(year) AS Age  
FROM hdfs.`/pj/m0/output.avro`  
WHERE year > 0;
```

1. The range of dates covered by the songs

- Results:

```
+-----+
|  Age  |
```

```
+-----+
```

```
| 12    |
```

```
+-----+
```

```
1 row selected
```

```
+-----+
|  Age  |
```

```
+-----+
```

```
| 96    |
```

```
+-----+
```

```
1 row selected
```

The oldest song's age is **96** and the youngest is **12**. As a result, the range of dates covered by the songs is **84** years.

2. The hottest song that is the shortest and shows highest energy with lowest tempo

- SQL:

```
SELECT title
FROM hdfs.`/pj/m0/output.avro`
WHERE song_hotttnesss <> 'NaN'
ORDER BY song_hotttnesss DESC,
        duration ASC,
        energy DESC,
        tempo ASC
LIMIT 10;
```

- Remarks: This query returns **5648** results, but we only display the first **10** records.

2. The hottest song that is the shortest and shows highest energy with lowest tempo

```

+-----+
|                                     |
|                               title |
+-----+
| b'Immigrant Song (Album Version)'  |
| b'Nothin' On You [feat. Bruno Mars] (Album Version)" |
| b'This Christmas (LP Version)'      |
| b'If Today Was Your Last Day (Album Version)' |
| b'Harder To Breathe'                |
| b'Blue Orchid'                      |
| b'Just Say Yes'                     |
| b'They Reminisce Over You (Single Version)' |
| b'Exogenesis: Symphony Part 1 [Overture]' |
| b'Inertiatic Esp'                   |
+-----+
10 rows selected (0.471 seconds)

```

3. The name of the album with the most tracks

- SQL:

```
SELECT release, COUNT(release) AS NumTrack
FROM hdfs.`/pj/m0/output.avro`
GROUP BY release
ORDER BY NumTrack desc
LIMIT 1;
```

- Results:

```
+-----+-----+
|      release      | NumTrack |
+-----+-----+
| b'Greatest Hits' | 21       |
+-----+-----+
1 row selected (0.695 seconds)
```

4. The name of the band who recorded the longest song

- SQL:

```
SELECT artist_name, duration
FROM hdfs.`/pj/m0/output.avro`
ORDER BY duration DESC
LIMIT 1;
```

- Results:

```
+-----+-----+
| artist_name | duration |
+-----+-----+
| b'UFO'      | 1819.7677 |
+-----+-----+
1 row selected (0.27 seconds)
```

Section 3


Milestone 2: Advanced Data Analysis

Goals

1. Determine distance between artists with adjacency matrix, using parallelized BFS
2. Propose similar songs with distance and “provide more diverse recommendations”
3. Implement the above algorithm in both Mapreduce and Spark
4. Compare the performance of Mapreduce and Spark


BFS with MapReduce - A Simple Example

Let's say we want to find artists similar to **A** with distance **3**, and we have following relationships (each edge has distance **1**):



Step 1: Initialize Graph File with Target Artist

Format: each line contains **Node** | **Distance** | **Neighbours**




A		0		A,B,C
B		∞		A,B
C		∞		A,C,D,E
D		∞		C,D
E		∞		C,E

Figure 5: Initialize Graph File

Step 2: Generate Distance Pairs in Mapper

Mapper: Generate **Neighbours**, **Node**, **Distance+1** if not itself



Step 3: Merge Distance Pairs in Reducer

Reducer: Merge the same **Neighbour**, keep distance **minimum**






Figure 6: Graph after 1 MapReduce Iteration

Iteration 2: Mapper



Iteration 2: Reducer

A, A, 0
 A, C, 2
 A, B, 2
 B, A, 1
 B, B, 1
 C, A, 1
 C, C, 1
 C, D, ∞
 C, E, ∞
 D, C, 2
 D, D, ∞
 E, C, 2
 E, E, ∞

Reduce
→

A|0|A,B,C

 B|1|A,B

 C|1|A,C,D,E

 D|2|C,D

 E|2|C,E




Figure 7: Graph after 2 MapReduce Iterations

BFS with Spark

- Same algorithm as is proposed before
- Implemented using Python with PySpark
- For the implementation, we:
 1. Convert data into RDD map
 2. Using Spark `sortByKey()` to sort RDD aggregated by node index and then combining the neighbours
 3. Using Spark `reduce()` to pick the minimum distance of different neighbours towards the central node
- Spark is assumed to be faster since subsequent steps are retained in memory with a trade-off of much more memory consumption

Benchmark

- Data size: around **200GB**
- Server: SJTU cluster with three machines
 - CPU: Dualcore Intel Xeon Processor (Skylake, IBRS)
 - Memory: 4GB

```
Searching for ARRMHA01187B9B9455
Time for MapReduce is 252 s
Searching for ARLGLTR1271F574286
Time for MapReduce is 250 s
Searching for ARRXPRY1187B9A8B34
Time for MapReduce is 252 s
Searching for AR1WWVL1187B9B0306
Time for MapReduce is 252 s
Searching for ARSRZFI11E2835D13C
Time for MapReduce is 252 s
```

Figure 8: MapReduce: around **250s**

```
AR150A1187B9B19E', 'AR220W11F50C4E3E0', 10000,
('ARZZQZ012509411C96', ('AR8GEH21187FB4F83E', 'ARCLH9U1
'ARG7X831187FB40B94', 'ARGXNL91187FB43641', 'ARH1PW91
'ARN1ETG1187FB41238', 'ARNXAVA1187FB4C57D', 'ARPA8501
'ARW508W1187B99D05A', 'ARZZQZ012509411C96\t', 10000,
('ARZZRAT1187B9892CA', ('AR0RYKS1187B98C179', 'AR359JA1
'ARD6VR81187B98FA76', 'AREMCGW121318C5844', 'ARGTLFS1
'ARJVBCE1187B9B30DB', 'ARJVBMK1187B99FFA9', 'AROA6811
'ARSU6FG1198866851B', 'ARZZRAT1187B9892CA\t', 10000,
('ARZZXCW11F50C4E4AB', ('ARAKXBP11F50C4A8F6', 'ARALTAC1
'ARFCHUX11EB9CD791E3', 'ARGTKL122ECCBB0FC', 'ARGWFNA1
'ARKVHSK1269FCFC92', 'ARMVCTR1252CCFA2F2', 'ARRGJY81
'ARTC1751187B99349C', 'ARU7RLY1187FB3C9B7', 'ARUHCNS1
'ARZXFRC1250940EE9D', 'ARZZXCW11F50C4E4AB\t', 10000,
('ARZZYRB1187B99D0B6', ('ARLISJI122ECCB8B81', 'ARZZYRB1
('ARZZZAI124207819C9', ('ARZZZAI124207819C9\t', 10000,
Removing temp directory /tmp/bfs_sp.root.20220729.072646

real    0m44.123s
user    0m0.431s
sys     0m0.592s
root@hadoop-master:/home/s/dev#
```

Figure 9: Spark: around **45s**

Reference

1. Million Song Dataset

`http://millionsongdataset.com`

2. Apache Avro Documentation

`https://avro.apache.org/docs/current/index.html`

3. Apache Spark Documentation

`https://spark.apache.org/docs/latest/`

Thanks for your attention!



Figure 10: Never Gonna Give You Up (by Rick Astley)