Internship Opportunities API Handover

Provider: Team 17 Internship Management

Consumer: Team 12 Campus Events and Clubs

Contract version: 1.0

Prepared: 7 November 2026, Thailand time

Production release verified

Production base URL: https://team17-internship.vercel.app

Public list: GET https://team17-internship.vercel.app/api/placements

Public detail: GET https://team17-internship.vercel.app/api/placements/{id}

Verified on 7 November 2026: list, detail, filters, detail-page links, and existing service status return HTTP 200; invalid limit returns 400. No authentication is required. Six fictional demo listings are stored in hosted Supabase PostgreSQL. Team 12 confirmation remains pending. The local setup instructions below are retained for development.

Local development background

The list and detail APIs are implemented and verified locally. The Opportunities, Saved opportunities, overview recommendations, and shareable detail pages read from the database. The local catalogue uses persistent PGlite PostgreSQL files under web/.data/placements. This is a real database-backed API, with six fictional demonstration listings marked is_demo=true. These are not genuine vacancies.

The production endpoints are deployed and publicly verified. Team 12 has not yet independently confirmed its integration. Application submission, advisor decisions, and weekly reports remain separate browser demos. No student records, CVs, or private applications are exposed here.

Connection details

Item	Value
Local base URL	http://127.0.0.1:3001
List endpoint	GET /api/placements
Detail endpoint	GET /api/placements/{id}
Human readable detail	/opportunities/{id}
Authentication	None for these two public read-only endpoints
Request body	None
Accept header	application/json recommended
Response encoding	JSON UTF-8
CORS	Public origins allowed; no credentials needed
Caching	Cache-Control: no-store; responses represent current availability
Public HTTPS base URL	Pending Team 17 deployment or tunnel

Do not give Team 12 a database password, service-role key, or the internal INTEGRATION_ADMIN_TOKEN. Existing A5 endpoints have separate contracts.

List query parameters

Parameter	Default	Accepted values and behavior
page	1	Integer 1 to 10000; one based
limit	12	Integer 1 to 50
status	open	Only open is supported
q	omitted	Up to 100 characters; case-insensitive literal substring in title, company, description, or skills
location	omitted	Up to 100 characters; case-insensitive literal substring
category	omitted	Up to 60 characters; case-insensitive exact category match
work_mode	omitted	remote, hybrid, or on-site

Filters combine with AND. Text filters are trimmed. Empty optional text filters act as no filter; an explicit empty status is invalid. Unknown or repeated parameters return 400. Page and limit must use positive decimal integer notation. No wildcard matching, private status queries, or custom sort parameters exist. Category examples in local fixtures are Design, Engineering, Marketing, and Data.

Results are sorted by application_deadline ascending, then id ascending. A record is public only when it is published, its published_at time has arrived, its status is open, and its deadline is today or later in Asia/Bangkok. Expiry occurs at the start of the following Thailand calendar day. Closed, draft, archived, expired, and future-publication records are excluded from both list and detail responses.

An empty search returns 200 with data=[] and total_pages=0. A page beyond the last page returns 200 with data=[] while retaining the true total. There is no frozen snapshot across requests; listings may change while a consumer paginates.

Ready to run requests

PowerShell or Windows Command Prompt:

```
curl.exe -i "http://127.0.0.1:3001/api/placements?status=open&page=1&limit=10"
curl.exe "http://127.0.0.1:3001/api/placements?q=React&work_mode=remote"
curl.exe "http://127.0.0.1:3001/api/placements/10000000-0000-4000-8000-000000000001"
```

POSIX shells can use curl instead of curl.exe. All URLs above are LOCAL examples. Replace only the base URL with the agreed HTTPS origin for Team 12's test.

Example list response

This is an actual local response captured on 2026-11-07T12:07:06.129Z. Request: GET /api/placements?limit=1. IDs are stable; request IDs, timestamps, deadlines, and counts should never be hardcoded by consumers.


```
{
  "success": true,
  "data": [
    {
      "id": "10000000-0000-4000-8000-000000000001",
      "title": "Product Design Intern",
      "skills": [
        "Figma",
        "UI/UX",
        "Prototyping"
      ],
      "status": "open",
      "company": "Sample Studio",
      "is_demo": true,
      "category": "Design",
      "location": "Bangkok, Thailand",
      "work_mode": "hybrid",
      "updated_at": "2026-11-07T11:56:20.628Z",
      "description": "Practice user research and turn ideas into thoughtful, accessible
  prototypes with a design mentor.",
      "published_at": "2026-11-07T11:56:20.628Z",
      "allowance_thb": 12000,
      "duration_weeks": 12,
      "application_deadline": "2027-02-05",
      "details_url": "http://127.0.0.1:3001/opportunities/
  10000000-0000-4000-8000-000000000001"
    }
  ],
  "pagination": {
    "page": 1,
    "limit": 1,
    "total": 6,
    "total_pages": 6,
    "has_next": true
  },
  "meta": {
    "api_version": "1.0",
    "request_id": "74bf4ab0-fed6-4758-9dad-02667b40baa8",
    "timestamp": "2026-11-07T12:07:06.129Z",
    "data_source": "local-postgresql"
  }
}
```

Field dictionary

Field	Type	Meaning
id	UUID string	Stable placement identifier; use to deduplicate
title	string	Opportunity title
company	string	Company or organizer name
description	string	Plain text description; do not treat as HTML
location	string	Display location, including Remote where relevant
category	string	Opportunity category
work_mode	string	remote, hybrid, or on-site
skills	string array	Skill tags
allowance_thb	integer or null	Monthly allowance in THB; null means unspecified
duration_weeks	integer	Internship duration in weeks
application_deadline	YYYY-MM-DD	Date in Thailand, not a workshop start time
status	string	Always open in public results
is_demo	boolean	True identifies a fictional demonstration record
published_at	ISO 8601 UTC timestamp	Publication time
updated_at	ISO 8601 UTC timestamp	Last update time; writers must maintain it
details_url	absolute HTTP or HTTPS URL	Link back to Team 17's human readable detail page

The detail endpoint returns {success:true,data:PLACEMENT,meta:META}, with no pagination object. It accepts no query parameters. It applies the same visibility rules as the list endpoint and returns 404 for an existing record that is hidden. Malformed UUIDs return 400. A details_url is not a registration or application API.

Pagination contains page, limit, total, total_pages, and has_next. Metadata contains api_version, request_id, timestamp, and data_source. A local response identifies data_source=local-postgresql; hosted PostgreSQL uses postgresql. Each response also includes X-Request-Id and exposes that header to browser clients.

Error handling

HTTP	Code	Consumer action
400	INVALID_QUERY	Fix unsupported, repeated, or malformed query parameters; do not blindly retry
400	INVALID_ID	Supply a valid UUID
404	PLACEMENT_NOT_FOUND	Hide the stale link or explain that it is unavailable
503	PLACEMENTS_UNAVAILABLE	Show a temporary-unavailable state; retry with backoff

Error envelope: {success:false,error:{code,message,retryable},meta:{...}}. Only 503 sets retryable=true. Storage connection details are never returned. GET is the supported integration operation. OPTIONS returns 204 for CORS; HEAD is framework supported. Unsupported write methods return 405 from Next.js, whose body is not part of this JSON contract. This API does not create bookings, registrations, applications, or callbacks. It does not publish webhooks.

Team 12 integration steps

1. Agree that internship opportunities satisfy your discovery use case. These records are not scheduled career workshops and have no event start time.

2. Set one backend configuration value for the shared HTTPS base URL.

3. Fetch GET /api/placements?page=1&limit=10 with a bounded client timeout, for example 10 seconds. Check both HTTP status and the success field.

4. Display title, company, description, location, and application_deadline. Use the deadline label, not event date. Render strings as text.

5. Link users to details_url. Deduplicate using id; do not use titles as keys.

6. Clearly label is_demo=true records in a test environment. Genuine discovery content requires reviewed real listings or explicit agreement on demo-only use.

7. Follow pagination.has_next to request the next page. Refresh on user request or a modest agreed polling interval; do not poll continuously.

8. Handle empty results, 404, 503, and network timeout without breaking your app.

9. Keep the returned request_id, HTTP status, and UTC timestamp for evidence.

10. Send Team 17 the result and a screenshot showing URL, status, and response.

```
const params = new URLSearchParams({ page: '1', limit: '10', status: 'open' });
const response = await fetch(BASE_URL + '/api/placements?' + params, {
  headers: { Accept: 'application/json' },
  signal: AbortSignal.timeout(10000)
});
const body = await response.json();
if (!response.ok || !body.success) {
  throw new Error(body.error?.code || 'PLACEMENTS_REQUEST_FAILED');
}
// body.data -> discovery cards; body.pagination -> next-page controls
```

Team 17 local operations

From the repository root, enter web, install with npm ci, and configure web/.env.local using web/.env.example. Set PLACEMENTS_DB_MODE=local and PUBLIC_SITE_URL=http://127.0.0.1:3001. No database password is needed for the LOCAL catalogue. Existing integration activity uses its own separate connection.

```
cd web
npm ci
npm run placements:setup
npm test
npm run build
npm run dev -- --hostname 127.0.0.1 --port 3001
```

Run setup while the server is stopped. It applies the new migration only if the local table is missing and inserts six fixed-ID demo records with ON CONFLICT DO NOTHING. Rerunning it does not overwrite edited records or extend their deadlines. The initial fixtures expire 90 days after first setup. Local files survive server restarts and are ignored by Git. Do not share or delete .data to hand over the API.

Team 17 sharing and deployment

For a temporary coordinated test, use your approved HTTPS tunnel to local port

3001. Set PUBLIC_SITE_URL to the tunnel origin and restart the app so returned details_url values point to that public origin. The tunnel and local server must remain running. Do not send the localhost address to Team 12 as their base URL. No tunnel has been opened by this implementation.

For a hosted release, first review and apply only the new migration supabase/migrations/202611070001_public_placements.sql to the chosen PostgreSQL database once, following the team's migration history. Existing A5 data is independent. Do not reapply old migrations or reset the database. Add reviewed placements through a trusted database operator; the local setup command does not populate or modify hosted data. Published inserts require published_at and an open deadline; maintain updated_at whenever editing a record.

Deploy Next.js with root directory web. Set PLACEMENTS_DB_MODE=postgres, PLACEMENTS_DATABASE_URL to a private Supabase PostgreSQL connection string, and PUBLIC_SITE_URL to the final HTTPS frontend origin. DATABASE_URL is a server-only fallback if PLACEMENTS_DATABASE_URL is omitted. The supplied CA certificate is used to verify TLS. Prefer a dedicated read-only database role with SELECT on public.placements and a deliberately scoped RLS read policy; do not give these credentials to consumers. Supabase's privileged postgres user can also read the table, but should not be the long-term runtime identity. A session or transaction pooler may be needed when hosting lacks direct IPv6 connectivity; prepared statements are disabled in the hosted adapter. Never use local PGlite mode on Vercel; local mode is explicitly rejected there.

Verify GET /api/placements from outside the development machine, verify a returned details_url, then update the base_url in the Postman collection and complete the joint test. Do not claim the new production endpoint is ready before these checks.

Handover acceptance checklist

[done] Database-backed local list and detail endpoints implemented.

[done] Six fictional records stored locally and labeled is_demo=true.

[done] Opportunities, saved listings, and shareable detail links use these APIs.

[done] Automated tests cover visibility, filters, pagination, validation, errors, SQL-like input, RLS installation, and redaction; 15 tests passed on 7 November.

[done] TypeScript production build passed; local HTTP 200, 400, and 404 verified.

[done] Browser search, save, and detail navigation verified locally.

[pending] Team 12 confirms the internship-listing contract meets its needs.

[pending] Team 17 supplies reviewed data or both teams agree on demo-only content.

[pending] Public HTTPS deployment or agreed temporary tunnel is verified.

[pending] Team 12 successfully calls the list endpoint from its backend.

[pending] Both teams retain matching request_id, timestamps, screenshots, and logs.

[pending] Team 12 confirms links and field mapping work in its discovery interface.

This checklist records local completion only. Partner sign-off and production availability remain pending. Tests here are not evidence of Team 12 participation.

Files to exchange

- Team17-Team12-API-Handover.pdf: shareable handover guide.

- README.md: editable technical guide (this file).

- placements.postman_collection.json: importable requests with base_url and placement_id collection variables; no secrets.

- placements.openapi.json: machine-readable OpenAPI 3.1 contract.

- example-list.json and example-detail.json: actual captured local responses.

Ready to send message

Hi Team 12, we have implemented a public read-only internship opportunities API and verified it locally. The main endpoint is GET /api/placements, with an optional GET /api/placements/{id} for details. It includes company, description, location, deadline, and a details link, with filters and pagination. No authentication is required. The current six records are fictional demonstration data. Please review the attached contract and confirm this meets your discovery use case. We will provide the verified HTTPS base URL and arrange a joint test before handover.