[illegible]

[illegible]

by [illegible]

□□

概述 2
表格 2
提示框 2
元素系统 2
龙 2
示例 2
属性框 2
人物框 3
法术 3
关于 3
UHEg 3
项目结构 3
快速开始 3
创建项目后清单 3
元素系统 3
字体 4
注意 4
部署网页 4
Cloudflare Pages 4
EdgeOne Pages 4

□□

本模板用于排版架空世界设定、冒险与规则文档。写正文时把每□章拆成 □容/ 下的独立 `.typ` 文件,在 □容/`index.typ` 里 `#include` 进来即可。

表格

□□□□

d10	结果
1	无事发生
2-8	遇到路人
9	拾获物品
10	触发事件

提示框

提示

提示框用于把□段说明从正文里单独拎出来强调。

正文照常书写,段落之间空□行即可。Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aeque doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem.

元素系统

同□个概念在不同「元素系统」下可以叫不同名字。数据放在附件/元素系统.csv,由配置.typ 的元素系统数据注入,# 元素总表() 列出全部:

元素	默认	别名	学术
龙	—	—	—
古龙	龙	—	古代龙
巨人	—	石头人	巨怪
法术	—	—	术式

正文引用概念用 # 元素[id]。当前是普通系统,# 元素[古龙] 取 CSV「默认」列的 “龙”(该列留空则取 id 本身),并自动链接到下面这条定义。

龙

古龙是龙的成年个体。

编译时传 `--input` 元素系统=学术,# 元素[古龙] 就显示为“古代龙”; 传 `--input` 元素系统=别名,总表里「巨人」□行会显示为“石头人”。

□□

属性框

box(width: 100%, inset: (x: 12pt, y: 7pt), fill: if type(标题色) == color { 标题色 } else { gradient.linear(.. 标题色) },)[

□□□

[illegible] [illegible] [illegible]

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
15 (+2)	11 (+0)	16 (+3)	6 (−2)	11 (+0)	7 (−2)

[illegible] [illegible] [illegible] [illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible], [illegible], [illegible]

[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
10 (+0)	12 (+1)	11 (+0)	13 (+1)	14 (+2)	15 (+2)

[illegible] [illegible],[illegible]

[illegible] [illegible],[illegible]

[illegible]

- [illegible]
- [illegible],[illegible]

[illegible]

[illegible]

2 [illegible] [illegible]

[illegible]: 1 [illegible] [illegible]: [illegible] [illegible]: 1 [illegible] [illegible]: V, S

[illegible],[illegible]Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore.

[illegible]

[illegible] README.md [illegible]——Markdown [illegible]:

UHEG

[illegible]UnderHell Template[illegible]/[illegible]/[illegible]

[illegible]

- [illegible].typ —— [illegible]
- Makefile —— [illegible]pdf / web / watch / clean[illegible]
- [illegible]/ —— [illegible] .typ [illegible] index.typ [illegible]
- [illegible]/ —— [illegible] [illegible].typ [illegible] web_post.sh
- [illegible]/ —— [illegible] [illegible].csv
- [illegible]/ —— [illegible] Git LFS [illegible] .gitattributes[illegible]
- .webfonts/ —— [illegible]. [illegible] .webfonts/README.md[illegible]
- SKILL.md —— AI [illegible]
- .github/workflows/web.yml —— [illegible]
- LICENSE —— [illegible]
- README.md —— [illegible] [illegible]/[illegible].typ [illegible]

[illegible]

```
make pdf    # □□/ □□□ .typ → PDF□□□□□□□□
make web    # □□□□□□□□□□□ CSS□□□□□□□□□□
make watch  # □□□□□□□□□□
```

[illegible]

- [ ] [illegible],[illegible]
- [ ] [illegible] [illegible].typ [illegible]
- [ ] [illegible] [illegible]/ [illegible] [illegible]/index.typ [illegible] #include
- [ ] [illegible] [illegible]/[illegible].csv [illegible]
- [ ] [illegible] .woff2 [illegible] .webfonts/ [illegible] .webfonts/README.md[illegible]
- [ ] [illegible][illegible].typ [illegible] [illegible]
- [ ] [illegible] Settings → Actions [illegible]
- [ ] [illegible] main [illegible] .github/workflows/web.yml[illegible] web [illegible]
- [ ] [illegible] web [illegible]
- [ ] [illegible] LICENSE [illegible]

[illegible]

[illegible]

[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]

元素	普通	别名	学术
巨人	巨人	石头人	巨怪

字体

网页的自托管字体放在 `.webfonts/`（. 开头，默认隐藏）默认不含字体文件（模板仓库不使用 Git LFS 托管大字体）需要时按 `.webfonts/README.md` 放入四个 `.woff2`，`make web` 会把它们拷到产物的 `dist/webfonts/`，CI 再按用字子集化；没放字体也能正常构建，只是网页回退到系统字体。

注意

- 引用概念用 `#元素[古龙]`，取词见 元素系统

本仓库也包含「导入 Markdown」示例：`内容/关于.typ` 会把这个 `README.md` 渲染进文档。

详见 https://typst.app/docs/。

部署网页

`make web` 产出的 `dist/` 是纯静态站点，可直接托管。仓库已内置并启用 GitHub Actions 工作流 `.github/workflows/web.yml`：推送 `main` 后会把产物强制推到 `web` 分支；然后 在托管平台绑定 `web` 分支并关闭平台构建即可。

Cloudflare Pages

1. 进入 Cloudflare 控制台 → **Workers & Pages** → 创建 → **Pages** → 连接到 **Git**，授权并选择本仓库。
2. 生产分支 选 `web`（即工作流产出的静态分支）
3. 构建设置保持不构建：
   - 框架预设：None
   - 构建命令：留空
   - 构建输出目录：`/`
4. 保存并部署。之后每次推送 `main`，工作流更新 `web` 分支，Cloudflare 会自动重新部署。
5. 在 自定义域 中绑定自己的域名即可。

EdgeOne Pages

1. 进入 腾讯云 EdgeOne 控制台 → 创建项目 → 导入 **Git** 仓库，授权 GitHub 并选择本仓库。
2. 生产分支 选 `web`。
3. 构建设置保持不构建：
   - 框架预设：其他 / 无
   - 构建命令：留空
   - 输出目录：`/`（根目录）
4. 点击 开始部署。之后推送 `main` 触发工作流更新 `web` 分支，EdgeOne 会自动重新部署。
5. 在 域名管理 中绑定自定义域名（关联大陆加速区域需完成备案）