Kasi Yedumati · Full Stack Training

Module: Arrays

Phase: Core Java
Previous module: Strings
Next module: Methods

Module Outcome:

- Store a fixed list of marks or prices and loop by index from `0`
- Know length vs last index so `ArrayIndexOutOfBounds` is not a surprise
- Leave `ArrayList` for Collections week — today is the raw array

Collections (`ArrayList`) are a later module. Stay on arrays.

What is an array?

An **array** is a numbered row of boxes of the **same type**. Index `0` is the first mark.

📦 Order | 👤 Employee | 🏦 Bank | 💰 Payroll | 💻 Laptop


Where used?
- College apps — marks per subject, attendance flags (syntax — keep generic)
- **Swiggy** — prices for a few SKUs in a demo
- **Employee Management Portal** — three allowances in a row
- **HDFC Bank** — last few transaction amounts
- **Apollo Hospitals** — a short queue of token numbers

```
marks:  [ 78 | 82 | 91 | 65 | 88 ]
index:     0    1    2    3    4
```

Purpose: Store many values without inventing `m1, m2, m3, …`. Size is **fixed** after you create the array.

```
int[] marks = new int[5];
int[] given = {78, 82, 91};
```

Visual — index map:



Key takeaways:
- Same type in every slot
- Index starts at 0; last index is `length - 1`
- `length` is a field, not a method (`marks.length`)

Important Concepts and Definitions

Term	Definition
Array	Fixed-size sequence of one type
Index	Position starting at 0
length	Number of slots (`marks.length`)
Enhanced for	`for (int m : marks)` — visit each element
2D array	Array of arrays — rows and columns
Linear search	Check each slot until you find the value
Off-by-one	Using `<= length` and falling off the end

Step-by-Step Notes (With Annotated Code)

Step 1: Create and read

```
public class CreateArray {
    public static void main(String[] args) {
        int[] marks = {78, 82, 91};
        System.out.println(marks[0]);
        System.out.println(marks[2]);
        System.out.println(marks.length);
    }
}
```

Expected Output:

```
78
91
3
```

Note:
- Wrong: `marks[3]` on a length-3 array → `ArrayIndexOutOfBoundsException`.
- Prefer: last index `marks.length - 1`.

Store names Priya, Ravi, and Meera in a `String` array, then print index 1 and the length.

```
public class NamesArray {
    public static void main(String[] args) {
        String[] names = {"Priya", "Ravi", "Meera"};
        System.out.println(names[1]);
        System.out.println(names.length);
    }
}
```

Create an `int` array of length 3, print the default value at index 0, set index 1 to 90, and print it.

```
public class EmptySlots {
    public static void main(String[] args) {
        int[] slots = new int[3];
        System.out.println(slots[0]);
        slots[1] = 90;
        System.out.println(slots[1]);
    }
}
```

Expected Output:

```
0
90
```

Step 2: Classic for vs enhanced for

```
public class LoopMarks {
    public static void main(String[] args) {
        int[] marks = {78, 82, 91};
        for (int i = 0; i < marks.length; i++) {
            System.out.println("Index " + i + ": " + marks[i]);
        }
        int sum = 0;
        for (int m : marks) {
            sum = sum + m;
        }
        System.out.println("Sum: " + sum);
    }
}
```

Expected Output:

```
Index 0: 78
Index 1: 82
Index 2: 91
Sum: 251
```

Enhanced `for` cannot easily **update by index**. Use classic `for` when you need `i`.

Store three INR amounts (`45.0`, `120.0`, `80.5`) and print each with an enhanced `for`.

```
public class Expenses {
    public static void main(String[] args) {
        double[] inr = {45.0, 120.0, 80.5};
        for (double x : inr) {
            System.out.println(x);
        }
    }
}
```

Average marks 80, 70, and 90 and print the result with two decimal places.

```
public class MarksAvg {
    public static void main(String[] args) {
```

```
        int[] marks = {80, 70, 90};
        int sum = 0;
        for (int m : marks) {
            sum += m;
        }
        double avg = sum / (double) marks.length;
        System.out.printf("Average: %.2f%n", avg);
    }
}
```

Step 3: Max and linear search

```
public class MaxSearch {
    public static void main(String[] args) {
        int[] marks = {78, 91, 65, 88};
        int max = marks[0];
        for (int i = 1; i < marks.length; i++) {
            if (marks[i] > max) {
                max = marks[i];
            }
        }
        System.out.println("Max: " + max);

        int find = 65;
        int foundAt = -1;
        for (int i = 0; i < marks.length; i++) {
            if (marks[i] == find) {
                foundAt = i;
                break;
            }
        }
        System.out.println("Found at: " + foundAt);
    }
}
```

Expected Output:

```
Max: 91
Found at: 2
```

Find and print the minimum of marks 78, 91, and 65.

```
public class MinMark {
    public static void main(String[] args) {
        int[] marks = {78, 91, 65};
        int min = marks[0];
        for (int m : marks) {
            if (m < min) {
                min = m;
            }
        }
        System.out.println(min);
    }
}
```

Count how many marks in `{90, 88, 95, 70}` are 90 or above, then print the count.

```
public class Toppers {
    public static void main(String[] args) {
        int[] marks = {90, 88, 95, 70};
        int count = 0;
        for (int m : marks) {
            if (m >= 90) {
                count++;
            }
        }
        System.out.println(count);
    }
}
```

Expected Output:

```
2
```

Step 4: 2D array — two students, three subjects

```
public class MarksTable {
    public static void main(String[] args) {
        int[][] table = {
            {80, 70, 90},
            {60, 75, 85}
        };
        System.out.println(table[0][2]);
        for (int r = 0; r < table.length; r++) {
            int rowSum = 0;
            for (int c = 0; c < table[r].length; c++) {
                rowSum += table[r][c];
            }
            System.out.println("Student " + r + " total: " + rowSum);
        }
    }
}
```

Expected Output:

```
90
Student 0 total: 240
Student 1 total: 220
```

Print every element of row 0 in a 2-by-2 table `{{1, 2}, {3, 4}}`.

```
public class PrintRow {
    public static void main(String[] args) {
        int[][] t = {{1, 2}, {3, 4}};
        for (int c = 0; c < t[0].length; c++) {
            System.out.println(t[0][c]);
        }
    }
}
```

Create a 2-by-3 boolean lab-seat grid and print the number of rows and the length of row 0.

```
public class SeatGrid {
    public static void main(String[] args) {
        boolean[][] lab = new boolean[2][3];
        System.out.println(lab.length);
        System.out.println(lab[0].length);
    }
}
```

Step 5: Marks manager idea — array + `count`

Fixed array of 20; `count` is how many marks are actually stored.

```
int[] marks = new int[20];
int count = 0;
// add: marks[count] = 88; count++;
// list: for (int i = 0; i < count; i++) ...
```

Guard empty average: `if (count == 0) { print message; } else { ... }`.

Lab kit: 15_Lab_Assets/07_marks_manager.

Practice Exercises

Basic

1. Create `int[] a = {10, 20, 30}` and print the last element using `length`.

Model answer: `System.out.println(a[a.length - 1]);`

2. Enhanced-for print of `{"idli", "dosa", "tea"}`.

Model answer: `for (String item : items) { System.out.println(item); }`

3. Sum of `{5, 5, 5}`.

Model answer: Loop add; print `15`.

4. What exception is `a[3]` on length 3?

Model answer: `ArrayIndexOutOfBoundsException`.

Intermediate

1. Average of five marks; print `%.2f`. Empty array: print a message (length 0).

Model answer: If `marks.length == 0` print skip; else sum / length.

2. Linear search: print index of `88` or `-1`.

Model answer: Loop; `break` when found; start `foundAt = -1`.

3. 2D: print each row total for `{{10,10},{20,30}}`.

Model answer: Nested `for`; row sums 20 and 50.

4. Marks menu: add (if `count < marks.length`), list, average (safe if `count==0`), toppers ≥90, quit.

Model answer: `while` menu; store in array + `count`. No `ArrayList`.

Interview-Oriented

1. Array vs later `List` in one sentence.

Model answer: Array size is fixed at creation; `List` can grow (Collections week).

2. Is `length` a method on arrays?

A: No. It is a **field**: `arr.length`. Strings use `length()`.

3. Enhanced for vs index for.

A: Enhanced for reads each element. Index for when you need the position or to write `arr[i] = …`.

4. Default values in `new int[3]`?

A: `0`. `boolean` is `false`. Object arrays are `null` (do not use that much yet).

Mini-Project (Assignment): Student Marks Manager (CLI)

Lab kit: 15_Lab_Assets/07_marks_manager

What to build

Menu: add mark (0–100), list, average (safe if empty), toppers (≥90), quit. Store in an `int[]` plus `count`.

Stretch

- Remove last mark (`count--`).
- **Later — Collections:** switch storage to `ArrayList`.

Done when

- [ ] Menu loop until quit
- [ ] Empty average does not crash (no divide by zero)
- [ ] Toppers printed by looping `0 .. count-1`
- [ ] No `ArrayList` in the core path

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

Q1. What is an array?
A: A fixed-size, indexed collection of the same type.

Q2. Why does index start at 0?
A: Language design; first slot is offset zero from the start.

Q3. How do you avoid `ArrayIndexOutOfBoundsException`?
A: Only use `0` through `length - 1`. For a partial fill, loop to `count`, not `length`.

Q4. What is a 2D array?
A: An array whose elements are arrays — a table of rows and columns.

Q5. Linear search cost in simple words?
A: You may look at every element. Fine for class-size lists; interviews mention “O(n)” later.