Kasi Yedumati · Full Stack Training

Biweekly Assessment BW05 — Weeks 9–10

Sessions covered: S41–50
Topics: Exception handling (try/except + custom), files/CSV/logging, Git/GitHub, MySQL setup and SELECT intro
Timebox: 45–60 minutes (homework or Friday of the even week).
Rules: Closed notes unless your trainer allows open notes. No copying.
Coding constraint: Files + SQL concepts OK.

A. Multiple Choice (12)

Circle the best option.

1. `with open(...) as f:` mainly helps:
   a) Faster CPU always
   b) Auto-close the file
   c) Skip encoding
   d) Avoid Python
2. CSV rows are often read with:
   a) django only
   b) React
   c) pip freeze
   d) csv.DictReader
3. Logging levels include:
   a) HTML/CSS
   b) SELECT/INSERT
   c) DEBUG/INFO/WARNING/ERROR
   d) Only PRINT
4. `git add` then `git commit`:
   a) Runs tests only
   b) Stages then records a snapshot
   c) Deletes repo
   d) Deploys to AWS
5. `git push` sends commits to:
   a) Local only
   b) Remote (e.g. GitHub)
   c) MySQL
   d) VS Code theme
6. Primary key in SQL uniquely identifies:
   a) A row
   b) A CSS class
   c) A React prop
   d) A column type
7. `SELECT ... WHERE` is used to:
   a) Commit git
   b) Create venv

c) Filter rows that match a condition
d) Style HTML

8. Parameterized queries help prevent:
   a) f-string typos
   b) Slow CSS
   c) SQL injection
   d) Git conflicts
9. Custom exception classes usually inherit from:
   a) str
   b) Exception
   c) list
   d) dict
10. `README.md` on GitHub should:
    a) Explain how to run the project
    b) Store passwords
    c) Replace git
    d) Be empty
11. `finally` block runs:
    a) Usually always after try
    b) Never
    c) Only on success
    d) Only on error
12. Foreign key links:
    a) Git branches only
    b) Two unrelated files
    c) A column to another table's key
    d) CSS to HTML only

B. Coding (2)

1. Write `add_expense(title, amount, category)` that raises `ValueError` if amount ≤ 0, else appends to a list of simple objects/dicts. Then sketch `export_csv(path)` using `csv.DictWriter`.

```
# your code
```

2. Write a safe age reader: convert input to int; if out of 1–120 raise a custom `InvalidAgeError`. Show try/except in a tiny demo loop.

```
# your code
```

C. Short answer (1)

Why commit often with clear messages during training? If `git push` is rejected because the remote moved, what do you do (no force-push)?

(Write 3–6 sentences.)