Kasi Yedumati · Full Stack Training

Module: Django Introduction and Setup

Theme apps this phase: Blog · Task Manager · Booking · Student Portal · CampusCart E-commerce

Previous module: JavaScript DOM Forms
Next module: URLs Views Templates Static

> **Module Outcome:**
> - `startproject`, run the server, and know what each default file is for
> - See request → Django → response as a story, not magic
> - Point settings at MySQL the safe way (`os.environ`) before writing views

Prerequisites

- MySQL 8+ available locally or on the lab server
- Completed MySQL labs + Python ↔ MySQL bridge (or parallel schedule)

What is Django?

Django is a free, open-source **web framework** written in Python. A **framework** is a pre-built skeleton that handles common web tasks so you write business logic faster — routing URLs, talking to databases, user login, admin panels, and security defaults.

Web framework means: you build **web applications** (sites/apps accessed through a browser or mobile app via HTTP), not desktop `.exe` apps.

> **Where used?**
> - Campus / student portal — login, marks, announcements (MTV + admin)
> - **Swiggy** / CampusCart catalog, orders, staff admin for products
> - Blog / Task Manager / Booking — course theme apps on the same Django project
> - IT services — internal HR / inventory portals with built-in admin
> - Capstone — full CRUD + auth stack recruiters expect on GitHub
>
> **Why Django in India?** Startups (Swiggy-era stacks), IT services (maintenance portals), ed-tech (student portals), and product companies hire **Python Django developers** for rapid MVP delivery, built-in admin, and strong ORM (Object-Relational Mapping — Python classes instead of raw SQL for most CRUD).

MTV Pattern (Model–Template–View)


Django uses **MTV**, often compared to **MVC** (Model–View–Controller) from Java/Spring:

MTV (Django)	MVC (typical)	Role
Model	Model	Data structure + database logic (`models.py`)
Template	View	HTML presentation (`.html` files)
View	Controller	Python function/class handling request logic (`views.py`)

MTV (Django)	MVC (typical)	Role
URL dispatcher	Routes config	Maps `/blog/` to the right view (`urls.py`)

Request flow (simple): Browser requests `http://127.0.0.1:8000/` → **URLconf** finds matching path → **View** runs Python code → **Template** renders HTML → Response sent to browser.

Visual — Django MTV on one CampusCart page visit:



Key takeaways:
- URL → View → Model (optional) → Template → HTML response
- MTV ≈ MVC with Django naming (Template ≈ View, View ≈ Controller)
- Admin + ORM are why Indian portals pick Django for fast CRUD

Think: **URL** picks the door, **View** is the worker, **Model** is the filing cabinet, **Template** is the printed page.

Virtual Environment (`venv`)

A **virtual environment** is an isolated folder containing its own Python and installed packages. Without it, Project A's Django 4 and Project B's Django 5 would conflict globally.

Terms:
- `venv` — folder name convention for the environment
- **Activate** — tell your terminal to use that environment's Python/pip
- `pip` — package installer for Python (`pip install django`)

Note:
- Forgot to activate venv → `ModuleNotFoundError: django`. Run `source venv/bin/activate` (Windows: `venv\Scripts\activate`) before pip/manage.py.
- Do not commit `venv/` — add it to `.gitignore` or the repo balloons.

Project vs App

- **Project** — entire website configuration (`settings.py`, root `urls.py`, `manage.py`). Example: `campus_portal` (Student Portal theme).
- **App** — reusable feature module inside the project. Example: `blog`, `tasks`, `booking`. One project contains many apps.

Key Files After Setup

File	Purpose
`manage.py`	Command-line utility — run server, migrations, shell
`settings.py`	Database, installed apps, middleware, static files config
`urls.py` (project)	Root URL routing
`wsgi.py` / `asgi.py`	Entry points for production servers (intro only today)

MySQL Connection (Concept)

Django does not ship MySQL driver inside the box. You install **`mysqlclient`** (preferred on Linux/Mac) or **`PyMySQL`** (common on Windows labs). **`DATABASES`** in `settings.py` tells Django which engine, database name, user, password, and host to use.

Concepts

1. Django 5.x Modern Practices (This Course)

- Use **`path()`** in URLs (not legacy `url()` with regex unless needed)
- **`django-admin startproject config .`** — project config package named `config`, dot places `manage.py` at root
- **Environment variables** for secrets (intro today; full module in Security & Deployment)
- **One app per domain feature** — `blog`, `inventory` for CampusCart, not one giant `models.py`

> **Note:**
> - `startproject` without a trailing `.` nests an extra folder. Prefer `django-admin startproject config .` (or move files if you already nested).
> Create a venv, install Django 5.x, and print the django-admin version so you confirm the isolated install.

```
python3 -m venv venv
source venv/bin/activate   # Windows: venv\Scripts\activate
pip install "django>=5.0,<6"
django-admin --version
```

Expected Output: (version numbers vary)

```
5.x.x
```

Write a short note listing Django 5.x course conventions for URLs, static storage, and Python version.

```
# Why Django 5.x here?

- Use `path()` in urls (not old url())
- Prefer `STORAGES` for static in later deploy module
- Keep Python 3.11+ in venv for campus lab machines
```

2. Development vs Production

Aspect	Development (`runserver`)	Production
Server	Django built-in	Gunicorn/uWSGI + Nginx
`DEBUG`	`True`	**`False`** always
Database	Local MySQL	Managed MySQL (RDS, PlanetScale, etc.)
Secret key	Can be default for learning	Must be unique, secret

Note:
- Never share or commit a real `SECRET_KEY` — use environment variables (Security & Deployment module). A leaked key is a production security risk.

Set DEBUG and ALLOWED_HOSTS for local development and print the DEBUG flag.

```
# settings.py (dev only — never ship like this)
DEBUG = True
ALLOWED_HOSTS = ["127.0.0.1", "localhost"]
# SECRET_KEY stays in .env later — Module 05
print("Dev mode: DEBUG =", DEBUG)
```

Expected Output:

```
Dev mode: DEBUG = True
```

Write a production checklist covering DEBUG, SECRET_KEY, ALLOWED_HOSTS, and HTTPS.

```
# Production (later)

- [ ] DEBUG = False
- [ ] SECRET_KEY from environment
- [ ] ALLOWED_HOSTS = your platform host
- [ ] HTTPS / secure cookies
```

3. INSTALLED_APPS

Every Django **app** you create must be listed in `INSTALLED_APPS` (or use auto-discovery patterns in advanced setups). Built-in apps include **`django.contrib.admin`**, **`auth`**, **`sessions`**, **`messages`**, **`staticfiles`**.

Note:
- App missing from `INSTALLED_APPS` → models/admin ignored. Add the app string (e.g. `"blog"`) after `startapp`.

Add the `blog` app to INSTALLED_APPS after `startapp`.

```
# config/settings.py — after startapp blog
INSTALLED_APPS = [
    "django.contrib.admin",
    "django.contrib.auth",
    "django.contrib.contenttypes",
    "django.contrib.sessions",
    "django.contrib.messages",
    "django.contrib.staticfiles",
    "blog",  # your app
]
```

Run Django system checks and list migrations to confirm apps load.

```
python manage.py check
python manage.py showmigrations
```

Expected Output: (abbreviated)

```
System check identified no issues (0 silenced).
```

Common Error: Forgetting to activate `venv` → `ModuleNotFoundError: No module named 'django'`. Activate first, then `manage.py`.

4. First Migrations

Django ships with tables for **users**, **sessions**, and **admin**. Running **`migrate`** creates these tables in MySQL before you write custom models.

Apply built-in migrations and show the auth app's migration status.

```
python manage.py migrate
python manage.py showmigrations auth
```

Create a superuser, then open `/admin/` after `runserver`.

```
python manage.py createsuperuser
# Then open http://127.0.0.1:8000/admin/ after runserver
```

Step-by-Step Lab (Annotated)

Step 1 — Folder and Virtual Environment

```
# Create course projects folder (adjust path to your machine)
mkdir -p ~/ksr_python_fullstack/django_labs
cd ~/ksr_python_fullstack/django_labs

# Create virtual environment named venv
python3 -m venv venv

# Activate — macOS/Linux
source venv/bin/activate
# Windows: venv\Scripts\activate

# Prompt shows (venv) — confirms isolation
pip install --upgrade pip
pip install "django>=5.0,<6.0" mysqlclient
# Windows lab fallback if mysqlclient fails:
# pip install pymysql
```

Step 2 — Create Project and App

```
# Project name: config (settings package), dot = manage.py in current folder
django-admin startproject config .

# App for Blog theme (repeat pattern for task_manager later)
python manage.py startapp blog
```

```
# Freeze dependencies for team/LMS submission
pip freeze > requirements.txt
```

Step 3 — Register App in Settings

```
# config/settings.py (excerpt)
INSTALLED_APPS = [
    "django.contrib.admin",
    "django.contrib.auth",
    "django.contrib.contenttypes",
    "django.contrib.sessions",
    "django.contrib.messages",
    "django.contrib.staticfiles",
    "blog",  # our first app — must match folder name
]
```

Step 4 — MySQL Database Configuration

Create database in MySQL Workbench or CLI first:

```
CREATE DATABASE campus_portal_db CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci;
CREATE USER 'django_user'@'localhost' IDENTIFIED BY 'StrongPass123!';
GRANT ALL PRIVILEGES ON campus_portal_db.* TO 'django_user'@'localhost';
FLUSH PRIVILEGES;
```

```
# config/settings.py
DATABASES = {
    "default": {
        "ENGINE": "django.db.backends.mysql",
        "NAME": "campus_portal_db",
        "USER": "django_user",
        "PASSWORD": "StrongPass123!",
        "HOST": "127.0.0.1",   # not localhost on some Mac setups — use 127.0.0.1
        "PORT": "3306",
        "OPTIONS": {
            "charset": "utf8mb4",
        },
    }
}
```

PyMySQL fallback (Windows) — add to `config/__init__.py`:

```
import pymysql
pymysql.install_as_MySQLdb()
```

Note:
- Wrong MySQL credentials → `Access denied for user`. Match Workbench user/password and `HOST`.
- `localhost` can hit socket issues on Mac — prefer `HOST: "127.0.0.1"`.

Step 5 — Migrate and Run Server

```
python manage.py migrate
# Creates auth, admin, sessions tables in MySQL
```

```
python manage.py runserver
# Visit http://127.0.0.1:8000/ — Django rocket welcome page
```

Expected Output: (abbreviated)

```
Applying auth.0001_initial... OK
...
Starting development server at http://127.0.0.1:8000/
```

Remember: `migrate` before celebrating `runserver` — auth/admin tables must exist in MySQL.

Step 6 — VS Code Workspace Tips

1. Open folder `django_labs` (not single file)
2. Select interpreter: `./venv/bin/python`
3. Optional: `.vscode/settings.json` → `"python.terminal.activateEnvironment": true`

Practice Exercises

Basic

1. Print Django version: `python -m django --version`
   Model answer:

```
python -m django --version
# example output: 5.x.x
```

2. List files created by `startproject` and explain each in one line
   Model answer:
   `manage.py` — CLI entry for migrate/runserver; project package `__init__.py`; `settings.py` — config; `urls.py` — root URL map; `asgi.py` / `wsgi.py` — deployment entry points; `wsgi.py` for traditional hosts, `asgi.py` for async.
3. Change runserver port: `python manage.py runserver 8080`
   Model answer:

```
python manage.py runserver 8080
```

App is then at `http://127.0.0.1:8080/`.

4. Create second app `tasks` for Task Manager theme; register in settings
   Model answer:

```
python manage.py startapp tasks
```

Add `"tasks"` to `INSTALLED_APPS` in `settings.py`.

Intermediate

1. Create MySQL database `booking_db` and second Django project `booking_portal` with MySQL config
   Model answer:

```
CREATE DATABASE booking_db CHARACTER SET utf8mb4;
```

`bash django-admin startproject booking_portal`
In settings, set `DATABASES` engine to `django.db.backends.mysql` with `NAME=booking_db`, user/password/host, then `pip install mysqlclient` (or `PyMySQL` bridge) and `migrate`.

2. Write `notes/django_folder_map.md` diagram: project vs apps
   Model answer:
   Project = config package (`settings`, root `urls`). Apps = feature packages (`accounts`, `blog`) with their own `models` / `views` / `urls`. One project can install many apps; apps should not hard-depend on project settings beyond Django APIs.
3. Run `migrate` and verify tables in MySQL Workbench (`auth_user`, etc.)
   Model answer:

```
python manage.py migrate
```

In Workbench, refresh the schema and confirm tables like `auth_user`, `django_migrations`, `django_session` exist.

Interview Prep

1. Explain MTV with Student Portal example (login page flow)
   Model answer:
   Browser hits `/login/` (URL → View). The View uses the Model (User) to authenticate and renders a Template (login HTML). MTV separates data, request logic, and presentation — same idea as MVC with Django naming.
2. Why virtual environment for every Django project?
   Model answer:
   A venv isolates package versions so Project A's Django 5 does not break Project B's Django 4. It keeps `requirements.txt` reproducible and avoids polluting the system Python.
3. Difference between `django-admin` and `manage.py`
   Model answer:
   `django-admin` is the global CLI (create projects). `manage.py` is project-local and sets `DJANGO_SETTINGS_MODULE` for that project, so day-to-day commands use `python manage.py …`.

Mini-Project / Activity (Assignment)

Activity: "Portal Bootstrap" (45 min)
Lab kit (preview for next sessions): 15_Lab_Assets/24_django_url_views_stub/

What to build

Build project **`student_portal`** with apps `core` (home placeholder) and `accounts` (empty for now):

- Working `runserver` welcome page
- MySQL connected; `migrate` success screenshot
- `requirements.txt` with Django + driver

- README with activate/run commands

Stretch

- Add custom `TIME_ZONE = "Asia/Kolkata"` and explain IST relevance for Indian apps.
- Add `.env.example` listing `DJANGO_SECRET_KEY` and DB vars (values filled later).

Done when

- [ ] `python manage.py runserver` shows Django welcome page
- [ ] MySQL `DATABASES` configured; `migrate` succeeds
- [ ] `requirements.txt` + README with activate/run steps
- [ ] Apps `core` and `accounts` exist and `core` is in `INSTALLED_APPS`

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

1. Is Django a programming language? How is it different from Python?
2. Why might a startup choose Django over building everything from scratch in plain Python?
3. Coming from Java: what is the Spring Boot equivalent idea in Django?
4. Should every mini-feature be a separate app, or one big app? Where do you draw the line?
5. Why does Django create admin/auth tables before we write any model?

Q1. What is Django?
A: High-level Python web framework with ORM, admin, auth, templating, and security helpers for building database-driven web apps quickly.

Q2. Explain MTV.
A: Model handles data; View handles request logic; Template renders HTML. URL dispatcher routes URLs to views.

Q3. Difference between Flask and Django?
A: Flask is minimal/micro — you choose components; Django is batteries-included with ORM, admin, auth conventions. Django suits large CRUD portals; Flask suits small APIs/services.

Q4. Purpose of `manage.py`?
A: CLI to run development server, migrations, shell, createsuperuser — sets `DJANGO_SETTINGS_MODULE` and delegates to Django management framework.

Q5. Why migrations?
A: Version-controlled schema changes; team syncs database structure without manual SQL drift.

Q6. How connect Django to MySQL?
A: Install driver (mysqlclient/PyMySQL), set `DATABASES` ENGINE to `django.db.backends.mysql`, configure NAME/USER/PASSWORD/HOST, run migrate.
