Kasi Yedumati · Full Stack Training

Module: Security and Deployment

Theme apps: Blog · Task Manager · Booking · Student Portal · CampusCart E-commerce

Previous module: Forms Sessions Auth
Next module: Lab CRUD Auth Consolidation

Module Outcome:

- Turn `DEBUG` off, hide `SECRET_KEY`, and load env vars before the internet sees you
- Know what CSRF, hashed passwords, and `check --deploy` are *for*
- Prepare a production-shaped settings story (HTTPS, static, allowed hosts)

Security Mindset

Security means protecting user data, passwords, and your server from attackers. Django includes many **defaults** (CSRF middleware, template auto-escaping, ORM parameterization) — but misconfiguration (`DEBUG=True` online, weak `SECRET_KEY`, missing HTTPS) causes real breaches.

Where used?
- Campus portal / Blog — public deploy must hide stack traces (`DEBUG=False`)
- **Swiggy** — CSRF on checkout forms; never commit CampusCart `.env`
- Admin — only staff on production; rotate leaked `SECRET_KEY`
- Capstone demo — Render/Railway/PythonAnywhere with env vars + `collectstatic`
- Interviews — explain why `DEBUG=True` online is a resume red flag

CSRF (Cross-Site Request Forgery)

Attacker site triggers browser to POST to **your** site while user is logged in. Django requires CSRF token in forms — validates request came from your pages.

XSS (Cross-Site Scripting)

Attacker injects **JavaScript** via stored or reflected user input (comment field). Django templates **auto-escape** HTML in `{{ variable }}`. Danger: marking untrusted data `safe` or using `|safe` filter without sanitization.

Note:
- `|safe` on user HTML enables XSS — escape by default, or sanitize with a library like bleach.

SQL Injection

Attacker manipulates input to alter SQL queries. Django **ORM** and **parameterized queries** prevent classic injection. **Never** build SQL with f-strings from user input.

Note:
- Raw SQL built with an f-string from user input → SQL injection. Prefer ORM `.filter(...)`.

DEBUG Setting

`DEBUG=True` (development): detailed error pages with code snippets — helpful locally.
`DEBUG=False` (production): generic error pages — hides internals from attackers.

> **Note:**
> - `DEBUG=True` on a public URL exposes full code/tracebacks — set it False via env in production.

SECRET_KEY

Random string used to sign cookies, sessions, CSRF tokens. **Must be unique per environment** and **never committed to Git**. Compromise allows session forgery.

> **Note:**
> - `SECRET_KEY` in GitHub enables session hijack — rotate the key and load it from the environment.

ALLOWED_HOSTS

List of domain names your Django app will serve. Prevents **HTTP Host header attacks**. Example after deploying to Render: `ALLOWED_HOSTS = ["myportal.onrender.com"]`.

> **Note:**
> - `ALLOWED_HOSTS = ['*']` is a lazy fix that invites Host-header attacks — list exact domains.

Static vs Media Files

Type	Examples	Production
Static	CSS, JS, admin assets	`collectstatic` → WhiteNoise or CDN
Media	User uploads (profile pics)	Cloud storage (S3) — not same as static

`collectstatic` — gathers all static files into **`STATIC_ROOT`** folder for production server.

> **Note:**
> - Skipping `collectstatic` → broken admin/CSS in production. Run it in the build step.

Environment Variables

Environment variables — key-value config outside code (database password, secret key).
Course standard: create a `.env` file and call **`load_dotenv()`** from `python-dotenv` at the top of `settings.py`, then read with **`os.environ.get(...)`**. Without `load_dotenv()`, Django will not see values sitting only in a `.env` file.
Alternate: `django-environ` — do not mix both in one beginner batch.
File **`.env`** is local only; list it in **`.gitignore`**. Commit **`.env.example`**.

> **Note:**
> - Never commit `.env` — credential leak; gitignore it and rotate passwords if leaked.
> - `.env` on disk without `load_dotenv()` → vars ignored (wrong DB/secret). Call `load_dotenv(BASE_DIR / ".env")` in settings.

Concepts

1. Production Settings Pattern

Split settings:

```
config/settings/
    base.py      # shared
    development.py  # DEBUG True
    production.py   # DEBUG False, security flags
```

Or single file with `if os.environ.get("DJANGO_ENV") == "production"`.

Load `.env` with python-dotenv and read SECRET_KEY, DEBUG, and ALLOWED_HOSTS from the environment.

```
from pathlib import Path
import os
from dotenv import load_dotenv

BASE_DIR = Path(__file__).resolve().parent.parent
load_dotenv(BASE_DIR / ".env")

SECRET_KEY = os.environ["DJANGO_SECRET_KEY"]
DEBUG = os.environ.get("DJANGO_DEBUG", "False").lower() == "true"
ALLOWED_HOSTS = os.environ.get("DJANGO_ALLOWED_HOSTS", "127.0.0.1").split(",")
```

Commit an `.env.example` with placeholder Django env vars — never commit a real `.env`.

```
# .env.example (commit this — never commit real .env)
DJANGO_SECRET_KEY=change-me
DJANGO_DEBUG=False
DJANGO_ALLOWED_HOSTS=127.0.0.1,localhost
```

2. HTTPS and Secure Cookies (Production)

```
SECURE_SSL_REDIRECT = True  # behind HTTPS terminator
SESSION_COOKIE_SECURE = True
CSRF_COOKIE_SECURE = True
```

PaaS platforms often terminate SSL at edge — follow platform docs.

Turn on secure session/CSRF cookies and SSL redirect for production behind HTTPS.

```
# Only when HTTPS is terminated in front of Django
SESSION_COOKIE_SECURE = True
CSRF_COOKIE_SECURE = True
SECURE_SSL_REDIRECT = True
```

Write a note that SECURE_* flags stay off on `http://127.0.0.1:8000` and on for HTTPS hosts.

```
# Local laptop

Keep SECURE_* flags off while using http://127.0.0.1:8000
Enable them on Render/Railway/PythonAnywhere with HTTPS.
```

3. Deployment Architecture (Simple)

```
User → HTTPS → PaaS (Render/Railway/PythonAnywhere)
                    → Gunicorn (WSGI server)
                    → Django app
                    → Managed MySQL
Static files → WhiteNoise or platform static handler
```

Gunicorn — production WSGI HTTP server; `runserver` is not for production.

Note:
- Using `runserver` in production → crashes and insecure defaults. Use Gunicorn (or similar) behind a platform/proxy.

Install Gunicorn and bind the WSGI application on 127.0.0.1:8000 as a production-server smoke test.

```
pip install gunicorn
gunicorn config.wsgi:application --bind 127.0.0.1:8000
```

Collect static files with `--noinput` for a deploy-style build.


```
python manage.py collectstatic --noinput
```

Expected Output: (counts vary)

```
X static files copied to '.../staticfiles'.
```

4. Platform Overviews (India-Friendly Free Tiers)

Visual — from laptop to live URL:



Key takeaways:
- Push code → set env on PaaS → migrate + collectstatic → live URL
- Secrets live in platform env, never in Git
- `check --deploy` before you call it production-ready

Platform	Pros	Notes
Render	Git push deploy, free web tier, MySQL add-on or external DB	Set env vars in dashboard
Railway	Simple UI, good for demos	Usage-based credits
PythonAnywhere	Django-friendly docs, console access	Free tier limited custom domains

All need: `DEBUG=False`, `ALLOWED_HOSTS`, static config, production database URL, migrations on deploy.

Write a DEPLOY_CHECKLIST.md covering env, DEBUG, ALLOWED_HOSTS, collectstatic, and the database URL.

```
# DEPLOY_CHECKLIST.md

- [ ] .env on platform, not in Git
- [ ] DEBUG=False
- [ ] ALLOWED_HOSTS includes platform host
- [ ] collectstatic in build
- [ ] MySQL/Postgres URL set
```

Add a README table documenting DJANGO_SECRET_KEY, DJANGO_DEBUG, and DATABASE_URL.

```
| Variable | Example | Notes |
|----------|---------|-------|
| DJANGO_SECRET_KEY | (random) | Never commit |
| DJANGO_DEBUG | False | True only locally |
| DATABASE_URL | mysql://... | Platform DB |
```

Step-by-Step Lab (Annotated)

Step 1 — Environment-Based Settings (recommended: `python-dotenv`)

Course standard: use `python-dotenv` + `load_dotenv()` so a local `.env` file is actually loaded. `os.environ.get()` alone only reads variables already exported in the shell — a `.env` file on disk is **ignored** until you load it.

```
pip install python-dotenv
```

```
# config/settings.py
import os
from pathlib import Path
from dotenv import load_dotenv

BASE_DIR = Path(__file__).resolve().parent.parent

# Load .env from project root (BASE_DIR / ".env")
load_dotenv(BASE_DIR / ".env")

SECRET_KEY = os.environ.get("DJANGO_SECRET_KEY", "dev-only-key-change-in-production")

DEBUG = os.environ.get("DJANGO_DEBUG", "True") == "True"

ALLOWED_HOSTS = [
    h.strip()
    for h in os.environ.get("ALLOWED_HOSTS", "127.0.0.1,localhost").split(",")
    if h.strip()
]

DATABASES = {
    "default": {
        "ENGINE": "django.db.backends.mysql",
        "NAME": os.environ.get("DB_NAME", "campus_portal_db"),
        "USER": os.environ.get("DB_USER", "django_user"),
        "PASSWORD": os.environ.get("DB_PASSWORD", ""),
        "HOST": os.environ.get("DB_HOST", "127.0.0.1"),
        "PORT": os.environ.get("DB_PORT", "3306"),
```

```
    }
}
```

```
# .env (local — NEVER commit)
DJANGO_SECRET_KEY=your-long-random-string-here
DJANGO_DEBUG=True
ALLOWED_HOSTS=127.0.0.1,localhost
DB_NAME=campus_portal_db
DB_USER=django_user
DB_PASSWORD=StrongPass123!
DB_HOST=127.0.0.1
DB_PORT=3306
```

```
# .env.example (COMMIT this — no real secrets)
DJANGO_SECRET_KEY=change-me
DJANGO_DEBUG=True
ALLOWED_HOSTS=127.0.0.1,localhost
DB_NAME=campus_portal_db
DB_USER=django_user
DB_PASSWORD=
DB_HOST=127.0.0.1
DB_PORT=3306
```

```
# .gitignore excerpt
venv/
.env
*.pyc
db.sqlite3
staticfiles/
__pycache__/
```

On PaaS (Render/Railway): set the same keys in the dashboard. `load_dotenv()` is harmless if `.env` is missing — platform env vars still populate `os.environ`.

Alternate (advanced batches): `django-environ` — same idea, different API. Pick **one** approach per batch; this course recommends `python-dotenv`.

Step 2 — Static Files for Production (Django 5.x `STORAGES`)

```
STATIC_URL = "static/"
STATICFILES_DIRS = [BASE_DIR / "static"]
STATIC_ROOT = BASE_DIR / "staticfiles"
```

```
python manage.py collectstatic --noinput
# Copies admin CSS/JS + your static/ into staticfiles/
```

Install **WhiteNoise** for simple PaaS static serving:

```
pip install whitenoise
```

```
MIDDLEWARE = [
    "django.middleware.security.SecurityMiddleware",
```

```
    "whitenoise.middleware.WhiteNoiseMiddleware",  # right after SecurityMiddleware
    # ... session, common, csrf, auth, messages, clickjacking ...
]

# Django 5.x preferred (replaces deprecated STATICFILES_STORAGE-only style)
STORAGES = {
    "default": {
        "BACKEND": "django.core.files.storage.FileSystemStorage",
    },
    "staticfiles": {
        "BACKEND": "whitenoise.storage.CompressedManifestStaticFilesStorage",
    },
}
```

> Avoid teaching only `STATICFILES_STORAGE = "..."` as the primary pattern for Django 5.x. Prefer `STORAGES["staticfiles"]` as documented in current Django settings.

Step 2b — Required pre-deploy check

```
# With production-like env loaded (.env or exported vars):
export DJANGO_DEBUG=False
export ALLOWED_HOSTS=your-app.example.com
python manage.py check --deploy
```

Expected Output: (goal)

```
System check identified no issues (0 silenced).
```

(Warnings about `SECURE_*` / HTTPS are normal locally — fix or understand each before public deploy.)

Remember: `DEBUG=True` on a public URL leaks code and secrets in error pages — always drive production via env (`DJANGO_DEBUG=False`).

Common Error: Committing `.env` with `SECRET_KEY` / DB password → rotate keys immediately and add `.env` to `.gitignore`.

Fix every warning/error before going live. Add this to the learner deploy checklist.

Step 3 — Production Toggle Exercise (Local Simulation)

```
export DJANGO_DEBUG=False
export ALLOWED_HOSTS=127.0.0.1,localhost
python manage.py runserver
# Visit site — generic 404/500 pages; verify no stack trace leak on broken URL
unset DJANGO_DEBUG  # return to dev
```

Step 4 — Security Audit Checklist (Forms)

Walk through your project checklist:

- [ ] Every POST form has `{% csrf_token %}`
- [ ] No `|safe` on user-generated blog comments

- [ ] Queries use ORM, not raw SQL with f-strings
- [ ] `@login_required` on sensitive views
- [ ] Passwords only via auth forms
- [ ] `.env` not in Git (`git status` clean for secrets)

Step 5 — requirements.txt for Deploy

```
django>=5.0,<6.0
mysqlclient
gunicorn
whitenoise
python-dotenv
```

Step 6 — Gunicorn Local Smoke Test

```
gunicorn config.wsgi:application --bind 0.0.0.0:8000
# Ctrl+C to stop — proves WSGI entry works before cloud deploy
```

Step 7 — Render deployment overview (walkthrough)

Typical steps (document in README — URLs change on platform):

1. Push project to GitHub (no `.env`, no `venv/`)
2. Create **Web Service** on Render → connect repo
3. **Build command:** `pip install -r requirements.txt && python manage.py collectstatic --noinput`
4. **Start command:** `gunicorn config.wsgi:application`
5. **Environment variables:** `DJANGO_SECRET_KEY`, `DJANGO_DEBUG=False`, `ALLOWED_HOSTS=myapp.onrender.com`, DB vars
6. **Release command (optional):** `python manage.py migrate`
7. Use external MySQL (PlanetScale, Aiven, or Render Postgres/MySQL offering) — update `DATABASES`
8. Open deployed URL — login, static admin CSS loads

Railway: Similar Git-based deploy; add MySQL plugin; set variables in Railway dashboard.

PythonAnywhere: Upload code or Git clone; configure virtualenv; WSGI file points to `config.wsgi`; static files mapping in web tab; MySQL from PythonAnywhere db console.

Step 8 — Deployment Checklist Document

Learners complete `docs/DEPLOY_CHECKLIST.md`:

1. Generate new SECRET_KEY (never reuse dev key)
2. DEBUG=False
3. ALLOWED_HOSTS set
4. Database credentials via env; `.env` loaded with `load_dotenv` locally
5. `python manage.py check --deploy` passes (or warnings understood/fixed)
6. migrate on server
7. collectstatic executed; `STORAGES["staticfiles"]` configured for WhiteNoise
8. HTTPS enabled (platform)

9. Superuser created on production (secure channel)
10. Backup strategy for MySQL
11. `.env` not in Git; `.env.example` committed

Practice Exercises

Basic

1. Generate SECRET_KEY using Django shell: `from django.core.management.utils import get_random_secret_key; print(get_random_secret_key())`
   Model answer:

```
python manage.py shell -c "from django.core.management.utils import get_random_secret_key; print(get_ra
```

Store the printed value in an environment variable — never commit it.

2. List three items from deployment checklist and explain each
   Model answer:
   (1) `DEBUG=False` so errors do not leak internals. (2) Set `ALLOWED_HOSTS` to your domain so Host-header attacks fail. (3) Use HTTPS/ `SECURE_*` settings and a strong `SECRET_KEY` from the environment.
3. Run collectstatic; count files in `staticfiles/admin/`
   Model answer:

```
python manage.py collectstatic --noinput
find staticfiles/admin -type f | wc -l
```

Count varies by Django version; non-zero means admin CSS/JS were gathered.

Intermediate

1. Split settings into `development.py` / `production.py` (stretch)
   Model answer:
   Keep shared defaults in `settings/base.py`, import them in `development.py` (`DEBUG=True`) and `production.py` (`DEBUG=False`, secure cookies, env-based DB). Point `DJANGO_SETTINGS_MODULE` at the right module per environment.
2. Document Render deploy steps with screenshots for Student Portal
   Model answer:
   Document: connect GitHub repo → set build (`pip install -r requirements.txt`) and start (`gunicorn project.wsgi`) → add env vars (`SECRET_KEY`, `DATABASE_URL`, `ALLOWED_HOSTS`) → run migrate → verify HTTPS homepage. Attach screenshots of env and deploy logs.
3. Intentionally break ALLOWED_HOSTS — capture error message, then fix
   Model answer:
   Set `ALLOWED_HOSTS = ["example.com"]` then visit `127.0.0.1` — Django returns DisallowedHost. Fix by adding `"127.0.0.1"` / your real domain, restart, confirm 200.

Interview Prep

1. Explain CSRF to non-technical HR interviewer in 30 seconds
   Model answer:
   CSRF is when a malicious site tricks your logged-in browser into submitting a form to our app. Django blocks

this by requiring a secret token on forms that attackers cannot read.

2. Difference DEBUG True vs False user experience
   Model answer:
   `DEBUG=True` shows detailed traceback pages for developers. `DEBUG=False` shows generic error pages to users and hides sensitive config — required in production.
3. Why environment variables for 12-factor apps?
   Model answer:
   Config (secrets, DB URLs, debug flags) changes per environment without code edits. Env vars keep secrets out of the repo and match the 12-factor rule: store config in the environment.

Mini-Project / Activity (Assignment)

Activity: "Staging Ready Portal" (90 min)
Lab kit: 19_git_portfolio_hygiene · 20_sql_injection_demo

What to build

1. Refactor secrets to env vars
2. Add WhiteNoise + STATIC_ROOT; successful collectstatic
3. Complete DEPLOY_CHECKLIST.md
4. Gunicorn smoke test locally
5. Optional: deploy one repo to Render for a shared class URL

Stretch

- Run `python manage.py check --deploy` with `DJANGO_DEBUG=False` and fix warnings.
- Add a short README section: "How a teammate in Bengaluru clones and runs this".

Done when

- [ ] No secrets in GitHub; `.env.example` present
- [ ] `collectstatic` succeeds; WhiteNoise/`STORAGES` configured
- [ ] DEPLOY_CHECKLIST.md completed
- [ ] Gunicorn smoke test **or** platform deploy started

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

1. If Django auto-escapes templates, can XSS still happen? How?
2. Why is committing `.env` worse than committing a wrong password in chat?
3. Free tier PaaS for India students — cost vs learning trade-offs?
4. Should CampusCart handle payments on first deploy? What goes first?
5. who owns security in a team — developer, DevOps, or both?

Q1. What is CSRF and how does Django prevent it?

A: Forged cross-site POST using victim session; Django CSRF middleware validates token in forms/ajax.

Q2. DEBUG True vs False?

A: True: verbose errors for development. False: production-safe generic errors, required for public deploy.

Q3. Why keep SECRET_KEY secret?

A: Used to sign sessions and tokens; leak enables forging session data.

Q4. SQL injection prevention in Django?

A: Use ORM QuerySets and parameterized raw queries; never interpolate user input into SQL strings.

Q5. collectstatic purpose?

A: Aggregate static assets from apps and project into STATIC_ROOT for production web server/CDN.

Q6. Name two Django deployment platforms and one consideration each.

A: Render — easy Git deploy, set ALLOWED_HOSTS to onrender.com hostname; PythonAnywhere — WSGI config file and static mapping; Railway — env vars and database plugin.
