Kasi Yedumati · Full Stack Training

Module: APIs, JSON, Postman & Django REST Framework

Phase: APIs & REST
Previous module: Flask Overview
Next module: React Fundamentals

Module Outcome:

- Explain an API as "React does not touch MySQL — it asks Django for JSON"
- Hit list/create/update/delete in Postman against a DRF endpoint
- Return a clean JSON contract a frontend can trust

What is an API?

An **API (Application Programming Interface)** is a agreed way for programs to talk to each other. Your React app does not read the database directly — it calls the Django **API**, which returns **JSON** data.


Order | Laptop | Employee | Bank | Payroll

Where used?

- **Swiggy** — React / mobile apps call `/api/products/` for CampusCart
- College apps — student portal SPA fetching enrollments as JSON
- **HDFC Bank** / **PhonePe** — apps talk to bank APIs, never the DB directly
- **Employee Management Portal** — HR mobile clients consume employee/leave REST endpoints
- Postman / QA — manual API checks before frontend is ready

Restaurant analogy: You (client) read the menu (API docs), tell the waiter your order (HTTP request), kitchen prepares food (server logic), waiter brings plate (JSON response). You never enter the kitchen.

Visual — React asking Django for products:



Key takeaways:

- Client → DRF → MySQL → JSON back (never React → DB direct)
- GET list → **200**; POST create → **201**
- Same contract for Postman, React, or mobile

What is REST?

REST (Representational State Transfer) is a style for designing APIs:

- Resources have URLs: `/api/products/`, `/api/products/5/`

- Use HTTP **methods** for actions
- **Stateless:** each request carries enough info (no server memory of "session" required for API itself — auth tokens are exception)
- Responses often **JSON**

Not every API is pure REST, but Indian job interviews expect REST vocabulary.

HTTP Methods (CRUD mapping)

Method	Action	Example URL	Body?
GET	Read list or one	`/api/products/`	No
POST	Create	`/api/products/`	Yes (JSON)
PUT	Replace entire resource	`/api/products/3/`	Yes
PATCH	Partial update	`/api/products/3/`	Yes (partial)
DELETE	Remove	`/api/products/3/`	Usually no

> **Note:**
> - GET conventionally has no body — putting a body on GET confuses proxies and clients.

Status Codes (memorize these)

Code	Meaning	When
200	OK	Successful GET, PUT, PATCH
201	Created	Successful POST
204	No Content	Successful DELETE
400	Bad Request	Invalid JSON or validation fail
401	Unauthorized	Missing/invalid auth
403	Forbidden	Authenticated but not allowed
404	Not Found	Wrong id or URL
500	Server Error	Bug on server — fix code/logs

Concepts

JSON in Python

```
import json

data = {'name': 'Laptop', 'price': 45000}
text = json.dumps(data)           # dict → JSON string
parsed = json.loads(text)         # JSON string → dict
```

Serialize a product dict to a JSON string with `json.dumps`, parse it back with `json.loads`, and print the string and the price field.

```
import json

data = {"name": "Laptop", "price": 45000, "city": "Bengaluru"}
text = json.dumps(data)
parsed = json.loads(text)
print(text)
print(parsed["price"])  # 45000
```

Expected Output:

```
{"name": "Laptop", "price": 45000, "city": "Bengaluru"}
45000
```

Pretty-print a product dict with `json.dumps(..., indent=2)` so nested keys are easy to read.

```
import json

product = {"name": "Masala Dosa", "price_inr": 60, "in_stock": True}
print(json.dumps(product, indent=2))
```

Expected Output:

```
{
  "name": "Masala Dosa",
  "price_inr": 60,
  "in_stock": true
}
```

Remember: `json.dumps` → Python dict to string; `json.loads` → string to dict. APIs exchange the string form over HTTP.

Common Error: Forgetting `Content-Type: application/json` on POST in Postman → empty body / 415. Set the header (or Body → raw → JSON).

Interview: REST maps CRUD to HTTP — GET read, POST create, PUT/PATCH update, DELETE remove — plus status codes (200/201/400/401/404/500).

Postman workflow

1. Create collection "Product API"
2. Set base URL variable `{{base}}` = `http://127.0.0.1:8000`
3. Add requests for each CRUD operation
4. Header: `Content-Type: application/json` for POST/PUT
5. Save examples for regression testing

Note:
- POST without a JSON `Content-Type` header → 415 or empty data. Set it in Postman.
- Bad JSON (e.g. Decimal as a bare number in invalid payloads) → parse errors; send valid JSON — DRF often accepts string decimals like `"45.00"`.

Write a short Postman collection checklist covering the base URL variable, GET/POST requests, and status-code assertions.

```
# Postman — Product API

1. Collection: Product API
2. Variable `{{base}}` = http://127.0.0.1:8000
3. GET {{base}}/api/products/
4. POST {{base}}/api/products/ with JSON body
5. Assert status 200 / 201 in Tests tab
```

Draft a sample POST JSON body for creating a product with name, price string, and in_stock flag.

```
{
  "name": "Notebook",
  "price": "45.00",
  "in_stock": true
}
```

Django REST Framework stack

```
Model → Serializer → ViewSet → Router → URL /api/products/
```

Serializer: Converts Django model instances ↔ JSON; validates input.
ViewSet: Groups list/create/retrieve/update/destroy logic.
Router: Auto-generates URL patterns.

Define a `ProductSerializer` ModelSerializer that exposes id, name, price, and in_stock from the Product model.

```
from rest_framework import serializers
from .models import Product

class ProductSerializer(serializers.ModelSerializer):
    class Meta:
        model = Product
        fields = ["id", "name", "price", "in_stock"]
```

Register a `ProductViewSet` on the default DRF router under the `products` basename.

```
from rest_framework.routers import DefaultRouter
from .views import ProductViewSet

router = DefaultRouter()
router.register("products", ProductViewSet, basename="product")
urlpatterns = router.urls
```

Step-by-Step Annotated Code

Step 1 — Install and configure DRF

```
pip install djangorestframework
```

`settings.py`:

```
INSTALLED_APPS = [
    # ...
    'rest_framework',
    'shop',                    # your app
]
```

Note:
- Forgot `rest_framework` in `INSTALLED_APPS` → import/config errors. Add it after install.

Step 2 — Product model

`shop/models.py`:

```
from django.db import models

class Product(models.Model):
    name = models.CharField(max_length=120)
    price = models.DecimalField(max_digits=10, decimal_places=2)
    in_stock = models.BooleanField(default=True)
    created_at = models.DateTimeField(auto_now_add=True)

    def __str__(self):
        return self.name
```

Run: `python manage.py makemigrations && python manage.py migrate`

Step 3 — Serializer (`shop/serializers.py`)

```
from rest_framework import serializers
from .models import Product

class ProductSerializer(serializers.ModelSerializer):
    class Meta:
        model = Product
        fields = ["id", "name", "price", "in_stock", "created_at"]
        read_only_fields = ["id", "created_at"]

    def validate_price(self, value):
        if value < 0:
            raise serializers.ValidationError("Price cannot be negative.")
        return value

    def validate_name(self, value):
        if len(value.strip()) < 2:
            raise serializers.ValidationError("Name must be at least 2 characters.")
        return value.strip()
```

Step 4 — ViewSet (`shop/views.py`)

```
from rest_framework import viewsets
from .models import Product
from .serializers import ProductSerializer

class ProductViewSet(viewsets.ModelViewSet):
    """
    Full CRUD for Product:
    list, create, retrieve, update, partial_update, destroy.
    """
    queryset = Product.objects.all().order_by("-created_at")
    serializer_class = ProductSerializer
```

Step 5 — URLs (app + project)

`shop/urls.py`:

```
from django.urls import path, include
from rest_framework.routers import DefaultRouter
from .views import ProductViewSet

router = DefaultRouter()
router.register(r"products", ProductViewSet, basename="product")

urlpatterns = [
    path("", include(router.urls)),
]
```

Project `config/urls.py` (or `yourproject/urls.py`):

```
from django.contrib import admin
from django.urls import path, include

urlpatterns = [
    path("admin/", admin.site.urls),
    path("api/", include("shop.urls")),
]
```

Routes created automatically

Method	URL	Action
GET	`/api/products/`	list
POST	`/api/products/`	create
GET	`/api/products/1/`	retrieve
PUT	`/api/products/1/`	update (full)
PATCH	`/api/products/1/`	partial_update
DELETE	`/api/products/1/`	destroy

Note:
- Wrong trailing slash → 404 on Django. Match `APPEND_SLASH` / router URLs (usually with a trailing `/`).

Optional DRF browsable API: open `http://127.0.0.1:8000/api/products/` in the browser while `DEBUG=True`.

Step 6 — Postman test create

```
POST http://127.0.0.1:8000/api/products/
Content-Type: application/json

{
  "name": "Wireless Mouse",
  "price": "899.00",
  "in_stock": true
}
```

Expected response — 201 Created

```
{
  "id": 1,
  "name": "Wireless Mouse",
  "price": "899.00",
  "in_stock": true,
  "created_at": "2026-07-31T12:00:00.123456Z"
}
```

Expected list — GET `/api/products/` → 200

```
[
  {
    "id": 1,
    "name": "Wireless Mouse",
    "price": "899.00",
    "in_stock": true,
    "created_at": "2026-07-31T12:00:00.123456Z"
  }
]
```

Expected validation error — POST with `"price": "-10"` → 400

```
{
  "price": ["Price cannot be negative."]
}
```

Step 7 — Consume with Python requests

```
import requests

BASE = 'http://127.0.0.1:8000/api/products/'

# List
resp = requests.get(BASE)
print(resp.status_code)      # 200
products = resp.json()       # list of dicts
```

```
print(products)

# Create
new_product = {'name': 'USB Hub', 'price': '1299.00', 'in_stock': True}
resp = requests.post(BASE, json=new_product)
print(resp.status_code)      # 201
print(resp.json())
```

Note:
- `requests` to the wrong port → connection refused (Django usually `8000`, Flask `5000`).
- List endpoints return an **array** — treating it as a dict → `KeyError` on `['id']`.
- Ignore status codes at your peril — check `resp.ok` (or equivalent) so failures are not silent.

Step 8 — Consume with fetch (browser / React preview)

```
const res = await fetch('http://127.0.0.1:8000/api/products/');
const products = await res.json();
```

Note: Browser calls may hit **CORS** errors until Django allows frontend origin — covered in React module; mention `django-cors-headers` preview here.

Practice Exercises

Basic

1. Add 3 products via Postman; export collection JSON.
   Model answer:
   Send three `POST /api/products/` requests with JSON bodies (name, price, stock). In Postman: Collection → Export → Collection v2.1 JSON, save as `products.postman_collection.json`.
2. Write Python script printing only in-stock product names.
   Model answer:

```
import requests

products = requests.get("http://127.0.0.1:8000/api/products/").json()
for p in products:
    if p.get("in_stock") or p.get("stock", 0) > 0:
        print(p["name"])
```

3. Match status codes to scenarios (wrong id, successful create, server crash).
   Model answer:
   Wrong id → **404**; successful create → **201**; unhandled server crash → **500**. Client errors are 4xx; server failures are 5xx.

Intermediate

1. Add `category` CharField to Product; update serializer; test PATCH one field.
   Model answer:
   Add `category = models.CharField(max_length=50, blank=True)` + migrate; include `"category"` in serializer fields; `PATCH /api/products/1/` with `{"category": "peripherals"}` and confirm partial update.

2. Filter: `GET /api/products/?search=mouse` using DRF `SearchFilter`.
   Model answer:

```
from rest_framework import filters

class ProductViewSet(viewsets.ModelViewSet):
    queryset = Product.objects.all()
    serializer_class = ProductSerializer
    filter_backends = [filters.SearchFilter]
    search_fields = ["name", "category"]
```

3. Return custom 400 when price is negative (serializer validation).
   Model answer:

```
def validate_price(self, value):
    if value < 0:
        raise serializers.ValidationError("price must be >= 0")
    return value
```

Interview-style

1. Difference between PUT and PATCH?
   Model answer:
   PUT replaces the whole resource (send all fields). PATCH updates only the fields you send. Prefer PATCH for partial edits.
2. What does serializer validation do before save?
   Model answer:
   It checks types/required fields and custom validators, builds validated data, and only then allows `save()` / `create()` / `update()`. Invalid input returns 400 with error details.
3. Why REST APIs prefer JSON over HTML for mobile apps?
   Model answer:
   Mobile apps need structured data to render their own UI. JSON is compact and language-neutral; HTML is meant for browsers, not for native clients to parse as data.

Mini-Project (Assignment): Swiggy Product Catalog API + Client Script

Lab kit (build here): 15_Lab_Assets/04_drf_products/
Deliverables: follow `Standard_Project_Deliverables.md`

What to build

- Django app with Product model and full DRF CRUD
- Postman collection with 5+ requests and tests on status code
- `client/list_products.py` using requests
- `README.md` with sample JSON responses (201 create, 200 list, 400 validation)
- `.env.example`, `requirements.txt`, screenshots

Stretch

- Add `price__gte` filter or search by name.
- Return Indian-friendly example products (Notebook ₹45, Thali ₹90).

Done when

- [ ] Lab kit Product JSON API ticket completed
- [ ] CRUD works in Postman (including validation 400)
- [ ] Client script prints product list
- [ ] README shows sample JSON for create/list/error

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

1. Why do companies expose APIs instead of giving database passwords to mobile teams?
2. Is `/api/getAllProducts` RESTful? What would be better?
3. how is an API similar to a bank's phone banking menu (press 1 for balance)?
4. When should API return 400 vs 422? (Simplified: DRF often uses 400 for validation.)
5. How does Postman help when you do not yet have a React UI?

Q1. What is a REST API?

A: HTTP-based interface exposing resources as URLs, using standard methods and status codes, typically JSON payloads, stateless communication.

Q2. Difference between API and REST?

A: API is general contract between software; REST is a specific architectural style for web APIs using HTTP resources.

Q3. What is Django REST Framework?

A: Toolkit on Django for building Web APIs — serializers, viewsets, authentication, browsable API.

Q4. GET vs POST?

A: GET retrieves data safely/idempotently without body; POST submits data to create or trigger action with body.

Q5. How do you test API without frontend?

A: Postman, curl, Python requests, DRF browsable API, automated pytest with APIClient.
