HTML & CSS for Full Stack — Learning Path

Shared topic for Python Full Stack and Java Full Stack · 9 sessions · Project: **AcmeHR**

This folder teaches HTML and CSS **together**, in the order you will use them at work. Every lesson builds one real page of AcmeHR, an employee management system. By Lesson 9 you have a small, responsive, accessible portal that you will later serve from Django or Spring Boot.

The path



#	Lesson	AcmeHR page you build	HTML you learn	CSS you learn	Lab
1	How the Web Works & Your First Page	Welcome page	Browser and server, status codes, page skeleton, `h1`, `p`, entities, comments	—	L01
2	Content & Your First CSS	Leave policy	Headings, `br`, lists, links and paths, `strong` / `em`, `id`, `class`	Linking CSS, colours and fonts, block vs inline, selectors, cascade, specificity, inheritance	L02
3	Page Structure & the Box Model	Employee profile	`header`, `nav`, `main`, `section`, `aside`, `footer`, `div` / `span`, `dl`	Box model, `box-sizing`, centring, margin collapse, `display`, units	L03
4	Images, Navigation & Flexbox	Employee directory	`img` and `alt`, `figure`, `article`	Flexbox: `justify-content`, `align-items`, `gap`, `flex-wrap`, `flex`	L04
5	Grid & Positioning	HR dashboard	—	Grid, `fr`, `repeat` / `minmax` / `auto-fit`, template areas, `position`, `z-index`, `sticky`	L05
6	Forms	Apply for leave	`form`, `label`, inputs, `select`, `textarea`, `fieldset`, validation, GET vs POST, what the server receives	Form styling, attribute selectors, `:focus-visible`	L06
7	Tables	Attendance report	`table`, `caption`, `thead` / `tbody` / `tfoot`, `th scope`, `colspan` / `rowspan`	`border-collapse`, `tabular-nums`, `:nth-child`, scrolling tables	L07
8	Responsive Design	Every page, phone to desktop	Viewport, `picture`	Mobile-first media queries, `min()`, `cl`	L08

#	Lesson	AcmeHR page you build	HTML you learn	CSS you learn	Lab
				`amp()`, `vw`, `ch`, responsive images	
9	Polish, Accessibility & Final Project	The whole portal	`details` / `summary`, `aria-current`, page `head`	Custom properties, `:hover` / `:active`, transitions, reduced motion, contrast	L09 — final project

The pages come from the AcmeHR Business Requirements Document (BRD): employee profile, employee directory, leave application, attendance reports, HR dashboards, and policy documents. Payroll is out of scope in Phase 1 of the BRD, so no lesson builds a payslip.


Why this order

1. A visible result in every session. CSS starts in Lesson 2, not after weeks of plain black-and-white pages. Every session ends with a page that looks better than the last one. That is what keeps learners going.

2. Meaning first, then look — for each feature. Inside every lesson you first write the HTML for *what the content is*, then style it. You never learn a CSS trick before you have something real to apply it to, and you never write HTML you will not style until weeks later.

3. Nothing appears before it is taught. Every example uses only the tags and properties taught up to that point. Each lesson's header lists exactly what is new.

4. Each lesson needs only what came before.



You cannot debug a layout without the box model, and you cannot fix a CSS conflict without the cascade. So those come first.


5. The most important topic for full stack gets its own session. Forms (Lesson 6) are where HTML meets your Django or Spring backend: every field `name` becomes a request parameter. It comes after layout so the form can be styled properly in the same session.

6. One project, not seventeen disconnected examples. Every lesson adds a page to the same AcmeHR site, using the same stylesheet. In the Django and Spring phases, these exact pages become your templates.

What is left out on purpose. Rare elements (`sub`, `sup`, `abbr`, audio and video players, iframes) and advanced CSS (animations with `@keyframes`, nesting) are not taught in class. They are in the reference modules below, for when you need them.

How to study a lesson on your own

Each lesson takes about 90 minutes of self-study. Follow the same loop every time:



Rules that make the difference:

- **Type the code. Do not copy-paste it.** Your fingers learn the syntax; your eyes only recognise it.
- **Break things on purpose.** Delete a closing tag, a semicolon, a dot. See what happens. That is how you recognise bugs later.
- **Do the lab "broken" part first.** Finding bugs in someone else's page is the fastest way to learn what correct looks like.
- **Only open a `solution/` folder after you finish.**

Every lesson has the same parts, so you always know where to look:

Part	What it gives you
Module Outcome	What you can do at the end
New HTML / New CSS	Exactly which tags and properties this lesson introduces
Code → Output	Every example shows the code and a real screenshot of what it produces. Type it yourself and compare.
Remember / Common Error / Where used?	The rule, the classic mistake, and how it appears in Django or Spring
Try these	Exercises from easy to stretch
Interview	Questions you will be asked, with short answers
Lab	A ticket from the AcmeHR team: fix a broken page, build one, and prove it works

---

Setup (once)

- **Editor:** VS Code
- **Browser:** Google Chrome (Edge and Firefox also work)
- **Local server:** `python3 -m http.server 8000` in your project folder — or the VS Code **Live Server** extension, or `jwebserver` on JDK 18+
- **Validator:** validator.w3.org/nu

Reference modules

The older topic-by-topic modules stay available as a **reference for lookup**, not for reading from start to finish:

- HTML reference — every HTML topic, one by one
- CSS reference — every CSS topic, one by one

Next phase: JavaScript, DOM & Forms

For maintainers

Screenshots are generated, never drawn. After you change any file in `examples/`, run:

```
python3 scripts/shoot_frontend_examples.py
```

from the repository root. It drives Chrome through its DevTools protocol (`pip install websockets` once), renders every example — at phone widths, scrolled, hovered or after pressing `Tab` where a lesson needs it — and saves the result in `screens/`. The final-project pages shown in Lesson 9 are rendered too.

One screenshot is not generated by the script: `screens/lesson01_server_404.png` is Chrome showing `http://localhost:8000/leave.html` (a missing page) while `python3 -m http.server 8000` runs.

Before publishing changes, run:

```
python3 scripts/check_frontend_lessons.py
```

It fails if any example, lab file or lesson code block uses an HTML tag or CSS property **before the lesson that teaches it**, or if any link is broken. When a lesson starts teaching something new, add it to that lesson's list at the top of the script.