Kasi Yedumati · Full Stack Training

Session 1 — From the Desktop mess to your first GitHub push

Shared topic (Python FS + Java FS) · **~75 minutes**

Index: Git and GitHub
Previous (Python FS): Logging
Previous (Java FS): File Handling
Next: Session 2 — Daily Git workflow

Session Outcome

By the end of this sitting you will have **KSR_MART** on GitHub.


You will be able to:

- Say why zip copies are not enough
- Tell Git and GitHub apart
- Install Git, set your name and email, and create a GitHub repo
- Save a checkpoint on your laptop and push it to GitHub

This course is **five sessions, about six hours**. We will not cover Git internals, rebase, cherry-pick, or a long command list. Today is one win: the project is online.

1. Look at the Desktop

You are building **KSR_MART**. Monday the home page works. Tuesday the cart breaks. Wednesday a teammate asks for the working copy.



Which zip is the real project? You cannot say quickly.

That is the problem. Not “I don’t know Git.” The project has **no history** — only extra copies.

Same mess, six ways:

- You keep `final`, `final2`, `USE_THIS`. Two people edit different copies.
- You delete working login code, save, and close the editor. Undo is gone tomorrow.


- The cart worked last night. This morning it does not. You cannot see what changed.
- Aisha, Rohan, and you all edited the project. A bug appears. Who touched the cart file?
- You send a zip on WhatsApp. They send `from_rohan.zip` back. Now there are two “latest” copies.
- Aisha builds **login**. Rohan builds **payment**. One copied folder overwrites the other.

Need: one current project, a history you can go back through, and a shared copy when other people are involved.

---

2. Two laptops, one broken cart

Aisha finishes login. Rohan finishes payment. Each has a folder named `KSR_MART`. They copy files together by hand.



They did not fail at coding. They failed at **combining work**. There is no shared history, so the old cart cannot be recovered.

---

3. Git and GitHub are not the same tool



Git runs on your computer. It records history for this project, even if Wi-Fi is off.

GitHub is a website. The team keeps a shared copy there instead of mailing zips.

You can use Git with no GitHub account. You cannot put the team copy online until GitHub (or a similar host) exists. This course uses GitHub because that is what most teams and recruiters open.

---

4. Get ready

GitHub account

Create a free account at github.com if you do not have one. Use an email you can open. Remember the username. You will need it in the repo URL.

Install Git

Install from git-scm.com. On Windows, the installer includes **Git Bash** — use that for the commands in this course. On Mac, Terminal is enough.

Check:

```
git --version
```

You should see a version number. That means Git is on this machine.

Tell Git who you are

Every checkpoint stores a name and email. Set them once on this computer:

```
git config --global user.name "Your Name"
git config --global user.email "you@example.com"
```

Use the same email as GitHub if you can. That is how GitHub links your work to your account.

When GitHub asks you to sign in later (browser or a credential window), sign in. GitHub no longer accepts your account password on `git push`. Do not hunt for extra token setup unless the sign-in window fails.

---

5. Create an empty GitHub repository

A **repository** (repo) is the project plus its history.

On GitHub: **New repository**.

- **Name:** `ksr-mart` (lowercase, hyphen — GitHub names cannot be `KSR_MART` with a space)
- **Public**
- **Do not** tick README, `.gitignore`, or License

Those extras create files on GitHub before your laptop has a history. Then `git push` is rejected. We will add a README from the laptop instead.

Copy the HTTPS URL. It looks like:

```
https://github.com/YOUR_USERNAME/ksr-mart.git
```

---

6. Put KSR_MART on GitHub

This is the whole move for today:



On your machine (Git Bash on Windows):

```
mkdir -p ~/KSR_MART
cd ~/KSR_MART
git init -b main
```

`git init` starts history in this folder. `-b main` names the first line of history `main` (the usual name on GitHub).

Create a README so the repo is not empty:

```
echo "# KSR_MART" > README.md
echo "Canteen ordering project for the Git course." >> README.md
```

Git does not snapshot a file the moment you save it. You choose what belongs in the checkpoint, then you seal it.

```
git status
git add README.md
git commit -m "Add README for KSR_MART"
```

`git status` is “what is going on in this folder?”

`git add` is “these files belong in the next checkpoint.”

`git commit` is “save that checkpoint on this laptop,” with a short message you can read later.

Connect this folder to the empty GitHub repo, then send the checkpoint:

```
git remote add origin https://github.com/YOUR_USERNAME/ksr-mart.git
git push -u origin main
```

Replace `YOUR_USERNAME` with your GitHub username.

`origin` is just the nickname for that GitHub URL. `push` copies your laptop history to GitHub. `-u` remembers the link so later you can type `git push`.

Refresh the GitHub page. You should see `README.md`.

You just put a project on GitHub. That is the session.

---

7. What happened?

Step	What you needed	What you ran
Start history in this folder	A project Git can track	`git init -b main`
Choose files for a checkpoint	Not every random file on the Desktop	`git add README.md`

Step	What you needed	What you ran
Save the checkpoint locally	A version you can come back to	`git commit -m "..."`
Name the GitHub copy	An address for the shared repo	`git remote add origin URL`
Send the history	Teammates / recruiters can see it	`git push -u origin main`

The checkpoint is on your laptop **and** on GitHub. If Wi-Fi dies after `commit` but before `push`, the work is still on this machine. Push is a copy, not the first save.

---

8. Try this

In `~/KSR_MART`, add one line to `README.md`, then:

```
git status
git add README.md
git commit -m "Update README with one more line"
git push
```

Refresh GitHub. The new line should be there.

Common mistakes

You created the GitHub repo with a README. GitHub already has a commit. Your laptop has a different first commit. `git push` is rejected. For this session, delete that GitHub repo and create an **empty** one, or ask the trainer. Next sessions will teach `git pull` for this situation.

You ran `git add .` from the Desktop. You may stage hundreds of files. Always `cd` into `KSR_MART` first. `git status` before `git add`.

You saved in the editor and thought Git had a checkpoint. Save writes the disk. `commit` writes history.

You mixed up Git and GitHub. Git made the checkpoint on the laptop. GitHub received the copy when you pushed.

Key takeaway

Git records history on your computer. **GitHub** holds the shared copy.

Today's loop:

```
edit → git add → git commit → git push
```

Session 2 explains that loop properly (including `status`, `log`, and how to start from someone else's GitHub repo). You already survived the first push. The next sitting is about using this every day.