Kasi Yedumati · Full Stack Training

Lesson 3 — Page Structure & the Box Model


Course: HTML & CSS for Full Stack · **Session 3 of 9** · Learning path · **Previous:** Lesson 2 · **Next:** Lesson 4 — Images, Navigation & Flexbox

> **Module Outcome:** You can divide a page into meaningful regions, show label–value data correctly, and control the size and spacing of every box on the page.

You will build	The AcmeHR **Employee profile** page
New HTML	`header`, `nav`, `main`, `section`, `aside`, `footer`, `div`, `span`, `dl`, `dt`, `dd`
New CSS	The box model: `margin`, `padding`, `border`, `border-radius`, `width`, `max-width`, `box-sizing`, the `*` selector · `display` · `list-style` · `font-size`, `text-align` · units `px`, `rem`, `%`
You need	Lessons 1 and 2

From the requirements. The AcmeHR employee profile stores the employee ID, name, contact information, emergency contact, employment details, reporting manager, department and designation. Employees can view their profile.

Where we are going:



All example files: `examples/lesson03/`


Part A — Structure

1. Page regions

Most pages have the same regions. HTML has an element for each one:

```
<header>
  <p>header — AcmeHR logo and name</p>
  <nav>
    <p>nav — links to other pages</p>
  </nav>
</header>
<main>
  <h1>main — Ananya Rao</h1>
  <section>
    <h2>section — Employment details</h2>
  </section>
  <section>
    <h2>section — Contact information</h2>
  </section>
</main>
<aside>
  <p>aside — related: reporting manager</p>
</aside>
<footer>
  <p>footer — © Acme · Help</p>
</footer>
```

Output (blue outlines = regions, red dashed = sections):



Element	Holds	Per page
`<header>`	Logo, site name, often the `nav`	Usually one at the top
`<nav>`	The main links to other pages	One or two
`<main>`	The content that is unique to this page	**Exactly one**

Element	Holds	Per page
`<section>`	One themed part of the content, **with a heading**	Any number
`<aside>`	Related but secondary content	Optional
`<footer>`	Copyright, help links, contact	Usually one at the bottom


Why it matters: Screen readers offer a "jump to main content" and "jump to navigation" shortcut for these regions. Search engines use them too. And your CSS becomes readable: `header`, `nav`, `main` say what they are.

2. `div` and `span` — boxes with no meaning

```
<div class="card">
  <h2>Ananya Rao</h2>
  <p>Senior Software Engineer · <span class="status">Active</span></p>
</div>
```

```
.status { color: #15803d; font-weight: bold; }
.card { background-color: #eef2f7; }
```

Output:



- `<div>` is a **block** box with no meaning. `<span>` is an **inline** box with no meaning.
- Use them only for styling hooks, when no meaningful element fits.

Common Error: "div soup" — a page built only from `div`s. If an element exists for the job (`header`, `nav`, `main`, `section`, `p`, `ul`), use it.

3. Label–value pairs — `dl`, `dt`, `dd`

```
<h2>Employment details</h2>
<dl>
  <dt>Employee ID</dt>
  <dd>E-1042</dd>
  <dt>Department</dt>
  <dd>Engineering</dd>
  <dt>Reporting manager</dt>
  <dd>Karthik Menon</dd>
</dl>
```

Output:



Element	Meaning
`<dl>`	Description list — a list of label–value pairs
`<dt>`	The label (term)
`<dd>`	The value (description)

Profile fields, order summaries, and settings pages are all label–value data. `dl` keeps each label tied to its value.

4. The profile page in HTML

```
<header>
  <p>AcmeHR</p>
  <nav>
    <ul>
      <li><a href="#">Home</a></li>
      <li><a href="#">Profile</a></li>
      <li><a href="#">Directory</a></li>
      <li><a href="#">Leave</a></li>
    </ul>
  </nav>
</header>

<main>
  <h1>Ananya Rao</h1>
  <p>Senior Software Engineer · <span class="status">Active</span></p>


  <section>
    <h2>Employment details</h2>
    <dl>
      <dt>Employee ID</dt>
      <dd>E-1042</dd>
      <dt>Department</dt>
      <dd>Engineering</dd>
      <dt>Designation</dt>
      <dd>Senior Software Engineer</dd>
      <dt>Reporting manager</dt>
      <dd>Karthik Menon</dd>
      <dt>Location</dt>
      <dd>Hyderabad</dd>
    </dl>
  </section>

  <section>
```

```
    <h2>Contact information</h2>
    <dl>
      <dt>Work email</dt>
      <dd><a href="mailto:ananya.rao@acme.example">ananya.rao@acme.example</a></dd>
      <dt>Phone</dt>
      <dd>+91 90000 01042</dd>
      <dt>Emergency contact</dt>
      <dd>Ravi Rao (father), +91 90000 11111</dd>
    </dl>
  </section>
</main>

<footer>
  <p>AcmeHR · Sample data for this course</p>
</footer>
```

Output:



AcmeHR

- Home
- Profile
- Directory
- Leave

Ananya Rao

Senior Software Engineer · Active

Employment details

Employee ID
E-1042
Department
Engineering
Designation
Senior Software Engineer
Reporting manager
Karthik Menon
Location
Hyderabad

Contact information

Work email
ananya.rao@acme.example
Phone
+91 90000 01042
Emergency contact
Ravi Rao (father), +91 90000 11111

AcmeHR · Sample data for this course


The navigation is a **list of links** inside `nav`. In section 11 it becomes a horizontal bar.

Note: The `href="#"` links are placeholders until those pages exist.

Part B — The box model

5. Every element is a box

Every element — block or inline — is drawn as a box with four layers:




```
body { background-color: #fde68a; }  /* yellow = the margin area around the box */
.box {
  margin: 32px;
  border: 8px solid #1a365d;
  padding: 24px;
  background-color: #bfdbfe;     /* blue = padding + content */
}
```

```
<div class="box">Content: Ananya Rao, Engineering</div>
```

Output:




- **Content** — the text.
- **Padding** — space between the content and the border. The background colour fills it.
- **Border** — `width style colour`, for example `8px solid #1a365d`.
- **Margin** — space outside the border, between this box and its neighbours. Always transparent.

6. Margin and padding values

```
p { background-color: #bfdbfe; }
.tight { padding: 0; margin: 0; }
.roomy { padding: 16px; margin: 24px 0; }
.sides { padding: 8px 32px; }
```

Output:



You write	Means
`padding: 16px`	All four sides 16px
`padding: 8px 32px`	Top and bottom 8px, left and right 32px
`margin: 24px 0 8px`	Top 24px, left and right 0, bottom 8px
`padding: 1px 2px 3px 4px`	Top, right, bottom, left — clockwise from the top
`margin-top: 24px`	One side only (also `-right`, `-bottom`, `-left`)

7. `box-sizing` — what does `width` measure?

```
.ruler { width: 300px; height: 8px; background-color: #1b2430; }
.box {
  width: 300px;
  padding: 20px;
  border: 5px solid #1a365d;
}
.content-box { box-sizing: content-box; }
.border-box  { box-sizing: border-box; }
```

Output (each black ruler is exactly 300px):



- **`content-box`** (the browser default): `width` is the content only. Padding and border are **added**: 300 + 40 + 10 = 350px.
- **`border-box`**: `width` includes padding and border. 300px means 300px.


Every professional stylesheet starts by switching every element to `border-box`. `*` is the **universal selector** — it matches every element:

```
* {
  box-sizing: border-box;
}
```

8. Centring a box — `max-width` + `margin: auto`

```
body { background-color: #f4f6f8; }
.card {
  max-width: 400px;
  margin: 24px auto;      /* auto left and right = centred */
  padding: 16px;
  background-color: #ffffff;
  border: 1px solid #d0d7de;
  border-radius: 8px;
}
```

Output:



- `max-width: 400px` — never wider than 400px, but narrower on a small screen. (`width: 400px` would overflow a phone.)
- `margin: 24px auto` — the browser splits the leftover space equally left and right.
- `border-radius` rounds the corners.

9. Margins between paragraphs collapse

```
.note { margin: 24px 0; background-color: #bfdbfe; }
```

```
<p class="note">This paragraph has margin-bottom: 24px.</p>
<p class="note">This one has margin-top: 24px. The gap between them is 24px, not 48px.</p>
```

Output:

This paragraph has margin-bottom: 24px.

This one has margin-top: 24px. The gap between them is 24px, not 48px.

When a bottom margin meets a top margin, the browser uses the **larger one**, not the sum. This is called **margin collapse**. It only happens with vertical (top and bottom) margins of block elements.

Common Error: "I added `margin-top: 24px` and nothing moved." The neighbour already had a margin of 24px or more, and the two collapsed.

10. `display` — choosing the box type

```
span { background-color: #bfdbfe; width: 120px; padding: 4px; }
.inline-block { display: inline-block; }
.block { display: block; }
.hidden { display: none; }
```

Output:

inline: Casual Sick — width is ignored

inline-block: Casual Sick — width works, stays in the line

block:
Casual
Sick

none: — the span is gone

`display`	New line?	`width` / `height` work?
`inline` (span, a, strong)	No	No
`inline-block`	No	Yes
`block` (div, p, li)	Yes	Yes
`none`	The element is removed from the page	—

11. The navigation bar

```
nav ul {
  list-style: none;   /* no bullets */
  margin: 0;
  padding: 0;
  background-color: #1a365d;
```

```
}
nav li {
  display: inline-block;
}
nav a {
  display: block;
  padding: 12px 16px;
  color: #ffffff;
}
```

Output:




1. `list-style: none` removes the bullets; `margin: 0` and `padding: 0` remove the list's default indent.
2. `display: inline-block` puts the `li`s side by side.
3. `display: block` + `padding` on the link makes the **whole padded area clickable**, not just the text.

In Lesson 4, Flexbox does this with less code.

12. Units — `px`, `rem`, `%`

```
.px  { font-size: 16px; }
.rem { font-size: 1.25rem; }   /* 1.25 × the root font size (16px by default) = 20px */
.half { width: 50%; }
```

Output:



Unit	Relative to	Use for
`px`	Nothing — fixed	Borders, small fixed details
`rem`	The root font size (16px unless the reader changed it)	**Font sizes**
`%`	The parent's width	Widths

Why `rem` for text: Some readers set a bigger default font in their browser. Text in `rem` grows with that setting; text in `px` ignores it.

13. Putting it together — the styled profile

The HTML from section 4, linked to `profile.css`:

```
/* AcmeHR — employee profile */

* {
  box-sizing: border-box;
}

body {
  margin: 0;
  font-family: system-ui, sans-serif;
  line-height: 1.5;
  color: #1b2430;
  background-color: #f4f6f8;
}

/* Header and navigation */
header {
  padding: 0 24px;
  background-color: #1a365d;
  color: #ffffff;
}

header p {
  display: inline-block;
  margin: 0;
  padding: 12px 0;
  font-weight: bold;
}

nav {
  display: inline-block;
  margin-left: 24px;
}

nav ul {
  list-style: none;
  margin: 0;
  padding: 0;
}

nav li {
  display: inline-block;
}

nav a {
  display: block;
  padding: 12px;
  color: #ffffff;
}

/* Main card */
main {
  max-width: 720px;
  margin: 24px auto;
  padding: 24px;
  background-color: #ffffff;
  border: 1px solid #d0d7de;
  border-radius: 8px;
}
```

```
h1 {
  margin: 0;
  font-size: 1.75rem;
  color: #1a365d;
}

h2 {
  margin: 24px 0 8px;
  padding-bottom: 4px;
  border-bottom: 2px solid #e2e8f0;
  font-size: 1.125rem;
  color: #1a365d;
}

.status {
  padding: 2px 8px;
  border-radius: 999px;
  background-color: #dcfce7;
  color: #166534;
  font-weight: bold;
}


/* Label and value pairs */
dl {
  margin: 0;
}

dt {
  font-weight: bold;
  font-size: 0.875rem;
  color: #3d4654;
}

dd {
  margin: 0 0 12px;
}

footer {
  text-align: center;
  font-size: 0.875rem;
  color: #3d4654;
}
```

Output:



Files: `13_profile_styled.html` · `profile.css`

- `body { margin: 0; }` removes the browser's default 8px margin, so the header touches the edges.
- `border-radius: 999px` on the badge gives a pill shape: any radius larger than the box rounds the ends fully.
- `text-align: center` centres the text inside the footer.

Common Error: Spacing that looks random. Use a small set of values — 4, 8, 12, 16, 24, 32px — and reuse them everywhere. Real design systems do exactly this.

Where used? Django and Spring apps reuse one header, nav and footer on every page through a **base template** (`{% extends "base.html" %}` in Django, a Thymeleaf layout in Spring). The regions you wrote today are what goes into that base template.

Try these

1. **(Easy)** Add an `<aside>` to the profile with the heading "Leave balance" and a `dl` of three leave types and their balances.
2. **(Easy)** Change `main` to `max-width: 960px`. What changes, and what stays the same?
3. **(Medium)** Remove the `*` rule from `profile.css`. Which boxes change size, and why?
4. **(Medium)** Give the `.status` badge a 1px solid border in `#166534`. Keep the pill shape.
5. **(Stretch)** Make the footer a navy bar like the header, with white text and 16px padding.

Interview: "*Explain the CSS box model.*" — Every element is a box: content, then padding, then border, then margin. By default, `width` sets only the content, so padding and border are added. With `box-sizing: border-box`, `width` includes padding and border, which is why most stylesheets set it on every element.

Interview: "*What is margin collapse?*" — When the vertical margins of two block elements meet, the browser uses the larger margin instead of adding them.

Interview: "*`section` or `div`?*" — `section` for a themed part of the content with its own heading. `div` only as a styling wrapper with no meaning.

Key takeaways

- Use `header`, `nav`, `main`, `section`, `aside`, `footer` for regions; `div` and `span` only as styling hooks.
- `dl` / `dt` / `dd` for label–value data.
- Box = content + padding + border + margin. Always set `box-sizing: border-box`.
- Centre a box with `max-width` and `margin: 0 auto`.
- Vertical margins collapse to the larger one.
- `rem` for font sizes.

Lab

👉 Lab 03 — AcmeHR employee profile

Next: Lesson 4 — Images, Navigation & Flexbox