Session 2 — Daily Git workflow

Shared topic (Python FS + Java FS) · **~75 minutes**

Index: Git and GitHub
Previous: Session 1 — First GitHub push
Next: Session 3 — Feature branches and Pull Requests

Session Outcome

Session 1 got **KSR_MART** onto GitHub. This sitting is the weekday loop you will type for the rest of the course (and at work).

By the end you will be able to:

- Read `git status` and know where each file sits
- Choose files for a checkpoint, commit with a useful message, and read history
- See what you changed with `git diff` before you pack it
- Pull when GitHub is ahead of your laptop
- Clone an existing GitHub repo instead of starting from `git init`
- Keep secrets and generated folders out of Git with `.gitignore`

You already know `add`, `commit`, and `push`. Today you learn *why* that packing step exists, and how a teammate starts from GitHub.

Lab after this sitting: labs/01_git_portfolio_hygiene

1. The problem after Session 1

You changed three files in KSR_MART:


- `README.md` — a typo
- login notes — unfinished
- a screenshot on the Desktop you copied into the folder by mistake

You need a checkpoint for the typo **only**. The unfinished login should stay on your desk. The screenshot should never go to GitHub.

Need: a packing list. Git does not have to snapshot every file you touched.

That packing list is the **staging area**. `git add` puts a file on the list. `git commit` seals only what is on the list.

2. The picture



Place	What it is	Why it exists
Working folder	Files you edit	This is the project on disk
Staging area	Files you **chose** for the next checkpoint	So one commit can be “fix README typo,” not “everything on my desk”
Local repo	Checkpoints on this laptop	History works with Wi-Fi off
GitHub (`origin`)	Shared copy	Teammates and recruiters see this

`git push` sends **commits**, not “the file I have open.” If you did not commit, GitHub does not change.

`git pull` is the other direction: GitHub has commits your laptop does not have yet. You will need this as soon as a teammate pushes — or as soon as you clone a second copy.

---

3. Daily commands

Stay in `~/KSR_MART` for this section (`cd ~/KSR_MART` first).

`git status` — what is going on?

You cannot see staging by looking at the folder in Explorer or Finder. Ask Git.

```
git status
```

Typical lines:

- `Untracked files` — Git has never checkpointed this file
- `Changes not staged for commit` — you edited a file Git already knows; it is **not** on the packing list yet
- `Changes to be committed` — on the packing list, waiting for `commit`
- `working tree clean` — no leftover edits

Run `status` before `add`, and again after `commit`.

`git diff` — what did I change?

The cart total looks wrong. You do not remember the edit.

```
git diff
```

That is the unstaged edit vs the last checkpoint. Read it **before** you pack.

After `git add`, that diff goes quiet. To re-read what you packed:

```
git diff --staged
```

`git add` — choose files for this checkpoint

```
git add README.md
```

One file. That is the usual beginner move.

`git add .` packs **everything** changed in this folder. Use it only after `git status` looks right. If you are in the wrong folder, you can pack the whole Desktop.

`git commit` — seal the checkpoint

```
git commit -m "Fix typo in KSR_MART README"
```

The message is the label on the box. You will read it weeks later in `git log`.

Write it like an order:

```
Add cart notes
Fix README typo
Update product list
```

Not `ok`, `final`, or `asdf`.

`git log` — what checkpoints exist?

```
git log --oneline
```

Newest is at the **top**. Hashes differ on every machine. Read the messages, not the hashes.

`git push` — send commits to GitHub

```
git push
```

Session 1 already set `-u origin main`. After that, `git push` is enough.

Push is a copy. The checkpoint is already on this laptop from `commit`.

`git pull` — GitHub has work you do not

A teammate pushed cart notes while you were at lunch. Your laptop is behind GitHub.

```
git pull
```

That copies their commits into your local repo and updates your files.

If GitHub is not ahead, pull does little. If both of you edited the **same lines**, Git cannot decide — that is a **merge conflict**, Session 4. For this sitting, pull when you did not touch those files, or pull before you start work.

Do not skip pull if someone else uses the same repo. Pushing while you are behind is rejected. Session 4 treats that incident. Today: pull, then work, then push.

---

4. Try the loop on KSR_MART

```
cd ~/KSR_MART
echo "Tea 20, lunch 80" > NOTES.txt
git status
git diff
git add NOTES.txt
git status
git commit -m "Add canteen spend notes"
git log --oneline
git push
```

After `git add`, `NOTES.txt` should sit under **Changes to be committed**. After `commit`, `status` should be clean. Refresh GitHub. `NOTES.txt` should be there.

Edit `NOTES.txt` once more, run `git diff`, then add, commit (`Update canteen spend notes`), and push.

---

5. Keep junk out of Git — `.gitignore`

Git will pack whatever you `add`. A virtual environment, compiled Java, and `.env` secrets do not belong on GitHub.

Create `~/KSR_MART/.gitignore`:

```
.env
venv/
.venv/
__pycache__/
*.pyc
target/
*.class
.idea/
.vscode/
.DS_Store
```

Then:

```
git add .gitignore
git commit -m "Ignore secrets and generated folders"
git push
```

Python regenerates `venv/` and `__pycache__/`. Java regenerates `target/` and `*.class`. Do **not** ignore `*.py` or `*.java` — that is your source.


`.env.example` (dummy names, no real secrets) is fine to commit. A real `.env` is not.

If you already committed a secret, deleting the file later is not enough — it stays in history. Tell the trainer. Session 4 covers leaked files at a beginner level. For today: ignore **before** you add.

---

6. Join an existing repo — `git clone`

At work you rarely `git init`. The repo already lives on GitHub. You copy it to a new folder.




```
GitHub repository
        ↓  git clone
Local folder (history + origin already set)
        ↓  edit
        ↓  add / commit
        ↓  git push
```

Do not `git init` inside a clone. The clone already is a Git repo.

Use a **new folder name** so you do not overwrite `~/KSR_MART`:

```
cd ~
git clone https://github.com/YOUR_USERNAME/ksr-mart.git KSR_MART_clone
cd KSR_MART_clone
git status
git log --oneline
```

You should see the commits from Session 1 and this sitting. `origin` is already set. No `git remote add`.

Add a line as if you were a teammate joining the project:

```
echo "Rohan: payment page next" >> NOTES.txt
git add NOTES.txt
git commit -m "Add teammate note on payment page"
git push
```

Now `~/KSR_MART` is behind GitHub (the clone pushed). Update the original folder:

```
cd ~/KSR_MART
git pull
```

`NOTES.txt` should include Rohan's line. You just did clone → edit → push → pull on a second copy, which is the same shape as two teammates.

For a real teammate's project, clone **their** URL, not yours. Same commands.

---

7. Two ways onto a project

Situation	What you do
New project on your laptop	`git init`, then `remote add`, then `push` (Session 1)
Project already on GitHub	`git clone URL`, then edit / add / commit / push

If `git status` says `not a git repository`, you are in the wrong folder — or you have not `init` / `clone` yet.

Practice

Task 1 — Packing list

In `~/KSR_MART`, change `README.md` and `NOTES.txt`. Stage **only** `README.md`. Commit. Confirm with `git status` that `NOTES.txt` is still unstaged. Then stage and commit `NOTES.txt` separately. Push.

Expected: two commits, two messages, GitHub has both files.

Task 2 — Lab

Do labs/01_git_portfolio_hygiene. Finish `.gitignore` and a README a teammate can run. Do not commit `.env`.

Common mistakes

`git add .` without `status`. You pack leftover screenshots, `.env`, or `venv/`. Status first. Ignore file first.

`git commit` with nothing staged. Git refuses, or you think the editor save was a commit. `status` until you see **Changes to be committed**.

`git init` inside a clone. Now you have a nested repo. Clone already created `.git`. Just `cd` into the clone.

`git clone` into a folder that already exists and is not empty. Clone wants a new directory. Use `KSR_MART_clone` or another empty name.

Push from one folder, then push from the other without pull. The second push is rejected. `git pull` in that folder, then `git push`. If Git reports a conflict, stop — Session 4.

Commit message `update`. Future you cannot search that. `Fix README typo` is enough.

Key takeaway

```
edit  →  status / diff  →  add  →  commit  →  push
```

When GitHub is ahead: **pull** first.

When the project already exists on GitHub: **clone**, do not init.

Staging exists so a checkpoint can be *one idea*, not every file you touched.

Session 3: the app on `main` is stable, but you need a login feature. You will work on a **branch** and open a Pull Request so unfinished login does not land on `main` by accident.