Module: Methods

Phase: Core Java
Previous module: Arrays
Next module: OOP Part 1 — Classes and Encapsulation

Module Outcome:

- Name a job (`withdraw`) and call it instead of pasting the ATM check twice
- Pass arguments and return a value — `void` vs `int` with intent
- Overload when the same job takes different inputs (amount vs amount+note)

What is a method?

A **method** is a named block of code that does one job. You **call** it when you need that job.


🏦 Bank 📱 UPI 👤 Employee 📦 Order 💰 Payroll

Where used?
- **HDFC Bank** — `deposit`, `withdraw` as separate jobs
- College apps — `average`, `isPass`
- **Swiggy** — `lineTotal(price, qty)`
- **Employee Management Portal** — `netPay(basic)`
- **Apollo Hospitals** — `formatPhone`

Purpose: Stop copy-paste. Name the idea (`gstTotal`) instead of repeating the formula.

```
public static double gstTotal(double price, int qty) {
    return price * qty * 1.05;
}
```

Visual — call stack lite:



Key takeaways:
- Definition = the recipe; call = using the recipe
- `return` sends a value back (or just ends a `void` method)
- `static` here means “belongs to the class” — enough until OOP

Important Concepts and Definitions

Term	Definition
Method	Named reusable block
Parameter	Input variable in the definition
Argument	Actual value you pass at the call
return type	Type after `static` (`int`, `void`, `double`)
void	Returns nothing
Overload	Same name, different parameters
Pass-by-value	The method gets a copy of the primitive
static	Callable as `ClassName.method` / from `main` without an object

Step-by-Step Notes (With Annotated Code)

Step 1: void method — print banner

```
public class Banner {
    public static void printBanner() {
        System.out.println("==== KSR ATM ====");
    }

    public static void main(String[] args) {
        printBanner();
        printBanner();
    }
}
```

Expected Output:

```
==== KSR ATM ====
==== KSR ATM ====
```

Write a `void greet` method that prints Namaste for Priya, then call it from `main`.

```
public class GreetMethod {
    public static void greet() {
        System.out.println("Namaste, Priya");
    }

    public static void main(String[] args) {
        greet();
    }
}
```

Write `showMenu` and `bye` as two `void` methods, then call both from `main`.

```
public class TwoJobs {
    public static void showMenu() {
        System.out.println("1 Add  2 List");
    }

    public static void bye() {
        System.out.println("Thank you");
    }

    public static void main(String[] args) {
        showMenu();
        bye();
    }
}
```

Step 2: Parameters and return

```
public class LineTotal {
    public static double lineTotal(double price, int qty) {
        return price * qty;
    }

    public static void main(String[] args) {
        double t = lineTotal(40.0, 2);
        System.out.println(t);
    }
}
```

Expected Output:

```
80.0
```

Note:

- Wrong: `return` then more statements that must run after it in the same path.
- Prefer: compute, then one `return`.

Write `average` that takes two doubles, returns their mean, and print `average(80, 70)`.

```
public class AvgTwo {
    public static double average(double a, double b) {
        return (a + b) / 2.0;
    }

    public static void main(String[] args) {
        System.out.println(average(80, 70));
    }
}
```

Expected Output:

```
75.0
```

Write a Swiggy `withGst` helper that multiplies a subtotal by 1.05, then print `withGst(80)` as rupees with two decimals.

```
public class GstHelper {
    public static double withGst(double subtotal) {
        return subtotal * 1.05;
    }

    public static void main(String[] args) {
        System.out.printf("₹%.2f%n", withGst(80));
    }
}
```

Step 3: Overloading

```
public class OverloadDemo {
    public static int add(int a, int b) {
        return a + b;
    }

    public static double add(double a, double b) {
        return a + b;
    }

    public static void main(String[] args) {
        System.out.println(add(2, 3));
        System.out.println(add(2.5, 3.5));
    }
}
```

Expected Output:

```
5
6.0
```

Same name is OK when the **parameter list** differs. Return type alone is **not** enough to overload.

Overload `greet` with a no-arg version that prints Hello and a `String` version that greets Ravi by name; call both.

```
public class GreetOverload {
    public static void greet() {
        System.out.println("Hello");
    }

    public static void greet(String name) {
        System.out.println("Hello, " + name);
    }

    public static void main(String[] args) {
        greet();
        greet("Ravi");
    }
}
```

Overload `area` for a square of side 4 and a 4-by-5 rectangle, then print both areas.

```
public class AreaOverload {
    public static int area(int side) {
        return side * side;
    }

    public static int area(int length, int width) {
        return length * width;
    }

    public static void main(String[] args) {
        System.out.println(area(4));
        System.out.println(area(4, 5));
    }
}
```

Step 4: Pass-by-value (primitives)

```
public class PassByValue {
    public static void tryChange(int n) {
        n = 99;
        System.out.println("inside: " + n);
    }

    public static void main(String[] args) {
        int balance = 1000;
        tryChange(balance);
        System.out.println("outside: " + balance);
    }
}
```

Expected Output:

```
inside: 99
outside: 1000
```

The method received a **copy**. To update balance, **return** the new value:

```
public static double deposit(double balance, double amount) {
    return balance + amount;
}
```

Interview: Java passes primitives by value. (Arrays are a reference copy — the method can change **elements**. Return is still clearer for ATM balance.)

Write an HDFC Bank `deposit` that returns the new balance; start at 1000, deposit 200, and print the result.

```
public class DepositReturn {
    public static double deposit(double balance, double amount) {
        return balance + amount;
    }

    public static void main(String[] args) {
        double balance = 1000;
        balance = deposit(balance, 200);
        System.out.println(balance);
```

```
    }
}
```

Expected Output:

```
1200.0
```

Write an HDFC Bank `withdraw` that prints Insufficient balance and returns the old balance on overdraft; call it with 1200 then 200 from 1000.

```
public class WithdrawReturn {
    public static double withdraw(double balance, double amount) {
        if (amount > balance) {
            System.out.println("Insufficient balance");
            return balance;
        }
        return balance - amount;
    }

    public static void main(String[] args) {
        System.out.println(withdraw(1000, 1200));
        System.out.println(withdraw(1000, 200));
    }
}
```

Expected Output:

```
Insufficient balance
1000.0
800.0
```

Step 5: Refactor calculator into methods

```
public class CalcMethods {
    public static double subtotal(double price, int qty) {
        return price * qty;
    }

    public static double totalWithGst(double subtotal) {
        return Math.round(subtotal * 1.05 * 100.0) / 100.0;
    }

    public static void main(String[] args) {
        double s = subtotal(40, 2);
        System.out.printf("Total: ₹%.2f%n", totalWithGst(s));
    }
}
```

Step 6: Refactor ATM — methods in one class

Keep `showMenu`, `deposit`, `withdraw` as `static`. `main` only loops and calls.

Bad amount: **print + return unchanged balance**. No `throw`.

Lab kit: 15_Lab_Assets/08_methods_refactor.

Practice Exercises

Basic

1. Write `static void printStars()` that prints `***`. Call it twice.

Model answer: Method with one `println`; `main` calls it twice.

2. `static int square(int n)` returning `n * n`. Print `square(6)`.

Model answer: `return n * n;` → `36`

3. Overload `max` for two `int` and two `double`.

Model answer: Two methods named `max` with different parameter types.

4. What does `void` mean?

Model answer: The method does not return a value. Use `return;` only to exit early.

Intermediate

1. Extract canteen GST into `subtotal` and `totalWithGst`.

Model answer: See Step 5.

2. `isPass(double marks)` returns `true` if `>= 35`. Print the boolean.

Model answer: `return marks >= 35;`

3. ATM `withdraw` returns the (possibly unchanged) balance; prints on overdraft.

Model answer: See Step 4 Program 2.

4. Refactor last week's ATM: `showMenu`, `deposit`, `withdraw` static; `main` loops.

Model answer: Lab kit 08. Still **one** class. No `new BankAccount()`.

Interview-Oriented

1. Method vs constructor (preview only).

Model answer: A constructor's name matches the class and has no `return` type — **OOP next**. Methods have a return type (`void` or other).

2. Can you overload by return type only?

A: No. Parameter list must differ.

3. Pass-by-value for `int`?

A: The callee gets a copy. Changing the copy does not change the caller's variable.

4. Why `static` in this week's demos?

A: `main` is `static` and can call other `static` methods without creating an object. Instance methods come with classes/objects next.

Mini-Project (Assignment): Refactor HDFC Bank ATM Into Methods

Lab kit: 15_Lab_Assets/08_methods_refactor

What to build

Same ATM behaviour as Flow week, but `deposit` / `withdraw` / `showMenu` are static methods. `main` is the loop only.

Stretch

- `printBalance(double balance)` helper.
- **Later — OOP:** move the same ideas onto a `BankAccount` object.

Done when

- [ ] No giant `main` with all math inline
- [ ] Overdraft prints and leaves balance unchanged (`print` + `return`, no `throw`)
- [ ] Menu repeats until Quit
- [ ] Still a single class (no `new` account object)

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

Q1. What is a method?
A: A named block you can call. It can take parameters and optionally return a value.

Q2. Parameter vs argument?
A: Parameter is the variable in the definition (`double amount`). Argument is the value at the call (`200`).

Q3. What is overloading?
A: Multiple methods with the same name and different parameter lists. The compiler picks the match.

Q4. How do you update a primitive from a method?
A: Return the new value and assign: `balance = deposit(balance, amt);`

Q5. `main` signature again?
A: `public static void main(String[] args)` — the JVM entry point that can call your other static methods.