Module: MySQL for Full Stack Developers

Phase: Database
SQL material (source of truth): `MYSQL/README.md` — open those files on lab days.
Schedule: Session Calendar — Weeks 10–11 / Sessions 46–54 (JDBC follows in `07_JDBC/`).
Java connectivity: `../07_JDBC/01_JDBC_CRUD.md`

> **Note:** This FS module is the **bridge** (ER, normalization, JDBC context). Placement-ready SQL depth is taught from `MYSQL/` during **Weeks 10–11**. Do not treat SQL as optional. Do not copy `MYSQL/` into `JAVA/`.

Previous module: Git and GitHub
Next module: JDBC CRUD

Module Outcome:

- Sketch an ER for AcmeHR / TechMart before JDBC
- Open the real SQL labs in `MYSQL/` — this file is the bridge, not the course
- Normalise enough that one fact does not live in three columns

Prerequisites

- MySQL installed — `MYSQL/00_MySQL_Setup_and_Connection.md`

Required MySQL labs (Weeks 10–11)

SQL is a **core placement skill**. Deep notes live in `MYSQL/`; the labs below are **mandatory** for every Java FS batch. Aim for independent CRUD + JOINs before JDBC and Spring Data JPA.

Done	When	Lab file	You must be able to
☐	W10	`MYSQL/00_MySQL_Setup_and_Connection.md` + `MYSQL/README.md`	Install/connect; create `training_db`
☐	W10	`MYSQL/01_Introduction_to_Databases.md`	Explain table/row/DBMS vs Excel
☐	W10	`MYSQL/02_Introduction_to_SQL_Basic_Concepts.md`	DDL + DML CRUD + constraints
☐	W10	`MYSQL/03_Querying_with_SQL.md`	WHERE, LIKE, ORDER BY, LIMIT
☐	W10	`MYSQL/labs/README.md`	Run `training_db_seed.sql` before ch. 03 drills
☐	W10	This bridge module	ER sketch for Library / CampusCart

Done	When	Lab file	You must be able to
☐	W11	`MYSQL/06_Modeling_Databases.md`	PK/FK, 1:N
☐	W11	`MYSQL/07_Joins.md`	INNER + LEFT JOIN multi-table reports
☐	W11	`MYSQL/09_Transactions_and_Indexes.md`	COMMIT/ROLLBACK; when index helps
☐	W11	`MYSQL/homework/10_Practice_Exercises.md`	Complete exercises for ch. 02, 03, 07
☐	W11–12	JDBC CRUD	Parameterized INSERT/SELECT/UPDATE/DELETE from Java

Strongly recommended before placement mocks: `MYSQL/04` · `MYSQL/05` · `MYSQL/08` · one project from `MYSQL/12`. Window functions (`MYSQL/11`) only if the required set is solid.

Exit ticket (without notes): CREATE with PK+FK · INSERT/UPDATE/DELETE · SELECT + WHERE/ORDER BY · INNER JOIN + explain LEFT JOIN · why `PreparedStatement` from Java (no string-concat SQL).

Teach order: why a DB (CSV/RAM pain) → connect + `training_db` → DDL with PK/FK → DML → DQL → ER sketch → INNER/LEFT JOIN → TCL + index lite → schema mini-project. JDBC is the **next** module.

Definition / Purpose

Definition: A **database** is **shared, structured storage that survives restart**. MySQL keeps CampusCart users, products, and orders in **tables** (rows + columns) on disk. A **table** is one kind of thing (products). A **row** is one record (Masala Dosa, ₹60). A **column** is one field (`price`).


Definition: A **full-stack application** has three layers: **frontend** (browser), **backend** (Java), and **database** (MySQL). When a student registers on CampusCart, the browser (or Postman) sends JSON to Java. Java validates it. SQL **INSERT**s a row into `users`.

Purpose: File Handling left you with an expense CSV that survives `java ExpenseFiles` on **one** laptop. Two canteen clerks cannot share it safely. An `ArrayList` dies when `main` ends. MySQL is the **shared source of truth**: concurrent orders, PK/FK rules, and the same tables the Java backend will talk to next with JDBC.



Where used?
- **TechMart** / CampusCart — customers, products, orders, order_items
- College apps — students, courses, enrollments in LMS / portals
- **AcmeHR** — `department` and `employee` tables
- **SecureBank** — accounts and `transaction_log` (PK/FK integrity matters)
- **MedCare** — patients, appointments, prescriptions as related rows

Visual — three layers talking:



Key takeaways:
- Browser → Java backend → MySQL (and back)
- Frontend never talks SQL directly — JDBC (**Later —** this phase) or JPA (**Later —** Spring) issues INSERT/SELECT
- Same pattern for a React SPA or a Postman collection

Definition: A **primary key (PK)** uniquely identifies each row. A **foreign key (FK)** references a PK in another table — how "this order belongs to that customer" is enforced.

SQL categories:

Category	Purpose	Examples
DDL	Define structure	CREATE TABLE, ALTER, DROP
DML	Change data	INSERT, UPDATE, DELETE
DQL	Read data	SELECT
TCL	Control transactions	COMMIT, ROLLBACK

This module is the **bridge**. For syntax labs, open `MYSQL/` from the checklist. **Later —** Java talks to those tables with JDBC (`PreparedStatement`), then Spring Data JPA.

> **Remember:** JPA does not replace SQL interviews. Finish the required `MYSQL/` labs.

> **Interview:** Be ready to write an INNER JOIN on a whiteboard *and* explain why the Java code will use placeholders (`?`) instead of string concatenation. Do not write that Java syntax this week.

Important Concepts

> **Depth:** Run these in MySQL Workbench / CLI. For full labs, follow the calendar and open `MYSQL/` files from the checklist — this module is the bridge, **`MYSQL/` is the source of truth**.

1. Three domains (reuse all course)

Definition: Course examples sit in named **products** so the same PK/FK/JOIN skills transfer to LMS, **AcmeHR**, and CampusCart / **TechMart**. Full DDL lives in `MYSQL/12_Real_Time_Projects.md`.

Purpose: One schema language covers college, office, store, clinic, and bank. You stop inventing a new table style for every ticket.

Domain	Named product	Core tables	Full-stack use
Student	(college LMS — keep generic)	students, courses, enrollments	LMS, college portals
Employee	**AcmeHR**	department, employee, leave_record	HRMS, payroll
Ecommerce	**TechMart** (CampusCart = college skin)	customer, product, cart, orders, order_item	CampusCart / store APIs
Hospital	**MedCare**	doctor, patient, appointment, prescription	Clinic booking
Banking	**SecureBank**	customer, account, transaction_log, loan	Teller / wallet

Note:
- Wrong: one giant `campus_data` spreadsheet with mixed students and orders.
- Prefer: one domain per set of tables; FKs between them when they truly relate.

Try these (2 programs):

Program 1 — Named-product domain sketch note

```
-- Which domain? CampusCart canteen = Ecommerce
-- Sketch only (comments) before CREATE:
-- users, vendors, products, orders, order_items
SELECT 'Ecommerce domain for CampusCart' AS note;
```

Expected Output:

```
+----------------------------------+
| note                             |
+----------------------------------+
| Ecommerce domain for CampusCart  |
+----------------------------------+
```

Program 2 — List tables you will need

```
-- Student portal needs:
-- students, courses, enrollments
SELECT 'students' AS table_name
```

```
UNION ALL SELECT 'courses'
UNION ALL SELECT 'enrollments';
```

Expected Output:

```
+-------------+
| table_name  |
+-------------+
| students    |
| courses     |
| enrollments |
+-------------+
```

2. DDL — creating structure

Definition: DDL (Data Definition Language) creates and changes **structure**: databases, tables, columns, keys. It does not insert Priya's order — that is DML.

Purpose: Without DDL, there is nowhere safe to put a row. `CREATE TABLE` with PK/FK is the contract the Java backend will later INSERT into.

Definition: An **ER sketch** (entity-relationship) is boxes-and-lines **before** SQL: which things exist, and how they relate (1:N). Draw it, then write CREATE.

Connect and create the lab database first — full install steps live in `MYSQL/00_MySQL_Setup_and_Connection.md`.

```
CREATE DATABASE IF NOT EXISTS training_db;
USE training_db;

CREATE TABLE students (
    student_id  INT PRIMARY KEY AUTO_INCREMENT,
    full_name   VARCHAR(100) NOT NULL,
    email       VARCHAR(150) UNIQUE NOT NULL,
    enrolled_on DATE DEFAULT (CURRENT_DATE)
);

CREATE TABLE departments (
    dept_id   INT PRIMARY KEY AUTO_INCREMENT,
    dept_name VARCHAR(80) NOT NULL UNIQUE
);

CREATE TABLE employees (
    emp_id    INT PRIMARY KEY AUTO_INCREMENT,
    full_name VARCHAR(100) NOT NULL,
    dept_id   INT NOT NULL,
    salary    DECIMAL(10, 2) DEFAULT 0,
    FOREIGN KEY (dept_id) REFERENCES departments(dept_id)
);


CREATE TABLE customers (
    customer_id INT PRIMARY KEY AUTO_INCREMENT,
    name        VARCHAR(100) NOT NULL,
    city        VARCHAR(60)
);

CREATE TABLE products (
    product_id INT PRIMARY KEY AUTO_INCREMENT,
    name       VARCHAR(120) NOT NULL,
    price      DECIMAL(10, 2) NOT NULL CHECK (price >= 0)
);
```

```
CREATE TABLE orders (
    order_id    INT PRIMARY KEY AUTO_INCREMENT,
    customer_id INT NOT NULL,
    order_date  DATETIME DEFAULT CURRENT_TIMESTAMP,
    FOREIGN KEY (customer_id) REFERENCES customers(customer_id)
);

CREATE TABLE order_items (
    item_id    INT PRIMARY KEY AUTO_INCREMENT,
    order_id   INT NOT NULL,
    product_id INT NOT NULL,
    quantity   INT NOT NULL DEFAULT 1,
    FOREIGN KEY (order_id) REFERENCES orders(order_id),
    FOREIGN KEY (product_id) REFERENCES products(product_id)
);
```

Visual — CampusCart relationships (why JOINs exist):



Key takeaways:

- Customer **1** → **many** Orders; Order **1** → **many** Order_items
- Order_item needs **both** `order_id` (FK) and `product_id` (FK)
- JOINs exist because related data lives in separate tables

One customer → many orders; one order → many line items; each line item points to a product.

Remember: Money columns use `DECIMAL(10,2)` — not `FLOAT` / `VARCHAR`.

Common Error: Forgetting `FOREIGN KEY` / UNIQUE on email → orphan orders and duplicate logins. Define constraints in DDL.

Note:

- VARCHAR/FLOAT for money — use `DECIMAL(10,2)` instead.
- No FOREIGN KEY — define FK in DDL.
- No UNIQUE on email — add a UNIQUE constraint.

Try these (2 programs):

Program 1 — Courses table for LMS

```
USE training_db;

CREATE TABLE IF NOT EXISTS courses (
    course_id INT PRIMARY KEY AUTO_INCREMENT,
    title     VARCHAR(120) NOT NULL,
    credits   INT NOT NULL CHECK (credits > 0)
);
```

```
SHOW COLUMNS FROM courses;
```

Program 2 — Enrollments with FKs

```
USE training_db;

CREATE TABLE IF NOT EXISTS enrollments (
    enrollment_id INT PRIMARY KEY AUTO_INCREMENT,
    student_id    INT NOT NULL,
    course_id     INT NOT NULL,
    enrolled_on   DATE DEFAULT (CURRENT_DATE),
    FOREIGN KEY (student_id) REFERENCES students(student_id),
    FOREIGN KEY (course_id) REFERENCES courses(course_id)
);
```

3. DML — changing data

Definition: DML (Data Manipulation Language) **changes rows**: INSERT, UPDATE, DELETE. Structure stays; data moves.

Purpose: DDL built empty shelves. DML stocks them. CampusCart cannot sell Filter Coffee until someone INSERTs it.

```
INSERT INTO students (full_name, email) VALUES
('Priya Sharma', 'priya@campus.in'), ('Rahul Verma', 'rahul@campus.in');

INSERT INTO departments (dept_name) VALUES ('Engineering'), ('HR');
INSERT INTO employees (full_name, dept_id, salary) VALUES ('Anita Rao', 1, 85000.00);

INSERT INTO customers (name, city) VALUES ('Meera', 'Hyderabad');
INSERT INTO products (name, price) VALUES ('Notebook', 45.00), ('Pen Pack', 120.00);
INSERT INTO orders (customer_id) VALUES (1);

UPDATE employees SET salary = salary * 1.10 WHERE dept_id = 1;
DELETE FROM students WHERE email = 'rahul@campus.in';  -- always use WHERE!
```

Note:
- `DELETE FROM students` without WHERE — always use WHERE; test with SELECT first.

Try these (2 programs):

Program 1 — TechMart seed canteen products (INR)

```
USE training_db;

INSERT INTO products (name, price) VALUES
('Masala Dosa', 60.00),
('Filter Coffee', 25.00),
('Veg Thali', 90.00);

SELECT product_id, name, price FROM products ORDER BY price;
```

Program 2 — Safe update then check

```
USE training_db;

-- Preview first
```

```
SELECT * FROM products WHERE name = 'Notebook';

UPDATE products SET price = 49.00 WHERE name = 'Notebook';

SELECT name, price FROM products WHERE name = 'Notebook';
```

4. DQL — reading data

Definition: DQL (Data Query Language) is **SELECT** — read without changing rows. Filters (`WHERE`), sort (`ORDER BY`), and cap (`LIMIT`) turn a table dump into a report.

Purpose: The canteen manager does not want every column of every order. They want products under ₹100, newest first.

```
SELECT full_name, email FROM students WHERE enrolled_on >= '2026-01-01';

SELECT e.full_name, d.dept_name, e.salary
FROM employees e JOIN departments d ON e.dept_id = d.dept_id
WHERE e.salary > 70000 ORDER BY e.salary DESC;

SELECT name, price FROM products WHERE price BETWEEN 40 AND 150;
```

Note:
- `SELECT *` in APIs — name columns explicitly.

Go deeper: `MYSQL/03_Querying_with_SQL.md`

Try these (2 programs):

Program 1 — TechMart products under ₹100

```
USE training_db;

SELECT name, price
FROM products
WHERE price < 100
ORDER BY price ASC;
```

Program 2 — TechMart Hyderabad customers

```
USE training_db;

SELECT customer_id, name, city
FROM customers
WHERE city = 'Hyderabad';
```

5. TCL + indexes lite

Definition: A **transaction** is a group of SQL statements that must **all succeed or all fail**. **TCL** (COMMIT / ROLLBACK) is the steering wheel.

Purpose: Checkout is two writes: insert the order **and** reduce stock. If the second fails, you must not keep a paid order with no stock change. `START TRANSACTION` … `COMMIT` / `ROLLBACK` protects that.

```
START TRANSACTION;
UPDATE products SET price = price - 10 WHERE product_id = 1;
```

```
-- ROLLBACK;  -- if error
COMMIT;
```

Definition: An **index** is a lookup shortcut on a column (like a book index). MySQL can find `email = 'priya@campus.in'` without scanning every row.

Purpose: PK and UNIQUE already create indexes. Extra indexes help frequent `WHERE` / JOIN columns. Too many indexes slow INSERT/UPDATE.

```
-- Lite: index a search column (products.name is used in WHERE)
CREATE INDEX idx_products_name ON products (name);
SHOW INDEX FROM products;
```

Remember: Index columns you filter or join on. Do not index every column.

Note:
- Autocommit is on by default in many clients — wrap multi-step money/stock changes in an explicit transaction.
- Index-everything "for speed" — writes get slower; index the queries you actually run.

Go deeper: `MYSQL/09_Transactions_and_Indexes.md`

Try these (2 programs):

Program 1 — TechMart rollback a bad price cut

```
USE training_db;

START TRANSACTION;
UPDATE products SET price = 1.00 WHERE name = 'Veg Thali';
SELECT name, price FROM products WHERE name = 'Veg Thali';
ROLLBACK;
SELECT name, price FROM products WHERE name = 'Veg Thali';  -- restored
```

Program 2 — TechMart commit a real discount

```
USE training_db;

START TRANSACTION;
UPDATE products SET price = price - 5 WHERE name = 'Filter Coffee';
COMMIT;
SELECT name, price FROM products WHERE name = 'Filter Coffee';
```

6. INNER JOIN vs LEFT JOIN

Definition: A **JOIN** combines rows from related tables using the FK = PK match. **INNER JOIN** keeps rows that match in **both** tables. **LEFT JOIN** keeps **all** left-table rows; missing right-side values are NULL.

Purpose: Names live in `customers`; dates live in `orders`. Reports need both. INNER JOIN is "people who ordered". LEFT JOIN is "all customers, even if they never ordered".

INNER JOIN — only rows matching in **both** tables:

```
SELECT e.full_name, d.dept_name
FROM employees e INNER JOIN departments d ON e.dept_id = d.dept_id;
```

LEFT JOIN — all rows from **left** table; NULL on right if no match:

```
SELECT c.name, o.order_id, o.order_date
FROM customers c LEFT JOIN orders o ON c.customer_id = o.customer_id;
```

Ecommerce chain (INNER JOINs):

```
SELECT c.name AS customer, p.name AS product, oi.quantity, p.price
FROM orders o
INNER JOIN customers c ON o.customer_id = c.customer_id
INNER JOIN order_items oi ON o.order_id = oi.order_id
INNER JOIN products p ON oi.product_id = p.product_id;
```

Go deeper: `MYSQL/07_Joins.md`

> **Note:**
> - JOIN without ON → Cartesian product — always write an explicit ON.

Try these (2 programs):

Program 1 — AcmeHR employees with department names

```
USE training_db;

SELECT e.full_name, d.dept_name, e.salary
FROM employees e
INNER JOIN departments d ON e.dept_id = d.dept_id
ORDER BY d.dept_name, e.full_name;
```

Program 2 — TechMart customers with or without orders

```
USE training_db;

INSERT INTO customers (name, city) VALUES ('Arjun', 'Pune');  -- no orders yet

SELECT c.name, o.order_id
FROM customers c
LEFT JOIN orders o ON c.customer_id = o.customer_id
ORDER BY c.name;
```

7. Normalization lite (1NF → 3NF)

Definition: Normalization splits repeating and derived facts into related tables so you update a fact **once**.

Purpose: `"Math, Physics"` in one column cannot be queried cleanly. Instructor stored on every enrollment row goes stale when the instructor changes. 1NF / 2NF / 3NF are the practical tests before you CREATE.

Normal Form	Rule	Bad example	Fix
1NF	Atomic columns; no repeating groups	`courses: "Math, Physics"`	`enrollments` junction table
2NF	No partial dependency on composite PK	instructor in enrollment row	Move to `courses`
3NF	No transitive dependency	dept_head in student row	Split `departments`

Go deeper: `MYSQL/06_Modeling_Databases.md`

> **Note:**
> - Comma-separated values in one column — use a junction table (1NF).

Try these (2 programs):

Program 1 — Fix a 1NF violation (sketch as SQL comments + create)

```
-- BAD: courses_csv VARCHAR storing "Math,Physics"
-- GOOD: enrollments rows
USE training_db;

INSERT INTO courses (title, credits) VALUES ('Math', 4), ('Physics', 3);
INSERT INTO enrollments (student_id, course_id) VALUES (1, 1), (1, 2);

SELECT s.full_name, c.title
FROM students s
INNER JOIN enrollments e ON s.student_id = e.student_id
INNER JOIN courses c ON e.course_id = c.course_id;
```

Program 2 — Spot the 3NF issue

```
-- BAD idea (do not create long-term):
-- students(full_name, dept_name, dept_head)
-- GOOD: departments(dept_name, dept_head) + students.dept_id FK
SELECT 'Move dept_head to departments table (3NF)' AS fix_note;
```

Expected Output:

```
+-----------------------------------------+
| fix_note                                |
+-----------------------------------------+
| Move dept_head to departments table (3NF)  |
+-----------------------------------------+
```

Step-by-Step Lab

Run in MySQL Workbench or CLI. Use the DDL/DML above. Do **not** open JDBC this week.

1. Connect per `MYSQL/00_MySQL_Setup_and_Connection.md`; run `CREATE DATABASE fullstack_lab; USE fullstack_lab;`
2. Execute DDL for student, employee, and ecommerce tables above (PK/FK on every relationship)
3. Seed 3+ rows per table with INSERT examples (INR prices on products)
4. DQL drills: Engineering employees; products under ₹100; students sorted by name
5. JOIN lab: INNER (employees + departments); LEFT (customers + orders, include a zero-order customer)
6. Normalize `bad_orders(order_id, customer_name, customer_city, product1, product2)` → sketch `customers`, `orders`, `order_items`, `products`
7. TCL lite: `START TRANSACTION` a bad price cut, `SELECT`, `ROLLBACK`, `SELECT` again
8. Sketch ER for Library **or** CampusCart (mini-project) — boxes + 1:N lines **before** extra CREATE

Annotated demo — CampusCart canteen report (after seed):

```
USE training_db;

-- 1) one more line item so the JOIN has something to show
INSERT INTO order_items (order_id, product_id, quantity)
VALUES (1, 1, 2);   -- 2 × Notebook for Meera's order

-- 2) report: who bought what (INNER JOIN chain)
SELECT
    c.name     AS customer,
    p.name     AS product,
    oi.quantity,
    p.price,
    (oi.quantity * p.price) AS line_total_inr
FROM orders o
INNER JOIN customers c   ON o.customer_id = c.customer_id
INNER JOIN order_items oi ON o.order_id = oi.order_id
INNER JOIN products p    ON oi.product_id = p.product_id;

-- 3) LEFT JOIN: customers who have not ordered yet stay visible
SELECT c.name, o.order_id
FROM customers c
LEFT JOIN orders o ON c.customer_id = o.customer_id;
```

Later — JDBC: the same SELECT will run from Java with `PreparedStatement` and `?` placeholders. Do not write that Java this week.

Practice Exercises

Basic

1. CREATE TABLE `courses` (course_id, title, credits); INSERT 5 rows; SELECT credits > 3.

Model answer:

```
CREATE TABLE IF NOT EXISTS courses (
  course_id INT PRIMARY KEY AUTO_INCREMENT,
  title VARCHAR(100) NOT NULL,
  credits INT NOT NULL
);
INSERT INTO courses (title, credits) VALUES
  ('Core Java', 4), ('MySQL', 3), ('OOP', 4), ('Collections', 3), ('Git', 2);
SELECT * FROM courses WHERE credits > 3;
```

2. UPDATE one title; DELETE one row by id.

Model answer:

```
UPDATE courses SET title = 'Core Java Lab' WHERE course_id = 1;
DELETE FROM courses WHERE course_id = 5;
```

3. List all departments alphabetically.

Model answer:

```
SELECT * FROM departments ORDER BY dept_name ASC;
```

Intermediate

1. Add `enrollments(student_id, course_id)`; INNER JOIN students + enrollments + courses.

Model answer:

```
CREATE TABLE IF NOT EXISTS enrollments (
  student_id INT,
  course_id INT,
  PRIMARY KEY (student_id, course_id),
  FOREIGN KEY (student_id) REFERENCES students(student_id),
  FOREIGN KEY (course_id) REFERENCES courses(course_id)
);
SELECT s.full_name, c.title
FROM students s
INNER JOIN enrollments e ON s.student_id = e.student_id
INNER JOIN courses c ON c.course_id = e.course_id;
```

2. LEFT JOIN — students with no enrollments.

Model answer:

```
SELECT s.student_id, s.full_name
FROM students s
LEFT JOIN enrollments e ON s.student_id = e.student_id
WHERE e.student_id IS NULL;
```

3. Employee report: dept_name, count, avg salary → see `MYSQL/04 Aggregations and Group By.md`.

Model answer:

```
SELECT d.dept_name, COUNT(e.emp_id) AS emp_count, AVG(e.salary) AS avg_salary
FROM departments d
LEFT JOIN employees e ON d.dept_id = e.dept_id
GROUP BY d.dept_name;
```

4. Fix denormalized `bad_library` table into 3NF.

Model answer:
Split repeating groups and transitive dependencies into separate tables such as `books(book_id, title, author_id)`, `authors(author_id, name)`, and `loans(loan_id, book_id, member_id, due_date)` so each non-key attribute depends only on the primary key.

Interview-style

1. INNER vs LEFT JOIN — write SQL showing NULL side.

Model answer:

```
-- INNER: only matching rows
SELECT * FROM students s INNER JOIN enrollments e ON s.student_id = e.student_id;
-- LEFT: keep all students; unmatched enrollment columns are NULL
SELECT s.full_name, e.course_id
FROM students s
LEFT JOIN enrollments e ON s.student_id = e.student_id;
```

2. When use TRANSACTION? (checkout, money transfer)

Model answer:
Use a transaction when multiple statements must succeed or fail together — e.g. debit one account and credit another, or place an order and decrement stock. `START TRANSACTION` … `COMMIT` / `ROLLBACK` protects consistency.

3. Design tables for CampusCart menu and daily orders.

Model answer:
Typical design: `menu_items(item_id, name, price, available)`, `orders(order_id, student_id, order_date, status)`, `order_items(order_id, item_id, qty, unit_price)` with FKs from `order_items` to `orders` and `menu_items`.

4. PRIMARY KEY vs UNIQUE — example.

Model answer:
PRIMARY KEY uniquely identifies a row and disallows NULL (e.g. `student_id`). UNIQUE enforces uniqueness on another column that may allow NULL depending on engine (e.g. `email UNIQUE`).

5. Why DECIMAL for price, not FLOAT?

Model answer:
FLOAT is binary approximate and can produce rounding errors in money. DECIMAL stores exact base-10 values, so INR totals and invoices stay accurate.

6. Why will Java use `PreparedStatement` instead of string-concat SQL? (idea only)

Model answer:
Placeholders (`?`) keep user input out of the SQL text, so a typed name cannot change the command. Concatenating `"'" + name + "'"` is how SQL injection starts. Syntax is **Later —** JDBC. This week: never build SQL by gluing strings, even in notes.

Mini-Project (Assignment): Schema Design (Library, TechMart / CampusCart, or AcmeHR)

SQL depth (source of truth): Weeks 10–11 · follow `MYSQL/` + the **Required MySQL labs** table in this module.

No Java lab kit this week. Kit `16_jdbc_library_crud` is reserved for JDBC (next module). MySQL seed practice stays in `MYSQL/`. Do not invent a second SQL textbook inside this file.

Option A — Library: members, books, copies, loans, fines
Option B — TechMart / CampusCart: users, vendors, products, orders, order_items
Option C — AcmeHR: department, employee, leave_record

What to build

- ER diagram (boxes + 1:N lines); DDL with PK/FK; 10+ INSERT rows; 3 queries with JOINs (overdue books **or** order history).

```
-- Sample CampusCart report query
SELECT u.full_name, o.order_id, p.name, oi.quantity
FROM orders o
JOIN users u ON o.user_id = u.user_id
JOIN order_items oi ON o.order_id = oi.order_id
JOIN products p ON oi.product_id = p.product_id
WHERE o.order_date >= '2026-07-01';
```

Work in MySQL Workbench / CLI. Commit the `.sql` script to your GitHub portfolio repo (Git week already taught `.gitignore` — still no `.env`). No JDBC. No Spring. No Lombok.

Stretch

- Add a fine/tax column with `DECIMAL(10,2)` and one aggregate report (`MYSQL/04_Aggregations_and_Group_By.md`).
- Write one `START TRANSACTION` … `COMMIT` checkout script (`MYSQL/09_Transactions_and_Indexes.md`).
- **Later — JDBC:** when Java INSERTs these rows, use `PreparedStatement` placeholders (`?`) — never string-concat SQL. Do not write that Java in this assignment.

Done when

- [ ] ER + DDL with PK/FK for chosen option (Library or CampusCart)
- [ ] Seed data (≥10 rows) + 3 JOIN queries run successfully
- [ ] You can point to the matching `MYSQL/` files you used for depth
- [ ] Required `MYSQL/` checklist rows for W10–W11 (this module) are ticked — JDBC row waits for the next module
- [ ] No `Connection` / `PreparedStatement` / Spring Boot / Lombok code in the deliverable

---

Bridge to Deep MySQL Modules

Need	File
Setup	`MYSQL/00_MySQL_Setup_and_Connection.md`
SQL basics	`MYSQL/02_Introduction_to_SQL_Basic_Concepts.md`
Querying	`MYSQL/03_Querying_with_SQL.md`
GROUP BY	`MYSQL/04_Aggregations_and_Group_By.md`
Keys, constraints	`MYSQL/05_Common_Concepts.md`
ER modeling	`MYSQL/06_Modeling_Databases.md`
All joins	`MYSQL/07_Joins.md`
Subqueries, views	`MYSQL/08_Views_and_Subqueries.md`
Transactions, indexes	`MYSQL/09_Transactions_and_Indexes.md`
Practice + projects	`MYSQL/homework/10_Practice_Exercises.md`, `MYSQL/12_Real_Time_Projects.md`

Java next: `07_JDBC/01_JDBC_CRUD.md` — `PreparedStatement` CRUD against **these** tables. No Spring Boot this week.

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

Q1. What is a relational database?

A: Data in tables with rows/columns linked by keys. MySQL is an open-source RDBMS. The Java backend (JDBC, later JPA) reads and writes those tables.

Q2. INNER JOIN vs LEFT JOIN?

A: INNER = matching rows only. LEFT = all left rows + matches, or NULL on the right when there is no match (e.g. **TechMart** customers with no orders; **AcmeHR** employees with no leave rows).

Q3. What is normalization? Why 3NF?

A: Normalization reduces redundancy. 3NF removes transitive dependencies (store `dept_head` on `departments`, not on every student) so one fact is updated in one place.

Q4. DELETE vs DROP?

A: DELETE removes rows (DML). DROP removes the table structure (DDL). `DELETE FROM t` with no WHERE can empty the table; DROP loses the table itself.

Q5. Where does MySQL sit in a Java full stack?

A: Persistent storage. Browser / Postman → Java API → SQL against MySQL. The frontend never issues SQL.

Q6. Why not keep CampusCart in an `ArrayList` or a CSV after File Handling week?

A: RAM dies when `main` ends. A CSV lives on one laptop, has no PK/FK, and cannot safely share concurrent **TechMart** / CampusCart orders. MySQL is the shared source of truth.

Q7. PRIMARY KEY vs UNIQUE?

A: PK identifies the row and disallows NULL (`student_id`). UNIQUE enforces uniqueness on another column (`email`) and may allow NULL depending on engine.

Q8. Why DECIMAL for price, not FLOAT?

A: FLOAT is approximate binary. DECIMAL stores exact base-10 INR amounts, so invoice totals do not drift.

Q9. When do you use a TRANSACTION?

A: When several statements must succeed or fail together — **SecureBank** money transfer, **TechMart** checkout + stock decrement. `START TRANSACTION` … `COMMIT` / `ROLLBACK`.

Q10. What does a foreign key actually do?

A: It is a database-enforced pointer: `orders.customer_id` must match an existing `customers.customer_id`. Orphan orders are rejected. Think of it as a hyperlink between tables, with rules.

Q11. Why will JDBC use `PreparedStatement` instead of string-concat SQL?

A: Placeholders (`?`) separate commands from data, which blocks SQL injection from typed names. Concatenating quotes into SQL is unsafe. The Java syntax is the **next** module — the idea is this week's exit ticket.

Q12. Is normalization always good? When might teams denormalize?

A: 3NF is the default for OLTP (**TechMart** / CampusCart orders). Teams sometimes denormalize read-heavy reports (copy a product name onto `order_items`) to avoid JOINs — that is a measured trade-off, not a first design.
