Module 09 — REST, DTOs, and Postman

Phase: Backend (JSON contract)
Previous module: Spring Data JPA and Validation
Next module: Spring Security Lite
Lab kit: 15_Lab_Assets/18_jpa_product_crud/

Learning Outcomes

By the end of this module, learners will be able to:

1. Keep **`Product` as the persistence class** and send **JSON as DTOs** — the table shape is not the API shape.
2. Write **`ProductRequest`** / **`ProductResponse`** and **map by hand** (getters / setters). MapStruct is not required.
3. Put **`spring-boot-starter-validation`** on the pom and run **`@Valid`** on **POST** with **`@NotBlank`**, **`@NotNull`**, and lite **`@Size` / `@Min`**.
4. Return a **lite 400 JSON body** (`error` + `fields`) with **`@RestControllerAdvice`** (or **`@ControllerAdvice`**) for validation failures — keep **404** from the previous modules.
5. Import and run a **Postman collection v1** (committed `.postman_collection.json`) for list / get / create / 400 / 404.
6. Name **CORS** as a **browser** rule and allow **Vite** **`http://localhost:5173`** in **dev lite** — production origins and React `fetch` wiring are **Later —**.

Teaching note: Module 03 already persists CampusCart snacks in MySQL (`@Entity`, `JpaRepository`, lab `ddl-auto=update`). **Do not rewrite that path.** Today the JSON **stops being the entity**. Module 03's lite `@Valid` peek sat on the entity and left Boot's default 400 ugly — that depth is **this** module, on the **request DTO**. No Spring Security / JWT. No MapStruct. No Lombok on the core path. No kit 19. **Later —** React weeks consume this same API; this file only recaps **CORS lite**.

Teach order today: entity-as-JSON pain → request / response DTOs + manual map → `starter-validation` + `@Valid` on POST → lite 400 advice → Postman collection v1 → CORS recap (Vite `:5173` → `:8080`).

Prerequisites

- **CampusCart JPA catalog** from Spring Data JPA and Validation — `Product` entity, `JpaRepository`, GET list / GET by id / POST, MySQL, env secrets. JDK 17 + Maven 3.9+ + Spring Boot 3.x (Tested Toolchain).
- **Postman** installed (same toolchain table). `curl` from module 02 still works; the collection is the new habit.

Definition / Purpose

Definition: A **DTO** (Data Transfer Object) is a class used **only for JSON in or JSON out**. It is **not** an `@Entity`. **`ProductRequest`** is the POST body (no id). **`ProductResponse`** is what clients read (id from MySQL). You **copy fields** in Java — that copy is **manual mapping**.

Definition: **`@Valid`** on **`@RequestBody`** runs **Bean Validation** (`jakarta.validation`) **before** the method body. **`@RestControllerAdvice`** catches **`MethodArgumentNotValidException`** and returns a **small 400 JSON** instead of Boot's default dump.

Definition: Postman is an HTTP client with **saved requests**. A **collection** is a JSON file of those requests (and lite tests) that you **commit** so the batch shares the same checks.

Definition: CORS (Cross-Origin Resource Sharing) is a **browser** rule: a page on one origin (`http://localhost:5173`) may not read JSON from another (`http://localhost:8080`) unless the API **allows** that origin.


Purpose: Priya's POST `{"id":99,"name":"Idli"}` must not pick the primary key. Ravi's React app (Later —) must not see Hibernate extras. Blank name must not become a row. QA must replay GET / POST without screenshots. Vite on **5173** must be allowed **in lab** before React weeks.

Bank Order Laptop Employee UPI

Where used?

- CampusCart — catalog JSON that is **not** the `campus_products` row
- Canteen / mess — POST body without id; GET with id from MySQL
- Banking / UPI — APIs hide ledger columns (**no money movement here**)
- Hospital — token APIs omit internal flags
- Postman / QA — same collection on every laptop

Visual — JSON is not the table:



Key takeaways:

- **Entity** = persistence. **DTO** = JSON contract
- Map **by hand** this module — MapStruct is not required
- `@Valid` on the **request DTO**, not as the only guard on the table class
- **400** from advice; **404** stays on GET by id
- Commit a `.postman_collection.json`, not only screenshots
- CORS is for the **browser**; curl / Postman do not show it

Motivation — Feel the pain of entity-as-JSON

Ravi POSTed `{"id":1,"name":"","priceInr":30}`. Hibernate treated the id like an update. The blank name became a row. Boot's 400 JSON filled the screen with `trace`. Priya had no Postman file to share — only a screenshot of 201.

```
public class EntityAsJsonPain {
    public static void main(String[] args) {
        System.out.println("POST body included id -> looked like UPDATE");
        System.out.println("Blank name became a campus_products row");
        System.out.println("Need DTO + @Valid + small 400 JSON");
    }
}
```

Expected Output:

```
POST body included id -> looked like UPDATE
Blank name became a campus_products row
Need DTO + @Valid + small 400 JSON
```

Remember: Module 03 practised **MySQL persist**. This module practises the **JSON contract** on that same catalog.

Interview: "Why not return the entity?" — Fine for a spike. Production APIs hide columns, block client ids, and validate the **request** type.

Important Concepts

1. Entity vs DTO — JSON is not the table

Definition: The `Product` `@Entity` maps to `campus_products`. Jackson will serialize **every getter** it can see. A **DTO** is a **second** class with **only** the fields the client may send or see.

Purpose: Without a split, POST can send `id`, and later a `costPrice` column would leak on GET. Interviews expect "entity stays persistence; DTO stays JSON."

Module 03 returned `Product` on purpose so HTTP + JPA could land first. **Today you contrast that** — do **not** redo `@Entity` / `JpaRepository` / Hikari / `ddl-auto`.

	Entity (`Product`)	Request DTO	Response DTO
Job	Row in MySQL	POST JSON in	JSON out
id	`@Id` generated	**omit**	from MySQL
Annotations	`jakarta.persistence`	`jakarta.validation`	none required
Client may send it?	Do not	Yes	No (you build it)

Copy-paste valid (Maven tree — not lone `javac`):

```
package in.ksr.campuscatalog;

public class ProductResponse {

    private Long id;
    private String name;
    private int priceInr;

    public ProductResponse() {
    }

    public ProductResponse(Long id, String name, int priceInr) {
        this.id = id;
        this.name = name;
        this.priceInr = priceInr;
    }
```

```
    public Long getId() {
        return id;
    }

    public void setId(Long id) {
        this.id = id;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public int getPriceInr() {
        return priceInr;
    }

    public void setPriceInr(int priceInr) {
        this.priceInr = priceInr;
    }
}
```

Note:
- Wrong: one class with both `@Entity` and the only `@NotBlank` — HTTP rules stuck to the table.
- Wrong: putting `id` on `ProductRequest` "so Postman can set it."
- Prefer: entity for Hibernate; DTOs for Jackson.

Common Error: Adding `@Table` on the DTO "so it matches." DTOs are not tables.

Remember: Happy-path JSON may still look like `{id, name, priceInr}`. The win is **POST has no id** and **validation lives on the request**.

Interview: DTO? Data Transfer Object — a type for the wire, not the database.

Try these (2 programs):

Program 1 — JSON is not the table

```
public class JsonIsNotTheTable {
    public static void main(String[] args) {
        System.out.println("Entity: campus_products columns");
        System.out.println("Request JSON: name + priceInr, no id");
        System.out.println("Response JSON: id from MySQL");
    }
}
```

Expected Output:

```
Entity: campus_products columns
Request JSON: name + priceInr, no id
Response JSON: id from MySQL
```

Program 2 — Client id is a trap

```
public class ClientIdTrap {
    public static void main(String[] args) {
        System.out.println("POST {\"id\":1,\"name\":\"Idli\"}");
        System.out.println("Entity as body: save may UPDATE id 1");
        System.out.println("Request DTO: no id field to bind");
    }
}
```

Expected Output:

```
POST {"id":1,"name":"Idli"}
Entity as body: save may UPDATE id 1
Request DTO: no id field to bind
```

---

2. Manual mapping — request in, entity, response out

Definition: Mapping copies `name` and `priceInr` from **`ProductRequest`** onto a **`Product`**, then copies `id` / `name` / `priceInr` onto **`ProductResponse`**. You write the getters. **MapStruct** is a code generator for this — **not** required.

Purpose: Without an explicit copy, juniors `save` the request object and wonder why `@Entity` is missing. A small **`ProductMapper`** with static methods keeps the controller readable.

```
package in.ksr.campuscatalog;

public class ProductMapper {

    private ProductMapper() {
    }

    public static Product toEntity(ProductRequest request) {
        Product product = new Product();
        product.setId(null);
        product.setName(request.getName());
        product.setPriceInr(request.getPriceInr());
        return product;
    }

    public static ProductResponse toResponse(Product product) {
        return new ProductResponse(
                product.getId(), product.getName(), product.getPriceInr());
    }
}
```

Controller sketch (same mappings as module 03 — **store is still the repository**):

```
@GetMapping
public List<ProductResponse> list() {
    List<ProductResponse> body = new ArrayList<>();
    for (Product row : products.findAll()) {
        body.add(ProductMapper.toResponse(row));
    }
    return body;
}
```

```
@PostMapping
@ResponseStatus(HttpStatus.CREATED)
public ProductResponse add(@Valid @RequestBody ProductRequest incoming) {
    Product saved = products.save(ProductMapper.toEntity(incoming));
    return ProductMapper.toResponse(saved);
}
```

`setId(null)` is the same INSERT habit as module 03 — now the request type **cannot** carry an id.

Note:
- Wrong: `products.save(incoming)` when `incoming` is a DTO.
- Wrong: requiring MapStruct / Lombok to pass.
- Prefer: a for-each on `findAll()` — streams are optional Stretch.

Remember: Mapping is boring on purpose. Boring copies do not leak columns.

Interview: "Who maps?" — You, in Java. Libraries are optional later.

Try these (2 programs):

Program 1 — Three steps of a POST

```
public class PostThreeSteps {
    public static void main(String[] args) {
        System.out.println("1 JSON -> ProductRequest");
        System.out.println("2 Request -> Product entity, id null");
        System.out.println("3 save -> ProductResponse");
    }
}
```

Expected Output:

```
1 JSON -> ProductRequest
2 Request -> Product entity, id null
3 save -> ProductResponse
```

Program 2 — GET list still uses findAll

```
public class ListStillFindAll {
    public static void main(String[] args) {
        System.out.println("findAll() still loads rows");
        System.out.println("loop maps each Product to ProductResponse");
        System.out.println("MySQL store — not ArrayList");
    }
}
```

Expected Output:

```
findAll() still loads rows
loop maps each Product to ProductResponse
MySQL store — not ArrayList
```

3. `@Valid` on the request DTO

Definition: `spring-boot-starter-validation` brings **Hibernate Validator**. Field annotations describe rules. `@Valid` on `@RequestBody ProductRequest` runs them. Imports are `jakarta.validation.Valid` and `jakarta.validation.constraints.*` (not `javax`).

Purpose: Module 03 named `@Valid` on the **entity** as a peek. **Today the annotations sit on `ProductRequest`.** Empty name / missing price never call `save`.

Pom (next to `starter-web` / `starter-data-jpa`):

```
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-validation</artifactId>
</dependency>
```

On the request (wrapper `Integer` so `@NotNull` can see a missing JSON field):

```
package in.ksr.campuscatalog;

import jakarta.validation.constraints.Min;
import jakarta.validation.constraints.NotBlank;
import jakarta.validation.constraints.NotNull;
import jakarta.validation.constraints.Size;

public class ProductRequest {

    @NotBlank
    @Size(max = 80)
    private String name;

    @NotNull
    @Min(1)
    private Integer priceInr;

    public ProductRequest() {
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public Integer getPriceInr() {
        return priceInr;
    }

    public void setPriceInr(Integer priceInr) {
        this.priceInr = priceInr;
    }
}
```

On POST:

```
@PostMapping
@ResponseStatus(HttpStatus.CREATED)
```

```
public ProductResponse add(@Valid @RequestBody ProductRequest incoming) {
    Product saved = products.save(ProductMapper.toEntity(incoming));
    return ProductMapper.toResponse(saved);
}
```

Annotation	Catches
`@NotBlank`	null, `""`, `"   "` on name
`@Size(max = 80)`	very long name (lite)
`@NotNull`	missing `priceInr` on **`Integer`**
`@Min(1)`	`0` or negative

Note:
- Wrong: `@NotNull` on primitive `int` — JSON omit becomes `0`; null never happens.
- Wrong: `@Valid` without `starter-validation` — checks do not run.
- Prefer: `@NotBlank` over `@NotEmpty` for names (whitespace is not a snack name).

Common Error: Leaving `@NotBlank` only on `Product` from the module 03 Stretch. Move (or copy) rules onto **`ProductRequest`**.

Remember: `@Valid` does nothing if you forget it on the parameter — annotations on a class are idle until something **runs** them.

Interview: Bean Validation is the **standard**. Hibernate Validator is the **engine** on the classpath (same idea as Hibernate for JPA).

Try these (2 programs):

Program 1 — What @Valid checks

```
public class ValidChecksPrint {
    public static void main(String[] args) {
        System.out.println("@NotBlank + @Size on name");
        System.out.println("@NotNull + @Min(1) on Integer priceInr");
        System.out.println("@Valid on POST ProductRequest");
    }
}
```

Expected Output:

```
@NotBlank + @Size on name
@NotNull + @Min(1) on Integer priceInr
@Valid on POST ProductRequest
```

Program 2 — Wrapper vs primitive

```
public class WrapperForNotNull {
    public static void main(String[] args) {
        System.out.println("Integer + @NotNull catches missing price");
        System.out.println("int cannot be null — omit becomes 0");
```

```
        System.out.println("Entity may still use int after mapping");
    }
}
```

Expected Output:

```
Integer + @NotNull catches missing price
int cannot be null — omit becomes 0
Entity may still use int after mapping
```

---

4. Lite error body — advice for 400, keep 404

Definition: `@RestControllerAdvice` is a class Spring asks when a controller throws. For `MethodArgumentNotValidException` (failed `@Valid`), you return **400** and a **small JSON map**. `@ControllerAdvice` plus a JSON return type is the same family.

Purpose: Default Boot 400 is huge (`timestamp`, `trace`, …). Priya's frontend (Later —) needs `error` and `fields`. GET missing id stays **404** in the **controller** — same as modules 02 / 03.

```
package in.ksr.campuscatalog;

import java.util.LinkedHashMap;
import java.util.Map;
import org.springframework.http.ResponseEntity;
import org.springframework.validation.FieldError;
import org.springframework.web.bind.MethodArgumentNotValidException;
import org.springframework.web.bind.annotation.ExceptionHandler;
import org.springframework.web.bind.annotation.RestControllerAdvice;

@RestControllerAdvice
public class ApiExceptionHandler {

    @ExceptionHandler(MethodArgumentNotValidException.class)
    public ResponseEntity<Map<String, Object>> handleValidation(
            MethodArgumentNotValidException ex) {
        Map<String, String> fields = new LinkedHashMap<>();
        for (FieldError err : ex.getBindingResult().getFieldErrors()) {
            String message = err.getDefaultMessage();
            if (message == null) {
                message = "invalid";
            }
            fields.put(err.getField(), message);
        }
        Map<String, Object> body = new LinkedHashMap<>();
        body.put("error", "Validation failed");
        body.put("fields", fields);
        return ResponseEntity.badRequest().body(body);
    }
}
```

Sample 400 (message text can vary slightly by validator version):

```
{"error":"Validation failed","fields":{"name":"must not be blank"}}
```

404 stays here (do **not** move it into advice this module):

```
@GetMapping("/{id}")
public ResponseEntity<?> getById(@PathVariable Long id) {
    Product found = products.findById(id).orElse(null);
    if (found != null) {
        return ResponseEntity.ok(ProductMapper.toResponse(found));
    }
    return ResponseEntity.status(HttpStatus.NOT_FOUND)
            .body(Map.of("error", "No product " + id));
}
```

Status	When	Who
200	GET list / GET found	controller
201	POST valid	controller
400	POST fails `@Valid`	**advice**
404	GET unknown id	**controller** (keep)

Note:
- Wrong: catching 404 in advice “to be consistent” — out of window; keep the known pattern.
- Wrong: returning 200 with `"error"` inside a 200 body.
- Prefer: `LinkedHashMap` so `error` then `fields` stay stable in demos.

Common Error: Advice class in the wrong package outside `@SpringBootApplication` scan — handler never runs; you still see the default 400.

Remember: 400 = bad **body**. 404 = unknown **id**. Do not mix them.

Interview: `@ControllerAdvice` is global exception handling for controllers. `@RestControllerAdvice` = advice + JSON `@ResponseBody`.

Try these (2 programs):

Program 1 — 400 keys

```
public class ErrorBodyKeys {
    public static void main(String[] args) {
        System.out.println("status 400");
        System.out.println("error");
        System.out.println("fields");
    }
}
```

Expected Output:

```
status 400
error
fields
```

Program 2 — 404 stays in the controller

```
public class NotFoundStays {
    public static void main(String[] args) {
        System.out.println("GET /products/99 -> 404");
        System.out.println("handler: ProductController.getById");
        System.out.println("advice this module: validation 400 only");
    }
}
```

Expected Output:

```
GET /products/99 -> 404
handler: ProductController.getById
advice this module: validation 400 only
```

---

5. Postman collection v1

Definition: A **Postman collection** is a **JSON file** of named HTTP requests (URL, method, headers, body) plus optional **Tests** (assertions on status / JSON). You **Import** it. You **commit** `CampusCart_Products_v1.postman_collection.json` in the kit — screenshots are not the source of truth.

Purpose: `curl` proved HTTP in module 02. A collection lets Priya's laptop and Ravi's laptop run the **same** list / create / 400 / 404 without retyping JSON.

Kit file: CampusCart_Products_v1.postman_collection.json

Request	Expect
GET `{{baseUrl}}/products`	200 array
POST create Pani puri	201 + `id`
GET `{{baseUrl}}/products/{{productId}}`	200
GET missing `99999`	404
POST `name: ""`	400 + `error` / `fields`

Workflow:

1. Start the Boot app (`mvn spring-boot:run`) with MySQL env set.
2. Postman → **Import** → the kit `.postman_collection.json`.
3. Collection variable **`baseUrl`** = `http://localhost:8080`.
4. Send **Create product** before **Get product by id** if the table is empty (or run kit seed).
5. POST bodies: **Body** → **raw** → **JSON**. That sets `Content-Type: application/json`.

Note:
- Wrong: screenshot-only "proof" — the batch cannot import a PNG.
- Wrong: POST with form-data — Jackson wants JSON, not a multipart form.
- Prefer: Tests tab `pm.response.to.have.status(201)` so a red test is a failed ticket.

Common Error: Forgetting `Content-Type: application/json` → 415 or an empty body. Use **raw JSON**.

Remember: Postman is **not** a browser. It will **not** fail CORS. That is the next topic.

Interview: Why Postman before React? You prove the API contract without a UI. QA and teammates import the same file.

Try these (2 programs):

Program 1 — Collection checklist

```
public class CollectionFiveCalls {
    public static void main(String[] args) {
        System.out.println("GET list 200");
        System.out.println("POST create 201");
        System.out.println("GET by id 200");
        System.out.println("GET missing 404");
        System.out.println("POST blank name 400");
    }
}
```

Expected Output:

```
GET list 200
POST create 201
GET by id 200
GET missing 404
POST blank name 400
```

Program 2 — Header on POST

```
public class PostmanJsonHeader {
    public static void main(String[] args) {
        System.out.println("Body raw JSON");
        System.out.println("Content-Type: application/json");
        System.out.println("baseUrl http://localhost:8080");
    }
}
```

Expected Output:

```
Body raw JSON
Content-Type: application/json
baseUrl http://localhost:8080
```

---

6. CORS lite — Vite `:5173` → `:8080` (recap)

Definition: An **origin** is **scheme + host + port**. `http://localhost:5173` and `http://localhost:8080` are **different**. The **browser** blocks the JS app from reading the API unless the API sends **`Access-Control-Allow-Origin`**. **`@CrossOrigin(origins = "http://localhost:5173")`** on the controller (or a small `WebMvcConfigurer`) is **dev lite**.

Purpose: Postman already works. **Later —** React on Vite calls this catalog. If CORS is missing, the **browser console** shows a CORS error and `fetch` looks “broken” while curl is fine. This recap lives **in these notes** so the API is ready. **Do not rewrite React chapters.** Production allow-lists are **Later —**.

```
import org.springframework.web.bind.annotation.CrossOrigin;

@CrossOrigin(origins = "http://localhost:5173")
@RestController
@RequestMapping("/products")
public class ProductController {
    // same GET / POST as before
}
```

Config equivalent (one place for many controllers):

```
package in.ksr.campuscatalog;

import org.springframework.context.annotation.Configuration;
import org.springframework.web.servlet.config.annotation.CorsRegistry;
import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;

@Configuration
public class CorsConfig implements WebMvcConfigurer {

    @Override
    public void addCorsMappings(CorsRegistry registry) {
        registry.addMapping("/**")
                .allowedOrigins("http://localhost:5173")
                .allowedMethods("GET", "POST", "OPTIONS");
    }
}
```

Note:
- Wrong: “Postman failed CORS.” Postman is not a browser.
- Wrong: `allowedOrigins("*")` as the production habit — lab `*` is a trap.
- Prefer: exact `http://localhost:5173` in class. **Later —** real HTTPS origins.

Common Error: Allowing `localhost:5173` without `http://` — the origin string must match.

Remember: CORS is **not** Spring Security. Login / JWT is the **next** module.

Interview: Why does curl work and the React app not? curl skips the browser SOP / CORS check. The API must opt in for the page’s origin.

Try these (2 programs):

Program 1 — Two origins

```
public class ViteOriginPrint {
    public static void main(String[] args) {
        System.out.println("Vite page:  http://localhost:5173");
        System.out.println("Boot API:   http://localhost:8080");
        System.out.println("@CrossOrigin origins = http://localhost:5173");
```

```
    }
}
```

Expected Output:

```
Vite page:  http://localhost:5173
Boot API:   http://localhost:8080
@CrossOrigin origins = http://localhost:5173
```

Program 2 — What stays Later

```
public class CorsLaterPrint {
    public static void main(String[] args) {
        System.out.println("Later — React fetch / useEffect");
        System.out.println("Later — production allowed origins");
        System.out.println("Later — Spring Security CORS");
    }
}
```

Expected Output:

```
Later — React fetch / useEffect
Later — production allowed origins
Later — Spring Security CORS
```

Step-by-Step Annotated Java Code

Work in lab kit **18_jpa_product_crud** (`starter/`). JDK 17. Open the folder that contains `pom.xml`. MySQL 8+ must be running. Export env from `.env.example`. Persistence (`Product`, `ProductRepository`, `ddl-auto=update`, secrets) is **already taught** — complete those TODOs if they are still open, then add DTOs.

Step 1: Persistence base still answers HTTP

Keep GET `/products`, GET `/products/{id}`, POST `/products` against **MySQL**. If list still returns `List.of()`, finish the JPA TODOs first (previous module). Prove with curl:

```
export MYSQL_PASSWORD='your_lab_password'
cd starter
mvn spring-boot:run
```

```
curl http://localhost:8080/products
```

Try these (2 programs):

Program 1 — Store has not changed

```
public class StoreStillMysql {
    public static void main(String[] args) {
        System.out.println("JpaRepository findAll / findById / save");
        System.out.println("Table campus_products");
        System.out.println("Not ArrayList");
```

```
    }
}
```

Expected Output:

```
JpaRepository findAll / findById / save
Table campus_products
Not ArrayList
```

Program 2 — Same three URLs

```
public class SameThreeUrls {
    public static void main(String[] args) {
        System.out.println("GET /products");
        System.out.println("GET /products/{id}");
        System.out.println("POST /products");
    }
}
```

Expected Output:

```
GET /products
GET /products/{id}
POST /products
```

Step 2: Add `ProductRequest` and `ProductResponse`

Create the two DTO classes (starter stubs). **No** `@Entity`. Request: `name` + `Integer priceInr`. Response: `id`, `name`, `priceInr`. Getters / setters + no-arg constructor.

Try these (2 programs):

Program 1 — Request fields

```
public class RequestFieldsPrint {
    public static void main(String[] args) {
        System.out.println("name");
        System.out.println("priceInr");
        System.out.println("no id");
    }
}
```

Expected Output:

```
name
priceInr
no id
```

Program 2 — Response fields

```
public class ResponseFieldsPrint {
    public static void main(String[] args) {
        System.out.println("id");
        System.out.println("name");
```

```
        System.out.println("priceInr");
    }
}
```

Expected Output:

```
id
name
priceInr
```

Step 3: Mapper + controller returns DTOs

Fill `ProductMapper.toEntity` / `toResponse`. Switch list / get / add to **`ProductResponse`**. POST parameter becomes **`ProductRequest`**. `save` still takes a **`Product`**.

Try these (2 programs):

Program 1 — save takes the entity

```
public class SaveTakesEntity {
    public static void main(String[] args) {
        System.out.println("products.save(Product)");
        System.out.println("not products.save(ProductRequest)");
    }
}
```

Expected Output:

```
products.save(Product)
not products.save(ProductRequest)
```

Program 2 — POST still 201

```
public class PostStill201 {
    public static void main(String[] args) {
        System.out.println("@ResponseStatus CREATED");
        System.out.println("body is ProductResponse");
        System.out.println("id from AUTO_INCREMENT");
    }
}
```

Expected Output:

```
@ResponseStatus CREATED
body is ProductResponse
id from AUTO_INCREMENT
```

Step 4: Validation starter + `@Valid`

Add **`spring-boot-starter-validation`** if the pom still lacks it (starter tree already lists it; **broken** does not). Annotate `ProductRequest`. Put **`@Valid`** on POST.

```
curl -X POST http://localhost:8080/products \
  -H "Content-Type: application/json" \
  -d '{"name":"","priceInr":30}'
```

Without advice you still get **400** (ugly). Next step shapes the body.

Try these (2 programs):

Program 1 — Dependency artifact

```
public class ValidationStarterName {
    public static void main(String[] args) {
        System.out.println("spring-boot-starter-validation");
        System.out.println("jakarta.validation.Valid");
        System.out.println("jakarta.validation.constraints");
    }
}
```

Expected Output:

```
spring-boot-starter-validation
jakarta.validation.Valid
jakarta.validation.constraints
```

Program 2 — TechMart blank name must not INSERT

```
public class BlankNameNoInsert {
    public static void main(String[] args) {
        System.out.println("POST name empty");
        System.out.println("400 before save");
        System.out.println("campus_products row count unchanged");
    }
}
```

Expected Output:

```
POST name empty
400 before save
campus_products row count unchanged
```

Step 5: `ApiExceptionHandler` 400 body

Implement `@RestControllerAdvice` as in the concept block. Re-send blank name. Body must include **`error`** and **`fields`**. GET `/products/99999` still **404**.

Try these (2 programs):

Program 1 — Exception type

```
public class ValidExceptionName {
    public static void main(String[] args) {
        System.out.println("MethodArgumentNotValidException");
        System.out.println("@ExceptionHandler");
        System.out.println("400 bad request");
```

```
    }
}
```

Expected Output:

```
MethodArgumentNotValidException
@ExceptionHandler
400 bad request
```

Program 2 — Curl invalid POST

```
public class CurlInvalidPost {
    public static void main(String[] args) {
        System.out.println("curl -X POST ... {\"name\":\"\",\"priceInr\":30}");
        System.out.println("expect 400");
        System.out.println("JSON keys error and fields");
    }
}
```

Expected Output:

```
curl -X POST ... {"name":"","priceInr":30}
expect 400
JSON keys error and fields
```

Step 6: Import Postman collection v1

Import CampusCart_Products_v1.postman_collection.json. Run the five requests. Green tests = ticket path. Commit the **file**; do not replace it with a screenshot.

Try these (2 programs):

Program 1 — Import path

```
public class CollectionFileName {
    public static void main(String[] args) {
        System.out.println("CampusCart_Products_v1.postman_collection.json");
        System.out.println("kit 18 root");
        System.out.println("Import in Postman");
    }
}
```

Expected Output:

```
CampusCart_Products_v1.postman_collection.json
kit 18 root
Import in Postman
```

Program 2 — Postman vs curl

```
public class PostmanVsCurl {
    public static void main(String[] args) {
        System.out.println("curl: typed in terminal");
        System.out.println("collection: shared JSON file");
```

```
        System.out.println("both hit the same Boot API");
    }
}
```

Expected Output:

```
curl: typed in terminal
collection: shared JSON file
both hit the same Boot API
```

Step 7: CORS recap + git hygiene

Optional for Done when: `@CrossOrigin(origins = "http://localhost:5173")` on `ProductController` (Stretch). Restart still shows POST rows. `git status` must not list `.env` or `target/`. README: JDK 17, Boot 3, env, `mvn spring-boot:run`, curl **and** Postman import.

Do **not** add Security / JWT / MapStruct / Lombok to pass.

Try these (2 programs):

Program 1 — Dev origin string

```
public class DevOriginString {
    public static void main(String[] args) {
        System.out.println("http://localhost:5173");
        System.out.println("not required to pass Done when");
    }
}
```

Expected Output:

```
http://localhost:5173
not required to pass Done when
```

Program 2 — Git hygiene

```
public class GitHygieneDto {
    public static void main(String[] args) {
        System.out.println("commit collection json");
        System.out.println("do not commit .env");
        System.out.println("do not commit target/");
    }
}
```

Expected Output:

```
commit collection json
do not commit .env
do not commit target/
```

Practice Exercises

(Each Practice item includes a filled Model answer: and Expected Output: where the demo prints.)

Basic

1. Print entity vs request vs response in three lines.

Model answer:

```
public class ThreeShapesPrint {
    public static void main(String[] args) {
        System.out.println("Entity: table row");
        System.out.println("Request: POST JSON, no id");
        System.out.println("Response: GET/POST JSON, id from MySQL");
    }
}
```

Expected Output:

```
Entity: table row
Request: POST JSON, no id
Response: GET/POST JSON, id from MySQL
```

2. Print the two validation annotations on name and price.

Model answer:

```
public class TwoPairAnnotations {
    public static void main(String[] args) {
        System.out.println("name: @NotBlank @Size");
        System.out.println("priceInr: @NotNull @Min");
    }
}
```

Expected Output:

```
name: @NotBlank @Size
priceInr: @NotNull @Min
```

3. Print the Postman POST header.

Model answer:

```
public class PostmanHeaderLine {
    public static void main(String[] args) {
        System.out.println("Content-Type: application/json");
    }
}
```

Expected Output:

```
Content-Type: application/json
```

Intermediate

1. Why `Integer` on the request and `int` on the entity is OK.

Model answer:

```
public class IntegerThenInt {
    public static void main(String[] args) {
        System.out.println("Request Integer: @NotNull can fail");
        System.out.println("After @Valid, value is present");
        System.out.println("Entity int: column price_inr");
    }
}
```

Expected Output:

```
Request Integer: @NotNull can fail
After @Valid, value is present
Entity int: column price_inr
```

2. Sketch the 400 JSON keys.

Model answer:

```
public class FourHundredSketch {
    public static void main(String[] args) {
        System.out.println("error: Validation failed");
        System.out.println("fields: name -> must not be blank");
    }
}
```

Expected Output:

```
error: Validation failed
fields: name -> must not be blank
```

3. Why MapStruct is not on the ticket.

Model answer:

```
public class NoMapStructRequired {
    public static void main(String[] args) {
        System.out.println("Manual getters are enough");
        System.out.println("MapStruct is extra tooling");
        System.out.println("Not Done when");
    }
}
```

Expected Output:

```
Manual getters are enough
MapStruct is extra tooling
Not Done when
```

4. Why Postman does not prove CORS.

Model answer:

```
public class PostmanNotCors {
    public static void main(String[] args) {
        System.out.println("Postman is not a browser");
        System.out.println("CORS is a browser check");
        System.out.println("curl is also not a browser");
    }
}
```

Expected Output:

```
Postman is not a browser
CORS is a browser check
curl is also not a browser
```

Interview-Oriented

1. Entity vs DTO — one sentence each?

Model answer: An entity is the JPA class mapped to a table. A DTO is a JSON in/out class that you map to and from the entity by hand.

2. Why omit `id` on `ProductRequest`?

Model answer: The database assigns `AUTO_INCREMENT` on INSERT. A client id on POST can look like an UPDATE (`save` with a non-null id). The request type simply has no id field.

3. `@Valid` on the entity vs on the DTO?

Model answer: Module 03 peeked `@Valid` on the entity. The API contract belongs on the request DTO so persistence annotations and HTTP rules stay apart.

4. What exception does failed `@Valid` on `@RequestBody` throw?

Model answer: `MethodArgumentNotValidException`. Handle it in `@RestControllerAdvice` / `@ControllerAdvice` for a 400 body.

5. Is CORS required to pass this assignment?

Model answer: No. Done when is DTO + `@Valid` + lite 400 + Postman v1 on the JPA catalog. `@CrossOrigin` for Vite `:5173` is Stretch. React `fetch` is **Later —**.

6. Does this module replace JPA?

Model answer: No. Same `Product` + `JpaRepository` + MySQL. Only the JSON types and validation / error JSON are new.

Mini-Project (Assignment): CampusCart Catalog DTOs and Postman v1

Lab kit: 15_Lab_Assets/18_jpa_product_crud/

Module 03 persisted the catalog. This assignment is the **portfolio JSON contract**: **DTOs**, **`@Valid` on POST**, a **lite 400 body**, and **Postman collection v1**, still on **MySQL**. Push a public repo. No secrets in git.

Do **not** add Security / JWT, MapStruct, or Lombok to pass. CORS is Stretch.

What to build

Piece	Detail
Persistence	Keep `Product` `@Entity`, `ProductRepository`, GET list / get / POST **save** on MySQL (kit 18 base)
`pom.xml`	Existing Boot 3 starters **plus** `spring-boot-starter-validation`
`ProductRequest`	`name`, `Integer priceInr`; `@NotBlank` / `@Size`; `@NotNull` / `@Min(1)`; **no id**
`ProductResponse`	`id`, `name`, `priceInr` — no JPA annotations
Mapper	Manual `toEntity` / `toResponse` (`ProductMapper`)
GET list	**GET** `/products` → JSON **array** of `ProductResponse`
GET by id	**200** `ProductResponse` or **404** (same 404 idea as before)
POST	`@Valid @RequestBody ProductRequest` → **201** `ProductResponse`
Advice	**400** JSON with `error` + `fields`
Postman	Commit / import `CampusCart_Products_v1.postman_collection.json`
Secrets	Unchanged: env / `.env.example`, no password in git

Sample POST 201:

```
{"id":4,"name":"Pani puri","priceInr":30}
```

Sample POST 400:

```
{"error":"Validation failed","fields":{"name":"must not be blank"}}
```

Work from `starter/` (TODOs) or `broken/` (debug). Compare `solution/` only after you finish (or when told in class). `solution/` is trainer-only in the student pack.

Stretch

- `@CrossOrigin(origins = "http://localhost:5173")` (or `CorsConfig`) — **not** Done when. Production origins **Later —**.
- Extra field (e.g. `category`) — not Done when.
- HTTP **DELETE** `/products/{id}` — optional.
- Lombok / records / MapStruct — optional, not in Done when.
- **Later —** Spring Security / JWT. **Later —** React list UI.

Done when

- [ ] `mvn spring-boot:run` starts (Tomcat + DataSource; MySQL reachable)
- [ ] `Product` remains `@Entity`; repository still `JpaRepository<Product, Long>`

- [ ] GET `/products` returns **`ProductResponse`** JSON array from **`findAll()`**
- [ ] GET `/products/{id}` returns **200** DTO or **404**
- [ ] POST uses **`@Valid`** **`ProductRequest`**, maps, **`save`**, **201**
- [ ] Invalid POST returns **400** with **`error`** and **`fields`**
- [ ] Restart; POST data is still in GET list
- [ ] Postman collection v1 imports; five requests match 200 / 201 / 404 / 400
- [ ] Password not a literal; `.env` not committed
- [ ] No Spring Security / JWT, no MapStruct, no Lombok required
- [ ] CORS **not** required to pass
- [ ] `target/` untracked; short README with run + curl + Postman (Standard Project Deliverables)

Interview Q&A

Shared with students after concepts and the mini-project. Use for review and interview prep — questions and model answers are included.

Q1. What is a DTO?
A: A Data Transfer Object — a class for JSON (or another wire format), not for the table. `ProductRequest` / `ProductResponse` in this module.

Q2. Why not expose the entity as JSON?
A: Clients could send `id`, extra columns leak, and validation gets mixed with persistence. A spike may return the entity; a junior-realistic API splits the types.

Q3. What is manual mapping?
A: Copying fields with getters / setters (or a small mapper class). MapStruct generates that code — optional, not required here.

Q4. Why does `ProductRequest` omit `id`?
A: MySQL `IDENTITY` assigns the key on INSERT. A client-supplied id on `save` looks like an UPDATE.

Q5. `@Valid` vs the annotations on fields?
A: Annotations declare rules. `@Valid` on the controller parameter **runs** them for that `@RequestBody`.

Q6. Why `Integer` for `priceInr` on the request?
A: `@NotNull` only fails on a wrapper. A primitive `int` becomes `0` when the JSON field is missing.

Q7. `javax.validation` vs `jakarta.validation`?
A: Boot 3 uses `jakarta.*`. Same story as `jakarta.persistence` on the entity.

Q8. What does `@RestControllerAdvice` do?
A: Global handler for controller exceptions. Here it turns `MethodArgumentNotValidException` into 400 JSON with `error` and `fields`.

Q9. Why keep 404 in the controller?
A: Modules 02 / 03 already taught GET-by-id 404. This module only designs the **validation** body. Mixing every error into advice is later depth.

Q10. 400 vs 404 vs 201?
A: 400 = invalid POST body. 404 = unknown id on GET. 201 = valid create.

Q11. What is a Postman collection?
A: A JSON file of saved requests (and optional tests) you import. The kit commits `CampusCart_Products_v1.postman_collection.json`.

Q12. Why not screenshots instead of the collection file?

A: Teammates cannot import a screenshot. Git reviews the JSON. Tests can assert status codes.

Q13. Does Postman need CORS?

A: No. CORS is enforced by browsers. Postman and curl are not browsers.

Q14. What origin do we allow in lab?

A: `http://localhost:5173` (Vite). Production origins are **Later —**. `@CrossOrigin` is Stretch, not Done when.

Q15. Is this Spring Security?

A: No. CORS headers are not login. JWT / `starter-security` is the next module.

Q16. Did we drop JPA?

A: No. `Product` + `JpaRepository` + MySQL remain. DTOs wrap the same rows.

Q17. How does this connect to CampusCart?

A: Capstone catalog JSON should be a stable contract (DTO + validation + Postman). React weeks call these URLs. Auth comes next.

Next

Push **CampusCart Catalog DTOs and Postman v1** (kit 18 — collection file committed, no secrets, `target/` ignored). Continue with **Spring Security Lite** — JWT lite. CORS on the React app is **Later —** React weeks; do not start kit 19 here.