Kasi Yedumati · Full Stack Training

Introduction to SQL (Basic Concepts)

Module Outcome:

- Place a command in DDL / DML / DQL / DCL / TCL — not “SQL is SELECT”
- Create a small table and insert a row with MySQL quotes (`'Ravi'`)
- Treat SQL as declaring *what* you want, not looping like Python

Introduction to SQL [Basics]

- SQL stands for **Structured Query Language**.
- SQL is used to perform operations on Relational DBMS.
- SQL is declarative. Hence, easy to learn.
- SQL provides multiple clauses (commands) to perform various operations like create, retrieve, update and delete the data.

Note: This course uses **MySQL 8+** syntax. Use single quotes for string literals (`'value'`). See MySQL Setup and Connection.

SQL Language Categories

SQL commands are grouped into five categories based on their purpose:

Category	Full Form	Purpose	Commands
DDL	Data Definition Language	Define and modify database structure	`CREATE` , `ALTER` , `DROP` , `TRUNCATE`
DML	Data Manipulation Language	Insert, update, and delete data	`INSERT` , `UPDATE` , `DELETE`
DQL	Data Query Language	Retrieve data from tables	`SELECT`
TCL	Transaction Control Language	Manage transactions	`COMMIT` , `ROLLBACK` , `SAVEPOINT`
DCL	Data Control Language	Manage user access and permissions	`GRANT` , `REVOKE`

```
DDL  →  Structure (tables, columns)
DML  →  Data changes (insert, update, delete)
DQL  →  Data retrieval (select)
TCL  →  Transaction safety (commit, rollback)
DCL  →  Security (grant, revoke)
```

Note: TCL and DCL are covered in Transactions and Indexes.

DDL vs DML: Commit Behavior

In MySQL, **DDL** and **DML** commands behave differently when it comes to saving changes.

	DDL	DML
Commands	`CREATE`, `ALTER`, `DROP`, `TRUNCATE`	`INSERT`, `UPDATE`, `DELETE`
What it changes	Database structure (tables, columns)	Data inside tables
Auto-commit	**Yes** — changes are saved immediately	**No** — changes are pending until you `COMMIT`
ROLLBACK	**Cannot** undo a completed DDL statement	**Can** undo uncommitted changes with `ROLLBACK`

Example — DDL is auto-committed:

```
CREATE TABLE customers (
    name VARCHAR(60),
    mobile_number VARCHAR(15),
    account_id VARCHAR(20) PRIMARY KEY
);
-- Table is created immediately. There is nothing to ROLLBACK.
```

Example — DML can be rolled back:

```
START TRANSACTION;

UPDATE customers
SET mobile_number = '9998888567'
WHERE account_id = '123456';

-- Changes are NOT permanent yet
ROLLBACK;   -- undoes the UPDATE

-- Or use COMMIT; to save the changes permanently
```

> **Note:** `DROP TABLE` and `TRUNCATE TABLE` are DDL commands — once they run successfully, the structure or data they remove cannot be recovered with `ROLLBACK`. Use them carefully.

Creating Tables

Create Table — Creates a new table in the database.

Syntax:

```
CREATE TABLE table_name (
    column1 type1,
    column2 type2,
    ....
);
```

Here, `type1` and `type2` in the syntax are the datatypes of `column1` and `column2` respectively.

Example: Create a player table to store the following details of players.

column_name	data_type	Constraint
id	INT / INTEGER	PRIMARY KEY
name	VARCHAR(200)	
age	INT / INTEGER	
score	INT / INTEGER	

```
CREATE TABLE player (
    id INT NOT NULL PRIMARY KEY AUTO_INCREMENT,
    name VARCHAR(200),
    age INT,
    score INT
);
```

A **primary key** uniquely identifies each row in a table. No two rows can have the same primary key value. `AUTO_INCREMENT` lets MySQL automatically assign the next `id` when we omit it in `INSERT`.

We can check the details of the created table using `DESCRIBE` or `SHOW COLUMNS`.

MySQL Data Types

MySQL provides a rich set of data types. Choose the right type based on the data you store.

Integer Types

Type	Storage	Range	Use Case
`TINYINT`	1 byte	-128 to 127	Age, status flags
`SMALLINT`	2 bytes	-32,768 to 32,767	Small counts
`INT` / `INTEGER`	4 bytes	±2 billion	IDs, quantities
`BIGINT`	8 bytes	±9 quintillion	Large IDs, timestamps

Decimal and Floating-Point Types

Type	Description	Use Case
`DECIMAL(p,s)` / `NUMERIC(p,s)`	Exact fixed-point (p=precision, s=scale)	**Money, prices** — no rounding errors
`FLOAT`	Approximate 4-byte floating point	Scientific calculations
`DOUBLE`	Approximate 8-byte floating point	Large approximate values

Example:

```
price DECIMAL(10,2)   -- up to 99999999.99 (exact)
rating FLOAT          -- approximate (e.g., 4.567890)
```

```
salary DECIMAL(12,2)  -- money: 1234567890.12
```

Note: Use `DECIMAL` for money. `FLOAT` / `DOUBLE` are approximate and can cause rounding errors in financial calculations.

String Types

Type	Description	Use Case
`CHAR(n)`	Fixed-length string (padded with spaces)	Country codes (`'IN'`), fixed codes
`VARCHAR(n)`	Variable-length string (up to n chars)	Names, emails, titles
`TEXT`	Large variable-length text	Descriptions, comments

Example:

```
country_code CHAR(2)        -- always 2 chars: 'IN', 'US'
name VARCHAR(200)           -- variable: 'Virat', 'Rakesh Kumar'
description TEXT            -- long text
```

Date and Time Types

Type	Format	Description
`DATE`	`'YYYY-MM-DD'`	Date only
`TIME`	`'HH:MM:SS'`	Time only
`DATETIME`	`'YYYY-MM-DD HH:MM:SS'`	Date and time
`TIMESTAMP`	`'YYYY-MM-DD HH:MM:SS'`	Date/time; auto-updates on row change

Example:

```
birth_date DATE                         -- '1990-05-15'
login_time TIME                         -- '14:30:00'
created_at DATETIME DEFAULT CURRENT_TIMESTAMP
updated_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
```

Other Types

Type	Description
`BOOLEAN` / `BOOL`	Stored as `TINYINT(1)` : 0 = FALSE, 1 = TRUE
`JSON`	Stores JSON documents (MySQL 8+)

JSON Example (MySQL 8+):

```
CREATE TABLE product_meta (
    id INT PRIMARY KEY AUTO_INCREMENT,
    name VARCHAR(200),
    attributes JSON
);

INSERT INTO product_meta (name, attributes)
VALUES ('Smart Watch', '{"brand": "Apple", "color": "black", "features": ["GPS", "HR"]}');

SELECT name, attributes->>'$.brand' AS brand FROM product_meta;
```

Inspecting Table Structure

Use these MySQL commands to view table details:

```
DESCRIBE player;
-- or
SHOW COLUMNS FROM player;
```

Example output:

Field	Type	Null	Key	Default	Extra
id	int	NO	PRI	NULL	auto_increment
name	varchar(200)	YES		NULL	
age	int	YES		NULL	
score	int	YES		NULL	

Table Constraints

Constraints enforce rules on the data stored in a table. Common constraints:

Constraint	Description
PRIMARY KEY	Uniquely identifies each row; cannot be NULL
NOT NULL	Column must always have a value
UNIQUE	All values in the column must be different
DEFAULT	Assigns a default value when none is provided
CHECK	Validates data against a condition
FOREIGN KEY	Links a column to a primary key in another table

Syntax:

```
CREATE TABLE table_name (
    column1 type1 NOT NULL,
    column2 type2 UNIQUE,
    column3 type3 CHECK (column3 > 0),
```

```
    ...
);
```

Example: Create an `employee` table with constraints.

```
CREATE TABLE employee (
    id INT NOT NULL PRIMARY KEY AUTO_INCREMENT,
    name VARCHAR(200) NOT NULL,
    email VARCHAR(200) UNIQUE,
    salary DECIMAL(12,2) CHECK (salary > 0),
    status VARCHAR(20) DEFAULT 'active',
    created_at DATETIME DEFAULT CURRENT_TIMESTAMP
);
```

Notes:

- `NOT NULL` prevents inserting NULL into that column.
- `UNIQUE` ensures no two rows share the same value in that column.
- `DEFAULT` assigns a value automatically when INSERT omits that column.
- `CHECK` rejects rows that fail the condition (e.g., negative salary).
- Foreign keys are covered in Modeling Databases.

Example — DEFAULT in action:

```
INSERT INTO employee (name, email, salary)
VALUES ('Ravi', 'ravi@email.com', 50000);
-- status defaults to 'active', created_at defaults to current timestamp
```

Inserting Rows (DML)

`INSERT` clause is used to insert new rows in a table.

Syntax:

```
INSERT INTO
    table_name (column1, column2, ..., columnN)
VALUES
    (value1, value2, ..., valueN),
    (value1, value2, ..., valueN);
```

Any number of rows from 1 to n can be inserted into a specific table using the above syntax.

Example: Insert name, age and score of 2 players in the player table.

```
INSERT INTO
    player (name, age, score)
VALUES
    ('Rakesh', 39, 35),
    ('Sai', 47, 38);
```

Upon executing the above code, both the entries would be added to the player table.

```
SELECT *
```

```
FROM player;
```

Output:

name	age	score
Rakesh	39	35
Sai	47	38

Possible Mistakes

Mistake 1: The number of values that we're inserting must match with the number of column names that are specified in the query.

```
INSERT INTO
    player (name, age, score)
VALUES
    ("Virat", 31);
```

Output: Error: 2 values for 3 columns

Mistake 2: We have to specify only the existing tables in the database.

```
INSERT INTO
    player_Information (name, age, score)
VALUES
    ("Virat", 31, 38);
```

Output: Error: no such table: player_Information

Mistake 3: Do not add additional parenthesis `()` post VALUES keyword in the code.

```
INSERT INTO
    player (name, age, score)
VALUES
    (("Rakesh", 39, 35), ("Sai", 39, 40));
```

Output: Error: 2 values for 3 columns

Mistake 4: While inserting data, be careful with the datatypes of the input values. Input value datatype should be same as the column datatype.

```
INSERT INTO
    player(name, age, score)
VALUES
    ('Virat', 30, 'Hundred');
```

WARNING: If the datatype of the input value doesn't match the column datatype, MySQL raises an error in strict mode (the default in MySQL 8+).

Retrieving Data (DQL)

`SELECT` clause is used to retrieve rows from a table.

The database consists of a **player** table that stores the details of players who are a part of a tournament. The player table stores the name, age and score of players.

Selecting Specific Columns

To retrieve the data of only specific columns from a table, add the respective column names in the SELECT clause.

Syntax:

```
SELECT
    Column1,
    Column2,
    ....
    columnN
FROM
    table_name;
```

Example: Fetch the name and age of the players from the player table.

```
SELECT
    name,
    age
FROM
    player;
```

Output:

name	age
Virat	32
Rakesh	39
Sai	47
...	...

Selecting All Columns

Sometimes, we may want to select all the columns from a table. Typing out every column name, for every time we have to retrieve the data, would be a pain.

Syntax:

```
SELECT *
FROM table_name;
```

Example: Get all the data of players from the player table.

```
SELECT *
FROM player;
```

Output:

name	age	score
Virat	32	50
Rakesh	39	35
Sai	47	30
...	...	...

Selecting Specific Rows

We use `WHERE` clause to retrieve only specific rows.

Syntax:

```
SELECT *
FROM table_name
WHERE condition;
```

Note: WHERE clause specifies a condition that has to be satisfied for retrieving the data from a database.

Example: Get the details of the player whose name is 'Ram' from the player table.

```
SELECT *
FROM player
WHERE name = 'Ram';
```

Output:

name	age	score
Ram	47	30

Update Rows (DML)

`UPDATE` clause is used to update the data of an existing table in database. We can update all the rows or only specific rows as per the requirement.

Update All Rows

Syntax:

```
UPDATE
    table_name
SET
    column1 = value1;
```

Example:

```
UPDATE
    player
SET
    score = 100;
```

Update Specific Rows

Syntax:

```
UPDATE
    table_name
SET
    column1 = value1
WHERE
    column2 = value2;
```

Example:

```
UPDATE
    player
SET
    score = 150
WHERE
    name = 'Ram';
```

Delete Rows (DML)

`DELETE` clause is used to delete existing records from a table.

Delete All Rows

Syntax:

```
DELETE FROM
    table_name;
```

Example: Delete all the rows from player table.

```
DELETE FROM
    player;
```

Delete Specific Rows

Syntax:

```
DELETE FROM
    table_name
WHERE
    column1 = value1;
```

Example: Delete 'shyam' from the player table.

> **Note:** We can uniquely identify a player by name.

```
DELETE FROM
    player
WHERE
    name = 'shyam';
```

Warning: We cannot retrieve the data once we delete the data from the table.

TRUNCATE (DDL)

`TRUNCATE` removes **all rows** from a table quickly. Unlike `DELETE`, it cannot use a `WHERE` clause and typically cannot be rolled back.

Syntax:

```
TRUNCATE TABLE table_name;
```

Example:

```
TRUNCATE TABLE player;
```

DELETE	TRUNCATE
DML command	DDL command
Can use `WHERE` to delete specific rows	Removes all rows only
Slower for large tables (logs each row)	Faster (deallocates data pages)
Can be rolled back (in a transaction)	Cannot be rolled back in most cases
Triggers fire on DELETE	Triggers do not fire on TRUNCATE

> **Note:** Use `DELETE` when you need conditional deletion or rollback. Use `TRUNCATE` when you need to empty an entire table quickly.

DROP Table (DDL)

`DROP` clause is used to delete a table from the database.

Syntax:

```
DROP TABLE
```

```
    table_name;
```

Example:

```
DROP TABLE player;
```

Alter Tables (DDL)

`ALTER` clause is used to add, delete, or modify columns in an existing table.

Add Column

Syntax:

```
ALTER TABLE
    table_name
ADD
    column_name datatype;
```

Example: Add a new column `jersey_num` of type integer to the player table.

```
ALTER TABLE
    player
ADD
    jersey_num INT;
```

Note: Default values for newly added columns in the existing rows will be NULL.

Rename Column

Syntax:

```
ALTER TABLE
    table_name RENAME COLUMN C1 TO C2;
```

Example: Rename the column `jersey_num` in the player table to `jersey_number`.

```
ALTER TABLE
    player RENAME COLUMN jersey_num TO jersey_number;
```

Drop Column

Syntax:

```
ALTER TABLE
    table_name DROP COLUMN column_name;
```

Example:

```
ALTER TABLE
    player DROP COLUMN jersey_number;
```

Note: `ALTER TABLE ... DROP COLUMN` is supported in MySQL 8.0+.