Kasi Yedumati · Full Stack Training

Lesson 3 — Request Body and Validation


Course: FastAPI for Full Stack · **Session 3 of 10** · Learning path · **Previous:** Lesson 2 · **Next:** Lesson 4

> **Module Outcome:** You can register an AcmeHR employee with a checked JSON body, and you can read a **422** response when a field is missing or invalid.

You will build	`POST /employees` that rejects a bad registration
New words	Request body, model, required, optional, 422
You need	The employee routes in `acmehr-api/main.py`

From the requirements. HR registers an employee: id, name, designation, department, work email, and an optional phone. A missing name, an id that is not `E-1042` shape, or an email without `@` must not be stored.

1. Three places a value can sit



Place	Example	Use it for
Path	`/employees/E-1042`	Which one
Query	`?department=Engineering`	A filter on a list
Body	`{"name":"Sana Qureshi", ...}`	The fields of a new or replaced employee

A `dict` body stores whatever JSON arrives. This POST was accepted, and the row was saved with no name and a useless id:

```
{"designation":"Accountant","employee_id":"hello"}
```

A **model** is a class that lists the fields and the rules. FastAPI checks the JSON against the model before your function runs. When the check fails, the client gets **422** and your function does not run. Nothing is appended to `employees`.

400 stays your own rule, such as "this id is already in the list." **422** is FastAPI's check on the shape of the body.

---

2. The registration model

Add the import and the class above the routes. Then add `email` and `phone` to each of the six people already in the list, so a GET and a new registration look the same. Ananya's email is `ananya.rao@acme.example` and her phone is `+91 90000 01042`. The others can use `firstname.lastname@acme.example` and `"phone": None`.

The whole file is `examples/lesson03/01_register.py`.

```
from pydantic import BaseModel, EmailStr, Field

class EmployeeCreate(BaseModel):
    employee_id: str = Field(pattern=r"^E-\d{4}$")
    name: str = Field(min_length=1)
    designation: str
    department: str
    email: EmailStr
    phone: str | None = None
```

Line	Job
`BaseModel`	The class FastAPI can check a JSON body against
`Field(pattern=...)`	`employee_id` must look like `E-1042`
`Field(min_length=1)`	`name` cannot be an empty string
`EmailStr`	The value must be an email address
`phone: str | None = None`	Optional. A missing phone is stored as `null`
`designation: str`	Required. No default, so a missing designation is 422

Replace `create_employee` so the argument is the model, not a dict. `model_dump()` turns the checked model back into a dictionary you can store.

```
@app.post("/employees", status_code=201)
def create_employee(employee: EmployeeCreate):
    if any(row["employee_id"] == employee.employee_id for row in employees):
        raise HTTPException(status_code=400, detail="Employee id already exists")
    row = employee.model_dump()
    employees.append(row)
    return row
```

Point `replace_employee` at `EmployeeCreate` too, so a full replace is checked the same way. PATCH still takes a `dict`. A partial update has a different shape. The next page separates that shape.

Common error: `ImportError` mentioning `email-validator`. The install was `fastapi` without `[standard]`. Run `pip install "fastapi[standard]"` in the active venv.

---

3. What 422 looks like

`fastapi dev` restarts when you save. In `/docs`, open **POST /employees** and send this body. The name is missing.

```
{
  "employee_id": "E-1049",
  "designation": "HR Executive",
  "department": "Human Resources",
  "email": "sana.qureshi@acme.example"
}
```

Output, status 422:

```
{
  "detail": [
    {
      "type": "missing",
      "loc": ["body", "name"],
      "msg": "Field required",
      "input": {
        "employee_id": "E-1049",
        "designation": "HR Executive",
        "department": "Human Resources",
        "email": "sana.qureshi@acme.example"
      }
    }
  ]
}
```

`loc` says where the problem is: in the body, the field `name`. `msg` says what is wrong. The function `create_employee` did not run.

Two more bodies to send yourself:

Body problem	`loc`	`msg`
`"email": "not-an-email"`	`["body", "email"]`	`value is not a valid email address: An email address must have an @-sign.`
`"employee_id": "1042"`	`["body", "employee_id"]`	`String should match pattern '^E-\\d{4}$'`

Now send a valid registration. Phone is left out on purpose.

```
{
  "employee_id": "E-1048",
  "name": "Sana Qureshi",
  "designation": "HR Executive",
  "department": "Human Resources",
  "email": "sana.qureshi@acme.example"
}
```

Output, status 201:

```
{
  "employee_id": "E-1048",
  "name": "Sana Qureshi",
  "designation": "HR Executive",
  "department": "Human Resources",
  "email": "sana.qureshi@acme.example",
  "phone": null
}
```

Send that same body again. **400** and `{"detail":"Employee id already exists"}`. That rule is yours. The model cannot know who is already in the list.

Common error: You made `phone: str` with no default. A registration without a phone is 422, `Field required`, on `phone`. Write `str | None = None`.

Common error: The pattern is pasted as a normal string and `\d` is lost. In Python the pattern needs the `r` prefix: `r"^E-\d{4}$"`.

Try these

1. **(Easy)** Register `E-1050` with a real email and no phone. GET that id. `phone` is `null`.
2. **(Easy)** Send `"name": ""`. Read `msg`.
3. **(Medium)** Send `"employee_id": "E-1042"` with Ananya's other fields filled in correctly. Which status comes back, 400 or 422, and why that one?
4. **(Medium)** PUT `/employees/E-1048` with a body whose email is `not-an-email`. The stored row does not change.
5. **(Stretch)** PATCH still accepts `{"email": "not-an-email"}`. Confirm with a GET. That loose dict is closed when PATCH gets its own model.

Interview: *Where can a value arrive, and what is each place for?* — The path picks one resource. The query filters a list. The body carries the fields.

Interview: *What is the difference between 400 and 422?* — 422 means the JSON does not match the model, and your function did not run. 400 means the JSON matched, and your own rule rejected it, such as a duplicate employee id.

Key takeaways

- A model lists the fields. FastAPI checks the body before the function runs.
- A field with no default is required. `= None` makes it optional.
- A failed check is **422**. Read `loc` and `msg`.
- A duplicate id is **400**, because only your code knows the list.

Lab — Ticket ACME-203

Homework

Next: Response models and error handling. The JSON you send and the JSON you return become two different shapes, and PATCH stops taking a loose dict.