

bool datatype:

We can use this datatype to represent boolean values

The allowed values for boolean data type are : True, False

is eligible -> Yes (True)

is not eligible --> No (False)

Is customer active --> yes or no --> True or False

a = True

status = True

is_eligible = True

is_active = True

internally **True** means 1 and **False** means 0

string datatype :

str is the representation of string datatype

A string is sequence of characters, enclosed within a single quotes or double quotes also

it can have a alphanumeric values as well


favourite_cricketer = "virat"

customer_name = "dhoni MS"


order_info = "ordered selected"

email_id = "test@gmail.com"

"Python class is very and useful" for java students also"



cricketer= "virat"



Slicing of Strings:

slice means a piece of big portion

[] is its slicing operator, which can be used to retrieve parts of string

In python string follows indexing mechanism to store characters

Index always starts from zero (0,1,2,3,4,.....)



In python indexes can be positive or negative

+ve index means forward direction from left to right

-ve index means backward direction from right to left


Note: if we try to fetch value using the index more than the indexed position then we get IndexError: string out of range

Get Kohli from Virat Kohli



Starting is position where you want to cut the piece and it includes that position character
endposition is where you want to end the piece but ending index **character won't be inclusive**
If we don't give any endposition, ending index will be treated as the end of entire string

cricketer= "virat"



Slicing of Strings:

slice means a piece of big portion

[] is its slicing operator, which can be used to retrieve parts of string

In python string follows indexing mechanism to store characters

Index always starts from zero (0,1,2,3,4,.....)



In python indexes can be positive or negative

+ve index means forward direction from left to right

-ve index means backward direction from right to left

Note: if we try to fetch value using the index more than the indexed position then we get IndexError: string out of range

Get Kohli from Virat Kohli



Starting is position where you want to cut the piece and it includes that position character
endposition is where you want to end the piece but ending index **character won't be inclusive**
If we don't give any endposition, ending index will be treated as the end of entire string

Note:

In python int, float, complex, bool and str are the fundamental datatypes

TYPE CASTING:

a = "10"

b = "20"

The process of converting one type to another type is nothing but a typecasting or type coercion.

These are the following functions for typecasting

1. int() :

We can use this function to convert values from other type to int

Note:

1. We can convert any type to int except complex type

2. If we want to convert string to int type, mandatorily string should have only integral values and that should have base-10, otherwise it will get ValueError

2. float() --> We can use float function to convert other types(int, bool, str, etcc) to float type

Note:

1. We can convert any type to float except complex type

2. If we want to convert string to float type, mandatorily string should have only floating or integral values and that should have base-10, otherwise it will get ValueError

3. complex() --> We can use this function to convert any other type to complex type

4. bool() --> We can use this function convert any toher type to bool


5. str() --> We use this function to convert any other type to string

Immutability w.r.to Fundamental DataTypes:

=====

If I'm able to change the object after creation we can call it as mutable object

If I'm unable to change the object after creation we can call it as immutable object.



In python if a new object is required, PVM wont create new object immediately rather it will check the exist object, if any object has same content or data, it will reuse that object.

If existing objects are not having same content, then only it will create a new object

Advanced Datatype or datastructures:

bytes
bytearray
list
tuple
set
range
dict

bytes datatype :

bytes data type is helpful to represent a group of numbers, like a an array

the only allowed values are 0 to 255, accidentally if we give more than this range then we will get valueerror

Syntax:

we have to use bytes(x) --> x is having sequence of numbers

Ex: bytes([10,20,30,40])

bytes is immutable we can not change its values or reassign once it is created, if we try to modify we will get type error

if we want to store data within 0 to 255 and i dont want anyone to be able to modify/change after creation, then bytes is right choice

1, 2 3 4 5 6 7 8 9, 10, 23 --> state codes in vodafone

bytearray data type:

bytearray is exactly same as bytes datatype except that it is mutable(i.e we can change the values)

the only different between byte and bytearray is bytes is immutable and bytearray is mutable

list datatype:

If we want to store group of values in a single variable, where values having different type of data or same type of data

marks = [10,20,30,40] --> Same type of data, this is possible (homegenious data)

student_data = [12345, "kasi yedumati", 98, True] --> Different type of data(heterogenous data)

1. It maintains insertion order
2. it allows heterogenous(different type of values) data
3. duplicate data also allowed
4. it is growable in nature(we can add data after creation or remove data or modify data or fetch data)
5. we should create list variable values using []

Ex: sutdent_list = ["kasi", "virat","dhoni"]

```
student_names = ["kasi", "bhuvan", "chandu", "varshith", "harika", "chandu"]
```

0 1 2 3 4 5

```
student_name[3] --> varshith
```

0 1 2 3 4 5 6 7

Note: List is an ordered, mutable, heterogeneous collection of elements and also duplicated are ordered

tuple data type:

tuple is exactly same as list, except that it is immutable i.e we cannot change the values once it is created

syntax : we have to create a tuple using paranthesis ()

Ex: (10,20,30)

0 1 2

Note: tuple is the read only version of list

range datatype:

range datatype represents sequence of numbers

range is also immutable, the values/numbers present range datatype are not modifiable.

Syntax1:

range(x) --> x will be a number

range(20) --> it generates numbers from 0 to 19

Syntax 2:

range(start, end) --> start will be a number and end also should be a number

Syntax3:

range(start, end, increment)

start --> it is where i want to sequence range should start from

end --> it is where i want to stop range

increment --> how many values you have to increment for every generate sequence numbers

range(10, 20, 2)

Set datatype:

Whenever we want to store group of values where insertion order is not required and duplicated are not allowed, in that case we go for set

1. insertion order is not preserved
2. duplicates are not allowed
3. hetergenious objects are allowed (same or different type of values)
4. it doesnt follow indexing
5. it follows hashing mechanism to insert or update data or manage data in set
6. it is mutable (once the object is created we can modify)
7. it is growable in nature

```
fruits_set = {'banana', 'apple'}
```

```
fruits_set = set() --> create an empty set
```

frozenset Datatype:

frozeznset is exactly same as set , except that it is immutable.

Once it is created, we cant add, remove or modify its items.

Syntax:

```
frozenset([10,20,30])
```

dict datatype :

If we want to store a group of values as **key-value** pairs then we should go for dictionary datatype

Syntax:

```
contacts = {"name" : "mobilenumber"}
```

```
employee_data = ["kasi", 1234, 123000, "hyd"] --> list data form
```

```
employee_data =
```

```
{  
    "name" : "kasi",  
    "employeeid" : 12345,  
    "salary" : 12345.50,  
    "location" : "hyd"  
}
```

Key must be unique

value can be unique or duplicate

immutable datatype (string, tuple, frozenset)

Using key we can access the data

Values can be any datattype

if we try to add same key twice, it will just consider latest entry value or it overrides values within the same key

it wont throw any error

Datatype	Duplicates	Insertion order	heterogenous	mutable or immutable	syntax	follows index?
int	not applicable	not applicable	only integers 0 to 9	immutable	a = 10; b = 20	
float	not applicates	not applicable	only floating values	immutable	a= 10.5	
complex	not applicable	not applicable	real and imaginary	immutable	a = 3+0j	
bool	not applicable	not applicable	True, False	immutable	a = True ; a= False	
string	allowed	applicable	No	immutable	a= "hello"	Yes, eg: a[2]
bytes	allowed	applicable	No(0 to 255)	immutable	b = bytes([10,20,30])	Yes
bytearray	allowed	applicable	No	mutable	b =bytearray([10,20])	Yes
list	allowed	applicable	Yes	mutable	names=['shreyas','sai']	Yes, eg: names[1]
tuple	allowed	applicable	Yes	Immutable	x=(1,3+2j, 'chandu')	Yes, eg: x[2][2]
range	allowed	applicable	No	mutable	x=range(0,9); 0,1,2,3 4,5,6,7,8	Yes
set	not allowed	not preserved	Yes	mutable	x={1,2,3,4}	No (because it follows hashing)
frozenset	not allowed	not preserved	Yes	Immutable	x=frozenset([1,2,3])	no
dict	duplicate keys are not allowed	applicables	Yes	Mutable	d={'a' : 1, 'b':2}	we access values with key

Operators:
Operator is a symbol or keyword using which we can perform operations

- 1. Arithmetic operators
 - + -> Addition/sum values
 - -> subtraction
 - * -> multiplication
 - / -> Division operator
 - % -> modulo operator (it returns the remainder)

// -> Floor division operator
**-> Power operator or exponential operator

+ operator we can against strings also, we call it as concatination operator
* operator also we can use against strings, but atleast one value should be integer
String multiplication operator

2. Relational or Comparison operators

>
<
>=
<=

Comparison operators will compare any two values and return boolean values True or False
Equality operators -> == !=

3. Logical operators

There are three logical operators: **and** , **or** , **not**
These keywords/operators we can apply on all datatypes

These operators also check and return **boolean value**

and -> If both arguments are **True** then only result is **True**
or -> If atleast one argument is **True** then output will be **True**
not -> **complement**(if we apply **not** for **True** it will become **False**, if we apply **not** for **False** it will return **False**

	A	result
not	True	False

	A	B	
and	True	True	True
	True	False	False
	False	True	False
	False	False	False

	A	B	Result
or	True	True	True
	True	False	True
	False	True	True
	False	False	False

0 means False
non-zero means True
empty string is always treated as False

if a is evaluates to False return a otherwise it returns y

4. Assignment operators

We can use assignment operator to assign value to a variable
Eg: x = 10
We can combine assignment operator with mathematical operators

x += 10

5. Ternary Operators

Syntax:

x = **firstValue** if **condition** else **secondValue**

if condition becomes True then firstValue will be returned, else(if condition becomes False) secondValue will be returned

5. Bitwise operators

6. Special operators
Python has two special category operators they are

6.1 : Identity Operators

We can use identity operators for address comparison

is
is not

Eg: a= 20
b = 30
a is b -> This returns **True** if both a and b are pointing to the same object, otherwise returns **False**
a is not b -> This returns **True** if both a and b are **not pointing** to same obj, otherwise returns **False**

Note: We can use is operator for addrpss comparison whereas == operator for content comparison

6.2: Membership operators:

We can use membership operators to check whether the given object is present in the collection or datastructures (String, List, Set, Tuple or Dict)

in -> Returns True if the given obj present in the specified collection
not in -> Returns True if the given object is not present in the collection

Bitwise Operators:

We can apply these operators bitwise
These operators we can apply only on int and boolean types, if we try to apply on any other type we will get Error

Eg: print(5&4) ->Valid
print(True & True) -> Valid
print("abc"&"xyz") -> Invalid (Error)
print(0.5&10.5) -> Invalid(Error)

5 ->
4 ->
&
|
^
~
<<
>>
4 - 0100
5 - 0101 -
8 - 0000 -> 0+4+0+0=4
1 - 0101 -> 5
6 - 0110
8 - 1000 -> 0
8 - 0000
1 -> 1110 -> 8+4+2+0=14
4 0100
5 0101
6001 -> 1

bitwise compliment operators:
We have to apply complement for total bits(single value)

Eg: print(~5) -> -6

Operator	Description
&	If both bits are 1 then only result is 1 otherwise result is 0
	If atleast one bit is 1 then result is 1 otherwise result is 0
^	if bits are different then result is 1 otherwise result is 0
~	bitwise complement operator i.e 1 means 0 and 0 means 1
>>	Bitwise right shift operator> it swifts positions to the right, and result the final value
<<	bitwise left shift operator -> it swifts positions to the right and result the final value

<< left shift operators
Eg: print(10<<2)
10 -> 40
40 = 32+8
right shift >>
print(10>>2)
10 -> 2

Python Comments:

Comments in python are used to explain the code and provide futuristic TODO items
these comments are ignore by python during program execution

Advantages:

- 1. Readability improvement
- 2. It can be used to identity the funcitonality or structure of the code

Single line comments :

Single line comments are starts with hashtag #

Ex:

this is a single comment

Multi-line comments:

We can apply hashtags multiple times
using a string literals using `"""comment"""`
`"""testcomment"""`

Input and Output Statements:

Static inputs/values --> If the value or input is always same, we call it as static value/input

Dynamic inputs/Values --> If the value or input keeps changing over the time, we call it as dynamic input

Whenever we are building applications or command line based scripts or automation scripts, we take the input from Either ui or command prompt or terminal

To take the dynamic inputs from the keyboard we have a function called **input()**

input():

it is used to take dynamic input from keyboard while running the program, and it will wait for user to enter the input
and start executing the program once the data is entered

input function always return data in string type, before performng any operatton we have to do the typecasting if at all it is needed.

reading multiple values at a time
split() is the function in string, which will split values based on delimiter/saperator, if we dont specify any saperator
by default it will saperate based on space(" ") and it will return splittted values in list type
a = input("Enter 2 numbers in a space saperated:").split()

eval():

It will take a string as in put and evaluate the result

eval can evaluate the input to list, tuple, set, based on the provided input


Command Line Arguments:

The argument which are passing at the time of execution are called command line arguments

Eg: python3 sum.py 10 30 20

Command line arugments

Within in the python program these arguments are available in **argv**, **which is present in sys module**
argv --> is an intenal python manged parameter which of list type



Note1: By default all arguments will be treated as strings only

Note2: Within the python program command line args are available in string form based on our requirement, we need to convert them to required type

Note3: Usually space is saperator between command line args, if our command line arg itself has a space then we should enclose within the double quotes

Output statements:

We can use print() function to display output

Form-1: print() without any argument

Print Syntax:

```
print(*args, sep= ' ', end='\n', file=sys.stdout, flush= False)
```

Form3: print() with variable number of arguments

```
a,b,c= 10,20,30  
print("numbers are", a,b,c)
```

by default sep is space, we can override by explicitly giving a separator

```
print(a,b,c, sep='&')
```

end parameter is used to end the current print statement, by default end will be \n which is new line

Form5: print with objects

Form6: print(string, variable list)

we can use print statement with string and any number of arguments

Form7: print(formatted string)

%i --> int value

%d --> int value


%f --> float

%s --> string

Form8: print with replacement operator { }

Flow Control:

Flow control describes the order in which statements should be executed and also which statements to execute



Conditional statements:

Conditional statements are such that, if your condition is met only then the statements will be executed.
aka, if we want to execute any statement(s) conditionally, then we go for conditional statement

if:

Syntax:

statement1

statement2

if condition:

statement3

statement4

statement5

statement6


**in this program statement3, 4 will be execution only when condition is True
statement1,2,5,6 will execute, irrespective of condition is True or False**

if block of statements

Note: At a time either if block statements or else block statements will execute not both

Flow Control:

Flow control describes the order in which statements should be executed and also which statements to execute



Conditional statements:

Conditional statements are such that, if your condition is met only then the statements will be executed.
aka, if we want to execute any statement(s) conditionally, then we go for conditional statement

if:

Syntax:

statement1

statement2

if condition:

statement3

statement4

statement5

statement6

**in this program statement3, 4 will be execution only when condition is True
statement1,2,5,6 will execute, irrespective of condition is True or False**

if block of statements

Note: At a time either if block statements or else block statements will execute not both

3. if-elif-else:

=====

Syntax:

```
if condition1:
```

```
    Action1
```

```
elif condition2:
```

```
    action2
```

```
elif condition3:
```

```
    action3
```

```
else:
```

```
    action4
```

At a time only one action will/has to be executed, then we got if-elif-else

condition1 is True --> Action1 will be executed

condition2 is True -> action2 will be executed

condition3 is True --> action3 will be executed

if no condition is True then else block will execute

we dont have switch cases in python unlike other programming languages

nested if :

a if within another if or if withing another else

Syntax:

outer if

```
if condition1:
```

```
    statement1
```

```
    statement2
```

```
    if condition2:
```

inner if

```
        statement3
```

```
    else:
```

inner else

```
        statement4
```

```
else:
```

outer else

```
    stement5
```

inside
outer if

if condition1 is True all the statements including nested if-else will execute

if condition1 and nested if condition 2 is True then only statement3 will execute

Iterative/repetitive Statements:

If we want to execute a group of statements multiple times then we should go for iterative statements

Python supports 2types of iteratives

1. for loop
2. while loop

1. for loop: _____

If we want to execute some action for every element present in the some sequence(string, list, tuple, dict, range, set, frozenset, etc...)

Syntax:

```
for x in sequence:
    body(statements)
```

sequence --> string or any collection(list, set, tuple,etc.....)

x means each value in the sequence

body will be executed for every element in the given string

2) while loop:

If we want to execute a group of statements iteratively/repetitively until some condition is false, then we should go while loop

Syntax:

while condition: _____ group of statments that we want to execute when condition is True
body _____

Nested loops:

Sometimes we can take a loop inside another loop, which we call it as nested loops.

for i in range(1,5): outer for loop Iter1: i=1,j= 1 2 3 4

```
for j in range(1,5): --> inner for loop    Iter2: i=2, j = 1 2 3 4
```

print(j) --> inner for loop body Iter3: i =3, j = 1 2 3 4

Iter4: i = 4, j = 1 2 3 4

```

Iter4: loop body
Iter5: end the loop

```

Transfer statements:

1) break

We can use break statement inside loops to break the loop execution based on some condition

2) continue:

we can use continue statement to skip current iteration and continue the next iteration

3) pass:

pass is a keyword in python

In our python programming syntactically, if block is requires a block of statements.

but if we want to give empty block python will throw an error, using pass keyword we can create empty blocks

pass -> it is an empty statement

--> it is null statement

del statements:

del is a keyword in python

We can delete variables and objects which are pointing to mutable objects, but we cannot delete immutable objects

```
name = "kasi"
```

del name --> valid

del name[0] --> not valid because "kasi" is immutable object

String Datatype:
Accessing elements in the string:

1. using index value
2. using slicing operator

Syntax: s[beginIndex:endIndex:step]

beginIndex: From where we have to consider/cut the slice(substring)
endIndex: Where/when We have to terminate the slice(substring)
step --> incremented value while slicing

virat kohli

Note:

1. If we are not specifying beginIndex then it will consider from the beginning of the string
2. If we are not specifying endIndex then it will consdier up to the end of the string
3. If we do not specify step value by default increment value is 1



step value can be either +ve or -ve
if step is +ve then it should be forward direction(left to right) and we have to consider to begin to end-1
if step is -ve then it should be backward direction(right to left) and we hvae to consider begin to end+1

len() is a pre-defined/built-in function to find bnnumber of characters present in the string

Operators in string:

1. + operator for concatination
2. * operators for repition

membership operators also can be used to check existing of a substring or a character in the given string

Functions in string datatype:

Removing spaces from the string

1. rstrip() -> To remove spaces from right hand side
2. lstrip() -> To remove spaces from left side
3. strip() --> To remove spaces from both side

4. find() --> it returns the index of first occurrence of the given string, if it is not available then we will get -1

Note: by default find() can search total string, we can also specify boundaries

find(substring, beginIndex, endIndex)

5. index() --> It is exactly same as find() except that it will throw ValueError if the given substring is not found

6. rindex()

7. rfind()

8. count(substring) -> it find the number of occurrences of the given string, it will search through the entire string

count(substring, beginindex, endindex) --> it will search from begin index to endindex

9. replace(oldstring, newstring)

10. split(saperator) --> we can split the given string based on the delimiter/saperator. if we dont specify any saperator it will saperate the given string with space by default

saperator can be anything, it can be a symbol or it can be a substring also

s= "Learning python is very easy, python is open source programming language"

s.split("python")

it will return the list of the splitted string

["Learning ", "is very easy, ", "is open source programming language"]

11. join() --> we can join a group of strings(list or tuple) with respect to the given delimiter

students = ["kasi", "virat", "dhoni"] --> list type

this will returns the joined string

changing the case of a string:

12. upper() --> To covert all the characters to uppercase

13. lower() --> To convert all the characters to lowercase

14. swapcase()--> to convert all the lower case character to upper case and all upper case characters to lower case

15. title() --> To convert all the character to title case, first character of every word should be capital and other

chars should be small

kasi yedumati --> Kasi Yedumati

16. capitalize() --> Only first character will be converted to upper case and all other characters in lower case

checking the starting and ending part of the string:

17. startswith(substring)

18. endswith(substring)

To check type of characters present in a string:

=====

1. isalnum() --> Returns True if all the characters are alphanumeric (a to z, A to Z and 0 to 9)

2. isalpha() --> Returns True if all the characters are alphabets(a to z, A to Z)

3. isdigit() --> Returns True if the given string contains all the chacters are numbers only (0 to 9)

4. islower() --> Returns True if all the characters are in lower case (a to z)

5. isupper() --> Returns True if all the chactrers are in upper case(A to Z)

6. istitle() --> Returns True if the string is in title case(Kasi Yedumati, Virat Kohli)

7. isspace() --> Returns True if the string is containing only spaces

List Data Structure:
If we want to represent a group of individual objects or elements in a single variable or single entity where insertion is maintained and duplicates are allowed. then we should go for list.

insertion order is preserved
duplicated are allowed
heterogeneous values are allowed (different type of value)
list is dynamic --> we can add or remove items from the list
it is mutable

Python supports indexing for list, both negative and positive indexes are possible

10	20	30	40	50
-5	-4	-3	-2	-1
0	1	2	3	4

- Creation of list objects:**
1. `l = []` --> Empty list
 2. `l = ["pizza", "chocolate", "coke"]` --> create a list with items
 3. using eval with input function, we can create a list
 4. we can create list with `list()`
 5. with `split()` function --> `"kasi yedumati".split()` --> `["kasi", "yedumati"]`

Accessing elements of list:
we can access the elements of the list using index
we can access elements using slice operator

1. by using index:
=====

list follows both +ve and -ve indexing
+ve means from left to right
-ve index means right to left

2. by using slice operator
=====

`list[startIndex: endIndex: step]`

Traversing the elements in the list:
sequential access of each element in the list is called traversal

1. by using while loop
2. by using for loop

Functions of list:

1. `len()` --> return the number of elements in the list
2. `count(item)` --> it returns the number of occurrence of specified item in the list
eg: `list.count("pizza")`

3. `index()` --> returns the index of first occurrence of the specified item
eg: `list.index("pizza")`
Note: if the specified item is not present we will get `ValueError`, before going to use `index()` we have to check whether it is present or not
manipulate/modify the existing list

4. `append()` --> used to append/add item in the end of the list

5. `insert(position, item)` --> to insert item at specified index position

6. `extend()` --> to add list of items at a time to existing list, or to add multiple items at a time

7. `remove(item)` --> used to remove item from the list, if multiple occurrences are found then it will remove only first occurrence
Note: if the given item is not found in the list, it will throw `ValueError`, before using remove function it is recommended to check if item exists or not

8. `pop()` --> it removes and returns the last element of the list
`pop(index)` --> it removes and returns the indexed value in the list

<code>remove()</code>	<code>pop()</code>
1. to remove specified element	1. used to remove last element or specific index from list
2. It can't return any value	2. it returns removed value
3. if the specified element is not present, we get <code>valueerror</code>	3. if the specified index is not there, we get <code>indexerror</code>

Ordering elements of List:

9. `reverse()` --> to reverse items in the list

10. `sort()` --> used to sort elements in both ascending order and descending order

Note: to use `sort()`, compulsorily list should contain only homogeneous elements/data, otherwise we will get `TypeError`.

List aliasing and cloning/copying:
The process of giving another reference variable to the existing list is called aliasing

`x = [10, 20, 30, 40, 50]`
`y = x`

the problem with aliasing approach is by using one reference variable if we are changing content, the that modification will be affected to the other reference variable also

To overcome this problem we should go for cloning
The process of creating exactly duplicate independent object is called cloning.

we can implement cloning by using slice operator or by using `copy()` function

Using mathematical operators for list objects:
We can use + and * operators on list objects

Note: to use + operator compulsorily both arguments should be list objects, otherwise we get `TypeError`

Comparing list objects:
Whenever we are using comparison operation (`==`, `!=`) for list objects the following order should be considered

1. number of elements
2. order of elements
3. content of elements including case

Membership operators:
used to check whether element is there or not in the list
`in`
`not in`

Nested List:
A list within another list is called nested list

`a = [1, 2, 3]`
`b = [4, 5, 6]`
`c = [7, 8, 9]`
`n = [a, b, c]`
`n = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]`

List comprehension:
it is very easy and compact of creating list objects from any iterable (list, tuple, dict, range, string) based on condition

Syntax: `list = [expression for item in list if condition]`

Tuple:

Tuple is exactly same as list except that it is immutable. i.e once tuple is created we cant change its values

1. if our data is fixed, and never changes then we should go for tuple
2. Insertion order is preserved
3. duplicates are allowed
4. homogenous and heterogenous are allowed
5. we can perform only read only operations, i.e immutable

Tuple creation:

1. **t = ()** -> it is empty tuple
2. **t = (10,)** --> creation of single valued tuple
3. **t = (10,20,30,40,50)** --> creation of multiple valued tuple, paranthesis is optional
4. **by using tuple()** --> **tuple(10,20,30)**

eg: **l = [1,2,3,4]**

t = tuple(l)

Accessing elements of a tuple:

1. by using index
2. by using slice operator

Operators : + and * are for concatenation and multiple times

Important functions of Tuple:

1. len() --> to return number of elements in the tuple
2. count() --> to return number of occurrence of element
3. index() --> returns the index of given elements
4. sorted() --> to sort the elements in the tuple

sorted(t) --> ascending order

sorted(t, reverse = True)

5. min() and max():

to return minimum and maximum values

Tuple packing and unpacking:

We can create tuple by packing a group of variables

a=10

b=20

t=(a,b)

here a, b are packed into tuple object, this is nothing but tuple packing

Tuple unpacking is the reverse process of tuple packing

converting tuple into multiple variables

Note: At the time of tuple unpacking the number of variables and number of values should be same, otherwise we will get ValueError: too many values to unpack(expected 2, got 3)

Tuple comprehension:

Tuple comprehension is not supported by python, because it is immutable

t = (x**2 for x in range(10))

here we are not creating tuple object and we are getting generator object

Set Data Structure:

If we want to store group of elements in a single collection, where unique elements are needed and order doesnt matter

1. duplicates are not not allowed
2. unordered collection
3. indexing and slicing are not allowed for the set
4. homogenous and heterogenous values are allowed
5. set objects are mutable i.e once we creates object we can perform modifications
6. we can perform mathematical operations like union, intersection, difference, etc...

Creation of set objects:

`s = {10,20,30}` --> set with homogenous values

`s = {10,20,30,30}` --> whenever we attempt to have duplicate values, it wont throw any error but it will keep only one occurrence

`s = { }` --> type of this is set or dict ?

`set(any sequence)` -->

Important functions of set:

1. `add(x)` --> add item x to set
2. `update(x,y,z)` --> To add multiple items to the set, arguments here are not individual elements they are the data structures or sequence(range, list, set,etc..)
3. `copy()` --> returns the copy of set, it is a cloned object
4. `pop()` --> it removes and returns some random element from the set
5. `remove(x)` --> it removes specified element from the set
If the element is not present in the set we will key `KeyError`
6. `discard(x)` --> it removes the specified element from the set, if the element is not present it wont throw any error

What is the difference b/w `remove()` and `discard()` function ?

What is the diff b/w `pop()`, `removed` and `discard()` functions ?

7. `clear()` --> to remove all elements from set

Mathematical functions on the set:


1. `union()` --> we can use this function to return all the elements in both sets

Ex: `x.union(y)` --> x and y both are sets

`x={10,20,30,40}`

`y = {30,40,50,60}`

`print(x.union(y))` # {10,20,30,40,50,60}



2. `intersection()` -> returns common elements present in both x and y

`x.intersection(y)` --> # {30,40}



3. `difference()` -> returns the elements present in x but not in y

`x.difference(y)` -> {10,20}

`y.difference(x)` -> {50,60}

4. `symmetric_difference()` --> returns elements present in either x or y but not in both

`x.symmetric_difference(y)` --> {10,20,50,60}

Membership operators(`in`, `not in`) --> we can use membership operators in set as well, to check if given item is present in the set or not

Set comprehension:

set comprehension is possible in python

syntax: {expression for i in sequence if condition}

`{x**2 for x in range(10)}`

`{x for x in range(10) if x%2==0}`

Dictionary Data structure:
We can use list, tuple and set to represent a group of individual object as a single entity

If we want a group of objects as key-value pairs then we should go dictionary

Eg:
rollno
name
phonenumber
address
ipaddress -> domainname

Duplicates keys are not allowed but values can be duplicate
heterogenous objects are allowed for both key and value
insertion order is not preserved
dictionaries are mutable and dynamic
indexing and slicing are not applicable

How to create dict:
d = {} --> empty dict
d = dict() --> empty dict
d = {"contactnumber": 456789}

emp_data = {1234: "kasu", 1122: "ravi", 1123: "raju"}

keys
d = {key:value, key:value}

Access elements from dict:
we can access data by keys
Ex: d["contactnumber"]

if the specified key is not available then we will KeyError

We can prevent this problem by checking whether key is already available or not by using has_key()

No, dict.has_key() is not available in Python 3. [1, 2]

Update dicts:
d[key] = value
if the key is not available then a new entry/item will be added to the dictionary with the specified key-value pair
If the key is available then it will update the value to the existing key

how to delete elements from dictionary:
del d[key]

it deletes entry associated with the specified key
if the key is not available then we will keyerror

clear() --> to remove all entries from dictionary
del d --> to delete total dictionary object, after this we cannot even access d

len() --> returns the number of items in the dictionary
pop(key) --> it removes the entry associated with the specified key and returns the corresponding value
if the specified key is not available then we will get key error

popitem() --> it removes random key-value pair from dictionary and returns it

keys() --> to return all keys from dictionary in a comma separated values
values() --> to return all values from dictionary
items() --> it returns the list of tuples representing key-value pairs

copy() --> to create exactly same copy of another dictionary
d1 = d.copy()

setdefault(k,v) -->
if the key is already available then this function returns the corresponding value
if the key is not present then the specified key-value will be added to the dictionary

d.update(x) --> all items present in the dictionary x will be added to dictionary d

nested dictionary:
a dictionary within another dictionary is called nested dictionary.

d = {
"message": "success",
"payload": {"attendance": 5},
}

d is called outer dictionary
message and payload are the keys for outer dictionary
success and {"attendance": 5} are the values for outer dictionary

{"attendance": 5} is the inner dictionary
attendance is the direct key of inner dict
5 is the value of inner dictionary

How to get attendance count 5 from above dictionary
inner_dict = d.get("payload") -> {"attendance": 5}
inner_dict.get("attendance") --> 5

Dict comprehension:
Comprehension concept is applicable for dictionaries also

to print squares of each numbers and store them as key and value, where key is the actual number and value is the squared value
Ex: {1:1, 2:4, 3:9, 4:16, 5:25}

squares = {x:x*x for x in range(1,6)}
{1:1, 2:4, 3:9, 4:16, 5:25}

Notes:

If a group of statements repeatedly required then it is not recommended to write these statements everytime saperately. we have to define these statements in a single unit and we can call that unit any number of time based on our requirement without rewriting.

This unit is nothing but function.

The main advantage of functions is code reusability.
we can have a control of what block/group of statments to execute and what not to execute.

Python supports 2 type of functions

1. Built/Pre-defined in functions

The functions which are coming along with python software automatically, are called built-in functions

Eg:

```
len()
find()
index()
id()
append()
input()
eval(), etc.....
```

2. User/Programmer defined functions:

The functions which are developed by programmer explicitly according to business requirements, are called user defined functions

Syntax:

```
def function_name(parameter1, parameter2, ....):
    block of statement(s)
    return value
```

def -> is a predefined keyword, used to defined a function, is is mandatory to define any function

function_name -> to provide snakecase, meaningful name for the function, using which anybody can call

parameters are the inputs to the functions, if a function contains parameters, then at the time of calling, compulsorily we should provide values otherwise, we will get error

block of statemets -> it is the actual logic or operation that we are performing as per business need

return -> is a keyword to return the final output from that function, its optional to return value

Ex:

```
def addition(a,b):
    c = a+b
    return c

addition(10,20)  _____ calling function with parameters
```

If a function is not returning anything, then it will be None

Types of arguments:

there are 4 types of arguments

1. positional arguments
2. keyword arguments
3. default arguments
4. variable length arguments

1. positional arguments:

These are the arguments passed to a function in correct positional order.

```
def sub(a,b):
    print(a-b)
sub(100,200)
sub(200,100)
```

The number of arguments and position of arguments must be matched, if we change the order output will be different

if we change number of arguments we will get a TypeError

2. keyword arguments:

we can pass arguments values by keyword i.e by parameter name

here the order of arguments is not important but number of arguments is important

3. Default arguments:

Sometimes we can provide default values for our positional arguments

If user/caller doesn't pass value, it by default assigns some value

```
def wish(name="guest");
    print("Hello", name, "good morning")
```

```
wish("Virat")
wish()
```

If we dont pass any name then only default value will be considered

Note: after default arguments in the function, we should not take any non default arguments

4. Variable length arguments:

Sometimes, we can pass variable number of arguments to our function and values are dynamically changes.

those kind of arguments we call it as variable length args

```
def sum(*n):
```

We can also declare keyword variable length arguments also for this we have to use **

Case study:

```
def f1(a,b, c=4, d=8):
    print(a,b,c,d)
```


1. f1(3,2) --> 3 2 4 8
2. f(10,20,30,40) --> 10 20 30 40
3. f1(25,50,d=100) -> 25 50 4 100
4. f1(d=2, a=3, b=4) --> 3 4 4 2
5. f1() --> invalid (missing 2positional arguments a and b)
6. f1(c=10,d=20,30,40) --> invalid becuase positional arguments follows keyword argument
7. f1(4,5,b=6) --> invalid: f1() got multiple valudes for the same argument b
8. f1(4,5,c=5,e=6) --> invalid

Notes: Function, Module and Library

1. a group of lines with some name is called a function

2. a group of functions saved in a python file, is called module

3. a group of modules is nothing library



Types of variables:

1. global variables

The variables which are declared outsidie the function are called global variables.

These variables can be accessed in all the functions of that module

2. local variables:

The variables which are declared inside a function are called local variables

local variables are available only for the function in which we declared it, i.e outside the function we cannot access

global keyword:

We can use global keyword for 2 purposes:

1. to declare global variable inside the function
2. To make global variable available to the function, so that we can perform required modifications

Recursive functions:

Factorial of 2 : 2*1 = 2
Factorial of 3 : 3*2*1 = 6
Factorial of 4: 4*3*2*1 = 24
Factorial of 5: 5*4*3*2*1 = 120

we have to multiple each value from n to 1 and final value will become factorial
n =5
fact = 1
for i in range(1,n+1): 1,2,3,4,5
 fact = fact*i # we are multiple every value from 1 to n and storing into fact variable
print(fact)

Iteration1: 1*1 = 1
Iteration2: 1*2 = 2
Iteration3: 2*3 = 6
Iteration4: 6*4 = 24
Iteration5: 24*5 = 120

A function that calls itself is known as recursive function

factorial(n) --> n*factorial(n-1)

- 1. base case --> where you have to stop the recursion
- 2. recursive case --> calls itself with a smaller input

Advantages:
1. we can reduce length of the code and improves readability
2. We can solve complex problems very easily

def factorial(n):
 if n==0 or n==1:
 return 1
 return n*factorial(n-1)

factorial(5)

Iteration1: return 5*factorial(4)
Iteration2: return 5* return 4*factorial(3)

Iteration3: return 5*4*3*factorial(2)

Iteration4: return 5*4*3*2*factorial(1)

Iteration5: return 5*4*3*2*1

return 120

Fibanocci series:

0 1 1 2 3 5 8 13 21.....

0 1
0 + 1 = 1 Iteration1
1 + 1 = 2 Iteration2
1 + 2 = 3 Iteration3
2 + 3 = 5 Iteration4
3 + 5 = 8

Sum of recent two values will be the next number in fibanocci series

first_value=0
second_value=1
fibanocci_series = []
n = 10 # until 10 i want to generate fibanocci
for i in range(2, n+1):
 fibanocci_series.extend([first_value, second_value])
 next_value = first_value+second_value
 first_value = second_value
 second_value = next_value

Lambda functions:

Sometimes we can declare a function without any name, such type of nameless functions are called ananymous functions or lambda functions

The main purpose of anonymous function is just for instant use(i.e one time usage)

Syntax:

we will define lambda function using lambda keyword

lambda argument_list: expression

Norma function

def function_name(arugment_list):
 expression

By using lambda expression we can write any concise code, so that readability of the program will be provided

Note:

- 1.Lambha functions internally returns the expression, we are not required to write return statement explicitly
- 2. Sometimes we can pass function as argument to another functon, in such cases labmda functions are best choice

We can use lambda function very commonly with filter(), map() and reduce() functions, these functions expect function as an argument

filter() functions:

=====

We can use filter() to filter values form the given sequence based on some condition

filter(function, sequence)

where function argument is responsible to perform conditional check

sequence can be list or tuple or string (eg: employee list dictionary, numbers list, etc...)

map() function:

For every element present in the given sequence, apply some functionality and generate a new element with the modified.

syntax:

map(function, sequence)

function to be applied to every element in the sequence

reduce() function:

reduce function is to reduce sequence of elements into a single element by applying some functionality with specified function

reduce(function, sequence)

Function Aliasing:

For the existing function we can give another name, which is nothing but function aliasing.

Nested functions:


We can declare a function inside another function, is called nested function.

def outer():
 block of statements
 def inner():
 block of statements
 block of statements

outs
ints

Function Decorators:

Decorator is a function which can take a function as argument and extend its functionality and returns a modified version of that function




The main objective of decorator is we can extend the funcctionality of existing function without modifies that function

Generators:

I have 1000 members waiting in the bank -->
I have collect all 100 members bank accounts and then process some loan
[list of bank accounts]

Generators is a function which is responsible to generate a sequence of values

We can write generator functions just ordinary functions, but its uses yield keyword to return values



```
def function_name():  
    block of statements  
    yield # using yield keyword
```

(x for x in range(10)) --> another way to create generator

List/list comprehension	generator (yield)
It is eager and build all values at atime In memory all items will be loaded	On demand generates values(lazy) In memory only one value at a time
[x for x in range(5)] we can access using index	(x for x in range(5)) or function using yield we use next/for loop
best for small data and reuse	best for large data and one time usage

Note: Calling a generator function does not run the body yet..... it return the generator object, Values appear only where you iterator using for or next()

yield vs return
return:
It ends the functions
it returns one value or none at a time
once return statement is executed function is over

yield:
it pauses and resumes on next request
it return one value per pause; many over time
once yield is executed, generator still keeps its state

Modules and Packages:

Function --> a named group of statements

Module :

A module is one python file (.py) that holds related names: variables, funcitons, classes

Package/Library:

A package is a folder of modules, A **__init__.py** (it can be empty) tells python: this folder is importable or python specific package

Without having modules and package, your script will contain lakhs of lines of code. it is hard to read, hard to reuse, impossible to share.

Recommendation to create a module or package:

1. you have to give meaningful name and you have to follow snake case (abc_xyz)
2. you have to keep related items only into that module

If you want to access or use members(variables or functions) of module in our program then we should import that module

import modulename

renaming a modfule at the time of aliasing (module aliasing)

import modulename as mn

various possibilities of import

import modulename ---> import everyhting from modulename (one module)

import mod1, mod2 -> importing two moduels and all theri members

import modulename as md --> aliasing

import mod1 as m1, mod2 as m2; --> importing two modules with aliasing

from module1 import member1, member2 -> import only two members from module1

from module1 import * --> imporintg everything from module

from module1 import member1 as m1 --> import member1 from module1 and aliasing m1 for member

Finding members of module by using dir() function:

python provides builtin function dir() to list out all members of current module or a specific module

dir() --> to list out all the members of current module

dir(modulename) -> list out all members of given module

Note: when you are importing a module or members, there is a logical existance of them in the current module

The special name **__name__** :

For every program, a special variable **__name__** will be added internally.

This variable stores information regarding whether the program is executed as an individual program or as module

If the program executed as an indivudal program then the value of this variable is **__main__**

if the program executed as a module from some other program then the value of this variable is name of that module

Hence, by using **__name__ variable we can identify whether the program is executed as a module or execute directly**

Packages:

It is an encapsulated mechanism of group of modules into a single unit

Any folder or directory contains **__init__.py** file, it is considered as package

A package contains sub packages also.

Advantages:

1. we can resolve naming conflicts
2. we can idetify components easily
3. it improves modularity of the application and readabilty

from pack1.module1 import membe1

from pack1.module1, pack2.module2 import *

recommended packages name:

com.companyname.functionalname.feature

com.ibm.loan.validators.email_validators.py

com.ibm.loan.massagers.registration_input_massager.py

com.ibm.netbanking.....

OOPS:
=====
Object oriented programming/principles

Functional programming disadvantages:

1. Anyone can corrupt your dictionary
2. related data/properties and behaviour are scattered. it is not combined as a unit
3. Adding new properties(like college, email, mobilenumber) and behaviour(is_pass()) means hunting functions everywhere within the project
4. As the project grows, modifying data models is very hard and hard to test
5. If i want to control my data model, or i want hide some properties there is no feature in functional programming (_balance, password)

1. class
2. object
3. encapsulation
4. inheritance
5. polymorphysm
6. dynamic binding

1. class:
a class is a keyword, using which we can develop **user defined data structure** -->
It is a comibation of properties and behaviour into a single unit

Syntax:

```
class class_name:  
    // initialise properties  
    // methods //behaviour
```

self is a keyword which always refers current object, using which we can access current object properties and methods

object:
object is an instance of a class, when an object is created a memory will be allocated for that object
we are filling the form

syntax:
object_name = class_name(prop1, prop2, prop3,...) # object creation
using object_name we can call its methods and variables

whenever we are creating an object, __init__ constructor will be called and initialise data members of that object

Difference between constructor(__init__) and method:

__init__ constructor	method
1. its always __init__ name	1. you can give your own functional name
2. it runs automatically whenever we create an object	2. it will run only when we explicitly call it with its name
3. This will be called only once per obj	3. it will be called as many times as we call
4. declares and initialized object	4. used to write business logic

Note:
self is mandatorily passed as first argument, otherwise we get an error

Type of variables in OOPS:

1. instance variables (object level variable)
2. class(or static) variables (clas level variable)
3. local variables (method level variable)

1. instance variables:
If the value of a variable is varied from object or object, then such type of variables are called instance variables becuse for every object a saperate copy of instance variable will be created

Where we can declare instance variable:

1. inside constructor by using self variable
2. inside instance method by using self variable
3. outside of a class by using object reference

We can access instance variable using object reference or self keyword

Static variable:
if the value of a variable is not varied from object to object, such type of variables we declare it as static variable
we can declare them directly within class but not methods or constructor.

We can access them using class name or by object reference

Difference between static vs instance variable:
static is one per all objects i.e one per class
instance variable is one copy for every object, i.e every object a new copy will be created

static variables can be accessed both using class and object reference
instance variables can be accessed with only through object reference

Type of methods in OOPS:

1. instance method
2. class method
3. static method

1. instance method :
inside a method implementation if we are using instance varaibls then such type of methods are called instance methods

inside instance method declaration, we have to pass self variable

```
def method_name(self, param1, param2,...):  
    block of statments
```

we can access instance methods using object reference or self keyword
self keyword we use to access instance variabels or methods inside the class
outside the class if we want to accesss instance method we have to use object reference

2. class methods:
inside method implementation, if we are using only class or static variables(like college_name, company_name, etc..) then that method we can declare it as class method

we can declare class method explicitly by using @classmethod decorator

```
@classmethod  
def method_name(cls):  
    block of statements
```

we can access class method using class name or object reference also

3. static methods:
In generally these methods utility methods
Inside these methods we wont use any class or instance variables

here we wont provide self or cls argument at the time of declaration

we can declare static method explicitly using using @staticmethod decorator
We can access static mehtod using class name or object rference


Inheritance:
Problemment statements:
if we are building an application for a bank, we may have different type of accounts with similar features

If we dont have inheritance concept we tend to write duplicate code iin all different classes
1. deploy/withdraw/ balance check all these behaviours are written multiple times --> duplication
2. code is redundant and reused
3. it is unnecessary memory usage

Inheritance is a principle that says, do not copy paste same behaviour from one class to another, I

Instead, inherit features from one class to another class, so that you can reuse

The process of inheriting features from one class to another class is nothing but inheirntance
--> class from where we get features is called parent/super class
--> class from wehere we are pulling features is called child/sub class class



Parent/Base/Super classes --> BankAccount, Person
Child/Derived/Sub class --> SavingsAccount, CurrentAccount, Employee


IS-A relationship --> SavingAccont IS-A BankAccount
Employee IS-A Person

super() --> super() is a pre-defined function using which we can called parent class methods or parent class constructor

Types of inheritance:

1. Single inheritance
2. Multi-level inheritance
3. Hierarchial inheritance
4. Muiltple inheritance
5. Hybrid inheritance
6. Cyclic inheritance


1. single inheritance:
A inheritance which has only one parent class and one child class is nothing but single inheritance



Person is one parent
Employee is one child

2. Multi-level inheritance
A chain: child inherits from parent , parent inherits from grandparent

A multi level inheritance contains, one parent and one child and multiple sub childs/parents




Method overriding:
the process of changing content of a method between parent class and child class is nothing butt overriding

here, method name and signature should be exactly, only definition should be different


if signature is different, that will be treated as new method

Note:
By default, all the class inherits object class, i.e predefined class
What is the super class for all the classes ? object


3. Hierarchial Inheritance
It contains one parent, many specialised children, this is nothing but heirarchial inheritance



4. Multiple inheritance
one child, two or more parents, this is called multiple inheritance



5. Hybrid Inheritance:
Combination of any two or more existing inheritances is nothing inheritance
Comibation of single inherianc,e multi level, multiple or hierarchial



Relationships in inheritance:

1. Composition(HAS-A relationship)
2. Inheritance (IS-A relationship)

1. HAS-A relationship:

Car HAS-A Engine
Employee Has a Laptop
Order has a Notifier

By using **class name** or **by creating object**, we can access members of one class inside another class is nothing but composition(HAS-A relationship)


Polymorphysm:
=====
Poly --> Many
Morphysm --> forms

Without using polymorphysm, if we want to support diffferent type of payment modes, follwoing is the approach

```
#
def checkout(payment_type, amount):
    if payment_type == "upi":
        print("Paid via: UPI"+ "amount: "+str(amount))
    elif payment_type == "card":
        print("Paid via: CARD"+ "amount: "+str(amount))
    elif payment_type == "cash":
        print("Paid via: CASH"+ "amount: "+str(amount))
    else:
        print("Unknown payment type")

checkout("upi", 100)
checkout("card", 100)
checkout("cash", 100)
we are taking a decision by simply matching magic string
```

- Disadvantages of this approach:
- 1. Every new payment mode needs a new elif condition
 - 2. easy to miss a branch/block (silent "unknown")
 - 3. business logic and type-switching live in one growing function



```
"""
class UPI:
    def pay(self, amount):
        print("Paid via UPI pay: " + str(amount))

class Card:
    def pay(self, amount):
        print("Paid via CARD pay: " + str(amount))

class Cash:
    def pay(self, amount):
        print("Paid via Cash pay: " + str(amount))

def checkout(payment_type, amount):
    payment_type.pay(amount)

checkout(UPI(), 100) # customer is calling checkout function after selecting payemnt mode
checkout(Card(), 100)
checkout(Cash(), 100)
checkout("kasi", 200)
```

this is nothing but duck typing(same method name, no shared parent(no inheritance))
Note: Polymorphym can be achieved using duck typeing and method overrdin using inheritance
Recommended approach is overrrding methods using inheritance

Method overloading in python :
If a method name is same but parameters are different, then we call it as method overloading

Method overloading can happen in a same class

```
def add(a, b) --> adding two values
def add(a,b,c). --> addging three values
def add(a,b,c,cd) --> adding four values
```

method name is same --> add
parameters are different
overloading

unlike java-style method/constructor overloading(same name, different signatures) is not supported in python.
the last defintion is always a winner

instead, we can use *args parameter to any number of args at runtime

__str__ special method:
=====
Whenever we work on projects, and want to debug the data of the objects
by default if we print object, it will print default text of the object like <__main__.Student object at 0x3456789)

instead of that if we override __str__ method and return that string you want to print, that will be printing

Note: you shouldn't print any security information in the logs, you shouldnt return any security information in the __string__

Encapsulation:

The processing hiding sensitive information by binding data and its related methods inside the same class
So that, outside code should not poke the raw fields, it must go through public methods(deposit, withdraw) that enforces the rules
If we want to expose fields to external classes or outside the class, we can name them without _ or __ (Eg: name)
if we want to keep fields private, we have to make then either with _ or __ (Eg: __ balance)
If we make fiedls with single _ then we call its protected variable
If we make fields with double __ then we call its private

Key takeaways:
_balance = polite hands off --> python does not stop you
__balance = renamed to __ClassName__balance --> this stops accidental access
this will provide privacy to the data
if somebody want to change the data, they should use deposit or withdraw

@property is an indicator that this is protected fields, so accidental access should be controlled

Abstract method:
=====

Sometimes we dont know about implementation, still we can declare a method. such type of methods are called abstract methods

i.e abstract methods has only declaration but not implementation

in python we can declare abstract method by using @abstractmethod decorator

Eg:
from abc import *
@abstractmethod
def m1(self): # declaration
 pass # no implementation

@abstractmethod decorator present in abc module, hence compulsorily we should import abc module, otherwise, we will get error

Abstract class:
Sometime implementation of a class is not complete, such type of partially implemented classes are called abstract classes
Every abstract class should be derived/inherited from ABC class which is present abc module

We cant create object for abstract class which has abstract methods
If we want to block anyone to create an object, we should inherit our class with ABC and write abstract methods with @abstractmethod

Conclusion:
if a class contains atleast one abstract method and if we are extending ABC then instantitaion is not possible
Note: if we are inheriting abstract classes, it is mandatory that you provide body for all abstract methods for that class,
otherwise child class also will be treated as abstract class and we cant create object for that class
-> An abstract class can contain both abstract and normal methods, normal method are the shared methods across children
--> ABC alone doesnt block objects
--> @abstractmethod along does not block objects
--> Both together block objects, this is highly recommended

Interface in python:
=====

In generally if an abstract clas contains only abstract methods such type of abstract classes are called interface
All the rules will be applicable to interface also as abstract classes

Exception Handling:

three type of errors:

1. Syntax errors: If we miss any syntactical mistakes, python cannot even read the program
syntax errors, we need fix our syntax to run the program

2. Logical error: The below program runs and finishes properly, the answer is just wrong.

GST 18% coded as 8%,
bill split among your fiends by you devide by friends+1

```
price = 1000
gst = price * 0.08 # gst
```

3. Runtime error(Exception):
The program started, then hit a problem it cannot solve: "abc" to int,
devide by zero, missing file, then pythhon raised a runtime error that we call it as Exception.

If nobody handles it, you get a traceback and the program stops intermitemently.

What is an exception:

A runtime error packaged as an **object** with a type (ValueError, ZeroDevisionError, FileNotFoundError, etc..) and a **message**, if nobody handly it, python stops and prints the traceback

Exception handling, catching the error that is thrown at runtime and convert system generated error messages to user friendly error message is nothing but exception handling

there are four keywords in python to handle exceptions/runtime errors

1. try
whatever the risky code is there, we need to keep that kind of risky code inside try block (eg:10/0, int("abc"))

2. except :
This is the error recovery block where we catch the exception at runtime.
If any erorr comes or any failures happend, do this instead of crashing the system

we can write any number of except blocks per one try block.
python uses the first match, so always sepcifiy the type of exception in except block, whichever the type is matching at runttime that exception block be will be executed

-> at a time only one except block will be excecuted
-> if we dont know exactly what type of error might come at runtitime, you create one except block with Exception, Exception is superclass for all the exception classees
--> it is always recommended keep Exception type except block at the last

3. else
4. finally