ResearchNote

Kyeong Sun Kim

1/1/23

Table of contents

Contents

- 1 Centrifuge Test
- 2 FE Analysis
- **3 Ambient Vibrations**

Part I Centrifuge Test

1 Background

- 1.1 Limitations of the Centrifuge Test
- 1.2 Failures due to scour

2 Test Setup

This is a book created from markdown and executable code.

2.1 Background

3 Material Properties

This is a book created from markdown and executable code.

3.1 Background

4 Scale Law

This is a book created from markdown and executable code.

4.1 Background

5 Analysis

This is a book created from markdown and executable code.

5.1 Background

6 Verification

This is a book created from markdown and executable code.

6.1 Background

7 References

This is a book created from markdown and executable code.

7.1 Background

Part II FE Analysis

8 Background

This is a book created from markdown and executable code.

8.1 Background

9 Numerical Setup

This is a book created from markdown and executable code.

9.1 Background

10 Material Calibration

This is a book created from markdown and executable code.

10.1 Background

11 Verification

This is a book created from markdown and executable code.

11.1 Background

12 Analysis

This is a book created from markdown and executable code.

12.1 Background

13 Validation

This is a book created from markdown and executable code.

13.1 Background

14 References

This is a book created from markdown and executable code.

14.1 Background

Part III Ambient Vibrations

15 Background

This is a book created from markdown and executable code.

15.1 Background

16 Test Setup

This is a book created from markdown and executable code.

16.1 Background

17 OMA

This is a book created from markdown and executable code.

17.1 Background

18 Statistical Analysis

This is a book created from markdown and executable code.

18.1 Background

19 Damage Detection

This is a book created from markdown and executable code.

19.1 Background

20 Validation

This is a book created from markdown and executable code.

21 References

This is a book created from markdown and executable code.

Part IV Proposal

22 Meeting Note

22.0.1 Soil Choice

- · Material model choice
 - Mohr-Coulomb Model
 - Hardening Mohr-Coulomb Model
 - Cyclic SANISAND Model
- Young's modulus and Poisson ratio
- Critical State Properties
- Nonlinear Parameters
- cohesion and tensile properties
- Cycllic strength parameters

22.0.2 Structure Choice

- Rigid or Linear Elastic Material
- Young's modulus and Poisson ratio
- Fatigue properties (SN Curve)
- Hardness properties (BHN)

22.0.3 SSI Choice

- Interface friction coefficient
 - Horizontal / Vertical
- Modulus of subgrade reaction of soil
 - Horizontal / Vertical / Rotational

22.0.4 Loading Choice

Actuators

Static vs Cyclic

Vibrations

Forced vs Ambient FFT vs FDD and EFDD

For experimental investigation, means and location of excitation, the density of the measurement point grid, the sampling rate and the length of time window must be optimized for good quality results.

Forced:

good:

- provides "scaled" results
- excites all (broad) range of natural frequencies
- known force and mass, which allows FE updating

bad:

- artificial vibration required
- first mode can be too low to be excited

Ambient:

good: - no artificial excitation

- better for low frequency (large and complex structures) (need sensors of the force balance type instead of piezoelectric sensors) f < 1 Hz
- cheap (no shaker)
- can be performed without embarrassing normal user (stopping traffic or humans)

bad:

- lack of stationarity (not controllable). scatter may occur.
- not all natural frequency may be excited
- non-linearity of structure itself (assumption of cross section). small movements in different locations (GPSS technique to syncronize time)
- requires long cables

- requires reference points >1 (3D or 1D sensors)
- Time window must be selected > $1000\sim2000$ times f_n
- requires manual techniques for FE updating

22.0.5 Software Choice

- ABAQUS
 - UMAT implementation
- Plaxis 3D
- ARTeMIS Modal Pro
 - Operational Modal Analayis
 - Structural Health Monitoring
- SAP 2000
 - natural frequency for 3D structure on Winkler foundation

22.1 Verification Plan

- Winkler model limitations
- Mass-spring model limitations
- Accelerometer locations
- Sensor Sensitivity and Capacity
- Clear damage detection control chart

•