

cheg325 hw1 q2

AUTHOR
kyle wodehouse

PUBLISHED
February 14, 2025

grabbing the fit parameters from the paper sandler references and quickly plotting the curve

also note that the equations from the paper are given in the form


$$\Delta_{\text{mix}}H = x(1-x)(h_0 + h_1(1-2x) + h_2(1-2x)^2)$$

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

def DeltaH_mix(x2, params):
    h0, h1, h2 = params
    return x2 * (1 - x2) * (h0 + h1 * (1 - 2*x2) + h2 * (1 - 2*x2)**2)

params_dict = {
    'H': (230, 578, 409),
    'F': (-1984, 1483, 1169),
    'Cl': (-2683, 929, 970),
    'Br': (-3087, 356, 696),
    'I': (-4322, -161, 324)
}

fig, ax = plt.subplots(figsize=(10,8), dpi=500)
for name in params_dict.keys():
    x = np.linspace(0,1,1000)
    y = DeltaH_mix(x, params_dict[name])
    ax.plot(x, y, label=name)
ax.legend()
ax.grid()
ax.set(xlim=(0,1), xlabel='$x_{C_6F_5Y}$', ylabel='$\Delta_{mix}\{H\}$');
```




the derivative of the equations the paper provides are in this form

$$\frac{d}{dx_2}\Delta H_{\text{mix}} = (1-2x_2)(h_0 + h_1(1-2x_2) + h_2(1-2x_2)^2) + x_2(1-x_2)(-2h_1 - 4h_2(1-2x_2))$$

```
def d_DeltaH_mix(x2, params):
    h0, h1, h2 = params
    term1 = (1 - 2*x2) * (h0 + h1 * (1 - 2*x2) + h2 * (1 - 2*x2)**2)
    term2 = x2 * (1 - x2) * (-2 * h1 - 4 * h2 * (1 - 2*x2))
    return term1 + term2

fig, ax = plt.subplots(figsize=(10,8), dpi=500)
colors = plt.cm.tab10(np.linspace(0, 1, 5))

for color, name in zip(colors, params_dict.keys()):
    x = np.linspace(0,1,1000)
    y = d_DeltaH_mix(x, params_dict[name])
    ax.plot(x, y, label=name, color=color)
ax.legend()
ax.grid()
ax.set(xlim=(0,1), xlabel='$x_{C_6F_5Y}$', ylabel='$\Delta_{mix}\{H\}$', title='plot of de
```



Now we can do all the calculations needed for this problem by evaluating the derivatives at the desired points and use this equation

$$\bar{H}_{C_6H_6} - \underline{H}_{C_6H_6} = \Delta_{\text{mix}}H - x_{C_6F_5Y} \frac{\partial \Delta_{\text{mix}}H}{\partial x_{C_6F_5Y}}$$

and then this equation for C_6F_5Y

```
def differences(x, params: tuple):
    """
    returns the difference between the partial molar properties and molar properties
    inputs:
    - x: mole fraction C6F5Y (float or nparray)
    - params: the h0, h1, h2 fit parameters (tuple)
    returns:
    - (1) difference for benzene
    - (2) difference for the C6F5Y
    """
    h0, h1, h2 = params
    derivative = d_DeltaH_mix(x, (h0, h1, h2))
    delta_mix = DeltaH_mix(x, (h0, h1, h2))
    return (delta_mix - x * derivative, delta_mix + (1 - x) * derivative)

composition = 0.333
benzenes, c6f5ys = [], []
for mixture, params in zip(['H', 'F', 'Cl', 'Br', 'I'], params_dict.keys()):
    diff_benzene, diff_c6f5 = differences(composition, params_dict[params])
    benzenes.append(diff_benzene)
    c6f5ys.append(diff_c6f5)

df = pd.DataFrame({'composition':composition,
                   'Y':['H', 'F', 'Cl', 'Br', 'I'],
                   'benzene difference': benzenes,
                   'C6F5Y difference':c6f5ys})

composition = 0.667
benzenes, c6f5ys = [], []
for mixture, params in zip(['H', 'F', 'Cl', 'Br', 'I'], params_dict.keys()):
    diff_benzene, diff_c6f5 = differences(composition, params_dict[params])
    benzenes.append(diff_benzene)
    c6f5ys.append(diff_c6f5)

df2 = pd.DataFrame({'composition':composition,
                    'Y':['H', 'F', 'Cl', 'Br', 'I'],
                    'benzene difference': benzenes,
                    'C6F5Y difference':c6f5ys})

df = pd.concat([df, df2])
```

benzene differences !!

```
df.pivot(index='composition', columns='Y')['benzene difference']
```

Y	Br	Cl	F	H	I
composition					
0.333	-199.082911	-17.835391	184.271225	177.887603	-473.017385
0.667	-1424.003857	-1200.267830	-836.973728	127.043932	-1994.638285

C6F5Y differences !!

```
df.pivot(index='composition', columns='Y')['C6F5Y difference']
```

Y	Br	Cl	F	H	I
composition					
0.333	-1529.168499	-1474.700279	-1275.061265	-43.700907	-1947.077871
0.667	-330.776461	-361.496370	-364.328594	-35.929454	-413.459347

```
# this is filler text. ignore please.
```