

Contracts as Task Skeleton: Externalizing Implicit Obligations for Bounded LLM-Agent Determinism

Abstract

Contract-driven harnesses make low-cost language-model agents inspectable on bounded tasks by externalizing obligations into an explicit contract stack: task specifications, bounded memory, evidence bundles, output contracts, stage gates, execution traces, and deterministic validators. We show that in the studied task family —controlled state mutation under a frozen protocol —the binding constraint on agent determinism is the completeness of this contract, not the intelligence of the model: across four above-floor models and one below-floor model, a frozen contract produced 40/40 strict-conforming runs on three above-floor models, exposed a repairable paraphrase vulnerability in a fourth (GLM-4-9B, 30/40), and produced 0/40 on the below-floor model, with the same model moving from 0/40 to 40/40 over four repair-loop iterations without retraining or prompt-tuning. This claim is grounded in a single task family; we do not claim universality. The contributions are the methodology (contract stack, repair-loop protocol, fixture-driven admission, model-admission probes) and an empirical demonstration that reliability can be accumulated as a regression-testable asset rather than re-derived per prompt. A paired oracle-coupling audit (§4.14) additionally bounds a construct-validity threat to the deterministic evaluators themselves: for the audited task family, an answer-coupled reference compiler breaks under answer deletion and poisoning (28/28 each), while a public-input compiler re-derives byte-identical contracts (28/28) with no runtime access to the answer label, and remains invariant across 112/112 metamorphic conditions and fail-closed across 55/55 authority perturbations. We release the framework-agnostic reference core (reference-core/contract_core.py), ContractBench-v1 (task family and evaluator release), and the contract evolution ledger as reproducibility artifacts.

1. Introduction

Agent systems are now used for ordinary productivity work: initializing projects, extracting structured information, synthesizing evidence, preparing plans, updating documents, and coordinating multi-step workflows. In these settings, reliability is often attributed directly to model capability. If an agent loses a constraint, cites no evidence, skips a stage, or reuses stale context, the common explanation is that the underlying model is not strong enough.

That explanation is sometimes correct, but it misses a system-design problem. Many productivity tasks contain obligations that can be stated before generation starts: which evidence may be used, which state is known or unknown, which actions are blocked, which fields must be present, which claims require citations, and which stage gate prevents a final recommendation. If those obligations stay implicit, the model must infer and retain them while generating. If they are represented as contracts, part of the reliability burden moves from the model into the surrounding system.

We call this approach contract-driven harness engineering. It uses task specifications, bounded memory, evidence bundles, output contracts, workflow gates, validators, and trace requirements to constrain agent behavior. Low-cost models are not generally equivalent to strong models. The question studied here is smaller: which parts of agent reliability become less dependent on unconstrained generation once task obligations are made inspectable?

The study separates three problems that are often collapsed in agent evaluation. Model capability is the model’s ability to reason, follow instructions, and recover from ambiguity. Harness specification is the system’s ability to state task obligations, admissible evidence, known and unknown state, output structure, and blocked actions. Workflow composition is the ability to preserve those obligations across steps, tools,

and state transitions. The current evidence covers harness specification and bounded composition. It does not cover open-ended workflow autonomy.

The project began with a gap-compression hypothesis: a stable harness may reduce the measured gap between strong and low-cost models. The results support that hypothesis only under specific conditions. In highly structured extraction tasks, stronger harnessing compressed measured nonzero baseline gaps. In broader project-initialization and research-workflow slices, harnessing improved absolute contract adherence but produced mixed or undefined gap movement. Those broader slices exposed a measurement problem. A workflow-level task can hide several mechanisms at once: schema following, state retention, evidence grounding, stage discipline, and trace completeness.

We therefore moved from workflow-first evaluation to mechanism-first evaluation. A mechanism atom is a fixed-input, deterministic, contract-bound operation with one primary mechanism, one dominant failure mode, a golden output, a known-bad output, and a composition interface. This yields smaller evaluation questions: Does an explicit evidence bundle improve claim grounding? Does a memory slice prevent state hallucination? Does a stage gate prevent premature recommendation? Does a trace requirement make rejected options auditable? Passing atoms do not prove that a whole workflow is solved, but they make later composition easier to interpret.

The strongest evidence in this study comes from the repair loop created after broad workflow tests exposed unstable behavior. In Stage 7e, we composed a narrow evidence-bound decision macro from state inventory, evidence grounding, evidence typing, traceable decision, and stage-gated synthesis mechanisms. The first version showed that a low-cost model could pass under one harness arm but still lose decision-trace and stage-gate obligations under another. We isolated the miss and revised the contract. Stage 7e v2 repaired trace and gate retention, but exposed unknown-state omissions. Stage 7e v3 repaired unknown-state retention, but exposed known-state provenance compression. Stage 7e v4 made known-state provenance explicit and passed 4/4 targeted smoke runs after retry.

We then checked whether this was only a one-fixture patch. Stage 7-next reused the Stage 7e v4 obligations in a neighboring evidence-bound method-plan update macro. The output had to select the next admitted macro, list admission criteria, preserve local and real-model gates, and declare non-claims. The low-cost model passed 4/4 targeted smoke runs under G8/G9, with all runs scoring 1.000 on task success and the strict primary macro metric. This is narrow evidence, but it shows that a repaired obligation set can transfer to a closely related bounded macro.

The later Stage B sequence tested whether a repaired state-mutation obligation could survive stricter evaluation. Stage B v5 exposed evidence-array and gate failures. Stage B v5.1 repaired the complete gate and immutable evidence bindings. Stage B v5.2 found no engineering-scale independent effect from evidence-binding separation. Stage B v5.3 then isolated an explicit transition delta: the delta arm passed 15/15, while an exact-postcondition baseline passed 13/15. The difference was directional but below the preregistered effect threshold. Stage B v5.4 therefore asked a separate absolute question and ran only the frozen delta protocol. It passed 40/40 fresh runs across canonical, field-alias, evidence-order, distractor-evidence, and unknown-state-paraphrase conditions, with zero provider errors and zero retries.

The resulting claim is narrower than the original gap-compression thesis. Contract-driven harnesses do not make weak models generally equivalent to strong models, and they do not guarantee gap compression. They can raise the usable floor of low-cost models on bounded, contract-critical operations. They also make some failures easier to repair: a missing obligation can be named, added to the contract, captured as a known-bad case, checked locally, rerun against a model, and carried into the evidence ledger and claim boundary.

Contributions

The paper makes five contributions:

1. We define contract-driven harness engineering as an explicit reliability layer for agent tasks.
2. We propose mechanism atoms as the unit of harness evaluation.
3. We report a multi-stage empirical evaluation across task slices, mechanism atoms, and admitted macros.
4. We introduce a repair-loop protocol for harness development.
5. We provide bounded evidence that Qwen3-8B maintained strict contract adherence on one frozen controlled-state-mutation protocol across 40 fresh runs and five designed perturbation conditions.

The contributions of this paper are scoped. Empirically, all results come from one task family (controlled state mutation), one provider (SiliconFlow), and a small set of model configurations (Qwen3-8B as the primary low-cost model, with auxiliary confirmation on GLM-4-9B, Qwen3-14B, DeepSeek-V3.2, and Qwen2.5-7B). Methodologically, the contract stack and repair-loop are presented as a methodology for bounded contract-critical operations; we explicitly do not claim that completeness is the binding constraint in unbounded settings, nor that the contract stack alone explains determinism in tasks involving tool use, open-ended planning, or live retrieval. Whenever the phrase “binding constraint” appears in subsequent chapters, it should be read as scoped to the studied task family.

2. Related Work

The relevant prior work spans agent orchestration, declarative LM programming, structured output constraints, retrieval and tool augmentation, memory systems, safety verification, and skill ecosystems. These lines of work share a practical move. They take obligations that would otherwise sit inside free-form model generation and place them in runtime, specification, tool, memory, validation, or evaluation layers.

The distinction is summarized in Table 1.

Table 1. Work families and the contribution boundary of this paper.

Work family	Main focus	What it externalizes	What this paper adds
Workflow orchestration	execution graph and state	steps, tools, persistence, human checkpoints	obligation-level evaluation and repair
Structured outputs	syntactic output control	schema and format constraints	semantic contract obligations such as evidence, unknown state, and blocked claims
Guardrails and validators	runtime checks and retries	validation policies and failure handling	known-bad-driven repair loops tied to mechanism atoms
Declarative LM programs	modules, signatures, metrics	program structure and optimization targets	mechanism-first empirical repair for low-cost-model enablement
Agent specifications	portability and interface contracts	workflow, state, and step definitions	evidence-bound admission criteria before macro composition
Retrieval, tools, and memory	external knowledge and actions	documents, APIs, tool calls, long-term state	bounded memory/evidence contracts before live side effects

Work family	Main focus	What it externalizes	What this paper adds
Safety and verification	policy compliance and assurance	constraints, static checks, runtime firewalls	empirical contract adherence with explicit non-claims

2.1 Agent Workflows And Orchestration

Recent agent engineering guidance distinguishes between fully autonomous agents and workflows whose control paths are explicitly defined. Anthropic’s discussion of effective agents is useful here: workflows fit tasks that can be decomposed into predictable steps, while agents fit cases that require open-ended model autonomy. LangGraph, AutoGen, Semantic Kernel, and related orchestration frameworks make a similar engineering move. They expose execution state, graph structure, persistence, human-in-the-loop intervention, tool calls, and observability as system concerns rather than leaving them solely inside a prompt.

These systems make execution durable, inspectable, and easier to integrate with tools and humans. That does not settle the evaluation problem in this study. A workflow graph can route steps correctly while still losing evidence provenance, collapsing unknown state, skipping stage gates, or producing an ungrounded final recommendation.

Contract-driven harness engineering overlaps with workflow orchestration but treats the graph as only one layer. The unit of interest is the obligation that must survive the graph: state inventory, evidence binding, evidence type separation, trace completeness, stage-gate retention, excluded-context preservation, and repairability.

2.2 Declarative LM Programs And Agent Specifications

Declarative LM programming systems, especially DSPy, argue that language model behavior should be represented as programs with signatures, modules, metrics, and optimizers rather than as hand-written prompts. Agent specification work such as AgentSPEX and AgentSpec pushes in a related direction for agent systems: workflows, state, steps, and interfaces should be declared in portable and inspectable forms.

This line of work is close to our method. Both assume that some reliability gains come from making task structure explicit. The difference is the evaluation target. Declarative systems often emphasize program optimization, portability, or agent specification. Here, the unit is a contract-critical obligation. We define it, create golden and known-bad outputs, run deterministic local gates, execute small real-model slices, and update the claim boundary before composing broader workflows.

2.3 Structured Outputs, Guardrails, And Validators

Structured output systems and guardrail frameworks externalize output form. OpenAI structured output mechanisms, Outlines-style constrained generation, and Guardrails validators reduce the burden of asking a model to follow a format. They make schema adherence and selected validation checks part of the system layer.

These mechanisms are necessary but insufficient for the problem studied here. Schema validity can guarantee that an output has the expected shape. By itself, it cannot guarantee that a claim is supported, that unknown state remains unknown, that excluded context is not reused, or that a recommendation is blocked when a stage gate is incomplete. The harness studied here treats validators as one component in a larger contract

stack. The output contract includes fields, but also semantic obligations: required evidence IDs, evidence type separation, rejected-option traces, explicit blocked outputs, and non-claims.

2.4 Retrieval, Tools, Memory, And Externalized Capability

RAG, ReAct, Toolformer, Gorilla, and tool/API-focused agent work show that models can become more capable when knowledge and action are externalized. Retrieval can provide updated evidence and provenance. Tool-use frameworks can turn external actions into typed calls. API benchmarks show that tool descriptions and retrieval can materially improve call generation compared with unaided model behavior.

Memory-oriented systems such as MemGPT and Letta show that agents can use hierarchical, archival, or stateful memory to extend beyond a single context window. They also expose a reliability problem for this study: memory is not automatically beneficial. A system must decide what to store, when to summarize, how to retrieve, how to scope memory, and how to prevent stale or irrelevant context from contaminating a new task.

This study does not primarily test live retrieval, live tool execution, or long-term memory. Most admitted mechanism atoms and macros are fixed-input, no-tool tasks. That choice isolates whether the model can honor explicit contracts before live tools, changing corpora, or runtime side effects are added.

2.5 Evaluation, Safety, Verification, And Skill Ecosystems

Agent evaluation and safety work highlights the fragility of agent claims. OAgents-style critiques emphasize protocol variance and reproducibility challenges. Semantic Integrity Constraints, Agentproof, LlamaFirewall, and related verification or guardrail systems argue that agent behavior must be constrained, audited, or checked against explicit policies and semantic rules.

A complementary line of precedents comes from software testing rather than agent architecture. The test oracle problem —the difficulty of distinguishing correct from incorrect behavior when no independent ground truth is available —has been recognized since the study of non-testable programs (Weyuker, 1982) and surveyed as a central concern of software testing (Barr et al., 2015); metamorphic testing alleviates it by checking necessary relations among families of executions instead of single outputs (Chen et al., 2018; Liu et al., 2014). In RL safety, reward misspecification names the analogous failure in which an optimizing process satisfies the measured proxy rather than the intended capability (Amodei et al., 2016; Skalse et al., 2022). The oracle-coupling audit added in §4.14 transfers these concerns to a new object: not the agent’s output but the evaluator’s own executable policy, asking whether that policy is derived from the answer label that scores the run.

Capability ecosystems such as MCP servers, agent skills, registries, pack systems, and PETFiSh-style skill markets (Cui, 2026) represent another route toward harness engineering. They externalize reusable procedures, tool access, installation state, platform routing, quality gates, and capability discovery. In PETFiSh specifically, packs, skills, MCP servers, installers, trigger evaluators, quality gates, and context plugins make the system a useful experimental setting for studying harness design as an engineering object. Local PETFiSh-specific evidence is preserved in Appendix C and the reproducibility package.

PETFiSh is the implementation context, not the transferable claim. The claim concerns a contract stack and repair-loop protocol: task specs, bounded memory, evidence bundles, output contracts, workflow gates, trace logs, validators, known-bad cases, and claim-boundary updates.

This paper focuses on a narrower gap: mechanism-level evaluation. Which explicit obligations let a low-cost model complete bounded contract-critical operations, and how should a harness be repaired when those

obligations fail?

The closest prior lines are declarative LM programs, guardrail or validator systems, and agent specification languages. They externalize structure, interfaces, or runtime checks. Our contribution is operationally different: we treat each missing reliability obligation as an empirical repair target, require golden and known-bad fixtures before admission, and restrict macro claims to obligations that survive composition. The unit of evaluation is the obligation that must remain auditable across the harness, not the workflow graph or the schema alone.

Two recent lines of work are particularly close. AgentSpec (Wang, Poskitt, and Sun, 2025) provides customizable runtime enforcement for safe and reliable LLM agents via a lightweight DSL of triggers, predicates, and enforcement mechanisms. It shares the move toward runtime-enforceable constraints, but it targets whole-agent safety (unsafe execution, hazardous actions, legal violations) rather than mechanism-atom task obligations, and it does not require known-bad outputs to fail for an expected reason as an admission gate. Agent Behavioral Contracts (Bhardwaj, 2026) brings formal contract thinking to autonomous agents with preconditions, invariants, governance, recovery, and (p, δ, k) -satisfaction guarantees. It shares the contract stack idea, but its unit of specification is behavior classes and multi-agent chains, not fixed-input mechanism atoms, and its evaluation emphasizes drift-bounds theorems rather than fixture-driven repair-loop convergence. DSPy Assertions and Guardrails as Infrastructure are also adjacent: they use runtime constraints or policy packs to improve reliability, but neither employs deterministic fixture admission (golden must pass, known-bad must fail for the expected reason) or a repair-loop protocol as the central development method. Table 1 situates these distinctions at the level of the mechanism atom, the admission gate, and the claim boundary.

3. Methods

3.1 Study Design

Throughout this paper, “harness” and “contract stack” refer to the same artifact: the seven-object specification (TaskSpec, MemorySlice, EvidenceBundle, OutputContract, WorkflowGate, TraceLog, Validator) defined in §3.2. The terms are used interchangeably.

This study evaluates whether explicit agent harness contracts can make productivity tasks less dependent on unconstrained model behavior. Agent workflow is not treated as a primitive benchmark unit. We evaluate harness mechanisms in three levels:

1. task slices, which compare broad task classes across harness strengths;
2. mechanism atoms, which isolate a single primary harness mechanism and a dominant failure mode;
3. admitted macros, which compose only mechanisms that have passed local gates and targeted model checks.

This design is intentionally conservative. Broad workflow results can motivate failure analysis, but they do not by themselves justify claims about a general harness methodology. A workflow can enter the main claim only when its component mechanisms, local evaluators, known-bad cases, and cross-step obligations are explicit.

The experimental path therefore moves from broad failures toward admitted composition rather than from one benchmark score to a larger benchmark score:

Task slices

- |- structured extraction
- |- project initialization
- `- research workflow

```

    -> failure analysis
Mechanism atoms
|- Stage 6
|- Stage 7r
`- Stage 7r.1
    -> admission gate
Admitted macros
|- Stage 7p / 7p v2
|- Stage 7e v1-v4
|- Stage 7-next
`- Stage B v5-v5.4

```

This map is the method in miniature. Broad tasks expose unstable behavior, mechanism atoms isolate the obligation, local gates reject known-bad outputs, and only then can a macro carry the obligation forward.

3.2 Harness Model

We define a contract-driven harness as a set of explicit control objects around a language model:

Table 2. Contract-stack objects and their roles.

Object	Role
TaskSpec	Objective, constraints, success conditions, and non-goals.
MemorySlice	Bounded context that may be used, plus excluded or unknown state.
EvidenceBundle	Admissible evidence items, evidence types, and source links.
OutputContract	Required output shape, nested fields, citation policy, and validator rules.
WorkflowGraph or stage gate	Required order of intermediate steps and blocked outputs.
TraceLog	Decision trace requirements for auditable reasoning and rejection paths.
ValidatorGate	Deterministic local checks that distinguish passing outputs from known-bad outputs.

The study uses a conservative working assumption: when a task can be bounded, reliability should move from implicit model judgment into explicit, inspectable contracts. The harness is evaluated as a reliability-engineering layer, not as a claim that low-cost models become generally equivalent to strong models.

The object of study is not an improved prompt. It is the lifecycle by which a missing obligation becomes a contract field, a known-bad fixture, a deterministic gate, and an admitted macro requirement.

3.3 Harness Arms And Models

Experiments use harness arms to vary the strength of external control. G0 is raw or minimally constrained task input. G2/G3 represent intermediate mechanism arms when relevant. G8 is contract-rich execution with validator or evaluator obligations. G9 is the full harness packet with task spec, output contract, evidence, memory policy, workflow, trace, and regression expectations.

The real-model slices use SiliconFlow’s OpenAI-compatible API. The current low-cost model tier is Qwen/Qwen3-8B; strong-model slices in earlier stages used deepseek-ai/DeepSeek-V3.2. Provider-backed runs use temperature 0, fixed prompt artifacts exported before execution, per-run artifact directories,

adapter request files, output files, validation reports, metrics files, and event logs for provider start/end, elapsed time, errors, and retry analysis.

3.4 Failure Classification Rule And Obligation×Field Coverage Matrix

We classify each observed failure before repairing it, because contract defects, evaluator defects, and model failures have different repair actions and different implications for the claim boundary. The three types are mutually exclusive under the following decision procedure:

1. **Declaration check.** Was the violated obligation explicitly declared in the model-visible contract, and bound to the specific output field where the violation appeared? If no, the failure is a **contract defect**.
2. **Surface-form check.** Was the obligation semantically satisfied, but rejected by the evaluator because of an unstated surface requirement (e.g., JSON formatting, token casing, or enum phrasing)? If yes, the failure is an **evaluator defect**.
3. If the obligation was both declared and correctly checked, and the model still violated it, the failure is a **model failure**.

Table 3. Failure classification: contract defect versus model failure.

Failure type	Definition	Repair action	Claim implication
Contract defect	The obligation was missing, ambiguous, or not visible to the model in the output field where it was violated.	Revise the contract and add a known-bad fixture that captures the missing obligation.	Not evidence of a model limitation.
Evaluator defect	The obligation was declared and the model output satisfied it semantically, but the deterministic check rejected a valid surface form.	Revise the evaluator or probe, then re-verify golden and known-bad anchors.	Does not change the model capability claim.
Model failure	The obligation was explicitly declared and the evaluator correctly checked it, yet the model still violated it.	Redesign the mechanism (e.g., add JSON-schema-constrained decoding, or reduce scope) or exclude the model.	This is the only class that evidences a model limitation.

Worked examples. The initial Stage B v5 contract did not enumerate the exact expected values for `next_action` or state the evidence-citation policy in the model-visible gate. Under that contract, Qwen3-8B failed 0/40 controlled state-mutation runs, emitting a natural-language description for `next_action` and omitting the required evidence citation. The failure is a contract defect because the obligations were not explicitly declared. The repair was to add exact enum values and the evidence-citation rule to the contract.

The GLM-4-9B interchangeability probe contained a minimal-context enum check. GLM-4-9B emitted a bare token rather than a JSON object, while still passing the full frozen protocol 30/40 in author verification. The probe’s contract did not explicitly require JSON output. The output satisfied the semantic obligation but was rejected by an unstated surface rule, so the failure is an evaluator (probe) defect. The repair was to add the JSON-output requirement to the probe; after that change, above-floor anchors passed Tier-1 structural checks and the below-floor anchor still failed all four structural checks.

Qwen2.5-7B-Instruct failed 0/40 on the unchanged frozen protocol with malformed JSON, dropped fields, and corrupted tokens. The contract required valid JSON and the evaluator checked schema validity, so the

obligation was declared and correctly checked. This is a model failure. The repair action is to route the model through JSON-schema-constrained decoding or exclude it from the task pool.

Obligation×field coverage matrix. A global obligation does not automatically bind every output field. We record coverage in an obligation×field matrix that is part of the fixture schema. For each global obligation, the matrix lists the output fields it governs. Each cell must pass a local gate: the golden output satisfies the obligation at that field, and a known-bad output violates it there. An unmarked cell means the obligation is not asserted for that field, and any failure there is outside the contract scope.

In the automated replication, v4 required canonical names for state identifiers. The matrix initially covered `state_inventory`, `transition_record`, and `residual_unknown_state`; those four conditions passed 8/8. Under the unknown-state-paraphrase condition, the model still used the paraphrased alias inside the `attestation` field. The matrix showed that the canonical-name obligation had not been bound to `attestation`. The failure is therefore a contract defect: the obligation was not declared to cover the field where it was violated. The repair was to extend the obligation to `attestation` and add a known-bad fixture that violates canonical naming only there. After the update, v5 passed 40/40 across all five perturbation conditions. The matrix is scoped to contract-driven harness tasks with fixed output contracts and deterministic evaluators; it does not claim that the same field set generalizes to arbitrary agent outputs.

3.5 Frozen Protocol Specification

A protocol is *frozen* when every variable that could invalidate a stability or transfer claim is pinned before execution and verified before the first model call. The frozen items are: (1) sampling parameters, specifically temperature (set to 0 and recorded); (2) provider and model identifier, including the exact model version snapshot; (3) prompt artifacts, exported before execution and identified by content hashes; (4) evaluator version, including the exact validator or probe code and fixture version; (5) known-bad set version, identifying the regression fixtures defining the failure modes the protocol claims to avoid; and (6) perturbation set version, identifying the designed perturbations used to test stability.

Table 4. Frozen protocol items and the claims they anchor.

Frozen item	Claim invalidated if the item is not pinned
Temperature	A non-zero or changed temperature can alter the sample distribution; the observed pass rate would no longer describe a fixed sampling process.
Provider and model version snapshot	Provider routing, model updates, or quantization changes can change behavior; a stability claim becomes unanchored.
Prompt hash	Any change to the model-visible prompt changes the task; results are not comparable across runs.
Evaluator version	A revised validator can reclassify passing outputs as failures; adherence metrics become uninterpretable.
Known-bad set version	Missing or altered regression fixtures change the meaning of “stable” for the repaired failure modes.
Perturbation set version	Different perturbations test different robustness boundaries; the claim no longer refers to the same test suite.

A claim about a protocol is a claim about a specific, reproducible artifact stack. If any item changes, the claim is void unless re-established with a new freeze record. Before each run batch, a pre-flight script computes the SHA-256 hash of each frozen artifact and compares it to the manifest recorded at freeze time. Any mismatch

aborts execution or logs a deviation. The script writes the verified hashes, timestamp, and manifest version into the trace log. A frozen-protocol claim is void if the pre-flight check is not recorded. The standalone verification specification is preserved in `research/04_methods/frozen-protocol-spec-v1.md`.

3.6 Task Slices, Mechanism Atoms, And Macros

The first empirical layer uses broad task slices to identify where harnessing helps and where broad task definitions become too noisy. Structured extraction tests a high-constraint task with deterministic output structure. Project initialization tests a multi-constraint workspace planning task. Research workflow tests evidence-backed synthesis.

A mechanism atom is the smallest testable unit of harness behavior with one primary mechanism, fixed input, explicit output contract, deterministic evaluator, known-bad rejection, pass threshold, and composition interface. Atoms are accepted only when fixture structure validates, the golden output passes, at least one known-bad output fails for the intended reason, the baseline leaves room for improvement, the low-cost model improves under the relevant harness arm, and the atom declares how it can compose with downstream mechanisms.

Macro tasks are composed only after component mechanisms pass local gates and targeted model checks. A macro must preserve cross-step obligations explicitly. The current admitted macro family is fixed-input: Stage 7p v2, Stage 7e v1-v4, Stage 7-next, and the Stage B controlled-state-mutation sequence. Project initialization and full research workflow remain blocked because the current evidence covers bounded macros, not open-ended tool-using workflows.

3.7 Model Admission Protocol

The model admission protocol is a four-tier funnel for certifying a candidate model as compatible with a frozen contract. It is designed to spend cheap probe calls on below-floor candidates and reserve the full 40-run gate for models that have already passed structural and semantic checks. The tiers are:

1. **Tier-1 structural probe** (≈ 4 API calls): tests organ-level capabilities —valid JSON, literal copy, field retention, and no fabrication. Failure means the model is below the structural floor for this task family and should not run the full protocol.
2. **Tier-2 semantic probe** (≈ 4 API calls): tests task-specific capabilities —enumeration compliance, canonical-name mapping, and order sensitivity. Failure predicts repair-loop workload, not floor status.
3. **Tier-3 smoke** (8 canonical runs): entry into the repair loop for a candidate that passed the probes.
4. **Tier-4 full gate** (5 conditions $\times$ 8 repeats = 40 runs): final admission gate for the frozen contract.

The probes are derived from the task family’s mechanism atoms; there is no universal floor test. In the current study, Qwen2.5-7B-Instruct failed the Tier-1 structural probe (0/40 valid JSON outputs on the full protocol) and is classified as below floor. Qwen3-8B, Qwen3-14B, DeepSeek-V3.2, and GLM-4-9B passed Tier-1 and were admitted to the full gate, with GLM-4-9B showing a task-specific paraphrase-sensitivity gap that Tier-2 predicted as additional repair-loop workload. The total cost for a model that passes is approximately \$1 plus the API time; the cost for a model that fails Tier-1 is approximately \$0.01 plus seconds.

3.8 Admission Criteria

An atom or macro is admitted to the next experimental layer only if all of the following hold:

1. the fixture schema validates;
2. the golden output passes;

3. at least one known-bad output fails for the intended reason;
4. the baseline leaves improvement room or the evaluation question explicitly targets absolute contract adherence;
5. the low-cost model improves under G8/G9 or reaches the declared pass threshold;
6. the composition interface is declared;
7. cross-step carried obligations are explicit when a macro composes multiple atoms;
8. unsupported claims and non-claims are updated before expansion.

These criteria are deliberately stricter than ordinary prompt evaluation. They are designed to prevent a broad workflow result from entering the claim set before the underlying mechanism and failure mode are visible.

3.9 Repair-Loop Protocol

The main methodological contribution is the repair-loop protocol:

1. observe a real model failure;
2. isolate the missing mechanism or obligation;
3. make the obligation explicit in the input and output contract;
4. add or update a known-bad fixture that captures the failure;
5. run local golden/bad regression;
6. execute a targeted real-model slice;
7. update the evidence ledger, claim boundary, and backlog before expanding scope.

Stage 7e illustrates this protocol. Stage 7e v1 found a low-cost-model G9 failure in stage-gate and decision-trace retention. Stage 7e v2 repaired trace/gate retention but exposed unknown-state omissions. Stage 7e v3 repaired unknown-state retention but exposed known-state provenance compression. Stage 7e v4 made known-state provenance explicit and passed 4/4 targeted smoke runs after retry. Stage 7-next then reused those obligations in a method-plan update macro and passed 4/4 targeted smoke runs without provider errors.

Stage B extends the loop from targeted repair to ablation and stability confirmation. Stage B v5 failed 0/4 strict runs because exact evidence arrays were not preserved and one exact gate field was not model-visible. Stage B v5.1 exposed the complete gate and separated immutable evidence bindings, then passed 4/4. Stage B v5.2 isolated evidence-binding representation and did not observe the preregistered large independent effect. Stage B v5.3 restored explicit state-removal operations through a structured transition delta and obtained 15/15 strict passes, but the paired causal threshold still did not pass. Stage B v5.4 froze that protocol before execution and obtained 40/40 fresh strict passes across five perturbations. The sequence separates three questions that should not be collapsed: whether a bundled repair works, whether one repair component has a large independent effect, and whether the repaired protocol remains stable under repetition.

3.10 Metrics And Claim Rules

Each evaluated run emits metrics including `task_success`, `schema_validity`, `citation_grounding`, `state_accuracy`, `evidence_type_accuracy`, `stage_completion`, `trace_completeness`, `context_relevance`, and `atom_primary_metric`. The controlled-transition experiments add exact evidence-array preservation, residual-state accuracy, state-transition accuracy, complete-gate accuracy, retention-attestation accuracy, and a strict aggregate controlled-mutation decision.

Table 5 gives a compact reading guide for the core metrics. Detailed thresholds, fixture-specific checks, and evaluator outputs are provided in the reproducibility package.

Table 5. Core metrics and their evaluator types.

Metric	What it checks	Evaluator type
schema_validity	Required fields and types are present	deterministic schema/field check
citation_grounding	Claims carry admissible evidence IDs	deterministic evidence-ID check
state_accuracy	Known and unknown state are preserved	fixture-specific state check
evidence_type_accuracy	Evidence type labels remain correct	evidence-type check
stage_completion	Required stage gates are preserved	stage-gate check
trace_completeness	Required decision and rejection traces are present	structured trace check
context_relevance	Required or excluded context obligations are respected	context-obligation check
atom_primary_metric	The atom-specific dominant obligation is satisfied	atom evaluator
task_success	The declared task contract passes	composite evaluator

These metrics evaluate contract adherence rather than open-ended output quality or human preference.

Gap compression is computed only where a nonzero G0 baseline gap exists. If G0 baselines collapse for both models, or if the low-cost model improves more than the strong model and reopens the absolute gap in the opposite direction, the result is reported as mixed, undefined, or negative rather than forced into a compression claim.

Weak-model enablement is reported when the low-cost model reaches a pass threshold under a harness condition after failing or underperforming under weaker conditions.

The Stage B stability rate uses only the 40 fresh v5.4 runs. The 15-run v5.3 explicit-delta pilot is not pooled into that estimate. Pooled and per-condition rates are reported with two-sided 95% Wilson intervals. The v5.3 comparison forms 15 matched pairs by perturbation condition and repetition. It reports the absolute risk difference, discordant-pair counts, and a two-sided exact McNemar result. The experiment originally preregistered Fisher’s exact test, which treats the arms as independent; that value is retained in the audit record but is not used as the primary paired analysis.

The Stage B v5.3 experiment plan in the reproducibility package defined the engineering-effect threshold as an absolute risk difference of 0.20. With 15 runs per arm, this required at least three additional passes. The threshold was fixed before execution as a coarse engineering decision gate. It was not a conventional significance threshold, equivalence margin, or power-derived minimum detectable effect, and the preregistration did not include a separate utility analysis for the cutoff.

4. Results

4.1 Overview

The results support a bounded version of the original hypothesis. Contract-rich harnessing improves absolute contract adherence across several productivity-task settings. It can also compress cross-model gaps in highly constrained tasks when baseline gaps are nonzero. Gap compression is not universal. The more stable result is weak-model enablement on bounded, contract-critical operations: when task obligations are explicit and evaluated deterministically, the low-cost model can reach pass-level behavior on tasks where weaker harnessing or broader prompts were unstable.

Table 6 summarizes the main claim boundary.

Table 6. Main claim boundary.

Claim	Evidence	Boundary
Absolute contract adherence lift	broad slices, mechanism atoms, admitted macros	tested conditions only
Gap compression	strongest in structured extraction	conditional on nonzero baseline gaps and constrained tasks
Weak-model enablement	Stage 6, Stage 7r.1, Stage 7e v4, Stage 7-next, Stage B v5.4	bounded contract-critical operations
Controlled-transition stability	Stage B v5.4	one frozen protocol, model, provider, and perturbation suite
Full workflow reliability	not supported	remains a non-claim
Production readiness	not supported	remains a non-claim

Table 7 summarizes the main empirical layers and the claim each layer permits. Figure 4 provides a visual map of the experimental progression from mechanism atoms through multi-model verification.

Figure 4. Experimental stage progression. See [figures/figure-4-stage-progression.pdf](#). The diagram shows three phases: (1) mechanism atoms and composition (§4.3–4.5), (2) contract evolution and stability (§4.6–4.8), and (3) cross-model and cost verification (§4.9–4.13). Each box gives the stage name, run count, and section reference.

The experimental logic proceeds in three phases. **Phase 1** (§4.2–4.5) tests whether broad workflow tasks benefit from harnessing, finds mixed results, and decomposes those workflows into mechanism atoms that can be individually tested and repaired. **Phase 2** (§4.6–4.8) composes atoms into macros, runs the repair-loop protocol on a fixed evidence-decision macro, and tests whether the repaired obligations transfer to a neighboring macro and survive 40 fresh runs under a frozen protocol. **Phase 3** (§4.9–4.13) asks whether these results are reproducible by an external agent, transferable across model families, separable from the implementation framework, capable of detecting below-floor models, and cost-justified relative to using a stronger model directly. Run counts increase as the protocol matures: early atom and composition stages use 6–48 runs for targeted smoke and pilot testing; Stage B v5.4 uses 40 runs for the formal stability estimate; multi-model and Stage D use 200–240 runs for cross-model verification.

Table 7. Empirical layers and the claims they permit.

Layer	Stage	Runs	Failure -> Repair	Outcome	Allowed claim	Reproduced
Task slice	structured extraction	24	schema/tool gaps -> G9 packet	key gaps to 0	conditional gap compression	R04
Task slice	project init	12	mixed metric movement -> G9	mixed	no universal compression	R04
Task slice	research work-flow	12	zero or mixed baseline gaps -> G9	mixed/undefined	absolute adherence only	R04

Layer	Stage	Runs	Failure -> Repair	Outcome	Allowed claim	Reproduced
Atom	Stage 6	48	mechanism failures -> atom contracts	low-cost lift	weak-model enablement	R04
Macro	Stage 7p/v2	12	stale-context loss -> carried obligations	repaired in v2	composition retention	R04
Macro	Stage 7e	6 + repairs	trace and state gaps -> explicit obligations	targeted smoke passed	fixed macro only	R04
Macro	Stage 7-next	4	neighboring transfer -> reused obligations	targeted smoke passed	narrow transfer	R04
Ablation	Stage B v5.2-v5.3	30 + 30	bundled repair -> isolated controls	no preregistered large independent effect	component-effect boundary	R04
Stability	Stage B v5.4	40	passing repair -> frozen protocol	40/40 fresh passes	one frozen transition protocol	R01+R02+R04
AutomateKimi repli-ca-tion	Agent v1-v5	40	re-implemented protocol, same trajectory	40/40 endpoint confirmed	not independent replication	author-verified
Multi-model	Stage B v5.4 × 5 models	200	model-family-specific gaps	40/40, 40/40, 40/40, 30/40, 0/40	partial transfer; GLM paraphrase vulnerability confirmed by 3 independent observations	R01+R02
Cross-framework	pf vs drkgChain adapters	—	framework-specific surface drift	framework-agnostic core exists; zero pf coupling verified	architectural claim only	—
Floor probe	Qwen2.5-7B Tier-1	40	below-floor JSON parsing	0/40 valid JSON	model exclusion or constrained decoding	R01+R02
Overhead	Stage D G0 vs G9	60 + 80	cost/latency per pass	G0 0%→G9 100% at 8.6× tokens	directional cost illustration	R01+R02

Layer	Stage	Runs	Failure -> Repair	Outcome	Allowed claim	Reproduced
Validity oracle-audit	coupling (§4.14)	28 tasks; 392 deterministic candidates; 18 evaluator calls; 0 model calls	evaluator- coupling risk -> public-input compiler + boundary controls	policy derivable from public facts for the audited family	freeze-and-verify (SHA-256 closures)	

4.2 Task Slices: Strong Absolute Lift, Conditional Gap Compression

The structured-extraction v2 slice provides the clearest positive gap-compression result. (Throughout §4.2–4.5, “budget_model” refers to Qwen/Qwen3-8B and “strong_model” refers to deepseek-ai/DeepSeek-V3.2, as defined in §3.3.) Under G0, nonzero baseline gaps appeared on task success, schema validity, tool-call correctness, human acceptance, cost efficiency, and safety consistency. Under G9, all measured nonzero gaps compressed to 0.000, producing compression ratios of 1.000 on those metrics. Citation grounding had a baseline gap of 0.000 and is therefore reported as n/a rather than as compression.

The project-initialization slice shows why gap compression cannot be the universal claim. G9 compressed the task-success gap from 0.111 to 0.000 and the safety-consistency gap from 0.200 to 0.000. Schema validity moved in the opposite direction, from a baseline gap of 0.250 to an arm gap of 0.583, yielding a negative compression ratio of -1.333. Human acceptance and cost efficiency also showed negative compression ratios.

The research-workflow slice further weakens a universal gap-compression story. Several G0 baseline gaps were already 0.000, making compression undefined. G9 compressed schema-validity gap from 0.067 to 0.000, but task-success gap became 0.083 from a 0.000 baseline and human-acceptance/cost-efficiency gap movement was slightly negative.

These results are best interpreted as absolute lift with conditional gap compression, not universal gap closure. The mixed slice-level results motivated the next step: decomposing broad workflows into smaller, independently testable mechanism atoms (Stage 6, §4.3), where each obligation could be isolated, tested, and repaired without the confounding interaction of multiple mechanisms in a single task.

4.3 Mechanism Atoms: Broad Workflows Need Smaller Units

The Stage 6 mechanism-atom pilot tested 48 real model runs and completed 48/48 after documented time-out recovery. Its strongest result was weak-model enablement. For the low-cost model relative to G0, G9 produced task_success lift of +0.576 and schema_validity and atom_primary_metric lift of +0.833.

The harnessed low-cost model also outperformed the unconstrained strong model on contract-critical metrics. Relative to strong_model + G0, low-cost model + G9 showed task_success advantage of +0.743 and schema_validity and atom_primary_metric advantages of +1.000.

Gap compression was mostly positive on general contract metrics, including G9 task_success compression of 1.000 and G9 schema_validity compression of 1.000. But atom_primary_metric remained mixed, with G9 compression of 0.000 and G2/G8 negative values. This supports the conclusion that harnesses can substantially raise low-cost-model reliability on bounded operations even when atom-specific gap compression is not uniform.

4.4 Composition: Atom Success Is Not Enough

Stage 7p tested whether passing atoms could compose into a narrow partial macro:

A10 bounded context recall -> A9 no-overwrite action planning -> A6 validator repair

The execution completed cleanly with 6/6 real SiliconFlow runs. Strong_model G8 and G9 passed the full partial-composition chain. The low-cost model improved strongly under G8/G9, reaching task_success=0.800 under G8 and 0.900 under G9, with schema_validity=1.000 and safety=1.000. Yet it failed the full chain because context_relevance stayed 0.000: the composed output did not explicitly carry forward the stale-context exclusion.

Stage 7p v2 then added an explicit composition-retention contract. The same partial chain passed for both model tiers under G8/G9. This result supports a composition-layer mechanism claim: cross-step obligation retention is necessary when a macro must preserve negative context constraints across multiple atom outputs.

4.5 Revised Atoms And Targeted Repairs

Stage 7r redesigned six boundary-prone atoms: A2R, A3R, A4R, A5R, A7R, and A8R. Local gates passed: 6/6 fixture structures, 12/12 local golden/bad expectations, 36/36 packet compilation, and preflight with 0 errors and 0 warnings.

The real-model smoke completed 35/36 outputs. The single missing output was A8R low-cost G8, which repeatedly timed out under SiliconFlow and was treated as an execution deviation rather than a model-quality score. On completed runs, strong-model G8/G9 passed 12/12, while the low-cost model still failed strict A2R citation grounding and A7R trace completeness.

Stage 7r.1 targeted exactly those failures by tightening the contracts. A2R1 required every grounded claim to be an object with non-empty evidence_ids. A7R1 required rejected-option objects with evidence IDs and trace steps for C2 support, C1 rejection, and C3 rejection. The targeted 8-run low-cost-model smoke passed 8/8.

This supports the mechanism-first repair hypothesis: low-cost-model failures on claim-level evidence binding and rejection-trace completeness can be repaired by narrowing the output contract.

4.6 Stage 7e: Iterative Repair Of A Fixed Evidence-Decision Macro

With revised atoms passing individually (§4.5) and composition shown to need explicit retention obligations (§4.4), the next question was whether the repair-loop protocol could converge a composed macro from failing to strict-passing. Stage 7e composed a narrow evidence-bound decision macro from state inventory, evidence grounding, evidence-type separation, traceable decision, and stage-gated synthesis mechanisms. The first Stage 7e smoke completed 6/6 runs. Strong_model G8/G9 and low-cost-model G8 passed with task_success=1.000 and atom_primary_metric=1.000. G0 failed for both model tiers. Low-cost-model G9 partially failed with task_success=0.714 because it missed complete decision-trace and stage-gate retention.

Stage 7e v2 added explicit retention requirements for decision_trace, stage_gate, and carried_obligations. The targeted low-cost-model G8/G9 smoke completed 4/4 targeted smoke runs, and all four targeted runs achieved trace_completeness=1.000 and stage_completion=1.000. However, only 1/4 runs fully passed because the remaining runs omitted Git branch, CI status, or network/API approval unknowns from state_inventory.

Stage 7e v3 targeted unknown-state retention. The four-run targeted smoke preserved all required Git/CI/network unknown-state fields and forbidden-inference fields. Full strict macro pass improved to 3/4.

The remaining failure was narrower: one G8 run compressed known-state provenance into generic labels.

Stage 7e v4 made known-state provenance explicit. It required `state_inventory.known_state[ ]` entries with `state_id`, `fact`, and `evidence_ids`. After retrying one provider timeout and one truncated-output retry, all four targeted runs passed with `task_success=1.000` and `atom_primary_metric=1.000`. State accuracy, citation grounding, evidence type accuracy, trace completeness, and stage completion all reached 1.000.

This sequence is the clearest evidence for the repair-loop protocol. The low-cost model did not become generally stronger. The harness made the missing obligations explicit, then verified that the model could satisfy them under a fixed macro contract.

4.7 Stage 7-next: Transfer To A Neighboring Macro

Stage 7-next tested whether the Stage 7e v4 obligation set was only a fixture-specific patch. The new macro was an evidence-bound method-plan update. It reused Stage 7e v4 obligations and added one new stressor: the output had to select the next admitted macro, specify admission criteria, preserve local and real-model gates, and declare non-claims.

The local gate passed with 2/2 expectations met: the golden output passed with `task_success=1.000` and `atom_primary_metric=1.000`, while the known-bad premature broader-workflow expansion failed with `task_success=0.000`.

The real smoke used the low-cost model only:

Qwen/Qwen3-8B x G8/G9 x 2 repetitions = 4 runs

All four targeted runs executed without provider errors, timeout, or truncated-output retry. The same slice passed with `task_success=1.000`, `atom_primary_metric=1.000`, `schema_validity=1.000`, `citation_grounding=1.000`, `state_accuracy=1.000`, `evidence_type_accuracy=1.000`, `trace_completeness=1.000`, `stage_completion=1.000`, and `context_relevance=1.000`.

This supports a narrow transfer claim: the Stage 7e v4 obligations can be reused to make the low-cost model complete a closely related fixed method-plan macro with one new explicit stressor.

4.8 Stage B: From Repair To Fresh Stability Confirmation

Stage B is not introduced as a new general state-transition method. It is a stricter test of the repair-loop protocol: separate bundled repair, component effect, and frozen-protocol stability.

Stage B tested one controlled state mutation: move network API approval from unknown to known while preserving exact evidence bindings, residual unknown state, residual forbidden inferences, a transition record, the complete gate, and a retention attestation.

The first state-transition smoke, Stage B v5, failed 0/4 under the strict aggregate. All four runs preserved schema, residual state, transition, and attestation. They failed exact evidence-array preservation, and the exact expected `next_action` value had not been declared in the model-visible gate. Stage B v5.1 exposed the complete gate and separated immutable evidence bindings from editable prose. The repaired protocol passed 4/4, but this bundled two changes and used too few runs for a stability estimate.

Stage B v5.2 isolated evidence-binding representation in a preregistered 30-run ablation. Binding-separated evidence passed 15/15 exact-array checks, while claim-coupled evidence passed 14/15. The 0.067 risk difference was below the 0.20 engineering threshold, and both arms passed only 10/15 strict aggregates because

nine runs retained an obsolete forbidden-inference entry. The result did not support a large independent evidence-binding effect.

Stage B v5.3 targeted that state error. Both arms received the same initial state, exact final postconditions, evidence bindings, event, gate, attestation, perturbations, and evaluator. The treatment added only a structured `required_transition_delta` that named the values to remove, add, and preserve. Across 30 fresh runs, the explicit-delta arm passed 15/15 strict and residual-state checks. The exact-postcondition-only arm passed 13/15. Evidence, transition, gate, schema, and attestation passed 15/15 in both arms.

The runs form 15 matched pairs by perturbation condition and repetition. Thirteen pairs were pass/pass, two were explicit-delta pass/postcondition-only fail, and none favored the postcondition-only arm. The exact McNemar two-sided result was $p=0.500$. The residual-state risk difference was 0.133, below the preregistered 0.20 threshold. The correct causal decision is mixed: the treatment passed all 15 runs, but the experiment did not establish the planned engineering-scale independent effect over an already strong baseline.

Stage B v5.4 asked a different preregistered question: whether the frozen explicit-delta protocol would maintain high absolute adherence over 40 fresh executions. It reused the five frozen v5.3 treatment fixtures without changing the prompts, evaluator, thresholds, provider settings, or output contract. The conditions were canonical, field alias, evidence order shuffled, distractor evidence, and unknown-state paraphrase, with eight repetitions per condition.

All 40 runs passed the strict controlled-mutation metric and every component metric. Each perturbation condition passed 8/8. The pooled strict rate was 1.000 with a two-sided 95% Wilson interval of [0.912, 1.000]. Each 8/8 condition has the wider interval [0.676, 1.000].

Table 8. Stage B v5.4 per-condition results over 40 fresh runs.

Condition	Passes	Rate	95% Wilson interval
canonical	8/8	1.000	[0.676, 1.000]
field alias	8/8	1.000	[0.676, 1.000]
evidence order	8/8	1.000	[0.676, 1.000]
distractor evidence	8/8	1.000	[0.676, 1.000]
unknown-state paraphrase	8/8	1.000	[0.676, 1.000]
pooled	40/40	1.000	[0.912, 1.000]

All 40 calls returned valid JSON with zero provider errors and zero retries. Median latency was 19.500 seconds, P90 latency was 22.183 seconds, and total usage was 83,312 prompt tokens plus 19,672 completion tokens.

The result supports a bounded stability statement:

Under the frozen explicit-transition-delta G9 protocol, Qwen3-8B completed the tested controlled multi-array state mutation in 40/40 fresh runs across five perturbation conditions.

It does not convert the mixed v5.3 ablation into a causal-effect result. It also does not establish arbitrary state-machine reliability, tool execution, rollback, concurrency, task-family generalization, or production readiness.

4.9 Automated Replication By An LLM Agent

We report an automated replication by an LLM agent (Kimi Agent, Moonshot AI) of the Stage B controlled-state-mutation repair-loop trajectory. Kimi re-implemented a simplified fixture family following the published protocol design and ran the same sequence of repair-loop iterations on Qwen3-8B. The agent observed a trajectory structurally similar to the author’s repair loop: the initial contract passed 0/40 strict runs, intermediate repairs surfaced missing obligations, and the final repaired contract passed 40/40 across the five perturbation conditions. This is not an independent replication by a separate human investigator; it is an automated execution trace produced by an LLM agent using the author’s SiliconFlow API key.

Table 9. Stage B repair-loop convergence by iteration.

Iteration	Pass rate	Key obligation surfaced
v1	0/40	Initial contract (same as author’s v5): missing gate, next_action enum, and citation policy
v2	single-point pass	Exact evidence array + next_action enumeration
v3	21/40	Full transition_record JSON structure
v4	33/40	Field-required declarations + canonical-name obligation
v5	40/40	Canonical-name obligation extended to the attestation field

The author verified the endpoint by re-running the frozen Stage B v5.4 protocol on Qwen3-8B through the live SiliconFlow API. The author-verified result was 40/40 strict passes, matching the automated replication exactly. The raw author-confirmation records, runner script, and execution manifest are preserved in the reproducibility package. The contract evolution ledger in Appendix E documents the v1→v5 obligation changes that produced the 0/40 → 40/40 trajectory.

After the author’s multi-model verification (§4.10) identified a material discrepancy in GLM-4-9B, Kimi Agent performed a full-trace re-run on 2026-07-27 with complete prompt/output capture across five groups: (A) GLM-4-9B on the original single-residual fixture, (B) GLM-4-9B on a harder double-residual adversarial variant matching the author’s fixture structure, and (C) Qwen3-8B on the same adversarial variant. The results (Group A: 40/40; Group B canonical: 8/8; Group B paraphrase: 1/8; Group C: 8/8 + 8/8) confirmed that the GLM discrepancy is explained by fixture difficulty, not model snapshot drift. Kimi’s README explicitly states (translated from the original Chinese): “Your fixture (double-residual plus semantically adjacent tempting options) stresses GLM along a dimension absent from my original single-residual fixture. The discrepancy is explained by fixture difficulty, not snapshot drift.” The original Chinese text and the full raw traces (including untruncated model outputs for every run) are preserved in the supplementary materials.

4.10 Multi-Model Interchangeability

The same frozen Stage B v5.4 protocol was executed across five model configurations to test whether the contract transfers to other model families without modification. The table below gives the author-verified pass rates. The label “author-verified” is important: the data were produced by the author via the live SiliconFlow API on 2026-07-27, not by the automated replication alone.

Table 10. Author-verified multi-model interchangeability results.

Model	Family	Author ver- ified	Wilson 95% CI	Notes
Qwen3-8B	Qwen3-8B	40/40	[0.912, 1.000]	Primary low-cost model; exact match with automated replication and V4 frozen result.
GLM-4-9B	GLM-9B	30/40	[0.598, 0.858]	Failures concentrated in <code>unknown_state_paraphrase</code> (0/8) and <code>field_alias</code> (6/8).
Qwen3-14B	Qwen3-14B	40/40*	[0.912, 1.000]	Initial run had 3 API read timeouts in canonical; targeted re-run (8/8 pass, 0 timeouts, avg 7.1s latency) confirmed timeouts were transient infrastructure issues.
DeepSeek-V3.2	DeepSeek-MoE	40/40	[0.912, 1.000]	Cross-family transfer; exact match with automated replication.
Qwen2.5-7B	Qwen2.5-7B	0/40	[0.000, 0.088]	Below-floor structural failure; could not produce valid JSON.

* Adjudicated endpoint, not a single observed batch: the raw 40-run gate observed 37/40 (three API read timeouts in the canonical condition); see Appendix D for raw counts and the re-run evidence supporting the adjudication.

Figure 1. Pass rates under a frozen contract across 5 models. See `figures/figure-1-multi-model-pass-rates.pdf`. Bars show strict pass counts out of 40 runs with 95% Wilson intervals; the dashed line marks the 0.912 Wilson lower bound. GLM-4-9B’s paraphrase vulnerability is annotated. Qwen3-14B shows the adjudicated endpoint (initial 37/40 with three transient API timeouts; targeted canonical re-run 8/8 — Appendix D).

Within the above-floor models tested, the frozen contract produced strict-conforming pass rates of 40/40 on Qwen3-8B, Qwen3-14B (adjudicated after transient API timeouts; Appendix D), and DeepSeek-V3.2, and 30/40 on GLM-4-9B. The contract transfers zero-shot to the Qwen3 and DeepSeek families. In one below-floor model tested (Qwen2.5-7B), we observed structural-level failure (0/40), characterized by inability to produce syntactically valid JSON. We do not claim universal interchangeability; the data show that contract transfer is real but model-family-specific.

GLM-4-9B paraphrase vulnerability. GLM-4-9B’s 30/40 result drew scrutiny because the automated replication had reported 40/40. After the author’s live API verification returned 30/40, Kimi Agent performed a full-trace re-run (§4.9) that confirmed the discrepancy and explained it. Kimi tested GLM-4-9B on two fixture variants: the original single-residual fixture (40/40) and a harder double-residual adversarial variant matching the author’s fixture structure (8/8 canonical, 1/8 paraphrase). The discrepancy is explained by fixture difficulty: the author’s fixture includes two residual unknown states plus a semantically adjacent “tempting” state (an evidence item mentioning a related but out-of-scope permission), which creates a pressure axis absent from the simpler original fixture.

Three independent observations of GLM-4-9B under the paraphrase condition are now on record:

Table 11. Independent observations of the GLM-4-9B paraphrase failure.

Observer	Date	Failure mode observed
Author (live API)	2026-07-27	Over-generation: added fabricated third state <code>permission_to_use_external_model_api</code>

Observer	Date	Failure mode observed
Kimi Agent (adversarial variant first test)	2026-07-27	Label normalization: shortened <code>branch_currently_checked_out</code> to <code>current_branch</code>
Kimi Agent (full-trace re-run)	2026-07-27	Language mixing: output Chinese paraphrases of labels instead of preserving canonical strings

The failure **mode** is unstable across observations —each run produced a different concrete failure form. The failure **location** is stable: all three observations converge on the `unknown_state_paraphrase` condition. This pattern supports the characterization that GLM-4-9B has a model-specific vulnerability to state-label discipline under paraphrased inputs, but the specific failure morphology is not reproducible. The paper therefore does not lock onto a single failure mode; it reports the convergent observation (paraphrase-condition failure) and discloses the mode instability.

Why the gradient is a feature, not a bug. The distribution 40/40, 40/40, 40/40, 30/40, 0/40 is more informative than “all above-floor models pass.” A result where every model scored 40/40 would not demonstrate that the contract has discriminating power —it might simply mean the task is too easy. The gradient shows that the frozen contract (a) admits models that can satisfy all obligations (Qwen3, DeepSeek), (b) identifies a specific condition where one model family needs additional repair (GLM paraphrase), and (c) cleanly separates structural-floor failures from contract-conformance failures. This is exactly the behavior expected of a methodology whose purpose is to surface and bound failure modes, not to declare universal success.

4.11 Framework-Agnostic Reference Core

The contract stack is implemented in a framework-agnostic reference core (`reference-core/contract_core.py`). The core contains approximately 260 lines of Python implementing the task specification, output contract, evidence bundle, validator gate, and deterministic evaluator without importing any agent framework. Adapters for PETFiSh and LangChain wrap this core in approximately 60 lines each. A dependency scan (`verify_zero_petfish_dep.py`) confirmed zero textual coupling between the core and any framework. This architecture makes the transferable artifact the contract stack, not the framework. Statistical equivalence testing across adapters (e.g., TOST on paired pf vs LangChain runs) is left to future work.

4.12 Floor Probe And Below-Floor Behavior

The model admission protocol in §3.7 includes a Tier-1 structural probe to eliminate below-floor candidates before the full 40-run gate. The Tier-1 probe tests four organ-level capabilities: valid JSON output, literal copy of a short provided value, field retention under a minimal prompt, and no fabrication when asked to return only what is given. A model that fails any of these is classified as below the structural floor for the task family and is excluded from the expensive Tier-4 full gate. The Tier-2 semantic probe tests task-specific capabilities such as enumeration compliance, canonical-name mapping, and order sensitivity; failure predicts repair-loop workload rather than floor status.

Qwen2.5-7B-Instruct is the below-floor candidate in this study. Across 40 runs of the unchanged frozen protocol, it produced malformed JSON, dropped fields, and corrupted tokens, with zero strict passes. This is a model failure under the §3.4 classification: the contract required valid JSON and the evaluator checked it correctly, yet the model could not satisfy the obligation. The correct repair action is either JSON-schema-constrained decoding or exclusion from the task pool. The result supports the use of a cheap structural probe: a model that cannot pass Tier-1 should not consume the full 40-run gate. We report only one below-floor model; the structural-floor claim is therefore scoped to this single observation.

4.13 Stage D Matched Overhead Matrix

Stage D compares the overhead of the no-contract (G0) and full-contract (G9) harness arms on the same frozen controlled-state-mutation macro. Figure 3 visualizes the comparison; the table below gives the matched results for Qwen3-8B and DeepSeek-V3.2. The G0 arm used a minimal prompt that still requested the same JSON schema; the G9 arm used the full contract stack.

Figure 3. Stage D matched overhead matrix. See `figures/figure-3-stage-d-overhead.pdf`. Three panels: (a) pass rate (G0 0% → G9 100%), (b) average prompt tokens per run (8.6× overhead), (c) average latency.

Table 12. Stage D overhead metrics: G0 versus G9.

Metric	Qwen3-8B G0	Qwen3-8B G9	Ratio	DeepSeek-V3.2 G0	DeepSeek-V3.2 G9	Ratio
Pass rate	0/20 (0%)	40/40 (100%)	—	0/20 (0%)	40/40 (100%)	—
Prompt tokens/run	247	2128	8.6×	251	2210	8.8×
Completion tokens/run	1344	1333	1.0×	254	478	1.9×
Average latency	75.3s	62.2s	0.8×	17.9s	24.9s	1.4×

Both models scored 0/20 without the contract and 40/40 with it. The contract stack —not the model —is the binding constraint on strict adherence in this task family. The full contract adds approximately 1,880 prompt tokens per call, which at SiliconFlow pricing costs approximately ¥0.001 per run. G9 latency is comparable to or lower than G0 on Qwen3-8B because the contract constrains the model to a compact structured output rather than allowing an unstructured “thinking aloud” response.

Table 13. Stage D cost per passing run.

Strategy	Cost per 40-run batch	Pass rate	Cost per passing run
G0 Qwen3-8B (cheap model, no contract)	¥0.7 (20 runs × ¥0.035)	0/20 (0%)	∞
G0 DeepSeek-V3.2 (premium model, no contract)	¥0.8 (20 runs × ¥0.040)	0/20 (0%)	∞
G9 Qwen3-8B (cheap model, full contract)	¥3.5 (40 runs × ¥0.087)	40/40 (100%)	¥0.087
G9 DeepSeek-V3.2 (premium model, full contract)	¥5.6 (40 runs × ¥0.14)	40/40 (100%)	¥0.14

The cheapest reliable strategy is G9 Qwen3-8B at approximately ¥0.087 per passing run; both G0 strategies are infinitely expensive per passing run because they produce zero passing runs. The comparison is limited to one task family and two models; it should be treated as a directional cost illustration, not a universal cost claim. Token pricing is approximate based on SiliconFlow listed rates at the time of testing.

4.14 Oracle-Coupling Audit: Where Does The Executable Policy Come From?

The methodology in §3 leans on deterministic evaluators: golden outputs, known-bad cases, and executable gate policies. This invites a construct-validity question that the earlier stages did not address directly. If the executable policy of the gate is itself derived from the answer that later scores the run —if the oracle and the policy share a source —then “the model satisfied the contract” reduces to “the model matched the answer key through an indirection.” We call this risk oracle coupling. The question instantiates the classical test oracle problem (Barr et al., 2015); the audit’s invariance conditions are metamorphic relations in the established sense (Chen et al., 2018; Liu et al., 2014); and the coupled-policy failure it guards against parallels reward misspecification, where satisfying the measured signal diverges from the intended capability (Amodei et al., 2016; Skalse et al., 2022). Version 5.1 adds a bounded, deterministic audit that separates the two sources for the audited task family and reports where the policy can and cannot come from.

The audit uses the same 28 fixed-transition fixtures (three task grammars) that back the FEC-v2 executable gate. It proceeds in paired steps, and every number in this subsection is an exact deterministic count over frozen artifacts —not a sample statistic. Figure 5 summarizes the design and results.

Figure 5. Oracle-coupling audit. See `figures/figure-oracle-coupling-audit.pdf`. Panel (a): paired policy-source interventions on the same 28 tasks —an answer-coupled reference compiler that reproduces all 392 frozen candidate classifications (56 valid accepted, 336 invalid blocked; label deletion blocks 28/28 compilations, label poisoning changes 28/28 contracts), a public-input compiler (label path not admitted; 28/28 contracts invariant under deletion and poisoning; 7/7 public-fact edits propagate), and an external evaluator boundary control. Panel (b): public-input metamorphic stress —112/112 invariance conditions nested in 28 tasks, and 55/55 fail-closed authority conditions nested in 13 baseline-apply tasks, with the five perturbation families grouped under the three coarse actions used in the text (remove 13/13, retarget 34/34, expire 8/8). Panel (c): external boundary control pinned to commit 2340fe2d —6/6 label-invariance groups, 2/2 public-fact relations, 2/2 policy-source relations, across 18 isolated evaluator calls and 0 model calls.

Answer-coupled reference compiler (FEC-v2, by construction). The authored oracle compiler reproduces all 28 task labels and all 392 frozen candidate classifications. Deleting its expected answer prevents 28/28 compilations; poisoning answer-derived authorization fields changes 28/28 compiled contracts. This is the coupling the audit exists to expose, reproduced as a same-run negative control.

Public-input compiler (positive control). A separate compiler receives only allowlisted public inputs —the request, current state, structured evidence, and structural policy constraints —with `expected_output`, the objective sentence, the prose gate rule, preselected decision-evidence IDs, and distractor IDs excluded and any injected answer-key aliases rejected. A static scan of the compiler core finds no answer-label tokens, fixture identifiers, I/O imports, or file, environment, network, or process access. Under the same interventions, deleting or poisoning the excluded fields leaves every compiled contract byte-identical under canonical serialization (28/28), while policy-relevant edits to public evidence or the public request change the derived decision in the specified direction (7/7 counterfactual relations over 4 base fixtures, spanning all three grammars). A metamorphic suite confirms the compiler responds to semantics rather than surface form: bijective renamings of domain and evidence identifiers and insertion of irrelevant evidence leave all 112 nested conditions invariant, while removing, retargeting, or expiring authority fails closed in all 55 nested conditions over the 13 baseline-apply tasks.

Commit-boundary and external controls. Two further controls bound the interpretation rather than extend it. Hardened file and SQLite state adapters test the post-acceptance check-to-commit boundary (version/CAS

binding, one-shot candidate freezing, nonce replay rejection, atomic same-directory replace); they record explicit residual assumptions —advisory locking, same-user trust, and pathname semantics —rather than claiming unconditional durability. A pinned external policy evaluator (Invariant, commit 2340fe2d, run in an isolated worker with network access disabled) keeps 6/6 fixed-input label groups unchanged under original, deleted, and poisoned labels, while responding to 2/2 public-trace edits and 2/2 policy-source edits, across 18 evaluator calls and 0 model calls. It is a boundary control on a second evaluator’s label dependence, not a replication of the FEC-v2 coupling pattern.

Claim boundary. The audit is offline, deterministic, and post hoc. The public-input compiler was developed after inspecting the three existing task grammars; it demonstrates that direct runtime answer dependence is unnecessary for these grammars, not that the compiler was cognitively independent of tasks seen during development or that the rules transfer to unseen grammars. Authority sensitivity is tested from apply to block only, not through block-to-apply repair. The nested metamorphic conditions are deterministic checks within 28 tasks, not independent samples. The audit does not establish prevalence of answer coupling across harnesses, independent task authorship, or complete mediation. Its frozen artifacts, per-module SHA-256 closures, and a single-command verifier (`code/runners/oracle-coupling/verify_all.py`) are released in the reproducibility package; regenerated byte-identity is not claimed —the supported reproduction model is freeze-and-verify.

5. Discussion And Limitations

5.1 What The Results Mean

The main finding is that some reliability requirements can be moved out of the model and into explicit contracts. When task state, admissible evidence, output shape, stage gates, trace requirements, and carried obligations are inspectable objects, low-cost models can satisfy bounded tasks that were unstable under weaker or broader prompts.

This changes how we interpret several failures in the experiments. The low-cost model did not preserve decision-trace retention until the trace was made structurally required. It did not preserve unknown state until unknown state was enumerated. It compressed known-state provenance until provenance-bearing state objects were required. It failed partial macro composition until cross-step carried obligations were made explicit. These are not just weaker answers. They are missing obligations that can be named and tested.

Stage B adds an important qualification. Making an obligation explicit can produce a stable passing protocol without proving that the added field has a large independent causal effect over every strong alternative specification. The v5.3 baseline already exposed exact final postconditions and passed 13/15. The explicit delta removed the remaining observed failures, but the preregistered effect threshold did not pass. With only two discordant pairs, the paired comparison has little power for small effects; it establishes neither equivalence nor the absence of a modest benefit. The v5.4 result is therefore evidence of bounded absolute stability, not proof that explicit delta is universally necessary or sufficient.

The GLM-4-9B discrepancy provides direct evidence for the value of the author-verification gate. Kimi’s automated replication reported 40/40 for GLM-4-9B, but the author’s live API verification found 30/40, with all eight failures concentrated in the `unknown_state_paraphrase` condition. After the author disclosed the discrepancy, Kimi Agent performed a full-trace re-run with complete prompt/output capture that confirmed the author’s finding and explained the gap: Kimi’s original fixture (single residual unknown state) did not exercise the pressure axis that the author’s fixture (double residual plus a semantically adjacent tempting state) creates. On the simpler fixture, GLM-4-9B still scores 40/40; on the harder fixture matching the author’s structure, it scores 8/8 canonical and 1/8 paraphrase. The discrepancy is therefore attributed to

fixture difficulty, not to model snapshot drift or API routing differences.

Three independent observations of GLM-4-9B under the paraphrase condition are now on record (author live API, Kimi adversarial-variant first test, Kimi full-trace re-run —all on 2026-07-27). Each produced a different concrete failure mode —over-generation of a third state, label shortening, and language mixing — but all three converged on the same condition. This failure-mode instability is itself a finding: the model’s vulnerability is to the *category* of paraphrased-label stress, not to any single mechanistic failure path. A contract that locks onto one failure mode would miss the others; the methodology correctly identifies the convergent location (paraphrase condition) without overfitting to a transient morphology.

Without the author-verification gate, the paper would have carried a false “40/40 cross-architecture” claim. The corrected 30/40 result is more valuable than the false 40/40: it identifies paraphrased state labels as a stress test that separates Qwen3 and DeepSeek families from GLM-4-9B, gives the repair loop a concrete next target, and demonstrates that the methodology has discriminating power —it can tell models apart on a specific contract dimension rather than declaring universal success. The gradient 40/40, 40/40, 40/40, 30/40, 0/40 is stronger evidence for the thesis (contract completeness is the binding constraint) than a uniform 40/40 would be, because it shows the contract surfaces real, model-specific, repairable failure modes.

5.2 Gap Compression Is Conditional

The original research motivation was model capability gap compression. The results support that idea in structured settings, but not as a general law. Structured extraction produced the clearest compression result because the input, output, and correctness criteria are highly constrained. Project initialization and research workflow produced a more complicated pattern: harnessing improved absolute contract adherence, but gap movement was mixed, undefined, or negative depending on the metric.

The implication is that gap compression is an observed outcome, not the thesis. It depends on the task, metric, baseline gap, and harness arm. The more useful question is whether the low-cost model reaches a declared contract-adherence threshold under explicit harnessing.

5.3 Why Negative Results Matter

Several negative or partial results carry real information. Stage 7p v1 showed that passing atoms do not automatically compose. Stage 7r showed that redesigned atoms could improve low-cost-model performance without fully repairing all contract-critical behavior. Stage 7e v2 and v3 exposed the missing obligations that made Stage 7e v4 meaningful.

The negative results are therefore part of the method, not noise around it.

5.4 Bounded Macros Are Not Full Workflows

Stage 7e v4 and Stage 7-next are fixed-input, no-tool, deterministic tasks. They do not involve live source discovery, file mutation, external tool execution, or changing workspace state. That boundary matters for how the results should be read.

The result should be stated carefully:

Low-cost models can complete bounded evidence-bound macros when reliability obligations are explicit.

It should not be stated as:

Low-cost models can reliably run full project initialization or full research workflows.

Full workflows introduce problems that the current macros do not test: tool selection, permission handling, filesystem mutation, live source volatility, partial failure recovery, long-horizon memory, user clarification, and multi-step state updates. The current work provides a method for approaching those workflows, not evidence that they are already solved.

5.5 Deterministic Evaluation, Sample Size, And Runtime Effects

The evaluation pipeline relies on deterministic evaluators, golden outputs, and known-bad outputs. This makes pass/fail decisions auditable and regression-testable. It also keeps the benchmark away from subjective preference scoring. The tradeoff is narrower validity: the metrics capture contract adherence, not prose quality, human usefulness, creative insight, or open-ended judgment.

The evaluator itself can also overfit. A known-bad suite covers only the failure modes that were anticipated or observed. Stage B v5.3-v5.4 partially addresses this risk with field-name, evidence-order, unknown-state-language, and distractor-evidence perturbations. Those conditions passed, but they remain a designed five-condition suite. The experiments do not cover arbitrary schema changes, adversarial evidence, event-order changes, multiple transitions, rollback, concurrent updates, or live tool state.

A distinct construct-validity risk is that the evaluator’s executable policy is derived from the same answer that scores the run. The oracle-coupling audit (§4.14) bounds this risk for the audited family: the policy is re-derivable from public task facts alone, byte-identically, with the answer path excluded and adversarially poisoned. The bound is real but narrow—it covers three inspected grammars and a post-hoc positive control, not unseen tasks or independently authored policies.

Several earlier repair experiments remain targeted smoke tests with small run counts. Stage 7e v4 used four targeted smoke runs after retry. Stage 7-next used four targeted smoke runs. Stage B v5.4 improves the repetition evidence for one controlled-transition protocol, but its 40 runs do not increase task diversity. Each perturbation condition has only eight runs, and its 8/8 Wilson interval is [0.676, 1.000]. The pooled interval describes repeated success under the frozen fixture family; it is not a population estimate over agent tasks.

Provider behavior also affected earlier experiments. Some SiliconFlow runs timed out, and Stage 7e v4 required retrying one timed-out run and one truncated-output retry before completion. Stage 7-next, Stage B v5.3, and Stage B v5.4 completed without provider errors or retries. In the multi-model verification (§4.10), Qwen3-14B initially produced 3 API read timeouts in the canonical condition; a targeted re-run of that condition (8 reps, 0 timeouts, avg 7.1s latency) confirmed the timeouts were transient infrastructure issues, and the model’s result was updated to 40/40. Runtime deviations remain validity threats because the study uses one provider and does not control provider-side batching, hardware, or service changes.

The present evidence uses SiliconFlow-backed runs and should be replicated across providers and model families before making provider-independent claims. This paper therefore does not make a provider-independent reliability claim.

5.6 PEtFiSh Specificity And Harness Cost

The fixtures and workflows are grounded in the PEtFiSh project context. The exact skills, packs, evidence ledgers, and backlog structures may not generalize to all agent systems. For this reason, PEtFiSh should be read as the implementation context. The transferable constructs are task specs, bounded memory, evidence bundles, output contracts, workflow gates, trace logs, validators, known-bad cases, and repair loops.

The claim is about the contract stack and the repair-loop protocol, not the specific pack catalog, skill names, or project directory conventions.

Contract-driven harnessing also adds overhead. It requires fixture design, schemas, evidence bundles, evaluators, local gates, manifests, event logs, and postprocessing. Stage B v5.4 records 102,984 total tokens and a 19.500-second median latency for 40 G9 runs. Stage D (§4.13) provides a matched G0/G9 overhead matrix for Qwen3-8B and DeepSeek-V3.2 on the same frozen macro: both models scored 0/20 without the contract and 40/40 with it, the G9 contract added approximately 1,880 prompt tokens per call (about ¥0.001 per run at SiliconFlow rates), and G9 latency on Qwen3-8B was lower than G0 because the contract constrained the model to compact structured output. The Stage D comparison is limited to one task family and two models; it should be treated as a directional cost illustration, not a universal claim that the low-cost-model harness is cheaper per successful task than using a stronger model directly. For simple tasks, engineering and inference overhead may exceed the benefit. There is also a risk of over-constraint: strong models may become more stable but less flexible under strict contracts.

5.7 Future Work

The next empirical decision is between breadth and economics. Stage D (§4.13) provides an initial matched overhead matrix for Qwen3-8B and DeepSeek-V3.2 under G0 and G9 on the same frozen macro; extending that matrix to GLM-4-9B, Qwen3-14B, and additional perturbation conditions would strengthen the cost illustration. A broader reliability path would instead add multiple transition events, rollback, event ordering, live tool state, or a second task family. Either path requires a new preregistration; the current 40-run result should not be reused as if it answered those questions.

A concrete repair target identified by the multi-model verification is GLM-4-9B’s paraphrase-condition vulnerability (§4.10). Three independent observations confirm that GLM-4-9B fails under paraphrased state labels, but the failure mode is unstable (over-generation, label shortening, language mixing). A v6 contract iteration that strengthens the canonical-name obligation for paraphrased inputs—for example, by adding an explicit “do not shorten, translate, or normalize state labels” clause with paraphrase-specific known-bad fixtures—is the natural next repair-loop step. If the v6 contract lifts GLM-4-9B from 30/40 to 40/40, it would provide a second end-to-end demonstration of the repair loop’s value on a different model family. If it does not, the failure classification (§3.4) would upgrade from “contract defect responsive to repair” to “model failure requiring constrained decoding or exclusion,” which is also a valid outcome.

6. Conclusion

Contract-driven harness engineering makes some low-cost-model failures observable, repairable, and regression-testable by moving reliability obligations into explicit contracts. Model quality still matters. The point is narrower: for bounded productivity tasks, part of agent reliability can be engineered outside the model.

The supported claim is weak-model enablement on bounded contract-critical operations. Gap compression remains conditional. It is clearest in structured extraction and present on some contract metrics in mechanism and partial macro tests. It is mixed or undefined in broader project-initialization and research-workflow slices.

The practical value is the repair loop. A harness failure can be turned into a named obligation, a contract revision, a known-bad fixture, a local regression gate, a targeted ablation, a fresh stability confirmation, and an updated claim boundary. In the controlled-transition case, that process produced 40/40 strict passes across five tested perturbations. The paired ablation still missed its preregistered large-effect threshold, so the conclusion remains bounded: the repaired protocol was stable in the tested setting; the isolated causal contribution of any single repair component and broader generality remain unresolved.

Version 5 of this paper adds three methodological layers that were not explicit in the frozen v4 body: a failure-classification rule (§3.4) that separates contract defects from evaluator defects and model failures; a frozen-protocol specification (§3.5) that pins every variable that could invalidate a stability claim; and a model-admission protocol (§3.7) that uses cheap structural probes to eliminate below-floor candidates before the full 40-run gate. It also adds the cross-model interchangeability evidence (§4.10), the automated-replication record (§4.9), the framework-agnostic core reference implementation (§4.11), the floor-probe result (§4.12), and the matched overhead matrix (§4.13). The GLM-4-9B discrepancy —initially reported as 40/40 by the automated replication, corrected to 30/40 by the author’s live verification, and subsequently confirmed by the automated agent’s full-trace re-run —is retained as the strongest evidence for the value of the verification gate. The discrepancy is explained by fixture difficulty (single-residual vs double-residual plus tempting state), not snapshot drift, and the three independent observations of GLM’s paraphrase-condition failure (with unstable failure modes but stable failure location) give the repair loop a concrete next target. These additions do not change the bounded claim; they make the methodology, its scope, and its reproducibility artifacts more explicit. Version 5.1 adds one further layer: the oracle-coupling audit (§4.14), which separates the executable policy’s source from the scoring answer for the audited family and ships the audit itself as freeze-and-verify artifacts.

Appendix A. Current Non-Claims

This paper should not claim:

- low-cost models are generally equivalent to strong models;
- harnessing universally compresses model gaps;
- full project initialization is solved;
- full research workflow is solved;
- the harness is production ready;
- fixed macro success implies open-ended tool-using workflow reliability;
- explicit transition delta has a proven 0.20 causal advantage over exact postconditions;
- one 40-run fixture family establishes arbitrary state-machine reliability;
- current evidence establishes a favorable cost or latency tradeoff against a strong model;
- the oracle-coupling audit establishes prevalence of answer coupling across harnesses, independent task authorship, unseen-grammar transfer, or complete mediation (§4.14).

Appendix B. Contribution-To-Evaluation Alignment

Table B.1. Contribution-to-evaluation alignment.

Contribution	Evaluation support	Boundary
Contract-driven harness model	Task slices and methods artifacts	Method definition, not a production-readiness claim.
Mechanism atoms	Atom definition, coverage framework, Stage 6-7 atom results	Atom pass does not prove workflow pass.
Conditional gap compression	Structured extraction, project initialization, research workflow slices	Compression only when baseline gaps are nonzero and gap movement is not reversed.
Repair-loop protocol	Stage 7e v1-v4 and Stage B v5-v5.4	Fixed evidence-decision and controlled-transition macros.

Contribution	Evaluation support	Boundary
Bounded weak-model enablement	Stage 7e v4, Stage 7-next, and Stage B v5.4	Fixed-input, no-tool, deterministic macros.
Controlled-transition stability	Stage B v5.4	One frozen model/provider/harness/fixture family.
Independent explicit-delta effect	Stage B v5.3	Mixed; preregistered 0.20 threshold not met.

Appendix C. Evidence Traceability Matrix

Table C.1. Evidence traceability matrix.

Paper claim	Evidence IDs	Source IDs	Status
Contract-rich harnessing improves absolute contract adherence and can compress gaps under constrained conditions.	P2-E28, P2-E30, P2-E32, P2-E33	P2-SILICONFLOW-V2-FULL24, P2-SILICONFLOW-PROJECT-INIT-12, P2-SILICONFLOW-RESEARCH-WORKFLOW-12, P2-CLAIM-BOUNDARY-MEMO	Supported with conditional wording.
Structured extraction is the clearest positive gap-compression task slice.	P2-E27, P2-E28	P2-SILICONFLOW-V2-FULL24	Supported for tested SiliconFlow v2 slice.
Project initialization and research workflow do not support universal gap compression.	P2-E30, P2-E32, P2-E33	P2-SILICONFLOW-PROJECT-INIT-12, P2-SILICONFLOW-RESEARCH-WORKFLOW-12, P2-CLAIM-BOUNDARY-MEMO	Supported; use mixed/undefined wording.
Mechanism atoms make broad workflow failures interpretable.	P2-E35, P2-E36, P2-E56, P2-E60	P2-MECHANISM-ATOM-DEFINITION, P2-MECHANISM-ATOM-COVERAGE, P2-STAGE7R-REVISED-ATOMS, P2-STAGE7R1-A2R-A7R-SMOKE	Supported as methodology and targeted empirical repair evidence.
Atom success does not automatically imply macro composition success.	P2-E51, P2-E52	P2-STAGE7P-PARTIAL-COMPOSITION	Supported by Stage 7p v1 failure.

Paper claim	Evidence IDs	Source IDs	Status
Explicit cross-step carried obligations can repair the Stage 7p composition failure.	P2-E53, P2-E54	P2-STAGE7P-V2-COMPOSITION-RETENTION	Supported for A10 -> A9 -> A6 partial macro.
Stage 7r.1 repaired low-cost-model A2R/A7R failures through tighter output contracts.	P2-E57, P2-E58, P2-E59, P2-E60	P2-STAGE7R1-A2R-A7R-PREP, P2-STAGE7R1-A2R-A7R-SMOKE	Supported for targeted atoms only.
Stage 7e v1-v4 demonstrates a repair-loop protocol for a fixed evidence-decision macro.	P2-E62, P2-E64, P2-E66, P2-E68, P2-E69, P2-E70	P2-STAGE7E-EVIDENCE-DECISION, P2-STAGE7E-V2-RETENTION, P2-STAGE7E-V3-STATE-RETENTION, P2-STAGE7E-V4-KNOWN-STATE-PROVENANCE, P2-CLAIM-BOUNDARY-MEMO	Supported with fixed-input/no-tool boundary.
Stage 7-next transfers Stage 7e v4 obligations to a neighboring method-plan macro.	P2-E72, P2-E74, P2-E75	P2-STAGE7-NEXT-METHOD-PLAN-LOCAL, P2-STAGE7-NEXT-METHOD-PLAN-SMOKE	Supported as narrow transfer evidence.
Evidence-binding separation did not show the preregistered large independent effect.	P2-E160, P2-E161, P2-E162, P2-E163, P2-E164	P2-STAGE-B-V52-EVIDENCE-BINDING-ABLATION-LOCAL, P2-STAGE-B-V52-EVIDENCE-BINDING-ABLATION-EXECUTION, P2-STAGE-B-V52-EVIDENCE-BINDING-ABLATION-EVALUATION, P2-STAGE-B-V52-EVIDENCE-BINDING-ABLATION-FAILURE-AUDIT, P2-STAGE-B-V52-EVIDENCE-BINDING-ABLATION-DECISION	Supported as a bounded negative ablation result.
Explicit transition delta passed 15/15, but the 0.133 risk difference missed the preregistered 0.20 threshold; exact McNemar $p=0.500$.	P2-E165, P2-E166, P2-E167, P2-E168, P2-E176	P2-STAGE-B-V53-EXPLICIT-DELTA-ABLATION, P2-STAGE-B-V53-PAIRED-ANALYSIS-CORRECTION	Supported as a mixed causal result.

Paper claim	Evidence IDs	Source IDs	Status
The frozen explicit-delta protocol passed 40/40 fresh runs across five perturbation conditions.	P2-E169, P2-E170, P2-E171, P2-E172	P2-STAGE-B-V54-EXPLICIT-DELTA-STABILITY	Supported as bounded absolute stability, not task-family or state-machine generality.
The executable policy for the audited family is derivable from public task facts without runtime answer access (§4.14).	OIC-v1, MPIV1, IEBV1 frozen result sets	data/reproduction/oracle-coupling/* SHA-256 closures; code/runners/oracle-coupling/verify_all.py	Supported as a post-hoc positive control over three inspected grammars; not cognitive independence or unseen-grammar transfer.
Full project initialization, full research workflow, production readiness, and general model equivalence remain non-claims.	P2-E33, P2-E63, P2-E69, P2-E70, P2-E75	P2-CLAIM-BOUNDARY-MEMO, P2-STAGE7E-EVIDENCE-DECISION, P2-STAGE7E-V4-KNOWN-STATE-PROVENANCE, P2-STAGE7-NEXT-METHOD-PLAN-SMOKE	Supported as explicit boundary.
Related work: orchestration, declarative programs, structured outputs, retrieval/tools, memory, verification, and skill ecosystems are adjacent lines.	P2-E05, P2-E06, P2-E07, P2-E08, P2-E09, P2-E83, P2-E84, P2-E85, P2-E86, P2-E87, P2-E88, P2-E89, P2-E90, P2-E91, P2-E92, P2-E93, P2-E94, P2-E95, P2-E96, P2-E98	External source IDs listed in source-index.md	Supported as background; convert to publication-style citations before submission.
Related work: oracle-coupling precedents in the test-oracle problem, metamorphic testing, and reward-misspecification literature (§2.5, §4.14).	Positioning only; no empirical dependency	P2_EXT_NONTESTABLE_PROGRAMS, P2_EXT_ORACLE_PROBLEM, P2_EXT_MT_ORACLE_ALLEVIATION, P2_EXT_METAMORPHIC_SURVEY, P2_EXT_AI_SAFETY, P2_EXT_REWARD_HACKING	Supported as background positioning; records verified against DBLP/Crossref 2026-08-17.

Appendix D. Multi-Model Interchangeability Records

This appendix contains the full author-verified multi-model records for the Stage B v5.4 frozen protocol. All runs used SiliconFlow, temperature 0, and the same frozen prompt/evaluator/perturbation manifest. Qwen3-8B was the primary model; the other four models provided auxiliary confirmation. The verification was run on 2026-07-27 with the runner script `research/04_methods/scripts/verify_stage_b_v54_live.py`.

Table D.1. Multi-model strict-pass summary.

Model	Model ID	Family	Pass	Fail	Rate	Wilson 95% CI
Qwen3-8B	Qwen/Qwen3-8B	Qwen3 8B	40	0	1.000	[0.912, 1.000]
GLM-4-9B	THUDM/GLM-4-9B-0414	GLM 9B	30	10	0.750	[0.598, 0.858]
Qwen3-14B	Qwen/Qwen3-14B	Qwen3 14B	37*	3	0.925	[0.801, 0.974]
DeepSeek-V3.2	deepseek-ai/DeepSeek-V3.2	DeepSeek MoE	40	0	1.000	[0.912, 1.000]
Qwen2.5-7B	Qwen/Qwen2.5-7B-Instruct	Qwen2.5 7B	0	40	0.000	[0.000, 0.088]

- Qwen3-14B: three failures were API read timeouts on the first three calls of the canonical condition; all 37 valid calls passed. A targeted re-run of the canonical condition (8/8 pass, 0 timeouts, avg 7.1 s latency) confirmed the timeouts were transient infrastructure faults, not model failures; §4.10 therefore reports the adjudicated endpoint 40/40 with Wilson CI [0.912, 1.000].

Per-condition strict-pass counts (8 runs per condition):

Table D.2. Per-condition strict-pass counts by model.

Condition	Qwen3-8B	GLM-4-9B	Qwen3-14B	DeepSeek-V3.2	Qwen2.5-7B
canonical	8/8	8/8	5/8*	8/8	0/8
field_alias	8/8	6/8	8/8	8/8	0/8
evidence_order_shuffled	8/8	8/8	8/8	8/8	0/8
distractor_evidence	8/8	8/8	8/8	8/8	0/8
unknown_state_paraphrase	8/8	0/8	8/8	8/8	0/8

- Qwen3-14B canonical: three API read timeouts, not model failures.

GLM-4-9B failures were concentrated in the `unknown_state_paraphrase` condition (all 8 runs failed `residual_unknown_vocabulary_accuracy`) and in `field_alias` (2 runs failed `state_transition_accuracy`). The `unknown_state_paraphrase` condition paraphrases state labels (e.g., “`current_git_branch`” → “active development branch”); GLM-4-9B maps these differently than the Qwen3 and DeepSeek families. This identifies a concrete repair target: extending canonical-name coverage to paraphrased aliases in the attestation field. The raw records, runner script, and execution manifest are in `research/05_analysis/author-confirmation-records/`.

Appendix E. Contract Evolution Ledger

This ledger documents how the controlled-state-mutation contract evolved through repair-loop iterations. Each entry records the failure observed, the missing obligation identified, the contract change, and the

resulting pass rate. Figure 2 visualizes the convergence trajectory. The full ledger is preserved in `research/05_analysis/contract-evolution-ledger.md`.

Figure 2. Repair-loop convergence: 0/40 $\rightarrow$ 40/40 over four iterations. See `figures/figure-2-repair-loop-convergence.pdf`. Each point shows the strict pass rate with 95% Wilson interval; annotations describe the obligation surfaced at each step (evidence array, next_action enumeration, transition record structure, canonical-name obligation, attestation field coverage).

Appendix F. Reproducibility Verification

All experiments reported in this paper were independently reproduced across four rounds totaling 1,458 API calls:

- **Round 01 - 02** (480 calls): bare API with full provenance capture (prompt, raw response, parsed JSON, metrics per run). Confirmed all multi-model (§4.10) and Stage D (§4.13) results. Stored in `experiment-rounds/round-01-author-verification-20260727/` and `experiment-rounds/round-02-full-reproducibility/`.
- **Round 03** (469 calls): bare API re-execution of all 29 frozen artifact directories covering §4.2–4.8. 425/469 runs produced valid JSON; 44 failures were API timeouts (infrastructure, not model issues). Stored in `experiment-rounds/round-03-full-history/`.
- **Round 04** (509 calls): petfishframework Agent + ReAct() pipeline —the exact original execution path. All 29 stages re-executed; Stage B v5.4 achieved 40/40 runs with 100% text similarity (`sim=1.0`) to frozen outputs. Stage B v3 – v5.3 achieved 97 – 100% high-similarity reproduction. Stored in `experiment-rounds/round-04-precise-petfishframework/`.
- **Deterministic offline audit** (0 API calls): the oracle-coupling audit of §4.14 —six frozen modules (authored-oracle baseline, public-input compiler, metamorphic suite, hardened adapters, SQLite second harness, external boundary control) with per-module SHA-256 manifests, verified by a single command (`python code/runners/oracle-coupling/verify_all.py`, 6/6 closures) on Windows and Linux. Stored in `data/reproduction/oracle-coupling/`.

Stage B v5.4 —the paper’s headline stability claim —achieved 100% text similarity (`sim=1.0`) on all 40 runs in Round 04, confirming that the frozen protocol is bit-exact reproducible through the original framework at `temperature=0`. Earlier stages (7e, 7p, 7r) produced structurally valid but textually divergent outputs, consistent with their longer reasoning chains and higher surface variability. The inter-round comparison is preserved in `experiment-rounds/_comparison-round-01-vs-02.md`.

Table D.3. Contract evolution ledger.

Version	Failure observed	Missing obligation	Contract change	Pass rate
v4	—	Exact evidence array, closed-vocabulary retention	Baseline exact-retention contract	4/4 local gate
v5	0/4 strict pass	Transition gate, next_action enum, evidence citation	Add transition event, postconditions, record	0/4
v5.1	Contract defects from v5	Gate visibility, immutable evidence bindings	Full model-visible gate, evidence_bindings separation	4/4 smoke

Version	Failure observed	Missing obligation	Contract change	Pass rate
v5.2	Null evidence-binding effect	—	Ablation: with/without explicit evidence bindings	15/15 vs 14/15; McNemar p=0.500
v5.3	Residual-state errors	Explicit transition delta	Add re-quired_transition_delta	15/15 strict
v5.4	Stability under freeze	—	Freeze all artifacts; run 40 fresh	40/40 author verified

The repair loop externalized five previously implicit obligations: transition gate visibility, next_action enumeration, evidence citation policy, transition delta operations, and canonical-name field coverage. Each was classified as a contract defect under §3.4 because the obligation existed in the author’s intent but was not declared in the model-visible contract.

Reproducibility Package

This draft is supported by a public reproducibility package in the project repository and by local artifacts under research/. The package includes the source index, evidence ledger, mechanism-atom definitions, macro fixtures, prompt manifests, provider event logs, model-output artifacts, deterministic evaluator outputs, metric summaries, stage reports, citation audit reports, and citation metadata.

Repository: <https://github.com/kylecui/contract-driven-harness-study>.

A reviewer can audit the claims in five steps:

1. Read Appendix C to map each paper claim to evidence IDs.
2. Read Appendix D for the full multi-model interchangeability records and Appendix E for the contract evolution ledger.
3. Open research/03_evidence/evidence-ledger.jsonl and locate those evidence IDs.
4. Inspect the referenced stage report, metric summary, fixture, validator output, provider event log, and model-output artifact.
5. Re-run the deterministic local gate for the corresponding fixture when a fixture/evaluator pair is provided.

For example, the Stage B v5.4 claim starts from P2-E169 through P2-E172. A reviewer should then inspect the preregistration, freeze manifest, prompt manifest, 40 execution records, raw outputs, deterministic evaluation, analysis, and freeze-integrity audit before treating the bounded stability claim as supported.

When available, stage reports include the exact command or script path used to regenerate local evaluator outputs. The repository README and method scripts provide the current entry points for local gate reruns and artifact inspection.

The core traceability files are:

- research/01_sources/source-index.md
- research/01_sources/contract-driven-harness-citation-metadata.md
- research/03_evidence/evidence-ledger.jsonl
- research/06_outputs/contract-driven-harness-compact-results-appendix.md
- research/07_reviews/contract-driven-harness-citation-audit.md

- `research/07_reviews/contract-driven-harness-source-coverage.md`
- `research/07_reviews/contract-driven-harness-unsupported-claims.md`
- `code/runners/oracle-coupling/` (audit runners; §4.14)
- `data/reproduction/oracle-coupling/` (frozen audit artifacts and SHA-256 closures; §4.14)
- `data/analysis/oracle-coupling/figure-source-data.json` (Figure 5 source data)
- `data/kimi-replication/kimi-automated-replication/` (Kimi Agent raw traces and README; §4.9, including the original Chinese text of the quoted fixture-difficulty statement)

External references are prepared in `research/06_outputs/contract-driven-harness-references.bib`. Local empirical claims should be checked against Appendix C and the evidence ledger rather than treated as ordinary literature citations.

Use Of AI Assistance

Kimi Agent, a commercial large-language-model assistant operated by Moonshot AI, was used to execute parts of the empirical work reported in this paper. The experiments in §4.9–4.13 were carried out by Kimi under the author’s direction, with the generated records, logs, and code artifacts archived in the reproducibility package.

Kimi executed four experimental batches: (a) the Stage B v5.4 protocol replication on Qwen/Qwen3-8B, with controlled state-mutation perturbations (five conditions $\times$ eight repetitions = 40 runs); (b) the multi-model interchangeability sweep across five models (Qwen3-8B, GLM-4-9B, Qwen3-14B, DeepSeek-V3.2, Qwen2.5-7B), 40 runs each; (c) the cross-framework comparison between the PETFiSh and LangChain execution pipelines on the same Stage B v5.4 protocol; and (d) the floor-model probe suite, comprising eight probe conditions across the same five models. For each batch Kimi ran the protocol, collected raw model outputs, applied the deterministic evaluator, and produced the pass-rate and Wilson-interval summaries.

Kimi did not author this paper, did not design the original contract or the harness methodology, and did not select the evaluation criteria, thresholds, or claim boundaries on its own. Those decisions were made by the human author and recorded in the preregistered protocol documents.

The author verified Kimi’s outputs through a four-round reproduction campaign totaling 1,458 API calls (Appendix F). Round 01–02 (480 calls) re-ran the full Stage B v5.4 protocol and Stage D through the live SiliconFlow API with complete provenance. The verification confirmed the Qwen3-8B endpoint (40/40), the DeepSeek-V3.2 result (40/40), the Qwen3-14B result (40/40 after confirming initial timeouts were transient), and the Qwen2.5-7B floor result (0/40). It also revealed a material discrepancy for GLM-4-9B: Kimi reported 40/40, while the author’s live runs found 30/40 (Round 01) and 29/40 (Round 02). Kimi subsequently performed a full-trace re-run that confirmed the discrepancy is explained by fixture difficulty, not model snapshot drift. Because of this discrepancy, all §4.9 results are labeled as **automated replication by an LLM agent (Kimi Agent)** and are not described as independent replication. Round 04 (509 calls) reproduced all frozen prompts through the petfishframework Agent + ReAct pipeline, achieving bit-exact reproduction ($\text{sim}=1.0$) on Stage B v5.4.

Kimi is itself a large language model. It may therefore share failure modes with the models under test, or it may interpret the contract in ways that flatter the protocol rather than stress it. Using an LLM agent to run an LLM-evaluation pipeline is a form of circular instrumentation: the executor and the evaluated system belong to the same model class. The replication should therefore be treated as an automated execution trace subject to the same validity threats as any LLM-mediated measurement, and it has been confirmed by the author’s own runs where stated.

A resource-level conflict of interest also exists. The author provided a personal SiliconFlow API key for

all Kimi-executed runs; the compute was paid for by the author. The automation was operational—Kimi followed the published protocol—but it was not resource-neutral.

This disclosure is provided in line with the AI assistance and reproducibility policies of ACL, EMNLP, AAAI, and NeurIPS, which require authors to report when generative AI or LLM-based tools were used in research execution, analysis, or writing.

References

- Amodei, Dario and Olah, Chris and Steinhardt, Jacob and Christiano, Paul and Schulman, John and Mané, Dan (2016). Concrete Problems in AI Safety. arXiv:1606.06565. doi:10.48550/arXiv.1606.06565.
- Anthropic (n.d.). Building Effective Agents. <https://www.anthropic.com/engineering/building-effective-agents>. [Accessed 2026-06-09]
- Barr, Earl T. and Harman, Mark and McMinn, Phil and Shahbaz, Muzammil and Yoo, Shin (2015). The Oracle Problem in Software Testing: A Survey. IEEE Transactions on Software Engineering, 41(5), pp. 507–525. doi:10.1109/TSE.2014.2372785.
- Bhardwaj, V. P. (2026). Agent Behavioral Contracts: Formal Specification and Runtime Enforcement for Reliable Autonomous AI Agents. arXiv:2602.22302. doi:10.48550/arXiv.2602.22302. [Abstract from arXiv; detailed overview via alphaXiv, accessed 2026-07-27]
- Chen, Tsong Yueh and Kuo, Fei-Ching and Liu, Huai and Poon, Pak-Lok and Towey, Dave and Tse, T. H. and Zhou, Zhi Quan (2018). Metamorphic Testing: A Review of Challenges and Opportunities. ACM Computing Surveys, 51(1), pp. 4:1–4:27. doi:10.1145/3143561.
- Chennabasappa, Sahana and Nikolaidis, Cyrus and Song, Daniel and Molnar, David and Ding, Stephanie and Wan, Shengye and Whitman, Spencer and Deason, Lauren and Doucette, Nicholas and Montilla, Abraham and Gampa, Alekhya and de Paola, Beto and Gabi, Dominik and Crnkovich, James and Testud, Jean-Christophe and He, Kat and Chaturvedi, Rashnil and Zhou, Wu and Saxe, Joshua (2025). LlamaFirewall: An Open Source Guardrail System for Building Secure AI Agents. arXiv:2505.03574. doi:10.48550/arXiv.2505.03574.
- Contract-Driven Harness Study (2026). Local Experiment Artifacts and Evidence Ledger. Local reproducibility package under research/.
- Cui, Yin (2026). PEtFiSh: Agent Skill Packs, MCP Services, and Harness Engineering Infrastructure. <https://github.com/kylecui/petfish.ai>. [Accessed 2026-08-27]
- dottxt-ai (n.d.). Outlines Documentation. <https://dottxt-ai.github.io/outlines/latest/>. [Accessed 2026-06-09]
- Guardrails AI (n.d.). Validators Documentation. <https://guardrailsai.com/docs/concepts/validators/>. [Accessed 2026-06-09]
- Khattab, Omar and others (2023). DSPy: Compiling Declarative Language Model Calls into Self-Improving Pipelines. arXiv:2310.03714. doi:10.48550/arXiv.2310.03714.
- LangChain (n.d.). LangGraph Documentation. <https://docs.langchain.com/oss/python/langgraph>. [Accessed 2026-06-09]
- Lee, Alexander W. and Chan, Justin and Fu, Michael and Kim, Nicolas and Mehta, Akshay and Raghavan, Deepti and Cetintemel, Ugur (2025). Semantic Integrity Constraints: Declarative Guardrails for AI-Augmented Data Processing Systems. arXiv:2503.00600. doi:10.48550/arXiv.2503.00600.
- Letta (n.d.). Agents Overview Documentation. <https://docs.letta.com/guides/agents/overview/>. [Accessed 2026-06-09]
- Lewis, Patrick and others (2020). Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. arXiv:2005.11401.
- Liu, Huai and Kuo, Fei-Ching and Towey, Dave and Chen, Tsong Yueh (2014). How Effectively Does

- Metamorphic Testing Alleviate the Oracle Problem?. *IEEE Transactions on Software Engineering*, 40(1), pp. 4–22. doi:10.1109/TSE.2013.46.
- Microsoft (n.d.). AutoGen Documentation. <https://microsoft.github.io/autogen/>. [Accessed 2026-06-09]
 - Microsoft (n.d.). Semantic Kernel Documentation. <https://learn.microsoft.com/en-us/semantic-kernel/>. [Accessed 2026-06-09]
 - OpenAI (n.d.). Structured Outputs Guide. <https://platform.openai.com/docs/guides/structured-outputs>. [Accessed 2026-06-09]
 - Packer, Charles and others (2023). MemGPT: Towards LLMs as Operating Systems. arXiv:2310.08560.
 - Patil, Shishir G. and others (2023). Gorilla: Large Language Model Connected with Massive APIs. arXiv:2305.15334.
 - Schick, Timo and others (2023). Toolformer: Language Models Can Teach Themselves to Use Tools. arXiv:2302.04761.
 - Sigdel, Baral (2026). Guardrails as Infrastructure: Policy-First Control for Tool-Orchestrated Workflows. arXiv:2603.18059. doi:10.48550/arXiv.2603.18059.
 - SiliconFlow (n.d.). Chat Completions and Model Documentation. <https://docs.siliconflow.cn/cn/api-reference/chat-completions/chat-completions>. [Accessed 2026-06-09; model list also consulted at <https://docs.siliconflow.cn/cn/userguide/models>]
 - Singhvi, Arjun and others (2023). DSPy Assertions: Computational Constraints for Self-Refining Language Model Pipelines. arXiv:2312.13382. doi:10.48550/arXiv.2312.13382.
 - Skalse, Joar and Howe, Nikolaus H. R. and Krasheninnikov, Dmitrii and Krueger, David (2022). Defining and Characterizing Reward Hacking. *Advances in Neural Information Processing Systems* 35 (NeurIPS 2022).
 - Wang, Pengcheng and others (2026). AgentSPEX: An Agent SPECification and EXecution Language. arXiv:2604.13346. doi:10.48550/arXiv.2604.13346.
 - Wang, H. and Poskitt, C. M. and Sun, J. (2026). AgentSpec: Customizable Runtime Enforcement for Safe and Reliable LLM Agents. 2026 IEEE/ACM 48th International Conference on Software Engineering (ICSE '26), ACM. arXiv:2503.18666. doi:10.48550/arXiv.2503.18666.
 - Weyuker, Elaine J. (1982). On Testing Non-Testable Programs. *The Computer Journal*, 25(4), pp. 465–470. doi:10.1093/comjnl/25.4.465.
 - Xavier, Melwin and M A, Vaisakh and Jolly, Melveena and Xavier, Midhun (2026). Agentproof: Static Verification of Agent Workflow Graphs. arXiv:2603.20356. doi:10.48550/arXiv.2603.20356.
 - Yao, Shunyu and others (2022). ReAct: Synergizing Reasoning and Acting in Language Models. arXiv:2210.03629.
 - Zhu, He and Qin, Tianrui and Zhu, King and Huang, Heyuan and Guan, Yeyi and Xia, Jinxiang and Yao, Yi and Li, Hanhao and Wang, Ningning and Liu, Pai and Peng, Tianhao and Gui, Xin and Li, Xiaowan and Liu, Yuhui and Jiang, Yuchen Eleanor and Wang, Jun and Zhang, Changwang and Tang, Xiangru and Zhang, Ge and Yang, Jian and Liu, Minghao and Gao, Xitong and Liu, Jiaheng and Zhou, Wangchunshu (2025). OAgents: An Empirical Study of Building Effective Agents. arXiv:2506.15741. doi:10.48550/arXiv.2506.15741.