

# A Neural Network Approach to Classifying Banana Ripeness

Kyle Demeule (kdd2@sfu.ca), Bernard S Chan (bernardc@sfu.ca), Saeed Soltani (saeeds@sfu.ca)

Department Computing Science, Faculty of Applied Sciences, Simon Fraser University

## Introduction

- Interested in classifying fruit ripeness using machine learning methods.
- Previously studied by Saad et al. [2009] through neural network methods.
- More than just bananas: Aim to improve upon previous work by incorporating non-banana objects.
- Previous data set unavailable; will establish our own data set.

## Data Collection

- Generated the data set by taking pictures of bananas and objects that are not bananas.
- Lighting, camera (Canon S90) and background were controlled.
- Used 12 unique bananas at various stages to represent the three stages ripeness:
  - 1 pre-ripe,
  - 2 ripe, and
  - 3 rotten.
- Used green pepper, apple, tomato, lemon and lime as non-banana objects.
- Pictures were resized and cropped to a square.
- Incorporated each picture at  $0^\circ$ ,  $90^\circ$ ,  $180^\circ$  and  $270^\circ$  of rotation to increase the number of pictures in the data set by four fold.



(a)



(b)



(c)

Figure 1: (a) Pre-ripe banana. (b) Ripe banana. (c) Overripe banana.

## Tools and Methods

- Caffe.
- AlexNet.
- SciKit Learn: a Python library of machine learning algorithms.

## Features Extraction via AlexNet

## Experimental Results

## Results

### General Nonlinear Criteria

Based on all aforementioned criteria, the digraph in Figure ?? is a nontrivial example that would admit a general nonlinear Hamiltonian coupled cell system.

### Conclusion and Potential Applications

- Able to enhance previous work by adding non-banana objects.
- Working towards generalizing ripeness detection for fruits, vegetable and other in general.
- Industrial application: automatic large scale sorting of fruits and vegetable based on ripeness and type.
- Mobile app for visually disabled: quickly find the ripeness of fruits and vegetables via machine learning model.

### Acknowledgement

We want to thank our TA Zhiwei (Lucas) Deng for his suggestions and guidance on using Caffe as well as AlexNet. Furthermore, we want to thank Dr. Mori for his insights and suggestions on this project.

### References

- A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.
- H. Saad, A. P. Ismail, N. Othman, M. H. Jusoh, N. F. Naim, and N. A. Ahmad. Recognizing the ripeness of bananas using artificial neural network based on histogram approach. In *Signal and Image Processing Applications (ICSIPA), 2009 IEEE International Conference on*, pages 536–541. IEEE, 2009.



SIMON FRASER UNIVERSITY  
ENGAGING THE WORLD