

Kyle Dillard

SOHO Network Documentation

Brief Summary

Designed a Small Office/Home Office (SOHO) network using Cisco Packet Tracer. The network supports two segmented VLANS for users and printers, provides inter-VLAN routing, and basic security configurations. This project demonstrates foundational networking concepts such as IP addressing, VLANS, routing, and device configuration.

IP Addressing Table for End Devices

VLAN	Purpose	Subnet	Gateway
10	User PC	192.168.10.8/24	192.168.10.1
10	User PC	192.168.10.9/24	192.168.10.1
10	Printer	192.168.10.10/24	192.168.10.1
20	User PC	192.168.20.11/24	192.168.20.1
20	User PC	192.168.20.12/24	192.168.20.1
20	Printer	192.168.20.13/24	192.168.20.1

IP Addressing Table for Router Interfaces

<u>Router Interface</u>	<u>VLAN</u>	<u>IP Address</u>	<u>Subnet</u>
Fa0/0	10	192.168.10.1	255.255.255.0
Fa0/1	20	192.168.20.1	255.255.255.0

Device Configuration Summary

Router2

- Default gateways configured on ports Fa0/0 and Fa0/1
- Allows for inter-VLAN connection
- Console and VTY passwords configured

- Enable secret used for privileged access
- Unused switchports administratively shut down
- Banner MOTD configured

Switch0

- Facilitates communication for VLAN 10
- Access port assigned to port Fa0/24
- Console and VTY passwords configured
- Enable secret used for privileged access
- Unused switchports administratively shut down
- Banner MOTD configured

Switch1

- Facilitates communication for VLAN 20
- Access port assigned to port Fa0/24
- Console and VTY passwords configured
- Enable secret used for privileged access
- Unused switchports administratively shut down
- Banner MOTD configured

Troubleshooting & Lessons Learned

During testing, the two printers located on separate VLANS initially experienced connectivity issues when users from their opposite VLAN tried to access them. Connectivity tests such as ping failed, and print jobs could not be completed.

Upon investigation, it was determined that the printers were missing the correct default gateway configuration, which prevented inter-VLAN communication. The issue was resolved assigning the appropriate default gateway corresponding to each printer's VLAN interface on the router.

After applying the fix, connectivity was successfully restored. Ping tests to both printer IP addresses succeeded, and print jobs completed as expected. This issue

reinforced the importance of proper Layer 3 configuration for networked devices operating across VLANs.