

```

-- MySQL dump 10.13  Distrib 8.0.32, for Win64 (x86_64)
--
-- Host: localhost    Database: mydb
--
-- Server version 8.0.32

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!50503 SET NAMES utf8 */;
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
/*!40103 SET TIME_ZONE='+00:00' */;
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0 */;
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;

--
-- Table structure for table `age_groups`
--

DROP TABLE IF EXISTS `age_groups`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `age_groups` (
  `age_id` int NOT NULL AUTO_INCREMENT,
  `min_age` int NOT NULL,
  `max_age` int NOT NULL,
  `age_group_description` varchar(45) NOT NULL,
  PRIMARY KEY (`age_id`),
  UNIQUE KEY `age_id_UNIQUE` (`age_id`)
) ENGINE=InnoDB AUTO_INCREMENT=9 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `age_groups`
--

LOCK TABLES `age_groups` WRITE;
/*!40000 ALTER TABLE `age_groups` DISABLE KEYS */;
INSERT INTO `age_groups` VALUES (1,0,1,'Infant'),(2,2,3,'Toddler'),
(3,4,5,'Preschooler'),(4,6,12,'School Age'),(5,13,17,'Teen'),(6,18,25,'Young
Adult'),(7,26,59,'Adult'),(8,60,120,'Senior');
/*!40000 ALTER TABLE `age_groups` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Temporary view structure for view `april_suspects`
--

DROP TABLE IF EXISTS `april_suspects`;
/*!50001 DROP VIEW IF EXISTS `april_suspects`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `april_suspects` AS SELECT
  1 AS `Suspect Name`,
  1 AS `Suspect Age`,
  1 AS `Date of Incident`*/;
SET character_set_client = @saved_cs_client;

```

```

--
-- Table structure for table `article`
--

DROP TABLE IF EXISTS `article`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `article` (
  `article_id` int NOT NULL,
  `article_title` varchar(500) NOT NULL,
  `article_date` date NOT NULL,
  `article_publisher` varchar(45) NOT NULL,
  `incident_id` int NOT NULL,
  PRIMARY KEY (`article_id`),
  UNIQUE KEY `article_id_UNIQUE` (`article_id`),
  KEY `fk_article_incident1_idx` (`incident_id`),
  CONSTRAINT `fk_article_incident1` FOREIGN KEY (`incident_id`) REFERENCES
`incident` (`incident_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `article`
--

LOCK TABLES `article` WRITE;
/*!40000 ALTER TABLE `article` DISABLE KEYS */;
INSERT INTO `article` VALUES (1,'Two Men Get 3 Years in Prison for Beating Sikh in
Richmond Hate Crime','2017-05-19','KQED',1),(2,'Man Gets Nearly 22 Years in Prison
for Shooting Teen in Hate Crime','2017-09-20','NYTimes',2),(3,'Term in MS Gender
Identity Murder is US Hate Crime First','2017-05-17','The Crime Report',3),
(4,'Timeline: What We Know About The Freddie Gray Arrest','2017-05-01','NPR',4),
(5,'Veteran Subdued Gunman in Colorado Club Where 5 Were Killed','2017-11-29','The
New York Times',5),(6,'Suspect in deadly 2022 California church shooting indicted
on 98 federal counts, including hate-crime charges','2017-05-11','CNN',6),(7,'San
Diego man convicted on hate crime charges against disabled individual','2017-04-
12','Fox5',7),(8,'Mississippi man gets 49 years for anti-transgender hate crime
killing','2017-05-15','Savannah Morning News',8),(9,'Two charged in Baltimore
dating app robberies','2017-05-11','San Diego Gay & Lesbian News',9),(10,'Man Who
Disfigured Gay Couple With Boiling Water Received 40 Years in Prison','2017-05-
04','The Ring of Fire Network',10),(11,'Sen. Mike Enzi says a man wearing a tutu in
a bar \"kind of asks\" to be beat up','2017-04-25','Mic',11),(12,'Indiana police:
Muslim professor charged with fabricating anti-Islamic hate crimes, assault','2017-
04-23','TheBlaze.com',12),(13,'Maryland Teenagers Charged With Hate Crime For
Burning Trump Sign','2017-04-21','The Ring of Fire Network',13),(14,'Man Accused of
Fresno Shooting Rampage Describes the Violent Details','2017-04-
21','EBONY.com',14),(15,'NEW: Florida man attacks clerk, saying \"I don't like
Arabs\"','2017-04-20','Palm Beach Post',15);
/*!40000 ALTER TABLE `article` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `crime_classification`
--

DROP TABLE IF EXISTS `crime_classification`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;

```

```

CREATE TABLE `crime_classification` (
  `classification_id` int NOT NULL AUTO_INCREMENT,
  `crime_category` varchar(45) NOT NULL,
  PRIMARY KEY (`classification_id`),
  UNIQUE KEY `classification_id_UNIQUE` (`classification_id`),
  UNIQUE KEY `crime_category_UNIQUE` (`crime_category`)
) ENGINE=InnoDB AUTO_INCREMENT=12 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `crime_classification`
--

LOCK TABLES `crime_classification` WRITE;
/*!40000 ALTER TABLE `crime_classification` DISABLE KEYS */;
INSERT INTO `crime_classification` VALUES (7,'Anti-LGBTQ'),(6,'Anti-semantic'),
(1,'Assault'),(2,'Battery'),(5,'Gang-related'),(10,'Hate Speech'),(4,'Murder'),
(8,'Police Brutality'),(11,'Property Damage'),(9,'Racism'),(3,'Robbery');
/*!40000 ALTER TABLE `crime_classification` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Temporary view structure for view `crime_classification_analysis`
--

DROP TABLE IF EXISTS `crime_classification_analysis`;
/*!50001 DROP VIEW IF EXISTS `crime_classification_analysis`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `crime_classification_analysis` AS SELECT
  1 AS `crime_category`,
  1 AS `crime_count`*/;
SET character_set_client = @saved_cs_client;

--
-- Table structure for table `ethnicities`
--

DROP TABLE IF EXISTS `ethnicities`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `ethnicities` (
  `ethnic_id` int NOT NULL AUTO_INCREMENT,
  `ethnic_group` varchar(45) NOT NULL,
  PRIMARY KEY (`ethnic_id`),
  UNIQUE KEY `ethnic_id_UNIQUE` (`ethnic_id`),
  UNIQUE KEY `ethnic_group_UNIQUE` (`ethnic_group`)
) ENGINE=InnoDB AUTO_INCREMENT=13 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `ethnicities`
--

LOCK TABLES `ethnicities` WRITE;
/*!40000 ALTER TABLE `ethnicities` DISABLE KEYS */;
INSERT INTO `ethnicities` VALUES (1,'African American'),(2,'Asian'),(9,'British'),
(10,'French'),(3,'Hispanic or Latino'),(8,'Middle Eastern'),(7,'Mixed'),(4,'Native
American or Alaska Native'),(5,'Native Hawaiian or Other Pacific Islander'),

```

```

(11, 'Russian'), (12, 'Unknown'), (6, 'White');
/*!40000 ALTER TABLE `ethnicities` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `incident`
--

DROP TABLE IF EXISTS `incident`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `incident` (
  `incident_id` int NOT NULL AUTO_INCREMENT,
  `incident_city` varchar(45) NOT NULL,
  `incident_state` varchar(2) NOT NULL,
  `incident_date` date NOT NULL,
  PRIMARY KEY (`incident_id`),
  UNIQUE KEY `incident_id_UNIQUE` (`incident_id`)
) ENGINE=InnoDB AUTO_INCREMENT=16 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `incident`
--

LOCK TABLES `incident` WRITE;
/*!40000 ALTER TABLE `incident` DISABLE KEYS */;
INSERT INTO `incident` VALUES (1, 'San Francisco', 'CA', '2017-04-24'), (2, 'Kansas
City', 'MO', '2017-04-20'), (3, 'New York', 'NY', '2017-05-10'),
(4, 'Baltimore', 'MD', '2017-04-19'), (5, 'Colorado Springs', 'CO', '2017-11-26'),
(6, 'Laguna Woods', 'CA', '2017-05-10'), (7, 'San Diego', 'CA', '2017-03-21'),
(8, 'Savannah', 'GA', '2017-05-01'), (9, 'San Diego', 'CA', '2017-05-11'),
(10, 'Penascola', 'FL', '2017-04-20'), (11, 'New York', 'NY', '2017-04-20'), (12, 'New
York', 'NY', '2017-04-21'), (13, 'Pensacola', 'FL', '2017-04-17'), (14, 'New
York', 'NY', '2017-04-18'), (15, 'Palm Beach', 'FL', '2017-04-16');
/*!40000 ALTER TABLE `incident` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `incident_classification`
--

DROP TABLE IF EXISTS `incident_classification`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `incident_classification` (
  `incident_id` int NOT NULL,
  `classification_id` int NOT NULL,
  PRIMARY KEY (`incident_id`, `classification_id`),
  KEY `fk_incident_classification_crime_classification1_idx` (`classification_id`),
  CONSTRAINT `fk_incident_classification_crime_classification1` FOREIGN KEY
(`classification_id`) REFERENCES `crime_classification` (`classification_id`),
  CONSTRAINT `fk_incident_classification_incident1` FOREIGN KEY (`incident_id`)
REFERENCES `incident` (`incident_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `incident_classification`

```

```

--

LOCK TABLES `incident_classification` WRITE;
/*!40000 ALTER TABLE `incident_classification` DISABLE KEYS */;
INSERT INTO `incident_classification` VALUES (1,1),(2,1),(6,1),(7,1),(12,1),(15,1),
(1,2),(3,2),(7,2),(15,2),(9,3),(1,4),(4,4),(5,4),(6,4),(8,4),(10,4),(14,4),(8,5),
(1,6),(11,6),(12,6),(2,7),(5,7),(8,7),(10,7),(4,8),(6,9),(14,9),(11,10),(12,10),
(13,10),(13,11);
/*!40000 ALTER TABLE `incident_classification` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Temporary view structure for view `murder_victims_analysis`
--

DROP TABLE IF EXISTS `murder_victims_analysis`;
/*!50001 DROP VIEW IF EXISTS `murder_victims_analysis`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `murder_victims_analysis` AS SELECT
  1 AS `article_title`,
  1 AS `Number of Victims`,
  1 AS `Average Victims Age`*/;
SET character_set_client = @saved_cs_client;

--
-- Temporary view structure for view `pct_of_suspects_by_ethnicity`
--

DROP TABLE IF EXISTS `pct_of_suspects_by_ethnicity`;
/*!50001 DROP VIEW IF EXISTS `pct_of_suspects_by_ethnicity`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `pct_of_suspects_by_ethnicity` AS SELECT
  1 AS `ethnic_group`,
  1 AS `perpetrator_count`,
  1 AS `perpetrator_percentage`*/;
SET character_set_client = @saved_cs_client;

--
-- Table structure for table `population_groups`
--

DROP TABLE IF EXISTS `population_groups`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `population_groups` (
  `population_id` int NOT NULL AUTO_INCREMENT,
  `population_group` varchar(45) NOT NULL,
  PRIMARY KEY (`population_id`),
  UNIQUE KEY `population_id_UNIQUE` (`population_id`),
  UNIQUE KEY `population_group_UNIQUE` (`population_group`)
) ENGINE=InnoDB AUTO_INCREMENT=18 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `population_groups`
--

```

```

LOCK TABLES `population_groups` WRITE;
/*!40000 ALTER TABLE `population_groups` DISABLE KEYS */;
INSERT INTO `population_groups` VALUES (5,'Blacks'),(14,'Children'),(11,'Elderly
People'),(6,'Immigrants and Refugees'),(3,'Jewish'),(10,'LGBTQ+ Individuals'),
(9,'Men'),(12,'Muslims'),(15,'People of Color'),(1,'People with Disabilities'),
(7,'Police'),(16,'Political Group'),(4,'Religious Group'),(13,'Sikhs'),
(2,'Veterans'),(17,'Whites'),(8,'Women');
/*!40000 ALTER TABLE `population_groups` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `related_population`
--

DROP TABLE IF EXISTS `related_population`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `related_population` (
  `article_id` int NOT NULL,
  `population_id` int NOT NULL,
  PRIMARY KEY (`article_id`,`population_id`),
  KEY `fk_related_population_population_groups1_idx` (`population_id`),
  CONSTRAINT `fk_related_population_article1` FOREIGN KEY (`article_id`) REFERENCES
`article` (`article_id`),
  CONSTRAINT `fk_related_population_population_groups1` FOREIGN KEY
(`population_id`) REFERENCES `population_groups` (`population_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `related_population`
--

LOCK TABLES `related_population` WRITE;
/*!40000 ALTER TABLE `related_population` DISABLE KEYS */;
INSERT INTO `related_population` VALUES (7,1),(5,2),(11,3),(6,4),(15,4),(4,5),
(6,6),(4,7),(9,8),(1,9),(10,9),(2,10),(3,10),(5,10),(8,10),(9,10),(10,10),(6,11),
(12,12),(15,12),(1,13),(2,14),(11,14),(13,16),(14,17);
/*!40000 ALTER TABLE `related_population` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `suspect_list`
--

DROP TABLE IF EXISTS `suspect_list`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `suspect_list` (
  `suspect_id` int NOT NULL AUTO_INCREMENT,
  `suspect_fname` varchar(45) NOT NULL,
  `suspect_lname` varchar(45) NOT NULL,
  `suspect_age` int NOT NULL,
  `ethnic_id` int NOT NULL,
  `age_id` int NOT NULL,
  `article_id` int NOT NULL,
  PRIMARY KEY (`suspect_id`),
  UNIQUE KEY `suspect_id_UNIQUE` (`suspect_id`),
  KEY `fk_suspect_list_ethnicities1_idx` (`ethnic_id`),

```

```

    KEY `fk_suspect_list_age_groups1_idx` (`age_id`),
    KEY `fk_suspect_list_article1_idx` (`article_id`),
    CONSTRAINT `fk_suspect_list_age_groups1` FOREIGN KEY (`age_id`) REFERENCES
`suspect_list` (`age_id`),
    CONSTRAINT `fk_suspect_list_article1` FOREIGN KEY (`article_id`) REFERENCES
`suspect_list` (`article_id`),
    CONSTRAINT `fk_suspect_list_ethnicities1` FOREIGN KEY (`ethnic_id`) REFERENCES
`suspect_list` (`ethnic_id`)
) ENGINE=InnoDB AUTO_INCREMENT=21 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

```

```

--
-- Dumping data for table `suspect_list`
--

```

```

LOCK TABLES `suspect_list` WRITE;
/*!40000 ALTER TABLE `suspect_list` DISABLE KEYS */;
INSERT INTO `suspect_list` VALUES (1,'Colton','Leblanc',25,6,6,1),
(2,'Chase','Little',24,6,6,1),(3,'Malachi','Robinson',25,1,6,2),
(4,'Joshua','Vallum',49,4,7,3),(5,'Caesar','Gordon',45,1,7,4),
(6,'Brian','Rice',41,1,7,4),(7,'William','Porter',25,6,6,4),
(8,'Anderson','Aldrich',22,6,6,5),(9,'David','Chou',68,2,8,6),
(10,'William','Padilla',42,3,7,7),(11,'Joshua','Guilora',19,7,6,8),
(12,'Victor','Bauer',20,11,6,9),(13,'Jack','James',21,4,6,9),
(14,'Martin','Blackwell',38,12,7,10),(15,'Mike','Enzi',73,6,8,11),
(16,'Azhar','Hussain',56,8,7,12),(17,'Joy','Shuford',19,5,6,13),
(18,'D\'Asia','Perry',19,1,6,13),(19,'Kori','Muhammad',25,1,6,14),
(20,'Jeremiah','Hendrix',33,6,7,15);
/*!40000 ALTER TABLE `suspect_list` ENABLE KEYS */;
UNLOCK TABLES;

```

```

--
-- Table structure for table `victim_list`
--

```

```

DROP TABLE IF EXISTS `victim_list`;
/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `victim_list` (
  `victim_id` int NOT NULL AUTO_INCREMENT,
  `victim_fname` varchar(45) NOT NULL,
  `victim_lname` varchar(45) NOT NULL,
  `victim_age` int NOT NULL,
  `ethnic_id` int NOT NULL,
  `age_id` int NOT NULL,
  `article_id` int NOT NULL,
  PRIMARY KEY (`victim_id`),
  UNIQUE KEY `suspect_id_UNIQUE` (`victim_id`),
  KEY `fk_victim_list_ethnicities1_idx` (`ethnic_id`),
  KEY `fk_victim_list_age_groups1_idx` (`age_id`),
  KEY `fk_victim_list_article1_idx` (`article_id`),
  CONSTRAINT `fk_victim_list_age_groups1` FOREIGN KEY (`age_id`) REFERENCES
`suspect_list` (`age_id`),
  CONSTRAINT `fk_victim_list_article1` FOREIGN KEY (`article_id`) REFERENCES
`suspect_list` (`article_id`),
  CONSTRAINT `fk_victim_list_ethnicities1` FOREIGN KEY (`ethnic_id`) REFERENCES
`suspect_list` (`ethnic_id`)
) ENGINE=InnoDB AUTO_INCREMENT=18 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

```

```

--
-- Dumping data for table `victim_list`
--

LOCK TABLES `victim_list` WRITE;
/*!40000 ALTER TABLE `victim_list` DISABLE KEYS */;
INSERT INTO `victim_list` VALUES (1,'Maan','Khalsa',25,8,6,1),
(2,'M.','S.',16,12,5,2),(3,'Christopher','Jackson',18,3,6,3),
(4,'Freddie','Gray',25,1,6,4),(5,'Daniel','Atson',20,3,6,5),
(6,'Kelly','Loving',19,4,6,5),(7,'Ashley','Paugh',22,7,6,5),
(8,'Derrick','Pump',30,10,7,5),(9,'John','Cheng',52,2,7,6),
(10,'Anderson','Cooper',46,5,7,7),(11,'Mercedes','Williamson',17,11,5,8),
(12,'Keve','Paul',19,12,6,9),(13,'Pedro','Perez',22,3,6,10),
(14,'Luis','Lambert',20,10,6,10),(15,'Sydney','Robinson',30,6,7,13),
(16,'Carl','Williams',25,6,7,14),(17,'Emmanuel','Dixie',35,8,7,15);
/*!40000 ALTER TABLE `victim_list` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Temporary view structure for view `young_adult_suspects`
--

DROP TABLE IF EXISTS `young_adult_suspects`;
/*!50001 DROP VIEW IF EXISTS `young_adult_suspects`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `young_adult_suspects` AS SELECT
  1 AS `Article`,
  1 AS `Number of Young Adult Suspects`,
  1 AS `Total Suspect`*/;
SET character_set_client = @saved_cs_client;

--
-- Final view structure for view `april_suspects`
--

/*!50001 DROP VIEW IF EXISTS `april_suspects`*/;
/*!50001 SET @saved_cs_client      = @@character_set_client */;
/*!50001 SET @saved_cs_results    = @@character_set_results */;
/*!50001 SET @saved_col_connection = @@collation_connection */;
/*!50001 SET character_set_client  = utf8mb4 */;
/*!50001 SET character_set_results = utf8mb4 */;
/*!50001 SET collation_connection  = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `april_suspects` AS select concat(`suspect_list`.`suspect_fname`,`
`,`suspect_list`.`suspect_lname`) AS `Suspect Name`,`suspect_list`.`suspect_age` AS
`Suspect Age`,`incident`.`incident_date` AS `Date of Incident` from
((`suspect_list` join `article` on((`suspect_list`.`article_id` =
`article`.`article_id`))) join `incident` on((`article`.`incident_id` =
`incident`.`incident_id`))) where (`incident`.`incident_date` between '2017-04-01'
and '2017-04-30') order by `suspect_list`.`suspect_fname` */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results    = @saved_cs_results */;
/*!50001 SET collation_connection    = @saved_col_connection */;

--
-- Final view structure for view `crime_classification_analysis`

```



```

--

/*!50001 DROP VIEW IF EXISTS `crime_classification_analysis`*/;
/*!50001 SET @saved_cs_client          = @@character_set_client */;
/*!50001 SET @saved_cs_results        = @@character_set_results */;
/*!50001 SET @saved_col_connection    = @@collation_connection */;
/*!50001 SET character_set_client      = utf8mb4 */;
/*!50001 SET character_set_results     = utf8mb4 */;
/*!50001 SET collation_connection     = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `crime_classification_analysis` AS select
`crime_classification`.`crime_category` AS
`crime_category`,count(`incident_classification`.`incident_id`) AS `crime_count`
from (`crime_classification` join `incident_classification`
on((`crime_classification`.`classification_id` =
`incident_classification`.`classification_id`))) group by
`crime_classification`.`classification_id` order by `crime_count` desc */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;

--
-- Final view structure for view `murder_victims_analysis`
--

/*!50001 DROP VIEW IF EXISTS `murder_victims_analysis`*/;
/*!50001 SET @saved_cs_client          = @@character_set_client */;
/*!50001 SET @saved_cs_results        = @@character_set_results */;
/*!50001 SET @saved_col_connection    = @@collation_connection */;
/*!50001 SET character_set_client      = utf8mb4 */;
/*!50001 SET character_set_results     = utf8mb4 */;
/*!50001 SET collation_connection     = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `murder_victims_analysis` AS select `article`.`article_title` AS
`article_title`,count(`victim_list`.`victim_id`) AS `Number of
Victims`,round(avg(`victim_list`.`victim_age`),0) AS `Average Victims Age` from
(`article` join `victim_list` on((`article`.`article_id` =
`victim_list`.`article_id`))) where `article`.`incident_id` in (select
`incident`.`incident_id` from ((`incident` join `incident_classification`
on((`incident`.`incident_id` = `incident_classification`.`incident_id`))) join
`crime_classification` on((`incident_classification`.`classification_id` =
`crime_classification`.`classification_id`))) where
(`crime_classification`.`crime_category` = 'Murder')) group by
`article`.`article_id` order by round(avg(`victim_list`.`victim_age`),0) */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;

--
-- Final view structure for view `pct_of_suspects_by_ethnicity`
--

/*!50001 DROP VIEW IF EXISTS `pct_of_suspects_by_ethnicity`*/;
/*!50001 SET @saved_cs_client          = @@character_set_client */;
/*!50001 SET @saved_cs_results        = @@character_set_results */;
/*!50001 SET @saved_col_connection    = @@collation_connection */;
/*!50001 SET character_set_client      = utf8mb4 */;

```

```

/*!50001 SET character_set_results      = utf8mb4 */;
/*!50001 SET collation_connection      = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `pct_of_suspects_by_ethnicity` AS select `e`.`ethnic_group` AS
`ethnic_group`,count(`sl`.`suspect_id`) AS
`perpetrator_count`,round((((count(`sl`.`suspect_id`) * 1.0) / (select
count(`suspect_list`.`suspect_id`) from `suspect_list`))),2) AS
`perpetrator_percentage` from (`suspect_list` `sl` join `ethnicities` `e`
on((`sl`.`ethnic_id` = `e`.`ethnic_id`))) group by `e`.`ethnic_id` order by
`perpetrator_percentage` desc */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;

--
-- Final view structure for view `young_adult_suspects`
--

/*!50001 DROP VIEW IF EXISTS `young_adult_suspects`*/;
/*!50001 SET @saved_cs_client          = @@character_set_client */;
/*!50001 SET @saved_cs_results        = @@character_set_results */;
/*!50001 SET @saved_col_connection    = @@collation_connection */;
/*!50001 SET character_set_client      = utf8mb4 */;
/*!50001 SET character_set_results     = utf8mb4 */;
/*!50001 SET collation_connection     = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `young_adult_suspects` AS with `suspect_counts` as (select
`suspect_list`.`article_id` AS `article_id`,count(`suspect_list`.`suspect_id`) AS
`suspect_count` from `suspect_list` group by `suspect_list`.`article_id`) select
`a`.`article_title` AS `Article`,count(`sl`.`suspect_id`) AS `Number of Young Adult
Suspects`,`sc`.`suspect_count` AS `Total Suspect` from (((`article` `a` join
`suspect_list` `sl` on((`a`.`article_id` = `sl`.`article_id`))) join
`suspect_counts` `sc` on((`a`.`article_id` = `sc`.`article_id`))) join `age_groups`
`ag` on((`sl`.`age_id` = `ag`.`age_id`))) where (`ag`.`age_group_description` =
'Young Adult') group by `a`.`article_id` order by `sc`.`suspect_count` desc */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;
/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;
/*!40014 SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;
/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;

```

```
-- Dump completed on 2023-05-15 18:35:25
```