QuickPhone — Physical ERD (complete): 16 tables with all keys and attributes

One diagram for the whole data model. Each line is named both ways: top or left from the "one" side, bottom or right back from the "many" side. PK primary key · FK foreign key (→ table) · UK unique · CK checked value list · NN not null · derived = denormalized

store — D7 Staff & Stores

PK	**store_id**	INTEGER	NN
UK	store_name	VARCHAR(60)	NN
	address	VARCHAR(200)	NN
	phone	VARCHAR(20)	NN
	email_address	VARCHAR(120)	NN
	business_hours	VARCHAR(120)	NN

appointment — D2 Appointments

PK	**appointment_id**	INTEGER	NN
FK	customer_id	INTEGER	→ customer
FK	store_id	INTEGER	→ store
FK	technician_id	INTEGER	→ employee
	scheduled_at	TIMESTAMP	NN
CK	appt_status	VARCHAR(12)	NN

repair_job — D3 Repair Jobs

PK	**repair_job_id**	INTEGER	NN
UK	ticket_number	VARCHAR(12)	NN
FK	device_id	INTEGER	→ device
FK	store_id	INTEGER	→ store
FK,UK	appointment_id	INTEGER	→ appointment
FK	assigned_tech_id	INTEGER	→ employee
CK	status	VARCHAR(20)	derived · NN
	reported_issue	VARCHAR(500)	NN
	device_passcode	VARCHAR(255)	encrypted
	intake_condition	VARCHAR(500)	
	diagnosis_notes	VARCHAR(2000)	
	repair_notes	VARCHAR(2000)	
	check_in_at	TIMESTAMP	NN
	completed_at	TIMESTAMP	
	final_cost	DECIMAL(10,2)	
	email_sent_at	TIMESTAMP	
FK	email_sent_by_id	INTEGER	→ employee
CK	email_status	VARCHAR(10)	
	picked_up_at	TIMESTAMP	
	id_verified_flag	BOOLEAN	NN
	signature_file	VARCHAR(255)	

payment — D3 Repair Jobs

PK	**payment_id**	INTEGER	NN
FK	repair_job_id	INTEGER	→ repair_job
	amount	DECIMAL(10,2)	NN
CK	method	VARCHAR(12)	NN
CK	payment_status	VARCHAR(10)	NN
	paid_at	TIMESTAMP	NN

employee — D7 Staff & Stores

PK	**employee_id**	INTEGER	NN
FK	store_id	INTEGER	→ store
	first_name	VARCHAR(40)	NN
	last_name	VARCHAR(40)	NN
UK	email	VARCHAR(120)	NN
CK	role	VARCHAR(12)	NN
	password_hash	VARCHAR(255)	NN
	active_flag	BOOLEAN	NN

customer — D1 Customers & Devices

PK	**customer_id**	INTEGER	NN
	first_name	VARCHAR(40)	NN
	last_name	VARCHAR(40)	NN
IX	phone	VARCHAR(20)	NN
	email	VARCHAR(120)	
	created_at	TIMESTAMP	NN

job_part — D3 Repair Jobs

PK	**job_part_id**	INTEGER	NN
FK	repair_job_id	INTEGER	→ repair_job
FK	part_id	INTEGER	→ part
FK	purchase_order_id	INTEGER	→ purchase_order
	quantity	INTEGER	NN
CK	part_status	VARCHAR(8)	NN
	recorded_at	TIMESTAMP	NN

device — D1 Customers & Devices

PK	**device_id**	INTEGER	NN
FK	customer_id	INTEGER	→ customer
	device_type	VARCHAR(20)	
	brand	VARCHAR(40)	
	model	VARCHAR(60)	NN
IX	serial_or_imei	VARCHAR(40)	

job_status_history — D3 Repair Jobs

PK	**history_id**	BIGINT	NN
FK	repair_job_id	INTEGER	→ repair_job
CK	status	VARCHAR(20)	NN
FK	changed_by_id	INTEGER	→ employee
	changed_at	TIMESTAMP	NN
	note	VARCHAR(300)	

part — D4 Parts Inventory

PK	**part_id**	INTEGER	NN
FK	default_supplier_id	INTEGER	→ supplier
	part_name	VARCHAR(100)	NN
	device_model	VARCHAR(60)	
	grade	VARCHAR(20)	
	standard_cost	DECIMAL(10,2)	NN
	active_flag	BOOLEAN	NN

supplier — D6 Suppliers

PK	**supplier_id**	INTEGER	NN
UK	supplier_name	VARCHAR(100)	NN
	contact_name	VARCHAR(80)	
	phone	VARCHAR(20)	
	email	VARCHAR(120)	
	active_flag	BOOLEAN	NN

quote — D3 Repair Jobs

PK	**quote_id**	INTEGER	NN
FK	repair_job_id	INTEGER	→ repair_job
	labor_amount	DECIMAL(10,2)	NN
	parts_amount	DECIMAL(10,2)	NN
	total_amount	DECIMAL(10,2)	derived · NN
CK	decision	VARCHAR(10)	NN
	decision_at	TIMESTAMP	
FK	decision_by_id	INTEGER	→ employee

store_part_stock — D4 Parts Inventory

PK,FK	**store_id**	INTEGER	→ store
PK,FK	**part_id**	INTEGER	→ part
CK	quantity_on_hand	INTEGER	derived · NN
	reorder_point	INTEGER	NN

purchase_order — D5 Purchase Orders

PK	**purchase_order_id**	INTEGER	NN
FK	store_id	INTEGER	→ store
FK	supplier_id	INTEGER	→ supplier
FK	created_by_id	INTEGER	→ employee
FK	approved_by_id	INTEGER	→ employee
CK	po_status	VARCHAR(20)	NN
	created_at	TIMESTAMP	NN
	approved_at	TIMESTAMP	
	placed_at	TIMESTAMP	
	rejection_reason	VARCHAR(300)	

inventory_txn — D4 Parts Inventory

PK	**inventory_txn_id**	BIGINT	NN
FK	store_id	INTEGER	→ store_part_stock
FK	part_id	INTEGER	→ store_part_stock
FK	recorded_by_id	INTEGER	→ employee
CK	txn_type	VARCHAR(12)	NN
	quantity_change	INTEGER	NN
	reason	VARCHAR(200)	
	txn_at	TIMESTAMP	NN

po_line — D5 Purchase Orders

PK	**po_line_id**	INTEGER	NN
FK	purchase_order_id	INTEGER	→ purchase_order
FK	part_id	INTEGER	→ part
	quantity_ordered	INTEGER	NN
	quantity_received	INTEGER	NN
	unit_cost	DECIMAL(10,2)	NN

schedules / is scheduled at
books / is booked by
leads to / results from
receives / is received for
employs / is employed by
handles / is handled by
works on / is assigned to
sends notification for / has notification sent by
uses / is used on
owns / is owned by
undergoes / is performed on
tracks / belongs to
is included in / includes
creates / is created by
generates / is generated for
appears in / is stock of
changes / is made by
provides / is provided by
logs / is logged for
approves / is approved by
decides / is decided by
appears on / lists
records / is recorded by
contains / is contained in
fulfills / is fulfilled by
supplies / is supplied by

Every foreign key is drawn as a relationship line. EMPLOYEE plays several roles: the technician assigned to (or claiming) a job or appointment, the sender of the pickup notification, and the person who changes a status, decides a quote, records a stock change, or creates or approves (a Manager) a purchase order.