matrixdiagrams.sty

Kyle Monette (kylemonette.github.io)
Released under the LaTeX Project Public License (LPPL), version 1.3c

October 18, 2026 — Version 1.4

Overview

`matrixdiagrams` is a LaTeX package that draws schematic matrix diagrams in TikZ for the purposes of illustrating structure in matrices. All diagrams use `\matrixdiagram[scale][aspect]{content}`, where `content` is a sequence of small drawing commands (`\mdFill`, `\mdLabel`, `\mdDiagBand`, ...) working in a normalized coordinate system that automatically adapts to the diagram's scale and aspect ratio. This easily allows one to visualize structure in matrices such as bidiagonal, tridiagonal, upper triangular, and Hessenberg varieties. The sections below give a quick reference followed by every command with a runnable example.

Contents

1 Quick Reference **3**

2 Main command **3**
2.1 Scale (aspect = 1) . . . 4
2.2 Aspect ratio (scale = 3) . . . 4
2.3 Rounded corners . . . 5
2.4 Parentheses . . . 5

3 Diagonal commands **6**
3.1 `\mdDiag` — main diagonal . . . 6
3.2 `\mdDiagBand` — tridiagonal band . . . 6
3.3 `\mdDiagBandN{n}` — variable band width . . . 6

4 Bidiagonal commands **7**
4.1 `\mdBidiagUpper` — main + super-diagonal . . . 7
4.2 `\mdBidiagLower` — main + sub-diagonal . . . 7

5 Hessenberg commands **7**
5.1 `\mdHessenberg` — outline only (default) . . . 7
5.2 `\mdHessenberg[color]` — with fill . . . 8
5.3 `\mdHessenbergLower[color]` — lower Hessenberg . . . 8

6 Fill and line commands **8**
6.1 `\mdFill[color]{x0}{y0}{x1}{y1}` . . . 8
6.2 `\mdVLine{x}` and `\mdHLine{y}` . . . 9

7 Label commands **10**
7.1 \mdLabel{x}{y}{text} — math mode . . . 10
7.2 \mdLabelCenter{text} — always centered . . . 10
7.3 \mdLabelRaw{x}{y}{text} — raw text . . . 11
7.4 \mdDiagLabel{text} — on the diagonal . . . 11

8 Spike commands **12**
8.1 \mdSpike{x}{y}{dir} — L-shaped corners . . . 12
8.2 \mdBidiagSpike[pos]{dir} — bidiagonal spikes . . . 13
8.3 \mdHessenbergSpike[pos][col]{dir} — Hessenberg spikes . . . 14
8.4 \mdDiagBidiagSpike[pos]{dir} — diagonal + bidiagonal spikes . . . 15

9 Clipped diagonal commands **15**
9.1 \mdDiagFrom{x1}{y1}{x2}{y2} . . . 15
9.2 \mdDiagBandFrom{x1}{y1}{x2}{y2} . . . 16
9.3 \mdDiagBandNFrom{n}{x1}{y1}{x2}{y2} . . . 16

10 Realistic equations **16**
10.1 QR decomposition: $A = QR$ . . . 16
10.2 Bidiagonalization: $A = UBV^T$ . . . 17
10.3 Similarity: $Q^T T_m Q = \widetilde{T}_m$ . . . 17
10.4 Hessenberg reduction: $Q^T AQ = H$ . . . 17
10.5 Schur complement structure . . . 17

11 Implementation **17**

1 Quick Reference

`\matrixdiagram[s][a][r]{c}`	Main command. `s` = scale (default 1), `a` = aspect (default 1). `r` = corner radius for interior drawings (default: the `roundedcorners` package option, else `0pt`). Position args below are $x, y \in [0, 1]$, any aspect.
`\usepackage[parentheses]`	Parentheses instead of square brackets, for every diagram.
`\mdDiag`	Main diagonal
`\mdDiagBand`	Tridiagonal band.
`\mdDiagBandN{n}`	n-diagonal band (n odd).
`\mdBidiagUpper`	Main diagonal + super-diagonal.
`\mdBidiagLower`	Main diagonal + sub-diagonal.
`\mdHessenberg`	Upper-triangular outline + sub-diagonal.
`\mdHessenberg[color]`	Same with filled interior.
`\mdHessenbergUpper[color]`	Same as `\mdHessenberg`.
`\mdHessenbergLower[color]`	Lower-triangular outline + super-diagonal.
`\mdDiagFrom{x1}{y1}{x2}{y2}`	Main diagonal from (x_1, y_1) to (x_2, y_2)
`\mdDiagBandFrom{x1}{y1}{x2}{y2}`	Tridiagonal band, clipped.
`\mdDiagBandNFrom{n}{x1}{y1}{x2}{y2}`	n-diagonal band, clipped.
`\mdFill[col]{x0}{y0}{x1}{y1}`	Filled rectangle. Default color `gray!20`.
`\mdVLine{x}`	Vertical line, full height.
`\mdHLine{y}`	Horizontal line, full width, at fractional height y.
`\mdLabel{x}{y}{text}`	Math-mode label at (x, y).
`\mdLabel[color]{x}{y}{text}`	Same with filled node label
`\mdLabelRaw{x}{y}{text}`	Raw-text label at (x, y).
`\mdLabelCenter{text}`	Math label at center (any aspect).
`\mdDiagLabel[pos][angle][fill]{text}`	Math label on the main diagonal; `pos` $\in [0, 1]$ (default 0.5), default fill `white`.
`\mdSpike{x}{y}{dir}`	L-corner; `dir` $\in$ {`tl, tr, bl, br`}.
`\mdBidiagSpike[pos]{dir}`	Bidiagonal block to `pos` on the diagonal, plus a spike; `dir` $\in$ {`up, left`}.
`\mdBidiagSpike*[pos]{dir}`	Same, with the bidiagonal continued to the bottom-right.
`\mdHessenbergSpike[pos][col]{dir}`	Hessenberg outline plus a spike; `dir` $\in$ {`left` (upper), `up` (lower)}.
`\mdDiagBidiagSpike[pos]{dir}`	Diagonal block to `pos`, spike, then bidiagonal; `dir` $\in$ {`up, left`}.
`\mdBlank`	Empty content (brackets only).
`\mdH`	Expands to the aspect value, i.e. the top edge's y-coordinate.

2 Main command

`\matrixdiagram[scale][aspect]{content}`

Inside `content`, the raw TikZ canvas runs $x \in [0, 1]$ and $y \in [0, \text{aspect}]$: `aspect` is literally the

y-coordinate of the top edge, and `\mdH` expands to that value, so `(0,\mdH)–(1,\mdH)` is always the top edge, whatever the aspect. Every built-in positioning command (`\mdFill`, `\mdLabel`, `\mdLabelRaw`, `\mdHLine`, `\mdSpike`, and the `...From` diagonal variants) instead takes y as a plain fraction of the height, $y \in [0, 1]$, and multiplies by `\mdH` internally — so `y=0.5` always means mid-height, regardless of aspect. Raw `\draw` commands written directly inside `content` see the unscaled canvas, so they must reference `\mdH` themselves, e.g. `(1,\mdH)` for the top-right corner.

2.1 Scale (aspect = 1)

```
$\matrixdiagram[1]{\mdBlank}$
```

$\matrixdiagram[1]{\mdBlank}$

```
$\matrixdiagram[2]{\mdBlank}$
```

$\matrixdiagram[2]{\mdBlank}$

```
$\matrixdiagram[3]{\mdBlank}$
```

$\matrixdiagram[3]{\mdBlank}$

```
$\matrixdiagram[4]{\mdBlank}$
```

$\matrixdiagram[4]{\mdBlank}$

```
$\matrixdiagram[5]{\mdBlank}$
```

$\matrixdiagram[5]{\mdBlank}$

2.2 Aspect ratio (scale = 3)

```
$\matrixdiagram[3][0.5]{
  \mdBlank
}$
```

$\matrixdiagram[3][0.5]{ \mdBlank }$


```
$\matrixdiagram[3][1]{
  \mdBlank
}$
```

$\matrixdiagram[3][1]{ \mdBlank }$


```
$\matrixdiagram[3][1.5]{
  \mdBlank
}$
```

$\matrixdiagram[3][1.5]{ \mdBlank }$

```
$\matrixdiagram[3][2]{
  \mdBlank
}$
```



```
$\matrixdiagram[3][3]{
  \mdBlank
}$
```



2.3 Rounded corners

The corner radius used by every interior drawing (fills, outlines, spikes, ...) can be set two ways. Load the package with `roundedcorners=<dimen>` to round every diagram in the document:


```
\usepackage[roundedcorners=2pt]{matrixdiagrams}
```

or override it for one diagram with the third optional argument to `\matrixdiagram`:


```
\matrixdiagram[scale][aspect][radius]{content}
```

All three must be given positionally, so pass the aspect explicitly even to keep its default. The default, for both the package option and the per-diagram argument, is `0pt`.


```
$\matrixdiagram[3]{
  \mdHessenberg[gray!20]
}$
```



```
$\matrixdiagram[3][1][4pt]{
  \mdHessenberg[gray!20]
}$
```



```
$\matrixdiagram[3][1][4pt]{
  \mdFill[blue!10]{0}{0}{0.49}{1}
  \mdFill[red!10]{0.51}{0}{1}{1}
}$
```



2.4 Parentheses


Diagrams are drawn with square brackets by default. Load the package with the `parentheses` option to draw every diagram in the document with parentheses instead. These are the math font's own extensible parentheses (the same ones `pmatrix` uses), sized to span the full diagram:

```
\usepackage[parentheses]{matrixdiagrams}
```

This is a document-wide choice; there is no per-diagram override. It can be combined with the `roundedcorners` option:

```
\usepackage[parentheses,roundedcorners=2pt]{matrixdiagrams}
```


The same diagrams without and with the option:



3 Diagonal commands

3.1 \mdDiag — main diagonal


The single diagonal line from $(0, H)$ to $(1, 0)$.



```
$\matrixdiagram[3]{\mdDiag} \matrixdiagram[3][2]{\mdDiag}$
```

3.2 \mdDiagBand — tridiagonal band

Three parallel anti-diagonals with spacing $d = 0.1$.




```
$\matrixdiagram[3]{\mdDiagBand} \matrixdiagram[3][2]{\mdDiagBand}$
```

3.3 \mdDiagBandN{n} — variable band width

$n = 3, 5, 7, 9$ (spacing fixed at $d = 0.1$ per diagonal); `\mdDiagBandN{3}` is identical to `\mdDiagBand`:

```
$\matrixdiagram[3]{\mdDiagBandN{3}}$
```



```
$\matrixdiagram[3]{\mdDiagBandN{5}}$
```



```
$\matrixdiagram[3]{\mdDiagBandN{7}}$
```




```
$\matrixdiagram[3]{\mdDiagBandN{9}}$
```




With aspect = 2:

```
$\matrixdiagram[3][2]{\mdDiagBandN{3}}$
```




```
$\matrixdiagram[3][2]{\mdDiagBandN{5}}$
```



4 Bidiagonal commands

4.1 \mdBidiagUpper — main + super-diagonal


Main diagonal plus a single super-diagonal, offset $d = 0.1$ toward the top-right.



```
$\matrixdiagram[3]{\mdBidiagUpper} \matrixdiagram[3][2]{\mdBidiagUpper}$
```

4.2 \mdBidiagLower — main + sub-diagonal

Main diagonal plus a single sub-diagonal, offset $d = 0.1$ toward the bottom-left.




```
$\matrixdiagram[3]{\mdBidiagLower} \matrixdiagram[3][2]{\mdBidiagLower}$
```

5 Hessenberg commands

5.1 \mdHessenberg — outline only (default)


Upper-triangular outline $(0, H) \to (1, H) \to (1, 0)$ plus one sub-diagonal. `\mdHessenbergUpper` is an alias for `\mdHessenberg`, with the same optional fill color.




```
$\matrixdiagram[3]{\mdHessenberg} \matrixdiagram[3][2]{\mdHessenberg}$
```

5.2 \mdHessenberg[color] — with fill


```
$\matrixdiagram[3]{\mdHessenberg[gray!15]}$
```




```
$\matrixdiagram[3]{\mdHessenberg[blue!15]}$
```



```
$\matrixdiagram[3]{\mdHessenberg[green!20]}$
```




```
$\matrixdiagram[3]{\mdHessenberg[orange!20]}$
```




5.3 \mdHessenbergLower[color] — lower Hessenberg

The transpose of **\mdHessenberg**: lower-triangular outline $(0, H) \to (0, 0) \to (1, 0)$ plus one super-diagonal, with the same optional fill color.

```
$\matrixdiagram[3]{\mdHessenbergLower}$
```



```
$\matrixdiagram[3]{\mdHessenbergLower[blue!15]}
    $
```




6 Fill and line commands


6.1 \mdFill[color]{x0}{y0}{x1}{y1}

The default color is `gray!20`:


```
$\matrixdiagram[3]{
  \mdFill[green!30]{0}{0.5}{0.5}{1}
}$
```




```
$\matrixdiagram[3]{
  \mdFill[blue!20]{0.5}{0.5}{1}{1}
}$
```




```
$\matrixdiagram[3]{
  \mdFill[red!20]{0}{0}{0.5}{0.5}
}$
```




```
$\matrixdiagram[3]{
  \mdFill{0}{0}{1}{1}
}$
```



With aspect = 2 (y is still a fraction of the height, in $[0,1]$):



```
$\matrixdiagram[3][2]{\mdFill[green!25]{0}{0.5}{0.5}{1}}$
```




```
$\matrixdiagram[3][2]{\mdFill[blue!15]{0}{0}{1}{0.5}}$
```


6.2 `\mdVLine{x}` and `\mdHLine{y}`

`\mdVLine{x}` runs the full height at $x \in [0,1]$; `\mdHLine{y}` runs the full width at height $y \in [0,1]$.


```
$\matrixdiagram[3]{
  \mdVLine{0.5}
}$
```




```
$\matrixdiagram[3]{
  \mdHLine{0.5}
}$
```




```
$\matrixdiagram[3]{
  \mdVLine{0.5}
  \mdHLine{0.5}
}$
```




```
$\matrixdiagram[3]{
  \mdVLine{0.33}
  \mdVLine{0.67}
}$
```




```
$\matrixdiagram[3]{
  \mdHLine{0.33}
  \mdHLine{0.67}
}$
```




```
$\matrixdiagram[3][2]{
  \mdVLine{0.5}
}$
```




```
$\matrixdiagram[3][2]{
  \mdHLine{0.5}
}$
```




```
$\matrixdiagram[3][2]{
  \mdVLine{0.5}
  \mdHLine{0.5}
}$
```



Combined with fills (block partitioning):




```
$\matrixdiagram[3]{
  \mdFill[blue!15]{0}{0.5}{0.5}{1}
  \mdFill[green!15]{0.5}{0}{1}{0.5}
  \mdVLine{0.5}
  \mdHLine{0.5}
  \mdLabel{0.25}{0.75}{A}
  \mdLabel{0.75}{0.25}{D}
}$
```





```
$\matrixdiagram[3][2]{
  \mdFill[gray!15]{0}{0}{0.75}{1}
  \mdVLine{0.75}
  \mdLabel{0.375}{0.5}{A}
  \mdLabel{0.875}{0.5}{b}
}$
```

7 Label commands


7.1 \mdLabel{x}{y}{text} — math mode

Places `text` in math mode at (x, y); the optional first argument fills the label's background node with that color.


```
$\matrixdiagram[3]{
  \mdLabel{0.2}{0.5}{A}
}$
```





```
$\matrixdiagram[3]{
  \mdLabel[red!20]{0.5}{0.5}{Q^T}
}$
```




```
$\matrixdiagram[3]{
  \mdLabel{0.5}{0.5}{\Sigma}
}$
```




```
$\matrixdiagram[3]{
  \mdDiagBand
  \mdLabel{0.25}{0.2}{T}
}$
```



7.2 \mdLabelCenter{text} — always centered

Automatically placed at $(0.5, H/2)$ regardless of aspect ratio:

```
$\matrixdiagram[3][1]{
  \mdLabelCenter{Q}
}$
```

$$\matrixdiagram[3][1]{\mdLabelCenter{Q}}$$

```
$\matrixdiagram[3][2]{
  \mdLabelCenter{Q}
}$
```

$$\matrixdiagram[3][2]{\mdLabelCenter{Q}}$$

```
$\matrixdiagram[3][3]{
  \mdLabelCenter{Q}
}$
```

$$\matrixdiagram[3][3]{\mdLabelCenter{Q}}$$

```
$\matrixdiagram[3][0.5]{
  \mdLabelCenter{Q}
}$
```

$$\matrixdiagram[3][0.5]{\mdLabelCenter{Q}}$$

7.3 \mdLabelRaw{x}{y}{text} — raw text

Same placement as \mdLabel, but `text` is typeset as-is instead of in math mode — useful for plain words like "dense" or for text that already contains its own `$...$`.


$$\matrixdiagram[3]{\mdLabelRaw{0.5}{0.5}{dense}}\matrixdiagram[3]{\mdLabelRaw{0.5}{0.5}{≈ 0}}$$

```
$\matrixdiagram[3]{
  \mdLabelRaw{0.5}{0.5}{dense}
}
\matrixdiagram[3]{
  \mdLabelRaw{0.5}{0.5}{$\approx 0$}
}$
```


7.4 \mdDiagLabel{text} — on the diagonal

Places `text` in math mode on the main diagonal, at fractional position `pos` $\in [0, 1]$ measured from the top-left corner toward the bottom-right (default 0.5, the midpoint). The optional second argument is a rotation angle in degrees (default 0); the optional third argument fills the label's background node (default `white`), as with \mdLabel. Setting the color to `none` removes all fill, but will have the (likely undesired!) effect of putting the text behind any diagonal lines or content, which does not look good.


```
$\matrixdiagram[3]{
  \mdDiagBand
  \mdDiagLabel{T_m}
}$
```





```
$\matrixdiagram[3]{
  \mdDiagBand
  \mdDiagLabel[0.25]{T_m}
}$
```




```
$\matrixdiagram[3]{
  \mdDiag
  \mdDiagLabel[0.5][-45]{T_m}
}$
```




```
$\matrixdiagram[3]{
  \mdHessenberg
  \mdDiagLabel[0.5][0][red!20]{T_m}
}$
```




8 Spike commands


8.1 \mdSpike{x}{y}{dir} — L-shaped corners

`\mdSpike{x}{y}{dir}` draws an L-shaped corner at (x, y). `tl` (top+left), `tr` (top+right), `bl` (bottom+left), `br` (bottom+right). To shade the block, pair it with `\mdFill` (see below).


```
$\matrixdiagram[3]{
  \mdSpike{0.5}{0.5}{tl}
}$
```




```
$\matrixdiagram[3]{
  \mdSpike{0.5}{0.5}{tr}
}$
```




```
$\matrixdiagram[3]{
  \mdSpike{0.5}{0.5}{bl}
}$
```




```
$\matrixdiagram[3]{
  \mdSpike{0.5}{0.5}{br}
}$
```



```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
}$
```




```
$\matrixdiagram[3]{
  \mdFill[blue!15]{0.5}{0.5}{1}{1}
  \mdSpike{0.5}{0.5}{tr}
}$
```




With aspect = 2, corner at mid-height $(0.5, 0.5)$:


```
$\matrixdiagram[3][2]{
  \mdFill[green
      !20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
}$
```



```
$\matrixdiagram[3][2]{
  \mdFill[blue
      !15]{0.5}{0.5}{1}{1}
  \mdSpike{0.5}{0.5}{tr}
}$
```



```
$\matrixdiagram[3][2]{
  \mdFill[red
      !15]{0}{0}{0.5}{0.5}
  \mdSpike{0.5}{0.5}{bl}
}$
```




8.2 `\mdBidiagSpike[pos]{dir}` — bidiagonal spikes

`\mdBidiagSpike[pos]{dir}` draws a bidiagonal block from the top-left corner to the point at `pos` on the main diagonal (`pos` $\in [0, 1]$, default 0.5, measured as in `\mdDiagLabel`), plus a spike coming off the off-diagonal line. `up` gives an upper bidiagonal block with a column spike at $x =$ `pos`, from the super-diagonal up to the top edge; `left` gives a lower bidiagonal block with a row spike at $y = 1 -$ `pos`, from the sub-diagonal across to the left edge. The starred form `\mdBidiagSpike*` continues the bidiagonal past the spike to the bottom-right corner.


```
$\matrixdiagram[3]{
  \mdBidiagSpike[0.5]{up}
}$
```




```
$\matrixdiagram[3]{
  \mdBidiagSpike[0.5]{left}
}$
```




```
$\matrixdiagram[3]{
  \mdBidiagSpike*[0.5]{up}
}$
```




```
$\matrixdiagram[3]{
  \mdBidiagSpike*[0.4]{left}
}$
```



```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdBidiagSpike*[0.5]{up}
}$
```




```
$\matrixdiagram[3][2]{
  \mdBidiagSpike*[0.5]{up}
}$
```




8.3 \mdHessenbergSpike[pos][col]{dir} — Hessenberg spikes

`\mdHessenbergSpike[pos][col]{dir}` draws a Hessenberg outline, filled with `col` if given (as in `\mdHessenberg[color]`), plus a spike coming off the off-diagonal line at `pos` on the main diagonal (default 0.5). `left` gives an upper Hessenberg matrix with a row spike at $y = 1 - \texttt{pos}$, from the sub-diagonal across to the left edge; `up` gives a lower Hessenberg matrix with a column spike at $x = \texttt{pos}$, from the super-diagonal up to the top edge.


```
$\matrixdiagram[3]{
  \mdHessenbergSpike[0.5]{left}
}$
```




```
$\matrixdiagram[3]{
  \mdHessenbergSpike[0.5]{up}
}$
```



```
$\matrixdiagram[3]{
  \mdHessenbergSpike[0.6][blue!15]{left}
}$
```



```
$\matrixdiagram[3][2]{
  \mdHessenbergSpike[0.4][green!20]{up}
}$
```




8.4 \mdDiagBidiagSpike[pos]{dir} — diagonal + bidiagonal spikes

`\mdDiagBidiagSpike[pos]{dir}` draws a diagonal block from the top-left corner to the point at `pos` on the main diagonal (default 0.5), then a spike, then a bidiagonal from the spike to the bottom-right corner. `up` gives a column spike at $x = \texttt{pos}$, from the top edge down to the super-diagonal of a trailing upper bidiagonal; `left` gives a row spike at $y = 1 - \texttt{pos}$, from the left edge across to the sub-diagonal of a trailing lower bidiagonal.


```
$\matrixdiagram[3]{
  \mdDiagBidiagSpike[0.5]{up}
}$
```




```
$\matrixdiagram[3]{
  \mdDiagBidiagSpike[0.5]{left}
}$
```



```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdDiagBidiagSpike[0.5]{up}
}$
```



```
$\matrixdiagram[3][2]{
  \mdDiagBidiagSpike[0.4]{up}
}$
```




9 Clipped diagonal commands


The `...From` variants force the diagonal band from $[x_1, y_1]$ to $[x_2, y_2]$. Always pair with `\mdSpike` at the same corner.

9.1 \mdDiagFrom{x1}{y1}{x2}{y2}

```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagFrom{0.5}{0.5}{1}{0}
}$
```




```
$\matrixdiagram[3][2]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagFrom{0.5}{0.5}{1}{0}
}$
```




9.2 \mdDiagBandFrom{x1}{y1}{x2}{y2}

```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagBandFrom{0.5}{0.5}{1}{0}
}$
```




```
$\matrixdiagram[3][2]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagBandFrom{0.5}{0.5}{1}{0}
}$
```




9.3 \mdDiagBandNFrom{n}{x1}{y1}{x2}{y2}

$n = 3, 5, 7$:


```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagBandNFrom{3}{0.5}{0.5}{1}{0}
}$
```



```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagBandNFrom{5}{0.5}{0.5}{1}{0}
}$
```



```
$\matrixdiagram[3]{
  \mdFill[green!20]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagBandNFrom{7}{0.5}{0.5}{1}{0}
}$
```




10 Realistic equations

10.1 QR decomposition: $A = QR$

$$\begin{bmatrix} \\ A \\ \\ \end{bmatrix} = \begin{bmatrix} \\ Q \\ \\ \end{bmatrix} \begin{bmatrix} \\ R \\ \\ \end{bmatrix}$$


```
$\matrixdiagram[3][2]{\mdLabelCenter{A}}
=
\matrixdiagram[3][2]{\mdLabelCenter{Q}}
\matrixdiagram[3]{\mdLabelCenter{R}}$
```

10.2 Bidiagonalization: $A = UBV^T$





```
$\matrixdiagram[3]{\mdLabelCenter{A}}
=
\matrixdiagram[3]{\mdLabelCenter{U}}
\matrixdiagram[3]{\mdBidiagUpper}
\matrixdiagram[3]{\mdLabelCenter{V^T}}$
```

10.3 Similarity: $Q^T T_m Q = \widetilde{T}_m$





```
$\matrixdiagram[3]{\mdLabelCenter{Q^T}}
\matrixdiagram[3]{
  \mdDiagBand
  \mdLabel{0.25}{0.15}{T_m}
}
\matrixdiagram[3]{\mdLabelCenter{Q}}
=
\matrixdiagram[3]{
  \mdFill[green!25]{0}{0.5}{0.5}{1}
  \mdSpike{0.5}{0.5}{tl}
  \mdDiagBandFrom{0.5}{0.5}{1}{0}
  \mdLabel{0.3}{0.12}{\widetilde{T}_m}
}$
```

10.4 Hessenberg reduction: $Q^T A Q = H$




```
$\matrixdiagram[3]{\mdLabelCenter{Q^T}}
\matrixdiagram[3]{\mdLabelCenter{A}}
\matrixdiagram[3]{\mdLabelCenter{Q}}
=
\matrixdiagram[3]{
  \mdHessenberg
  \mdLabel{0.7}{0.55}{H}
}$
```

10.5 Schur complement structure




```
$\matrixdiagram[4]{
  \mdFill[blue!10]{0}{0.5}{0.5}{1}
  \mdFill[green!10]{0.5}{0}{1}{0.5}
  \mdFill[gray!10]{0.5}{0.5}{1}{1}
  \mdVLine{0.5}
  \mdHLine{0.5}
  \mdLabel{0.25}{0.75}{A}
  \mdLabel{0.75}{0.75}{B}
  \mdLabel{0.25}{0.25}{C}
  \mdLabel{0.75}{0.25}{S}
}$
```

11 Implementation

⟨∗package⟩
```
\RequirePackage{tikz}
\RequirePackage{xparse}
\RequirePackage{calc}
```

```
\RequirePackage{kvoptions}

%% ---------------------------------------------------------------------
%% Package options
%% roundedcorners=<dimen> sets the default corner radius used by every
%% interior drawing (fills, outlines, spikes, etc.); individual diagrams
%% can override it via \matrixdiagram's third optional argument. Default
%% 0pt (sharp). Defines \md@roundedcorners.
%% parentheses draws every diagram's border with the math font's
%% parentheses instead of square brackets. Document-wide only; no per-diagram override.
%% Defines \ifmd@parentheses.
%% ---------------------------------------------------------------------
\SetupKeyvalOptions{family=matrixdiagrams, prefix=md@}
\DeclareStringOption[0pt]{roundedcorners}
\DeclareBoolOption[false]{parentheses}
\ProcessKeyvalOptions*

\usetikzlibrary{arrows.meta, bending, matrix, positioning, calc, arrows}

%% ---------------------------------------------------------------------
%% Internal dimensions
%% ---------------------------------------------------------------------
\newdimen\md@bracewidth   % length of the horizontal tick at each bracket corner
\newdimen\md@innersep     % gap between the content and the brackets
\newdimen\md@baseunit     % size of one coordinate unit at scale=1
\newdimen\md@hsep         % margin added left and right of every \matrixdiagram
\md@bracewidth=3pt
\md@innersep=2pt
\md@baseunit=0.5cm
\md@hsep=3pt

%% \md@H: current aspect ratio = y-coordinate of top edge. Default 1.
\def\md@H{1}
%% \mdH: user-facing alias usable inside content arguments
\def\mdH{\md@H}

%% \md@bandstep: spacing between adjacent diagonals in a band, in x-units.
\def\md@bandstep{0.1}

%% ---------------------------------------------------------------------
%% \md@draw@brackets | draws square brackets around node MDNODO
%% ---------------------------------------------------------------------
\newcommand{\md@draw@brackets}{%
  \draw[thick]
    (MDNODO.north west)+(\md@bracewidth,0)
    -- (MDNODO.north west)
    -- (MDNODO.south west)
    -- ($(MDNODO.south west)+(\md@bracewidth,0)$);
  \draw[thick]
    (MDNODO.north east)+(-\md@bracewidth,0)
    -- (MDNODO.north east)
    -- (MDNODO.south east)
    -- ($(MDNODO.south east)+(-\md@bracewidth,0)$);
}

%% ---------------------------------------------------------------------
```

```
%% \md@draw@picture{scale}{aspect}{radius}{content} | the diagram itself:
%% node MDNODO holding the content canvas, plus square brackets unless the
%% parentheses package option is set
%% ------------------------------------------------------------------------
\newcommand{\md@draw@picture}[4]{%
  \tikz[baseline={(MDNODO.base)}]{%
    \node[inner sep=\md@innersep](MDNODO){%
      \tikz[baseline={($(MDcenter)-(0.25em,0.25em)$)},
            x={#1*\md@baseunit}, y={#1*\md@baseunit},
            rounded corners=#3]{%
        \coordinate (MDcenter) at (0.5,{#2*0.5});
        \draw[draw=none] (0,0) rectangle (1,#2);
        #4
      }%
    };
    \ifmd@parentheses\else\md@draw@brackets\fi
  }%
}

%% ------------------------------------------------------------------------
%% Core drawing macro: \md@draw@box{scale}{aspect}{radius}{content}
%% With the parentheses option, the picture is wrapped in the math font's
%% extensible \left( ... \right), as in pmatrix; \delimiterfactor and
%% \delimitershortfall are set so the parentheses span the full picture.
%% ------------------------------------------------------------------------
\newcommand{\md@draw@box}[4]{%
  \def\md@H{#2}%
  \vcenter{\hbox{%
    \kern\md@hsep
    \ifmd@parentheses
      $\delimiterfactor=1000 \delimitershortfall=0pt
       \left(\vcenter{\hbox{\md@draw@picture{#1}{#2}{#3}{#4}}}\right)$%
    \else
      \md@draw@picture{#1}{#2}{#3}{#4}%
    \fi
    \kern\md@hsep
  }}%
}

%% ------------------------------------------------------------------------
%% \matrixdiagram[scale][aspect][radius]{content} | radius, if omitted,
%% falls back to \md@roundedcorners (set by the roundedcorners package option)
%% ------------------------------------------------------------------------
\NewDocumentCommand{\matrixdiagram}{O{1} O{1} o m}{%
  \IfNoValueTF{#3}
    {\md@draw@box{#1}{#2}{\md@roundedcorners}{#4}}
    {\md@draw@box{#1}{#2}{#3}{#4}}%
}

%% ------------------------------------------------------------------------
%% Content commands | all use \md@H for the top edge
%% ------------------------------------------------------------------------

%% \md@superdiag{k} | super-diagonal offset by k*\md@bandstep
\newcommand{\md@superdiag}[1]{%
  \draw[thick] ({#1*\md@bandstep},\md@H) -- (1,{#1*\md@bandstep*\md@H});%
```

```
}
%% \md@subdiag{k} | sub-diagonal offset by k*\md@bandstep
\newcommand{\md@subdiag}[1]{%
  \draw[thick] (0,{\md@H-#1*\md@bandstep*\md@H}) -- ({1-#1*\md@bandstep},0);%
}

%% \mdDiagBandN{n} | n-diagonal band (n odd), spacing \md@bandstep between diagonals.
%% n=1 draws only the main diagonal. Max useful n is 9.
\newcommand{\mdDiagBandN}[1]{%
  \draw[thick] (0,\md@H) -- (1,0);%
  \pgfmathtruncatemacro{\md@half}{int((#1-1)/2)}%
  \ifnum\md@half>0
    \foreach \md@k in {1,...,\md@half}{%
      \md@subdiag{\md@k}%
      \md@superdiag{\md@k}%
    }%
  \fi
}

%% \mdDiag | main anti-diagonal (top-left to bottom-right)
\newcommand{\mdDiag}{\mdDiagBandN{1}}
\let\mdIdentity\mdDiag

%% \mdDiagBand | tridiagonal band
\newcommand{\mdDiagBand}{\mdDiagBandN{3}}

%% \mdFill[color]{x0}{y0}{x1}{y1} | y0,y1 are fractions of the height, in [0,1]
\newcommand{\mdFill}[5][gray!20]{%
  \fill[#1] (#2,{#3*\md@H}) rectangle (#4,{#5*\md@H});%
}

%% \mdLabel[fill]{x}{y}{text} | math-mode label, optional node fill color; y in [0,1]
\newcommand{\mdLabel}[4][none]{%
  \node[fill=#1] at (#2,{#3*\md@H}) {$#4$};%
}

%% \mdLabelRaw[fill]{x}{y}{text} | raw text label, optional node fill color; y in [0,1]
\newcommand{\mdLabelRaw}[4][none]{%
  \node[fill=#1] at (#2,{#3*\md@H}) {#4};%
}

%% \mdLabelCenter{text} | math label at the center (x=0.5, y=H/2)
\newcommand{\mdLabelCenter}[1]{%
  \node at (0.5,{0.5*\md@H}) {$#1$};%
}

%% \mdDiagLabel[pos][angle][fill]{text} | math-mode label on the main
%% diagonal; pos in [0,1] (default 0.5), measured from the top-left corner
%% toward the bottom-right; angle in degrees (default 0); fill is an
%% optional background color (default white)
\NewDocumentCommand{\mdDiagLabel}{O{0.5} O{0} O{white} m}{%
  \node[fill=#3, rotate=#2] at ({#1},{(1-#1)*\md@H}) {$#4$};%
}

%% \mdVLine{x} | full-height vertical line (0 to H)
\newcommand{\mdVLine}[1]{%
```

```
  \draw[thick] (#1,0) -- (#1,\md@H);%
}

%% \mdHLine{y} | full-width horizontal line; y is a fraction of the height, in [0,1]
\newcommand{\mdHLine}[1]{%
  \draw[thick] (0,{#1*\md@H}) -- (1,{#1*\md@H});%
}

%% ---------------------------------------------------------------------
%% Clipped diagonal commands
%% Draw diagonal bands clipped to the rectangle (x1,y1)--(x2,y2),
%% where (x1,y1) is the bottom-left corner and (x2,y2) is the top-right.
%%
%% \mdDiagFrom{x1}{y1}{x2}{y2}
%% \mdDiagBandFrom{x1}{y1}{x2}{y2}
%% \mdDiagBandNFrom{n}{x1}{y1}{x2}{y2}
%%   n=1 draws only the main diagonal (no off-diagonals).
%%
%% Typical spike usage | clip to the region outside the block:
%%   \mdSpike{0.5}{0.5}{tl}
%%   \mdDiagBandFrom{0.5}{0}{1}{0.5}    % bottom-left=(0.5,0), top-right=(1,0.5)
%% ---------------------------------------------------------------------

%% \mdDiagBandNFrom{n}{x1}{y1}{x2}{y2} | y1,y2 are fractions of the height, in [0,1]
\newcommand{\mdDiagBandNFrom}[5]{%
  \begin{scope}%
    \clip (#2,{#3*\md@H}) rectangle (#4,{#5*\md@H});%
    \mdDiagBandN{#1}%
  \end{scope}%
}

%% \mdDiagFrom{x1}{y1}{x2}{y2}
\newcommand{\mdDiagFrom}[4]{\mdDiagBandNFrom{1}{#1}{#2}{#3}{#4}}

%% \mdDiagBandFrom{x1}{y1}{x2}{y2}
\newcommand{\mdDiagBandFrom}[4]{\mdDiagBandNFrom{3}{#1}{#2}{#3}{#4}}

%% ---------------------------------------------------------------------
%% Spike commands | L-shaped block boundary corners
%%   tl: corner at (x,y), arms to top (y=H) and left (x=0)
%%   tr: corner at (x,y), arms to top (y=H) and right (x=1)
%%   bl: corner at (x,y), arms to bottom (y=0) and left (x=0)
%%   br: corner at (x,y), arms to bottom (y=0) and right (x=1)
%% ---------------------------------------------------------------------
\def\md@tl{tl}\def\md@tr{tr}\def\md@bl{bl}\def\md@br{br}

%% \mdSpike{x}{y}{dir} | y is a fraction of the height, in [0,1]
\newcommand{\mdSpike}[3]{%
  \def\md@spikedir{#3}%
  \ifx\md@spikedir\md@tl \draw[thick] (#1,\md@H) -- (#1,{#2*\md@H}) -- (0,{#2*\md@H});%
  \else\ifx\md@spikedir\md@tr \draw[thick] (#1,\md@H) -- (#1,{#2*\md@H}) -- (1,{#2*\md@H});%
  \else\ifx\md@spikedir\md@bl \draw[thick] (#1,0) -- (#1,{#2*\md@H}) -- (0,{#2*\md@H});%
  \else\ifx\md@spikedir\md@br \draw[thick] (#1,0) -- (#1,{#2*\md@H}) -- (1,{#2*\md@H});%
  \fi\fi\fi\fi
}
```

```
%% ---------------------------------------------------------------------
%% Bidiagonal spike command
%% \mdBidiagSpike[pos]{dir} | bidiagonal block from the top-left corner to
%% the point at pos on the main diagonal (pos in [0,1], default 0.5,
%% measured as in \mdDiagLabel), plus a spike off the off-diagonal line:
%%   up:   upper bidiagonal; vertical spike at x=pos from the
%%         super-diagonal up to the top edge
%%   left: lower bidiagonal; horizontal spike at y=1-pos from the
%%         sub-diagonal across to the left edge
%% \mdBidiagSpike*[pos]{dir} | same, but the bidiagonal continues past the
%% spike to the bottom-right corner.
%% ---------------------------------------------------------------------
\def\md@up{up}\def\md@left{left}

%% \md@spike@up{pos} | column spike at x=pos, from the super-diagonal up to
%% the top edge
\newcommand{\md@spike@up}[1]{%
  \draw[thick] ({#1},{(1-#1+\md@bandstep)*\md@H}) -- ({#1},\md@H);%
}
%% \md@spike@left{pos} | row spike at y=1-pos, from the sub-diagonal across
%% to the left edge
\newcommand{\md@spike@left}[1]{%
  \draw[thick] ({#1-\md@bandstep},{(1-#1)*\md@H}) -- (0,{(1-#1)*\md@H});%
}

\NewDocumentCommand{\mdBidiagSpike}{s O{0.5} m}{%
  \def\md@spikedir{#3}%
  \ifx\md@spikedir\md@up
    \IfBooleanTF{#1}
      {\mdBidiagUpper\md@spike@up{#2}}
      {\draw[thick] (0,\md@H) -- ({#2},{(1-#2)*\md@H});%
       \draw[thick] (\md@bandstep,\md@H)
         -- ({#2},{(1-#2+\md@bandstep)*\md@H}) -- ({#2},\md@H);}%
  \else\ifx\md@spikedir\md@left
    \IfBooleanTF{#1}
      {\mdBidiagLower\md@spike@left{#2}}
      {\draw[thick] (0,\md@H) -- ({#2},{(1-#2)*\md@H});%
       \draw[thick] (0,{(1-\md@bandstep)*\md@H})
         -- ({#2-\md@bandstep},{(1-#2)*\md@H}) -- (0,{(1-#2)*\md@H});}%
  \else
    \PackageError{matrixdiagrams}{Unknown \string\mdBidiagSpike\space
      direction '#3'}{Use 'up' or 'left'.}%
  \fi\fi
}

%% ---------------------------------------------------------------------
%% Hessenberg spike command
%% \mdHessenbergSpike[pos][fillcolor]{dir} | Hessenberg outline (filled if
%% fillcolor is given, as in \mdHessenberg) plus a spike off the
%% off-diagonal line at pos on the main diagonal (pos in [0,1], default 0.5):
%%   left: upper Hessenberg; row spike at y=1-pos, from the sub-diagonal
%%         across to the left edge
%%   up:   lower Hessenberg; column spike at x=pos, from the super-diagonal
%%         up to the top edge
%% ---------------------------------------------------------------------
\NewDocumentCommand{\mdHessenbergSpike}{O{0.5} O{none} m}{%
```

```
  \def\md@spikedir{#3}%
  \ifx\md@spikedir\md@left
    \mdHessenberg[#2]\md@spike@left{#1}%
  \else\ifx\md@spikedir\md@up
    \mdHessenbergLower[#2]\md@spike@up{#1}%
  \else
    \PackageError{matrixdiagrams}{Unknown \string\mdHessenbergSpike\space
      direction '#3'}{Use 'left' or 'up'.}%
  \fi\fi
}

%% ---------------------------------------------------------------------
%% Diagonal + bidiagonal spike command
%% \mdDiagBidiagSpike[pos]{dir} | diagonal block from the top-left corner
%% to the point at pos on the main diagonal (pos in [0,1], default 0.5),
%% a spike, then a bidiagonal from the spike to the bottom-right corner:
%%   up:   column spike at x=pos from the top edge down to the
%%         super-diagonal, which continues to the bottom-right
%%   left: row spike at y=1-pos from the left edge across to the
%%         sub-diagonal, which continues to the bottom-right
%% ---------------------------------------------------------------------
\NewDocumentCommand{\mdDiagBidiagSpike}{O{0.5} m}{%
  \def\md@spikedir{#2}%
  \ifx\md@spikedir\md@up
    \draw[thick] (0,\md@H) -- (1,0);%
    \draw[thick] ({#1},\md@H) -- ({#1},{(1-#1+\md@bandstep)*\md@H})
      -- (1,{\md@bandstep*\md@H});%
  \else\ifx\md@spikedir\md@left
    \draw[thick] (0,\md@H) -- (1,0);%
    \draw[thick] (0,{(1-#1)*\md@H}) -- ({#1-\md@bandstep},{(1-#1)*\md@H})
      -- ({1-\md@bandstep},0);%
  \else
    \PackageError{matrixdiagrams}{Unknown \string\mdDiagBidiagSpike\space
      direction '#2'}{Use 'up' or 'left'.}%
  \fi\fi
}

%% ---------------------------------------------------------------------
%% Bidiagonal commands
%%   upper: main diagonal + one super-diagonal
%%   lower: main diagonal + one sub-diagonal
%% ---------------------------------------------------------------------

%% \mdBidiagUpper | main diagonal + super-diagonal
\newcommand{\mdBidiagUpper}{%
  \draw[thick] (0,\md@H) -- (1,0);%
  \md@superdiag{1}%
}

%% \mdBidiagLower | main diagonal + sub-diagonal
\newcommand{\mdBidiagLower}{%
  \draw[thick] (0,\md@H) -- (1,0);%
  \md@subdiag{1}%
}

%% ---------------------------------------------------------------------
```

```
%% Hessenberg commands
%% \mdHessenberg[fillcolor] (alias \mdHessenbergUpper), and its transpose
%% \mdHessenbergLower[fillcolor]
%%   No argument: outline only (default).
%%   With color argument: filled triangle + outline.
%% ------------------------------------------------------------------------
\newcommand{\mdHessenberg}[1][none]{%
  \def\md@hessarg{#1}\def\md@hessnone{none}%
  \ifx\md@hessarg\md@hessnone
    \draw[thick] (0,\md@H) -- (1,\md@H) -- (1,0) -- cycle;%
  \else
    \fill[#1] (0,\md@H) -- (1,\md@H) -- (1,0) -- cycle;%
    \draw[thick] (0,\md@H) -- (1,\md@H) -- (1,0) -- cycle;%
  \fi
  \md@subdiag{1}%
}

%% \mdHessenbergUpper[fillcolor] | alias for \mdHessenberg
\let\mdHessenbergUpper\mdHessenberg

%% \mdHessenbergLower[fillcolor] | lower-triangular outline + super-diagonal;
%% the transpose of \mdHessenberg
\newcommand{\mdHessenbergLower}[1][none]{%
  \def\md@hessarg{#1}\def\md@hessnone{none}%
  \ifx\md@hessarg\md@hessnone\else
    \fill[#1] (0,\md@H) -- (0,0) -- (1,0) -- cycle;%
  \fi
  \draw[thick] (0,\md@H) -- (0,0) -- (1,0) -- cycle;%
  \md@superdiag{1}%
}

%% \mdBlank | empty content (brackets only)
\newcommand{\mdBlank}{}
⟨/package⟩
```