## SPECIFICATION FOR APPROVAL

★ Commodity: 5050 SMD

★ Model No: 5050-RGB


**★** Emission Color: RGB

★ Lens Appearance: Water Clear

★ Quality & Safety Certification: RoHS

CUSTOMER A	APPROVED	ВҮ	DATE

### Package Dimensions



1/2/3. Anode. 4/5/6. Cathode.

#### Notes

- 1: All dimensions are in millimeters.
- 2: Tolerance is  $\pm 0.1$ mm unless otherwise specified.

# ■ Absolute Maximum Ratings (Ta = 25°C)

Parameter	Symbol	Rating	Unit
Power Dissipation	Pd	R:100 G:100 B:100	mW
Forward Current	I <sub>F</sub>	R:20 G:20 B:20	mA
Peak Forward Current*1	I <sub>FP</sub>	R:100 G:100 B:100	mA
Reverse Voltage	$V_R$	R:5 G:5 B:5	٧
Operating Temperature Range	Topr	-20~80	${\mathbb C}$
Storage Temperature Range	Tstg	-40~85	$^{\circ}$
Soldering Temperature	Tsol	260 (for 5 seconds)	$^{\circ}$ C

### ● Typical Electrical-Optical Characteristics Curves (Ta=25°C)

Parameter	Symbol	Condition	Min	Тур	Max	Unit
Forward Voltage	V <sub>F</sub>	R	1.8	2.0	2.2	V
		G	3.0	3.2	3.4	V
		В	3.0	3.2	3.4	V
Reverse Current	I <sub>R</sub>	VR=5V			10	μΑ
Dominant Wavelength	λD	R	620	625	630	nm
		G	515	520	525	nm
		В	460	465	470	nm
Luminous Intensity	lv	R	500	650	800	mcd
		G	800	1000	1200	mcd
		В	300	400	500	mcd
Viewing Angle	201/2	IF =20mA		120		deg

### Typical Electrical/Optical Characteristics Curves (R)




Fig.1 Forward Current vs. Forward Voltage




Fig.3 Relative Luminous Intensity vs. Ambient Temperature




Fig.5 Maximum Forward Current vs. Ambient Temperature




Fig.2 Relative Luminous Intensit vs. Forward Current




Fig.4 Relative Luminous Flux vs. Wavelength




Fig.6 Relative Luminous Intensity vs.Radiation Angle

### Typical Electrical/Optical Characteristics Curves (G)





Fig.1 Forward Current vs. Forward Voltage






Fig.5 Maximum Forward Current vs. Ambient Temperature




Fig.2 Relative Luminous Intensit vs. Forward Current




Fig.4 Relative Luminous Flux vs. Wavelength




Fig.6 Relative Luminous Intensity vs.Radiation Angle

### Typical Electrical/Optical Characteristics Curves (B)





Fig.1 Forward Current vs. Forward Voltage



If(mA)50 40 30 20

Ta(.) 20 Fig.5 Maximum Forward Current vs. Ambient Temperature

80

40

10

0




Fig.2 Relative Luminous Intensit vs. Forward Current




Fig.4 Relative Luminous Flux vs. Wavelength




Fig.6 Relative Luminous Intensity vs.Radiation Angle