

Daily-Level GAM Analysis of Monarch Butterfly Abundance

Kyle Nessen

2025-09-30

Table of contents

Introduction	1
Setup	2
Data Exploration	2
Data Structure and Summary	2
Response Variable Distribution	4
Correlation Analysis	5
Response Variable Normality Assessment	7
Temperature Patterns	13
Wind and Sun Exposure	15
Data Preparation	17
Modeling Strategy	18
Model Building and Selection	19
Model Fitting	23
Model Comparison	25
Best Model Analysis	28
Effect Visualizations	30
Model Diagnostics	33
Models with Strong Support ($\Delta AICc < 2$)	36
Model Summaries for Supported Models	38
Partial Effects for Supported Models	44

Introduction

This analysis investigates daily-level patterns in overwintering monarch butterfly abundance using Generalized Additive Models (GAMs). Unlike the 30-minute interval analysis, this approach aggregates data to daily summaries, examining how previous day's weather conditions

affect butterfly abundance. The response variable is the 95th percentile of butterfly counts, providing a robust measure of daily peak abundance while being less sensitive to outliers than the maximum.

Setup

Load libraries and data:

```
library(tidyverse)
library(mgcv)
library(lubridate)
library(plotly)
library(knitr)
library(DT)
library(here)
library(gratia)
library(patchwork)
library(corrplot)

# Load the daily lag analysis data
daily_data <- read_csv(here("data", "monarch_daily_lag_analysis.csv"))

# Create the square root transformed response variable early for use throughout
daily_data <- daily_data %>%
  mutate(
    butterfly_diff_95th_sqrt = ifelse(butterfly_diff_95th >= 0,
      sqrt(butterfly_diff_95th),
      -sqrt(-butterfly_diff_95th)
    )
  )
```

Data Exploration

Data Structure and Summary

```
# Basic summary statistics
cat("Dataset dimensions:", nrow(daily_data), "rows x", ncol(daily_data), "columns\n")
```

Dataset dimensions: 103 rows x 46 columns

```
cat("Number of deployments:", n_distinct(daily_data$deployment_id), "\n")
```

Number of deployments: 7

```
cat("Date range:", min(daily_data$date_t), "to", max(daily_data$date_t), "\n\n")
```

Date range: 19680 to 19756

```
# Summary of key variables
summary_vars <- daily_data %>%
  select(
    butterflies_95th_percentile_t,
    butterflies_95th_percentile_t_1,
    butterfly_diff_95th,
    temp_max_t_1,
    temp_min_t_1,
    temp_at_max_count_t_1,
    wind_max_gust_t_1,
    sum_butterflies_direct_sun_t_1
  )

summary(summary_vars)
```

butterflies_95th_percentile_t	butterflies_95th_percentile_t_1
Min. : 0.00	Min. : 0.0
1st Qu.: 14.85	1st Qu.: 17.5
Median : 70.05	Median : 77.0
Mean : 107.41	Mean : 116.3
3rd Qu.: 166.95	3rd Qu.: 199.5
Max. : 499.00	Max. : 499.0

butterfly_diff_95th	temp_max_t_1	temp_min_t_1	temp_at_max_count_t_1
Min. : -310.000	Min. : 14.00	Min. : 3.000	Min. : 5.00
1st Qu.: -31.000	1st Qu.: 16.00	1st Qu.: 7.000	1st Qu.: 11.50
Median : -2.950	Median : 18.00	Median : 10.000	Median : 14.00
Mean : -8.919	Mean : 19.43	Mean : 9.573	Mean : 13.37
3rd Qu.: 18.000	3rd Qu.: 22.00	3rd Qu.: 12.000	3rd Qu.: 15.50
Max. : 256.600	Max. : 37.00	Max. : 16.000	Max. : 25.00

wind_max_gust_t_1	sum_butterflies_direct_sun_t_1
-------------------	--------------------------------

Min.	:0.000	Min.	: 0.00
1st Qu.:	2.750	1st Qu.:	2.00
Median	:3.750	Median	: 19.00
Mean	:3.718	Mean	: 94.77
3rd Qu.:	4.500	3rd Qu.:	104.00
Max.	:7.200	Max.	:1122.00
NA's	:3		

Response Variable Distribution

```
library(gridExtra)

# Current day's 95th percentile
p1 <- ggplot(daily_data, aes(x = butterflies_95th_percentile_t)) +
  geom_histogram(bins = 30, fill = "steelblue", alpha = 0.7) +
  labs(
    title = "Current Day: 95th Percentile Butterfly Count",
    x = "95th Percentile Count", y = "Frequency"
  ) +
  theme_minimal()


# Previous day's 95th percentile
p2 <- ggplot(daily_data, aes(x = butterflies_95th_percentile_t_1)) +
  geom_histogram(bins = 30, fill = "orange", alpha = 0.7) +
  labs(
    title = "Previous Day: 95th Percentile Butterfly Count",
    x = "95th Percentile Count", y = "Frequency"
  ) +
  theme_minimal()

# Difference in 95th percentile
p3 <- ggplot(daily_data, aes(x = butterfly_diff_95th)) +
  geom_histogram(bins = 30, fill = "purple", alpha = 0.7) +
  geom_vline(xintercept = 0, linetype = "dashed", color = "red") +
  labs(
    title = "Change in 95th Percentile (Current - Previous)",
    x = "Difference in 95th Percentile", y = "Frequency"
  ) +
  theme_minimal()

# Square root transformed difference
```

```
p4 <- ggplot(daily_data, aes(x = butterfly_diff_95th_sqrt)) +
  geom_histogram(bins = 30, fill = "darkgreen", alpha = 0.7) +
  geom_vline(xintercept = 0, linetype = "dashed", color = "red") +
  labs(
    title = "Change in 95th Percentile (Square Root Transformed)",
    x = "Difference (Square Root)", y = "Frequency"
  ) +
  theme_minimal()

grid.arrange(p1, p2, p3, p4, ncol = 2)
```



Correlation Analysis

```
# Select model variables
model_vars <- daily_data %>%
  select(
    butterfly_diff_95th_sqrt,
    butterflies_95th_percentile_t_1,
    temp_max_t_1,
    temp_min_t_1,
    temp_at_max_count_t_1,
```


```

        wind_max_gust_t_1,
        sum_butterflies_direct_sun_t_1
    ) %>%
    na.omit()

# Correlation matrix
cor_matrix <- cor(model_vars)

# Create correlation plot
corrplot(cor_matrix,
  method = "color",
  type = "upper",
  order = "hclust",
  tl.cex = 0.8,
  tl.col = "black",
  tl.srt = 45,
  addCoef.col = "black",
  number.cex = 0.6,
  title = "Correlation Matrix: Daily Model Variables"
)

```



```
# Print correlation table
kable(round(cor_matrix, 3),
       caption = "Correlation Matrix for Daily Model Variables"
)
```

Table 1: Correlation Matrix for Daily Model Variables

	butterfly_diff_95th_percentile	butterflies_95th_percentile_t_1	temp_max_t_1	temp_min_t_1	temp_at_max_count	wind_max_gust_t_1	sum_butterflies_direct_sun_t_1
butterfly_diff_95th_percentile	1.000	-0.389	-	-	0.145	0.193	-0.072
butterflies_95th_percentile_t_1	-0.389	1.000	-	-	-0.132	-0.211	0.442
temp_max_t_1	-0.112	-0.146	1.000	0.173	0.215	-0.334	0.016
temp_min_t_1	-0.042	-0.299	0.173	1.000	0.351	0.210	-0.331
temp_at_max_count	0.145	-0.132	0.215	0.351	1.000	-0.116	0.098
wind_max_gust_t_1	0.193	-0.211	-	0.210	-0.116	1.000	-0.122
sum_butterflies_direct_sun_t_1	-0.072	0.442	0.016	-	0.098	-0.122	1.000

Response Variable Normality Assessment

```
library(nortest)

# First, identify all potential response variables in the dataset
# Exclude already-transformed variables to prevent double-transformation
response_candidates <- daily_data %>%
  select(contains("diff"), contains("butterfly")) %>%
  select(-contains("direct_sun"), -contains("sqrt"), -contains("cbrt"), -contains("log")) %>%
  names()

cat("Available response variable candidates:\n")
```

Available response variable candidates:

```
print(response_candidates)
```

```
[1] "butterfly_diff"      "butterfly_diff_95th" "butterfly_diff_top3"
```

```

# Define transformations to test
transformations <- list(
  "original" = function(x) x,
  "sqrt" = function(x) ifelse(x >= 0, sqrt(x), -sqrt(-x)) # Signed square root
)

# Function to calculate normality statistics
assess_normality <- function(x, var_name, transform_name) {
  # Remove NA values
  x_clean <- x[!is.na(x)]

  if (length(x_clean) < 10) {
    return(data.frame(
      Variable = var_name,
      Transformation = transform_name,
      N = length(x_clean),
      Mean = NA,
      SD = NA,
      Skewness = NA,
      Kurtosis = NA,
      Shapiro_p = NA,
      Anderson_p = NA,
      Normality_Score = 0
    ))
  }

  # Calculate statistics
  mean_val <- mean(x_clean)
  sd_val <- sd(x_clean)
  skew_val <- moments::skewness(x_clean)
  kurt_val <- moments::kurtosis(x_clean) - 3 # Excess kurtosis

  # Normality tests
  shapiro_p <- if (length(x_clean) <= 5000) shapiro.test(x_clean)$p.value else NA
  anderson_p <- tryCatch(nortest::ad.test(x_clean)$p.value, error = function(e) NA)

  # Create composite normality score (higher = more normal)
  # Based on: low absolute skewness, low absolute kurtosis, high p-values
  skew_score <- max(0, 1 - abs(skew_val) / 2) # Penalize skewness > 2
  kurt_score <- max(0, 1 - abs(kurt_val) / 4) # Penalize excess kurtosis > 4
  shapiro_score <- ifelse(is.na(shapiro_p), 0.5, shapiro_p)
  anderson_score <- ifelse(is.na(anderson_p), 0.5, anderson_p)

```



```

# Weighted composite score
normality_score <- (skew_score * 0.3 + kurt_score * 0.3 +
  shapiro_score * 0.2 + anderson_score * 0.2)

return(data.frame(
  Variable = var_name,
  Transformation = transform_name,
  N = length(x_clean),
  Mean = round(mean_val, 3),
  SD = round(sd_val, 3),
  Skewness = round(skew_val, 3),
  Kurtosis = round(kurt_val, 3),
  Shapiro_p = ifelse(is.na(shapiro_p), NA, round(shapiro_p, 4)),
  Anderson_p = ifelse(is.na(anderson_p), NA, round(anderson_p, 4)),
  Normality_Score = round(normality_score, 4)
))
}

# Load required library for moments
library(moments)

# Apply transformations and assess normality for each response variable
normality_results <- list()

for (var_name in response_candidates) {
  if (var_name %in% names(daily_data)) {
    var_data <- daily_data[[var_name]]

    for (trans_name in names(transformations)) {
      trans_func <- transformations[[trans_name]]

      # Apply transformation
      transformed_data <- tryCatch(
        trans_func(var_data),
        error = function(e) rep(NA, length(var_data))
      )

      # Assess normality
      result <- assess_normality(transformed_data, var_name, trans_name)
      normality_results[[paste(var_name, trans_name, sep = "_")]] <- result
    }
  }
}

```

```

}

# Combine results
normality_df <- do.call(rbind, normality_results)

# Rank by normality score
normality_ranking <- normality_df %>%
  arrange(desc(Normality_Score)) %>%
  filter(!is.na(Normality_Score)) %>%
  mutate(Rank = row_number()) %>%
  select(
    Rank, Variable, Transformation, N, Mean, SD, Skewness, Kurtosis,
    Shapiro_p, Anderson_p, Normality_Score
  )

# Display top 15 most normal distributions
cat("Top 15 most normal response variable transformations:\n\n")

```

Top 15 most normal response variable transformations:

```

kable(head(normality_ranking, 15),
  caption = "Response variables ranked by normality (higher score = more normal)"
)

```

Table 2: Response variables ranked by normality (higher score = more normal)

	Rank	Variable	Transformation	N	Mean	SD	Skewness	Kurtosis	Shapiro_p	Anderson_p	Normality_Score
butterfly_diff_95th_butterfly_diff	1	butterfly_diff_95th_butterfly_diff	95th	103	-	7.382	0.021	-	0.6501	0.5918	0.8102
					0.809			0.467			
butterfly_diff_top3_butterfly_diff	2	butterfly_diff_top3_butterfly_diff	top3	103	-	7.379	0.039	-	0.6273	0.5818	0.8033
					0.751			0.436			
butterfly_diff_sqrt_butterfly_diff	3	butterfly_diff_sqrt_butterfly_diff	sqrt	103	-	8.033	0.238	-	0.6179	0.3799	0.7552
					1.148			0.117			
butterfly_diff_top3_butterfly_diff	4	butterfly_diff_top3_butterfly_diff	top3	103	-	87.141	-	2.983	0.0000	0.0000	0.3724
					8.547		0.026				
butterfly_diff_95th_butterfly_diff	5	butterfly_diff_95th_butterfly_diff	95th	103	-	86.928	-	2.525	0.0000	0.0000	0.3502
					8.919		0.402				
butterfly_diff_orig_butterfly_diff	6	butterfly_diff_orig_butterfly_diff	orig	103	-	108.330	0.389	5.076	0.0000	0.0000	0.2417
					10.097						

```
# Create summary by variable
variable_summary <- normality_ranking %>%
  group_by(Variable) %>%
  slice_max(Normality_Score, n = 1) %>%
  ungroup() %>%
  arrange(desc(Normality_Score)) %>%
  select(Variable,
         Best_Transformation = Transformation, Best_Score = Normality_Score,
         Skewness, Kurtosis, Shapiro_p
  )

cat("\n\nBest transformation for each response variable:\n")
```

Best transformation for each response variable:

```
kable(variable_summary,
      caption = "Best transformation for each response variable"
)
```

Table 3: Best transformation for each response variable

Variable	Best_Transformation	Best_Score	Skewness	Kurtosis	Shapiro_p
butterfly_diff_95th	sqrt	0.8102	0.021	-0.467	0.6501
butterfly_diff_top3	sqrt	0.8033	0.039	-0.436	0.6273
butterfly_diff	sqrt	0.7552	0.238	-0.117	0.6179

```
cat("\n\nUsing the best response variable transformation: butterfly_diff_95th_sqrt\n")
```

Using the best response variable transformation: butterfly_diff_95th_sqrt

```
cat("Summary of transformed response variable:\n")
```

Summary of transformed response variable:

```
print(summary(daily_data$butterfly_diff_95th_sqrt))
```

```
      Min.   1st Qu.   Median     Mean  3rd Qu.    Max.
-17.6068  -5.5649  -1.7176  -0.8088   4.2426  16.0187
```

```
# Visualize all transformations (original and sqrt)
top_transformations <- normality_ranking

plots <- list()
for (i in 1:nrow(top_transformations)) {
  row <- top_transformations[i, ]
  var_name <- row$Variable
  trans_name <- row$Transformation

  if (var_name %in% names(daily_data)) {
    var_data <- daily_data[[var_name]]
    trans_func <- transformations[[trans_name]]
    transformed_data <- trans_func(var_data)

    # Create histogram with normal overlay
    p <- ggplot(data.frame(x = transformed_data), aes(x = x)) +
      geom_histogram(aes(y = after_stat(density)),
        bins = 30,
        fill = "steelblue", alpha = 0.7
      ) +
      stat_function(
        fun = dnorm,
        args = list(
          mean = mean(transformed_data, na.rm = TRUE),
          sd = sd(transformed_data, na.rm = TRUE)
        ),
        color = "red", size = 1
      ) +
      labs(
        title = paste0("Rank ", i, ": ", var_name),
        subtitle = paste0(trans_name, " (Score: ", row$Normality_Score, ")"),
        x = paste0(var_name, " (", trans_name, ")"),
        y = "Density"
      ) +
      theme_minimal() +
      theme(
```


```

        plot.title = element_text(size = 10),
        plot.subtitle = element_text(size = 8)
    )

    plots[[i]] <- p
}

# Arrange plots in grid
do.call(grid.arrange, c(plots, ncol = 3))

```



Temperature Patterns

```

# Temperature relationships
p1 <- ggplot(daily_data, aes(x = temp_max_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "red") +
  geom_smooth(method = "loess", se = TRUE, color = "darkred") +
  labs(
    title = "Maximum Temperature vs Butterfly Change",
    x = "Previous Day Max Temperature (°C)",
    y = "Change in 95th Percentile (sqrt)"
  )

```

```

) +
  theme_minimal()

p2 <- ggplot(daily_data, aes(x = temp_min_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "blue") +
  geom_smooth(method = "loess", se = TRUE, color = "darkblue") +
  labs(
    title = "Minimum Temperature vs Butterfly Change",
    x = "Previous Day Min Temperature (°C)",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()


p3 <- ggplot(daily_data, aes(x = temp_at_max_count_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "orange") +
  geom_smooth(method = "loess", se = TRUE, color = "darkorange") +
  labs(
    title = "Temperature at Max Count vs Butterfly Change",
    x = "Previous Day Temp at Max Count (°C)",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()

# Temperature range
daily_data <- daily_data %>%
  mutate(temp_range_t_1 = temp_max_t_1 - temp_min_t_1)

p4 <- ggplot(daily_data, aes(x = temp_range_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "purple") +
  geom_smooth(method = "loess", se = TRUE, color = "darkviolet") +
  labs(
    title = "Temperature Range vs Butterfly Change",
    x = "Previous Day Temp Range (°C)",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()

grid.arrange(p1, p2, p3, p4, ncol = 2)

```



Wind and Sun Exposure

```
# Wind effect
p1 <- ggplot(daily_data, aes(x = wind_max_gust_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "steelblue") +
  geom_smooth(method = "loess", se = TRUE, color = "darkblue") +
  geom_vline(xintercept = 2, linetype = "dashed", color = "red", alpha = 0.5) +
  labs(
    title = "Maximum Wind Gust vs Butterfly Change",
    x = "Previous Day Max Wind Gust (m/s)",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()

# Sun exposure
p2 <- ggplot(daily_data, aes(x = sum_butterflies_direct_sun_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "orange") +
  geom_smooth(method = "loess", se = TRUE, color = "darkorange") +
  labs(
    title = "Direct Sun Exposure vs Butterfly Change",
    x = "Previous Day Sum of Butterflies in Direct Sun",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()
```

```


      y = "Change in 95th Percentile (sqrt)"
    ) +
    theme_minimal()

# Note: Seasonal progression will be handled via temporal autocorrelation
# rather than as a fixed effect
p3 <- ggplot(daily_data, aes(x = date_t, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "darkgreen") +
  geom_smooth(method = "loess", se = TRUE, color = "forestgreen") +
  labs(
    title = "Temporal Pattern vs Butterfly Change",
    x = "Date",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()

# Previous day baseline
p4 <- ggplot(daily_data, aes(x = butterflies_95th_percentile_t_1, y = butterfly_diff_95th_sqrt)) +
  geom_point(alpha = 0.3, color = "purple") +
  geom_smooth(method = "loess", se = TRUE, color = "darkviolet") +
  labs(
    title = "Previous Day Baseline vs Change",
    x = "Previous Day 95th Percentile Count",
    y = "Change in 95th Percentile (sqrt)"
  ) +
  theme_minimal()

grid.arrange(p1, p2, p3, p4, ncol = 2)

```

Data Preparation

```
# Remove missing values and prepare modeling dataset
model_data <- daily_data %>%
  filter(
    !is.na(butterfly_diff_95th_sqrt),
    !is.na(butterflies_95th_percentile_t_1),
    !is.na(temp_max_t_1),
    !is.na(temp_min_t_1),
    !is.na(temp_at_max_count_t_1),
    !is.na(wind_max_gust_t_1),
    !is.na(sum_butterflies_direct_sun_t_1),
    !is.na(deployment_id)
  ) %>%
  # Create standardized versions for interpretation
  mutate(
    wind_max_gust_std = scale(wind_max_gust_t_1)[, 1],
    temp_max_std = scale(temp_max_t_1)[, 1],
    temp_min_std = scale(temp_min_t_1)[, 1],
    temp_at_max_std = scale(temp_at_max_count_t_1)[, 1],
    sun_exposure_std = scale(sum_butterflies_direct_sun_t_1)[, 1],
```

```

baseline_std = scale(butterflies_95th_percentile_t_1)[, 1],
# Note: day_sequence is now provided by the data preparation script
# Each deployment has its own day counter starting from 1
)

cat("Clean dataset has", nrow(model_data), "observations\n")

```

Clean dataset has 100 observations

```
cat("Number of unique deployment days:", n_distinct(paste(model_data$deployment_id, model_data$day)))
```

Number of unique deployment days: 100

Modeling Strategy

Our modeling approach for daily-level data tests both **absolute effects** and **proportional effects** of environmental variables on butterfly abundance changes:

1. **Response Variable:** `butterfly_diff_95th_sqrt` - square root transformed difference in 95th percentile butterfly counts between consecutive days (selected as the most normal transformation)

2. **Two Model Sets:**

M Models (Absolute Effects): Test whether environmental variables have direct effects on absolute changes in abundance:

- Do NOT include previous day's butterfly count
- Test if weather has consistent magnitude effects regardless of population size

B Models (Proportional/Density-Dependent Effects): Test whether environmental effects depend on baseline population:

- Include `butterflies_95th_percentile_t_1` as a covariate
- Test if weather effects scale with population size
- Include interactions between baseline count and environmental variables

3. **Fixed Effects** (tested in various combinations):

- Temperature variables: max, min, and temperature at max count
- Wind: maximum gust from previous day
- Sun exposure: sum of butterflies in direct sun from previous day
- Previous day baseline: 95th percentile count (B models only)

4. Random Effects:

- Deployment ID (random intercept)
- AR1 temporal autocorrelation within deployments using `day_sequence | deployment_id`

5. Correlation Structures:

- No correlation (baseline)
- AR1 within deployments to account for temporal autocorrelation

This dual approach allows us to distinguish between: - **Absolute effects:** Environmental variables cause fixed-magnitude changes regardless of population size - **Proportional effects:** Environmental impacts scale with the existing population (density-dependence)

Model Building and Selection

```
library(nlme)

# Define random effects structure with temporal autocorrelation
# We'll test different correlation structures
random_structure <- list(deployment_id = ~1)

# Define correlation structures to test
correlation_structures <- list(
  "no_corr" = NULL, # No temporal correlation
  "AR1" = corAR1(form = ~ day_sequence | deployment_id) # AR1 within deployments
)

# Model specifications for AIC comparison - WITHOUT previous day baseline
model_specs <- list(
  # Null model
  "M1" = "butterfly_diff_95th_sqrt ~ 1",

  # Single predictor models (linear)
  "M2" = "butterfly_diff_95th_sqrt ~ wind_max_gust_t_1",
  "M3" = "butterfly_diff_95th_sqrt ~ temp_max_t_1",
  "M4" = "butterfly_diff_95th_sqrt ~ temp_min_t_1",
  "M5" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1",
  "M6" = "butterfly_diff_95th_sqrt ~ sum_butterflies_direct_sun_t_1",

  # Temperature combinations (linear)
```

```

"M8" = "butterfly_diff_95th_sqrt ~ temp_max_t_1 + temp_min_t_1",
"M9" = "butterfly_diff_95th_sqrt ~ temp_max_t_1 + temp_at_max_count_t_1",
"M10" = "butterfly_diff_95th_sqrt ~ temp_min_t_1 + temp_at_max_count_t_1",
"M11" = "butterfly_diff_95th_sqrt ~ temp_max_t_1 + temp_min_t_1 + temp_at_max_count_t_1"

# Two-variable combinations
"M12" = "butterfly_diff_95th_sqrt ~ wind_max_gust_t_1 + temp_max_t_1",
"M13" = "butterfly_diff_95th_sqrt ~ wind_max_gust_t_1 + temp_min_t_1",
"M14" = "butterfly_diff_95th_sqrt ~ wind_max_gust_t_1 + temp_at_max_count_t_1",
"M15" = "butterfly_diff_95th_sqrt ~ wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M16" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 + sum_butterflies_direct_sun_t_1"

# Full models with various temperature specs (linear)
"M17" = "butterfly_diff_95th_sqrt ~ temp_max_t_1 + wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M18" = "butterfly_diff_95th_sqrt ~ temp_min_t_1 + wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M19" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 + wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M20" = "butterfly_diff_95th_sqrt ~ temp_max_t_1 + temp_min_t_1 + wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M21" = "butterfly_diff_95th_sqrt ~ temp_max_t_1 + temp_min_t_1 + temp_at_max_count_t_1 + sum_butterflies_direct_sun_t_1"

# Smooth terms models - single predictors
"M24" = "butterfly_diff_95th_sqrt ~ s(wind_max_gust_t_1)",
"M25" = "butterfly_diff_95th_sqrt ~ s(temp_max_t_1)",
"M26" = "butterfly_diff_95th_sqrt ~ s(temp_min_t_1)",
"M27" = "butterfly_diff_95th_sqrt ~ s(temp_at_max_count_t_1)",
"M28" = "butterfly_diff_95th_sqrt ~ s(sum_butterflies_direct_sun_t_1)",

# Smooth terms - combinations
"M30" = "butterfly_diff_95th_sqrt ~ s(temp_max_t_1) + s(temp_min_t_1)",
"M31" = "butterfly_diff_95th_sqrt ~ s(temp_at_max_count_t_1) + s(wind_max_gust_t_1)",
"M32" = "butterfly_diff_95th_sqrt ~ s(temp_at_max_count_t_1) + s(sum_butterflies_direct_sun_t_1)",
"M33" = "butterfly_diff_95th_sqrt ~ s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)",

# Complex smooth models
"M34" = "butterfly_diff_95th_sqrt ~ s(temp_at_max_count_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)",
"M35" = "butterfly_diff_95th_sqrt ~ s(temp_max_t_1) + s(temp_min_t_1) + s(wind_max_gust_t_1)",
"M37" = "butterfly_diff_95th_sqrt ~ s(temp_max_t_1) + s(temp_min_t_1) + s(temp_at_max_count_t_1)",

# Mixed linear and smooth
"M38" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)",
"M39" = "butterfly_diff_95th_sqrt ~ s(temp_at_max_count_t_1) + wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M40" = "butterfly_diff_95th_sqrt ~ s(temp_at_max_count_t_1) + wind_max_gust_t_1 + s(sum_butterflies_direct_sun_t_1)"

```

```

# Interaction models (without baseline)
"M41" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 * wind_max_gust_t_1",
"M42" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 * sum_butterflies_direct_sun_t_1",
"M43" = "butterfly_diff_95th_sqrt ~ wind_max_gust_t_1 * sum_butterflies_direct_sun_t_1",
"M44" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 * wind_max_gust_t_1 + sum_butterflies_direct_sun_t_1",
"M45" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 + wind_max_gust_t_1 * sum_butterflies_direct_sun_t_1",
"M46" = "butterfly_diff_95th_sqrt ~ temp_at_max_count_t_1 * wind_max_gust_t_1 * sum_butterflies_direct_sun_t_1",

# Temperature range models
"M47" = "butterfly_diff_95th_sqrt ~ I(temp_max_t_1 - temp_min_t_1)",
"M48" = "butterfly_diff_95th_sqrt ~ I(temp_max_t_1 - temp_min_t_1) + wind_max_gust_t_1",
"M49" = "butterfly_diff_95th_sqrt ~ s(I(temp_max_t_1 - temp_min_t_1))",
"M50" = "butterfly_diff_95th_sqrt ~ s(I(temp_max_t_1 - temp_min_t_1)) + s(wind_max_gust_t_1)",

# ===== MODELS WITH PREVIOUS DAY BASELINE =====
# All models below include butterflies_95th_percentile_t_1 to test proportional effects

# Baseline-only model
"B1" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1",

# Single predictor models + baseline (linear)
"B2" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + wind_max_gust_t_1",
"B3" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1",
"B4" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_min_t_1",
"B5" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1",
"B6" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + sum_butterflies_direct_sun_t_1",

# Temperature combinations + baseline (linear)
"B8" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1 + temp_min_t_1",
"B9" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1 + temp_at_max_count_t_1",
"B10" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_min_t_1 + temp_at_max_count_t_1",
"B11" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1 + temp_at_max_count_t_1",

# Two-variable combinations + baseline
"B12" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + wind_max_gust_t_1 + temp_max_t_1",
"B13" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + wind_max_gust_t_1 + temp_min_t_1",
"B14" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + wind_max_gust_t_1 + temp_at_max_count_t_1",
"B15" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + wind_max_gust_t_1 + temp_max_t_1 + temp_min_t_1",
"B16" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1 + temp_max_t_1 + temp_min_t_1",

# Full models with various temperature specs + baseline (linear)
"B17" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1 + wind_max_gust_t_1 + temp_min_t_1 + temp_at_max_count_t_1"

```

```

"B18" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_min_t_1 + wind_max_gust_t_1",
"B19" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1",
"B20" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1 + temp_min_t_1",
"B21" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_max_t_1 + temp_at_max_count_t_1",

# Smooth terms models - single predictors + baseline
"B24" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1)",
"B25" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1)",
"B26" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_min_t_1)",
"B27" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1)",
"B28" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(sum_butterflies_count_t_1)",

# Smooth baseline + other predictors
"B29" = "butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1)",
"B29a" = "butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + wind_max_gust_t_1",
"B29b" = "butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + temp_at_max_count_t_1",
"B29c" = "butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + s(wind_max_gust_t_1)",
"B29d" = "butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + s(temp_at_max_count_t_1)",

# Smooth terms - combinations + baseline
"B30" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1)",
"B31" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1)",
"B32" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1) + s(temp_max_t_1)",
"B33" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1) + s(temp_at_max_count_t_1)",

# Complex smooth models + baseline
"B34" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1) + s(temp_max_t_1)",
"B35" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1)",
"B37" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(temp_at_max_count_t_1)",

# Mixed linear and smooth + baseline
"B38" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1",
"B39" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1)",
"B40" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1) + temp_max_t_1",

# Interaction models with baseline
"B41" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1 + temp_max_t_1",
"B42" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1 + temp_min_t_1",
"B43" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + wind_max_gust_t_1 + temp_at_max_count_t_1",
"B44" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1 + temp_max_t_1",
"B45" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1 + temp_min_t_1",
"B46" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + temp_at_max_count_t_1 + temp_max_t_1 + temp_min_t_1"

```

```

# Temperature range models + baseline
"B47" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + I(temp_max_t_1 - t
"B48" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + I(temp_max_t_1 - t
"B49" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(I(temp_max_t_1 - t
"B50" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(I(temp_max_t_1 - t

# Interaction with baseline (testing if environmental effects depend on population size)
"B51" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 * wind_max_gust_t_1"
"B52" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 * temp_at_max_count_t_1"
"B53" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 * sum_butterflies_diff_t_1"
"B54" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 * wind_max_gust_t_1 +
"B55" = "butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 * temp_at_max_count_t_1
)

cat("Total models to fit:", length(model_specs), "\n")

```

Total models to fit: 100

```

cat("- M models (M1-M50):", sum(grepl("^M", names(model_specs))), "models WITHOUT previous day baseline")

```

- M models (M1-M50): 45 models WITHOUT previous day baseline

```

cat("- B models (B1-B55):", sum(grepl("^B", names(model_specs))), "models WITH previous day baseline")

```

- B models (B1-B55): 55 models WITH previous day baseline

Model Fitting

```

# Function to safely fit models with correlation structures
fit_model_safely <- function(formula_str, data, correlation = NULL, corr_name = "no_corr") {
  tryCatch(
    {
      formula_obj <- as.formula(formula_str)

      # Fit the model with or without correlation structure
      if (is.null(correlation)) {
        model <- gamm(formula_obj,

```

```

        data = data,
        random = random_structure,
        method = "REML"
    )
} else {
    model <- gamm(formula_obj,
        data = data,
        random = random_structure,
        correlation = correlation,
        method = "REML"
    )
}

# Add correlation structure name to the model for tracking
model$correlation_structure <- corr_name
return(model)
},
error = function(e) {
    message("Failed to fit model: ", formula_str, " with correlation: ", corr_name)
    message("Error: ", e$message)
    return(NULL)
}
)
}

# Fit all models with different correlation structures
cat("Fitting models...\n")

```

Fitting models...

```

fitted_models <- list()

# Fit each model specification with each correlation structure
for (model_name in names(model_specs)) {
    formula_str <- model_specs[[model_name]]

    for (corr_name in names(correlation_structures)) {
        corr_struct <- correlation_structures[[corr_name]]

        # Create unique model name with correlation structure
        full_model_name <- paste(model_name, corr_name, sep = "_")
    }
}

```



```

        fitted_models[[full_model_name]] <- fit_model_safely(
          formula_str, model_data, corr_struct, corr_name
        )
      }
    }

# Remove failed models
successful_models <- fitted_models[!map_lgl(fitted_models, is.null)]
cat(
  "Successfully fitted", length(successful_models), "out of",
  length(model_specs), "models\n"
)

```

Successfully fitted 200 out of 100 models

Model Comparison

```

# Extract AIC values
aic_results <- map_dfr(names(successful_models), function(full_model_name) {
  model <- successful_models[[full_model_name]]

  # Parse model name and correlation structure
  name_parts <- strsplit(full_model_name, "_")[[1]]
  corr_suffix <- name_parts[length(name_parts)]
  base_model_name <- paste(name_parts[-length(name_parts)], collapse = "_")

  # Get the formula from the base model name
  formula_str <- model_specs[[base_model_name]]
  if (is.null(formula_str)) {
    formula_str <- "Unknown formula"
  }

  data.frame(
    Model = full_model_name,
    Base_Model = base_model_name,
    Correlation = corr_suffix,
    Formula = formula_str,
    AIC = AIC(model$lme),
    LogLik = logLik(model$lme)[1],
  )
})

```

```

    df = attr(logLik(model$lme), "df"),
    stringsAsFactors = FALSE
  )
}) %>%
  arrange(AIC) %>%
  mutate(
    Delta_AIC = AIC - min(AIC),
    AIC_weight = exp(-0.5 * Delta_AIC) / sum(exp(-0.5 * Delta_AIC))
  )

# Display top 10 models
top_10_table <- aic_results %>%
  head(10) %>%
  select(Model, Correlation, AIC, Delta_AIC, AIC_weight, df)

top_10_table %>%
  kable(digits = 3, caption = "Top 10 models by AIC")

```

Table 4: Top 10 models by AIC

Model	Correlation	AIC	Delta_AIC	AIC_weight	df
B33_AR1	AR1	668.401	0.000	0.148	9
B29c_AR1	AR1	668.671	0.270	0.129	8
B28_AR1	AR1	669.101	0.700	0.104	7
B35_AR1	AR1	669.573	1.172	0.082	13
B37_AR1	AR1	669.594	1.193	0.081	15
B29_AR1	AR1	669.685	1.284	0.078	6
B34_AR1	AR1	670.016	1.615	0.066	11
B29a_AR1	AR1	670.504	2.103	0.052	7
B38_AR1	AR1	670.691	2.289	0.047	10
B29d_AR1	AR1	670.864	2.463	0.043	8

```

# Show model formulas for top 5
cat("\nTop 5 model specifications:\n")

```

Top 5 model specifications:

```
top_5_formulas <- head(aic_results, 5) %>%
  select(Base_Model, Correlation, Formula, Delta_AIC)

top_5_formulas %>%
  kable(digits = 3)
```

	Model	Formula	Delta_AIC
B33	AR1	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	0.000
B29c	AR1	butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + s(wind_max_gust_t_1)	0.270
B28	AR1	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(sum_butterflies_direct_sun_t_1)	0.700
B35	AR1	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	1.172
B37	AR1	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(temp_at_max_count_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	1.193

```
# Export model comparison tables as CSV for results write-up
write_csv(
  aic_results,
  here("analysis", "reports", "figures", "all_models_aic_table.csv")
)

write_csv(
  top_10_table,
  here("analysis", "reports", "figures", "top_10_models.csv")
)

cat("Exported AIC tables to: analysis/reports/figures/\n")
```

Exported AIC tables to: analysis/reports/figures/

```
cat("Note: strong_support_models will be exported after it's created\n")
```

Note: strong_support_models will be exported after it's created

Best Model Analysis

```
# Get the best model
best_model_name <- aic_results$Model[1]
best_model <- successful_models[[best_model_name]]

cat("Best model:", best_model_name, "\n")
```

Best model: B33_AR1

```
cat("Formula:", aic_results$Formula[1], "\n\n")
```

Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1) +

```
# Model summary
best_model_summary <- summary(best_model$gam)
print(best_model_summary)
```

Family: gaussian
Link function: identity

Formula:
butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 +
s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.444416	1.263453	2.726	0.00766 **
butterflies_95th_percentile_t_1	-0.037703	0.006972	-5.408	4.95e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(wind_max_gust_t_1)	2.466	2.466	2.725	0.08649 .
s(sum_butterflies_direct_sun_t_1)	2.918	2.918	6.122	0.00245 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
R-sq.(adj) = 0.226
  Scale est. = 43.072    n = 100
```

```
# Calculate R-squared
r_squared <- best_model_summary$r_sq
dev_explained <- best_model_summary$dev.expl

cat("\n\nModel Performance:\n")
```

Model Performance:

```
cat("R-squared:", round(r_squared, 4), "\n")
```

R-squared: 0.2264

```
cat("Deviance explained:", round(dev_explained * 100, 2), "%\n")
```

Deviance explained: %

```
# Export best model summary info for results write-up
# Use list-column approach to avoid vector length issues
best_model_info <- tribble(
  ~Metric, ~Value,
  "Model_Name", as.character(best_model_name)[1],
  "Formula", as.character(aic_results$Formula[1])[1],
  "Correlation", as.character(aic_results$Correlation[1])[1],
  "AIC", as.character(round(aic_results$AIC[1], 3)),
  "Delta_AIC", "0",
  "AIC_Weight", as.character(round(aic_results$AIC_weight[1], 4)),
  "R_squared", as.character(round(r_squared, 4)),
  "Deviance_Explained", as.character(round(dev_explained * 100, 2)),
  "N_obs", as.character(nrow(model_data))
)

write_csv(
  best_model_info,
  here("analysis", "reports", "figures", "best_model_summary.csv")
)
```

```
)

cat("Exported best model summary to: analysis/reports/figures/best_model_summary.csv\n")
```

Exported best model summary to: analysis/reports/figures/best_model_summary.csv

Effect Visualizations

```
# Define custom theme
custom_theme <- theme_minimal(base_size = 12) +
  theme(
    panel.grid.major = element_line(color = "gray90", size = 0.5),
    panel.grid.minor = element_line(color = "gray95", size = 0.3),
    axis.text = element_text(color = "black", size = 11),
    axis.title = element_text(color = "black", size = 12, face = "bold"),
    plot.title = element_text(color = "black", size = 14, face = "bold", hjust = 0.5),
    panel.border = element_rect(color = "black", fill = NA, size = 0.5),
    plot.margin = margin(10, 10, 10, 10)
  )

# Function to add zero line
add_zero_line <- function(plot) {
  zero_line_layer <- geom_hline(yintercept = 0, color = "gray70", size = 0.8, alpha = 1)
  plot$layers <- c(list(zero_line_layer), plot$layers)
  return(plot)
}
```

```
# Create effect plots for the best model
# Extract which terms are in the best model
best_formula <- aic_results$Formula[1]
has_smooth <- grepl("s\\(", best_formula)

if (has_smooth) {
  # For GAM with smooth terms
  plots <- list()

  # Check which smooth terms are in the model
  smooth_terms <- summary(best_model$gam)$s.table

  # Plot each smooth term
```


```

for (i in 1:nrow(smooth_terms)) {
  term_name <- rownames(smooth_terms)[i]
  p <- draw(best_model$gam, select = term_name, rug = FALSE, residuals = FALSE) +
    custom_theme +
    theme(plot.caption = element_blank())
  p <- add_zero_line(p)
  plots[[i]] <- p
}

# Combine plots
if (length(plots) > 0) {
  if (length(plots) <= 2) {
    combined_plots <- wrap_plots(plots, nrow = 1)
  } else if (length(plots) <= 4) {
    combined_plots <- wrap_plots(plots, nrow = 2)
  } else {
    combined_plots <- wrap_plots(plots, nrow = 3)
  }
  print(combined_plots)
}
} else {
  # For linear models, create partial residual plots
  cat("Best model uses linear terms. Creating partial residual plots...\n")

  # Extract coefficients
  coef_summary <- summary(best_model$gam)$p.table
  print(coef_summary)
}

```




```
# Export partial effects plot for best model (for results write-up)
if (has_smooth && length(plots) > 0) {
  ggsave(
    here("analysis", "reports", "figures", "best_model_partial_effects.png"),
    plot = combined_plots,
    width = 12, height = 8, dpi = 300
  )
  cat("Exported best model partial effects to: analysis/reports/figures/best_model_partial_effects.png\n")
}
```

Exported best model partial effects to: analysis/reports/figures/best_model_partial_effects.png

Model Diagnostics

```
# Create diagnostic plots
par(mfrow = c(2, 2))

# Residuals vs Fitted
plot(best_model$lme, main = "Residuals vs Fitted Values")
```



```
# Q-Q plot
qqnorm(residuals(best_model$lme, type = "normalized"), main = "Q-Q Plot")
qqline(residuals(best_model$lme, type = "normalized"))

# Scale-location plot
```




```

plot(fitted(best_model$lme), sqrt(abs(residuals(best_model$lme, type = "normalized"))),
     main = "Scale-Location Plot",
     xlab = "Fitted values",
     ylab = "sqrt(|Standardized residuals|)")
)
lines(lowess(fitted(best_model$lme), sqrt(abs(residuals(best_model$lme, type = "normalized")))),
      col = "red", lty = 2)

# Histogram of residuals
hist(residuals(best_model$lme, type = "normalized"),
     breaks = 30,
     main = "Distribution of Residuals",
     xlab = "Standardized Residuals",
     col = "lightblue")
)

par(mfrow = c(1, 1))

```



```
# Export diagnostic plots for results write-up
png(here("analysis", "reports", "figures", "best_model_diagnostics.png"),
    width = 12, height = 10, units = "in", res = 300)
par(mfrow = c(2, 2))

# Residuals vs Fitted
plot(best_model$lme, main = "Residuals vs Fitted Values")

# Q-Q plot
qqnorm(residuals(best_model$lme, type = "normalized"), main = "Q-Q Plot")
qqline(residuals(best_model$lme, type = "normalized"))

# Scale-location plot
plot(fitted(best_model$lme), sqrt(abs(residuals(best_model$lme, type = "normalized"))),
     main = "Scale-Location Plot",
```

```

      xlab = "Fitted values",
      ylab = "sqrt(|Standardized residuals|)"
    )
    lines(lowess(fitted(best_model$lme), sqrt(abs(residuals(best_model$lme, type = "normalized"))
  )

# Histogram of residuals
hist(residuals(best_model$lme, type = "normalized"),
      breaks = 30,
      main = "Distribution of Residuals",
      xlab = "Standardized Residuals",
      col = "lightblue"
)

par(mfrow = c(1, 1))
dev.off()

```

pdf
2

```
cat("Exported diagnostic plots to: analysis/reports/figures/best_model_diagnostics.png\n")
```

Exported diagnostic plots to: analysis/reports/figures/best_model_diagnostics.png

Models with Strong Support ($\Delta AIC_c < 2$)

This section examines all models with AIC differences less than 2 from the best model, as these represent models with substantial empirical support. For each supported model, we display the model summary and visualize partial effects.

```

# Filter models with Delta AIC < 2
strong_support_models <- aic_results %>%
  filter(Delta_AIC < 2) %>%
  arrange(Delta_AIC)

cat("Number of models with  $\Delta AIC < 2$ :", nrow(strong_support_models), "\n\n")

```

Number of models with $\Delta AIC < 2$: 7

```
# Display the supported models
strong_support_models %>%
  select(Model, Correlation, Formula, AIC, Delta_AIC, AIC_weight, df) %>%
  kable(digits = 4, caption = "Models with Strong Empirical Support ( $\Delta AIC < 2$ )")
```

Table 6: Models with Strong Empirical Support ($\Delta AIC < 2$)

Model	Correlation	Formula	AIC	Delta_AIC	AIC_weight
B33_AR1	0.10000	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	668.401	0.0000	0.14779
B29c_AR1	0.12700	butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + s(wind_max_gust_t_1)	668.671	0.2700	0.12918
B28_AR1	0.10999	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(sum_butterflies_direct_sun_t_1)	669.101	0.6999	0.10417
B35_AR1	0.10719	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	669.573	0.1719	0.082213
B37_AR1	0.11930	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(temp_at_max_count_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	669.594	0.1930	0.081415
B29_AR1	0.12842	butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1)	669.685	0.2842	0.07776
B34_AR1	0.11520	butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)	670.016	0.1520	0.065911

```
# Export strong support models
write_csv(
  strong_support_models,
  here("analysis", "reports", "figures", "strong_support_models.csv")
)
cat("Exported strong support models table\n")
```

Exported strong support models table

Model Summaries for Supported Models

```
# Display summary for each supported model
for (i in 1:nrow(strong_support_models)) {
  model_name <- strong_support_models$Model[i]
  model_obj <- successful_models[[model_name]]

  cat("\n")
  cat("=====\n")
  cat("MODEL:", model_name, "\n")
  cat("Formula:", strong_support_models$Formula[i], "\n")
  cat("ΔAIC:", round(strong_support_models$Delta_AIC[i], 3), "\n")
  cat("AIC Weight:", round(strong_support_models$AIC_weight[i], 4), "\n")
  cat("=====\n")

  # Model summary
  print(summary(model_obj$gam))

  # Calculate performance metrics
  r_squared <- summary(model_obj$gam)$r.sq
  dev_explained <- summary(model_obj$gam)$dev.expl

  cat("\nModel Performance:\n")
  cat("R-squared:", round(r_squared, 4), "\n")
  cat("Deviance explained:", round(dev_explained * 100, 2), "%\n")
  cat("\n")
}
```

```
=====
MODEL: B33_AR1
Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1) +
<U+0394>AIC: 0
AIC Weight: 0.1477
=====

Family: gaussian
Link function: identity
```

Formula:

butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 +
s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.444416	1.263453	2.726	0.00766 **
butterflies_95th_percentile_t_1	-0.037703	0.006972	-5.408	4.95e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(wind_max_gust_t_1)	2.466	2.466	2.725	0.08649 .
s(sum_butterflies_direct_sun_t_1)	2.918	2.918	6.122	0.00245 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

R-sq.(adj) = 0.226

Scale est. = 43.072 n = 100

Model Performance:

R-squared: 0.2264

Deviance explained: %

=====

MODEL: B29c_AR1

Formula: butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + s(wind_max_gust_t_1)

<U+0394>AIC: 0.27

AIC Weight: 0.1291

=====

Family: gaussian

Link function: identity

Formula:

butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) +
s(wind_max_gust_t_1)

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-1.078	1.068	-1.009	0.315

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(butterflies_95th_percentile_t_1)	1.153	1.153	24.194	1.55e-06 ***
s(wind_max_gust_t_1)	2.491	2.491	2.877	0.0649 .

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

R-sq.(adj) = 0.175

Scale est. = 44.916 n = 100

Model Performance:

R-squared: 0.1753

Deviance explained: %

=====

MODEL: B28_AR1

Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(sum_butterflies_direct_sun_t_1)

<U+0394>AIC: 0.7

AIC Weight: 0.1041

=====

Family: gaussian

Link function: identity

Formula:

butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 +
s(sum_butterflies_direct_sun_t_1)

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.560773	1.315741	2.706	0.00807 **
butterflies_95th_percentile_t_1	-0.038876	0.007134	-5.449	3.97e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(sum_butterflies_direct_sun_t_1)	2.886	2.886	6.284	0.00297 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1


```
R-sq.(adj) = 0.168
Scale est. = 46.265    n = 100
```

```
Model Performance:
R-squared: 0.1679
Deviance explained: %
```

```
=====
MODEL: B35_AR1
Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(tem
<U+0394>AIC: 1.172
AIC Weight: 0.0822
=====
```

```
Family: gaussian
Link function: identity
```

```
Formula:
butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 +
    s(temp_max_t_1) + s(temp_min_t_1) + s(wind_max_gust_t_1) +
    s(sum_butterflies_direct_sun_t_1)
```

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	3.711029	1.247939	2.974	0.00377	**
butterflies_95th_percentile_t_1	-0.039470	0.006988	-5.648	1.84e-07	***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value	
s(temp_max_t_1)	1.000	1.000	2.272	0.13522	
s(temp_min_t_1)	1.000	1.000	0.842	0.36135	
s(wind_max_gust_t_1)	2.362	2.362	2.184	0.16218	
s(sum_butterflies_direct_sun_t_1)	2.856	2.856	6.450	0.00261	**

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
R-sq.(adj) = 0.254
Scale est. = 41.83    n = 100
```

```
Model Performance:
```

R-squared: 0.2541
Deviance explained: %

```
=====
MODEL: B37_AR1
Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(tem
<U+0394>AIC: 1.193
AIC Weight: 0.0814
=====
```

Family: gaussian
Link function: identity

Formula:
butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 +
s(temp_max_t_1) + s(temp_min_t_1) + s(temp_at_max_count_t_1) +
s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.436246	1.240927	2.769	0.00684 **
butterflies_95th_percentile_t_1	-0.037152	0.006818	-5.449	4.47e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(temp_max_t_1)	1.000	1.000	1.714	0.1939
s(temp_min_t_1)	1.000	1.000	2.726	0.1023
s(temp_at_max_count_t_1)	1.713	1.713	1.396	0.1648
s(wind_max_gust_t_1)	2.508	2.508	1.695	0.1173
s(sum_butterflies_direct_sun_t_1)	2.876	2.876	5.087	0.0067 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

R-sq.(adj) = 0.301
Scale est. = 38.569 n = 100

Model Performance:
R-squared: 0.3011
Deviance explained: %

```
=====
MODEL: B29_AR1
Formula: butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1)
<U+0394>AIC: 1.284
AIC Weight: 0.0777
=====
```

```
Family: gaussian
Link function: identity
```

```
Formula:
butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1)
```

```
Parametric coefficients:
              Estimate Std. Error t value Pr(>|t|)
(Intercept) -1.0431      0.9863  -1.058    0.293
```

```
Approximate significance of smooth terms:
              edf Ref.df      F  p-value
s(butterflies_95th_percentile_t_1)  1      1 29.03 6.26e-07 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
R-sq.(adj) = 0.103
Scale est. = 50.178    n = 100
```

```
Model Performance:
R-squared: 0.1026
Deviance explained: %
```

```
=====
MODEL: B34_AR1
Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_
<U+0394>AIC: 1.615
AIC Weight: 0.0659
=====
```

```
Family: gaussian
Link function: identity
```

```
Formula:
```

```
butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 +
  s(temp_at_max_count_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)
```

Parametric coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.322212	1.285420	2.585	0.0113 *
butterflies_95th_percentile_t_1	-0.036858	0.007003	-5.264	9.26e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Approximate significance of smooth terms:

	edf	Ref.df	F	p-value
s(temp_at_max_count_t_1)	1.000	1.000	1.600	0.20906
s(wind_max_gust_t_1)	2.585	2.585	3.234	0.04986 *
s(sum_butterflies_direct_sun_t_1)	2.845	2.845	5.172	0.00734 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

R-sq.(adj) = 0.227

Scale est. = 42.79 n = 100

Model Performance:

R-squared: 0.2268

Deviance explained: %

Partial Effects for Supported Models

```
# Create effect plots for each supported model
for (i in 1:nrow(strong_support_models)) {
  model_name <- strong_support_models$Model[i]
  model_obj <- successful_models[[model_name]]
  formula_str <- strong_support_models$Formula[i]

  cat("\n")
  cat("PARTIAL EFFECTS FOR MODEL:", model_name, "\n")
  cat("Formula:", formula_str, "\n")
  cat("ΔAIC:", round(strong_support_models$Delta_AIC[i], 3), "\n\n")

  # Check if model has smooth terms
  has_smooth <- grepl("s\\(", formula_str)
```

```

if (has_smooth) {
  # For GAM with smooth terms
  tryCatch(
    {
      smooth_terms <- summary(model_obj$gam)$s.table

      if (nrow(smooth_terms) > 0) {
        plots <- list()

        # Plot each smooth term
        for (j in 1:nrow(smooth_terms)) {
          term_name <- rownames(smooth_terms)[j]
          p <- draw(model_obj$gam, select = term_name, rug = FALSE, residuals =
            custom_theme +
            theme(plot.caption = element_blank()) +
            labs(
              title = paste("Smooth effect:", term_name),
              subtitle = paste("Model:", model_name, "|  $\Delta$ AIC =", round(str
            )
          p <- add_zero_line(p)
          plots[[j]] <- p
        }

        # Combine plots
        if (length(plots) > 0) {
          if (length(plots) <= 2) {
            combined_plots <- wrap_plots(plots, nrow = 1)
          } else if (length(plots) <= 4) {
            combined_plots <- wrap_plots(plots, nrow = 2)
          } else {
            combined_plots <- wrap_plots(plots, nrow = 3)
          }
          print(combined_plots)
        }
      } else {
        cat("No smooth terms found in this model.\n")
      }
    },
    error = function(e) {
      cat("Error creating smooth term plots:", e$message, "\n")
    }
  )
}

```

```

}


# Always show coefficient table if available
tryCatch(
  {
    if (nrow(summary(model_obj$gam)$p.table) > 0) {
      cat("\nParametric coefficients:\n")
      coef_table <- summary(model_obj$gam)$p.table
      print(kable(coef_table, digits = 4, caption = paste("Parametric coefficients")))
    }
  },
  error = function(e) {
    cat("Error displaying coefficients:", e$message, "\n")
  }
)

cat("\n", paste(rep("=", 80), collapse = ""), "\n")
}

```

PARTIAL EFFECTS FOR MODEL: B33_AR1

Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(wind_max_gust_t_1) +
 <U+0394>AIC: 0



Parametric coefficients:



Table: Parametric coefficients for B33_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.4444	1.2635	2.7262	0.0077
butterflies_95th_percentile_t_1	-0.0377	0.0070	-5.4078	0.0000

=====

PARTIAL EFFECTS FOR MODEL: B29c_AR1

Formula: butterfly_diff_95th_sqrt ~ s(butterflies_95th_percentile_t_1) + s(wind_max_gust_t_1)
<U+0394>AIC: 0.27




Parametric coefficients:

Table: Parametric coefficients for B29c_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-1.078	1.0681	-1.0093	0.3154

PARTIAL EFFECTS FOR MODEL: B28_AR1
 Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(sum_butterflies_direct_sun_t_1)
 <U+0394>AIC: 0.7




Parametric coefficients:

Table: Parametric coefficients for B28_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.5608	1.3157	2.7063	0.0081
butterflies_95th_percentile_t_1	-0.0389	0.0071	-5.4491	0.0000

PARTIAL EFFECTS FOR MODEL: B35_AR1

Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)
<U+0394>AIC: 1.172



Parametric coefficients:


Table: Parametric coefficients for B35_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.7110	1.2479	2.9737	0.0038
butterflies_95th_percentile_t_1	-0.0395	0.0070	-5.6480	0.0000

=====

PARTIAL EFFECTS FOR MODEL: B37_AR1

Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_max_t_1) + s(temp_min_t_1) + s(wind_max_gust_t_1) + s(sum_butterflies_direct_sun_t_1)
<U+0394>AIC: 1.193



Parametric coefficients:


Table: Parametric coefficients for B37_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.4362	1.2409	2.7691	0.0068
butterflies_95th_percentile_t_1	-0.0372	0.0068	-5.4491	0.0000

PARTIAL EFFECTS FOR MODEL: B29_AR1

Formula: butterfly_diff_95th_sqrt ~ $s(\text{butterflies_95th_percentile_t_1})$

<U+0394>AIC: 1.284



Parametric coefficients:




Table: Parametric coefficients for B29_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-1.0431	0.9863	-1.0577	0.2928

PARTIAL EFFECTS FOR MODEL: B34_AR1

Formula: butterfly_diff_95th_sqrt ~ butterflies_95th_percentile_t_1 + s(temp_at_max_count_t_1)

<U+0394>AIC: 1.615



Parametric coefficients:

Table: Parametric coefficients for B34_AR1

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.3222	1.2854	2.5845	0.0113
butterflies_95th_percentile_t_1	-0.0369	0.0070	-5.2635	0.0000

```

# Export partial effects for all supported models (for results write-up)
for (i in 1:nrow(strong_support_models)) {
  model_name <- strong_support_models$Model[i]
  model_obj <- successful_models[[model_name]]
  formula_str <- strong_support_models$Formula[i]

  has_smooth <- grepl("s\\(", formula_str)

  if (has_smooth) {
    tryCatch({

```

```

smooth_terms <- summary(model_obj$gam)$s.table

if (nrow(smooth_terms) > 0) {
  plots <- list()

  for (j in 1:nrow(smooth_terms)) {
    term_name <- rownames(smooth_terms)[j]
    p <- draw(model_obj$gam, select = term_name, rug = FALSE, residuals = FALSE,
              custom_theme +
              theme(plot.caption = element_blank()) +
              labs(
                title = paste("Smooth effect:", term_name),
                subtitle = paste("Model:", model_name, "|  $\Delta$ AIC =", round(strong_
              )
    p <- add_zero_line(p)
    plots[[j]] <- p
  }

  if (length(plots) > 0) {
    if (length(plots) <= 2) {
      combined_plots <- wrap_plots(plots, nrow = 1)
    } else if (length(plots) <= 4) {
      combined_plots <- wrap_plots(plots, nrow = 2)
    } else {
      combined_plots <- wrap_plots(plots, nrow = 3)
    }

    # Export this model's plots
    ggsave(
      here("analysis", "reports", "figures",
           paste0("model_", model_name, "_partial_effects.png")),
      plot = combined_plots,
      width = 14, height = 8, dpi = 300
    )
  }
}

}, error = function(e) {
  cat("Could not export plots for model", model_name, "\n")
})
}

}
cat("Exported partial effects for all supported models to: analysis/reports/figures/\n")

```

Exported partial effects for all supported models to: analysis/reports/figures/