

Croatian Kuna


Henry Carver, Ricky Lin, Kyle Tau

APCS1 pd 2

2018-01-04

Final Project UML Diagram

Texas Hold 'Em



Class Woo
<ul style="list-style-type: none"> + Double pot + Double bet + ArrayList<Card> comHand + int comHandType + int pHandType <hr/> <ul style="list-style-type: none"> + Boolean broke?() + Main method runs entire game
<ul style="list-style-type: none"> + Void deal() + Void raise() + Void call() + Void fold() + Int findHandType() + Void win() + Void lose() + Void DisplayTable() + Void DisplayHand() + 10 different methods that check for if a hand has that special ranking (pairs, full house, etc.) + Void comCall() + Void comRaise() + Card retGet()
Class Player
<ul style="list-style-type: none"> + Constructor Initialize hand and balance, takes name <hr/> <ul style="list-style-type: none"> + Void addHand() + String name + Double balance + ArrayList<Card> hand + ArrayList<Card> all + ArrayList<Card> table
Class Cardkeys
<ul style="list-style-type: none"> + String stringifyV() + String stringifyS() + String stringify()

<ul style="list-style-type: none">+ Void makeDeck()+ Object get()
Class Deck
<ul style="list-style-type: none">+ Void resetDeck()+ ArrayList<Card> getDeck
Class Card
<ul style="list-style-type: none">+ Constructor Initializes suit and value <hr/> <ul style="list-style-type: none">+ String suit+ Int value+ compareTo()