


✔ APP SCORES



Security Score **47/100**
Trackers Detection **0/432**

📁 FILE INFORMATION

File Name CAPS_2_.apk
Size 56.58MB
MD5 c00cf03dbcdcf2b06e99280f34c90cf5
SHA1 3b4a5dea3b52cb151b0c0d2cb84af398c1e19408
SHA256 68b6d5bb446d7fa1bc1a22804e3393d11d32df974787fb51f7832d96b9b1ed2d

i APP INFORMATION

App Name CAPS
Package Name com.caps.mobile
Main Activity com.caps.mobile.MainActivity
Target SDK 36 Min SDK 24 Max SDK
Android Version Name 2.0.2 Android Version Code 4

0 / 3

EXPORTED ACTIVITIES

View All ⌵

2 / 4

EXPORTED RECEIVERS

View All ⌵

0 / 5

EXPORTED SERVICES

View All ⌵

1 / 6

EXPORTED PROVIDERS

View All ⌵

⚙️ SCAN OPTIONS

📄 DECOMPILED CODE

🔑 SIGNER CERTIFICATE

```
Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=US, ST=Unknown, L=Unknown, O=Unknown, OU=Android, CN=Android Debug
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2013-12-31 22:35:04+00:00
Valid To: 2052-04-30 22:35:04+00:00
Issuer: C=US, ST=Unknown, L=Unknown, O=Unknown, OU=Android, CN=Android Debug
Serial Number: 0x232eae62
Hash Algorithm: sha1
md5: 20f46148b72d8e5e5ca23d37a4f41490
sha1: 5e8f16062ea3cd2c4a0d547876baa6f38cabf625
sha256: fac61745dc0903786fb9ede62a962b399f7348f0bb6f899b8332667591033b9c
sha512: 926c0550edaee7aed1211b91fde06be4cc4748e61d8f1afbe0bd12f3949a0d09a1cf4306c72e6662ae4c7b8ae7a573a81d7e52e5b6124444eaf8f413e6b1fa69
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: b759a55bdc298b16f7a102f3107f3db38110f3dc7da00b1e981e9b257a9cf1af
Found 1 unique certificates
```

≡ APPLICATION PERMISSIONS

Search:

PERMISSION	STATUS	INFO	DESCRIPTION	CODE MAPPINGS
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.	
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.	
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.	

PERMISSION	STATUS	INFO	DESCRIPTION	CODE MAPPINGS
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications	
android.permission.READ_APP_BADGE	normal	show app notification	Allows an application to show app icon badges.	
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.	
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.	
android.permission.SYSTEM_ALERT_WINDOW	dangerous	display system-level alerts	Allows an application to show system-alert windows. Malicious applications can take over the entire screen of the phone.	
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.	
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.	

Showing 1 to 10 of 31 entries

[Previous](#)
[1](#)
[2](#)
[3](#)
[4](#)
[Next](#)

Search:

API	FILES
Android Notifications	
Base64 Decode	
Base64 Encode	
Content Provider	
Crypto	
Get Installed Applications	
Get Network Interface information	
Get System Service	
Get WiFi Details	
HTTP Connection	

Showing 1 to 10 of 27 entries

[Previous](#)

1

[2](#)[3](#)[Next](#)

BROWSABLE ACTIVITIES

Search:

ACTIVITY	INTENT
com.caps.mobile.MainActivity	Schemes: caps://,

Showing 1 to 1 of 1 entries

[Previous](#)[1](#)[Next](#)

🔒 NETWORK SECURITY

HIGH
1**WARNING**
0**INFO**
0**SECURE**
0

Search:

NO	SCOPE	SEVERITY	DESCRIPTION
1	100.91.44.24 localhost	high	Domain config is insecurely configured to permit clear text traffic to these domains in scope.

Showing 1 to 1 of 1 entries

[Previous](#)[1](#)[Next](#)

📜 CERTIFICATE ANALYSIS

HIGH
2**WARNING**
0**INFO**
1

Search:

TITLE	SEVERITY	DESCRIPTION
Application signed with debug certificate	high	Application signed with a debug certificate. Production application must not be shipped with a debug certificate.
Certificate algorithm vulnerable to hash collision	high	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues.

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

Showing 1 to 3 of 3 entries

[Previous](#) [1](#) [Next](#)

MANIFEST ANALYSIS

HIGH
1**WARNING**
4**INFO**
0**SUPPRESSED**
0Search:

NO	ISSUE	SEVERITY	DESCRIPTION	OPTIONS
1	App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.	
2	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.	

NO 	ISSUE 	SEVERITY 	DESCRIPTION 	OPTIONS 
3	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.	
4	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.	
5	Content Provider (expo.modules.clipboard.ClipboardFileProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.	

NO 	ISSUE 	SEVERITY 	DESCRIPTION 	OPTIONS 
6	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.	

Showing 1 to 6 of 6 entries

[Previous](#)[1](#)[Next](#)**</> CODE ANALYSIS****HIGH**
1**WARNING**
5**INFO**
3**SECURE**
1**SUPPRESSED**
0

Search:

NO	ISSUE	SEVERITY	STANDARDS	FILES	OPTIONS
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3		
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14		
3	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	coil3/decode/SourceImageSource.java com/reactnativelcommunity/webview/RNCWebViewModuleImpl.java	
4	This app listens to Clipboard changes. Some malware also listen to Clipboard changes.	info	OWASP MASVS: MSTG-PLATFORM-4	expo/modules/clipboard/ClipboardModule.java	
5	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	expo/modules/clipboard/ClipboardModule.java	

NO	ISSUE	SEVERITY	STANDARDS	FILES	OPTIONS
6	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/reactnativemodule/webview/RNCWebViewModuleImpl.java expo/modules/clipboard/ClipboardFileProvider.java	
7	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4		
8	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/reactnativemodule/asyncstorage/AsyncLocalStorageUtil.java com/reactnativemodule/asyncstorage/ReactDatabaseSupplier.java	
9	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	expo/modules/device/DeviceModule.java	
10	Remote WebView debugging is enabled.	high	CWE: CWE-919: Weaknesses in Mobile Applications OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-RESILIENCE-2	com/reactnativemodule/webview/RNCWebViewManagerImpl.java	

Showing 1 to 10 of 10 entries

🚩 SHARED LIBRARY BINARY ANALYSIS

Search:

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libfbjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libnative-imagetranscoder.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libhermestooling.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libworklets.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libnative-filters.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libimagepipeline.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libavif_android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libanimation-decoder-gif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
				unless Dart FFI is used.					
10	arm64-v8a/libexpo-modules-core.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

Showing 1 to 10 of 92 entries

NIAP ANALYSIS v1.3

Search:

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
No data available in table				

Showing 0 to 0 of 0 entries

[Previous](#)[Next](#)

FILE ANALYSIS

Search:

NO	ISSUE	FILES
No data available in table		

Showing 0 to 0 of 0 entries

[Previous](#)[Next](#)

FIREBASE DATABASE ANALYSIS

Search:

TITLE 	SEVERITY 	DESCRIPTION 
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/114127676015/namespaces/firebase:fetch?key=AlzaSyCyqdqP3mFQm6wfSp92mpLB115i4kDwpWA . This is indicated by the response: {'state': 'NO_TEMPLATE'}

Showing 1 to 1 of 1 entries

[Previous](#)

1

[Next](#)

MALWARE LOOKUP

[VirusTotal Report](#)[Triage Report](#)[MetaDefender Report](#)[Hybrid Analysis Report](#)

APKiD ANALYSIS

Search:

DEX	DETECTIONS						
classes.dex	Search: <table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table> Showing 1 to 2 of 2 entries Previous1Next	FINDINGS	DETAILS	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check	Compiler	r8
FINDINGS	DETAILS						
Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check possible Build.SERIAL check						
Compiler	r8						
classes2.dex	Search: <table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check SIM operator check network operator name check</td></tr><tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr></table> Showing 1 to 2 of 2 entries Previous1Next	FINDINGS	DETAILS	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check SIM operator check network operator name check	Compiler	r8 without marker (suspicious)
FINDINGS	DETAILS						
Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check SIM operator check network operator name check						
Compiler	r8 without marker (suspicious)						

DEX	DETECTIONS						
classes3.dex	Search: <table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr></table> Showing 1 to 2 of 2 entries Previous1Next	FINDINGS	DETAILS	Anti-VM Code	Build.MANUFACTURER check	Compiler	r8 without marker (suspicious)
FINDINGS	DETAILS						
Anti-VM Code	Build.MANUFACTURER check						
Compiler	r8 without marker (suspicious)						

Showing 1 to 3 of 3 entries

Previous1Next

BEHAVIOUR ANALYSIS

Search:

RULE ID	BEHAVIOUR	LABEL	FILES
00001	Initialize bitmap object and compress data (e.g. JPEG) into bitmap object	camera	expo/modules/clipboard/ClipboardImageKt.java
00009	Put data in cursor to JSON object	file	com/reactnativecommunity/asyncstorage/AsyncLocalStorageUtil.java
00011	Query data from URI (SMS, CALLLOGS)	sms callog collection	me/leolin/shortcutbadger/impl/SamsungHomeBadger.java
00013	Read file and put it into a stream	file	

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	
00023	Start another application from current application	reflection control	expo/modules/intentlauncher/IntentLauncherModule.java
00024	Write file after Base64 decoding	reflection file	expo/modules/filesystem/legacy/FileSystemLegacyModule.java
00028	Read file from assets directory	file	com/caverock/androidsvg/SimpleAssetResolver.java
00030	Connect to the remote server through the given URL	network	com/bumptech/glide/load/data/HttpUrlFetcher.java
00036	Get resource file from res/raw directory	reflection	

Showing 1 to 10 of 27 entries

ABUSED PERMISSIONS

Top Malware Permissions

android.permission.ACCESS_NETWORK_STATE,
 android.permission.INTERNET,
 android.permission.READ_EXTERNAL_STORAGE,
 android.permission.SYSTEM_ALERT_WINDOW,
 android.permission.VIBRATE,
 android.permission.WRITE_EXTERNAL_STORAGE,
 android.permission.ACCESS_WIFI_STATE,
 android.permission.RECEIVE_BOOT_COMPLETED,
 android.permission.WAKE_LOCK

9/25 Other Common Permissions

com.google.android.c2dm.permission.RECEIVE,
 com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE

2/44

Malware Permissions are the top permissions that are widely abused by known malware.

Other Common Permissions are permissions that are commonly abused by known malware.

 SERVER LOCATIONS



This app may communicate with the following OFAC sanctioned list of countries.

Search:

DOMAIN	COUNTRY/REGION
No data available in table	

Showing 0 to 0 of 0 entries

 DOMAIN MALWARE CHECKSearch:

DOMAIN	STATUS	GEOLOCATION
docs.expo.dev	ok	IP: 104.18.5.104 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
docs.swmansion.com	ok	IP: 172.67.70.192 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
expo.dev	ok	IP: 104.18.4.104 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
filesystem.local	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 20.205.243.166 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
reactnative.dev	ok	IP: 52.74.6.109 Country: Singapore Region: Singapore City: Singapore Latitude: 1.289670 Longitude: 103.850067 View: Google Map
www.w3.org	ok	IP: 104.18.22.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
xml.org	ok	IP: 104.21.66.164 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
xmlpull.org	ok	IP: 185.199.109.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map

Showing 1 to 9 of 9 entries

[Previous](#)

1

[Next](#)

URLs

Search:

URL	FILE
data:image	com/bumptech/glide/load/model/DataUriLoader.java
data:image/png;base64,	expo/modules/intentlauncher/IntentLauncherModule.java
file:///	expo/modules/filesystem/FileSystemPathKt.java
file:///	expo/modules/filesystem/legacy/FileSystemLegacyModuleKt.java
file:///android_asset/	com/bumptech/glide/load/model/AssetUriLoader.java
file:///android_asset/ http://filesystem.local	expo/modules/fetch/OkHttpFileUrlInterceptorKt.java
file:///android_asset/ http://filesystem.local	expo/modules/fetch/OkHttpFileUrlInterceptor.java

URL	FILE
file:///android_res/	expo/modules/asset/ResourceAssetKt.java
http://xml.org/sax/features/external-general-entities http://xmlpull.org/v1/doc/features.html#process-namespaces http://www.w3.org/2000/svg http://xmlpull.org/v1/doc/features.html#process-docdecl http://xml.org/sax/features/external-parameter-entities http://www.w3.org/TR/SVG11/feature# http://xml.org/sax/properties/lexical-handler http://www.w3.org/1999/xlink	com/caverock/androidsvg/SVGParser.java
https://docs.expo.dev/push-notifications/fcm-credentials/	expo/modules/notifications/tokens/PushTokenModule.java

Showing 1 to 10 of 23 entries

✉ EMAILS

🏠 TRACKERS

Search:

TRACKER NAME	CATEGORIES	URL
No data available in table		

Showing 0 to 0 of 0 entries

POSSIBLE HARDCODED SECRETS

▼ Showing all 6 secrets

"google_crash_reporting_api_key" : "AlzaSyCyqdqP3mFQm6wfSp92mpLB115i4kDwpWA"

"google_api_key" : "AlzaSyCyqdqP3mFQm6wfSp92mpLB115i4kDwpWA"

01360240043788015936020505

16a09e667f3bcc908b2fb1366ea957d3e3adec17512775099da2f590b0667322a

258EAF5-E914-47DA-95CA-C5AB0DC85B11

23456789abcdefghijklmnopqrstuvwxyz

A STRINGS

From APK Resource

► Show all **12456** strings

From Code

► Show all **43469** strings

From Shared Objects

apktool_out/lib/arm64-v8a/libfbjni.so

► Show all **156** strings

apktool_out/lib/arm64-v8a/libnative-imagetranscoder.so

► Show all **495** strings

apktool_out/lib/arm64-v8a/libhermestooling.so

► Show all **124** strings

apktool_out/lib/arm64-v8a/libworklets.so

► Show all **498** strings

apktool_out/lib/arm64-v8a/libnative-filters.so

► Show all **45** strings

apktool_out/lib/arm64-v8a/libimagepipeline.so

► Show all **25** strings

apktool_out/lib/arm64-v8a/libavif_android.so

► Show all **512** strings

apktool_out/lib/arm64-v8a/libanimation-decoder-gif.so

► Show all **331** strings

apktool_out/lib/arm64-v8a/libc++_shared.so

► Show all **695** strings

apktool_out/lib/arm64-v8a/libexpo-modules-core.so

► Show all **701** strings

apktool_out/lib/arm64-v8a/libstatic-webp.so

► Show all **406** strings

apktool_out/lib/arm64-v8a/libgifimage.so

► Show all **402** strings

apktool_out/lib/arm64-v8a/libappmodules.so

► Show all **720** strings

apktool_out/lib/arm64-v8a/libreactnative.so

► Show all **4472** strings

apktool_out/lib/arm64-v8a/libreactnative.so

► Show all **893** strings

apktool_out/lib/arm64-v8a/libhermes.so

► Show all **2215** strings

apktool_out/lib/arm64-v8a/libreact_codegen_safeareacontext.so

► Show all **89** strings

apktool_out/lib/arm64-v8a/libreact_codegen_rnscreens.so

► Show all **580** strings

apktool_out/lib/arm64-v8a/libgesturehandler.so

► Show all **46** strings

apktool_out/lib/arm64-v8a/librnworklets.so

► Show all **300** strings

apktool_out/lib/arm64-v8a/libjsi.so

► Show all **441** strings

apktool_out/lib/arm64-v8a/libreact_codegen_rnsvg.so

► Show all **320** strings

apktool_out/lib/arm64-v8a/librnscreens.so

► Show all **104** strings

apktool_out/lib/armeabi-v7a/libfbjni.so

► Show all **136** strings

apktool_out/lib/armeabi-v7a/libnative-imagetranscoder.so

► Show all **477** strings

apktool_out/lib/armeabi-v7a/libhermestooling.so

► Show all **86** strings

apktool_out/lib/armeabi-v7a/libworklets.so

► Show all **460** strings

apktool_out/lib/armeabi-v7a/libnative-filters.so

► Show all **45** strings

apktool_out/lib/armeabi-v7a/libimagepipeline.so

► Show all **25** strings

apktool_out/lib/armeabi-v7a/libavif_android.so

► Show all **458** strings

apktool_out/lib/armeabi-v7a/libanimation-decoder-gif.so

► Show all **322** strings

apktool_out/lib/armeabi-v7a/libc++_shared.so

► Show all **686** strings

apktool_out/lib/armeabi-v7a/libexpo-modules-core.so

► Show all **665** strings

apktool_out/lib/armeabi-v7a/libstatic-webp.so

► Show all **396** strings

apktool_out/lib/armeabi-v7a/libgifimage.so

► Show all **393** strings

apktool_out/lib/armeabi-v7a/libappmodules.so

► Show all **695** strings

apktool_out/lib/armeabi-v7a/libreactnative.so

► Show all **4630** strings

apktool_out/lib/armeabi-v7a/libreactnative.so

► Show all **861** strings

apktool_out/lib/armeabi-v7a/libhermes.so

► Show all **2177** strings

apktool_out/lib/armeabi-v7a/libreact_codegen_safeareacontext.so

► Show all **54** strings

apktool_out/lib/armeabi-v7a/libreact_codegen_rnscreens.so

► Show all **561** strings

apktool_out/lib/armeabi-v7a/libgesturehandler.so

► Show all **8** strings

apktool_out/lib/armeabi-v7a/librnworklets.so

► Show all **262** strings

apktool_out/lib/armeabi-v7a/libjsi.so

► Show all **404** strings

apktool_out/lib/armeabi-v7a/libreact_codegen_rnsvg.so

► Show all **288** strings

apktool_out/lib/armeabi-v7a/librnscreens.so

► Show all **66** strings

lib/arm64-v8a/libfbjni.so

► Show all **156** strings

lib/arm64-v8a/libnative-imagetranscoder.so

► Show all **495** strings

lib/arm64-v8a/libhermestooling.so

► Show all **124** strings

lib/arm64-v8a/libworklets.so

► Show all **498** strings

lib/arm64-v8a/libnative-filters.so

► Show all **45** strings

lib/arm64-v8a/libimagepipeline.so

► Show all **25** strings

lib/arm64-v8a/libavif_android.so

► Show all **512** strings

lib/arm64-v8a/libanimation-decoder-gif.so

► Show all **331** strings

lib/arm64-v8a/libc++_shared.so

► Show all **695** strings

lib/arm64-v8a/libexpo-modules-core.so

► Show all **701** strings

lib/arm64-v8a/libstatic-webp.so

► Show all **406** strings

lib/arm64-v8a/libgifimage.so

► Show all **402** strings

lib/arm64-v8a/libappmodules.so

► Show all **720** strings

lib/arm64-v8a/libreactnative.so

► Show all **4472** strings

lib/arm64-v8a/libreactnative.so

► Show all **893** strings

lib/arm64-v8a/libhermes.so

► Show all **2215** strings

lib/arm64-v8a/libreact_codegen_safeareacontext.so

► Show all **89** strings

lib/arm64-v8a/libreact_codegen_rnscreens.so

► Show all **580** strings

lib/arm64-v8a/libgesturehandler.so

► Show all **46** strings

lib/arm64-v8a/librnworklets.so

► Show all **300** strings

lib/arm64-v8a/libjsi.so

► Show all **441** strings

lib/arm64-v8a/libreact_codegen_rnsvg.so

► Show all **320** strings

lib/arm64-v8a/librnscreens.so

► Show all **104** strings

lib/armeabi-v7a/libfbjni.so

► Show all **136** strings

lib/armeabi-v7a/libnative-imagetranscoder.so

► Show all **477** strings

lib/armeabi-v7a/libhermestooling.so

► Show all **86** strings

lib/armeabi-v7a/libworklets.so

► Show all **460** strings

lib/armeabi-v7a/libnative-filters.so

► Show all **45** strings

lib/armeabi-v7a/libimagepipeline.so

► Show all **25** strings

lib/armeabi-v7a/libavif_android.so

► Show all **458** strings

lib/armeabi-v7a/libanimation-decoder-gif.so

► Show all **322** strings

lib/armeabi-v7a/libc++_shared.so

► Show all **686** strings

lib/armeabi-v7a/libexpo-modules-core.so

► Show all **665** strings

lib/armeabi-v7a/libstatic-webp.so

► Show all **396** strings

lib/armeabi-v7a/libgifimage.so

► Show all **393** strings

lib/armeabi-v7a/libappmodules.so

► Show all **695** strings

lib/armeabi-v7a/libreactnative.so

► Show all **4630** strings

lib/armeabi-v7a/libreactnative.so

► Show all **861** strings

lib/armeabi-v7a/libhermes.so

► Show all **2177** strings

lib/armeabi-v7a/libreact_codegen_safeareacontext.so

► Show all **54** strings

lib/armeabi-v7a/libreact_codegen_rnscreens.so

► Show all **561** strings

lib/armeabi-v7a/libgesturehandler.so

► Show all **8** strings

lib/armeabi-v7a/librnworklets.so

► Show all **262** strings

lib/armeabi-v7a/libjsi.so

► Show all **404** strings

lib/armeabi-v7a/libreact_codegen_rnsvg.so

► Show all **288** strings

lib/armeabi-v7a/librnscreens.so

► Show all **66** strings

ACTIVITIES

▼ Showing all **3** activities

[com.caps.mobile.MainActivity](#)

[expo.modules.notifications.service.NotificationForwarderActivity](#)

[com.google.android.gms.common.api.GoogleApiActivity](#)

SERVICES

▼ Showing all **5** services

[expo.modules.notifications.service.ExpoFirebaseMessagingService](#)

[com.google.firebase.messaging.FirebaseMessagingService](#)

[com.google.firebase.components.ComponentDiscoveryService](#)

[com.google.android.datatransport.runtime.backends.TransportBackendDiscovery](#)

[com.google.android.datatransport.runtime.scheduling.jobscheduling.JobInfoSchedulerService](#)

 RECEIVERS

▼ Showing all **4** receivers

[expo.modules.notifications.service.NotificationsService](#)

[com.google.firebase.iid.FirebaseInstanceIdReceiver](#)

[androidx.profileinstaller.ProfileInstallReceiver](#)

[com.google.android.datatransport.runtime.scheduling.jobscheduling.AlarmManagerSchedulerBroadcastReceiver](#)

 PROVIDERS

▼ Showing all **6** providers

[com.reactnativecommunity.webview.RNCWebViewFileProvider](#)

[expo.modules.clipboard.ClipboardFileProvider](#)

[expo.modules.filesystem.FileSystemFileProvider](#)

[expo.modules.sharing.SharingFileProvider](#)

[com.google.firebase.provider.FirebaseInitProvider](#)

[androidx.startup.InitializationProvider](#)

 LIBRARIES **SBOM**

▼ Showing all **63** Versioned Packages

androidx.activity:activity-ktx@1.8.0

androidx.activity:activity@1.8.0

androidx.annotation:annotation-experimental@1.4.1

androidx.appcompat:appcompat-resources@1.7.1

androidx.appcompat:appcompat@1.7.1

androidx.arch.core:core-runtime@dynamic

androidx.asynclayoutinflater:asynclayoutinflater@1.0.0

androidx.autofill:autofill@1.1.0

androidx.biometric:biometric@1.2.0-alpha04
androidx.browser:browser@1.6.0
androidx.cardview:cardview@1.0.0
androidx.coordinatorlayout:coordinatorlayout@1.2.0
androidx.core:core-ktx@1.17.0
androidx.core:core-splashscreen@1.2.0-alpha02
androidx.core:core-viewtree@1.0.0
androidx.core:core@1.17.0
androidx.cursoradapter:cursoradapter@1.0.0
androidx.customview:customview@1.1.0
androidx.documentfile:documentfile@1.1.0
androidx.drawerlayout:drawerlayout@1.1.1
androidx.dynamicanimation:dynamicanimation@1.0.0
androidx.emoji2:emoji2-views-helper@1.3.0
androidx.emoji2:emoji2@1.3.0
androidx.exifinterface:exifinterface@1.3.7
androidx.fragment:fragment-ktx@1.6.1
androidx.fragment:fragment@1.6.1
androidx.interpolator:interpolator@1.0.0
androidx.legacy:legacy-support-core-ui@1.0.0
androidx.legacy:legacy-support-core-utils@1.0.0
androidx.legacy:legacy-support-v4@1.0.0
androidx.lifecycle:lifecycle-livedata-core-ktx@2.8.7
androidx.lifecycle:lifecycle-livedata-core@2.8.7
androidx.lifecycle:lifecycle-livedata@2.8.7
androidx.lifecycle:lifecycle-process@2.8.7
androidx.lifecycle:lifecycle-runtime-ktx@2.8.7
androidx.lifecycle:lifecycle-runtime@2.8.7
androidx.lifecycle:lifecycle-viewmodel-ktx@2.8.7
androidx.lifecycle:lifecycle-viewmodel-savedstate@2.8.7
androidx.lifecycle:lifecycle-viewmodel@2.8.7
androidx.loader:loader@1.0.0
androidx.localbroadcastmanager:localbroadcastmanager@1.0.0
androidx.media:media@1.0.0
androidx.print:print@1.0.0
androidx.profileinstaller:profileinstaller@1.4.1
androidx.recyclerview:recyclerview@1.1.0
androidx.savedstate:savedstate-ktx@1.2.1

androidx.savedstate:savedstate@1.2.1
androidx.slidingpanelayout:slidingpanelayout@1.0.0
androidx.startup:startup-runtime@1.1.1
androidx.swiperefreshlayout:swiperefreshlayout@1.1.0
androidx.tracing:tracing-ktx@1.2.0
androidx.tracing:tracing@1.2.0
androidx.transition:transition@1.5.0
androidx.vectordrawable:vectordrawable-animated@1.1.0
androidx.vectordrawable:vectordrawable@1.1.0
androidx.versionedparcelable:versionedparcelable@1.1.1
androidx.viewpager2:viewpager2@1.0.0
androidx.viewpager:viewpager@1.0.0
androidx.webkit:webkit@1.14.0
com.google.android.material:material@1.12.0
org.jetbrains.kotlin:kotlinx-coroutines-android@1.9.0
org.jetbrains.kotlin:kotlinx-coroutines-core@1.9.0
org.jetbrains.kotlin:kotlinx-coroutines-play-services@1.9.0

▼ Showing all **33** Packages

a.a
android.print
bolts
coil3
com.bumptech.glide
com.caps.mobile
com.caverock.androidsvg
com.github.penfeizhou.animation
com.horcrux.svg
com.reactnativecommunity.asyncstorage
com.reactnativecommunity.netinfo
com.reactnativecommunity.webview
com.swmansion.common
com.swmansion.gesturehandler
com.swmansion.reanimated
com.swmansion.rnscreens
com.swmansion.worklets
com.th3rdwave.safeareacontext
com.worklets
expo.core

expo.modules
javax.annotation
javax.inject
jp.wasabeef.glide.transformations
me.leolin.shortcutbadger
okio
org.aomedia.avif.android
org.checkerframework.checker.nullness.compatqual
org.codehaus.mojo.animal_sniffer
org.intellij.lang.annotations
org.jetbrains.annotations
org.jspecify.annotations
third_party.libavif

FILES

► Show all **1360** files