Kode Setup Guide

Repository: Kode CLI
License: Apache 2.0

1. Installation

Basic Installation

```
npm install -g @shareai-lab/kode
```

Node.js Version Issues

If you encounter NVM version issues during installation:

```
# Install/update NVM
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.40.3/install.sh |
bash
source "$HOME/.nvm/nvm.sh"

# Check available Node.js versions
nvm ls-remote

# Install recommended Node.js version
nvm install 22.19.0

# Verify installation
node -v  # Should print "v22.19.0"
npm -v   # Should print "10.9.3"
```

2. Proxy Setup

To connect to the Intel internal network, you need to configure proxy environment variables. It's recommended to add these to your `~/.bashrc` file:

```
export http_proxy="http://proxy-prc.intel.com:913/"
export https_proxy="http://proxy-prc.intel.com:913/"
export no_proxy="localhost,127.0.0.1,gateway.aichina.intel.com"
```

3. Configuration

Navigate to your project directory (e.g., `wasm-micro-runtime`) and run:

```
git clone https://github.com/pugong2019/wasm-micro-runtime/
cd wasm-micro-runtime
git checkout llm/wamr_enhanced_cases_collections
kode
```

Press the Enter key until the following content appears:

```
Provider Selection

Select your preferred AI provider for this model profile:

Choose the provider you want to use for this model profile.
This will determine which models are available to you.

  ❯Kimi (Moonshot)  (1 models)
  Claude  (3 models)
  BurnCloud (All models)  (0 models)
  DeepSeek  (3 models)
  Qwen (Alibaba)  (0 models)


You can change this later by running /model again
```

Initial Kode Setup Screen

pleas

Select OpenRouter Option

Navigate down to select the OpenRouter option:

```
Provider Selection

Select your preferred AI provider for this model profile:

Choose the provider you want to use for this model profile.
This will determine which models are available to you.

  Ollama  (0 models)
  Gemini  (3 models)
  Custom OpenAI-Compatible API  (0 models)
  ❯OpenRouter  (0 models)
  MiniMax  (3 models)


You can change this later by running /model again
```

Select OpenRouter from the available options

Configure Gateway URL

Replace the default URL with the Intel China-IT LLM service gateway:

```
OpenRouter API Configuration

Configure the API endpoint for OpenRouter:

This is the base URL for the OpenRouter API.
You can modify this URL or press Enter to use the default.

https://openrouter.ai/api/v1


[Submit Base URL] - Press Enter or click to continue


Press Enter to continue or Esc to go back
```

URL Configuration Screen

Gateway URL: `http://gateway.aichina.intel.com`

> **Note:** This is the China-IT LLM service gateway. If you need to switch to other LLM services later, simply replace this URL.

```
OpenRouter API Configuration

Configure the API endpoint for OpenRouter:

This is the base URL for the OpenRouter API.
You can modify this URL or press Enter to use the default.

http://gateway.aichina.intel.com


[Submit Base URL] - Press Enter or click to continue


Press Enter to continue or Esc to go back
```

Enter the gateway URL in the input field

Enter API Key

Input your API key when prompted:

```
API Key Setup

Enter your OpenRouter  API key for this model profile:

This key will be stored locally and used to access the openrouter API.
Your key is never sent to our servers.



******************TbGuwQ


[Submit API Key] - Press Enter or click to continue with this API key
```

Enter your API key securely

Select LLM Model

The system will display available models on the LiteLLM service:

```
Model Selection

Select a model from OpenRouter  for this model profile:

This model profile can be assigned to different pointers (main, task,
reasoning, quick) for various use cases.


Search models:Type to filter models...


  ❯claude-sonnet-4-20250514-v1:0-stg
  DCAI_GAUDI2_DeepSeek-R1-671B
  FLEX_STG_DeepSeek-V3-0324-671B
  FLEX_STG_Qwen2.5-32B-Instruct-AWQ
  gpt-4o-stg

Showing 13 of 13 models
```

Available LLM models on the service

Recommended Model: `claude-sonnet-4-20250514-v1:0-stg`

Configure Token Limits

Set up the LLM input/output token limits. Claude Sonnet 4 supports:

- **Maximum context window:** 200k tokens
- **Maximum output length:** 64k tokens

```
Maximum Tokens
Select the maximum number of tokens to generate.

  8K tokens (recommended)✓
  16K tokens
  32K tokens
  ❯64K tokens
  128K tokens
```

Token Configuration - Step 1

```
Context Length Configuration

Choose the context window length for your model:

This determines how much conversation history and context the model
can process at once. Higher values allow for longer conversations but
may increase costs.


  32K tokens
  64K tokens
  128K tokens (recommended)
→ 200K tokens
  256K tokens
  300K tokens
  512K tokens
  1000K tokens
  2000K tokens
  3000K tokens
  5000K tokens
  10000K tokens
```

Token Configuration - Step 2

```
Configuration Confirmation

Confirm your model configuration:

Please review your selections before saving.


 Provider: OpenRouter
 Model: claude-sonnet-4-20250514-v1:0-stg
 API Key: ****GuwQ
 Max Tokens: 8192
 Context Length: 200K tokens
```

Token Configuration - Step 3

Verify Setup

Once configured, the system should be working:

```
✻ Welcome to Kode research preview!

  /help for help

  cwd: /home/pugong

Tips for getting started:

- Run /init to create a AGENTS.md file with instructions for Kode.
- Run /terminal-setup to set up terminal integration
- Ask Kode questions about your codebase.
- Ask Kode to implement changes to your codebase.

Note: You have launched anon-code in your home directory. For the best experience, launch it in a project directory instead.
                                                    [openrouter] claude-sonnet-4-20250514-v1:0-stg: 0k / 200k

>

! for bash mode · # for AGENTS.md · / for commands · shift+m to switch model · esc to undo        \⏎ for newline
```

Successfully configured Kode system

Test the setup by typing "Hi" to verify functionality.

```
Tips for getting started:

- Run /terminal-setup to set up terminal integration
- Ask Kode questions about your codebase.
- Ask Kode to implement changes to your codebase.

> hi

● Hello! I'm Kode, your WAMR Unit Test specialist. I can help you with analyzing, designing, and generating comprehensive unit
  tests for the WebAssembly Micro Runtime (WAMR) project.

  I can assist with:
  - Analyzing existing test cases and coverage
  - Designing test suites for WAMR features
  - Generating high-quality unit tests with GTest
  - Building and running tests with coverage reports
  - Working with core WAMR modules like interpreter, AOT runtime, memory management, and WASI libraries

  What would you like to work on today?
                                                    [openrouter] claude-sonnet-4-20250514-v1:0-stg: 21k / 200
```

Successfully configured Kode system

Troubleshooting

Common Issues

1. **NVM Installation Issues**: Ensure you restart your terminal after installing NVM or run `source ~/.bashrc`
2. **Proxy Connection Errors**: Verify the proxy settings are correctly added to your `~/.bashrc` and restart your terminal
3. **API Key Issues**: Double-check that your API key is valid and has proper permissions
4. **Model Selection Problems**: If the model list doesn't load, verify your gateway URL and network connectivity

Additional Tips

- Make sure your Node.js version is compatible (v22.19.0 recommended)
- Keep your API key secure and don't share it in version control

For more information, visit the Kode CLI repository.