

1. (a) See Code

$$\begin{aligned}
 (b) P(\{R_j = r_j^{(t)}\}_{j \in \Omega_t}) &= \sum_{i=1}^k P(z=i, \{R_j = r_j^{(t)}\}_{j \in \Omega_t}) \quad \text{「Marg.」} \\
 &= \sum_{i=1}^k P(z=i) P(\{R_j = r_j^{(t)}\}_{j \in \Omega_t} | z=i) \quad \text{「PR」} \\
 &= \sum_{i=1}^k P(z=i) \prod_{j \in \Omega_t} P(R_j = r_j^{(t)} | z=i) \quad \text{「CI」}
 \end{aligned}$$

$$\begin{aligned}
 (c) P(z=i | \{R_j = r_j^{(t)}\}_{j \in \Omega_t}) &= \frac{P(z=i, \{R_j = r_j^{(t)}\}_{j \in \Omega_t})}{\sum_{i'=1}^k P(z=i', \{R_j = r_j^{(t)}\}_{j \in \Omega_t})} \quad \text{「By Baye's Rule and} \\
 &\quad \text{denom. is Marg.} \\
 &\quad (= P(\{R_j = r_j^{(t)}\}_{j \in \Omega_t})) \\
 &= \frac{P(z=i) \prod_{j \in \Omega_t} P(R_j = r_j^{(t)} | z=i)}{\sum_{i'=1}^k P(z=i') \prod_{j \in \Omega_t} P(R_j = r_j^{(t)} | z=i')} \quad \text{「pt. (b) w/o } \bar{z} \text{」}
 \end{aligned}$$

$$\begin{aligned}
 (d) \text{Root: } P(z=i) &= \frac{1}{T} \sum_{t=1}^T P(z=i | V_t = v_t) \\
 &\quad \hookrightarrow \text{visible} \\
 &= \frac{1}{T} \sum_{t=1}^T P(z=i | \{R_j = r_j^{(t)}\}_{j \in \Omega_t}) \\
 &= \frac{1}{T} \sum_{t=1}^T p_{it}
 \end{aligned}$$

$$\text{Other: } P(R_j=1 | z=i) = \frac{\sum_{t=1}^T P(R_j=1, z=i | \{R_j = r_j^{(t)}\}_{j \in \Omega_t})}{\sum_{t=1}^T P(z=i | \{R_j = r_j^{(t)}\}_{j \in \Omega_t})}$$

$$= \frac{\sum_{t: 1 \in \Omega_t} I(R_j^{(t)}, 1) P(z=i | \{R_j = r_j^{(t)}\}_{j \in \Omega_t}) + \sum_{t: 1 \notin \Omega_t} P(z=i | \{R_j = r_j^{(t)}\}_{j \in \Omega_t}) \cdot P(R_j=1 | z=i, \{R_j = r_j^{(t)}\}_{j \in \Omega_t})}{\sum_{t=1}^T p_{it}}$$

$$= \frac{\sum_{t: 1 \in \Omega_t} I(R_j^{(t)}, 1) p_{it} + \sum_{t: 1 \notin \Omega_t} p_{it} P(R_j=1 | z=i)}{\sum_{t=1}^T p_{it}} \quad \text{「split + into } t, \text{ s.t. } j \in \Omega_t \text{ so we can use indicator \& } t, \text{ s.t. } j \notin \Omega_t \text{ where we use PR」} \\
 \text{「CI, since in this sum, } j \text{ is not in } \Omega_t \text{」}$$

(e) likelihood increases, the form is

(f) See code

The rec. seems fit for my taste for first few movies.

iter	$\mathcal{L}$
0	-27.0358
1	-17.5604
2	-16.0024
4	-15.0606
8	-14.5016
16	-14.2638
32	-14.1802
64	-14.1701

iter	$\mathcal{L}$
128	-14.1640
256	-14.1637

$$\begin{aligned}
 2.(a) P(y=1|\bar{x}) &= \frac{P(\bar{x}|y=1)P(y=1)}{\sum_j P(\bar{x}, y=j)} \quad \text{「BR \& Marg.」} \\
 &= \frac{P(\bar{x}|y=1)P(y=1)}{P(\bar{x}|y=0)P(y=0) + P(\bar{x}|y=1)P(y=1)} \\
 &= \frac{(2\pi)^{-d/2} |\Sigma_1|^{-1/2} \exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_1)^T \Sigma_1^{-1}(\bar{x}-\bar{\mu}_1)) \pi_1}{(2\pi)^{-d/2} |\Sigma_0|^{-1/2} \exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_0)^T \Sigma_0^{-1}(\bar{x}-\bar{\mu}_0)) \pi_0 + \text{num.}}
 \end{aligned}$$

(b) In denom. of part (a), 2 parts now share the term  $(2\pi)^{-d/2} |\Sigma|^{-1/2}$ , so this cancels out w/ the same part in num.,

so we have

$$P(y=1|\bar{x}) = \frac{\exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_1)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_1)) \pi_1}{\exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_0)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_0)) \pi_0 + \exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_1)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_1)) \pi_1}$$

$$\text{so } \frac{1}{P(y=1|\bar{x})} = 1 + \frac{\exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_0)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_0)) \pi_0}{\exp(-\frac{1}{2}(\bar{x}-\bar{\mu}_1)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_1)) \pi_1}$$

$$= 1 + \exp\left[-\frac{1}{2}((\bar{x}-\bar{\mu}_0)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_0) - (\bar{x}-\bar{\mu}_1)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_1))\right] \cdot \exp(\log \frac{\pi_0}{\pi_1}) \quad \left[\frac{\pi_0}{\pi_1} = e^{\log \frac{\pi_0}{\pi_1}}\right]$$

$$\text{let } -z = -\frac{1}{2}((\bar{x}-\bar{\mu}_0)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_0) - (\bar{x}-\bar{\mu}_1)^T \Sigma^{-1}(\bar{x}-\bar{\mu}_1)) + \log \frac{\pi_0}{\pi_1}$$

$$= -\frac{1}{2}((\bar{x}^T \Sigma^{-1} \bar{x} - \bar{x}^T \Sigma^{-1} \bar{\mu}_0 - \bar{\mu}_0^T \Sigma^{-1} \bar{x} + \bar{\mu}_0^T \Sigma^{-1} \bar{\mu}_0) - (\bar{x}^T \Sigma^{-1} \bar{x} - \bar{x}^T \Sigma^{-1} \bar{\mu}_1 - \bar{\mu}_1^T \Sigma^{-1} \bar{x} + \bar{\mu}_1^T \Sigma^{-1} \bar{\mu}_1)) + \log \frac{\pi_0}{\pi_1}$$

$$= -\frac{1}{2}(\underbrace{\bar{x}^T \Sigma^{-1} \bar{x}}_{\text{cancel}} - 2\bar{x}^T \Sigma^{-1} \bar{\mu}_0 + \bar{\mu}_0^T \Sigma^{-1} \bar{\mu}_0 - \underbrace{\bar{x}^T \Sigma^{-1} \bar{x}}_{\text{cancel}} + 2\bar{x}^T \Sigma^{-1} \bar{\mu}_1 - \bar{\mu}_1^T \Sigma^{-1} \bar{\mu}_1) + \log \frac{\pi_0}{\pi_1}$$

$$= -\frac{1}{2}(\bar{x}^T (2\Sigma^{-1} \bar{\mu}_1 - \bar{\mu}_0) + \bar{\mu}_0^T \Sigma^{-1} \bar{\mu}_0 - \bar{\mu}_1^T \Sigma^{-1} \bar{\mu}_1) + \log \frac{\pi_0}{\pi_1}$$

$$= \bar{x}^T \Sigma^{-1} (\bar{\mu}_0 - \bar{\mu}_1) - \frac{1}{2}(\bar{\mu}_0^T \Sigma^{-1} \bar{\mu}_0 - \bar{\mu}_1^T \Sigma^{-1} \bar{\mu}_1) + \log \frac{\pi_0}{\pi_1}$$

Since  $\Sigma^{-1}(\bar{\mu}_0 - \bar{\mu}_1)$  is col. vector

then  $\bar{x}^T \Sigma^{-1}(\bar{\mu}_0 - \bar{\mu}_1)$  is equivalent to  $\bar{x} \cdot (\Sigma^{-1}(\bar{\mu}_0 - \bar{\mu}_1))$

then writing  $z$  as  $\bar{w} \cdot \bar{x} + b$ , we have ( $-z$  before, flip sign)

$$\bar{w} = \Sigma^{-1}(\bar{\mu}_1 - \bar{\mu}_0), \quad b = -\log \frac{\pi_0}{\pi_1} + \frac{1}{2}(\bar{\mu}_0^T \Sigma^{-1} \bar{\mu}_0 - \bar{\mu}_1^T \Sigma^{-1} \bar{\mu}_1)$$

$$(c) \frac{P(y=1|\bar{x})}{P(y=0|\bar{x})} = \frac{P(y=1|\bar{x})}{1 - P(y=1|\bar{x})} = \frac{1/(1+e^{-z})}{1 - 1/(1+e^{-z})} = \frac{1/(1+e^{-z})}{e^{-z}/(1+e^{-z})} = \frac{1}{e^{-z}}$$

then if this fraction is constant, then  $\frac{1}{e^{-z}} = k$ , which means

$z$  must be constant, then  $\bar{w} \cdot \bar{x} + b = z = -\log \frac{1}{k}$ , which is indeed constant.

if  $k=1$ , then  $z = -\log 1 = 0 \Rightarrow \bar{w} \cdot \bar{x} + b = 0$ .

$$\begin{aligned}
 3. (a) \mathcal{L}(\bar{v}) &= \sum_{t=1}^T \log P(y_t | \bar{x}_t) \\
 &= \sum_{t=1}^T y_t \log P(y_t=1 | \bar{x}_t) + (1-y_t) \log P(y_t=0 | \bar{x}_t) \\
 &= \sum_{t=1}^T y_t \log(1 - e^{-\bar{v} \cdot \bar{x}_t}) + (1-y_t) \log e^{-\bar{v} \cdot \bar{x}_t} \\
 &= \sum_{t=1}^T y_t \log(1 - e^{-\bar{v} \cdot \bar{x}_t}) - (1-y_t)(\bar{v} \cdot \bar{x}_t)
 \end{aligned}$$

$$\begin{aligned}
 (b) \frac{\partial \mathcal{L}}{\partial \bar{v}} &= \sum_{t=1}^T y_t \frac{-(-\bar{x}_t e^{-\bar{v} \cdot \bar{x}_t})}{1 - e^{-\bar{v} \cdot \bar{x}_t}} - (1-y_t) \bar{x}_t \\
 &= \sum_{t=1}^T y_t \bar{x}_t \frac{e^{-\bar{v} \cdot \bar{x}_t}}{1 - e^{-\bar{v} \cdot \bar{x}_t}} - (1-y_t) \bar{x}_t \\
 &= \sum_{t=1}^T \left( \frac{y_t e^{-\bar{v} \cdot \bar{x}_t}}{1 - e^{-\bar{v} \cdot \bar{x}_t}} + y_t - 1 \right) \bar{x}_t \\
 &= \sum_{t=1}^T \left( \frac{y_t e^{-\bar{v} \cdot \bar{x}_t} + y_t - y_t e^{-\bar{v} \cdot \bar{x}_t} - 1 + e^{-\bar{v} \cdot \bar{x}_t}}{1 - e^{-\bar{v} \cdot \bar{x}_t}} \right) \bar{x}_t \\
 &= \sum_{t=1}^T \left( \frac{y_t - (1 - e^{-\bar{v} \cdot \bar{x}_t})}{1 - e^{-\bar{v} \cdot \bar{x}_t}} \right) \bar{x}_t = \sum_{t=1}^T \left( \frac{y_t - p_t}{p_t} \right) \bar{x}_t, \quad p_t = 1 - e^{-\bar{v} \cdot \bar{x}_t} \\
 &= P(y_t=1 | \bar{x}_t)
 \end{aligned}$$

$$\begin{aligned}
 (c) P(y=1 | \bar{x}) &= 1 - e^{-\bar{v} \cdot \bar{x}} \\
 &= 1 - e^{-\sum v_i x_i} \\
 &= 1 - e^{\sum \log(1-p_i) x_i} \\
 &= 1 - \prod e^{\log(1-p_i) x_i} \\
 &= 1 - \prod (1-p_i)^{x_i} \\
 P(y=0 | \bar{x}) &= 1 - P(y=1 | \bar{x}) \\
 &= \prod (1-p_i)^{x_i}
 \end{aligned}$$

So this is equivalent to noisy-OR

$$\begin{aligned}
 (d) \frac{\partial \mathcal{L}}{\partial p_i} &= \frac{\partial \mathcal{L}}{\partial v_i} \cdot \frac{\partial v_i}{\partial p_i} = \left( \frac{1}{1-p_i} \right) \frac{\partial \mathcal{L}}{\partial v_i} \\
 \text{Chain rule } v &= f(p), \mathcal{L} = g(v), \\
 \Rightarrow \mathcal{L}'(p) &= \mathcal{L}'(f(p)) v'(p) \\
 &= \mathcal{L}'(v) v'(p)
 \end{aligned}$$

$$\begin{aligned}
 (e) GA &= p_i + \eta \left( \frac{\partial \mathcal{L}}{\partial p_i} \right) = p_i + \frac{p_i(1-p_i)}{T_i} \left( \frac{1}{1-p_i} \right) \frac{\partial \mathcal{L}}{\partial v_i} \\
 &= p_i + \frac{p_i}{T_i} \sum_{t=1}^T \left( \frac{y_t - p_t}{p_t} x_{it} \right), \text{ since it is ith term of } \bar{x}_t \\
 &= p_i + \frac{p_i}{T_i} \sum_{t=1}^T \left( \frac{y_t x_{it}}{p_t} - x_{it} \right) = p_i + \frac{p_i}{T_i} \left( \sum_{t=1}^T \frac{y_t x_{it}}{p_t} - \sum_{t=1}^T x_{it} \right) = p_i + \frac{p_i}{T_i} \left( \sum_{t=1}^T \frac{y_t x_{it}}{p_t} - T_i \right)
 \end{aligned}$$

$$\begin{aligned}
4. (a) & P(y=1, y'=1 | \bar{x}, \bar{x}', s=1) \\
&= \frac{P(s=1 | y=1, y'=1, \bar{x}, \bar{x}') P(y=1, y'=1 | \bar{x}, \bar{x}')}{P(s=1 | \bar{x}, \bar{x}')} \quad \text{BR}_1 \\
&= \frac{P(y=1 | \bar{x}, \bar{x}') P(y'=1 | y=1, \bar{x}, \bar{x}')}{P(s=1 | \bar{x}, \bar{x}')} \quad \text{PR}_1 \\
&= \frac{P(y=1 | \bar{x}) P(y'=1 | \bar{x}')}{P(s=1 | \bar{x}, \bar{x}')} \quad \text{d.sep(3)}_1 \\
&= \frac{\sigma(\bar{w} \cdot \bar{x}) \sigma(\bar{w} \cdot \bar{x}')}{\sum_{y, y'} P(s=1, y, y' | \bar{x}, \bar{x}')} \\
&= \frac{\sigma(\bar{w} \cdot \bar{x}) \sigma(\bar{w} \cdot \bar{x}')}{\sum_{y, y'} P(s=1 | y, y', \bar{x}, \bar{x}') P(y | \bar{x}) P(y' | \bar{x}')} \rightarrow \text{same d.sep(3) as last step} \\
&= \frac{\sigma(\bar{w} \cdot \bar{x}) \sigma(\bar{w} \cdot \bar{x}')}{P(y=0 | \bar{x}) P(y'=0 | \bar{x}) + P(y=1 | \bar{x}) P(y'=1 | \bar{x})} \\
&= \frac{\sigma(\bar{w} \cdot \bar{x}) \sigma(\bar{w} \cdot \bar{x}')}{(1 - \sigma(\bar{w} \cdot \bar{x})) (1 - \sigma(\bar{w} \cdot \bar{x}')) + \sigma(\bar{w} \cdot \bar{x}) \sigma(\bar{w} \cdot \bar{x}')}
\end{aligned}$$

(b) Similarly,

$$\begin{aligned}
& P(y=1, y'=0 | \bar{x}, \bar{x}', s=0) \\
&= \frac{P(y=1 | \bar{x}) P(y'=0 | \bar{x}')}{\sum_{y, y'} P(s=0, y, y' | \bar{x}, \bar{x}')} \\
&\quad \hookrightarrow \text{need } y=0, y'=1 \text{ \& } y=1, y'=0 \\
&= \frac{\sigma(\bar{w} \cdot \bar{x}) (1 - \sigma(\bar{w} \cdot \bar{x}'))}{P(y=0 | \bar{x}) P(y'=1 | \bar{x}) + P(y=1 | \bar{x}) P(y'=0 | \bar{x})} \\
&= \frac{\sigma(\bar{w} \cdot \bar{x}) (1 - \sigma(\bar{w} \cdot \bar{x}'))}{(1 - \sigma(\bar{w} \cdot \bar{x})) \sigma(\bar{w} \cdot \bar{x}') + \sigma(\bar{w} \cdot \bar{x}) (1 - \sigma(\bar{w} \cdot \bar{x}'))}
\end{aligned}$$

(c) BBAC

$$s=1 \Rightarrow y=y' \quad \hookrightarrow \quad s=0 \Rightarrow y \neq y'$$

(d)  $Z(\bar{w}) = \sum_t \log P(s_t | \bar{x}_t, \bar{x}'_t)$

$$= \sum_t s_t \log P(s_t=1 | \bar{x}_t, \bar{x}'_t) + (1-s_t) \log P(s_t=0 | \bar{x}_t, \bar{x}'_t)$$

$$\begin{aligned}
&= \sum_t s_t \log [(1 - \sigma(\bar{w} \cdot \bar{x}_t)) (1 - \sigma(\bar{w} \cdot \bar{x}'_t)) + \sigma(\bar{w} \cdot \bar{x}_t) \sigma(\bar{w} \cdot \bar{x}'_t)] \\
&\quad + (1-s_t) \log [(1 - \sigma(\bar{w} \cdot \bar{x}_t)) \sigma(\bar{w} \cdot \bar{x}'_t) + \sigma(\bar{w} \cdot \bar{x}_t) (1 - \sigma(\bar{w} \cdot \bar{x}'_t))]
\end{aligned}$$

from denom. in (a), (b)



$$\begin{aligned}
 (e) \frac{\partial \mathcal{L}}{\partial \bar{w}} &= \frac{1}{t} \left[ \bar{y}_t \frac{\sigma(\bar{w} \cdot \bar{x}_t)}{\sigma(\bar{w} \cdot \bar{x}_t)} \sigma(-\bar{w} \cdot \bar{x}_t) \bar{x}_t + (1 - \bar{y}_t) \frac{\sigma(-\bar{w} \cdot \bar{x}_t)}{\sigma(-\bar{w} \cdot \bar{x}_t)} \sigma(\bar{w} \cdot \bar{x}_t) \bar{x}_t \right. \\
 &\quad \left. + \bar{y}_t' \frac{\sigma(\bar{w} \cdot \bar{x}_t')}{\sigma(\bar{w} \cdot \bar{x}_t')} \sigma(-\bar{w} \cdot \bar{x}_t') \bar{x}_t' + (1 - \bar{y}_t') \frac{\sigma(-\bar{w} \cdot \bar{x}_t')}{\sigma(-\bar{w} \cdot \bar{x}_t')} \sigma(\bar{w} \cdot \bar{x}_t') \bar{x}_t' \right] \\
 &= \frac{1}{t} \left[ (\bar{y}_t - \sigma(\bar{w} \cdot \bar{x}_t)) \bar{x}_t + (\bar{y}_t' - \sigma(\bar{w} \cdot \bar{x}_t')) \bar{x}_t' \right]
 \end{aligned}$$

and the expression in  $[\ ]$  goes into the bracket.

$$5. (a) \alpha_{it} = P(Y_t = i | Y_0, \bar{x}_1, \dots, \bar{x}_t)$$

$$\begin{aligned}
 &= \sum_{j \in \{0,1\}} P(Y_t = i, Y_{t+1} = j | Y_0, \bar{x}_1, \dots, \bar{x}_t) \\
 &= \sum_j P(Y_{t+1} = j | Y_0, \bar{x}_1, \dots, \bar{x}_t) P(Y_t = i | Y_0, \bar{x}_1, \dots, \bar{x}_t, Y_{t+1} = j) \\
 &= \sum_j \underbrace{P(Y_{t+1} = j | Y_0, \bar{x}_1, \dots, \bar{x}_{t+1})}_{d. \text{sep}(3)} \underbrace{P(Y_t = i | \bar{x}_t, Y_{t+1} = j)}_{d. \text{sep}(1)} \\
 &= \begin{cases} \alpha_{0(t-1)} \sigma(\bar{w}_0 \cdot \bar{x}_t) + \alpha_{1(t-1)} \sigma(\bar{w}_1 \cdot \bar{x}_t) & , \text{ if } i=1 \\ \alpha_{0(t-1)} (1 - \sigma(\bar{w}_0 \cdot \bar{x}_t)) + \alpha_{1(t-1)} (1 - \sigma(\bar{w}_1 \cdot \bar{x}_t)) & , \text{ if } i=0. \end{cases}
 \end{aligned}$$

$$(b) \ell_{it}^* = \max_{Y_1, \dots, Y_{t-1}} [\log P(Y_1, \dots, Y_t = i | Y_0, \bar{x}_1, \dots, \bar{x}_t)]$$

$$\begin{aligned}
 &= \max_{Y_1, \dots, Y_{t-1}} [\log P(Y_1, \dots, Y_{t-1} | Y_0, \bar{x}_1, \dots, \bar{x}_t) + \log P(Y_t = i | Y_0, \bar{x}_1, \dots, \bar{x}_t, Y_1, \dots, Y_{t-1})] \\
 &= \max_{Y_1, \dots, Y_t} \log P(Y_1, \dots, Y_{t-1} | Y_0, \bar{x}_1, \dots, \bar{x}_{t-1}) + \max_{Y_1, \dots, Y_t} \log P(Y_t = i | \bar{x}_t, Y_{t-1}) \quad \text{PR}_1 \\
 &= \ell_{i(t-1)}^* + \max_{d. \text{sep}(3)} (\log \sigma(\bar{w}_0 \cdot \bar{x}_t), \log \sigma(\bar{w}_1 \cdot \bar{x}_t), \log (1 - \sigma(\bar{w}_0 \cdot \bar{x}_t)), \log (1 - \sigma(\bar{w}_1 \cdot \bar{x}_t)))
 \end{aligned}$$

$$\begin{aligned}
 (c) \alpha_{it} &= \sum_{j \in \{0,1\}} P(Y_t = i, Y_{t+1} = j | Y_0, \bar{x}_1, \dots, \bar{x}_t) \log(1 - \sigma(\bar{w}_1 \cdot \bar{x}_t)) \\
 &= \sum_{j \in \{0,1\}} \underbrace{P(Y_t = i | Y_0, \bar{x}_1, \dots, \bar{x}_{t+1})}_{(*)} P(Y_{t+1} = j | Y_t = i, \bar{x}_{t+1})
 \end{aligned}$$

Take log we have  $(*) = \ell_{it}^* + \log P(Y_{t+1} = j | Y_t = i, \bar{x}_{t+1})$ .

this is analogous to the viterbi algo. for HMM,

$$\text{so } \Phi_{t+1}(j) = \arg \max_{i \in \{0,1\}} [\ell_{it}^* + \log P(Y_{t+1} = j | Y_t = i, \bar{x}_{t+1})]$$

$$\text{and } y_t^* = \Phi_{t+1}(y_{t+1}^*).$$

# HW8 Code

November 23, 2021

```
[1]: import numpy as np

pid = []

with open("hw8_ids.txt", "r") as ids:
    for line in ids.readlines():
        pid.append(line[:-1])

movie = []
with open("hw8_movies.txt", "r") as mvs:
    for line in mvs.readlines():
        movie.append(line[:-1])

rating = []
with open("hw8_ratings.txt", "r") as rts:
    for line in rts.readlines():
        line = line.strip('\n')
        line = line.split(' ')
        rating.append(line)

rating = np.array(rating)
print(rating.shape)

index = {}
for i in range(rating.shape[1]):
    saw = 0
    rec = 0
    for j in range(rating.shape[0]):
        if rating[j][i] != '?':
            saw += 1
        if rating[j][i] == '1':
            rec += 1
    index[i] = rec / saw

index_sorted = sorted(index.items(), key=lambda x: x[1])
movie_sorted = []
for i in range(len(index_sorted)):
    movie_sorted.append(movie[index_sorted[i][0]])
```

```

print(movie_sorted)

# 8.1.e
probR = np.loadtxt("hw8_probR_init.txt")
probZ = np.loadtxt("hw8_probZ_init.txt").flatten()

# returns Omega_t
def seen(t) -> list:
    res = []
    for rate in rating[t]:
        if rate != '?':
            res.append(1)
        else:
            res.append(0)
    return res

# Z R are ndarray
def prior(Z, R, t):
    K = Z.shape[0] # 4
    O_t = seen(t)
    J = len(movie) # 76
    sum = 0

    for i in range(K):
        prod = 1
        for j in range(J):
            if O_t[j] == 0:
                continue
            r_jt = int(rating[t][j])
            if r_jt == 1:
                prod *= R[j][i]
            else:
                prod *= 1 - R[j][i]
        sum += Z[i] * prod
    return sum

def rou_it(Z, R, i, t):
    denom = prior(Z, R, t)
    prod = 1
    O_t = seen(t)
    J = len(movie)
    for j in range(J):
        if O_t[j] == 0:
            continue

```

```

        r_jt = int(rating[t][j])
        if r_jt == 1:
            prod *= R[j][i]
        else:
            prod *= 1 - R[j][i]
    num = Z[i] * prod
    return num / denom

def likelihood(Z, R):
    sum = 0
    T = len(pid)
    for t in range(T):
        sum += np.log(prior(Z, R, t))
    return sum / T

def update(Z, R, iter):
    res_Z = np.copy(Z)
    res_R = np.copy(R)
    K = Z.shape[0] # 4

    T = len(pid) # 362
    J = len(movie) # 76

    for k in range(iter): # 256
        if k in [0, 1, 2, 4, 8, 16, 32, 64, 128, 256]:
            print(k)
            ll = likelihood(res_Z, res_R)
            print(ll)

            # rou_it = rou_it_mat[t][i]
            rou_it_mat = np.zeros((362, 4))
            for t in range(362):
                for i in range(4):
                    rou_it_mat[t][i] = rou_it(res_Z, res_R, i, t)

            # update P(Z=i)

            for i in range(K): # 4
                sum = 0
                for t in range(T):
                    sum += rou_it_mat[t][i]
                res_Z[i] = sum / T

            # Update P(R_j=1/Z=i)
            for j in range(J): # 76
                for i in range(K): # 4

```



```

        denom = 0
        for t in range(T):
            denom += rou_it_mat[t][i]
        num = 0
        for t in range(T): # 362
            if seen(t)[j] == 1:
                if int(rating[t][j]) == 1:
                    num += rou_it_mat[t][i]
                else:
                    continue
            else:
                num += rou_it_mat[t][i] * res_R[j][i]
        res_R[j][i] = num / denom
    return res_Z, res_R

# takes about 10 minutes to run :(
final_Z, final_R = update(probZ, probR, 257)

prob = [0] * len(movie)
pid = np.array(pid)

row = int(np.where(pid == 'A15058075')[0])
# row = 344
rate = rating[row]
binary_seen = seen(row)
for k in range(len(prob)):
    if binary_seen[k] == 1:
        continue
    sum = 0
    for i in range(4):
        sum += rou_it(final_Z, final_R, i, row) * final_R[k][i]
    prob[k] = sum
index_mine = {}
for i in range(len(prob)):
    if prob[i] == 0:
        continue
    index_mine[i] = prob[i]

index_mine_sorted = sorted(index_mine.items(), key=lambda x: x[1], reverse=True)
movie_mine_sorted = []
for i in range(len(index_mine_sorted)):
    movie_mine_sorted.append(movie[index_mine_sorted[i][0]])
print(movie_mine_sorted)

```

(362, 76)

['I\_Feel\_Pretty', 'Fifty\_Shades\_of\_Grey', 'Hustlers', 'The\_Last\_Airbender',  
'Magic\_Mike', 'Fast\_&\_Furious:\_Hobbs\_&\_Shaw', 'The\_Shape\_of\_Water',

'Prometheus', 'Phantom\_Thread', 'World\_War\_Z', 'Star\_Wars:\_The\_Force\_Awakens',  
 'Rocketman', 'Chappaquidick', 'Bridemaids', 'Man\_of\_Steel', 'American\_Hustle',  
 'Terminator:\_Dark\_Fat', 'Room', 'Good\_Boys', 'Pokemon\_Detective\_Pikachu',  
 'Fast\_Five', 'Mad\_Max:\_Fury\_Road', 'Drive', 'Us', 'The\_Help', 'Pitch\_Perfect',  
 'Jurassic\_World', 'Frozen', 'X-Men:\_First\_Class', 'The\_Revenant', 'Ex\_Machina',  
 'Avengers:\_Age\_of\_Ultron', 'La\_La\_Land', 'Midnight\_in\_Paris',  
 'Manchester\_by\_the\_Sea', 'Once\_Upon\_a\_Time\_in\_Hollywood',  
 'Three\_Billboards\_Outside\_Ebbing', 'Darkest\_Hour', 'The\_Great\_Gatsby',  
 'Dunkirk', 'Her', 'Captain\_America:\_The\_First\_Avenger',  
 'The\_Girls\_with\_the\_Dragon\_Tattoo', 'Ready\_Player\_One', 'Hidden\_Figures',  
 'The\_Hateful\_Eight', 'Thor', 'Toy\_Story\_3', 'The\_Hunger\_Games',  
 '12\_Years\_a\_Slave', 'Iron\_Man\_2', 'The\_Perks\_of\_Being\_a\_Wallflower', 'Joker',  
 'Les\_Miserables', '21\_Jump\_Street', 'Spiderman:\_Far\_From\_Home', 'Black\_Swan',  
 'Parasite', 'The\_Avengers', 'The\_Farewell', 'Django\_Unchained',  
 'Now\_You\_See\_Me', 'Avengers:\_Endgame', 'Avengers:\_Infinity\_War',  
 'Wolf\_of\_Wall\_Street', 'The\_Lion\_King', 'Gone\_Girl',  
 'Harry\_Potter\_and\_the\_Deathly\_Hallows:\_Part\_1', 'The\_Social\_Network',  
 'Harry\_Potter\_and\_the\_Deathly\_Hallows:\_Part\_2', 'The\_Theory\_of\_Everything',  
 'Interstellar', 'The\_Martian', 'The\_Dark\_Knight\_Rises', 'Shutter\_Island',  
 'Inception']

0

-27.03581500351123

1

-17.5604038243144

2

-16.002362630627825

4

-15.060597317892249

8

-14.501649272824999

16

-14.26378857143746

32

-14.180178075094306

64

-14.170077781591038

128

-14.163960358152185

256

-14.163692439007862

['Shutter\_Island', 'The\_Social\_Network', 'Avengers:\_Age\_of\_Ultron',  
 'The\_Theory\_of\_Everything', 'The\_Farewell', 'Now\_You\_See\_Me', 'The\_Martian',  
 '21\_Jump\_Street', 'The\_Perks\_of\_Being\_a\_Wallflower', 'Django\_Unchained',  
 'Midnight\_in\_Paris', 'The\_Hateful\_Eight', 'Toy\_Story\_3', 'Parasite',  
 'Black\_Swan', 'The\_Last\_Airbender', 'X-Men:\_First\_Class', 'Us',  
 'Ready\_Player\_One', 'The\_Girls\_with\_the\_Dragon\_Tattoo', 'Pitch\_Perfect',  
 'Frozen', 'Man\_of\_Steel', 'Hidden\_Figures', 'Jurassic\_World', 'Fast\_Five',  
 'Rocketman', 'Ex\_Machina', 'Chappaquidick', 'American\_Hustle', 'The\_Help',

```
'Good_Boys', 'Magic_Mike', 'Darkest_Hour', 'Three_Billboards_Outside_Ebbing',  
'The_Revenant', 'Mad_Max:_Fury_Road', 'The_Shape_of_Water', 'Her',  
'Fifty_Shades_of_Grey', 'Drive', 'Bridemaids', 'Phantom_Thread', 'Hustlers',  
'Prometheus', 'I_Feel_Pretty']
```

[ ]: