

# Basic SQL Practice


VLDB Lab.

Professor Sangwon Lee

# Contents

- **Export CSV File - LiveSQL**
- **Import CSV File – Postgres**
- **Create Table**
- **Insert Tuples**
- **Update Tuples**
- **Delete Tuples**
- **Drop Table**

# Scott Schema



# Export CSV File

1. Sign In to LiveSQL. (<https://livesql.oracle.com/>)
2. Select Data from emp table and dept table. Then, download csv file of each table.

SQL Worksheet

1 `select * from scott.emp;` ①

Run ②

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7839	KING	PRESIDENT	-	17-NOV-81	5000	-	10
7698	BLAKE	MANAGER	7839	01-MAY-81	2850	-	30
7782	CLARK	MANAGER	7839	09-JUN-81	2450	-	20
7566	JONES	MANAGER	7839	02-APR-81	2975	-	20
7788	SCOTT	ANALYST	7566	19-APR-87	3000	-	20
7902	FORD	ANALYST	7566	03-DEC-81	3000	-	10
7369	SMITH	CLERK	7902	17-DEC-80	800	-	20
7499	ALLEN	SALESMAN	7698	20-FEB-81	1600	300	30
7521	WARD	SALESMAN	7698	22-FEB-81	1250	500	30
7654	MARTIN	SALESMAN	7698	28-SEP-81	1250	1400	30
7844	TURNER	SALESMAN	7698	08-SEP-81	1500	0	30
7876	ADAMS	CLERK	7788	23-MAY-87	1100	-	20
7900	JAMES	CLERK	7698	03-DEC-81	950	-	30
7934	MILLER	CLERK	7782	23-JAN-82	1300	-	10

Download CSV ③

SQL Worksheet

1 `select * from scott.dept;` ①

Run ②

DEPTNO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON


Download CSV ③

4 rows selected.


# Start Postgres

## 1. Start Postgres.




[Mac]



[Windows]




## 2. Start pgAdmin and connect postgres server.



Now you can write sql query!

# Import CSV File

## 1. Right Click dept table and click 'Import/Export Data...'




## 2. Repeat process 1. for the emp table.

# CREATE TABLE

## 1. Create dept, emp table in postgres.




If you refresh postgres server, you can now see two tables.




# SELECT statement

1. Now, you can search data within the Scott account table using the SELECT statement.



The screenshot shows a PostgreSQL query editor with the query `select * from dept;` executed. The results are displayed in a table with three columns: deptno, dname, and loc.

	deptno [PK] numeric (2)	dname character varying (14)	loc character varying (13)
1	20	RESEARCH	DALLAS
2	30	SALES	CHICAGO
3	40	OPERATIONS	BOSTON



The screenshot shows a PostgreSQL query editor with the query `select * from emp;` executed. The results are displayed in a table with 14 columns: empno, ename, job, mgr, hiredate, sal, comm, and deptno.

	empno [PK] numeric (4)	ename character varying (10)	job character varying (9)	mgr numeric (4)	hiredate date	sal numeric (7,2)	comm numeric (7,2)	deptno numeric (2)
1	7839	KING	PRESIDENT	[null]	1981-11-17	5000.00	[null]	10
2	7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	[null]	30
3	7782	CLARK	MANAGER	7839	1981-06-09	2450.00	[null]	20
4	7566	JONES	MANAGER	7839	1981-04-02	2975.00	[null]	20
5	7788	SCOTT	ANALYST	7566	1987-04-19	3000.00	[null]	20
6	7902	FORD	ANALYST	7566	1981-12-03	3000.00	[null]	10
7	7369	SMITH	CLERK	7902	1980-12-17	800.00	[null]	20
8	7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
9	7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
10	7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
11	7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
12	7876	ADAMS	CLERK	7788	1987-05-23	1100.00	[null]	20
13	7900	JAMES	CLERK	7698	1981-12-03	950.00	[null]	30
14	7934	MILLER	CLERK	7782	1982-01-23	1300.00	[null]	10



# SELECT statement

## 2. You can also execute advanced queries.

Query	Query History
1	<code>select * from emp where job not in('PRESIDENT','MANAGER');</code>

Query	Query History
1	<code>select max(sal) from emp;</code>

Query	Query History
1	<code>select * from emp where deptno in (</code>
2	<code>select deptno from emp where ename='JAMES'</code>
3	<code>)</code>

Query	Query History
1	<code>select emp.ename, emp.deptno, dept.loc from emp</code>
2	<code>join dept on emp.deptno = dept.deptno</code>
3	<code>where emp.ename = 'KING'</code>

# INSERT statement

- Insert new tuple in the emp table.

[Syntax]


```
INSERT INTO table_name(column1, column2, ...)  
VALUES (value1, value2, ...);
```

[Example]



The screenshot shows a PostgreSQL query editor interface. The top bar indicates the connection is 'postgres/postgres@Postgres'. Below the toolbar, the 'Query' tab is active, showing a query history with two entries. The first entry is an INSERT statement:

```
1 INSERT INTO emp VALUES  
2 (1234, 'BKMS1', 'MANAGER', null, '2024-03-26', 3000.00, null, 10);
```



The screenshot shows the same PostgreSQL query editor interface, but now the 'Query' tab displays a SELECT query and its results. The query is:

```
1 select * from emp;
```

Below the query, the 'Data Output' tab is active, showing a table with 15 rows. The first 14 rows are the existing data in the 'emp' table, and the 15th row is the newly inserted tuple, which is highlighted with a red border.

	empno [PK] numeric (4)	ename character varying (10)	job character varying (9)	mgr numeric (4)	hiredate date	sal numeric (7,2)	comm numeric (7,2)	deptno numeric (2)
1	7839	KING	PRESIDENT	[null]	1981-11-17	5000.00	[null]	10
2	7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	[null]	30
3	7782	CLARK	MANAGER	7839	1981-06-09	2450.00	[null]	20
4	7566	JONES	MANAGER	7839	1981-04-02	2975.00	[null]	20
5	7788	SCOTT	ANALYST	7566	1987-04-19	3000.00	[null]	20
6	7902	FORD	ANALYST	7566	1981-12-03	3000.00	[null]	10
7	7369	SMITH	CLERK	7902	1980-12-17	800.00	[null]	20
8	7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
9	7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
10	7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
11	7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
12	7876	ADAMS	CLERK	7788	1987-05-23	1100.00	[null]	20
13	7900	JAMES	CLERK	7698	1981-12-03	950.00	[null]	30
14	7934	MILLER	CLERK	7782	1982-01-23	1300.00	[null]	10
15	1234	BKMS1	MANAGER	[null]	2024-03-26	3000.00	[null]	10


# Update statement

- Insert new tuple in the emp table.


[Syntax]

```
UPDATE table
SET column1 = value1, column2 = value2, ...
WHERE condition;
```

[Example]



The screenshot shows a PostgreSQL query editor interface. The top bar indicates the connection is to 'postgres/postgres@Postgres'. Below the toolbar, the query editor displays a single query: `1 update emp set sal=10000.00 where ename='KING'`.



The screenshot shows the query result table for the executed query. The table has columns: empno, ename, job, mgr, hiredate, sal, comm, and deptno. The row for King (empno 7839) is highlighted in red, showing a salary of 10000.00.

	empno [PK] numeric (4)	ename character varying (10)	job character varying (9)	mgr numeric (4)	hiredate date	sal numeric (7,2)	comm numeric (7,2)	deptno numeric (2)
1	7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	[null]	30
2	7782	CLARK	MANAGER	7839	1981-06-09	2450.00	[null]	20
3	7566	JONES	MANAGER	7839	1981-04-02	2975.00	[null]	20
4	7788	SCOTT	ANALYST	7566	1987-04-19	3000.00	[null]	20
5	7902	FORD	ANALYST	7566	1981-12-03	3000.00	[null]	10
6	7369	SMITH	CLERK	7902	1980-12-17	800.00	[null]	20
7	7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
8	7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
9	7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
10	7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
11	7876	ADAMS	CLERK	7788	1987-05-23	1100.00	[null]	20
12	7900	JAMES	CLERK	7698	1981-12-03	950.00	[null]	30
13	7934	MILLER	CLERK	7782	1982-01-23	1300.00	[null]	10
14	7839	KING	PRESIDENT	[null]	1981-11-17	10000.00	[null]	10


# DELETE statement

- Delete the tuple in the table.


[Syntax]

```
DELETE FROM  
table_name  
WHERE condition ;
```

[Example]



A screenshot of a PostgreSQL query editor interface. The top bar shows the connection 'postgres/postgres@Postgres'. Below the toolbar, the 'Query' tab is active, displaying a single SQL statement: `1 delete from emp where ename = 'BKMS1';`. The 'Query History' tab is also visible.



A screenshot of a PostgreSQL query result interface. The top bar shows the connection 'postgres/postgres@Postgres'. Below the toolbar, the 'Query' tab is active, displaying a single SQL statement: `1 select * from emp;`. The 'Data Output' tab is active, showing a table with 14 rows and 9 columns. The columns are: empno (PK) numeric (4), ename character varying (10), job character varying (9), mgr numeric (4), hiredate date, sal numeric (7,2), comm numeric (7,2), and deptno numeric (2). The table contains data for 14 employees, including KING, BLAKE, CLARK, JONES, SCOTT, FORD, SMITH, ALLEN, WARD, MARTIN, TURNER, ADAMS, JAMES, and MILLER. A red box at the bottom of the table contains the text 'No 'BKMS1'', indicating that no rows were deleted.

	empno [PK] numeric (4)	ename character varying (10)	job character varying (9)	mgr numeric (4)	hiredate date	sal numeric (7,2)	comm numeric (7,2)	deptno numeric (2)
1	7839	KING	PRESIDENT	[null]	1981-11-17	5000.00	[null]	10
2	7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	[null]	30
3	7782	CLARK	MANAGER	7839	1981-06-09	2450.00	[null]	20
4	7566	JONES	MANAGER	7839	1981-04-02	2975.00	[null]	20
5	7788	SCOTT	ANALYST	7566	1987-04-19	3000.00	[null]	20
6	7902	FORD	ANALYST	7566	1981-12-03	3000.00	[null]	10
7	7369	SMITH	CLERK	7902	1980-12-17	800.00	[null]	20
8	7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
9	7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
10	7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
11	7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
12	7876	ADAMS	CLERK	7788	1987-05-23	1100.00	[null]	20
13	7900	JAMES	CLERK	7698	1981-12-03	950.00	[null]	30
14	7934	MILLER	CLERK	7782	1982-01-23	1300.00	[null]	10

No 'BKMS1'



# DROP Table

- Drop table

[Syntax]

```
DROP TABLE [IF EXISTS]  
table_name [CASCADE | RESTRICT];
```

[Example]



Think💡: Why does DROP table without cascade condition doesn't work in dept table?

Think💡: What is the difference between DROP table and TRUNCATE table?