

# *RTI CORBA Compatibility Kit*

## **CORBA-DDS Example Using C++**

### **Instructions**

Version 5.3.0



Your systems. Working as one.



© 2007-2017 Real-Time Innovations, Inc.  
All rights reserved.  
Printed in U.S.A. First printing.  
June 2017.

### **Trademarks**

Real-Time Innovations, RTI, NDDS, RTI Data Distribution Service, DataBus, Connex, Micro DDS, the RTI logo, 1RTI and the phrase, “Your Systems. Working as one,” are registered trademarks, trademarks or service marks of Real-Time Innovations, Inc. All other trademarks belong to their respective owners.

### **Copy and Use Restrictions**

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form (including electronic, mechanical, photocopy, and facsimile) without the prior written permission of Real-Time Innovations, Inc. The software described in this document is furnished under and subject to the RTI software license agreement. The software may be used or copied only under the terms of the license agreement.

### **Technical Support**

Real-Time Innovations, Inc.

232 E. Java Drive  
Sunnyvale, CA 94089

Phone: (408) 990-7444

Email: [support@rti.com](mailto:support@rti.com)

Website: <https://support.rti.com/>

# CORBA-DDS Example Using C++

This document will guide you through the steps required to create a CORBA-DDS publisher and a CORBA-DDS subscriber based on an example IDL file. Then it will show you how to adapt those steps to create your own application (the provided example).

This example shows you how to create applications that use CORBA and *RTI<sup>®</sup> Connex<sup>®</sup> DDS* and share a common set of types for both APIs.

The example includes:

- ❑ A CORBA server application.
- ❑ An *RTI Connex DDS* subscriber application.
- ❑ A combined CORBA client-DDS publisher application. This application uses CORBA and DDS to send text messages to the CORBA server and the *Connex DDS* subscriber. Both receiving applications print the messages to the console.

For more information, please see the *RTI CORBA Compatibility Kit Installation Guide* (<NDDSHOME>/doc/manuals/corba/RTI\_CORBA\_Compatibility\_Kit\_InstallationGuide.pdf).

---

## 1 Paths Mentioned in Documentation

The documentation refers to:

- ❑ <NDDSHOME>

This refers to the installation directory for *Connex DDS*.

The default installation paths are:

- UNIX-based systems, non-*root* user:  
*/home/your user name/rti\_connex\_dds-version*
- UNIX-based systems, *root* user:  
*/opt/rti\_connex\_dds-version*
- Windows systems, user without Administrator privileges:  
*<your home directory>\rti\_connex\_dds-version*
- Windows systems, user with Administrator privileges:  
**C:\Program Files\rti\_connex\_dds-version**

(You can specify a different location for the **rti\_workspace** directory. See the *RTI Connex DDS Core Libraries Getting Started Guide*.)

You may also see \$NDDSHOME or %NDDSHOME%, which refers to an environment variable set to the installation path.

Wherever you see <NDDSHOME> used in a path, replace it with your installation path.

Note for Windows Users: When using a command prompt to enter a command that includes the path **C:\Program Files** (or any directory name that has a space), enclose the path in quotation marks. For example:

```
"C:\Program Files\rti_connext_dds-version\bin\rtiddsgen"
```

or if you have defined the NDDSHOME environment variable:

```
"%NDDSHOME%\bin\rtiddsgen"
```

#### ❑ <path to examples>

Examples are copied into your home directory the first time you run *RTI Launcher* or any script in <NDDSHOME>/bin. This document refers to the location of these examples as <path to examples>.

Wherever you see <path to examples>, replace it with the appropriate path.

By default, the examples are copied here:

- UNIX-based systems:  
*/home/your user name/rti\_workspace/version/examples*
- Windows systems:  
*<your home directory>\rti\_workspace\version\examples*

(You can specify that you do not want the examples copied to the workspace. See the *RTI Connext DDS Core Libraries Getting Started Guide*.)

---

## 2 Introduction

The example is in <path to examples>/corba/c++/corba\_dds. The data type for the test is in **Message.idl**. The application source file is **MessageApp.cxx**. The rest of the source files will be generated by *rtiddsgen* (the *Connext DDS* IDL code generator) and *tao\_idl* (TAO's IDL code generator).

---

## 3 Setting up Your Environment

If you need general instructions for setting environment variables, please see the *RTI Core Libraries and Utilities Getting Started Guide*.

**Note:** Your libraries may be located in either \$(ACE\_ROOT)/lib or \$(ACE\_ROOT)/lib/<arch> (such as \$(ACE\_ROOT)/lib/i686). Therefore, \$(ACE\_ROOT)/lib[/<arch>] will refer to the location of the libraries throughout this document.

1. Set the ACE\_ROOT, TAO\_ROOT and LD\_LIBRARY\_PATH environment variables.

For example, if you are using a csh or tcsh shell and ACE+TAO is installed in /opt/ACE\_wrappers:

```
setenv ACE_ROOT /opt/ACE_wrappers
```

```
setenv TAO_ROOT ${ACE_ROOT}/TAO
setenv LD_LIBRARY_PATH ${LD_LIBRARY_PATH}:${ACE_ROOT}/lib[/<arch>]
```

2. Make sure the **NDDSHOME** environment variable is set as described in the *RTI Connexx DDS Core Libraries Getting Started Guide*. For example, if you are using a `csh` or `tcsh` shell and *Connexx DDS* is installed in `/home/your user name/rti_connexx_dds-5.x.y` (where *x* and *y* are part of the version number for the current release):

```
setenv NDDSHOME /home/your user name/rti-connexx_dds-5.x.y
```

## 4 Generating the Source Code

To generate the source code, you will use *rtiddsgen* (*Connexx DDS*'s IDL code generator) and *tao\_idl* (TAO's IDL code generator).

**Note for Cross-compiling:** When using cross-compilation, you may need to run *tao\_idl* and *rtiddsgen* on the host system. Please refer to **ACE+TAO** documentation for details.

1. Both *tao\_idl* and *rtiddsgen* use the **cpp** preprocessor. Make sure that the preprocessor is in your Path (for help, see the *RTI Core Libraries and Utilities Getting Started Guide*).
2. **Copy the IDL file (Message.idl) to a new directory.** In that directory, invoke *tao\_idl* on the *Message.idl* file.

```
$ACE_ROOT/bin/tao_idl -GT Message.idl
```

This will generate the following CORBA support files:

- **MessageC.cpp, MessageS.cpp, MessageS\_T.cpp**
- **MessageC.inl, MessageS.inl**
- **MessageC.h, MessageS.h, MessageS\_T.h**

3. Invoke *rtiddsgen* on the *.idl* file with **-corba MessageC.h** (which contains the CORBA type definitions):

```
$NDDSHOME/bin/rtiddsgen -language C++ \
-corba MessageC.h -orb <ACE_TAOversion>
-example <architecture> Message.idl
```

Where **<ACE\_TAOversion>** depends on your version of TAO (for example, **ACE\_TAO1.6**) and **<architecture>** depends on which architecture you are using (see supported platforms in the *Release Notes*), for example, **i86Linux2.6gcc4.1.2**.

This will generate the following *Connexx DDS* support files:

- **Message.cxx, MessagePlugin.cxx, MessageSupport.cxx**
- **Message.h, MessagePlugin.h, MessageSupport.h**
- **Message\_subscriber.cxx, Message\_publisher.cxx**
- **Message.mwc, Message\_subscriber.mpc, Message\_publisher.mpc** (will be used by TAO's Makefile, Project and Workspace Creator (MPC) tool.
- **USER\_QOS\_PROFILES.xml**

**Note:** If you copied the entire contents of the example directory, remove the **\*.mpc** files (or specify **-replace** on the *rtiddsgen* command line)—these files refer to architecture-specific *Connexx DDS* libraries.

## 5 Generating the Makefile

TAO's Makefile, Project and Workspace Creator (MPC) can be used to generate the makefile for the example. Note that Perl must be available to use MPC.

**Note for Cross-compiling:** When using cross-compilation, you may need to run `mwc.pl` on the host system. Please refer to **ACE+TAO** documentation for details.

Invoke MPC in the same directory you created in [Step 2 on Page 3](#):

```
$ACE_ROOT/bin/mwc.pl -type gnuace Message.mwc
```

This will generate three makefiles:

- ☐ For the publisher application: **GNUmakefile.Message\_publisher**
- ☐ For the subscriber application: **GNUmakefile.Message\_subscriber**
- ☐ **GNUmakefile**, which executes the above two makefiles.

**Note:** If you want to use the `.mpc` and `.mwc` files generated by *rtiddsgen* for data types other than the ones in **Message.idl**, you may need to modify your `.mpc` files in order to link against additional TAO libraries.

You may need to modify the makefiles if the TAO libraries are not in `$ACE_HOME/lib`. The libraries may be in `$ACE_HOME/lib/<arch>` (e.g., `$ACE_HOME/lib/i686`). If so, use `sed` to replace all the references to the `lib` directory in both the publisher and subscriber makefiles:

```
sed -i 's/ACE_ROOT)/lib/ACE_ROOT)/lib/i686/' GNUmakefile.Message_publisher
sed -i 's/ACE_ROOT)/lib/ACE_ROOT)/lib/i686/' GNUmakefile.Message_subscriber
```

Also remove the include line for **rules.dds.GNU**:

```
sed -i '/rules.dds.GNU/s/^/#/g' GNUmakefile.Message_publisher
sed -i '/rules.dds.GNU/s/^/#/g' GNUmakefile.Message_subscriber
```

---

## 6 Compiling and Running the Publisher and Subscriber Example

### 6.1 Compiling the Publisher and Subscriber

In the same directory created in [Step 2 on Page 3](#), run the following:

```
gmake -f GNUmakefile
```

This will execute **GNUmakefile.Message\_publisher** and **GNUmakefile.Message\_subscriber** and create a **Message\_publisher** executable and a **Message\_subscriber** executable in your working directory.

**Note for Cross-compiling:** When using cross-compilation, you will need to have the cross-compile environment set up and run **gmake** on the host system to compile. Please refer to **ACE+TAO** documentation for details.

### 6.2 Running the Example Publisher and Subscriber

You have now successfully created a publisher and a subscriber for the CORBA data types included in the IDL file, **Message.idl**.

Work in the same directory created in [Step 2 on Page 3](#).

First, set up `LD_LIBRARY_PATH` in two separate terminals (as in [Step 1 on Page 2](#)). Then run the application by entering :

Message\_subscriber <Domain\_ID> <Number\_of\_Samples> (in the 1st window)

Message\_publisher <Domain\_ID> <Number\_of\_Samples> (in the 2nd window)

Example output from **Message\_subscriber**:

```
time:
  year: 0
  month: 0
  day: 0
  hour: 0
  minute: 0
  second: 0
msg: "xxxxxxxxxxxxx"
```

Example output from **Message\_publisher**:

```
Writing HelloWorld, count 0
Writing HelloWorld, count 1
Writing HelloWorld, count 2
```

Please refer to the *RTI Core Libraries and Utilities Getting Started Guide* for more on how to run *rtiddsgen*-generated Publisher and Subscriber applications.

---

## 7 Compiling and Running the CORBA Example Application

### 7.1 Using the Generated Files to Build the CORBA Example Application

This section describes how to use the code generated by *tao\_idl/rtiddsgen* from **Message.IDL** to build a custom application:

1. The custom application code has already been provided for you in `<path to examples>/corba/c++/corba_dds/MessageApp.cxx` in your *Connex DDS* installation directory. Copy that file into the same directory created in [Step 2 on Page 3](#).
2. Copy **Message\_publisher.mpc** to a new file named **MessageApp.mpc**. Then edit **MessageApp.mpc**:

- a. Replace the executable name with **MessageApp**:

```
//exename = Message_publisher
exename = MessageApp
```

- b. In the `Source_Files` section, comment out **Message\_publisher.cxx** and add **MessageApp.cxx**, so that it looks like this:

```
Source_Files {
  MessageC.cpp
  MessageS.cpp
  MessagePlugin.cxx
  Message.cxx
  MessageSupport.cxx
  //Message_publisher.cxx
  MessageApp.cxx
}
```

- c. Save **MessageApp.mpc**.

3. Edit **Message.mwc**: remove **Message\_publisher.mpc** and **Message\_subscriber.mpc** from the workspace section, replacing them with **MessageApp.mpc**:

```
workspace {  
    // Message_publisher.mpc  
    // Message_subscriber.mpc  
    MessageApp.mpc  
}
```

4. Generate the makefile/Visual Studio Project File as described in [Section 5](#).
5. Compile your application:

```
gmake -f GNUmakefile.MessageApp
```

**Note for Cross-Compiling:** When using cross-compilation, you will need to have the cross-compile environment set up and run **gmake** on the host system to compile. Please refer to **ACE+TAO** documentation for details.

## 7.2 Running the CORBA Example Application

You will need 3 separate command shells. Make sure that each one has the TAO libraries in the dynamic library search path:

- ❑ Add **\$ACE\_ROOT/lib[<arch>]** to the **LD\_LIBRARY\_PATH** environment variable.

1. In the first command shell, start the CORBA server application:

```
MessageApp -cr Message.ior
```

The CORBA server will store an IOR (Interoperable Object Reference) in **Message.ior**; this file will be passed to the client application in [Step 3](#).

2. In the second command shell, start the *Connex* DDS subscriber application:

```
MessageApp -nr <domainId>
```

The domain ID is required. Only applications using the same domain ID will communicate with each other.

3. In the third command shell, start the combined CORBA-DDS application, which will publish CORBA and DDS messages:

```
MessageApp -s Message.ior <domainId>
```

The domain ID is required. Use the same value that you used for the subscriber.

Notice that this is the same filename passed to the CORBA server in [Step 1](#).

4. Type some messages in the combined CORBA-DDS application prompt (command shell 3).

The messages will be sent to the CORBA Server (command shell 1) *and* the DDS subscriber (command shell 2) using the same types programmatically!

**Note:** If you enter **quit** in command shell 3, only the third application will exit; the other two will not be affected.