

Learning and Inference in Deep, Unsupervised Neural Networks

Kyunghyun Cho

Department of Information and Computer Science
Aalto University, School of Science
kyunghyun.cho@aalto.fi

21 March 2014

This work was done under the supervision of Prof. Juha Karhunen, Prof. Tapani Raiko and Dr. Alexander Ilin at the Deep Learning and Bayesian Modeling Group, Department of Information and Computer Science, Aalto University School of Science between mid 2009 and early 2014.



Boltzmann machines? I remember working on them in 80s and 90s..

– Anonymous, 2011
paraphrased

Introduction


- Machine Learning
- Deep Learning
- Challenges

Deep, Unsupervised Neural Networks

- Restricted Boltzmann Machines
- Deep Boltzmann Machines
- Deep Autoencoders


Discussion

Machine Learning




1. Let the model \mathcal{M} *learn* the data D
2. Let the model \mathcal{M} *infer* unknown quantities

Examples



Data	Query
Labeled Images	Is a cat in this image?
Transcribed Speech	What is this person saying?
Paraphrases	Is this sentence a paraphrase?
Movie Ratings	Will a user X like a movie Y ?
Parallel Corpora	What is "moi" in English?

Deep Learning: Motivated from Human Learning



Learn massive data

Information flow through neurons






Figure 68.26 (Biological Sciences), 2/e
© 2005 Pearson Education, Inc.



(Van Essen&Gallant, 1994)

simple functions


Multi-layered



(Krizhevsky et al., 2012)


Conventional Machine Learning

1. Feature engineering ← **not learned!**
2. Learning
3. Inference




Deep Learning (1)

1. Jointly **learn** everything
2. **Inference**



Deep Learning (2): Learning Representation

- 1a. Feature engineering
- 1b. Feature/Representation **learning**
2. **Learning**
3. **Inference**




Deep Learning

With massive amounts of computational power, machines can now recognize objects and translate speech in real time. Artificial intelligence is finally getting smart.




- ▶ Object Detection (Krizhevsky et al., 2012; Hinton et al., 2012)
- ▶ Speech Recognition (Hinton et al., 2012; Dahl et al., 2012; Deng et al., 2013)
- ▶ Natural language processing (Socher et al., 2011)

Challenges in Machine Learning




1. **Learning** is *not* trivial
2. **Learning** and **inference** are *not* separate

Learning Difficulties



- ▶ True cost \mathcal{C} is *not* available: Only empirical cost $\tilde{\mathcal{C}}$ available
- ▶ Often, non-convex optimization with many local/apparent minima
- ▶ Impractical to compute either \mathcal{C} or $\tilde{\mathcal{C}}$, as $|D| \rightarrow \infty$

Vicious Cycle or Virtuous Cycle?



Example: MLE for feedforward neural networks

$$\min_{\theta} \mathcal{C}(\theta) \approx \min_{\theta} \tilde{\mathcal{C}}(\theta) = \min_{\theta} -\frac{1}{N} \sum_{(\mathbf{x}, t) \in D} \log p(y = t \mid \mathbf{x}, \theta)$$

What gets worse with *deep* learning?

► Learning

- No access to \mathcal{C} , but only to $\tilde{\mathcal{C}}$
- Highly entangled inference and learning
- **High-dimensional**
- **Non-convex with a lot of local (apparent) minima**
- **Intractable to compute even $\tilde{\mathcal{C}}$, because $|D| \rightarrow \infty$**


► Inference

- **No analytical expression**, often
- **Intractable to compute**, often
- Difficult to analyze and understand

Deep, Unsupervised Neural Networks Boltzmann Machines and Autoencoders

- I Enhanced Gradient for Training Restricted Boltzmann Machines
- II Enhanced Gradient and Adaptive Learning Rate for Training Restricted Boltzmann Machines
- III Parallel Tempering is Efficient for Learning Restricted Boltzmann Machines
- VII A Two-Stage Pretraining Algorithm for Deep Boltzmann Machines
- VIII Simple Sparsification Improves Sparse Denoising Autoencoders in Denoising Highly Corrupted Images

Boltzmann Machines



Popular variants:

- ▶ If $\mathbf{V} = \mathbf{0}$ and $\mathbf{U} = \mathbf{0}$, restricted Boltzmann machine (RBM)
- ▶ If $\mathbf{U} = \mathbf{0}$ and layered \mathbf{h} , deep Boltzmann machine (DBM)

1. Negative energy over \mathbf{x} and \mathbf{h} :

$$-E(\mathbf{x}, \mathbf{h} \mid \theta) = \mathbf{b}^\top \mathbf{x} + \mathbf{c}^\top \mathbf{h} + \mathbf{x}^\top \mathbf{W} \mathbf{h} + \frac{1}{2} \mathbf{x}^\top \mathbf{U} \mathbf{x} + \frac{1}{2} \mathbf{h}^\top \mathbf{V} \mathbf{h}$$

2. Probability over \mathbf{x} and \mathbf{h} :


$$p(\mathbf{x}, \mathbf{h} \mid \theta) = \frac{1}{Z(\theta)} \exp \{-E(\mathbf{x}, \mathbf{h} \mid \theta)\}$$

3. Learn $p(\mathbf{x})$ by maximizing

$$\mathcal{L}(\theta) = \mathbb{E}_{\mathbf{x} \in D} \left[\log \frac{1}{Z(\theta)} \sum_{\mathbf{h}} e^{-E(\mathbf{x}, \mathbf{h} \mid \theta)} \right]$$


with stochastic gradient descent

Learning: Observations




- Invariant to bit-flipping transformation
- 2^{p+q} descent directions
- leading to (potentially all) different solutions
- Which direction?
- How to tractably decide?

Learning: Enhanced Gradient



Covariance of Weight Updates



Conventional

Enhanced

- Importance/weight of each direction $\nabla_{\mathbf{f}} \mathcal{L}$

$$\prod_{k=1}^{n_v+n_h} \langle x_k \rangle_{\text{dm}}^{f_k} (1 - \langle x_k \rangle_{\text{dm}})^{1-f_k}$$

- Weighted sum of all possible updates

$$\nabla_e w_{ij} = \text{Cov}_d(x_i, h_j) - \text{Cov}_m(x_i, h_j)$$

$$\nabla_e b_i = \langle x_i \rangle_d - \langle x_i \rangle_m - \sum_j \langle h_j \rangle_{\text{dm}} \nabla_e w_{ij}$$

$$\nabla_e c_j = \langle h_j \rangle_d - \langle h_j \rangle_m - \sum_i \langle x_i \rangle_{\text{dm}} \nabla_e w_{ij}$$

Learning vs. Inference

- ▶ Boltzmann machine **learning** requires **inference**.


$$\nabla_e w_{ij} = \text{Cov}_d(x_i, h_j) - \text{Cov}_m(x_i, h_j)$$

- ▶ *What is the covariance between x_i and h_j with the current θ ?*
 - ▶ NP-Hard problem even in the case of RBMs (Long&Servedio, 2010)
 - ▶ Monte Carlo approximation with persistent MCMC

$$\text{Cov}_m(x_i, h_j) \approx \left(\frac{1}{N} \sum_{n=1}^N x_i^{(n)} h_j^{(n)} \right) - \left(\frac{1}{N} \sum_{n=1}^N x_i^{(n)} \right) \left(\frac{1}{N} \sum_{n=1}^N h_j^{(n)} \right)$$

- ▶ Gibbs sampling



Learning vs. Inference: Vicious Cycle




Failed **inference** (sampling) breaks **learning**

→ *Good MCMC sampler is needed!*

Inference: Better MCMC Sampler



- ▶ MCMC with a *local* jump cannot easily escape an isolated mode




Parallel Tempering


- ▶ Parallel chains between P_0 and P_∞
- ▶ Jump via tempered chains
- ▶ Better exploration of the state space

From an RBM to a *deeper* neural network..


Deep Belief Network
(Pretrained MLP)



Deep Boltzmann Machine



Deep Boltzmann Machines



► *Undirected* Hierarchical Model

► Negative Energy

$$\begin{aligned} -E(\mathbf{x}, \mathbf{h} \mid \theta) = & \mathbf{b}^\top \mathbf{x} + \mathbf{c}_{[1]}^\top \mathbf{h}_{[1]} + \mathbf{x}^\top \mathbf{W} \mathbf{h}_{[1]} \\ & + \sum_{l=2}^L \left(\mathbf{c}_{[l]}^\top \mathbf{h}_{[l]} + \mathbf{h}_{[l-1]}^\top \mathbf{U}_{[l-1]} \mathbf{h}_{[l]} \right) \end{aligned}$$

- The further away a layer from \mathbf{x} , the more abstract concept the layer learns
- Hierarchical representation with both bottom-up and top-down signals

Learning: Depressing Observation

Observation: Lack of Structures in Deeper Hidden Layers


Which direction does learning move toward? – matching **data** and **model** statistics

$$\frac{\partial \mathcal{L}(\theta)}{\partial u_{ij}^{[l]}} \propto \left\langle h_i^{[l]} h_j^{[l+1]} \right\rangle_{p(\mathbf{h}|\mathbf{v},\theta)p_D(\mathbf{v})} - \left\langle h_i^{[l]} h_j^{[l+1]} \right\rangle_{p(\mathbf{v},\mathbf{h}|\theta)}$$

What happens if $p(\mathbf{h} | \mathbf{v}, \theta)$ does not have *any* structure?

- ▶ Learning will *not* utilize deeper layers easily
- ▶ Especially severe at the initial stage of learning

Learning: Hierarchical structure *borrowed* from DBN



Stage 1 Recursively train a stack of RBMs to get $Q(\mathbf{h}_- | \mathbf{x})$

Stage 2 Train a large RBM \iff Maximize the variational lower-bound of DBM

$$\mathbb{E}_{D(\mathbf{v})} \left[\log p(\mathbf{v}^{(n)} | \boldsymbol{\theta}) \right] \geq \mathbb{E}_{D(\mathbf{v}) Q(\mathbf{h}_-)} \left[\log \sum_{\mathbf{h}_+} e^{\{-E(\mathbf{v}^{(n)}, \mathbf{h}_-, \mathbf{h}_+)\}} \right] + \mathcal{H}(Q) - \log Z(\boldsymbol{\theta})$$

Q: Have I worked on anything other than Boltzmann machines?

Unsupervised Learning: Encoder-Decoder Perspective

- Sparse coding:

Encoder $\mathbf{h} = \arg \min_{\mathbf{h}} \|\mathbf{x} - \mathbf{W}^T \mathbf{h}\| + \lambda \Omega(\mathbf{h})$

Decoder $\mathbf{x} = \mathbf{W}^T \mathbf{h}$

- Probabilistic PCA:

Encoder $\mathbb{E}[\mathbf{h}] = (\mathbf{W}^T \mathbf{W} + \sigma^2 \mathbf{I})^{-1} \mathbf{W}^T \mathbf{x}$

Decoder $\mathbb{E}[\mathbf{x}] = \mathbf{W}^T \mathbf{h}$

- RBM:


Encoder $\mathbb{E}[\mathbf{h}] = \sigma(\mathbf{W}\mathbf{x} + \mathbf{c})$

Decoder $\mathbb{E}[\mathbf{x}] = \sigma(\mathbf{W}^T \mathbf{h} + \mathbf{b})$

- DBM:

Encoder $\mu^{[l]} \leftarrow \sigma(\mathbf{U}_{[l]}^T \mu^{[l+1]} + \mathbf{U}_{[l-1]} \mu^{[l-1]} + \mathbf{c}^{[l]}),$
 $\mathbb{E}[\mathbf{h}^{[l]}] \approx \mu^{[l]}$


Decoder $\mathbb{E}[\mathbf{x}] = \sigma(\mathbf{W}^T \mathbf{h}^{[1]} + \mathbf{b})$



Denoising Autoencoder: Explicit Sparsification

Sparse Denoising Autoencoder


- ▶ Encoder $\mathbf{h} = f(\mathbf{x}) : \mathbb{P} \rightarrow \mathbb{Q}$
- ▶ Decoder $\tilde{\mathbf{x}} = g(\mathbf{h}) : \mathbb{Q} \rightarrow \mathbb{P}$



$$\mathbb{P} = \left\{ \mathbf{x} \in \mathbb{R}^p \mid \exists \mathbf{x}^{(n)} \in D, \|\mathbf{x} - \mathbf{x}^{(n)}\|_2^2 \leq \epsilon \right\}$$

$$\mathbb{Q} \approx \left\{ \mathbf{h} = f(\mathbf{x}) \mid \mathbf{x} \in \mathbb{P}, \|\mathbb{E}_{\mathbf{x} \in \mathbb{P}} [h_j] - \rho\|_2^2 = 0 \right\}$$

What do we do with $\mathbf{x} \notin \mathbb{P}$?



1. Encode: $\mathbf{h} = f(\mathbf{x})$
2. **Sparsify**: $\tilde{\mathbf{h}} = R(\mathbf{h})$
3. Decode: $\tilde{\mathbf{x}} = g(\tilde{\mathbf{h}})$

And beyond..

- ▶ Theoretical understanding beyond universal approximator properties
- ▶ Deep learning for long sequences
- ▶ Deep learning for $p \gg n$ and $n \rightarrow 1$
- ▶ New models that tackles learning and inference directly