



Kourosh Davoudi
kourosh@uoit.ca

Ensample Techniques

CSCI 4150U: Data Mining


Learning Outcome

- What is the **Nearest Neighbor Classifier**?
 - Learn the ideas
 - Know the issues
- What is the **Naïve Bayes** classifier
 - Learn the main ideas
 - Explain are the issues and considerations
- What is **Bayesian Belief Network**?
- What are the **Support Vector Machines**?
 - Understand the main ideas
- What are **ensemble** approaches?
 - Learn the ideas and different approaches

Ensemble Methods

- Construct **a set of classifiers** from the training data
- Predict class label of test records by combining the **predictions** made by **multiple classifiers**

General Approach



Bagging

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

- Sampling with replacement

Original Data	1	2	3	4	5	6	7	8	9	10
Bagging (Round 1)	7	8	10	8	2	5	10	10	5	9
Bagging (Round 2)	1	4	9	1	2	3	2	7	3	2
Bagging (Round 3)	1	8	5	10	5	5	9	6	3	7

- Build classifier on each **bootstrap sample**
- Each data instance has probability $1 - (1 - 1/n)^n$ of being selected as part of the bootstrap sample

At least once



Bagging Algorithm

Algorithm 5.6 Bagging Algorithm

- 1: Let k be the number of bootstrap samples.
 - 2: for $i = 1$ to k do
 - 3: Create a bootstrap sample of size n , D_i .
 - 4: Train a base classifier C_i on the bootstrap sample D_i .
 - 5: end for
 - 6: $C^*(x) = \arg \max_y \sum_i \delta(C_i(x) = y)$, $\{\delta(\cdot) = 1$ if its argument is true, and 0 otherwise. $\}$
-


Bagging Example

- Consider 1-dimensional data set:

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

- Classifier is a **decision stump**
 - Decision rule: $x \leq k$ versus $x > k$
 - Split point k is chosen based on entropy
 - Use the majority as the leaf label



Bagging Example

Bagging Round 1:

x	0.1	0.2	0.2	0.3	0.4	0.4	0.5	0.6	0.9	0.9
y	1	1	1	1	-1	-1	-1	-1	1	1

$x \leq 0.35 \rightarrow y = 1$

$x > 0.35 \rightarrow y = -1$

Bagging Example

Bagging Round 1:

x	0.1	0.2	0.2	0.3	0.4	0.4	0.5	0.6	0.9	0.9
y	1	1	1	1	-1	-1	-1	-1	1	1

$x \leq 0.35 \rightarrow y = 1$
 $x > 0.35 \rightarrow y = -1$

Bagging Round 2:

x	0.1	0.2	0.3	0.4	0.5	0.5	0.9	1	1	1
y	1	1	1	-1	-1	-1	1	1	1	1

$x \leq 0.7 \rightarrow y = 1$
 $x > 0.7 \rightarrow y = -1$

Bagging Round 3:

x	0.1	0.2	0.3	0.4	0.4	0.5	0.7	0.7	0.8	0.9
y	1	1	1	-1	-1	-1	-1	-1	1	1

$x \leq 0.35 \rightarrow y = 1$
 $x > 0.35 \rightarrow y = -1$

Bagging Round 4:

x	0.1	0.1	0.2	0.4	0.4	0.5	0.5	0.7	0.8	0.9
y	1	1	1	-1	-1	-1	-1	-1	1	1

$x \leq 0.3 \rightarrow y = 1$
 $x > 0.3 \rightarrow y = -1$

Bagging Round 5:

x	0.1	0.1	0.2	0.5	0.6	0.6	0.6	1	1	1
y	1	1	1	-1	-1	-1	-1	1	1	1

$x \leq 0.35 \rightarrow y = 1$
 $x > 0.35 \rightarrow y = -1$

Bagging Example

Bagging Round 6:

x	0.2	0.4	0.5	0.6	0.7	0.7	0.7	0.8	0.9	1
y	1	-1	-1	-1	-1	-1	-1	1	1	1

$x \leq 0.75 \rightarrow y = -1$
 $x > 0.75 \rightarrow y = 1$

Bagging Round 7:

x	0.1	0.4	0.4	0.6	0.7	0.8	0.9	0.9	0.9	1
y	1	-1	-1	-1	-1	1	1	1	1	1

$x \leq 0.75 \rightarrow y = -1$
 $x > 0.75 \rightarrow y = 1$

Bagging Round 8:

x	0.1	0.2	0.5	0.5	0.5	0.7	0.7	0.8	0.9	1
y	1	1	-1	-1	-1	-1	-1	1	1	1

$x \leq 0.75 \rightarrow y = -1$
 $x > 0.75 \rightarrow y = 1$

Bagging Round 9:

x	0.1	0.3	0.4	0.4	0.6	0.7	0.7	0.8	1	1
y	1	1	-1	-1	-1	-1	-1	1	1	1

$x \leq 0.75 \rightarrow y = -1$
 $x > 0.75 \rightarrow y = 1$

Bagging Round 10:


x	0.1	0.1	0.1	0.1	0.3	0.3	0.8	0.8	0.9	0.9
y	1	1	1	1	1	1	1	1	1	1

$x \leq 0.05 \rightarrow y = 1$
 $x > 0.05 \rightarrow y = 1$

Bagging Example

- Summary of Training sets:

Round	Split Point	Left Class	Right Class
1	0.35	1	-1
2	0.7	1	1
3	0.35	1	-1
4	0.3	1	-1
5	0.35	1	-1
6	0.75	-1	1
7	0.75	-1	1
8	0.75	-1	1
9	0.75	-1	1
10	0.05	1	1



Original Data:

Bagging Example

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

- Assume test set is the same as the original data
- Use majority vote to determine class of ensemble classifier

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	1	1	1	-1	-1	-1	-1	-1	-1	-1
2	1	1	1	1	1	1	1	1	1	1
3	1	1	1	-1	-1	-1	-1	-1	-1	-1
4	1	1	1	-1	-1	-1	-1	-1	-1	-1
5	1	1	1	-1	-1	-1	-1	-1	-1	-1
6	-1	-1	-1	-1	-1	-1	-1	1	1	1
7	-1	-1	-1	-1	-1	-1	-1	1	1	1
8	-1	-1	-1	-1	-1	-1	-1	1	1	1
9	-1	-1	-1	-1	-1	-1	-1	1	1	1
10	1	1	1	1	1	1	1	1	1	1
Sum	2	2	2	-6	-6	-6	-6	2	2	2
Sign	1	1	1	-1	-1	-1	-1	1	1	1

Predicted
Class



Boosting

- An iterative procedure to adaptively **change distribution of training data** by focusing more on previously misclassified records:
 - Initially, all N records are assigned equal weights
 - Unlike bagging, weights may change at the end of each boosting round

Boosting

- Records that are wrongly classified will have their **weights** increased
- Records that are classified correctly will have their **weights** decreased

Original Data	1	2	3	4	5	6	7	8	9	10
Boosting (Round 1)	7	3	2	8	7	9	4	10	6	3
Boosting (Round 2)	5	4	9	4	2	5	1	7	4	2
Boosting (Round 3)	4	4	8	10	4	5	4	6	3	4

- Example 4 is hard to classify
- Its **weight** is increased, therefore it is more likely to be chosen again in subsequent rounds

AdaBoost


- Base classifiers: C_1, C_2, \dots, C_T

- **Error rate** of classifier i :

$$\varepsilon_i = \frac{1}{N} \sum_{j=1}^N w_j \delta(C_i(x_j) \neq y_j)$$

- **Importance** of a classifier:

$$\alpha_i = \frac{1}{2} \ln \left(\frac{1 - \varepsilon_i}{\varepsilon_i} \right)$$



How to update weights in AdaBoost?

- Weight update:

$$w_j^{(i+1)} = \frac{w_j^{(i)}}{Z_i} \begin{cases} \exp^{-\alpha_i} & \text{if } C_i(x_j) = y_j \\ \exp^{\alpha_i} & \text{if } C_i(x_j) \neq y_j \end{cases}$$

The weight w_j decreases if x_j is classified correctly

The weight w_j increases if x_j is classified incorrectly

where Z_i is the normalization factor: $Z_i = \sum_j w_j^{(i)}$

AdaBoost Algorithm

- If any intermediate rounds produce **error rate higher** than 50%, the weights are reverted back to $1/n$ and the resampling procedure is repeated
- **Classification:**

$$C^*(x) = \operatorname{argmax}_y \sum_{i=1}^T \alpha_i \delta(C_i(x) = y)$$

AdaBoost Algorithm

Algorithm 5.7 AdaBoost Algorithm

```
1:  $w = \{w_j = 1/n \mid j = 1, 2, \dots, n\}$ .    {Initialize the weights for all  $n$  instances.}
2: Let  $k$  be the number of boosting rounds.
3: for  $i = 1$  to  $k$  do
4:   Create training set  $D_i$  by sampling (with replacement) from  $D$  according to  $w$ .
5:   Train a base classifier  $C_i$  on  $D_i$ .
6:   Apply  $C_i$  to all instances in the original training set,  $D$ .
7:    $\epsilon_i = \frac{1}{n} [\sum_j w_j \delta(C_i(x_j) \neq y_j)]$     {Calculate the weighted error}
8:   if  $\epsilon_i > 0.5$  then
9:      $w = \{w_j = 1/n \mid j = 1, 2, \dots, n\}$ .    {Reset the weights for all  $n$  instances.}
10:    Go back to Step 4.
11:  end if
12:   $\alpha_i = \frac{1}{2} \ln \frac{1-\epsilon_i}{\epsilon_i}$ .
13:  Update the weight of each instance according to equation  $w_j^{(i+1)} = \frac{w_j^{(i)}}{Z_i} \begin{cases} \exp^{-\alpha_i} & \text{if } C_i(x_j) = y_j \\ \exp^{\alpha_i} & \text{if } C_i(x_j) \neq y_j \end{cases}$ 
14: end for
15:  $C^*(x) = \arg \max_y \sum_{j=1}^T \alpha_j \delta(C_j(x) = y)$ .
```


AdaBoost Example

- Consider 1-dimensional data set:

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

- Classifier is a decision stump
 - Decision rule: $x \leq k$ versus $x > k$
 - Split point k is chosen based on entropy



AdaBoost Example

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

Weights

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1

AdaBoost Example

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

Weights

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1

Boosting Round 1:

x	0.1	0.4	0.5	0.6	0.6	0.7	0.7	0.7	0.8	1
y	1	-1	-1	-1	-1	-1	-1	-1	1	1

AdaBoost Example

$$w_j^{(i+1)} = \frac{w_j^{(i)}}{Z_i} \begin{cases} \exp^{-\alpha_i} & \text{if } C_i(x_j) = y_j \\ \exp^{\alpha_i} & \text{if } C_i(x_j) \neq y_j \end{cases}$$

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

Weights

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
2	0.311	0.311	0.311	0.01	0.01	0.01	0.01	0.01	0.01	0.01

Boosting Round 1:

x	0.1	0.4	0.5	0.6	0.6	0.7	0.7	0.7	0.8	1
y	1	-1	-1	-1	-1	-1	-1	-1	1	1

Boosting Round 2:

x	0.1	0.1	0.2	0.2	0.2	0.2	0.3	0.3	0.3	0.3
y	1	1	1	1	1	1	1	1	1	1

AdaBoost Example

$$w_j^{(i+1)} = \frac{w_j^{(i)}}{Z_i} \begin{cases} \exp^{-\alpha_i} & \text{if } C_i(x_j) = y_j \\ \exp^{\alpha_i} & \text{if } C_i(x_j) \neq y_j \end{cases}$$

Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1

Weights

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
2	0.311	0.311	0.311	0.01	0.01	0.01	0.01	0.01	0.01	0.01
3	0.029	0.029	0.029	0.228	0.228	0.228	0.228	0.009	0.009	0.009

Boosting Round 1:

x	0.1	0.4	0.5	0.6	0.6	0.7	0.7	0.7	0.8	1
y	1	-1	-1	-1	-1	-1	-1	-1	1	1

Boosting Round 2:

x	0.1	0.1	0.2	0.2	0.2	0.2	0.3	0.3	0.3	0.3
y	1	1	1	1	1	1	1	1	1	1

Boosting Round 3:

x	0.2	0.2	0.4	0.4	0.4	0.4	0.5	0.6	0.6	0.7
y	1	1	-1	-1	-1	-1	-1	-1	-1	-1

AdaBoost Example

- Training sets for the first 3 boosting rounds:

Boosting Round 1:

x	0.1	0.4	0.5	0.6	0.6	0.7	0.7	0.7	0.8	1
y	1	-1	-1	-1	-1	-1	-1	-1	1	1

Boosting Round 2:

x	0.1	0.1	0.2	0.2	0.2	0.2	0.3	0.3	0.3	0.3
y	1	1	1	1	1	1	1	1	1	1

Boosting Round 3:

x	0.2	0.2	0.4	0.4	0.4	0.4	0.5	0.6	0.6	0.7
y	1	1	-1	-1	-1	-1	-1	-1	-1	-1

- Summary:

Round	Split Point	Left Class	Right Class	alpha
1	0.75	-1	1	1.738
2	0.05	1	1	2.7784
3	0.3	1	-1	4.1195

AdaBoost Example

- Weights

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
2	0.311	0.311	0.311	0.01	0.01	0.01	0.01	0.01	0.01	0.01
3	0.029	0.029	0.029	0.228	0.228	0.228	0.228	0.009	0.009	0.009

- Classification

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	-1	-1	-1	-1	-1	-1	-1	1	1	1
2	1	1	1	1	1	1	1	1	1	1
3	1	1	1	-1	-1	-1	-1	-1	-1	-1
Sum	5.16	5.16	5.16	-3.08	-3.08	-3.08	-3.08	0.397	0.397	0.397
Predicted Class	1	1	1	-1	-1	-1	-1	1	1	1

$$C^*(x) = \operatorname{argmax}_y \sum_{i=1}^T \alpha_i \delta(C_i(x) = y)$$

AdaBoost Example

- Weights

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
2	0.311	0.311	0.311	0.01	0.01	0.01	0.01	0.01	0.01	0.01
3	0.029	0.029	0.029	0.228	0.228	0.228	0.228	0.009	0.009	0.009

- Classification

Round	x=0.1	x=0.2	x=0.3	x=0.4	x=0.5	x=0.6	x=0.7	x=0.8	x=0.9	x=1.0
1	-1	-1	-1	-1	-1	-1	-1	1	1	1
2	1	1	1	1	1	1	1	1	1	1
3	1	1	1	-1	-1	-1	-1	-1	-1	-1
Sum	5.16	5.16	5.16	-3.08	-3.08	-3.08	-3.08	0.397	0.397	0.397
Predicted Class	1	1	1	-1	-1	-1	-1	1	1	1



Original Data:

x	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1
y	1	1	1	-1	-1	-1	-1	1	1	1