

# Pandas II - working with data

Last time, we met some of the basic data structures in pandas.

Basic pandas objects:

- Index
- Series
- Data Frame

We also learned how these three things are related. Namely, we can think of a pandas `DataFrame` as being composed of several *named columns*, each of which is like a `Series`, and a special `Index` column along the left-hand side.

In this tutorial, we'll learn about

- some common methods that pandas objects have – the "verbs" that make them do useful things
- accessing row/column subsets of data
- working with grouped data: aggregation and pivot tables

## Make a data frame to play with

Let's build a little data frame and take a look at it to remind ourselves of this structure. We'll build one similar to a data frame we played with last time.

It will have 5 columns

First, import `pandas` because of course, and `numpy` in order to simulate some data.

```
In [1]: import pandas as pd
import numpy as np      # to make some simulated data
```

Now we can make the data frame. It will have 4 variables of cardiovascular data for a number of patients that we can specify. Because a pandas `DataFrame` has that special index column, we'll just use it to correspond to "patient ID" instead of making a fifth variable.

```
In [3]: num_patients = 10    # specify the number of patients

# make some simulated data
sys_bp = np.int64(125 + 5*np.random.randn(num_patients,)) # creates 10 integers moving
dia_bp = np.int64(80 + 5*np.random.randn(num_patients,))
b_oxy = np.round(98.5 + 0.3*np.random.randn(num_patients,)), 2)
pulse = np.int64(65 + 2*np.random.randn(num_patients,))

# Make a dictionary with a "key" for each variable name, and
# the "values" being the num_patients long data vectors
df_dict = {'systolic BP' : sys_bp,
           'diastolic BP' : dia_bp,
           'blood oxygenation' : b_oxy,
```

```

        'pulse rate' : pulse
    }

our_df = pd.DataFrame(df_dict)    # Now make a data frame out of the dictionary

```

And now lets look at it.

In [4]:

```
our_df
```

Out[4]:

	systolic BP	diastolic BP	blood oxygenation	pulse rate
0	123	81	98.54	67
1	126	88	98.44	63
2	127	89	98.63	61
3	127	73	98.49	65
4	118	75	98.74	67
5	123	74	98.85	64
6	133	73	98.09	65
7	125	78	98.60	66
8	129	84	98.15	62
9	127	77	98.42	66

Now we can see the nice structure of the `DataFrame` object. We have four columns corresponding to our measurement variables, and each row is an "observation" which, in the case, corresponds to an individual patient.

To appreciate some of the features of a pandas `DataFrame`, let's compare it with a numpy `Array` holding the same information. (Which we can do because we're only dealing with numbers here - one of the main features of a pandas data frame is that it can hold non-numeric information too).

In [5]:

```
our_array = np.transpose(np.vstack((sys_bp, dia_bp, b_oxy, pulse)))
our_array
```

Out[5]:

```
array([[123. ,  81. ,  98.54,  67. ],
       [126. ,  88. ,  98.44,  63. ],
       [127. ,  89. ,  98.63,  61. ],
       [127. ,  73. ,  98.49,  65. ],
       [118. ,  75. ,  98.74,  67. ],
       [123. ,  74. ,  98.85,  64. ],
       [133. ,  73. ,  98.09,  65. ],
       [125. ,  78. ,  98.6 ,  66. ],
       [129. ,  84. ,  98.15,  62. ],
       [127. ,  77. ,  98.42,  66. ]])
```

We can see here that our array, `our_array`, contains exactly the same information as our dataframe, `our_df`. There are 3 main differences between the two:

- they have different verbs – things they know how to do

- we have more ways to access the information in a data frame
- the data frame could contain non-numeric information (e.g. gender) if we wanted

(Also notice that the data frame is just prettier when printed than the numpy array)

## Verbs

Let's look at some verbs. Intuitively, it seems like the should both know how to take a mean. Let's see.

```
In [6]: our_array.mean()
```

```
Out[6]: 92.02375
```

So the numpy array does indeed know how to take the mean of itself, but it takes the mean of the entire array by default, which is not very useful in this case. If we want the mean of each variable, we have to specify that we want the means of the columns (i.e. row-wise means).

```
In [7]: our_array.mean(axis=0)
```

```
Out[7]: array([125.8 ,  79.2 ,  98.495,  64.6  ])
```

But look what happens if we ask for the mean of our data frame:

```
In [8]: our_df.mean()
```

```
Out[8]: systolic BP      125.800
diastolic BP      79.200
blood oxygenation  98.495
pulse rate        64.600
dtype: float64
```

Visually, that is much more useful! We have the mean of each of our variables, nicely labeled by the variable name.

Data frames can also `describe()` themselves.

```
In [9]: our_df.describe()
```

```
Out[9]:
```

	systolic BP	diastolic BP	blood oxygenation	pulse rate
<b>count</b>	10.000000	10.000000	10.000000	10.000000
<b>mean</b>	125.800000	79.200000	98.495000	64.600000
<b>std</b>	3.994441	6.033241	0.237826	2.065591
<b>min</b>	118.000000	73.000000	98.090000	61.000000
<b>25%</b>	123.500000	74.250000	98.425000	63.250000
<b>50%</b>	126.500000	77.500000	98.515000	65.000000
<b>75%</b>	127.000000	83.250000	98.622500	66.000000

	systolic BP	diastolic BP	blood oxygenation	pulse rate
max	133.000000	89.000000	98.850000	67.000000

Gives us a nice summary table of the data in our data frame.

Numpy arrays don't know how to do this.


```
In [10]: our_array.describe()
```

```
-----
AttributeError                                Traceback (most recent call last)
~\AppData\Local\Temp\ipykernel_13084\94104930.py in <module>
----> 1 our_array.describe()
```


**AttributeError:** 'numpy.ndarray' object has no attribute 'describe'

Data frames can also make histograms and boxplots of themselves. They aren't publication quality, but super useful for getting a feel for our data.

```
In [11]: our_df.hist();
```



```
In [12]: our_df.boxplot();
```



For a complete listing of what our data frame knows how to do, we can type `our_df.` and then hit the tab key.

```
In [ ]: our_df.
```

Let's return to the `mean()` function, and see what, exactly, it is returning. We can do this by assigning the output to a variable and looking at its type.

```
In [13]: our_means = our_df.mean()  
our_means # the names act as indexes
```

```
Out[13]: systolic BP      125.800  
diastolic BP      79.200  
blood oxygenation  98.495  
pulse rate        64.600  
dtype: float64
```

```
In [14]: type(our_means)
```

```
Out[14]: pandas.core.series.Series
```

So it is a pandas series, but, rather than the index being 0, 1, 2, 3, the *index values are actually the names of our variables*.

If we want the mean pulse rate, we *can actually ask for it by name!*

```
In [15]: our_means['pulse rate']
```

```
Out[15]: 64.6
```

This introduces another key feature of pandas: **you can access data by name**.

## Accessing data

Accessing data by name is kind of a big deal. It makes code more readable and faster and easier to write.

So, for example, let's say we wanted the mean pulse rate for our patients. Using numpy, we would have to remember or figure out which column of our numpy array was pulse rate. And we'd have to remember that Python indexes start at 0. *And* we'd have to remember that we have to tell numpy to take the mean down the columns explicitly. Ha.

So our code might look something like...

```
In [16]: np_style_means = our_array.mean(axis=0)  
pulse_mean = np_style_means[3]  
pulse_mean
```

```
Out[16]: 64.6
```

Compare that to doing it the pandas way:

```
In [17]: our_means = our_df.mean()
our_means['pulse rate']
```

Out[17]: 64.6

The pandas way makes it very clear what we are doing! People like things to have names and, in pandas, things have names.

## Accessing data using square brackets

Let's look at our little data frame again.

```
In [18]: our_df
```

```
Out[18]:
```

	systolic BP	diastolic BP	blood oxygenation	pulse rate
0	123	81	98.54	67
1	126	88	98.44	63
2	127	89	98.63	61
3	127	73	98.49	65
4	118	75	98.74	67
5	123	74	98.85	64
6	133	73	98.09	65
7	125	78	98.60	66
8	129	84	98.15	62
9	127	77	98.42	66

We can grab a column (variable) by name if we want:

```
In [19]: our_df['pulse rate']
```

```
Out[19]:
```

0	67
1	63
2	61
3	65
4	67
5	64
6	65
7	66
8	62
9	66

Name: pulse rate, dtype: int64

Doing this creates another `DataFrame` (or `Series`), so it knows how to do stuff to. This allows us to do things like, for example, compute the mean pulse rate in one step instead of two. Like this:

```
In [20]: our_df['pulse rate'].mean()    # creates a series, then make it compute its own mean
```

```
Out[20]: 64.6
```

We can grab as many columns as we want by using a list of column names.

```
In [21]: needed_cols = ['diastolic BP', 'systolic BP']    # make a list
         our_df[needed_cols]                               # use the list to grab columns
```

```
Out[21]:
```

	<b>diastolic BP</b>	<b>systolic BP</b>
<b>0</b>	81	123
<b>1</b>	88	126
<b>2</b>	89	127
<b>3</b>	73	127
<b>4</b>	75	118
<b>5</b>	74	123
<b>6</b>	73	133
<b>7</b>	78	125
<b>8</b>	84	129
<b>9</b>	77	127

We could also do this in one step.

```
In [22]: our_df[['diastolic BP', 'systolic BP']]    # the inner brackets define our list
```

```
Out[22]:
```

	<b>diastolic BP</b>	<b>systolic BP</b>
<b>0</b>	81	123
<b>1</b>	88	126
<b>2</b>	89	127
<b>3</b>	73	127
<b>4</b>	75	118
<b>5</b>	74	123
<b>6</b>	73	133
<b>7</b>	78	125
<b>8</b>	84	129
<b>9</b>	77	127

(although the double brackets might look a little confusing at first)

## Getting row and row/column combinations of data: "indexing"

**Terminology Warning!** "Indexing" is a general term which means "accessing data by location". In pandas, as we have seen, objects like DataFrames also have an "index" which is a special column of row identifiers. So, in pandas, we can index data using column names, row names (indexing using the index), or both. (We can also index into pandas data frames as if they were numpy arrays, which sometimes comes in handy.)

## Changing the index to make (row) indexing more intuitive

Speaking of indexes, it's a little weird to have our patient IDs start at "0". Both because "patient zero" has a special meaning and also because it's just not intuitive to number a sequence of actual things starting at "0".

Fortunately, pandas `DataFrame` (and `Series`) objects allow you to customize their index column fairly easily.

Let's set the index to start at 1 rather than 0:

```
In [23]: my_ind = np.linspace(1, 10, 10) # make a sequence from 1 to 10
          my_ind = np.int64(my_ind)      # change it from decimal to integer (not really necess
          our_df.index = my_ind
```

```
In [24]: our_df
```

```
Out[24]:
```

	systolic BP	diastolic BP	blood oxygenation	pulse rate
1	123	81	98.54	67
2	126	88	98.44	63
3	127	89	98.63	61
4	127	73	98.49	65
5	118	75	98.74	67
6	123	74	98.85	64
7	133	73	98.09	65
8	125	78	98.60	66
9	129	84	98.15	62
10	127	77	98.42	66

## Accessing data using `pd.DataFrame.loc[]`

In the section above, we saw that you can get columns of data out of a data frame using square brackets `[]`. Pandas data frames also know how to give you subsets of rows or row/column combinations.

The primary method for accessing specific bits of data from a pandas data frame is with the `loc[]` verb. It provides an easy way to get rows of data based upon the index column. In other words, `loc[]` is the way we use the data frame index as an index!



So this will give us the data for patient number 3:

```
In [25]: our_df.loc[3] # 3 is a name, not a position
```

```
Out[25]: systolic BP      127.00
          diastolic BP    89.00
          blood oxygenation 98.63
          pulse rate      61.00
          Name: 3, dtype: float64
```

**Note!** The above call did **not** behave like a Python or numpy index! If it had, we would have gotten the data for patient number 4 because Python and numpy use *zero based indexing*.

But using the `loc[]` function gives us back the row "named" 3. We literally get what we asked for! Yay!

We can also *slice* out rows in chunks:

```
In [26]: our_df.loc[3:6]
```

```
Out[26]:
```

	systolic BP	diastolic BP	blood oxygenation	pulse rate
3	127	89	98.63	61
4	127	73	98.49	65
5	118	75	98.74	67
6	123	74	98.85	64

Which, again, gives us what we asked for without having to worry about the zero-based business.

But `.loc[]` also allows us to get specific columns too. Like:

```
In [27]: our_df.loc[3:6, 'blood oxygenation']
```

```
Out[27]: 3    98.63
          4    98.49
          5    98.74
          6    98.85
          Name: blood oxygenation, dtype: float64
```

For a single column, or:

```
In [28]: our_df.loc[3:6, 'systolic BP': 'blood oxygenation']
```

```
Out[28]:
```

	systolic BP	diastolic BP	blood oxygenation
3	127	89	98.63
4	127	73	98.49
5	118	75	98.74
6	123	74	98.85

for multiple columns.

In summary, there are 3 main ways to get chunks of data out of a data frame "by name".

- square brackets (only) gives us columns, e.g. `our_df['systolic BP']`
- `loc[]` with one argument gives us rows, e.g. `our_df.loc[3]`
- `loc[]` with two arguments gives us row-column combinations, e.g. `our_df.loc[3, 'systolic BP']`

Additionally, with `loc[]`, we can specify index ranges for the rows or columns or both, e.g. `new_df.loc[3:6, 'systolic BP': 'blood oxygenation']`

One final thing about using `loc[]` is that the index column in a `DataFrame` doesn't have to be numbers. It can be date/time strings (as we'll see next time), or just plain strings (as we've seen above with `Series` objects).

Let's look at a summary of our data using the `describe()` method:

```
In [29]: our_sum = our_df.describe()
         our_sum
```

```
Out[29]:
```

	systolic BP	diastolic BP	blood oxygenation	pulse rate
<b>count</b>	10.000000	10.000000	10.000000	10.000000
<b>mean</b>	125.800000	79.200000	98.495000	64.600000
<b>std</b>	3.994441	6.033241	0.237826	2.065591
<b>min</b>	118.000000	73.000000	98.090000	61.000000
<b>25%</b>	123.500000	74.250000	98.425000	63.250000
<b>50%</b>	126.500000	77.500000	98.515000	65.000000
<b>75%</b>	127.000000	83.250000	98.622500	66.000000
<b>max</b>	133.000000	89.000000	98.850000	67.000000

This looks suspiciously like a data frame except the index column looks like they're... er... not indexes. Let's see.

```
In [30]: type(our_sum)
```

```
Out[30]: pandas.core.frame.DataFrame
```

Yep, it's a data frame! But let's see if that index column actually works:

```
In [31]: our_sum.loc['mean']
```

```
Out[31]: systolic BP      125.800
         diastolic BP    79.200
         blood oxygenation 98.495
         pulse rate      64.600
         Name: mean, dtype: float64
```

Note that, with a `Series` object, we use square brackets (only) to get rows. With a `DataFrame`, square brackets (only) are used to get columns. It won't work for `DataFrame` objects:

In [32]:

```
our_sum['mean']
```

```
-----
KeyError                                Traceback (most recent call last)
~\anaconda3\lib\site-packages\pandas\core\indexes\base.py in get_loc(self, key, method,
tolerance)
    3360         try:
-> 3361             return self._engine.get_loc(casted_key)
    3362         except KeyError as err:

~\anaconda3\lib\site-packages\pandas\_libs\index.pyx in pandas._libs.index.IndexEngine.g
et_loc()

~\anaconda3\lib\site-packages\pandas\_libs\index.pyx in pandas._libs.index.IndexEngine.g
et_loc()

pandas\_libs\hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_
item()

pandas\_libs\hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_
item()

KeyError: 'mean'
```

The above exception was the direct cause of the following exception:

```
KeyError                                Traceback (most recent call last)
~\AppData\Local\Temp\ipykernel_13084\658435288.py in <module>
----> 1 our_sum['mean']

~\anaconda3\lib\site-packages\pandas\core\frame.py in __getitem__(self, key)
    3456         if self.columns.nlevels > 1:
    3457             return self._getitem_multilevel(key)
-> 3458         indexer = self.columns.get_loc(key)
    3459         if is_integer(indexer):
    3460             indexer = [indexer]

~\anaconda3\lib\site-packages\pandas\core\indexes\base.py in get_loc(self, key, method,
tolerance)
    3361             return self._engine.get_loc(casted_key)
    3362         except KeyError as err:
-> 3363             raise KeyError(key) from err
    3364
    3365         if is_scalar(key) and isna(key) and not self.hasnans:

KeyError: 'mean'
```

So, with a `DataFrame`, we have to use `.loc[]` to get rows.

And now we can slice out (get a range of) rows:

In [33]:

```
our_sum.loc['count':'std']
```

Out[33]:

```
systolic BP  diastolic BP  blood oxygenation  pulse rate
```

	<b>systolic BP</b>	<b>diastolic BP</b>	<b>blood oxygenation</b>	<b>pulse rate</b>
<b>count</b>	10.000000	10.000000	10.000000	10.000000
<b>mean</b>	125.800000	79.200000	98.495000	64.600000
<b>std</b>	3.994441	6.033241	0.237826	2.065591

Or rows and columns:

```
In [34]: our_sum.loc['count':'std', 'systolic BP':'diastolic BP']
```

```
Out[34]:
```

	<b>systolic BP</b>	<b>diastolic BP</b>
<b>count</b>	10.000000	10.000000
<b>mean</b>	125.800000	79.200000
<b>std</b>	3.994441	6.033241

## Accessing data using pd.DataFrame.iloc[]

Occasionally, you might want to treat a pandas `DataFrame` as a numpy `Array` and index into it using the *implicit* row and column indexes (which start as zero of course). So support this, pandas `DataFrame` objects also have an `iloc[]`.

Let's look at our data frame again:

```
In [35]: our_df
```

```
Out[35]:
```

	<b>systolic BP</b>	<b>diastolic BP</b>	<b>blood oxygenation</b>	<b>pulse rate</b>
<b>1</b>	123	81	98.54	67
<b>2</b>	126	88	98.44	63
<b>3</b>	127	89	98.63	61
<b>4</b>	127	73	98.49	65
<b>5</b>	118	75	98.74	67
<b>6</b>	123	74	98.85	64
<b>7</b>	133	73	98.09	65
<b>8</b>	125	78	98.60	66
<b>9</b>	129	84	98.15	62
<b>10</b>	127	77	98.42	66

And let's check its shape:

```
In [36]: our_df.shape
```

```
Out[36]: (10, 4)
```

At some level, then, Python considers this to be just a 10x4 array (like a numpy array). This is where `iloc[]` comes in; `iloc[]` will treat the data frame as though it were a numpy array – no names!

So let's index into `our_df` using `iloc[]`:

```
In [37]: our_df.iloc[3] # get the fourth row
```

```
Out[37]: systolic BP      127.00
          diastolic BP    73.00
          blood oxygenation 98.49
          pulse rate      65.00
          Name: 4, dtype: float64
```

And compare that to using `loc[]`:

```
In [38]: our_df.loc[3]
```

```
Out[38]: systolic BP      127.00
          diastolic BP    89.00
          blood oxygenation 98.63
          pulse rate      61.00
          Name: 3, dtype: float64
```

And of course you can slice out rows and columns:

```
In [39]: our_df.iloc[2:5, 0:2]
```

```
Out[39]:
```

	<b>systolic BP</b>	<b>diastolic BP</b>
<b>3</b>	127	89
<b>4</b>	127	73
<b>5</b>	118	75

Indexing using `iloc[]` is rarely needed on regular data frames (if you're using it, you should probably be working with a numpy `Array`).

It is, however, very handy for pulling data out of summary data tables (see below).

## Non-numerical information (categories or factors)

One of the huge benefits of pandas objects is that, unlike numpy arrays, they can contain categorical variables.

## Make another data frame to play with

Let's use tools we've learned to make a data frame that has both numerical and categorical variables.

First, we'll make the numerical data:

```
In [40]: num_patients = 20 # specify the number of patients
```

```
# make some simulated data with realistic numbers.
sys_bp = np.int64(125 + 5*np.random.randn(num_patients,))
dia_bp = np.int64(80 + 5*np.random.randn(num_patients,))
b_oxy = np.round(98.5 + 0.3*np.random.randn(num_patients,), 2)
pulse = np.int64(65 + 2*np.random.randn(num_patients,))
```

(Now we'll make them interesting – this will be clear later)

```
In [41]: sys_bp[0:10] = sys_bp[0:10] + 15
        dia_bp[0:10] = dia_bp[0:10] + 15
        sys_bp[0:5] = sys_bp[0:5] + 5
        dia_bp[0:5] = dia_bp[0:5] + 5
        sys_bp[10:15] = sys_bp[10:15] + 5
        dia_bp[10:15] = dia_bp[10:15] + 5
```

Now let's make a categorical variable indicating whether the patient is diabetic or not. We'll make the first half be diabetic.

```
In [42]: diabetic = pd.Series(['yes', 'no']) # make the short series
        diabetic = diabetic.repeat(num_patients/2) # repeat each over two cell's worth of
        diabetic = diabetic.reset_index(drop=True) # reset the series's index value
```

Now will make an "inner" gender variable.

```
In [43]: gender = pd.Series(['male', 'female']) # make the short series
        gender = gender.repeat(num_patients/4) # repeat each over one cell's wo
        gender = pd.concat([gender]*2, ignore_index=True) # stack or "concatenate" two copies
```

Now we'll make a dictionary containing all our data.

```
In [44]: # Make a dictionary with a "key" for each variable name, and
        # the "values" being the num_patients long data vectors
        df_dict = {'systolic BP' : sys_bp,
                   'diastolic BP' : dia_bp,
                   'blood oxygenation' : b_oxy,
                   'pulse rate' : pulse,
                   'gender': gender,
                   'diabetes': diabetic
                  }
```

And turn it into a data frame.

```
In [45]: new_df = pd.DataFrame(df_dict) # Now make a data frame out of the dictionary
```

Finally, let's up our game and make a more descriptive index column!

```
In [46]: basename = 'patient ' # make a "base" row name
        my_index = [] # make an empty list
        for i in range(1, num_patients+1) : # use a for loop to add
            my_index.append(basename + str(i)) # id numbers so the base name
```

Assign our new row names to the index of our data frame.

```
In [47]: new_df.index = my_index
```

Let's look at our creation!

```
In [48]: new_df
```

```
Out[48]:
```


	systolic BP	diastolic BP	blood oxygenation	pulse rate	gender	diabetes
<b>patient 1</b>	150	94	98.29	67	male	yes
<b>patient 2</b>	147	94	98.31	66	male	yes
<b>patient 3</b>	144	94	98.41	65	male	yes
<b>patient 4</b>	154	105	98.58	62	male	yes
<b>patient 5</b>	149	84	98.57	67	male	yes
<b>patient 6</b>	139	96	98.54	63	female	yes
<b>patient 7</b>	140	91	98.43	66	female	yes
<b>patient 8</b>	145	95	98.80	62	female	yes
<b>patient 9</b>	139	97	98.07	69	female	yes
<b>patient 10</b>	140	98	98.42	62	female	yes
<b>patient 11</b>	137	91	98.74	61	male	no
<b>patient 12</b>	129	90	99.24	62	male	no
<b>patient 13</b>	135	92	98.88	63	male	no
<b>patient 14</b>	131	79	98.25	65	male	no
<b>patient 15</b>	128	83	98.15	64	male	no
<b>patient 16</b>	126	84	98.04	67	female	no
<b>patient 17</b>	126	71	98.95	65	female	no
<b>patient 18</b>	134	81	98.09	65	female	no
<b>patient 19</b>	129	76	98.22	63	female	no
<b>patient 20</b>	115	84	98.09	64	female	no

## Looking at our data

Another really nice thing about pandas DataFrames is that they naturally lend themselves to interogation via Seaborn. So let's peek at some stuff.


```
In [49]: import seaborn as sns

sns.catplot(data=new_df, x='diabetes', y='systolic BP');
```




Okay, now let's go crazy and do a bunch of plots.

```
In [50]: sns.catplot(data=new_df, x='gender', y='systolic BP', hue='diabetes');
```




```
In [51]: sns.catplot(data=new_df, x='gender', y='pulse rate', hue='diabetes');
```





```
In [52]: sns.catplot(data=new_df, x='gender', y='diastolic BP', hue='diabetes', kind='bar');
```



## Computing within groups

Now that we have an idea of what's going on, let's look at how we could go about computing things like the mean systolic blood pressure in females vs. males, etc.

### Using the `groupby()` method

Data frames all have a `group_by()` method that, as the name implies, will group our data by a categorical variable. Let's try it.

```
In [53]: new_df.groupby('gender')
```

```
Out[53]: <pandas.core.groupby.generic.DataFrameGroupBy object at 0x000002224447C4C0>
```

So this gave us a `DataFrameGroupBy` object which, in and of itself, is very useful. However, *it knows how to do things!*

In general, `GroupBy` objects know how to do pretty much anything that regular `DataFrame` objects do. So, if we want the mean by gender, we can ask the `GroupBy` (for short) object to give us the mean:

```
In [54]: new_df.groupby('gender').mean()
```

```
Out[54]:
```

	systolic BP	diastolic BP	blood oxygenation	pulse rate
gender				
female	133.3	87.3	98.365	64.6
male	140.4	90.6	98.542	64.2

## Using the `groupby()` followed by `aggregate()`

More powerfully, we can use a `GroupBy` object's `aggregate()` method to compute many things at once.

```
In [55]: new_df.groupby('diabetes').aggregate(['mean', 'std', 'min', 'max'])
```

```
Out[55]:
```

	systolic BP				diastolic BP				blood oxygenation				
	mean	std	min	max	mean	std	min	max	mean	std	min	max	mean
diabetes													
no	129.0	6.182412	115	137	83.1	6.740425	71	92	98.465	0.441091	98.04	99.24	63.9
yes	144.7	5.250397	139	154	94.8	5.308274	84	105	98.442	0.198259	98.07	98.80	64.9

Okay, what's going on here? First, we got a lot of information out. Second, we got a warning because pandas couldn't compute the mean, etc., on the gender variable, which is perfectly reasonable of course.

We can handle this by using our skills to carve out a subset of our data frame – just the columns of interest – and then use `groupby()` and `aggregate()` on that.

```
In [56]: temp_df = new_df[['systolic BP', 'diastolic BP', 'diabetes']] # make a data frame
our_summary = temp_df.groupby('diabetes').aggregate(['mean', 'std', 'min', 'max'])
our_summary
```

```
Out[56]:
```

	systolic BP	diastolic BP
--	-------------	--------------

	systolic BP				diastolic BP			
	mean	std	min	max	mean	std	min	max
diabetes								
no	129.0	6.182412	115	137	83.1	6.740425	71	92
yes	144.7	5.250397	139	154	94.8	5.308274	84	105

Notice here that there are *groups of columns*. Like there are two "meta-columns", each with four data columns in them. This makes getting the actual values out of the table for further computation, etc., kind of a pain. It's called "multi-indexing" or "hierarchical indexing". It's a pain.

Here are a couple examples.

```
In [57]: our_summary[("systolic BP", "mean")]
```

```
Out[57]: diabetes
no      129.0
yes     144.7
Name: (systolic BP, mean), dtype: float64
```

```
In [58]: our_summary.loc[("no")]
```

```
Out[58]: systolic BP    mean    129.000000
          std         6.182412
          min    115.000000
          max    137.000000
diastolic BP  mean     83.100000
          std         6.740425
          min     71.000000
          max     92.000000
Name: no, dtype: float64
```

Of course, we could do the blood pressure variables separately and store them for later plotting, etc.

```
In [59]: temp_df = new_df[['systolic BP', 'diabetes']] # make a data frame with only the
our_summary = temp_df.groupby('diabetes').aggregate(['mean', 'std', 'min', 'max'])
our_summary
```

```
Out[59]:
```

	systolic BP			
	mean	std	min	max
diabetes				
no	129.0	6.182412	115	137
yes	144.7	5.250397	139	154

But we still have a meta-column label!

Here's where `.iloc[]` comes to the rescue!

If we look at the shape of the summary:

```
In [60]: our_summary.shape
```

```
Out[60]: (2, 4)
```

We see that, ultimately, the data is just a 2x4 table. So if we want, say, the standard deviation of non-diabetics, we can just do:

```
In [61]: our_summary.iloc[0, 1]
```

```
Out[61]: 6.182412330330467
```

And we get back a pure number.

We can also do things "backwards", that is, instead of subsetting the data and then doing a `groupby()`, we can do the `groupby()` and then index into it and compute what we want. For example, if we wanted the mean of systolic blood pressure grouped by whether patients had diabetes or not, we could go one of two ways.

We could subset and then group:

```
In [62]: new_df[['systolic BP', 'diabetes']].groupby('diabetes').mean()
```

```
Out[62]:
```

systolic BP	
diabetes	
no	129.0
yes	144.7

Or we could group and then subset:

```
In [63]: new_df.groupby('diabetes')[['systolic BP']].mean()
```

```
Out[63]:
```

systolic BP	
diabetes	
no	129.0
yes	144.7

Okay, first, it's cool that there are multiple ways to do things. Second – **aarrgghh!** – things are starting to get complicated and code is getting hard to read!

## Using pivot tables

"Pivot tables" (so named because allow you to look at data along different dimensions or directions) provide a handy solution for summarizing data.

By default, pivot tables tabulate the mean of data. So if we wish to compute the average systolic

blood pressure broken out by diabetes status, all we have to do is:

```
In [64]: new_df.pivot_table('systolic BP', index='diabetes')
```

```
Out[64]:
```

systolic BP	
diabetes	
no	129.0
yes	144.7

Here, `index` is used in the "row names" sense of the word.

We can also have another grouping variables map to the columns of the output if we wish:

```
In [65]: new_df.pivot_table('systolic BP', index='diabetes', columns='gender')
```

```
Out[65]:
```

	gender	female	male
diabetes			
no	126.0	132.0	
yes	140.6	148.8	

Finally, we can specify pretty much any other summary function we want to "aggregate" by:

```
In [66]: new_df.pivot_table('systolic BP', index='diabetes', columns='gender', aggfunc='median')
```

```
Out[66]:
```

	gender	female	male
diabetes			
no	126	131	
yes	140	149	

(Where `aggfunc` can be 'min', 'sum', 'std', etc., etc.)

## Summary

In this tutorial, we have covered some key aspects of working with data using pandas data frames. These were:

- doing things with data using the methods – the verbs – of pandas objects
- accessing subsets of the data with
  - square brackets
  - the `.loc[]` method
  - the `.iloc[]` method
- assembling data frames and customizing the index
- grouping data and computing summaries using

- `groupby()` and `aggregate()`
- pivot tables

## Exercise

Let's do the following on our own

1. Make a data frame that has
  - one categorical variable, "bilingual", that splits the data in half ("yes" and "no")
  - two numerical variables, verbal GRE and quant GRE
  - (you can build in, or not, whatever effect of bilingual you wish)
  - (GRE scores have a mean of about 151 and a std. dev. of about 8.5)
2. Set the index to be "Student 1", "Student 2", etc.
3. Do a seaborn plot of verbal GRE vs. bilinguality (is that a word?)
4. Make another one of quant GRE vs. bilingual status
5. Compute the mean and standard *error* of each score separated by bilingual status (using any method you wish!)

```
In [99]: num_students = 100

bilingual = pd.Series(['yes', 'no'])
bilingual = bilingual.repeat(num_students/2)
bilingual = bilingual.reset_index(drop=True)
```

```
In [100... # verbal GRE
verbal_GRE = np.int64(151 + 8.5*np.random.randn(num_students,))

# quant GRE
quant_GRE = np.int64(151 + 8.5*np.random.randn(num_students,))
```

```
In [101... # creating an effect of bilingual
verbal_GRE[0:50] = verbal_GRE[0:50] + 10
quant_GRE[0:50] = quant_GRE[0:50] + 10
```

```
In [102... # Make a dictionary with a "key" for each variable name, and
# the "values" being the num_patients long data vectors
df_dict = {'Bilingual' : bilingual,
           'Verbal GRE Scores' : verbal_GRE,
           'Quant GRE Scores' : quant_GRE}
```

```
In [103... scores_df = pd.DataFrame(df_dict)
```

```
In [104... basename = 'student ' # make a "base" row name
my_index = [] # make an empty list
for i in range(1, num_students+1) : # use a for loop to add
    my_index.append(basename + str(i)) # id numbers so the base name
```

```
In [106... scores_df.index = my_index
```

```
In [107... scores_df
```


```
Out[107...      Bilingual  Verbal GRE Scores  Quant GRE Scores
```

	Bilingual	Verbal GRE Scores	Quant GRE Scores
student 1	yes	165	167
student 2	yes	172	151
student 3	yes	165	152
student 4	yes	168	154
student 5	yes	161	153
...	...	...	...
student 96	no	154	154
student 97	no	165	144
student 98	no	140	140
student 99	no	155	144
student 100	no	152	164

100 rows × 3 columns


```
In [108... sns.catplot(data=scores_df, x='Bilingual', y='Verbal GRE Scores')
```

```
Out[108... <seaborn.axisgrid.FacetGrid at 0x22244538ca0>
```



```
In [109... sns.catplot(data=scores_df, x='Bilingual', y='Quant GRE Scores')
```

Out[109... <seaborn.axisgrid.FacetGrid at 0x222445386a0>



```
In [111... scores_df.groupby('Bilingual').aggregate(['mean', 'sem'])
```

Out[111...

	Verbal GRE Scores		Quant GRE Scores	
	mean	sem	mean	sem
Bilingual				
no	151.08	1.133116	151.14	1.102505
yes	162.92	1.333046	159.66	1.065454