

# Automating data wrangling

## Introduction

Sometimes we require a "one off" solution to a unique data analysis problem. In this situation, we write code to do a particular analysis on a particular data set. Then, if the analysis is part of a publication, we make the code and data publically available and... we're done.

Often, however, we require a **reusable** solution that operates on data of a given format even though some of the particulars, such as sample size or variable names, might change. In this case, we want our code to be "dynamic" in the sense that it should be able to handle any anticipated changes to the details of the input data.

Here, we'll tackle the same problem as last time – reformatting a data set from a cumbersome format into a more useful and "tidy" format.

Learning goals:

- write reusable code for a data wrangling problem
- create a function to make the code handy to use

## Import pandas and look at the data from last time

```
In [1]: import pandas as pd
```

Read in the data from last time.

```
In [2]: my_input_data = pd.read_csv('datasets/017DataFile.csv')
```

Take a peek to remind ourselves of the data format.

```
In [3]: my_input_data.head()
```

```
Out[3]:
```

	Male Mutant	Female Mutant	Male Wild Type	Female Wild Type
0	10.485451	8.250013	20.127063	25.946384
1	11.747948	8.453839	20.068147	23.464870
2	13.412580	9.706605	21.215148	22.989480
3	12.910095	9.522116	20.706416	25.324376
4	10.367770	8.583212	18.074795	22.607487

In this data set, there are two "independent variables", sex and genotype of laboratory rats, and one "dependent variable", response time. The data are formatted such that each column contains the

data from a unique combination of the two independent variables, *i.e.* a "cell" of the experimental design. Like this:

	male	female
mutant	mm	fm
wildtype	mw	fw

This format might seem to make sense, but it's actually not very flexible. For analysis purposes, it's generally better to have data in a format that obeys a couple of rules:

- *each row should correspond to a single observation (measurement)*
- *each column should correspond to a single variable*

Data in this format are also referred to as "tidy".

So in this case, our goal is to take the above data and put it into a format like this:

response time	sex	genotype
rt value	male or female	wild or not

Once the data are in this format, we can easily use our tools to do things like compare wild to mutant, or compare wild to mutant only in females, etc.

Last time, we stacked the reaction time values into a single column using pandas functions. This relied on us knowing and "hard coding" the column names ("Male Mutant", etc.). If we're going to automate things, we want our code to be agnostic about these. One way would be to somehow read the column names into variables and work with them somehow...

But what about numpy arrays? We already know how to manipulate those and, since they are just numbers, there are no column names or pesky row indexes to worry about. So let's try using numpy!

```
In [4]: import numpy as np
```

Pandas dataframes know how to convert themselves to numpy arrays. They have a `to_numpy()` method that will pull *just the numbers* out of our dataframe, ignoring the column labels and row indexes.

```
In [5]: raw_data = my_input_data.to_numpy()
```

Let's take a look!

```
In [6]: raw_data
```

```
Out[6]: array([[10.48545088,  8.2500131 , 20.12706278, 25.94638414],
 [11.74794775,  8.45383932, 20.06814699, 23.46487013],
 [13.41258004,  9.70660484, 21.21514789, 22.98948034],
 [12.91009526,  9.52211638, 20.70641578, 25.32437595],
 [10.36777045,  8.58321246, 18.07479515, 22.60748688],
 [11.69842177,  9.83500171, 20.36762403, 23.05218737],
```

```
[11.58315277, 10.53209602, 20.15252058, 25.3690367 ],  
[11.44734892, 9.39416641, 19.39247581, 23.37270897],  
[10.85227619, 8.73947266, 18.52434071, 25.21564644],  
[11.28589742, 10.89239399, 20.32502629, 24.99050453]])
```

## Get some useful information from the original data

So far so good! Now we are going to put the data into the format we want. To automate this, we are going to get

- the number of observations in each group (which is the number of rows), and
- the number of groups (which is the number of columns)

and store them in variables.

```
In [7]: obs_per_grp, grps = raw_data.shape  
print("We have ", obs_per_grp, " observations per group and ", grps, " groups.")
```

We have 10 observations per group and 4 groups.

Now we'll calculate the total number of observations, which is also how long we want our new data frame to be.

```
In [8]: new_length = obs_per_grp*grps  
print("We have ", new_length, " total observations.")
```

We have 40 total observations.

## Build our response time (dependent variable) column

We could now play legos "by hand", stacking the columns of our numpy array on top of each other to make a new array (and we already know how to do that).

Or we could take advantage of the fact that one of the things numpy arrays know how to do – one of the methods they have – is to change their shape. So we'll take our `obs by cols` array and `numpy.reshape()` into a `new_length` by 1 array.

What this command does (effectively) is read out the data values from the original array one-by-one, and places them in the cells of a new array of a shape you specify. The only catch is that the total number of cells in the new array has to be the same as in the old array – in other words, each and every data value has to have one and only one place to go in the new array. Which makes sense.

```
In [9]: values_col = np.reshape(raw_data, (new_length, 1))
```

I called it `values_col` because it will eventually become the values column of our new pandas data frame.

Let's see if that worked:

```
In [10]: values_col
```

```
Out[10]: array([[10.48545088],
 [ 8.2500131 ],
 [20.12706278],
 [25.94638414],
 [11.74794775],
 [ 8.45383932],
 [20.06814699],
 [23.46487013],
 [13.41258004],
 [ 9.70660484],
 [21.21514789],
 [22.98948034],
 [12.91009526],
 [ 9.52211638],
 [20.70641578],
 [25.32437595],
 [10.36777045],
 [ 8.58321246],
 [18.07479515],
 [22.60748688],
 [11.69842177],
 [ 9.83500171],
 [20.36762403],
 [23.05218737],
 [11.58315277],
 [10.53209602],
 [20.15252058],
 [25.3690367 ],
 [11.44734892],
 [ 9.39416641],
 [19.39247581],
 [23.37270897],
 [10.85227619],
 [ 8.73947266],
 [18.52434071],
 [25.21564644],
 [11.28589742],
 [10.89239399],
 [20.32502629],
 [24.99050453]])
```

Nice! But let's make absolutely sure that worked. What we want is for the columns of the original data to be stacked on top of one another. Is that what we have?

Nope, it's not right. What happened is that the values got read out *left to right, top to bottom* (or row-wise) and placed into the new array one-by-one. But what we want is for the values to be read *top to bottom, left to right* (or columnwise). We can make this happen with the `order=` argument of `numpy.reshape()`.

```
In [11]: values_col = np.reshape(raw_data, (new_length, 1), order = 'F')
```

Let's make sure that worked:

```
In [12]: values_col
array([[10.48545088],
```

```
Out[12]: [11.74794775],
[13.41258004],
[12.91009526],
[10.36777045],
[11.69842177],
[11.58315277],
[11.44734892],
[10.85227619],
[11.28589742],
[ 8.2500131 ],
[ 8.45383932],
[ 9.70660484],
[ 9.52211638],
[ 8.58321246],
[ 9.83500171],
[10.53209602],
[ 9.39416641],
[ 8.73947266],
[10.89239399],
[20.12706278],
[20.06814699],
[21.21514789],
[20.70641578],
[18.07479515],
[20.36762403],
[20.15252058],
[19.39247581],
[18.52434071],
[20.32502629],
[25.94638414],
[23.46487013],
[22.98948034],
[25.32437595],
[22.60748688],
[23.05218737],
[25.3690367 ],
[23.37270897],
[25.21564644],
[24.99050453]])
```

**Yay!** It did!

**Useless trivia:** Two of Ye Olde Major Programming Languages are **C** (used mainly by programmers) and **Fortran** (used mainly by scientists). C (the language used to write Python) uses row-wise indexing, whereas Fortran uses columnwise indexing. That's why "F" is used to specify columnwise indexing above: the "F" is for "Fortran".

Minor annoying thing: (there is always at least one that pops up in any coding task, amirite?)

`values_col` is a (40x1) 2-dimensional numpy array but, when we go to build our new data frame, we'll need it to be a 40 long (40,) 1-dimensional array.

This actually comes up so often that `numpy` has a `squeeze()` function to squeeze the dimension of length one into nothingness. It turns (n, 1) things into (n,) things.

Let's check the shape of our new array:

```
In [13]: values_col.shape
```



DataFrames know how to do `somefunction()` . So if you had a Series named `Phred` , you would say `Phred.somefunction()` to use `somefunction()` .

## Make the genetic strain variable

In the way we have formatted the data, genetic strain is the "outer" variable, in that it only changes once as we go down the data set: all the wildtypes are on top, and all mutants are on the bottom. The sex variable is the "inner" variable, because it changes once within each value of strain, so it needs to three times as we go down the data set.

This is arbitrary and has nothing to do with the experimental design; we could have formatted the data such that the roles were reversed.

What we will do is

- make a short series containing the two levels of our variable
- repeat each value to make the long series
- deal with annoying index values (there's always something...)

```
In [18]: strain = pd.Series(['wildtype', 'mutant']) # make the short series
          strain = strain.repeat(2*obs_per_grp)    # repeat each over two cell's worth of data
          strain = strain.reset_index(drop=True)    # reset the series's index value
```

Let's see if that worked:

```
In [19]: print(strain)
```

```
0    wildtype
1    wildtype
2    wildtype
3    wildtype
4    wildtype
5    wildtype
6    wildtype
7    wildtype
8    wildtype
9    wildtype
10   wildtype
11   wildtype
12   wildtype
13   wildtype
14   wildtype
15   wildtype
16   wildtype
17   wildtype
18   wildtype
19   wildtype
20    mutant
21    mutant
22    mutant
23    mutant
24    mutant
25    mutant
26    mutant
```

```
27      mutant
28      mutant
29      mutant
30      mutant
31      mutant
32      mutant
33      mutant
34      mutant
35      mutant
36      mutant
37      mutant
38      mutant
39      mutant
dtype: object
```

## Make the sex variable

As the sex variable is the inner variable, we need it have ['male'..., 'female'...] within each outer block of genotype. So what we'll do is make one block of ['male'..., 'female'...] and then just stack two copies of that to make our variable. So the steps are

- make a short series containing the two levels of our variable (just like above)
- repeat it (just like above)
- stack two copies on top of each other (dropping the annoying indexes in the process)

```
In [20]: sexes = pd.Series(['male', 'female'])           # make the short series
sexes = sexes.repeat(obs_per_grp)                     # repeat each over one cell's worth o
sexes = pd.concat([sexes]*2, ignore_index=True)        # stack or "concatonate" two copies
```

```
In [21]: print(sexes)
```

```
0      male
1      male
2      male
3      male
4      male
5      male
6      male
7      male
8      male
9      male
10     female
11     female
12     female
13     female
14     female
15     female
16     female
17     female
18     female
19     female
20      male
21      male
22      male
23      male
24      male
```



```

25     male
26     male
27     male
28     male
29     male
30    female
31    female
32    female
33    female
34    female
35    female
36    female
37    female
38    female
39    female
dtype: object

```

## Build our new data frame!

Data frames are created in pandas by handing it data it can make sense of. There are various ways to accomplish this, and one handy one is to hand it data in a "column label 1 : data 1, column label 2 : data 2, ..." format.

We can accomplish this with a python "dictionary", which is a thing associates a label (the "word") with a value or set of values or whatever (the "definition"). They are very useful, so let's take a look at a simple example before we use one to build out data frame. You create a dictionary using curly braces, and then use colons to bind each word or `key` with its definition or `value`. Commas separate each key-value pair.

```
In [22]: myData = {"name": "Larry", "rank": "full", "years": 30, "bikes": 5, "motorcycles": 2, "
```

```
In [23]: myData["name"]
```

```
Out[23]: 'Larry'
```

```
In [24]: myData["bikes"]
```

```
Out[24]: 5
```

So a dictionary associates a label with data values. **Perfect!**

Time to build our data frame!

```
In [25]: my_tidy_data = pd.DataFrame(           # invoke creation
    {                                           # start the dictionary with a {
        "RTs": values_col,                    # assign each variable to a label
        "sex": sexes,
        "strain": strain
    }                                           # end the dictionary with a }
)                                              # end of creation
```

Note that the formatting above is just to make the columns we're creating more obvious and

human-readable. This will work too:

```
In [26]: my_tidy_data = pd.DataFrame({"RTs": values_col, "sex": sexes, "strain": strain})
```

It's just not as pretty.

Let's look at our creation!

```
In [27]: my_tidy_data
```

```
Out[27]:
```

	RTs	sex	strain
0	10.485451	male	wildtype
1	11.747948	male	wildtype
2	13.412580	male	wildtype
3	12.910095	male	wildtype
4	10.367770	male	wildtype
5	11.698422	male	wildtype
6	11.583153	male	wildtype
7	11.447349	male	wildtype
8	10.852276	male	wildtype
9	11.285897	male	wildtype
10	8.250013	female	wildtype
11	8.453839	female	wildtype
12	9.706605	female	wildtype
13	9.522116	female	wildtype
14	8.583212	female	wildtype
15	9.835002	female	wildtype
16	10.532096	female	wildtype
17	9.394166	female	wildtype
18	8.739473	female	wildtype
19	10.892394	female	wildtype
20	20.127063	male	mutant
21	20.068147	male	mutant
22	21.215148	male	mutant
23	20.706416	male	mutant
24	18.074795	male	mutant
25	20.367624	male	mutant

	RTs	sex	strain
26	20.152521	male	mutant
27	19.392476	male	mutant
28	18.524341	male	mutant
29	20.325026	male	mutant
30	25.946384	female	mutant
31	23.464870	female	mutant
32	22.989480	female	mutant
33	25.324376	female	mutant
34	22.607487	female	mutant
35	23.052187	female	mutant
36	25.369037	female	mutant
37	23.372709	female	mutant
38	25.215646	female	mutant
39	24.990505	female	mutant

Yay! We win!

**Important point:** Crucially, *the above code doesn't rely on us knowing much about the input data ahead of time*. As long as it's a pandas data frame that contains numerical values, the code will run. It's automatic.

## Look at new data with more observations with same code

We'll make this code self-contained, so it can be run without running anything above. We'll also add comments, so that future-us can read the code more easily without having to wade through the notebook text above.

```
In [28]: # import our libraries
import pandas as pd
import numpy as np

my_input_data = pd.read_csv('datasets/018DataFile.csv') # read the data

raw_data = my_input_data.to_numpy() # convert to numpy array (gets

obs, grps = raw_data.shape # get the number of rows and c
```

Check the size of the new data real quick:

```
In [29]: print("We have ", obs, " observations per group and ", grps, " groups.")
```

We have 20 observations per group and 4 groups.

And now run the "meat" of the code:

```
In [30]: new_length = obs*grps                                # compute total number of obse

values_col = np.reshape(raw_data, (new_length, 1),           # reshape the array
                        order = 'F')
values_col = np.squeeze(values_col)                          # squeeze to make 1D

# construct the inner grouping variable
sexes = pd.Series(['male', 'female'])                        # define the levels
sexes = sexes.repeat(obs)                                    # make one cycle of the levels
sexes = pd.concat([sexes]*2, ignore_index=True)              # and repeat the cycle, ditchi

# construct the outer grouping variable
strain = pd.Series(['wildtype', 'mutant'])                   # define the levels
strain = strain.repeat(2*obs)                                 # make the one cycle
strain = strain.reset_index(drop=True)                        # drop the pesky index

# construct the data frame
my_new_tidy_data = pd.DataFrame(
    {
        "RTs": values_col,                                   # make a column named RTs and
        "sex": sexes,                                         # ditto for sex
        "strain": strain                                       # and for genetic strain
    }
)
```

```
In [31]: my_new_tidy_data
```

```
Out[31]:
```

	RTs	sex	strain
0	12.333785	male	wildtype
1	11.675152	male	wildtype
2	12.029059	male	wildtype
3	12.126430	male	wildtype
4	10.307197	male	wildtype
...	...	...	...
75	24.886821	female	mutant
76	24.475663	female	mutant
77	21.935896	female	mutant
78	23.852748	female	mutant
79	25.515138	female	mutant

80 rows × 3 columns

**Success!**

## Making the code even more functional

Now we have a chunk of code that seems handy and re-usable. How could we make it ever more handy?

If we make it into a **function**, then we can run the whole entire thing just by typing one command – no copying, no pasting, fewer ways to make mistakes.

## Defining a function

Since we already have all the code, we can literally just indent it and throw a `def...` in front of it!

```
In [32]: def tidyMyData() :
import pandas as pd
import numpy as np

my_input_data = pd.read_csv('datasets/018DataFile.csv') # read the data

raw_data = my_input_data.to_numpy() # convert to numpy array

obs, grps = raw_data.shape # get the number of rows a

new_length = obs*grps # compute total number of

values_col = np.reshape(raw_data, (new_length, 1),
                        order = 'F') # reshape the array
values_col = np.squeeze(values_col) # squeeze to make 1D

# construct the inner grouping variable
sexes = pd.Series(['male', 'female']) # define the levels
sexes = sexes.repeat(obs) # make one cycle of the le
sexes = pd.concat([sexes]*2, ignore_index=True) # and repeat the cycle, ditchin

# construct the outer grouping variable
strain = pd.Series(['wildtype', 'mutant']) # define the levels
strain = strain.repeat(2*obs) # make the one cycle
strain = strain.reset_index(drop=True) # drop the pesky index

# construct the data frame
my_new_tidy_data = pd.DataFrame(
    {
        "RTs": values_col, # make a column named RTs
        "sex": sexes, # ditto for sex
        "strain": strain # and for genetic strain
    }
)

return my_new_tidy_data
```

```
In [33]: datFromFun = tidyMyData()
```

```
In [34]: datFromFun
```

```
Out[34]:
```

	RTs	sex	strain
0	12.333785	male	wildtype

	RTs	sex	strain
1	11.675152	male	wildtype
2	12.029059	male	wildtype
3	12.126430	male	wildtype
4	10.307197	male	wildtype
...	...	...	...
75	24.886821	female	mutant
76	24.475663	female	mutant
77	21.935896	female	mutant
78	23.852748	female	mutant
79	25.515138	female	mutant

80 rows × 3 columns

## Defining a function with an argument

A common (very common) scenario in data analysis is wanting to run the same code – like the code we just wrote – on different files. So one really nice addition to this function would be to add the ability for the user to specify a filename to tell the function which data file to read.

This is actually fairly straightforward. All we have to do as add an **argument** to our function, and then replace the hardcoded filename in the function with the **variable** created by the function argument.

In [35]:

```
def tidyMyData(filename) :
    import pandas as pd
    import numpy as np

    my_input_data = pd.read_csv(filename) # read the data

    raw_data = my_input_data.to_numpy() # convert to numpy array

    obs, grps = raw_data.shape # get the number of rows and columns
    new_length = obs*grps # compute total number of observations

    values_col = np.reshape(raw_data, (new_length, 1),
                             order = 'F') # reshape the array
    values_col = np.squeeze(values_col) # squeeze to make 1D

    # construct the inner grouping variable
    sexes = pd.Series(['male', 'female']) # define the levels
    sexes = sexes.repeat(obs) # make one cycle of the levels
    sexes = pd.concat([sexes]*2, ignore_index=True) # and repeat the cycle, ditchin

    # construct the outer grouping variable
    strain = pd.Series(['wildtype', 'mutant']) # define the levels
    strain = strain.repeat(2*obs) # make the one cycle
```

```

strain = strain.reset_index(drop=True)           # drop the pesky index

# construct the data frame
my_new_tidy_data = pd.DataFrame(
    {
        "RTs": values_col,
        "sex": sexes,
        "strain": strain
    }
)

return my_new_tidy_data

```

Now we can call the function and specify whatever data files exist. Let's try it with "datasets/018DataFile2.csv"!

```
In [36]: newDataFromFun = tidyMyData("datasets/018DataFile2.csv")
```

```
In [37]: newDataFromFun
```

```
Out[37]:
```

	RTs	sex	strain
<b>0</b>	12.577226	male	wildtype
<b>1</b>	12.778183	male	wildtype
<b>2</b>	13.389130	male	wildtype
<b>3</b>	12.747877	male	wildtype
<b>4</b>	13.615121	male	wildtype
...	...	...	...
<b>163</b>	24.539374	female	mutant
<b>164</b>	23.877924	female	mutant
<b>165</b>	23.161896	female	mutant
<b>166</b>	24.426455	female	mutant
<b>167</b>	21.990136	female	mutant

168 rows × 3 columns

## Adding help

It's always a good idea to **heavily comment your code!**

When writing fuctions, it's also a good idea to add a documentation string, called a `docstring`, to your function. This way people can get help on your function with the `help()` function. Like `help(tidyMyData)`.

```
In [38]: def tidyMyData(filename) :
```

```

tidyMyData() Takes one-column-per-cell rat reaction time data as input.
Returns tidy one-column-per-variable data.
User specifies a filename string.
'''

import pandas as pd
import numpy as np

my_input_data = pd.read_csv(filename) # read the data

raw_data = my_input_data.to_numpy() # convert to numpy array

obs, grps = raw_data.shape # get the number of rows a

new_length = obs*grps # compute total number of

values_col = np.reshape(raw_data, (new_length, 1),
                          order = 'F') # reshape the array
values_col = np.squeeze(values_col) # squeeze to make 1D

# construct the inner grouping variable
sexes = pd.Series(['male', 'female']) # define the levels
sexes = sexes.repeat(obs) # make one cycle of the le
sexes = pd.concat([sexes]*2, ignore_index=True) # and repeat the cycle, ditchin

# construct the outer grouping variable
strain = pd.Series(['wildtype', 'mutant']) # define the levels
strain = strain.repeat(2*obs) # make the one cycle
strain = strain.reset_index(drop=True) # drop the pesky index

# construct the data frame
my_new_tidy_data = pd.DataFrame(
    {
        "RTs": values_col, # make a column named RTs
        "sex": sexes, # ditto for sex
        "strain": strain # and for genetic strain
    }
)

return my_new_tidy_data

```

In [39]:

```
help(tidyMyData)
```

Help on function tidyMyData in module \_\_main\_\_:

```

tidyMyData(filename)
tidyMyData() Takes one-column-per-cell rat reaction time data as input.
Returns tidy one-column-per-variable data.
User specifies a filename string.

```

## Coding Challenge!

Modify our function to make it even more flexible. Let the user specify the output column headers to be whatever they want.



You would do this with arguments (obviously). But you could do it with multiple arguments, so users would call it like:

```
tidyMyData("datasets/018DataFile2.csv", "Times", "Gender", "Genotype")
```

or you could do it with one additional arguments, so the user would call it by either:

```
tidyMyData("datasets/018DataFile2.csv", ["Times", "Gender", "Genotype"])
```

or

```
colNames = ["Times", "Gender", "Genotype"]
```

```
tidyMyData("datasets/018DataFile2.csv", colNames)
```

Pro tip: The function would probably be most handy if there were *default* values for the column names, so that user could just type something like

```
myTidyData = tidyMyData("datasets/018DataFile2.csv")
```

if they didn't want to specify custom column headers.

Have at it!

```
In [40]: # multiple arguments to specify the column headers
def tidyMyData(filename, col1, col2, col3) :
    ...
    tidyMyData() Takes one-column-per-cell rat reaction time data as input.
    Returns tidy one-column-per-variable data.
    User specifies a filename string.
    ...

import pandas as pd
import numpy as np

my_input_data = pd.read_csv(filename) # read the data

raw_data = my_input_data.to_numpy() # convert to numpy array

obs, grps = raw_data.shape # get the number of rows a

new_length = obs*grps # compute total number of

values_col = np.reshape(raw_data, (new_length, 1), # reshape the array
                        order = 'F')
values_col = np.squeeze(values_col) # squeeze to make 1D

# construct the inner grouping variable
sexes = pd.Series(['male', 'female']) # define the levels
sexes = sexes.repeat(obs) # make one cycle of the levels
sexes = pd.concat([sexes]*2, ignore_index=True) # and repeat the cycle, ditchin

# construct the outer grouping variable
strain = pd.Series(['wildtype', 'mutant']) # define the levels
strain = strain.repeat(2*obs) # make the one cycle
strain = strain.reset_index(drop=True) # drop the pesky index
```

```

# construct the data frame
my_new_tidy_data = pd.DataFrame(
    {
        col1 : values_col,
        col2 : sexes,
        col3: strain
    }
)

return my_new_tidy_data

```

*# make a column named RTs  
# ditto for sex  
# and for genetic strain*

```
In [42]: newDataFromFun = tidyMyData("datasets/018DataFile2.csv", "Times", "Gender", "Genotype")
```

```
In [43]: newDataFromFun
```

```
Out[43]:
```

	Times	Gender	Genotype
0	12.577226	male	wildtype
1	12.778183	male	wildtype
2	13.389130	male	wildtype
3	12.747877	male	wildtype
4	13.615121	male	wildtype
...	...	...	...
163	24.539374	female	mutant
164	23.877924	female	mutant
165	23.161896	female	mutant
166	24.426455	female	mutant
167	21.990136	female	mutant

168 rows × 3 columns

```

In [48]:
# one argument to specify the column headers with default values
def tidyMyData(filename, colNames = ["Times", "Gender", "Genotype"]) :
    """
    tidyMyData() Takes one-column-per-cell rat reaction time data as input.
    Returns tidy one-column-per-variable data.
    User specifies a filename string.
    """

    import pandas as pd
    import numpy as np

    my_input_data = pd.read_csv(filename) # read the data

    raw_data = my_input_data.to_numpy() # convert to numpy array

    obs, grps = raw_data.shape # get the number of rows a

```

```

new_length = obs*grps                                # compute total number of

values_col = np.reshape(raw_data, (new_length, 1),
                           order = 'F')              # reshape the array
values_col = np.squeeze(values_col)                  # squeeze to make 1D

# construct the inner grouping variable
sexes = pd.Series(['male', 'female'])                # define the Levels
sexes = sexes.repeat(obs)                            # make one cycle of the Le
sexes = pd.concat([sexes]*2, ignore_index=True)       # and repeat the cycle, ditchin

# construct the outer grouping variable
strain = pd.Series(['wildtype', 'mutant'])            # define the Levels
strain = strain.repeat(2*obs)                         # make the one cycle
strain = strain.reset_index(drop=True)                # drop the pesky index

# construct the data frame
my_new_tidy_data = pd.DataFrame(
    {
        colNames[0] : values_col,                    # make a column nam
        colNames[1] : sexes,                          # ditto for sex
        colNames[2]: strain                          # and for genetic strai
    }
)

return my_new_tidy_data

```

```
In [49]: myNewData = tidyMyData("datasets/018DataFile2.csv") # using the defaul values for colN
```

```
In [50]: myNewData
```

```
Out[50]:
```

	Times	Gender	Genotype
0	12.577226	male	wildtype
1	12.778183	male	wildtype
2	13.389130	male	wildtype
3	12.747877	male	wildtype
4	13.615121	male	wildtype
...	...	...	...
163	24.539374	female	mutant
164	23.877924	female	mutant
165	23.161896	female	mutant
166	24.426455	female	mutant
167	21.990136	female	mutant

168 rows × 3 columns

```
In [51]: myNewData = tidyMyData("datasets/018DataFile2.csv", ["RTs", "Sex", "Strain"]) # changi
```

```
In [52]: myNewData
```

```
Out[52]:
```

	RTs	Sex	Strain
--	-----	-----	--------

<b>0</b>	12.577226	male	wildtype
<b>1</b>	12.778183	male	wildtype
<b>2</b>	13.389130	male	wildtype
<b>3</b>	12.747877	male	wildtype
<b>4</b>	13.615121	male	wildtype
...	...	...	...
<b>163</b>	24.539374	female	mutant
<b>164</b>	23.877924	female	mutant
<b>165</b>	23.161896	female	mutant
<b>166</b>	24.426455	female	mutant
<b>167</b>	21.990136	female	mutant

168 rows × 3 columns

```
In [55]: # setting the column names outside of the function just to prove it works  
colNames = ["Times", "Gender", "Genotype"]  
myNewData = tidyMyData("datasets/018DataFile2.csv", colNames)  
myNewData
```

```
Out[55]:
```

	Times	Gender	Genotype
--	-------	--------	----------

<b>0</b>	12.577226	male	wildtype
<b>1</b>	12.778183	male	wildtype
<b>2</b>	13.389130	male	wildtype
<b>3</b>	12.747877	male	wildtype
<b>4</b>	13.615121	male	wildtype
...	...	...	...
<b>163</b>	24.539374	female	mutant
<b>164</b>	23.877924	female	mutant
<b>165</b>	23.161896	female	mutant
<b>166</b>	24.426455	female	mutant
<b>167</b>	21.990136	female	mutant

168 rows × 3 columns